

**IN THE UNITED STATES DISTRICT COURT
FOR THE DISTRICT OF DELAWARE**

MENTONE SOLUTIONS LLC,

Plaintiff,

vs.

MVG, INC.

Defendant.

§
§
§
§
§
§
§
§
§
§

Case No:

PATENT CASE

JURY TRIAL DEMANDED

COMPLAINT

Plaintiff Mentone Solutions LLC (“Plaintiff” or “Mentone”) files this Complaint against MVG, Inc. (“Defendant” or “MVG”) for infringement of United States Patent No. 6,952,413 (hereinafter “the ‘413 Patent”).

PARTIES AND JURISDICTION

1. This is an action for patent infringement under Title 35 of the United States Code. Plaintiff is seeking injunctive relief as well as damages.

2. Jurisdiction is proper in this Court pursuant to 28 U.S.C. §§ 1331 (Federal Question) and 1338(a) (Patents) because this is a civil action for patent infringement arising under the United States patent statutes.

3. Plaintiff is a Texas limited liability company with its office address at 15922 Eldorado Pkwy, Suite 500-1534, Frisco, Texas 75035.

4. On information and belief, Defendant is a Delaware corporation with a principal place of business at 2105 Barrett Park Dr., Suite 104, Kennesaw, GA 30144. Defendant can be served through its registered agent, Corporation Service Company, 251 Little Falls Drive, Wilmington, DE 19808.

5. On information and belief, this Court has personal jurisdiction over Defendant because Defendant is incorporated in Delaware, Defendant has committed, and continues to commit, acts of infringement in this District, has conducted business in this District, and/or has engaged in continuous and systematic activities in this District.

6. On information and belief, Defendant's instrumentalities that are alleged herein to infringe were and continue to be used, imported, offered for sale, and/or sold in this District.

VENUE

7. Venue is proper in this District pursuant to 28 U.S.C. § 1400(b) because Defendant is deemed to be a resident of this District.

COUNT I
(INFRINGEMENT OF UNITED STATES PATENT NO. 6,952,413)

8. Plaintiff incorporates paragraphs 1 through 7 herein by reference.

9. This cause of action arises under the patent laws of the United States and, in particular, under 35 U.S.C. §§ 271, *et seq.*

10. Plaintiff is the owner by assignment of the '413 Patent with sole rights to enforce the '413 Patent and sue infringers.

11. A copy of the '413 Patent, titled "Extended dynamic resource allocation in packet data transfer," is attached hereto as Exhibit A.

12. The '413 Patent is valid, enforceable, and was duly issued in full compliance with Title 35 of the United States Code.

13. On information and belief, Defendant has infringed and continues to infringe one or more claims, including at least Claim 5, of the '413 Patent by making, using (at least during internal testing and maintenance), importing, selling, and/or offering computer devices which are covered by at least Claim 5 of the '413 Patent. Defendant has infringed and continues to infringe

the ‘413 patent directly in violation of 35 U.S.C. § 271.

14. Regarding Claim 5, Defendant sells, offers to sell, and/or uses computing devices including, without limitation, the NeptuLink mobile device, and any similar devices (“Product”), which infringe at least Claim 5 of the ‘413 Patent. The Product is a mobile station that practices a multiple access communication method (e.g., time division multiple access). The Product has Dual Carrier HSPA+ (also referred to as DC-HSPA+) capability. Certain aspects of these elements are illustrated in the screen shots below and/or in screen shots provided in connection with other allegations herein.

HOME / PRODUCTS BY CATEGORY / NEPTULINK / NEPTULINK BY MVG - NEW VERSION

DATASHEET NEPTULINK

TESTS CAMPAIGNS DOCUMENT

PRODUCT BROCHURE

YOUTUBE

CONTACT US

First Name

Last Name *

Company *

Country *

State *

Email *

NeptuLink by MVG - New Version

700-2 700 MHz

NeptuLink by MVG satisfies the communication needs of maritime travelers by delivering a continuous high-speed Internet connectivity (100 Mbps) up to 20 nautical miles offshore.

Specifically designed with the maritime environment in mind, the new version of NeptuLink by MVG is suitable for all vessel types. With reinforced mechanics, it is tailored to withstand harsh marine conditions: high winds, corrosive elements, the swells and lulls of the ocean. The Dual SIM allows users to select the most optimized Internet coverage thus avoid roaming cost while traveling between countries. NeptuLink by MVG is the ideal solution for both professional and leisure sailors.

MAIN FEATURES

User profile

- For users looking for fast broadband internet access on board ships and various vessels in coastal areas (fishing boats, sail boats, yachts, scientific ships, wind farms, oil platforms, coast guard & sea rescue vessels, etc.) as well as in port areas (video transmission for crane operators, etc.).

Maximum data rates

- LTE/4G Downlink: Up to 100 Mbps (20 MHz bandwidth), Up to 50 Mbps (10 MHz bandwidth)
- LTE/4G Uplink: Up to 50 Mbps (20 MHz bandwidth), Up to 25 Mbps (10 MHz bandwidth)
- HSPA+ Downlink: Up to 42 Mbps
- HSPA+ Uplink: Up to 5.76 Mbps

https://www.mvg-world.com/en/products/field_product_family/neptulink-114/neptulink-mvg-nouvelle-version

NeptuLink
by MVG

- ✦ High-speed, optimal 4G connection while at sea
- ✦ Smart Network Switch 4G to Wi-Fi in the harbour
- ✦ Resistant to the harsh marine conditions
- ✦ Optimized coverage and roaming cost avoided with Dual SIM
- ✦ Configuration via Smartphone for easy set up

Stay connected
4G at sea

4G and Wi-Fi system for Internet access in coastal areas

https://www.mvg-world.com/en/system/files/neptulink_datasheet_11_16_en.pdf

TRANSCEIVER UNIT

Frequency bands


- LTE with MIMO diversity:

- Band 1 (2100 MHz)
- Band 2 (1900 MHz)
- Band 3 (1800 MHz)
- Band 4 (AWS)
- Band 5 (850 MHz)
- Band 7 (2600 MHz)
- Band 12 (700a)
- Band 13 (700 MHz)
- Band 20 (800DD)
- Band 25 (1900+)
- Band 26 (850+)
- Band 29 (700d)
- Band 41 (TD2500)

- UMTS (WCDMA), HSDPA, HSUPA, HSPA+, DC-HSPA+ with diversity:

- Band 1 (2100 MHz)
- Band 2 (1900 MHz)
- Band 3 (1800 MHz)
- Band 4 (AWS)
- Band 5 (850 MHz)
- Band 8 (900 MHz)

Distance from transmitter*	Up to 20 NM
Antenna gain	2 dBi ± 1dB
System weight	3.5 Kg
System dimensions	750 x 225 x 83 mm
SIM Type (Dual SIM)	Mini SIM (micro & nano SIM accepted with mini SIM adapter)



https://www.mvg-world.com/en/system/files/neptulink_datasheet_11_16_en.pdf

15. Dual Carrier HSPA+ has been defined in ETSI Release 8 as shown below. Also as shown below, the use of shifted USF has been approved in Release 8 (TS 45.002 version 8.1.0) and Release 9 (version 45.002 9.5.0) in combination with dual carrier.

Dual-Carrier HSPA+

3GPP Release 8 defines dual-carrier or dual-cell high-speed downlink packet access (DC-HSDPA) to allow the network to transmit HSDPA data to a mobile device from two cells simultaneously, doubling achievable downlink data rate to 42 Mbits/s. Dual-carrier operation is characterized as simultaneous reception of more than one HS-DSCH transport channel. Dual-cell operation may be activated and deactivated using HS-SCCH orders.

<https://www.electronicdesign.com/communications/understanding-hspa-cellular-technology#5>

ETSI TS 145 002 V8.1.0 (2011-04)

Technical Specification

Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path (3GPP TS 45.002 version 8.1.0 Release 8)

https://www.etsi.org/deliver/etsi_ts/145000_145099/145002/08.01.00_60/ts_145002v080100p.pdf

3GPP TS 45.002 version 8.1.0 Release 8

8

ETSI TS 145 002 V8.1.0 (2011-04)

1 Scope

The present document defines the physical channels of the radio sub-system required to support the logical channels. For the Flexible Layer One, it defines the physical channels of the radio sub-system required to support the transport channels. It includes a description of the logical channels, transport channels and the definition of frequency hopping, TDMA frames, timeslots and bursts.

https://www.etsi.org/deliver/etsi_ts/145000_145099/145002/08.01.00_60/ts_145002v080100p.pdf

In addition, The use of shifted USF has been approved in Release 8 (TS 45.002 version 8.1.0), and Release 9 (version 45.002 9.5.0) in combination with dual carrier.

0151	1	A	Rel-8	8.0.0	8.1.0	Clarification of Shifted USF operation in combination with Dual Carrier DL	GP-49	GP-110464	approved	G1	G1-49	GP-110464	agreed	2011-03-03	TEI7	-	2011-03-14
0152	-	-	Rel-9	-	-	Clarification of receiver characteristics for multicarrier BTS equipped with multicarrier receiver	-	-	-	-	G1-49	GP-110193	revised	2011-03-03	-	-	2011-03-14
0152	1	A	Rel-9	9.4.0	9.5.0	Clarification of Shifted USF operation in combination with Dual Carrier DL	GP-49	GP-110465	approved	G1	G1-49	GP-110465	agreed	2011-03-03	TEI7	-	2011-03-14
0153	-	-	Rel-9	-	-	Clarification of Shifted USF in combination with EFTA	-	-	-	-	G1-49	GP-110194	revised	2011-03-03	-	-	2011-03-14
0153	1	F	Rel-9	9.4.0	9.5.0	Clarification of Shifted USF in combination with EFTA	GP-49	GP-110454	approved	G1	G1-49	GP-110454	agreed	2011-03-03	TEI9	-	2011-03-14

<http://www.3gpp.org/DynaReport/45002-CRs.htm>

Release-8, 8.1.0: http://www.3gpp.org/ftp/tsg_geran/TSG_GERAN/GERAN_49_Chengdu/Docs/GP-110464.zip

ETSI Source: https://www.etsi.org/deliver/etsi_ts/145000_145099/145002/08.01.00_60/ts_145002v080100p.pdf

3GPP TS 45.002 version 8.1.0 Release 8

48

ETSI TS 145 002 V8.1.0 (2011-04)

Note: In case of extended dynamic allocation, the MS needs to support USF monitoring on the downlink PDCHs corresponding to (i.e. with the same timeslot number as) all assigned uplink PDCHs as defined in 3GPP TS 44.060.

In a dual carrier configuration, all the downlink timeslots on both radio frequency channels shall be assigned within a window of size "d" and all the uplink timeslots on both radio frequency channels shall be assigned within a window of size "u" where "d" and "u" are defined in Table 6.4.2.2.1. The maximum number of timeslots that may be assigned depends on the multislot class of the MS (or the Equivalent multislot class if different from the Signalled multislot class as described in B.4).

In a dual carrier configuration, Shifted USF operation shall be determined per carrier according to the number of downlink and uplink timeslots assigned on each carrier.

Release TS 44.060

Source: https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

16. The Product practices receiving an assignment of at least a first PDCH (e.g., first assigned uplink PDCH) and a second PDCH (e.g., second assigned uplink PDCH). These elements are illustrated in the screen shots below and/or in screen shots provided in connection with other allegations herein.

When Shifted USF operation is used, the USF for the first assigned uplink PDCH shall be sent on the downlink PDCH corresponding to (i.e. with the same timeslot number as) the second assigned uplink PDCH. The MS shall monitor this downlink PDCH for the USF corresponding to both the first assigned uplink PDCH and the second assigned uplink PDCH. If the USF corresponding to the first assigned uplink PDCH is detected then the mobile station shall transmit on the first assigned uplink PDCH and all higher numbered assigned uplink PDCHs. Otherwise, operation shall be as described in sub-clause 8.1.1.2.1.

The USF value corresponding to the first assigned uplink PDCH shall be different from the USF value corresponding to the second assigned uplink PDCH.

When Shifted USF operation is used, PACCH operation shall be as described in sub-clause 8.1.1.2.2 except that the network shall transmit all PACCH messages on the PDCH carried on the downlink timeslot corresponding to the second lowest numbered timeslot in the uplink assignment, and the mobile station shall attempt to decode every downlink RLC/MAC block on that downlink PDCH.

If a PACKET PDCH RELEASE message releases the second uplink PDCH in the current timeslot configuration of a mobile station using Shifted USF operation then the first uplink timeslot shall also be considered released. If any PDCHs remain in the new timeslot configuration then normal USF operation shall continue starting on the lowest available timeslot.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

8.1.1.2.1 Uplink PDCH Allocation

The PACKET UPLINK ASSIGNMENT and MULTIPLE TBF UPLINK ASSIGNMENT messages assign to the mobile station a subset of 1 to N uplink PDCHs (when the uplink TBF operates in BTTI configuration) or uplink PDCH-pairs (when the uplink TBF operates in RTTI configuration), where N depends on the mobile station multislot class.

An uplink TBF that operates in RTTI configuration may receive the assigned USFs either in BTTI USF mode or in RTTI USF mode. The indication of whether BTTI USF mode or RTTI USF mode is to be used is provided during the assignment of the corresponding uplink TBF.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/06.20.00_60/ts_144060v062000p.pdf

17. The Product practices monitoring (e.g., reading the header of each RLC/MAC block on a downlink PDCH) an assigned PDCH to detect a USF (uplink state flag). This is illustrated in in the screen shot below and/or in screen shots provided in connection with other allegations herein.

5.2.3 Uplink State Flag

An Uplink State Flag (USF) is included in the header of each RLC/MAC block on a downlink PDCH, as specified in clause 10. It may be used by the network to control the multiplexing of different mobile stations and TBFs on an uplink PDCH. The use of USF is further specified in 3GPP TS 45.002.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

18. The Product practices monitoring a first assigned PDCH to detect a USF corresponding to the first assigned PDCH and transmitting on the assigned PDCH

corresponding to the USF if shifted USF operation is not used. The Product will monitor the USF of the downlink PDCH corresponding to the assigned PDCH having the same slot number because there is no shifting operation. This is illustrated in the screen shots below and/or in screen shots provided in connection with other allegations herein.

5.2.3 Uplink State Flag

An Uplink State Flag (USF) is included in the header of each RLC/MAC block on a downlink PDCH, as specified in clause 10. It may be used by the network to control the multiplexing of different mobile stations and TBFs on an uplink PDCH. The use of USF is further specified in 3GPP TS 45.002.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

8.1.1.2.1 Uplink PDCH Allocation

The PACKET UPLINK ASSIGNMENT and MULTIPLE TBF UPLINK ASSIGNMENT messages assign to the mobile station a subset of 1 to N uplink PDCHs (when the uplink TBF operates in BTTI configuration) or uplink PDCH-pairs (when the uplink TBF operates in RTTI configuration), where N depends on the mobile station multislot class.

An uplink TBF that operates in RTTI configuration may receive the assigned USFs either in BTTI USF mode or in RTTI USF mode. The indication of whether BTTI USF mode or RTTI USF mode is to be used is provided during the assignment of the corresponding uplink TBF.

If a mobile station supports Downlink Dual Carrier, the PACKET UPLINK ASSIGNMENT or MULTIPLE TBF UPLINK ASSIGNMENT message may assign PDCHs (corresponding to any given uplink TBF) on more than one carrier frequency. If this occurs, the Extended Dynamic Allocation procedures shall operate independently on each of the two carriers.

A mobile station that has an uplink TBF operating in BTTI configuration shall monitor the downlink PDCHs corresponding to (i.e. with the same timeslot number as) its assigned uplink PDCHs starting with the lowest numbered PDCH, then the next lowest numbered PDCH, etc., up to the one corresponding to the highest numbered assigned uplink PDCH. A mobile station that has an uplink TBF operating in RTTI configuration shall monitor the downlink PDCH-pairs starting with the one corresponding to the uplink PDCH-pair with the lowest numbered timeslots, then the next uplink PDCH-pair, etc., up to the downlink PDCH-pair corresponding to the uplink PDCH-pair with the highest numbered timeslots assigned to the mobile station. When in dual transfer mode, the network shall not assign uplink PDCHs whose corresponding downlink PDCH cannot be monitored by the mobile station because of the presence of the uplink dedicated channel. As an exception, in the case of dual transfer mode, if the mobile station indicates support of DTM high multislot class capability, the network may also assign uplink PDCHs whose corresponding downlink PDCH cannot be monitored by the mobile station. In this case, the mobile station shall monitor only those downlink PDCHs that are feasible when taking into account the position of the uplink dedicated channel and the switching requirements of its multislot class (see 3GPP TS 45.002).

Whenever a mobile station with an uplink TBF operating in BTTI configuration detects an assigned USF value on a monitored PDCH, the mobile station shall transmit either a single RLC/MAC block or a sequence of four RLC/MAC blocks on the corresponding uplink PDCH (i.e. with the same timeslot number as the downlink PDCH on which the USF was detected) and all higher numbered assigned uplink PDCHs.

The following applies for an uplink TBF in RTTI configuration that receives USFs in BTTI USF mode:

- An assigned USF received on the first PDCH of a monitored downlink PDCH-pair allocates resources for one or four uplink RTTI radio blocks in the first two TDMA frames of the following basic radio block period(s) on the corresponding uplink PDCH-pair and all assigned uplink PDCH-pairs with higher numbered timeslots.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

19. The accused product practices monitoring a second assigned PDCH to detect the USF corresponding to the first assigned PDCH and a USF corresponding to the second

assigned PDCH (e.g., USF corresponding to both PDCHs are monitored on a second assigned PDCH) if the shifted USF operation is used. This is illustrated in the screen shots below and/or in screen shots provided in connection with other allegations herein.

3GPP TS 45.002 version 8.1.0 Release 8

50

ETSI TS 145 002 V8.1.0 (2011-04)

Note 0	If the downlink timeslots assigned (allocated) to the mobile station are not contiguous, d shall also include the number of downlink timeslots not assigned (allocated) to the mobile station that are located between assigned (allocated) downlink timeslots. Similarly, if the uplink timeslots assigned (allocated) to the mobile station are not contiguous, u shall also include the number of uplink timeslots not assigned (allocated) to the mobile station that are located between assigned (allocated) uplink timeslots.
Note 1	Normal measurements are not possible (see 3GPP TS 45.008).
Note 2	Normal BSIC decoding is not possible (see 3GPP TS 45.008) except e.g. in case of a downlink dual carrier capable MS operating in single carrier mode using its second receiver for BSIC decoding.
Note 3	TA offset required for multislot classes 35-39.
Note 4	TA offset required for multislot classes 40-45.
Note 5	Shifted USF operation shall apply (see 3GPP TS 44.060).
Note 6	The network may fallback to a lower multislot class and may not apply T_{ra} . A multislot class 38 or 39 MS shall in this case use T_{ra} for timing advance values below 31.
Note 7	For dual carrier operation the Applicable Multislot class is the Signalled multislot class or the Equivalent multislot class (if different from the Signalled multislot class) as defined in Table B.2.
Note 8	These configurations can only be used for assignment to an MS supporting Flexible Timeslot Assignment (see 3GPP TS 24.008). For allocation additional restrictions apply.
Note 9	These configurations can be used only in RTTI configuration.
Note 10	These configurations can be used in RTTI configurations only when the timeslots of the corresponding downlink PDCH-pair are contiguous.
Note 11	These configurations can be used only in RTTI configurations when the timeslots of the corresponding downlink PDCH-pair are not contiguous.

https://www.etsi.org/deliver/etsi_ts/145000_145099/145002/08.01.00_60/ts_145002v080100p.pdf

8.1.1.2.4 Shifted USF operation

In some instances (see 3GPP TS 45.002), Shifted USF operation shall apply.

When Shifted USF operation is used, the USF for the first assigned uplink PDCH shall be sent on the downlink PDCH corresponding to (i.e. with the same timeslot number as) the second assigned uplink PDCH. The MS shall monitor this downlink PDCH for the USF corresponding to both the first assigned uplink PDCH and the second assigned uplink PDCH. If the USF corresponding to the first assigned uplink PDCH is detected then the mobile station shall transmit on the first assigned uplink PDCH and all higher numbered assigned uplink PDCHs. Otherwise, operation shall be as described in sub-clause 8.1.1.2.1.

The USF value corresponding to the first assigned uplink PDCH shall be different from the USF value corresponding to the second assigned uplink PDCH.

When Shifted USF operation is used, PACCH operation shall be as described in sub-clause 8.1.1.2.2 except that the network shall transmit all PACCH messages on the PDCH carried on the downlink timeslot corresponding to the second lowest numbered timeslot in the uplink assignment, and the mobile station shall attempt to decode every downlink RLC/MAC block on that downlink PDCH.

If a PACKET PDCH RELEASE message releases the second uplink PDCH in the current timeslot configuration of a mobile station using Shifted USF operation then the first uplink timeslot shall also be considered released. If any PDCHs remain in the new timeslot configuration then normal USF operation shall continue starting on the lowest available timeslot.

https://www.etsi.org/deliver/etsi_ts/144000_144099/144060/08.07.00_60/ts_144060v080700p.pdf

3GPP TS 45.002 version 8.1.0 Release 8

48

ETSI TS 145 002 V8.1.0 (2011-04)

Note: In case of extended dynamic allocation, the MS needs to support USF monitoring on the downlink PDCHs corresponding to (i.e. with the same timeslot number as) all assigned uplink PDCHs as defined in 3GPP TS 44.060.

In a dual carrier configuration, all the downlink timeslots on both radio frequency channels shall be assigned within a window of size "d" and all the uplink timeslots on both radio frequency channels shall be assigned within a window of size "u" where "d" and "u" are defined in Table 6.4.2.2.1. The maximum number of timeslots that may be assigned depends on the multislot class of the MS (or the Equivalent multislot class if different from the Signalled multislot class as described in B.4).

In a dual carrier configuration, Shifted USF operation shall be determined per carrier according to the number of downlink and uplink timeslots assigned on each carrier.

https://www.etsi.org/deliver/etsi_ts/145000_145099/145002/08.01.00_60/ts_145002v080100p.pdf

20. Defendant’s actions complained of herein will continue unless Defendant is enjoined by this court.

21. Defendant’s actions complained of herein are causing irreparable harm and monetary damage to Plaintiff and will continue to do so unless and until Defendant is enjoined and restrained by this Court.

22. Plaintiff is in compliance with 35 U.S.C. § 287.

PRAYER FOR RELIEF

WHEREFORE, Plaintiff asks the Court to:

- (a) Enter judgment for Plaintiff on this Complaint on all causes of action asserted herein;
- (b) Enter an Order enjoining Defendant, its agents, officers, servants, employees, attorneys, and all persons in active concert or participation with Defendant who receive notice of the order from further infringement of United States Patent No. 6,952,413 (or, in the alternative, awarding Plaintiff a running royalty from the time of judgment going forward);
- (c) Award Plaintiff damages resulting from Defendant's infringement in accordance with 35 U.S.C. § 284;
- (d) Award Plaintiff an accounting for all acts of infringement not addressed at trial;
- (e) Award Plaintiff pre-judgment and post-judgment interest and costs; and
- (f) Award Plaintiff such further relief to which the Court finds Plaintiff entitled under law or equity.

Dated: October 31, 2018

Respectfully submitted,

DEVLIN LAW FIRM LLC

/s/ Timothy Devlin

Timothy Devlin (#4241)
tdevlin@devlinlawfirm.com
1306 N. Broom St., 1st Floor
Wilmington, Delaware 19806
Telephone: (302) 449-9010
Facsimile: (302) 353-4251

JAY JOHNSON
State Bar No. 24067322
D. BRADLEY KIZZIA
State Bar No. 11547550
KIZZIA JOHNSON, PLLC
1910 Pacific Ave., Suite 13000
Dallas, Texas 75201
(214) 451-0164
Fax: (214) 451-0165
jay@kjpllc.com
bkizzia@kjpllc.com

ATTORNEYS FOR PLAINTIFF