

1 BRANDON C. FERNALD (SBN 222429)
2 brandon@fernaldlawgroup.com
3 **FERNALD LAW GROUP APC**
4 510 West Sixth Street, Suite 700
5 Los Angeles, California 90014
6 Telephone: 323.410.0320
7 Facsimile: 323.410.0330

8 LOUIS M. HEIDELBERGER (Pro Hac Vice To Be Filed)
9 Louis.heidelberger@gmail.com
10 **THE LAW OFFICES OF LOUIS M. HEIDELBERGER,**
11 **ESQ. LLC.**
12 1229 Laurel Oak Lane
13 York, Pennsylvania 17403
14 Telephone: 215.284.8910
15 Facsimile: 267.388.3996

16 Attorneys for Plaintiff
17 **TECHNICAL LED INTELLECTUAL PROPERTY, LLC**
18
19 **UNITED STATES DISTRICT COURT**
20
21 **CENTRAL DISTRICT OF CALIFORNIA**

22
23 TECHNICAL LED
24 INTELLECTUAL PROPERTY,
25 LLC, a Delaware limited liability
26 company,
27
28 Plaintiff,
v.
ADURO TECHNOLOGIES LLC., a
California limited liability company,
Defendant.

Case No.

**COMPLAINT FOR PATENT
INFRINGEMENT (U.S. PATENT
NO. RE41,685)**
DEMAND FOR JURY TRIAL

29 This is an action for patent infringement in which Technical LED Intellectual
30 Property, LLC (“Technical LED” or “Plaintiff”) makes the following allegations
31 against Aduro Technologies LLC. (“Aduro” or “Defendant”):
32
33
34

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

PARTIES

1. Plaintiff Technical LED is a Delaware limited liability company, with its principal place of business located at 251 Little Falls Dr., Wilmington, DE 19808.

2. On information and belief, Defendant Aduro is a California limited liability company and has a principal place of business at 153 W. Rosecrans Ave., Suite 02, Gardena, CA 90248.

JURISDICTION AND VENUE

3. This action arises under the patent laws of the United States, Title 35 of the United States Code. This Court has subject matter jurisdiction pursuant to 28 U.S.C. §§ 1331 and 1338(a).

4. Venue is proper in this district under 28 U.S.C. §§ 1391(c) and 1400(b). On information and belief, Defendant has transacted business in this district, and has committed and/or induced acts of patent infringement in this district.

5. On information and belief, Defendant is subject to this Court’s specific and general personal jurisdiction pursuant to due process and/or California’s Long Arm Statue, due at least to its substantial business in this forum, including: (i) at least a portion of the infringements alleged herein; (ii) regularly doing or soliciting business, engaging in other persistent courses of conduct, and/or deriving substantial revenue from goods and services provided to individuals in California and in this Judicial District; and having a regular and established place of business in this Judicial District.

FIRST CAUSE OF ACTION

Infringement of U.S. Patent No. RE41,685

6. Plaintiff is the owner by assignment of United States Patent No. RE41,685 (“the ’685 Patent”) titled “Light Source with Non-White and Phosphor-Based White LED Devices and LCD Assembly.” The ’685 Patent reissued on

1 September 14, 2010. A true and correct copy of the '685 Patent is attached as **Exhibit**
2 **A.**

3 7. Upon information and belief, Defendant directly or through
4 intermediaries has been and is now infringing the '685 Patent in the State of
5 California, in this judicial district, and elsewhere in the United States, by, making,
6 using, providing, supplying, distributing, selling, and/or offering for sale products
7 (including at least its website at www.aduro.com) further including its smart ERIA
8 lights and similar type assemblies, comprising a light source that infringes one or
9 more claims of the '685 Patent and particularly, e.g., claims 10 through 14 of the '685
10 Patent. The '685 Patent reads on Aduro's smart lights as set forth in the exemplary
11 claims chart attached as **Exhibit B.**

12 8. Upon information and belief and in view of the foregoing, Defendant
13 has been and is continuing to directly infringe, literally infringe, and/or infringe the
14 '685 Patent under the doctrine of equivalents. Defendant is thus liable for
15 infringement of the '685 Patent pursuant to 35 U.S.C. § 271.

16 9. As a result of Defendant's infringement of the '685 Patent, Plaintiff has
17 suffered monetary damages and is entitled to a money judgment in an amount
18 adequate to compensate for Defendant's infringement, but in no event less than a
19 reasonable royalty for the use made of the invention by Defendant, together with
20 interest and costs as fixed by the court, and Plaintiff will continue to suffer damages
21 in the future unless Defendant's infringing activities are enjoined by this Court.
22 Unless a permanent injunction is issued enjoining Defendant and its agents, servants,
23 employees, representatives, affiliates, and all others acting on in active concert
24 therewith from infringing the '685 Patent, Plaintiff will be greatly and irreparably
25 harmed.

26 **PRAYER FOR RELIEF**

27 WHEREFORE, Plaintiff respectfully requests that this Court enter:
28

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

1. A judgment in favor of Plaintiff that Defendant has infringed and is infringing the ‘685 Patent;


2. A permanent injunction enjoining Defendant and its officers, directors, agents servants, affiliates, employees, divisions, branches, subsidiaries, parents, and all others acting in active concert therewith from infringement, inducing the infringement of, or contributing to the infringement of ‘685 Patent, or such other equitable relief the Court determines is just and proper;

3. A judgment and order requiring Defendant pay to Plaintiff its damages, attorneys fees, costs, expenses, and prejudgment and post-judgment interest for Defendant’s infringement and willful infringement of the ‘685 Patent as provided under 35 U.S.C. § 284, and an accounting of ongoing post-judgment infringement; and

4. Any and all other relief, at law or equity, to which Plaintiff may show itself to be entitled.

DATED: January 22, 2019

FERNALD LAW GROUP APC

By: 
Brandon C. Fernald

Attorneys for Plaintiff
TECHNICAL LED INTELLECTUAL
PROPERTY, LLC


1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

DEMAND FOR JURY TRIAL

Technical LED, pursuant to Rule 38 of the Federal Rules of Civil Procedure and Local Rule 38-1, hereby requests a trial by jury of any issues so triable by right.

DATED: January 22, 2019

FERNALD LAW GROUP APC

By: 
Brandon C. Fernald

Attorneys for Plaintiff
TECHNICAL LED INTELLECTUAL
PROPERTY, LLC

EXHIBIT A

(19) **United States**
 (12) **Reissued Patent**
Feldman et al.

(10) **Patent Number:** **US RE41,685 E**
 (45) **Date of Reissued Patent:** **Sep. 14, 2010**

- (54) **LIGHT SOURCE WITH NON-WHITE AND PHOSPHOR-BASED WHITE LED DEVICES, AND LCD ASSEMBLY** 3,805,065 A 4/1974 Williams
 3,875,456 A 4/1975 Kano et al.
 3,875,473 A 4/1975 Lebailly
 4,677,533 A * 6/1987 McDermott et al. 362/240
 4,822,144 A * 4/1989 Vriens 349/71
 4,837,565 A * 6/1989 White 345/46
 4,946,259 A 8/1990 Matino et al.
 4,992,704 A * 2/1991 Stinson 315/312
 5,008,788 A * 4/1991 Palinkas 362/231
 5,136,483 A * 8/1992 Schoniger et al. 362/545
 5,143,433 A * 9/1992 Farrell 362/29
- (75) Inventors: **Alan Stuart Feldman**, Phoenix, AZ
 (US); **Brian David Cull**, Massillon, OH
 (US); **Dennis Michael Davey**, Glendale,
 AZ (US)
- (73) Assignee: **Honeywell International, Inc.**,
 Morristown, NJ (US)

(Continued)

(21) Appl. No.: **11/788,399**

(22) Filed: **Apr. 19, 2007**

FOREIGN PATENT DOCUMENTS

AU	2004200183	A1	2/2004
EP	1 234 140	B1	8/2005
JP	09006260	A	1/1997
JP	2000208815		7/2000
JP	2002198573		7/2002
JP	2003179259		6/2003
WO	WO 01/36864	A2	5/2001

Related U.S. Patent Documents

Reissue of:

- (64) Patent No.: **6,666,567**
 Issued: **Dec. 23, 2003**
 Appl. No.: **09/473,301**
 Filed: **Dec. 28, 1999**

Primary Examiner—Ismael Negron

(74) Attorney, Agent, or Firm—Alston & Bird LLP

- (51) **Int. Cl.**
G09F 13/04 (2006.01)
F21V 9/00 (2006.01)
F21S 4/00 (2006.01)

(57) **ABSTRACT**

A light source incorporates *phosphor-based white* light emitting diodes (LEDs). The LEDs may be raised off the floor of the optical cavity to permit light to be emitted from the base of the LED. Additionally, a reflective protrusion may be placed beneath the raised LED to aid in redirecting light forward. The LEDs may be skewed in relation to adjacent LEDs to reduce interference. Non-white LEDs may be incorporated into the light source to permit for selective color tuning. Fluorescent lamps may also be implemented in combination with the LEDs to form a hybrid light source. *The light source may be used as a backlight for a liquid crystal display assembly.*


- (52) **U.S. Cl.** **362/237**; 362/97.3; 362/231;
 362/236; 362/249.02; 349/69; 349/70
- (58) **Field of Classification Search** 362/97,
 362/228, 230, 231, 237, 249, 800, 240, 236,
 362/249.02, 97.3; 349/69, 70
- See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 2,850,563 A 9/1958 Gretener
 3,794,828 A 2/1974 Arpino

16 Claims, 10 Drawing Sheets



US RE41,685 E

Page 2

U.S. PATENT DOCUMENTS

5,164,715	A	*	11/1992	Kashiwabara et al.	345/4	5,934,798	A	*	8/1999	Roller et al.	362/497
5,365,411	A	*	11/1994	Rycroft et al.	362/20	5,962,971	A	*	10/1999	Chen	313/512
5,375,043	A	*	12/1994	Tokunaga	362/601	5,998,925	A		12/1999	Shimizu et al.	
5,384,519	A		1/1995	Gotoh		6,039,451	A	*	3/2000	Grave	362/225
5,532,848	A		7/1996	Beretta		6,139,166	A	*	10/2000	Marshall et al.	362/231
5,618,096	A	*	4/1997	Parker et al.	362/629	6,139,171	A	*	10/2000	Waldmann	362/494
5,655,832	A	*	8/1997	Pelka et al.	362/296	6,144,424	A	*	11/2000	Okuda et al.	349/65
5,661,578	A		8/1997	Habing et al.		6,149,283	A	*	11/2000	Conway et al.	362/236
5,726,862	A		3/1998	Huynh et al.		6,179,449	B1	*	1/2001	Chen	313/501
5,752,766	A	*	5/1998	Bailey et al.	362/250	6,234,648	B1		5/2001	Börner et al.	
5,807,122	A	*	9/1998	Heeb et al.		6,299,329	B1	*	10/2001	Mui et al.	362/227
5,813,752	A	*	9/1998	Singer et al.	362/293	6,307,527	B1	*	10/2001	Youngquist et al.	257/676
5,813,753	A	*	9/1998	Vriens et al.	362/293	6,513,949	B1		2/2003	Marshall et al.	
5,847,507	A		12/1998	Butterworth et al.		6,692,136	B2		2/2004	Marshall et al.	
5,852,343	A		12/1998	Ravi et al.		2004/0113568	A1		6/2004	Dowling et al.	
5,924,785	A	*	7/1999	Zhang et al.	362/244	2004/0212993	A1		10/2004	Morgan et al.	
5,929,999	A		7/1999	Butterworth		2005/0063194	A1		3/2005	Lys et al.	

* cited by examiner




FIGURE 1
(Prior Art)




FIGURE 2
(Prior Art)





FIGURE 3
(PRIOR ART)



405
FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15

US RE41,685 E

1

**LIGHT SOURCE WITH NON-WHITE AND
PHOSPHOR-BASED WHITE LED DEVICES,
AND LCD ASSEMBLY**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

Notice: More than one reissue application has been filed for the reissue of U.S. Pat. No. 6,666,567. The reissue applications are application Ser. No. 11/788,399 (the present application), Ser. No. 11/788,398 (filed concurrently herewith), and Ser. No. 11/316,597, all of which are divisional reissues of U.S. Pat. No. 6,666,567.

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention generally relates to lighting systems, and more particularly, to light sources implementing light emitting diodes (LEDs).

2. Background

Many industries and applications need backlighting to illuminate an information source. In particular, transmissive liquid crystal displays (LCDs) have become very popular in many electronic media. LCDs are useful in applications such as, but not limited to, displays in avionics, laptop computers, video cameras, and automatic teller machine displays. However, many LCDs require backlighting to illuminate the information being displayed.

Many systems perform the backlighting function in conventional displays. For example, one way to backlight an information source employs an array of conventional straight tubular fluorescent lamps. While these conventional lamps are inexpensive and do not require complex electronic controls, they are sometimes inadequate for particular applications. For instance, in avionics applications, the poor color quality of the phosphors and the short lamp life of these conventional lamps, among other shortcomings, limit their usefulness.

To avoid the various problems with conventional lamps, many manufacturers employ customized lamps, such as tubular serpentine lamps. Unlike conventional fluorescent lamp arrays, custom-made serpentine lamps commonly provide good color characteristics, light luminance uniformity, and long lamp life. These lamps are typically hand made, and consequently, are comparatively costly. Moreover, these lamps are extremely fragile and difficult to install. Therefore, while custom-made tubular serpentine lamps may meet certain standards for the backlighting function, the high cost and fragility associated with these lamps detract from the advantages they offer.

A third alternative for backlighting information sources is flat fluorescent lamps. An exemplary flat fluorescent lamp, described in U.S. Pat. No. 5,343,116, issued Aug. 30, 1994, to Winsor, comprises a substrate fritted to a transparent cover lid, forming an enclosure. Diffuse channels are formed into the substrate in the interior of the enclosure. Standard phosphors are added to the interior of the enclosure which is further flushed with a material for emitting energy, such as argon or mercury. Energy is emitted in the form of visible light when an electric potential is introduced to the lamp by two electrodes, with one electrode placed at each end of the diffuse channel. Such lamps potentially offer greater ruggedness and lower manufacturing costs than serpentine tubular lamp alternatives. However, these lamps are still costly to manufacture and are difficult to repair.

2

Yet another alternative for backlighting information sources implements LEDs. The use of LEDs as light sources can be advantageous for several reasons. LEDs have a long life, which reduces the frequency for replacing non-functioning diodes. Further, when it is time to replace an LED, replacement is easier and more cost effective than when replacing a fluorescent light source. Additionally, LEDs are mechanically robust, i.e., they can typically withstand greater shocks and vibration than conventional fluorescent lights. Referring now to FIGS. 1 and 2, a conventional light source **100** incorporating LEDs comprises an optical cavity **102**, multiple LEDs **104**, a power source (not shown), and a diffuser **106** (FIG. 2). Optical cavity **102** has a floor **108** in the interior portion of light source **100** and an exterior surface **110**.

As shown in FIG. 2, in conventional LED light systems, the LEDs **104** are attached directly to the floor **108** of the optical cavity **102**. Referring to FIG. 3, LED **104** typically comprises a surface mount device constructed by encasing a diode **300** near the center of a small translucent rectangular block **302**. Electrical contacts **304** and **306** at the ends of block **302** connect to the diode via a small lead frame **308**.

Conventional LED lighting systems, however, fail to perform adequately for many backlighting applications, such as avionics, in which strict display performance requirements restrict their use. For example, LEDs typically use power less efficiently than conventional fluorescent lamps to produce comparable light intensity. Further, a conventional fluorescent lamp relies on phosphors which have narrowly defined spectral emission peaks that must be carefully controlled to provide repeatable color output. Control of the phosphor mixture to produce production-quality lamps requires significant investment of time and effort to maintain a uniform mixture, produce an acceptable color point, and ensure color purity based on phosphor chemistry. Moreover, in conventional white LEDs, the spectral emission is dominated by the blue spectral emission, and thus, the resulting "white" light is heavily shifted toward the blue spectrum. This shift limits the usefulness of LED light sources in backlighting applications.

SUMMARY OF THE INVENTION

A light source according to various aspects of the present invention comprises LEDs raised above the floor of the optical cavity. The raised LEDs may optionally have a protrusion under the LED for assisting in redirecting light. In another embodiment, adjacent LEDs may be skewed relative to one another to reduce absorption and reflection among the LEDs. In a further embodiment, non-white LEDs may be incorporated into the light source to permit selective color tuning. In an alternative embodiment, a hybrid light source may be created when fluorescent lamps are augmented with LEDs. These LEDs, which may optionally be raised above the floor of the optical cavity, may also optionally have a protrusion beneath the raised LED.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter of the invention is particularly pointed out and distinctly claimed in the concluding portion of the specification. The invention, however, both as to organization and method of operation, may best be understood by reference to the following description taken in conjunction with the claims and the accompanying drawings, in which like parts may be referred to by like numerals:

FIG. 1 is plan view of a prior art light source incorporating LED technology;

US RE41,685 E

3

FIG. 2 is a side cross-sectional view of the light source of FIG. 1;

FIG. 3 is a perspective view of a conventional diode;

FIG. 4 is a perspective view of an elevated diode in accordance with an exemplary embodiment of the present invention;

FIG. 5 is plan view of a light source implementing LEDs in accordance with an exemplary embodiment of the present invention;

FIG. 6 is a side cross-sectional view of the light source of FIG. 5;

FIG. 7 is a side cross-sectional view of the light source of FIG. 5 having protrusions beneath the raised LEDs in accordance with a further embodiment of the present invention;

FIG. 8 is a plan view of a light source configuring LEDs in an orthogonal arrangement in accordance with an exemplary embodiment of the present invention;

FIG. 9 is a plan view of a light source configuring LEDs in an oblique arrangement in accordance with an exemplary embodiment of the present invention;

FIG. 10 is a plan view of a hybrid light source incorporating LEDs and tubular fluorescent lamps in accordance with an exemplary embodiment of the present invention;

FIG. 11 is a plan view of a hybrid light source incorporating LEDs and U-shaped fluorescent lamps in accordance with an exemplary embodiment of the present invention;

FIG. 12 is a plan view of a hybrid light source incorporating LEDs and a serpentine fluorescent lamp in accordance with an exemplary embodiment of the present invention; and

FIGS. 13–15 are plan views of further embodiments of hybrid light source configurations in accordance with various aspects of the present invention.

DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

The ensuing descriptions are preferred exemplary embodiments only, and are not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the ensuing descriptions provide a convenient description for implementing various exemplary embodiments of light sources according to various aspects of the present invention, it being understood that various changes may be made in the function and arrangement of elements described in the preferred embodiments without departing from the spirit and scope of the invention as set forth in the appended claims.

Referring now to FIGS. 4–6, a light source 500 in accordance with various aspects of the present invention implements an LED that is not flush with floor of the optical cavity. Raising LEDs 504 above the surface tends to capture rear-emitted light that is otherwise absorbed or otherwise lost, enabling the light source to emit more light without additional power. In the present embodiment, the light source 500 comprises: a housing 501 having a floor 410 and an exterior wall 503 forming an optical cavity 502; multiple LEDs 400; and a power source (not shown). The light source may further include a diffuser 516 (FIG. 6). Housing 501 may be constructed of any suitable material according to the criteria of the application, such as heat exposure, mechanical shock resistance, or cost. In the present embodiment, the housing 501 comprises aluminum, steel, glass, or ceramics, and defines the optical cavity 502. The optical cavity comprises any cavity defined in the housing in which light is to be dispersed. The floor 410 and or wall 503 may optionally be coated with a reflective material, for example,

4

Durafllect™, expanded polytetrafluoroethylene, or any diffuse white paint such as a polyurethane paint. The floor 410 comprises any suitable base or surface for supporting the LEDs 400 or other relevant components.

The power source provides appropriate power supply and control to operate the lamp. The power source may provide power in any appropriate form, such as AC electrical current, and may control the power in any suitable manner, for example in conjunction with a voltage source with current limiting resistance, a constant current source, or a pulse width modulated current source,

LED 400 may be any LED suitable for the application, such as a phosphor-based white LED sold by Nichia Corp, Tokushima, Japan. The color, type, configuration, performance, and other characteristics may be selected according to any appropriate criteria. In the present embodiment, LED 400 includes a diode 402 encased in a translucent rectangular package 404. The LED 400 is raised by a support system 405 such that the base of LED 400 is elevated above the floor 410 of optical cavity 502. For example, the support system 405 suitably comprises a pair of L-brackets 406 and 408 attached to either side of the LED 400 to support the LED 400 above the floor 410. L-brackets 406 and 408 may be affixed to floor 410 according to any suitable technique, such as by an adhesive, fastener or solder. Any support system 405 that raises the LED 400 above floor 410, for example, by using raised, a support matrix, or the like, may be used to support the LED 400.

The support system 405 may further connect the LED 400 to the power source. For example, in the present embodiment, the L-brackets 406 and 408 may be constructed of a suitable electrically conductive material that supports the LED above the surface of the floor 410, such as copper or beryllium. A lead frame 412 electrically connects the diode 402 with L-brackets 406 and 408. L-brackets 406 and 408 are suitably connected to a printed circuit board which is connected to the power source, for example through control electronics.

In configurations where LEDs 400 are raised above floor 410, as in FIGS. 5 and 6, the light output of the light source may be further accomplished by providing a reflective protrusion beneath the raised LEDs 504, further optimizing the recapture of emitted light. By placing the protrusions under the raised LEDs 504, a greater amount of light may be redirected forward, causing a greater light output without requiring a corresponding increase in power. Referring to the exemplary embodiment of FIG. 7, light source 700 has an optical cavity 502 above which LEDs 504 are mounted, suitably by L-brackets 512 and 514. Protrusions 518 are located approximately below LEDs 504. Protrusions 518 may be prepared in any suitable manner and shape, such as according to the desired application. For example, protrusions 518 may be prepared by stamping the floor 410 of the optical cavity 502 such that protrusions 518 form in the surface of the floor 410. Alternatively, protrusions 518 may be constructed by adding materials onto floor 410, for example, by placing droplets of an epoxy material onto floor 410 and then covering the surface of the epoxy with a reflective material. Protrusions 518 suitably have an approximately parabolic or semi-spherical shape that is convex relative to the floor 410 of optical cavity 502. Further, protrusions 518 may alternatively be shaped to direct in a predetermined direction. This configuration may be useful in applications having a narrow range of desired viewing angles for an associated display.

US RE41,685 E

5

In accordance with various aspects of the present invention, the light emitted by the light source may be further enhanced by arranging the LEDs in an array that reduces any absorptive or reflective effects of adjacent LEDs. For example, referring to FIG. 8, in accordance with a further embodiment of the present invention, a light source **800** has an optical cavity **802** with a floor **804**. The longitudinal axes of a first set of LEDs are oriented in a first direction, such as horizontally **806**, and those of a second set of LEDs are oriented in a second direction, such as vertically **808**, such that they are perpendicular to one another. This orthogonal arrangement of adjacent LEDs, due to the relative placement of neighboring LEDs, tends to reduce the absorptive or reflective effect that adjacent LEDs may have on each other, permitting a greater light output without requiring an additional power input. Further, any or all of the LEDs may be mounted either directly onto floor **804**, or alternatively, may be mounted above floor **804** as described above. Additionally, protrusions, as described above in accordance with FIG. 7, may be added to further enhance the recapture of rear-emitted light. Therefore, by skewing orientation of the LEDs relative to one another, the intensity of the light provided by the light source tends to increase without requiring a corresponding increase in power. Light output may be further enhanced by raising the LEDs above the optical cavity floor.

Several variations in the orientation of the LEDs may be implemented to enhance light output. For example, referring now to FIG. 9, in accordance with yet another embodiment of the present invention, light source **900** has an optical cavity **902** with a floor **904**. Three sets of LEDs are oriented in three different directions, such as vertically **908** and at approximately 45° from the vertical **906**, **910**. Due to the relative placement of neighboring LEDs, this oblique configuration also tends to reduce the absorptive or reflective effects of adjacent LEDs, yielding improved output without requiring additional power. Further, in accordance with other aspects of the present invention, any or all of the LEDs may be mounted either directly onto floor **904**, or alternatively, may be mounted above floor **904** as described above. Additionally, protrusions, as described in accordance with FIG. 7, may be added to further enhance the recapture of rear-emitted light.

A light source according to various aspects of the invention may further be configured to exhibit improved spectral characteristics. In accordance with a further embodiment of the present invention, non-white LEDs, preferably, red, green, and blue LEDs, and more preferably red and green LEDs, may be incorporated into the light source as described and constructed in FIGS. 4–15 to enable it to have a tunable color output. Non-white LEDs, in particular red, green and blue LEDs may be any commercially available non-white LED.

The non-white LEDs may be configured in the light source in a variety of manners, including, but not limited to, clustering the different LED types together, and by laying down each color in separate rows. Further, non-white LEDs may be randomly dispersed throughout the light source with white LEDs, and may also be used in combination with fluorescent lamps as described below. The non-white LEDs may be mounted directly on the floor of the optical cavity, or as described in detail above, or they may be elevated above the optical cavity floor, and further, they may optionally be elevated above reflective protrusions as described above.

By incorporating non-white LEDs, multiple-wavelength LED light sources are introduced into a diffuse optical cavity to allow color mixing, with the purpose of increasing the

6

color saturation of an LED-based backlight to increase its usefulness in lighting an LCD panel. These emission spectra allow tuning of the color balance of the backlight by actively driving the LEDs or selectively enhancing particular colors to achieve a desired balance. This tunability allows one LED backlight to be used with a wide variety of LCD panels possessing different combinations of color filters. It also allows active tuning of the color balance of an LED-based light source across the color spectrum, limited only by the saturation of the individual color elements comprising the backlight.

To exploit the advantages of both LEDs and fluorescent light sources, a hybrid light source may incorporate both LEDs and fluorescent lights. Referring to FIG. 10, in accordance with an exemplary embodiment according to various aspects of the present invention, a light source **1000** has an optical cavity **1002** containing alternating rows of tubular fluorescent lamps and LEDs. An optional reflective cavity **1028** may be added to the light source to further enhance light output. In accordance with this exemplary embodiment, six tubular fluorescent lamps **1004**, **1006**, **1008**, **1010**, **1012**, and **1014** are arranged in a parallel configuration within the optical cavity **1002**. The fluorescent lamps may be mounted in any suitable manner, for example, by using a support to mount the fluorescent lamp in optical cavity **1002**. Fluorescent lamps **1004**, **1006**, **1008**, **1010**, **1012**, and **1014** may be any commercially available tubular fluorescent lamp. These lamps may be either hot cathode or cold cathode lamps and may have a variety of shapes, including, but not limited to, straight, U-shaped (e.g., as elements **1106**, **1108**, and **1110** are illustrated in the exemplary embodiment shown in FIG. 11), and serpentine fluorescent lamps (e.g., as element **1206** is illustrated in the exemplary embodiment shown in FIG. 12).

LEDs may be interspersed among the fluorescent lamps in a variety of configurations in the hybrid light source. As seen in FIG. 10, rows of LEDs **1018**, **1020**, **1022**, **1024**, and **1026** are alternated in between the fluorescent lamps **1004**, **1006**, **1008**, **1010**, **1012**, and **1014**. LEDs may be white LEDs, non-white LEDs, or may be a mixture of both white and non-white LEDs as described above. Further, the LEDs may be mounted directly to the floor **1030** of the optical cavity **1002**, or may be mounted above the optical cavity **1002** as shown in FIG. 4, and may further be mounted over reflective protrusions as described above. Further, the LEDs may be mounted in skewed directions relative to adjacent LEDs as described in FIGS. 8 and 9.

It should be appreciated that the present invention is not limited to the configurations described above. For example, referring to FIGS. 13–15, various alternative embodiments may include an edge-lit configuration, i.e., light floods the cavity from the sides and is randomly reflected. In the edge-lit configurations, the LEDs suitably face into the cavity, and not toward the view.

Referring now to FIGS. 13 and 14, these figures illustrate light source embodiments having the illumination sources around the perimeter of the lamp. In FIG. 13, light source **1300** has LED rows **1302** and **1304** on opposite sides **1312** and **1314** of optical cavity **1306**. Fluorescent lamps **1308** and **1310** are also located on opposite sides **1316** and **1318** of optical cavity **1308**. In FIG. 14, light source **1400** has LEDs **1402** around the perimeter of optical cavity **1404**. Fluorescent lamps **1406** and **1408** are on opposite side **1410** and **1412** of optical cavity **1404**. The LEDs **1302**, **1304** and **1402** of FIGS. 13 and 14 may be in a variety of orientations,

US RE41,685 E

7

including skewed relative to one another, raised from the optical cavity surface, and having a protrusion under the elevated LED. Further, a variety of LED color combinations may be implemented to permit selective color tuning

Referring now to FIGS. 13 and 14, these figures illustrate light source embodiments having the illumination sources around the perimeter of the lamp. In FIG. 13, light source 1300 has LED rows 1302 and 1304 on opposite sides 1312 and 1314 of optical cavity 1306. Fluorescent lamps 1308 and 1310 are also located on opposite sides 1316 and 1318 of optical cavity 1306. In FIG. 14, light source 1400 has LEDs 1402 around the perimeter of optical cavity 1404. Fluorescent lamps 1406 and 1408 are on opposite side 1410 and 1412 of optical cavity 1404. The LEDs 1302, 1304 and 1402 of FIGS. 13 and 14 may be in a variety of orientations, including skewed relative to one another, raised from the optical cavity surface, and having a protrusion under the elevated LED. Further, a variety of LED color combinations may be implemented to permit selective color tuning.

It should be appreciated that in all embodiments of the present invention any number of LEDs and fluorescent lamps may be used according to the particular application or design criteria of the backlight or the display. As such, the drawing figures and the present description are only meant to illustrate exemplary embodiments in accordance with the present invention and are not intended to limit the invention to the configurations illustrated herein.

Thus, a light source incorporating LEDs and fluorescent lamps according to various aspects of the present invention provides several features and advantages, such as light output uniformity. In addition, the above descriptions are preferred exemplary embodiments only, and are not intended to be limiting in any way. Various modifications, substitutions, and other applications of the present embodiments may be made without departing from the spirit and the scope of the invention as set forth in the appended claims.

What is claimed is:

1. A light source, comprising:

an optical cavity having a floor;

at least one light emitting diode (LED) having a top and a bottom coupled to said floor such that said bottom of said at least one light emitting diode is elevated above said floor of said optical cavity; and

a reflective protrusion located below said at least one LED.

2. A light source comprising:

an optical cavity having a floor;

at least one fluorescent lamp coupled to said optical cavity; and

at least two LEDs coupled to said optical cavity, wherein adjacent said at least two LEDs are skewed at approximately 45° relative to one another.

3. A light source comprising:

an optical cavity having a floor;

at least one fluorescent lamp coupled to said optical cavity; and

at least two LEDs coupled to said optical cavity, wherein adjacent said at least two LEDs are perpendicular to one another.

4. A light source comprising:

an optical cavity having a floor;

at least one fluorescent lamp coupled to said optical cavity; and

at least one LED coupled to said optical cavity, wherein said at least one LED is coupled with said optical cavity

8

such that said LED is elevated from said floor of said optical cavity.

5. A light source according to claim 4 further comprising a protrusion on said floor positioned beneath said elevated LED.

6. A light source comprising:

an optical cavity having a floor;

at least two fluorescent lamps coupled to said optical cavity; and

at least one LED coupled to said optical cavity, wherein two of said fluorescent lamps are located at opposing sides of said optical cavity, and said LEDs are located at intervals around substantially the perimeter of said optical cavity.

7. A method of manufacturing a light source comprising the steps of:

providing an optical cavity having a floor;

mounting at least one LED having a top and bottom in said optical cavity such that said bottom of said LED is elevated above said floor of said optical cavity; and

providing a protrusion below said at least at one LED.

8. A method of manufacturing a light source comprising the steps of:

providing an optical cavity having a floor;

mounting at least one LED having a top and bottom in said optical cavity such that said bottom of said LED is elevated above said floor of said optical cavity; and

mounting at least one fluorescent lamp in said optical cavity.

9. A light source comprising:

an optical cavity having a floor;

a plurality of fluorescent lamps coupled to said optical cavity substantially parallel to one other; and

a plurality of LEDs coupled to said optical cavity interspersed among said fluorescent lamps, wherein said plurality of LEDs are coupled to said optical cavity, said plurality of LEDs having tops and bottoms and being coupled to said optical cavity such that said bottoms of said LEDs are elevated above said floor.

10. A light source comprising:

an optical cavity;

a plurality of first light-emitting diodes each of which is a phosphor light-emitting diode that emits white light, each first light-emitting diode comprising a diode encased in a light-transmitting package;

a plurality of second light-emitting diodes each of which emits non-white light, each second light-emitting diode comprising a diode encased in a light-transmitting package;

wherein the first and second light-emitting diodes are arranged to emit light into the optical cavity such that mixing of spectral outputs from the first and second light-emitting diodes occurs in the optical cavity.

11. A light source of claim 10, further comprising at least one third light-emitting diode having a spectral output different from those of the first and second light-emitting diodes.

12. A light source of claim 11, wherein the spectral output of the second light-emitting diodes is a red output.

13. A light source of claim 11, wherein the spectral output of the third light-emitting diode is a green output.

14. A light source of claim 13, further comprising at least one fourth light-emitting diode having a blue output.

US RE41,685 E

9




15. A liquid crystal display assembly comprising:
a backlight including:
an optical cavity;
a plurality of first light-emitting diodes each of which is
a phosphor light-emitting diode that emits white 5
light, each first light-emitting diode comprising a
diode encased in a light-transmitting package;
a plurality of second light-emitting diodes each of
which emits non-white light, each second light-
emitting diode comprising a diode encased in a light-
transmitting package; 10
wherein spectral outputs of the first and second light-
emitting diodes are operative to tune a color balance
of the backlight;




10




wherein the first and second light-emitting diodes are
arranged to emit light into the optical cavity such
that mixing of the spectral outputs from the first and
second light-emitting diodes occurs in the optical
cavity; and
a liquid crystal display panel positioned adjacent to the
backlight so as to be illuminated by the backlight.
16. A liquid crystal display assembly of claim 15, further
comprising at least one filter that is configured to be used
with the liquid crystal display panel and the backlight.

* * * * *

EXHIBIT B

<p>US Patent US RE41,685</p>		<p>Aduro Smart ERIA Light Bulb</p>
<p>10. A light source</p>		<p>The Aduro Smart ERIA Light Bulb is a light source.</p>
<p>comprising: an optical cavity;</p>	 <p>Optical Cavity</p>	<p>The opaque plastic dome creates an optical cavity.</p>
<p>a plurality of first light-emitting diodes each of which is a phosphor light-emitting diode that emits white light,</p>	 <p>Phosphor LED that emits white light</p>	<p>The bulb has 8 white LEDs. Each white LED is a phosphor LED that emits white light.</p>

<p><i>each first light-emitting diode comprising a diode encased in a light-transmitting package;</i></p>		<p>Each first LED is encased in a light trasmittig package.</p>
<p><i>a plurality of second light-emitting diodes each of which emits non-white light, each second light-emitting diode comprising a diode encased in a light-transmitting package;</i></p>		<p>Each bulb has 5 non-white LEDs. Each non-white LED is encased in a light transmitting package.</p>
<p><i>wherein the first and second light-emitting diodes are arranged to emit light into the optical cavity such that mixing of spectral outputs from the first and second light-emitting diodes occurs in the optical cavity.</i></p>		<p>The white, red, green, and blue LEDs are arranged to mix light spectral outputs within the optical cavity.</p>

<p>11. A light source of claim 10, further comprising at least one third light-emitting diode having a spectral output different from those of the first and second light-emitting diodes.</p>	<p>Blue LED</p>  A close-up photograph of the base of a white LED bulb. The base is a circular printed circuit board (PCB) with several small, square LED chips mounted on it. A callout bubble with a purple border and a white background points to one of the chips, which is labeled "Blue LED". The chip is a small, square, blue-emitting diode. The PCB also has some text and markings, including "3030" and "3030-UP66-15-0350".	<p>Each bulb has a third LED (blue) that has a spectral output different than the first (white) and second (red) LED's.</p>
<p>12. A light source of claim 11, wherein the spectral output of the second light-emitting diodes is a red output.</p>	<p>RED LED</p>  A close-up photograph of the base of a white LED bulb, similar to the one in the first image. A callout bubble with a purple border and a white background points to one of the LED chips, which is labeled "RED LED". The chip is a small, square, red-emitting diode. The PCB has the same markings as in the first image.	<p>Each bulb second non-white (red) LED encased in a light transmitting package.</p>
<p>13. A light source of claim 11, wherein the spectral output 65 of the third light-emitting diode is a green output.</p>	<p>Green LED</p>  A close-up photograph of the base of a white LED bulb, similar to the previous images. A callout bubble with a purple border and a white background points to one of the LED chips, which is labeled "Green LED". The chip is a small, square, green-emitting diode. The PCB has the same markings as in the previous images.	<p>Each bulb has a third (green) LED encased in a light transmitting package.</p>

14. A light source of claim 13, further comprising at least one fourth light-emitting diode having a blue output.



Each bulb has a fourth (blue) LED encased in a light transmitting package.