	Case 8:19-cv-01807	Document 1	Filed 09/20/19	Page 1 of 50	Page ID #:1
1 2 3 4 5 6 7 8 9 10 11	Brandon C. Fernal brandon@fernaldla FERNALD LAW GF 510 West Sixth Str Los Angeles, Calif Telephone: 323.41 Facsimile: 323.410 Timothy E. Groche tim@nbafirm.com Joseph P. Oldaker joseph@nbafirm.c NELSON BUMGARI 15020 S. Ravinia A Orland Park, Illino Telephone: 708.67	d (SBN 2224 awgroup.com ROUP reet, Suite 700 Fornia 90014 0.0320 0.0330 Docinski (<i>PHV</i> (<i>PHV to be st</i> om DNER ALBRIT Avenue, Suite is 60462 5.1975	29)) to be submitted ubmitted) TON PC 29	2)	
 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 	Attorneys for Pla VOICE CONTRO VOICE CONTRO LLC, P BEST CHOICE F D	intiff DL VEHICL UNITED S CENTRAL DL VEHICLE laintiff, PRODUCTS, efendant.	ES, LLC STATES DIST DISTRICT OF S, Case 1 COM PATE	RICT COUR F CALIFORN No. PLAINT FO ENT INFRING	AT NIA R GEMENT

1 Plaintiff Voice Control Vehicles, LLC ("VCV" or "Plaintiff") files this 2 Complaint against Best Choice Products, Inc. ("Best Choice" or "Defendant") for 3 infringement of U.S. Patent No. 8,401,860 ("the '860 patent"). 4 THE PARTIES 5 VCV is a Texas limited liability company with its principal place of 1. 6 business at 836 Diamond Street, Laguna Beach, California 92651. 7 Best Choice is a California corporation with its principal place of 2. 8 business at 2010 Main Street, Suite 650, Irvine, California 92614. Best Choice does 9 business in the State of California and in the Central District of California. Best 10 Choice can be served with process through its agent Suzanne M. Graves, 1317 W. 11 Foothill Blvd, Suite 245, Upland, California 91786. 12 JURISDICTION AND VENUE 13 3. This action arises under the patent laws of the United States, namely 35 14 U.S.C. §§ 271, 281, and 284, among others. 15 This Court has subject matter jurisdiction pursuant to 28 U.S.C. §§ 4. 16 1331, 1338(a), and 1367. 17 5. Venue is proper in this judicial district pursuant to 28 U.S.C. § 1400(b). 18 Defendant has committed acts of infringement in this judicial district and has regular 19 and established places of business in this judicial district at 2010 Main Street, Suite 20 650, Irvine, California 92614. In addition, Defendant is a California corporation. 21 6. Defendant is subject to this Court's specific and general personal 22 jurisdiction pursuant to due process and/or the California Long Arm Statute, due at 23 least to their substantial business in this State and judicial district, including: (a) at 24 least part of their infringing activities alleged herein; and (b) regularly doing or 25 soliciting business, engaging in other persistent conduct, and/or deriving substantial 26 revenue from goods sold, and services provided, to California residents. 27 28 - 2 -

	Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 3 of 50 Page ID #:3
1	COUNT I
2	(Infringement of U.S. Detent No. 9 401 960)
3	(Infringement of U.S. Patent No. 8,401,800)
4	7. VCV incorporates paragraphs 1 through 6 herein by reference.
5	8. This cause of action arises under the patent laws of the United States
6	and, in particular, 35 U.S.C. \S 2/1, <i>et seq</i> .
7	9. On March 19, 2013, the '860 patent was issued by the United States
8	Patent and Trademark Office ("USPTO") to Paul R. Evans for an invention entitled,
9	"Voice-Activated Command and Control for Remotely Controlled Model Vehicles."
10	A true and correct copy of the '860 patent is attached hereto as Exhibit A.
11	10. VCV is the assignee of the '860 patent, with ownership of all substantial
11	rights, including the right to exclude others and to enforce, sue, and recover damages
12	for past, present, and future infringements.
13	11. The '860 patent is valid, enforceable, and was duly issued in full
14	compliance with Title 35 of the United States Code.
15	Direct Infringement (35 U.S.C. § 271(a))
16	12. Defendant Best Choice has infringed, and continues to infringe, one or
17	more claims of the '860 patent in this judicial district and elsewhere in California and
18	the United States.
19	13. In particular, on information and belief, Defendant has, and continues
20	to, infringe at least claim 1 of the '860 patent by, among other things, using its 2.4
21	GHz Voice Command Quadcopter (the "Accused Product") in combination with the
22	Accused Product's app and a smartphone.
23	14. Defendant is liable for these infringements of the '860 patent pursuant
24	to 35 U.S.C. § 271.
25	15. Attached hereto as Exhibit B, and incorporated herein by reference, is a
26	claim chart detailing how the Accused Product infringes the '860 patent.
27	
28	
	- 3 -

16. VCV has been damaged as a result of Defendant's infringing conduct described in this Count. Defendant is, thus, liable to VCV in an amount that adequately compensates VCV for Defendant's infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

Indirect Infringement (Inducement- 35 U.S.C. § 271(b))

17. Based on the information presently available to Plaintiff, absent discovery, and in the alternative to direct infringement, Plaintiff contends that Defendant has, and continues to, indirectly infringe one or more claims of the '860 patent by inducing direct infringement by end users of the Accused Products.

18. Defendant has had knowledge of the '860 patent since at least receipt of VCV's January 15, 2019 notice letter. In addition, on February 10, 2019, VCV sent Defendant a claim chart and exhibits, similar to Exhibit B attached hereto, detailing Defendant's infringement of the '860 patent.

19. On information and belief, despite having knowledge of the '860 patent, Defendant has specifically intended for persons who acquire and use the Accused Product, including Defendant's customers and end consumers, to acquire and/or use such devices in a way that infringes the '860 patent, including at least claim 1 and Defendant knew or should have known that its actions were inducing infringement.

20. Defendant instructs and encourages users to use the Accused Products in a manner that infringes the '860 patent. For example, Defendant's provide end users detailed instructions on how to use the Accused Products in combination with the Accused Product's app and a smartphone. *See e.g.*, Exhibit B and exhibits thereto.

25 21. In accordance with Fed. R. Civ. P. 11(b)(3), Plaintiff will likely have
 additional evidentiary support after a reasonable opportunity for discovery on this
 issue.

- 4 -

1	22.	Plaintiff has been damaged as a result of Defendant's infringing conduct
2	described i	n this Count. Defendant is, thus, liable to Plaintiff in an amount that
3	adequately	compensates Plaintiff for Defendant's infringements, which, by law,
4	cannot be l	ess than a reasonable royalty, together with interest and costs as fixed by
5	this Court ı	under 35 U.S.C. § 284.
6		PRAYER FOR RELIEF
7	WH	EREFORE, VCV requests that the Court find in its favor and against
8	Defendant,	and that the Court grant VCV the following relief:
9		
10	a.	Judgment that one or more claims of the '860 patent has been infringed directly or indirectly either literally and/or under the doctrine of
11		equivalents, by Defendant;
12	b.	Judgment that Defendant accounts for and pay to VCV all damages to,
13 14		and costs incurred by, VCV because of Defendant's infringing activities
15		sales or damages not presented at trial;
16	с.	Judgment that Defendant account for and pay to VCV a reasonable,
17		ongoing, post-judgment royalty because of Defendant's infringing activities and other conduct complained of herein:
18	đ	That VCV be granted pre-judgment and post-judgment interest on the
19	u.	damages caused by Defendant's infringing activities and other conduct
20		complained of herein; and
21	e.	That VCV be granted such other and further relief as the Court may
22		deem just and proper under the circumstances.
23		
24		
25		
26		
27		
28		5
		- 3 -
	I	

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 6 of 50 Page ID #:6

1	Dated: September 20, 2019	Respectfully submitted,
2		/s/ Brandon C Fernald
3		Brandon C. Fernald (SBN 222429)
4		FERNALD LAW GROUP
5		510 West Sixth Street, Suite 700
6		Telephone: 323.410.0320
7		Facsimile: 323.410.0330
8		Attorney for Plaintiff
9		Voice Control Vehicles, LLC
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23 24		
24		
23 26		
20 27		
∠1 28		
20		- 6 -

	Case 8:19-cv-01807 Document 1	Filed 09/20/19 Page 7 of 50 Page ID #:7			
1	DEMAND FOR JURY TRIAL				
2	Plaintiff respectfully reque	ests a jury trial on all issues so triable pursuant to			
3	FED. R. CIV. P. 38(b) and L.R. 38	3-1.			
4					
5	Dated: September 20, 2019	Respectfully submitted,			
6		/s/ Brandon C Fernald			
7		Brandon C. Fernald (SBN 222429)			
8		brandon@fernaldlawgroup.com FERNALD LAW GROUP			
9		510 West Sixth Street, Suite 700			
10		Los Angeles, California 90014 Telephone: 323.410.0320			
11		Facsimile: 323.410.0330			
12		Attornev for Plaintiff			
13		Voice Control Vehicles, LLC			
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28		- 7 -			

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 8 of 50 Page ID #:8

EXHIBIT A

Case 8:19-cv-01807 Document 1



US008401860B1

(12) United States Patent

Evans

(54) VOICE-ACTIVATED COMMAND AND CONTROL FOR REMOTELY CONTROLLED MODEL VEHICLES

- (76) Inventor: Paul R Evans, Big Rock, IL (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 912 days.
- (21) Appl. No.: 11/123,626
- (22) Filed: May 6, 2005
- (51) Int. Cl.
- G10L 15/265 (2006.01)
- (52) **U.S. Cl.** **704/275**; 704/225; 701/9; 701/3; 701/2; 701/16; 701/1; 398/129; 342/129; 341/176; 340/995.14; 340/945
- (58) Field of Classification Search 704/275, 704/225; 381/172; 341/176; 701/9, 3, 2, 701/16, 1; 398/129; 342/29; 340/995.14, 340/945

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,725,956	Α	*	2/1988	Jenkins 701/2
4,739,311	Α	*	4/1988	Yamamoto et al 341/176
4,929,949	Α	*	5/1990	Yamamoto et al 341/176

(10) Patent No.: US 8,401,860 B1

(45) **Date of Patent:** Mar. 19, 2013

5,077,671	A *	12/1991	Leslie et al 701/3
5,323,257	A *	6/1994	Abe et al 398/129
5,751,237	A *	5/1998	Tanaka 341/176
5,774,841	A *	6/1998	Salazar et al 704/225
6,230,136	B1 *	5/2001	Yamamoto et al 704/275
6,262,679	B1 *	7/2001	Tran 342/29
7,221,290	B2 *	5/2007	Burgemeister 340/945
7,840,317	B2 *	11/2010	Matos et al 701/16
2003/0093187	A1*	5/2003	Walker 701/1
2004/0102876	A1*	5/2004	Doane 701/9
2005/0195096	A1*	9/2005	Ward et al 340/995.14

* cited by examiner

Primary Examiner - Michael Colucci

(74) Attorney, Agent, or Firm — Cleere IP Law Office LLC; Scott R. Cleere

(57) **ABSTRACT**

A voice-activated command and control system for remotelycontrolled vehicles includes a voice-activated control module, a microphone, and a verbal or visual feedback indicator such as a speaker. The operator speaks instructions into the microphone to activate control functions on the vehicle. Confirmation of receipt and/or status of the verbally commanded instructions are sent back to the operator such as spoken through the speaker. The microphone and speaker can be implemented, for example, either in a headset (with a microphone and earphones) worn by the operator, or in the handheld controller for the vehicle. The system can be alternately implemented without the speaker or other feedback element.

20 Claims, 8 Drawing Sheets





Mar. 19, 2013 S

Sheet 1 of 8

US 8,401,860 B1





Mar. 19, 2013



U.S. Patent

Mar. 19, 2013

Sheet 3 of 8

US 8,401,860 B1



U.S.	Patent	Mar. 19, 2013	Sheet 4 of 8	US 8,401,860 B1
		,		/ /







U.S. Patent	Mar. 19. 2013	Sheet 6 of 8	US 8,401,860 B1
	11111 1 J		00 0,101,000 21





U.S. Patent

Mar. 19, 2013

Sheet 7 of 8

US 8,401,860 B1





FIG. 10



U.S. Patent	Mar. 19, 2013	Sheet 8 of 8	US 8,401,860 B1
			0.00,101,000 1

FIG. 11



5

30

VOICE-ACTIVATED COMMAND AND **CONTROL FOR REMOTELY CONTROLLED** MODEL VEHICLES

CROSS-REFERENCES TO RELATED APPLICATIONS

None.

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC

Not Applicable.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not Applicable.

BACKGROUND OF THE INVENTION

1. Field of Invention

The present invention relates generally to flight controls for remotely controlled vehicles.

More particularly, the invention relates to, preferably two- 25 way, voice-activated command and control for radio-controlled (R/C) vehicles, as well as for control of virtual or simulated remotely-controlled vehicles such as utilized in a vehicle control simulator.

2. Background Art

Ownership and operation of R/C model vehicles has increased over the past few decades. It is now a hobby enjoyed by many adults, as well as younger people.

The following is a brief description and example of a typical control scenario for piloting a conventional R/C model 35 airplane, variations on this description are available in the art. Pilot controls consist of a hand-held controller with various modules including an electrical, electronic or micro-processor-based control function, a radio frequency transmitter function, and a radio frequency receiver function. The con- 40 troller is commonly configured to be held in both of (between) the user's hands, and contains two (left and right) flight control levers (commonly referred to as "joysticks") that can be manually actuated (pivoted) in at least two orthogonal directions. These levers commonly control the basic flight control 45 unique control of remotely controlled vehicles, including virfunctions of the airplane. The pilot using his or her right-hand fingers (or right-hand thumb) moves the right control lever left or right for proportional movement of the airplane's ailerons (banking control) and up and down for proportional movement of elevator (pitch control). The pilot's left hand 50 lation and training in the control of R/C vehicles. fingers (or left hand thumb) moves the left control lever left to right for proportional movement of rudder (vaw control) and up and down for proportional movement of engine throttle (engine speed or vehicle velocity control). Collectively, these controls are generally to referred to herein as aircraft "trim" 55 controls. All other controls (the "auxiliary" controls) for the aircraft, such as raising and lowering of retractable landing gear and flaps, electronically changing the proportional rate of aircraft "trim" controls and the linear to exponential rate of aircraft "trim" controls (dual-rate controls), applying landing 60 gear wheel brakes, applying air brakes, shutting off the engine, opening and closing boom doors, etc., are commonly triggered with a variety of mechanical switches and equivalent manually-operable devices mounted on the hand-held controller. Common switch types used for these purposes 65 include push button, rotary, toggle, and slide switches. The pilot actuates these switches with his or her fingers as well as,

2

and sometimes simultaneously with actuation of the aircraft "trim" controls. Thus, proper control of R/C aircraft 20 requires a developed level and combination of manual dexterity, manual response times, and visual line-of-sight with the vehicle.

Problems in control of R/C aircraft can arise in a number of circumstances. For example, any need to take your eyes off of the aircraft while flying under control even for a moment many times causes a problem upon trying to regain a visual on ¹⁰ it in the air. When the pilot looks back up in the sky for the aircraft, the aircraft's anticipated position is not always where its true position is. By the time the pilot finds the aircraft position by sight and determines its current attitude in the air and responds with the corrective control adjustments to 15 regain controlled flight the aircraft many have crashed.

One of the more difficult aspects of flying R/C aircraft under control involves controlling an aircraft at low altitude flight. The reaction times with administering changes to aircraft "trim" controls are very minimal to overt crash landings.

20 So any loss of the pilot's line of sight to the aircraft as well as allowing his or her fingers and or thumbs to break contact with the aircraft "trim" controls are conditions which will frequently lead to crashes.

As both the field and the users have matured during the past number of years, the market has responded and model R/C vehicles have become more realistic, more complicated, larger sized, and more expensive. The danger of practicing on this expensive equipment is the risk of loss if the vehicle crashes.

Simulation software is available to simulate the operation and control of R/C vehicles. This software assists the novice in acquiring the needed skills without the danger of crashing and destroying a potentially expensive vehicle, and to assist the experienced person in keeping and honing control skills when not in the field. Although available, not all novice users will utilize this software to acquire the necessary skills to become proficient in controlling R/C vehicles.

Thus, there is a need for improved control of R/C vehicles, including during simulation and training in the control of such vehicles.

SUMMARY OF THE INVENTION

The general objective of the invention is to provide new and tual or simulated vehicles such as utilized in a vehicle control simulator.

Another objective of the invention is to provide such new and unique control for R/C vehicles, including during simu-

A detailed objective of the invention is to achieve the foregoing with new and unique, preferably two-way, voiceactivated command and control for remotely controlled vehicles, including for R/C vehicles, and virtual or simulated vehicles

These and other objectives and advantages of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

A preferred embodiment, two-way voice-activated command and control system in accordance with the invention, when applied in piloting a model airplane, provides for administration of airplane control functions with an integrated voice-activated control and feedback indicator unit. This unit can be, for example, a headset worn by the "pilot" (i.e., the vehicle operator) that includes a microphone and earphones, or a microphone and speaker implemented in an

alternate unit that is convenient for operator interaction such as in a pocket-sized unit or a belt clip-on unit or built into the conventional hand-held controller for the vehicle. The twoway voice-activated unit (generally referred to herein as a "headset") allows the pilot, using his or her voice, to speak 5 words into the microphone to voice activate the various control functions to the airplane (or other remotely-controlled vehicle). The speaker (generally referred to herein as the "earphones") is used to provide verbal feedback, i.e., voice recognition in verbal words, back to the pilot's ears from the 10 airplane to confirm receipt, status and/or completion of the previous administered control functions, enunciation of alarms, and various operational and/or environmental data via the airplane's on-board data storage system. The headset is used in coordination with the conventional (e.g., levers, 15 switches, buttons, etc.) aircraft trim controls and auxiliary controls of the hand-held transmitter/receiver controller to enact various control functions which can be administered simultaneously from the pilot and at his or hers discretion. The aircraft trim and auxiliary control movement applied to 20 the hand-held controller, the words spoken into the microphone by the pilot, and the words the pilot hears through the earphones from the airplane's on-board transmitter/receiver controller are electronically converted by the hand-held controller and sent or received back and fourth from the airplane 25 via radio waves. The airplane's on-board controller transmits and receives controlling information and data information via radio waves back and fourth from the hand-held controller and converts this radio wave information electronically to control motorized actuators (servos) linked to the airplane's 30 controls such as ailerons, elevator, rudder, throttle, flaps, landing gear, doors, etc. The two-way voice activated command and control system also controls the transfer of data captured nom the airplane's on-board telemetry data system. The airplane's on-board telemetry system is an electronic 35 device that stores data that is obtained from various types of electronic sensors attached to it. These sensors are mounted about the airplane. Some sensor examples include a sensor in the engine's exhaust flow to sense temperature level, an accelerometer sensor on-board to sense "g" forces applied to air- 40 plane's structure, etc. To operate and or fly the R/C model airplane under control, the pilot using his or her eyes must visually see the airplane and apply control commands via the hand-held controller and headset.

Using one example of a control being initiated by the pilot 45 to the airplane and the flow of operational interface in carrying out the command with the two-way voice activated command and control system in controlling the airplane's flaps is as follows: The pilot speaks the words "flaps thirty" into the headset's microphone and the microphone converts these 50 words into a electronic signal. This command signal is sent to the hand-held controller where the signal is matched by a prior programmed microprocessor which triggers the control action to the flap control interface then is transmitted to the on-board controller via radio waves. Here the signal is 55 received and converted to operate the controlling servo linked to the flaps and the flaps move down to a thirty-degree position. After the electronic task is completed a prior microprocessor voice programmed confirmation message is sent back to the headset's earphones by the on-board controller via 60 radio waves to the hand-held controller and is converted to an audio sound by the earphones and is heard by the pilot's ear. The confirmation message could include these words "copy flaps thirty", a busier sound, etc. The command and confirmation, prior electrically microprocessor stored words, can 65 be any words the pilot and or the microprocessor programmer elect.

4

The above electronic interface routing can vary, depending upon the electrical hardware's physical location. Using the two-way voice activated command and control system allows the pilot to have a "virtual reality like" communication between him or her-self and the airplane using his or her speaking voice and hearing capabilities. Two benefits when using the two-way voice activated command and control system are as follows: (i) allowing multiple control functions to be administered simultaneously by the pilot without moving his or her fingers off the aircraft "trim" controls which control the basic flight controls discussed above, and (ii) allowing the pilot to keep his or her eyes looking at the airplane instead of taking them off the airplane momentarily to look for a control switch to activate by his or her fingers or displayed data on the hand-held controller while in operation of the airplane.

The two-way voice activated command and control system can be used to operate a simulated model airplane that is produced within a flight simulator, as well as for selection or control the operational or environmental parameters of the simulator.

The voice activated command and control system of the invention can alternately be implemented with a one-way communication from the operator for control of the vehicle.

A basic voice-activated command and control system in accordance with the invention is configured for use with a remotely controlled vehicle of the type having an on-board controller to (a) receive control function signals by wireless transmission and (b) control the corresponding control functions on the vehicle. In this instance, the voice-activated command and control system includes (a) a microphone for receiving a verbal command; and (b) a voice-activated control module for transmitting a control function signal responsive to a verbal command received by the microphone to the vehicle by wireless transmission; wherein the microphone and control module allow an operator, using his or her voice, to speak a word command into the microphone to voice activate and remotely control the control functions of the vehicle.

A two-way voice-activated command and control system in accordance with the invention is configured for use with a remotely controlled vehicle of the type having an on-board controller to (a) receive control function signals by wireless transmission, (b) control the corresponding control functions on the vehicle, and (c) transmit feedback signals by return wireless transmission indicative of at least one of (i) receipt of the control function signals, (ii) status of the corresponding control functions on the vehicle, and (iii) vehicle operational or environment data. In this instance, the voice-activated command and control system includes (a) a microphone for receiving a verbal command; (b) a voice-activated control module for transmitting a control function signal responsive to a verbal command received by the microphone to the vehicle by wireless transmission; and (c) a feedback indicator responsive to feedback signals by return wireless transmission from the vehicle; wherein the microphone and control module allow an operator, using his or her voice, to speak a word command into the microphone to voice activate and remotely control the control functions of the vehicle.

The control module of the voice-activated command and control system will be programmed to recognize certain verbal commands corresponding to certain control functions of the vehicle, and distinguish between such verbal commands and other verbal commands or sound waves as may be received by the microphone. In certain preferred embodiments, the control module will distinguish applicable parts the recognized verbal commands including a descriptive part

10

identifying the applicable control function (e.g., flaps or wheels), and a numeric part (e.g., thirty degrees) and/or a relational part (e.g., down).

The microphone of the voice-activated command and control system will be located for the convenience of the operator, such as in a pocket-sized unit or clip-on unit or a hand-held unit such as the conventional hand-held controller of the vehicle. In one preferred embodiment, the voice-activated command and control system includes a headset that carries the microphone. In certain alternate embodiments, both the microphone and the control module of the voice-activated command and control system are located together in a single unit, such as in a hand-held unit, a pocket-sized unit, a clip-on unit, or a headset. 15

In the two-way voice-activated command and control system, microphone and feedback indicator may be carried together in a single unit such as a pocket-sized unit, a clip-on unit, or a hand-held unit such as the conventional hand-held controller. The feedback indicator includes an audible feed- 20 back indicator and/or a visual feedback indicator responsive to the return feedback signals from the vehicle. One preferred feedback indicator includes a speaker to produce audible feedback in the form of spoken communication. A preferred implementation of this the feedback indicator is to provide a 25 headset that carries the microphone and the speaker in the form of an earphone in a single unit worn by the user.

The voice-activated command and control system in accordance with the invention may also be implemented for cooperative vehicle control with a separate controller utilizing 30 either parallel or a series command configuration, or a combination thereof. In such instances, the separate controller will include provision for certain control functions (designated the trim control functions for purposes hereof), with the control module of the system and the controller cooperatively 35 transmitting (a) control function signals responsive to verbal commands received by the microphone and (b) trim control function signals, respectively, to the vehicle by wireless transmission. In the parallel command control implementation, there will be a common command set whereby the vehicle is 40 alternately responsive to the control function signals in the common command set from the verbal commands received by the microphone and from the trim control functions independently of each other. In the series command control implementation, there will be a common command set whereby the 45 vehicle is exclusively responsive to individual control function signals in the common command set from either a verbal command received by the microphone or a trim control function. In preferred embodiments, such cooperative implementation is effected with the conventional hand-held manual 50 controller capable of providing manual trim control functions.

In general, a voice-activated command and control system in accordance with the invention transmits control function signals via radio waves or other applicable technologies for a 55 wireless-controlled powered airplane, a sail plane, a boat, a helicopter, a wheeled vehicle or like remotely controlled devices. Such vehicles may be real or simulated vehicles. Thus, for simulated vehicles, the voice-activated command and control system (a) communicates with a microprocessor 60 simulated environment for implementing the vehicle, and (b) transmits the control function signals by simulated wireless transmission to the simulated vehicle. In certain embodiments, the voice-activated command and control system is further configured to select or control operational or environ-65 mental parameters of the simulated environment responsive to additional verbal commands spoken to the microphone.

6

The two-way voice-activated command and control system may be further implemented in a multiplexed monitoring and/or interactive system for communications with, for example, other operators, ground personnel, observers, a microprocessor-based system in the roll of an observer or supervisor.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a flowchart illustrating a one-way voice activated command and control system and a R/C device.

FIG. 2 is a flowchart illustrating a two-way voice activated command and control system and a R/C device, with voicefeedback.

FIG. 3 is a flowchart illustrating an alternate two-way voice activated command and control system and a R/C device, with non-voice-feedback.

FIG. 4 is a flowchart illustrating a two-way voice activated command and control system and a R/C simulation device.

FIG. 5 is a flowchart illustrating a two-way voice activated command and control system with multiple signal transmission and a R/C device.

FIG. 6 is a view of a conventional hand-held controller, with the center antenna being substantially cut-off from view.

FIG. 7 is a view of a headset for communicating with an R/C device through a two-way voice activated command and control system.

FIG. 8 is a perspective view of a pocket unit for communications with an R/C device.

FIG. 9 is a perspective view of a clip-on unit for communications with an R/C device.

FIG. 10 is a flowchart illustrating parallel independent control of an R/C device by a hand-held controller and a voice-activated command and control system.

FIG. 11 is a flowchart illustrating series dependent control of an R/C device by a hand-held controller and a voiceactivated command and control system.

While the invention is susceptible of various modifications and alternative constructions, certain illustrated embodiments have been shown in the drawings and will be described below in detail. It should be understood, however, that there is no intention to limit the invention to the specific forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions, and equivalents falling within the spirit and scope of the invention.

DETAILED DESCRIPTION OF THE INVENTION

This invention relates to a voice-activated, and optionally voice-enunciated, command and control for remotely controlled vehicles. For purposes of illustration, the system is generally described herein in connection with a radio-controlled (R/C) remotely-controlled vehicle, but is applicable for use with all types of real and simulated or virtual remotely-controlled vehicles. In preferred embodiments, the invention relates to two-way voice-activated, and optionally voice-enunciated, command and control for remotely controlled vehicles. The invention may also be implemented in a one-way voice-activated command and control for remotely controlled vehicles. Of the several embodiments illustrated in the drawings and described herein, a common aspect of the invention relates to voice-triggering or voice-activation of command and control functions of the R/C device, with optional voice-activated feedback indicators provided to the operator in relation to various functions of the vehicle and/or its environment.

A preferred system in accordance with the invention provides two-way voice-activated command and control between operational control and/or telemetry data systems on-board an R/C device, and its operator and/or operators (interchangeably referred to herein as the "operator"). The 5 two-way voice system causes the data captured by a telemetry system on-board the R/C device to be transferred to the operator using the operator's speaking voice spoken through a microphone commanding or triggering the transfer. This data transfer is presented to the operator by a microprocessor- 10 generated voice that is transmitted through a speaker or through earphones worn over the operator's ears. Control of this two-way R/C system is to enable the operator to use his or her voice speaking through a microphone to command or trigger a R/C device's on-board control systems to effect 15 response and control of various control functions in real time to the R/C device. Another use of the system is to allow the operator to command or trigger as described herein to a simulated R/C device through the use of a R/C simulator.

One implementation of the invention is represented in the 20 flowchart shown in the drawings in FIG. 1 in a one-way voice activated command and control system as used by an operator 10 with a R/C device 22. The R/C device is a conventional type R/C device, equipped with wireless control and telemetry data module including an on-board radio-wave transmit- 25 ter/receiver controller, control servos and electronic sensors. The voice activated command and control system includes a voice activated microphone 14, and a voice activated wireless control and telemetry data module 18. To operate the R/C device, the operator 10 speaks a command that is transmitted 30 via sound waves 12. The microphone 14 includes receiver, converter and transmitter modules to receive the sound waves and convert the verbal instruction into a transmitted signal 16 (e.g., electrical, electronic, digital, wireless). The control module 18 includes receiver, converter and transmitter mod- 35 ules to receive and convert the transmitted signal 16 and transmit a wireless (e.g., radio wave) signal 20 to the R/C device. This microphone can be located in a headset 34 such as shown in FIG. 7, in a pocket unit 72 (FIG. 8) or clip-on unit 74 (FIG. 9), or in the hand-held controller 50 such as shown in 40 FIG. 6.

The control module **18** is programmed (or otherwise operable) to recognize an array of converted verbal instructions corresponding to the operational variables of the R/C device, and to transmit associated wireless interactions to the R/C 45 device such that the R/C device responds to the wireless instructions in its normal manner. For example, if the operator speaks the words "flaps thirty" into the microphone, the microphone converts this verbal instruction into an electronic signal. This electronic command signal is sent to the control 50 module which recognizes the command, converts it, and transmits to the R/C device a wireless command signal to cause or result in the flaps moving to their thirty-degree position.

The control module **18** is located in a unit in communica-55 tion with or integrated with the microphone. In a preferred embodiment, the control module **18** is integrated into a handheld R/C controller **50** such as an otherwise generally conventional-type configuration with which the operator is familiar (see e.g., FIG. **6**). The control module includes a prior 60 programmed microprocessor and will comprise a second control path, in parallel to and/or in series with the conventional control path, in the hand-held controller so that the R/C device can be controlled verbally in accordance with the invention, and/or with conventional levers and switches (see further 65 discussion below). The converted verbal signal is matched by the microprocessor to the applicable command signal which 8

triggers the control action to the flap control interface and generating of the applicable wireless signal which is then transmitted to the on-board receiver on the R/C device via radio waves. The transmitted signal is received by the R/C device and then converted to operate the controlling servo linked to the flaps and the flaps move down to a thirty-degree position.

The voice activated command and control system of the invention is applicable for use with all types of R/C vehicles, each of which will have a hand-held controller similar in function and operation to an aircraft controller (as described above), but of course, with trim and auxiliary controls and switches modified to control operation of the applicable vehicle, with the variable operational parameters particularly applicable to such specific-type vehicles.

For example, other commonly available R/C vehicles include other air vehicles such as sail planes and helicopters, water vehicles such as boats, and land vehicles such as cars and trucks. Examples of the controllable operational variables in such vehicles include:

- (a) for sail planes: rudder, elevators and ailerons (collectively aircraft "trim" controls), air brake, flaps and dualrate controls;
- (b) for boats: rudder and throttle (collectively boat "trim" controls), horn, lights, and trim;
- (c) for helicopters: cyclic control forward, backward, left, and right, main rotor pitch control, rear rotor pitch control, and throttle (collectively helicopter "trim" controls), standard forward flight, aerobatic flight, exponential, lights and retractable landing gear, smoke; and
- (d) for cars and trucks: steering and throttle or engine speed (collectively wheeled vehicle "trim" controls), and lights, sounds (e.g., horns, engine, air brakes), smoke, forward and reverse, vibration.

The invention, when modified for the specific-type vehicle, will be applicable to all types of R/C vehicles and devices.

The invention is also applicable, and will be functionally equivalently provided for by persons skilled in the relevant art, for voice-activated command and control for control of virtual (simulated) vehicles as utilized in vehicle control simulators. In this instance, the voice activated command and control system can be configured for selection or control of the operational or environmental parameters of the simulator or simulation software.

As further illustration, a second implementation of the present invention is represented in the flowchart shown in the drawings in FIG. 2 in a two-way command and control system as used by an operator 10 with a R/C device 22. In this instance, operational control of the device 22 proceeds as described above, but the system includes provision for return data, from the R/C device back to the operator, to provide the operator with audible feedback and confirmation of completion of control commands transmitted to the R/C device. More particularly, the control system further includes a wireless voice generating and telemetry data module 26 and a wireless receiving speaker included in the voice-activated unit with the microphone, such as an ear piece 30 included in an operator's headset 34. The module 26 includes receiver, converter and transmitter modules to receive and convert a signal 24 from the on-board controller 22 of the R/C device confirming receipt and/or completion of a control command and transmit a wireless (e.g., radio wave) signal 28 to the headset or other configured control unit. The headset and/or ear piece includes receiver, converter and transmitter modules to receive the wireless signal 28 and convert it into a spoken or other sound at the ear piece to provide the operator with audible confirmation of receipt and/or execution of the con-

5

trol command. In the case of the system providing confirmation of execution, the R/C device will include appropriate sensors and/or feedback elements, conventional for the parameter to be detected, to provide the on-board controller with a signal confirming completion of the command.

A second alternate implementation of the invention represented in the flowchart shown in FIG. 3 is a two-way command and control system as generally described above, except that in this instance the system includes provision for return data, from the R/C device to the operator as audible or 10 visual non-voice feedback and/or confirmation of completion of control commands transmitted to the R/C device. More particularly, the control system is provided with feedback 48 from the R/C device to a non-voice generating data module 52 that generates a non-voice audible or visual feedback indica- 15 tor 54 to the operator. The data module 52 can be located in the hand-held controller 50 as shown, or it can be located otherwise for the convenience of the operator such as indicated above. This non-voice feedback is provided to the operator responsive to voice-activation by the operator such 20 that the operator controls what feedback he receives and when for timing of the feedback at his convenience. This non-voice feedback can be presented to the operator in any convenient manner such as by illumination of an LED screen, illumination of LED indicators, beeping, etc. 25

As illustrated in FIG. **4**, the voice activated command and control system of the invention is applicable for use with a simulation program or in a flight simulating device with such a program. In this instance, a computer **36** (or other configured, processor-controlled device) is programmed to simulate 30 the operation and response of the R/C device, and the voice activated command and control system of one of the types discussed herein, including all of the operative modules, for interfacing with the simulated remotely-controlled vehicle and the headset **34**. 35

As illustrated in the flowchart shown in FIG. 5, the voice activated command and control system of the invention, shown as implemented in a two-way system, is also applicable for multiplexing headsets 34, earphones 30 and the like as applicable for use by or in connection with one or more 40 operators 10A, ground support personnel 10B, an observer 10D, a loudspeaker 10E, and/or a computer and voice activated control unit or other microprocessor-based unit 10C at one time. Primary voice-activated command and control is affected by the operator(s) with voice signals 12A converted 45 through microphone(s) 14 that transmit the converted signal to a control signal buss 12 that delivers the control signal to the module 18. A multiplex system of this type may further include provision for optional and/or override voice-activated command and control as desired by the ground support per- 50 sonnel with voice signal 12B that is similarly converted and delivered to the control signal buss 12; and/or by the computer 10C with an electronic signal 12C transmitted through or converted by module 14C for delivery of a compatible signal to the control signal buss 12. This multiplex system will also 55 include provision for all parties in the system to monitor all two-way communications between the control signal buss 12 and the R/C device. As illustrated in FIG. 5, the operator(s) 10A, the ground support personnel 10B, and the observer 10D will receive both signals 12 from the control buss and 28 from 60 the R/C device through ear piece 30 which signals are delivered via combined audible signal 42. The loudspeaker 10E and the computer 10C will also receive both signals 12 from the control buss and 28 from the R/C device but transmitted through compatible modules 30E, 30C for delivery of com- 65 patible signals 42E, 42C indicative of the two-way communications with the R/C device.

10

A voice-activated command and control system in accordance with the invention can be further implemented in either (1) a parallel-type system wherein operation of the voiceactivated command control system is independent from operation of manual controls such as provided by a hand-held controller 50, or (2) a series-type system wherein operation of the voice-activated command control system is interdependent with operation of manual controls. To the extent that the voice-activated controls are independent from the conventional manual controls, the R/C device will be provided with a separate, independent on-board system for each the voiceactivated controls and the manual controls. It is further noted that of the numerous control parameters of the various R/C devices, only the proportional trim controls, such as controlled by the two joy sticks of the conventional hand-held controller, are typically considered as essential controls aspects, and that in all preferred embodiments of the invention such essential control aspects can at least be optionally controlled by the hand-held controller. To the extent that the controls are implemented in parallel, the conventional controller provides an operational backup should the voice-activated control system experience operational difficulties, such as not recognizing the operator's verbal commands.

A parallel-type system is illustrated in the flowchart in FIG. 10. The operator 10 controls at least a first set of control functions of the R/C device 22 via manual control indicated at 58 through the manually-controlled module 60 of the handheld controller which delivers signal 62 to the R/C device for control of said first set of control functions. The operator further controls at least a second set of control functions of the R/C device via voice signal 12 as converted and transmitted as described above and delivered via signal 20 to the R/C device for control of said second set of control functions. This second set of control functions may include some or all of the first set of control functions, in which case operation of the overlapping control functions can be operated independently by either manual or voice-activated control. The second set of control functions may alternately not overlap the first set of control functions, in which case both manual and voice-activated control will be required for full control of the R/C vehicle.

A cascaded or series-type system is illustrated in the flowchart in FIG. 11. The operator 10 is capable of controlling a first set of control functions of the R/C device 22 via manual control indicated at 58 through the manually-controlled module 60 of the hand-held controller via signal 62. The operator is further capable of controlling a second set of control functions of the R/C device via voice signal 12 as converted and transmitted as described above via signal 20. In this instance, the signals 62 and 20 are delivered to a signal conditioning module 66 that selects the signal(s) 20 and/or 62 to deliver to the R/C vehicle. Thus, if both signals 20 and 62 carry instructions for the same control function of the R/C device, only one signal will be delivered the R/C device (or a combination thereof), which signal will be selected (combined, conditioned, etc.) according to an algorithm pre-established in the module 66 according to the vehicle with which the controller is used including consideration for operational control and safety parameters of the vehicle. In this instance, it is presumed that the first set of control functions applicable to manual control and the second set of control functions applicable to the voice-activated control overlap, and that the selection, combination or conditioning algorithm that is preestablished in the device 66 acts only on such overlapping functions, passing through those signals associated with nonoverlapping R/C device control functions. Otherwise, with-

out overlapping control functions, the system illustrated in FIG. **11** will be operatively equivalent to the system illustrated in FIG. **10**.

One example of overlapping control functions and a suitable control algorithm, using the voice activated command 5 and control system in controlling an R/C airplane (22) in controlled flight with over lapping control functions, is as follows: While the pilot is controlling the airplane in level flight with the manually actuated joysticks in the hand held transmitter/receiver unit 50; he or she speaks the words "snap 10 roll" into the microphone 14. Snap Roll is a name of an aerobatic flight maneuver performed by the airplane using its control surfaces. These words are matched by the microprocessor to the proper preprogrammed "flight controls sequence program" (in module 66), which will momentarily over ride the manual joy stick controls administered by the pilot's fingers and/or thumbs and run though its control function produced by the microprocessor controlling the airplanes flight control surfaces to cause the airplane to perform a snap roll maneuver. After the microprocessor-generated control 20 function ends the flight control is reverted immediately back to the pilot's manually operated joysticks (via module 66). If for any reason the pilot wants to terminate the preprogrammed "flight controls sequence program" before it's completion he or she speaks the word "stop" into the micro- 25 phone which immediately reverts the control back to the manual flight control joysticks from the microprocessor and resets the "flight controls sequence program". In a two-way voice activated command and control system the pilot would receive a microprocessor-generated voice feed back in the 30 headset speaker 30. These words could be "copy snap roll" followed by "snap roll complete" or "copy stop" to let the pilot know that the flight control process has been received and completed or function terminated electronically. Of course, many other operational scenarios for overlapping 35 control functions can be implemented within the scope of the invention.

As previously noted, those skilled in the art will readily devise additional alternate embodiments and implementations of the invention in view of the disclosure of the unique 40 arrangement shown in the drawings and discussed above. Such additional alternate embodiments and implementations will include, but not be limited to combinations of various aspects of the specific implementations illustrated in the drawings and discussed above. 45

I claim:

1. A voice-activated command and control system for a line-of-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control 50 functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if applicable, 55 the auxiliary control functions on the model responsive to corresponding trim control function signals and auxiliary control function signals received; the voice-activated command and control system comprising:

- a) a portable microphone for receiving an audible com- 60 mand from an operator; and
- b) a portable voice-activated control module for transmitting a control function signal responsive to the audible command received by the microphone to the model by wireless transmission;

65

c) wherein the portable microphone and portable voiceactivated control module allow the operator, using his or 12

her voice, to speak a word command into the portable microphone to voice activate and remotely control at least one of said control functions of the model; and

 d) a portable hand-held controller with manually operated trim-function controls corresponding to the trim control functions of the model, the portable hand-held controller transmitting said trim control function signals by wireless transmission to the model responsive to the operator's manual operation of said trim-function controls; whereby stable propulsion and control of the model can be achieved with the portable hand-held controller independently of the voice-activated control module.

2. The voice-activated command and control system as defined in claim 1 in which the portable control module recognizes certain audible commands comprising a first descriptive part and a second numeric or relational part.

3. The voice-activated command and control system as defined in claim 1 further comprising a headset that carries the portable microphone.

4. The voice-activated command and control system as defined in claim 1 in which the portable microphone and the portable control module are located together in a single unit.

5. The voice-activated command and control system as defined in claim 1 wherein portable control module and the portable hand-held controller cooperatively transmitting (a) control function signals responsive to audible commands received by the portable microphone and (b) manual trim control function signals, respectively, to the model by wire-less transmission in parallel for a common command set whereby the model is alternatively responsive to the control function signals in said common command set from the audible commands received by the portable microphone and from the manual trim control functions independently of each other.

6. The voice-activated command and control system as defined in claim **1** wherein the portable voice-activated control module and the portable hand-held controller cooperatively transmitting control function signals responsive to audible commands received by the portable microphone and manual trim control function signals, respectively, to the model by wireless transmission in series for a common command set whereby the model is exclusively responsive to individual control function signals in said common command set from either an audible command received by the portable microphone or a manual trim control function.

7. The voice-activated command and control system as defined in claim 1 in which the portable control module (a) communicates with a microprocessor simulated environment for implementing the model, and (b) transmits the control function signals by simulated wireless transmission to the simulated model.

8. The voice-activated command and control system as defined in claim 7 in which the portable control module is further configured to select or control operational or environmental parameters of the simulated environment responsive to additional audible commands spoken to the portable microphone.

9. The voice-activated command and control system as defined in claim **1** in which the portable control module transmits the control function signals by radio waves to the model.

10. A two-way voice-activated command and control system for a line-of-sight remotely controlled model; the model having trim control functions that are required for stable propulsion and control of the module; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the model; the model having

15

35

an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission, (b) control the trim control function and, if applicable, the auxiliary control functions on the model responsive to corresponding trim control function sig- 5 nals and auxiliary control function signals received, and (c) transmit feedback signals by return wireless transmission indicative of at least one of (i) the control function signals received, (ii) status of the control functions on the model responsive to the corresponding control function signals 10 received, and (iii) model operational or environmental data; the two-way voice-activated command and control system comprising:

- a) a portable microphone for receiving an audible command from an operator;
- b) a portable voice-activated control module for transmitting a control function signal responsive to the audible command received by the microphone to the model by wireless transmission;
- c) a portable feedback indicator responsive to feedback 20 signals received by return wireless transmission from the model;
- d) wherein the portable microphone and portable voiceactivated control module allow the operator, using his or her voice, to speak a word command into the portable 25 microphone to voice activate and remotely control at least one of said control functions of the model; and
- e) a portable hand-held controller with manually operated trim-functions controls corresponding to the trim control function signals by wireless transmission to the 30 model responsive to the operator's manual operation of the trim-function controls whereby stable propulsion and control of the model can be achieved with the portable hand-held controller independently of the portable voice-activated control module.

11. The two-way voice-activated command and control system as defined in claim 10 in which the portable control module recognizes certain audible commands comprising a first descriptive part and a second numeric or relational part.

12. The two-way voice-activated command and control 40 system as defined in claim 10 in which the portable microphone and portable feedback indicator are located together in a single unit.

13. The two-way voice-activated command and control system as defined in claim 10 in which the portable feedback 45 indicator provides at least one of an audible feedback indicator and a visual feedback indicator responsive to return feedback signals from the model.

14. The two-way voice-activated command and control system as defined in claim 10 in which the portable feedback indicator includes a speaker to produce said audible feedback in the form of spoken communication, and a headset that carries the portable microphone and the speaker in a single unit.

15. The two-way voice-activated command and control system as defined in claim 10 wherein the portable voiceactivated control module and the portable hand-held controller cooperatively transmitting (a) control function signals responsive to audible commands received by the portable microphone and (b) manual trim control function signals, respectively, to the model by wireless transmission in parallel for a common command set whereby the vehicle is alternatively responsive to the control function signals in said common command set from the audible commands received by the microphone and from the manual trim control functions independently of each other.

16. The two-way voice-activated command and control system as defined in claim 10 wherein the portable voiceactivated control module and the portable hand-held controller cooperatively transmitting (a) control function signals responsive to audible commands received by the portable microphone and (b) manual trim control function signals, respectively, to the model by wireless transmission in series for a common command set whereby the model is exclusively responsive to individual control function signals in said common command set from either an audible command received by the microphone or a manual trim control function.

17. The two-way voice-activated command and control system as defined in claim 10 in which the portable control module (a) communicates with a microprocessor simulated environment for implementing the model, and (b) transmits the control function signals by simulated wireless transmission to the simulated model.

18. The two-way voice-activated command and control system as defined in claim 10 in which the portable control module is further configured to select or control operational or environmental parameters of the simulated environment responsive to additional audible commands spoken to the portable microphone.

19. The two-way voice-activated command and control system as defined in claim 10 in which the portable control module transmits the control function signals by radio waves to the model.

20. The two-way voice-activated command and control system as defined in claim 10 further comprising a second portable feedback indicator connected for multiplexed monitoring of the audible commands and the return feedback signals.

EXHIBIT B

Application of U.S. Patent No. 8,401,860 to Best Choice Products ("BCP") Voice Command Quadcopter with HD Camera ("the Accused Product") *,**

* The term "the Accused Products" includes BCP's Voice Command Quadcopter as well as all other products made, used, sold, offered for sale and/or imported by BCP, or one of its subsidiaries, that have the features shown in this chart, or substantially similar features.

** This claim chart is meant to be illustrative for purposes of meeting Plaintiff's pleading obligations and should not be construed as limiting or binding. Plaintiff will serve infringement contentions in this case in accord with the Local Rules and schedule entered by the Court.

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 26 of 50 Page ID #:26 Application of U.S. Patent No. 8,401,860 to the Accused Product

1. A voice-activated command and control system for a lineof-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if applicable, the auxiliary control functions on the model responsive to corresponding trim control function signals and auxiliary control function signals received; the voiceactivated command and control system comprising:

The Accused Product is part of the claimed voice-activated command and control system. The Accused Product, in combination with the Accused Product's phone app and a user's smartphone, constitutes an infringing system. On information and belief, Best Choice Products ("BCP") has directly infringed the `860 patent via its use of the infringing system in connection with at least its testing and use of the Accused Product. In addition, and in the alternative, BCP has induced infringement of the `860 patent by end users (*e.g.*, customers) of the Accused Product using the infringing system. The Accused Product includes a voice-activated command and control system for a line-of-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model, as evidenced below.



HOVER UP & DOWN: Move the left control lever (throttle) up or down, and the quadcopter will gain or lose elevation.



ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter will roll to the left or right.



FORWARD & BACKWARD: Move the right control lever up or down, and the quadcopter will fly forward or backward.



RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

Source: Exhibit 1, Accused Product Instruction Manual.

Claim 1 (cont'd) Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 27 of 50 Page ID #:27 Application of U.S. Patent No. 8,401,860 to the Accused Product

1. A voice-activated command and control system for a lineof-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if applicable, the auxiliary control functions on the model responsive to corresponding trim control function signals and auxiliary control function signals received; the voiceactivated command and control system comprising:



Source: Exhibit 2, Picture of Accused Product



Source: Exhibit 3, Picture of Product Packaging for Accused Product

Claim 1 Case 8:	19-cv-01807 Document 1 Filed 09/20/19 Page 28 of 50 Page ID #:28 Application of U.S. Patent No. 8,401,860 to the Accused Product
1. A voice-activated command and control system for a line- of-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if	The Accused Product has trim control functions that are required for stable propulsion and control of the model (e.g., evidenced at least by the left control lever, right control lever, and fine tuning controls).
functions on the model responsive to corresponding trim control function signals	ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

Source: Exhibit 1, Accused Product Instruction Manual.

signals received; the voiceactivated command and control

system comprising:

Claim 1 Case 8:	19-cv-01807 Document 1 Filed 09/20/19 Page 29 of 50 Page ID #:29 Application of U.S. Patent No. 8,401,860 to the Accused Product
1. A voice-activated command and control system for a line- of-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if applicable, the auxiliary control functions on the model responsive to corresponding trim control function signals and auxiliary control function signals received; the voice- activated command and control system comprising:	The Accused Product has trim control functions that are required for stable propulsion and control of the model (<i>e.g.</i> , evidenced at least by the left control lever, right control lever, and fine tuning controls).

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 30 of 50 Page ID #:30 <u>Application of U.S. Patent No. 8,401,860 to the Accused Product</u>

1. A voice-activated command and control system for a lineof-sight remotely controlled model having trim control functions that are required for stable propulsion and control of the model; the model optionally having auxiliary control functions that are not required for stable propulsion and control of the module; the model having an on-board controller to (a) receive trim control function signals and, if applicable, auxiliary control function signals, by wireless transmission and (b) control the trim control functions and, if applicable, the auxiliary control functions on the model responsive to corresponding trim control function signals and auxiliary control function signals received; the voiceactivated command and control system comprising:

On information and belief, there is a controller onboard the Accused Product that (a) receives the trim control function signals by wireless transmission, and (b) control the trim control functions on the model responsive to corresponding trim control function signals received. The controller onboard the Accused Product executes said functions by making the quadcopter move, as evidenced below.



HOVER UP & DOWN: Move the left control lever (throttle) up or down, and the quadcopter will gain or lose elevation.



ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter will roll to the left or right.

FORWARD & BACKWARD: Move the right control lever up or down, and the quadcopter will fly forward or backward.



RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

Source: Exhibit 1, Accused Product Instruction Manual.



<u>Claim 1 (cont'd)</u>	19-cv-01807 Document 1 Filed 09/20/19 Page 32 of 50 Page ID #:32 Application of U.S. Patent No. 8,401,860 to the Accused Product		
b) a portable voice-activated control module for transmitting a control function signal responsive to the audible command received by the microphone to the model by wireless transmission;	<complex-block></complex-block>		

Claim 1 (cont'd)	:19-cv-01807 Document 1 Filed 09/20/19 Page 33 of 50 Page ID #:33 Application of U.S. Patent No. 8,401,860 to the Accused Product		
Claim 1 (cont'd) c) wherein the portable microphone and portable voice- activated control module allow the operator, using his or her voice, to speak a word command into the portable microphone to voice activate and remotely control at least one of said control functions of the model; and	The portable microphone and portable voice-activated control module of the Accused Product allow the operator, using his or her voice, to speak a word command into the portable microphone to voice activate and remotely control at least one of said control functions of the model.		
	Flight Planning: Flightpath mimics what you draw Headless Mode: Fly the drone at any orientation Calibrate Gyroscope		
	One touch take-off		
	Emergency stop Emergency stop Take off" "Landing" "Forward" "Backward" "Left" "Right"		
	Source: Exhibit 1 Accuracy Draduct Instruction Manual		
	Source: Exhibit 1, Accused Product Instruction Manual.		

Claim 1 (cont'd) Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 34 of 50 Page ID #:34 Application of U.S. Patent No. 8,401,860 to the Accused Product

c) wherein the portable microphone and portable voiceactivated control module allow the operator, using his or her voice, to speak a word command into the portable microphone to voice activate and remotely control at least one of said control functions of the model; and

The portable microphone and portable voice-activated control module of the Accused Product allow the operator, using his or her voice, to speak a word command into the portable microphone to voice activate and remotely control at least one of said control functions of the model.



Source: Exhibit 3, Picture of Product Packaging for Accused Product

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 35 of 50 Page ID #:35 <u>Application of U.S. Patent No. 8,401,860 to the Accused Product</u>

d) a portable hand-held controller with manually operated trim-function controls corresponding to the trim control functions of the model, the portable handheld controller transmitting said trim control function signals by wireless transmission to the model responsive to the operator's manual operation of said trim-function controls; whereby stable propulsion and control of the model can be achieved with the portable hand-held controller independently of the voiceactivated control module.

The Accused Product includes a portable hand-held controller with manually operated trim-function controls corresponding to the trim control functions of the model (*e.g.*, at least left control lever, right control lever, and fine tuning controls). The controller transmits said trim control functions via wireless transmission to the quadcopter, which responds to the operator's manual command(s). The same is also true if the manual controls in the Accused Product phone app are used (*see supra* slide 10).



HOVER UP & DOWN: Move the left control lever (throttle) up or down, and the quadcopter will gain or lose elevation.



FORWARD & BACKWARD: Move the right control lever up or down, and the quadcopter will fly forward or backward.



ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter will roll to the left or right.



RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

Source: Exhibit 1, Accused Product Instruction Manual.

Claim 1 (cont'd) Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 36 of 50 Page ID #:36 Application of U.S. Patent No. 8,401,860 to the Accused Product

d) a portable hand-held controller with manually operated trim-function controls corresponding to the trim control functions of the model. the portable hand-held controller transmitting said trim control function signals by wireless transmission to the model responsive to the operator's manual operation of said trim-function controls; whereby stable propulsion and control of the model can be achieved with the portable hand-held controller independently of the voiceactivated control module.

Via the hand-held controller of the Accused Product, stable propulsion and control of the model can be achieved with the portable hand-held controller independently of the voice-activated control module. The same is also true if the manual controls in the Accused Product phone app are used (*see supra* slide 10).



HOVER UP & DOWN: Move the left control lever (throttle) up or down, and the quadcopter will gain or lose elevation. FORWARD & BACKWARD: Move the right control lever up or down, and the quadcopter will fly forward or backward.



ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter will roll to the left or right.



RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

Source: Exhibit 1, Accused Product Instruction Manual.

bcb

bestchoiceproducts

EXHIBIT 1



Voice Command Quadcopter with HD Camera

SKY3474



- explosion. Only use the supplied battery and charger. Use of the rechargeable battery and charger for any other product may result in overheating, fire, or
- explosion. Never use the supplied rechargeable battery and charger with another product.
- Explosive gases are created during charging. Charge the battery in a well-ventilated area. Do not charge the battery near heat or flammable materials.
- Contact between the positive and negative terminals may result in fire or explosion. Avoid direct contact Contact between the positive up the battery by the wires or charger can cause damage to the battery by its case or bandles and may result in a fire. Always pick up the battery by its case or handles.
- · Liquids on the battery may cause fire or electric shock. Always keep all liquids away from the battery and keep the battery dry. Contact or exposure to battery leakage (lead acid) may cause serious injury. If contact or exposure occurs immediately call your physician. If the chemical is on the skin or in the eyes flush with cool water for 15 minutes. If the chemical was swallowed, immediately give the person water or milk. Do not give water or milk if the patient is vomiting or has a decreased level of alertness. Do not induce vomiting.
- Battery posts, terminals, and related accessories contain lead and lead compounds (acid) chemicals known to the State of California to cause cancer, reproductive harm, and are toxic and corrosive. Never open the battery.
- Tampering or modifying the electric circuit system may cause a shock, fire or explosion and permanently damage the system. Exposed wiring and circuitry in the charger may cause electric shock. Always keep the charger housing closed.

TOOLS REQUIRED.



PHILLIPS SCREWDRIVER (PROVIDED)



DXIMATELY

APPP

1 PERSON

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 39 of 50 Page ID #:39



SETTING UP YOUR QUADCOPTER DRONE:





Install the landing gear onto the bottom of the quadcopter with the four part 1 screws. NOTE: the landing gear is numbered and must be arranged according to the diagram above.

Install the propeller cages onto the corners of the quadcopter with four part 1 screws.

Pg.



1. Slide the camera into the designated slot on the battery cover.

2. Open the battery cover.

3. On the underside of the battery cover, secure the camera to the battery cover with two screws specific to the camera. Then close the battery cover

4. Insert the 3-pin plug from the camera into the designated slot next to the battery cover.



• R

• 1



HOVER UP & DOWN: Move the left control lever (throttle) up or down, and the quadcopter will gain or lose elevation.

FORWARD & BACKWARD: Move the right control lever up or down, and the quadcopter will fly forward or backward.



ROLL LEFT & ROLL RIGHT: Move the left control lever (throttle) left or right, and the quadcopter will roll to the left or right.

RIGHT & LEFT: Move the right control lever left or right, and the quadcopter will fly to the left or right.

FINE-TUNING YOUR QUADCOPTER (MODE 1)



FORWARD/BACKWARD FINE TUNING: If your quadcopter veers forward or backward, correct it with the forward/backward fine tuning button.

LEFT/RIGHT TURN FINE TUNING: If your quadcopter veers to the left or right, correct it with the left/right turn fine tuning button.



LEFT/RIGHT ROLL FINE TUNING: If your quadcopter rolls too much to the left or right, correct it with the left/right roll fine tuning button.

360° EVERSION

- Once you have a general understanding of how to control the quadcopter you can activate the 360-degree eversion function.
- Fly the quadcopter at a minimum height of 9 feet.
- Press the 360-degree eversion button located on the top right of the remote control, then move the right control lever in the direction you wish to flip.









Turn on the remote control and the quadcopter.

Push the left control lever (throttle) to the highest position, and then pull it back to the lowest position.

 (\bigcirc)

Hold the left and right control levers in the lower right corner position for 2 to 3

seconds. The lights will

a successful restart.

flash normally to indicate

CHARGING THE BATTERY

- Remove the battery from the quadcopter before charging.
- Charge the battery in a dry and ventilated location away from children.
- Let the the battery cool down before charging. Charging a warm battery could cause swelling and result in a fire hazard. If the battery becomes swollen, replace it immediately.
- Only use the provided USB charging cable.

CHARGE TIME: 1.5 hours | FLIGHT TIME: 5.5 to 6.5 minutes



Turn the quadcopter off and open the battery cover.

Pull the battery wire out of the

Connect the battery to the USB

power port.

charging cable. Make sure that the ports are securely attached. Plug the USB charging cable into an outlet or computer to charge.

Pg. 5



INSTALLING SPARE PROPELLERS

Make sure that the propellers (A) and reverse propellers (B) are attached to the correct locations. The following is the correct arrangement:



REMOTE CONTROL DIAGRAM

- 1. L/R turn fine tuning
- 2. Forward/backward fine tuning
- 3. L/R roll fine tuning
- 4. Throttle indicator
- 5. Forward indicator
- 6. Backward indicator
- 7. Left indicator
- 8. Right indicator
- 9. Left roll indicator
- 10. Right roll indicator
- 11. High/low speed display

- Battery level of remote control
 Mode 1 indicates normal roll and turn controls. Mode 2 indicates flipped roll and turn controls.
- 14. Wi-Fi signal strength

∇
01

Pg. 7

FOR FULL ACCESS TO THE DRONE'S FEATURES, DOWNLOAD THE PHONE APPI

iOS or Android: Download and install the app "FYD-FPV" from the following URL:

https://d.ihunuo.com/app/hoiy

DOWNLOAD & INSTALLATION

Use t

PR

AU

Pa

R

Note: The app will initially appear to be in Chinese because the product is made in China. This is a third-party app; Best Choice Products does not own or operate this app. Please contact the developer through the app store if you have any questions or concerns.

APP OPERATION

Turn on the drone. Navigate to your phone's Wi-Fi settings and connect to the drone's Wi-Fi hotspot. The hotspot is named: YD-UFO-XXXXXX

Open the FYD-FPV app and the following menu will appear:

The following is the main menu:

APP SETTINGS

REMOTE CONTROL INTERFACE

PRACTICE MODE

Pg. 8

Case 8:19-cv-01807 Document 1 Filed 09/20/19 Page 45 of 50 Page ID #:45

Auto Save Parameters

ON: Photo/video saves to media storage within app

Parameters

SETTINGS

0

OFF: Photo/video saves to camera's SD card

Reset

Right hand mode

Flip roll and turn controls

Use the on-screen controls to practice flying a drone.

0

phone

remote control interface

additional functions Toggle

Flip the camera

~ First Person View (FPV) Fly the drone in first person view (FPV headset not included)

drone at any orientation Headless Mode: Fly the

Calibrate Gyroscope

One touch landing

"Right"

JI L

>

TROUBLESHOOTING

PROBLEM	CAUSE	SOLUTION
Non-responsive drone	 Drone battery is depleted Remote control battery is depleted Frequency on the remote control does not correspond to the drone 	 Charge the drone battery Charge/replace the remote control battery Adjust the frequency on the remote control while maintaining the frequency on the drone
Drone slow to respond or difficult to maneuver	 Remote control has insufficient power Another remote control on the same frequency is being used nearby 	 Change/replace the remote control battery Move out of range of the othe remote control

PRODUCT WARRANTY INFORMATION

All items can be returned for any reason within 60 days of the receipt and will receive a full refund as long as the item is returned in its original product packaging and all accessories from its original shipment are included. All returned items will receive a full refund back to the original payment method. All returned items will not be charged a re-stocking fee.

All returned items require an RA (Return Authorization) number, which can only be provided by a Best Choice Products Customer Service Representative when the return request is submitted. Items received without an RA may not be accepted or may increase your return processing time. Once an item has been received by Best Choice Products, refunds or replacements will be processed within 5 business days.

All returns must be shipped back to the Best Choice Products Return Center at the customer's expense. If the reason for return is a result of an error by Best Choice Products then Best Choice Products will provide a pre-paid shipping label via email. Boxes for return shipping will not be provided by Best Choice Products, and is the customer's responsibility to either use the original shipping boxes or purchase new boxes.

Pictures may be required for some returns to ensure an item is not damaged prior to its return. Items returned are not considered undamaged until they are received by Best Choice Products and verified as such. All damages to items are the customer's responsibility until the item has been received by and acknowledge by Best Choice Products as undamaged.

CONTACT US; WE'RE HERE 7 DAYS A WEEK TO HELP YOU!

bestchoiceproducts.com

customerservice@ bestchoiceproducts.com

or do in the lot of

844.948.8400

LEARN MORE

AWARNING

Manufacturer and seller expressly disclaim any and all liability for personal injury, property damage or loss, whether direct, indirect, or incidental, resulting from the incorrect attachment, improper use, inadequate maintenance, or neglect of this product.

EXHIBIT 3