

**IN THE UNITED STATES DISTRICT COURT  
FOR THE WESTERN DISTRICT OF TEXAS  
WACO DIVISION**

AMERICAN PATENTS LLC,

Plaintiff,

v.

ZEBRA TECHNOLOGIES  
CORPORATION,

Defendant.

CIVIL ACTION NO. 6:21-cv-639

ORIGINAL COMPLAINT FOR  
PATENT INFRINGEMENT

**JURY TRIAL DEMANDED**

**ORIGINAL COMPLAINT FOR PATENT INFRINGEMENT**

Plaintiff American Patents LLC (“American Patents” or “Plaintiff”) files this original complaint against Defendant Zebra Technologies Corporation (“Zebra”), alleging, based on its own knowledge as to itself and its own actions and based on information and belief as to all other matters, as follows:

**PARTIES**

1. American Patents is a limited liability company formed under the laws of the State of Texas, with its principal place of business at 2325 Oak Alley, Tyler, Texas, 75703.
2. Zebra Technologies Corporation is a corporation duly organized and existing under the laws of Delaware. Zebra Technologies Corporation may be served through its registered agent CT Corporation System at 1999 Bryan St., Ste. 900, Dallas, Texas 75201.
3. Zebra Technologies Corporation and its foreign and United States subsidiaries, affiliates, and related companies (“Zebra and its affiliates”) comprise one of the world’s largest manufacturers and sellers of marking, tracking, and printing technologies, including under the Zebra brand.

4. Zebra and its affiliates are part of the same corporate structure and distribution chain for the making, importing, offering to sell, selling, and using of the accused devices in the United States, including in the State of Texas generally and this judicial district in particular.

5. Zebra and its affiliates share the same management, common ownership, advertising platforms, facilities, distribution chains and platforms, and accused product lines and products involving related technologies.

6. Zebra and its affiliates regularly contract with customers regarding equipment or services that will be provided by their affiliates on their behalf.

7. Thus, Zebra and its affiliates operate as a unitary business venture and are jointly and severally liable for the acts of patent infringement alleged herein.

#### **JURISDICTION AND VENUE**

8. This is an action for infringement of United States patents arising under 35 U.S.C. §§ 271, 281, and 284–85, among others. This Court has subject matter jurisdiction of the action under 28 U.S.C. § 1331 and § 1338(a).

9. This Court has personal jurisdiction over Zebra pursuant to due process and/or the Texas Long Arm Statute because, *inter alia*, (i) Zebra has done and continues to do business in Texas; (ii) Zebra has committed and continues to commit acts of patent infringement in the State of Texas, including making, using, offering to sell, and/or selling accused products in Texas, and/or importing accused products into Texas, including by Internet sales and sales via retail and wholesale stores, inducing others to commit acts of patent infringement in Texas, and/or committing a least a portion of any other infringements alleged herein; and (iii) Zebra is registered to do business in Texas.

10. Venue is proper in this district pursuant to 28 U.S.C. § 1400(b). Venue is further proper because Zebra has committed and continues to commit acts of patent infringement in this

district, including making, using, offering to sell, and/or selling accused products in this district, and/or importing accused products into this district, including by Internet sales and sales via retail and wholesale stores, inducing others to commit acts of patent infringement in Texas, and/or committing at least a portion of any other infringements alleged herein in this district. Zebra has regular and established places of business in this district, including at least at 14000 Summit Dr. #900, Austin, Texas 78728, as Zebra has admitted in prior litigation, and at 507 E Howard Lane, Bldg 1, Austin, Texas 78753 as shown in the below screenshots:

**ZEBRA AROUND THE WORLD**

Zebra is a global leader in enterprise mobile computing, data capture, barcode printing and radio frequency identification devices. We provide **customers in more than 170 countries** with tools to help them achieve their mission-critical strategic business objectives. We have **6,500 employees in approximately 120 locations around the world**. Use the country selector below to find contact information for our offices, warehouses and facilities.

Select Your Location : <input type="text" value="United States"/>		
<b>Lincolnshire, IL - Corporate Headquarters</b> 3 Overlook Point Lincolnshire, Illinois 60069	<b>Holtsville, NY</b> 1 Zebra Plaza Holtsville, NY 11742 USA	<b>Agoura Hills, CA</b> 30601 West Agoura Road Agoura Hills, CA 91301 USA
<b>Alpharetta, GA</b> The Falls at Sanctuary Park 1125 Sanctuary Parkway Alpharetta, GA 30009-7610 USA	<b>Austin, TX</b> 507 E Howard Lane, Bldg 1 Austin, TX 78753	<b>Bentonville, AR</b> 1201 S.E. 28th Street Bentonville, AR 72712 USA

(Source: <https://www.zebra.com/us/en/about-zebra/contact-zebra/global-locations.html>)

**Travis CAD** Property Search Map Search

**Property Search Results > 1 - 1 of 1 for Year 2021** Export Results New Search

*Click the "Details" or "Map" link to view more information about the property or click the checkbox next to each property and click "View Selected on Map" to view the properties on a single map.*

Property Address   
  Legal Description

Property ID	Geographic ID	Type	Property Address	Owner Name	DBA Name	Appraised Value	
<input type="checkbox"/> 559795		Personal	507 E HOWARD LN 100 AUSTIN, TX 78753	ZEBRA TECHNOLOGIES CORPORATION	ZEBRA TECHNOLOGIES	\$795,301	<a href="#">View Details</a>

Page: 1

**Questions Please Call (512) 834-9317**

This site requires cookies to be enabled in your browser settings.

Website version: 1.2.2.30      Database last updated on: 6/8/2021 2:13 AM      © N. Harris Computer Corporation

(Source: screenshot from Travis County Appraisal District website)

### **BACKGROUND**

11. The patents-in-suit generally pertain to communications networks and other technology used in “smart” devices such as smartphones, smart TVs, and smart appliances. The technology disclosed by the patents was developed by personnel at Georgia Institute of Technology (“Georgia Tech”) and Nokia Corporation (“Nokia”).

12. Georgia Tech is a leading public research university located in Atlanta, Georgia. Founded in 1885, Georgia Tech is often ranked as one of the top ten public universities in the United States. The patents from Georgia Tech (“the Mody patents”) were developed by a professor and a graduate student in Georgia Tech’s Electrical and Computer Engineering department. The undergraduate and graduate programs of this department are often ranked in the top five of their respective categories.

13. The Mody patents are related to Multi-Input, Multi-Output (MIMO) technology. The inventors of the Mody patents were at the forefront of MIMO, developing, disclosing, and patenting a solution for achieving both time and frequency synchronization in MIMO systems. The Mody patents (or the applications leading to them) have been cited during patent prosecution hundreds of times, by numerous leading companies in the computing and communications

industries, including AMD, Alcatel Lucent, Altair, AT&T, Atheros, Blackberry, Broadcom, Comcast, Ericsson, Facebook, HP, Hitachi, Huawei, Infineon, Intel, Interdigital, IBM, Kyocera, Marvell, Matsushita, Mediatek, Motorola, NEC, Nokia, Nortel Networks, NXP, Panasonic, Philips, Qualcomm, Realtek, Samsung, Sanyo, Sharp, Sony, STMicroelectronics, Texas Instruments, and Toshiba.

14. Nokia is a Finnish multinational telecommunications, IT, and consumer electronics company. Listed on both the Helsinki Stock Exchange and the New York Stock Exchange, Nokia regularly makes the Fortune Global 500. Nokia has been the largest worldwide vendor of mobile phones and smartphones and has been a major contributor to the mobile phone industry.

15. The patent developed at Nokia (“the Rauhala patent”) is related to reduction of interference in receivers with multiple antennas. The inventors of the Rauhala patent have a combined fifty plus years of experience at Nokia and were prolific inventors for Nokia. Inventor Jyri Rauhala spent over 25 years at Nokia. Mr. Rauhala obtained a Master of Science in Applied Electronics, Digital Electronics from Tampere University of Technology in Finland and is named as an inventor on 15 U.S. patents. Inventor Olli-Pekka Lunden spent over 8 years at Nokia. Dr. Lunden obtained a Doctor of Science in Technology, Radio Engineering from Aalto University and is named as an inventor on 5 U.S. patents. Currently, Dr. Lunden works as a university lecturer at Tampere University of Technology in Finland. Inventor Marko Erkkila spent over twenty years at Nokia. Mr. Erkkila obtained a Master of Science in Digital Signal Processing, Electronics, Computer Science from Tampere University of Technology in Finland and is named as an inventor on 6 U.S. patents.

**COUNT I**

**INFRINGEMENT OF U.S. PATENT NO. 7,088,782**

16. On August 8, 2006, United States Patent No. 7,088,782 (“the ‘782 Patent”) was duly and legally issued by the United States Patent and Trademark Office for an invention entitled “Time And Frequency Synchronization In Multi-Input, Multi-Output (MIMO) Systems.”

17. American Patents is the owner of the ‘782 Patent, with all substantive rights in and to that patent, including the sole and exclusive right to prosecute this action and enforce the ‘782 Patent against infringers, and to collect damages for all relevant times.

18. Zebra used products and/or systems including, for example, its Zebra VC8300 Vehicle Mount Computer, Zebra TC52 and TC57 Series Touch Computer, and Zebra WT6300 Wearable Computer families of products that include 802.11n and above capabilities (“accused products”):

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER



**ZEBRA**  
CAPTURE  
YOUR EDGE

## VC8300 Vehicle Mount Computer

The ultimate ultra-rugged Android™ keyboard/touch vehicle mount computer

Since your Windows-based vehicle mount mobile computers are near their end-of-life and support for Windows-based mobile devices is ending, you're ready to migrate to Android™. You need a rugged device that will make that migration and device management simple, easy and cost-effective. Get it all with the VC8300. Designed for the most extreme environments, the VC8300 can go everywhere your vehicle operators need to go—inside the warehouse, out in the yard, on the loading dock and even in the freezer. Run your existing 'green screen' apps right out of the box—no ramp-up time required. Re-use all of your existing accessories<sup>1</sup>, minimizing the cost to upgrade to the latest technology. Replacement couldn't be easier—just drop it in place and you're ready to go. With Mobility DNA, only from Zebra, you get powerful features that transform Android into an easy-to-manage robust enterprise-class OS, complete with unique tools that not only boost workforce productivity, but also simplify deployment and application development. And since the same platform is shared with Zebra's rugged handheld and wearable mobile devices, virtually any worker can use any device with practically no training, providing the flexibility to deploy and re-deploy workers to address changing workloads.



### The Ultimate in Android Migration Simplicity

#### Run Your Terminal Emulation (TE) Apps, Right Out of the Box

Since Ivanti Velocity is pre-loaded and pre-licensed, you can run your TE apps right out of the box—no backend modification or user training required.

#### The Best of Both Worlds: Large Touchscreen and Keyboard

When it comes to data input, the VC8300 offers complete flexibility. The integrated full alphanumeric keyboard gives your workers the same familiar key-based interaction they use today—no change to workflow required. And the touchscreen allows you to integrate touch into your apps whenever you're ready.

#### Automatically Migrate Your TE Apps to Interactive Android Apps

When you're ready to transform your TE key-based apps to Android interactive apps, All-touch TE makes it easy. With this pre-loaded Zebra-only Mobility DNA application, just press a button to change TE 'green screens' to fully interactive Android screens that can be easily customized with All-touch TE tools—all without any coding.

### The Ultimate Android Platform for Business

#### Easy Viewing Indoors or Outside

The 8-inch display provides plenty of space for graphics-intensive, interactive applications, while best-in-class display resolution and brightness ensure easy viewing in any lighting condition. And the capacitive touch screen is easy to use, even with gloves.

#### Maximum Power for Maximum Application Performance

Get all the power you need to ensure superior performance with the ultra-powerful 8-core processor, plus up to eight times the RAM and 32 times the Flash memory of prior generation devices. And memory lasts 10 times longer through an advanced memory architecture.

#### A Lifetime Security Guard for Android

With LifeGuard™ for Android™, you get the security updates you need to keep your Zebra Android devices secure every day they are in service—along with easy end-to-end control of the OS update process, plus support for future versions of Android.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf))



PRODUCT SPEC SHEET  
TC52/TC57 SERIES TOUCH COMPUTER



## TC52 and TC57 Series Touch Computer

### The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA™, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

#### **Full shift power your workers can count on**

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>1</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

#### **Active Edge™ Touch Zone for One-touch Feature Access**

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))



PRODUCT SPEC SHEET  
WT6300 WEARABLE COMPUTER



## WT6300 Wearable Computer

The ultimate industrial wearable computer for hands-free mobility

With the explosion of ecommerce, picking and sorting have become full time jobs, not only in the warehouse, but in the retail store, where orders placed online need to be ready for pickup in as little as two hours. Empower your pickers and sorters to handle it all with the hands-free WT6300. Building on Zebra's WT6000, the WT6300 offers new features that take productivity and order accuracy to the next level. A new keypad option provides a familiar interface for manual keyed input. Get lightning fast application performance with more processing power, RAM and Flash memory. You get superior future proofing with Android 10, with a pathway to Android 11. It is rugged and ready for the toughest environments, including the freezer. Improved WiFi support delivers 'no-drop' dependable connections. Users get maximum Bluetooth peripheral performance and range with Bluetooth 5.0. Connect a Zebra Bluetooth ring scanner and HD4000 Head-Mounted Display for a complete solution. Plus, users can capture photos via a paired Zebra ring scanner to document proof of condition on-the-fly. The WT6300 — empowering your workers to keep pace with the e-commerce explosion.



Purpose-built industrial wearable computer

### Rugged and ready for everyday use in any environment — including the freezer

The WT6300 is dustproof, water-resistant and built to handle the inevitable everyday bumps and drops. Gorilla Glass delivers scratch and shatter resistance on the most crucial and vulnerable device component — the touchscreen display. The WT6300 is the only device in its class rated for freezer use, with a battery rated for operation at -22° F/-30° C. And it is drop-tested across the entire temperature range — crucial in freezer environments, where plastics become very brittle.

### Advanced glove-optimized rugged display

Many of your workers wear gloves — that's why the display automatically detects gloves and adjusts touch sensitivity as needed. The display works even when wet. And workers can use the many gestures they already know, such as pinch-to-zoom and swipe.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER

### Dependably Superior WiFi Connections

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement**

**improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**Fast ‘won’t drop’ high-performance WiFi connections**

Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

**Wireless LAN**

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

19. By doing so, Zebra has directly infringed (literally and/or under the doctrine of equivalents) at least Claim 30 of the ‘782 Patent. Zebra’s infringement in this regard is ongoing.

20. Zebra has infringed the ‘782 Patent by using the accused products and thereby practicing a method for synchronizing a Multi-Input Multi-Output (MIMO) Orthogonal Frequency Division Multiplexing (OFDM) system in time and frequency domains. For example, the accused products support IEEE 802.11 n/ac standards and MIMO technology. According to the IEEE 802.11n standard, the PLCP Protocol Data Unit (PPDU) has training fields and signaling fields for helping in synchronizing the communication system.

**PRODUCT SPEC SHEET**  
VC8300 VEHICLE MOUNTED COMPUTER

**Dependably Superior WiFi Connections**

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; 2x2 MU-MIMO
--------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement improves WiFi range and speed — with less power**

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

## WIRELESS LAN

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

### Fast ‘won’t drop’ high-performance WiFi connections


Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

## Wireless LAN

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))




(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

**Table 20-4—Elements of the HT PLCP packet**

Element	Description
L-STF	Non-HT Short Training field
L-LTF	Non-HT Long Training field
L-SIG	Non-HT SIGNAL field
HT-SIG	HT SIGNAL field
HT-STF	HT Short Training field
HT-GF-STF	HT-Greenfield Short Training field
HT-LTF1	First HT Long Training field (Data)
HT-LTFs	Additional HT Long Training fields (Data and Extension)
Data	The Data field includes the PSDU

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)





(Source: <https://www.cnrood.com/en/media/solutions/Wi-Fi-Overview-of-the-802.11-Physical-Layer.pdf>)

21. The methods practiced by Zebra's use of the accused products include producing a frame of data comprising a training symbol that includes a synchronization component that aids in synchronization, a plurality of data symbols, and a plurality of cyclic prefixes. For example, as part of the 802.11n standard, two preamble formats are defined for frames: HT-mixed format and HT-greenfield format. The non-HT and HT-mixed format preambles consist of training symbols, data symbols and guard intervals/cyclic prefixes, and the training symbols (L-STF and L-LTF fields) are and have been used for frame synchronization. Alternatively, on request from accused products, an 802.11 n/ac compliant WiFi access point can act as a transmitter and perform the step of producing a frame of data comprising a training symbol that includes a synchronization component that aids in synchronization, a plurality of data symbols, and a plurality of cyclic prefixes.


Two preamble formats are defined. For HT-mixed format operation, the preamble has a non-HT portion and an HT portion. The non-HT portion of the HT-mixed format preamble enables detection of the PPDU and acquisition of carrier frequency and timing by both HT STAs and STAs that are compliant with Clause 17 and/or Clause 19. The non-HT portion of the HT-mixed format preamble also consists of the SIGNAL field defined in Clause 17 and is thus decodable by STAs compliant with Clause 17 and Clause 19 as well as HT STAs.

The HT portion of the HT-mixed format preamble enables estimation of the MIMO channel to support demodulation of the HT data by HT STAs. The HT portion of the HT-mixed format preamble also includes the HT-SIG field, which supports HT operation. The SERVICE field is prepended to the PSDU.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



(Source: <https://www.cnrood.com/en/media/solutions/Wi-Fi-Overview-of-the-802.11-Physical-Layer.pdf>)

GI_TYPE	FORMAT is HT_MF or HT_GF	Indicates whether a short guard interval is used in the transmission of the packet. Enumerated type: LONG_GI indicates short GI is not used in the packet. SHORT_GI indicates short GI is used in the packet.	Y	Y
	Otherwise	Not present	N	N

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

22. The methods practiced by Zebra’s use of the accused products include transmitting the frame over a channel. The data frames containing the preambles are transmitted using one or more transmitting antennas. Alternatively, on request from an accused product, an 802.11 n/ac compliant WiFi access point can act as a transmitter and transmit the frame over a channel using one or more transmitting antennas.

### **20.3.9 HT preamble**

#### **20.3.9.1 Introduction**

The HT preambles are defined in HT-mixed format and in HT-greenfield format to carry the required information to operate in a system with multiple transmit and multiple receive antennas.

In the HT-mixed format, to ensure compatibility with non-HT STAs, specific non-HT fields are defined so that they can be received by non-HT STAs compliant with Clause 17 or Clause 19 followed by the fields specific to HT STAs.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

### **20.3.10 Transmission of NON\_HT format PPDU with more than one antenna**

When an HT device transmits a NON\_HT format PPDU with the MODULATION parameter set to OFDM or ERP-OFDM using more than one transmit chain, it shall apply the cyclic shifts defined in Table 20-8 to the transmission in each chain.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

23. The methods practiced by Zebra's use of the accused products include receiving the transmitted frame. For example, the receiving antennas of the accused products can receive the transmitted frames for further processing.

### **20.3.24 PLCP receive procedure**

Typical PLCP receive procedures are shown in Figure 20-23 and Figure 20-24. The receive procedures correspond to HT-mixed format and HT-greenfield format, respectively. A typical state machine implementation of the receive PLCP is given in Figure 20-25. These receive procedures and state machine do not describe the operation of optional features, such as LDPC or STBC. If the detected format indicates a non-HT PPDU format, refer to the receive procedure and state machine in Clause 17 or Clause 19. Further, through station management (via the PLME), the PHY is set to the appropriate frequency, as specified in 20.4. Other receive parameters, such as RSSI and indicated DATARATE, may be accessed via the PHY-SAP.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

24. The methods practiced by Zebra's use of the accused products include demodulating the received frame. For example, the received data frames are demodulated using the PLCP preambles.

**20.3 HT PLCP sublayer**

**20.3.1 Introduction**

A convergence procedure, in which PSDUs are converted to and from PPDU, is provided for the HT PHY in 20.3. During transmission, the PSDU is processed (i.e., scrambled and coded) and appended to the PLCP preamble to create the PPDU. At the receiver, the PLCP preamble is processed to aid in demodulation and delivery of the PSDU.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

25. The methods practiced by Zebra’s use of the accused products include synchronizing the received demodulated frame to the transmitted frame such that the data symbols are synchronized in the time domain and frequency domain. For example, different fields of data like training symbols, cyclic prefixes and other signal bits are present in the received frame. The training symbols (L-STF and L-LTF fields) help in synchronizing the frame in both the time domain and frequency domain.

**PRODUCT SPEC SHEET**  
VC8300 VEHICLE MOUNTED COMPUTER

**Dependably Superior WiFi Connections**  
Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**Fast ‘won’t drop’ high-performance WiFi connections**

Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.



(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

## Wireless LAN

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

- a) Detect the start of frame.
- b) Detect the transition from short sequences to channel estimation sequences, and establish fine timing (with one sample resolution).
- c) Estimate the coarse and fine frequency offsets.
- d) Derotate the frame according to estimated frequency offset.
- e) Estimate the complex channel response coefficients for each of the subcarriers and each of the transmit chains.
- f) For each of the data OFDM symbols, transform the symbol into subcarrier received values, estimate the phase from the pilot subcarriers in all spatial streams, derotate the subcarrier values according to estimated phase, group the results from all the receiver chains in each subcarrier to a vector, multiply the vector by a zero-forcing equalization matrix generated from the channel estimated during the channel estimation phase.
- g) For each data-carrying subcarrier in each spatial stream, find the closest constellation point and compute the Euclidean distance from it.
- h) Compute the average of the RMS of all errors in a frame. It is given by Equation (20-89).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

#### 17.3.2.1 Overview of the PPDU encoding process

The encoding process is composed of many detailed steps, which are described fully in later subclauses, as noted below. The following overview intends to facilitate understanding the details of the convergence procedure:

- a) Produce the PLCP Preamble field, composed of 10 repetitions of a "short training sequence" (used for AGC convergence, diversity selection, timing acquisition, and coarse frequency acquisition in the receiver) and two repetitions of a "long training sequence" (used for channel estimation and fine frequency acquisition in the receiver), preceded by a guard interval (GI). Refer to 17.3.3 for details.

(Source: <https://www.iith.ac.in/~tbr/teaching/docs/802.11-2007.pdf>)

26. The methods practiced by Zebra's use of the accused products include wherein the synchronizing in the time domain comprises coarse time synchronizing and fine time synchronizing. For example, the demodulation of PPDU frames also includes detecting training field bits and establishing a timing synchronization. This time synchronization would include both coarse and fine time synchronization. In general, coarse time synchronization is done using L-STF field and fine time synchronization is done using L-LTF field present in the preamble.

- a) Detect the start of frame.
- b) Detect the transition from short sequences to channel estimation sequences, and establish fine timing (with one sample resolution).
- c) Estimate the coarse and fine frequency offsets.
- d) Derotate the frame according to estimated frequency offset.
- e) Estimate the complex channel response coefficients for each of the subcarriers and each of the transmit chains.
- f) For each of the data OFDM symbols, transform the symbol into subcarrier received values, estimate the phase from the pilot subcarriers in all spatial streams, derotate the subcarrier values according to estimated phase, group the results from all the receiver chains in each subcarrier to a vector, multiply the vector by a zero-forcing equalization matrix generated from the channel estimated during the channel estimation phase.
- g) For each data-carrying subcarrier in each spatial stream, find the closest constellation point and compute the Euclidean distance from it.
- h) Compute the average of the RMS of all errors in a frame. It is given by Equation (20-89).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The simplest packet is the one used when operating in the legacy mode, which has the same format as the packets used in 802.11a/g. The L-STF field, which stands for the *legacy-short training field*, consists of two augmented OFDM symbols of 4  $\mu$ s duration each, and these are used by the receiver to perform time and frequency synchronization and to adjust its AGC. After the two L-STF augmented OFDM symbols, there is a second field called L-LTF, which stands for *legacy-long training field*, which is used to perform fine timing adjustments after the initial coarse acquisition in the L-STF field. The third field, called L-SIG, which stands for *legacy signal field*, contains data that tell the receiver what modulation and coding will be used in the data portion of the packet. The L-SIG field consists of one augmented OFDM symbol.

(Source: Introduction to MIMO Communications, Hampton, Jerry R. (2014))



### Receive procedure

Typically, the receiver waits for a signal to exceed a threshold before initiating the packet reception procedure. The minimum requirement in 802.11a is to detect the start of a valid transmission received at a power level of at least  $-82$  dBm within  $4 \mu\text{s}$  with a probability greater than 90%. Due to competitive pressures, most products exceed this specification by 5–10 dB.

The short training symbols are processed to set the AGC, initial frequency correction, and initial timing acquisition. This is followed by processing the long training symbols for fine frequency correction and fine timing adjustment. The LTF is also used to generate the channel estimate.

(Source: Next Generation Wireless LANs: 802.11n and 802.11ac, Perahia, Eldad and Stacey, Robert)

27. Zebra has had actual knowledge of the ‘782 Patent at least as of the date when it was notified of the filing of this action. By the time of trial, Zebra will have known and intended (since receiving such notice) that its continued actions would infringe and actively induce and contribute to the infringement of one or more claims of the ‘782 Patent.

28. Zebra has also indirectly and willfully infringed, and continues to indirectly and willfully infringe, the ‘782 Patent, as explained further below in the “Additional Allegations Regarding Infringement” section.

29. American Patents has been damaged as a result of the infringing conduct by Zebra alleged above. Thus, Zebra is liable to American Patents in an amount that adequately compensates it for such infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

30. American Patents and/or its predecessors-in-interest have satisfied all statutory obligations required to collect pre-filing damages for the full period allowed by law for infringement of the ‘782 Patent.

**COUNT II**

**INFRINGEMENT OF U.S. PATENT NO. 7,310,304**

31. On December 18, 2007, United States Patent No. 7,310,304 (“the ‘304 Patent”) was duly and legally issued by the United States Patent and Trademark Office for an invention entitled “Estimating Channel Parameters in Multi-Input, Multi-Output (MIMO) Systems.”

32. American Patents is the owner of the ‘304 Patent, with all substantive rights in and to that patent, including the sole and exclusive right to prosecute this action and enforce the ‘304 Patent against infringers, and to collect damages for all relevant times.

33. Zebra made, had made, used, imported, provided, supplied, distributed, sold, and/or offered for sale products and/or systems including, for example, its Zebra VC8300 Vehicle Mount Computer, Zebra TC52 and TC57 Series Touch Computer, and Zebra WT6300 Wearable Computer families of products that include 802.11n and above capabilities (“accused products”):

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER



**ZEBRA**  
CAPTURE  
YOUR EDGE

## VC8300 Vehicle Mount Computer

The ultimate ultra-rugged Android™ keyboard/touch vehicle mount computer

Since your Windows-based vehicle mount mobile computers are near their end-of-life and support for Windows-based mobile devices is ending, you're ready to migrate to Android™. You need a rugged device that will make that migration and device management simple, easy and cost-effective. Get it all with the VC8300. Designed for the most extreme environments, the VC8300 can go everywhere your vehicle operators need to go—inside the warehouse, out in the yard, on the loading dock and even in the freezer. Run your existing 'green screen' apps right out of the box—no ramp-up time required. Re-use all of your existing accessories<sup>1</sup>, minimizing the cost to upgrade to the latest technology. Replacement couldn't be easier—just drop it in place and you're ready to go. With Mobility DNA, only from Zebra, you get powerful features that transform Android into an easy-to-manage robust enterprise-class OS, complete with unique tools that not only boost workforce productivity, but also simplify deployment and application development. And since the same platform is shared with Zebra's rugged handheld and wearable mobile devices, virtually any worker can use any device with practically no training, providing the flexibility to deploy and re-deploy workers to address changing workloads.



### The Ultimate in Android Migration Simplicity

#### Run Your Terminal Emulation (TE) Apps, Right Out of the Box

Since Ivanti Velocity is pre-loaded and pre-licensed, you can run your TE apps right out of the box—no backend modification or user training required.

#### The Best of Both Worlds: Large Touchscreen and Keyboard

When it comes to data input, the VC8300 offers complete flexibility. The integrated full alphanumeric keyboard gives your workers the same familiar key-based interaction they use today—no change to workflow required. And the touchscreen allows you to integrate touch into your apps whenever you're ready.

#### Automatically Migrate Your TE Apps to Interactive Android Apps

When you're ready to transform your TE key-based apps to Android interactive apps, All-touch TE makes it easy. With this pre-loaded Zebra-only Mobility DNA application, just press a button to change TE 'green screens' to fully interactive Android screens that can be easily customized with All-touch TE tools—all without any coding.

### The Ultimate Android Platform for Business

#### Easy Viewing Indoors or Outside

The 8-inch display provides plenty of space for graphics-intensive, interactive applications, while best-in-class display resolution and brightness ensure easy viewing in any lighting condition. And the capacitive touch screen is easy to use, even with gloves.

#### Maximum Power for Maximum Application Performance

Get all the power you need to ensure superior performance with the ultra-powerful 8-core processor, plus up to eight times the RAM and 32 times the Flash memory of prior generation devices. And memory lasts 10 times longer through an advanced memory architecture.

#### A Lifetime Security Guard for Android

With LifeGuard™ for Android™, you get the security updates you need to keep your Zebra Android devices secure every day they are in service—along with easy end-to-end control of the OS update process, plus support for future versions of Android.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-)

[verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf))



PRODUCT SPEC SHEET  
TC52/TC57 SERIES TOUCH COMPUTER



## TC52 and TC57 Series Touch Computer

### The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA™, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

#### **Full shift power your workers can count on**

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>1</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

#### **Active Edge™ Touch Zone for One-touch Feature Access**

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

(Source : [https://www.zebra.com/content/dam/zebra\\_new/ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new/ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
WT6300 WEARABLE COMPUTER



## WT6300 Wearable Computer

The ultimate industrial wearable computer for hands-free mobility

With the explosion of ecommerce, picking and sorting have become full time jobs, not only in the warehouse, but in the retail store, where orders placed online need to be ready for pickup in as little as two hours. Empower your pickers and sorters to handle it all with the hands-free WT6300. Building on Zebra's WT6000, the WT6300 offers new features that take productivity and order accuracy to the next level. A new keypad option provides a familiar interface for manual keyed input. Get lightning fast application performance with more processing power, RAM and Flash memory. You get superior future proofing with Android 10, with a pathway to Android 11. It is rugged and ready for the toughest environments, including the freezer. Improved WiFi support delivers 'no-drop' dependable connections. Users get maximum Bluetooth peripheral performance and range with Bluetooth 5.0. Connect a Zebra Bluetooth ring scanner and HD4000 Head-Mounted Display for a complete solution. Plus, users can capture photos via a paired Zebra ring scanner to document proof of condition on-the-fly. The WT6300 — empowering your workers to keep pace with the e-commerce explosion.



Purpose-built industrial wearable computer

### Rugged and ready for everyday use in any environment — including the freezer

The WT6300 is dustproof, water-resistant and built to handle the inevitable everyday bumps and drops. Gorilla Glass delivers scratch and shatter resistance on the most crucial and vulnerable device component — the touchscreen display. The WT6300 is the only device in its class rated for freezer use, with a battery rated for operation at -22° F/-30° C. And it is drop-tested across the entire temperature range — crucial in freezer environments, where plastics become very brittle.

### Advanced glove-optimized rugged display

Many of your workers wear gloves — that's why the display automatically detects gloves and adjusts touch sensitivity as needed. The display works even when wet. And workers can use the many gestures they already know, such as pinch-to-zoom and swipe.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER

### Dependably Superior WiFi Connections

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement**

**improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**Fast ‘won’t drop’ high-performance WiFi connections**

Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

**Wireless LAN**

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

34. By doing so, Zebra has directly infringed (literally and/or under the doctrine of equivalents) at least Claim 1 of the ‘304 Patent. Zebra’s infringement in this regard is ongoing.

35. Zebra has infringed the ‘304 Patent by making, having made, using, importing, providing, supplying, distributing, selling or offering for sale products including an Orthogonal Frequency Division Multiplexing (OFDM) transmitter. For example, the accused products support IEEE 802.11 n/ac standards and MIMO technology. The IEEE 802.11n standard “uses OFDM modulation to transmit all data.”



The 802.11n-2009 wireless LAN standard provides Higher Throughput (HT) rates. These higher rates are achieved by a combination of MAC and PHY layer enhancements. The enhancements include:

- Reducing the per-packet overhead in the MAC layer.
- Allowing multiple MAC packets to be combined into a single PHY-layer burst.
- Allowing (optionally) a more efficient LDPC encoder.
- Allowing (optionally) a shorter guard interval (cyclic prefix) on the data symbols.
- Increasing the number of subcarriers used in the default 20 MHz physical channel.
- Providing an (optional) 40 MHz mode.
- Using MIMO techniques to broadcast multiple data streams over a single frequency channel.

By combining these techniques, the goal is to increase the usable data transfer rate by a factor of 10.

#### Signal Characteristics

The 802.11n standard uses OFDM modulation to transmit all data. It defines three operating modes:

(Source:

[http://rfmw.em.keysight.com/wireless/helpfiles/89600b/webhelp/subsystems/wlan-mimo/Content/mimo\\_80211n\\_overview.htm](http://rfmw.em.keysight.com/wireless/helpfiles/89600b/webhelp/subsystems/wlan-mimo/Content/mimo_80211n_overview.htm))

36. The accused products include an encoder configured to process data to be transmitted within an OFDM system, the encoder further configured to separate the data onto one or more transmit diversity branches (TDBs). For example, the 802.11 ac standard is backwards compatible with 802.11n and 802.11a. Thus, if a device, such as an accused product, implements 802.11ac, then it also supports 802.11n and all previous versions of the WiFi standards (i.e., IEEE 802.11 a/b/g/n). According to the IEEE 802.11n standard, an encoder block is present in a transmitter section of general OFDM systems. The encoder(s) output(s) the data onto multiple transmit chains (transmit diversity branches) for further processing.

The introduction of 802.11ac expands the compatibility matrix in the 5 GHz band from two concurrently operating technologies to three, and the compatibility considerations in a broadcast network medium extend not only to intended receivers but to any receiver. Table 3-4 describes the compatibility between transmitters of frames and their intended receivers. That is, if a transmitter of the type in the left column sends a frame directed to a receiver of the type in any of the other three columns, what will the result be? One of the major methods used to support coexistence is backward compatibility. When built, 802.11ac devices will also incorporate 802.11a and 802.11n data rates, and thus will be able to send to older peers at older data rates.



(Source: 802.11ac: A Survival Guide: Wi-Fi at Gigabit and Beyond, Gast, Matthew S.)

*Table 3-5. Compatibility between transmitters and listening devices*

Transmitter type	802.11a listener	802.11n listener	802.11ac listener
802.11a	Designed operation	802.11n devices listen to 802.11a frames and defer medium access to avoid collisions	802.11ac devices listen to 802.11a frames and defer medium access to avoid collisions
802.11n	802.11n greenfield frames require RTS/CTS or CTS-to-self protection; 802.11n mixed-mode frames require no special protection	Designed operation	802.11ac devices listen to 802.11n frames and defer medium access to avoid collisions
802.11ac	802.11ac uses a compatible physical preamble, allowing 802.11a devices to read the medium as busy and avoid collisions	802.11ac uses a compatible preamble, allowing 802.11n devices to read the medium as busy and avoid collisions	Designed operation


(Source: 802.11ac: A Survival Guide: Wi-Fi at Gigabit and Beyond, Gast, Matthew S.)

**20.3.3 Transmitter block diagram**

HT-mixed format and HT-greenfield format transmissions can be generated using a transmitter consisting of the following blocks:

- Scrambler* scrambles the data to reduce the probability of long sequences of zeros or ones; see 20.3.11.2.
- Encoder parser*, if BCC encoding is to be used, demultiplexes the scrambled bits among  $N_{ES}$  (number of BCC encoders for the Data field) BCC encoders, in a round robin manner.
- FEC encoders* encode the data to enable error correction. An FEC encoder may include a binary convolutional encoder followed by a puncturing device, or it may include an LDPC encoder.
- Stream parser* divides the outputs of the encoders into blocks that are sent to different interleaver and mapping devices. The sequence of the bits sent to an interleaver is called a *spatial stream*.
- Interleaver* interleaves the bits of each spatial stream (changes order of bits) to prevent long sequences of adjacent noisy bits from entering the BCC decoder. Interleaving is applied only when BCC encoding is used.
- Constellation mapper* maps the sequence of bits in each spatial stream to constellation points (complex numbers).
- STBC encoder* spreads constellation points from  $N_{SS}$  spatial streams into  $N_{STS}$  space-time streams using a space-time block code. STBC is used only when  $N_{SS} < N_{STS}$ ; see 20.3.11.8.1.
- Spatial mapper* maps space-time streams to transmit chains. This may include one of the following:
  - Direct mapping*: Constellation points from each space-time stream are mapped directly onto the transmit chains (one-to-one mapping).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

37. The accused products include one or more OFDM modulators, each OFDM modulator connected to a respective TDB, each OFDM modulator configured to produce a frame including a plurality of data symbols, a training structure, and cyclic prefixes inserted among the data symbols. For example, according to the IEEE 802.11n standard, a transmitter block would contain different functional blocks which include constellation mappers, IDFT stage, and Guard interval insertion. The constellation mapper maps the bits and the constellation points for different modulation schemes like QPSK, BPSK, 16-QAM, and 64-QAM. Hence, there would be modulator blocks for performing the modulation. After modulating the signal, it is converted

into the time domain and is transmitted as frames of data. These transmitted frames include a training structure, signal bits, cyclic prefixes and data bits.

### 20.3.3 Transmitter block diagram

HT-mixed format and HT-greenfield format transmissions can be generated using a transmitter consisting of the following blocks:


- a) *Scrambler* scrambles the data to reduce the probability of long sequences of zeros or ones; see 20.3.11.2.
- b) *Encoder parser*, if BCC encoding is to be used, demultiplexes the scrambled bits among  $N_{ES}$  (number of BCC encoders for the Data field) BCC encoders, in a round robin manner.
- c) *FEC encoders* encode the data to enable error correction. An FEC encoder may include a binary convolutional encoder followed by a puncturing device, or it may include an LDPC encoder.
- d) *Stream parser* divides the outputs of the encoders into blocks that are sent to different interleaver and mapping devices. The sequence of the bits sent to an interleaver is called a *spatial stream*.
- e) *Interleaver* interleaves the bits of each spatial stream (changes order of bits) to prevent long sequences of adjacent noisy bits from entering the BCC decoder. Interleaving is applied only when BCC encoding is used.
- f) *Constellation mapper* maps the sequence of bits in each spatial stream to constellation points (complex numbers).
- g) *STBC encoder* spreads constellation points from  $N_{SS}$  spatial streams into  $N_{STS}$  space-time streams using a space-time block code. STBC is used only when  $N_{SS} < N_{STS}$ ; see 20.3.11.8.1.
- h) *Spatial mapper* maps space-time streams to transmit chains. This may include one of the following:
  - 1) *Direct mapping*: Constellation points from each space-time stream are mapped directly onto the transmit chains (one-to-one mapping).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

38. The accused products include one or more transmitting antennas in communication with the one or more OFDM modulators, respectively, each transmitting antenna configured to transmit the respective frame over a channel. The accused products support 802.11 a/b/g/n/ac WiFi standards and comprise one or more transmitting and one or more receiving antennas. These transmitting antennas transmit multiple OFDM frames with various signal fields over a channel. Thus, these transmitting antennas are connected to the OFDM modulators to obtain the OFDM frames for further transmission.



**PRODUCT SPEC SHEET**  
VC8300 VEHICLE MOUNTED COMPUTER

**Dependably Superior WiFi Connections**

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; 2x2 MU-MIMO
--------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement improves WiFi range and speed — with less power**

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**Fast 'won't drop' high-performance WiFi connections**

Stay connected with unmatched, fast and dependable 'wired-quality' WiFi connections that deliver near instant application response times with Zebra's Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

**Wireless LAN**

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

The 802.11n-2009 wireless LAN standard provides Higher Throughput (HT) rates. These higher rates are achieved by a combination of MAC and PHY layer enhancements. The enhancements include:

- Reducing the per-packet overhead in the MAC layer.
- Allowing multiple MAC packets to be combined into a single PHY-layer burst.
- Allowing (optionally) a more efficient LDPC encoder.
- Allowing (optionally) a shorter guard interval (cyclic prefix) on the data symbols.
- Increasing the number of subcarriers used in the default 20 MHz physical channel.
- Providing an (optional) 40 MHz mode.
- Using MIMO techniques to broadcast multiple data streams over a single frequency channel.

By combining these techniques, the goal is to increase the usable data transfer rate by a factor of 10.

#### Signal Characteristics

The 802.11n standard uses OFDM modulation to transmit all data. It defines three operating modes:

(Source: [http://rfmw.em.keysight.com/wireless/helpfiles/89600b/webhelp/subsystems/wlan-mimo/Content/mimo\\_80211n\\_overview.htm](http://rfmw.em.keysight.com/wireless/helpfiles/89600b/webhelp/subsystems/wlan-mimo/Content/mimo_80211n_overview.htm))

#### 20.3.4 Overview of the PPDU encoding process

The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

39. The accused products include wherein the training structure of each frame includes a predetermined signal transmission matrix at a respective sub-channel, each training

structure adjusted to have a substantially constant amplitude in a time domain, and the cyclic prefixes are further inserted within the training symbol, and wherein the cyclic prefixes within the training symbol are longer than the cyclic prefixes among the data symbols, thereby countering an extended channel impulse response and improving synchronization performance. For example, a space time matrix is part of the data symbols and the training symbols in the transmission data. This data is transmitted over different antennas. The WiFi standards use guard intervals while transmitting frames to help the synchronization of frames at the receiver end. These guard intervals are of different lengths for the preamble and data symbols. The screenshots below show the Guard interval in the Long Training Field is 1.6 micro seconds, and the data field uses a Short guard interval of 0.4 micro seconds, so the cyclic prefix for the training symbols is longer than the cyclic prefix for data symbols. The training symbols (L-STF, HT-STF fields) in the 802.11n preamble have a constant amplitude in the time domain.

- p) Map each of the complex numbers in each of the  $N_{ST}$  subcarriers in each of the OFDM symbols in each of the  $N_{STS}$  space-time streams to the  $N_{TX}$  transmit chain inputs. For direct-mapped operation,  $N_{TX} = N_{STS}$ , and there is a one-to-one correspondence between space-time streams and transmit chains. In this case, the OFDM symbols associated with each space-time stream are also associated with the corresponding transmit chain. Otherwise, a spatial mapping matrix associated with each OFDM subcarrier, as indicated by the EXPANSION\_MAT parameter of the TXVECTOR, is used to perform a linear transformation on the vector of  $N_{STS}$  complex numbers associated with each subcarrier in each OFDM symbol. This spatial mapping matrix maps the vector of  $N_{STS}$  complex numbers in each subcarrier into a vector of  $N_{TX}$  complex numbers in each subcarrier. The sequence of  $N_{ST}$  complex numbers associated with each transmit chain (where each of the  $N_{ST}$  complex numbers is taken from the same position in the  $N_{TX}$  vector of complex numbers across the  $N_{ST}$  subcarriers associated with an OFDM symbol) constitutes an OFDM symbol associated with the corresponding transmit chain. For details, see 20.3.11.10. Spatial mapping matrices may include cyclic shifts, as described in 20.3.11.10.1.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



$T_{DFT}$ : IDFT/DFT period	3.2 $\mu$ s	3.2 $\mu$ s	3.2 $\mu$ s
$T_{GI}$ : Guard interval duration	0.8 $\mu$ s = $T_{DFT}/4$	0.8 $\mu$ s	0.8 $\mu$ s
$T_{GI2}$ : Double guard interval	1.6 $\mu$ s	1.6 $\mu$ s	1.6 $\mu$ s
$T_{GIS}$ : Short guard interval duration	N/A	0.4 $\mu$ s = $T_{DFT}/8$	0.4 $\mu$ s See NOTE 2
$T_{L-STF}$ : Non-HT short training sequence duration	8 $\mu$ s = $10 \times T_{DFT}/4$	8 $\mu$ s	8 $\mu$ s
$T_{HT-GF-STF}$ : HT-greenfield short training field duration	N/A	8 $\mu$ s = $10 \times T_{DFT}/4$	8 $\mu$ s See NOTE 2
$T_{L-LTF}$ : Non-HT long training field duration	8 $\mu$ s = $2 \times T_{DFT} + T_{GI2}$	8 $\mu$ s	8 $\mu$ s
$T_{SYM}$ : Symbol interval	4 $\mu$ s = $T_{DFT} + T_{GI}$	4 $\mu$ s	4 $\mu$ s
$T_{SYMS}$ : Short GI symbol interval	N/A	3.6 $\mu$ s = $T_{DFT} + T_{GIS}$	3.6 $\mu$ s See NOTE 2

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

STBC	2	Set to a nonzero number, to indicate the difference between the number of space-time streams ( $N_{STS}$ ) and the number of spatial streams ( $N_{SS}$ ) indicated by the MCS. Set to 00 to indicate no STBC ( $N_{STS} = N_{SS}$ ). See NOTE 1.
FEC coding	1	Set to 1 for LDPC. Set to 0 for BCC.
Short GI	1	Set to 1 to indicate that the short GI is used after the HT training. Set to 0 otherwise.


(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

#### 20.3.11.10.5 Transmission with a short GI


Short GI is used in the data field of the packet when the Short GI field in the HT-SIG is set to 1. When it is used, the same formula for the formation of the signal shall be used as in 20.3.11.10.2, 20.3.11.10.3, and 20.3.11.10.4, with  $T_{GI}$  replaced by  $T_{GIS}$  and  $T_{SYM}$  replaced by  $T_{SYMS}$ .

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)





(Source: <http://www.ahltek.com/WhitePaperspdf/802.11-20%20specs/802.11a-1999.pdf>)



(Source: Next Generation Wireless LANs: 802.11n and 802.11ac, Perahia, Eldad and Stacey, Robert)

40. Zebra has had actual knowledge of the ‘304 Patent at least as of the date when it was notified of the filing of this action. By the time of trial, Zebra will have known and intended (since receiving such notice) that its continued actions would infringe and actively induce and contribute to the infringement of one or more claims of the ‘304 Patent.

41. Zebra has also indirectly and willfully infringed, and continues to indirectly and willfully infringe, the ‘304 Patent, as explained further below in the “Additional Allegations Regarding Infringement” section.

42. American Patents has been damaged as a result of the infringing conduct by Zebra alleged above. Thus, Zebra is liable to American Patents in an amount that adequately compensates it for such infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

43. American Patents and/or its predecessors-in-interest have satisfied all statutory obligations required to collect pre-filing damages for the full period allowed by law for infringement of the ‘304 Patent.

### **COUNT III**

#### **INFRINGEMENT OF U.S. PATENT NO. 7,706,458**

44. On April 27, 2010, United States Patent No. 7,706,458 (“the ‘458 Patent”) was duly and legally issued by the United States Patent and Trademark Office for an invention entitled “Time And Frequency Synchronization In Multi-Input, Multi-Output (MIMO) Systems.”

45. American Patents is the owner of the ‘458 Patent, with all substantive rights in and to that patent, including the sole and exclusive right to prosecute this action and enforce the ‘458 Patent against infringers, and to collect damages for all relevant times.

46. Zebra made, had made, used, imported, provided, supplied, distributed, sold, and/or offered for sale products and/or systems including, for example, its Zebra VC8300

Vehicle Mount Computer, Zebra TC52 and TC57 Series Touch Computer, and Zebra WT6300 Wearable Computer families of products that include 802.11n and above capabilities (“accused products”):

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER



## VC8300 Vehicle Mount Computer

The ultimate ultra-rugged Android™ keyboard/touch vehicle mount computer

Since your Windows-based vehicle mount mobile computers are near their end-of-life and support for Windows-based mobile devices is ending, you're ready to migrate to Android™. You need a rugged device that will make that migration and device management simple, easy and cost-effective. Get it all with the VC8300. Designed for the most extreme environments, the VC8300 can go everywhere your vehicle operators need to go—inside the warehouse, out in the yard, on the loading dock and even in the freezer. Run your existing 'green screen' apps right out of the box—no ramp-up time required. Re-use all of your existing accessories<sup>1</sup>, minimizing the cost to upgrade to the latest technology. Replacement couldn't be easier—just drop it in place and you're ready to go. With Mobility DNA, only from Zebra, you get powerful features that transform Android into an easy-to-manage robust enterprise-class OS, complete with unique tools that not only boost workforce productivity, but also simplify deployment and application development. And since the same platform is shared with Zebra's rugged handheld and wearable mobile devices, virtually any worker can use any device with practically no training, providing the flexibility to deploy and re-deploy workers to address changing workloads.



### The Ultimate in Android Migration Simplicity

#### Run Your Terminal Emulation (TE) Apps, Right Out of the Box

Since Ivanti Velocity is pre-loaded and pre-licensed, you can run your TE apps right out of the box—no backend modification or user training required.

#### The Best of Both Worlds: Large Touchscreen and Keyboard

When it comes to data input, the VC8300 offers complete flexibility. The integrated full alphanumeric keyboard gives your workers the same familiar key-based interaction they use today—no change to workflow required. And the touchscreen allows you to integrate touch into your apps whenever you're ready.

#### Automatically Migrate Your TE Apps to Interactive Android Apps

When you're ready to transform your TE key-based apps to Android interactive apps, All-touch TE makes it easy. With this pre-loaded Zebra-only Mobility DNA application, just press a button to change TE 'green screens' to fully interactive Android screens that can be easily customized with All-touch TE tools—all without any coding.

#### The Ultimate Android Platform for Business

##### Easy Viewing Indoors or Outside

The 8-inch display provides plenty of space for graphics-intensive, interactive applications, while best-in-class display resolution and brightness ensure easy viewing in any lighting condition. And the capacitive touch screen is easy to use, even with gloves.

##### Maximum Power for Maximum Application Performance

Get all the power you need to ensure superior performance with the ultra-powerful 8-core processor, plus up to eight times the RAM and 32 times the Flash memory of prior generation devices. And memory lasts 10 times longer through an advanced memory architecture.

##### A Lifetime Security Guard for Android

With LifeGuard™ for Android™, you get the security updates you need to keep your Zebra Android devices secure every day they are in service—along with easy end-to-end control of the OS update process, plus support for future versions of Android.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
TC52/TC57 SERIES TOUCH COMPUTER



**ZEBRA**  
CAPTURE  
YOUR EDGE

## TC52 and TC57 Series Touch Computer

### The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA™, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

#### **Full shift power your workers can count on**

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>1</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

#### **Active Edge™ Touch Zone for One-touch Feature Access**

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))



PRODUCT SPEC SHEET  
WT6300 WEARABLE COMPUTER



## WT6300 Wearable Computer

The ultimate industrial wearable computer for hands-free mobility

With the explosion of ecommerce, picking and sorting have become full time jobs, not only in the warehouse, but in the retail store, where orders placed online need to be ready for pickup in as little as two hours. Empower your pickers and sorters to handle it all with the hands-free WT6300. Building on Zebra's WT6000, the WT6300 offers new features that take productivity and order accuracy to the next level. A new keypad option provides a familiar interface for manual keyed input. Get lightning fast application performance with more processing power, RAM and Flash memory. You get superior future proofing with Android 10, with a pathway to Android 11. It is rugged and ready for the toughest environments, including the freezer. Improved WiFi support delivers 'no-drop' dependable connections. Users get maximum Bluetooth peripheral performance and range with Bluetooth 5.0. Connect a Zebra Bluetooth ring scanner and HD4000 Head-Mounted Display for a complete solution. Plus, users can capture photos via a paired Zebra ring scanner to document proof of condition on-the-fly. The WT6300 — empowering your workers to keep pace with the e-commerce explosion.



Purpose-built industrial wearable computer

### Rugged and ready for everyday use in any environment — including the freezer

The WT6300 is dustproof, water-resistant and built to handle the inevitable everyday bumps and drops. Gorilla Glass delivers scratch and shatter resistance on the most crucial and vulnerable device component — the touchscreen display. The WT6300 is the only device in its class rated for freezer use, with a battery rated for operation at -22° F/-30° C. And it is drop-tested across the entire temperature range — crucial in freezer environments, where plastics become very brittle.

### Advanced glove-optimized rugged display

Many of your workers wear gloves — that's why the display automatically detects gloves and adjusts touch sensitivity as needed. The display works even when wet. And workers can use the many gestures they already know, such as pinch-to-zoom and swipe.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER

### Dependably Superior WiFi Connections

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.



(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement**

**improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**Fast ‘won’t drop’ high-performance WiFi connections**

Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

**Wireless LAN**

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

47. By doing so, Zebra has directly infringed (literally and/or under the doctrine of equivalents) at least Claim 1 of the ‘458 Patent. Zebra’s infringement in this regard is ongoing.

48. Zebra has infringed the ‘458 Patent by making, having made, using, importing, providing, supplying, distributing, selling or offering for sale products including an apparatus for synchronizing a communication system. For example, the accused products can act and have acted as a receiver in an apparatus for synchronizing a communication system. An 802.11 n/ac compliant WiFi access point that is communicating with an accused product can be part of the apparatus, acting as a transmitter. The accused products support IEEE 802.11 n/ac standards and MIMO technology. The IEEE 802.11ac standard is backwards compatible with the 802.11n standard. If a device such as an accused product complies with IEEE 802.11ac, it also complies

with IEEE 802.11n and all prior versions of the WiFi standards (802.11 a/b/g/n). According to the 802.11a standard, the physical layer services include an OFDM system. According to the IEEE 802.11n standard, all Protocol Data Unit (PPDU) frame formats have training fields and signaling fields which would help in synchronizing the communication system.

The introduction of 802.11ac expands the compatibility matrix in the 5 GHz band from two concurrently operating technologies to three, and the compatibility considerations in a broadcast network medium extend not only to intended receivers but to any receiver. Table 3-4 describes the compatibility between transmitters of frames and their intended receivers. That is, if a transmitter of the type in the left column sends a frame directed to a receiver of the type in any of the other three columns, what will the result be? One of the major methods used to support coexistence is backward compatibility. When built, 802.11ac devices will also incorporate 802.11a and 802.11n data rates, and thus will be able to send to older peers at older data rates.

(Source: 802.11ac: A Survival Guide: Wi-Fi at Gigabit and Beyond, Gast, Matthew S.)

*Table 3-5. Compatibility between transmitters and listening devices*

Transmitter type	802.11a listener	802.11n listener	802.11ac listener
802.11a	Designed operation	802.11n devices listen to 802.11a frames and defer medium access to avoid collisions	802.11ac devices listen to 802.11a frames and defer medium access to avoid collisions
802.11n	802.11n greenfield frames require RTS/CTS or CTS-to-self protection; 802.11n mixed-mode frames require no special protection	Designed operation	802.11ac devices listen to 802.11n frames and defer medium access to avoid collisions
802.11ac	802.11ac uses a compatible physical preamble, allowing 802.11a devices to read the medium as busy and avoid collisions	802.11ac uses a compatible preamble, allowing 802.11n devices to read the medium as busy and avoid collisions	Designed operation


(Source: 802.11ac: A Survival Guide: Wi-Fi at Gigabit and Beyond, Gast, Matthew S.)

### 17.1.1 Scope

This subclause describes the PHY services provided to the IEEE 802.11 wireless LAN MAC by the 5 GHz (bands) OFDM system. The OFDM PHY layer consists of two protocol functions, as follows:

- a) A PHY convergence function, which adapts the capabilities of the physical medium dependent (PMD) system to the PHY service. This function is supported by the physical layer convergence procedure (PLCP), which defines a method of mapping the IEEE 802.11 PHY sublayer service data units (PSDU) into a framing format suitable for sending and receiving user data and management information between two or more stations using the associated PMD system.
- b) A PMD system whose function defines the characteristics and method of transmitting and receiving data through a wireless medium between two or more stations, each using the OFDM system.

(Source: [https://standards.ieee.org/standard/802\\_11a-1999.html](https://standards.ieee.org/standard/802_11a-1999.html))



(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The fields of the VHT PPDU format are summarized in Table 22-4.

**Table 22-4—Fields of the VHT PPDU**

Field	Description
L-STF	Non-HT Short Training field
L-LTF	Non-HT Long Training field
L-SIG	Non-HT SIGNAL field
VHT-SIG-A	VHT Signal A field
VHT-STF	VHT Short Training field
VHT-LTF	VHT Long Training field
VHT-SIG-B	VHT Signal B field
Data	The Data field carries the PSDU(s)

(Source: <https://ieeexplore.ieee.org/document/7797535/>)

49. The accused products include a number (Q) of Orthogonal Frequency Division Multiplexing (OFDM) modulators, each OFDM modulator producing a frame having at least one inserted symbol, a plurality of data symbols, and cyclic prefixes. According to the IEEE 802.11n standard, a transmitter block contains different functional blocks which include, but are not limited to, constellation mappers, IDFT stage, and Guard interval insertion. Constellation mappers map the bits and the constellation points for different modulation schemes like QPSK, BPSK, 16-QAM, 64-QAM. After modulating the signal, it is converted into time domain and is transmitted as frames of data. These transmitted frames include training field bits, signal bits, cyclic prefixes and data bits. Alternatively, on request from an accused product, an 802.11 n/ac compliant WiFi access point can act as a transmitter that includes a number (Q) of OFDM modulators, each OFDM modulator producing a frame having at least one inserted symbol, a plurality of data symbols, and cyclic prefixes.



### 20.3.3 Transmitter block diagram

HT-mixed format and HT-greenfield format transmissions can be generated using a transmitter consisting of the following blocks:


- a) *Scrambler* scrambles the data to reduce the probability of long sequences of zeros or ones; see 20.3.11.2.
- b) *Encoder parser*, if BCC encoding is to be used, demultiplexes the scrambled bits among  $N_{ES}$  (number of BCC encoders for the Data field) BCC encoders, in a round robin manner.
- c) *FEC encoders* encode the data to enable error correction. An FEC encoder may include a binary convolutional encoder followed by a puncturing device, or it may include an LDPC encoder.
- d) *Stream parser* divides the outputs of the encoders into blocks that are sent to different interleaver and mapping devices. The sequence of the bits sent to an interleaver is called a *spatial stream*.
- e) *Interleaver* interleaves the bits of each spatial stream (changes order of bits) to prevent long sequences of adjacent noisy bits from entering the BCC decoder. Interleaving is applied only when BCC encoding is used.
- f) *Constellation mapper* maps the sequence of bits in each spatial stream to constellation points (complex numbers).
- g) *STBC encoder* spreads constellation points from  $N_{SS}$  spatial streams into  $N_{STS}$  space-time streams using a space-time block code. STBC is used only when  $N_{SS} < N_{STS}$ ; see 20.3.11.8.1.
- h) *Spatial mapper* maps space-time streams to transmit chains. This may include one of the following:
  - 1) *Direct mapping*: Constellation points from each space-time stream are mapped directly onto the transmit chains (one-to-one mapping).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

50. The accused products include Q transmitting antennas, each transmitting antenna connected to a respective OFDM modulator, the transmitting antennas configured to transmit a respective frame over a channel. The accused products support MIMO and comply with IEEE 802.11 a/b/g/n/ac standards. The transmitting antennas transmit multiple OFDM frames over a channel. The transmitting antennas are connected to OFDM modulators to transmit the OFDM frames over a channel. Alternatively, on request from an accused product, a WiFi access point acts as a device that includes Q transmitting antennas, each transmitting antenna connected to a respective OFDM modulator, the transmitting antennas configured to transmit a respective frame over a channel.

**PRODUCT SPEC SHEET**  
VC8300 VEHICLE MOUNTED COMPUTER

**Dependably Superior WiFi Connections**

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; 2x2 MU-MIMO
--------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement improves WiFi range and speed — with less power**

2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf) )

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**Fast 'won't drop' high-performance WiFi connections**

Stay connected with unmatched, fast and dependable 'wired-quality' WiFi connections that deliver near instant application response times with Zebra's Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

**Wireless LAN**

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

### 20.3.4 Overview of the PPDU encoding process

The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

51. The accused products include a number (L) of receiving antennas for receiving the transmitted frames. For example, the accused products support MIMO and comply with 802.11 a/b/g/n/ac WiFi standards. The receiving antennas receive the transmitted frames.

**PRODUCT SPEC SHEET**  
VC8300 VEHICLE MOUNTED COMPUTER

#### **Dependably Superior WiFi Connections**

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.



(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement**

**improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

### Fast 'won't drop' high-performance WiFi connections

Stay connected with unmatched, fast and dependable 'wired-quality' WiFi connections that deliver near instant application response times with Zebra's Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

#### Wireless LAN

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

52. The accused products include L OFDM demodulators, each OFDM demodulator corresponding to a respective receiving antenna, the L OFDM demodulators including a synchronization circuit that processes the received frame in order to synchronize the received frame in both time domain and frequency domain. For example, there is a demodulator block for performing demodulation on the received frames. Further, synchronizing the received frame in time and frequency domains occurs. In an OFDM transmitter section, a modulated signal is converted into time domain and is transmitted as multiple frames of data. The functional blocks present at the receiver end processes the received data, converts the data into frequency domain, and performs demodulation. Various signal bits present in the transmitted frames' preamble helps in demodulating the signal. A demodulator block is present at the receiver to perform

demodulation. Different fields of data like training bits, cyclic prefixes and other signal bits present in the received frame helps in synchronizing the frame in both time and frequency domain. There is a synchronization circuit which processes the received frame and synchronizes them in both time and frequency domain.

### 20.3.1 Introduction

A convergence procedure, in which PSDUs are converted to and from PPDU, is provided for the HT PHY in 20.3. During transmission, the PSDU is processed (i.e., scrambled and coded) and appended to the PLCP preamble to create the PPDU. At the receiver, the PLCP preamble is processed to aid in demodulation and delivery of the PSDU.

Two preamble formats are defined. For HT-mixed format operation, the preamble has a non-HT portion and an HT portion. The non-HT portion of the HT-mixed format preamble enables detection of the PPDU and acquisition of carrier frequency and timing by both HT STAs and STAs that are compliant with Clause 17 and/or Clause 19. The non-HT portion of the HT-mixed format preamble also consists of the SIGNAL field defined in Clause 17 and is thus decodable by STAs compliant with Clause 17 and Clause 19 as well as HT STAs.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

**3.244 receive chain:** The physical entity that implements any necessary signal processing to provide the received signal to the digital baseband. Such signal processing includes filtering, amplification, down-conversion, and sampling.

**3.245 sounding:** The use of preamble training fields to measure the channel for purposes other than demodulation of the Data portion of the physical layer convergence procedure (PLCP) protocol data unit (PPDU) containing the training fields.

NOTE—These uses include calculation of transmit steering, calculation of recommended MCS, and calculation of calibration parameters.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the N\_TX field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

- a) Detect the start of frame.
- b) Detect the transition from short sequences to channel estimation sequences, and establish fine timing (with one sample resolution).
- c) Estimate the coarse and fine frequency offsets.
- d) Derotate the frame according to estimated frequency offset.
- e) Estimate the complex channel response coefficients for each of the subcarriers and each of the transmit chains.
- f) For each of the data OFDM symbols, transform the symbol into subcarrier received values, estimate the phase from the pilot subcarriers in all spatial streams, derotate the subcarrier values according to estimated phase, group the results from all the receiver chains in each subcarrier to a vector, multiply the vector by a zero-forcing equalization matrix generated from the channel estimated during the channel estimation phase.
- g) For each data-carrying subcarrier in each spatial stream, find the closest constellation point and compute the Euclidean distance from it.
- h) Compute the average of the RMS of all errors in a frame. It is given by Equation (20-89).

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

53. The accused products include wherein each of the L OFDM demodulators comprises a pre-amplifier, a local oscillator, a mixer having a first input and a second input, the first input connected to an output of the pre-amplifier, the second input connected to an output of

the local oscillator, an analog-to-digital converter (ADC) connected to an output of the mixer. The demodulating section at the receiver end includes a pre-amplifier, a local oscillator, a mixer, and an ADC. The received frames undergo filtering, amplification (pre-amplifier), down-conversion and sampling (ADC). There are respective functional blocks for performing these functions. After transmitting the data, the data is received by a receiving antenna for further processing. To prevent the demodulator from demodulating the noise associated with the received signal, an RF front end circuit is implemented to increase the SNR of the demodulated signal. The RF front end circuit generally consists of amplifiers, local oscillator, filters and mixers. The output from the mixer is generally fed to an analog-to-digital converter (ADC). This RF front end circuit generally lies at the start of the demodulation process.

**3.244 receive chain:** The physical entity that implements any necessary signal processing to provide the received signal to the digital baseband. Such signal processing includes filtering, amplification, down-conversion, and sampling.


**3.245 sounding:** The use of preamble training fields to measure the channel for purposes other than demodulation of the Data portion of the physical layer convergence procedure (PLCP) protocol data unit (PPDU) containing the training fields.

NOTE—These uses include calculation of transmit steering, calculation of recommended MCS, and calculation of calibration parameters.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The technique to combat a low  $\text{SNR}_{\text{demod\_in}}$  is by adding a front end block, which processes (conditions) the received signal/AWGN/interference before admitting it to the demodulator. This processing can be done in several ways:

(Source: VLSI for Wireless Communication)






(Source: VLSI for Wireless Communication)

## 2.4 Rest of Receiver Front End: Nonidealities and Design Parameters

Now that we have talked about the design of filters in the receiver front, we turn our attention to the design of the rest of the components. Normally these components consist of circuits such as LNA, mixer, IF amplifier, and analog/digital (A/D) converter. Unlike filters, their relevant design parameters are different. Hence our first task is to discuss these design parameters.

(Source: VLSI for Wireless Communication)



(Source: RF Imperfections in High-rate Wireless Systems: Impact and Digital Compression, Schenk, Tim)

The RF front end is generally defined as everything between the antenna and the digital baseband system. For a receiver, this "between" area includes all the filters, low-noise amplifiers (LNAs), and down-conversion mixer(s) needed to process the modulated signals received at the antenna into signals suitable for input into the baseband analog-to-digital converter (ADC). For this reason, the RF front end is often called the analog-to-digital or RF-to-baseband portion of a receiver.

(Source: [https://www.eetimes.com/document.asp?doc\\_id=1276331](https://www.eetimes.com/document.asp?doc_id=1276331))

54. The accused products include the synchronization circuit having one input connected to an output of the ADC. The PPDU frames that are transmitted are demodulated at the receiver end. The demodulation process includes estimating time and frequency offsets and synchronizing accordingly.

- |    |  |
|----|--|
| a) | Detect the start of frame.   |
| b) | Detect the transition from short sequences to channel estimation sequences, and establish fine timing (with one sample resolution).  |
| c) | Estimate the coarse and fine frequency offsets.  |
| d) | Derotate the frame according to estimated frequency offset.  |
| e) | Estimate the complex channel response coefficients for each of the subcarriers and each of the transmit chains.  |
| f) | For each of the data OFDM symbols, transform the symbol into subcarrier received values, estimate the phase from the pilot subcarriers in all spatial streams, derotate the subcarrier values according to estimated phase, group the results from all the receiver chains in each subcarrier to a vector, multiply the vector by a zero-forcing equalization matrix generated from the channel estimated during the channel estimation phase. |
| g) | For each data-carrying subcarrier in each spatial stream, find the closest constellation point and compute the Euclidean distance from it.   |
| h) | Compute the average of the RMS of all errors in a frame. It is given by Equation (20-89).  |

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)

The RF front end is generally defined as everything between the antenna and the digital baseband system. For a receiver, this "between" area includes all the filters, low-noise amplifiers (LNAs), and down-conversion mixer(s) needed to process the modulated signals received at the antenna into signals suitable for input into the baseband analog-to-digital converter (ADC). For this reason, the RF front end is often called the analog-to-digital or RF-to-baseband portion of a receiver.

(Source: [https://www.eetimes.com/document.asp?doc\\_id=1276331](https://www.eetimes.com/document.asp?doc_id=1276331))


55. The accused products include a cyclic-prefix remover connected to an output of the synchronization circuit, a serial-to-parallel converter connected to an output of the cyclic prefix remover, and a discrete Fourier transform (DFT) stage connected to an output of the serial-to-parallel converter, an output of the DFT stage connected to another input to the synchronization circuit. Cyclic prefixes are added in the preamble for each transmitted frame.

In a general OFDM system, a cyclic prefix remover circuit would be present at the receiver end. The output from the cyclic prefix remover circuit would be fed to a serial-to-parallel converter for performing a DFT operation on its output. The evidence also shows that the output of the DFT stage is connected to the phase correction block that is part of the synchronization circuit.


The encoding process is composed of the steps described below. The following overview is intended to facilitate an understanding of the details of the convergence procedure:

- a) Determine the number of transmit chains,  $N_{TX}$ , from the  $N_{TX}$  field of the TXVECTOR. Produce the PLCP preamble training fields for each of the  $N_{TX}$  transmit chains based on the FORMAT, NUM\_EXTEN\_SS, CH\_BANDWIDTH, and MCS parameters of the TXVECTOR. The format and relative placement of the PLCP preamble training fields vary depending on the frame format being used, as indicated by these parameters. Apply cyclic shifts. Determine spatial mapping to be used for HT-STF and HT-LTFs in HT-mixed format frame and HT-GF-STF and HT-LTFs in HT-greenfield format frame from the EXPANSION\_MAT parameter of the TXVECTOR. Refer to 20.3.9 for details.
- b) Construct the PLCP preamble SIGNAL fields from the appropriate fields of the TXVECTOR by adding tail bits, applying convolutional coding, formatting into one or more OFDM symbols, applying cyclic shifts, applying spatial processing, calculating an inverse Fourier transform for each OFDM symbol and transmit chain, and prepending a cyclic prefix or GI to each OFDM symbol in each transmit chain. The number and placement of the PLCP preamble SIGNAL fields depend on the frame format being used. Refer to 20.3.9.3.5, 20.3.9.4.3, and 20.3.9.5.3.
- c) Concatenate the PLCP preamble training and SIGNAL fields for each transmit chain one field after another, in the appropriate order, as described in 20.3.2 and 20.3.7.

(Source: <http://luci.subsignal.org/~jow/802.11n-2009.pdf>)



(Source: RF Imperfections in High-rate Wireless Systems: Impact and Digital Compression, Schenk, Tim)



(Source: Next Generation Wireless LANs: 802.11n and 802.11ac, Perahia, Eldad and Stacey, Robert)

56. Zebra has had actual knowledge of the '458 Patent at least as of the date when it was notified of the filing of this action. By the time of trial, Zebra will have known and intended (since receiving such notice) that its continued actions would infringe and actively induce and contribute to the infringement of one or more claims of the '458 Patent.

57. Zebra has also indirectly and willfully infringed, and continues to indirectly and willfully infringe, the '458 Patent, as explained further below in the "Additional Allegations Regarding Infringement" section.

58. American Patents has been damaged as a result of the infringing conduct by Zebra alleged above. Thus, Zebra is liable to American Patents in an amount that adequately

compensates it for such infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

59. American Patents and/or its predecessors-in-interest have satisfied all statutory obligations required to collect pre-filing damages for the full period allowed by law for infringement of the '458 Patent.

#### **COUNT IV**

#### **INFRINGEMENT OF U.S. PATENT NO. 6,847,803**

60. On January 25, 2005, United States Patent No. 6,847,803 (“the ‘803 Patent”) was duly and legally issued by the United States Patent and Trademark Office for an invention entitled “Method for Reducing Interference in a Receiver.”

61. American Patents is the owner of the ‘803 Patent, with all substantive rights in and to that patent, including the sole and exclusive right to prosecute this action and enforce the ‘803 Patent against infringers, and to collect damages for all relevant times.

62. Zebra made, had made, used, imported, provided, supplied, distributed, sold, and/or offered for sale products and/or systems including, for example, its Zebra VC8300 Vehicle Mount Computer, Zebra TC52 and TC57 Series Touch Computer, and Zebra WT6300 Wearable Computer families of products, that include 802.11ac beamforming capabilities (“accused products”):



PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER



**ZEBRA**  
CAPTURE  
YOUR EDGE

## VC8300 Vehicle Mount Computer

The ultimate ultra-rugged Android™ keyboard/touch vehicle mount computer

Since your Windows-based vehicle mount mobile computers are near their end-of-life and support for Windows-based mobile devices is ending, you're ready to migrate to Android™. You need a rugged device that will make that migration and device management simple, easy and cost-effective. Get it all with the VC8300. Designed for the most extreme environments, the VC8300 can go everywhere your vehicle operators need to go—inside the warehouse, out in the yard, on the loading dock and even in the freezer. Run your existing 'green screen' apps right out of the box—no ramp-up time required. Re-use all of your existing accessories<sup>1</sup>, minimizing the cost to upgrade to the latest technology. Replacement couldn't be easier—just drop it in place and you're ready to go. With Mobility DNA, only from Zebra, you get powerful features that transform Android into an easy-to-manage robust enterprise-class OS, complete with unique tools that not only boost workforce productivity, but also simplify deployment and application development. And since the same platform is shared with Zebra's rugged handheld and wearable mobile devices, virtually any worker can use any device with practically no training, providing the flexibility to deploy and re-deploy workers to address changing workloads.



### The Ultimate in Android Migration Simplicity

#### Run Your Terminal Emulation (TE) Apps, Right Out of the Box

Since Ivanti Velocity is pre-loaded and pre-licensed, you can run your TE apps right out of the box—no backend modification or user training required.

#### The Best of Both Worlds: Large Touchscreen and Keyboard

When it comes to data input, the VC8300 offers complete flexibility. The integrated full alphanumeric keyboard gives your workers the same familiar key-based interaction they use today—no change to workflow required. And the touchscreen allows you to integrate touch into your apps whenever you're ready.

#### Automatically Migrate Your TE Apps to Interactive Android Apps

When you're ready to transform your TE key-based apps to Android interactive apps, All-touch TE makes it easy. With this pre-loaded Zebra-only Mobility DNA application, just press a button to change TE 'green screens' to fully interactive Android screens that can be easily customized with All-touch TE tools—all without any coding.

#### The Ultimate Android Platform for Business

##### Easy Viewing Indoors or Outside

The 8-inch display provides plenty of space for graphics-intensive, interactive applications, while best-in-class display resolution and brightness ensure easy viewing in any lighting condition. And the capacitive touch screen is easy to use, even with gloves.

##### Maximum Power for Maximum Application Performance

Get all the power you need to ensure superior performance with the ultra-powerful 8-core processor, plus up to eight times the RAM and 32 times the Flash memory of prior generation devices. And memory lasts 10 times longer through an advanced memory architecture.

##### A Lifetime Security Guard for Android

With LifeGuard™ for Android™, you get the security updates you need to keep your Zebra Android devices secure every day they are in service—along with easy end-to-end control of the OS update process, plus support for future versions of Android.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-)

[verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
TC52/TC57 SERIES TOUCH COMPUTER



## TC52 and TC57 Series Touch Computer

### The ultimate in enterprise-class touch computing

The TC52/TC57 Touch Computers build on the highly successful TC51/TC56, adding a new platform and new capabilities to deliver the ultimate in enterprise-class touch computing. You get the ultimate user experience — the simplicity of Android with all the business features workers need to maximize productivity and minimize process cycle times. You get the ultimate technology advancements on a cutting edge platform, maximizing the benefits of mobility today, with the future proofing you need to serve your business tomorrow. You get the ultimate collection of value-add apps, Mobility DNA™, with four new complimentary solutions that deliver unparalleled functionality — including the best possible WiFi performance, centralized control of the device update process, control over access to Google Mobile Services (GMS) and more. And optional Visibility Services offer the ultimate in device management capabilities to maximize device value.



Need to capture multiple barcodes on a single label or data on a form, such as checkboxes, text fields, signatures and more? You can do it all with the press of a single button with Zebra's SimulScan, a no-cost pre-installed Mobility DNA application.

#### Full shift power your workers can count on

The PowerPrecision+ high capacity battery delivers an impressive 14 hours of power<sup>1</sup> — plenty for the longest shift. With Warm Swap mode, swapping batteries is fast and easy — there's no need to turn off the device or close active apps. And with fast charging, batteries are fully charged and ready to go in record time.

#### Active Edge™ Touch Zone for One-touch Feature Access

Your users can easily create unique dedicated soft keys on either side of the display to access their most frequently used device features and applications with single touch simplicity — from the scanner, camera and line-of-business applications to push-to-talk and text messaging.

(Source : [https://www.zebra.com/content/dam/zebra\\_new/ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new/ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
WT6300 WEARABLE COMPUTER



## WT6300 Wearable Computer

The ultimate industrial wearable computer for hands-free mobility

With the explosion of ecommerce, picking and sorting have become full time jobs, not only in the warehouse, but in the retail store, where orders placed online need to be ready for pickup in as little as two hours. Empower your pickers and sorters to handle it all with the hands-free WT6300. Building on Zebra's WT6000, the WT6300 offers new features that take productivity and order accuracy to the next level. A new keypad option provides a familiar interface for manual keyed input. Get lightning fast application performance with more processing power, RAM and Flash memory. You get superior future proofing with Android 10, with a pathway to Android 11. It is rugged and ready for the toughest environments, including the freezer. Improved WiFi support delivers 'no-drop' dependable connections. Users get maximum Bluetooth peripheral performance and range with Bluetooth 5.0. Connect a Zebra Bluetooth ring scanner and HD4000 Head-Mounted Display for a complete solution. Plus, users can capture photos via a paired Zebra ring scanner to document proof of condition on-the-fly. The WT6300 — empowering your workers to keep pace with the e-commerce explosion.



Purpose-built industrial wearable computer

### Rugged and ready for everyday use in any environment — including the freezer

The WT6300 is dustproof, water-resistant and built to handle the inevitable everyday bumps and drops. Gorilla Glass delivers scratch and shatter resistance on the most crucial and vulnerable device component — the touchscreen display. The WT6300 is the only device in its class rated for freezer use, with a battery rated for operation at -22° F/-30° C. And it is drop-tested across the entire temperature range — crucial in freezer environments, where plastics become very brittle.

### Advanced glove-optimized rugged display

Many of your workers wear gloves — that's why the display automatically detects gloves and adjusts touch sensitivity as needed. The display works even when wet. And workers can use the many gestures they already know, such as pinch-to-zoom and swipe.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

PRODUCT SPEC SHEET  
VC8300 VEHICLE MOUNTED COMPUTER

### Dependably Superior WiFi Connections

Advanced WiFi technologies extend WiFi range, increase WiFi speed and strengthen WiFi connections, providing on-the-move workers with constant application availability and near-instant application response times. Features include 2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO), WorryFree WiFi—a free Mobility DNA tool and software-switchable internal or external antennas.



(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Wireless LAN**

<b>Radio</b>	IEEE 802.11a/b/g/n/ac/k/r; <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Vehicle-Mounted/vc8300/spec-sheet/vc8300-spec-sheet-en-us.pdf) )

**Support for the latest WiFi enhancement**

**improves WiFi range and speed — with less power**

**2x2 Multiple-User Multiple Input Multiple Output (MU-MIMO) technology** allows access points to communicate with multiple devices simultaneously via pinpoint beamforming, boosting WiFi network capacity, speed and range. And processing is shifted from the mobile device to the access point, extending battery cycle time.

**WorryFree WiFi — dependably superior WiFi, delivered**

Provide every worker with the best possible WiFi connection, every minute of every shift. This free tool delivers near instant application response times, unmatched roaming performance, plus exceptional voice quality and network diagnostics — everything you need to leverage your WiFi network to increase workforce productivity and better serve customers.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

**WIRELESS LAN**

<b>Radio</b>	TC52: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, <b>2x2 MU-MIMO</b> TC57: IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/v/w; Wi-Fi™ certified; IPv4, IPv6, 5GHz <b>2x2 MU-MIMO</b>
--------------	---

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Hand-Held%20Computers/tc52-tc57-touch-computer/spec-sheet/tc52-tc57-specification-sheet-en-us.pdf))

### Fast ‘won’t drop’ high-performance WiFi connections

Stay connected with unmatched, fast and dependable ‘wired-quality’ WiFi connections that deliver near instant application response times with Zebra’s Fusion, **2x2 MU-MIMO** support and WorryFree WiFi.

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

#### Wireless LAN

<b>WLAN Radio</b>	IEEE 802.11 a/b/g/n/ac/d/h/i/r/k/w/v/mc; <b>2x2 MU-MIMO</b> Wi-Fi™ certified; Dual Band Simultaneous; IPv4, IPv6
-------------------	--

(Source : [https://www.zebra.com/content/dam/zebra\\_new\\_ia/en-us/solutions-verticals/product/Mobile\\_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf](https://www.zebra.com/content/dam/zebra_new_ia/en-us/solutions-verticals/product/Mobile_Computers/Wearable%20Computers/wt6300/spec-sheet/wt6300-spec-sheet-en-us.pdf))

## Beamforming and MU-MIMO

Beamforming is key for the support of multiuser MIMO, or MU-MIMO, which is becoming more popular as 802.11ax routers roll out. As the name implies, MU-MIMO involves multiple users that can each communicate to multiple antennas on the router. MU-MIMO uses beamforming to make sure communication from the router is efficiently targeted to each connected client.

(Source: <https://www.networkworld.com/article/3445039/beamforming-explained-how-it-makes-wireless-communication-faster.html>)

63. By doing so, Zebra has directly infringed (literally and/or under the doctrine of equivalents) at least Claim 1 of the ‘803 Patent.



64. Zebra has infringed the '803 Patent by using the accused products and thereby practicing a method for reducing interference in a receiver for receiving information in receiving time slots, in which receiver signals are received with at least a first antenna (ANT1) and a second antenna (ANT2). For example, the accused products are and have been used by Defendant to implement the IEEE 802.11-2016 Standard, whose requirements were in effect five years before the Complaint. Devices that can communicate using 802.11 protocol are known as Stations (STAs). Multiple Input Multiple Output (MIMO) and Beamforming techniques are and have been used by a STA with multiple antennas for steering the signals to each STA ("receiver") for reception. In such MIMO transmissions, the space-time streams in the transmitted signal would be intended for reception by each STA in its corresponding time slots. These time slots at which the STA receives the space-time streams with actual data information can be construed as receiving time slots. Since, there are multiple antennas, when they transmit simultaneously, the signal appears as interference at each of the receive antennas. Further, a STA will also be able to identify the space-time streams intended for other STAs that act as interference. STA uses the channel state information that is obtained by estimating a channel to reduce the interference caused by other space time streams. The beamforming calibration procedures ("method for reducing interference") involves channel estimation and matrix calculations which help in reducing the interference in a receiver. Indeed, the IEEE 802.11-2016 Standard shows MIMO systems with two STAs (i.e., STA A and STA B) using multiple antennas ("a first antenna (ANT1) and a second antenna (ANT2)") for receiving transmitted signals.

### **21.3.11.1 General**

SU-MIMO and DL-MU-MIMO beamforming are techniques used by a STA with multiple antennas (the beamformer) to steer signals using knowledge of the channel to improve throughput. With SU-MIMO beamforming all space-time streams in the transmitted signal are intended for reception at a single STA. With DL-MU-MIMO beamforming, disjoint subsets of the space-time streams are intended for reception at different STAs.

(Source : IEEE 802.11-2016 Standard, p. 2578)

### **19.3.12 Beamforming**

#### **19.3.12.1 General**

Beamforming is a technique in which the beamformer utilizes the knowledge of the MIMO channel to generate a steering matrix  $Q_k$  that improves reception in the beamformee.


(Source : IEEE 802.11-2016 Standard, p. 2392)

A STA is also able to identify the space-time streams intended for other STAs that act as interference. VHT-LTF symbols in the VHT MU PPDU are used to measure the channel for the space-time streams intended for the STA and can also be used to measure the channel for the interfering space-time streams. To successfully demodulate the space-time streams intended for the STA, the STA may use the channel state information for all space-time streams to reduce the effect of interfering space-time streams.

(Source : IEEE 802.11-2016 Standard, p. 2580)


**(2) (STAtion)** A client device in an 802.11 (Wi-Fi) wireless network such as a computer, laptop or smartphone. The term STA is sometimes used for the access point (AP) as well, in which case a STA is any device communicating via the 802.11 protocol. See [wireless LAN](#) and [access point](#).

(Source : <https://www.pcmag.com/encyclopedia/term/sta>)



(Source : IEEE 802.11-2016 Standard, p. 2393)

65. The methods practiced by Zebra's use of the accused products include methods where signals are received with said first antenna (ANT1) and second antenna (ANT2) at moments of time other than in said receiving time slot, when no information is being received. For example, the accused products are and have been used by Defendant to implement the IEEE 802.11-2016 Standard, whose requirements were in effect five years before the Complaint. A STA in that Standard transmits data in PHY Protocol Data Units (PPDUs). PPDUs can be transmitted in High Throughput (HT) mode and Very High Throughput (VHT) mode. A Null Data Packet (NDP) can be transmitted in both HT and VHT Modes. Training Fields (TFs) inside the NDP carry no data related information and can be used as sounding PPDUs in beamforming calibration procedures. Sounding PPDUs would help in channel estimation at the STA. Certain TFs include the interference information which is used as reference during calibration procedures. The NDPs ("signals received") in HT-PPDU and VHT PPDU format includes several TFs which are and have been used as a reference for the receiver to perform calibration/tuning. Thus, there is no actual data information that is received during the beamforming calibration procedures ("at moments of time other than in said receiving time slots").



(Source : IEEE 802.11-2016 Standard, p. 2393)

Element	Description
L-STF	Non-HT Short Training field
L-LTF	Non-HT Long Training field
L-SIG	Non-HT SIGNAL field
HT-SIG	HT SIGNAL field
HT-STF	HT Short Training field
HT-GF-STF	HT-Greenfield Short Training field
HT-LTF1	First HT Long Training field (Data)
HT-LTFs	Additional HT Long Training fields (Data and Extension)
Data	The Data field includes the PSDU

(Source : IEEE 802.11-2016 Standard, p. 2347)

**Table 21-4—Fields of the VHT PPDU**

Field	Description
L-STF	Non-HT Short Training field
L-LTF	Non-HT Long Training field
L-SIG	Non-HT SIGNAL field
VHT-SIG-A	VHT Signal A field
VHT-STF	VHT Short Training field
VHT-LTF	VHT Long Training field
VHT-SIG-B	VHT Signal B field
Data	The Data field carrying the PSDU(s)

The VHT-SIG-A, VHT-STF, VHT-LTF, and VHT-SIG-B fields exist only in VHT PPDU. In a VHT NDP the Data field is not present. The number of symbols in the VHT-LTF field,  $N_{VHTLTF}$ , can be either 1, 2, 4, 6, or 8 and is determined by the total number of space-time streams across all users being transmitted in the VHT PPDU (see Table 21-13).

(Source : IEEE 802.11-2016 Standard, p. 2514)

In both HT-mixed format and HT-greenfield format frames, there are two types of HT-LTFs: Data HT-LTFs (HT-DLTFs) and Extension HT-LTFs (HT-ELTFs). HT-DLTFs are always included in HT PPDU to provide the necessary reference for the receiver to form a channel estimate that allows it to demodulate the data

(Source : IEEE 802.11-2016 Standard, p. 2347)

**null data packet (NDP):** A physical layer (PHY) protocol data unit (PPDU) that carries no Data field.


**off-channel:** A channel used by a tunneled direct link setup (TDLS) station (STA) that does not overlap the channel(s) used by the access point (AP) with which the TDLS STA is associated.

(Source : IEEE 802.11-2016 Standard, p. 157)

**sounding physical layer (PHY) protocol data unit (PPDU):** A PPDU that is intended by the transmitting station (STA) to enable the receiving STA to estimate the channel between the transmitting STA and the receiving STA. The Not Sounding field in the High Throughput SIGNAL field (HT-SIG) is equal to 0 in sounding PPDU.

(Source : IEEE 802.11-2016 Standard, p. 163)





(Source : IEEE 802.11-2016 Standard, p. 2580)

### 10.34 Null data packet (NDP) sounding

#### 10.34.1 HT NDP sounding protocol

Sounding may be accomplished using either staggered sounding PDU or HT NDP, as described in 19.3.13. The MAC rules associated with sounding using HT NDP are described in 10.34.1 to 10.34.4.

(Source : IEEE 802.11-2016 Standard, p. 1485)

66. The methods practiced by Zebra's use of the accused products include methods in which a reference signal representing interference in said other time slot is formed and used for the tuning of the receiver in said receiving time slots. For example, the accused products are and have been used by Defendant to implement the IEEE 802.11-2016 Standard, whose requirements were in effect five years before the Complaint. In that Standard, beamforming techniques are and have been used to improve the reception at a receiver STA. These techniques use the channel state information and generate steering matrices for the transmission of data. There are two types of beamforming methods described in the standard, Implicit feedback beamforming and Explicit feedback beamforming. A steering matrix,  $Q_k$ , is calculated in both beamforming methods. Explicit feedback beamforming enables a beamformee i.e., receiving STA to calculate

beamforming feedback matrix based on the received sounding packets/PPDUs. NDPs can be used as sounding PPDUs and hence, no data/information is received during the beamforming procedures. The Standard shows a scenario wherein STA A (transmit STA) transmits a sounding packet (which can be NDP PDU) that is used by STA B (receiving STA) to calculate a beamforming feedback matrix  $V_k$  (“reference signal”). The feedback matrix is later sent to STA A for determining a steering matrix which is used to tune and re-calibrate the receiver STA in order to demodulate the transmitted signal. Implicit feedback beamforming enables STA to estimate a MIMO channel and calculate channel matrices, based on a received sounding PDU. NDPs can be used as sounding PPDUs and hence, no data/information is received during the beamforming procedures. The Standard shows a scenario wherein STA A and STA B (receiving STA) follow beamforming calibration procedures using sounding PPDUs. STA A and STA B will exchange sounding PPDUs (which can be NDP PPDUs), using which each of the STAs will estimate respective channel matrices. Quantized estimates of the channel matrices (“reference signal”) are sent from STA B to STA A. Later, STA A uses its local estimates and the received quantized estimates from STA B to calculate set of correction matrices. These correction matrices that are formed using the received quantized estimates, are applied at transmit side of a STA to correct/tune the amplitude and phase differences in transmit and receive chains. All the above discussed steps are performed as a part of beamforming calibration procedures using sounding PPDUs. The Standard also shows equations for the received signal with beamforming. The channel estimates and beamforming steering matrix are and have been used to tune and re-calibrate the receiver in order to demodulate the transmitted signal.

### 19.3.12 Beamforming

#### 19.3.12.1 General

Beamforming is a technique in which the beamformer utilizes the knowledge of the MIMO channel to generate a steering matrix  $Q_k$  that improves reception in the beamformee.

The equivalent complex baseband MIMO channel model is one in which, when a vector  $\mathbf{x}_k = [x_1, x_2, \dots, x_{N_{TX}}]^T$  is transmitted in subcarrier  $k$ , the received vector  $\mathbf{y}_k = [y_1, y_2, \dots, y_{N_{RX}}]^T$  is modeled as shown in Equation (19-62).

$$\mathbf{y}_k = H_k \mathbf{x}_k + \mathbf{n} \quad (19-62)$$

where

$H_k$  is channel matrix of dimensions  $N_{RX} \times N_{TX}$

$\mathbf{n}$  is white (spatially and temporally) Gaussian noise as illustrated in Figure 19-14

(Source : IEEE 802.11-2016 Standard, p. 2392-2393)

When beamforming is used, the beamformer replaces  $\mathbf{x}_k$ , which in this case has  $N_{STS} \leq N_{TX}$  elements, with  $Q_k \mathbf{x}_k$ , where  $Q_k$  has  $N_{TX}$  rows and  $N_{STS}$  columns, so that the received vector is as shown in Equation (19-63).

$$\mathbf{y}_k = H_k Q_k \mathbf{x}_k + \mathbf{n} \quad (19-63)$$

The beamforming steering matrix that is computed (or updated) from a new channel measurement replaces the existing  $Q_k$  for the next beamformed data transmission. There are several methods of beamforming, differing in the way the beamformer acquires the knowledge of the channel matrices  $H_k$  and on whether the beamformer generates  $Q_k$  or the beamformee provides feedback information for the beamformer to generate  $Q_k$ .

(Source : IEEE 802.11-2016 Standard, p. 2393)

### 19.3.12.3 Explicit feedback beamforming

#### 19.3.12.3.1 General

In explicit beamforming, in order for STA A to transmit a beamformed packet to STA B, STA B measures the channel matrices and sends STA A either the effective channel,  $H_{eff,k}$ , or the beamforming feedback matrix,  $V_k$ , for STA A to determine a steering matrix,  $Q_{steer,k} = Q_k V_k$ , with  $V_k$  found from  $H_k Q_k$ , where  $Q_k$  is the orthonormal spatial mapping matrix that was used to transmit the sounding packet that elicited the  $V_k$  feedback. The effective channel,  $H_{eff,k} = H_k Q_k$ , is the product of the spatial mapping matrix used on transmit with the channel matrix. When new steering matrix  $Q_{steer,k}$  is found,  $Q_{steer,k}$  may replace  $Q_k$  for the next beamformed data transmission.

NOTE— $Q_{steer,k}$  is a mathematical term to update a new steering matrix for  $Q_k$  in the next beamformed data transmission.

(Source : IEEE 802.11-2016 Standard, p. 1477)

### 10.32.3 Explicit feedback beamforming

The procedures in this subclause apply only to HT and non-HT PPDU for which the HT Control field, if present, is the HT variant HT Control field.

In this subclause, the terms *HT beamformer* and *HT beamformee* refer to STAs that are involved in explicit feedback beamforming.

An HT beamformer uses the feedback response that it receives from the HT beamformee to calculate a beamforming feedback matrix for transmit beamforming. This feedback response may have one of three formats:

- *CSI*: The HT beamformee sends the MIMO channel coefficients to the HT beamformer.
- *Noncompressed beamforming*: The HT beamformee sends calculated beamforming feedback matrices to the HT beamformer.
- *Compressed beamforming*: The HT beamformee sends compressed beamforming feedback matrices to the HT beamformer.

(Source : IEEE 802.11-2016 Standard, p. 1477)

### 10.34 Null data packet (NDP) sounding

#### 10.34.1 HT NDP sounding protocol

Sounding may be accomplished using either staggered sounding PPDU or HT NDP, as described in 19.3.13. The MAC rules associated with sounding using HT NDP are described in 10.34.1 to 10.34.4.

(Source : IEEE 802.11-2016 Standard, p. 1477)

### 10.34.5 VHT sounding protocol

#### 10.34.5.1 General

Transmit beamforming and DL-MU-MIMO require knowledge of the channel state to compute a steering matrix that is applied to the transmitted signal to optimize reception at one or more receivers. The STA transmitting using the steering matrix is called the *VHT beamformer*, and a STA for which reception is optimized is called a *VHT beamformee*. An explicit feedback mechanism is used where the VHT beamformee directly measures the channel from the training symbols transmitted by the VHT beamformer and sends back a transformed estimate of the channel state to the VHT beamformer. The VHT beamformer then uses this estimate, perhaps combining estimates from multiple VHT beamformees, to derive the steering matrix.

(Source : IEEE 802.11-2016 Standard, p. 1477)

#### 21.3.12 VHT preamble format for sounding PPDU

NDP is the only VHT sounding format.

The format of a VHT NDP PPDU is shown in Figure 21-28.



Figure 21-28—VHT NDP format


NOTE—The number of VHT-LTF symbols in the NDP is determined by the SU NSTS field in VHT-SIG-A.

The VHT NDP PPDU has the following properties:

- Uses the VHT PPDU format but without the Data field.
- Is a VHT SU PPDU as indicated by the VHT-SIG-A field.
- Has the data bits of the VHT-SIG-B field set to a fixed bit pattern (see 21.3.8.3.6).

(Source : IEEE 802.11-2016 Standard, p. 2580)






(Source : IEEE 802.11-2016 Standard, p. 2393)


Focusing on STA A, the procedure for estimating  $K_{A,k}$  is as follows:

- a) STA A sends STA B a sounding PPDU, the reception of which allows STA B to estimate the channel matrices  $\tilde{H}_{AB,k}$ .
- b) STA B sends STA A a sounding PPDU, the reception of which allows STA A to estimate the channel matrices  $\tilde{H}_{BA,k}$ .
- c) STA B sends the quantized estimates of  $\tilde{H}_{AB,k}$  to STA A.
- d) STA A uses its local estimates of  $\tilde{H}_{BA,k}$  and the quantized estimates of  $\tilde{H}_{AB,k}$  received from STA B to compute the correction matrices  $K_{A,k}$ .

(Source : IEEE 802.11-2016 Standard, p. 2395)



(Source : IEEE 802.11-2016 Standard, p. 1475)



(Source : IEEE 802.11-2016 Standard, p. 2580)

While the over-the-air channel between the antenna(s) at one STA and the antenna(s) at a second STA is reciprocal, the observed baseband-to-baseband channel used for communication might not be, as it includes the transmit and receive chains of the STAs. Differences in the amplitude and phase characteristics of the transmit and receive chains associated with individual antennas degrade the reciprocity of the over-the-air channel and cause degradation of performance of implicit beamforming techniques. The over-the-air calibration procedure described in 10.32.2.4 may be used to restore reciprocity. The procedure provides the means for calculating a set of correction matrices that can be applied at the transmit side of a STA to correct the amplitude and phase differences between the transmit and receive chains in the STA. If this correction is done at least at the STA that serves as the beamformer, there is sufficient reciprocity for implicit feedback in the baseband-to-baseband response of the forward link and reverse channel.

(Source : IEEE 802.11-2016 Standard, p. 2394)

### **19.3.13.3 Sounding PPDU for calibration**

In the case of a bidirectional calibration exchange, two STAs exchange sounding PPDU, the exchange of which enables the receiving STA to compute an estimate of the MIMO channel matrix  $H_k$  for each subcarrier  $k$ . In general, in an exchange of calibration messages, the number of spatial streams is less than the number of transmit antennas. In such cases, HT-ELTFs are used. In the case of sounding PPDU for calibration, the antenna mapping matrix shall be as shown in Equation (19-86).

(Source : IEEE 802.11-2016 Standard, p. 2401)

Two preamble formats are defined. For HT-mixed format operation, the preamble has a non-HT portion and an HT portion. The non-HT portion of the HT-mixed format preamble enables detection of the PPDU and acquisition of carrier frequency and timing by both HT STAs and STAs that are compliant with Clause 17 and/or Clause 18. The non-HT portion of the HT-mixed format preamble also consists of the SIGNAL field defined in Clause 17 and is thus decodable by STAs compliant with Clause 17 and Clause 18 as well as HT STAs.

The HT portion of the HT-mixed format preamble enables estimation of the MIMO channel to support demodulation of the HT data by HT STAs. The HT portion of the HT-mixed format preamble also includes the HT-SIG field, which supports HT operation. The SERVICE field is prepended to the PSDU.

(Source : IEEE 802.11-2016 Standard, p. 2346)

### 19.3.12 Beamforming

#### 19.3.12.1 General

Beamforming is a technique in which the beamformer utilizes the knowledge of the MIMO channel to generate a steering matrix  $Q_k$  that improves reception in the beamformee.

The equivalent complex baseband MIMO channel model is one in which, when a vector  $\mathbf{x}_k = [x_1, x_2, \dots, x_{N_{TX}}]^T$  is transmitted in subcarrier  $k$ , the received vector  $\mathbf{y}_k = [y_1, y_2, \dots, y_{N_{RX}}]^T$  is modeled as shown in Equation (19-62).

$$\mathbf{y}_k = H_k \mathbf{x}_k + \mathbf{n} \quad (19-62)$$

where

$H_k$  is channel matrix of dimensions  $N_{RX} \times N_{TX}$

$\mathbf{n}$  is white (spatially and temporally) Gaussian noise as illustrated in Figure 19-14

(Source : IEEE 802.11-2016 Standard, p. 2392-2393)

When beamforming is used, the beamformer replaces  $\mathbf{x}_k$ , which in this case has  $N_{STS} \leq N_{TX}$  elements, with  $Q_k \mathbf{x}_k$ , where  $Q_k$  has  $N_{TX}$  rows and  $N_{STS}$  columns, so that the received vector is as shown in Equation (19-63).

$$\mathbf{y}_k = H_k Q_k \mathbf{x}_k + \mathbf{n} \quad (19-63)$$

The beamforming steering matrix that is computed (or updated) from a new channel measurement replaces the existing  $Q_k$  for the next beamformed data transmission. There are several methods of beamforming, differing in the way the beamformer acquires the knowledge of the channel matrices  $H_k$  and on whether the beamformer generates  $Q_k$  or the beamformee provides feedback information for the beamformer to generate  $Q_k$ .

(Source : IEEE 802.11-2016 Standard, p. 2393)

67. American Patents only asserts method claims from the '803 Patent.

68. American Patents has been damaged as a result of the infringing conduct by Zebra alleged above. Thus, Zebra is liable to American Patents in an amount that adequately compensates it for such infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

69. American Patents and/or its predecessors-in-interest have satisfied all statutory obligations required to collect pre-filing damages for the full period allowed by law for infringement of the '803 Patent.

**ADDITIONAL ALLEGATIONS REGARDING INFRINGEMENT**

70. In addition to any specific products mentioned above, the accused products also include at least the following products: Zebra AP0622 Access Point, Zebra AP7502 Access Point, Zebra AP7522 Access Point, Zebra AP7522I Access Point, Zebra AP7532 Access Point, Zebra AP7532I Access Point, Zebra AP7602 Access Point, Zebra AP7622 Access Point, Zebra AP8432I Access Point, Zebra AP8533 Access Point, Zebra AP8533I Access Point, Zebra CC5000-10 CUSTOMER CONCIERGE, Zebra CC600 CUSTOMER CONCIERGE, Zebra CC6000 Customer Concierge, Zebra CCHUB1 CONCIERGE HUB, Zebra EC30 Enterprise Companion, Zebra EC50 Enterprise Mobile Computer, Zebra EC55 Enterprise Mobile Computer, Zebra EC55 Enterprise Tablet, Zebra ET51 Android Enterprise Tablet With 1D/2D Barcode Scanner, Zebra ET51 Enterprise Rugged Tablet - Android, Zebra ET51 Enterprise Rugged Tablet - Windows, Zebra ET51 Windows Enterprise Tablet With 1D/2D Barcode Scanner, Zebra ET56 Enterprise Rugged Tablet - Android, Zebra ET56 Enterprise Rugged Tablet - Windows, Zebra Hub, Zebra KHUSB600 USB dongle, Zebra KHUSB601 USB dongle, Zebra M60 RUGGED ANDROID HANDHELD COMPUTER, Zebra MB5000 Fixed-Location IoT Bridge, Zebra MB6000 Mobile IoT Bridge, Zebra MC18 PERSONAL SHOPPER, Zebra MC2200 Mobile Computer, Zebra MC2700 Mobile Computer, Zebra MC3200 Mobile Computer, Zebra MC3300 MOBILE COMPUTER, Zebra MC3300X MOBILE COMPUTER, Zebra MC3330R INTEGRATED UHF RFID READER, Zebra MC3330XR UHF RFID READER, Zebra MC3390R LONG-RANGE UHF RFID READER, Zebra MC3390XR UHF RFID READER, Zebra MC40N0 Mobile Computer, Zebra MC55X MOBILE COMPUTER,



Zebra MC55X-HC MOBILE COMPUTER, Zebra MC67 MOBILE COMPUTER SERIES, Zebra MC9200 Mobile Computer, Zebra MC9300 Mobile Computer, Zebra MK3100 MICRO KIOSK, Zebra OCEABridge Wireless gateway, Zebra OMNII XT15 MOBILE COMPUTER, Zebra PS20 Personal Shopper, Zebra TC20 MOBILE COMPUTER, Zebra TC21 Touch Computer, Zebra TC21-HC Mobile Computer, Zebra TC25 RUGGED SMARTPHONE, Zebra TC26 Touch Computer, Zebra TC26-HC Mobile Computer, Zebra TC51 Touch Computer, Zebra TC52 Series Touch Computer, Zebra TC52-HC TOUCH COMPUTER, Zebra TC52x Touch Computer, Zebra TC52x-HC TOUCH COMPUTER, Zebra TC55 TOUCH COMPUTER, Zebra TC56 Touch Computer, Zebra TC57 Series Touch Computer, Zebra TC57x Touch Computer, Zebra TC70x Touch Computer, Zebra TC72 Series Touch Computer, Zebra TC75x Touch Computer, Zebra TC77 Series Touch Computer, Zebra TC8000 Touch Computer, Zebra TC8300 Touch Computer, Zebra Trailer Monitoring Unit TM2000, Zebra TW522, Zebra VC70N0 VEHICLE-MOUNTED COMPUTER, Zebra VC80 VEHICLE MOUNT COMPUTER, Zebra VC80X VEHICLE MOUNT MOBILE COMPUTER, Zebra VC8300 VEHICLE MOUNT COMPUTER, Zebra VH10/VH10F Vehicle-Mounted Computer, Zebra WORKABOUT PRO 4, Zebra WT41N0 VOW Wearable Computer, Zebra WT41N0 Wearable Computer, Zebra WT6000 Wearable Computer, Zebra WT6300 WEARABLE COMPUTER, Zebra XBOOK L10 Rugged 2-in-1 Tablet - Android, Zebra XBOOK L10 Rugged 2-in-1 Tablet - ATEX, Zebra XBOOK L10 Rugged 2-in-1 Tablet - Windows, Zebra XC6 SERIES ULTRA-RUGGED TABLET PC, Zebra XPAD L10 Rugged Tablet - Android, Zebra XPAD L10 Rugged Tablet - ATEX, Zebra XPAD L10 Rugged Tablet - Windows, Zebra XSLATE B10 RUGGED WINDOWS TABLET, Zebra XSLATE L10 Rugged Tablet - Android, Zebra XSLATE L10 Rugged Tablet - ATEX, Zebra XSLATE L10 Rugged Tablet - Windows, Zebra XSLATE R12 RUGGED TABLET, Zebra ZC100 Card Printer, Zebra ZC300 Card Printer, Zebra ZC350 Card

Printer, Zebra ZD410 Direct Thermal Desktop Printer, Zebra ZD410 Direct Thermal Desktop Printer – Healthcare Model, Zebra ZD420 Healthcare Ribbon Cartridge Printer, Zebra ZD420 Healthcare Thermal Transfer and Direct Thermal Printers, Zebra ZD420 Ribbon Cartridge Printer, Zebra ZD420 Thermal Transfer and Direct Thermal Printers, Zebra ZD421 Healthcare Ribbon Cartridge Printer, Zebra ZD421 Healthcare Thermal Transfer and Direct Thermal Printers, Zebra ZD421 Ribbon Cartridge Printer, Zebra ZD421 Thermal Transfer and Direct Thermal Printers, Zebra ZD500 Thermal Transfer Desktop Printer, Zebra ZD500R RFID Printer, Zebra ZD510-HC WRISTBAND PRINTING SOLUTION, Zebra ZD620 HEALTHCARE DESKTOP PRINTERS, Zebra ZD620 PERFORMANCE DESKTOP PRINTERS, Zebra ZD621 4-INCH DESKTOP PRINTERS, Zebra ZD621-HC 4-INCH DESKTOP PRINTERS, Zebra ZD621R 4-INCH DESKTOP PRINTERS, Zebra ZQ110 Series, Zebra ZQ310/ZQ320 Mobile Label and Receipt Printers, Zebra ZQ310/ZQ320 Mobile Receipt Printers, Zebra ZQ510 Mobile Printer, Zebra ZQ511 Mobile Printer, Zebra ZQ511 RFID Mobile Printer, Zebra ZQ520 Mobile Printer, Zebra ZQ520 RFID Mobile Printer, Zebra ZQ521 Mobile Printer, Zebra ZQ521 RFID Mobile Printer, Zebra ZQ610 Healthcare Mobile Printer, Zebra ZQ610 Mobile Printer, Zebra ZQ620 Healthcare Mobile Printer, Zebra ZQ620 Mobile Printer, Zebra ZQ630 Mobile Printer, Zebra ZQ630 RFID MOBILE PRINTER, Zebra ZSB-DP12 Label Printer, Zebra ZSB-DP14 Label Printer, Zebra ZT220 Industrial Printer, Zebra ZT230 Industrial Printer, Zebra ZT410 Industrial Printer, Zebra ZT411 Industrial Printer, Zebra ZT411 RFID Industrial Printer, Zebra ZT411 RFID On-Metal Tagging Solution, Zebra ZT420 Industrial Printer, Zebra ZT421 Industrial Printer, Zebra ZT421 RFID Industrial Printer, Zebra ZT510 Industrial Printer, Zebra ZT610 Industrial Printer, Zebra ZT610 RFID Industrial Printer, Zebra ZT620 Industrial Printer, Zebra ZT620 RFID Industrial Printer.

71. Zebra has also indirectly infringed the '782 Patent, the '304 Patent, and the '458 Patent by inducing others to directly infringe the '782 Patent, the '304 Patent, and the '458 Patent. Zebra has induced the end-users, Zebra's customers, to directly infringe (literally and/or under the doctrine of equivalents) the '782 Patent, the '304 Patent, and the '458 Patent by using the accused products.

72. Zebra took active steps, directly and/or through contractual relationships with others, with the specific intent to cause them to use the accused products in a manner that infringes one or more claims of the patents-in-suit, including, for example, Claim 30 of the '782 Patent, Claim 1 of the '304 Patent, and Claim 1 of the '458 Patent.

73. Such steps by Zebra included, among other things, advising or directing customers and end-users to use the accused products in an infringing manner; advertising and promoting the use of the accused products in an infringing manner; and/or distributing instructions that guide users to use the accused products in an infringing manner.

74. Zebra has performed these steps, which constitute induced infringement, with the knowledge of the '782 Patent, the '304 Patent, and the '458 Patent and with the knowledge that the induced acts constitute infringement.

75. Zebra was and is aware that the normal and customary use of the accused products by Zebra's customers would infringe the '782 Patent, the '304 Patent, and the '458 Patent. Zebra's inducement is ongoing.

76. Zebra has also induced its affiliates, or third-party manufacturers, shippers, distributors, retailers, or other persons acting on its or its affiliates' behalf, to directly infringe (literally and/or under the doctrine of equivalents) the '782 Patent, the '304 Patent, and the '458 Patent by importing, selling, offering to sell, and/or using the accused products.

77. Zebra has at least a significant role in placing the accused products in the stream of commerce in Texas and elsewhere in the United States.

78. Zebra directs or controls the making of accused products and their shipment to the United States, using established distribution channels, for sale in Texas and elsewhere within the United States.

79. Zebra directs or controls the sale of the accused products into established United States distribution channels, including sales to nationwide retailers.

80. Zebra's established United States distribution channels include one or more United States based affiliates (*e.g.*, at least Zebra Technologies International, LLC and Zebra Technologies US LLC).

81. Zebra directs or controls the sale of the accused products nationwide on its own website as well as in nationwide retailers such as Grainger, Amazon, Staples, Arrowhead, and OfficeMax, including for sale in Texas and elsewhere in the United States, and expects and intends that the accused products will be so sold.

82. Zebra took active steps, directly and/or through contractual relationships with others, with the specific intent to cause such persons to import, sell, or offer to sell the accused products in a manner that infringes one or more claims of the patents-in-suit, including, for example, Claim 30 of the '782 Patent, Claim 1 of the '304 Patent, and Claim 1 of the '458 Patent.

83. Such steps by Zebra included, among other things, making or selling the accused products outside of the United States for importation into or sale in the United States, or knowing that such importation or sale would occur; and directing, facilitating, or influencing its affiliates, or third-party manufacturers, shippers, distributors, retailers, or other persons acting on its or their behalf, to import, sell, or offer to sell the accused products in an infringing manner.

84. Zebra performed these steps, which constitute induced infringement, with the knowledge of the '782 Patent, the '304 Patent, and the '458 Patent and with the knowledge that the induced acts would constitute infringement.

85. Zebra performed such steps in order to profit from the eventual sale of the accused products in the United States.

86. Zebra's inducement is ongoing.

87. Zebra has also indirectly infringed by contributing to the infringement of the '782 Patent, the '304 Patent, and the '458 Patent. Zebra has contributed to the direct infringement of the '782 Patent, the '304 Patent, and the '458 Patent by the end-user of the accused products.

88. The accused products have special features that are specially designed to be used in an infringing way and that have no substantial uses other than ones that infringe the '782 Patent, the '304 Patent, and the '458 Patent, including, for example, Claim 30 of the '782 Patent, Claim 1 of the '304 Patent, and Claim 1 of the '458 Patent.

89. As described above, the special features include improved wireless communication capabilities used in a manner that infringes the '782 Patent, the '304 Patent, and the '458 Patent.

90. The special features constitute a material part of the invention of one or more of the claims of the '782 Patent, the '304 Patent, and the '458 Patent and are not staple articles of commerce suitable for substantial non-infringing use.

91. Zebra's contributory infringement is ongoing.

92. Furthermore, Zebra has a policy or practice of not reviewing the patents of others (including instructing its employees to not review the patents of others), and thus has been willfully blind of American Patents' patent rights. *See, e.g.*, M. Lemley, "Ignoring Patents," 2008 Mich. St. L. Rev. 19 (2008).



93. Zebra's actions are at least objectively reckless as to the risk of infringing valid patents and this objective risk was either known or should have been known by Zebra.

94. Zebra has knowledge of the '782 Patent, the '304 Patent, and the '458 Patent.

95. Zebra's customers have infringed the '782 Patent, the '304 Patent, and the '458 Patent.

96. Zebra encouraged its customers' infringement.

97. Zebra's direct and indirect infringement of the '782 Patent, the '304 Patent, and the '458 Patent is, has been, and/or continues to be willful, intentional, deliberate, and/or in conscious disregard of American Patents' rights under the patents.

98. American Patents has been damaged as a result of the infringing conduct by Zebra alleged above. Thus, Zebra is liable to American Patents in an amount that adequately compensates it for such infringements, which, by law, cannot be less than a reasonable royalty, together with interest and costs as fixed by this Court under 35 U.S.C. § 284.

#### **CLARIFICATION REGARDING PATENT EXPIRATION**

99. For the avoidance of doubt, American Patents does not seek relief under any asserted patent for acts occurring after the expiration of that patent.

#### **JURY DEMAND**

American Patents hereby requests a trial by jury on all issues so triable by right.

#### **PRAYER FOR RELIEF**

American Patents requests that the Court find in its favor and against Zebra, and that the Court grant American Patents the following relief:

a. Judgment that one or more claims of the '782 Patent, the '304 Patent, the '458 Patent, and the '803 Patent have been infringed, either literally and/or under the doctrine of equivalents, by Zebra and/or all others acting in concert therewith;

b. A permanent injunction enjoining Zebra and its officers, directors, agents, servants, affiliates, employees, divisions, branches, subsidiaries, parents, and all others acting in concert therewith from infringement of the '782 Patent, the '304 Patent, and the '458 Patent; or, in the alternative, an award of a reasonable ongoing royalty for future infringement of the '782 Patent, the '304 Patent, and the '458 Patent by such entities;

c. Judgment that Zebra account for and pay to American Patents all damages to and costs incurred by American Patents because of Zebra's infringing activities and other conduct complained of herein, including an award of all increased damages to which American Patents is entitled under 35 U.S.C. § 284;

d. That American Patents be granted pre-judgment and post-judgment interest on the damages caused by Zebra's infringing activities and other conduct complained of herein;

e. That this Court declare this an exceptional case and award American Patents its reasonable attorney's fees and costs in accordance with 35 U.S.C. § 285; and

f. That American Patents be granted such other and further relief as the Court may deem just and proper under the circumstances.

Dated: June 21, 2021

Respectfully submitted,

/s/ Zachariah S. Harrington

Matthew J. Antonelli

Texas Bar No. 24068432

matt@ahtlawfirm.com

Zachariah S. Harrington

Texas Bar No. 24057886

zac@ahtlawfirm.com

Larry D. Thompson, Jr.

Texas Bar No. 24051428

larry@ahtlawfirm.com

Christopher Ryan Pinckney

Texas Bar No. 24067819

ryan@ahtlawfirm.com

ANTONELLI, HARRINGTON  
& THOMPSON LLP

4306 Yoakum Blvd., Ste. 450  
Houston, TX 77006  
(713) 581-3000

Stafford Davis  
State Bar No. 24054605  
sdavis@stafforddavisfirm.com  
Catherine Bartles  
Texas Bar No. 24104849  
cbartles@stafforddavisfirm.com  
THE STAFFORD DAVIS FIRM  
815 South Broadway Avenue  
Tyler, Texas 75701  
(903) 593-7000  
(903) 705-7369 fax

*Attorneys for American Patents LLC*