	Case 4:11-cv-00036-HTW -LRA Document 1 Filed 03/03/11 Page File D  United States District Court  MAR 03 2011  Southern District of Mississippi  BY					
	PEAVEY ELECTRONICS CORPORATION, PLAINTIFF,  V.  Music Group Services US, Inc.; AND Does 1-10 Inclusive, Defendants.  S S S S S S S S S S S S S S S S CIVIL Action No. 4: 11 Cu31. HTU-LRA COMPLAINT FOR PATENT INFRINGEMENT  JURY TRIAL DEMANDED  S S S S S S S S S S S S S S S S S S					
	ORIGINAL COMPLAINT					
	Plaintiff, Peavey Electronics Corporation, (hereinafter "PLAINTIFF") files this, its Original					
	Complaint against Defendant Music Group Services US, Inc., a Washington Corporation doing					
5	business in Mississippi, (hereinafter "DEFENDANT"), and states as follows:					
,	I. PARTIES					
3						
)	1. Peavey Electronics Corporation is a Delaware Corporation registered to do business					
)	in the State of Mississippi, which is doing business in the Southern District of Mississippi. Plaintiff's					
2	address is 5022 Hartley Peavey Drive, Meridian, MS 39305.					
3	2. Defendant, Music Group Services US, Inc., is a Washington corporation doing					
1	business in the State of Mississippi and in the Southern District of Mississippi. Service of process is					
5	Seattle, WA 98101. On information and belief, Music Group Services US, Inc. is the parent					
5						
7	A same and the Debute continues in the United States					
ا	<ol> <li>Behringer has been known to utilize complex international corporate structures</li> </ol>					
$\dashv$	Original Complaint					

11

9

12 13

14 15

16

17 18

19

20

21

22 23

24 25

26

27

28

among which assets and liabilities are transferred. Defendants John Does 1-10 are those legal entities or other legal entities utilized by or acting in concert with Music Group Services US, Inc. to infringe the patent at issue in this case.

#### JURISDICTION AND VENUE II.

- This is an action for patent infringement arising under the patent laws of the United 4. States, Title 35, United States Code.
- This Court has subject matter jurisdiction over this action pursuant to 28 U.S.C. §§ 5. 1331 (federal question) and 1338(a) (action arising under an Act of Congress related to patents).
- This Court has personal jurisdiction over Defendant because Defendant has 6. constitutionally sufficient contacts with Mississippi to make personal jurisdiction proper in this Court. This Court has personal jurisdiction over Defendant based upon Defendant's business practices and contacts within this judicial district. In particular, Defendant has purposefully directed activities to this judicial district and does business in this judicial district.
- Venue is proper in this District pursuant to 28 U.S.C. §§ 1391(b), 1391(c) and 7. 1400(b) because a substantial part of the events giving rise to the claims occurred in this District, Defendant has sufficient contacts with this District to subject it to personal jurisdiction, and Defendant has committed acts of infringement and conducts business in this District.

#### III. JURY DEMAND

8. Pursuant to Federal Rule of Civil Procedure 38, Plaintiff demands a trial by jury of any issue triable of right by a jury pursuant to the Seventh Amendment to the Constitution of the United States or as given by a statute in the United States.

#### IV. BACKGROUND

Plaintiff is the owner of United States Patent Number 7,469,052 for a "Portable 9. Sound System, Apparatus and Method", issued December 23, 2008 (the "'052 patent"). A true and correct copy of this patent is attached hereto as Exhibit 1.

10. On information and belief, Defendant manufactures, sells, uses, and imports into the United States a product incorporating the apparatus and methods described in the '052 patent without license or authorization from Plaintiff. The Defendant's webpage has images of the infringing device, referred to by Defendant as the "EPA 150", and is attached hereto as Exhibit 2. Multiple websites clearly offer for sale the EPA 150, which contains the technology of the '052 patent. True and correct copies of those websites are attached hereto as Exhibit 3.

- 11. The manufacture, sale and use by Defendant of the technology described in the '052 patent in the EPA 150 product infringes Plaintiff's rights under the '052 patent.
- 12. On information and belief, the infringing embodiments of the '052 patent are being sold and used by Defendant in this judicial district and throughout the United States.

# **CAUSE OF ACTION**

- 13. Plaintiff incorporates the allegations of paragraphs 1-12 as though fully set forth herein.
- 14. On December 23, 2008, United States Patent No. 7,469,052, entitled "Portable Sound System, Apparatus and Method," was duly and legally issued to Hartley D. Peavey, inventor, and then assigned to Peavey Electronics Corporation. A true and correct copy of the '052 patent is attached to this Complaint as Exhibit 1. The '052 patent remains in full force and effect and Plaintiff continues to own it.
- 15. On information and belief, Defendant has infringed the '052 patent by making, having made, using, importing, selling and/or offering for sale, products embodying the invention claimed in the patent.
- 16. On information and belief, Defendant has induced infringement of and/or contributed to the infringement of the '052 patent by others.

7

12

13

14

15

16 17

18

19

20

21

22

23

24

25 26

27

28

- Each of Defendant's infringing activities is without the consent of, authority of, or 17. license from Plaintiff.
- On information and belief, Defendant has infringed claims 1 and 14 of the '052 18. patent either literally or under the Doctrine of Equivalents.
  - Defendant's infringement has been willful, knowing and deliberate. 19.
- As a direct and proximate result of Defendant's infringement, Plaintiff has been 20. damaged in an amount that cannot yet be fully ascertained, however, will be proven at trial.
- Unless permanently enjoined, Defendant will continue to engage in the 21. aforementioned acts to Plaintiff's further and continuing damage. Such continuing acts, unless enjoined, will cause irreparable damage in that Plaintiff will have no adequate remedy at law to compel Defendant to cease such acts.

# PRAYER FOR RELIEF

WHEREFORE, Plaintiff prays that the Court enter judgment in its favor and against Defendant, including:

- Entry of a permanent injunction enjoining Defendant, its officers, agents, servants, 1. employees and attorneys, and those persons in active concert or participation with it who receive actual notice thereof, from directly or indirectly infringing, or inducing, or contributing to the infringement of the '052 patent;
- Judgment in favor of Plaintiff and against Defendant for infringement of the '052 2. patent;
- An award to Plaintiff of damages for patent infringement in an amount adequate to 3. compensate, but in no event less than a reasonable royalty;
- 4. A treble award of Plaintiff's damages for willful, knowing and deliberate infringement of the '052 patent;

	Case 4:11-cv-00036-HTW -LRA Document 1 Filed 03/03/11 Page 5 of 34
1	5. Entry of judgment for Plaintiff's costs, interest, and reasonable attorneys' fees
2	incurred herein;
3	
4	6. An award in favor of Plaintiff for such other and further relief as the Court deems
5	proper.
6	Respectfully submitted,
7	$M \cap C \subset C$
8	
9	Michael D. Goggans  ATTORNEY FOR PLAINTIFF
10	Date: March 3, 2011
11	
12	MICHAEL D. GOGGANS (MSBN 10581) Peavey Electronics Corporation
13	5022 Hartley Peavey Drive
14	Meridian, MS 39305 Tel: 601.486.1113
15	Fax: 601.703.0012
16	
17	ATTORNEY FOR PLAINTIFF PEAVEY ELECTRONICS CORPORATION
18	
19	
20	
21	
22	
23	
<ul><li>24</li><li>25</li></ul>	
<ul><li>25</li><li>26</li></ul>	
27	
28	
20	

H	Case 4:1	1-cv-00036	-HTW -LRA Document 1 Filed 03/03/11 Page 6 of 34
1			
2			
3			
4			
5			
6			TABLE OF EXHIBITS TO COMPLAINT
7		Exhibit 1	U.S. Patent No. 7,469,052
8	-	Exhibit 2 Exhibit 3	Images of Behringer EPA150 from Behringer website Websites offering sale of EPA150
9		EXHIBIT 5	Websites offering sale of Ervized
10			
11			
12	,		
13			
14			
15			
16			
17			
18			
19			
20			
21	. *		
22			
23			
24	·		
25			
26			
27			
28			
			-6- Original Complaint

	Case 4:11-cv-00036-HTW -LRA Document 1 Filed 03/03/11 Page 7 of 34
1	
2	
3	
4	
5	
6	
7	
8	EXHIBIT 1
9	LAIIIDII I
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
	-7- Original Complaint
	Original Complaint



# (12) United States Patent Peavey

(10) Patent No.: US 7,469,052 B2 (45) Date of Patent: Dec. 23, 2008

(54)	PORTABLE SOUND SYSTEM, APPARATUS, AND METHOD				
(75)	Inventor:	Hartley D. Peavey, Meridian, MS (US)			
(73)	Assignee:	Peavey Electronics Corporation, Meridian, MI (US)			
(*)	Notice:	Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 998 days.			
(21)	Appl. No.:	10/872,260			
(22)	Filed:	Jun. 18, 2004			
(65)		Prior Publication Data			
	US 2005/0	281426 A1 Dec. 22, 2005			
(51)	Int. Cl. H04R 9/06 H04R 1/02 H04R 27/0 A45C 13/0	2 (2006.01) 00 (2006.01)			
(52)	U.S. Cl				
(58)	381/300, 24	381/82; 190/102 lassification Search			
(56)		References Cited			
	U.	S. PATENT DOCUMENTS			

6/1962 Bose ...... 179/1

3,038,964 A

4,061,890	A	12/1977	Froeschle 179/115.5
4,146,745	A	3/1979	Froeschle et al 179/1
4,158,756		6/1979	Keezer 179/115.5
4,450,495		5/1984	Naruki 360/137
4,896,360	A *	1/1990	Knight 381/82
5,903,657		5/1999	Chuo381/388
5,933,507	A *	8/1999	Woolley et al 381/300
7,043,044	B2 *	5/2006	Amid-Hozour 381/388
7,242,785		7/2007	McNary 381/182
2002/0176593		11/2002	Magnusson et al 381/301
2003/0076971		4/2003	Sperle et al 381/306
2003/0095671	Al*	5/2003	Long 381/87

#### FOREIGN PATENT DOCUMENTS

EP

15590 A1 \* 9/1980


\* cited by examiner

Primary Examiner—Vivian Chin Assistant Examiner—Kile Blair (74) Attorney, Agent, or Firm—Thomas, Kayden, Horstemeyer & Risley, LLP

#### 57) ABSTRACT

A portable sound unit is shown having a central case and one or more speakers. Each speaker has tongue rails around a portion of its circumference. The central case includes an openable lid permitting access to sound equipment contained within the central case. The central case has openings at either end when the lid is closed and grooves inside a portion of the central case near each opening. The grooves receive the tongue rails on the speaker when the lid is open. Upon positioning a speaker in the grooves in the central body, the lid may be closed, thereby securing the speakers to the central case. When the speakers are separated from the central case and electronically coupled to the sound equipment, the opened lid may serve as a lectern.


# 15 Claims, 9 Drawing Sheets



U.S. Patent


Dec. 23, 2008

Sheet 1 of 9



U.S. Patent Dec. 23, 2008

Sheet 2 of 9



U.S. Patent Dec. 23, 2008 Sheet 3 of 9 US 7,469,052 B2






FIG.3

U.S. Patent Dec. 23, 2008 Sheet 4 of 9




U.S. Patent Dec. 23, 2008

Sheet 5 of 9



U.S. Patent Dec. 23, 2008

Sheet 6 of 9



U.S. Patent

Dec. 23, 2008

Sheet 7 of 9





FIG.7


U.S. Patent Dec. 23, 2008

Sheet 8 of 9



U.S. Patent Dec. 23, 2008

Sheet 9 of 9 US 7,469,052 B2



# US 7,469,052 B2

#### PORTABLE SOUND SYSTEM, APPARATUS, AND METHOD

#### FIELD OF THE INVENTION

The present invention relates to audio systems, more specifically to a system and method for configuring a portable sound system.

#### BACKGROUND OF THE INVENTION

Before the advent of electronic sound amplification, public speaking and performing was typically accomplished by vocal projection in an effort to communicate to, by today's standards, small crowds and audiences. In rural areas, speak- 15 ers have historically been, and to some extent still are, limited in clearly communicating their messages to large numbers of people at one time. Indeed, politicians have been known to stand on tree stumps and plead for constituent's votes. However, "stumping," as it is called, has always limited the com- 20 municator to reaching just the people within the sound of the communicator's unamplified voice.

Yet, with the invention of sound amplification devices, speakers at churches, civic organizations and even outdoor arenas are able to communicate their message to a greater 25 number of people through electronic microphones, amplifiers and speakers placed within the facility or arena. Indeed, many such facilities are electronically prewired with sound amplification equipment so that speakers and other performing artists can speak to or perform before a greater number of 30 effects into the speech or other performed art. people.

However, a problem exists where people attempt to communicate to groups, crowds, etc. at facilities that are not necessarily prewired for sound amplification. Even today, many speakers and other performing artists are limited by 35 either the number of people who can hear their unamplified voice or by venues having sound systems, as many venues are not electronically wired for sound amplification.

Speakers, such as preachers and politicians, and other performing artists commonly travel to areas that are not equipped 40 with sound amplification equipment. As a result, the message or performed art cannot generally be viewed or heard by a large number of people. For that reason, speakers and other performing artists sometimes bring their own sound amplification equipment in an attempt to communicate with larger 45 audiences. Because of the size of such equipment and the number of requisite components, this oftentimes results in the speaker or other performing artist having to arrange for special transportation (i.e., a separate truck or trailer) for the sound amplification equipment. Indeed, in this instance, 50 assistance in unloading and assembling the equipment prior to the event is common due to the size and number of components. Likewise, disassembly of the equipment and reloading of the truck or trailer after the event typically involves assistance. Plus, in each case, planning and supervision are 55 typically required.

In many instances, this is impractical for individuals who merely desire to deliver a speech to a school, a church, a civic organization, or to some other small venue where it is impractical to also bring a large amount of sound amplification 60 position. equipment. For example, many politicians attempt to get their message out to as many people as possible in as short a period of time as possible; therefore, continually erecting and taking down sound amplification equipment is not practical for a politician who may have a number of speaking engagements 65 in one day. Thus, in this nonlimiting example, the politician typically either utilizes venues previously equipped with

appropriate sound amplification equipment, which may be too expensive to obtain or otherwise be unavailable, or they

as possible.

At least one attempt to solve these problems is found in devices where an amplifier mixer, speakers, and microphones are prepackaged together as a single unit. In such devices, the speakers are latched to the amplifier so that the unit is relatively small and capable of being transported by one or a small 10 number of people. Upon arrival at the desired location, which may not have adequate sound amplification equipment, the speakers can be unlatched and electrically connected to the amplifier mixer, which itself may be connected to, for example, a microphone.

use their unamplified voice and hope to reach as many people

However, the problem with these types of units is that, because the speakers are commonly one of the larger components of the unit, insuring secure transport of the device is difficult. Securing the speakers to these types of units for transport in a way that allows safe handling of the unit and protection of the equipment must be considered. For if the speakers become unattached from the unit during transport, damage to the equipment and/or injury to the handler could

Consequently, some such systems include latches or other coupling components to secure the speakers to the unit during non-use and/or transportation between events. When the components are unpacked and prepared for use, the latches or other metal coupling components on the speakers vibrate during performances, thereby introducing undesirable sound

For these reasons then, a heretofore unaddressed need exists in the industry to address the aforementioned deficien-

#### DESCRIPTION OF THE DRAWINGS

Many aspects of the invention can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the present invention. In fact, no particular emphasis is placed on any ornamental aspect shown in the drawings. Indeed, one or ordinary skill in the art would know that other ornamentally different embodiments may be configured that still illustrate the principles of the invention described herein. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

FIG. 1 is a perspective view diagram of the portable sound unit of the present invention, as shown in a closed position with two speakers attached.

FIG. 2 is a perspective view diagram of the portable sound unit of FIG. 1 with the lid shown in an open position exposing the speakers and mixer panel.

FIG. 3 is a perspective view of a speaker of the portable sound unit of FIG. 1.

FIG. 4 is a rear perspective view of the portable sound unit of FIG. 1 with the speakers unattached and electronically coupled to the mixer of FIG. 2 and also with the lid in an open

FIG. 5 is a perspective view of the portable sound unit of FIG. 1, with the lid shown in an open position and one of the speakers separated from the main unit, exposing the mixer, of FIG. 2 and exemplary signal generation devices.

FIG. 6 is a diagram of the portable sound unit of FIG. 1 with a speaker shown detached from the main body and electrically coupled to the mixer of FIG. 2.

FIG. 7 is a front and side diagram of an alternative embodiment of the speaker of the portable sound unit of FIG. 1.

FIG. 8 is a diagram of an alternative embodiment of the portable sound unit of FIG. 1, which also depicts the lid as a lectern.

FIG. 9 is a diagram of yet another alternate embodiment of the portable sound unit of FIGS. 1 and 2.

# DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A portable sound unit with a central case and one or more speakers is described and shown herein. In one nonlimiting example, each speaker has "tongue" rails around all of, or a portion of, its circumference. The central case includes an 15 openable lid permitting access to sound equipment contained within the central case. The central case has openings at either end when the lid is closed and grooves inside a portion of the central case near each opening. The grooves receive the "tongue" rails on the speaker when the lid is open. Upon  $_{20}$ positioning a speaker in the grooves of the central body, the lid containing grooves similar to the central case may be closed, thereby securing the speakers around the entire periphery of the speaker to the central case. When the speakers are separated from the central case and electronically 25 coupled to the sound equipment, the opened lid may serve as a lectern.

The drawings referenced herein are showings for the purposes of illustrating embodiments of the invention and not for purposes of limiting same. In fact, this description of each preferred and alternative embodiment comprises but select embodiments among others, which one of ordinary skill in the art would know upon review of this disclosure.

FIG. 1 is a diagram of the portable sound unit 10. In this embodiment, the portable sound unit 10 includes central body 12 and speakers 14, 16. Central body 12 is shown herein with lid 17 in a closed position. Attached on either side of the central body 12 are speakers 14 and 16, which are shown as being captured by the central body 12 and the lid 17.

As discussed in more detail below, lid 17 of central body 12 40 may be removable by several methods, as one skilled in the art would know. As nonlimiting examples, hinges, clips, latches, etc. may be used to secure lid 17 to central body 12. In this nonlimiting example, lid 17 is securable to central body 12 by latch 20 and hinges 60 (FIG. 4).

Attached to lid 17 is edge 19, which as described in more detail below, enables lid 17 to operate as a lectern for holding papers and other items in place when lid 17 is held in an open position by a support bar 24 or some other auto-open method. One of ordinary skill in the art should know that edge 19 may be configured in different arrangements in addition to as shown herein. For example, edge 19 may indeed be molded into the lid 17 so as to not extend beyond the surface plane of lid 17. Stated another way, the surface of lid 17 may actually indent into the lid 17 so as to create edge 19 for holding papers or other items in place on lid 17.

Also shown in FIG. 1 is handle 18 attached to central body 12. One of ordinary skill in the art would know that any type of handle or handling mechanism could be implementing in addition to handle 18, which is merely a nonlimiting example.  $_{60}$ 

As portable sound unit 10 is shown in a closed position, speakers 14 and 16 are held in place by the closing of the grooved lid 17 such that a portion of speakers 14 and 16, as more thoroughly described below, is trapped or captured within the interior of central body 12 and the lid 17. Thus, 65 when speakers 14 and 16 are attached to central body 12, the portable sound unit 10 may be transported by an individual by

being carried by handle 18. As an additional nonlimiting example, portable sound unit 10 may be rolled by wheels attached to the underside of central body 12 (not shown) in similar fashion to rollable luggable. In this nonlimiting example, handle 18 may be configured such that it telescopes to an extended position to enable a user to roll the portable sound unit 10 to its desired location.

FIG. 2 is a diagram of portable sound unit 10 shown with lid 17 in an open position. Shown attached to the inside surface of lid 17 is support 24. In this nonlimiting example, support 24 hinges from the inside surface of lid 17 for supporting lid 17 in an angled position relative to the plane of central body 12. In this way and as more thoroughly described below, the outer surface of lid 17 operates as lectern while portable sound unit 10 is in use.

One of ordinary skill in the art would know that support 24 may be likewise coupled to central body 12 or may be an entirely separate member that may be used to hold lid 17 open and at a predetermined angle relative to central body 12. In addition, two or more supports 24 may be implemented on lid 17, central body 12, or otherwise as described herein to provide additional support to hold lid 17 at a predetermined angle, which will generally be acute, as shown in FIG. 4.

Instead of support 24 holding lid 17 in an angled position, hinges 60 (FIG. 4) may be tensionally configured to support lid 17 at a predetermined angle wherein lid 17 may be used as a lectern. Thus, support 24 and hinges 60 are two of many methods, as known in the art, for enabling lid 17 to operate as a lectern.

Speakers 14 and 16 are shown in FIG. 2 as resting in a groove that secures speakers 14 and 16 in place. As shown on lid 17, groove portions 27 and 29 are configured on each lateral side of lid 17. Groove portion 27 is comprised of wall sections 31 and 33 separated by a predetermined space to therefore create groove 34. Likewise, groove portion 29 is formed by wall section 36 and 38, thereby creating groove 39. As shown in this nonlimiting example, the groove portions 27 and 29 on lid 17 are also continued on the base and sides of central body 12.

Speakers 14 and 16 each have a tongue rail 41 (on speaker 16) and 43 (on speaker 14), which comprise the male portions that fit into grooves 34 and 39. Furthermore, tongue rails 41 and 43 are shown resting in grooves 27 and 29 respectively, created on central body 12.

FIG. 3 is a perspective view of speaker 14 of FIG. 2. In this nonlimiting example, speaker 14 is comprised of a rear section 45 that couples to a front section 47. Also shown in front section 14 is wide range driver 51, tweeter 52, and wide range driver 53. In this nonlimiting example, tongue rail 43 is shown positioned between rear section 45 and front section 47 extending completely around the outer circumference of speaker 14. Although, not separately shown is FIG. 3, speaker 16 is configured similarly to speaker 14, as shown and described herein.

Tongue rail 43 is shown rising by a predetermined amount beyond the outer surface of speaker 14 to thereby create a tongue rail, which operates as a male portion for integration with groove 39 or 34 of FIG. 2, which operates as the female portion of the "tongue-and-groove" fastening method. Upon separation from the central body 12, speaker 14 in FIG. 3 or speaker 16 in FIG. 2 may be electrically coupled to power mixer 22 of FIG. 2.

FIG. 4 is a diagram of the portable sound unit 10 shown in a separated format wherein speakers 14 and 16 are detached from central body 12. In this nonlimiting example, support 24

is shown in an extended position extending between the inside surface of lid 17 and a supporting point in central body 12.

In this nonlimiting example, lid 17 is coupled to central body 12 by hinge 60, which permits lid 17 to swing open and 5 close. As discussed above, one of ordinary skill in the art would know that support 24 may be positioned at different points to create different angles of rise of lid 17 relative to central body 12. As a nonlimiting example, support 24 may also be positioned on ledge 55, which forms a portion of 10 central body 12. This placement and positioning results in lid 17 being at a greater angle relative to the plane of central body 12. In the nonlimiting example wherein the surface of lid 17 is used as a lectern, the angle between lid 17 and central body 12 is acute.

Shown attached to powered mixer 22 in central body 12 are a number of input/output jacks 61. Input/output jacks 61 may comprise various inputs or outputs to mixer 22 which may be inputs from signal sources and/or outputs for signal connection to speakers 14, 16.

In this nonlimiting example, cable 58 is shown coupled between output 61 and rear input 59 of speaker 16. Likewise, cable 56 is shown coupled between a second output 61 and rear input 57 of speaker 14. One of ordinary skill in the art would know that rear speaker inputs 57, 59 may be positioned at any point on speaker 14, 16.

43. When speaker 14 is coupled to central body 12 verill and groove 39, speaker 14 essentially be integral part of central body 12. Likewise, in this no example, speaker 16 is shown separated from central would know that rear speaker inputs 57, 59 may be positioned at any point on speaker 14, 16.

As speaker 16 is separated from central body 12, groove 34 of central body 12 is displayed extending around the interior surface of central body 12. One of ordinary skill would know that speakers 14, 16 may be positioned distally (wired or wirelessly) from central body 12. Indeed, if the portable sound unit 10 is used for, as a nonlimiting example, for a speech, etc., the speakers 14, 16 may be positioned in the arena, or other facility, to output the amplified voice of the speaker. Additionally, lid 17, as supported by support 24 or 35 tensioned hinges 60, may operate as a lectern for the speaker to position items such as papers, notecards, etc., as held or stopped by edge 19.

FIG. 5 is another diagram of portable sound unit 10 with lid 17 shown in an open position with speaker 14 separated from 40 central body 12 and with speaker 16 shown positioned in groove 34 of central body 12. More specifically, the tongue rail 41 of speaker 16 is shown positioned in groove 34 of central body 12. Likewise, speaker 14 is detached from central body 12 such that tongue rail 43 is separated from groove 45 39, which, in this nonlimiting example, extends around the interior surface of central body 12 and lid 17.

In this nonlimiting example, mixer 22 includes a cassette player 68 and a compact disc player 69 as signal generation sources for producing sound output through speakers 14 and 50 16. One of ordinary skill in the art would know, however, that other integral or external sound generation sources could be implemented in addition to tape cassette 68 and compact disc player 69 for producing audio output through mixer 22 and speakers 14 and 16. In addition and as nonlimiting examples, 55 additional signal generation sources, such as an MP3 player or other computer may be electronically coupled to mixer 22 via one or more inputs 61, as shown in FIG. 4.

It should be noted that mixer 22 may be configured as any type of electronic audio manipulation equipment, as known in 60 the art. As a nonlimiting example, mixer 22 may include an amplifier for driving speakers 14, 16.

It should be understood from FIG. 5 that when tongue rail 43 of speaker 14 and tongue rail 41 of 16 are positioned within grooves 39 or 34, respectively, and when lid 17 is in closed 65 position on central body 12, speaker 14 and 16 are secured to central body 12. In this situation, neither speaker 14, 16 can

become separated from central body 12 during transport or storage. It should be noted that speaker 14 and 16 lack any type of vibrating devices, such as latches, buckles, or other securing mechanisms to secure speaker 14 and 16 to central body 12. It is known that devices such as latches or other buckles on speakers commonly create undesired vibration noise during operation, which deteriorates overall sound quality produced by speakers 14 and 16. Thus, by the incorporation of tongue rails 41 and 43 for coupling with grooves 34 and 39, speakers 14, 16 and cannot be removed from central body 12 when lid 17 is in a closed position (FIG. 1) and do not introduce undesired sounds (rattles) during opera-

FIG. 6 is a diagram of the portable sound unit 10 of FIG. 1 with lid 17 shown in an open position and speaker 16 shown detached from central body 12 and electrically coupled to mixer 22. In this diagram, speaker 14 is shown with tongue rail 43 positioned in groove 39 of central body 12. Groove 39 of lid 17 is shown removed from the top portion of tongue rail 43. When speaker 14 is coupled to central body 12 via tongue rail 43 and groove 39, speaker 14 essentially becomes an integral part of central body 12. Likewise, in this nonlimiting example, speaker 16 is shown separated from central body 12 and coupled via cable 58 to output 61 of mixer 22.

Compartments 77 and 78 in central body 12 are shown as storage areas for items such as cables 58 and 56 (FIG. 4), microphones (not shown), speaker stands for placing speakers 14 and/or 16 above the ground (not shown), or any other similar item, which one of ordinary skill in the art would know may be found in and/or transported with portable sound equipment 10.

FIG. 7 is a diagram of speaker 80, which is an alternative embodiment of speakers 14 and 16 described above. In this alternative embodiment, speaker 80 lacks a tongue rail extending completely around the outer perimeter of the speaker 80, as described above in regard to tongue rail 43 on speaker 14 and tongue rail 41 on speaker 16. In this alternative embodiment, speaker 80 includes tongue rail 82, which, as a nonlimiting example, is placed near a top portion of speaker 80 extending along the top side of speaker 80. Likewise, speaker 80 also includes tongue rail 84 along a bottom portion of speaker 80. As shown in FIG. 7, neither tongue rail 82 nor tongue rail 84 substantially extend along the vertical sides of speaker 8. Instead, tongue rails 82 and 84 are positioned on the top and bottom portions in this nonlimiting example.

FIG. 8 displays portable sound unit 90 with the speaker 80 of FIG. 7. Central body 12 is configured with groove rails appropriately positioned for securing speaker 80 to central body 12.

As stated above, speaker 80 includes tongue rails 82 and 84 at the top and bottom sections of speaker 80. Likewise, central body 12 is configured with groove 95 along with the vertical walls of central body 12. More specifically, groove 95 is surrounded by wall sections 92 and 94 to create groove 95. Likewise, wall section 97 is also placed near an additional inner wall section (not shown), but similar to wall section 92. In this fashion, speaker 80 may be positioned within groove 95 and the corresponding groove proximate to wall 97 for securing speaker 80 to central body 12. It should be noted that similar wall sections and grooves are located at the other opening in central body 12.

One of ordinary skill in the art would also know that the tongue rail and groove system as described in this alternative embodiment may be configured in a multitude of fashions such that the tongue rails 82 and 84 are placed on different

portions of speaker 80, such as in one nonlimiting example on the vertical side portions of speaker 80 for mating with central body 12.

Another such alternative embodiment is shown in FIG. 9. Here, inside wall sections 102, 104 on lid 17 couple to inside 5 wall sections 106, 108 on central body 12 to secure tongue rails 82 and 84 to central body 12. In this nonlimiting example, tongue rails 82, 84 do not extend completely around speaker 80, and grooves 102, 104, 106, 108 do not extend completely around the interior of central body 12. Yet, when 10 lid 17 is in a closed position and latch 20 is locked, speaker 80 is secured to central body 12 and cannot become unattached.

In yet another embodiment, the tongue rails and the corresponding grooves may be configured in reverse fashion as described above. More specifically, the grooves of the previously described tongue-and-groove configuration may also be configured on the speakers 14, 16. Likewise, the tongue rails may also be configured on central body 12 (in the position of the grooves in, for example, FIG. 6). This alternative embodiment shows that the male and female portions of the 20 tongue and groove assembly may be on either the central body or the speakers, respectively, to the extent that the speakers 14, 16 may slidably couple to the central body by the tongue-and-groove assembly.

It should be emphasized that the above-described embodiments, particularly, any "preferred" embodiments, are merely possible examples of implementations, merely set forth for a clear understanding of the principles of this disclosure. Many variations and modifications may be made to the above-described embodiments without departing substantially from the spirit and principles this disclosure. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims.

#### I claim:

- 1. A portable sound unit, comprising:
- one or more speakers, each having tongue rails around a portion of the circumference of the speaker;
- a central case with a openable lid, the central case having openings at either end when the lid is in a closed position and the lid configured to maintain the acute angle when in an open position;
- electronic audio manipulation equipment contained in the 45 central case having one or more inputs and outputs:
- one or more grooves inside a portion of the central case near each of the openings or receipt of the tongue rails of the one or more speakers when the lid is in an open position such that the one or more speakers may be 50 secured to the central case when the lid is closed; and
- an edge fashioned along at least a portion of the width of the outer surface of the lid, the edge configured to hold items against the outer surface of the lid hen the lid maintains an open position.
- 2. The portable sound unit of claim 1, wherein tongue rails of the one or more speakers are configured completely around the outer circumference of the one or more speakers, and wherein the grooves near each of the openings extend completely around the interior of the case so that the tongue rails on each side of the outer circumference of the one or more speakers is positioned in a groove when the lid is in a closed

position thereby preventing each of the one or more speakers from separating from the central case when the lid is in the closed position.

8

- 3. The portable sound unit of claim 1, further comprising: means for connecting electronic signals between the electronic audio manipulation equipment and each speaker when the speaker is distally positioned from the central case.
- 4. The portable sound unit of claim 1, further comprising: a lip configured on the outer portion of the central case at each of the openings to prevent the one or more speakers from separating from the central case when the lid is in a closed position and the tongue rails of the one or more speakers are positioned in the grooves at one of the openings, wherein the grooves inside the central case near each of the openings do not extend completely around each of the openings.
- The portable sound unit of claim 1, wherein the one or more speakers lack securing agents that vibrate when the one or more speakers produce sound.
  - 6. The portable sound unit of claim 1, further comprising: a supporting member coupled to the inner surface of the lid to hold the lid at an acute angle relative to the central case.
  - 7. The portable sound unit of claim 1, further comprising: a supporting member coupled to an interior portion of the central case and adjustable to support the lid at an acute angle relative to the central case.
  - 8. The portable sound unit of claim 1, further comprising: one or more hinges coupled to the central case and the lid, the hinges configured to hold the lid at an acute angle relative to the central case when the lid is in an open position.
- 9. portable sound unit of claim 1, wherein the outer surface of the lid comprises a lectern when in the open position.
  - 10. The portable sound unit of claim 1, further comprising: a handle coupled to the central case.
  - 11. The portable sound unit of claim 1, further comprising: one or more storage compartments within the central case.
  - 12. The portable sound unit of claim 1, wherein the electronic audio manipulation equipment is coupled to one or more signal input devices.
  - 13. The portable sound unit of claim 12, wherein the signal generating device is a compact disc player.
    - 14. A portable sound unit, comprising:
    - one or more speakers, each having grooves around a portion of the circumference of the speaker;
  - a central case with an openable lid permitting access to sound manipulation equipment contained within the central case, the central case having openings at either end when the lid is in a closed position and tongue rails inside a portion of the central case near each of the openings for receipt of the grooves of the one or more speakers when the lid is in an open opposition such that the one or more speakers may be secured to the central case when the lid is closed;
  - the lid having a stop for holding items against the lid when the lid is opened forming a lectern.
- 15. The portable sound unit of claim 14, wherein the outersurface of the lid operates a lectern when the lid is positioned in the open position.

\* \* \* \* \*

	Case 4:11-cv-00036-HTW -LRA Document 1 Filed 03/03/11 Page 22 of 34
1	
2	
3	
4	
5	
6	
7	
8	EXHIBIT 2
9	
10	
11	
12	
13	
14	
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
	-8- Original Complaint



Products

Support

Community

Our Story

Join Us

**Buy Now** 

Artists

News

Language: Loading...

You are here: Home » Products » EPA150

Overview Features Documentation Photos

# **EUROPORT EPA150**

Ultra-Compact 150-Watt 5-Channel Portable PA System with Digital Effects and FBQ Feedback Detection

Ultra-compact 2 x 75-Watt, 5-channel portable PA system in a briefcase format

System sets up in seconds—perfect for entertainment, multi-media presentations, press conferences, board meetings, etc.

Enormous power, incredible sonic performance and super-light weight

Studio-grade 24-bit stereo FX processor with 100 awesome presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects

Revolutionary FBQ Feedback Detection system instantly reveals critical frequencies for easy feedback removal

2 "Invisible" mic preamps with phantom power for condenser microphones,  $1\,$  mic/inst channel and  $1\,$  stereo channel with separate CD input

Stereo 7-band graphic EQ allows precise frequency correction of main outputs


Comes with one BEHRINGER XM1800S microphone, mic clip and cable

Compact speakers contain powerful 4" woofers and a 1" tweeter, 17 mm stand insert suitable for use with standard microphone stand and come with 12' cables

Integrated storage compartment for microphone, cables, and accessories

"Planet Earth" switching power supply for maximum flexibility (100 - 240 V~), noise-free audio, superior transient response plus low power consumption for energy savings

High-quality components and exceptionally rugged construction ensure long life Conceived and designed by BEHRINGER Germany









Large [121.9 KB] Extra Large [847.9 KB]

Large [84.9 KB] Extra Large [947.4 KB]





Large [141.3 KB] Extra Large [1.1 MB]

Large [112.6 KB] Extra Large [1.2 MB]





Large [141.7 KB] Extra Large [1.1 MB]

Large [116.2 KB] Extra Large [1.3 MB]

**Products** 

Sometimes you just don't need a large, complicated PA system to get your message across. In fact, you might not need a big system at all! For those occasions when you do need to get your voice above the crowd, such as a company meeting, a picnic or party, the EPA150 brings that extra volume, along with all the accessories you'll need, in a convenient, easy to carry and setup package. And the good news is you don't have to be a sound engineer to run it!

## Lots of Connections

The EPA150 comes ready for your input, literally. Channels 1 and 2 accept balanced XLR mics, as well as balanced and unbalanced 14" line sources, such as electronic keyboards and the like. An acoustic or electric guitar can be connected directly via Channel 3's Mic/Inst input. Want to play some of your favorite tunes at the picnic? Just plug a CD/MP3 player into the Channel 4/5 RCA jacks and crank it up!





# Superb Sound Quality

A great deal of engineering went into the design of the EPA150. Since we already make some of the best-sounding audio mixers, amplifiers and loudspeakers on the planet, it should come as no surprise that the EPA150 provides far superior sound quality than other products in this class. The satellite loudspeakers feature twin custom-designed 4.0" woofers and a 1.0" tweeter for incredible fidelity and clarity that belies their small size.

#### Loaded With Features...

And we mean truly professional features: long-throw faders, instead of rotary controls for precise level adjustments; active 3-band channel EQ, for exceptional tone control of signal sources; phantom power, so you can use studio-grade condenser mics; a 7-band stereo graphic EQ, to adjust overall system response;



Mixers

Small Format Mixers Large Format Mixers Digital Mixers Rackmount Mixers Powered Mixers DI Mixers Mixer Accessories

Loudspeakers and Studio Monitors

Professional Passive Speakers Professional Powered Speakers On-Wall Distributed Speakers Studio Monitors Multimedia Speakers

Loudspeaker Mounts and Accessories

**Power Ampliflers** 

Studio Monitor Amplifiers PA Amplifiers

PA Systems

Handheld PA Systems

Portable PA Systems

Signal Processors

Multi-Effects Processors Crossovers

Equalizers

Audio Enhancers and Exciters

Feedback Suppressors

Patchbays

Microphone Preamplifiers

Audio Converters

Headphone Amplifiers and Monitoring

Phono Preamplifiers

Compressors and Limiters

Noise Gates Beat Counters

Test Equipment

Modeling and Effects Processors

Bass Modeling/Effects Processors Guitar Modeling/Effects Processors

Stompboxes, Tuners and Accessories

Guitar Stompboxes Bass Stompboxes Stompbox Combo Packs Stompbox Accessories Footswitches and Remote Control

Tuners

Guitar Amplifiers and Speakers

Acoustic Guitar Amplifiers Electric Guitar Amplifiers Guitar Speaker Cabinets

Bass Amplifiers and Speakers

Bass Amplifiers

Bass Speaker Cabinets

Keyboard Amplifiers

Keyboard Amplifiers Microphones

Large Diaphragm Microphones

Condenser Microphones Dynamic Microphones

Wireless Microphone Systems

Headphones

DJ Headphones

Studio Headphones

MIDI Controllers

Desktop Controllers

Keyboard Controllers

DJ Controllers

MIDI Accessories

Audio Interfaces

Recording Packages and Software

Recording Packages and Software

and our state-of-the-art FBQ Feedback Detection System, to track and eliminate those annoying mic squeals.





# The Sweet Sound of Reverb, or Delay, or ...

If you're making a speech, chances are you won't need it, but if you're playing a musical instrument and/or singing, you might want to add some effects. So, we've included a 24-bit stereo FX processor with 100 great-sounding presets including reverb, chorus, fl anger, delay, pitch shifter and various multi-effects to sweeten your performance.

## Everything You Need


The EPA150 is a complete system. Just set up the main unit on a tabletop, deploy the speakers and connect them with the included cables. Connect the highquality XM1800S microphone (we've even included a long mic cable and mic stand clip) and hit the power switch-voilá, instant PA system! When you are done, just stow the mic and all accessories in the onboard storage compartment.



#### Value

When you compare the sound quality, features and price to the competition, we think you will agree the EPA150 provides extreme value as a complete, portable PA solution.

#### **EPA150 Mixer Features**



#### Musical Instruments

Electric Guitars Digital Pianos

Musical Instrument Packages

## Lighting Systems

DMX Controllers

Power Packs Luminaires

Lighting Accessories

#### Support

Warranty and Service Information

Find Answers or Ask Behringer

Downloads and Drivers Product Registration


Locations

Limited Warranty

Copyright 2011, Red Chip Company Ltd. All rights reserved, | Privacy Policy | Imprint & Terms of Use | Site Map | Behringer Newsletter


#### **EPA150 Rear Mixer Panel Features**

0




EPA150 Hookup Example

# Live Performance with Backing Tracks



# EPA150 Business Presentation Hookup Example Business Presentation Setup



9	Case 4:11-cv-00036-HTW -LRA	Document 1	Filed 03/03/11	Page 27 of 34	
1					
2					
3					
4					
5					
6					
7					
8		EXHIE	BIT 3		
9					
10					
11					
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
		-9- Original Compl			
		Original Compl	aint		



**Products** 

Support

Community

Our Story

Join Us


**Buy Now** 

Αi

You are here: Home » Buy Now

# Your Results

Click on the icon to get directions.




Total Matching Results: 3

In USA for Postal code 39201 with a search radius of 50 Miles, Would you like to Search Again

1. Lakeland Music 5200 Hwy 25 Flowood, MS 39232 Phone: 601–992–0089 Fax: 1 601 992 4497

mark@lakelandmusic.com

- 2. Guitar Center 790 1189 East County Line Road, Jackson, MS 39211 Phone: 1 601 956 8053 Fax: 1 601 956 8455
- 3. Powerline Music & More 411 E Franklin St Carthage, MS 39051 Phone: 601–267–4475 Fax:



© Copyright 2011. Red Chip Company Ltd. All rights reserved. | Privacy Policy | Imprint & Terms of Use | Site Map | Behrin


[AD]

Web Images Videos Maps News Shopping Gmail more - Sign in

Google products behringer epa150 Search Products

# Behringer EPA150 Europort Briefcase-Style Portable PA System

Overview - Online stores - Details - Related items



# \$248 online

The Behringer EUROPORT EPA150 is a portable briefcase-style PA system with 150-Watts stereo output and two detachable high-fidelity loudspeakers (both featuring a 4" woofer and a 1" tweeter). It offers an excellent power-to-weight ratio with its Class-D a Add to Shopping List

_			
()n	line	STO	res

Show only: Google Checkout Free shipping New items Your location: Meridian, MS 39301 - Change							
Relevance	Seller rating	Condition	Tax and shipping	Total price	Base price		
Amazon.com	5.517 seller ratings	New			\$326.99		
B&H Photo-Video-Audio	39.720 seller ratings	New	No tax + Free shipping	\$326.99	\$326.99		
American Musical	2,162 seller ratings	New	No tax + Free shipping	\$326.99	\$326.99		
zZounds	1,334 seller ratings	New	No tax + Free shipping	\$326.99	\$326.99		
<u>Newark</u>	11 seller ratings	New			\$326.99		
ProSound & Stage Lighting	16 seller ratings	New	No tax + Free shipping	\$326.99	\$326.99		
MCM Electronics	19 seller ratings	New			\$326.99		
<u>Studica</u>	11 seller ratings	New			\$299.95		
Focused Technology	310 seller ratings	New	No tax + Shipping: \$45.00	\$324.00	\$279.00		
KaraokeEquipment.com	23 seller ratings	New			\$248.00		

View all 25 online stores »

Online stores 1 - 10 of 25 Next >

Ads

Quality Briefcases www.leathertree.com

Wide Variety, Fine Designer Leather Briefcases, Great Prices, Free Ship

Behringer EPA150 System

zzounds.com We'll beat any price on Behringer! 4 payments. No interest.

#### **Details**

Brand

**BEHRINGER** 

Part Numbers

000-64202-00000, EPA150

UPC

4033653061452

#### Related items



PWMA930I 600-W PRTBL PA w/WRLS/IPOD Dk

1 review \$145 new



B-52 Matrix 1000V2 Sound System Package 2 reviews

\$670 new



Audio Unlimited Premium 900MHz Wireless Indoor/Outdoor 4 Speaker ...

22 reviews

\$150 new



**Behringer** Eurolive B212XL 800-Watt 2-Way PA Speaker System with

\$143 new



Marathon (ENT-118) Single 18" Subwoofer System - Entertainer <u>Series</u> \$229 new

View all related items »

#### \$99 Loud Portable PA VHF

www.dak.com

Small, Light AC/DC VHF Wireless Mic & 20-Watt PA for up to 100 people.

#### Portable PA Systems

www.schooloutfitters.com

Get portable PA systems for audiences from 5 to 5,000 people.

#### Portable PA's On Sale

www.audiolinks.com

All Portable Public Address Systems Great Prices! Specials. Rush Orders

Google Home

Advertising Solutions

**Business Solutions** 

Privacy

About Google

Google does not charge for inclusion in its search results and all advertisements are clearly marked. Tax and shipping costs are estimates.

<u>Home</u> » <u>Audio & Sound Equipment</u> » <u>Speakers</u> » <u>Portable Powered Sound Systems</u> » <u>Portable Self Powered Sound Systems</u> » <u>EPA150</u> Print Email

# Behringer EPA150 Portable PA System, 150W, 5-Channel Mixer w/Digital FX

Our Price: \$326.99List Price: \$653.99
You save 50%! (Low Price Guarantee)
Usually ships in 1-2 business days

Qty: 1 BUY NOW Add to Quote Add to Wishlist



CLICK TO ENLARGE

<u>Description</u>



**EPA150** 

Sometimes you just don't need a large, complicated PA system to get your message across. In fact, you might not need a bit system at all. For those occasions when you do need to get your voice above the crowd, such as a company meeting, a picnic or party, the EPA150 brings that extra volume, along with all the accessories you'll need, in a convenient, easy to carry and setup package. And the good news is you don't have to be a sound engineer to run it.

#### **Features**

- Ultra-compact 2 x 75W, 5-channel portable PA system in a briefcase format
- System sets up in seconds perfect for entertainment, multi-media presentations, press conferences, board meetings, etc
- Enormous power, incredible sonic performance and super-light weight
- Studio-grade 24-bit stereo FX processor with 100 presets including reverb, chorus, flanger, delay, pitch shifter and various multi-effects
- Revolutionary FBQ Feedback Detection system instantly reveals critical frequencies for easy feedback removal

- 2 "Invisible" mic preamps with phantom power for condenser microphones, 1 mic/inst channel and 1 stereo channel with separate CD input
- Stereo 7-band graphic EQ allows precise frequency correction of main outputs
- Comes with one Behringer XM1800S microphone, mic clip and cable
- Compact speakers contain powerful 4" woofers and a 1" tweeter, 17mm stand insert suitable for use with standard microphone stand and comes with 12' cables
- Integrated storage compartment for microphone, cables, and accessories
- "Planet Earth" switching power supply for maximum flexibility (100-240 V), noise-free audio, superior transient response plus low power consumption for energy savings
- High-quality components and exceptionally rugged construction ensure long life

#### TMGR# EPA150

# Copyright © 2011 <u>Full Compass Systems</u>, LTD. All rights reserved.

Please read our <u>Terms of Service</u>, <u>Privacy Policy</u> and <u>Conditions Statement</u>.

Not responsible for typographical errors in pricing or product specification inaccuracies in our catalog or web site. Prices are subject to change without notice.

best possible value with exceptional customer service. We offer over 700 top equipment brands including, Shure, Yamaha, Panasonic, Sony, JBL,

### **Proud Member of:**



Full Compass is a national leader in Professional Audio, Professional Video, A/V and Lighting sales. For over 30 years, our goal has been to provide the best possible value with exceptional customer service. We offer over 700 top equipment brands including, Shure, Yamaha, Panasonic, Sony, JBL, Sennheiser, Sanyo, QSC, Audio-Technica, Crown and much more. We also provide services such as computer systems integration, lighting design, and rentals. Full Compass is an authorized service center and parts distributor for most of the major manufacturers we carry.