

FILED

1 **WANG, HARTMANN, GIBBS & CAULEY, P.C.**

2 A Professional Law Corporation

3 Franklin E. Gibbs (SBN: 189015)

4 Erick P. Wolf (SBN: 224906)

5 1301 Dove Street, Suite 1050

6 Newport Beach, CA 92660

7 Telephone: (949) 833-8483

8 Facsimile: (949) 833-2281

9 Attorneys for Plaintiff

2010 FEB 23 PM 3:21

CLERK U.S. DISTRICT COURT
CENTRAL DIST. OF CALIF.
SANTA ANA

BY: _____

10 **UNITED STATES DISTRICT COURT**
11 **CENTRAL DISTRICT OF CALIFORNIA**

12 **DOBERMAN SECURITY**
13 **PRODUCTS, INC., a California**
14 **corporation,**

15 Plaintiff,

16 vs.

17 **TECHKO, INC., a California**
18 **corporation,**

19 Defendant.

Case No. **SACV10-00225 JVS (RNBx)**

COMPLAINT FOR:

1. DECLARATORY JUDGMENT OF
NON-INFRINGEMENT; AND
2. DECLARATORY JUDGMENT OF
INVALIDITY;

DEMAND FOR JURY TRIAL

20 Plaintiff Doberman Security Products, Inc. ("Doberman"), for its Complaint
21 against Defendant Techko, Inc. ("Techko"), states as follows:

22 **NATURE OF THE ACTION**

23 1. This is an action for declaratory relief regarding invalidity and non-
24 infringement of U.S. Patent No. 7,187,280 ("the '280 Patent") and U.S. Patent No.
25 5,473,310 ("the '310 Patent"), true and correct copies of which are attached as
26 Exhibits 1 and 2, respectively, to this Complaint.

27 **PARTIES**

28 2. Plaintiff Doberman is a California corporation with a principal place
of business at 3002 Dow Avenue, Suite 408, Tustin, California 92780.

1 3. Defendant Techko is a California corporation with, on information
2 and belief, a principal place of business at 27301 Calle De La Rosa, San Juan
3 Capistrano, California 92675.

4 **JURISDICTION AND VENUE**

5 4. This action seeks declaratory judgment under the Declaratory
6 Judgment Act, 28 U.S.C. § 2201 et seq. and under the Patent Laws of the United
7 States, including 35 U.S.C. § 1 et seq. It presents an actual case or controversy
8 under Article III of the United States Constitution and serves a useful purpose in
9 clarifying and settling the legal rights at issue.

10 5. This Court has subject matter jurisdiction over this action pursuant to
11 28 U.S.C. §§ 1331 and 1338(a), because this action involves a claim arising under
12 the patent laws of the United States, 35 U.S.C § 1, *et seq*, and under the Federal
13 Declaratory Judgment Act, 28 U.S.C. §§ 2201 and 2202.

14 6. Personal jurisdiction and venue are proper in the Court pursuant to 28
15 U.S.C. §§ 1391(a), 1391(b), 1391(c), and/or 1400(b), in that Techko resides in this
16 judicial district, and a substantial part of the events giving rise to this action are
17 occurring in this judicial district. Techko products, upon information and belief,
18 are offered for sale and/or sold in the Central District of California through retail
19 outlets and online at www.techkousa.com.

20 **FACTS**

21 7. On December 19, 2008, attorneys for Techko sent Doberman a cease
22 and desist letter alleging that Doberman's Pool Alert alarm system infringed the
23 '310 Patent and that Doberman's Door and Window Defender alarm system, and
24 related home bundles, infringed the '280 Patent. The letter demanded that
25 Doberman cease sales of the allegedly infringing alarm systems. A true and
26 correct copy of this letter is attached as Exhibit 3.

1 8. On March 25, 2009, Doberman submitted a Request for
2 Reexamination of the '280 Patent. On April 30, 2009 the United States Patent and
3 Trademark Office ("USPTO") granted the Request.

4 9. On September 29, 2009, the USPTO issued a Reexamination Office
5 Action rejecting all eight claims of the '280 patent under 35 U.S.C. § 102 and/or §
6 103 in view of Japanese Utility Model Registration No. 3,087,940 to Nakano
7 ("Nakano").

8 10. On November 25, 2009, Techko filed a Response to the September
9 25, 2009 Office Action. The Response included a declaration made under 37
10 C.F.R. § 1.131 by the inventor and CEO of Techko, Joseph Ko ("Ko"). The
11 declaration included testimony from Ko, along with supporting exhibits, that
12 purported to establish a conception and reduction to practice date for the invention
13 prior to the August 23, 2002 publication date of Nakano.

14 11. On January 27, 2010, the USPTO issued a Notice of Intent to Issue Ex
15 Parte Reexamination Certificate.

16 12. Based on the above conduct, this Court has jurisdiction over this
17 action. There is a clear and objective basis for Doberman to believe that there is a
18 real an imminent danger that Techko will sue for alleged infringement of the '280
19 Patent and the '310 Patent.

20 13. Accordingly, a valid and justiciable controversy has arisen and exists
21 between Doberman and Techko. Doberman desires a judicial determination and
22 declaration of the respective rights and duties of the parties herein. Such a
23 determination and declaration is necessary and appropriate at this time so that the
24 parties may ascertain their respective rights and duties.

25 **First Cause of Action**

26 **(Declaratory Judgment of Invalidity of U.S. Patent No. 7,187,280)**

27 14. Doberman repeats and realleges paragraphs 1 through 13 as though
28 fully set forth herein.

1 15. Techko claims that the '280 Patent is valid and enforceable, while
2 Doberman believes the '280 Patent is invalid and unenforceable because it fails to
3 satisfy the conditions and requirements for patentability as set forth, *inter alia*, in
4 Sections 102, 103, and/or 112 of Title 35 of the United States Code.

5 16. An actual, present, and justiciable controversy has arisen between
6 Techko and Doberman concerning the validity and enforceability of the '280
7 Patent.

8 17. Doberman seeks declaratory judgment from this Court that the '280
9 Patents is invalid and unenforceable.

10 **Second Cause of Action**

11 **(Declaratory Judgment of Invalidity of U.S. Patent No. 5,473,310)**

12 18. Doberman repeats and realleges paragraphs 1 through 17 as though
13 fully set forth herein.

14 19. Techko claims that the '310 Patent is valid and enforceable, while
15 Doberman believes the '310 Patent is invalid and unenforceable because it fails to
16 satisfy the conditions and requirements for patentability as set forth, *inter alia*, in
17 Sections 102, 103, and/or 112 of Title 35 of the United States Code.

18 20. An actual, present, and justiciable controversy has arisen between
19 Techko and Doberman concerning the validity and enforceability of the '310
20 Patent.

21 21. Doberman seeks declaratory judgment from this Court that the '310
22 Patents is invalid and unenforceable.

23 **Third Cause of Action**

24 **(Declaratory Judgment of Non-Infringement of U.S. Patent No. 7,187,280)**

25 22. Doberman repeats and realleges paragraphs 1 through 21 as though
26 fully set forth herein.

27 23. Techko claims that Doberman's alarm systems, including Doberman's
28 Door and Window Defender alarm system, and related home bundles, infringe the

1 '280 Patent and demands that Doberman cease and desist offering to sell these
2 products in the United States.

3 24. As discussed above, Doberman believes that the claims of the '280
4 patent are invalid because they fails to satisfy the conditions and requirements for
5 patentability as set forth, *inter alia*, in Sections 102, 103, and/or 112 of Title 35 of
6 the United States Code. Unless a patent claim is valid, there can be no finding of
7 infringement.

8 25. Doberman contends that it has not infringed, has not willfully
9 infringed, is not now infringing, has not contributorily infringed, and has not
10 induced infringement of any claim of the '280 patent.

11 26. An actual, present, and justiciable controversy has arisen between
12 Techko and Doberman concerning Doberman's right to sell its alarm systems,
13 including Doberman's Door and Window Defender alarm system, and related
14 home bundles, in the United States.

15 27. Doberman seeks declaratory judgment from this Court that its alarm
16 systems, including Doberman's Door and Window Defender alarm system, and
17 related home bundles, do not infringe the '280 Patent.

18 **Fourth Cause of Action**

19 **(Declaratory Judgment of Non-Infringement of U.S. Patent No. 5,473,310)**

20 28. Doberman repeats and realleges paragraphs 1 through 27 as though
21 fully set forth herein.

22 29. Techko claims that Doberman's alarm systems, including Doberman's
23 Pool Alert alarm system, infringe the '310 Patent and demands that Doberman
24 cease and desist offering to sell these products in the United States.

25 30. As discussed above, Doberman believes that the claims of the '310
26 patent are invalid because they fails to satisfy the conditions and requirements for
27 patentability as set forth, *inter alia*, in Sections 102, 103, and/or 112 of Title 35 of
28

1 the United States Code. Unless a patent claim is valid, there can be no finding of
2 infringement.

3 31. Doberman contends that it has not infringed, has not willfully
4 infringed, is not now infringing, has not contributorily infringed, and has not
5 induced infringement of any claim of the '310 patent.

6 32. An actual, present, and justiciable controversy has arisen between
7 Techko and Doberman concerning Doberman's alarm systems, including
8 Doberman's Pool Alert alarm system, in the United States.

9 33. Doberman seeks declaratory judgment from this Court that its alarm
10 systems, including Doberman's Pool Alert alarm system, do not infringe the '280
11 Patent.

12
13 **PRAYER FOR RELIEF**

14 WHEREFORE, Doberman requests that the Court grant the following relief:

15 A. A declaratory judgment against Techko that the '280 Patent is invalid
16 and unenforceable;

17 B. A declaratory judgment against Techko that the '310 Patent is invalid
18 and unenforceable;

19 C. A declaratory judgment against Techko that Doberman's alarm
20 systems, including Doberman's Door and Window Defender alarm system, and
21 related home bundles, do not infringe the '280 Patent;

22 D. A declaratory judgment against Techko that Doberman's alarm
23 systems, including Doberman's Pool Alert alarm system, do not infringe the '310
24 Patent;

25 E. Attorneys' fees;

26 F. Costs; and

27 G. For such other and further relief as the Court may deem proper.
28

1 Dated: February 23, 2010

WANG, HARTMANN, GIBBS & CAULEY
A Professional Law Corporation

3 By:

Franklin E. Gibbs

Erick P. Wolf

Attorneys for Plaintiff

DEMAND FOR JURY TRIAL

Plaintiff hereby demands a jury trial as provided by Rule 38 of the Federal Rules of Civil Procedure.

Dated: February 23, 2010

WANG, HARTMANN, GIBBS & CAULEY
A Professional Law Corporation



By:  
Franklin E. Gibbs
Erick P. Wolf
Attorneys for Plaintiff

EXHIBIT 1



US007187280B2

(12) **United States Patent**
Ko

(10) **Patent No.:** **US 7,187,280 B2**

(45) **Date of Patent:** **Mar. 6, 2007**

(54) **ALARM SYSTEM WITH THIN PROFILE**

(75) Inventor: **Joseph Y. Ko**, Laguna Niguel, CA (US)

(73) Assignee: **Techko, Inc.**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 271 days.

(21) Appl. No.: **10/903,330**

(22) Filed: **Jul. 30, 2004**

(65) **Prior Publication Data**

US 2005/0068176 A1 Mar. 31, 2005

Related U.S. Application Data

(60) Provisional application No. 60/491,391, filed on Jul. 31, 2003.

(51) **Int. Cl.**
G08B 13/08 (2006.01)

(52) **U.S. Cl.** **340/545.2**; 340/547; 340/521;
340/693.5

(58) **Field of Classification Search** 340/547,
340/545.2, 521, 693.5, 541, 545.1, 545.5;
200/61.7–61.73, 61.45 R, 61.45 M; 335/207,
335/205, 206

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,319,228 A 3/1982 Daniels

4,327,359 A	4/1982	Kurtz	
4,438,430 A	3/1984	Young et al.	
4,677,424 A	6/1987	Hollinger	
4,847,719 A	7/1989	Cook et al.	
4,864,087 A	9/1989	Chen	
4,910,634 A	3/1990	Pipkorn	
4,962,602 A *	10/1990	Meyrowitsch	40/541
5,164,705 A	11/1992	Dunagan et al.	
5,353,015 A	10/1994	Robinson	
5,554,833 A	9/1996	Johnson	
5,576,678 A	11/1996	Saunders	
6,078,050 A *	6/2000	Castleman	250/339.15
6,278,367 B1 *	8/2001	Baglin	340/546
6,570,508 B1 *	5/2003	Kvenvold	340/870.17
6,989,746 B2 *	1/2006	Rasmussen	340/541

* cited by examiner


Primary Examiner—Anh V. La

(74) *Attorney, Agent, or Firm*—Knobbe Martens Olson & Bear LLP

(57) **ABSTRACT**

An alarm system includes a housing that substantially encloses a plurality of sensors and an alarm-signal generator. The housing has a thin profile and may be mountable in various locations, such as on a window surface. The thin profile of the housing allows the alarm system to be attached to the surface of a first window and capable of being located between the first window surface and a second window surface upon relative motion between the first window surface and the second window surface.

8 Claims, 9 Drawing Sheets



U.S. Patent

Mar. 6, 2007

Sheet 1 of 9

US 7,187,280 B2




FIG. 1

U.S. Patent

Mar. 6, 2007

Sheet 2 of 9

US 7,187,280 B2




FIG. 2

U.S. Patent

Mar. 6, 2007

Sheet 3 of 9

US 7,187,280 B2




FIG. 3

U.S. Patent

Mar. 6, 2007

Sheet 4 of 9

US 7,187,280 B2




FIG. 4

U.S. Patent

Mar. 6, 2007

Sheet 5 of 9

US 7,187,280 B2




FIG. 5

U.S. Patent

Mar. 6, 2007

Sheet 6 of 9

US 7,187,280 B2




FIG. 6B




FIG. 6A

U.S. Patent

Mar. 6, 2007

Sheet 7 of 9

US 7,187,280 B2




FIG. 7B




FIG. 7A

U.S. Patent

Mar. 6, 2007

Sheet 8 of 9

US 7,187,280 B2




FIG. 8B




FIG. 8A

U.S. Patent

Mar. 6, 2007

Sheet 9 of 9

US 7,187,280 B2




FIG. 9

US 7,187,280 B2

1

ALARM SYSTEM WITH THIN PROFILE

REFERENCE TO RELATED APPLICATION

This application claims the benefit of priority under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 60/491,391, filed on Jul. 31, 2003, and entitled "ALARM SYSTEM WITH THIN PROFILE," the entirety of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

Embodiments of the present invention relate generally to alarm systems, and more particularly, to alarm systems having a thin profile.

2. Description of the Related Art

Alarm systems generally are used to secure an area from unwanted intrusion. For example, alarm systems are often found in dwellings, places of business, and other locations where safety is a concern or where the protection of personal property is desired. Typically, an alarm system triggers a perceptible signal, such as a sound or a light, when the area protected by the alarm system has been breached. Conventional alarm systems use sensors, such as motion sensors, to detect the breaches of security. Oftentimes, these breaches of security occur through entryways, such as a door of a building, or through windows.

Conventional alarm systems often include components that are large, unsightly, or obstructive. For example, alarm systems that are installed to monitor the security of a window often require components that must be affixed to the window and/or window pane and that obstruct the relative movement of window surfaces. In addition, typical alarm systems require that physical modifications, such as the drilling of holes, be made to a window or surrounding area to install components of the alarm system. Furthermore, conventional alarm systems often include wiring or unsightly components connecting sensors to a central monitoring system.

Such conventional alarm are often difficult to install or maintain and can require significant labor during installation or maintenance of the system. This often increases the cost of purchasing, installing, and/or maintaining the alarm system.

SUMMARY OF THE INVENTION

Embodiments of the invention improve upon conventional alarm systems with the use of a plurality of sensors and a housing having a thin profile. Features of embodiments of the invention allow for unobstructed use of a secured window, quick and easy installation and maintenance, and reduced manufacturing and production costs over conventional alarms.

In one embodiment, an alarm system includes a vibration sensor, a magnetic sensor, a speaker, control circuitry, and a housing. The vibration sensor senses vibration of the alarm system and is configured to output a first signal upon sensing the vibration. The magnetic sensor is configured to sense changes in distance between the alarm system and a signal-generating device and is configured to output a second signal upon sensing the changes in distance. The control circuitry is coupled to the vibration sensor, to the magnetic sensor, and to the speaker, and is configured to cause an audible alarm through the speaker in response to receiving the first signal or the second signal. The housing substantially

2

encloses the vibration sensor, the magnetic sensor, the speaker, and the control circuitry, and comprises a thin profile. For example, the thin profile of the housing allows the alarm system to be attached to a first window surface such that the housing is capable of being located between the first window surface and a second window surface upon relative motion between the first window surface and the second window surface.

In another embodiment of the invention, a self-contained alarm system includes a plurality of sensors, an alarm-signal generator, and a housing. The plurality of sensors and the alarm signal generator are disposed within the housing. In addition, the housing comprises a thin profile and is mountable on a first window surface such that the housing is capable of being located between the first window surface and a second window surface upon relative motion between the first window surface and the second window surface.

In another embodiment of the invention, a self-contained alarm system comprises a plurality of sensors, an alarm-signal generator, and a housing, wherein the plurality of sensors and the alarm signal generator are disposed within the housing, and wherein the housing comprises a profile of less than about 0.5 inch.

In another embodiment, an alarm system comprises a plurality of means for sensing, a means for generating an alarm signal, and a means for housing the plurality of means for sensing and the means for generating an alarm signal. The means for housing comprises a thin profile and is mountable on a first window surface such that the means for housing is capable of being located between the first window surface and a second window surface upon relative motion between the first window surface and the second window surface.

In another embodiment, a method of installing a security device on a window assembly comprises: attaching a signal-generating element to a first location of a window assembly having a first window and a second window, wherein the surfaces of the first window and the second window are in substantially parallel planes; and attaching a self-contained alarm system to the surface of the first window, wherein the alarm system is configured to sense a signal emitted by the signal generating element, and wherein the alarm system comprises a thin profile and is capable of being located between the first window surface and the surface of the second window upon relative motion between the first window surface and the second window surface.

For purposes of summarizing the invention, certain aspects, advantages and novel features of the invention have been described herein. It is to be understood that not necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a perspective view of one embodiment of an alarm system having a thin profile;

FIG. 2 is an exploded perspective view of one embodiment of the alarm system;

FIG. 3 illustrates a perspective view of the bottom side of one embodiment of the alarm system;

FIG. 4 illustrates a block diagram of alarm circuitry of the alarm system, according to one embodiment of the invention;

US 7,187,280 B2

3

FIG. 5 illustrates a flow chart of one embodiment of an alarm process executed by the alarm system;

FIGS. 6A and 6B illustrate elevational views of a window assembly and the alarm system, according to one embodiment of the invention;

FIGS. 7A and 7B illustrate elevational views of a window assembly and the alarm system, according to another embodiment of the invention;

FIGS. 8A and 8B illustrate elevational views of a window assembly and the alarm system, according to yet another embodiment of the invention; and

FIG. 9 illustrates a side view of one embodiment of the alarm system being positioned between two window surfaces.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The features of embodiments of the invention will now be described with reference to the drawings summarized above. Throughout the drawings, reference numbers are re-used to indicate correspondence between referenced elements. The drawings, associated descriptions, and specific implementation are provided to illustrate embodiments of the invention and not to limit the scope of the invention.

In addition, methods and functions described herein are not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state.

FIG. 1 illustrates one embodiment of an alarm system 10. The alarm system 10 comprises a housing 12 having an upper portion 14 and a lower portion 16. The housing 12 is structured to enclose at least a portion of alarm circuitry, which is described in more detail with reference to FIG. 4.

In certain embodiments of the invention, the housing 12 advantageously has a thin profile. The term "profile" as used herein is a broad term and is used in its ordinary sense and includes without limitation the thickness of at least one dimension of the alarm system 10. For example, the term "profile" may relate to the width, length, and/or height of the housing 12 of the alarm system 10.

A thin profile advantageously facilitates placement of the alarm system 10 in locations with limited space, such as between windows. For example, in one embodiment, the housing 12 preferably has a profile of approximately 0.5 inch (1.27 centimeters) or less. In other embodiments, the housing 12 has a profile of approximately 0.375 inch (0.95 centimeters) or less. In yet other embodiments, the housing 12 advantageously has a profile of approximately 0.25 inch (0.635 centimeters) or less. In other embodiments of the invention, the housing 12 may have a profile of greater than 0.5 inch.

In one embodiment, the upper portion 14 is coupled to the lower portion 16. The upper portion 14 may be marked with a symbol 18 that indicates to a user the proper orientation of the alarm system 10. For example, the alarm system 10 may need to be oriented in a particular direction in order to function correctly (e.g., internal sensors may require a certain orientation). In one embodiment, the symbol 18 is an arrow. In other embodiments, the symbol 18 may comprise words, characters, illustrations, indentations, or the like that indicate to the user the proper positioning of the alarm system 10. In other embodiments of the invention, the alarm system 10 is not orientation-dependent.

4

In one embodiment, the upper portion 14 defines one or more vents 20. The vents 20 advantageously provide a location for sound, such as that created by the alarm circuitry or an alarm-signal generator, to escape from the housing 12.

The upper portion 14 may also define an indicator opening 22 that permits viewing of an indicator, such as a light, that displays the status of the alarm system 10. For example, the indicator may display whether the alarm system 10 is activated or deactivated, or may display the battery status of the alarm system 10.

The alarm system 10 also comprises a control switch 24. In one embodiment, the control switch 24 preferably is coupled with the alarm circuitry and extends through an opening in the upper portion 14 of the housing 12. The control switch 24 preferably has a plurality of positions. For example, the control switch 24 may comprise an "OFF" position that indicates when the alarm system 10 is deactivated. The control switch 24 may also comprise a plurality of decibel-level positions that indicate the loudness of an alarm signal emitted or caused by the alarm system 10. In one embodiment of the invention, the control switch comprises a 70-decibel position and a 90-decibel position. In other embodiments, another number of levels may be used or the magnitude of the decibel options may differ. When the control switch 24 is in one of the plurality of decibel positions, the alarm system 10 preferably is activated, and upon being triggered, the alarm system 10 sounds an audible alarm at the selected decibel level.

It is contemplated that in other embodiments of the invention the control switch 24 may take on forms or configurations other than a switch. For example, the control switch 24 may comprise a rotatable knob that allows for a continuous range of possible outputs. In other embodiments, the control switch 24 may comprise a touch screen, a sliding control, or other interface that allows for a user to select between different modes of operation of the alarm system 10.

FIG. 2 illustrates an embodiment of the invention wherein the upper portion 14 further comprises a removable portion 26. The removable portion 26 comprises a plurality of tabs 28, 30, 32 that communicate with a plurality of slots 34, 36, 38 defined in the lower portion 16 to retain the removable portion 26 in a closed configuration. In certain embodiments, the removable portion 26 advantageously comprises a plurality of ridges 40 to facilitate sliding the removable portion 26 relative to the lower portion 16 to allow the removable portion 26 to be removed. In other embodiments of the invention, the removable portion 26 may be configured without tabs or may be configured so as to be partially removable from the alarm system 10. For example, the removable portion 26 may be attached by a hinge to the lower portion 16 or to the remainder of the upper portion 14. In one embodiment, the removable portion 26 allows access to a power source 42 of the alarm system 10 when the removable portion 26 is at least partially removed.

FIG. 3 illustrates a perspective view of the bottom of one embodiment of the alarm system 10. The lower portion 16 of the housing 12 preferably comprises a layer of adhesive 44 to facilitate mounting the alarm system 10. Such suitable adhesives are generally known in the art and may be applied directly to the lower portion 16 or may be provided by a suitable material, such as dual-sided sticky-backed tape. In one embodiment, the adhesive 44 of the lower portion 16 facilitates mounting the alarm system 10 to a window surface.

The lower portion 16 may also comprise a warning label 46. When the alarm system 10 is mounted to a window

US 7,187,280 B2

5

surface, the warning label **46** preferably is viewable from an opposite side of the window surface. In this respect, the warning label **46** serves as a deterrent by providing notification to would-be intruders that the area is secure and/or protected by the alarm system **10**.

FIG. **4** illustrates a block diagram of one embodiment of an alarm circuitry **48** of the alarm system **10**. The alarm circuitry **48** includes a vibration sensor **50**, a magnetic sensor **52**, an alarm-signal generator **54**, the power source **42**, the control switch **24**, and an indicator light **56**. The alarm circuitry **48** also comprises control circuitry **58** that is coupled to at least one of the other components of the alarm circuitry **48**.

The vibration sensor **50** is configured to detect vibration or movement. For example, the vibration sensor **50** may detect movement or vibration of an apparatus to which the alarm system **10** is attached or which the alarm system **10** is configured to monitor, such as a window or a door. In other embodiments, the vibration sensor **50** senses vibration of the alarm system **10**. The vibration sensor **50** preferably sends a signal to the control circuitry **58** upon detection of vibration. The control circuitry **58** then triggers the alarm-signal generator **54** to activate the alarm.

In one embodiment of the invention, the vibration sensor **50** comprises a piezoelectric material, which piezoelectric materials are known in the art. For example, the vibration sensor **52** may comprise a piezoelectric crystal. When the piezoelectric material is exposed to vibration (e.g., vibration of the alarm system **10**), the piezoelectric material undergoes a compression or distortion and, as a result, produces an electric field. This electric field is then used in activating or in causing to activate the alarm-signal generator **54**. In addition, certain piezoelectric materials vibrate when a particular voltage is applied to the material, which vibration results in a perceptible sound. Thus, the piezoelectric material can be advantageously used in sensing vibration (e.g., in the vibration sensor **50**) and/or in generating an alarm signal (e.g., in the alarm-signal generator **54**).

In one embodiment of the invention, the vibration sensor **50** outputs a signal to the control circuitry **58** if the magnitude of the vibration sensed is above a threshold amount. In other embodiments of the invention, the vibration sensor **50** outputs a signal that is based on characteristics of the vibration being sensed, and the control circuitry **58** determines whether the alarm-signal generator **54** should be activated. For example, vibrations of certain frequencies may be filtered out so that they do not activate the alarm-signal generator **54**.

The magnetic sensor **52** preferably detects relative movement of the alarm system **10** with respect to another device. In one embodiment, the magnetic sensor **52** comprises a reed switch. The magnetic sensor **52** advantageously detects motion of the alarm system **10** toward or away from a signal-generating element (not shown). For example, the alarm system **10** having the magnetic sensor **52** may be located on a window while the signal-generating element is located on another surface, such as a second window, a window sill, or a window pane. In one embodiment, the signal-generating element causes an electromagnetic field that is detectable by the magnetic sensor **52**. When the distance between the magnetic sensor **52** and the signal-generating element changes, the electromagnetic field at the magnetic sensor **52** also changes. The magnetic sensor **52** preferably is coupled to the control circuitry **58** and sends a signal to the control circuitry **58** upon detection of relative movement between the alarm system **10** and the signal-generating element. Upon detection of relative movement,

6

the control circuitry **58** preferably triggers the alarm-signal generator **54** to activate the alarm.

In one embodiment, the signal-generating element comprises a permanent magnet and can be mounted to a metallic surface by magnetic force. The magnetic signal-generating element may also be marked to facilitate proper orientation of the alarm system **10** relative to the magnetic signal-generating element. In one embodiment of the invention, the magnetic signal-generating element and the alarm system **10** are located in close proximity to each other, such as within a few inches, during normal use.

It is contemplated that the alarm circuitry **48** may comprise more or fewer sensors than the two sensors depicted in FIG. **4**. In addition, in other embodiments of the invention, other types of sensors may be used. For example, in one embodiment a sound sensor could be used to detect sounds that could trigger the alarm. In other embodiments, optical sensors may be used to detect motion. While embodiments have been described with exemplary types of sensors, any type or combination of sensors may be used. For example, the alarm system **10** may comprise a magnet, and an external magnetic sensor may be used to detect motion of the alarm system **10**.

The alarm-signal generator **54** is configured to generate an alarm when triggered or activated by the control circuitry **58**. The term "alarm-signal generator" as used herein is a broad term and is used in its ordinary sense and includes without limitation any device, component, apparatus, system or method of generating, causing, emitting or transmitting a signal that indicates the occurrence of some event or condition.

In one embodiment of the invention, the alarm-signal generator **54** generates or transmits an audible alarm upon being triggered by the control circuitry **58** in response to a signal received from one of the plurality of sensors **50**, **52**. For example, the alarm-signal generator **54** may comprise a speaker. In one embodiment, the alarm-signal generator **54** is configured to generate alarms at a plurality of decibel levels. For example, the alarm-signal generator **54** may generate an alarm at approximately 70 decibels. In other embodiments, the alarm-signal generator **54** generates an alarm at approximately 90 decibels, or more.

The power source **42** preferably provides power to the control circuitry **58** and to other components of the alarm circuitry **48**. In one embodiment, the power source **42** comprises one or more batteries. For example, the power source **42** may comprise three 1.5-volt alkaline button cell batteries. In other embodiments, other types of batteries may be used, such as lithium ion batteries, solar cell batteries, and the like. In yet other embodiments of the invention, the power source **42** may comprise other types of devices or systems that can provide power to the alarm circuitry **48**.

In certain embodiments, the power source **42** is accessed by removing the removable portion **26** of the alarm system **10** as described above. In some embodiments, the power source **42** may comprise a primary power source and a secondary power source, wherein the secondary power source preferably provides back-up power to the primary power source.

With continued reference to FIG. **4**, the indicator light **56** provides an alert as to certain conditions of the alarm system **10**. For example, the indicator light **56** may comprise a light-emitting diode (LED) that illuminates when the power source **42** is low. In certain embodiments, the indicator light **56** illuminates when the alarm system **10** is active and turns off when the alarm system **10** is inactive or has run out of power. In other embodiments, the indicator light **56** blinks

US 7,187,280 B2

7

when the power source **42** is low. In further embodiments of the invention, the alarm-signal generator **54** may chirp, or generate other audible sounds, when the power source **42** is low. As discussed above, the indicator light **56** is advantageously visible through the indicator opening **22** in the housing **12**.

The control circuitry **58** is configured to communicate with the sensors **50**, **52**, the alarm-signal generator **54**, the control switch **24**, and the indicator light **56**. The control circuitry **58** may be implemented in hardware, firmware, or and/or software. For example, the control circuitry **58** may comprise various logic gates coupled so as to perform the functions described above. The control circuitry **58** is advantageously powered by the power source **42**.

In some embodiments, the alarm system **10** is a self-contained system with all components of the alarm circuitry **48** disposed or substantially contained within the housing **12**. A self-contained alarm system **10** may be a stand-alone system or work in connection with a signal-generating element located outside of the housing **12**. For example, in some embodiments, a self-contained alarm system **10** is a stand-alone system having all components of the alarm circuitry **48** substantially enclosed by the housing **12**, and no interaction with a signal-generating element is needed for activation of the alarm. In other embodiments, a self-contained alarm system **10** has all the components of the alarm circuitry **48** located within the housing **12**, and the alarm system **10** interacts with a signal-generating element located outside of the housing **12**.

It is also contemplated that all the components of the alarm circuitry **48** need not be enclosed by the housing **12**. For example, certain components of the alarm circuitry **48** may be located within the housing **12** and may communicate with other components of the alarm circuitry **48** that are located outside the housing **12**. For example, in some embodiments, a sensor **50** or **52** of the alarm circuitry **48** may be located within the housing **12**, while other components of the alarm circuitry **48**, such as, for example, the alarm-signal generator **54**, may be located outside of the housing **12**. In other embodiments, components of the alarm circuitry **48** that are located in the housing **12** can be coupled to, or in communication with, a central alarm control system (not shown) having other components of the alarm circuitry **48**. In yet other embodiments of the invention, a central alarm control system is advantageously coupled to, or in communication with, a plurality of alarm systems **10**. In some embodiments, the alarm system **10** can be remotely activated or controlled.

The components of the alarm circuitry **48** can also be separated into multiple subcomponents or can be separated into multiple devices that reside at different locations and that communicate with each other, such as through wired or wireless communications (e.g., radio frequency communication). Multiple components may also be combined into a single component. It is also contemplated that the components described herein may be integrated into a fewer number of modules. One module may also be separated into multiple modules.

FIG. 5 illustrates a block diagram of an alarm process **100** for the alarm system **10** according to one embodiment of the invention. The alarm process **100** begins with State **102**, wherein it is determined if the alarm system **10** is powered on. If the alarm system **10** is not powered on, the alarm process **100** remains in State **102**. If the alarm system **10** is powered on, the alarm process **100** moves to State **104**.

At State **104**, it is determined whether the alarm system **10** is armed. In certain situations, a user of the alarm system **10**

8

may want the alarm system **10** to be in an “unarmed” state. For example, a home user may want to open a window or a door without having the alarm system **10** trigger an alarm. In one embodiment of the invention, the control switch **24** allows the user to select an “unarmed” state. In other embodiments, the alarm system **10** may be preprogrammed to enter an armed or an unarmed state according to an established schedule. For example, the alarm system **10** may automatically enter an armed state at a certain time each day, such as at 11:00 P.M.

If the alarm system **10** is not in an armed state, the alarm process **100** remains in State **104**. If the alarm system **10** is armed, the alarm process **100** moves to a State **106**. At State **106**, the alarm process **100** determines if the alarm system **10** senses vibration. For example, the vibration sensor **50** may be used to sense vibration of the alarm system **10** or vibration of an object being monitored.

If vibration is sensed, the alarm process **100** moves to a State **110**, wherein an alarm is activated. The alarm may comprise any signal, notification, or output that indicates that the alarm system **10** has been triggered. In one embodiment, the alarm comprises an audible alert, such as a loud noise. In other embodiments, the alarm comprises a visual alert, such as a flashing light. In yet other embodiments, the alarm comprises a signal that is sent to a monitoring system or device that records the signal and manages or coordinates a response, such as the dispatching of persons to the site of the triggered alarm system **10**. Multiple alarms may also be activated that comprise at least one of the above-described alarms or that comprise other devices or methods for emitting an alert.

If no vibration is sensed, the alarm process **100** moves to a State **108**, wherein it is determined if the magnetic sensor is triggered. In one embodiment, the alarm system **10** comprises the magnetic sensor **52**, which is triggered by certain motions or movements, as described above. If the magnetic sensor is triggered, then the alarm process **100** moves to State **110** and activates the alarm. If the magnetic sensor is not triggered, the alarm process **100** returns to State **106** to monitor for vibration.

Embodiments of the alarm system **10** are able to be used in a variety of locations or to monitor a variety of objects. For example, in one embodiment, the alarm system **10** is configured to mount or attach to a window surface. In such an embodiment, a securing material, such as the adhesive **44**, allows for the lower portion **16** of the alarm system **10** to easily mount to the window surface. As a result, physical modifications, such as the drilling of holes or the insertion of screws or nails, to the window or window assembly (e.g., window sill) are not needed to install the alarm system **10**. In one embodiment, the thin profile of the alarm system **10**, allows for the alarm system **10** to be mounted to a window without obstructing the functioning (e.g., sliding) of the window, an associated screen, or another associated window.

FIGS. 6A and 6B illustrate one method of monitoring a window assembly utilizing embodiments of the alarm system **10** that sense vibration. As illustrated, the alarm system **10** is affixed to a stationary window **200**. In one embodiment, the alarm system **10** is affixed with an adhesive or other material as described previously. Using an adhesive allows for the alarm system **10** to be easily attached to the window **200** without the need for extra tools and without requiring a substantial amount of time or effort to complete the installation process.

When the alarm system **10** is armed, or in the state of monitoring the window, vibrations of the window **200** may

US 7,187,280 B2

9

cause the alarm system 10 to activate an alarm. For example, FIG. 6B illustrates the window 200 being broken, such as by a rock or a would-be intruder. The vibrations resulting from the breaking of the window 200 are sensed by the alarm system 10, and as a result, the alarm is activated.

FIGS. 7A and 7B illustrate one method of monitoring a window assembly utilizing embodiments of the alarm system 10 that sense movement. For example, such embodiments of the alarm system 10 may comprise the magnetic sensor 52. As illustrated, the alarm system 10 is affixed to a moveable window 202. In one embodiment, the alarm system is affixed with an adhesive or other like material. A signal-generating element 204 is affixed or mounted to a stationary surface 206. The signal-generating element 204 may comprise a magnet or other type of device that is capable of emitting and/or receiving a signal, as was discussed previously. The stationary surface 206 may comprise any apparatus, object or device that normally remains in a fixed position, such as a window pane, a wall, or a stationary window.

When the alarm system 10 is armed, or in the state of monitoring the window, movement of the alarm system 10 away from or toward the signal-generating element 204 causes the alarm system 10 to activate an alarm. In other embodiments, movement of the signal-generating element 204 away from or toward the alarm system 10 activates an alarm. For example, FIG. 7B illustrates the moveable window 202 being slid away from the signal-generating element 204, which is affixed to the stationary surface 206. This movement is sensed by the alarm system 10, and as a result, an alarm is activated.

FIGS. 8A and 8B illustrate another method of monitoring a window assembly utilizing embodiments of the alarm system 10 that sense movement. As illustrated, the alarm system 10 is affixed to a second window 208, and the signal-generating element 204 is affixed to the moveable window 202. When the alarm system 10 is armed, and the moveable window 202 is opened or moved, the alarm system 10 activates an alarm, as is illustrated in FIG. 8B. In other embodiments, the alarm system 10 may be affixed to the moveable window 202, and the signal-generating element may be affixed to the second window 208.

FIGS. 8A and 8B also illustrate one of the advantages of embodiments of the alarm system 10 having a thin profile. The thin profile of the alarm system housing 12 allows the moveable window 202 to slide past the second window 208, and other structures, without obstruction, while the alarm system 10 is attached to the second window 208. As illustrated in FIG. 9, in one embodiment, the thin-profile housing 12 allows for the alarm system 10 to fit between two windows, such as the moveable window 202 and the second window 208, having surfaces that are in approximately parallel planes.

10

While certain embodiments of the inventions have been described, these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel methods and systems described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and changes in the form of the methods and systems described herein may be made without departing from the spirit of the inventions.

What is claimed is:

1. An alarm system comprising:

a vibration sensor configured to sense vibration of the alarm system and configured to output a first signal upon sensing said vibration;

a magnetic sensor configured to sense changes in distance between the alarm system and a signal-generating device and configured to output a second signal upon sensing said changes in distance;

a speaker;

control circuitry coupled to the vibration sensor, to the magnetic sensor, and to the speaker, wherein said control circuitry is configured to cause an audible alarm through said speaker in response to receiving said first signal or said second signal; and

a housing substantially enclosing the vibration sensor, the magnetic sensor, the speaker, and the control circuitry, wherein said housing comprises a thin profile and is attachable to a first window surface such that said housing is capable of being located between the first window surface and a second window surface upon relative motion between the first window surface and the second window surface.

2. The alarm system of claim 1, wherein said housing has a profile of about 0.5 inch or less.

3. The alarm system of claim 1, wherein said housing has a profile of about 0.375 inch or less.

4. The alarm system of claim 1, wherein said housing has a profile of about 0.25 inch or less.

5. The alarm system of claim 1, further comprising an adhesive layer for attaching a lower portion of said housing to said first window surface.

6. The alarm system of claim 1, wherein said speaker is configured to emit an audible alarm of at least 70 decibels.

7. The alarm system of claim 1, further comprising a switch configured to select between at least an active state of said alarm system and an inactive state of said alarm system.

8. The alarm system of claim 1, wherein the housing is further configured to substantially enclose a power supply of said alarm system.

* * * * *