

ORIGINAL
CLERK'S OFFICE
FEB 03 2004

**IN THE UNITED STATES DISTRICT COURT
FOR THE NORTHERN DISTRICT OF GEORGIA
ATLANTA DIVISION**

LUTHER Clerk
Deputy Clerk

SCIENTIFIC-ATLANTA, INC.)
a Georgia corporation,)
)
Plaintiff,)
)
v.)
)
SIRIUS SATELLITE RADIO, INC.)
a Delaware corporation,)
)
Defendant.)
_____)

Civil Action File No.: **BBM**
1:04-CV-0282

JURY TRIAL DEMANDED

COMPLAINT FOR PATENT INFRINGEMENT

The plaintiff, Scientific-Atlanta, Inc. ("S-A"), for its complaint against the defendant Sirius Satellite Radio, Inc. hereby demands a jury trial and alleges as follows:

NATURE OF ACTION

1. This is an action in which S-A seeks damages and injunctive relief under the patent laws of the United States, 35 U.S.C. § 1 *et seq.*, for infringement of each of U.S. Patent Nos. 5,239,540 and 6,055,244 (collectively the "patents-in-suit") resulting from the defendant's actions and conduct, as set forth herein.

FORMS RECEIVED
Consent to US Mag.
Pretrial Instructions
File VII NTC

THE PARTIES

2. S-A is a corporation organized under the laws of the State of Georgia, having its principal place of business at 5030 Sugarloaf Parkway, Lawrenceville, Georgia, 30044.

3. Sirius Satellite Radio, Inc. is a corporation organized under the laws of the State of Delaware, having its principal place of business at 1221 Avenue of the Americas, 36th Floor, New York, New York 10020 ("Sirius"). S-A is informed and believes that Sirius is doing business in the State of Georgia and in this Judicial District.

JURISDICTION AND VENUE

4. This Court has subject matter jurisdiction under 28 U.S.C. §§ 1331 and 1338(a).

5. Personal jurisdiction exists over defendant, on information and belief, by virtue of its actions and those of its agents which directly infringe or which induce or knowingly contribute in the infringement of S-A's patents-in-suit, within this state and/or their systematic and continuous contact with this state and/or the sale of infringing products in this state, pursuant to, *inter alia*, the Georgia long-arm statute, Official Code of Georgia Annotated § 9-10-91 (1995).

6. Venue is proper in this district in accordance with 28 U.S.C. §§ 1391 and 1400(b).

PLAINTIFF

7. S-A is engaged in the business of designing, manufacturing and selling advanced terrestrial and satellite network products and systems to deliver voice, video and data communications services. Over the years, S-A has developed and patented various novel inventions and improvements for use in the display of various kinds of information on its products. S-A has designed and manufactures an extensive line of equipment used in subscription television systems, including terrestrial and satellite transmission equipment and television set-top boxes that are used by subscription television subscribers to, among other things, unscramble cable transmissions and convert them into signals and data useable by the subscriber's television set ("S-A Equipment"). Among the features incorporated, enabled or implemented in the S-A Equipment is the ability to listen to digital music presented to the listener along with information describing the artist, song title and other descriptive information.

DEFENDANT

8. Sirius is engaged in the business of broadcasting digital-quality audio from orbiting satellites throughout the continental United States for a monthly

subscription fee. On information and belief, Sirius delivers 60 streams of 100% commercial-free music in virtually every genre, and over 40 streams of news, sports, weather, talk, comedy, public radio and children's programming.

9. On information and belief, Sirius has since its inception, used substantial resources to develop its satellite radio system. On information and belief, its satellite radio system consists of its FCC license, satellite system, national broadcast studio, terrestrial repeater network and satellite telemetry, tracking and control facilities.

10. On information and belief, Sirius had, as of December 15, 2003, approximately 200,000 subscribers for its digital satellite radio service. On information and belief, the Sirius digital satellite radio service includes the transmission of information relating to the artist, song title and other descriptive information along with the broadcast of a digital signal, including an audio signal to its subscribers. On information and belief, Sirius's primary source of revenue is the fees it collects from its subscribers.

11. On information and belief, Defendant, through agreements with leading consumer electronics manufacturers such as Kenwood, Panasonic, Audiovox, Clarion, and Jensen, provides radio devices capable of receiving its digital radio service, including transmitted descriptive information.

12. Defendant through such consumer electronics manufacturers sells digital satellite radios in the United States, including the Northern District of Georgia.

13. On information and belief, defendant has agreements to install its digital satellite radios capable of receiving its digital satellite radio service, including transmitted descriptive information, in Ford, Chrysler, BMW, Mercedes-Benz, Jaguar, Volvo, Mazda, Land Rover, Dodge, Jeep, MINI, Volkswagen, Audi, Nissan, and Infiniti vehicles, along with trucks from Freightliner and Sterling. Defendant's radios also are available in new Monaco Coach recreational vehicles, Thunderbird Formula powerboats, and on John Deere agricultural equipment.

14. Such automobile manufacturers include Defendant's digital satellite radio in automobiles they sell in the United States, including the Northern District of Georgia.

INFRINGEMENT PATENTS

15. United States Patent No. 5,239,540 entitled "Method and Apparatus for Transmitting, Receiving and Communicating Digital Data Signals With Corresponding Program Data Signals Which Describe the Digital Data Signals," issued August 24, 1993 to Scientific-Atlanta, Inc. as the assignee of the inventors, Luis A. Rovira and William E. Wall (the '540 Patent"). S-A is the owner of the

entire right, title and interest in and to the '540 Patent. A copy of the '540 Patent is attached as Exhibit A.

16. The '540 Patent generally relates to a novel system and method for transmitting, receiving and communicating program data signals with digital data signals.

17. United States Patent No. 6,055,244 entitled "Method and Apparatus for Communicating Different Types of Data in a Data Stream," issued April 25, 2000 to Scientific-Atlanta, Inc. as the assignee of the inventors, William E. Wall, Jay C. McMullan, Jr., and Luis A. Rovira (the '244 Patent"). S-A is the owner of the entire right, title and interest in and to the '244 Patent. A copy of the '244 Patent is attached as Exhibit B.

18. The '244 Patent generally relates to a novel method for constructing a data stream that combines program data, header information, and another type of data.

19. On information and belief, defendant has, without authority, infringed, contributed to the infringement of and/or actively induced the infringement of, the claims of the patents-in-suit within the United States and in this judicial district.

20. Defendant has had notice of the patents-in-suit and their infringement, contributory infringement, and/or inducement of infringement of the patents-in-suit (defendant's "infringing acts") have been knowing and willful.

21. S-A has been damaged by defendant's infringing acts, and will continue to be damaged if defendant is not enjoined by this Court from further infringing acts.

22. Defendant's infringing acts have been without express or implied license by S-A, and are in violation of S-A's rights.

COUNT 1

Infringement of U.S. Patent No. 5,239,540

23. S-A incorporates and re-alleges paragraphs 1-22 above.

24. Through the conduct alleged above, defendant has, and continues to, infringe, contribute to the infringement of, and/or induce the infringement of the '540 Patent by making, using, selling, and/or offering for sale products, including but not limited to, digital satellite radio equipment and services, without authorization of S-A.

25. S-A has not authorized defendant to make, use, sell and/or offer for sale products covered by the claims of the '540 Patent.

26. The defendant's infringement, contributory infringement, and/or induced infringement of the '540 Patent has been done willfully and with knowledge of the '540 Patent.

27. By reason of defendant's infringement, contributory infringement, and/or induced infringement of the '540 Patent, defendant has caused and continues to cause S-A to suffer damage and irreparable harm. On information and belief, defendant's infringement, contributory infringement, and/or induced infringement of the '540 Patent will continue unless enjoined by this Court.

28. S-A has no adequate remedy at law for defendant's infringement, contributory infringement, and/or induced infringement of the '540 Patent.

COUNT 2

Infringement of U.S. Patent No. 6,055,244

29. S-A incorporates and re-alleges paragraphs 1-22 above.

30. Through the conduct alleged above, defendant has, and continues to, infringe, contribute to the infringement of, and/or induce the infringement of the '244 Patent by making, using, selling, and/or offering for sale products, including but not limited to, digital satellite radio equipment and services, without authorization of S-A.

31. S-A has not authorized defendant to make, use, sell and/or offer for sale products covered by the claims of the '244 Patent.

32. The defendant's infringement, contributory infringement, and/or induced infringement of the '244 Patent has been done willfully and with knowledge of the '244 Patent.

33. By reason of defendant's infringement, contributory infringement, and/or induced infringement of the '244 Patent, defendant has caused and continues to cause S-A to suffer damage and irreparable harm. On information and belief, defendant's infringement, contributory infringement, and/or induced infringement of the '244 Patent will continue unless enjoined by this Court.

34. S-A has no adequate remedy at law for defendant's infringement, contributory infringement, and/or induced infringement of the '244 Patent.

DEMAND FOR A JURY TRIAL

35. S-A demands a jury trial, pursuant to Fed. R. Civ. P. 38(b), as to all issues which may be tried by a jury.

REQUEST FOR RELIEF

WHEREFORE, S-A prays that the Court:

A. Enter judgment that defendant has infringed, contributorily infringed or knowingly induced infringement of the patents-in-suit;

B. Preliminarily and permanently enjoin defendant from further acts of infringement of the patents-in-suit;

C. Enter judgment awarding S-A damages adequate to compensate for defendant's infringement of the patents-in-suit;

D. Enter judgment that defendant's infringement of the patents-in-suit has been knowing and willful;

E. Enter judgment increasing the damages for infringement of the patents-in-suit to three times the amount found by the jury or assessed by the Court against the defendant;

F. Enter judgment declaring this to be an exceptional case and awarding S-A its attorney fees pursuant to 35 U.S.C. §285; and

G. Enter judgment awarding S-A costs, prejudgment interest, and such further relief as the Court deems just and proper.

This 2nd day of February, 2004.

Respectfully submitted,

A handwritten signature in black ink, appearing to read "Patrick J. Flinn", is written over a horizontal line.

Patrick J. Flinn

Georgia Bar No. 254540

John D. Haynes

Georgia Bar No. 340599

One Atlantic Center
1201 West Peachtree Street
Atlanta, Georgia 30303-3424
Telephone: (404) 881-7000
Fax: (404) 881-7777

Attorneys for Plaintiff
SCIENTIFIC-ATLANTA, INC.



EXHIBIT ATTACHMENT

A

(To be scanned in place of tab)

United States Patent [19]
Rovira et al.

[11] **Patent Number:** 5,239,540
 [45] **Date of Patent:** Aug. 24, 1993

[54] **METHOD AND APPARATUS FOR TRANSMITTING, RECEIVING AND COMMUNICATING DIGITAL DATA SIGNALS WITH CORRESPONDING PROGRAM DATA SIGNALS WHICH DESCRIBE THE DIGITAL DATA SIGNALS**

[75] **Inventors:** Luis A. Rovira; William E. Wall, Jr., both of Atlanta, Ga.

[73] **Assignee:** Scientific-Atlanta, Inc., Norcross, Ga.

[21] **Appl. No.:** 618,744

[22] **Filed:** Nov. 27, 1990

[51] **Int. Cl.⁵** H04J 3/00

[52] **U.S. Cl.** 370/77; 370/73; 455/45; 455/66

[58] **Field of Search** 370/71, 73, 76, 77, 370/110.1, 110.4, 111, 69.1; 358/84, 86, 140, 141; 455/45, 66

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,696,297	10/1972	Otero	325/55
3,757,225	9/1973	Ulicki	325/308
3,936,595	2/1976	Yanagimachi et al.	178/5.6
4,052,719	10/1977	Hutt et al.	340/324
4,079,419	3/1978	Siegle et al.	358/193
4,203,130	5/1980	Doumit et al.	358/1
4,305,101	12/1981	Yarbrough et al.	360/69

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

52-48428	4/1977	Japan
68227195	9/1988	Japan
WO84/01873	5/1984	PCT Int'l Appl.
WO88/0454-		
07	6/1988	PCT Int'l Appl.
2166328A	4/1986	United Kingdom
2207314	1/1989	United Kingdom

OTHER PUBLICATIONS

National Technical Report, vol. 25, No. 4, (Aug. 1979).
 Article from Broadcasting, "The Return of Digital Radio on Cable", Jun. 25, 1990.

J. S. Lublin, Article from The Wall Street Journal, "Cable TV to See if Cable Radio Means Sweet Music for Revenue", Nov. 6, 1990.

E. Bryan Carne, "The Wired Household", IEEE Spectrum, Oct. 1979, 61-66.

G. A. McKenzie, "ORACLE—An Information Broadcasting Service Using Data Transmission in the Vertical Interval", Journal of the SMPTE, Jan. 1974, 6-10.

S. M. Edwardson and A. Gee, "CEEFAX: A Proposed New Broadcasting Service", Journal of the SMPTE, Jan. 1974, 14-19.

A. James, "ORACLE—Broadcasting The Written Word", Wireless World, Jul. 1973, xx-xx.

R. T. Russell, "Teletext Remote Control-2", Wireless World, May 1979, 83.

Primary Examiner—Douglas W. Oims

Assistant Examiner—Shick Hom


Attorney, Agent, or Firm—William A. Marvin;

Frederick W. Powers, III

[57] **ABSTRACT**

An apparatus and method is described for transmitting, receiving and communicating program data signals which are combined with digital data signals. Preferably, the present invention compresses 30 digital audio signals, multiplexes them with title, track, artist, record label, year, etc., program information, and transmits the combined signals via satellite to a receiving station. The receiving station demultiplexes the signals and sends them via a cable distribution system to a subscriber's digital music tuner. This tuner further demultiplexes and decodes the signals so that the digital audio signals may be converted to analog and output for listening, while the corresponding data signals are communicated to the subscriber. In an alternative preferred embodiment, the program data signals are transmitted to a remote control receiver where they are displayed. The system described in the present invention may be used for transmitting video, software or games with program data to subscribers.

22 Claims, 8 Drawing Sheets



5,239,540

Page 2

OTHER PUBLICATIONS

4,390,901	6/1983	Keiser	358/147	4,829,372	5/1989	McCalley et al.	358/86
4,488,179	12/1984	Kruger et al.	358/181	4,871,992	10/1989	Petersen	340/407
4,605,793	8/1986	Von Kohorn	358/335	4,894,714	1/1990	Christis	358/86
4,623,887	11/1986	Welles, II	340/825.57	4,905,094	2/1990	Pocock et al.	358/342
4,691,351	9/1987	Hayashi et al.	380/10	4,908,707	3/1990	Kinghorn	358/147
4,706,121	11/1987	Young	358/142	4,914,517	4/1990	Duffield	358/191.1
4,750,036	6/1988	Martinez	358/147	4,922,483	5/1990	Kobayashi	370/73
4,751,578	6/1988	Reiter et al.	358/183	4,922,537	5/1990	Frederiksen	381/31
4,764,981	8/1988	Miyahara et al.	455/603	4,937,821	6/1990	Boulton	370/69.1
4,788,675	11/1988	Jones et al.	370/69.1	4,959,720	9/1990	Duffield et al.	358/191.1
4,792,849	12/1988	McCalley et al.	358/86	5,014,125	5/1989	Pocock et al.	358/86
4,821,097	4/1989	Robbins	358/143	5,027,400	6/1991	Baji et al.	380/20
4,825,200	4/1989	Evans et al.	341/23	5,038,211	8/1991	Hallenbeck	358/142
4,825,209	4/1989	Sasaki et al.	340/825.72	5,063,610	11/1991	Alwadish	455/45
				5,086,298	2/1992	Katsu et al.	340/825.69
				5,119,503	6/1992	Mankovitz	455/45





FIG. 1






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

FIG. 8

<u>FIELD</u>	<u>BIT SIZE</u>	<u>DEFINITIONS</u>
<SI>	1	Start of TITLE Field
<TITLE>	24	TITLE Information
<DLE>	1	Start of TRACK Field
<TRACK>	24	TRACK Information
<DC1>	1	Start of ARTIST Field
<ARTIST>	24	ARTIST Information
<DC2>	1	Start of LP LABEL Field
<LP LABEL>	24	LP LABEL Information
<DC3>	1	Start of COMPOSER Field
<COMPOSER>	24	COMPOSER Information
<DC4>	1	Start of SONG ID Field
<SONG ID>	10	SONG ID Information
<COPY PROTECT>	1	Copy protect ('Y'= On, 'N'= Off)
<PLAYTIME>	4	(0000-9999) # of Seconds the Current Selection Will Play

5,239,540

1

**METHOD AND APPARATUS FOR
TRANSMITTING, RECEIVING AND
COMMUNICATING DIGITAL DATA SIGNALS
WITH CORRESPONDING PROGRAM DATA
SIGNALS WHICH DESCRIBE THE DIGITAL DATA
SIGNALS**

TECHNICAL FIELD

The present invention relates to the field of digital signal transmission and more particularly, to transmitting digital signals accompanied by program content data so that listeners/viewers may see a display of the program content data as they are listening/viewing the performance, without interrupting the performance.

BACKGROUND OF THE INVENTION

Presently, program content information, for example, song title, artist, record label, etc., is communicated to the customer/listener by announcers' disc jockeys (DJs). In the case of video programs transmitted by broadcast means, video text messages are presented between programs and during interruptions of programs. In the case of many premium services, it is undesirable to interrupt programs for presentation of program content information. It may also be undesirable to have any form of announcer or DJ between program or selection of music.

Those such announcers or interruptions of program may be undesirable in some services. Nevertheless, it is highly desirable to communicate program content information. Frustration of customers, and possible loss of revenue due to subscription cancellation can occur if a subscriber has no method of knowing the title, composer or artist of the particular selection of music. To the music industry, identification of recording label and identification number is critical to sale of the recordings. Currently, a subscriber viewing a premium video program must consult a separate listing, tune to a different channel, or wait till the end of the program for its identification.

Similarly, the cable television industry is currently introducing audio-only services. Program content information is printed in a separate listing. These cable "radio stations" may play a continuous succession of musical selections without commercial interruptions. These services may not use a "disc-jockey" to identify the musical or other selections. Instead, under the present invention, data channels will contain information about the music being played.

In one embodiment of the present invention, a display of this data has been envisioned that has been termed an "electronic DJ". This display could be built into the subscriber terminal itself, or it could be a separate display unit that would connect to a port on the rear panel of the terminal.

The problem with such displays is that, unless they are very large and therefore costly, they cannot be easily placed within reading distance of the listener. Long cables for the display would be difficult to route in a typical living room, and we need only look at the success of VCR wired remote controls to convince ourselves that such a tethered display would not be optimum.

Wireless remote controls have brought great convenience to the control of consumer products. Highly intelligent remote controls with liquid crystal displays are available. Programmable and universal "learning"

2

remote controls are available that assume the functions of multiple other controls. These remote controls receive information from each other, and display the functions available to the user.

It can be a frustrating experience to enjoy a piece of music on the radio, only to have the station fail to identify the piece. To lovers of music, having such information as music title, composer, artist and record label is vital. Without this information, the service will be reduced to the level of generic background music.

SUMMARY OF THE INVENTION

The problems and related problems of transmitting and providing a display of program content data are solved by the principles of the present invention. In furtherance of these principles, it is an object of the present invention to provide program information to subscribers without interrupting the program.

It is an object of the present invention to transmit and provide program information for digital audio transmitted to subscribers, where the program information is combined with the digital audio.

It is a further object of the present invention to provide program data to subscribers of video information.

It is another object of the present invention to provide program information to subscribers where the information is communicated through a remote control unit.

It is a further object of the present invention to provide a system where digital program information is combined with digital audio/video signals which are transmitted via satellite, coaxial cable, or other means to subscribers.

It is another object of the present invention to provide program data corresponding to audio/video signals to subscribers with disabilities.

In accordance with these and other objects, apparatus for encoding according to the present invention comprises: a plurality of means for producing digital signals; a plurality of means for producing a plurality of program data signals, each program data signal corresponding to one digital signal; and, at least one encoding means, coupled to the plurality of means for producing digital and program data signals, for encoding the plurality of program data signals with the plurality of digital signals to produce a plurality of combined digital and program data signals.

Additionally, under these and other objects, a method is disclosed for encoding program information into a digital data stream comprising the steps of: producing a plurality of digital signals; producing a plurality of program data signals, each program data signal corresponding to one digital signal; and encoding the plurality of program data signals with the plurality of digital signals to produce a plurality of combined digital and program data signals.

Conversely, under the above and other objects, an apparatus is disclosed for communicating program information corresponding to a track of digital data from a signal containing a plurality of digital and program information signals comprising: first receiving means for receiving an encoded signal containing a plurality of digital signals and a plurality of program data signals, each program data signal corresponding to one digital signal; at least one selecting means, coupled to the first receiving means, for selecting one digital signal and one corresponding program data signal from the received

5,239,540

3

signal; at least one decoding means, coupled to the selecting means, for decoding the selected one digital signal and the one corresponding program data signal so as to separate the corresponding program data signal from the selected one digital signal; transmitting means, 5 coupled to the decoding means, for transmitting the one corresponding program data signal; second receiving means, coupled to the transmitting means, for receiving the one corresponding program data signal; and, communicating means, coupled to the second receiving means, for communicating the one corresponding program data signal.

Similarly, a method under the above objects is disclosed for communicating program information corresponding to a track from signal containing a plurality of digital and program information signals comprising the steps of: receiving an encoded signal containing a plurality of digital signals and a plurality of program data signals, each program data signal corresponding to one digital signal; selecting one digital signal and one corresponding program data signal from the received encoded signal; decoding the selected one digital signal and the one corresponding program data signal so as to separate the corresponding program data signal from the selected one digital signal; transmitting the one corresponding program data signal to a communicator; receiving the transmitted one corresponding program data signal; and, communicating the received one corresponding program data signal via the communicator.

Finally, under the objects of the present invention, a handheld apparatus for communicating program information corresponding to digital data is disclosed comprising: receiving means for receiving a program data signal corresponding to a digital track; processing means, coupled to the receiving means, for processing the received program data signal; and, communicating means, coupled to the processing means, for communicating the processed program data signal.

The communicating means under the present invention could take the form of a standard remote control, i.e. a hand-held unit with a display of some sort. The display could be a liquid crystal or other suitable technology. A benefit of having the display in a remote unit under the present invention is that the cost of the display need not be included in the base unit. The display can be a value-added extra-cost feature. It can thus be seen as a means of increasing revenue, or of making the service more affordable to those not desiring the feature.

The communicating means under the present invention could also take the form of a table-mounted unit. It could use a larger display than might be possible on a hand-held remote. It could also use ac power instead of batteries and thus power a brighter and larger display more suitable for low light viewing. The control and display functions could be separated into two individual units.

The base subscriber terminal could automatically update the remote display/control unit whenever there has been a change in programming. This, however, may result in brief intervals during which the use of other remote controls might be disrupted. Instead, the communications may be structured such that for information to be sent from the base subscriber terminal, it must be polled from the remote unit. Memory could be used in either the base unit or the remote to store information on previous selections. This information could be recalled by the user on demand.

4

The communications link between the base subscriber terminal and the remote unit could use radio frequencies, infrared, visible light, acoustical transmission through air, or other wireless means. The concept could also be extended to carrying the information on the household power lines, telephone wires, coaxial cable, fiber-optic cable or means other than the direct connection of a cable to the base unit.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention may be appreciated from studying the following detailed description together with the drawings in which:

FIG. 1 is a blocked diagram of the overall system in the present invention;

FIG. 2 shows a detailed block diagram of the encoding and transmitter portion of the present invention;

FIG. 3 shows a block diagram of the encoding portion of the present invention;

FIG. 4 shows a block diagram of the receiving portion of the present invention;

FIG. 5 shows a block diagram of the digital music tuner;

FIG. 6 shows a block diagram of the application specific integrated circuit shown in FIG. 5;

FIG. 7 shows a block diagram for the remote communication device of the present invention; and,

FIG. 8 shows a diagram of a simplified frame format using the present invention.

DETAILED DESCRIPTION

Referring to FIG. 1, a block diagram of an overall system in the present invention is described. The present invention will be described with respect to transmitting audio signals with program data. However, those skilled in the art will recognize that the present invention may, instead of transmitting audio with corresponding program data, transmit any of the following, with corresponding program data: television, games, software, video, and other combinations of audio/video or software information.

Compact disc players 10-1 through 10-n provide a plurality of digital audio signals to the present invention. These CD players may be the so called "jukebox" type wherein up to sixty or more compact discs may be stored and accessible by the player.

The digital audio signals from CD players 10-1 through 10-n are input to encoders 20-1 through 20-n which will be described in greater detail with reference to FIG. 3. Controller and music database 30-1 through 30-k controls the output of CD players 10-1 through 10-n and any respective selection of compact discs within these players and also provides a database containing program data with a one to one correspondence to the tracks contained on the compact discs. This program data includes title, track, artist, publisher, composer, song identification and play time information blocks for each song contained on a compact disc. These program data signals could also include other information relevant to describing the particular track contained on a compact disc, as those skilled in the art can appreciate. For example, if the information were historical audio data, information on the time and place such data was first conceived or transmitted may also be contained within this program information. Additionally, if the digital signals transmitted contained video information, the corresponding program data signals would relate to the video program being transmitted,

5,239,540

5

for example, the title, actors, director, publisher, year, or other relevant information.

The plurality of digital audio signals inputted by the CD players 10-1 through 10-*n* are combined in encoders 20-1 through 20-*n* with the program data signals inputted by controller and music databases 30-1 through 30-*k*. The combined signals from encoders 20-1 through 20-*n* are then inputted into multiplexer 40 which combines the signals into a serial digital data stream.

Additional signals may be combined with the digital audio and program information signals. Subscriber control 45 contains information on various subscribers who may receive the digital audio data produced by the present invention. This subscriber information stored in subscriber control 45 is multiplexed with the digital audio and program data signals in multiplexer 40, producing a serial digital data stream containing digital audio, program information, and national subscriber information.

The serial digital audio/program data stream from multiplexer 40 is input into the digital satellite transmitter 50 and broadcast, via satellite, to digital satellite receiver 60. However, those skilled in the art will realize that any delivery system, not just satellite transmission, may be used, such as cable television (CATV), microwave distribution (MDS or MMDS), telephone systems, terrestrial broadcasts, and other coaxial or optical cable lines.

The previously described transmitter section will be more fully discussed with reference to FIG. 2, while the following receiver section will be more fully described with reference to FIG. 4. Digital satellite receiver 60 transfers the digital data to headend processing 70 which in turn converts and sends the information to digital cable modulators 75. The digital audio data is then added with signals from other cable modulators in summing circuit 80 and sent over a cable distribution system.

The cable distribution system includes line amplifiers 90 for boosting the signal and compensating for any line loss. System tap 85 directs the combined signal to a subscriber's premises and into digital music tuner 100. Digital music tuner 100, more fully described with respect to FIG. 5, selects the channel containing the digital audio and program data signals. Additionally, digital music tuner 100 separates the digital audio signal from the program information signal. The digital audio signal is converted to analog, amplified and output on a subscriber's audio electronics, while the program information signal is processed and sent to a local display or remote using information display 200. The demultiplexing and decoding of the signals is discussed more fully with reference to FIG. 6. These displays then communicate to the subscriber the particular program information corresponding to an audio track currently being listened to by the subscriber. The remote music information display is more fully described with respect to FIG. 7.

TRANSMITTING SECTION

Referring to FIG. 2, a block diagram of the studio and transmitter, or uplink, section of the present invention is described. Compact disc players 10-1 through 10-*n* are driven by microcomputers 15-1 through 15-*n*. Microcomputers 15-1 through 15-*n* could be IBM Model AT microcomputers. These microcomputers are in turn controlled by the studio sequencing master controllers 30-1 through 30-*k*. These master controllers

6

30-1 through 30-*k* include a database containing the program information described above. These master controllers are preferably IBM Model PS/2 microcomputers or other computers containing a 386 type microprocessors.

The digital audio output from CD players 10-1 through 10-*n* is input into encoders 20-1 through 20-*n* along with program information supplied by master controllers 30-1 through 30-*k*. Encoders 20-1 through 20-*n* combined the digital audio signals with the program data signals and output the combined signal to system data multiplexers 40-1 and 40-2. Preferably, the outputs of 30 encoders 20-1 through 20-30 are input into multiplexers 40-1 and 40-2 where the signals are time division multiplexed. Multiplexers 40-1 and 40-2 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocquenghen (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art.

Billing system 47 includes subscriber information of the present invention and national control information and may be comprised of an IBM Model PS/2 microcomputer. The subscriber information and other billing system data would be contained within a large database within billing system 47. Typical billing system data could include, for example, identity, location, etc. for subscribers and their current billing status. Billing system information from billing system 47 is input into the system manager digital audio controller 45. System manager 45 is preferably comprised of a series 8500 System Manager manufactured by Scientific Atlanta or a similar product. System manager digital audio controller 45 controls master controllers 30-1 through 30-*k*. Additionally, the system manager 45 may also input subscriber data from the subscriber database within billing system 47 into multiplexers 40-1 and 40-2.

The subscriber information may be combined with the digital audio and program signals through multiplexers 40-1 and 40-2. Multiplexers 40-1 and 40-2 provide the master clock to all the decoders 20-1 through 20-*n* and to satellite exciters 53-1 and 53-2. The output of multiplexers 40-1 and 40-2 is a 34 megabits per second (Mbps) data stream comprising the preferred 30 channels outputted by the 30 encoders 20-1 through 20-30.

Relay circuit 43 provides fault protection so as to switch the system to multiplexers 40-2 and 40-2 from multiplexer 40-1 in event of a fault. The outputs from multiplexers 40-1 and 40-2 are two coaxial cables, for plus and minus balanced connections. These balanced coaxial cables are used from the output of multiplexers 40-1 and 40-2 through satellite transmitting and receiving electronics. The combined signal from multiplexer 40-1 passes through relay 43 into fiber-optic transmitter 49. Fiber-optic transmitter 49 transports the signal from the studio to the transmitter site and into fiber-optic receiver 51. The output of the fiber-optic receiver drives an offset quadrature phase shift keying (OQPSK) satellite modulator 50. The signals is then up converted, amplified and transmitted to the satellite, as more fully described below.

The signals are received from fiber-optic transmitter 49 into fiber-optic receiver 51 in transmitter 50. From fiber-optic receiver 51 the signals pass through fault protection relay 52-1 into OQPSK Exciter 53-1. The digital signals from OQPSK exciter 53-1 enter splitter 57-1 and through fault protection relay 52-2. Thereafter, the signals pass through an upconverter 58-1. From upconverter 58-1 the signals pass through switch 56-1

5,239,540

7

into high powered amplifier 59-1 and once again through switch circuit 56-2 and then transmitted. The transmitting is preferably performed via a satellite. The transmission may also occur via coaxial cables or fiber-optic cables.

Redundancy control logic 55 controls transmitter 50, so in the event of a fault, redundant circuitry is activated. Specifically, redundancy control logic 55 controls relays 52-1 and 52-2 and switches 56-1 and 56-2 so as to switch to redundant exciter 53-2 and splitter 57-2, redundant up converter 58-2 and high powered amplifier 59-2.

Referring to FIG. 3, a more detailed block diagram of an encoder 20-1 is described. Outputs from CD players 10 are input to multiplexer 31. Preferably, the outputs from 16 CD players 10-1 through 10-16 are input into multiplexer 31 where their signals are combined and output as two channels to rate synchronizers 33-1 and 33-2. The rate synchronized signals are then input into mixer and signal compressor 35. Mixer and signal compressor 35 preferably uses the data compression format described in U.S. Pat. No. 4,922,537, incorporated herein by reference. Mixer and data compressor 35 is controlled by input signals from master controller 30-1 which also inputs the program data signals corresponding to the digital audio signals. The digital audio signals are compressed, program data signals are mixed therewith, and then the mixed signal is input into frame sync detector and output formatter 37. Circuit 37 may also include circuitry to encrypt the mixed and compressed signals using, for example, the Data Encryption Standard (DES) or using other similar encryption techniques known in the art. Circuit 37 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocquenghen (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art. Hamming encoding is disclosed in *Electronic Engineers Reference Book*, edited by F. Mazda, page 32/10, incorporated herein by reference.

The audio data is clocked into and out of circuits 33-1, 33-2, 35 and 37 at a rate 44.1 kilosamples per second. The mixed compressed and encrypted signals are output of circuit 37 at 1.12896 Mbps in Applicant's preferred embodiment.

RECEIVING SECTION

Referring to FIG. 4, the mixed, compressed and encrypted signal is received in the C-band via satellite receive antenna and amplified and block converted in a low-noise block converter 63, along with other satellite distributed signals. The signal is output in the L-band at 950 to 1450 megahertz and input into splitter 65 where the audio signal is input into OQPSK receiver 67. Receiver 67 demodulates the OQPSK information and provides one 34 Mbps signal stream containing the preferred 30 satellite distributed channels. The 34 Mbps signal is output of receiver 67 at 34 megahertz clock rate into demultiplexer 70. Preferably, demultiplexer 70 is a 1:6 demultiplexer which separates the single data stream into six channels containing 5.6 Mbps digital audio and program data each. These six channels contain five stations each.

The signals are clocked at 11 megahertz to modulators 75-1 through 75-6. Each modulator 75-1 through 75-6 is a nine state quadrature partial response (9-QPR) modulator capable of handling five stations and each occupying a 3 megahertz bandwidth. Those skilled in

8

the art will appreciate that one may also use phase shift key modulation or other modulation methods known in the art with fewer or greater numbers of states.

The modulated signals from modulators 75-1 through 75-6 are combined in radio frequency combiner 80 along with other modulated signals from other cable modulators 77. Modulators 75-1 through 75-6 digitally filter the data, quadrature partial response (QPR) modulate and convert the data to the selected output frequency for combining with other modulated channels 77 in the present cable television system. Each block of five stereo pairs occupies 3 megahertz of band width and can be carried in half of one 6 megahertz video channel of the present cable television system. Since the present system uses a common 6 megahertz video channel, no modifications of current CATV distribution system equipment is required.

The combined signals from RF combiner 80 are distributed over a coaxial cable or fiber-optic distribution system into a subscriber's home. Directional coupler 85 directs most of the signal to video set top terminal 87. A sample of the signal is sent from directional coupler 85, at a loss of 10 decibels to digital music tuner 100. Tuner 100 is controlled by either a plain remote 201 or a music information display remote 200. Additionally, tuner 100 outputs left and right analog audio signals, and may also output an optional digital signal output.

Referring to FIG. 5, a block diagram of digital music tuner 100 is shown. The digital audio and program data signal is inputted from directional coupler 85 into set top terminal tuner 110. This tuner preferably includes phase locked loop circuitry. The signal from tuner 110 is amplified by amplifier 115 and filtered by saw filter 120 before being demodulated by demodulator 125. Tuner 110 converts the selected radio frequency channel to a demodulation intermediate frequency. The output of demodulator 125 is QPR demodulated to produce a 5.6 Mbps data stream containing five stereo pair of digital audio data to applications specific integrated circuit (ASIC) 140. Demodulator 125 also provides an automatic gain control signal 130 to tuner 110 to maintain constant signal level. Additionally, demodulator 125 provides data to clock recovery phase locked loop (PLL) 135. Data clock PLL 135 contains a 33.8 megahertz crystal 137 from timing purposes.

This timing signal is sent to ASIC 140, which will be discussed in greater detail with reference to FIG. 6. ASIC 140 provides a digital audio output to interface 170. Interface 170 uses the Sony-Philips digital interface format (SPDIF). Similarly, the digital audio signals are input from ASIC 140 to digital to audio converter 160. From digital to audio converter 160, the analog left and right audio signals are filtered through filters 165-1 and 165-2 and input into bypass 170. Bypass 170 allows additional audio components (e.g., a CD player or tape deck) to be switchably connected with the digital music tuner 100.

Microprocessor 150 controls phase locked loop of tuner 110, ASIC 140, digital to analog converter 160 and bypass 170. The program data signal from ASIC 140 is sent to microprocessor 150 where it is stored in internal memory of the microprocessor, and may be displayed on front panel interface 180 or transmitted through remote control transmitter 190. Remote control receiver 195 may select particular program data information or audio channels through microprocessor 150.

5,239,540

9

Power supply 175 would supply both positive five volts digital and analog power, and a negative five volt supply to the system. Positive 12 volt and positive 30 volt power supply signals are also provided from power supply 175. Additionally, tuner 100 would preferably have input means, e.g., push buttons or toggle switches, on the exterior of its housing (not shown). These input means would allow selection of channels, stations, display of program data, and display of particular information blocks contained in the program data signal. Additional selections or inputs may be provided as those skilled in the art recognize.

Referring to FIG. 6, a more detailed block diagram of ASIC 140 is provided. The signal from demodulator 125 is input into demodulator support circuit 141 which comprises logic circuitry (e.g., flip-flops) required in demodulation of the signal. The signal from demodulator support circuit 141 is then input into demultiplexer 143 which separates the 5.6 Mbps data stream to select one of five stereo pairs of digital audio signals. This signal is then sent to decrypting circuit 145. The decrypted signal is then separated in signal separator 148 where program data is sent to microprocessor in/out circuit 149 while audio data is sent and decoded in circuit 147. Decoder 147 uses the data decompression technique described in U.S. Pat. No. 4,922,537, incorporated herein by reference.

Microprocessor in/out, address and control circuit 149 interfaces with microprocessor 150. All circuits within ASIC 140 are driven by clock 146. Memory 144 stores bits of data to support the demultiplexing, decrypting and decoding functions occurring in circuits 143, 145 and 147 respectively. The memory may be of a nonvolatile type such as an EPROM or similar ROM memory or may be a volatile type RAM memory supported by battery 171, preferably a lithium type battery. Such a battery 175 would prevent loss of data stored in memory 144.

REMOTE DISPLAY UNIT

Referring to FIG. 7, a block diagram of the remote music information display unit 200 is shown. Program data signals are received by receiver 201 from remote control transmitter 190. Preferably, infrared transmitter and receivers 190, 195, 201 and 205 are used. However, radio frequency, ultrasonic, wire, fiber-optic cables or other means could be used as those skilled in the art can appreciate. The received signal is then input into processor 203 which processes and sends the program data signal to display 209 for communicating program data corresponding to currently playing audio track to a subscriber. Display 209 may be a liquid crystal display, a light emitting diode, a braille reader, a voice synthesizer or a cathode-ray tube or any other communicating device as may be appreciated by those skilled in the art. Audible or tactile communicating means would allow communication of the program data signals to subscribers with disabilities, as would the use of a remote unit.

Input means shown as keyboard 207 may receive program data selection commands or audio track commands from a subscriber which are sent to processor 203. Keyboard 207 may also include means to allow a subscriber to control volume, power, channel selection, station selection, display, or other suitable subscriber commands that those skilled in the art appreciate. Processor 203 then converts and transmits the subscriber command signal to transmitter 205 which is received by remote control receiver 195. The received signal from

10

receiver 195 is input into microprocessor 150 where appropriate signals are sent therefrom to ASIC 140 and tuner 110 so as to bring about the subscriber's desired audio track, audio channel or program information.

Repeaters could be placed throughout a dwelling to extend the range of the display/control unit. Additionally, processor 203 could contain memory for storing various information, particularly program information.

In an alternative embodiment, the remote display unit may display only a code number representing the program data signals, whereby a subscriber may reference the number in printed material for a full description of the currently playing audio track. The printed material could be a publication which would rotate monthly or weekly as the programs on respective stations change. Such a system would allow for a smaller display on the remote unit, and thus be less costly to a subscriber. Such a printed publication would also allow a subscriber to determine which programs were playing on the various channels.

Additionally, the remote display unit or tuner 100 could display, upon a subscriber's request, program data corresponding to data being transmitted on channels not currently being listened to/viewed by the subscriber. In this way, a subscriber may scan what is being broadcast on alternate channels while listening to a currently playing channel.

DATA FORMAT

The preferred thirty stereo audio stations are multiplexed as follows. Groups of five stations are formatted into a frame of data. Six such frames are interleaved bit by bit for transmission over the satellite. Each such frame containing five stations has a header. This header is used by the headend demultiplexer 70 to deinterleave the satellite received data into six frames of five stations each. The header is also used in the ASIC 140 to synchronize on the frame. A second header contains subscriber control transaction data. This second header would preferably include channel and subscriber transaction data as previously described with respective billing system 47. The headers include additional bits for error detection.

Following the headers, compressed audio data with its associated program data is sent. Audio data for each station includes a seven bit "k factor" and a three bit "exponent" for each block of nine samples as described in previously referenced U.S. Pat. No. 4,922,573. Five such k factor and exponent blocks for each station are included in each frame.

The audio and program data for the five stations in the frame are interleaved bit by bit. That is, the first bit is sent for station No. 1, followed by the first bit for station No. 2 and so on until the first bit of each station has been sent. Then the second bit of each station is sent and so on. After the last audio data bits in each block of nine samples have been sent, the program data bits are sent in the same manner. Thus, the program data for each station is multiplexed in the frame with its associated station so that when the frame is demultiplexed or rearranged, the program information for that station is kept with its station. The advantage of multiplexing the program information with the audio data is that one may easily process the combined signal without fear of scrambling channels of audio data with their respective program information. Error correction and detection bits are also sent with the audio data and the program data.

5,239,540

9

Power supply 175 would supply both positive five volts digital and analog power, and a negative five volt supply to the system. Positive 12 volt and positive 30 volt power supply signals are also provided from power supply 175. Additionally, tuner 100 would preferably have input means, e.g., push buttons or toggle switches, on the exterior of its housing (not shown). These input means would allow selection of channels, stations, display of program data, and display of particular information blocks contained in the program data signal. Additional selections or inputs may be provided as those skilled in the art recognize.

Referring to FIG. 6, a more detailed block diagram of ASIC 140 is provided. The signal from demodulator 125 is input into demodulator support circuit 141 which comprises logic circuitry (e.g., flip-flops) required in demodulation of the signal. The signal from demodulator support circuit 141 is then input into demultiplexer 143 which separates the 5.6 Mbps data stream to select one of five stereo pairs of digital audio signals. This signal is then sent to decrypting circuit 145. The decrypted signal is then separated in signal separator 148 where program data is sent to microprocessor in/out circuit 149 while audio data is sent and decoded in circuit 147. Decoder 147 uses the data decompression technique described in U.S. Pat. No. 4,922,537, incorporated herein by reference.

Microprocessor in/out, address and control circuit 149 interfaces with microprocessor 150. All circuits within ASIC 140 are driven by clock 146. Memory 144 stores bits of data to support the demultiplexing, decrypting and decoding functions occurring in circuits 143, 145 and 147 respectively. The memory may be of a nonvolatile type such as an EPROM or similar ROM memory or may be a volatile type RAM memory supported by battery 171, preferably a lithium type battery. Such a battery 175 would prevent loss of data stored in memory 144.

REMOTE DISPLAY UNIT

Referring to FIG. 7, a block diagram of the remote music information display unit 200 is shown. Program data signals are received by receiver 201 from remote control transmitter 190. Preferably, infrared transmitter and receivers 190, 195, 201 and 205 are used. However, radio frequency, ultrasonic, wire, fiber-optic cables or other means could be used as those skilled in the art can appreciate. The received signal is then input into processor 203 which processes and sends the program data signal to display 209 for communicating program data corresponding to currently playing audio track to a subscriber. Display 209 may be a liquid crystal display, a light emitting diode, a braille reader, a voice synthesizer or a cathode-ray tube or any other communicating device as may be appreciated by those skilled in the art. Audible or tactile communicating means would allow communication of the program data signals to subscribers with disabilities, as would the use of a remote unit.

Input means shown as keyboard 207 may receive program data selection commands or audio track commands from a subscriber which are sent to processor 203. Keyboard 207 may also include means to allow a subscriber to control volume, power, channel selection, station selection, display, or other suitable subscriber commands that those skilled in the art appreciate. Processor 203 then converts and transmits the subscriber command signal to transmitter 205 which is received by remote control receiver 195. The received signal from

10

receiver 195 is input into microprocessor 150 where appropriate signals are sent therefrom to ASIC 140 and tuner 110 so as to bring about the subscriber's desired audio track, audio channel or program information.

Repeaters could be placed throughout a dwelling to extend the range of the display/control unit. Additionally, processor 203 could contain memory for storing various information, particularly program information.

In an alternative embodiment, the remote display unit may display only a code number representing the program data signals, whereby a subscriber may reference the number in printed material for a full description of the currently playing audio track. The printed material could be a publication which would rotate monthly or weekly as the programs on respective stations change. Such a system would allow for a smaller display on the remote unit, and thus be less costly to a subscriber. Such a printed publication would also allow a subscriber to determine which programs were playing on the various channels.

Additionally, the remote display unit or tuner 100 could display, upon a subscriber's request, program data corresponding to data being transmitted on channels not currently being listened to/viewed by the subscriber. In this way, a subscriber may scan what is being broadcast on alternate channels while listening to a currently playing channel.

DATA FORMAT

The preferred thirty stereo audio stations are multiplexed as follows. Groups of five stations are formatted into a frame of data. Six such frames are interleaved bit by bit for transmission over the satellite. Each such frame containing five stations has a header. This header is used by the headend demultiplexer 70 to deinterleave the satellite received data into six frames of five stations each. The header is also used in the ASIC 140 to synchronize on the frame. A second header contains subscriber control transaction data. This second header would preferably include channel and subscriber transaction data as previously described with respective billing system 47. The headers include additional bits for error detection.

Following the headers, compressed audio data with its associated program data is sent. Audio data for each station includes a seven bit "k factor" and a three bit "exponent" for each block of nine samples as described in previously referenced U.S. Pat. No. 4,922,573. Five such k factor and exponent blocks for each station are included in each frame.

The audio and program data for the five stations in the frame are interleaved bit by bit. That is, the first bit is sent for station No. 1, followed by the first bit for station No. 2 and so on until the first bit of each station has been sent. Then the second bit of each station is sent and so on. After the last audio data bits in each block of nine samples have been sent, the program data bits are sent in the same manner. Thus, the program data for each station is multiplexed in the frame with its associated station so that when the frame is demultiplexed or rearranged, the program information for that station is kept with its station. The advantage of multiplexing the program information with the audio data is that one may easily process the combined signal without fear of scrambling channels of audio data with their respective program information. Error correction and detection bits are also sent with the audio data and the program data.

5,239,540

11

Two program data bits are sent in the same block together with every nine compressed samples (100 bits) of audio data. This effectively provides a data channel of about 9800 baud used to transmit program data information. The information is sent in ASCII representation, but could easily be sent in other formats such as EBCDIC as would be apparent to those skilled in the art. FIG. 8 shows the program information as preferably sent and the size of each field in the present embodiment. Other information can be sent, such as music classification for selection of station by music type, special event announcements, or other such information, known by those skilled in the art.

We claim:

1. A method of generating a digital data stream including program data information and program selection information for transmission, comprising the steps of:

- producing a plurality of digital program data signals, each of which corresponds to the contents of a program selection;
 - producing a plurality of digital program selection signals, each of which corresponds to one of said program data signals and describes the attributes of the associated program selection;
 - encoding the plurality of digital program data signals with the plurality of digital program selection signals into a plurality of digital combined signals, each of said combined digital signals being arranged in blocks of a predetermined number of bits of a program data signal and a predetermined number of bits of an associated program selection signal, whereby each program selection signal remains associated with its corresponding program data signal during transmissions therewith; and
 - multiplexing the plurality of digital combined signals into the data stream.
2. The method of claim 1 wherein the transmission occurs via a satellite.
3. The method of claim 1 wherein the transmission occurs via coaxial cable.
4. The method of claim 1 wherein the multiplexing is time division multiplexing.
5. The method of claim 1 further comprising the step of compressing the plurality of digital combined signals to produce a plurality of compressed digital combined signals.
6. The method of claim 1 further comprising the step of encrypting the plurality of digital combined signals.
7. The method of claim 1 further comprising the step wherein subscriber data signals are multiplexed with the digital combined signals.
8. The method of claim 1 wherein the digital program data signals are digital audio signals.
9. The method of claim 8 wherein the program selection signals include at least one of a title, a track, an

12

artist, a publisher, a composer, a song identification, and a play time information block.

10. The method of claim 1 wherein the digital program data signals are digital video signals.

11. The method of claim 1 wherein the digital program data signals are software.

12. An apparatus for generating a digital data stream including program data information and program selection information for transmission by a transmission means, comprising:

- means for producing a plurality of digital program data signals, each of which corresponds to the contents of a program selection;
- means for producing a plurality of digital program selection signals, each of which corresponds to one of said program data signals and describes the attributes of the associated program selection;
- means for encoding the plurality of digital program data signals with the plurality of digital program selection signals into a plurality of combined digital signals, each of said combined digital signals being arranged in blocks of a predetermined number of bits of a program data signal and a predetermined number of bits of an associated program selection signal, whereby each program selection signal remains associated with its corresponding program data signal during transmissions therewith; and
- means for multiplexing the plurality of digital combined signals into the data stream.

13. An apparatus according to claim 12 wherein the transmission means comprises a satellite.

14. The apparatus according to claim 12 wherein the transmission means comprises coaxial cable.

15. The apparatus according to claim 12 wherein the multiplexing means uses time division multiplexing.

16. The apparatus according to claim 12 further comprising the step wherein subscriber data signals are multiplexed with the digital combined signals.

17. The apparatus according to claim 12 further comprising at least one compression means, coupled to the encoding means, for compressing the digital combined signals to produce a plurality of compressed digital combined signals.

18. The apparatus according to claim 12 further comprising at least one encrypting means, coupled to the encoding means, for encrypting the plurality of digital combined signals.

19. The apparatus according to claim 12 wherein the digital program data signals are digital audio signals.

20. The apparatus according to claim 12 wherein the program selection signals include at least one of a title, a track, an artist, a publisher, a composer, a song identification, and a play time information block.

21. The apparatus according to claim 12 wherein the digital program data signals are digital video signals.

22. The apparatus according to claim 12 wherein the digital program data signals are digital software signals.

* * * * *

60

65



EXHIBIT / ATTACHMENT

 B

(To be scanned in place of tab)

United States Patent [19]
Wall, Jr. et al.

[11] **Patent Number:** **6,055,244**
 [45] **Date of Patent:** **Apr. 25, 2000**

[54] **METHOD AND APPARATUS FOR COMMUNICATING DIFFERENT TYPES OF DATA IN A DATA STREAM**

WO88/045407 6/1988 WIPO H04N 7/087

OTHER PUBLICATIONS

Dietrich Schwarze, "Digital Sound Broadcasting and its Significance for the Listener", pp. 521-530 and the English translation, pp. 1-10, Nov. 28, 1989.
 P. Treyll, "Digital Sound Service For Direct Broadcasting Satellites", pp. III-114, undated.
 National Technical Report, vol. 25, No. 4 (Aug. 1979).
 Article from Broadcasting, "The Return Of Digital Radio On Cable", Jun. 25, 1990.
 J.S. Lublin, Article from the Wall Street Journal, "Cable TV to See If Cable Radio Means Sweet Music for Revenue", Nov. 6, 1990.
 R.T. Russell, "Teletext Remote Control-2", Wireless World, May 1979, p. 83.
 E. Bryan Carne, "The Wired Household", IEEE Spectrum, Oct. 1979, 61-66.

(List continued on next page.)

Primary Examiner—Douglas W. Olms
Assistant Examiner—Shick Hom
Attorney, Agent, or Firm—Kenneth M. Massaroni; Hubert J. Barnhardt, III; Kelly A. Gardner

[75] **Inventors:** **William Edgar Wall, Jr.**, Atlanta; **Jay Cauthern McMullan, Jr.**, Doraville; **Luis Agustin Rovira**, Atlanta, all of Ga.

[73] **Assignee:** **Scientific-Atlanta, Inc.**, Norcross, Ga.

[21] **Appl. No.:** **08/449,844**

[22] **Filed:** **May 24, 1995**

Related U.S. Application Data

[63] Continuation of application No. 08/171,453, Dec. 22, 1993, abandoned, which is a continuation of application No. 08/056,560, May 3, 1993, Pat. No. 5,406,558, which is a division of application No. 07/618,744, Nov. 27, 1990, Pat. No. 5,239,540.

[51] **Int. Cl.⁷** **H04H 1/08**

[52] **U.S. Cl.** **370/487; 370/326; 370/345; 370/498; 455/154.1; 455/158.4; 455/186.1**

[58] **Field of Search** **370/71, 73, 77, 370/94.1, 99, 110.1, 485, 486, 498, 476, 522, 326, 345, 487, 349, 474; 358/342, 332, 335; 380/10, 19, 20; 455/45, 46, 66, 158.4, 158.5, 186.1, 186.2, 154.1**

[57] **ABSTRACT**

An apparatus and method is described for transmitting, receiving and communicating program data signals which are combined with digital data signals. Preferably, the present invention compresses 30 digital audio signals, multiplexes them with title, track, artist, record label, year, etc., program information, and transmits the combined signals via satellite to a receiving station. The receiving station demultiplexes the signals and sends them via a cable distribution system to a subscriber's digital music tuner. This tuner further demultiplexes and decodes the signals so that the digital audio signals may be converted to analog and output for listening, while the corresponding data signals are communicated to the subscriber. In an alternative preferred embodiment, the program data signals are transmitted to a remote control receiver where they are displayed. The system described in the present invention may be used for transmitting video, software or games with program data to subscribers.

[56] **References Cited**

U.S. PATENT DOCUMENTS

3,696,297 10/1972 Otero 325/55
 3,743,767 7/1973 Bitzer et al. 178/5.6
 3,757,225 9/1973 Ulicki 325/308

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

3126466 A1 9/1983 Germany H04H 5/00
 52-48428 4/1977 Japan H04N 5/00
 68-227195 9/1988 Japan H04Q 9/00
 2166328 4/1986 United Kingdom H04H 1/02
 2207314 1/1989 United Kingdom H04N 7/00
 WO84/01873 5/1984 WIPO H04H 7/10

3 Claims, 9 Drawing Sheets

<u>FIELD</u>	<u>SIZE</u>	<u>DEFINITIONS</u>
<SI>	1	Start of TITLE Field
<TITLE>	24	TITLE Information
<DLE>	1	Start of TRACK Field
<TRACK>	24	TRACK Information
<DC1>	1	Start of ARTIST Field
<ARTIST>	24	ARTIST Information
<DC2>	1	Start of LP LABEL Field
<LP LABEL>	24	LP LABEL Information
<DC3>	1	Start of COMPOSER Field
<COMPOSER>	24	COMPOSER Information
<DC4>	1	Start of SONG ID Field
<SONG ID>	10	SONG ID Information
<COPY PROTECT>	1	Copy protect ('Y'= On, 'N'= Off)
<PLAYTIME>	4	(0000-9999) # of Seconds the Current Selection Will Play

6,055,244

Page 2

U.S. PATENT DOCUMENTS

3,936,595	2/1976	Yangimachi et al.	178/5.6	4,922,483	5/1990	Kobayashi	370/73
4,052,719	10/1977	Hutt et al.	340/324	4,922,537	5/1990	Fredericksen	375/122
4,079,419	3/1978	Siegle et al.	358/193	4,937,807	6/1990	Weitz et al.	369/85
4,203,130	5/1980	Domit et al.	358/1	4,937,821	6/1990	Boulton	370/69.1
4,305,101	12/1981	Yarbrough et al.	360/69	4,953,208	8/1990	Ideno	380/15
4,323,922	4/1982	den Toonder et al.	358/117	4,959,720	9/1990	Duffield et al.	358/191.1
4,390,901	6/1983	Keiser	358/147	5,014,125	5/1991	Pocock et al.	358/86
4,390,986	6/1983	Moses	370/99	5,027,400	6/1991	Baji et al.	380/20
4,488,179	12/1984	Kruger et al.	358/181	5,036,537	7/1991	Jeffers et al.	380/20
4,605,793	8/1986	Von Kohorn	358/335	5,038,211	8/1991	Hallenbeck	358/142
4,613,901	9/1986	Gilhousen et al.	380/21	5,038,402	8/1991	Robbins	455/3
4,623,887	11/1986	Welles, II	340/825.57	5,063,610	11/1991	Alwadish	455/45
4,682,360	7/1987	Frederiksen	380/10	5,086,298	2/1992	Katsu et al.	340/825.69
4,684,981	8/1987	Toyoshima et al.	358/86	5,091,936	2/1992	Katznelson et al.	380/19
4,691,351	9/1987	Hayashi et al.	380/10	5,119,503	6/1992	Mankovitz	455/45
4,706,121	11/1987	Young	358/142	5,119,507	6/1992	Mankovitz	455/154.1
4,710,921	12/1987	Ishidoh et al.	370/110.1	5,134,719	7/1992	Mankovitz	455/154.1
4,712,239	12/1987	Frezza et al.	380/20	5,173,900	12/1992	Miller et al.	370/94.1
4,739,510	4/1988	Jeffers et al.	380/19	5,191,410	3/1993	McCalley et al.	358/86
4,750,036	6/1988	Martinez	358/147	5,195,092	3/1993	Wilson et al.	370/94.2
4,750,167	6/1988	Meyer	370/77	5,214,792	5/1993	Alwadish	455/45
4,751,578	6/1988	Reiter et al.	358/183	5,239,540	8/1993	Rovira et al.	370/77
4,764,981	8/1988	Miyahara et al.	455/603	5,287,351	2/1994	Wall, Jr.	370/77
4,788,675	11/1988	Jones et al.	370/69.1	5,293,633	3/1994	Robbins	455/3.1
4,792,849	12/1988	McCalley et al.	358/86	5,319,707	6/1994	Wasilewski et al.	380/10
4,821,097	4/1989	Robbins	358/143	5,406,558	4/1995	Rovira et al.	370/77
4,821,260	4/1989	Klank et al.	370/77	5,446,739	8/1995	Nakano et al.	370/95.3
4,825,200	4/1989	Evans et al.	341/23				
4,825,209	4/1989	Sasaki et al.	340/825.72				
4,829,372	5/1989	McCalley et al.	358/86				
4,871,992	10/1989	Petersen	340/407				
4,887,152	12/1989	Matsuzaki	358/86				
4,894,714	1/1990	Christis	358/86				
4,905,094	2/1990	Pocock et al.	358/342				
4,908,707	3/1990	Kinghorn	358/172				
4,914,517	4/1990	Duffield	358/191.1				
4,920,566	4/1990	Robbins et al.	380/19				

OTHER PUBLICATIONS

G.A. McKenzie, "ORACLE—An Information Broadcasting Service Using Data Transmission In the Vertical Interval", Journal of the SMPTE, Jan. 1974, 6–10.

S.M. Edwardson and A. Gee, "CEEFAX: A Proposed New Broadcasting Service", Journal of the SMPTE, Jan. 1974, pp. 14–19.

A. James, "ORACLE—Broadcasting the Written Word", Wireless World, Jul. 1973.





FIG. 1







FIG. 3






FIG. 5




FIG. 6




FIG. 7

FIG. 8

<u>FIELD</u>	<u>SIZE</u>	<u>DEFINITIONS</u>
<SI>	1	Start of TITLE Field
<TITLE>	24	TITLE Information
<DLE>	1	Start of TRACK Field
<TRACK>	24	TRACK Information
<DC1>	1	Start of ARTIST Field
<ARTIST>	24	ARTIST Information
<DC2>	1	Start of LP LABEL Field
<LP LABEL>	24	LP LABEL Information
<DC3>	1	Start of COMPOSER Field
<COMPOSER>	24	COMPOSER Information
<DC4>	1	Start of SONG ID Field
<SONG ID>	10	SONG ID Information
<COPY PROTECT>	1	Copy protect ('Y'= On, 'N'= Off)
<PLAYTIME>	4	(0000-9999) # of Seconds the Current Selection Will Play

U.S. Patent

Apr. 25, 2000

Sheet 9 of 9

6,055,244




FIG. 9




FIG. 10

6,055,244

1

METHOD AND APPARATUS FOR COMMUNICATING DIFFERENT TYPES OF DATA IN A DATA STREAM

This application is a continuation of Ser. No. 08/171,453
filed Dec. 22, 1993, now abandoned, which is a continuation
of Ser. No. 08/056,560 filed May 3, 1993, now U.S. Pat. No.
5,406,558, which is a division of Ser. No. 07/618,744 filed
Nov. 27, 1990, now U.S. Pat. No. 5,239,540.

TECHNICAL FIELD

The present invention relates to the field of digital signal
transmission and more particularly, to transmitting digital
signals accompanied by program content data so that
listeners/viewers may see a display of the program content
data as they are listening/viewing the performance, without
interrupting the performance.

BACKGROUND OF THE INVENTION

Presently, program content information, for example,
song title, artist, record label, etc., is communicated to the
customer/listener by announcers' disc jockeys (DJs). In the
case of video programs transmitted by broadcast means,
video text messages are presented between programs and
during interruptions of programs. In the case of many
premium services, it is undesirable to interrupt programs for
presentation of program content information. It may also be
undesirable to have any form of announcer or DJ between
program or selection of music.

Those such announcers or interruptions of program may
be undesirable in some services. Nevertheless, it is highly
desirable to communicate program content information.
Frustration of customers, and possible loss of revenue due to
subscription cancellation can occur if a subscriber has no
method of knowing the title, composer or artist of the
particular selection of music. To the music industry, identifi-
cation of recording label and identification number is
critical to sale of the recordings. Currently, a subscriber
viewing a premium video program must consult a separate
listing, tune to a different channel, or wait till the end of the
program for its identification.

Similarly, the cable television industry is currently intro-
ducing audio-only services. Program content information is
printed in a separate listing. These cable "radio stations"
may play a continuous succession of musical selections
without commercial interruptions. These services may not
use a "disc-jockey" to identify the musical or other selec-
tions. Instead, under the present invention, data channels
will contain information about the music being played.

In one embodiment of the present invention, a display of
this data has been envisioned that has been termed an
"electronic DJ". This display could be built into the sub-
scriber terminal itself, or it could be a separate display unit
that would connect to a port on the rear panel of the terminal.

The problem with such displays is that, unless they are
very large and therefore costly, they cannot be easily placed
within reading distance of the listener. Long cables for the
display would be difficult to route in a typical living room,
and we need only look at the success of VCR wired remote
controls to convince ourselves that such a tethered display
would not be optimum.

Wireless remote controls have brought great convenience
to the control of consumer products. Highly intelligent
remote controls with liquid crystal displays are available.
Programmable and universal "learning" remote controls are

2

available that assume the functions of multiple other con-
trols. These remote controls receive information from each
other, and display the functions available to the user.

It can be a frustrating experience to enjoy a piece of music
on the radio, only to have the station fail to identify the
piece. To lovers of music, having such information as music
title, composer, artist and record label is vital. Without this
information, the service will be reduced to the level of
generic background music.

SUMMARY OF THE INVENTION

The problems and related problems of transmitting and
providing a display of program content data are solved by
the principles of the present invention. In furtherance of
these principles, it is an object of the present invention to
provide program information to subscribers without inter-
rupting the program.

It is an object of the present invention to transmit and
provide program information for digital audio transmitted to
subscribers, where the program information is combined
with the digital audio.

It is a further object of the present invention to provide
program data to subscribers of video information.

It is another object of the present invention to provide
program information to subscribers where the information is
communicated through a remote control unit.

It is a further object of the present invention to provide a
system where digital program information is combined with
digital audio/video signals which are transmitted via
satellite, coaxial cable, or other means to subscribers.

It is another object of the present invention to provide
program data corresponding to audio/video signals to sub-
scribers with disabilities.

In accordance with these and other objects, apparatus for
encoding according to the present invention comprises: a
plurality of means for producing digital signals; a plurality
of means for producing a plurality of program data signals,
each program data signal corresponding to one digital sig-
nal; and, at least one encoding means, coupled to the
plurality of means for producing digital and program data
signals, for encoding the plurality of program data signals
with the plurality of digital signals to produce a plurality of
combined digital and program data signals.

Additionally, under these and other objects, a method is
disclosed for encoding program information into a digital
data stream comprising the steps of: producing a plurality of
digital signals; producing a plurality of program data
signals, each program data signal corresponding to one
digital signal; and encoding the plurality of program data
signals with the plurality of digital signals to produce a
plurality of combined digital and program data signals.

Conversely, under the above and other objects, an appa-
ratus is disclosed for communicating program information
corresponding to a track of digital data from a signal
containing a plurality of digital and program information
signals comprising: first receiving means for receiving an
encoded signal containing a plurality of digital signals and
a plurality of program data signals, each program data signal
corresponding to one digital signal; at least one selecting
means, coupled to the first receiving means, for selecting
one digital signal and one corresponding program data
signal from the received encode signal; at least one decoding
means, coupled to the selecting means, for decoding the
selected one digital signal and the one corresponding pro-
gram data signal so as to separate the corresponding pro-

6,055,244

3

gram data signal from the selected one digital signal; transmitting means, coupled to the decoding means, for transmitting the one corresponding program data signal; second receiving means, coupled to the transmitting means, for receiving the one corresponding program data signal; and, communicating means, coupled to the second receiving means, for communicating the one corresponding program data signal.

Similarly, a method under the above objects is disclosed for communicating program information corresponding to a track from signal containing a plurality of digital and program information signals comprising the steps of: receiving an encoded signal containing a plurality of digital signals and a plurality of program data signals, each program data signal corresponding to one digital signal; selecting one digital signal and one corresponding program data signal from the received encoded signal; decoding the selected one digital signal and the one corresponding program data signal so as to separate the corresponding program data signal from the selected one digital signal; transmitting the one corresponding program data signal to a communicator; receiving the transmitted one corresponding program data signal; and, communicating the received one corresponding program data signal via the communicator.

Finally, under the objects of the present invention, a handheld apparatus for communicating program information corresponding to digital data is disclosed comprising: receiving means for receiving a program data signal corresponding to a digital track; processing means, coupled to the receiving means, for processing the received program data signal; and, communicating means, coupled to the processing means, for communicating the processed program data signal.

The communicating means under the present invention could take the form of a standard remote control, i.e. a hand-held unit with a display of some sort. The display could be a liquid crystal or other suitable technology. A benefit of having the display in a remote unit under the present invention is that the cost of the display need not be included in the base unit. The display can be a value-added extra-cost feature. It can thus be seen as a means of increasing revenue, or of making the service more affordable to those not desiring the feature.

The communicating means under the present invention could also take the form of a table-mounted unit. It could use a larger display than might be possible on a hand-held remote. It could also use ac power instead of batteries and thus power a brighter and larger display more suitable for low light viewing. The control and display functions could be separated into two individual units.

The base subscriber terminal could automatically update the remote display/control unit whenever there has been a change in programming. This, however, may result in brief intervals during which the use of other remote controls might be disrupted. Instead, the communications may be structured such that for information to be sent from the base subscriber terminal, it must be polled from the remote unit. Memory could be used in either the base unit or the remote to store information on previous selections. This information could be recalled by the user on demand.

The communications link between the base subscriber terminal and the remote unit could use radio frequencies, infrared, visible light, acoustical transmission through air, or other wireless means. The concept could also be extended to carrying the information on the household power lines, telephone wires, coaxial cable, fiber-optic cable or means other than the direct connection of a cable to the base unit.

4

BRIEF DESCRIPTION OF THE DRAWINGS

These and other advantages of the present invention may be appreciated from studying the following detailed description together with the drawings in which:

FIG. 1 is a blocked diagram of the overall system in the present invention;

FIG. 2 shows a detailed block diagram of the encoding and transmitter portion of the present invention;

FIG. 3 shows a block diagram of the encoding portion of the present invention;

FIG. 4 shows a block diagram of the receiving portion of the present invention;

FIG. 5 shows a block diagram of the digital music tuner;

FIG. 6 shows a block diagram of the application specific integrated circuit shown in FIG. 5;

FIG. 7 shows a block diagram for the remote communication device of the present invention; and,

FIG. 8 shows a diagram of a simplified frame format using the present invention.

FIG. 9 illustrates the composition of the data frame of the present invention.

FIG. 10 illustrates the composition of the data block portion of the data frame of FIG. 9.

DETAILED DESCRIPTION

Referring to FIG. 1, a block diagram of an overall system in the present invention is described. The present invention will be described with respect to transmitting audio signals with program data. However, those skilled in the art will recognize that the present invention may, instead of transmitting audio with corresponding program data, transmit any of the following, with corresponding program data: television, games, software, video, and other combinations of audio/video or software information.

Compact disc players 10-1 through 10-n provide a plurality of digital audio signals to the present invention. These CD players may be the so called "Jukebox" type wherein up to sixty or more compact discs may be stored and accessible by the player.

The digital audio signals from CD players 10-1 through 10-n are input to encoders 20-1 through 20-n which will be described in greater detail with reference to FIG. 3. Controller and music database 30-1 through 30-k controls the output of CD players 10-1 through 10-n and any respective selection of compact discs within these players and also provides a database containing program data with a one to one correspondence to the tracks contained on the compact discs. This program data includes title, track, artist, publisher, composer, song identification and play time information blocks for each song contained on a compact disc. These program data signals could also include other information relevant to describing the particular track contained on a compact disc, as those skilled in the art can appreciate. For example, if the information were historical audio data, information on the time and place such data was first conceived or transmitted may also be contained within this program information. Additionally, if the digital signals transmitted contained video information, the corresponding program data signals would relate to the video program being transmitted, for example, the title, actors, director, publisher, year, or other relevant information.

The plurality of digital audio signals inputted by the CD players 10-1 through 10-n are combined in encoders 20-1 through 20-n with the program data signals inputted by

6,055,244

5

controller and music databases 30-1 through 30-k. The combined signals from encoders 20-1 through 20-n are then inputted into multiplexer 40 which combines the signals into a serial digital data stream.

Additional signals may be combined with the digital audio and program information signals. Subscriber control 45 contains information on various subscribers who may receive the digital audio data produced by the present invention. This subscriber information stored in subscriber control 45 is multiplexed with the digital audio and program data signals in multiplexer 40, producing a serial digital data stream containing digital audio, program information, and national subscriber information.

The serial digital audio/program data stream from multiplexer 40 is input into the digital satellite transmitter 50 and broadcast, via satellite, to digital satellite receiver 60. However, those skilled in the art will realize that any delivery system, not just satellite transmission, may be used, such as cable television (CATV), microwave distribution (MDS or MMDS), telephone systems, terrestrial broadcasts, and other coaxial or optical cable lines.

The previously described transmitter section will be more fully discussed with reference to FIG. 2, while the following receiver section will be more fully described with reference to FIG. 4. Digital satellite receiver 60 transfers the digital data to headend processing 70 which in turn converts and sends the information to digital cable modulators 75. The digital audio data is then added with signals from other cable modulators in summing circuit 80 and sent over a cable distribution system.

The cable distribution system includes line amplifiers 90 for boosting the signal and compensating for any line loss. System tap 85 directs the combined signal to a subscriber's premises and into digital music tuner 100. Digital music tuner 100, more fully described with respect to FIG. 5, selects the channel containing the digital audio and program data signals. Additionally, digital music tuner 100 separates the digital audio signal from the program information signal. The digital audio signal is converted to analog, amplified and output on a subscriber's audio electronics, while the program information signal is processed and sent to a local display or remote using information display 200. The demultiplexing and decoding of the signals is discussed more fully with reference to FIG. 6. These displays then communicate to the subscriber the particular program information corresponding to an audio track currently being listened to by the subscriber. The remote music information display is more fully described with respect to FIG. 7.

Transmitting Section

Referring to FIG. 2, a block diagram of the studio and transmitter, or uplink, section of the present invention is described. Compact disc players 10-1 through 10-n are driven by microcomputers 15-1 through 15-n. Microcomputers 15-1 through 15-n could be IBM Model AT microcomputers. These microcomputers are in turn controlled by the studio sequencing master controllers 30-1 through 30-k. These master controllers 30-1 through 30-k include a database containing the program information described above. These master controllers are preferably IBM Model PS/2 microcomputers or other computers containing a 386 type microprocessors.

The digital audio output from CD players 10-1 through 10-n is input into encoders 20-1 through 20-n along with program information supplied by master controllers 30-1 through 30-k. Encoders 20-1 through 20-n combine the

6

digital audio signals with the program data signals and output the combined signal to system data multiplexers 40-1 and 40-2. Preferably, the outputs of 30 encoders 20-1 through 20-30 are input into multiplexers 40-1 and 40-2 where the signals are time division multiplexed. Multiplexers 40-1 and 40-2 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocquengben (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art.

Billing system 47 includes subscriber information of the present invention and national control information and may be comprised of an IBM Model PS/2 microcomputer. The subscriber information and other billing system data would be contained within a large database within billing system 47. Typical billing system data could include, for example, identity, location, etc. for subscribers and their current billing status. Billing system information from billing system 47 is input into the system manager digital audio controller 45. System manager 45 is preferably comprised of a series 8500 System Manager manufactured by Scientific Atlanta or a similar product. System manager digital audio controller 45 controls master controllers 30-1 through 30-k. Additionally, the system manager 45 may also input subscriber data from the subscriber database within billing system 47 into multiplexers 40-1 and 40-2.

The subscriber information may be combined with the digital audio and program signals through multiplexers 40-1 and 40-2. Multiplexers 40-1 and 40-2 provide the master clock to all the encoders 20-1 through 20-n and to satellite exciters 53-1 and 53-2. The output of multiplexers 40-1 and 40-2 is a 34 megabits per second (Mbps) data stream comprising the preferred 30 channels outputted by the 30 encoders 20-1 through 20-30.

Relay circuit 43 provides fault protection so as to switch the system to multiplexers 40-2 and 40-2 from multiplexer 40-1 in event of a fault. The outputs from multiplexers 40-1 and 40-2 are two coaxial cables, for plus and minus balanced connections. These balanced coaxial cables are used from the output of multiplexers 40-1 and 40-2 through satellite transmitting and receiving electronics. The combined signal from multiplexer 40-1 passes through relay 43 into fiber-optic transmitter 49. Fiber-optic transmitter 49 transports the signal from the studio to the transmitter site and into fiber-optic receiver 51. The output of the fiber-optic receiver drives an offset quadrature phase shift keying (OQPSK) satellite modulator 50. The signal is then up converted, amplified and transmitted to the satellite, as more fully described below.

The signals are received from fiber-optic transmitter 49 into fiber-optic receiver 51 in transmitter 50. From fiber-optic receiver 51 the signals pass through fault protection relay 52-1 into OQPSK Exciter 53-1. The digital signals from OQPSK exciter 53-1 enter splitter 57-1 and through fault protection relay 52-2. Thereafter, the signals pass through an upconverter 58-1. From upconverter 58-1 the signals pass through switch 56-1 into high powered amplifier 59-1 and once again through switch circuit 56-2 and then transmitted. The transmitting is preferably performed via a satellite. The transmission may also occur via coaxial cables or fiber-optic cables.

Redundancy control logic 55 controls transmitter 50, so in the event of a fault, redundant circuitry is activated. Specifically, redundancy control logic 55 controls relays 52-1 and 52-2 and switches 56-1 and 56-2 so as to switch to redundant exciter 53-2 and splitter 57-2, redundant up converter 58-2 and high powered amplifier 59-2.

6,055,244

7

Referring to FIG. 3, a more detailed block diagram of an encoder 20-1 is described. Outputs from CD players 10 are input to multiplexer 31. Preferably, the outputs from 16 CD players 10-1 through 10-16 are input into multiplexer 31 where their signals are combined and output as two channels to rate synchronizers 33-1 and 33-2. The rate synchronized signals are then input into mixer and signal compressor 35. Mixer and signal compressor 35 preferably uses

The signals are clocked at 11 megahertz to modulators 75-1 through 75-6. Each modulator 75-1 through 75-6 is a nine state quadrature partial response (9-QPR) modulator capable of handling five stations and each occupying a 3 megahertz bandwidth. Those skilled in the art will appreciate that one may also use phase shift key modulation or other modulation methods known in the art with fewer or greater numbers of states.

The modulated signals from modulators 75-1 through 75-6 are combined in radio frequency combiner 80 along with other modulated signals from other cable modulators 77. Modulators 75-1 through 75-6 digitally filter the data, quadrature partial response (QPR) modulate and convert the data to the selected output frequency for combining with other modulated channels 77 in the present cable television system. Each block of five stereo pairs occupies 3 megahertz of band width and can be carried in half of one 6 megahertz video channel of the present cable television system. Since the present system uses a common 6 megahertz video channel, no modifications of current CATV distribution system equipment is required.

The combined signals from RP combiner 80 are distributed over a coaxial cable or fiber-optic distribution system into a subscriber's home. Directional coupler 85 directs most of the signal to video set top terminal 87. A sample of the signal is sent from directional coupler 85, at a loss of 10 decibels to digital music tuner 100. Tuner 100 is controlled by either a plain remote 201 or a music information display remote 200. Additionally, tuner 100 outputs left and right analog audio signals, and may also output an optional digital signal output.

Referring to FIG. 5, a block diagram of digital music tuner 100 is shown. The digital audio and program data signal is inputted from directional coupler 85 into set top terminal tuner 110. This tuner preferably includes phase locked loop circuitry. The signal from tuner 110 is amplified by amplifier 115 and filtered by saw filter 120 before being demodulated by demodulator 125. Tuner 110 converts the selected radio frequency channel to a demodulation intermediate frequency. The output of demodulator 125 is QPR demodulated to produce a 5.6 Mbps data stream containing five stereo pair of digital the data compression format described in U.S. Pat. No. 4,922,537, incorporated herein by reference. Mixer and data compressor 35 is controlled by input signals from master controller 30-1 which also inputs the program data signals corresponding to the digital audio signals. The digital audio signals are compressed, program data signals are mixed therewith, and then the mixed signal is input into frame sync detector and output formatter 37. Circuit 37 may also include circuitry to encrypt the mixed and compressed signals using, for example, the Data Encryption Standard (DES) or using other similar encryption techniques known in the art. Circuit 37 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocquenghen (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art. Hamming encoding is disclosed in *Electronic Engineers Reference Book*, edited by F. Mazda, page 32/10, incorporated herein by reference.

8

The audio data is clocked into and out of circuits 33-1, 33-2, 35 and 37 at a rate of 44.1 kilo samples per second. The mixed compressed and encrypted signals are output of circuit 37 at 1.12896 Mbps in Applicant's preferred embodiment.

Receiving Section

Referring to FIG. 4, the mixed, compressed and encrypted signal is received in the C-band via satellite receive antenna and amplified and block converted in a low-noise block converter 63, along with other satellite distributed signals. The signal is output in the L-band at 950 to 1450 megahertz and input into splitter 65 where the audio signal is input into OQPSK receiver 67. Receiver 67 demodulates the OQPSK information and provides one 34 Mbps signal stream containing the preferred 30 satellite distributed channels. The 34 Mbps signal is output of receiver 37 at 34 megahertz clock rate into demultiplexer 70. Preferably, demultiplexer 70 is a 1:6 demultiplexer which separates the single data stream into six channels containing 5.6 Mbps digital audio and program data each. These six channels contain five stations each. audio data to applications specific integrated circuit (ASIC) 140. Demodulator 125 also provides an automatic gain control signal 130 to tuner 110 to maintain constant signal level. Additionally, demodulator 125 provides data to clock recovery phase locked loop (PLL) 135. Data clock PLL 135 contains a 33.8 megahertz crystal 137 from timing purposes.

This ramp signal is sent to ASIC 140, which will be discussed in greater detail with reference to FIG. 6. ASIC 140 provide a digital audio output to interface 170. Interface 170 uses the Sony-Philips digital interface format (SPDIF). Similarly, the digital audio signals are input from ASIC 140 to digital to audio converter 160. From digital to audio converter 160, the analog left and right audio signals are filtered through filters 165-1 and 165-2 and input into bypass 170. Bypass 170 allows additional audio components (e.g., a CD player or tape deck) to be switchably connected with the digital music tuner 100.

Microprocessor 150 controls phase locked loop of tuner 110, ASIC 140, digital to analog converter 160 and bypass 170. The program data signal from ASIC 140 is sent to microprocessor 150 where it is stored in internal memory of the microprocessor, and may be displayed on front panel interface 180 or transmitted through remote control transmitter 190. Remote control receiver 195 may select particular program data information or audio channels through microprocessor 150.

Power supply 175 would supply both positive five volt digital and analog power, and a negative five volt supply to the system. Positive 12 volt and positive 30 volt power supply signals are also provided from power supply 175. Additionally, tuner 100 would preferably have input means, e.g., push buttons or toggle switches, on the exterior of its housing (not shown). These input means would allow selection of channels, stations, display of program data, and display of particular information blocks contained in the program data signal. Additional selections or inputs may be provided as those skilled in the art recognize.

Referring to FIG. 6, a more detailed block diagram of ASIC 140 is provided. The signal from demodulator 125 is input into demodulator support circuit 141 which comprises logic circuitry (e.g., flip-flops) required in demodulation of the signal. The signal from demodulator support circuit 141 is then input into demultiplexer 143 which separates the 5.6 Mbps data stream to select one of five stereo pairs of digital

6,055,244

9

audio signals. This signal is then sent to decrypting circuit 145. The decrypted signal is then separated in signal separator 148 where program data is sent to microprocessor in/out circuit 149 while audio data is sent and decoded in circuit 147. Decoder 147 uses the data decompression technique described in U.S. Pat. No. 4,922,537, incorporated herein by reference.

Microprocessor in/out, address and control circuit 149 interfaces with microprocessor 150. All circuits within ASIC 140 are driven by clock 146. Memory 144 stores bits of data to support the demultiplexing, decrypting and decoding functions occurring in circuits 143, 145 and 147 respectively. The memory may be of a nonvolatile type such as an EPROM or similar ROM memory or may be a volatile type RAM memory supported by battery 175, preferably a lithium type battery. Such a battery 175 would prevent loss of data stored in memory 144.

Remote Display Unit

Referring to FIG. 7, a block diagram of the remote music information display unit 200 is shown. Program data signals are received by receiver 201 from remote control transmitter 190. Preferably, infrared transmitter and receivers 190, 193, 201 and 205 are used. However, radio frequency, ultrasonic, wire, fiber-optic cables or other means could be used as those skilled in the art can appreciate.

The received signal is then input into processor 203 which processes and sends the program data signal to display 209 for communicating program data corresponding to currently playing audio track to a subscriber. Display 209 may be a liquid crystal display, a light emitting diode, a braille reader, a voice synthesizer or a cathode-ray tube or any other communicating device as may be appreciated by those skilled in the art. Audible or tactile communicating means would allow communication of the program data signals to subscribers with disabilities, as would the use of a remote unit.

Input means shown as keyboard 207 may receive program data selection commands or audio track commands from a subscriber which are sent to processor 203. Keyboard 207 may also include means to allow a subscriber to control volume, power, channel selection, station selection, display, or other suitable subscriber commands that those skilled in the art appreciate. Processor 203 then converts and transmits the subscriber command signal to transmitter 205 which is received by remote control receiver 195. The received signal from receiver 195 is input into microprocessor 150 where appropriate signals are sent therefrom to ASIC 140 and tuner 110 so as to bring about the subscriber's desired audio track, audio channel or program information.

Repeaters could be placed throughout a dwelling to extend the range of the display/control unit. Additionally, processor 203 could contain memory for storing various information, particularly program information.

In an alternative embodiment, the remote display unit may display only a code number representing the program data signals, whereby a subscriber may reference the number in printed material for a full description of the currently playing audio track. The printed material could be a publication which would rotate monthly or weekly as the programs on respective stations change. Such a system would allow for a smaller display on the remote unit, and thus be less costly to a subscriber. Such a printed publication would also allow a subscriber to determine which programs were playing on the various channels.

Additionally, the remote display unit or tuner 100 could display, upon a subscriber's request, program data corre-

10

sponding to data being transmitted on channels not currently being listened to/viewed by the subscriber. In this way, a subscriber may scan what is being broadcast on alternate channels while listening to a currently playing channel.

Data Format

The preferred thirty stereo audio stations are multiplexed as follows. Groups of five stations are formatted into a frame of data. Six such frames are interleaved bit by bit for transmission over the satellite. Each such frame containing five stations has a header. This header is used by the headend demultiplexer 70 to deinterleave the satellite received data into six frames of five stations each. The header is also used in the ASIC 140 to synchronize on the frame. A second header contains subscriber control transaction data. This section header would preferably include channel and subscriber transaction data as previously described with respective billing system 47. The headers include additional bits for error detection.

Following the headers, compressed audio data with its associated program data is sent. Audio data for each station includes a seven bit "k factor" and a three bit "exponent" for each block of nine samples as described in previously referenced U.S. Pat. No. 4,992,537. Five such k factor and exponent blocks for each station are included in each frame.

The audio and program data for the five stations in the frame are interleaved bit by bit. That is, the first bit is sent for station No. 1, followed by the first bit for station No. 2 and so on until the first bit of each station has been sent. Then the second bit of each station is sent and so on. After the last audio data bits in each block of nine samples have been sent, the program data bits are sent in the same manner. Thus, the program data for each station is multiplexed in the frame with its associated station so that when the frame is demultiplexed or rearranged, the program information for that station is kept with its station. The advantage of multiplexing the program information with the audio data is that one may easily process the combined signal without fear of scrambling channels of audio data with their respective program information. Error correction and detection bits are also sent with the audio data and the program data.

Two program data bits are sent in the same block together with every nine compressed samples (100bits) of audio data. This effectively provides a data channel of about 9800 baud used to transmit program data information. The information is sent in ASCII representation, but could easily be sent in other formats such as EBCDIC as would be apparent to those skilled in the art. FIG. 8 shows the program information as preferably sent and the size of each field in the present embodiment. Other information can be sent, such as music classification for selection of station by music type, special event announcements, or other such information, known by those skilled in the art.

We claim:

1. A method for transmitting different types of data in a single data stream comprising the steps of:

- generating program data for insertion into said data stream;
- generating program selection data which describes the attributes of said program data for insertion into said data stream, wherein said program selection data includes at least one of a title, a track number, an artist, a publisher, a composer, a song identification, and a play time information block;
- generating another type of data for insertion into said data stream;

6,055,244

11

combining said program data with said program selection data to form data groups;

generating a header containing data from said another type of data;

combining said header with said data groups to form a unit; and

constructing said data stream by joining a plurality of successive units for transmission.

2. Apparatus for communicating different types of digital data to a receiver comprising:

first means for generating program selection data which describes attributes of program data for insertion into a data stream, wherein said program selection data includes at least one of a title, a track number, an artist, a publisher, a composer, a song identification, and a play time information block;

second means for generating another type of data for insertion into said data stream;

third means for generating said program data for insertion into said data stream;

means operatively associated with said first and third means for combining said program data with said program selection data to form data groups;

means operatively associated with said second means for generating a header containing data from said another type of data;

12

means for combining said header with a plurality of data groups to form a unit; and

means for constructing said data stream by joining a plurality of successive units for transmission.

3. A digital data receiver for receiving a data stream containing successive headers including data of a first type, with each header followed by a plurality of mixed data groups including digital data and program selection data which describes the attributes of said digital data, said receiver comprising:

first means for detecting said program selection data from successive mixed data groups contained in a received data stream, wherein said program selection data includes at least one of a title, a track number, an artist, a publisher, a composer, a song identification, and a play time information block;

second means for detecting data of the first type from successive headers contained in the received data stream;

means responsive to the detected data of the first type and the detected program selection data for recovering the digital data from the received data stream; and

means for reproducing a program from the recovered digital data.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,055,244
DATED : April 25, 2000
INVENTOR(S) : Wall et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 8,

Line 30, delete "tamp" and insert -- timing --
Line 61, delete "FIG. 6." and insert -- FIG. 6, --

Column 9,

Line 22, delete "193" and insert therefore -- 195 --
Line 67, delete "display." and insert therefore -- display,--


Column 10,

Line 16, delete "section" and insert therefore -- second --
Line 43, delete (100bits) and insert therefore -- (100 bits) --

Signed and Sealed this

Thirtieth Day of April, 2002

Attest:



Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,055,244
 DATED : April 25, 2000
 INVENTOR(S) : Wall et al.

Page 1 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Line 36, delete "title." and insert therefore -- title, --

Line 37, delete "industry." and insert therefore -- industry, --

Column 2,

Line 64, delete "encode" and insert therefore -- encoded --

Column 3,

Line 66, delete "cable. fiber-optic" and insert therefore -- cable, fiber-optic --

Column 6,

Line 50, delete "fiberoptic" and insert therefore -- fiber-optic --

Column 7,

Line 8, insert -- the data compression format described in United States Patent No. 4,922,537, incorporated herein by reference. Mixer and data compressor 35 is controlled by input signals from master controller 30-1 which also inputs the program data signals corresponding to the digital audio signals. The digital audio signals are compressed, program data signals are mixed therewith, and then the mixed signal is input into frame sync detector and output formatter 37. Circuit 37 may also include circuitry to encrypt the mixed and compressed signals using, for example, the Data Encryption Standard (DES) or using other similar encryption techniques known in the art. Circuit 37 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocqenghen (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art. Hamming encoding is disclosed in Electronic Engineers Reference Book, edited by F. Mazda, page 32/10, incorporated herein by reference.

The audio data is clocked into and out of circuits 33-1,33-2, 35 and 37 at a rate of 44.1 kilosamples per second. The mixed compressed and encrypted signals are output of circuit 37 at 1.12896 Mbps in Applicant's preferred embodiment.

Receiving Section

Referring to Fig. 4, the mixed, compressed and encrypted signal is received in the C-band via satellite receive antenna and amplified and block converted in a low-noise block converter 63, along with other satellite distributed signals. The signal is output in the L-band at 950 to 1450 megahertz and input into splitter 65 where the audio signal is input into OQPSK receiver 67. Receiver 67 demodulates the OQPSK information and provides one 34 Mbps signal stream containing the preferred 30 satellite distributed channels. The 34 Mbps signal is output of receiver 37 at 34 megahertz clock rate into demultiplexer 70. Preferably, demultiplexer 70 is a 1:6 demultiplexer which separates the single data stream into six channels containing 5.6 Mbps digital audio and program data each. These six channels contain five stations each. --

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTIONPATENT NO. : 6,055,244
DATED : April 25, 2000
INVENTOR(S) : Wall et al.

Page 2 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 7 con't.

Line 19, delete "7-56" and insert therefore -- 75-6 --

Line 30, delete "RP" and insert therefore -- RF --

Column 7, lines 50-67 and Column 8, lines 1-23.

Delete "the data compression format described in United States Patent No. 4,922,537, incorporated herein by reference. Mixer and data compressor 35 is controlled by input signals from master controller 30-1 which also inputs the program data signals corresponding to the digital audio signals. The digital audio signals are compressed, program data signals are mixed therewith, and then the mixed signal is input into frame sync detector and output formatter 37. Circuit 37 may also include circuitry to encrypt the mixed and compressed signals using, for example, the Data Encryption Standard (DES) or using other similar encryption techniques known in the art. Circuit 37 may include error correction encoding using, for example, Hamming encoding or Bose Chaudhuri Hocqenghen (BCH) encoding, or other error correcting/encoding methods known by those skilled in the art. Hamming encoding is disclosed in Electronic Engineers Reference Book, edited by F. Mazda, page 32/10, incorporated herein by reference.

The audio data is clocked into and out of circuits 33-1, 33-2, 35 and 37 at a rate of 44.1 kilosamples per second. The mixed compressed and encrypted signals are output of circuit 37 at 1.12896 Mbps in Applicant's preferred embodiment.

Receiving Section

Referring to Fig. 4, the mixed, compressed and encrypted signal is received in the C-band via satellite receive antenna and amplified and block converted in a low-noise block converter 63, along with other satellite distributed signals. The signal is output in the L-band at 950 to 1450 megahertz and input into splitter 65 where the audio signal is input into OQPSK receiver 67. Receiver 67 demodulates the OQPSK information and provides one 34 Mbps signal stream containing the preferred 30 satellite distributed channels. The 34 Mbps signal is output of receiver 37 at 34 megahertz clock rate into demultiplexer 70. Preferably, demultiplexer 70 is a 1:6 demultiplexer which separates the single data stream into six channels containing 5.6 Mbps digital audio and program data each. These six channels contain five stations each."

Column 8.

Line 30, delete "tamp" and insert -- timing --

Line 61, delete "FIG. 6." and insert -- FIG. 6, --

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,055,244
DATED : April 25, 2000
INVENTOR(S) : Wall et al.

Page 3 of 3

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 9,

Line 22, delete "193" and insert therefore -- 195 --

Line 67, delete "display." and insert therefore -- display, --

Column 10,

Line 16, delete "section" and insert therefore -- second --


Line 43, delete "(100bits)" and insert therefore -- (100 bits) --

This certificate supersedes Certificate of Correction issued April 13, 2002

Signed and Sealed this

Twentieth Day of August, 2002

Attest:



Attesting Officer

JAMES E. ROGAN
Director of the United States Patent and Trademark Office