

1 NIXON PEABODY LLP  
David. B. Ritchie (112018)  
2 dritchier@nixonpeabody.com  
Margarita Gevondyan (245536)  
3 mgevondyan@nixonpeabody.com  
200 Page Mill Road, Suite 200  
4 Palo Alto, CA 94306-2022  
Telephone: (650) 320-7747  
5 Facsimile: (866) 294-6031

6 BARCELÓ & HARRISON, LLP  
Reynaldo C. Barceló (199741)  
7 rey@bhiplaw.com  
2901 West Coast Hwy, Suite 200  
8 Newport Beach, California 92663  
Telephone: (949) 340-9736  
9 Facsimile: (949) 258-5752

10 Attorneys for Plaintiff,  
11 TMI PRODUCTS, INC.

12 UNITED STATES DISTRICT COURT  
13 CENTRAL DISTRICT OF CALIFORNIA  
14

15 TMI PRODUCTS, INC.,  
16 Plaintiff

17 v.

18 AUDIOVOX CORPORATION and  
19 AUDIOVOX ELECTRONICS  
CORPORATION,  
20 Defendants

Case No.

CV 09-01437 JFW (JCx)

COMPLAINT FOR PATENT  
INFRINGEMENT

DEMAND FOR JURY TRIAL

FILED  
2009 FEB 27 PM 4:05  
CLERK U.S. DISTRICT COURT  
CENTRAL DISTRICT OF CALIF.  
LOS ANGELES

21  
22  
23  
24  
25  
26  
27  
28

1 For its complaint against Audiovox Corporation and Audiovox Electronics  
2 Corporation (collectively, "Audiovox," or "Defendants"), Plaintiff TMI Products,  
3 Inc. ("TMI") alleges as follows:

4 **THE PARTIES**

5 1. TMI is a corporation duly organized and existing under the laws of the  
6 California, with its principal place of business at 1493 E. Bentley Drive, Corona,  
7 California 92879. TMI holds an exclusive license to U.S. Patent Nos. 7,040,697  
8 ("the '697 patent") and 7,407,227 ("the '227 patent") (collectively, "the Patents in  
9 Suit"). TMI's exclusive license includes the exclusive world-wide rights to  
10 sublicense the '697 and '227 patents, and to enforce the '697 and '227 patents  
11 against alleged infringers.

12 2. Upon information and belief, Audiovox Corporation is a corporation  
13 organized and existing under the laws of the State of Delaware, with its principal  
14 place of business at 180 Marcus Boulevard, Hauppauge, New York.

15 3. Upon information and belief, Audiovox Electronics Corporation is a  
16 corporation organized and existing under the laws of the State of Delaware, with its  
17 principal place of business at 180 Marcus Boulevard, Hauppauge, New York, and it  
18 is a wholly owned subsidiary of Audiovox Corporation.

19 **NATURE OF THE ACTION**

20 4. In this civil action, TMI seeks damages and injunctive relief against  
21 Defendants for acts of patent infringement in violation of the Patent Act of the  
22 United States, 35 U.S.C. §§ 1 et seq.

23 **JURISDICTION AND VENUE**

24 5. This Court has subject matter jurisdiction pursuant to the provisions of  
25 28 U.S.C. §§ 1331 and 1338(a), because this is an action for patent infringement  
26 arising under the laws of the United States, including 35 U.S.C. §§ 1 et seq.

27 6. Venue is proper under 28 U.S.C. §§ 1391(c) and 1400(b), in that the  
28 acts and transactions complained of herein were conceived, carried out, made

1 effective, or had effect within the State of California and within this Judicial  
2 District, among other places.

3 7. On information and belief, Audiovox Corporation resides in this  
4 Judicial District by virtue of its business activities in this Judicial District. For  
5 example, and without limitation, on information and belief, Audiovox Corporation  
6 is licensed to do business in California by the California Secretary of State, and  
7 Audiovox maintains a registered agent for service of process in this Judicial District  
8 – namely, James Wohlberg, 16808 Marquardt Avenue, Cerritos, CA 90701.

9 8. On information and belief, Audiovox Electronics Corporation resides in  
10 this Judicial District by virtue of its business activities in this Judicial District. For  
11 example, and without limitation, on information and belief, Audiovox Electronics  
12 Corporation is licensed to do business in California by the California Secretary of  
13 State, and Audiovox maintains a registered agent for service of process in California  
14 – namely, HIQ Corporate Services, Inc., 1903 21st St., Sacramento, CA 95811.

15 9. On information and belief, Audiovox Corporation markets and sells,  
16 throughout the United States and including in this Judicial District, headrest  
17 mountable video systems through its wholly owned subsidiary, Audiovox  
18 Electronics Corporation. On information and belief, all profits from Audiovox  
19 Electronics Corporation’s sales of headrest mountable video systems flow to  
20 Audiovox Corporation.

21 10. On information and belief, based at least on the facts stated above, this  
22 Court has personal jurisdiction over Defendants.

23 **BACKGROUND**

24 11. On May 9, 2006, the United States Patent & Trademark Office duly  
25 and legally issued United States Letters Patent No. 7,040,697 (“the ’697 patent”),  
26 entitled “HEADREST HAVING AN INTEGRATED VIDEO SCREEN.” A true  
27 and correct copy of the ’697 Patent is attached as Exhibit A and incorporated herein  
28 by reference.



1 had knowledge of the '697 Patent and knew or should have known that their actions  
2 would induce direct infringement by others and intended that their actions would  
3 induce direct infringement by others.

4 17. On information and belief, Defendants have indirectly infringed and  
5 continue to indirectly infringe the '697 Patent by contributory infringement by  
6 providing non-staple articles of commerce to others for use in an infringing system  
7 or method with respect to mobile video headrest systems such as, without limitation,  
8 products and systems marketed as the "Movies2Go Universal Headrest" and the  
9 "Advent Custom Headrest Systems," with knowledge of the '697 Patent and  
10 knowledge that these non-staple articles of commerce are used as a material part of  
11 the claimed inventions of the '697 Patent.

12 18. On information and belief, Defendants will continue to infringe the  
13 '697 Patent as alleged in this Complaint unless enjoined by this Court.

14 19. On information and belief, Defendants' infringement of the '697 patent  
15 is, has been, and continues to be willful and deliberate.

16 20. As a direct and proximate result of Defendants' infringement of the  
17 '697 patent, TMI has been and continues to be damaged in an amount yet to be  
18 determined.

19 21. Unless Defendants and their respective officers, agents, servants, and  
20 employees, and all persons acting in concert with Defendants, are enjoined from  
21 infringing the '697 patent, TMI will be greatly and irreparably harmed.

22 22. By reason of the above acts, TMI is entitled to injunctive relief  
23 enjoining and restraining Defendants, and their respective officers, agents, servants,  
24 and employees, and all persons acting in concert with Defendants, from further  
25 infringement of the '697 patent.

26  
27 ///

28 ///

**SECOND CLAIM FOR RELIEF**

**(Infringement of U.S. Patent No. 7,407,227)**

1  
2  
3 23. TMI incorporates herein by reference the allegations set forth in  
4 paragraphs 1-12 of this Complaint as though fully set forth herein.

5 24. On information and belief, Calli Ventosa, Inc. and Tierra Vista Corp.  
6 are the joint legal owners by assignment of the '227 patent from Timely  
7 Innovations, LP, which is the original assignee listed on the front page of the '227  
8 patent. TMI is the exclusive licensee of the '227 patent, having acquired from Calli  
9 Ventosa, Inc. and Tierra Vista Corp. substantially all rights in the '227 patent,  
10 including the exclusive world-wide right to sublicense the '227 patent and to enforce  
11 the '227 patent against any and all infringers.

12 25. Defendants have directly infringed and continue to directly infringe the  
13 '227 Patent by making, using, selling, or offering for sale in or importing into the  
14 United States mobile video headrest systems that embody or otherwise practice one  
15 or more of the claims of the '227 Patent, such as, without limitation, products and  
16 systems marketed as the "Movies2Go Universal Headrest" and the "Advent Custom  
17 Headrest Systems."

18 26. On information and belief, Defendants have indirectly infringed and  
19 continue to indirectly infringe the '227 Patent by actively inducing direct  
20 infringement by other persons who operate and/or use mobile video headrest  
21 systems such as, without limitation, products and systems marketed as the  
22 "Movies2Go Universal Headrest" and the "Advent Custom Headrest Systems," or  
23 otherwise practice one or more of the claims of the '227 Patent, when Defendants  
24 had knowledge of the '227 Patent and knew or should have known that their actions  
25 would induce direct infringement by others and intended that their actions would  
26 induce direct infringement by others.

27 27. On information and belief, Defendants have indirectly infringed and  
28 continue to indirectly infringe the '227 Patent by contributory infringement by

1 providing non-staple articles of commerce to others for use in an infringing system  
2 or method with respect to mobile video headrest systems such as, without limitation,  
3 products and systems marketed as the “Movies2Go Universal Headrest” and the  
4 “Advent Custom Headrest Systems,” with knowledge of the ’227 Patent and  
5 knowledge that these non-staple articles of commerce are used as a material part of  
6 the claimed inventions of the ’227 Patent.

7 28. On information and belief, Defendants will continue to infringe the  
8 ’227 Patent as alleged in this Complaint unless enjoined by this Court.

9 29. On information and belief, Defendants’ infringement of the ’227 patent  
10 is, has been, and continues to be willful and deliberate.

11 30. As a direct and proximate result of Defendants’ infringement of the  
12 ’227 patent, TMI has been and continues to be damaged in an amount yet to be  
13 determined.

14 31. Unless Defendants and their respective officers, agents, servants, and  
15 employees, and all persons acting in concert with Defendants, are enjoined from  
16 infringing the ’227 patent, TMI will be greatly and irreparably harmed.

17 32. By reason of the above acts, TMI is entitled to injunctive relief  
18 enjoining and restraining Defendants, and their respective officers, agents, servants,  
19 and employees, and all persons acting in concert with Defendants, from further  
20 infringement of the ’227 patent.

21 ///

22 ///

23 ///

24 ///

25 ///

26 ///

27 ///

28 ///

**PRAYER FOR RELIEF**

WHEREFORE, TMI prays for judgment against Defendants as follows:

1. For a judicial determination and declaration that Defendants directly infringe United States Letters Patent Nos. 7,040,697 and 7,407,227 by making, using, offering to sell and/or selling mobile video headrest systems such as, without limitation, products and systems marketed as the “Movies2Go Universal Headrest” and the “Advent Custom Headrest Systems”;

2. For a judicial determination and declaration that Defendants induce direct infringement of United States Letters Patent Nos. 7,040,697 and 7,407,227;

3. For a judicial determination and declaration that Defendants commit contributory infringement of United States Letters Patent Nos. 7,040,697 and 7,407,227;

4. For a judicial determination and decree that Defendants’ infringement of United States Letters Patent Nos. 7,040,697 and 7,407,227 is willful;

5. For damages resulting from Defendants’ past and present infringement of United States Letters Patent Nos. 7,040,697 and 7,407,227, and the trebling of such damages because of the willful and deliberate nature of its infringement;

6. For injunctive relief against further infringement of United States Letters Patent Nos. 7,040,697 and 7,407,227 by Defendants, their respective officers, directors, shareholders, agents, servants, employees, and all other entities and individuals acting in concert with the enjoined entities or on their behalf;

7. For a declaration that this is an exceptional case under 35 U.S.C. § 285 and for an award of attorneys’ fees and costs in this action;

24 ///  
25 ///  
26 ///  
27 ///  
28 ///



- 1           8.     For an assessment of prejudgment interest; and  
2           9.     For such other and further relief as the Court may deem just and proper  
3 under the circumstances.

4  
5 Dated: February 27, 2009

By: 

6  
7           David B. Ritchie (112018)  
8           Margarita Gevondyan (245536)  
9           NIXON PEABODY LLP  
10           200 Page Mill Road, Suite 200  
11           Palo Alto, CA 94306-2022  
12           (650) 320-7747

13           Reynaldo C. Barceló (199741)  
14           BARCELO & HARRISON, LLP  
15           2901 West Coast Hwy, Suite 200  
16           Newport Beach, CA 92663  
17           (949) 340-9736

18           *Attorneys for Plaintiff, TMI Products, Inc.*

19  
20  
21  
22  
23  
24  
25  
26  
27  
28


1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28

**DEMAND FOR JURY TRIAL**

TMI hereby demands a jury trial pursuant to Rule 38 of the Federal Rules of Civil Procedure as to all issues in this lawsuit.

Dated: February 27, 2009

By:



David B. Ritchie (112018)  
Margarita Gevondyan (245536)  
NIXON PEABODY LLP  
200 Page Mill Road, Suite 200  
Palo Alto, CA 94306-2022  
(650) 320-7747

Reynaldo C. Barceló (199741)  
BARCELO & HARRISON, LLP  
2901 West Coast Hwy, Suite 200  
Newport Beach, CA 92663  
(949) 340-9736

*Attorneys for Plaintiff, TMI Products, Inc.*

# EXHIBIT A



US007040697B1

(12) **United States Patent**  
**Tuccinardi et al.**

(10) **Patent No.:** US 7,040,697 B1  
 (45) **Date of Patent:** May 9, 2006

- (54) **HEADREST HAVING AN INTEGRATED VIDEO SCREEN**
- (75) Inventors: **Eugene M. Tuccinardi**, Temecula, CA (US); **Ernesto R. Haack**, Perris, CA (US); **Robert Murphy**, Lake Elsinore, CA (US); **Frank Barrese**, Temecula, CA (US); **Roel C. Espina**, Loma Linda, CA (US); **Jon A. Molo**, Ontario, CA (US); **Theo Zoetemelk**, Riverside, CA (US)

5,267,775 A	12/1993	Nguyen	
5,292,174 A	3/1994	Ohnuma	
5,293,244 A *	3/1994	Kawaguchi	348/789
5,311,302 A	5/1994	Berry et al.	
5,333,416 A	8/1994	Harris et al.	
5,359,349 A	10/1994	Jambor et al.	
5,507,556 A *	4/1996	Dixon	297/217.3
5,529,265 A	6/1996	Sakurai	
5,555,466 A	9/1996	Scribner et al.	
5,640,297 A	6/1997	Labaze	
5,713,633 A	2/1998	Lu	

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3637772 A1 \* 5/1988

(Continued)

*Primary Examiner*—Peter M. Cuomo  
*Assistant Examiner*—Sarah B. McPartlin  
 (74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson & Bear, LLP

- (73) Assignee: **Timely Innovations, LP**, Temecula, CA (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/395,870**

(22) Filed: **Mar. 20, 2003**

(51) **Int. Cl.**  
*A47C 31/00* (2006.01)  
*A47C 7/62* (2006.01)

(52) **U.S. Cl.** ..... 297/217.3; 297/188.04

(58) **Field of Classification Search** ..... 297/217.3, 297/188.04, 188.07, 185; 411/510; 312/242, 312/245

See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

3,004,815 A *	10/1961	O'Kain et al.	312/242
4,584,603 A	4/1986	Harrison	
4,635,110 A	1/1987	Weinblatt	
4,647,980 A	3/1987	Steventon et al.	
4,756,528 A	7/1988	Umashankar	
4,776,739 A *	10/1988	Hamman	411/510
4,788,588 A	11/1988	Tomita	
4,866,515 A	9/1989	Tagawa et al.	
RE33,423 E *	11/1990	Lobanoff	297/188.06
4,983,951 A	1/1991	Igarashi et al.	

(57) **ABSTRACT**

A seat back video display assembly adapted to be positioned in the back of a vehicle seat having an outer skin cover. In one aspect, the assembly may comprise a receptacle member having sidewalls and a back wall so as to define an opening wherein the receptacle member is adapted to be positioned in the back of the vehicle seat. In addition, the assembly may further comprise a carrier member having sidewalls and a back wall so as to define an opening, wherein the carrier member includes at least one fastener that extends from the back wall of the carrier member and engages with the back wall of the receptacle member to secure the carrier member into the receptacle member. Moreover, the assembly may still further comprise a video display unit that is sized so as to be positioned secured within the opening in the carrier member, wherein the video display unit provides video signals.

24 Claims, 10 Drawing Sheets



**US 7,040,697 B1**

Page 2

U.S. PATENT DOCUMENTS							
D398,921	S	9/1998	Rosen	6,669,285	B1 *	12/2003	Park et al. .... 297/217.3
5,842,715	A	12/1998	Jones	6,739,654	B1 *	5/2004	Shen et al. .... 297/188.04
6,024,027	A *	2/2000	Esmaili ..... 109/50	6,750,599	B1 *	6/2004	Tajima ..... 313/292
D434,400	S	11/2000	Rosen	6,755,491	B1 *	6/2004	McElheney ..... 312/242
6,199,948	B1	3/2001	Bush et al.	2001/0008266	A1	7/2001	Lambert
6,216,927	B1	4/2001	Meritt	2003/0025367	A1	2/2003	Boudinot
6,250,967	B1	6/2001	Chu	2004/0007906	A1 *	1/2004	Park et al. .... 297/217.3
6,292,236	B1	9/2001	Rosen	2004/0160096	A1 *	8/2004	Boudinot ..... 297/217.3
6,339,455	B1	1/2002	Allan et al.	FOREIGN PATENT DOCUMENTS			
6,394,551	B1	5/2002	Beukema	FR	2764563	A1	12/1998
6,406,334	B1	6/2002	Chu	JP	01094048	A	4/1989
6,409,242	B1	6/2002	Chang	* cited by examiner			
6,480,243	B1 *	11/2002	Yamamoto ..... 348/836				

U.S. Patent

May 9, 2006

Sheet 1 of 10

US 7,040,697 B1




FIG. 1A

U.S. Patent

May 9, 2006

Sheet 2 of 10

US 7,040,697 B1




FIG. 1B

U.S. Patent

May 9, 2006

Sheet 3 of 10

US 7,040,697 B1




FIG. 3A




FIG. 2






FIG. 3B




FIG. 4

U.S. Patent

May 9, 2006

Sheet 6 of 10

US 7,040,697 B1




FIG. 5

U.S. Patent

May 9, 2006

Sheet 7 of 10

US 7,040,697 B1




FIG. 6B

FIG. 6A




FIG. 6C

U.S. Patent

May 9, 2006

Sheet 9 of 10

US 7,040,697 B1




FIG. 7

U.S. Patent

May 9, 2006

Sheet 10 of 10

US 7,040,697 B1




FIG. 8

US 7,040,697 B1

1

**HEADREST HAVING AN INTEGRATED  
VIDEO SCREEN**

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to motor vehicles and, in particular, to a headrest for motor vehicle seats having an integrated video screen mounted therein.

## 2. Description of the Related Art

Seat back video monitors are becoming increasingly popular in vehicles. Originally, these entertainment systems were largely confined to airplanes, however, recently, these systems have become much more popular with cars, trucks and SUVs. These entertainment systems provide the opportunity for passengers to view entertainment or educational video programs during long trips.

Typically, these systems have been installed as aftermarket products where the seat back is modified to accept the video display device, however, more of these systems are being installed as original equipment. Unfortunately, existing systems are often difficult and labor intensive to mount, particularly as an aftermarket product and are also subject to being dislodged.

Generally, the devices are mounted on the outer surface of the seat back where they protrude. In many vehicles, the space between seats and seat backs is limited, hence the protruding video display unit can inhibit the ability of passengers to easily get into and out of the vehicles. Moreover, passenger contact with the protruding video display screen may result in the screens being inadvertently dislodged.

A further difficulty with many existing video display unit designs is that they are not well secured to the seat. This is particularly the case for designs that allow the video display unit to pivot about an axis to improve the viewing angle of the passenger. One common way that these display units are installed is that a bucket is installed into the seat and the peripheral rim of the bucket includes openings that receive pivot posts that extend outward from the housing of the display unit. The pivot posts are positioned within the openings and keepers or caps are then positioned in the openings to prevent the pivot posts from being removed from the openings.

In these designs, the keepers or caps are generally press fit and are exposed to the passenger. Hence, inadvertent contact may result in the keepers or caps being dislodged. Moreover, many of the passengers are children who, through boredom, may attempt to remove the keepers which can result in the video display being dislodged and potentially damaged.

Hence, from the foregoing, there is a need for a seat back video display system and method of mounting that provides more secure mounting of the video display unit. To this end, there is a need for an assembly that is less likely to be dislodged through inadvertent contact and does not have exposed detachable mounting components.

## SUMMARY OF THE INVENTION

The aforementioned needs may be satisfied by a seat back video display assembly adapted to be positioned in the back of a vehicle seat having an outer skin cover. In one aspect, the assembly may comprise a receptacle member having sidewalls and a back wall so as to define an opening, wherein the receptacle member is adapted to be positioned in the back of the vehicle seat. In addition the assembly may

2

further comprise a carrier member having sidewalls and a back wall so as to define an opening, wherein the carrier member includes at least one fastener that extends from the back wall of the carrier member and engages with the back wall of the receptacle member to secure the carrier member into the receptacle member, and a video display unit that is sized so as to be positioned secured within the opening in the carrier member, wherein the video display unit provides video signals.

Additionally, in one embodiment, the at least one fastener may comprise a plurality of fasteners that include a central member that extends outward from back wall of the carrier member and a plurality of flexible engagement members attached to the central member, wherein the flexible engagement members are deformable so as to allow insertion of the central member into the openings in the back wall of the receptacle member, and wherein the flexible engagement members are biased outward so as to inhibit removal of the central member from the openings in the back wall of the receptacle member. Also, the video display unit may be pivotally attached to the carrier member such that the plane of the video display unit can be adjusted by a user about a pivot point or axis, wherein the video display unit may be pivotable about a substantially horizontal pivot axis, a substantially vertical pivot axis, or pivot point that allows a continuous range of pivotal motion about the pivot point. Also, the openings may be positioned in the sidewalls of the receptacle member and the plurality of capture members are positioned within the openings, and wherein the plurality of capture members define a pointed surface that engages with the outer skin and inhibits removal of the outer skin from the opening defined by the receptacle member so as to securely fasten the outer skin to the receptacle member.

Additionally, in certain embodiments, the seat back video display assembly includes a screen cover that is dimensioned to cover the video display unit such that the screen cover can disengageably cover the screen of the video display unit to occlude the screen. The screen cover can include an impact attenuating material, a rigid protective layer, or any combination thereof.

The aforementioned needs may also be satisfied by a vehicle seat assembly having a seat back display. In one aspect, the vehicle seat assembly may comprise a vehicle seat adapted to receive an occupant during travel of a vehicle, the vehicle seat defining a seat back with an outer contour and a skin, and a receptacle member having sidewalls and a back wall to as to define an opening, wherein the receptacle member is mounted in the seat back of the vehicle seat such that the sidewalls are located at or below the outer contour of the seat back. In addition, the vehicle seat assembly may further comprise a video display unit mounted within the receptacle member, wherein the video display unit is generally planar with the outer plane being mounted at or below the outer contour of the seat back.

Moreover, the aforementioned needs may also be satisfied by a method of installing a video display unit into a seat back of a vehicle seat. In one embodiment, the method may comprise cutting an opening through an outer skin of the seat back, forming an aperture in the seat back, and positioning a receptacle in the aperture such that the receptacle is mounted at or below the level of the seat back. In addition, the method may comprise securing the video display unit to a carrier, and mounting the carrier into the receptacle such that an upper surface of the video display unit is mounted below the outer surface of the seat back. These and other objects and advantages of the present invention will become



US 7,040,697 B1

3

more fully apparent from the following description taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates an adjustable headrest for a motor vehicle seat having an integrated video screen mounted therein.

FIG. 1B illustrates a fixed headrest for a motor vehicle seat having the integrated video screen of FIG. 1A mounted therein.

FIG. 2 illustrates a side view of the adjustable headrest shown in FIG. 1A having the integrated video screen mounted therein with a recessed orientation.

FIGS. 3A, 3B illustrate a cross-sectional view of the adjustable headrest shown in FIG. 1A having the integrated video screen mounted therein with a screen cover.

FIG. 4 illustrates a cross-sectional view of the integrated video screen being mounted to the headrest via a carrier receptacle, a carrier member, and a plurality of fasteners.

FIG. 5 illustrates an perspective view of the integrated video screen being mounted to the headrest via the carrier member and the plurality of fasteners of FIG. 4.

FIGS. 6A, 6B illustrate a perspective view of mounting the integrated video screen to the carrier member.

FIG. 6C illustrates a side view of mounting the integrated video screen to the carrier member via pivot member.

FIG. 7 illustrates a perspective view of mounting the integrated video screen to the adjustable headrest of FIG. 1A.

FIG. 8 illustrates a cross-sectional view of the video screen mounted to the headrest, wherein an outer skin from the headrest is secured to the carrier receptacle.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made to the drawings wherein like numerals refer to like parts throughout. A headrest for motor vehicle seats having an integrated video screen mounted therein in a flush or recessed manner will be described in greater detail herein below with reference to the drawings. In one aspect, it should be appreciated that the term motor vehicle seats refers to a plurality of generally known motor vehicles seats, such as those manufactured for automobiles, buses, boats, cars, semi-trucks, etc., wherein the following discussion can be similarly applied to these various types of motor vehicle seats without departing from scope of the present teachings. In addition, the following discussion refers to mounting the integrated video screen to the headrest of motor vehicle seats but may also be applied to other various component features of motor vehicle seats, such as the seat back, without departing from the scope of the present teachings.

FIG. 1A illustrates an adjustable headrest 100 for a first motor vehicle seat 102 having an integrated video screen 104 mounted therein. As illustrated in FIG. 1A, the adjustable headrest 100 is coupled to the seat 102 via posts 106 that extend therefrom and allow vertical adjustment of the adjustable headrest 100 with respect to the seat 102 in a generally known manner. FIG. 1B illustrates a fixed headrest 110 for a second motor vehicle seat 112 having the integrated video screen 104 mounted therein. In one embodiment, the video screen 104 is mounted within a headrest bun 106, 116 that is adapted to receive the video screen 104 for firm attachment therein in a manner that will be described in greater detail herein below. In addition, as will be described

4

in greater detail herein below, the video screen 102 is mounted such that a front surface 120 of the video screen 104 is either flush or recessed from a contour 122 of the headrest 100, 110.

In one embodiment, the video screen 104 comprises a generally known LCD (liquid crystal display) monitor or terminal that can be electrically coupled to a video entertainment system so as to receive video signals therefrom for viewing of movies, television, internet web pages, video games, etc. As illustrated, the video screen 104 is generally rectangular in shape with the planar front surface 120 that is viewable by a user. In one aspect, it should be appreciated that the degree of recessed depth (with no depth comprising a flush mount) of the integrated video screen 104 and the manner in which the contour 122 of the seat 102, 112 is shaped may be selected such that the shape (side view, for example) of the headrest 100, 110 with the integrated video screen 104 mounted therein is generally similar to the shape of the headrest 100, 110 without the integrated video screen 104. Moreover, it should be appreciated that the motor vehicle seats 102, 112 may comprise any one of a number of various types or models of generally known motor vehicle seats without departing from the scope of the present invention.

FIG. 2 illustrates a side view of the adjustable headrest 100 shown in FIG. 1A having the integrated video screen 104 mounted therein with a recessed orientation. It should be appreciated that the following discussion is with respect to the adjustable headrest 100 of FIG. 1A but may be similarly applied to the fixed headrest 110 of FIG. 1B without departing from the scope of the present teachings.

FIG. 2 further illustrates the side view shape or contour 122 of the headrest 100. As illustrated in FIG. 2, the contour 122 of the headrest 100 is maintained due to the recessed orientation of the video screen 104 within the headrest bun 106. In addition, an opening 130 is formed in a rear section 132 of the headrest 100 so as to define a substantially rectangular interior region 136 within the headrest bun 106 below an outer surface 134 of the headrest 100. As further illustrated in FIG. 2, the video screen 104 can then be positioned adjacent the opening 130 so as to be firmly positioned within the interior region 136 of the headrest bun 106. Moreover, the recessed orientation may be defined by a depth 138 between the front surface 120 of the video screen 104 and the outer surface 134 of the headrest 100. The depth 138 therebetween may vary in magnitude depending on the thickness of the headrest bun 106 and/or the internal structural characteristics of the headrest 100, which may vary with respect to the type or model of motor vehicle seat used. In one aspect, the depth 138 of the recessed orientation may comprise a magnitude of approximately zero so as to define a flush mounted video screen 104, wherein the front surface 1120 of the video screen 104 is substantially aligned with the outer surface 134 of the headrest 100.

FIG. 3A illustrates a cross-sectional view of the adjustable headrest 102 shown in FIGS. 1A having the integrated video screen 104 mounted therein with the recessed orientation shown in FIG. 2 and a screen cover 140. In one embodiment, the screen cover 140 is coupled to the rear section 132 of the headrest 100 via a hinge 142 so as to overlie the video screen 104 and at least part of the opening 130 formed therein. The screen cover 140 may comprise generally rectangular shape and is oriented generally parallel to the front surface 120 of the video screen 104 so as to temporarily occlude the video screen 104. In one aspect, as further illustrated in FIG. 3A, the screen cover 140 can be positioned adjacent the opening

US 7,040,697 B1

5

130 so as to substantially align with the outer surface 134 of the headrest 100 thus forming a flush mounting therewith. It should be appreciated that the screen cover 140 may be positioned within the opening 130 so as to be recessed with respect to the outer surface 134 of the headrest 100 without departing from the scope of the present teachings. Moreover, the screen cover 140 may comprise a rigid material, such as plastic, metal, etc. Alternatively, in another aspect, the screen cover 140 may comprise a piece or flap of material from an outer skin 230 (FIG. 8) of the motor vehicle seat 102 that is attached to the headrest 100 adjacent the lower side of the video screen 104.

In still another aspect, as illustrated in FIG. 3B, the screen cover 140 may comprise an impact attenuating section 143 comprising a material such as foam, various types of padding, an air cushion, etc. so as to soften the force of an impact from an object. For example, during a car accident, a person's head may be propelled towards the screen cover 140, wherein the impact attenuating material may soften the impact to the headrest 102 to thereby protect the person's head and the video screen 104 from damage.

Also, in one embodiment, the video screen 104 can be viewed by opening the screen cover 140 or temporarily occluded by closing the screen cover 140. Hence, the screen cover 140 can be outwardly rotated about the hinge 142 in a first direction 144 to openly view the video screen 104, or the screen cover 140 can be inwardly rotated about the hinge 142 in a second direction 144 opposite the first direction 144 to temporarily occlude the video screen 104. Advantageously, the screen cover 104, when closed, conceals the video screen 104 from view thus, in some situations, functions as a thief deterrent.

Moreover, in one aspect, the recessed configuration of the video screen 104 facilitates the manner in which the screen cover 140 may be deployed. For example, the video screen 104 may not physically interfere with the closing of the screen cover 140. In addition, as illustrated in FIGS. 3A, 3B, the screen cover 140 is intended to "hide" the video screen 104 from outside observers, thereby reducing the probability that the video screen 104 will be a target of theft. As further illustrated in FIGS. 3A, 3B, the screen cover 140 may further comprise a means for engagement 144 that allows the screen cover 140 to remain in the "up" or closed configuration. In general, it should be appreciated that some possible means for achieving such an engagement include but are not limited to magnetic strips, mechanical clips, velcro strips, and the like.

FIG. 4 illustrates a cross-sectional view of the integrated video screen 104 being mounted to the headrest 100 via a carrier receptacle 150, a carrier member 160, and first fasteners 170. FIG. 5 illustrates a perspective view of the integrated video screen 104 being mounted to the headrest 100 via the carrier receptacle 150, the carrier member 152, and the first fasteners 170. In one embodiment, the carrier receptacle 150 comprises a plurality of planar sidewalls 152 and a rear planar wall 154 that are joined together in a manner so as to form a substantially rectangular outer structure 156 having an inner recessed region 158 that is adapted to receive the carrier member 152 therein. Similarly, the carrier member 152 comprises a plurality of planar sidewalls 162 and a rear planar wall 164 that are joined together in a manner so as to form a substantially rectangular outer structure 166 having an inner recessed region 168 that is adapted to receive the video screen 104 therein.

As illustrated in FIG. 4, the video screen 104 may be mounted within the carrier member 160 via side fasteners 180 (shown in FIGS. 6A, 6B) and then the carrier member

6

152 is mounted within the carrier receptacle 150 via the first fasteners 170 so as to simplify the mounting of the video screen 104 to the headrest 100 including the headrest bun 106. In one aspect, the first fasteners 170 may comprise a plurality of flexible engagement members 172 that extend therefrom so as to mechanically couple with a plurality of mounting apertures 174 (FIG. 5) formed in the rear wall 154 of the carrier receptacle 150. The first fasteners 170 may further comprise a central member 173 that extends outward from the rear wall 164 of the carrier member 160. Also, the flexible engagement members 172 are attached to the central member 173, wherein the flexible engagement members 172 are deformable so as to allow insertion of the central member 173 into the mounting apertures 174 in the rear wall 164 of the receptacle member 150. Moreover, the flexible engagement members 170 are biased outward so as to inhibit removal of the central member 173 from the mounting apertures 174 in the rear wall 154 of the receptacle member 150. In addition, the first fasteners 170 comprise a head 176 that abuts the rear wall 164 of the carrier member 152 and is positioned through a plurality of second apertures 178 formed in the rear wall 164 of the carrier member 152.

Advantageously, the video screen 104 can be mounted to the headrest 100 via the carrier receptacle 150 and the carrier member 152 without using external fasteners that may be seen. Hence, the video screen 104 can be mounted to the headrest 100 in a more aesthetically appealing manner, wherein the front surface 120 of the video screen 104 recessed or flush mounted with respect to the outer surface 134 of the headrest 100, and wherein the first and second fasteners 170, 180 are concealed from view.

As illustrated in FIG. 5, the sidewalls 152 of the carrier receptacle 150 each comprise at least one sidewall aperture 200 having at least one serrated tooth 202 protruding from an interior sidewall 204. In one embodiment, the at least one serrated tooth 202 is triangular in shape having a pointed tip 206 that projects outward from the interior sidewall 204 in a horizontal manner. It should be appreciated that the serrated tooth 202 may comprise any one of a number of various shapes known in the art without departing from the scope of the present teachings. Additionally, as will be shown in FIG. 8, the pointed tip 234 engages with the outer skin 230 (FIG. 8) and inhibits removal of the outer skin 230 from the at least one sidewall aperture 200 formed in the carrier receptacle 150. Advantageously, as will be described in greater detail herein below, the serrated tooth 200 allows outer skin from the motor vehicle seat 102, 112 to be attached to the carrier receptacle 150 by wrapping the outer skin around the planar sidewalls 152 and into the recessed region 158 of the carrier receptacle 150 and then securing the outer skin to the serrated tooth 200.

FIG. 6A illustrates a perspective view of attaching the integrated video screen 104 to the carrier member 152 via the second fasteners 180. In one embodiment, the planar sidewalls 162 of the carrier member 160 comprise pivot apertures 184 that allow the video display 104 to be mounted to the carrier member 160. Also, the pivot apertures 184 are adapted to rotatably receive the second fasteners 180. As illustrated in FIG. 6A, the second fasteners 180 comprise a threaded region 186 that mechanically couples to threaded apertures 196 (FIG. 7) formed in the video screen 104 in a generally known manner so as to be securely attached thereto. Moreover, the second fasteners 180 further comprise a head 182 and a smooth pivot region 188 interposed between the threaded region and the head 182.

In one aspect, the pivot region 188 of the second fastener 180 rotatably communicates with the pivot aperture 184 of

US 7,040,697 B1

7

the carrier member 160 to thereby allow the video screen 104 to pivot or tilt with respect to the carrier member 160 and/or the headrest 100 along a horizontal pivot axis 190 defined by the horizontally mounted second fasteners 180. Hence, the video screen 104 is pivotally attached to the carrier member 160 such that the plane of the video screen 104 can be adjusted with respect to the headrest 100 by a user about the defined horizontal pivot axis 190. Advantageously, the horizontal pivot axis 190 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

FIG. 6B further illustrates a perspective view of attaching the integrated video screen 104 to the carrier member 152 via the second fasteners 180. In one embodiment, as illustrated in FIG. 6B, the second fasteners 180 can be mounted vertically through the planar sidewalls 162 of the carrier member 160. The pivot region 188 of the vertically mounted second fasteners 180 rotatably communicates with the pivot aperture 184 of the carrier member 160 to thereby allow the video screen 104 to pivot or tilt side-to-side with respect to the carrier member 160 and/or the headrest 100 along a vertical pivot axis 191 defined by the vertically mounted second fasteners 180. Hence, the video screen 104 is pivotally attached to the carrier member 160 such that the plane of the video screen 104 can be adjusted with respect to the headrest 100 by a user about the vertical pivot axis 191. Advantageously, the vertical pivot axis 191 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

In one aspect, it should be appreciated that the second fasteners 180 may comprise generally known screws, such as sheet metal screws, without departing from the scope of the present invention. It should also be appreciated that the pivot region 188 of the second fasteners 180 may be threaded in a manner such that the video screen 104 can still pivot with respect to the carrier member 150 without departing from the scope of the present invention.

FIG. 6C illustrates a view of attaching the integrated video screen 104 to the carrier member 152 via a pivot member 240. In one embodiment, as illustrated in FIG. 6C, the pivot member 240 comprises a spherical ball 242 attached to the video screen 104 via a shaft 244 and a plate 246. The spherical ball 242 is positioned within a spherical receptacle 248 formed in the rear wall 164 of the carrier member 160. As illustrated in FIG. 6C, the rear wall 164 of the carrier member 160 may be dimensioned so as to accommodate the spherical receptacle 248. In one aspect, the plate 246 of the pivot member 240 may be attached to the video screen 104 using an adhesive, such as epoxy or glue, or fasteners, such as screws or bolts. In addition, the shaft 244 distally extends from the plate 246 towards the spherical receptacle 248 of the carrier member 160. Also, the shaft 244 and the spherical ball 242 may be formed as an integral part of the plate 246 or may be formed separately and interconnected to the plate 246 via an adhesive or fasteners.

Moreover, once the pivot member 240 is attached to the video screen 104 in a manner as previously described, the spherical ball 242 of the pivot member 240 can be pressed to fit within the spherical receptacle 248 formed in the rear wall 164 of the carrier member 160. In one aspect, the spherical ball 242 may be sized at least less than the size of the spherical receptacle 248 so as to allow rotational movement therein. Advantageously, the resulting interconnection between the spherical ball 242 of the pivot member 240 and the spherical receptacle 248 of the carrier member 160

8

defines a pivot point 250 to thereby allow the video screen 104 to pivot, tilt, or rotate in a multi-directional manner with respect to the defined pivot point 250. Therefore, the defined pivot point 250 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

FIG. 7 illustrates a perspective view of mounting the integrated video screen 104 to the headrest 100 of FIG. 1A. In one embodiment, as illustrated in FIG. 7, the opening 130 is formed in the headrest bun 106 so as to define the substantially rectangular interior region 136 and to receive the carrier receptacle 150. The carrier receptacle 150 can then be positioned within the opening 130 so that the planar sidewalls 152 and the planar rear wall 154 abut the interior walls 226 of the mounting recess 136 formed in the headrest bun 106. In one embodiment, the carrier receptacle 150 can be secured to the headrest 100 via one or more third fasteners 220, such as screws, machine screws, sheet metal screws, etc. As illustrated in FIG. 7, the third fasteners 220 are positioned through rear wall apertures 222 formed in the rear wall 154 of the carrier receptacle 150 and coupled to rear mounting apertures 224 formed in a back wall 226 of the mounting recess 136 of the headrest bun 106. Advantageously, the third fasteners 220 can be securely attached to a structural component (not shown) of the headrest 100, such as an internal framework member of the headrest 100, so as to form a rigid attachment between the carrier receptacle 150 and the headrest 100.

In addition, the video screen 104 may be mounted to the carrier member 160 so as to pivot with respect thereto in a manner as previously described with reference to FIGS. 6A, 6B, 6C. Following, the carrier member 160 including the video screen 104 can then be mounted to the carrier receptacle 150 via the first fasteners 170 in a manner as previously described with reference to FIG. 4. Advantageously, this method of attaching the video screen 104 to the headrest 100 via the carrier receptacle 150, the carrier member 160, and the fasteners 170, 180 allows the video screen 104 to be securely mounted to the headrest 100 while providing a means for pivoting the video screen 104 with respect to the headrest 100 so as to improve the viewing range by a user.

FIG. 8 illustrates a cross-sectional view of the video screen 104 mounted to the headrest 100, wherein the outer skin 230 of the headrest 100 of the motor vehicle seat 102 is attached to the carrier receptacle 150 and the carrier member 160 with the video screen 104 mounted therein is mounted within the mounting recess 136 of the carrier receptacle 150. As is generally known, many motor vehicle car seats comprise the illustrated outer skin 230, such as fabric, leather, upholstery, vinyl, etc., that provides a outer surface 232 for a user to lean against or rest upon. In one aspect, when mounting the integrated video screen 104 into the headrest 100 of the motor vehicle seat 102, the outer skin 230 is adapted to accommodate the video screen 104 including the carrier receptacle 150. In some situations, one or more flaps 234 can be formed in the outer skin 230 and attached to the one or more serrated teeth 202 formed in the planar sidewalls 152 of the carrier receptacle 150.

As further illustrated in FIG. 8, the carrier receptacle 150 may be positioned within the mounting recess 136 formed in the headrest bun 106, and then the outer skin 230 is secured to the serrated teeth 202 via the flaps 234 formed therein by hooking the flaps 234 to one or more of the serrated teeth 202. Once the outer skin 230 is attached to the serrated teeth 202 via the flaps 234, the carrier member 160 is firmly pressed within the mounting recess 136 of the headrest bun

US 7,040,697 B1

9

106 so that the first fasteners 170 couple to the mounting apertures 174 formed in the rear wall 154 of the carrier receptacle 150.

Advantageously, this interconnection between the carrier member 160 and carrier receptacle 150 provides a quick and easy means for mounting of the video screen 104 to the headrest 100. In addition, the pressed fit of the outer skin between the carrier member 160 and the carrier receptacle 150 further secures the outer skin of the motor vehicle seat 102 to the carrier receptacle 150. As a result, the outer skin is securely held to the carrier receptacle 150 via the one or more serrated teeth 202 formed in the planar sidewalls 152 of the carrier receptacle 150 and the pressed fit of the carrier member 160 within the mourning recess 136 of the carrier receptacle 150.

Although the foregoing description has shown, described and pointed out the fundamental novel features of the invention, it will be understood that various omissions, substitutions, and changes in the form of the detail of the apparatus as illustrated, as well as the uses thereof, may be made by those skilled in the art, without departing from the spirit or scope of the present invention. Consequently, the scope of the invention should not be limited to the foregoing discussion, but should be defined by the appended claims.

What is claimed is:

1. A seat back video display assembly adapted to be positioned in a back of a vehicle seat having an outer skin, the assembly comprising:

a receptacle member having sidewalls and a back wall so as to define an opening wherein the receptacle member is adapted to be positioned in the back of the vehicle seat wherein the opening is facing away from the back of the vehicle seat when the receptacle member is positioned within the back of the vehicle seat and wherein the receptacle member includes at least one securing opening formed in the back wall of the receptacle member;

a carrier member having sidewalls and a back wall so as to define an opening, wherein the carrier member includes at least one fastener that is coupled to the back wall that extends from the back wall of the carrier member and engages with the at least one securing opening in the back wall of the receptacle member to secure the carrier member into the receptacle member and wherein the opening in the carrier member is facing away from the back of the vehicle seat when the carrier member is positioned within the receptacle member; and

a video display unit that is sized so as to be positioned secured within the opening in the carrier member and substantially conceal the at least one fastener, wherein the video display unit provides video signals wherein the video display unit is pre-assembled into the carrier member so that the combined video display unit and the carrier member can be simultaneously secured within the receptacle member by positioning the carrier member in the receptacle member such that the back wall of the carrier member is flush with the back wall of the receptacle member and the at least one fastener of the carrier member is pushed through the at least one securing opening.

2. The assembly of claim 1, wherein the receptacle member includes a plurality of openings positioned within the back wall that receive the fasteners of the carrier member.

3. The assembly of claim 2, wherein the at least one fastener comprises a plurality of fasteners that include a

10

central member that extends outward from back wall of the carrier member and a plurality of flexible engagement members attached to the central member, wherein the flexible engagement members are deformable so as to allow insertion of the central member into the openings in the back wall of the receptacle member, and wherein the flexible engagement members are biased outward so as to inhibit removal of the central member from the openings in the back wall of the receptacle member.

4. The assembly of claim 1, wherein the video display unit defines a plane and is pivotally attached to the carrier member such that the plane of the video display unit can be adjusted by a user about a pivot axis.

5. The assembly of claim 4, wherein the video display unit is pivotable about a substantially horizontal axis.

6. The assembly of claim 4, wherein at least a first and second fasteners are positioned through the carrier into the display unit so as to secure the video display unit to the carrier member prior to installation of the carrier into the receptacle member, and wherein the at least first and second fasteners engage with the video display unit so as to define a pivot axis.

7. The assembly of claim 1, wherein the receptacle member includes an outer lip and a plurality of outer skin capture members that engage with the outer skin of the seat back following installation such that the outer skin is extended over the outer lip of the receptacle member and secured to the outer skin capture members.

8. The assembly of claim 7, wherein openings are positioned in the sidewalls of the receptacle member and the plurality of capture members are positioned within the openings, and wherein the plurality of capture members define a pointed surface that engages with the outer skin and inhibits removal of the outer skin from the opening defined by the receptacle member.

9. The assembly of claim 1, further comprising a screen cover that is dimensioned to cover the video display unit in a first configuration following installation into the seat back, and wherein the cover is selectively disengagable so as to allow visual access to the video display unit.

10. The assembly of claim 9, wherein the cover includes an impact attenuating material.

11. The assembly of claim 9, wherein the cover includes a generally rigid layer to provide physical protection of the video display unit.

12. A vehicle seat assembly having a seat back display, the assembly comprising:

a vehicle seat adapted to receive an occupant during travel of a vehicle, the vehicle seat defining a seat back with an outer contour and an outer skin;

a receptacle member having sidewalls and a back wall so as to define an opening, wherein the receptacle member is mounted in the seat back of the vehicle seat such that the sidewalls are located at or below the outer contour of the seat back and wherein the receptacle member includes at least one opening in the side walls and at least one outer skin capture member having a pointed surface positioned within the at least one opening such that the at least one outer skin capture member captures the outer skin of the seat back to inhibit removal of the outer skin from the at least one opening; and

a video display unit mounted within the receptacle member, wherein the video display unit is generally planar with an outer plane that is at or below the outer contour of the vehicle seat.

13. The assembly of claim 12, further comprising a carrier member having sidewalls and a back wall so as to define an

US 7,040,697 B1

11

opening, wherein the carrier member includes at least one fastener that extends from the back wall of the carrier member and engages with the back wall of the receptacle member to secure the carrier member into the receptacle member, and wherein the video display unit is positioned within the carrier unit.

14. The assembly of claim 13, wherein the receptacle member includes a plurality of openings positioned within the back wall that receive the fasteners of the carrier member.

15. The assembly of claim 14, wherein the at least one fastener comprises a plurality of fasteners that include a central member that extends outward from back wall of the carrier member and a plurality of flexible engagement members attached to the central member, wherein the flexible engagement members are deformable so as to allow insertion of the central member into the openings in the back wall of the receptacle member, and wherein the flexible engagement members are biased outward so as to inhibit removal of the central member from the openings in the back wall of the receptacle member.

16. The assembly of claim 13, wherein the video display unit is pivotally attached to the carrier member such that the outer plane of the video display unit can be adjusted by a user about a pivot axis.

17. The assembly of claim 16, wherein the video display unit is pivotable about a substantially horizontal axis.

18. The assembly of claim 16, wherein at least a first and second fasteners are positioned through the carrier into the display unit so as to secure the video display unit to the

12

carrier member prior to installation of the carrier into the receptacle member, and wherein the at least first and second fasteners engage with the video display unit so as to define a pivot axis.

19. The assembly of claim 12, further comprising a screen cover that is dimensioned to cover the video display unit in a first configuration following installation into the seat back, and wherein the cover is selectively disengagable so as to allow visual access to the video display unit.

20. The assembly of claim 19, wherein the screen cover comprises at least a portion of the outer skin that is attached to the seat back adjacent a bottom side of the video display unit and a fastener assembly attached to the portion of outer skin and the seat back adjacent a top side of the video display unit such that the portion of outer skin can hide the video display unit from view.

21. The assembly of claim 19, wherein the screen cover includes an impact attenuating material selected from the group consisting of foam, padding, and an air cushion.

22. The assembly of claim 19, wherein the screen cover includes a generally rigid layer to provide physical protection of the video display unit.

23. The assembly of claim 12, wherein the outer skin is selected from the group consisting of fabric, leather, upholstery, and vinyl.

24. The assembly of claim 12, wherein the vehicle seat includes a head rest and the receptacle member is positioned within the head rest.

\* \* \* \* \*

**EXHIBIT B**



US007407227B1

(12) **United States Patent**  
**Tuccinardi et al.**

(10) **Patent No.:** **US 7,407,227 B1**  
(45) **Date of Patent:** **\*Aug. 5, 2008**

(54) **HEADREST HAVING AN INTEGRATED VIDEO SCREEN**

4,584,603 A 4/1986 Harrison  
4,635,110 A 1/1987 Weinblatt  
4,647,980 A 3/1987 Steventon et al.

(75) Inventors: **Eugene M. Tuccinardi**, Temecula, CA (US); **Ernesto R. Haack**, Perris, CA (US); **Robert Murphy**, Lake Elsinore, CA (US); **Frank Barrese**, Temecula, CA (US); **Roel C. Espina**, Loma Linda, CA (US); **Jon A. Molo**, Ontario (CA); **Theo Zoetemelk**, Riverside, CA (US)

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE 3637772 A1 5/1988

(Continued)

**OTHER PUBLICATIONS**

WO 02/074577. Jost, Gilbert. Headrest, Particularly for a Motor Vehicle Seat, Sep. 26, 2002.\*

(Continued)

*Primary Examiner*—Sarah B McParlin

(74) *Attorney, Agent, or Firm*—Knobbe, Martens, Olson & Bear, LLP

(73) Assignee: **Timely Innovations, L.P.**, Temecula, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/415,696**

(57) **ABSTRACT**

(22) Filed: **May 2, 2006**

**Related U.S. Application Data**

(63) Continuation of application No. 10/395,870, filed on Mar. 20, 2003, now Pat. No. 7,040,697.

(51) **Int. Cl.**  
*A47C 7/62* (2006.01)

(52) **U.S. Cl.** ..... 297/217.3; 297/188.04

(58) **Field of Classification Search** ..... 297/217.3, 297/188.04, 188.07, 408, 391; 5/643, 645  
See application file for complete search history.


(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,004,815 A 10/1961 O’Kain et al.

A seat back video display assembly adapted to be positioned in the back of a vehicle seat having an outer skin cover. In one aspect, the assembly may comprise a receptacle member having sidewalls and a back wall so as to define an opening wherein the receptacle member is adapted to be positioned in the back of the vehicle seat. In addition, the assembly may further comprise a carrier member having sidewalls and a back wall so as to define an opening, wherein the carrier member includes at least one fastener that extends from the back wall of the carrier member and engages with the back wall of the receptacle member to secure the carrier member into the receptacle member. Moreover, the assembly may still further comprise a video display unit that is sized so as to be positioned secured within the opening in the carrier member, wherein the video display unit provides video signals.

**14 Claims, 10 Drawing Sheets**



US 7,407,227 B1

Page 2

U.S. PATENT DOCUMENTS

4,681,366	A *	7/1987	Lobanoff	297/188.06
4,756,528	A	7/1988	Umashankar	
4,776,739	A *	10/1988	Hamman	411/510
4,788,588	A	11/1988	Tomita	
4,866,515	A	9/1989	Tagawa et al.	
RE33,423	E	11/1990	Lobanoff	
4,983,951	A	1/1991	Igarashi et al.	
5,267,775	A *	12/1993	Nguyen	297/217.3
5,292,174	A	3/1994	Ohnuma	
5,293,244	A	3/1994	Kawaguchi	
5,311,302	A	5/1994	Berry et al.	
5,333,416	A	8/1994	Harris et al.	
5,359,349	A	10/1994	Jambor et al.	
5,507,556	A *	4/1996	Dixon	297/217.3
5,529,265	A	6/1996	Sakurai	
5,555,466	A	9/1996	Scribner et al.	
5,640,297	A	6/1997	Labaze	
5,713,633	A	2/1998	Lu	
D398,921	S	9/1998	Rosen	
5,842,715	A	12/1998	Jones	
5,953,784	A *	9/1999	Suzuki et al.	15/209.1
6,024,027	A	2/2000	Esmaili	
6,055,478	A	4/2000	Heron	
D434,400	S	11/2000	Rosen	
6,199,948	B1	3/2001	Bush et al.	
6,216,927	B1	4/2001	Mcritt	
6,250,967	B1	6/2001	Chu	
6,292,236	B1	9/2001	Rosen	
6,305,046	B1 *	10/2001	Kingry et al.	15/231
6,339,455	B1	1/2002	Allan et al.	
6,394,551	B1	5/2002	Beukema	
6,406,334	B2	6/2002	Chu	
6,409,242	B1	6/2002	Chang	
6,480,243	B2	11/2002	Yamamoto	
6,669,285	B1 *	12/2003	Park et al.	297/217.3
6,739,654	B1	5/2004	Shen et al.	
6,750,599	B2	6/2004	Tajima	
6,755,491	B2	6/2004	McElheney	
6,762,929	B2	7/2004	Sawyer	
6,883,870	B2 *	4/2005	Jost	297/391
7,036,879	B2	5/2006	Chang	
7,038,581	B2	5/2006	Kendall et al.	

7,040,697	B1 *	5/2006	Tuccinardi et al.	297/217.3
7,044,546	B2	5/2006	Chang	
2001/0008266	A1	7/2001	Lambert	
2003/0025367	A1 *	2/2003	Boudinot	297/217.3
2004/0007906	A1	1/2004	Park et al.	
2004/0032543	A1 *	2/2004	Chang	348/837
2004/0160096	A1	8/2004	Boudinot	
2005/0099042	A1	5/2005	Vitito	
2005/0242638	A1	11/2005	Vitito	
2007/0001492	A1	1/2007	Chang	
2007/0102973	A1	5/2007	Vitito	

FOREIGN PATENT DOCUMENTS

DE	19601582	A1	1/1996
FR	2764563	A1	12/1998
JP	01094048	A2	4/1989

OTHER PUBLICATIONS

Office Action of Jul. 27, 2007 for U.S. Appl. No. 10/819,341.  
 Response to Office Action of Jul. 27, 2007 for U.S. Appl. No. 10/819,341.  
 Office Action of Jan. 31, 2007 for U.S. Appl. No. 11/415,918.  
 Response to Restriction Requirement of May 10, 2007 for U.S. Appl. No. 10/819,341.  
 Restriction Requirement of May 10, 2007 for U.S. Appl. No. 10/819,341.  
 Response to Office Action of Jan. 31, 2007 for U.S. Appl. No. 11/415,918.  
 Final Office Action of Jul. 30, 2007 for U.S. Appl. No. 11/415,918.  
 RCE and Response to Final Office Action of Jul. 30, 2007 for U.S. Appl. No. 11/415,918.  
 Restriction Requirement of Jul. 19, 2004 for U.S. Appl. No. 10/395,870.  
 Response to Restriction Requirement of Jul. 19, 2004 for U.S. Appl. No. 10/395,870.  
 Office Action of Sep. 27, 2004 for U.S. Appl. No. 10/395,870.  
 Response to Office Action of Sep. 27, 2004 for U.S. Appl. No. 10/395,870.  
 Final Office Action of May 3, 2005 for U.S. Appl. No. 10/395,870.  
 RCE & Response to Final Action of May 3, 2005 for U.S. Appl. No. 10/395,870.  
 Notice of Allowance of Dec. 6, 2005 for U.S. Appl. No. 10/395,870.

\* cited by examiner



U.S. Patent

Aug. 5, 2008

Sheet 1 of 10

US 7,407,227 B1




FIG. 1A

U.S. Patent

Aug. 5, 2008

Sheet 2 of 10

US 7,407,227 B1




FIG. 1B

U.S. Patent

Aug. 5, 2008

Sheet 3 of 10

US 7,407,227 B1




FIG. 3A




FIG. 2

U.S. Patent

Aug. 5, 2008

Sheet 4 of 10

US 7,407,227 B1




FIG. 3B




FIG. 4

U.S. Patent

Aug. 5, 2008

Sheet 6 of 10

US 7,407,227 B1




FIG. 5

U.S. Patent

Aug. 5, 2008

Sheet 7 of 10

US 7,407,227 B1




FIG. 6A




FIG. 6B

U.S. Patent

Aug. 5, 2008

Sheet 8 of 10

US 7,407,227 B1




FIG. 6C



U.S. Patent

Aug. 5, 2008

Sheet 9 of 10

US 7,407,227 B1




FIG. 7

U.S. Patent

Aug. 5, 2008

Sheet 10 of 10

US 7,407,227 B1




FIG. 8

US 7,407,227 B1

1

**HEADREST HAVING AN INTEGRATED  
VIDEO SCREEN**

## RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 10/395,870 filed Mar. 20, 2003 now U.S. Pat. No. 7,040,697, entitled "HEADREST HAVING AN INTEGRATED VIDEO SCREEN," which is hereby incorporated by reference herein in its entirety; and this application is related to U.S. application Ser. No. 10/819,341 filed Apr. 5, 2004, entitled "HEADREST/HEAD RESTRAINT HAVING AN INTEGRATED VIDEO SCREEN," and to U.S. application Ser. No. 11/415,918 filed concurrently with this application, entitled "HEADREST HAVING AN INTEGRATED VIDEO SCREEN," which is a divisional of the above-identified Ser. No. 10/395,870 application.

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

The present invention relates to motor vehicles and, in particular, to a headrest for motor vehicle seats having an integrated video screen mounted therein.

## 2. Description of the Related Art

Seat back video monitors are becoming increasingly popular in vehicles. Originally, these entertainment systems were largely confined to airplanes, however, recently, these systems have become much more popular with cars, trucks and SUVs. These entertainment systems provide the opportunity for passengers to view entertainment or educational video programs during long trips.

Typically, these systems have been installed as aftermarket products where the seat back is modified to accept the video display device, however, more of these systems are being installed as original equipment. Unfortunately, existing systems are often difficult and labor intensive to mount, particularly as an aftermarket product and are also subject to being dislodged.

Generally, the devices are mounted on the outer surface of the seat back where they protrude. In many vehicles, the space between seats and seat backs is limited, hence the protruding video display unit can inhibit the ability of passengers to easily get into and out of the vehicles. Moreover, passenger contact with the protruding video display screen may result in the screens being inadvertently dislodged.

A further difficulty with many existing video display unit designs is that they are not well secured to the seat. This is particularly the case for designs that allow the video display unit to pivot about an axis to improve the viewing angle of the passenger. One common way that these display units are installed is that a bucket is installed into the seat and the peripheral rim of the bucket includes openings that receive pivot posts that extend outward from the housing of the display unit. The pivot posts are positioned within the openings and keepers or caps are then positioned in the openings to prevent the pivot posts from being removed from the openings.

In these designs, the keepers or caps are generally press fit and are exposed to the passenger. Hence, inadvertent contact may result in the keepers or caps being dislodged. Moreover, many of the passengers are children who, through boredom, may attempt to remove the keepers which can result in the video display being dislodged and potentially damaged.

Hence, from the foregoing, there is a need for a seat back video display system and method of mounting that provides more secure mounting of the video display unit. To this end,

2

there is a need for an assembly that is less likely to be dislodged through inadvertent contact and does not have exposed detachable mounting components.

## SUMMARY OF THE INVENTION

The aforementioned needs may be satisfied by a seat back video display assembly adapted to be positioned in the back of a vehicle seat having an outer skin cover. In one aspect, the assembly may comprise a receptacle member having sidewalls and a back wall so as to define an opening, wherein the receptacle member is adapted to be positioned in the back of the vehicle seat. In addition the assembly may further comprise a carrier member having sidewalls and a back wall so as to define an opening, wherein the carrier member includes at least one fastener that extends from the back wall of the carrier member and engages with the back wall of the receptacle member to secure the carrier member into the receptacle member, and a video display unit that is sized so as to be positioned secured within the opening in the carrier member, wherein the video display unit provides video signals.

Additionally, in one embodiment, the at least one fastener may comprise a plurality of fasteners that include a central member that extends outward from back wall of the carrier member and a plurality of flexible engagement members attached to the central member, wherein the flexible engagement members are deformable so as to allow insertion of the central member into the openings in the back wall of the receptacle member, and wherein the flexible engagement members are biased outward so as to inhibit removal of the central member from the openings in the back wall of the receptacle member. Also, the video display unit may be pivotally attached to the carrier member such that the plane of the video display unit can be adjusted by a user about a pivot point or axis, wherein the video display unit may be pivotable about a substantially horizontal pivot axis, a substantially vertical pivot axis, or pivot point that allows a continuous range of pivotal motion about the pivot point. Also, the openings may be positioned in the sidewalls of the receptacle member and the plurality of capture members are positioned within the openings, and wherein the plurality of capture members define a pointed surface that engages with the outer skin and inhibits removal of the outer skin from the opening defined by the receptacle member so as to securely fasten the outer skin to the receptacle member.

Additionally, in certain embodiments, the seat back video display assembly includes a screen cover that is dimensioned to cover the video display unit such that the screen cover can disengageably cover the screen of the video display unit to occlude the screen. The screen cover can include an impact attenuating material, a rigid protective layer, or any combination thereof.

The aforementioned needs may also be satisfied by a vehicle seat assembly having a seat back display. In one aspect, the vehicle seat assembly may comprise a vehicle seat adapted to receive an occupant during travel of a vehicle, the vehicle seat defining a seat back with an outer contour and a skin, and a receptacle member having sidewalls and a back wall to as to define an opening, wherein the receptacle member is mounted in the seat back of the vehicle seat such that the sidewalls are located at or below the outer contour of the seat back. In addition, the vehicle seat assembly may further comprise a video display unit mounted within the receptacle member, wherein the video display unit is generally planar with the outer plane being mounted at or below the outer contour of the seat back.

US 7,407,227 B1

3

Moreover, the aforementioned needs may also be satisfied by a method of installing a video display unit into a seat back of a vehicle seat. In one embodiment, the method may comprise cutting an opening through an outer skin of the seat back, forming an aperture in the seat back, and positioning a receptacle in the aperture such that the receptacle is mounted at or below the level of the seat back. In addition, the method may comprise securing the video display unit to a carrier, and mounting the carrier into the receptacle such that an upper surface of the video display unit is mounted below the outer surface of the seat back. These and other objects and advantages of the present invention will become more fully apparent from the following description taken in conjunction with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates an adjustable headrest for a motor vehicle seat having an integrated video screen mounted therein.

FIG. 1B illustrates a fixed headrest for a motor vehicle seat having the integrated video screen of FIG. 1A mounted therein.

FIG. 2 illustrates a side view of the adjustable headrest shown in FIG. 1A having the integrated video screen mounted therein with a recessed orientation.

FIGS. 3A, 3B illustrate a cross-sectional view of the adjustable headrest shown in FIG. 1A having the integrated video screen mounted therein with a screen cover.

FIG. 4 illustrates a cross-sectional view of the integrated video screen being mounted to the headrest via a carrier receptacle, a carrier member, and a plurality of fasteners.

FIG. 5 illustrates a perspective view of the integrated video screen being mounted to the headrest via the carrier member and the plurality of fasteners of FIG. 4.

FIGS. 6A, 6B illustrate a perspective view of mounting the integrated video screen to the carrier member.

FIG. 6C illustrates a side view of mounting the integrated video screen to the carrier member via pivot member.

FIG. 7 illustrates a perspective view of mounting the integrated video screen to the adjustable headrest of FIG. 1A.

FIG. 8 illustrates a cross-sectional view of the video screen mounted to the headrest, wherein an outer skin from the headrest is secured to the carrier receptacle.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made to the drawings wherein like numerals refer to like parts throughout. A headrest for motor vehicle seats having an integrated video screen mounted therein in a flush or recessed manner will be described in greater detail herein below with reference to the drawings. In one aspect, it should be appreciated that the term motor vehicle seats refers to a plurality of generally known motor vehicles seats, such as those manufactured for automobiles, buses, boats, cars, semi-trucks, etc., wherein the following discussion can be similarly applied to these various types of motor vehicle seats without departing from scope of the present teachings. In addition, the following discussion refers to mounting the integrated video screen to the headrest of motor vehicle seats but may also be applied to other various component features of motor vehicle seats, such as the seat back, without departing from the scope of the present teachings.

FIG. 1A illustrates an adjustable headrest 100 for a first motor vehicle seat 102 having an integrated video screen 104

4

mounted therein. As illustrated in FIG. 1A, the adjustable headrest 100 is coupled to the seat 102 via posts 107 that extend therefrom and allow vertical adjustment of the adjustable headrest 100 with respect to the seat 102 in a generally known manner. FIG. 1B illustrates a fixed headrest 110 for a second motor vehicle seat 112 having the integrated video screen 104 mounted therein. In one embodiment, the video screen 104 is mounted within a headrest bun 106, 116 that is adapted to receive the video screen 104 for firm attachment therein in a manner that will be described in greater detail herein below. In addition, as will be described in greater detail herein below, the video screen 102 is mounted such that a front surface 120 of the video screen 104 is either flush or recessed from a contour 122 of the headrest 100, 110.

In one embodiment, the video screen 104 comprises a generally known LCD (liquid crystal display) monitor or terminal that can be electrically coupled to a video entertainment system so as to receive video signals therefrom for viewing of movies, television, internet web pages, video games, etc. As illustrated, the video screen 104 is generally rectangular in shape with the planar front surface 120 that is viewable by a user. In one aspect, it should be appreciated that the degree of recessed depth (with no depth comprising a flush mount) of the integrated video screen 104 and the manner in which the contour 122 of the seat 102, 112 is shaped may be selected such that the shape (side view, for example) of the headrest 100, 110 with the integrated video screen 104 mounted therein is generally similar to the shape of the headrest 100, 110 without the integrated video screen 104. Moreover, it should be appreciated that the motor vehicle seats 102, 112 may comprise any one of a number of various types or models of generally known motor vehicle seats without departing from the scope of the present invention.

FIG. 2 illustrates a side view of the adjustable headrest 100 shown in FIG. 1A having the integrated video screen 104 mounted therein with a recessed orientation. It should be appreciated that the following discussion is with respect to the adjustable headrest 100 of FIG. 1A but may be similarly applied to the fixed headrest 110 of FIG. 1B without departing from the scope of the present teachings.

FIG. 2 further illustrates the side view shape or contour 122 of the headrest 100. As illustrated in FIG. 2, the contour 122 of the headrest 100 is maintained due to the recessed orientation of the video screen 104 within the headrest bun 106. In addition, an opening 130 is formed in a rear section 132 of the headrest 100 so as to define a substantially rectangular interior region 136 within the headrest bun 106 below an outer surface 134 of the headrest 100. As further illustrated in FIG. 2, the video screen 104 can then be positioned adjacent the opening 130 so as to be firmly positioned within the interior region 136 of the headrest bun 106. Moreover, the recessed orientation may be defined by a depth 138 between the front surface 120 of the video screen 104 and the outer surface 134 of the headrest 100. The depth 138 therebetween may vary in magnitude depending on the thickness of the headrest bun 106 and/or the internal structural characteristics of the headrest 100, which may vary with respect to the type or model of motor vehicle seat used. In one aspect, the depth 138 of the recessed orientation may comprise a magnitude of approximately zero so as to define a flush mounted video screen 104, wherein the front surface 1120 of the video screen 104 is substantially aligned with the outer surface 134 of the headrest 100.

FIG. 3A illustrates a cross-sectional view of the adjustable headrest 102 shown in FIG. 1A having the integrated video screen 104 mounted therein with the recessed orientation shown in FIG. 2 and a screen cover 140. In one embodiment,

US 7,407,227 B1

5

the screen cover 140 is coupled to the rear section 132 of the headrest 100 via a hinge 142 so as to overlie the video screen 104 and at least part of the opening 130 formed therein. The screen cover 140 may comprise generally rectangular shape and is oriented generally parallel to the front surface 120 of the video screen 104 so as to temporarily occlude the video screen 104. In one aspect, as further illustrated in FIG. 3A, the screen cover 140 can be positioned adjacent the opening 130 so as to substantially align with the outer surface 134 of the headrest 100 thus forming a flush mounting therewith. It should be appreciated that the screen cover 140 may be positioned within the opening 130 so as to be recessed with respect to the outer surface 134 of the headrest 100 without departing from the scope of the present teachings. Moreover, the screen cover 140 may comprise a rigid material, such as plastic, metal, etc. Alternatively, in another aspect, the screen cover 140 may comprise a piece or flap of material from an outer skin 230 (FIG. 8) of the motor vehicle seat 102 that is attached to the headrest 100 adjacent the lower side of the video screen 104.

In still another aspect, as illustrated in FIG. 3B, the screen cover 140 may comprise an impact attenuating section 143 comprising a material such as foam, various types of padding, an air cushion, etc. so as to soften the force of an impact from an object. For example, during a car accident, a person's head may be propelled towards the screen cover 140, wherein the impact attenuating material may soften the impact to the headrest 102 to thereby protect the person's head and the video screen 104 from damage.

Also, in one embodiment, the video screen 104 can be viewed by opening the screen cover 140 or temporarily occluded by closing the screen cover 140. Hence, the screen cover 140 can be outwardly rotated about the hinge 142 in a first direction 144 to openly view the video screen 104, or the screen cover 140 can be inwardly rotated about the hinge 142 in a second direction 144 opposite the first direction 144 to temporarily occlude the video screen 104. Advantageously, the screen cover 104, when closed, conceals the video screen 104 from view thus, in some situations, functions as a thief deterrent.

Moreover, in one aspect, the recessed configuration of the video screen 104 facilitates the manner in which the screen cover 140 may be deployed. For example, the video screen 104 may not physically interfere with the closing of the screen cover 140. In addition, as illustrated in FIGS. 3A, 3B, the screen cover 140 is intended to "hide" the video screen 104 from outside observers, thereby reducing the probability that the video screen 104 will be a target of theft. As further illustrated in FIGS. 3A, 3B, the screen cover 140 may further comprise a means for engagement 147 that allows the screen cover 140 to remain in the "up" or closed configuration. In general, it should be appreciated that some possible means for achieving such an engagement include but are not limited to magnetic strips, mechanical clips, velcro strips, and the like.

FIG. 4 illustrates a cross-sectional view of the integrated video screen 104 being mounted to the headrest 100 via a carrier receptacle 150, a carrier member 160, and first fasteners 170. FIG. 5 illustrates a perspective view of the integrated video screen 104 being mounted to the headrest 100 via the carrier receptacle 150, the carrier member 152, and the first fasteners 170. In one embodiment, the carrier receptacle 150 comprises a plurality of planar sidewalls 152 and a rear planar wall 154 that are joined together in a manner so as to form a substantially rectangular outer structure 156 having an inner recessed region 158 that is adapted to receive the carrier member 152 therein. Similarly, the carrier member 152 comprises a plurality of planar sidewalls 162 and a rear planar wall

6

164 that are joined together in a manner so as to form a substantially rectangular outer structure 166 having an inner recessed region 168 that is adapted to receive the video screen 104 therein.

As illustrated in FIG. 4, the video screen 104 may be mounted within the carrier member 160 via side fasteners 180 (shown in FIGS. 6A, 6B) and then the carrier member 152 is mounted within the carrier receptacle 150 via the first fasteners 170 so as to simplify the mounting of the video screen 104 to the headrest 100 including the headrest bun 106. In one aspect, the first fasteners 170 may comprise a plurality of flexible engagement members 172 that extend therefrom so as to mechanically couple with a plurality of mounting apertures 174 (FIG. 5) formed in the rear wall 154 of the carrier receptacle 150. The first fasteners 170 may further comprise a central member 173 that extends outward from the rear wall 164 of the carrier member 160. Also, the flexible engagement members 172 are attached to the central member 173, wherein the flexible engagement members 172 are deformable so as to allow insertion of the central member 173 into the mounting apertures 174 in the rear wall 164 of the carrier receptacle 150. Moreover, the flexible engagement members 170 are biased outward so as to inhibit removal of the central member 173 from the mounting apertures 174 in the rear wall 154 of the carrier receptacle 150. In addition, the first fasteners 170 comprise a head 176 that abuts the rear wall 164 of the carrier member 152 and is positioned through a plurality of second apertures 178 formed in the rear wall 164 of the carrier member 152.

Advantageously, the video screen 104 can be mounted to the headrest 100 via the carrier receptacle 150 and the carrier member 152 without using external fasteners that may be seen. Hence, the video screen 104 can be mounted to the headrest 100 in a more aesthetically appealing manner, wherein the front surface 120 of the video screen 104 recessed or flush mounted with respect to the outer surface 134 of the headrest 100, and wherein the first and second fasteners 170, 180 are concealed from view.

As illustrated in FIG. 5, the sidewalls 152 of the carrier receptacle 150 each comprise at least one sidewall aperture 200 having at least one serrated tooth 202 protruding from an interior sidewall 204. In one embodiment, the at least one serrated tooth 202 is triangular in shape having a pointed tip 206 that projects outward from the interior sidewall 204 in a horizontal manner. It should be appreciated that the serrated tooth 202 may comprise any one of a number of various shapes known in the art without departing from the scope of the present teachings. Additionally, as will be shown in FIG. 8, the pointed tip 234 engages with the outer skin 230 (FIG. 8) and inhibits removal of the outer skin 230 from the at least one sidewall aperture 200 formed in the carrier receptacle 150. Advantageously, as will be described in greater detail herein below, the serrated tooth 200 allows outer skin from the motor vehicle seat 102, 112 to be attached to the carrier receptacle 150 by wrapping the outer skin around the planar sidewalls 152 and into the recessed region 158 of the carrier receptacle 150 and then securing the outer skin to the serrated tooth 200.

FIG. 6A illustrates a perspective view of attaching the integrated video screen 104 to the carrier member 152 via the second fasteners 180. In one embodiment, the planar sidewalls 162 of the carrier member 160 comprise pivot apertures 184 that allow the video display 104 to be mounted to the carrier member 160. Also, the pivot apertures 184 are adapted to rotatably receive the second fasteners 180. As illustrated in FIG. 6A, the second fasteners 180 comprise a threaded region 186 that mechanically couples to threaded apertures 196 (FIG. 7) formed in the video screen 104 in a generally known

US 7,407,227 B1

7

manner so as to be securely attached thereto. Moreover, the second fasteners 180 further comprise a head 182 and a smooth pivot region 188 interposed between the threaded region and the head 182.

In one aspect, the pivot region 188 of the second fastener 180 rotatably communicates with the pivot aperture 184 of the carrier member 160 to thereby allow the video screen 104 to pivot or tilt with respect to the carrier member 160 and/or the headrest 100 along a horizontal pivot axis 190 defined by the horizontally mounted second fasteners 180. Hence, the video screen 104 is pivotally attached to the carrier member 160 such that the plane of the video screen 104 can be adjusted with respect to the headrest 100 by a user about the defined horizontal pivot axis 190. Advantageously, the horizontal pivot axis 190 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

FIG. 6B further illustrates a perspective view of attaching the integrated video screen 104 to the carrier member 152 via the second fasteners 180. In one embodiment, as illustrated in FIG. 6B, the second fasteners 180 can be mounted vertically through the planar sidewalls 162 of the carrier member 160. The pivot region 188 of the vertically mounted second fasteners 180 rotatably communicates with the pivot aperture 184 of the carrier member 160 to thereby allow the video screen 104 to pivot or tilt side-to-side with respect to the carrier member 160 and/or the headrest 100 along a vertical pivot axis 191 defined by the vertically mounted second fasteners 180. Hence, the video screen 104 is pivotally attached to the carrier member 160 such that the plane of the video screen 104 can be adjusted with respect to the headrest 100 by a user about the vertical pivot axis 191. Advantageously, the vertical pivot axis 191 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

In one aspect, it should be appreciated that the second fasteners 180 may comprise generally known screws, such as sheet metal screws, without departing from the scope of the present invention. It should also be appreciated that the pivot region 188 of the second fasteners 180 may be threaded in a manner such that the video screen 104 can still pivot with respect to the carrier member 150 without departing from the scope of the present invention.

FIG. 6C illustrates a view of attaching the integrated video screen 104 to the carrier member 152 via a pivot member 240. In one embodiment, as illustrated in FIG. 6C, the pivot member 240 comprises a spherical ball 242 attached to the video screen 104 via a shaft 244 and a plate 246. The spherical ball 242 is positioned within a spherical receptacle 248 formed in the rear wall 164 of the carrier member 160. As illustrated in FIG. 6C, the rear wall 164 of the carrier member 160 may be dimensioned so as to accommodate the spherical receptacle 248. In one aspect, the plate 246 of the pivot member 240 may be attached to the video screen 104 using an adhesive, such as epoxy or glue, or fasteners, such as screws or bolts. In addition, the shaft 244 distally extends from the plate 246 towards the spherical receptacle 248 of the carrier member 160. Also, the shaft 244 and the spherical ball 242 may be formed as an integral part of the plate 246 or may be formed separately and interconnected to the plate 246 via an adhesive or fasteners.

Moreover, once the pivot member 240 is attached to the video screen 104 in a manner as previously described, the spherical ball 242 of the pivot member 240 can be pressed to fit within the spherical receptacle 248 formed in the rear wall 164 of the carrier member 160. In one aspect, the spherical ball 242 may be sized at least less than the size of the spherical receptacle 248 so as to allow rotational movement therein. Advantageously, the resulting interconnection between the

8

spherical ball 242 of the pivot member 240 and the spherical receptacle 248 of the carrier member 160 defines a pivot point 250 to thereby allow the video screen 104 to pivot, tilt, or rotate in a multi-directional manner with respect to the defined pivot point 250. Therefore, the defined pivot point 250 allows the video screen 104 to readily pivot when mounted to the headrest 100 to thereby allow greater positional flexibility during viewing of the video screen 104 by a user.

FIG. 7 illustrates a perspective view of mounting the integrated video screen 104 to the headrest 100 of FIG. 1A. In one embodiment, as illustrated in FIG. 7, the opening 130 is formed in the headrest bun 106 so as to define the substantially rectangular interior region 136 and to receive the carrier receptacle 150. The carrier receptacle 150 can then be positioned within the opening 130 so that the planar sidewalls 152 and the planar rear wall 154 abut the interior walls 226 of the mounting recess 136 formed in the headrest bun 106. In one embodiment, the carrier receptacle 150 can be secured to the headrest 100 via one or more third fasteners 220, such as screws, machine screws, sheet metal screws, etc. As illustrated in FIG. 7, the third fasteners 220 are positioned through rear wall apertures 222 formed in the rear wall 154 of the carrier receptacle 150 and coupled to rear mounting apertures 224 formed in a back wall 226 of the mounting recess 136 of the headrest bun 106. Advantageously, the third fasteners 220 can be securely attached to a structural component (not shown) of the headrest 100, such as an internal framework member of the headrest 100, so as to form a rigid attachment between the carrier receptacle 150 and the headrest 100.

In addition, the video screen 104 may be mounted to the carrier member 160 so as to pivot with respect thereto in a manner as previously described with reference to FIGS. 6A, 6B, 6C. Following, the carrier member 160 including the video screen 104 can then be mounted to the carrier receptacle 150 via the first fasteners 170 in a manner as previously described with reference to FIG. 4. Advantageously, this method of attaching the video screen 104 to the headrest 100 via the carrier receptacle 150, the carrier member 160, and the fasteners 170, 180 allows the video screen 104 to be securely mounted to the headrest 100 while providing a means for pivoting the video screen 104 with respect to the headrest 100 so as to improve the viewing range by a user.

FIG. 8 illustrates a cross-sectional view of the video screen 104 mounted to the headrest 100, wherein the outer skin 230 of the headrest 100 of the motor vehicle seat 102 is attached to the carrier receptacle 150 and the carrier member 160 with the video screen 104 mounted therein is mounted within the mounting recess 136 of the carrier receptacle 150. As is generally known, many motor vehicle car seats comprise the illustrated outer skin 230, such as fabric, leather, upholstery, vinyl, etc., that provides a outer surface 232 for a user to lean against or rest upon. In one aspect, when mounting the integrated video screen 104 into the headrest 100 of the motor vehicle seat 102, the outer skin 230 is adapted to accommodate the video screen 104 including the carrier receptacle 150. In some situations, one or more flaps 234 can be formed in the outer skin 230 and attached to the one or more serrated teeth 202 formed in the planar sidewalls 152 of the carrier receptacle 150.

As further illustrated in FIG. 8, the carrier receptacle 150 may be positioned within the mounting recess 136 formed in the headrest bun 106, and then the outer skin 230 is secured to the serrated teeth 202 via the flaps 234 formed therein by hooking the flaps 234 to one or more of the serrated teeth 202. Once the outer skin 230 is attached to the serrated teeth 202 via the flaps 234, the carrier member 160 is firmly pressed within the mounting recess 136 of the headrest bun 106 so that the first fasteners 170 couple to the mounting apertures 174 formed in the rear wall 154 of the carrier receptacle 150.

US 7,407,227 B1

9

10

Advantageously, this interconnection between the carrier member 160 and carrier receptacle 150 provides a quick and easy means for mounting of the video screen 104 to the headrest 100. In addition, the pressed fit of the outer skin between the carrier member 160 and the carrier receptacle 150 further secures the outer skin of the motor vehicle seat 102 to the carrier receptacle 150. As a result, the outer skin is securely held to the carrier receptacle 150 via the one or more serrated teeth 202 formed in the planar sidewalls 152 of the carrier receptacle 150 and the pressed fit of the carrier member 160 within the mousing recess 136 of the carrier receptacle 150.

Although the foregoing description has shown, described and pointed out the fundamental novel features of the invention, it will be understood that various omissions, substitutions, and changes in the form of the detail of the apparatus as illustrated, as well as the uses thereof, may be made by those skilled in the art, without departing from the spirit or scope of the present invention. Consequently, the scope of the invention should not be limited to the foregoing discussion, but should be defined by the appended claims.

What is claimed is:

1. A headrest assembly for a vehicle seat, the assembly comprising:

a receptacle member having a plurality of sidewalls and a back wall so as to define an opening wherein the receptacle member is adapted to be positioned in a back of the vehicle seat wherein the opening is facing away from the back of the vehicle seat when the receptacle member is positioned within the back of the vehicle seat and wherein the back wall of the receptacle member defines at least one securing aperture;

a carrier member having a plurality of sidewalls and a back wall so as to define an opening, wherein the opening in the carrier member is facing away from the back of the vehicle seat when the carrier member is positioned within the receptacle member and wherein the back wall of the carrier member defines at least one securing aperture;

an outer skin having edges that extend into the opening of the receptacle member and attached to at least some of the plurality of sidewalls of the receptacle member and wherein the edges of the outer skin are substantially concealed when the carrier member is positioned within the opening of the receptacle member;

at least one fastener that extends through the at least one securing aperture of the carrier member and engages with the at least one securing aperture of the receptacle member to allow securing of the carrier member in the opening of the receptacle member;

a video display unit that is sized so as to be positioned within the opening in the carrier member and substantially conceal the at least one fastener when in a viewing orientation.

2. The assembly of claim 1, wherein the at least one fastener comprises a plurality of fasteners that include a central member dimensioned to extend through the securing aperture of the carrier member and a plurality of flexible engagement members attached to the central member, wherein the flexible engagement members are deformable so as to allow insertion of the central member into the corresponding securing aperture of the receptacle member, and wherein the flexible engagement members are biased outward so as to inhibit removal of the central member from the apertures of the receptacle member.

3. The assembly of claim 1, wherein the video display unit defines a plane and is pivotally attached to the carrier member such that the plane of the video display unit can be adjusted by a user about a pivot axis.

4. The assembly of claim 3, wherein the video display unit is pivotable about a substantially horizontal axis.

5. The assembly of claim 3, wherein first and second pivot member coupled to the video display unit are positioned through the carrier member so as to define the pivot axis and pivotably secure the video display unit to the carrier member.

6. The assembly of claim 1, wherein the receptacle member includes an outer lip and a plurality of outer skin capture members that engage with the outer skin such that the outer skin is extended over the outer lip of the receptacle member and secured to the outer skin capture members.

7. The assembly of claim 6, wherein the plurality of capture members define a pointed surface that engages with the outer skin and inhibits removal of the outer skin from the opening defined by the receptacle member.

8. The assembly of claim 1, further comprising a screen cover that is dimensioned to cover the video display unit, and wherein the cover is selectively disengagable so as to allow visual access to the video display unit.

9. The assembly of claim 8, wherein the cover includes an impact attenuating material.

10. The assembly of claim 8, wherein the cover includes a generally rigid layer to provide physical protection of the video display unit.

11. The assembly of claim 1, wherein the receptacle member has four sidewalls.

12. The assembly of claim 1, wherein the carrier member has four sidewalls.

13. The assembly of claim 1, wherein the edges of the outer skin are secured to each of the plurality of sidewalls.

14. A headrest assembly for a vehicle seat, the assembly comprising:

a receptacle member having a plurality of sidewalls that are joined to a back wall so as to define an opening wherein the receptacle member is adapted to be positioned in a back of the vehicle seat wherein the opening is facing away from the back of the vehicle seat when the receptacle member is positioned within the back of the vehicle seat and wherein the back wall of the receptacle member defines at least one securing aperture;

a carrier member having a plurality of sidewalls and a back wall so as to define an opening, wherein the opening in the carrier member is facing away from the back of the vehicle seat when the carrier member is positioned within the receptacle member and wherein the back wall of the carrier member defines at least one securing aperture;

an outer skin having edges that extend into the opening of the receptacle member and secured to at least some of the plurality of sidewalls of the receptacle member, and wherein the edges of the outer skin are substantially concealed when the carrier member is positioned within the opening of the receptacle member;

at least one fastener that extends through the at least one securing aperture of the carrier member and engages with the at least one securing aperture of the receptacle member to allow securing of the carrier member in the opening of the receptacle member;

a video display unit that is sized so as to be positioned within the opening in the carrier member and substantially conceal the at least one fastener when in a viewing orientation.

\* \* \* \* \*

**UNITED STATES DISTRICT COURT  
CENTRAL DISTRICT OF CALIFORNIA**

**NOTICE OF ASSIGNMENT TO UNITED STATES MAGISTRATE JUDGE FOR DISCOVERY**

This case has been assigned to District Judge John F. Walter and the assigned discovery Magistrate Judge is Jacqueline Chooljian.

The case number on all documents filed with the Court should read as follows:

**CV09- 1437 JFW (JCx)**

Pursuant to General Order 05-07 of the United States District Court for the Central District of California, the Magistrate Judge has been designated to hear discovery related motions.

All discovery related motions should be noticed on the calendar of the Magistrate Judge

=====  
**NOTICE TO COUNSEL**

*A copy of this notice must be served with the summons and complaint on all defendants (if a removal action is filed, a copy of this notice must be served on all plaintiffs).*

Subsequent documents must be filed at the following location:

**Western Division**  
312 N. Spring St., Rm. G-8  
Los Angeles, CA 90012

**Southern Division**  
411 West Fourth St., Rm. 1-053  
Santa Ana, CA 92701-4516

**Eastern Division**  
3470 Twelfth St., Rm. 134  
Riverside, CA 92501

Failure to file at the proper location will result in your documents being returned to you.



UNITED STATES DISTRICT COURT  
CENTRAL DISTRICT OF CALIFORNIA

TMI PRODUCTS, INC.

PLAINTIFF(S)

v.  
AUDIOVOX CORPORATION and  
AUDIOVOX ELECTRONICS CORPORATION

DEFENDANT(S).

CASE NUMBER

CV09-01437 JFW (JCx)

SUMMONS

TO: DEFENDANT(S): Audiovox Corporation and Audiovox Electronics Corporation

A lawsuit has been filed against you.


Within 20 days after service of this summons on you (not counting the day you received it), you must serve on the plaintiff an answer to the attached  complaint  \_\_\_\_\_ amended complaint  counterclaim  cross-claim or a motion under Rule 12 of the Federal Rules of Civil Procedure. The answer or motion must be served on the plaintiff's attorney, David B. Ritchie, whose address is Nixon Peabody LLP, 200 Page Mill Road, Suite 200, Palo Alto, CA 94306-2022. If you fail to do so, judgment by default will be entered against you for the relief demanded in the complaint. You also must file your answer or motion with the court.

Clerk, U.S. District Court

FEB 27 2009

Dated: \_\_\_\_\_

By: \_\_\_\_\_



[Use 60 days if the defendant is the United States or a United States agency, or is an officer or employee of the United States. Allowed 60 days by Rule 12(a)(3)].

**UNITED STATES DISTRICT COURT, CENTRAL DISTRICT OF CALIFORNIA  
CIVIL COVER SHEET**

<b>I (a) PLAINTIFFS</b> (Check box if you are representing yourself <input type="checkbox"/> )  TMI PRODUCTS, INC	<b>DEFENDANTS</b>  AUDIOVOX CORPORATION and AUDIOVOX ELECTRONICS CORPORATION
<b>(b)</b> Attorneys (Firm Name, Address and Telephone Number. If you are representing yourself, provide same.)  David. B. Ritchie (112018); Margarita Gevondyan (245536) NIXON PEABODY LLP 200 Page Mill Road, Suite 200, Palo Alto, CA 94306-2022 (650) 320-7747	Attorneys (If Known)  Not yet known

<b>II. BASIS OF JURISDICTION</b> (Place an X in one box only.)  <input type="checkbox"/> 1 U.S. Government Plaintiff <input checked="" type="checkbox"/> 3 Federal Question (U.S. Government Not a Party)  <input type="checkbox"/> 2 U.S. Government Defendant <input type="checkbox"/> 4 Diversity (Indicate Citizenship of Parties in Item III)	<b>III. CITIZENSHIP OF PRINCIPAL PARTIES - For Diversity Cases Only</b> (Place an X in one box for plaintiff and one for defendant.) <table style="width:100%; border: none;"> <tr> <td style="border: none;"></td> <td style="border: none; text-align: center;"><b>PTF</b></td> <td style="border: none; text-align: center;"><b>DEF</b></td> <td style="border: none;"></td> <td style="border: none; text-align: center;"><b>PTF</b></td> <td style="border: none; text-align: center;"><b>DEF</b></td> </tr> <tr> <td style="border: none;">Citizen of This State</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 1</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 1</td> <td style="border: none;">Incorporated or Principal Place of Business in this State</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 4</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 4</td> </tr> <tr> <td style="border: none;">Citizen of Another State</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 2</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 2</td> <td style="border: none;">Incorporated and Principal Place of Business in Another State</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 5</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 5</td> </tr> <tr> <td style="border: none;">Citizen or Subject of a Foreign Country</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 3</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 3</td> <td style="border: none;">Foreign Nation</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 6</td> <td style="border: none; text-align: center;"><input type="checkbox"/> 6</td> </tr> </table>		<b>PTF</b>	<b>DEF</b>		<b>PTF</b>	<b>DEF</b>	Citizen of This State	<input type="checkbox"/> 1	<input type="checkbox"/> 1	Incorporated or Principal Place of Business in this State	<input type="checkbox"/> 4	<input type="checkbox"/> 4	Citizen of Another State	<input type="checkbox"/> 2	<input type="checkbox"/> 2	Incorporated and Principal Place of Business in Another State	<input type="checkbox"/> 5	<input type="checkbox"/> 5	Citizen or Subject of a Foreign Country	<input type="checkbox"/> 3	<input type="checkbox"/> 3	Foreign Nation	<input type="checkbox"/> 6	<input type="checkbox"/> 6
	<b>PTF</b>	<b>DEF</b>		<b>PTF</b>	<b>DEF</b>																				
Citizen of This State	<input type="checkbox"/> 1	<input type="checkbox"/> 1	Incorporated or Principal Place of Business in this State	<input type="checkbox"/> 4	<input type="checkbox"/> 4																				
Citizen of Another State	<input type="checkbox"/> 2	<input type="checkbox"/> 2	Incorporated and Principal Place of Business in Another State	<input type="checkbox"/> 5	<input type="checkbox"/> 5																				
Citizen or Subject of a Foreign Country	<input type="checkbox"/> 3	<input type="checkbox"/> 3	Foreign Nation	<input type="checkbox"/> 6	<input type="checkbox"/> 6																				

**IV. ORIGIN** (Place an X in one box only.)

1 Original Proceeding    
  2 Removed from State Court    
  3 Remanded from Appellate Court    
  4 Reinstated or Reopened    
  5 Transferred from another district (specify):    
  6 Multi-District Litigation    
  7 Appeal to District Judge from Magistrate Judge

**V. REQUESTED IN COMPLAINT: JURY DEMAND:**  Yes    No (Check 'Yes' only if demanded in complaint.)

**CLASS ACTION under F.R.C.P. 23:**  Yes    No     **MONEY DEMANDED IN COMPLAINT: \$** To be determined at trial

**VI. CAUSE OF ACTION** (Cite the U.S. Civil Statute under which you are filing and write a brief statement of cause. Do not cite jurisdictional statutes unless diversity.)

**VII. NATURE OF SUIT** (Place an X in one box only.)

<b>OTHER STATUTES</b> <input type="checkbox"/> 400 State Reapportionment <input type="checkbox"/> 410 Antitrust <input type="checkbox"/> 430 Banks and Banking <input type="checkbox"/> 450 Commerce/ICC Rates/etc. <input type="checkbox"/> 460 Deportation <input type="checkbox"/> 470 Racketeer Influenced and Corrupt Organizations <input type="checkbox"/> 480 Consumer Credit <input type="checkbox"/> 490 Cable/Sat TV <input type="checkbox"/> 810 Selective Service <input type="checkbox"/> 850 Securities/Commodities/Exchange <input type="checkbox"/> 875 Customer Challenge 12 USC 3410 <input type="checkbox"/> 890 Other Statutory Actions <input type="checkbox"/> 891 Agricultural Act <input type="checkbox"/> 892 Economic Stabilization Act <input type="checkbox"/> 893 Environmental Matters <input type="checkbox"/> 894 Energy Allocation Act <input type="checkbox"/> 895 Freedom of Info. Act <input type="checkbox"/> 900 Appeal of Fee Determination Under Equal Access to Justice <input type="checkbox"/> 950 Constitutionality of State Statutes	<b>CONTRACT</b> <input type="checkbox"/> 110 Insurance <input type="checkbox"/> 120 Marine <input type="checkbox"/> 130 Miller Act <input type="checkbox"/> 140 Negotiable Instrument <input type="checkbox"/> 150 Recovery of Overpayment & Enforcement of Judgment <input type="checkbox"/> 151 Medicare Act <input type="checkbox"/> 152 Recovery of Defaulted Student Loan (Excl. Veterans) <input type="checkbox"/> 153 Recovery of Overpayment of Veteran's Benefits <input type="checkbox"/> 160 Stockholders' Suits <input type="checkbox"/> 190 Other Contract <input type="checkbox"/> 195 Contract Product Liability <input type="checkbox"/> 196 Franchise <b>REAL PROPERTY</b> <input type="checkbox"/> 210 Land Condemnation <input type="checkbox"/> 220 Foreclosure <input type="checkbox"/> 230 Rent Lease & Ejectment <input type="checkbox"/> 240 Torts to Land <input type="checkbox"/> 245 Tort Product Liability <input type="checkbox"/> 290 All Other Real Property	<b>TORTS</b> <b>PERSONAL INJURY</b> <input type="checkbox"/> 310 Airplane <input type="checkbox"/> 315 Airplane Product Liability <input type="checkbox"/> 320 Assault, Libel & Slander <input type="checkbox"/> 330 Fed. Employers' Liability <input type="checkbox"/> 340 Marine <input type="checkbox"/> 345 Marine Product Liability <input type="checkbox"/> 350 Motor Vehicle <input type="checkbox"/> 355 Motor Vehicle Product Liability <input type="checkbox"/> 360 Other Personal Injury <input type="checkbox"/> 362 Personal Injury-Med Malpractice <input type="checkbox"/> 365 Personal Injury-Product Liability <input type="checkbox"/> 368 Asbestos Personal Injury Product Liability <b>IMMIGRATION</b> <input type="checkbox"/> 462 Naturalization Application <input type="checkbox"/> 463 Habeas Corpus-Alien Detainee <input type="checkbox"/> 465 Other Immigration Actions	<b>TORTS</b> <b>PERSONAL PROPERTY</b> <input type="checkbox"/> 370 Other Fraud <input type="checkbox"/> 371 Truth in Lending <input type="checkbox"/> 380 Other Personal Property Damage <input type="checkbox"/> 385 Property Damage Product Liability <b>BANKRUPTCY</b> <input type="checkbox"/> 422 Appeal 28 USC 158 <input type="checkbox"/> 423 Withdrawal 28 USC 157 <b>CIVIL RIGHTS</b> <input type="checkbox"/> 441 Voting <input type="checkbox"/> 442 Employment <input type="checkbox"/> 443 Housing/Accommodations <input type="checkbox"/> 444 Welfare <input type="checkbox"/> 445 American with Disabilities - Employment <input type="checkbox"/> 446 American with Disabilities - Other <input type="checkbox"/> 440 Other Civil Rights	<b>PRISONER PETITIONS</b> <input type="checkbox"/> 510 Motions to Vacate Sentence Habeas Corpus <input type="checkbox"/> 530 General <input type="checkbox"/> 535 Death Penalty <input type="checkbox"/> 540 Mandamus/Other <input type="checkbox"/> 550 Civil Rights <input type="checkbox"/> 555 Prison Condition <b>FORFEITURE / PENALTY</b> <input type="checkbox"/> 610 Agriculture <input type="checkbox"/> 620 Other Food & Drug <input type="checkbox"/> 625 Drug Related Seizure of Property 21 USC 881 <input type="checkbox"/> 630 Liquor Laws <input type="checkbox"/> 640 R.R. & Truck <input type="checkbox"/> 650 Airline Regs <input type="checkbox"/> 660 Occupational Safety /Health <input type="checkbox"/> 690 Other	<b>LABOR</b> <input type="checkbox"/> 710 Fair Labor Standards Act <input type="checkbox"/> 720 Labor/Mgmt. Relations <input type="checkbox"/> 730 Labor/Mgmt. Reporting & Disclosure Act <input type="checkbox"/> 740 Railway Labor Act <input type="checkbox"/> 790 Other Labor Litigation <input type="checkbox"/> 791 Empl. Ret. Inc. Security Act <b>PROPERTY RIGHTS</b> <input type="checkbox"/> 820 Copyrights <input checked="" type="checkbox"/> 830 Patent <input type="checkbox"/> 840 Trademark <b>SOCIAL SECURITY</b> <input type="checkbox"/> 861 HIA (1395ff) <input type="checkbox"/> 862 Black Lung (923) <input type="checkbox"/> 863 DIWC/DIWW (405(g)) <input type="checkbox"/> 864 SSID Title XVI <input type="checkbox"/> 865 RSI (405(g)) <b>FEDERAL TAX SUITS</b> <input type="checkbox"/> 870 Taxes (U.S. Plaintiff or Defendant) <input type="checkbox"/> 871 IRS-Third Party 26 USC 7609
---	--	--	---	--	--

**FOR OFFICE USE ONLY:** Case Number: CV09-01437

AFTER COMPLETING THE FRONT SIDE OF FORM CV-71, COMPLETE THE INFORMATION REQUESTED BELOW.

UNITED STATES DISTRICT COURT, CENTRAL DISTRICT OF CALIFORNIA  
CIVIL COVER SHEET

VIII(a). IDENTICAL CASES: Has this action been previously filed in this court and dismissed, remanded or closed?  No  Yes

If yes, list case number(s): \_\_\_\_\_

VIII(b). RELATED CASES: Have any cases been previously filed in this court that are related to the present case?  No  Yes

If yes, list case number(s): \_\_\_\_\_

Civil cases are deemed related if a previously filed case and the present case:

- (Check all boxes that apply)  A. Arise from the same or closely related transactions, happenings, or events; or  
 B. Call for determination of the same or substantially related or similar questions of law and fact; or  
 C. For other reasons would entail substantial duplication of labor if heard by different judges; or  
 D. Involve the same patent, trademark or copyright, and one of the factors identified above in a, b or c also is present.

IX. VENUE: (When completing the following information, use an additional sheet if necessary.)

(a) List the County in this District; California County outside of this District; State if other than California; or Foreign Country, in which EACH named plaintiff resides.  
 Check here if the government, its agencies or employees is a named plaintiff. If this box is checked, go to item (b).

County in this District:*	California County outside of this District; State, if other than California; or Foreign Country
TMI PRODUCTS, INC.: LOS ANGELES, RIVERSIDE, ORANGE, VENTURA, SANTA BARBARA, SAN LUIS OBISPO, & SAN BERNARDINO COUNTIES, CALIFORNIA.	

(b) List the County in this District; California County outside of this District; State if other than California; or Foreign Country, in which EACH named defendant resides.  
 Check here if the government, its agencies or employees is a named defendant. If this box is checked, go to item (c).

County in this District:*	California County outside of this District; State, if other than California; or Foreign Country
CA.	
CALIFORNIA	

(c) List the County in this District; California County outside of this District; State if other than California; or Foreign Country, in which EACH claim arose.  
**Note: In land condemnation cases, use the location of the tract of land involved.**

County in this District:*	California County outside of this District; State, if other than California; or Foreign Country
LOS ANGELES, RIVERSIDE, ORANGE, VENTURA, SANTA BARBARA, SAN LUIS OBISPO, & SAN BERNARDINO COUNTIES, CALIFORNIA AS TO SOME CLAIMS, OTHER CLAIMS UNKNOWN.	UNKNOWN

\* Los Angeles, Orange, San Bernardino, Riverside, Ventura, Santa Barbara, or San Luis Obispo Counties

Note: In land condemnation cases, use the location of the tract of land involved

X. SIGNATURE OF ATTORNEY (OR PRO PER): \_\_\_\_\_ Date 2/27/09

Notice to Counsel/Parties: The CV-71 (JS-44) Civil Cover Sheet and the information contained herein neither replace nor supplement the filing and service of pleadings or other papers as required by law. This form, approved by the Judicial Conference of the United States in September 1974, is required pursuant to Local Rule 3-1 is not filed but is used by the Clerk of the Court for the purpose of statistics, venue and initiating the civil docket sheet. (For more detailed instructions, see separate instructions sheet.)

Key to Statistical codes relating to Social Security Cases:

Nature of Suit Code	Abbreviation	Substantive Statement of Cause of Action
861	HIA	All claims for health insurance benefits (Medicare) under Title 18, Part A, of the Social Security Act, as amended. Also, include claims by hospitals, skilled nursing facilities, etc., for certification as providers of services under the program. (42 U.S.C. 1935FF(b))
862	BL	All claims for "Black Lung" benefits under Title 4, Part B, of the Federal Coal Mine Health and Safety Act of 1969. (30 U.S.C. 923)
863	DIWC	All claims filed by insured workers for disability insurance benefits under Title 2 of the Social Security Act, as amended; plus all claims filed for child's insurance benefits based on disability. (42 U.S.C. 405(g))
863	DIWW	All claims filed for widows or widowers insurance benefits based on disability under Title 2 of the Social Security Act, as amended. (42 U.S.C. 405(g))
864	SSID	All claims for supplemental security income payments based upon disability filed under Title 16 of the Social Security Act, as amended.
865	RSI	All claims for retirement (old age) and survivors benefits under Title 2 of the Social Security Act, as amended. (42 U.S.C. (g))