



US007822455B2

(12) **United States Patent**
Hoss et al.

(10) **Patent No.:** **US 7,822,455 B2**
(45) **Date of Patent:** ***Oct. 26, 2010**

(54) **ANALYTE SENSORS AND METHODS OF USE**

(75) Inventors: **Udo Hoss**, Castro Valley, CA (US);
Zenghe Liu, Alameda, CA (US);
Benjamin Jay Feldman, Oakland, CA (US)

(73) Assignee: **Abbott Diabetes Care Inc.**, Alameda, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/533,742**

(22) Filed: **Jul. 31, 2009**

(65) **Prior Publication Data**

US 2009/0292188 A1 Nov. 26, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/365,169, filed on Feb. 28, 2006.

(51) **Int. Cl.**

A61B 5/1473 (2006.01)

A61B 5/05 (2006.01)

(52) **U.S. Cl.** **600/347**; 600/365; 600/345; 204/403.01; 204/403.14

(58) **Field of Classification Search** 204/403.01, 204/403.14; 600/345, 347, 365
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,581,062 A 5/1971 Aston
3,926,760 A 12/1975 Allen et al.
3,949,388 A 4/1976 Fuller
4,036,749 A 7/1977 Anderson

4,055,175 A 10/1977 Clemens et al.

4,129,128 A 12/1978 McFarlane

4,245,634 A 1/1981 Albisser et al.

4,327,725 A 5/1982 Cortese et al.

4,344,438 A 8/1982 Schultz

4,349,728 A 9/1982 Phillips et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4401400 7/1995

(Continued)

OTHER PUBLICATIONS

Armour, J. C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs", *Diabetes*, vol. 39, 1990, pp. 1519-1526.

(Continued)

Primary Examiner—Alexa D Neckel

Assistant Examiner—Jennifer Dieterle


(74) *Attorney, Agent, or Firm*—Jackson & Co., LLP

(57)

ABSTRACT

An analyte sensor system including a substrate, a first electrode disposed on a first surface of the substrate, a second electrode disposed on a second surface of the substrate, a third electrode provided in electrical contact with at least one of the first or second electrodes, where at least a portion of the first electrode and the second electrode are subcutaneously positioned in a patient, and where the third electrode is substantially entirely positioned external to the patient, and corresponding methods are provided.

14 Claims, 3 Drawing Sheets



U.S. PATENT DOCUMENTS				
4,425,920 A	1/1984	Bourland et al.	5,711,861 A	1/1998 Ward et al.
4,478,976 A	10/1984	Goertz et al.	5,735,285 A	4/1998 Albert et al.
4,494,950 A	1/1985	Fischell	5,772,586 A	6/1998 Heinonen et al.
4,509,531 A	4/1985	Ward	5,791,344 A	8/1998 Schulman et al.
4,527,240 A	7/1985	Kvitash	5,899,855 A	5/1999 Brown
4,538,616 A	9/1985	Rogoff	5,925,021 A	7/1999 Castellano et al.
4,619,793 A	10/1986	Lee	5,942,979 A	8/1999 Luppino
4,671,288 A	6/1987	Gough	5,957,854 A	9/1999 Besson et al.
4,703,756 A	11/1987	Gough et al.	5,961,451 A	10/1999 Reber et al.
4,731,726 A	3/1988	Allen, III	5,964,993 A	10/1999 Blubaugh, Jr. et al.
4,749,985 A	6/1988	Corsberg	5,965,380 A	10/1999 Heller et al.
4,757,022 A	7/1988	Shults et al.	5,971,922 A	10/1999 Arita et al.
4,777,953 A	10/1988	Ash et al.	5,995,860 A	11/1999 Sun et al.
4,779,618 A	10/1988	Mund et al.	6,001,067 A	12/1999 Shults et al.
4,854,322 A	8/1989	Ash et al.	6,024,699 A	2/2000 Surwit et al.
4,890,620 A	1/1990	Gough	6,049,727 A	4/2000 Crothall
4,925,268 A	5/1990	Iyer et al.	6,083,710 A	7/2000 Heller et al.
4,953,552 A	9/1990	DeMarzo	6,088,608 A	7/2000 Schulman et al.
4,986,271 A	1/1991	Wilkins	6,091,976 A	7/2000 Pfeiffer et al.
4,995,402 A	2/1991	Smith et al.	6,093,172 A	7/2000 Funderburk et al.
5,000,180 A	3/1991	Kuypers et al.	6,103,033 A	8/2000 Say et al.
5,002,054 A	3/1991	Ash et al.	6,117,290 A	9/2000 Say et al.
5,019,974 A	5/1991	Beckers	6,119,028 A	9/2000 Schulman et al.
5,050,612 A	9/1991	Matsumura	6,120,676 A	9/2000 Heller et al.
5,055,171 A	10/1991	Peck	6,121,009 A	9/2000 Heller et al.
5,082,550 A	1/1992	Rishpon et al.	6,121,611 A	9/2000 Lindsay et al.
5,106,365 A	4/1992	Hernandez	6,122,351 A	9/2000 Schlueter, Jr. et al.
5,122,925 A	6/1992	Inpy	6,134,461 A	10/2000 Say et al.
5,165,407 A	11/1992	Wilson et al.	6,159,147 A	12/2000 Lichter et al.
5,246,867 A	9/1993	Lakowicz et al.	6,162,611 A	12/2000 Heller et al.
5,262,035 A	11/1993	Gregg et al.	6,175,752 B1 *	1/2001 Say et al. 600/345
5,262,305 A	11/1993	Heller et al.	6,200,265 B1	3/2001 Walsh et al.
5,264,104 A	11/1993	Gregg et al.	6,212,416 B1	4/2001 Ward et al.
5,264,105 A	11/1993	Gregg et al.	6,219,574 B1	4/2001 Cormier et al.
5,279,294 A	1/1994	Anderson et al.	6,248,067 B1	6/2001 Causey, III et al.
5,285,792 A	2/1994	Sjoquist et al.	6,275,717 B1	8/2001 Gross et al.
5,293,877 A	3/1994	O'Hara et al.	6,283,761 B1	9/2001 Joao
5,299,571 A	4/1994	Mastrototaro	6,284,478 B1	9/2001 Heller et al.
5,320,725 A	6/1994	Gregg et al.	6,293,925 B1	9/2001 Safabash et al.
5,322,063 A	6/1994	Allen et al.	6,295,506 B1	9/2001 Heinonen et al.
5,340,722 A	8/1994	Wolfbeis et al.	6,306,104 B1	10/2001 Cunningham et al.
5,342,789 A	8/1994	Chick et al.	6,309,884 B1	10/2001 Cooper et al.
5,356,786 A	10/1994	Heller et al.	6,329,161 B1	12/2001 Heller et al.
5,360,404 A	11/1994	Novacek et al.	6,348,640 B1	2/2002 Navot et al.
5,372,427 A	12/1994	Padovani et al.	6,359,444 B1	3/2002 Grimes
5,379,238 A	1/1995	Stark	6,360,888 B1	3/2002 McIvor et al.
5,390,671 A	2/1995	Lord et al.	6,366,794 B1	4/2002 Moussy et al.
5,391,250 A	2/1995	Cheney, II et al.	6,377,828 B1	4/2002 Chaiken et al.
5,408,999 A	4/1995	Singh et al.	6,379,301 B1	4/2002 Worthington et al.
5,411,647 A	5/1995	Johnson et al.	6,418,346 B1	7/2002 Nelson et al.
5,431,160 A	7/1995	Wilkins	6,424,847 B1	7/2002 Mastrototaro et al.
5,431,921 A	7/1995	Thombre	6,427,088 B1	7/2002 Bowman, IV et al.
5,462,645 A	10/1995	Albery et al.	6,440,068 B1	8/2002 Brown et al.
5,472,317 A	12/1995	Field et al.	6,478,736 B1	11/2002 Mault
5,489,414 A	2/1996	Schreiber et al.	6,484,046 B1	11/2002 Say et al.
5,497,772 A	3/1996	Schulman et al.	6,497,655 B1	12/2002 Linberg et al.
5,507,288 A	4/1996	Bocker et al.	6,514,689 B2	2/2003 Han et al.
5,509,410 A	4/1996	Hill et al.	6,514,718 B2	2/2003 Heller et al.
5,514,718 A	5/1996	Lewis et al.	6,522,927 B1	2/2003 Bishay et al.
5,531,878 A	7/1996	Vadgama et al.	6,549,796 B2	4/2003 Sohrab
5,568,806 A	10/1996	Cheney, II et al.	6,551,494 B1	4/2003 Heller et al.
5,569,186 A	10/1996	Lord et al.	6,558,320 B1	5/2003 Causey, III et al.
5,582,184 A	12/1996	Erickson et al.	6,558,321 B1	5/2003 Burd et al.
5,586,553 A	12/1996	Halili et al.	6,560,471 B1	5/2003 Heller et al.
5,593,852 A	1/1997	Heller et al.	6,561,978 B1	5/2003 Conn et al.
5,601,435 A	2/1997	Quy	6,562,001 B2	5/2003 Lebel et al.
5,609,575 A	3/1997	Larson et al.	6,564,105 B2	5/2003 Starkweather et al.
5,628,310 A	5/1997	Rao et al.	6,565,509 B1	5/2003 Say et al.
5,653,239 A	8/1997	Pompei et al.	6,571,128 B2	5/2003 Lebel et al.
5,665,222 A	9/1997	Heller et al.	6,576,101 B1	6/2003 Heller et al.
5,711,001 A	1/1998	Bussan et al.	6,577,899 B2	6/2003 Lebel et al.
			6,579,690 B1	6/2003 Bonnecaze et al.
			6,585,644 B2	7/2003 Lebel et al.

US 7,822,455 B2

Page 3

6,591,125	B1	7/2003	Buse et al.	7,198,606	B2	4/2007	Boecker et al.
6,595,919	B2	7/2003	Berner et al.	7,225,535	B2	6/2007	Feldman et al.
6,605,200	B1	8/2003	Mao et al.	7,226,978	B2	6/2007	Tapsak et al.
6,605,201	B1	8/2003	Mao et al.	7,267,665	B2	9/2007	Steil et al.
6,607,509	B2	8/2003	Bobroff et al.	7,276,029	B2	10/2007	Goode, Jr. et al.
6,610,012	B2	8/2003	Mault	7,278,983	B2	10/2007	Ireland et al.
6,633,772	B2	10/2003	Ford et al.	7,291,497	B2	11/2007	Holmes et al.
6,635,014	B2	10/2003	Starkweather et al.	7,299,082	B2	11/2007	Feldman et al.
6,641,533	B2	11/2003	Causey, III et al.	7,310,544	B2	12/2007	Brister et al.
6,648,821	B2	11/2003	Lebel et al.	7,335,294	B2	2/2008	Heller et al.
6,654,625	B1	11/2003	Say et al.	7,354,420	B2	4/2008	Steil et al.
6,659,948	B2	12/2003	Lebel et al.	7,364,592	B2	4/2008	Carr-Brendel et al.
6,668,196	B1	12/2003	Villegas et al.	7,366,556	B2	4/2008	Brister et al.
6,687,546	B2	2/2004	Lebel et al.	7,379,765	B2	5/2008	Petisce et al.
6,689,056	B1	2/2004	Kilcoyne et al.	7,384,397	B2	6/2008	Zhang et al.
6,694,191	B2	2/2004	Starkweather et al.	7,386,937	B2	6/2008	Bhullar et al.
6,695,860	B1	2/2004	Ward et al.	7,424,318	B2	9/2008	Brister et al.
6,702,857	B2	3/2004	Brauker et al.	7,460,898	B2	12/2008	Brister et al.
6,733,446	B2	5/2004	Lebel et al.	7,467,003	B2	12/2008	Brister et al.
6,740,075	B2	5/2004	Lebel et al.	7,471,972	B2	12/2008	Rhodes et al.
6,741,877	B1	5/2004	Shults et al.	7,494,465	B2	2/2009	Brister et al.
6,746,582	B2	6/2004	Heller et al.	7,497,827	B2	3/2009	Brister et al.
6,758,810	B2	7/2004	Lebel et al.	7,519,408	B2	4/2009	Rasdal et al.
6,770,030	B1	8/2004	Schaupp et al.	7,565,197	B2	7/2009	Haubrich et al.
6,790,178	B1	9/2004	Mault et al.	7,574,266	B2	8/2009	Dudding et al.
6,804,558	B2	10/2004	Haller et al.	7,583,990	B2	9/2009	Goode, Jr. et al.
6,809,653	B1	10/2004	Mann et al.	7,591,801	B2	9/2009	Brauker et al.
6,810,290	B2	10/2004	Lebel et al.	7,599,726	B2	10/2009	Goode, Jr. et al.
6,811,533	B2	11/2004	Lebel et al.	7,602,310	B2	10/2009	Mann et al.
6,811,534	B2	11/2004	Bowman, IV et al.	7,613,491	B2	11/2009	Boock et al.
6,813,519	B2	11/2004	Lebel et al.	7,615,007	B2	11/2009	Shults et al.
6,862,465	B2	3/2005	Shults et al.	7,632,228	B2	12/2009	Brauker et al.
6,873,268	B2	3/2005	Lebel et al.	7,637,868	B2	12/2009	Saint et al.
6,878,112	B2	4/2005	Linberg et al.	7,640,048	B2	12/2009	Dobbles et al.
6,881,551	B2	4/2005	Heller et al.	7,651,596	B2	1/2010	Petisce et al.
6,892,085	B2	5/2005	McIvor et al.	7,654,956	B2	2/2010	Brister et al.
6,895,265	B2	5/2005	Silver	7,657,297	B2	2/2010	Simpson et al.
6,931,327	B2	8/2005	Goode, Jr. et al.	7,711,402	B2	5/2010	Shults et al.
6,932,894	B2	8/2005	Mao et al.	7,713,574	B2	5/2010	Brister et al.
6,936,006	B2	8/2005	Sabra	7,715,893	B2	5/2010	Kamath et al.
6,942,518	B2	9/2005	Liamos et al.	2002/0019022	A1	2/2002	Dunn et al.
6,950,708	B2	9/2005	Bowman, IV et al.	2002/0042090	A1	4/2002	Heller et al.
6,958,705	B2	10/2005	Lebel et al.	2002/0050250	A1*	5/2002	Peterson et al. 119/721
6,968,294	B2	11/2005	Gutta et al.	2002/0103499	A1	8/2002	Perez et al.
6,971,274	B2	12/2005	Olin	2002/0106709	A1	8/2002	Potts et al.
6,974,437	B2	12/2005	Lebel et al.	2002/0128594	A1	9/2002	Das et al.
6,990,366	B2	1/2006	Say et al.	2002/0161288	A1	10/2002	Shin et al.
6,997,907	B2	2/2006	Safabash et al.	2003/0023317	A1	1/2003	Brauker et al.
6,998,247	B2	2/2006	Monfre et al.	2003/0023461	A1	1/2003	Quintanilla et al.
7,003,336	B2	2/2006	Holker et al.	2003/0032867	A1	2/2003	Crothall et al.
7,003,340	B2	2/2006	Say et al.	2003/0032874	A1	2/2003	Rhodes et al.
7,003,341	B2	2/2006	Say et al.	2003/0042137	A1	3/2003	Mao et al.
7,024,245	B2	4/2006	Lebel et al.	2003/0065308	A1	4/2003	Lebel et al.
7,041,068	B2	5/2006	Freeman et al.	2003/0134347	A1	7/2003	Heller et al.
7,041,468	B2	5/2006	Drucker et al.	2003/0168338	A1	9/2003	Gao et al.
7,052,483	B2	5/2006	Wojcik	2003/0176933	A1	9/2003	Lebel et al.
7,056,302	B2	6/2006	Douglas	2003/0187338	A1	10/2003	Say et al.
7,058,453	B2	6/2006	Nelson et al.	2003/0199790	A1	10/2003	Boecker et al.
7,060,031	B2	6/2006	Webb et al.	2003/0212379	A1	11/2003	Bylund et al.
7,073,246	B2	7/2006	Bhullar et al.	2003/0217966	A1	11/2003	Tapsak et al.
7,074,307	B2	7/2006	Simpson et al.	2004/0010207	A1	1/2004	Flaherty et al.
7,081,195	B2	7/2006	Simpson et al.	2004/0011671	A1	1/2004	Shults et al.
7,098,803	B2	8/2006	Mann et al.	2004/0040840	A1	3/2004	Mao et al.
7,108,778	B2	9/2006	Simpson et al.	2004/0045879	A1	3/2004	Shults et al.
7,110,803	B2	9/2006	Shults et al.	2004/0054263	A1	3/2004	Moerman et al.
7,113,821	B1	9/2006	Sun et al.	2004/0064068	A1	4/2004	DeNuzzio et al.
7,118,667	B2	10/2006	Lee	2004/0106858	A1	6/2004	Say et al.
7,125,382	B2	10/2006	Zhou et al.	2004/0122353	A1	6/2004	Shahmirian et al.
7,134,999	B2	11/2006	Brauker et al.	2004/0133164	A1	7/2004	Funderburk et al.
7,136,689	B2	11/2006	Shults et al.	2004/0135684	A1	7/2004	Steinthal et al.
7,171,274	B2	1/2007	Starkweather et al.	2004/0138588	A1	7/2004	Saikley et al.
7,190,988	B2	3/2007	Say et al.	2004/0152622	A1	8/2004	Keith et al.
7,192,450	B2	3/2007	Brauker et al.	2004/0167801	A1	8/2004	Say et al.

US 7,822,455 B2

Page 4

2004/0171921	A1	9/2004	Say et al.	2007/0078321	A1	4/2007	Mazza et al.
2004/0176672	A1	9/2004	Silver et al.	2007/0078322	A1	4/2007	Stafford
2004/0186362	A1	9/2004	Brauker et al.	2007/0106135	A1	5/2007	Sloan et al.
2004/0186365	A1	9/2004	Jin et al.	2007/0149875	A1	6/2007	Ouyang et al.
2004/0193090	A1	9/2004	Lebel et al.	2007/0156033	A1	7/2007	Causey, III et al.
2004/0199059	A1	10/2004	Brauker et al.	2007/0163880	A1	7/2007	Woo et al.
2004/0204687	A1	10/2004	Mogensen et al.	2007/0173706	A1	7/2007	Neinast et al.
2004/0225338	A1	11/2004	Lebel et al.	2007/0191701	A1	8/2007	Feldman et al.
2004/0236200	A1	11/2004	Say et al.	2007/0203407	A1	8/2007	Hoss et al.
2004/0254433	A1	12/2004	Bandis et al.	2007/0203966	A1	8/2007	Brauker et al.
2004/0254434	A1	12/2004	Goodnow et al.	2007/0235331	A1	10/2007	Simpson et al.
2004/0267300	A1	12/2004	Mace	2007/0244383	A1	10/2007	Talbot et al.
2005/0003470	A1	1/2005	Nelson et al.	2007/0249922	A1	10/2007	Peyser et al.
2005/0004494	A1	1/2005	Perez et al.	2007/0255531	A1	11/2007	Drew
2005/0010269	A1	1/2005	Lebel et al.	2007/0258395	A1	11/2007	Jollota et al.
2005/0027177	A1	2/2005	Shin et al.	2008/0009692	A1	1/2008	Stafford
2005/0031689	A1	2/2005	Shults et al.	2008/0017522	A1	1/2008	Heller et al.
2005/0043598	A1	2/2005	Goode, Jr. et al.	2008/0021666	A1	1/2008	Goode, Jr. et al.
2005/0090607	A1	4/2005	Tapsak et al.	2008/0029391	A1	2/2008	Mao et al.
2005/0103624	A1	5/2005	Bhullar et al.	2008/0030369	A1	2/2008	Mann et al.
2005/0112169	A1	5/2005	Brauker et al.	2008/0033254	A1	2/2008	Kamath et al.
2005/0114068	A1	5/2005	Chey et al.	2008/0039702	A1	2/2008	Hayter et al.
2005/0121322	A1	6/2005	Say et al.	2008/0045824	A1	2/2008	Tapsak et al.
2005/0131346	A1	6/2005	Douglas	2008/0064943	A1	3/2008	Talbot et al.
2005/0143635	A1	6/2005	Kamath et al.	2008/0071156	A1	3/2008	Brister et al.
2005/0176136	A1	8/2005	Burd et al.	2008/0071328	A1	3/2008	Haubrich et al.
2005/0182306	A1	8/2005	Sloan	2008/0083617	A1	4/2008	Simpson et al.
2005/0187720	A1	8/2005	Goode, Jr. et al.	2008/0086042	A1	4/2008	Brister et al.
2005/0192557	A1	9/2005	Brauker et al.	2008/0086044	A1	4/2008	Brister et al.
2005/0195930	A1	9/2005	Spital et al.	2008/0086273	A1	4/2008	Shults et al.
2005/0199494	A1	9/2005	Say et al.	2008/0108942	A1	5/2008	Brister et al.
2005/0203360	A1	9/2005	Brauker et al.	2008/0119705	A1	5/2008	Patel et al.
2005/0239154	A1	10/2005	Feldman et al.	2008/0183061	A1	7/2008	Goode, Jr. et al.
2005/0239156	A1	10/2005	Drucker et al.	2008/0183399	A1	7/2008	Goode, Jr. et al.
2005/0241957	A1	11/2005	Mao et al.	2008/0188731	A1	8/2008	Brister et al.
2005/0245795	A1	11/2005	Goode, Jr. et al.	2008/0189051	A1	8/2008	Goode, Jr. et al.
2005/0245799	A1	11/2005	Brauker et al.	2008/0194935	A1	8/2008	Brister et al.
2005/0277164	A1	12/2005	Drucker et al.	2008/0194936	A1	8/2008	Goode, Jr. et al.
2005/0287620	A1	12/2005	Heller et al.	2008/0194937	A1	8/2008	Goode, Jr. et al.
2006/0001538	A1	1/2006	Kraft et al.	2008/0194938	A1	8/2008	Brister et al.
2006/0010098	A1	1/2006	Goodnow et al.	2008/0195232	A1	8/2008	Carr-Brendel et al.
2006/0015020	A1	1/2006	Neale et al.	2008/0195967	A1	8/2008	Goode, Jr. et al.
2006/0015024	A1	1/2006	Brister et al.	2008/0197024	A1	8/2008	Simpson et al.
2006/0016700	A1	1/2006	Brister et al.	2008/0200788	A1	8/2008	Brister et al.
2006/0019327	A1	1/2006	Brister et al.	2008/0200789	A1	8/2008	Brister et al.
2006/0020186	A1	1/2006	Brister et al.	2008/0200791	A1	8/2008	Simpson et al.
2006/0020187	A1	1/2006	Brister et al.	2008/0208025	A1	8/2008	Shults et al.
2006/0020188	A1	1/2006	Kamath et al.	2008/0214915	A1	9/2008	Brister et al.
2006/0020189	A1	1/2006	Brister et al.	2008/0214918	A1	9/2008	Brister et al.
2006/0020190	A1	1/2006	Kamath et al.	2008/0228051	A1	9/2008	Shults et al.
2006/0020191	A1	1/2006	Brister et al.	2008/0228054	A1	9/2008	Shults et al.
2006/0020192	A1	1/2006	Brister et al.	2008/0235469	A1	9/2008	Drew
2006/0036139	A1	2/2006	Brister et al.	2008/0242961	A1	10/2008	Brister et al.
2006/0036140	A1	2/2006	Brister et al.	2008/0255438	A1	10/2008	Saidara et al.
2006/0036141	A1	2/2006	Kamath et al.	2008/0262469	A1	10/2008	Brister et al.
2006/0036142	A1	2/2006	Brister et al.	2008/0275313	A1	11/2008	Brister et al.
2006/0036143	A1	2/2006	Brister et al.	2008/0287764	A1	11/2008	Rasdal et al.
2006/0036144	A1	2/2006	Brister et al.	2008/0287765	A1	11/2008	Rasdal et al.
2006/0036145	A1	2/2006	Brister et al.	2008/0287766	A1	11/2008	Rasdal et al.
2006/0166629	A1	7/2006	Reggiardo	2008/0296155	A1	12/2008	Shults et al.
2006/0173444	A1	8/2006	Choy et al.	2008/0306368	A1	12/2008	Goode, Jr. et al.
2006/0189863	A1	8/2006	Heller et al.	2008/0306434	A1	12/2008	Dobbles et al.
2006/0222566	A1	10/2006	Brauker et al.	2008/0306435	A1	12/2008	Kamath et al.
2006/0226985	A1	10/2006	Goodnow et al.	2008/0306444	A1	12/2008	Brister et al.
2006/0247508	A1	11/2006	Fennell	2008/0312518	A1	12/2008	Jina et al.
2006/0247710	A1	11/2006	Goetz et al.	2009/0005666	A1	1/2009	Shin et al.
2006/0253085	A1	11/2006	Geismar et al.	2009/0012379	A1	1/2009	Goode, Jr. et al.
2006/0253086	A1	11/2006	Moberg et al.	2009/0018424	A1	1/2009	Kamath et al.
2006/0287691	A1	12/2006	Drew	2009/0018425	A1	1/2009	Ouyang et al.
2007/0027381	A1	2/2007	Stafford	2009/0020502	A1	1/2009	Bhullar et al.
2007/0060814	A1	3/2007	Stafford	2009/0030294	A1	1/2009	Petisce et al.
2007/0073129	A1	3/2007	Shah et al.	2009/0036758	A1	2/2009	Brauker et al.
2007/0078320	A1	4/2007	Stafford	2009/0036763	A1	2/2009	Brauker et al.

2009/0043181 A1 2/2009 Brauker et al.
 2009/0043182 A1 2/2009 Brauker et al.
 2009/0043525 A1 2/2009 Brauker et al.
 2009/0043541 A1 2/2009 Brauker et al.
 2009/0043542 A1 2/2009 Brauker et al.
 2009/0045055 A1 2/2009 Rhodes et al.
 2009/0062633 A1 3/2009 Brauker et al.
 2009/0062635 A1 3/2009 Brauker et al.
 2009/0076356 A1 3/2009 Simpson et al.
 2009/0076360 A1 3/2009 Brister et al.
 2009/0076361 A1 3/2009 Kamath et al.
 2009/0085768 A1 4/2009 Patel et al.
 2009/0099436 A1 4/2009 Brister et al.
 2009/0112478 A1 4/2009 Mueller, Jr. et al.
 2009/0124877 A1 5/2009 Goode, Jr. et al.
 2009/0124878 A1 5/2009 Goode, Jr. et al.
 2009/0124879 A1 5/2009 Brister et al.
 2009/0124964 A1 5/2009 Leach et al.
 2009/0131768 A1 5/2009 Simpson et al.
 2009/0131769 A1 5/2009 Leach et al.
 2009/0131776 A1 5/2009 Simpson et al.
 2009/0131777 A1 5/2009 Simpson et al.
 2009/0137886 A1 5/2009 Shariati et al.
 2009/0137887 A1 5/2009 Shariati et al.
 2009/0143659 A1 6/2009 Li et al.
 2009/0143660 A1 6/2009 Brister et al.
 2009/0150186 A1 6/2009 Cohen et al.
 2009/0156919 A1 6/2009 Brister et al.
 2009/0156924 A1 6/2009 Shariati et al.
 2009/0163790 A1 6/2009 Brister et al.
 2009/0163791 A1 6/2009 Brister et al.
 2009/0178459 A1 7/2009 Li et al.
 2009/0182217 A1 7/2009 Li et al.
 2009/0192366 A1 7/2009 Mensinger et al.
 2009/0192380 A1 7/2009 Shariati et al.
 2009/0192722 A1 7/2009 Shariati et al.
 2009/0192724 A1 7/2009 Brauker et al.
 2009/0192745 A1 7/2009 Kamath et al.
 2009/0192751 A1 7/2009 Kamath et al.
 2009/0203981 A1 8/2009 Brauker et al.
 2009/0204341 A1 8/2009 Brauker et al.
 2009/0216103 A1 8/2009 Brister et al.
 2009/0240120 A1 9/2009 Mensinger et al.
 2009/0240128 A1 9/2009 Mensinger et al.
 2009/0240193 A1 9/2009 Mensinger et al.
 2009/0242399 A1 10/2009 Kamath et al.
 2009/0242425 A1 10/2009 Kamath et al.
 2009/0247855 A1 10/2009 Boock et al.
 2009/0247856 A1 10/2009 Boock et al.
 2009/0287073 A1 11/2009 Boock et al.
 2009/0287074 A1 11/2009 Shults et al.
 2009/0299155 A1 12/2009 Yang et al.
 2009/0299156 A1 12/2009 Simpson et al.
 2009/0299162 A1 12/2009 Brauker et al.
 2009/0299276 A1 12/2009 Brauker et al.
 2010/0010324 A1 1/2010 Brauker et al.
 2010/0010331 A1 1/2010 Brauker et al.
 2010/0010332 A1 1/2010 Brauker et al.
 2010/0016687 A1 1/2010 Brauker et al.
 2010/0016698 A1 1/2010 Rasdal et al.
 2010/0022855 A1 1/2010 Brauker et al.
 2010/0030038 A1 2/2010 Brauker et al.
 2010/0030053 A1 2/2010 Goode, Jr. et al.
 2010/0030484 A1 2/2010 Brauker et al.
 2010/0030485 A1 2/2010 Brauker et al.
 2010/0036215 A1 2/2010 Goode, Jr. et al.
 2010/0036216 A1 2/2010 Goode, Jr. et al.
 2010/0036222 A1 2/2010 Goode, Jr. et al.
 2010/0036223 A1 2/2010 Goode, Jr. et al.
 2010/0036225 A1 2/2010 Goode, Jr. et al.
 2010/0041971 A1 2/2010 Goode, Jr. et al.
 2010/0045465 A1 2/2010 Brauker et al.
 2010/0049024 A1 2/2010 Saint et al.

2010/0063373 A1 3/2010 Kamath et al.
 2010/0076283 A1 3/2010 Simpson et al.
 2010/0081908 A1 4/2010 Dobbles et al.
 2010/0081910 A1 4/2010 Brister et al.
 2010/0087724 A1 4/2010 Brauker et al.
 2010/0096259 A1 4/2010 Zhang et al.
 2010/0099970 A1 4/2010 Shults et al.
 2010/0099971 A1 4/2010 Shults et al.
 2010/0119693 A1 5/2010 Tapsak et al.
 2010/0121169 A1 5/2010 Petissee et al.

FOREIGN PATENT DOCUMENTS



EP 0098592 1/1984
 EP 0127958 12/1984
 EP 0320109 6/1989
 EP 0353328 2/1990
 EP 0390390 10/1990
 EP 0396788 11/1990
 EP 0286118 1/1995
 EP 1048264 11/2000
 WO WO-96/25089 8/1996
 WO WO-96/35370 11/1996
 WO WO-98/35053 8/1998
 WO WO-99/56613 11/1999
 WO WO-00/49940 8/2000
 WO WO-00/59370 10/2000
 WO WO-00/78992 12/2000
 WO WO-01/52935 7/2001
 WO WO-01/54753 8/2001
 WO WO-02/16905 2/2002
 WO WO-02/058537 8/2002
 WO WO-03/076893 9/2003
 WO WO-03/082091 10/2003
 WO WO-03/085372 10/2003
 WO WO-2004/061420 7/2004
 WO WO-2005/041766 5/2005
 WO WO-2005/089103 9/2005
 WO WO-2005/119524 12/2005
 WO WO-2006/024671 3/2006
 WO WO-2006/079114 7/2006
 WO WO-2006/086423 8/2006
 WO WO-2006/118947 11/2006
 WO WO-2007/016399 2/2007
 WO WO-2007/027788 3/2007
 WO WO-2007/041069 4/2007
 WO WO-2007/041070 4/2007
 WO WO-2007/041248 4/2007
 WO WO-2007/056638 5/2007
 WO WO-2007/101223 9/2007
 WO WO-2007/120363 10/2007
 WO WO-2007/126444 11/2007
 WO WO-2007/053832 12/2007
 WO WO-2007/143225 12/2007

OTHER PUBLICATIONS

Bennion, N., et al., "Alternate Site Glucose Testing: A Crossover Design", *Diabetes Technology & Therapeutics*, vol. 4, No. 1, 2002, pp. 25-33.
 Blank, T. B., et al., "Clinical Results From a Non-Invasive Blood Glucose Monitor", *Optical Diagnostics and Sensing of Biological Fluids and Glucose and Cholesterol Monitoring II, Proceedings of SPIE*, vol. 4624, 2002, pp. 1-10.
 Brooks, S. L., et al., "Development of an On-Line Glucose Sensor for Fermentation Monitoring", *Biosensors*, vol. 3, 1987/88, pp. 45-56.
 Cass, A. E., et al., "Ferrocene-Medicated Enzyme Electrode for Amperometric Determination of Glucose", *Analytical Chemistry*, vol. 56 No. 4, 1984, 667-671.
 Csoregi, E., et al., "Design and Optimization of a Selective Subcutaneously Implantable Glucose Electrode Based on 'Wired' Glucose Oxidase", *Analytical Chemistry*, vol. 67, No. 7, 1995, pp. 1240-1244.

- Feldman, B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes", *Diabetes Technology & Therapeutics*, vol. 5, No. 5, 2003, pp. 769-779.
- Feldman, B., et al., "Correlation of Glucose Concentrations in Interstitial Fluid and Venous Blood During Periods of Rapid Glucose Change", *Abbott Diabetes Care, Inc. Freestyle Navigator Continuous Glucose Monitor Pamphlet*, 2004.
- Isermann, R., "Supervision, Fault-Detection and Fault-Diagnosis Methods—An Introduction", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 639-652.
- Isermann, R., et al., "Trends in the Application of Model-Based Fault Detection and Diagnosis of Technical Processes", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 709-719.
- Johnson, P. C., "Peripheral Circulation", *John Wiley & Sons*, 1978, pp. 198.
- Jungheim, K., et al., "How Rapid Does Glucose Concentration Change in Daily Life of Patients with Type 1 Diabetes?", 2002, pp. 250.
- Jungheim, K., et al., "Risky Delay of Hypoglycemia Detection by Glucose Monitoring at the Arm", *Diabetes Care*, vol. 24, No. 7, 2001, pp. 1303-1304.
- Kaplan, S. M., "Wiley Electrical and Electronics Engineering Dictionary", *IEEE Press*, 2004, pp. 141, 142, 548, 549.
- Lortz, J., et al., "What is Bluetooth? We Explain The Newest Short-Range Connectivity Technology", *Smart Computing Learning Series, Wireless Computing*, vol. 8, Issue 5, 2002, pp. 72-74.
- Malin, S. F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy", *Clinical Chemistry*, vol. 45, No. 9, 1999, pp. 1651-1658.
- McGarraugh, G., et al., "Glucose Measurements Using Blood Extracted from the Forearm and the Finger", *TheraSense, Inc.*, 2001, 16 Pages.
- McGarraugh, G., et al., "Physiological Influences on Off-Finger Glucose Testing", *Diabetes Technology & Therapeutics*, vol. 3, No. 3, 2001, pp. 367-376.
- McKean, B. D., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 7, 1988, pp. 526-532.
- Pickup, J., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensing Strategy", *Biosensors*, vol. 3, 1987/88, pp. 335-346.
- Pickup, J., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer", *Diabetologia*, vol. 32, 1989, pp. 213-217.
- Pishko, M. V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels", *Analytical Chemistry*, vol. 63, No. 20, 1991, pp. 2268-2272.
- Quinn, C. P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors", *The American Physiological Society*, 1995, E155-E161.
- Roe, J. N., et al., "Bloodless Glucose Measurements", *Critical Review in Therapeutic Drug Carrier Systems*, vol. 15, Issue 3, 1998, pp. 199-241.
- Sakakida, M., et al., "Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations", *Artificial Organs Today*, vol. 2, No. 2, 1992, pp. 145-158.
- Sakakida, M., et al., "Ferrocene-Mediated Needle-Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322.
- Salehi, C., et al., "A Telemetry-Instrumentation System for Long-Term Implantable Glucose and Oxygen Sensors", *Analytical Letters*, vol. 29, No. 13, 1996, pp. 2289-2308.
- Schmidtke, D. W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin", *Proceedings of the National Academy of Sciences*, vol. 95, 1998, pp. 294-299.
- Shaw, G. W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.
- Shichiri, M., et al., "Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas", *Diabetologia*, vol. 24, 1983, pp. 179-184.
- Shichiri, M., et al., "In Vivo Characteristics of Needle-Type Glucose Sensor—Measurements of Subcutaneous Glucose Concentrations in Human Volunteers", *Hormone and Metabolic Research Supplement Series*, vol. 20, 1988, pp. 17-20.
- Shichiri, M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor", *Diabetes Nutrition and Metabolism*, vol. 2, 1989, pp. 309-313.
- Shichiri, M., et al., "Needle-type Glucose Sensor for Wearable Artificial Endocrine Pancreas", *Implantable Sensors for Closed-Loop Prosthetic Systems*, Chapter 15, 1985, pp. 197-210.
- Shichiri, M., et al., "Telemetry Glucose Monitoring Device With Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals", *Diabetes Care*, vol. 9, No. 3, 1986, pp. 298-301.
- Shichiri, M., et al., "Wearable Artificial Endocrine Pancreas With Needle-Type Glucose Sensor", *The Lancet*, 1982, pp. 1129-1131.
- Shults, M. C., et al., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 41, No. 10, 1994, pp. 937-942.
- Sternberg, R., et al., "Study and Development of Multilayer Needle-Type Enzyme-Based Glucose Microsensors", *Biosensors*, vol. 4, 1988, pp. 27-40.
- Thompson, M., et al., "In Vivo Probes: Problems and Perspectives", *Clinical Biochemistry*, vol. 19, 1986, pp. 255-261.
- Turner, A., et al., "Diabetes Mellitus: Biosensors for Research and Management", *Biosensors*, vol. 1, 1985, pp. 85-115.
- Updike, S. J., et al., "Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose from Inside a Subcutaneous Foreign Body Capsule (FBC)", *Biosensors in the Body: Continuous in vivo Monitoring*, Chapter 4, 1997, pp. 117-137.
- Velho, G., et al., "Strategies for Calibrating a Subcutaneous Glucose Sensor", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 957-964.
- Wilson, G. S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose", *Clinical Chemistry*, vol. 38, No. 9, 1992, pp. 1613-1617.
- PCT Application No. PCT/US2007/062915, International Preliminary Report on Patentability and Written Opinion of the International Searching Authority mailed Sep. 12, 2008.
- PCT Application No. PCT/US2007/062915, International Search Report and Written Opinion of the International Searching Authority mailed Mar. 4, 2008.
- U.S. Appl. No. 11/365,169, Advisory Action mailed Mar. 17, 2010.
- U.S. Appl. No. 11/365,169, Office Action mailed Jan. 8, 2010.
- U.S. Appl. No. 11/365,169, Office Action mailed May 5, 2009.

* cited by examiner






FIGURE 3A




FIGURE 3B




FIGURE 4A




FIGURE 4B




FIGURE 4C




FIGURE 5A




FIGURE 5B




FIGURE 6A




FIGURE 6B




FIGURE 6C




FIGURE 7

1

ANALYTE SENSORS AND METHODS OF USE

RELATED APPLICATION

The present application is a continuation of pending U.S. patent application Ser. No. 11/365,169 filed Feb. 28, 2006, entitled "Analyte Sensors and Methods of Use", the disclosure of which is incorporated herein by reference for all purposes.

BACKGROUND

Continuous analyte monitoring systems such as continuous glucose monitoring systems use analyte sensors a portion of which is placed in contact with the patient's bodily fluid such as interstitial fluid or blood. The analyte sensor such as glucose sensors are configured with electrodes such as a working electrode, a counter electrode and a reference electrode, and where at least a portion of the sensor is placed in vivo so as to detect the level of the patient's analyte. In the three electrode configuration, the reference electrode is maintained substantially current free, and is configured to establish a substantially constant electrical potential difference with respect to the working electrode. The electrical potential difference then is used to drive certain electrochemical reactions that result in a current signal which is directly proportional to the level of analyte in the patient (such as the patient's glucose concentration).

The analyte sensor configuration described above, and in most glucose sensors that employ multiple electrodes for detecting the glucose level, for example, the counter electrode is generally configured to close the circuit. That is, since the electrons resulting from the electrochemical reactions by the analyte sensor are flowing into the working electrode from the electrolyte solution (the patient's body), the counter electrode of the analyte sensor needs to dispose of the electrons back into the electrolyte (that is, the counter electrode must find molecules or ions that can be reduced). The applied electrical potential at the counter electrode is regulated through a feedback loop such that the necessary reduction reactions can take place. Therefore, it is necessary for the counter electrode of the analyte sensor be electrically coupled to the human body.

In view of the foregoing, it would be desirable to have methods and device for providing a compact, cost effective analyte sensor configuration. Indeed, it would be desirable to have methods and device for providing analyte sensors with external counter electrode which is not placed in vivo along with the working and reference electrodes of the analyte sensor so as to be in fluid contact with the patient's analyte. Moreover, it would be desirable to have method and system for manufacturing analyte sensors to achieve cost effectiveness and scalability by, for example, reducing the number of necessary manufacturing steps.

SUMMARY OF THE INVENTION

In view of the foregoing, in accordance with the various embodiments of the present invention, there is provided methods and devices for analyte sensor configuration with an external on-body counter electrode forming a two electrode analyte sensor such as glucose sensors, which is provided with the working and reference electrodes at least a portion of each of which are placed in fluid contact with the patient's analyte, and which is provided with an external non-invasive counter electrode provided on the patient's skin.

These and other objects, features and advantages of the present invention will become more fully apparent from the

2

following detailed description of the embodiments, the appended claims and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a data monitoring and management system such as, for example, an analyte monitoring system **100** for practicing one embodiment of the present invention;

FIG. 2 is a block diagram of the transmitter unit of the data monitoring and detection system shown in FIG. 1 in accordance with one embodiment of the present invention;

FIGS. 3A-3B illustrate a bottom view of the transmitter unit housing with counter electrode contact in accordance with one embodiment of the present invention;

FIGS. 4A-4C each illustrates the transmitter unit coupled with an analyte sensor with external counter electrode in accordance with various alternate embodiments of the present invention;

FIGS. 5A and 5B illustrate the side cross-sectional view and bottom view of the transmitter unit coupled with an analyte sensor with external counter electrode with dislocation detection mechanism in accordance with one embodiment of the present invention;

FIG. 6A illustrates a two working electrode analyte sensor with external counter electrode, FIG. 6B illustrates a three working electrode analyte sensor with external counter electrode in accordance with various embodiments of the present invention, and FIG. 6C illustrates a two working electrode analyte sensor with external counter electrode of another embodiment; and

FIG. 7 illustrates a cross sectional view of a two sided analyte sensor with external counter electrode in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION

FIG. 1 illustrates a data monitoring and management system such as, for example, an analyte monitoring system **100** for practicing one embodiment of the present invention. In such embodiment, the analyte monitoring system **100** includes an analyte sensor **101**, a transmitter unit **102** coupled to the sensor **101**, and a receiver unit **104** which is configured to communicate with the transmitter unit **102** via a communication link **103**. The receiver unit **104** may be further configured to transmit data to a data processing terminal **105** for evaluating the data received by the receiver unit **104**.

Only one sensor **101**, transmitter unit **102**, communication link **103**, receiver unit **104**, and data processing terminal **105** are shown in the embodiment of the analyte monitoring system **100** illustrated in FIG. 1. However, it will be appreciated by one of ordinary skill in the art that the analyte monitoring system **100** may include one or more sensor **101**, transmitter unit **102**, communication link **103**, receiver unit **104**, and data processing terminal **105**, where each receiver unit **104** is uniquely synchronized with a respective transmitter unit **102**. Moreover, within the scope of the present invention, the analyte monitoring system **100** may be a continuous monitoring system, or a semi-continuous or discrete monitoring system.

In one embodiment of the present invention, the sensor **101** is physically positioned on the body of a user whose analyte level is being monitored. The sensor **101** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level into a corresponding data signal for transmission by the transmitter unit **102**. In one embodiment, the transmitter unit **102** is mounted on the sensor **101** so that both devices are positioned on the user's body. The transmitter unit **102** performs data processing such as filtering and

encoding on data signals, each of which corresponds to a sampled glucose level of the user, for transmission to the receiver unit **104** via the communication link **103**.

Additional analytes that may be monitored or determined by sensor **101** include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and troponin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be determined.

In one embodiment, the analyte monitoring system **100** is configured as a one-way RF communication path from the transmitter unit **102** to the receiver unit **104**. In such embodiment, the transmitter unit **102** transmits the sampled data signals received from the sensor **101** without acknowledgement from the receiver unit **104** that the transmitted sampled data signals have been received. For example, the transmitter unit **102** may be configured to transmit the encoded sampled data signals at a fixed rate (e.g., at one minute intervals) after the completion of the initial power on procedure. Likewise, the receiver unit **104** may be configured to detect such transmitted encoded sampled data signals at predetermined time intervals. Alternatively, the analyte monitoring system **100** may be configured with a bidirectional RF communication between the transmitter unit **102** and the receiver unit **104**.

Additionally, in one aspect, the receiver unit **104** may include two sections. The first section is an analog interface section that is configured to communicate with the transmitter unit **102** via the communication link **103**. In one embodiment, the analog interface section may include an RF receiver and an antenna for receiving and amplifying the data signals from the transmitter unit **102**, which are thereafter, demodulated with a local oscillator and filtered through a band-pass filter. The second section of the receiver unit **104** is a data processing section which is configured to process the data signals received from the transmitter unit **102** such as by performing data decoding, error detection and correction, data clock generation, and data bit recovery.

In operation, upon completing the power-on procedure, the receiver unit **104** is configured to detect the presence of the transmitter unit **102** within its range based on, for example, the strength of the detected data signals received from the transmitter unit **102** or a predetermined transmitter identification information. Upon successful synchronization with the corresponding transmitter unit **102**, the receiver unit **104** is configured to begin receiving from the transmitter unit **102** data signals corresponding to the user's detected analyte level. More specifically, the receiver unit **104** in one embodiment is configured to perform synchronized time hopping with the corresponding synchronized transmitter unit **102** via the communication link **103** to obtain the user's detected analyte level.

Referring again to FIG. 1, the data processing terminal **105** may include a personal computer, a portable computer such as a laptop or a handheld device (e.g., personal digital assistants (PDAs)), and the like, each of which may be configured for data communication with the receiver via a wired or a wireless connection. Additionally, the data processing terminal **105** may further be connected to a data network (not shown) for storing, retrieving and updating data corresponding to the detected analyte level of the user.

Within the scope of the present invention, the data processing terminal **105** may include an infusion device such as an insulin infusion pump, which may be configured to adminis-

ter insulin to patients, and which is configured to communicate with the receiver unit **104** for receiving, among others, the measured analyte level. Alternatively, the receiver unit **104** may be configured to integrate an infusion device therein so that the receiver unit **104** is configured to administer insulin therapy to patients, for example, for administering and modifying basal profiles, as well as for determining appropriate boluses (e.g., correction bolus, carbohydrate bolus, dual wave bolus including normal and extended bolus such as square wave bolus, and so on) for administration based on, among others, the detected analyte levels received from the transmitter unit **102**.

FIG. 2 is a block diagram of the transmitter of the data monitoring and detection system shown in FIG. 1 in accordance with one embodiment of the present invention. Referring to the Figure, the transmitter unit **102** in one embodiment includes an analog interface **201** configured to communicate with the sensor **101** (FIG. 1), a user input **202**, and a temperature detection section **203**, each of which is operatively coupled to a transmitter processor **204** such as a central processing unit (CPU). As can be seen from FIG. 2, there are provided two contacts working electrode (W) **210** and reference electrode (R) **212**, each operatively coupled to the analog interface **201** of the transmitter unit **102** for connection to the sensor unit **201** (FIG. 1). In one embodiment, the working electrode (W) **210** and reference electrode (R) **212** may be made using a conductive material that is either printed or etched, for example, such as carbon which may be printed, or metal foil (e.g., gold) which may be etched.

Referring to FIG. 2, also shown is the transmitter unit **102** is a contact **214** which is operatively coupled to the analog interface **201**. In one embodiment, the contact **214** is configured to function as the external counter electrode and is positioned so as to establish physical contact with the skin surface of the patient wearing the transmitter unit on body.

Further shown in FIG. 2 are a transmitter serial communication section **205** and an RF transmitter **206**, each of which is also operatively coupled to the transmitter processor **204**. Moreover, a power supply **207** such as a battery is also provided in the transmitter unit **102** to provide the necessary power for the transmitter unit **102**. Additionally, as can be seen from the Figure, clock **208** is provided to, among others, supply real time information to the transmitter processor **204**.

In one embodiment, a unidirectional input path is established from the sensor **101** (FIG. 1) and/or manufacturing and testing equipment to the analog interface **201** of the transmitter unit **102**, while a unidirectional output is established from the output of the RF transmitter **206** of the transmitter unit **102** for transmission to the receiver **104**. In this manner, a data path is shown in FIG. 2 between the aforementioned unidirectional input and output via a dedicated link **209** from the analog interface **201** to serial communication section **205**, thereafter to the processor **204**, and then to the RF transmitter **206**. As such, in one embodiment, via the data path described above, the transmitter unit **102** is configured to transmit to the receiver **104** (FIG. 1), via the communication link **103** (FIG. 1), processed and encoded data signals received from the sensor **101** (FIG. 1). Additionally, the unidirectional communication data path between the analog interface **201** and the RF transmitter **206** discussed above allows for the configuration of the transmitter unit **102** for operation upon completion of the manufacturing process as well as for direct communication for diagnostic and testing purposes.

As discussed above, the transmitter processor **204** is configured to transmit control signals to the various sections of the transmitter unit **102** during the operation of the transmitter unit **102**. In one embodiment, the transmitter processor **204**

5

also includes a memory (not shown) for storing data such as the identification information for the transmitter unit **102**, as well as the data signals received from the sensor **101**. The stored information may be retrieved and processed for transmission to the receiver **104** under the control of the transmitter processor **204**. Furthermore, the power supply **207** may include a commercially available battery.

The transmitter unit **102** is also configured such that the power supply section **207** is capable of providing power to the transmitter for a minimum of three months of continuous operation after having been stored for 18 months in a low-power (non-operating) mode. In one embodiment, this may be achieved by the transmitter processor **204** operating in low power modes in the non-operating state, for example, drawing no more than approximately 1 μ A of current. Indeed, in one embodiment, the final step during the manufacturing process of the transmitter unit **102** may place the transmitter unit **102** in the lower power, non-operating state (i.e., post-manufacture sleep mode). In this manner, the shelf life of the transmitter unit **102** may be significantly improved.

Referring yet again to FIG. 2, the temperature detection section **203** of the transmitter unit **102** is configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust the analyte readings obtained from the analog interface **201**. The RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of 315 MHz to 322 MHz, for example, in the United States. Further, in one embodiment, the RF transmitter **206** is configured to modulate the carrier frequency by performing Frequency Shift Keying and Manchester encoding. In one embodiment, the data transmission rate is 19,200 symbols per second, with a minimum transmission range for communication with the receiver **104**.

Additional detailed description of the analyte monitoring system, its various components including the functional descriptions of the transmitter unit are provided in U.S. Pat. No. 6,175,752 issued Jan. 16, 2001 entitled "Analyte Monitoring Device and Methods of Use", and in application Ser. No. 10/745,878 filed Dec. 26, 2003 entitled "Continuous Glucose Monitoring System and Methods of Use", each assigned to the Assignee of the present application.

FIGS. 3A-3B illustrate a bottom view of the transmitter unit housing with counter electrode contact in accordance with one embodiment of the present invention. Referring to FIG. 3A, the housing of the transmitter unit **102** is provided with a temperature probe **301** on the bottom surface of the transmitter unit **102** housing. In one embodiment, the temperature probe **301** is operatively coupled to the temperature measurement section **203** (FIG. 2) of the transmitter unit **102**, and configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust or modify the analyte readings obtained from the analog interface **201**. Also shown in FIG. 3A is a plurality of contact points **302**, two of which are configured to operatively couple to a respective one of the working electrode and the reference electrode of the analyte sensor.

In this manner, in one embodiment of the present invention, using the two electrode analyte sensor, the counter reference point is provided by the skin contact point established with a connection to the conductive exterior housing of the temperature probe **301**. Accordingly, the analyte sensor may be configured with working electrode and the reference electrode only, and the counter electrode may be provided external to the patient's body.

Referring now to FIG. 3B, there is provided a plurality of contacts **303** disposed substantially at a predetermined pattern (for example, concentric, circular, or any other suitable

6

spatial arrangement or distribution) on the bottom surface of the transmitter unit **102**. Each of the plurality of contacts **303** are configured to establish on-skin contact when the transmitter unit **102** is worn on the patient's body. Moreover, each of the plurality of contacts **303** is configured for electrical communication with the counter electrode connection **214** (FIG. 2).

Moreover, in one embodiment, by providing a plurality of counter electrode contacts on the external surface of the transmitter unit **102** housing in contact with the patient's skin, slight displacement of the transmitter unit **102** and/or the sensor segment (including the working and the reference electrodes in fluid contact with the patient's analytes) ensures that the external counter electrode **214** connection to the transmitter unit **102** is retained even if one or more of the counter electrode contact **603** temporarily separate from physically connecting to the patient's skin. In this manner, an effective redundancy is provided to improve potential sensor failure modes by having a separate connection to the external counter electrode **214**.

FIGS. 4A-4C each illustrates the transmitter unit coupled with an analyte sensor with external counter electrode in accordance with various alternate embodiments of the present invention. Referring to FIG. 4A, transmitter unit **102** is operatively coupled to an analyte sensor system which includes a first sensor segment **402** including the working and reference electrodes, and at least a portion of which is configured to be placed subcutaneously in a patient, so as to maintain fluid contact with the patient's analyte. Additionally, there is also provided a second sensor segment **401** including a counter electrode which is provided wholly and substantially entirely outside of the patient's body, and in electrical contact with the transmitter unit **102**. More specifically, in one embodiment, the second sensor segment **401** including the counter electrode is provided on the transmitter unit **102** so as to be in physical contact with the patient's skin during the time that the transmitter unit **102** is worn by the patient (e.g., by placement and securement of the transmitter unit **102** on the patient's skin).

Referring to FIG. 4B, it can be seen that the transmitter unit **102** is coupled to a sensor housing **410** by a physical connection **420** which may include, among others, a cable connection. In this embodiment, the first sensor segment **402** is provided in the sensor housing **410** as shown in the Figure, while the second sensor segment **401** is provided on the transmitter unit **102** housing. The sensor housing **410** in one embodiment is configured to be positioned on the patient's skin, and further, to retain the subcutaneously placed first sensor segment **402** in fluid contact with the patient's analyte. In one embodiment, the physical connection **420** is configured to provide electrical connection between the transmitter unit **102** and the first sensor segment **402** such that the detected analyte level of the patient from the first sensor segment **402** may be provided to the transmitter unit **102** for data transmission and/or processing.

Referring to FIG. 4C, it can be seen that the first sensor segment **402** including the working electrode and the reference electrode, and the second sensor segment **401** including the counter electrode of the analyte sensor, are both provided in the sensor housing **410**. More specifically, compared to the embodiment shown in FIG. 4B, the first sensor segment **401** as shown in FIG. 4C is provided on the sensor housing **410** so as to be in physical contact with the surface of the patient's skin. In this manner, the first sensor segment **420** and the second sensor segment **410** are both configured for electrical communication with the transmitter unit **102** by the physical connection **420**.

7

FIGS. 5A and 5B illustrate the side cross-sectional view and bottom view of the transmitter unit coupled with an analyte sensor with external counter electrode with dislocation detection mechanism in accordance with one embodiment of the present invention. It can be seen that the illustration shown in FIG. 5B is along the direction following arrow A shown in FIG. 5A. Referring to FIGS. 5A and 5B, there is provided an insulation layer 510 which is provided between the patient's skin and the transmitter unit 102. For example, the insulation layer 510 may include an adhesive layer for securely retaining the transmitter unit 102 on the patient's skin. Also shown in FIGS. 5A-5B is a conductive segment 520 disposed in the insulation layer 510 to substantially surround the first sensor segment 402, and which is configured to physically couple with the second sensor segment 401 including the counter electrode of the sensor 101.

In this manner, in one embodiment of the present invention, the counter electrode of the second sensor segment 401 maintains contact with the patient's skin through the conductive segment 520 of the insulation layer 510, and when the transmitter unit 102 is dislocated (for example, by inadvertent movement of the transmitter unit 102 housing after placement on the patient, and thus dislocating the position of the sensor 101), interruption of the contact between the first sensor segment 402 and the conductive segment 520 of the insulation layer 510 may be detected through a change in the counter electrode voltage level. This change in voltage level at the counter electrode may be associated with an alarm condition on the transmitter unit 102 detected by the processor unit 204 (FIG. 2), to provide a warning to the patient indicating a dislocation of the transmitter unit 102, and further, a possible sensor dislocation from the measuring site of the patient that may lead to erroneous and/or no measured data associated with the patient's analyte level.

FIG. 6A illustrates a two working electrode analyte sensor with external counter electrode, FIG. 6B illustrates a three working electrode analyte sensor with external counter electrode in accordance with various embodiments of the present invention, and FIG. 6C illustrates a two working electrode analyte sensor with external counter electrode of another embodiment. Referring to FIG. 6A, a sensor system in one embodiment may include a substrate layer 601 with two working electrodes 602, 603 disposed thereon, as well as a reference electrode 604. Since the counter electrode in the three electrode sensor system in one embodiment is provided externally, using substantially the same sensor dimensions, a two working electrode sensor system may be obtained. Furthermore, since the counter electrode of the second sensor segment 401 is placed external to the patient, in one embodiment, the plurality of working electrodes 602, 603 may share the same external counter electrode of the second sensor segment 401.

Referring to FIG. 6B, in yet another embodiment, a third working electrode 605 may be configured to be part of the sensor system that includes a counter electrode (external), a reference electrode 604, and multiple working electrodes 602, 603, 605. In this manner, multiple working electrodes in the analyte sensor system may improve and/or facilitate sensor calibration and accuracy of measured data. In addition, each of the three working electrodes 602, 603, 605 (or more), may be configured to work with a single external counter electrode of the second sensor segment 401. Referring now to FIG. 6C, a sensor electrode configuration in accordance with still another embodiment includes two working electrodes 602, 603 and a reference electrode 604 provided on the substrate 601, where the three electrodes are configured to be in electrical communication with the single external counter

8

electrode (FIG. 2, contact 214, for example). Compared with the embodiment shown in FIG. 6A, the analyte sensor system shown in FIG. 6C is provided with a one segment of the sensor which is configured to be in fluid contact with the analyte of the patient (rather than two segments, one for each working electrode as shown in FIG. 6A).

FIG. 7 illustrates a cross sectional view of a two sided analyte sensor with external counter electrode in accordance with one embodiment of the present invention. Referring to FIG. 7, a two sided three electrode sensor system is provided with a substrate 701 with a working electrode 702 disposed on a first side of the substrate 701, and a reference electrode 703 disposed on a second side of the substrate 701, the first and second sides of the substrate 701 being opposite sides. As compared with a single sided sensor configuration where each electrode layer separated by a thin layer of insulation material such as Melinex, in the embodiment shown in FIG. 7, the working electrode 701 is separated from the reference electrode 702 by the relatively thick substrate layer 701.

In this manner, during the screen printing process for manufacturing the sensors, the potential for the thin insulation layer shorting the two electrode layers that it is separating can be minimized since the thickness of the substrate layer 701 provides substantial separation between the working electrode layer 702 and the reference electrode layer 703. Moreover, referring back to FIG. 7, in one embodiment, there is provided a conducting path such as a via 704 through the substrate layer 701 so as to provide the sensor electrode contacts on the same side of the substrate 701. The via 704 in one embodiment is configured to provide electrical connection between the reference electrode 703 and the opposite side of the substrate layer 701 so that the transmitter unit 102 may be electrically coupled to the sensor on the side of the sensor where the working electrode 702 is disposed. Moreover, in the case where the transmitter contacts are disposed on the reference electrode 703 side of the sensor, the via 704 may be positioned on the reference electrode layer 703.

Alternatively, the via 704 may be removed from the sensor configuration in which case, the transmitter unit 102 is configured to electrically coupled to the sensor on both sides of the substrate 701 to establish electrical connection to the working electrode 702 and the reference electrode 703. For example, referring back to FIGS. 4B and 4C, it can be seen that the sensor housing 410 may include contacts for each of the working, reference and counter electrodes so as to electrically communicate with the transmitter unit 102 over the connection 420. In this case, the sensor housing 410 may be configured to provide electrical contacts to both sides of the sensor substrate 701 so that the sensor housing 420 may be configured to establish electrical contacts with the working electrode 702 and the reference electrode 703 disposed on opposite sides of the substrate layer 701.

In the manner described above, in accordance with the various embodiments of the present invention, it is possible to achieve cost reduction and/or increased yield in the manufacturing of analyte sensors by, for example, removing the counter electrode from the sensor configuration which, in the screen printing process or any other processes for manufacturing the analyte sensors for example, may eliminate a number of necessary and/or critical manufacturing steps. For example, in one embodiment, it may no longer be necessary to obtain precise alignment of the carbon layers for the electrodes during the screen printing process in the manufacturing of the two sided analyte sensor, as there is no potential for shorting the electrodes through the thin insulation layers disposed between the carbon layers during the manufacturing process. Moreover, in one embodiment, by providing the

working and the reference electrodes on two opposite surfaces of the analyte sensor, it may be possible to achieve cost and sensor size reduction which are desirable.

In addition, by eliminating the number of requisite electrical contact points between the transmitter unit and the analyte sensor electrodes from three (working, reference and counter) to two contact points (working and reference electrodes), analyte monitoring system failure can be improved, for example, resulting from introduction of foreign or undesirable matters such as water between the transmitter contacts and the respective electrodes of the analyte sensor.

In yet a further embodiment, the external counter electrode may be configured as a patient alert feature, such as an alarm for notifying failure modes of the sensor such as the adhesive failure. More specifically, by monitoring the signal level on the external counter electrode, alarm conditions may be easily and accurately provided to the patient. For example, displacement of the subcutaneously placed analyte sensor from the desired implanted position to a position where the measured values are no longer accurate can be detected by monitoring the voltage level of the external counter electrode. Moreover, in the case when the sensor is accidentally retracted from the implanted position, the counter electrode voltage will correspondingly change, and thus, such sensor failure mode may be easily and readily detected using the external counter electrode.

Accordingly, an analyte sensor system in one embodiment of the present invention includes a substrate, a first electrode disposed on a first surface of the substrate, a second electrode disposed on a second surface of the substrate, and a third electrode provided in electrical contact with at least one of the first or second electrode, where at least a portion of the first electrode and the second electrode are subcutaneously positioned in a patient, and where the third electrode is substantially entirely positioned external to the patient.

In one embodiment, the first electrode is a working electrode, the second electrode is a reference electrode, and the third electrode is a counter electrode.

Moreover, the first and second surfaces of the substrate may be the same. Alternatively, the first surface of the substrate may be on the opposite side of the substrate as the second surface of the substrate.

In still another embodiment, the analyte may include one of an interstitial fluid or blood.

The system in a further embodiment may include a second working electrode at least a portion of which is subcutaneously positioned in the patient.

The third electrode may in one embodiment include an external skin contact counter electrode.

In yet another embodiment, the system may also include a transmitter unit configured to establish electrical contact with one or more of the first, second or third electrodes.

Also, the third electrode may be disposed on a surface of the transmitter unit such that at least a portion of the third electrode is in physical contact with the patient's skin and the transmitter unit.

Moreover, the system may additionally include an alarm unit configured to alert the patient when the third electrode physically separates from the skin of the patient. In one aspect, the alarm unit may be integrated in the transmitter unit.

A method of providing an analyte sensor in another embodiment includes providing a substrate, disposing a first electrode on a first surface of the substrate, disposing a second electrode on a second surface of the substrate, and positioning

a third electrode in electrical contact with the first and second electrodes, where the third electrode is substantially entirely external to the patient.

The method may further include the step of disposing a second working electrode on either of said first or second surface of the substrate, where at least a portion of the second working electrode may be subcutaneously positioned in the patient.

A system for monitoring analyte in a patient in still a further embodiment of the present invention includes a sensor including a working electrode, a reference electrode, and a counter electrode, at least a portion of the sensor configured for transcutaneous placement in a patient such that the at least the portion of the sensor is in fluid contact with an analyte of the patient, and wherein the counter electrode is provided on the external surface of the patient's skin, and a transmitter unit operatively coupled to the sensor and configured to receive one or more signals from the sensor corresponding to an analyte level of the patient.

In one embodiment, the portion of the sensor in fluid contact with the Patient's analyte includes a portion of the working electrode.

Additionally, the counter electrode may be positioned substantially completely external to the body of the patient, and further, the counter electrode may be configured for electrical communication with the transmitter unit.

Various other modifications and alterations in the structure and method of operation of this invention will be apparent to those skilled in the art without departing from the scope and spirit of the invention. Although the invention has been described in connection with specific preferred embodiments, it should be understood that the invention as claimed should not be unduly limited to such specific embodiments. It is intended that the following claims define the scope of the present invention and that structures and methods within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

1. A system for monitoring analyte in a patient, comprising:

a sensor including a first and a second electrode disposed thereon wherein at least a portion of the sensor is configured for transcutaneous placement in a patient such that at least one of the first and second electrodes is in fluid contact with an analyte of a patient; and

a transmitter unit operatively coupled to the sensor and configured to receive one or more signals from the sensor corresponding to an analyte level of the patient, wherein an external surface of the transmitter comprises at least one conductive point in electrical contact with a third electrode, wherein the at least one conductive point is in contact with the patient's skin when the transmitter is operatively coupled to the sensor.

2. The system of claim 1 wherein the third electrode is positionable external to the patient.

3. The system of claim 1 wherein the third electrode is disposed on a portion of the sensor that is positionable external to the patient.

4. The system of claim 1 wherein the external surface of the transmitter comprises a plurality of conductive points in electrical contact with the third electrode, wherein the plurality of conductive points are disposed substantially in a predetermined pattern.

5. The system of claim 1 wherein the at least one conductive point comprises a conductive segment disposed in an insulation layer substantially surrounding the portion of the sensor configured for transcutaneous placement.

11

6. The system of claim **5** wherein the insulation layer is disposed on a portion of the external surface of the transmitter and comprises an adhesive for securing the transmitter to the patient's skin.

7. The system of claim **1** wherein the first electrode is a working electrode, the second electrode is a reference electrode and the third electrode is a counter electrode.

8. The system of claim **7** further comprising at least a second working electrode.

9. The system of claim **8** wherein at least a portion of the second working electrode is subcutaneously positionable in the patient.

12

10. The system of claim **1** wherein the sensor comprises a substrate.

11. The system of claim **10** wherein the first electrode is disposed on a first surface of the substrate and the second electrode is disposed on a second surface of the substrate.

12. The system of claim **10** wherein the first and second electrodes are disposed on a first surface of the substrate.

13. The system of claim **1** further comprising an alarm unit configured to alert the patient when the third electrode is no longer in electrical contact with the skin of the patient.

14. The system of claim **13** wherein the alarm unit is integrated with the transmitter unit.

* * * * *