



US007728721B2

(12) **United States Patent**
Schofield et al.

(10) **Patent No.:** **US 7,728,721 B2**
(45) **Date of Patent:** **Jun. 1, 2010**

(54) **ACCESSORY SYSTEM SUITABLE FOR USE
IN A VEHICLE**

(75) Inventors: **Kenneth Schofield**, Holland, MI (US);
Niall R. Lynam, Holland, MI (US)

(73) Assignee: **Donnelly Corporation**, Holland, MI
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 55 days.

(21) Appl. No.: **12/276,770**

(22) Filed: **Nov. 24, 2008**

(65) **Prior Publication Data**

US 2009/0134606 A1 May 28, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/441,592, filed on
May 26, 2006, now Pat. No. 7,460,007, which is a
continuation of application No. 10/940,545, filed on

(Continued)

(60) Provisional application No. 60/263,680, filed on Jan.
23, 2001, provisional application No. 60/243,986,
filed on Oct. 27, 2000, provisional application No.
60/238,483, filed on Oct. 6, 2000, provisional applica-
tion No. 60/237,077, filed on Sep. 30, 2000, provi-
sional application No. 60/234,412, filed on Sep. 21,
2000, provisional application No. 60/218,336, filed on
Jul. 14, 2000, provisional application No. 60/186,520,
filed on Mar. 2, 2000.

(51) **Int. Cl.**
B60R 1/00 (2006.01)

(52) **U.S. Cl.** **340/438; 340/461; 340/815.49**

(58) **Field of Classification Search** **340/438,**
340/442, 443, 457, 461, 462, 815.48, 815.49;
307/10.1, 10.2; 362/492, 494, 503

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,166,303 A	7/1939	Hodny et al.	
3,185,020 A	5/1965	Thelen	88/1
3,432,225 A	3/1969	Rock	350/164

(Continued)

FOREIGN PATENT DOCUMENTS

DE	941408	4/1956
DE	944531	7/1956
DE	7323996	11/1973

(Continued)

OTHER PUBLICATIONS

PCT Search Report for PCT/US01/06122 dated Jun. 5, 2001, which
corresponds to the present application.
Japanese Patent Abstract for Document No. 11254925 dated Sep. 21,
1999.

(Continued)


Primary Examiner—Van T. Trieu

(74) *Attorney, Agent, or Firm*—Van Dyke, Gardner, Linn &
Burkhart, LLP

(57) **ABSTRACT**

An accessory system suitable for use in an interior cabin of a
vehicle includes an attachment element adhesively attached to
an interior surface of a windshield of a vehicle, and an
accessory module. The accessory module includes structure
adapted to attach to the attachment element. The accessory
module encompasses an antenna and a forward facing cam-
era. The forward facing camera has a forward field of view
through the windshield of the vehicle and in the direction of
forward travel of the vehicle. The accessory system may
include an image processor for processing image data cap-
tured by the forward facing camera. The forward facing cam-
era may capture images for at least one of a collision avoid-
ance system and an automatic headlamp control system.

57 Claims, 21 Drawing Sheets



Related U.S. Application Data

Sep. 14, 2004, now Pat. No. 7,053,761, which is a continuation of application No. 10/232,122, filed on Aug. 30, 2002, now Pat. No. 6,975,215, which is a continuation of application No. 09/710,016, filed on Nov. 10, 2000, now Pat. No. 6,445,287, which is a continuation-in-part of application No. 09/513,941, filed on Feb. 28, 2000, now Pat. No. 6,294,989, application No. 12/276,770, which is a continuation-in-part of application No. 12/467,660, filed on May 18, 2009, which is a continuation of application No. 12/197,660, filed on Aug. 25, 2008, now Pat. No. 7,538,316, which is a continuation of application No. 11/828,880, filed on Jul. 26, 2007, now Pat. No. 7,420,159, which is a continuation of application No. 11/699,271, filed on Jan. 29, 2007, now Pat. No. 7,265,342, which is a continuation of application No. 11/418,906, filed on May 5, 2006, now Pat. No. 7,262,406, which is a continuation of application No. 10/913,748, filed on Aug. 6, 2004, now Pat. No. 7,041,965, which is a continuation of application No. 10/618,334, filed on Jul. 11, 2003, now Pat. No. 6,774,356, which is a continuation of application No. 09/997,579, filed on Nov. 29, 2001, now Pat. No. 6,593,565, which is a continuation of application No. 09/433,467, filed on Nov. 4, 1999, now Pat. No. 6,326,613, which is a continuation-in-part of application No. 09/003,966, filed on Jan. 7, 1998, now Pat. No. 6,250,148, application No. 12/276,770, which is a continuation-in-part of application No. 12/052,341, filed on Mar. 20, 2008, which is a continuation of application No. 11/625,374, filed on Jan. 22, 2007, which is a continuation of application No. 10/755,915, filed on Jan. 13, 2004, now Pat. No. 7,446,650, which is a continuation of application No. 09/793,002, filed on Feb. 26, 2001, now Pat. No. 6,690,268, and a continuation-in-part of application No. 10/232,122, filed on Aug. 30, 2002, now Pat. No. 6,975,215, which is a continuation of application No. 09/710,016, filed on Nov. 10, 2000, now Pat. No. 6,445,287, which is a continuation-in-part of application No. 09/513,941, filed on Feb. 28, 2000, now Pat. No. 6,294,989, which is a continuation-in-part of application No. 09/213,075, filed on Dec. 16, 1998, now Pat. No. 6,124,647, said application No. 10/755,915 is a continuation-in-part of application No. 10/279,059, filed on Oct. 23, 2002, now Pat. No. 6,774,774, which is a continuation of application No. 09/876,816, filed on Jun. 7, 2001, now Pat. No. 6,472,979, which is a continuation of application No. 09/513,941, filed on Feb. 28, 2000, now Pat. No. 6,294,989, which is a continuation-in-part of application No. 09/213,075, filed on Dec. 16, 1998, now Pat. No. 6,124,647, said application No. 10/755,915 is a continuation-in-part of application No. 10/618,334, filed on Jul. 11, 2003, now Pat. No. 6,774,356, which is a continuation of application No. 09/997,579, filed on Nov. 29, 2001, now Pat. No. 6,593,565, which is a continuation of application No. 09/433,467, filed on Nov. 4, 1999, now Pat. No. 6,326,613, which is a continuation-in-part of application No. 09/003,966, filed on Jan. 7, 1998, now Pat. No. 6,250,148, said application No. 10/755,915 is a continuation-in-part of application No. 10/270,830, filed on Oct. 15, 2002, now Pat. No. 6,717,524, which is a continuation of application No. 09/903,336, filed on Jul. 11, 2001, now Pat. No. 6,466,136, which is a

continuation of application No. 09/396,179, filed on Sep. 14, 1999, now Pat. No. 6,278,377, which is a continuation-in-part of application No. 09/382,720, filed on Aug. 25, 1999, now Pat. No. 6,243,003.

(56)

References Cited

U.S. PATENT DOCUMENTS

3,543,018	A	11/1970	Barcus et al.	
3,557,265	A	1/1971	Chisholm et al.	
3,565,985	A	2/1971	Schrenk et al.	
3,628,851	A	12/1971	Robertson	
3,676,668	A	7/1972	Collins et al.	
3,711,176	A	1/1973	Alfrey, Jr. et al.	
3,781,090	A	12/1973	Sumita	350/164
3,821,590	A	6/1974	Kosman et al.	
3,860,847	A	1/1975	Carley	
4,035,681	A	7/1977	Savage	
4,065,750	A	12/1977	Duncan et al.	
4,075,468	A	2/1978	Marcus	
4,109,235	A	8/1978	Bouthors	
4,211,955	A	7/1980	Ray	
4,214,266	A	7/1980	Myers	
4,228,490	A	10/1980	Thillays	
4,257,703	A	3/1981	Goodrich	
4,274,078	A	6/1981	Isobe et al.	
4,277,804	A	7/1981	Robison	
4,281,899	A	8/1981	Oskam	
4,306,768	A	12/1981	Egging	
4,310,851	A	1/1982	Pierrat	
4,331,382	A	5/1982	Graff	
4,377,613	A	3/1983	Gordon	
4,419,386	A	12/1983	Gordon	
4,435,042	A	3/1984	Wood et al.	350/281
4,436,371	A	3/1984	Wood et al.	350/281
4,446,171	A	5/1984	Thomas	427/160
4,490,227	A	12/1984	Bitter	
4,499,451	A	2/1985	Suzuki et al.	
4,524,941	A	6/1985	Wood et al.	
4,546,551	A	10/1985	Franks	
4,580,196	A	4/1986	Task	
4,588,267	A	5/1986	Pastore	
4,630,904	A	12/1986	Pastore	
4,638,287	A	1/1987	Umebayashi et al.	
4,646,210	A	2/1987	Skogler et al.	362/142
4,646,673	A	3/1987	Fordyce	
4,665,430	A	5/1987	Hiroyasu	
4,692,798	A	9/1987	Seko et al.	
4,712,879	A	12/1987	Lynam et al.	350/357
4,729,076	A	3/1988	Masami et al.	
4,733,335	A	3/1988	Serizawa et al.	
4,733,336	A	3/1988	Skogler et al.	362/142
4,740,838	A	4/1988	Mase et al.	
4,761,061	A	8/1988	Nishiyama et al.	
4,780,752	A	10/1988	Angerstein et al.	
4,781,436	A	11/1988	Armbruster	350/281
4,793,690	A	12/1988	Gahan et al.	350/279
4,793,695	A	12/1988	Wada et al.	
4,807,096	A	2/1989	Skogler et al.	
4,855,161	A	8/1989	Moser et al.	
4,859,867	A	8/1989	Larson et al.	307/10.1
4,871,917	A	10/1989	O'Farrell et al.	250/341
4,882,565	A	11/1989	Gallmeyer	340/461
4,883,349	A	11/1989	Mittelhäuser	
4,895,097	A	1/1990	Lechnir	
4,910,591	A	3/1990	Petrosian et al.	
4,916,374	A	4/1990	Schierbeek et al.	318/483
4,930,742	A	6/1990	Schofield et al.	248/475.1
4,935,665	A	6/1990	Murata	
4,936,533	A	6/1990	Adams et al.	248/222.1
4,953,305	A	9/1990	Van Lente et al.	
4,956,591	A	9/1990	Schierbeek et al.	318/483

US 7,728,721 B2

Page 3

4,959,247 A	9/1990	Moser et al.	5,515,448 A	5/1996	Nishitani
4,959,865 A	9/1990	Stettiner et al. 381/46	5,521,760 A	5/1996	De Young et al. 359/601
4,973,844 A	11/1990	O'Farrell et al. 250/341	5,523,811 A	6/1996	Wada et al.
4,996,083 A	2/1991	Moser et al.	5,525,264 A	6/1996	Cronin et al. 252/583
5,005,213 A	4/1991	Hanson et al.	5,528,474 A	6/1996	Roney et al.
5,006,971 A	4/1991	Jenkins	5,530,240 A	6/1996	Larson et al. 250/214
5,014,167 A	5/1991	Roberts 362/83.1	5,530,421 A	6/1996	Marshall et al.
5,016,996 A	5/1991	Ueno	5,535,056 A	7/1996	Caskey et al. 359/603
5,027,200 A	6/1991	Petrossian et al.	5,535,144 A	7/1996	Kise
5,038,255 A	8/1991	Nishihashi et al.	5,541,590 A	7/1996	Nishio
5,058,851 A	10/1991	Lawlor et al. 248/549	5,550,677 A	8/1996	Schofield et al. 359/604
5,066,112 A	11/1991	Lynam et al. 359/267	5,567,360 A	10/1996	Varaprasad et al. 252/583
5,073,012 A	12/1991	Lynam 359/265	5,570,127 A	10/1996	Schmidt
5,076,673 A	12/1991	Lynam et al. 359/271	5,572,354 A	11/1996	Desmond et al. 359/265
5,076,674 A	12/1991	Lynam 359/274	5,574,443 A	11/1996	Hsieh
5,100,095 A	3/1992	Haan et al. 248/549	5,576,687 A	11/1996	Blank et al. 340/438
5,117,346 A	5/1992	Gard 363/51	5,576,975 A	11/1996	Sasaki et al.
5,121,200 A	6/1992	Choi et al.	5,587,236 A	12/1996	Agrawal et al. 428/334
5,136,483 A	8/1992	Schöniger et al. 362/61	5,602,542 A	2/1997	Widmann et al.
5,140,455 A	8/1992	Varaprasad et al. 359/275	5,610,756 A	3/1997	Lynam et al. 359/267
5,142,407 A	8/1992	Varaprasad et al. 359/276	5,611,966 A	3/1997	Varaprasad et al.
5,151,816 A	9/1992	Varaprasad et al. 359/275	5,615,023 A	3/1997	Yang
5,151,824 A	9/1992	O'Farrell	5,615,857 A	4/1997	Hook 248/549
5,160,200 A	11/1992	Cheselske	5,617,085 A	4/1997	Tsutsumi et al.
5,160,201 A	11/1992	Wrobel	5,632,092 A	5/1997	Blank et al.
5,178,448 A	1/1993	Adams et al. 362/83.1	5,632,551 A	5/1997	Roney et al.
5,179,471 A	1/1993	Caskey et al.	5,634,709 A	6/1997	Iwama
5,189,537 A	2/1993	O'Farrell	5,642,238 A	6/1997	Sala
5,193,029 A	3/1993	Schofield et al. 359/604	5,644,851 A	7/1997	Blank et al.
5,197,562 A	3/1993	Kakinami et al.	5,646,614 A	7/1997	Abersfelder et al.
5,207,492 A	5/1993	Roberts 362/30	5,649,756 A	7/1997	Adams et al. 362/83.1
5,230,400 A	7/1993	Kakinami et al.	5,650,765 A	7/1997	Park
5,233,461 A	8/1993	Dornan et al.	5,654,686 A	8/1997	Geschke et al.
5,239,405 A	8/1993	Varaprasad et al.	5,662,375 A	9/1997	Adams et al. 296/214
5,243,417 A	9/1993	Pollard	5,668,663 A	9/1997	Varaprasad et al. 359/608
5,252,354 A	10/1993	Cronin et al.	5,669,698 A	9/1997	Veldman et al. 362/83.1
5,253,109 A	10/1993	O'Farrell et al. 359/604	5,669,699 A	9/1997	Pastrick et al.
5,255,442 A	10/1993	Schierbeek et al.	5,669,704 A	9/1997	Pastrick
5,277,986 A	1/1994	Cronin et al.	5,669,705 A	9/1997	Pastrick et al.
5,285,060 A	2/1994	Larson et al. 250/214	5,670,935 A	9/1997	Schofield et al. 340/461
5,289,321 A	2/1994	Secor	5,671,996 A	9/1997	Bos et al. 362/83.1
5,296,924 A	3/1994	Blancard et al.	5,673,994 A	10/1997	Fant, Jr. et al. 362/831
5,303,205 A	4/1994	Gauthier et al.	5,680,123 A	10/1997	Lee
5,304,980 A	4/1994	Maekawa	5,680,245 A	10/1997	Lynam 359/265
5,330,149 A	7/1994	Haan et al. 248/549	5,699,044 A	12/1997	Van Lente et al.
5,355,284 A	10/1994	Roberts	5,708,410 A	1/1998	Blank et al. 340/438
5,361,190 A	11/1994	Roberts et al.	5,708,857 A	1/1998	Ishibashi
5,371,659 A	12/1994	Pastrick et al.	5,715,093 A	2/1998	Schierbeek et al. 359/601
5,386,285 A	1/1995	Asayama	5,724,187 A	3/1998	Varaprasad et al. 359/608
5,406,414 A	4/1995	O'Farrell et al. 359/604	5,724,316 A	3/1998	Brunts
5,408,357 A	4/1995	Beukema	5,729,194 A	3/1998	Spears et al.
5,414,461 A	5/1995	Kishi et al.	5,737,226 A	4/1998	Olson et al.
5,416,313 A	5/1995	Larson et al. 250/214	5,741,966 A	4/1998	Handfield et al. 73/146.5
5,416,478 A	5/1995	Morinaga	5,745,050 A	4/1998	Nakagawa
5,418,610 A	5/1995	Fischer	5,751,211 A	5/1998	Shirai et al.
5,424,865 A	6/1995	Lynam	5,751,489 A	5/1998	Caskey et al. 359/603
5,424,952 A	6/1995	Asayama	5,754,099 A	5/1998	Nishimura et al.
5,432,496 A	7/1995	Lin	5,760,828 A	6/1998	Cortes
5,439,305 A	8/1995	Santo 403/76	5,760,962 A	6/1998	Schofield et al. 359/604
5,444,478 A	8/1995	LeLong et al.	5,761,094 A	6/1998	Olson et al.
5,446,576 A	8/1995	Lynam et al. 359/267	5,764,139 A	6/1998	Nojima et al.
5,469,298 A	11/1995	Suman et al.	5,765,940 A	6/1998	Levy et al.
5,475,366 A	12/1995	Van Lente et al. 340/525	5,767,793 A	6/1998	Agravante et al.
5,475,494 A	12/1995	Nishida et al.	5,774,283 A	6/1998	Nagel et al.
5,481,409 A	1/1996	Roberts	5,775,762 A	7/1998	Vitito
5,483,453 A	1/1996	Uemura et al.	5,786,772 A	7/1998	Schofield et al.
5,485,378 A	1/1996	Franke et al.	5,788,357 A	8/1998	Muth et al.
5,487,522 A	1/1996	Hook 248/549	5,790,973 A	8/1998	Blaker et al.
5,488,352 A	1/1996	Jasper	5,793,308 A	8/1998	Rosinski et al.
5,488,496 A	1/1996	Pine	5,793,420 A	8/1998	Schmidt
5,497,305 A	3/1996	Pastrick et al.	5,796,094 A	8/1998	Schofield et al. 250/208.1
5,497,306 A	3/1996	Pastrick 362/83.1	5,796,176 A	8/1998	Kramer et al. 307/10.1
5,500,760 A	3/1996	Varaprasad et al.	5,798,575 A	8/1998	O'Farrell et al. 307/10.1

US 7,728,721 B2

Page 4

5,798,688 A	8/1998	Schofield	340/438	6,099,155 A	8/2000	Pastrick et al.
5,802,727 A	9/1998	Blank et al.		6,100,798 A	8/2000	Liang
5,803,579 A	9/1998	Turnbull et al.	362/83.1	6,102,559 A	8/2000	Nold et al.
5,805,367 A	9/1998	Kanazawa		6,104,552 A	8/2000	Thau et al. 359/726
5,806,965 A	9/1998	Deese		6,106,121 A	8/2000	Buckley et al.
5,808,777 A	9/1998	Lynam et al.	359/265	6,111,498 A	8/2000	Jobes et al.
5,813,745 A	9/1998	Fant, Jr. et al.	362/83.1	6,115,651 A	9/2000	Cruz
5,820,097 A	10/1998	Spooner	248/549	6,116,743 A	9/2000	Hoek
5,820,245 A	10/1998	Desmond et al.	362/83.1	6,122,597 A	9/2000	Saneyoshi et al.
5,823,654 A	10/1998	Pastrick et al.		6,124,647 A	9/2000	Marcus et al.
5,825,283 A	10/1998	Camhi		6,124,886 A	9/2000	DeLine et al.
5,837,891 A	11/1998	Bridge		6,128,576 A	10/2000	Nishimoto et al.
5,844,505 A	12/1998	Van Ryzin		6,132,072 A	10/2000	Turnbull et al.
5,850,176 A	12/1998	Kinoshita et al.		6,139,171 A	10/2000	Waldmann
5,863,116 A	1/1999	Pastrick et al.		6,139,172 A	10/2000	Bos et al. 362/494
5,871,275 A	2/1999	O'Farrell et al.		6,140,933 A	10/2000	Bugno et al.
5,877,707 A	3/1999	Kowalick		6,146,003 A	11/2000	Thau
5,877,897 A	3/1999	Schofield et al.	359/604	6,149,287 A	11/2000	Pastrick et al.
5,878,370 A	3/1999	Olson		6,150,014 A	11/2000	Chu et al.
5,879,074 A	3/1999	Pastrick		6,151,065 A	11/2000	Steed et al.
5,883,739 A	3/1999	Ashihara et al.		6,151,539 A	11/2000	Bergholz et al.
5,899,956 A	5/1999	Chan		6,152,590 A	11/2000	Furst et al.
5,904,729 A	5/1999	Ruzicka		6,154,149 A	11/2000	Tyckowski et al.
5,910,854 A	6/1999	Varaprasad et al.	359/273	6,154,306 A	11/2000	Varaprasad et al. 359/273
5,914,815 A	6/1999	Bos	359/571	6,157,294 A	12/2000	Urai et al.
5,923,027 A	7/1999	Stam et al.	250/208.1	6,158,655 A	12/2000	DeVries, Jr. et al. 235/380
5,924,212 A	7/1999	Domanski	33/355	6,166,625 A	12/2000	Teowee et al. 340/426
5,926,087 A	7/1999	Busch et al.		6,166,628 A	12/2000	Andreas
5,929,786 A	7/1999	Schofield et al.	340/903	6,166,698 A	12/2000	Turnbull et al.
5,938,321 A	8/1999	Bos et al.	362/494	6,166,848 A	12/2000	Cammenga et al.
5,940,011 A	8/1999	Agravante et al.		6,167,755 B1	1/2001	Damson et al.
5,940,120 A	8/1999	Frankhouse et al.	348/61	6,169,955 B1	1/2001	Fultz
5,949,331 A	9/1999	Schofield et al.	340/461	6,172,600 B1	1/2001	Kakinami et al.
5,956,079 A	9/1999	Ridgley		6,172,601 B1	1/2001	Wada et al.
5,956,181 A	9/1999	Lin	359/630	6,172,613 B1	1/2001	DeLine et al. 340/815.4
5,959,367 A	9/1999	O'Farrell et al.	307/10.1	6,173,501 B1	1/2001	Blank et al.
5,959,555 A	9/1999	Furuta		6,175,164 B1	1/2001	O'Farrell et al. 307/10.1
5,971,552 A	10/1999	O'Farrell et al.	359/871	6,175,300 B1	1/2001	Kendrick 340/436
5,975,715 A	11/1999	Bauder		6,176,602 B1	1/2001	Pastrick et al.
6,000,823 A	12/1999	Desmond et al.	362/494	6,178,034 B1	1/2001	Allemand et al. 359/265
6,001,486 A	12/1999	Varaprasad et al.	428/428	6,183,119 B1	2/2001	Desmond et al. 362/494
6,002,511 A	12/1999	Varaprasad et al.	359/265	6,184,781 B1	2/2001	Ramakesavan
6,002,544 A	12/1999	Yatsu	360/78.09	6,185,492 B1	2/2001	Kagawa et al.
6,006,159 A	12/1999	Schmier et al.		6,191,704 B1	2/2001	Takenaga et al.
6,007,222 A	12/1999	Thau		6,196,688 B1	3/2001	Caskey et al. 359/603
6,009,359 A	12/1999	El-Hakim et al.		6,198,409 B1	3/2001	Schofield et al. 340/903
6,016,035 A	1/2000	Eberspacher et al.		6,199,014 B1	3/2001	Walker et al.
6,019,411 A	2/2000	Carter et al.	296/37.7	6,200,010 B1	3/2001	Anders
6,019,475 A	2/2000	Lynam et al.	359/879	6,201,642 B1	3/2001	Bos 359/565
6,023,229 A	2/2000	Bugno et al.		6,207,967 B1	3/2001	Hochstein
6,025,872 A	2/2000	Ozaki et al.		6,210,008 B1	4/2001	Hoekstra et al. 359/603
6,028,537 A	2/2000	Suman et al.		6,217,181 B1	4/2001	Lynam et al. 359/879
6,037,689 A	3/2000	Bingle et al.		6,218,934 B1	4/2001	Regan
6,042,253 A	3/2000	Fant, Jr. et al.	362/494	6,222,447 B1	4/2001	Schofield et al. 340/461
6,045,243 A	4/2000	Muth et al.		6,222,460 B1	4/2001	DeLine et al. 340/815.4
6,046,766 A	4/2000	Sakata		6,227,689 B1	5/2001	Miller
6,046,837 A	4/2000	Yamamoto		6,229,434 B1	5/2001	Knapp et al.
6,060,989 A	5/2000	Gehlot		6,243,003 B1	6/2001	DeLine et al. 340/425.5
6,061,002 A	5/2000	Weber et al.		6,245,262 B1	6/2001	Varaprasad et al.
6,065,840 A	5/2000	Caskey et al.	359/603	6,249,214 B1	6/2001	Kashiwazaki
6,067,111 A	5/2000	Hahn et al.		6,250,148 B1	6/2001	Lynam 73/170.17
6,072,391 A	6/2000	Suzuki et al.		6,250,766 B1	6/2001	Strumolo et al.
6,074,777 A	6/2000	Reimers et al.		6,250,783 B1	6/2001	Stidham et al.
6,078,355 A	6/2000	Zengel		6,257,746 B1	7/2001	Todd et al.
6,078,865 A	6/2000	Koyanagi		6,259,412 B1	7/2001	Duroux
6,082,881 A	7/2000	Hicks		6,259,475 B1	7/2001	Ramachandran et al.
6,086,131 A	7/2000	Bingle et al.	296/76	6,265,968 B1	7/2001	Betzitza et al.
6,086,229 A	7/2000	Pastrick		6,268,803 B1	7/2001	Gunderson et al.
6,087,012 A	7/2000	Varaprasad et al.	428/428	6,269,308 B1	7/2001	Kodaka et al.
6,087,942 A	7/2000	Sleighter, III et al.		6,276,821 B1	8/2001	Pastrick et al.
6,087,953 A	7/2000	DeLine et al.	340/815.4	6,276,822 B1	8/2001	Bedrosian et al.
6,097,023 A	8/2000	Schofield et al.	250/208.1	6,278,377 B1	8/2001	DeLine et al. 340/815.4
6,099,131 A	8/2000	Fletcher et al.	359/604	6,278,941 B1	8/2001	Yokoyama

6,280,068 B1	8/2001	Mertens et al.	6,447,128 B1	9/2002	Lang et al.
6,280,069 B1	8/2001	Pastrick et al.	6,452,533 B1	9/2002	Yamabuchi et al.
6,281,804 B1	8/2001	Haller et al.	6,463,369 B2	10/2002	Sadano et al.
6,286,965 B1	9/2001	Caskey et al. 359/603	6,466,701 B1	10/2002	Ejiri et al.
6,286,984 B1	9/2001	Berg	6,472,977 B1	10/2002	Pöschmüller
6,289,332 B2	9/2001	Menig et al.	6,473,001 B1	10/2002	Blum
6,291,906 B1	9/2001	Marcus et al. 307/10.1	6,474,853 B2	11/2002	Pastrick et al.
6,294,989 B1	9/2001	Schofield et al.	6,476,731 B1	11/2002	Miki et al.
6,296,379 B1	10/2001	Pastrick	6,477,460 B2	11/2002	Kepler
6,296,381 B1	10/2001	Sinn et al.	6,477,464 B2	11/2002	McCarthy et al. 701/213
6,297,781 B1	10/2001	Turnbull et al.	6,483,429 B1	11/2002	Yasui et al.
6,299,333 B1	10/2001	Pastrick et al.	6,483,438 B2	11/2002	DeLine et al.
6,300,879 B1	10/2001	Regan et al.	6,487,500 B2	11/2002	Lemelson et al.
6,304,173 B2	10/2001	Pala et al.	6,494,602 B2	12/2002	Pastrick et al.
6,305,807 B1	10/2001	Schierbeek 359/603	6,498,620 B2	12/2002	Schofield et al.
6,310,611 B1	10/2001	Caldwell	6,498,967 B1	12/2002	Hopkins et al.
6,310,738 B1	10/2001	Chu 359/883	6,501,387 B2	12/2002	Skiver et al.
6,313,454 B1	11/2001	Bos et al. 250/208.1	6,513,252 B1	2/2003	Schierbeek et al.
6,317,057 B1	11/2001	Lee	6,515,581 B1	2/2003	Ho
6,317,248 B1	11/2001	Agrawal et al.	6,515,597 B1	2/2003	Wada et al.
6,318,697 B1	11/2001	Corrado et al.	6,516,664 B2	2/2003	Lynam 75/170.17
6,318,870 B1	11/2001	Spooner et al. 359/872	6,520,667 B1	2/2003	Mousseau
6,320,176 B1	11/2001	Schofield et al.	6,522,451 B1	2/2003	Lynam
6,320,282 B1	11/2001	Caldwell	6,522,969 B2	2/2003	Kannonji
6,320,612 B1	11/2001	Young	6,539,306 B2	3/2003	Turnbull
6,324,295 B1	11/2001	Valery et al.	6,542,085 B1	4/2003	Yang
6,326,613 B1	12/2001	Heslin et al. 250/239	6,542,182 B1	4/2003	Chutorash
6,326,900 B2	12/2001	DeLine et al.	6,545,598 B1	4/2003	De Villeroche
6,329,925 B1	12/2001	Skiver et al. 340/815.4	6,568,839 B1	5/2003	Pastrick et al.
6,330,511 B2	12/2001	Ogura et al.	6,572,233 B1	6/2003	Northman et al.
6,331,066 B1	12/2001	Desmond et al. 362/494	6,575,643 B2	6/2003	Takahashi
6,333,759 B1	12/2001	Mazzilli 348/148	6,580,373 B1	6/2003	Ohashi
6,335,680 B1	1/2002	Matsuoka	6,581,007 B2	6/2003	Hasegawa et al.
6,336,737 B1	1/2002	Thau	6,583,730 B2	6/2003	Lang et al.
6,341,013 B1	1/2002	Battiti et al.	6,591,192 B2	7/2003	Okamura et al.
6,341,523 B2	1/2002	Lynam 73/170.17	6,593,565 B2	7/2003	Heslin et al. 250/239
6,344,805 B1	2/2002	Yasui et al.	6,594,583 B2	7/2003	Ogura et al.
6,348,858 B2	2/2002	Weis et al.	6,594,614 B2	7/2003	Studt et al.
6,353,392 B1	3/2002	Schofield et al. 340/602	6,611,202 B2	8/2003	Schofield et al.
6,356,206 B1	3/2002	Takenaga et al.	6,611,227 B1	8/2003	Nebiyeloul-Kifle
6,357,883 B1	3/2002	Strumolo et al.	6,611,759 B2	8/2003	Brosche
6,362,548 B1	3/2002	Bingle et al.	6,614,387 B1	9/2003	Deadman
6,363,326 B1	3/2002	Scully	6,616,764 B2	9/2003	Krämer et al.
6,366,213 B2	4/2002	DeLine et al. 340/815.4	6,618,672 B2	9/2003	Sasaki et al.
6,370,329 B1	4/2002	Teuchert 396/7	6,627,918 B2	9/2003	Getz et al.
6,371,636 B1	4/2002	Wesson	6,630,888 B2	10/2003	Lang et al.
6,386,742 B1	5/2002	DeLine et al.	6,636,258 B2	10/2003	Strumolo
6,390,529 B1	5/2002	Bingle et al.	6,642,840 B2	11/2003	Lang et al.
6,390,635 B2	5/2002	Whitehead et al.	6,642,851 B2	11/2003	Deline et al.
6,396,397 B1	5/2002	Bos et al.	6,648,477 B2	11/2003	Hutzel et al.
6,408,247 B1	6/2002	Ichikawa et al.	6,665,592 B2	12/2003	Kodama
6,411,204 B1	6/2002	Bloomfield et al.	6,670,207 B1	12/2003	Roberts
6,412,959 B1	7/2002	Tseng	6,670,910 B2	12/2003	Delcheccolo et al.
6,412,973 B1	7/2002	Bos et al. 362/494	6,672,744 B2	1/2004	DeLine et al.
6,415,230 B1	7/2002	Maruko et al.	6,674,370 B2	1/2004	Rodewald et al.
6,416,208 B2	7/2002	Pastrick et al.	6,675,075 B1	1/2004	Engelsberg et al.
6,418,376 B1	7/2002	Olson	6,678,614 B2	1/2004	McCarthy et al.
6,419,300 B1	7/2002	Pavao et al.	6,683,539 B2	1/2004	Trajkovic et al.
6,420,975 B1	7/2002	DeLine et al.	6,683,969 B1	1/2004	Nishigaki et al.
6,421,081 B1	7/2002	Markus	6,685,348 B2	2/2004	Pastrick et al.
6,424,272 B1	7/2002	Gutta et al.	6,690,268 B2	2/2004	Schofield et al.
6,424,273 B1	7/2002	Gutta et al.	6,690,413 B1	2/2004	Moore
6,424,892 B1	7/2002	Matsuoka	6,693,517 B2	2/2004	McCarthy et al.
6,426,492 B1	7/2002	Bos et al.	6,693,518 B2	2/2004	Kumata
6,427,349 B1	8/2002	Blank et al.	6,693,519 B2	2/2004	Keirstead
6,428,172 B1	8/2002	Hutzel et al. 359/838	6,693,524 B1	2/2004	Payne
6,433,676 B2	8/2002	DeLine et al.	6,700,692 B2	3/2004	Tonar et al.
6,433,680 B1	8/2002	Ho	6,709,136 B2	3/2004	Pastrick et al.
6,437,688 B1	8/2002	Kobayashi	6,717,610 B1	4/2004	Bos et al.
6,438,491 B1	8/2002	Farmer	6,717,712 B2	4/2004	Lynam et al.
6,439,755 B1	8/2002	Fant et al.	6,726,337 B2	4/2004	Whitehead et al.
6,441,872 B1	8/2002	Ho	6,727,808 B1	4/2004	Uselmann et al.
6,445,287 B1	9/2002	Schofield et al.	6,727,844 B1	4/2004	Zimmermann et al.

US 7,728,721 B2

Page 6

6,731,332	B1	5/2004	Yasui et al.	2003/0030724	A1	2/2003	Okamoto
6,734,807	B2	5/2004	King	2003/0035050	A1	2/2003	Mizusawa
6,737,964	B2	5/2004	Samman et al.	2003/0043269	A1	3/2003	Park
6,738,088	B1	5/2004	Uskolovsky et al.	2003/0052969	A1	3/2003	Satoh et al.
6,744,353	B2	6/2004	Sjónell	2003/0058338	A1	3/2003	Kawauchi et al.
6,748,211	B1	6/2004	Isaac et al.	2003/0067383	A1	4/2003	Yang
6,756,912	B2	6/2004	Skiver et al.	2003/0069690	A1	4/2003	Correia et al.
6,757,109	B2	6/2004	Bos	2003/0076415	A1	4/2003	Strumolo
6,774,356	B2	8/2004	Heslin et al. 250/239	2003/0080877	A1	5/2003	Takagi et al.
6,778,904	B2	8/2004	Iwami et al.	2003/0085806	A1	5/2003	Samman et al.
6,784,129	B2	8/2004	Seto et al.	2003/0088361	A1	5/2003	Sekiguchi
6,810,323	B1	10/2004	Bullock et al.	2003/0090568	A1	5/2003	Pico
6,824,281	B2	11/2004	Schofield et al.	2003/0090569	A1	5/2003	Poechmueller
6,832,848	B2	12/2004	Pastrick	2003/0090570	A1	5/2003	Takagi et al.
6,836,725	B2	12/2004	Millington et al.	2003/0098908	A1	5/2003	Misaiji et al.
6,847,487	B2	1/2005	Burgner	2003/0103141	A1	6/2003	Bechtel et al.
6,848,817	B2	2/2005	Bos et al.	2003/0103142	A1	6/2003	Hitomi et al.
6,877,888	B2	4/2005	DeLine et al. 362/494	2003/0117522	A1	6/2003	Okada
6,882,287	B2	4/2005	Schofield	2003/0122929	A1	7/2003	Minaudo et al.
6,902,284	B2	6/2005	Hutzel et al.	2003/0122930	A1	7/2003	Schofield et al.
6,906,632	B2	6/2005	DeLine et al.	2003/0133014	A1	7/2003	Mendoza
6,912,396	B2	6/2005	Sziraki et al.	2003/0137586	A1	7/2003	Lewellen
6,946,978	B2	9/2005	Schofield	2003/0141965	A1	7/2003	Gunderson et al.
6,975,215	B2	12/2005	Schofield et al.	2003/0146831	A1	8/2003	Berberich et al.
7,004,592	B2	2/2006	Varaprasad et al.	2003/0169158	A1	9/2003	Paul, Jr.
7,004,593	B2	2/2006	Weller et al.	2003/0169522	A1	9/2003	Schofield et al.
7,041,965	B2	5/2006	Heslin et al. 250/239	2003/0179293	A1	9/2003	Oizumi
7,046,448	B2	5/2006	Burgner	2003/0202096	A1	10/2003	Kim
7,053,761	B2	5/2006	Schofield et al.	2003/0214576	A1	11/2003	Koga
7,167,796	B2	1/2007	Taylor et al.	2003/0214584	A1	11/2003	Ross, Jr.
7,175,291	B1	2/2007	Li	2003/0214733	A1	11/2003	Fujikawa et al.
7,184,190	B2	2/2007	McCabe et al.	2003/0222793	A1	12/2003	Tanaka et al.
7,195,381	B2	3/2007	Lynam et al.	2003/0222983	A1	12/2003	Nobori et al.
7,199,767	B2	4/2007	Spero	2003/0227546	A1	12/2003	Hilborn et al.
7,255,451	B2	8/2007	McCabe et al.	2004/0004541	A1	1/2004	Hong
7,262,406	B2	8/2007	Heslin et al.	2004/0027695	A1	2/2004	Lin
7,265,342	B2	9/2007	Heslin et al.	2004/0032321	A1	2/2004	McMahon et al.
7,274,501	B2	9/2007	McCabe et al.	2004/0036768	A1	2/2004	Green
7,310,177	B2	12/2007	McCabe et al.	2004/0046870	A1	3/2004	Leigh Travis
7,328,103	B2	2/2008	McCarthy et al.	2004/0051634	A1	3/2004	Schofield et al.
7,344,284	B2	3/2008	Lynam et al.	2004/0056955	A1	3/2004	Berberich et al.
7,370,983	B2	5/2008	DeWind et al.	2004/0057131	A1	3/2004	Hutzel et al.
7,412,328	B2	8/2008	Uhlmann et al.	2004/0064241	A1	4/2004	Sekiguchi
7,420,159	B2	9/2008	Heslin et al.	2004/0066285	A1	4/2004	Sekiguchi
7,446,650	B2	11/2008	Schofield et al.	2004/0075603	A1	4/2004	Kodama
7,460,007	B2	12/2008	Schofield et al.	2004/0077359	A1	4/2004	Bernas et al.
7,471,438	B2	12/2008	McCabe et al.	2004/0080404	A1	4/2004	White
7,490,007	B2	2/2009	Taylor et al.	2004/0080431	A1	4/2004	White
7,494,231	B2	2/2009	Varaprasad et al.	2004/0085196	A1	5/2004	Miller et al.
7,538,316	B2	5/2009	Heslin et al.	2004/0090314	A1	5/2004	Iwamoto
2001/0019356	A1	9/2001	Takeda et al.	2004/0090317	A1	5/2004	Rothkop
2001/0022616	A1	9/2001	Rademacher et al.	2004/0096082	A1	5/2004	Nakai et al.
2001/0026316	A1	10/2001	Senatore	2004/0098196	A1	5/2004	Sekiguchi
2001/0045981	A1	11/2001	Gloger et al.	2004/0107030	A1	6/2004	Nishira et al.
2002/0003571	A1	1/2002	Schofield et al.	2004/0107617	A1	6/2004	Shoen et al.
2002/0049535	A1	4/2002	Rigo et al.	2004/0109060	A1	6/2004	Ishii
2002/0072026	A1	6/2002	Lynam et al.	2004/0114039	A1	6/2004	Ishikura
2002/0093826	A1	7/2002	Bos et al.	2004/0128065	A1	7/2004	Taylor et al.
2002/0126497	A1	9/2002	Pastrick	2004/0145457	A1	7/2004	Schofield et al.
2002/0154007	A1	10/2002	Yang	2004/0202001	A1	10/2004	Roberts et al.
2002/0159270	A1	10/2002	Lynam et al.	2004/0243303	A1	12/2004	Padmanabhan
2002/0172053	A1	11/2002	Pastrick et al.	2005/0024729	A1	2/2005	Ockerse et al.
2002/0191409	A1	12/2002	Deline et al.	2005/0078389	A1	4/2005	Kulas et al.
2003/0002165	A1	1/2003	Mathias et al.	2005/0079326	A1	4/2005	Varaprasad et al.
2003/0007261	A1	1/2003	Hutzel et al.	2005/0083577	A1	4/2005	Varaprasad et al.
2003/0016125	A1	1/2003	Lang et al.	2006/0007550	A1	1/2006	Tonar et al.
2003/0016287	A1	1/2003	Nakayama et al.	2006/0028730	A1	2/2006	Varaprasad et al.
2003/0016542	A1	1/2003	Pastrick et al.	2006/0050018	A1	3/2006	Hutzel et al.
2003/0020603	A1	1/2003	DeLine et al.	2006/0164230	A1	7/2006	DeWind et al.
2003/0025596	A1	2/2003	Lang et al.	2006/0202111	A1	9/2006	Heslin et al.
2003/0025597	A1	2/2003	Schofield	2007/0118287	A1	5/2007	Taylor et al.
2003/0030546	A1	2/2003	Tseng	2007/0120043	A1	5/2007	Heslin et al.
2003/0030551	A1	2/2003	Ho	2007/0132567	A1	6/2007	Schofield et al.

2007/0162229	A1	7/2007	McCarthy et al.	GB	2351055	12/2000
2007/0171037	A1	7/2007	Schofield et al.	JP	5730639	2/1982
2007/0183066	A1	8/2007	Varaprasad et al.	JP	57208530	12/1982
2007/0184284	A1	8/2007	Varaprasad et al.	JP	5830729	2/1983
2008/0013153	A1	1/2008	McCabe et al.	JP	59-114139	7/1984
2008/0068520	A1	3/2008	Minikey, Jr. et al.	JP	6243543	2/1987
2008/0094684	A1	4/2008	Varaprasad et al.	JP	63106730	5/1988
2008/0094685	A1	4/2008	Varaprasad et al.	JP	63106731	5/1988
2008/0180529	A1	7/2008	Taylor et al.	JP	64-14700	1/1989
2008/0180781	A1	7/2008	Varaprasad et al.	JP	4-114587	4/1992
2008/0183355	A1	7/2008	Taylor et al.	JP	5-213113	8/1993
2008/0186724	A1	8/2008	Lynam et al.	JP	11078693	3/1999
2008/0201075	A1	8/2008	Taylor et al.	WO	WO 9814974	4/1998
2008/0212189	A1	9/2008	Baur et al.	WO	WO 9830415	7/1998
2008/0212215	A1	9/2008	Schofield et al.	WO	WO 9914088	3/1999
2008/0225538	A1	9/2008	Lynam et al.	WO	WO 9923828	5/1999
2008/0266389	A1	10/2008	DeWind et al.	WO	WO 0018612	4/2000
2008/0291522	A1	11/2008	Varaprasad et al.	WO	WO 0055685	9/2000
2009/0015736	A1	1/2009	Weller et al.			

FOREIGN PATENT DOCUMENTS

DE	2631713	A1	2/1977
DE	3301945		7/1984
DE	3525672		1/1987
DE	3614882		11/1987
DE	4329983	A1	3/1995
DE	29703084		6/1997
DE	29805142	U1	5/1998
DE	19755008	A1	7/1999
DE	29902344		7/1999
EP	0165817		12/1985
EP	0254435		5/1992
EP	0667254	A1	8/1995
EP	0928723	A2	7/1999
EP	0969275		1/2000
EP	1148328		10/2001
FR	1021987		2/1953
FR	1461419		12/1966
FR	2 759 045		8/1998
GB	810010		3/1959
GB	1008411		10/1965
GB	1136134		12/1968
GB	2210836	A	6/1989

OTHER PUBLICATIONS

Research Disclosure, Kenneth Mason Publications, Hampshire, GB, No. 385, May 1, 1996, p. 327, XP000599745.

European Search Report dated Aug. 28, 2003, in European Application No. EP 00 65 0114, Publication No. EP 1 097 848, published May 9, 2001.

"Combination of rain sensing, autolamps and telephone antenna in one module," Research Disclosure, Kenneth Mason Publications, Hampshire, GB No. 412, Aug. 1998, p. 1045XP-000824825.

Steward, James W.; HP SnapLED: LED Assemblies for Automotive Signal Applications; Nov. 1, 1998; Hewlett-Packard Journal; vol. 50, No. 1, www.hpl.hp.com/hpjournal/98nov/nov98al.pdf.


Edgar, Julian; Goodbye 12 Volts . . . Hello 42 Volts!; Oct. 5, 1999; Autospeed 50; Issue 50; www.autospeed.co.nz/cms/A_0319/article.html.

Kobe, Gerry; 42 Volts Goes Underhood; Mar. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_3_180/ai_61361677.

Jewett, Dale; Aug. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_8_180ai_64341779.

National Semiconductor, LM78S40, Universal Switching Regulator Subsystem, National Semiconductor Corporation, Apr. 1996, p. 6.

G. Wang, D. Renshaw, P.B. Denyer and M. Lu, CMOS Video Cameras, article, 1991, 4 pages, University of Edinburgh, UK.












FIG. 2












Figure 7




Figure 8






Figure 9






FIG. 12





FIG. 13










Figure 16








FIG. 20A




FIG. 20B




FIG. 21A




FIG. 21B




FIG. 22A





FIG. 22B

6700




Figure 24

6800




Figure 24a

1

ACCESSORY SYSTEM SUITABLE FOR USE IN A VEHICLE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 11/441,592, filed May 26, 2006, now U.S. Pat. No. 7,460,007, which is a continuation of U.S. patent application Ser. No. 10/940,545, filed Sep. 14, 2004, now U.S. Pat. No. 7,053,761, which is a continuation of U.S. patent application Ser. No. 10/232,122, filed Aug. 30, 2002, now U.S. Pat. No. 6,975,215, which is a continuation of U.S. patent application Ser. No. 09/710,016, filed Nov. 10, 2000, now U.S. Pat. No. 6,445,287, which is a continuation-in-part of U.S. patent application Ser. No. 09/513,941, filed Feb. 28, 2000, now U.S. Pat. No. 6,294,989, which are incorporated by reference herein in their entirety; and the present application is a continuation-in-part of U.S. patent application Ser. No. 12/467,660, filed May 18, 2009 (MAG04 P-1515), which is a continuation of U.S. patent application Ser. No. 12/197,660, filed Aug. 25, 2008, now U.S. Pat. No. 7,538,316, which is a continuation of U.S. patent application Ser. No. 11/828,880, filed Jul. 26, 2007, now U.S. Pat. No. 7,420,159, which is a continuation of U.S. patent application Ser. No. 11/699,271, filed Jan. 29, 2007, now U.S. Pat. No. 7,265,342, which is a continuation of U.S. patent application Ser. No. 11/418,906, filed May 5, 2006, now U.S. Pat. No. 7,262,406, which is a continuation of U.S. patent application Ser. No. 10/913,748, filed Aug. 6, 2004, now U.S. Pat. No. 7,041,965, which is a continuation of U.S. patent application Ser. No. 10/618,334, filed Jul. 11, 2003, now U.S. Pat. No. 6,774,356, which is a continuation of U.S. patent application Ser. No. 09/997,579, filed Nov. 29, 2001, now U.S. Pat. No. 6,593,565, which is a continuation of U.S. patent application Ser. No. 09/433,467, filed Nov. 4, 1999, now U.S. Pat. No. 6,326,613, which is a continuation-in-part of U.S. patent application Ser. No. 09/003,966, filed Jan. 7, 1998, by Niall R. Lynam, now U.S. Pat. No. 6,250,148; and the present application is a continuation-in-part of U.S. patent application Ser. No. 12/052,341, filed Mar. 20, 2008, now U.S. Pat. No. 7,579,940 which is a continuation of U.S. patent application Ser. No. 11/625,374, filed Jan. 22, 2007, now U.S. Pat. No. 7,579,939 which is a continuation of U.S. patent application Ser. No. 10/755,915, filed Jan. 13, 2004, now U.S. Pat. No. 7,446,650, which is a continuation of U.S. application Ser. No. 09/793,002, filed Feb. 26, 2001, now U.S. Pat. No. 6,690,268, which claims benefit of U.S. provisional applications, Ser. No. 60/263,680, filed Jan. 23, 2001; Ser. No. 60/243,986, filed Oct. 27, 2000; Ser. No. 60/238,483, filed Oct. 6, 2000; Ser. No. 60/237,077, filed Sep. 30, 2000; Ser. No. 60/234,412, filed Sep. 21, 2000; Ser. No. 60/218,336, filed Jul. 14, 2000; and Ser. No. 60/186,520, filed Mar. 2, 2000; and U.S. patent application Ser. No. 10/755,915 is also a continuation-in-part of U.S. patent application Ser. No. 10/232,122, filed Aug. 30, 2002, now U.S. Pat. No. 6,975,215, which is a continuation of U.S. Pat. No. 6,445,287, which is a continuation-in-part of U.S. Pat. No. 6,294,989, which is a continuation-in-part of U.S. Pat. No. 6,124,647; and U.S. patent application Ser. No. 10/755,915 is also a continuation-in-part of U.S. patent application Ser. No. 10/279,059, filed Oct. 23, 2002, now U.S. Pat. No. 6,774,774, which is a continuation of U.S. Pat. No. 6,472,979, which is a continuation of U.S. Pat. No. 6,294,989, which is a continuation-in-part of U.S. Pat. No. 6,124,647; and U.S. patent application Ser. No. 10/755,915 is also a continuation-in-part of U.S. patent application Ser. No. 10/618,334, filed Jul. 11, 2003, now U.S. Pat. No. 6,774,356, which is a continuation of

2

U.S. Pat. No. 6,593,565, which is a continuation of U.S. Pat. No. 6,326,613, which is a continuation-in-part of U.S. Pat. No. 6,250,148; and U.S. patent application Ser. No. 10/755,915 is also a continuation-in-part of U.S. patent application Ser. No. 10/270,830, filed Oct. 15, 2002, now U.S. Pat. No. 6,717,524, which is a continuation of U.S. Pat. No. 6,466,136, which is a continuation of U.S. Pat. No. 6,278,377, which is a continuation-in-part of U.S. Pat. No. 6,243,003.

BACKGROUND OF THE INVENTION

This invention relates generally to vehicular function monitoring and display systems. More particularly, the invention is related to a system for assisting the manual inflating of tires while mounted on the wheels of a vehicle. Most particularly, this invention is related to a system for assisting the manual inflating of tires of the vehicle that includes an indicator assembly positioned on an exterior vehicle portion such as an exterior mirror assembly.

Remote tire pressure sensors have been developed which sense tire pressure and transmit, such as via a radio frequency link, the tire pressure to a vehicle-based controller. The information regarding tire pressure may be used to control vehicle safety-based devices, such as ride and comfort control systems, road-handling systems, braking systems, and the like. It is also known to utilize such sensors in combination with tires that can run without inflation in order to warn the driver that the tire is operating in an emergency mode and should be driven at a limited speed for a limited distance.

It is known to utilize various gauges and displays in view of the driver. For example, it is known to place a display of vehicle tire pressure within the interior cabin of the vehicle in view of the driver. This includes displaying the vehicle tire pressure in an interior mirror-based display. Typically, such displays mounted in the interior cabin provide a read-out of the inflation status of individual tires on the vehicle, such as an alphanumeric read-out of tire pressure or an icon indicative of tire pressure status. For example, a read-out or an icon indicative of the individual tire pressures at the four wheels on an automobile can be displayed at the reflective element of the interior rearview mirror assembly. While such displays alert the driver of the vehicle sitting in the interior vehicular cabin when the vehicle is operating as to the inflation status of individual tires present on the vehicle, they are little to no aid to a driver or other person while actually pumping air into or bleeding air from an individual tire in response to recognition of an undesired tire inflation pressure. While pumping air into or bleeding air from a tire mounted on a vehicle (such as commonly occurs at service stations and the like), a person typically uses an air line connected to an air compressor. The air line is manually connected to an inflation valve provided at the vehicular tire; the person presses the air line to a nipple of the tire valve, and, by so doing, pressurized air is allowed pass through the tire valve, or escape from the tire valve, to inflate or deflate tire pressure to the desired pressure value. To so do, typically the engine is turned off and the driver exits the vehicle, and crouches down at a particular wheel on a side of the vehicle in order to adjust the tire pressure at that particular wheel. While so doing, the driver typically does not have a view of the vehicle interior, and typically relies on a hand-held tire pressure gauge or on a gauge provided on the air line used for tire pressure adjustment. Thus, even though the vehicle tire may be equipped with a sensor for measuring the air pressure in the tire, in systems known to date, this tire pressure monitoring sensor does not provide a readily readable indication of correct or incorrect tire inflation pressure to the person external to the vehicle who is adjusting the tire

pressure in that tire on the vehicle, and especially while that person is in the act of adjusting that tire pressure.

SUMMARY OF THE INVENTION

The present invention provides a new and useful system that provides an indicator external of the vehicle to indicate the inflation condition of the vehicle tires. The present invention provides a readily interpretable indication of correct or incorrect tire inflation pressure to a person external to the vehicle who is adjusting the tire pressure in that tire on the vehicle, and especially while that person is in the act of adjusting that tire pressure. Preferably, the indicator is positioned at an exterior vehicle portion, such as a vehicle exterior rearview mirror assembly, where the indicator can be observed by a user inflating or deflating the vehicle tires located at the vehicle side of that exterior vehicle portion. However, the present invention may also be used as a convenient indicator to the driver or passenger entering a vehicle that one or more of the vehicle tires are in an under-pressure or over-pressure condition.

According to the invention, a tire inflation monitoring system suitable for use on a vehicle is provided that comprises at least one tire inflation indicator assembly positioned at an exterior vehicle portion at a side of the vehicle and visible exterior the vehicle. The at least one tire inflation indicator assembly provides an indication of the inflation condition of at least one vehicle tire positioned at that side of the vehicle, and wherein the tire inflation monitoring system includes a control receiving at least one input from at least one tire pressure sensor sensing pressure of the at least one vehicle tire, and the control producing an output to illuminate the at least one tire inflation indicator assembly in response to a tire pressure condition.

A vehicle exterior rearview mirror system, according to an aspect of the invention, includes at least one exterior rearview mirror assembly mounted on a side of the vehicle. The exterior rearview mirror assembly includes a reflective element and a support for the reflective element. The system further includes a tire inflation monitor including at least one tire inflation indicator assembly positioned at the exterior rearview mirror assembly and visible exterior of the vehicle. The at least one indicator assembly provides an indication of the inflation condition of at least one of the vehicle tires mounted to wheels of the vehicle on the side of the vehicle to which the exterior mirror assembly is mounted. The tire inflation monitor includes a control receiving at least one input from at least one tire pressure sensor sensing pressure of at least one of the vehicle tires. The tire inflation monitor further includes a control producing an output to illuminate the at least one tire inflation indicator assembly.

By providing a tire inflation monitor visible exterior of the vehicle, the present invention provides an indication to a vehicle user at a desirable location that provides a useful assistance to the user, or an attendant, inflating the vehicle tires. This is accomplished by providing a tire inflation indicator at the exterior rearview mirror assembly in order to be visible at the vehicle tires. As the vehicle tires are inflated from an under-pressure to an operating pressure range, the indicator provides an indication of this change. The indicator may also provide an indication when the tires are inflated to an over-inflated condition. The invention also provides a useful indication as the driver enters the vehicle or exits the vehicle that attention to the tires is necessary.

These and other objects, advantages, and features of this invention will become apparent upon review of the following specification in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top plan view of a vehicle exterior rearview mirror system equipped with tire pressure indicator assemblies, according to the invention;

FIG. 2 is a side elevation of the vehicle in FIG. 1;

FIG. 3 is a perspective view of a vehicle exterior rearview mirror assembly, according to the invention;

FIG. 4 is the same view as FIG. 3 of an alternative embodiment thereof;

FIG. 5 is the same view as FIG. 3 of an alternative embodiment thereof;

FIG. 6 is an electrical block diagram of a tire inflation monitoring system, according to the invention;

FIG. 6A is an electrical block diagram of another embodiment of the tire inflation monitoring system according to the present invention;

FIG. 7 is a front elevation view of a video mirror system incorporating a tire pressure display of the present invention;

FIG. 8 is an enlarged perspective view of a rearview mirror support incorporating a tire pressure display of the present invention;

FIG. 9 is a side elevation view of an accessory module/mirror system incorporating a vehicle tire pressure monitoring system of the present invention;

FIG. 10 is a front elevation view of another embodiment of an accessory module/mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 11 is a side elevation view of the accessory module/mirror system of FIG. 10;

FIG. 12 is an enlarged side elevation view similar to FIG. 11;

FIG. 13 is an exploded side elevation view of the accessory module/mirror system of FIGS. 10-12;

FIG. 14 is a partial front elevation view of another embodiment of an accessory module incorporating the tire pressure monitoring and/or display system of the present invention;

FIG. 15 is an exploded perspective view of another embodiment of an accessory module/mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 15A is a partial perspective view of the accessory module of FIG. 15 illustrating a portion of the module telescoping between two viewing positions;

FIG. 16 is a side elevation view of another embodiment of an accessory module/mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 16A is a side elevation view of another embodiment of an accessory module/mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 16B is a side elevation view of another embodiment of an accessory module/mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 17 is a side elevation view of another embodiment of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 18 is a side elevation view of another embodiment of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 19 is another embodiment of a video mirror system and a video display assembly incorporating a tire pressure monitoring and/or display system of the present invention;

5

FIG. 20A is a rear perspective view of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 20B is a rear perspective view of a video display attachment mount for the video mirror system of FIG. 20A;

FIG. 21A is a side elevation view of a video mirror system of FIG. 20A with the video display assembly moved to a stowed position;

FIG. 21B is a similar view to FIG. 21A illustrating the video display housing moved to a viewing position;

FIG. 22A is a similar view to FIG. 21A illustrating the video display assembly moved to a second viewing position;

FIG. 22B is a similar view to FIG. 22A illustrating the video display housing rotated to another viewing position;

FIG. 23 is a side elevation view of another embodiment of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention;

FIG. 24 is a side elevation view of another embodiment of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention; and

FIG. 24A is a side elevation view of yet another embodiment of a video mirror system incorporating a tire pressure monitoring and/or display system of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now specifically to the drawings, and the illustrative embodiments depicted therein, a vehicle exterior rearview mirror system 10 for use with vehicle 12 includes one or more exterior rearview mirror assemblies 14 and a tire inflation monitoring system 16 (FIGS. 1, 2 and 6). Tire inflation monitoring system 16 includes at least one tire pressure indicator assembly 19 positioned at exterior rearview mirror assembly 14, a control 18, and one or more tire pressure sensors 20, each associated with one of the vehicle tires. Each tire pressure sensor 20 is connected wirelessly with control 18 by a wireless communication link 22 that, in the illustrated embodiment, is a radio frequency (RF) link. Tire pressure sensor 20 is commercially available from several sources and conventionally includes a wireless communication link 22 with a vehicle controller. Control 18 is an electronic control, and is preferably a microprocessor-based electronic control, but may, alternatively, be a digital logic controller, an analog controller, or the like. Preferably, control 18 performs additional vehicle functions. Most preferably, control 18 is interconnected with a vehicle serial bus system such as of the type disclosed in commonly assigned U.S. Pat. No. 5,959,367, the disclosure of which is hereby incorporated herein by reference.

Exterior rearview mirror assembly 14 includes a reflective element 24 and a support 26 supporting the reflective element by vehicle 12 (FIGS. 3-5). As is conventional, support 26 includes a fixed portion 28 attached to vehicle 12 and a movable portion (not shown) which movably supports reflective element 24. Preferably, the movable portion is an electrically controlled actuator of the type disclosed in commonly assigned patent application Ser. No. 09/228,348, filed Jan. 11, 1999, by Schnell et al., now U.S. Pat. No. 6,213,612, the disclosure of which is hereby incorporated herein by reference. Reflective element 24 may be any of several reflectors such as glass coated on its first or second surface with a suitable reflective layer or layers, such as disclosed in U.S. Pat. No. 5,179,471, the disclosure of which is hereby incorporated herein by reference, or, preferably, an electro-optic reflective element, and, most preferably, an electrochromic mirror element. However, the invention applies to all forms of

6

reflective element 24. Electrochromic reflective elements 24 may be of any type such as disclosed in U.S. Pat. No. 4,902,108 issued to Byker; commonly assigned U.S. Pat. No. 5,668,663 issued to Varaprasad et al.; commonly assigned U.S. Pat. No. 5,724,187 issued to Varaprasad et al.; commonly assigned U.S. Pat. No. 6,002,511 issued to Varaprasad et al.; commonly assigned U.S. Pat. No. 5,140,455 issued to Varaprasad et al.; commonly assigned U.S. Pat. No. 5,910,854 issued to Varaprasad et al. and commonly assigned U.S. patent application Ser. No. 08/429,643, filed Apr. 27, 1995, by Varaprasad et al., entitled ELECTROCHROMIC MIRRORS AND DEVICES, now U.S. Pat. No. 5,724,187, the disclosures of which are hereby all incorporated herein by reference. Electrochromic reflective elements 24 include electrochromic units, or cells, that decrease in transmissivity in response to a drive signal applied thereto. Most preferably, reflective element 24 comprises a front substrate and a rear substrate with an electrochromic medium disposed between, such as a solid polymer matrix electrochromic medium such as is disclosed in U.S. patent application Ser. No. 09/350,930, filed Jul. 12, 1999, entitled ELECTROCHROMIC POLYMERIC SOLID FILMS, MANUFACTURING ELECTROCHROMIC DEVICES USING SUCH FILMS, AND PROCESSES FOR MAKING SUCH SOLID FILMS AND DEVICES, to Desaraju V. Varaprasad et al., now U.S. Pat. No. 6,154,306, the entire disclosure of which is hereby incorporated by reference herein. Most preferably, the front substrate comprises a glass plate of thickness less than about 1.6 mm, most preferably about 1.1 mm thickness or lower, and the rear substrate comprises a glass plate of thickness equal to or greater than about 1.6 mm, more preferably greater than about 1.8 mm thickness, most preferably equal to or greater than about 2.0 mm thickness. The rearmost surface of the rear substrate (the fourth surface as known in the mirror art) is reflector coated with a high reflecting metal film such as of aluminum or silver, or an alloy of aluminum or silver. Most preferably, the frontmost surface of the rear substrate (the third surface as known in the mirror art) is reflector coated with a high reflecting metal film such as of aluminum or silver, or an alloy of aluminum or silver, optionally overcoated with a transparent electronic conductor coating such as of indium tin oxide or of doped tin oxide.

Exterior rearview mirror assembly 14 may include other elements and functions as disclosed in commonly assigned U.S. Pat. Nos. 6,019,475; 5,371,659; 5,971,552; and 5,497,306, the disclosures of which are hereby incorporated herein by reference.

Tire inflation indicator assembly 19 preferably generates a pattern of light P viewable from the location of the tires of the vehicle on the side of the vehicle with which tire pressure sensors 20 are associated. In this manner, a user of the vehicle or an attendant or mechanic may inflate the vehicle tires while observing the pattern of light P generated by the tire pressure indicator assembly 19. This may be accomplished by mounting tire inflation indicator assembly 19 to a lower surface 30 of the portion of exterior rearview mirror assembly 14 that houses the mirror reflector. In addition to producing a pattern of light P, which is visible at the tires on the side of the vehicle with which the associated tire inflation indicator assembly 19 is located, the pattern of light P preferably will not be substantially visible to the driver of the vehicle. This avoids any distraction to the driver from the tire inflation indicator assembly while the driver is in the vehicle. Furthermore, there is less wind noise below the exterior rearview mirror assembly 14. Thus, the presence of the tire pressure indicator assembly there does not substantially contribute to wind noise generated by the exterior rearview mirror assembly.

Furthermore, the bottom portion of exterior rearview mirror assembly **14** is typically hollow and provides a convenient attachment point for the tire inflation indicator assembly. Because the exterior mirror assembly protrudes outwardly from the vehicle body, locating the tire inflation indicator assembly at the exterior mirror assembly, and especially at a lower portion of the part of the exterior mirror assembly that houses the mirror reflector element, is advantageous. This is because such a location renders the indicator of the tire inflation indicator assembly readily visible to a person positioned at either or both of the front wheel tire and the rear wheel tire of the vehicle who is inflating/deflating a tire, and especially when the person adjusting the tire pressure is crouched down at a vehicle wheel tire while manually adjusting its tire pressure. For example, a tire inflation indicator assembly that includes a light source, such as a light-emitting diode, can protrude from the underside of the casing part of the exterior mirror assembly that houses the mirror reflector element. Thus, whether the user adjusting tire pressure is located at a front wheel tire or a rear wheel tire at one of the driver side or the passenger side of the vehicle, the user can see a single indicator of the tire inflation indicator assembly that is positioned below the casing of the exterior mirror assembly on that side, and that preferably protrudes therefrom (for example, as a pendant element), as he or she crouches down at that particular wheel tire on that particular vehicle side. It is preferable, for economy, that a single tire inflation indicator assembly be provided on an exterior vehicle portion of a side of the vehicle at a location visible to a person inflating either a front wheel tire of that side or a rear wheel tire of that side.

In an alternative embodiment, a tire inflation indicator assembly **19a** may be positioned at fixed portion **28** of support **26**. In the embodiment illustrated in FIG. 4, tire inflation indicator assembly **19a** is illustrated on a surface directed rearwardly of vehicle **12** where it would generate a pattern of light visible at a rear tire of the vehicle on the side of the vehicle on which tire inflation indicator assembly **19a** is located. Another tire inflation indicator assembly (not shown) may be positioned on a forward-facing portion of fixed portion **28**, thereby being visible at the area around the forward tire on the same side of the vehicle on which the tire inflation assembly is located.

In another alternative embodiment illustrated in FIG. 5, a tire inflation indicator assembly **19b** is positioned with the movable portion of support **26**, such as on reflective element **24**. Preferably, tire inflation indicator assembly **19b** is positioned behind reflective element **24**, thereby protected from environmental elements such as road splash, car washes, and the like. This is accomplished by removing a portion of a reflective coating on reflective element **24** such that tire inflation indicator assembly **19b** is viewable through reflective element **24** (or by using a semitransparent mirror reflector such a dichroic mirror element such as is described in U.S. Pat. No. 5,361,190, the entire disclosure of which is hereby incorporated by reference herein). Tire inflation indicator assembly **19b** may be joined with reflective element **24** according to the principles disclosed in U.S. Pat. No. 5,416,313, entitled DISPLAY FOR AUTOMATIC REARVIEW MIRROR, the disclosure of which is hereby incorporated herein by reference.

Other mountings for tire inflation indicator assembly, according to the invention, may be apparent to the skilled artisan. For example, the tire inflation indicator assembly may be mounted at the sail portion **30** of exterior rearview member assembly **14** or a portion of vehicle **12** adjacent to exterior rearview mirror assembly **14**. Also, the tire inflation indicator assembly can be located at an exterior vehicle portion other

than at the exterior mirror assembly. For example, a tire inflation indicator assembly can be located at a vehicle body side panel, such as at or part of a side marker assembly, or as part of a door panel assembly. Optionally, a tire inflation indicator assembly can be located at each wheel tire location, so that a person inflating or deflating a particular tire can see the indicator of tire pressure local to the particular wheel tire being inflated/deflated. Other elements may be combined with the tire inflation indicator assembly. For example, a temperature sensor for sensing the exterior temperature surrounding the vehicle may be positioned in a common housing with the tire inflation indicator assembly. Furthermore, the tire inflation indicator assembly may be positioned at a side-mounted camera assembly for a rearview camera vision system of the type disclosed in commonly assigned International Publication WO 96/38319, published Dec. 5, 1996, the disclosure of which is hereby incorporated herein by reference.

Tire inflation indicator system **16** optionally comprises a lockout **33** that prevents inadvertent actuation of tire inflation indicator assemblies **19** during operation of vehicle **12**. Such lockouts are conventional and preferably comprise a circuit that is responsive to the vehicle being placed in gear to the vehicle reaching a determined speed (such as at least 5 miles per hour), or to turning an ignition switch to operate the engine. When the lockout circuit senses that the vehicle is operating or in a condition to operate, operation of tire inflation indicator assemblies **19** is optionally disabled. Thus, receipt of an input indicative of operation of the vehicle by tire pressure monitoring controller **18** from lockout **33** would disable operation of tire inflation indicator assemblies **19**. Thus, and optionally, control **18** processes the input **32** in order to lock out illumination of tire inflation indicator assemblies **19** during operation of vehicle **12**. This further reduces the likelihood of the tire inflation monitoring system providing a distraction not only to the driver of vehicle **12** during normal driving of vehicle **12**, but also to operators of vehicles in the vicinity of vehicle **12**. Tire inflation monitoring system **16** may additionally receive an input **34** indicative of the locked state of the vehicle doors. Preferably, control **18** provides outputs to illuminate tire inflation indicator assemblies **19** only when the vehicle doors are in an unlocked state, which is likely when the tires of the vehicle are being inflated. Most preferably, control **18** is capable of illuminating tire inflation indicator assemblies **19** in response to a sensed tire inflation condition only for a predetermined period of time after door lock input **34** indicates that the vehicle doors have changed to an unlocked state and, optionally and preferably, after ignition sensing circuit **32** indicates that the vehicle ignition is not operating (i.e., the engine is off). This period of time, which is determined by timeout **37**, may be less than or equal to about two hours and, preferably, less than or equal to about 30 minutes. Most preferably, this predetermined period of time is less than or equal to about 15 minutes. Control **18** may additionally produce outputs to illuminate tire inflation indicator assemblies **19** in response to a tire pressure sensor **20** sensing commencement of a manual tire pressure adjust event such as by sensing a change in pressure of its associated tire indicative of a user of the vehicle inflating/deflating that tire, or sensing depression of the close-out nipple provided in the tire valve stem to allow connection to an air hose/to allow bleed off of tire pressure. In this manner, the tire inflation indicator assembly is illuminated when it is of assistance to the manual inflation of the tires. The tire inflation assembly may stay capable of illumination after a given event (such as unlocking a door, opening a door, turning off the vehicle ignition, detection of an indication of a manual tire pressure adjust event) for a predetermined period of time which, for

example, is less than or equal to about two hours and, preferably, is less than or equal to about 30 minutes and, most preferably, is less than or equal to about 15 minutes.

Provision of door lock input 34 and/or ignition sensing circuit 32 and/or timeout 37 is advantageous towards ensuring that the tire inflation indicator system 16 remains armed and powered for a sufficient time period to allow the driver to pull up to a service station to service tire pressures, but not so that the tire inflation indicator system 16 would remain powered and armed all the time a vehicle is parked (and thus risk depleting the vehicle battery which typically operates at 12 volts nominal). Since sensors 19, controller 18 and other electronic elements of system 16 require electric power to operate, and since when stopped at a service station it is usual and safest to turn off the vehicle ignition while attending to the tire pressures, tire inflation indicator system 16 typically will operate on vehicle battery power while the driver is inflating/deflating tires on wheels mounted to the vehicle, and so system 16 includes a battery depletion protection to obviate running down the battery when the vehicle is normally parked.

Tire inflation indicator system 16 optionally comprises a tire pressure adjust sensor 39 that provides an input to controller 18 alerting that a manual tire pressure adjust event is beginning. Thus, for example, when the vehicle is parked, tire inflation indicator system 16 optionally remains in a quiescent, armed mode (that draws very little current from the vehicle battery, with a current draw of less than about 15 milliamps preferred, a current draw of less than about 10 milliamps more preferred, and a current draw of less than about 5 milliamps most preferred). Thus, even when prolonged parked, tire inflation indicator system 16 is powered but active only in a monitoring, low-current state, and with controller 18 monitoring an input from tire pressure adjust sensor 39. When a manual tire pressure adjust event is detected by tire pressure adjust sensor 39 (such as by detection of depression of the close-off nipple in the valve stem at the particular wheel tire at a side of the vehicle a person is manually inflating from a compressed air line, or by detection of a change in tire pressure indicative of a user-actuated tire inflate/deflate event), controller 18 activates the appropriate tire inflation indicator assembly 19 on that particular vehicle side in order to indicate to the person attending to the tire, who typically is crouching down at the wheel tire, the tire pressure status in that particular tire. Since significant current consumption is typically only required by the indicator light sources themselves, use of tire pressure adjust sensor 39 can allow system 16 to be in an armed but low power state continually and with the vehicle parked and the vehicle ignition turned off so that vehicle battery power alone is provided to system 16. Once tire pressure adjust sensor 39 detects that the tire adjust event is complete and/or timeout 37 times-out, any illumination of indicator(s) 19 can cease, and system 16 can revert to its quiescent, low current consumption state (and so minimize depletion of vehicle battery charge).

Note also that an interior cabin display of tire pressure status (such as via a display at a location within the vehicle interior cabin such as at or on the interior rearview mirror assembly) can optionally be provided as part of system 16, most preferably though only when ignition sensing circuit 32 indicates that the vehicle ignition is operational and the engine is running. Thus, when operating the vehicle while driving on the highway, or when stopped with the engine running, the driver can view a display located in the interior cabin that alerts as to tire pressure status at the individual vehicle wheels. When the driver determines that the tire pressure at a particular wheel needs adjustment, he or she can

drive to a service station or the like, stop at an air compressor, preferably (for safety) turn off the engine, and exit the vehicle to manually inflate/deflate the particular tire, while aided by the tire inflation assistance monitoring system of this present invention. Alternately, the driver can remain in the vehicle, and have a service attendant manually inflate/deflate the particular tire, while aided by the tire inflation assistance monitoring system of this present invention. Provision of the tire inflation assistance monitoring system of this present invention as an additional feature to an interior vehicle cabin tire pressure status displaying system is a significant enhancement to such a system, and it can be added economically, given that many of the components, such as tire pressure sensors, wireless transmission transmitter/receivers and the like, are already existing in the interior vehicle cabin tire pressure status displaying system.

Tire inflation indicator assembly 19 may include a plurality of different colored indicators or lamps in order to indicate various inflation conditions of the tires of vehicle 12. Such indicators can be coded (such as by color coding, intensity coding, frequency of flash coding, sequence coding, positional coding or the like) in order to signal to the driver when the tire pressure is below, at, or above the desired tire pressure. For example, one such indicator may be a green indicator which indicates that the pressure of the monitored tire or tires is within an acceptable pressure range, such as recommended by the manufacturer of the vehicle. A red indicator may illuminate when the pressure monitored by pressure sensor 20 is less than that recommended by the vehicle operator. The red indicator may flash when the pressure sensed by a pressure sensor 20 is greater than the range of pressures recommended by the vehicle manufacturer. Preferably, tire inflation indicator assembly 19 includes a single color indicator in order to reduce the cost thereof. The single color indicator may, for example, be a green indicator which is illuminated in a steady fashion when the pressure sensed by tire pressure sensor 20 is within an acceptable range recommended by the vehicle manufacturer and flashing when outside of that range. Preferably, the indicator may flash at a first rate, such as at a relatively slow rate, when the pressure sensed by the pressure sensor 20 is less than the range recommended by the vehicle manufacturer and at a faster rate when the pressure sensed by sensor 20 is above the range recommended by the vehicle manufacturer. This single color indicator could be in an OFF condition during inflation of the tire until the inflation condition reaches the normal operating range recommended by the vehicle manufacturer. Other lamp operation protocols may suggest themselves to the skilled artisan.

Preferably, tire inflation indicator 19 includes one or more light-emitting light sources, such as solid-state light emitting diodes (LEDs), available from numerous sources. Various colors of LED can be used (or combined) such as blue, white, orange, yellow, red, amber and red-orange. Alternatively, the tire inflation indicator may be supplied as a conventional incandescent light source, a halogen light source, a fluorescent light source such as a vacuum fluorescent lamp, a light pipe such as fiber-optic bundle forming a light pipe, and the like. Most preferably, illumination by the tire inflation indicator is achieved using non-incandescent light sources, such as light-emitting diodes (LEDs), organic light-emitting material, electroluminescent sources (both organic and inorganic), and the like, and most preferably such non-incandescent sources are low power and are directed sources, such as described in U.S. Pat. No. 5,938,321 and application entitled INTERIOR MIRROR ASSEMBLY FOR A VEHICLE INCORPORATING A SOLID-STATE LIGHT SOURCE, Ser. No. 09/287,926, filed Apr. 7, 1999, now U.S. Pat. No.

11

6,139,172, which are incorporated herein by reference in their entireties, and in such as is disclosed in co-assigned U.S. patent application Ser. No. 09/466,010, filed Dec. 17, 1999, now U.S. Pat. No. 6,420,975, the entire disclosure of which is hereby incorporated by reference herein, and in co-assigned U.S. patent application Ser. No. 09/449,121, filed Nov. 24, 1999, entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, by Barry W. Hutzet et al. of Donnelly Corporation, now U.S. Pat. No. 6,428,172, the entire disclosure of which is hereby incorporated by reference herein.

The light source of tire inflation indicator assembly 19 can include a lens, which may be supplied as a segmented lens, a prismatic lens, or a Fresnel lens, which may be clear or tinted, and may be provided over such light source.

Other modifications may include providing an input 36 from a vehicle keyless entry system. Control 18 may respond to input 36 by providing outputs to illuminate tire inflation indicators 19 upon the user operating the keyless entry system to unlock the doors. The control 18 would preferably illuminate tire inflation indicator assemblies 19 upon actuation of the keyless entry system until the outputs to the tire inflation indicator assemblies are locked out by receiving an input 32 indicating that the vehicle is operating and/or until after a predetermined time interval, determined by timeout 37, has elapsed. Although the invention is illustrated in use with an exterior vehicle portion such as exterior rearview mirror assemblies, a tire inflation indicator assembly, according to the invention, could also be positioned within the interior cabin of the vehicle, such as at a vehicle interior rearview mirror assembly 228 (FIG. 1), or at an inner cabin roof portion such as a header console 229, or at an instrumentation panel 227, or the like. However, this is less preferred as an interior cabin portion such as the interior mirror assembly is not as readily visible to a person inflating a tire mounted on a vehicular wheel (as compared to mounting the indicator of the tire inflation indicator assembly on an exterior vehicle portion such as an exterior side view mirror assembly, or at/on a side marker turn indicator, or at/on an exterior side body panel such as a door panel, wheel well, fender portion or at/on a door handle assembly or the like). Also, the tire inflation indicator assembly can optionally be provided as part of the vehicle wheel assembly itself. For example, the valve provided at the wheel tire to inflate the tire can include a tire inflation indicator assembly (such as a non-incandescent light emitting source such as an electroluminescent source (organic or inorganic) or a light-emitting diode) which has a light emission coded to the inflation status of the tire.

Also, the tire inflation indicator assembly, according to the invention, can be mounted at, or combined with, a light assembly already present on an exterior vehicle portion such as a mirror-mounted turn signal or a side marker turn signal or an exterior mirror-mounted security light. Thus, for example, a side marker turn signal light source present on the side body panel for the purpose of signaling a lane change when a turn signal stalk in the interior vehicle cabin is actuated can also serve the dual purpose of acting as the tire inflation indicator for the tire inflation indicator assembly, according to the invention, and with the inflation status being indicated to the person inflating a tire on the side of the vehicle on which the side marker turn signal is mounted by flashing the turn signal to a code pattern determined and understood to signal a below-desired tire pressure state, a desired tire pressure state, and/or an overly inflated tire pressure state. Likewise, a mirror-mounted signal light or a security light, such as are disclosed in U.S. Pat. No. 5,669,704, the entire disclosure of

12

which is hereby incorporated by reference herein, can be similarly used for dual-purposes.

Optionally, an audible tire inflation indicator can be provided in addition to (or as an alternate to) the visible tire inflation indicators described above for the tire inflation monitoring systems of the present invention. Thus, and referring to FIG. 6, tire inflation indicator system 116 is similar to tire inflation indicator system 16 described above. Thus, tire inflation indicator system 116 includes a tire pressure monitoring controller 118 (that typically includes an antenna, a microprocessor and associated electronic circuitry and that preferably includes user actuation/manual input elements such as switches or buttons or voice actuated input elements that allow a driver select, for example, a particular tire for display of its tire pressure or change the display from Imperial units to Metric units or enter a "training" mode whereby the driver can identify to the controller the location of a tire sensor on a particular wheel of the vehicle so that, during, for example, a tire rotation, the controller can learn which sensor is on what wheel such as by, for example, the driver "burping" tire pressure on a particular identified wheel such as the front passenger-side wheel when the system is in "learning" mode so that the controller can associate that particular wireless broadcast signal with that particular wheel) that receives tire pressure level input signals 122a, 122b, 122c, 122d (preferably via short-range RF wireless transmission and most preferably in accordance with the BLUETOOTH protocol) from tire pressure sensors 120a, 120b, 120c, 120d located, respectively, within the pressurized cavity of the front passenger-side tire, the front driver-side tire, the rear passenger-side tire and the rear driver-side tire (said tires mounted onto the respective wheels of a vehicle). System 116 is optionally, and preferably provided with at least one of lockout 133, door lock status input 134, ignition sensing circuit 132, timeout 137, and tire pressure adjust sensor 139 (preferably, one such tire pressure adjust sensors at each wheel of the vehicle). System 116 also preferably includes visible exterior passenger-side mounted tire inflation indicator 119 (preferably a passenger-side exterior side view mirror-mounted visible mounted tire inflation indicator) and visible exterior driver-side mounted tire inflation indicator 119' (preferably a driver-side exterior side view mirror-mounted visible mounted tire inflation indicator) that operates as described above. System 116 also includes audible tire inflation indicator 145. Audible tire inflation indicator 145 can be of several types. For example, audible tire inflation indicator 145 can comprise a sound-generating microchip or similar solid-state sound or audible tone generating element that is part of tire pressure sensors 120a-d and that "chirps" or sounds or otherwise gives an audible sound coded to the state of inflation of the tire while air is being pumped in or bled out by a driver or service attendant during a tire inflation/deflation event such as at an air pump at a service station. The tone or audible signature of audible tire inflation indicator 145 can signal to the driver or service attendant, while that person is in the act of adjusting air pressure of a particular tire on a vehicle such as at a service station, whether the instantaneous tire pressure of the particular tire being serviced is at, below or above the tire pressure recommended for that particular tire on that particular model vehicle (and optionally, at the particular ambient temperature and/or vehicle load at which the tire pressure adjust event is occurring). Note that where a solid-state sound generator is used as audible tire inflation indicator 145, and where it is incorporated as part of a tire pressure sensor that is located within the pressurized-air tire cavity of a vehicular wheel, then audible tire inflation indicator 145 can optionally, and preferably, operate as part of the tire pressure sensor itself

13

without a need for wireless transmission to and from an interior cabin-mounted controller **118**. In this regard, the tire sensor, the audible tire inflation indicator and the controller are collocated as part of the same tire cavity-mounted tire pressure sensing module. Alternately, audible tire inflation indicator **145** can comprise the vehicle horn. In such an embodiment, and while the person is actually adjusting the tire pressure on a particular tire when external to the vehicle (and typically crouched down at that particular wheel being serviced and preferably with the vehicle ignition turned off), a wheel-mounted tire pressure sensor **120a** (taking the example where the person is outside the vehicle adjusting the tire pressure of the front passenger-side wheel) transmits a wireless signal **122a** that is received at vehicle tire pressure monitoring controller **118** that is preferably located within the interior cabin of the vehicle (preferably at, on, or within an interior rearview mirror assembly or at, on or within a display assembly such as a flip-down video display assembly, as described below). Controller **118** processes signal **122a**, and determines whether the tire pressure being sensed by tire sensor **120a** is below, at, or above the tire pressure recommended by the vehicle manufacturer/tire manufacturer for that particular model/type of tire on that particular model vehicle (optionally taking into account the ambient temperature the vehicle is operating in and the load in the vehicle, such as might be determined by sensors associated with and sensing the vehicle suspension system). Dependent on the tire pressure sensed, controller **118** causes the circuitry controlling the vehicle horn to cause the horn to sound an audible signal or pattern of sounds that signal to the person adjusting the front passenger-side tire pressure that that tire is below, above and/or at the desired tire pressure recommended for that particular tire, and that audibly guide or prompt that person to pump more air in or bleed air out in order to adjust that tire's pressure to the correct pressure level, for example, 35 psi (pounds per square inch). In addition, and optionally and preferably, visual passenger-side tire inflation indicator **119** can visually signal the instantaneous tire pressure being sensed at the front passenger-side wheel as its tire pressure is being adjusted. To avoid distracting or perturbing others in the vicinity, the sound level emitted by the car horn when functioning as an audible tire pressure indicator can be reduced in level from that normal for the horn, and it can also be of a sound pattern distinctive to a particular brand of vehicle/automaker so that a person adjusting tire pressure on his or her vehicle can identify and distinguish the audible tire pressure adjust signal of that person's vehicle from other audible signals from other vehicles, including from any other audible tire pressure indicator device-equipped vehicle that happens to be undergoing a tire pressure adjust in the immediate vicinity (a relatively rare/unlikely event given that most service stations have only one air hose provide to pump air into customers' tires). Other locations for audible tire inflation indicator **145** are possible on a vehicle such as a sound/tone generator located in either of, or both of, the driver-side and passenger-side exterior side view mirror assemblies and/or in any of the door handle assemblies of the vehicle or in an engine compartment or in a trunk compartment or in a side door panel or in a wheel well or in a body panel of the vehicle. Note that in the context of the present invention, an audible tire pressure indicator comprises a sound device that generates a sound pattern audible to a person outside the vehicle while that person is undertaking a tire pressure adjustment of a tire on a wheel mounted on the vehicle (such as with an air hose from a pressurized air pump such as at a service station), and such that the audible sound indicator encompasses generating an audible sound that indicates to the person adjusting

14

the tire pressure that the tire pressure is at, below and/or above a recommended level for that tire on that vehicle, and as known to the vehicle tire pressure monitoring controller (typically stored in an electronic storage element thereof) of the vehicle tire pressure monitoring system. Note also that in the context of the present invention, a visible or visual tire pressure indicator comprises a light emitting light source (such as a light emitting diode or an incandescent source or a fluorescent source or an electroluminescent source) that, when powered, emits a light pattern visible to a person outside the vehicle while that person is undertaking a tire pressure adjustment of a tire on a wheel mounted on the vehicle (such as with an air hose from a pressurized air pump such as at a service station), and such that the visual or visible tire pressure indicator encompasses generating a light that indicates to the person adjusting the tire pressure that the tire pressure is at, below and/or above a recommended level for that tire on that vehicle, and as known to the vehicle tire pressure monitoring controller (typically stored in an electronic storage element thereof) of the vehicle tire pressure monitoring system. An audible tire pressure indicator device can be located anywhere in the vehicle such as in the vehicle interior cabin, in an engine compartment, in a trunk compartment, in a body panel, or in a vehicular accessory (such as an interior mirror assembly or an exterior mirror assembly or a door handle assembly or a console assembly), but is preferably located exterior to the interior cabin of the vehicle (so as to be more readily audible to a person outside the vehicle in the act of adjusting tire pressure). A visible or visual tire pressure indicator device can be located in an interior portion of the vehicle (such as at, on, within or adjacent an interior mirror assembly or a header console assembly or a dome light assembly) or at an exterior portion of the vehicle (such as at, within or adjacent an exterior side view mirror assembly or a door handle assembly), but preferably at a location readily visible to a person outside crouched at a wheel.

Also, in any of the above embodiments, a tire pressure sensor can be located in a spare tire of the vehicle, and the spare tire pressure can be adjusted aided by the audible and/or visible and/or tactile tire pressure inflation status indicators of the present invention.

Also, optionally, the tire pressure sensor located in each tire on the vehicle can include a solid-state vibrator or trembler (such as the vibration devices common on pagers and cell phones that provide a vibration indication of receipt of a call or of a message, as known in the art). Thus, when, for example, a tire pressure sensor at a particular wheel senses that the tire pressure in that particular tire is at (or close to) the recommended or desired tire pressure, then the air inlet/outlet valve or stalk or valve stem to which an air hose connects is caused to vibrate, by (referring to FIG. 6) vibrator elements **124a**, **124b**, **124c**, **124d** (that are respectively associated with the tire pressure sensor/air inlet valve of the front wheel tires and the rear wheel tires), and thus indicate to a person in the act of a tire pressure adjust that the tire pressure is at (or close to at) the desired tire pressure. Such trembler or vibrator can be configured only to operate when an actual tire pressure adjust event is occurring (such as only being active when tire pressure is rapidly changing such as might indicate (and be characteristic of) a tire pressure adjust event occurring, or when the nipple in the valve stem is depressed). Thus for example, should an air hose be connected to the valve stem that allows inflation/deflation of a tire on a wheel equipped with a tire sensor of this invention that includes a vibrator element, then, upon recognition that a tire adjust event is occurring (such as by detection or depression of the tire inlet nipple and/or by detection of a rapid rate of change of air

15

pressure), the tire pressure sensor determines whether the instantaneous tire pressure is above or below the desired, pre-determined tire pressure level recommended for that tire on that vehicle, and upon detecting (for example) that tire pressure is higher than desired, the tire pressure sensor causes its in-built vibrator to vibrate or tremble which in turn causes the valve stem to tremble. Since the person adjusting the tire pressure is holding the nozzle of an air hose to that tire valve stem, that person will feel these vibrations, and knowing from the vehicle owner's manual that "vibration" means that "tire pressure is too great", is instructed by the tactile feel of the nozzle on the nipple to deflate the tires. Once the correct tire pressure is reached, the vibrations cease, and upon feeling that the vibrations have ceased, the person can cease deflating the tire. If however the valve stem is not trembling or vibrating when the person first initiates a tire pressure adjust, the person knows (again from the vehicle owner's manual) that this signifies that the tire is under-inflated, and so the person is prompted to pump air in to inflate the tire, but to cease once a vibration or tremble in the valve stem is first felt, as this signifies that the air pressure in the tire has now reached the recommended pressure level. Different tactile codes can be envisaged that are indicative of tire pressure level in a tire while that tire is being inflated or deflated using an air hose from an air pump at a service station. The advantages of a tactile tire pressure indicator as described herein include that a module comprising the tire pressure sensing transducer, a tire pressure processor (preferably a microprocessor-based tire pressure monitor), a battery, associated circuitry, the inlet valve (including its stem and nipple), and the vibrator or tremble-generator can be provided as a sealed (preferred), unitary package that can be placed onto a wide variety of tire cavities on wheels, and without the necessity and/or expense of providing a wireless link to an in-cabin controller (although such is preferable when there is a desire to provide a vehicle tire pressure display to the driver while the driver is driving). Further, a tactile tire pressure indicator such as described herein such as shown in FIG. 6 can be used in conjunction with a tire pressure display system that senses states of tire inflation or deflation by monitoring a performance characteristic of an ABS braking system on the vehicle.

As described above, it is preferable that a display of tire pressure status be provided in the interior cabin of the vehicle (such as interior cabin tire pressure status display 123 of system 116) so that the driver, when operating the vehicle such as when driving down the highway, can check/be made aware of the tire pressure at any of the wheels on the vehicle. Note, and as described above, such interior cabin tire pressure displays are intended for use while driving the vehicle on a highway, and are normally not intended for use when the vehicle is stopped and with its ignition turned off, and are not normally adapted to be visible or useful to a person outside a vehicle and crouched down at a wheel in the act of making a tire pressure adjustment using an air hose as typically provided at a service station or the like. As described above, a preferred location for such an interior cabin tire pressure status display is at, on or within an interior mirror assembly of the vehicle. Also, and as disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/237,077, filed Sep. 30, 2000, pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No.

16

60/234,412, filed Sep. 21, 2000, pending U.S. provisional application entitled INTERIOR REARVIEW MIRROR ASSEMBLY INCORPORATING A VIDEO SCREEN, Ser. No. 60/218,336, filed Jul. 14, 2000, and pending U.S. provisional application entitled INTERIOR REARVIEW MIRROR ASSEMBLY INCORPORATING A VIDEO SCREEN, Ser. No. 60/186,520, filed Mar. 2, 2000, U.S. Pat. No. 6,124,647 and U.S. patent application entitled INFORMATION DISPLAY IN A REARVIEW MIRROR, Ser. No. 09/660,712, filed Sep. 13, 2000, now U.S. Pat. No. 6,291,906, the entire disclosures of which are hereby incorporated by reference herein, an interior cabin-located tire pressure status display can be displayed at a variety of interior mirror assemblies, accessory modules mounted at, on, within or adjacent to the interior mirror assembly, and display assemblies including flip/down, stowable video display assemblies (and preferably display assemblies including flip/down, stowable video display assemblies mounted at, on, within or adjacent to the interior mirror assembly). In this regard, it is preferable that the vehicle tire pressure monitoring controller (such as controllers 16 and 116 of, respectively, FIGS. 5 and 6) be incorporated into such interior mirror assemblies or such accessory modules or such flip-down video display assemblies.

Thus, as referring to FIGS. 7 and 8 (and such as is disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, the entire disclosures of which are hereby incorporated by reference herein), an interior cabin tire pressure status display 7624 can be included in interior mirror assembly system 7600. Referring to the FIGS., rearview mirror support 7710 includes a vehicle information display 7624, 7724 of tire pressure status, similar to the unitary interior mirror support and information display assembly disclosed in U.S. Pat. No. 6,087,953, entitled REARVIEW MIRROR SUPPORT INCORPORATING VEHICLE INFORMATION DISPLAY, to Jonathan E. DeLine et al., issued Jul. 11, 2000, the entire disclosure of which is hereby incorporated by reference herein. Support 7710 further includes a pivot/swivel joint 7731 that allows adjustment of the viewing position of information display 7624, 7724 when support 7710 fixedly mounts to a windshield-mounted mirror attachment button as described in U.S. Pat. No. 6,087,953. As seen in FIG. 8, information display 7724 can display tire pressure status and/or can display a variety of information (such as the tire pressure display/compass directional heading/exterior temperature display shown in display 7624 in FIG. 7) and such as is described above in relation to the other embodiments of the present invention. Mirror housing 7612b mounts to ball member 7718 to form a pivot joint that allows adjustment of mirror housing 7612b about support 7710. Note that the connection of mirror housing 7612b to support 7710 can include a second pivot joint to allow "two-ball" adjustability of the mirror housing. Also, ball member 7718 can optionally be replaced with a mirror assembly attachment member (such as with the mirror button configuration as used on that particular vehicle) and then the interior mirror assembly can detachably and preferably, break-away attach to support assembly 7710. This allows removal of an existing interior mirror assembly from the windshield button in a vehicle, mounting of support assembly 7710 on that windshield-mounted button, and reattachment of the existing interior mirror assembly (or another) onto support assembly 7710 via the mirror-mounting button provided thereon. Note also that the various circuitry, anten-

17

nae and transmitters/receiver, including the vehicle tire pressure monitoring controller discussed above, can be included in housing **7714** of adjustable support/accessory assembly **7710** such as vehicle tire pressure monitoring controller **7723** (that preferably includes an RF receiving antenna, a microprocessor and all the circuitry, user input controls/buttons and other controls needed to receive and process wireless signals broadcast from the various tire pressure sensors located in the tire on the wheels of the vehicle) of rearview mirror support **7710** (or alternately, can be positioned in adjustable mirror housing **7612b** behind reflective element **7612d**). Further, housing **7612b** or support/accessory assembly **7710** can include a telematic system including a telematic system including floating car data can be included in any of the assemblies of the present invention whereby the vehicle transmits its position to a central aggregator (such as in support assembly **7710** or in mirror housing **7612b**). The central aggregator also receives positional data from many other vehicles on that highway/in that region. The central aggregator integrates the position, speed, direction etc of all the vehicles inputting, as well as weather data, road repair data etc, traffic-flow data, road-condition data and the like, and integrates these to report back to individual vehicles the best possible route for that vehicle, taking all conditions including traffic, weather etc into account. Also, telematic and/or cellular phone transmissions from the vehicle can be detected and analyzed using wireless location technology (such as is available from Webraska) in order to locate the position of a mobile device user in a vehicle on a highway. Also, any of the telematic systems of the present invention can include a vehicle emergency messaging system.

Referring to FIG. 9, another embodiment **8300** of an accessory module/mirror system that includes a vehicle tire pressure monitoring controller **8323** (that preferably includes an RF receiving antenna, a microprocessor and all the circuitry, user input controls/buttons and other controls needed to receive and process wireless signals broadcast from the various tire pressure sensors located in the tire on the wheels of the vehicle) is illustrated. Accessory module/mirror system **8300** includes an interior rearview mirror assembly **8310** and an accessory module **8312**. Rearview mirror assembly **8310** can be a double-ball (as illustrated) or a single-ball mirror assembly, as such are known in the rearview mirror art. Accessory module **8312** is adapted to releasably mounted to an interior vehicle, such as a windshield **8318** on a mirror mounting button **8320**, and such as is disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, the entire disclosures of which are hereby incorporated by reference herein. Modular **8312** includes a housing **8340** with an upper portion **8346**, a lower portion **8342**, and a medial or central portion **8343**. In the illustrated embodiment, lower portion **8342** comprises a fixed portion, which extends below central portion **8343** and below support **8329** of interior rearview mirror assembly **8310** but preferably forwardly of housing **8314** of interior rearview mirror assembly **8310**. In this manner, lower portion **8342** is essentially hidden or in an unobtrusive/unnoticeable position to minimize the distraction to the driver while optimizing the use of the space below and behind the mirror housing **8314** of interior rearview mirror assembly **8310**, while minimizing interference with the driver's forward field of view through the windshield. Lower portion **8342**, similar to lower portion **8242**, includes a plurality of user interface accessories **8352** (including user inter-

18

faces to controller **8323**), which are positioned in such a manner to permit easy physical access to the various accessories mounted thereon or therein. For example, lower portion **8342** may include a microphone **8366**, a speaker **8368**, and a digital message recorder and/or note taker **8370**. In addition, accessory module **8312** also incorporates as interior cabin-located vehicle tire pressure monitoring controller **8323**. The tire pressure monitoring controller **8323** preferably include a wireless receiver such as an RF receiver that receives wireless communication from individual tire pressure sensors, such as piezo-electric transducers, located in the individual tire valves and/or wells of the vehicle such as is described in U.S. Pat. No. 5,741,966 to Hanfield et al. entitled METHOD AND SYSTEM FOR MONITORING A PARAMETER OF A VEHICLE TIRE, issued Apr. 21, 2000, the disclosure of which is herein incorporated by reference in its entirety. Various other accessories may also be incorporated into module **8312**. For further details of additional or other accessories which may be incorporated, reference is made to the previous embodiments and to the various patents and applications incorporated by reference herein. It should also be understood that lower portion **8342** may optionally comprise an adjustable portion. Also, controller **8323** can be located in any portion of module. Accessory module **8312** includes an information display element **8324** (such as a vacuum fluorescent display or a liquid crystal display or a field-emission display or an electroluminescent display or a light emitting diode display, and preferably a multi-pixel display and more preferable, a reconfigurable display) that displays an output of controller **8323** and that conveys information to the driver as to the tire pressure status of one, some or all of the tires on the wheels of the vehicle. Note, and as disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, the entire disclosures of which are hereby incorporated by reference herein, the provision of a module **8312** such as shown in FIG. 9 that includes both controller **8323** and display element **8324** of a tire pressure monitoring and/or tire pressure display system is particularly advantageous as it includes mounting the module onto a windshield-mounted rearview mirror attachment element or button **8320** (or alternately, a header-mounted rearview mirror attachment element or plate), and with the interior rearview mirror assembly **8310** detachably and, preferably, break-away mounting to mirror assembly attachment button or element **8321** that is part of module **8312**. In this manner, a tire pressure monitoring and/or tire pressure display system can be readily mounted into a vehicle by first detaching the existing rearview mirror assembly from its mount (typically a windshield-mounted button), next attaching module **8312** to that windshield-mounted button, and then re-attaching the rearview mirror assembly to the mirror-mounting element or button (that is the same as on the windshield) that is part of module **8312**. The read-out/indication of tire pressure is readily viewable by the driver such as at display **8321**. Note that optionally, the viewing position of display **8321** is positionable such as by swivel or pivot joint **8346a**, or optionally display **8321** can be canted or angled towards the driver to enhance viewability by the driver of information displayed thereon. Also, optionally, display **8321** can be positioned on module **8312** so as to be visible below the mirror case of the interior mirror assembly (as opposed to above as in FIG. 9).

Also, and as disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPO-

19

RATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, the entire disclosures of which are hereby incorporated by reference herein, and referring to FIG. 10, an accessory module/mirror system 7900 incorporating a controller 7923 for a tire pressure monitoring and/or tire pressure display system is illustrated. Accessory module/mirror system 7900 includes an interior rearview mirror assembly 7910 and an accessory module 7912, which includes one or more viewable user interface accessories 7950 and optionally one or more user interface accessories 7951 which are accessible but positioned in a manner behind interior rearview mirror 7910 so that they are not necessarily visible to the driver of the vehicle when the driver is in a normal sitting position, such as when driving.

As best seen in FIGS. 12 and 13, interior rearview mirror assembly 7910 includes a mirror casing or housing 7914 and a reflective element 7916 (for example a prismatic or an electro-optic reflective element) and, further, a mirror housing support 7929, similar to the previous embodiments. Optionally and preferably, when reflective element 7916 comprises a prismatic reflective element, interior rearview mirror assembly 7910 includes a toggle for adjusting the position of the reflective element between its day and night viewing positions, such as described in pending U.S. patent application entitled TOGGLE ASSEMBLY FOR REAR-VIEW MIRROR, Ser. No. 09/533,127, filed Mar. 23, 2000, now U.S. Pat. No. 6,318,870, which is incorporated herein by reference in its entirety. In addition, though illustrated as a dual ball mount support, housing support 7929 may include a fixed support arm or may include a single ball mount arrangement.

Accessory module 7912 is adapted to mount to a vehicle and, preferably, adapted to releasably mount in the interior of the vehicle. In the illustrated embodiment, accessory module 7912 is adapted to releasably mount to windshield 7918 on a windshield mounting button 7920 and, preferably, includes a mirror mount 7944, such as a channel shaped member, which provides a break-away mounting for module 7912 on button 7920. It should be understood that module 7912 may also be mounted to a header of the vehicle. Button 7920 may be of conventional design and is preferably mounted to the inner surface of windshield 7918 by an adhesive. In addition, accessory module 7912 preferably includes a mirror mounting button 7936 for releasably mounting interior rearview mirror assembly 7910 to module 7912 and, in turn, to windshield 7918. Alternately, accessory module 7912 can mount adjacent to but separate from the attachment element of the interior mirror assembly (such as mounting to a separate windshield-mounted attachment element or header-mounted attachment member, such as described above).

Mirror housing support 7929 preferably comprises a dual ball mount support with a support arm 7924 and a mirror mount 7926 with ball and socket connections between support arm 7924 and mirror mount 7926 and between support arm 7924 and mirror casing 7914 to provide pivoting of support arm 7924 about mirror mount 7926 and/or pivoting of housing 7914 about support arm 7924. Mirror mount 7926 releasably engages mirror mounting button 7936 of accessory module 7912 and provides a break-away mounting of interior rearview mirror assembly 7910 to module 7912.

Referring again to FIG. 10, accessory module 7912 includes a module housing 7940 with a lower portion 7942 (FIGS. 11-13) including mirror mount 7944 for releasably engaging mirror mounting button 7920. Mirror mount 7944 is provided by a channel shaped recess which is either formed in

20

housing 7940 or provided by a channel shaped member mounted to housing 7940. An opposed side of lower portion 7942 of body 7940 is provided with mirror mounting button 7936 and, preferably, with mirror mounting button 7936 aligned with mirror mount 7944. In this manner, when interior rearview mirror assembly 7910 is mounted to mirror mounting button 7936 and module 7912 is mounted to button 7920, mirror mounting button 7920 and mirror mounting button 7936 are aligned along a common axis.

An upper portion 7946 of body 7940 is positioned above housing 7914, including bezel 7948, and reflective element 7916 of interior rearview mirror assembly 7910 and includes one or more of the viewable user interface accessories 7950. Accessories 7950 may include, for example, a display 7952, user-actuatable controls/buttons 7954, and/or lights 7956. In the illustrated embodiment, accessories 7950 are positioned on a rearwardly facing portion of upper portion 7946 and are preferably aligned to provide a compact arrangement which offers a wealth of information in a small space.

In addition, accessory module 7912 may house a variety of vehicle accessories and controls in addition to tire pressure system controller 7923. For example, a GPS navigational system, including a GPS antenna, may be included in housing 7940. Other accessories that may, for example, be included in housing 7940 include a trainable garage door opener, such as a Homelink® Video System registered trademark system available from JCI of Holland, Mich., and/or may include a cellular phone system including a complete telecommunication system/antenna/transceiver and/or telematic system including antenna and transceiver and/or an automatic toll booth/remote transaction transceiver system and/or a compass direction system, including a compass sensor, such as described above and/or any of the vehicle accessories and functions described above. In addition, housing 7940 may include a microphone system (preferably a multi-microphone array including a digital sound processing system, which may also be including in housing 7940). Such a microphone system is suitable for use in voice command interactions, cellular phone interactions, hands-free phone operations, telematic communications, and the like. Furthermore, accessory module/mirror system 7900 may include a loud speaker, located, for example in housing 7940 or mirror casing 7914 (or, less preferably, elsewhere in the vehicle) that, for example, functions as a speaker for an audible tire pressure indicator device. Preferably, the loudspeaker comprises a solid-state, ceramic speaker element (such as a piezo-electric loudspeaker element). Such solid-state, ceramic speakers are provided in a thin configuration (less than 5 mm in thickness and often less than 3 mm in thickness), and are available from such as Panasonic of Tokyo, Japan. These solid-state loudspeakers are particularly adaptable to mounting in a compact space (such as within the various housings of the present invention) and/or mounting onto a PCB. Preferably, module 7912 also includes a carrier member 7958 positioned in housing 7940, for example, in lower portion 7942, for supporting one or more of the vehicle accessories and controls, including supporting circuitry for the various user interface accessories.

User interface accessories 7950, such as user-actuatable buttons 7954, may be used to actuate or interface with one or more of the various systems (including a tire pressure monitoring system and/or a tire pressure display system, such as described above and in the patents and applications incorporated by reference herein, which may be incorporated into accessory module/mirror system 7900. For example, buttons 7954 may be used to actuate such vehicle functions as the opening of a trunk or hood of the vehicle, emergency light flashers, a road side assistance system, such as an ONSTAR®

21

system, selection of display of tire pressure of a particular wheel, entering a "learning/training" state for a tire pressure system or the like. Display 7952 can function as a display screen for a tire pressure system and optionally for other systems as well such as a GPS system, telematic system, a remote transaction system, or the like, which may or may not be incorporated into module 7912. However, it is preferable that module 7912 provide a self-contained unitary module which houses complete or sub-systems, such as the components (such as an antenna, user-input controls, microprocessor, electronic memory, and associated circuitry) of a tire pressure monitoring/tire pressure display system (other than those components that are located outside the interior cabin, such as in the wheels or as part of an exterior mirror assembly) and may additionally house other systems or sub-systems such as a GPS system comprising a GPS antenna, GPS circuitry, and a display screen displaying the GPS information. In this manner, module 7912 is especially suitable as an after-market product. However, optionally, module 7912 can be installed when the vehicle is being produced at the OEM automaker. Alternately or in addition, display 7952 can function as a display for a portable computer device, portable cellular phone, and/or a portable personal digital assistance device, such as a PalmPilot® or other personal digital assistance devices. In addition, display 7952 may serve multiple purposes, such as a video screen for an onboard vehicular camera and/or a video monitor screen for a portable computing/PDA/cellular phone/communication device. For example, a removable telecommunication and/or computing accessory, as previously described, can be removably docked into a docking station of accessory module 7912. In addition, optionally, display 7952 may be removably mounted in accessory module 7912 so that display 7952 may be detached and used remote from the vehicle such as part of a portable video device, portable computer monitor, portable PDA, or a portable navigation device.

Display 7952 may include a display element 7952a (FIG. 10), such as a vacuum fluorescent display, an LED display, a field emission display, an electroluminescent display, or a liquid crystal display and optionally may comprise a multi pixel display capable of being reconfigured and capable of displaying scrolling text including alphanumeric text in various fonts and languages. In this manner, display 7952 may be used to display text messaging. For example, display element 7952a may display, in response to a GPS system, for example the name of the next street or junction or highway or entrance or exit ramp being approached by the vehicle equipped with accessory module/mirror system 7900, or display element 7952a may display the tire pressure in a particular wheel tire in response to an interrogation by the driver or in response to the tire pressure display system detecting that a particular tire's tire pressure has fallen below, or is above, a recommended tire pressure level that is stored in controller 7923.

Light or lights 7956 may form part of an interior camera surveillance system, and preferably comprise low-level non-incandescent light sources, such as light emitting diodes, organic light emitting diodes, electroluminescent sources (inorganic and organic), or the like. Other features that may be incorporated into accessory module/mirror system 7900 and, preferably into accessory module 7912, include an inclinometer, such as an accelerometer-based inclinometer or a liquid based inclinometer. Such an inclinometer may serve as a sensor to detect vehicle inclination and may be coupled to a system such as a comprehensive anti-rollover system, which is especially desirable in vehicles with high centers of gravity (such as sports utility vehicles).

22

In preferred form, upper portion 7946 of housing 7940 includes an adjustable portion such as telescoping portion 7960 on which user interface accessories 7950 are mounted. In this manner, an occupant of the vehicle may adjust the position of the user interface accessories to suit their needs. In order to accommodate the repositioning of user interface accessories 7950, accessories 7950 are connected to carrier 7958 by extendable cable or wiring 7962. In addition, generally non-viewable user interface accessories 7951, such as phone jacks, power sockets, or card readers, or the like may be positioned behind mirror case 7914 on housing 7940. Since these accessories do not require visual interface, unlike the video display buttons, or the like, they may be advantageously positioned in non-viewable and otherwise unused space though these accessories may be viewed if the interior rearview mirror assembly is removed or the user shifts their position to, for example, a bent position.

Referring again to FIG. 12, in preferred form, upper portion 7946 of housing 7940 is spaced above casing 7914 of interior rearview mirror assembly 7910 to permit an occupant of the vehicle to grasp housing 7914 to adjust the position of reflective element 7916 without hindrance from upper portion 7946 of housing 7940. In addition, movable portion 7960 of housing 7940 may optionally be provided with a sliding/swivel adjustment so that, in addition to moving the user interface accessory 7950 toward or away from the user, user interface accessory 7950 may be tilted or adjusted downwardly or upwardly as desired.

In the illustrated embodiment, housing 7940 provides the various user actuatable or user visible accessories and/or displays at its upper portion. In this manner, the user interface accessories, such as user actuatable buttons 7954 and display 7952 and lights 7956 are positioned above bezel 7948 and reflective element 7916, as previously noted, causing minimal distraction to the driver and, further, without hampering the driver's forward field of view. Alternately, accessory module 7912 may include a housing with an enlarged lower portion which extends and projects below bezel 7948 and reflective element 7916 or may include both upper and lower portions which provide and position accessories both above and below housing 7914, as will be more fully described in reference to FIGS. 12 and 13. Preferably, the lower portion of module 7912 is substantially located or nested behind the lower portion of the adjustable mirror housing (such as casing 7914 of mirror assembly 7910) of the interior mirror assembly so as to be essentially not visible/noticable and thus unobtrusive to the driver during the driver's normal driving task, and such as not to significantly intrude into the driver's forward field of vision through the windshield.

It can be appreciated from the foregoing description, that accessory module 7912 provides a suitable after-market product which can be simply installed on an existing mirror mounting button, already provided by the vehicle manufacturer, with the interior rearview mirror assembly mounted directly onto the accessory module. Furthermore, accessory module 7912 may be removed for repair, replacement, or upgrade as needed or as desired. It should be noted that accessory module is separate and distinct from interior mirror assembly 7910, and for example, optionally can be manufactured and sold independent of the interior mirror assembly, and by a different manufacturer. Also, optionally, accessory module 7912 (as with other accessory modules of the present invention) can attach to the windshield (or header region) at an attachment element different than that of the interior mirror assembly.

Referring to FIG. 14, the numeral 8012 generally designates another embodiment of the accessory module that

includes components of a tire pressure monitoring system and/or tire pressure display system. Accessory module **8012** includes a housing **8040**, similar to the previous embodiment, and illustrates an alternate arrangement for viewable user interface accessories **8050**. User interface accessories **8050** are positioned similar to user interface accessories **7950** above bezel **7948** and reflective element **7916** of interior rearview mirror assembly **7910**. In the illustrated embodiment, user interface accessories **8050** include a display **8052** which is positioned closer to the left hand side of module **8012** to be positioned for closer viewing to the driver of the vehicle (in the case of a vehicle that drives on the right hand side of the road) and a plurality of buttons **8054** which are grouped together on the right hand side of accessory module **8012** (as viewed in FIG. 14). Similar to the previous embodiment, user interface accessories **8050** include a pair of lights **8056** which are positioned on opposed ends of upper portion housing **8040** to provide lighting to both sides of the vehicle interior.

It should be understood, that the selection and arrangement of user interface accessories **7950**, **8050** may be modified to suit the needs of the vehicle manufacturer or the customer. In addition, because accessory modules **7912** and **8012** comprise separate unitary modules, modules **7912** and **8012** are particularly suitable in an after-market installation or for being produced at the OEM automaker. In addition, modules **7912**, **8012** may be provided in a variety of models including economy, mid-range, and deluxe models, for example.

Referring to FIG. 15, another embodiment of the accessory module/mirror system **8100** is illustrated that includes components of a tire pressure monitoring system and/or tire pressure display system. Accessory module/mirror system **8100** includes an interior rearview mirror assembly **8110** and an accessory module **8112**. Interior rearview mirror assembly **8110** may be similar to any one of the previous embodiments and, therefore, reference is made therein for further details. Similar to the previous embodiments, accessory module **8112** mounts to the vehicle and, preferably, to windshield **8118** on a mirror mounting button **8120**, which is provided on the windshield typically by the vehicle manufacturer. Accessory module **8112** includes a housing **8140** with a lower portion **8142** including a channel or mirror mount (similar to mirror mount **7944**) on one side of housing **8140**, for releasably mounting module **8112** to button **8120**, and a mirror mounting button **8136** on its opposed side for releasably mounting interior rearview mirror assembly **8110** to mirror mount **8112** using a break-away connection, which in turn is releasably mounted to windshield **8118** using a break-away connection on button **8120**. As noted in reference to the previous embodiment, mirror mounting button **8136** may be formed on housing **8140** or may be secured thereto using conventional means, such as fasteners, an adhesive, or the like.

Upper portion **8146** of housing **8140** preferably comprises a telescoping portion which permits adjustment or repositioning of the viewable user interface accessories **8150**, which are mounted in housing **8140**. User interface accessories **8150** may include for example a display **8152**, a plurality of user actuable buttons **8154**, and a microphone and/or speaker **8156**. As described in reference to the previous embodiment, accessory module **8112** may incorporate a plurality of different systems including user interface systems, such as a GPS system, a roadside assistance system, a telematic system, a remote transaction system or the like. Display **8152**, therefore, may display information relating to a tire pressure monitoring system and/or tire pressure display system as well as, optionally, information relating to other systems such as a GPS system, telematic system, remote transaction interaction

system, and/or roadside assistance system, for example using text messaging or the like. Furthermore, buttons **8154** may be used to actuate or communicate with any of the various systems. For example, one button may be used to activate a roadside assistance system, such as an ONSTAR® system. In addition, buttons **8154** may be used to activate vehicle systems, such as a hood or trunk latch, to turn on an interior light, or the like.

Similar to the previous embodiments, accessory module **8112** is especially suitable as an after-market product which can be mounted to a conventional mirror mounting button which is provided by the vehicle manufacturer. Other accessories which may be included in accessory module **8112** include antennas, including antennas for a tire pressure monitoring system and/or tire pressure display system, garage door openers, keyless entry systems, radio receiver, microwave receivers, remote transaction transceivers, toll payment transceivers, cellular phone systems, telematic systems, or the like. In addition, accessory module **8112** may incorporate one or more image capturing devices, such as a CCD camera or a CMOS camera, for use, for example, as a video phone camera or a seat occupancy camera, or a vehicle interior surveillance camera, or the like, or may incorporate a compass direction sensor (such as described above) or a rain sensor/fog sensor/fogging sensor (such as described above). In addition, display **8152** may display images collected from the image capturing device and/or information from any of the accessories in accessory module **8112** (and/or from accessories located elsewhere in the vehicle such as at, on or within the interior mirror assembly and/or an exterior mirror assembly).

Referring again to FIG. 15, accessory module **8112** further optionally includes a vehicle power socket **8160** connected to the vehicle ignition system or a battery electrical system, such as a cigarette lighter type socket (conventional in many automobiles) into which accessories can be plugged. In the illustrated embodiment, socket **8160** is located on the rearward facing side **8140a** (when module **8112** is mounted to mounting button **8120**) and preferably behind interior rearview mirror casing **8114**. In this manner, socket **8160** is located in a portion of module **8112** hidden by interior rearview mirror assembly **8114** and, yet, is accessible to an occupant of the vehicle. Alternately, module **8112** can be wired to the vehicle electrical system and/or be solar-powered via solar panels. In preferred form, user interface accessories which require visual interaction or recognition are preferably located in the visible portions of module **8112**, such as upper portion **8146** of housing **8140**, which is above interior rearview mirror casing **8114**.

Referring to FIG. 16, another embodiment **8200** of an accessory module/mirror system that includes components of a tire pressure monitoring system and/or tire pressure display system is illustrated. Accessory module/mirror system **8200** includes an interior rearview mirror assembly **8210** and an accessory module **8212**. For further details of interior rearview mirror assembly **8210**, reference is made to the previous embodiments. Accessory module **8212** is adapted to releasably mount to an interior of a vehicle, such as to a windshield **8218**, on a mirror mounting button **8220**. In addition, accessory module **8212** includes a mirror mounting button **8236** on which interior rearview mirror assembly **8210** may be releasably mounted to accessory module **8212** and in turn windshield **8218**. Similar to the previous embodiments, preferably mirror mounting buttons **8220** and **8236** are aligned along a common axis to provide a serial mounting of interior rearview mirror assembly **8210** and accessory module **8212** (although other mounting configurations are possible including a parallel mounting on a common attachment adapter element, or

25

separate mounting, as described above). Alternately, other attachment elements can be used, such as described above.

In the illustrated embodiment, accessory module **8212** includes a housing **8240** with a generally C-shaped cross-section to form an upper portion **8246**, for positioning above casing **8214** of interior rearview mirror assembly **8210**, and a lower portion **8242** for positioning below housing **8214** of interior rearview mirror assembly **8210**. In addition, housing **8240** includes a central portion **8243**, which includes a mounting member **8244** for releasably engaging mirror mounting button **8220** and, further, includes mirror mounting button **8236**. As previously described above, mirror mounting button **8236** is preferably aligned with mirror mount **8244** and, thus, is provided on central portion **8243** of housing **8240** on an opposed side or rearward facing side of accessory module **8212**.

In the illustrated embodiment, upper portion **8246** is adapted to be adjustable, by an adjustable element such as by a pivot, tilt, swivel, or nesting connection **8242a** or a combination thereof, so that the viewable user interface accessories **8250** are visually and/or physically accessible to an occupant of the vehicle and, further, are adjustable to meet the occupant's needs. For examples of optional user interface accessories, reference is made to the previous embodiments.

Lower portion **8242** is optionally similarly adapted to be adjustable, such as by a pivot, tilt, swivel, or nesting connection **8242a**, so that the various user interface accessories **8252** supported thereon or therein may be repositioned along with lower portion **8242** of housing **8240**. In the illustrated embodiment, lower portion **8242** protrudes rearwardly from central portion **8243** such that accessories **8252** are positionable below housing **8214** of interior rearview mirror assembly **8210** or slightly rearward of bezel **8248** and reflective element **8216** as desired.

Module **8212**, similar to the previous embodiment, may include a plurality of systems and accessories as previously described, such as an antenna **8262**, an image capturing device **8264**, a microphone **8266**, and/or a speaker **8268**. Accessory module **8212** may include other or further accessories, including, for example a message recorder or digital note taker **8270**, whereby voice recordings, such as telephone numbers, notes, dictation, preferably short dictations, can be recorded for easy replay by an occupant of the vehicle. In addition, digital message recorder or digital note taker **8270** may be used in conjunction with microphones (such as **8266**) or speakers (such as **8268**) located in module **8212** or elsewhere in the vehicle. In addition, recorder and/or note taker **8270** may be used as an answering machine for use with a digital phone, which is either incorporated into module **8212**, interior rearview mirror assembly **8210**, or elsewhere in the vehicle. Thus, digital message recorder and/or note taker **8270** can play back the message or notes as the occupant of the vehicle so chooses or as controlled by a setting in the digital message recorder or not taker. In addition, digital message recorder or digital note taker **8270** may be adapted to communicate with a dockable cellular phone, such as described in U.S. patent application entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, Ser. No. 09/449,121, filed Nov. 24, 1999, now U.S. Pat. No. 6,428,172, and U.S. patent application entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, Ser. No. 09/585,379, filed Jun. 1, 2000, which are herein incorporated in their entireties by reference herein. Alternately, digital message recorder or digital note taker **8270** (or any other accessory in module **8212**) may communicate with (and/or serve as a message recorder for) a phone remote from module **8212** or interior rearview mirror assembly **8210**, such as a

26

phone in a pocket of a vehicle occupant, a bag, or a compartment, so that messages may be downloaded from the remote cellular phone to the digital message recorder or digital note taker using, for example, a short range communication protocol, such as BLUETOOTH, as previously described. In this manner, the occupant of the vehicle may choose to screen incoming calls on their phone.

Also, as an alternate to having an accessory module (such as described above and herein) that attaches to or adjacent to a windshield-mounted (or header-mounted) interior mirror assembly, an accessory module can be incorporated as a portion of a header console or header/headliner portion of the vehicle such that the accessory module (that can house the accessories including displays, antennae and controllers such as disclosed herein) can be an extension of the header that extends down from the header to the region, for example, where an interior mirror assembly typically attaches to a windshield. Thus, and as illustrated in FIG. 16A, an accessory module/mirror system **8400** of the present invention includes an interior rearview mirror assembly **8410** and a header console **8412**, which mounts to the headliner H of a roof portion of a vehicle. As will be more fully described below header console **8412** includes an extension **8413** which extends down from headliner H along the inner surface of windshield W of the vehicle and extends behind mirror assembly **8410** to provide ample space and mounting surfaces for one or more vehicle accessories, such as described above. Header console **8412** is particularly suitable for mounting vehicle systems, such as the tire pressure monitoring system described above, user actuatable devices, such as user actuatable buttons, displays, such as video displays, so that the user actuatable devices and displays are at a location accessible or viewable by one or more occupants of the vehicle.

As shown in FIG. 16A, a lower portion **8413a** of extension **8413** of header console **8412**, which extends downwardly behind the upper portion of windshield W (such portion of windshield W which typically includes a shadeband element as known in the art), includes a mirror mounting button **8436** on which mirror assembly **8410** detachably attaches to header console **8412**. Optionally, the downwardly extending portion of header/console **8412** may be mounted to the inner surface of windshield W, such as by an adhesive or may be releasably, mechanically attached such as by being received by and/or supported by one or more attaching members adhered to the inner surface of the windshield, such as by attachment members, including rails, channels, or the like. Or, the downwardly extending portion of header/console **8412** may be spaced or set-off from the inner surface. Or, the downwardly extending portion of header/console **8412** may contact or rest on inner surface of the windshield.

Desirably, wiring and/or cables which supply power and/or signals to components in interior rearview mirror assembly **8410**, including components in casing **8414**, such as reflective element **8416**, may be carried by header console **8412** and may pass through extension **8413** so that the wires and/or cables are protected from damage and further are hidden from view for aesthetic reasons.

In the illustrated embodiment, interior rearview mirror **8410** includes a casing **8414**, a reflective element **8416** which is supported in casing **8414**, and a support **8430**. Reflective element **8416** preferably comprises a variable reflectance reflective element, such as a prismatic or an electrochromic (EC) reflective element. Support **8430** comprises a dual-ball mount type support of the type described in reference to the previous embodiments, which provides for multi-axis repositioning of casing **8414** and, therefore, reflective element **8416** or may comprise a single-ball support, as such are

known in the rearview mirror art. Support **8430** includes a channel shaped mirror mount **8440** for releasably engaging mounting button **8436** to form a break-away connection between mirror assembly **8410** and header console **8412**.

As noted above, header console **8412** may support a plurality of vehicle accessories, including for example an antenna **8422**, including a global positioning system (GPS) antenna; a rain sensor, including a contacting and a non-contacting rain sensor; one or more cameras; lights; components of or an entire electronic toll collection (ETC) assembly; loud speakers and/or microphones, including for example a microphone array, such as for a sound system (such as disclosed in co-assigned U.S. patent application Ser. Nos. 09/466,010 filed Dec. 17, 1999, now U.S. Pat. No. 6,420,975; 09/396,179 filed Sep. 14, 1999, now U.S. Pat. No. 6,278,377; 09/382,720 filed Aug. 25, 1999, now U.S. Pat. No. 6,243,003; 09/449,121 filed Nov. 24, 1999, now U.S. Pat. No. 6,428,172; 09/433,467 filed Nov. 4, 1999, now U.S. Pat. Nos. 6,326,613; and 09/448,700 filed Nov. 24, 1999, now U.S. Pat. No. 6,329,925, the entire disclosures of all of which are hereby incorporated by reference herein); components of or an entire cellular phone system; components of or an entire telematic system, including a transceiver, an antenna, one or more user actuable devices, such as user actuable buttons; pull down or flip displays, including video displays, such as described and reference previously; universal garage door opener systems, such as HOMELINK; digital sound processing systems; a trip computer, seat occupancy detector; air bag actuation status display; sensors for compass headings or temperature; a vehicle tire pressure monitoring controller **8423** (that preferably includes an RF receiving antenna, a microprocessor and all the circuitry, user input controls/buttons and other controls needed to receive and process wireless signals broadcast from the various tire pressure sensors located in the tire on the wheels of the vehicle), a display element **8445** for display information relating to, for example the tire pressure monitoring system, other vehicle status, including coolant temperature, fuel levels, or the like, and/or external environmental status or information, such as outside temperature, compass headings or the like. In addition, accessory module/mirror system **8400** may include a second display element **8446** for displaying other information, such as email messages, or for displaying images such as images relating to interior surveillance systems, rearvision aid systems, or teleconferencing images or the like.

As best seen in FIG. 16A, displays **8445** and **8446** are positioned above and forwardly of mirror casing **8414** whereby the displays do not interfere with or distract the driver and yet are accessible for easy viewing and are accessible for touching in the case of touch activated display screens. Optionally, at least one of the displays screens is positioned high enough within the vehicle cabin so that the images, such as tire pressure indicators, may be viewable from outside the vehicle, including at the rear of the vehicle so that a person inflating a rear tire could view the indications provided by the tire pressure indicators. In addition, display element **8445** may be provided in a separate housing or module **8447** which can be removed for replacement, repair or upgrade.

In this manner, accessory module/mirror system **8400** can be removed as an assembly for repair, replacement, or upgrade with features removed or added to either the mirror assembly **8410** or header console **8412** to thereby customize the accessory module/mirror system **8400** to suit the particular needs of the vehicle customer. Furthermore, by extending the header console downwardly and forward of the mirror

assembly, significantly increased storage spaced is realized at the mirror mounting location but outside of casing **8414**.

Referring to FIG. 16B, another embodiment **8500** of an accessory module/mirror system of the present invention is illustrated. Accessory module/mirror system **8500** includes an interior rearview mirror assembly **8510** and a header console **8512**, which mounts to the headliner H of a roof portion of a vehicle, similar to the previous embodiment.

As will be more fully described below header console **8512** includes an extension **8513** which extends down from headliner H along the inner surface of windshield W of the vehicle and extends behind mirror assembly **8510** to provide ample space and mounting surfaces for one or more vehicle accessories, such as described in reference to the previous embodiments and the referenced copending applications. Header console **8512** is particularly suitable for mounting vehicle systems, such as the tire pressure monitoring system described above, user actuable devices, such as user actuable buttons, displays, such as video displays, so that the user actuable devices and displays are at a location accessible or viewable by one or more occupants of the vehicle similar to the previous embodiment.

As best understood from FIG. 16B, extension **8513** of header console **8512** extends downwardly behind the upper portion of windshield W (such portion of windshield W which typically includes a shadeband element as known in the art) and includes a forked portion **8513a**, such as an inverted V-shaped or U-shaped portion, which straddles a mirror mounting button **8536** that is mounted to windshield W. Optionally, the downwardly extending portion of header/header console **8512** may be mounted to the inner surface of windshield W, such as by an adhesive or may be releasably, mechanically attached such as by being received by and/or supported by one or more attaching members adhered to the inner surface of the windshield, such as by attachment members, including rails, channels, or the like. Or, the downwardly extending portion of header/header console **8512** may be spaced or set-off from the inner surface. Or, the downwardly extending portion of header/header console **8512** may contact or rest on inner surface of the windshield. Similarly, wiring and/or cables which supply power and/or signals to components in interior rearview mirror assembly **8510** may pass through extension **8513** so that the wires and/or cables are protected from damage and further are hidden from view for aesthetic reasons.

Mirror mounting button **8536** provides a mount for mirror assembly **8510**, which detachably attaches to mounting button **8536** by a channel shaped mirror mount **8540**. In the illustrated embodiment, interior rearview mirror **8510** includes a casing **8514**, a reflective element **8516** which is supported in casing **8514**, and a support **8530**. Reflective element **8516** preferably comprises a variable reflectance reflective element, such as a prismatic or an electrochromic (EC) reflective element. Support **8530** comprises a dual-ball mount type support of the type described in reference to the previous embodiments, which provides for multi-axis repositioning of casing **8514** and, therefore, reflective element **8516** or may comprise a single-ball support, as such are known in the rearview mirror art. Support **8530** includes mirror mount **8540** for releasably engaging mounting button **8536** to thereby form a break-away connection between mirror assembly **8510** and windshield W.

As noted above, header console **8512** may support a plurality of vehicle accessories, including for example an antenna **8522**, including a global positioning system (GPS) antenna; a rain sensor, including a contacting and a non-contacting rain sensor; one or more cameras; lights; compo-

nents of or an entire electronic toll collection (ETC) assembly; loud speakers and/or microphones, including for example a microphone array, such as for a sound system (such as disclosed in co-assigned U.S. patent application Ser. Nos. 09/466,010 filed Dec. 17, 1999, now U.S. Pat. No. 6,326,613; 09/396,179 filed Sep. 14, 1999, now U.S. Pat. No. 6,278,377; 09/382,720 filed Aug. 25, 1999, now U.S. Pat. No. 6,243,003; 09/449,121 filed Nov. 24, 1999, now U.S. Pat. No. 6,428,172; 09/433,467 filed Nov. 4, 1999, now U.S. Pat. Nos. 6,326,613; and 09/448,700 filed Nov. 24, 1999, now U.S. Pat. No. 6,329,925, the entire disclosures of all of which are hereby incorporated by reference herein); components of or an entire cellular phone system; components of or an entire telematic system, including a transceiver, an antenna, one or more user actuatable devices, such as user actuatable buttons; pull down or flip displays, including video displays, such as described and reference previously; universal garage door opener systems, such as HOMELINK; digital sound processing systems; a trip computer, seat occupancy detector; air bag actuation status display; sensors for compass headings or temperature; a vehicle tire pressure monitoring controller **8523** (that preferably includes an RF receiving antenna, a microprocessor and all the circuitry, user input controls/buttons and other controls needed to receive and process wireless signals broadcast from the various tire pressure sensors located in the tire on the wheels of the vehicle), a display element **8545** for display information relating to, for example the tire pressure monitoring system, other vehicle status, including coolant temperature, fuel levels, or the like, and external environmental status or information, such as outside temperature, compass headings or for displaying other information, such as email messages, or for displaying images such as images relating to interior surveillance systems, rearvision aid systems, or teleconferencing images or the like.

As best seen in FIG. **16B**, display **8545** is positioned above and forwardly of mirror casing **8514** whereby display **8545** does not interfere with or distract the driver and yet is accessible for easy viewing and, further, is optionally accessible for touching in the case of a touch activated display screen. In addition, display element **8545** optionally is positioned high enough within the vehicle cabin so that the images, such as tire pressure indicators, may be viewable from outside the vehicle, including at the rear of the vehicle so that a person inflating a rear tire could view the indications provided by the tire pressure indicators.

As noted in reference to the previous embodiment, by extending the header console downwardly and forward of the mirror assembly, significantly increased storage space is realized at the mirror mounting location but outside of casing **8514**. In a similar manner, the mirror assembly **8510** and/or header console **8512** may be removed for upgrade or replacement of components within either the mirror assembly or the console to thereby customize the accessory module/mirror system **8500** to suit the particular needs of the vehicle customer.

It can be appreciated that the mirror assemblies of the previous embodiments either connect to or through the header console. Optionally, one or more electrical/electronic devices or functions housed or provided in the interior rearview mirror assemblies may communicate with, such as by wireless communication, including RF communication, or electrically couple, such as by wires and/or cables, to control circuitry either wholly or partially housed in the header console. For example, the interior rearview mirror assemblies may include a sensor, such as a photo sensor, which communicates with or electrically couples to sensor circuitry located at least partially in the respective header console. For an example of a

suitable communication system that may be incorporated in the present invention reference is made to U.S. Pat. No. 6,099,131, which is commonly assigned to Donnelly Corporation of Holland, Mich., which is incorporated by reference in its entirety herein.

FIG. **17** shows a video mirror system **6100** comprising an interior mirror assembly **6135** that is attached by mirror mount **6120** to vehicle windshield **6110**. Video mirror system **6100** includes a controller **6123** (preferably including an antenna, a microprocessor, user input controls, electronic memory and allied circuitry) that is a component of a tire pressure monitoring system and/or a tire pressure display system. Pod **6190** removably attaches to mirror mount **6120** via pod attachment element **6193**. Pod **6190** includes a video controller board **6194** and a video display driver board **6192**. Pod **6190** connect to video display housing **6170** via cable **6196** which carries video and electronic signals to the video screen housed in video display housing **6170**. Video display attachment element **6160** removably attaches to ball joint **6150** of mirror support arm **6130**. Video display housing is movable about joint **6162** to move in the direction indicated by arrow **6171** to stow under mirror assembly **6135** when view of the screen in video display housing **6170** is not desired. Video display housing is also movable about joint **6162** to move in the direction indicated by arrow **6173** to allow rotation of video display housing **6170** in order to adjust the viewing angle of the video screen in housing **6170**. Buttons **6180** allow user-access to the control functions and features of the video mirror system **6100**. By placing the electronic boards in pod **6190**, weight in housing **6170** is beneficially decreased, leading to reduced effect on mirror reflective element image vibration.

FIG. **18** shows a video mirror system **6200** (that includes a controller **6223** (preferably including an antenna, a microprocessor, user input controls, electronic memory and allied circuitry) that is a component of a tire pressure monitoring system and/or a tire pressure display system) including a video display housing **6270** that is attached via pivot joint **6262** to video pod **6290** that in turn attaches (removably) via video attachment element **6293** to the lower ball-joint of mirror support arm **6230** of interior mirror assembly **6235**. As shown by arrow **6271**, video display housing **6270** can move about pivot joint **6262** to stow below video pod **6290** (as in **6270'**). Video pod **6290** contains various electronic boards **6291**, **6292**, that can include a variety of electronic features and accessories, as described above. Buttons **6280** allow user-access to the control functions and features of the video mirror system **6200**.

FIG. **19** shows a video mirror system **6300** and a video display assembly **6370** (that includes a controller (preferably including an antenna, a microprocessor, user input controls, electronic memory and allied circuitry) that is a component of a tire pressure monitoring system and/or a tire pressure display system) that includes a video screen **6372** in video display housing **6374** and user-access controls **6380**. Video display housing **6374** rotates and articulates about video housing support arm **6390**. When not desired for viewing, video display housing **6374** can move to stow to the rear and below bezel **6338** of interior rearview mirror assembly **6335**.

FIGS. **20A**, **20B**, **21A**, **21B**, **22A**, and **22B** show various views of a video mirror system that includes a controller preferably including an antenna, a microprocessor, user input controls, electronic memory and allied circuitry) that is a component of a tire pressure monitoring system and/or a tire pressure display system. As best seen in FIG. **20B**, a detachable video display attachment mount is provided that snaps onto the lower ball-joint/mirror mount of the interior mirror

assembly (as best seen in FIG. 20A). An example of a suitable video attachment mount can be found in U.S. Pat. No. 5,576,687, to Rodney K. Blank et al., entitled VEHICLE INFORMATION DISPLAY, issued Nov. 19, 1996, the entire disclosure of which is hereby incorporated by reference herein. A preferred attachment mount to attach the video display assembly to the interior mirror assembly includes a coupler for engaging the mirror mount that supports the interior mirror assembly on a windshield mirror button. The coupler of the mount of the video display assembly includes a tab at one end for catching the interior mirror mount and a clip at another end to engage a portion of the interior mirror assembly. The coupler of the video display assembly also preferably includes a shafted fastener received in the interior mirror mount and/or a sliding fastener engaging a cooperating element of the mirror mount and/or a shafted fastener received in the mirror mount. Preferably, the coupler of the video display assembly includes an attachment member for snapping onto the interior mirror assembly (preferably at the interior mirror mount). As can best be seen in FIGS. 21A and 21B, the video display housing can rotate about a T-joint to stow generally horizontally behind the interior mirror housing when video screen viewing is not desired (FIG. 21A), but can flip down to a generally vertical plane when desired to be viewed (see FIG. 21B). Also, as seen in FIGS. 22A and 22B, the video display housing can rotate about its attachment joint to allow the viewing angle of the video screen to be positioned to suit the user's needs.

Use of a flip-down display assembly (and preferably a flip down or stowable video display assembly) to house a component of a tire pressure monitoring system and/or a tire pressure display system (such as its controller including antenna, microprocessor, user-input controls, electronic memory and allied circuitry) or to display an information output of a tire pressure monitoring system and/or a tire pressure display system has several advantages. For example, use of a video display facilitates a detailed and consumer-friendly display of all four tire pressures simultaneously on a video representation of the vehicle. Also, the video display of, for example, a flip-down video display assembly (that attaches to, for example, the mount of an interior mirror assembly; an example of a suitable video display assembly attachment mount can be found in U.S. Pat. No. 5,576,687, to Rodney K. Blank et al., entitled VEHICLE INFORMATION DISPLAY, issued Nov. 19, 1996, the entire disclosure of which is hereby incorporated by reference herein; and a preferred attachment mount to attach the video display assembly to the interior mirror assembly includes a coupler for engaging the mirror mount that supports the interior mirror assembly on a windshield mirror button or an assembly that attaches local to or at the attachment point in the vehicle where the interior mirror attaches (such as is described in U.S. Pat. No. 4,930,742, entitled REARVIEW MIRROR AND ACCESSORY MOUNT FOR VEHICLES, to Kenneth Schofield et al., issued Jun. 5, 1990, the entire disclosure of which is hereby incorporated by reference herein) can, for example, display the output of an interior-cabin monitoring camera, such as a baby-view camera, or of an external viewing camera, such as a forward viewing camera or rearward viewing camera such as a forward park-aid camera or a reverse-aid camera (such camera/display systems as disclosed in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, Ser. No. 60/243,986, filed Oct. 27, 2000, in pending U.S. provisional application entitled VIDEO MIRROR SYSTEMS, Ser. No. 60/238,483, filed Oct. 6, 2000, and in U.S. patent application Ser. No. 09/466,010, filed Dec. 17, 1999,

by DeLine et al., entitled INTERIOR REARVIEW MIRROR SOUND PROCESSING SYSTEM, now U.S. Pat. No. 6,420,975, the entire disclosures of which are hereby incorporated by reference herein), and with the tire pressure information generated by the tire pressure display/monitoring system controller (and preferably with the tire pressure display/monitoring system controller included in the flip-down display assembly, including the antenna that receives wireless broadcasts, typically RF signals, from the tire sensors in the individual wheels on the vehicle, as well as any microprocessor, user-input controls/buttons, electronic memory and allied circuitry associated with the controller) displayed as an alternate to other images displayed on the display screen and/or superimposed upon any display being displayed (or as a "picture in a picture") by the display screen. For example, a flip-down video screen may be displaying a view of a baby in a rear-seat child seat and/or be displaying a GPS data display that guides the driver with regard to direction/local geography. When requested by the driver (such as by voice command or by actuation of a user-input control such as a button or touch screen) or when the tire pressure display/monitoring system detects that tire pressure in a particular tire is below or above a recommended level for that tire on that vehicle, then a display of tire pressure (for example, a display that indicates that the rear passenger-side tire pressure is at 26 psi and that the correct tire pressure should be 35 psi, thus alerting the driver to make a tire pressure adjustment at a convenient service station) is displayed at the flip-down video display assembly, either separate from or superimposed upon whatever that display screen was currently displaying. Note that the flip-down video display assembly (or any other display assembly/accessory assembly/interior rear view mirror assembly/exterior side view mirror assembly used in conjunction with a tire pressure display/monitoring system, such as described herein), can include a range of accessories, including an antenna (such as an RF antenna or a microwave antenna) and/or receiver circuitry (and any allied circuitry) associated with receipt of wireless communication from, for example, a GPS satellite or a telematics service provider or a satellite provider of information or entertainment to the vehicle (such as from a satellite news, information and entertainment provider such as Sirius Inc., that provides, for example, digital broadcast signals via satellite of radio stations, or from a provider that broadcasts digital television signals that are received, and processed in the vehicle, and preferably with at least some components, such as the antenna and receiver circuitry located at, on, in or adjacent to the interior rearview mirror assembly and/or at, on or adjacent to any associated video display assembly).

A further embodiment of a video mirror system 6700 that included in a tire pressure monitoring system and/or a tire pressure display system is shown in FIG. 23. Video mirror system 6700 includes an interior rearview mirror assembly 6710 and a video display assembly 6712, which incorporates movable support 6732 that includes support arm 6738 and pivot joints 6732a, 6732b. Similar to the previous embodiments, interior rearview mirror assembly 6710 includes a mirror housing 6714 and a reflective element 6716 (preferably, an electrochromic reflective element) and, further, a mirror housing support 6729. Mirror housing support 6729 includes a mirror mount 6726 and a support arm 6724. Though illustrated with a dual ball mount arrangement, support 6729 may include a fixed support arm or may include a single ball mount arrangement to permit either pivoting of support arm 6724 about mirror mount 6726 or pivoting between support arm 6724 and housing 6714, as will be understood by those skilled in the art.

Video display support **6732** comprises an elongate support arm **6738** with an upper fixed portion **6751** which is adapted to detachably mount to windshield mirror mounting button **6720**. Upper fixed portion **6751** includes a mirror mounting button **6736**, on which mirror mount **6726** of mirror assembly **6710** is detachably mounted to provide a detachable, and preferably break-away connection, for interior rearview mirror assembly **6710**. The lower portion of support arm **6738** includes a pivot joint **6732b** to video screen housing **6730** of video display assembly **6712**. Pivot joints **6732a**, **6732b** allow a viewer of video screen **6731** to adjust its viewing angle to suit the need/preference of the driver or front-seat passenger of the vehicle. Similar to the previous embodiments, video display assembly **6712** includes a video screen **6731** (that, preferably, is coated on its outer surface with an antiglare means, such as described above, and most preferably an interference-stack anti-glare multi-coating stack of thin films, typically metal oxides, forming an anti-glare multilayer stack), which is housed in a housing **6730**, and a carrier **6742**, such as a printed circuit which supports electronics for various functions preferably within assembly **6712**, including video screen **6731**. Further, video display assembly **6712** preferably includes at least one control button **6744** which may be used, for example, to actuate screen **6731** (or change a contrast/color tint, display intensity, or the like) and/or other functions provided by the circuit board on carrier **6742**.

Upper fixed portion **6751** of video display assembly **6712** includes a housing portion that includes a variety of vehicle accessories and controls including tire pressure display controller **6773**. For example, a GPS navigational system **6754**, including a GPS antenna, is included in housing **6751**. Also included is another accessory **6756** that may, for example, comprise a trainable garage door opener such as the HomeLink® GDO system available from JCI of Holland, Mich. and/or may comprise a cellular phone system including a complete telecommunication system/antenna/transceiver and/or a telematic system including antenna and transceiver and/or an automatic toll booth/remote transaction transceiver system and/or a compass direction system including a compass sensor, such as is described above and/or any of the vehicle accessories and functions described above. Upper fixed portion **6751** also includes a microphone system **6750** (preferably a multi-microphone array including a digital sound processing system included in housing **6751**) suitable for use in voice command interactions, cellular phone interactions, hands-free phone operations, telematic communications and the like, and a loudspeaker **6752** suitable to, for example, audibly convey to the driver navigational directions/instructions from the GPS system **6754** and/or audibly read out e-mail messages received through an INTERNET connection via a telematic link, and the like, or can function as a component of a speaker phone system included in video display assembly **6712**. A rain sensor **6758** is included in or at upper portion **6751**. Cell phone and other function user access control interfaces/buttons **6746** are included in the forward facing upper portion of video display housing **6730**. The lower portion of video display housing **6730** includes an information display **6748** that includes a non-video information display element **6749** that is visible to the driver and/or occupant of the vehicle. Information display element **6749** can be any one of the display types described previously (such as a vacuum fluorescent display, an LED display, an electroluminescent display, or a liquid crystal display), and preferably is a multi-pixel display capable of being reconfigured, and capable of displaying scrolling text including alphanumeric text in various fonts and languages. For example, display element **6749** can display, in response to GPS system **6754**,

the name of the next street or junction or highway entry/exit ramp being approached by the vehicle equipped with video mirror system **6700**. Display element **6749** can display an information output of a tire pressure monitoring system and/or a tire pressure display system, and a component (such as the controller) of a tire pressure monitoring system and/or a tire pressure display system can be incorporated into video mirror system **6700**.

As seen in video mirror system **6700**, a stand-alone GPS and/or cellular phone and/or telematic system, including voice operated and voice recognizing systems, and/or stand-alone tire pressure display/monitoring systems, can be provided in an assembly that attaches local to or at the attachment point in the vehicle where the interior mirror attaches (such as is described in U.S. Pat. No. 4,930,742, entitled REARVIEW MIRROR AND ACCESSORY MOUNT FOR VEHICLES, to Kenneth Schofield et al., issued Jun. 5, 1990, the entire disclosure of which is hereby incorporated by reference herein) and in a manner that use can be made of the microphones and/or control buttons and/or other accessories in the video display assembly without effecting the position of the mirror housing of the interior mirror assembly (and thereby the field of view of its reflective element). Thus, for example, a driver can dial a phone number or actuate a telematic control button or actuate a control of a tire pressure display/monitoring system in video mirror system **6700** without effecting the position of the mirror housing or otherwise perturbing the interior mirror assembly (the interior mirror assembly being separate from and independent of the video display assembly). Also, the weight of the accessories, controls, microphones, antennae, circuitry, and the like in the video display assembly is supported by the windshield mounting button/header mounting plate (or alternately, by a separate windshield attachment member/header attachment member as previously described) and not by the interior mirror assembly so that vibration of the mirror reflective element is unaffected. Also, by mounting the video display assembly as in video mirror system **6700**, provision of a stand-alone telematic system and/or telecommunication/phone system (including a video phone system) and/or a GPS navigational system as an aftermarket/dealership option/OEM option item is facilitated. Note that variants of video mirror system **6700** are possible, including some where the video display and its support are dispensed with and display element **6749** is located at fixed portion **6751** (such as part of a lobe or gondola visible below the interior mirror assembly) and is used to convey information to the driver, in conjunction with audio instructions played via loudspeaker **6752** (or alternately, played over another loudspeaker in the vehicle cabin).

Also, the video display in any of the video mirror applications of the present invention, such as video mirror system **6700**, can function as the display screen for a portable computer device, a portable cellular phone, and/or a portable personal digital assistant device (PDA) such as a PalmPilot® or other personal digital assistant. When serving as the display screen of a PDA, the PDA/in-vehicle display screen can optionally operate in combination with a cellular phone or as a stand-alone device. Also, any of the video display screens of the present invention, such as video display screen **6731**, can serve multiple purposes such as a video screen for an on-board vehicular camera and/or as the video monitor screen for a portable computing/PDA/cellular phone/telecommunication device, an added on as or time. The video display system of the present invention can itself function as an in-vehicle PDA and/or cellular phone, in addition to other functions as described above. Portable devices such as PDAs, cellular phones, and palm/notebook/laptop portable computers can

35

connect to/communicate with the video mirror systems of the present invention by direct wired connection/docking or by wireless communication such as described in U.S. patent application Ser. No. 09/561,023, filed Apr. 28, 2000, entitled VEHICLE-BASED NAVIGATION SYSTEM WITH SMART MAP FILTERING, PORTABLE UNIT HOME-BASE REGISTRATION AND MULTIPLE NAVIGATION SYSTEM PREFERENTIAL USE, to Eugenie V. Uhlmann et al., now U.S. Pat. No. 6,553,308; U.S. provisional Pat. application Ser. No. 60/131,593, filed Apr. 29, 1999, entitled VEHICLE-BASED NAVIGATION SYSTEM WITH SMART MAP FILTERING, PORTABLE UNIT HOME-BASE REGISTRATION AND MULTIPLE NAVIGATION SYSTEM PREFERENTIAL USE, to Eugenie V. Uhlmann et al.; and U.S. provisional Pat. application Ser. No. 60/199,676, filed Apr. 21, 2000, entitled VEHICLE MIRROR ASSEMBLY COMMUNICATING WIRELESSLY WITH VEHICLE ACCESSORIES AND OCCUPANTS, the entire disclosures of which are hereby incorporated by reference herein. Preferably, the video mirror systems of the present invention, such as video mirror system **6700**, is equipped with a mobile device communication port (such as an IrDA-port) that transmits/receives data via wireless infrared communication. For example, any of the video display housings and/or any of the video attachment members/mounts and/or any of the interior mirror assemblies can be equipped with a mobile device communication port (such as an IrDA-port) that transmits/receives data via wireless infrared communication. Also, any of the video display assemblies, including any of the video display screens or video display housings can be adapted to receive data input by touch such as by a human finger or a stylus such as via a touch screen, and such as is disclosed in U.S. provisional Pat. application Ser. No. 60/192,721, filed Mar. 27, 2000, entitled INTERACTIVE AUTOMOTIVE REARVISION SYSTEM, to Niall R. Lynam et al, the entire disclosure of which is hereby incorporated by reference herein. The flip down/positionable video display assemblies of the present invention are preferred locations for a wireless telecommunications receiver, transmitter or communications node, including such used as part of a GPS navigational system. Also, the front surface of the stowed flip-down video display assemblies of the present invention can optionally be used as an information display location itself or as a location for a transmitter or receiver for the like of a GPS system, an interactive system, and a telematic system. Also, since it is perceived unsafe, and in some jurisdictions illegal, to transport children in a 5th wheel towed vehicle unless there is aural communication with the towing vehicle, placement of microphones and cameras in the towed vehicle, in combination with the video mirror systems and other displays of the present invention, can allow full communication with any towed vehicle, both visual and oral/aural, an aspect of the present invention that is of importance for the RV industry in particular. Note also a reverse-aid camera that views immediately rearward of the vehicle is useful in guiding a driver when maneuvering the vehicle to attach a tow bar receiving element on the vehicle (typically, a ball element) to a "tow ball" receiving socket on a tow bar of a trailer or the like. By "seeing" the ball element on a video screen such as any of those described herein, the driver can position the vehicle to engage the hitch-joining element of the trailer to be towed. Note also that any of the interior mirror assemblies or video display assemblies can include a camera-based "black box" recorder of the forward driving scene and/or the cabin of the vehicle. Such a "black box" recorder can, for example, be located in the cavity formed by the mirror housing of the interior rearview mirror assembly, or can be mounted to the

36

mount that attached the mirror assembly to a windshield or header portion of the interior cabin of the vehicle. Note that, for economy, a preferable audible tire pressure indicator device comprises the horn of the vehicle that is normally present (such as in an engine compartment of the vehicle) to be sounded when the driver needs to alert others of his/her presence. Note also that, optionally, any of the video display assemblies and interior rearview mirror assemblies disclosed herein can include an electronic toll collection transceiver (located such as in an interior mirror housing or in an attachment to an interior mirror mount or in a display assembly).

A further embodiment of a video mirror system **6800** that includes components of and/or displays information generated by a tire pressure monitoring system and/or a tire pressure display system is shown in FIG. **24**. Video mirror system **6800** includes an interior rearview mirror assembly **6810**. Similar to the previous embodiments, interior rearview mirror assembly **6810** includes a mirror housing **6814** and a reflective element **6816** (preferably, an electrochromic reflective element) and, further, a mirror housing support **6824**. Mirror housing **6814** further includes a video screen **6831** and control circuitry **6846**. The mirror mount **6826** mounts to a mirror mounting member or button **6836**. Mirror button **6836** is part of the attachment portion **6851** of accessory assembly **6812**. Attachment portion **6851** of accessory assembly **6812** is adapted to detachably mount to windshield mirror mounting button **6820**. As described above, attachment portion **6851** includes a mirror mounting button **6836**, on which mirror mount **6826** of mirror assembly **6810** is detachably mounted to provide a detachable, and preferably break-away connection, for interior rearview mirror assembly **6810**. Note that windshield mounting button **6820** is generally co-axial with mirror mounting button **6836** of attachment member or portion **6851**. Accessory assembly **6812** preferably includes at least one control button **6876** which may be used, for example, to actuate screen **6831** (or change a contrast/color tint, display intensity, or the like) and/or other functions provided by circuit board **6846**.

Attachment portion **6851** of accessory assembly **6812** includes a housing portion **6859** that includes a variety of vehicle accessories and controls, such as the controller and/or display for a tire pressure monitoring system and/or a tire pressure display system. For example, a GPS navigational system **6854**, preferably including a GPS antenna, is included in housing **6859**. Also included are other accessories **6856**, **6855**, **6858** that may, for example, comprise a trainable garage door opener such as the HomeLink® GDO system available from JCI of Holland, Mich. and/or may comprise a cellular phone system including the complete telecommunication system/antenna/transceiver and/or a telematic system including antenna and transceiver and/or an automatic toll booth/remote transaction transceiver system and/or a compass direction system including a compass sensor, and/or a complete tire pressure display/monitoring controller, such as is described above and/or any of the vehicle accessories and functions described above. Accessory housing **6859** also includes a microphone system **6850** (preferably a multi-microphone array including a digital sound processing system included in housing **6859**) suitable for use in voice command interactions, cellular phone interactions, telematic communications and the like, and a loudspeaker **6852** suitable to, for example, audibly convey to the driver navigational directions/instructions from the GPS system **6854** and/or audibly read out e-mail messages received through an INTERNET connection via a telematic link, and the like. A rain sensor **6858** is included in or at attachment portion **6851**. Cell phone and other function user access control interfaces/buttons **6874**,

6876 are included in the forward facing (towards the driver/interior cabin occupant) of accessory housing **6859**. Accessory housing **6859** includes an information display **6848** that includes a non-video information display element **6849** that is visible to the driver and/or occupant of the vehicle. Information display element **6849** can be any one of the display types described previously (such as a vacuum fluorescent display, an LED display, an electroluminescent display, or a liquid crystal display), and preferably is a multi-pixel display capable of being reconfigured, and capable of displaying scrolling text including alphanumeric text in various fonts and languages. For example, display element **6849** can display, in response to GPS system **6854**, the name of the next street or junction or highway entry/exit ramp being approached by the vehicle equipped with video mirror system **6800**. Accessory module **6812** is also equipped with a video camera **6843** for viewing a portion of the interior cabin (such as, for example, viewing a front passenger seat so as to function as a seat occupancy detector) and/or for viewing an occupant of the vehicle (such as a driver's head/face portion). Optionally, near-IR and/or visible light sources, as described previously, can be positioned at housing **6859** so as to illuminate the target area being viewed by camera **6843**. A forward facing camera **6821** is also provided at or within accessory module **6812** with a field of view through the front windshield (for automatic headlamp control and/or collision avoidance and/or windshield fogging detection and/or rain sensing and/or smart headlamp control). User actuatable controls **6875** are provided on the front portion of accessory housing **6859** to allow user actuation of a variety of vehicle functions and/or accessories (such as actuation of or color/tint control of video screen **6831**). A photo sensor **6811** (such as a photo diode, or a photo transistor, or a photo resistor) is provided to allow measurement of cabin ambient lighting for a variety of purposes, such as automatic intensity control of the video image displayed on video screen **6831**. An instrument panel/floor console/gear shift console illuminating light source **6801** (preferably an LED) is provided at the lower surface of accessory housing **6859**.

As seen in video mirror system **6800**, a stand-alone GPS and/or cellular phone and/or telematic system, including voice operated and voice recognizing systems, as well as other vehicle functions such as a keyless entry receiver, a map/reading light, an intrusion detector, a seat occupancy detector, a trainable/universal garage door opener, a rain sensor, a compass sensor, a headlamp controller, a twilight sentinel, a tool transceiver, a remote transaction transceiver, a windshield fogging detector as well as any other vehicle accessory described above, can be provided in a module assembly that attaches local to or at the attachment point in the vehicle where the interior mirror attaches (such as is described in U.S. Pat. No. 4,930,742, entitled REARVIEW MIRROR AND ACCESSORY MOUNT FOR VEHICLES, to Kenneth Schofield et al., issued Jun. 5, 1990, the entire disclosure of which is hereby incorporated by reference herein) and in a manner that use can be made of the microphones and/or control buttons and/or other accessories in the accessory assembly without effecting the position of the mirror housing of the interior mirror assembly (and thereby the field of view of its reflective element), and preferably in a manner and at a location such that at least a portion, and preferably at least a substantial portion, of the accessory module is disposed behind the rear of the interior mirror housing of the interior rearview mirror assembly (and so in a region that minimizes obstruction of the driver's forward field of view through the front windshield). Thus, for example, a driver can dial a phone number or actuate a telematic control

button in video mirror system **6800** without effecting the position of the mirror housing or otherwise perturbing the interior mirror assembly (the interior mirror assembly being separate from and independent of the accessory assembly). Also, the weight of the accessories, controls, microphones, antennae, circuitry, and the like in the accessory assembly is supported by the windshield mounting button/header mounting plate (or alternately, by a separate windshield attachment member/header attachment member as previously described) and not by the interior mirror assembly so that vibration of the mirror reflective element is unaffected. Also, by mounting the accessory assembly as in video mirror system **6800**, provision of a stand-alone telematic system and/or telecommunication/phone system (including a video phone system) and/or a GPS navigational system as an aftermarket/dealership option/OEM option item is facilitated. Note that variants of video mirror system **6800** are possible, such as where the accessory assembly is provided with pivot joints, as previously described, in order to allow positioning at a position and/or viewing angle desirable to a driver and/or occupant. Thus, for example, accessory housing **6859** of accessory module assembly **6812** can be movable about accessory module attachment portion **6851** so that the position of accessory module housing **6859** can be adjusted (about at least one axis, preferably about at least two axes, more preferably, about at least three axes) to position the user access/control buttons, information display and the like at the accessory housing **6859** at a location and/or a viewing angle desired/preferred by an occupant of the vehicle such as a driver or front seat passenger. Also, optionally and preferably, accessory module housing **6859** can be stowed as previously described when viewing of its information display and/or access to its control inputs is not desired. Thus, accessory module **6812** can comprise a flip-down accessory housing **6859** that is articulatable left to right and up and down. Also, when a cellular phone and/or a telematic device and/or a PDA and/or personal computing device is docked in or included in the accessory assembly **6812**, accessory assembly **6812** can include a loudspeaker (as described above) and associated sound amplification circuitry so that accessory module assembly **6812** functions as a stand-alone in-vehicle sound system, thus providing, for example, a speaker-phone function. Also, a passenger side inflatable restraint indicator display that indicates the state of activation/deactivation of an air bag or similar inflatable occupant restraint in the vehicle cabin (such as is described in U.S. Pat. No. 6,087,953 to Jonathan E. DeLine et al., entitled REARVIEW MIRROR SUPPORT INCORPORATING VEHICLE INFORMATION DISPLAY, issued Jul. 11, 2000, the entire disclosure of which is hereby incorporated by reference herein) can be included in accessory assembly **6812** such as at information display **6848**. Also, accessory assembly **6812** can include various accessories and devices such as a seat occupancy detector (visible detector, ultrasound detector, radar detector, microwave detector, thermal detector (including a pyrodetector), infra red detector) and/or a keyless entry receiver and/or a cabin occupancy detector (such as a pyrodetector or an infra red detector or an ultrasound detector or an infra red detector) and/or a map light/reading light.

A further embodiment of a video mirror system **6800'** that includes components of (such as a controller that includes an antenna, a microprocessor, user-input controls, and/or allied electronic circuitry) and/or an information display of a tire pressure monitoring system and/or a tire pressure display system is shown in FIG. 24A. Video mirror system **6800'** is similar in features and content to video mirror system **6800** of FIG. 25, and comprises an interior mirror assembly **6810'** and an accessory module assembly **6812'**. Accessory module

attachment portion **6851'** of accessory module assembly **6812'** attaches to windshield-mounted attachment member **6820'** via a break-away mount that detaches when an impact at above a pre-determined impact force is experienced. Preferably, attachment member **6820'** consists of a mirror mounting button such as is commonly found on the inner surface of vehicular windshields of MY00 vehicles such as from Ford Motor Company, Toyota Motors, BMW, General Motors Corporation, Volkswagen, Mazda, Daimler Chrysler Corporation, Nissan, Renault, Volvo, Audi and the like. Also, preferably, the receiving portion of accessory module attachment portion **6851'** that attaches to windshield-mounted attachment member **6820'** is the same as would be found on the mounting portion of an interior rearview mirror assembly that would attach to the windshield mounting button on the windshield of that particular vehicle model. This has several advantages. By making the mounting-to-the-windshield-button portion of accessory module assembly **6812'** the same as that of the interior rearview mirror assembly that would normally attach to that particular type/construction of windshield-mounted mirror button, an automaker can supply an interior rearview mirror assembly and/or an accessory module assembly (with an interior mirror assembly mounting thereto) in accordance with the option(s) selected by a consumer ordering an individual vehicle. Also, dealership and after-market installation of an accessory module assembly is greatly facilitated. Only one mirror button need be mounted on the windshield (typically by the windshield manufacturer), although, optionally more than one attachment member can be adhered to the glass inner surface of the windshield, preferably with a substantially opaque black-out frit to mask the presence of such members when viewed from outside the vehicle through the front windshield. Also, because a mirror mount design is used for the attachment of accessory module attachment portion **6851'** to the windshield-mounted attachment member **6820'**, such attachment can be a break-away/detachable mounting that passes automaker and governmental safety standards and specifications for head impact, air-bag deployment, and the like, as well as being easy to install (such as at a vehicle assembly line) and/or to remove (such as during a service repair or the like) while maintaining a secure, reliable attachment during normal use for the vehicle lifetime. Also, a pivot joint **6803'** (such as a ball joint similar to that commonly used on interior mirror assembly support arms, as described above) is provided on accessory module attachment portion **6851'** so that should accessory module housing **6859'** be impacted, such as in an accident, the housing moves away from the impacting body (such as an occupant's head), thus reducing potential injury. Thus, accessory module **6812'** is adapted to meet automaker and regulatory head impact standards and specifications. Pivot joint **6803'** also allows positioning of accessory housing **6859'** to suit a driver's and/or occupant's needs, such as, for example, to position information display element **6849'** for view by the driver and/or controls **6876'**, **6874'**, **6875'** for ready access by the driver.

Also, and optionally, the accessory module assembly **6812** and the other flip-down, articulatable video display assemblies described above can be supported by an attachment member separate from the windshield-mounted or header-mounted mirror attachment button or plate. Examples of such separate mounting members are described above. A preferred adhesive to attach windshield mirror mounting buttons and/or windshield mounting attachment members for supporting an accessory module assembly or a video display assembly is a structural adhesive such as a modified epoxy structural bonding tape available from 3M of Minneapolis-St. Paul, Minn.

under the trade names SBT9214, SBT9263 and SBT9270. Alternately, a silicone adhesive, such the silicone adhesive available from Dow Corning of Midland, Mich. under the trade name SOTFEA can be used or a polyvinyl butyral adhesive such as available from Solutia is can be used. For heavier video mirror systems/accessory module assemblies, such as those weighing in excess of 500 g and particularly in excess of 750 g, use of a structural bonding tape such as described above to bond the attachment member (such as the windshield mirror button) to the inner surface of the windshield is preferred.

Also, the video display in any of the video mirror/video display assemblies above, such as video mirror system **6800**, can function as the display screen for a portable computer device, a portable cellular phone, and/or a portable personal digital assistant device (PDA) such as a PalmPilot® or other personal digital assistant. When serving as the display screen of a PDA, the PDA/in-vehicle display screen can optionally operate in combination with a cellular phone or as a stand-alone device. Also, any of the video display screens above, such as video display screen **6831**, can serve multiple purposes such as a video screen for an on-board vehicular camera and/or as the video monitor screen for a portable computing/PDA/cellular phone/telecommunication device in addition to, or as an alternative to, functioning as a display of a tire pressure display/monitoring system. For example, a removable telecommunication and/or computing accessory **6827** can be removably docked into docking station **6828** of accessory module **6812**. For example, and as described in disclosed in co-pending U.S. patent application entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, Ser. No. 09/585,679 filed by Barry W. Hutzel et al., on Jun. 1, 2000; which is incorporated herein in its entirety and in U.S. patent application Ser. No. 09/449,121, filed Nov. 24, 1999, entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, by Barry W. Hutzel et al. of Donnelly Corporation, now U.S. Pat. No. 6,428,172, the entire disclosure of which is hereby incorporated by reference herein, a cellular phone or a personal digital assistant device such as a PalmPilot® or a pager or a hand-held communication device and the like can be removably attached to accessory module **6812**. Also, note that, optionally, any of the display assemblies (such as the flip down displays described above) of the present invention and/or the camera assemblies of the present invention can be detached and used remote from the vehicle (or hand-held in the vehicle) as part of a portable video device, portable computer monitor, portable PDA or portable navigation device.

Thus, it is seen that the present invention provides a tire inflation monitoring system which provides a useful adjunct to the inflation of the vehicle tires. Because the visible tire inflation indicator assembly is positioned at or on an exterior vehicle portion such as a body side panel or on an exterior rearview mirror assembly where it is readily visible from the area surrounding each of the vehicle tires, it facilitates rapid adjustment of the inflation condition of the tires, thus increasing the safe operation of the vehicle. Also, preferably, the tire inflation indicator assembly is positioned on the exterior body portion at a location readily visible to a person crouching down at a wheel tire to inflate. The present invention includes provision of audible and/or tactile tire pressure indicators, as described above.

Furthermore, a tire inflation monitoring system, according to the invention, provides a useful indication to the vehicle user when the user is entering or leaving the vehicle that the tire pressure monitored by each of the tire inflation indicator assemblies is within a range of pressure as recommended by

the manufacturer or outside of that range, thus alerting the user to take action to bring the pressure of the tire within the range specified by the manufacturer preferably before operating the vehicle.

Other modifications may suggest themselves to the skilled artisan. For example, a single tire inflation indicator assembly **19** may include one color indicator for the rear tire on that side of the vehicle and a different color indicator for the front tire on that side of the vehicle. Alternatively, one tire inflation indicator assembly may be provided for indicating the tire inflation condition of the rear tire assembly, and a different tire inflation indicator assembly may indicate the direct inflation condition of the front tire on that side of the vehicle.

Also, communication between components of the tire inflation assistance monitoring system of this present invention can be by wire (such as a direct wire connection or via an optical fiber link) or via a bus system (such as a CAN or LIN system, as known in the arts) or wirelessly such as by IR or RF communication (such as using a local area RF broadcast network such as the BLUETOOTH protocol from Motorola of Schaumburg, Ill.), such as is disclosed in and co-assigned U.S. patent application Ser. No. 09/466,010, filed Dec. 17, 1999, now U.S. Pat. No. 6,420,975, the entire disclosure of which is hereby incorporated by reference herein, and in and co-assigned U.S. patent application Ser. No. 09/449,121, filed Nov. 24, 1999, entitled REARVIEW MIRROR ASSEMBLY WITH UTILITY FUNCTIONS, by Barry W. Hutzler et al. of Donnelly Corporation, now U.S. Pat. No. 6,428,172, the entire disclosure of which is hereby incorporated by reference herein.

Note also, while it is preferable to position the visible tire pressure indicator (such as a high intensity LED light source) on an exterior portion of the vehicle, it may optionally be located at an interior cabin portion (such as at a rearview mirror assembly (preferably at its mount to a header or windshield portion, or at a lower/underside portion of the mirror housing), or as part of an interior roof portion such as a headliner region or a dome light or as part of a door panel/frame/assembly (inside the vehicle but visible via a side window)). However, preferably it is mounted at an interior portion that is visible to a person crouching down to pump air into a tire on the vehicle. Use of an audible tire pressure indicator (such as a horn of the vehicle or another sound generator that momentarily sounds or "chirps" when the correct tire pressure is reached) in conjunction with a visible tire pressure indicator (and especially an interior cabin-mounted visible tire pressure indicator) is most preferred.

Also, it may be advantageous to mount a controller for the passenger-side wheel tire sensors (or at least the antenna thereof) in or at the passenger-side exterior side view mirror assembly (such as in the mirror casing thereof) so that a passenger-side tire adjust event is readily recognized. Also, it may be advantageous to mount a controller for the driver-side wheel tire sensors (or at least the antenna thereof) in or at the driver-side exterior side view mirror assembly (such as in the mirror casing thereof) so that a driver-side tire adjust event is readily recognized. Also, it may be advantageous to mount a controller for the passenger-side wheel tire sensors (or at least the antenna thereof) in or at the passenger-side door handle assembly(s) (such as in the casing thereof) so that a driver-side tire adjust event is readily recognized. Also, it may be advantageous to mount a controller for the passenger-side wheel tire sensors (or at least the antenna thereof) in or at the passenger-side door handle assembly(s) (such as in the casing thereof) so that a passenger-side tire adjust event is readily recognized.

Also, any of the displays or video displays above can display tire pressure status, as described above, and further can optionally, occasionally, or frequently display other types of information, such as temperature, compass headings, messages, including pager status, pager messages, E-mail messages, images from an interior cabin surveillance system or back-up system, or the like, in addition to or alternately to the tire pressure status.

Other displays are possible, such as of a night-vision camera (preferably a multi-pixel pyrodetection array) that views forward of the vehicle (or rearward) when driving/parking at night. Location at or within an exterior side view mirror assembly is a desired location. Also, preferably, either or both of the night vision camera and the video display screen it displays on is removable from the vehicle. Thus, for example, a vehicle can be equipped with a night vision camera assembly (such as available from Raytheon) and with the night vision camera assembly detachably mounted to the vehicle (such as to a door of the vehicle such that the imaging surface/lens of the camera assembly is outside the vehicle. The field of view of the night vision camera is in the direction of the vehicle's forward direction of travel. A display screen for this camera can be provided in the interior cabin (such as at, on or adjacent to the interior rearview mirror assembly). The display screen is included in a display assembly that is also detachably mounted in the vehicle. Then, for example, when a driver drives to a dark site (such as a field or woods while out hunting) using and guided by the vehicle-mounted night vision camera/display system, the driver can optionally detach the camera from its mount on the vehicle and detach the display from its mount on the vehicle, and then remount the night vision camera and the display assembly onto a portable, battery-powered module that the driver can then use as a portable night vision system that allows the driver "see" in the dark by using viewing the image generated by the night vision camera on the display screen of the display device. This provides a night vision "flashlight" utility. Upon return to the vehicle, the driver demounts the camera and display assemblies from the portable module, remounts them on the vehicle, and recommences in-vehicle use while driving home.

Also, tire pressure monitoring systems of the type which include at each wheel, within the pressurized cavity of the tire, a pressure transducer, preferably also a temperature transducer, a microcontroller or control circuit, and a radio frequency transmitter, in many cases do not have any external source of power. A small battery must support the continuous transmission of data for many years, 10 years being typical of automotive component required lifetimes. It is, therefore, essential that the wheel based measuring and transmitting units consume as little power as possible. In order to achieve minimum power consumption, pressure and temperature conditions are measured and transmitted on a regular but relatively infrequent basis. Typically, the measurement and transmission periods may be in the order of micro or milliseconds, while the delay between these periods may be in the order of seconds or tens of seconds. While, since generally tire pressures and temperatures change relatively slowly, these frequencies of transmission are sufficient for normal communication of tire conditions. However, they are not sufficient to monitor the rapid changes associated with typical inflation rates, or deflation rates resulting from severe tire damage. It is preferable, therefore, to increase the rate of data transmission, to the order of several transmissions per second, during periods of rapid tire pressure change, to provide timely feedback to the operator during the tire inflation process during a tire pressure adjust event such as at a service station, or to provide timely warning of a relatively rapid tire deflation

due to tire damage to a driver while driving the vehicle (such as via any of the in-cabin tire pressure/status displays described above. While the tire pressure monitoring system may be put into tire inflation mode by a user operated switch (or by detection of depression of a tire valve nipple or the like), it may preferably be selected automatically when the central control unit detects the increased frequency of transmissions from a particular wheel mounted unit.

It should be noted that the above described system to aid the tire inflation process may be applied to tire pressure monitoring systems which do not rely on battery powered transmissions such as wireless induction systems or systems which incorporate mechanically generated power based on wheel rotation.

The temperature of the air within a tire cavity varies significantly over time due to varying ambient temperature, road surface temperature, and heat generation due to tire wall flexing while driving. Since the air within the tire obeys Boyle's Law, the pressure and tire volume vary with varying temperature according to the formula: $P \times V/T = \text{a constant}$. Typically the desired tire air pressure is specified at a nominal ambient temperature, but in a typical tire inflation situation in which the vehicle has been driven to a service station or suitable source of compressed air, the tires on the wheels on that vehicle are typically at temperatures other than (and higher than) the nominal ambient value (for example, if parked for a prolonged period so that tire temperature matched ambient temperature), depending on the recent driving history or current ambient conditions. It is undesirable to wait such as at a service station for sufficient time for the tires to cool to ambient temperatures before inflation. It is, therefore, preferable that the tire pressure monitoring system includes an algorithm based on Boyle's Law (or another gas pressure/temperature relationship), which corrects for the effect of temperature, and with the tire pressure monitoring system determining the appropriate pressure set point on the basis of the desired pressure at ambient temperature and the temperature of the air in the tire, and a pressure volume relationship for the particular tire and wheel rim combination. It is reasonable to ignore the volume variable since this will be approximately constant for a particular pressure for a particular wheel rim and tire combination. Thus a tire pressure indicator provided such as at an outside side view mirror assembly, or by use of a horn chirp or similar momentary sounding of the car horn, by flashing of the turn signal lamps, or by other means can provide a signal to the operator at a temperature compensated pressure such that on return to nominal ambient temperature the pressure will return to the desired set point. By this means the vehicle operator does not have to be concerned with absolute pressure values, or with the effects of temperature. This same algorithm may be used for continuous monitoring such that out of adjustment pressure warnings are only initiated after temperature compensations have been made. Thus, on setting up the system, it is only necessary to input the manufacturer's recommended pressure at nominal temperatures for each tire on the vehicle. If the system requires wheel position training, the appropriate action such as a slight inflation or deflation of tires in sequence can be taken. Thereafter the tire condition indication merely requires a system-active status and a low or high pressure condition (if present) input, and wheel position identification.

It is known to provide a system with a receiver local to each wheel on the vehicle, for instance located in the wheel well, such that the system does not require the wheel position training step described above. For economic reasons, however, a single omni-directional receiver is more typically used. However, it is practical to combine the described tire

monitoring system with two directional antennae in a central location such that one antenna is responsive to transmission sources to the left and right hand sides of the vehicle, the second responsive to transmission sources to the rear and front of the vehicle. Combination of the two antennae responses allows the economic determination, such as by a triangulation algorithm, of each wheel transmitter position without the need for local antennae, thus avoiding the need for the above described position training step, and retraining after tire rotation, and allowing an automatic identification of from what wheel type (front or rear; passenger-side or driver-side) an individual wireless broadcast of tire pressure data received at a central controller is being broadcast from. Such an autosensing tire pressure system (that automatically identifies the particular wheel on the vehicle from which a received wireless signal is being broadcast from so that it can distinguish that, for example, a tire sensor broadcasting is located on a rear driver's side wheel rather than any other wheel) has many advantages. Preferably, such an autosensing tire pressure system includes two spaced antennae (either spaced apart on a common assembly in the vehicle or at different locations in the vehicle, such as one antenna on a driver side, such as at a driver side exterior rearview mirror assembly, with the other on a passenger side, such as at a passenger side exterior rearview mirror assembly or with one located at an interior rearview mirror assembly and the other in a header console or other roof portion of the vehicle). By the receiving antennae of the tire pressure display/monitoring system being spaced apart but in known locations within or at the vehicle, a control or processor, such as within the tire pressure monitoring controller, can identify the location of a given tire sensor in a given wheel by analyzing the differences in the respective signals using, for example, triangulation techniques, which triangulation techniques are known in the art. Thus, the driver can rotate or change the position of tires on the vehicle and the tire monitoring system will "learn" or automatically identify the location of each tire sensor broadcasting, and will then be able to inform the driver, for example, that "Tire pressure for Front Passenger-Side Tire is 32 psi". Thus, an automatic vehicle wheel identification function is provided for the tire pressure display/monitoring system of the present invention.

The present invention provides a method of assisting manual tire inflation by a person whereby, for example, a driver can pull up to an air compressor station at a service station, turn off the vehicle engine and exit the vehicle, and crouch down at a particular wheel tire to inflate using the air hose provided at the service center. Upon connecting the air hose to the valve stem of that tire, the driver can view a visible indicator provided at an exterior vehicle portion such as on the underside of the casing that houses the exterior mirror reflector in the exterior side view mirror assembly on that side of the vehicle, and/or hear an audible tire pressure indicator such as can be provided via a sound pattern produced by the horn on the vehicle that is coded to/indicative of the tire pressure condition being sensed in a particular tire that is having its tire pressure adjusted, and/or experience actuation of a tactile tire pressure indicator while pumping air into a tire. Upon commencing the tire pressure adjust event, the driver can view the indicator, whose illumination is coded to indicate the tire pressure status (whether it be in an under pressure condition, a correct pressure condition or an over pressure condition) and/or listen for/to the sound generated by the audible tire pressure indicator, and/or experience actuation of a tactile tire pressure indicator while pumping air into a tire. Guided by the coded illumination of the indicator(s) and/or audible sounds provided external the vehicle and/or tactile feedback from the

45

tactile tire pressure sensor, and while still crouched in the act of adjusting tire pressure, the driver can inflate/deflate that tire's pressure to the recommended, desired pressure level (a pressure level preferably stored in a memory of the vehicle).

Other changes and modifications in the specifically described embodiments can be carried out without departing from the principles of the invention which is intended to be limited only by the scope of the appended claims, as interpreted according to the principles of patent law including the doctrine of equivalents.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. An accessory system suitable for use in an interior cabin of a vehicle, the interior cabin having a windshield, said accessory system comprising:

an attachment element adhesively attached to an interior surface of the windshield of the vehicle;

an accessory module, said accessory module comprising structure adapted to attach to said attachment element; and

wherein said structure detachably attaches to said attachment element and wherein said accessory module encompasses (a) an antenna for a tire pressure monitoring system and (b) a forward facing camera, said forward facing camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle, and wherein said forward facing camera captures images for at least one of a collision avoidance system and an automatic headlamp control system.

2. The accessory system of claim 1, wherein said forward facing camera captures images for a collision avoidance system.

3. The accessory system of claim 1, wherein said forward facing camera captures images for an automatic headlamp control system.

4. The accessory system of claim 1 further comprising an interior rearview mirror, wherein said interior rearview mirror comprises a mirror casing and a mirror reflective element, and wherein said interior rearview mirror is one of (a) pivotally mounted to said accessory module, (b) pivotally mounted to an interior portion of the vehicle, (c) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle, (d) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to said accessory module and (e) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to and at least partially enveloped by said accessory module.

5. The accessory system of claim 4, wherein said interior rearview mirror is pivotally mounted to said accessory module via a double pivot joint mounting configuration.

6. The accessory system of claim 5, wherein said double pivot joint mounting configuration includes a mirror mounting element that detachably mounts to a mirror receiving attachment element of said accessory module.

7. The accessory system of claim 4, wherein said interior rearview mirror is pivotally mounted to said accessory module via a single pivot joint mounting configuration.

8. The accessory system of claim 4, wherein said interior rearview mirror is pivotally mounted to an interior portion of the vehicle and wherein said interior rearview mirror is pivotally mounted via one of (a) a double pivot joint mounting configuration and (b) a single pivot joint mounting configuration.

46

9. The accessory system of claim 8, wherein the interior portion of the vehicle comprises the interior surface of the windshield and wherein said interior rearview mirror is pivotally mounted to a second attachment adhesively attached to the interior surface of the windshield of the vehicle.

10. The accessory system of claim 1, wherein said accessory module comprises a housing and wherein said housing encompasses said antenna and said forward facing camera.

11. The accessory system of claim 10, wherein said housing accommodates at least one of said antenna and said forward facing camera.

12. The accessory system of claim 10, wherein said housing accommodates said antenna and said forward facing camera.

13. The accessory system of claim 1, wherein said accessory module encompasses a rain sensor.

14. The accessory system of claim 1, wherein said forward facing camera comprises a forward facing CMOS camera.

15. The accessory system of claim 1, wherein said accessory module encompasses circuitry associated with said tire pressure monitoring system.

16. The accessory system of claim 1, wherein said tire pressure monitoring system comprises a control that receives signals from wheel-based sensors of the vehicle, and wherein said accessory module accommodates said control.

17. The accessory system of claim 1, wherein said accessory module comprises at least one user input for controlling at least one accessory of the vehicle.

18. An accessory system suitable for use in an interior cabin of a vehicle, the interior cabin having a windshield, said accessory system comprising:

an attachment element adhesively attached to an interior surface of the windshield of the vehicle;

an accessory module, said accessory module comprising structure adapted to attach to said attachment element; and

wherein said structure detachably attaches to said attachment element and wherein said accessory module encompasses (a) an antenna for a tire pressure monitoring system, (b) a forward facing camera and (c) a rain sensor, said forward facing camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle.

19. The accessory system of claim 18, wherein said forward facing camera captures images for at least one of a collision avoidance system and an automatic headlamp control system.

20. The accessory system of claim 18, wherein said accessory module encompasses circuitry associated with said tire pressure monitoring system.

21. The accessory system of claim 18, wherein said tire pressure monitoring system comprises a control that receives signals from wheel-based sensors of the vehicle, and wherein said accessory module accommodates said control.

22. The accessory system of claim 18, wherein said accessory module comprises a housing and wherein said housing encompasses said antenna, said forward facing camera and said rain sensor.

23. The accessory system of claim 18, wherein said accessory module accommodates at least one of said antenna, said forward facing camera and said rain sensor.

24. The accessory system of claim 18 further comprising an interior rearview mirror, wherein said interior rearview mirror comprises a mirror casing and a mirror reflective element, and wherein said interior rearview mirror is one of (a) pivotally mounted to said accessory module, (b) pivotally mounted to an interior portion of the vehicle, (c) pivotally

47

mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle, (d) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to said accessory module and (e) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to and at least partially enveloped by said accessory module.

25. The accessory system of claim 24, wherein said interior rearview mirror is pivotally mounted via one of (a) a double pivot joint mounting configuration and (b) a single pivot joint mounting configuration.

26. An accessory system suitable for use in an interior cabin of a vehicle, the interior cabin having a windshield, said accessory system comprising:

an attachment element adhesively attached to an interior surface of the windshield of the vehicle;

an accessory module, said accessory module comprising structure adapted to attach to said attachment element; wherein said structure detachably attaches to said attachment element and wherein said accessory module encompasses (a) an antenna and (b) a forward facing CMOS camera, said forward facing CMOS camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle; and

an interior rearview mirror, wherein said interior rearview mirror comprises a mirror casing and a mirror reflective element, and wherein said interior rearview mirror is one of (a) pivotally mounted to said accessory module, (b) pivotally mounted to an interior portion of the vehicle, (c) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle, (d) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to said accessory module and (e) pivotally mounted to a second attachment element adhesively attached to the interior surface of the windshield of the vehicle adjacent to and at least partially enveloped by said accessory module.

27. The accessory system of claim 26, wherein said interior rearview mirror is pivotally mounted via one of (a) a double pivot joint mounting configuration and (b) a single pivot joint mounting configuration.

28. The accessory system of claim 26, wherein said forward facing CMOS camera captures images for at least one of a collision avoidance system and an automatic headlamp control system.

29. The accessory system of claim 26, wherein said antenna comprises an antenna for a tire pressure monitoring system and wherein said accessory module encompasses circuitry associated with said tire pressure monitoring system.

30. The accessory system of claim 26, wherein said antenna comprises an antenna for a tire pressure monitoring system and wherein said tire pressure monitoring system comprises a control that receives signals from wheel-based sensors of the vehicle, and wherein said accessory module accommodates said control.

31. The accessory system of claim 26, wherein said accessory module encompasses a rain sensor.

32. The accessory system of claim 31, wherein said accessory module accommodates at least one of said antenna, said forward facing camera and said rain sensor.

33. The accessory system of claim 26, wherein said accessory module comprises a housing and wherein said housing encompasses said antenna and said forward facing camera.

48

34. An accessory system suitable for use in an interior cabin of a vehicle, the interior cabin having a windshield, said accessory system comprising:

at least one accessory-module attachment element adhesively attached to an interior surface of the windshield of the vehicle;

an accessory module, said accessory module comprising structure adapted to detachably attach to said accessory-module attachment element;

wherein said accessory module attached to said accessory-module attachment element encompasses at least two accessories selected from the group consisting of (i) a rain sensor, (ii) an antenna, (iii) a forward facing CCD camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle, (iv) a forward facing CMOS camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle, (v) a photo sensor, (vi) a transceiver, (vii) a keyless entry receiver, (viii) a compass sensor, (ix) a headlamp controller, (x) a display and (xi) a microphone;

a mirror mounting button adhesively attached to the interior surface of the windshield of the vehicle;

an interior rearview mirror assembly;

wherein said interior rearview mirror assembly is detachably mounted to said mirror mounting button by a mounting configuration of said interior rearview mirror assembly, said mounting configuration comprising a support having a mirror mount configured to mount to said mirror mounting button;

wherein said mounting configuration comprises one of (a) a double pivot joint mounting configuration and (b) a single pivot joint mounting configuration; and

wherein when said interior rearview mirror assembly is mounted to said mirror mounting button and when said accessory module is attached to said at least one accessory-module attachment element, said mounting configuration of interior rearview mirror assembly is at least partially enveloped by said accessory module.

35. The accessory system of claim 34, wherein one of said at least two accessories comprises a forward facing CMOS camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle.

36. The accessory system of claim 35, wherein said forward facing CMOS camera captures images for at least one of a collision avoidance system and an automatic headlamp control system.

37. The accessory system of claim 36, wherein another of said at least two accessories comprises an antenna.

38. The accessory system of claim 37, wherein said antenna comprises an antenna for a tire pressure monitoring system.

39. The accessory system of claim 37, wherein said antenna comprises an antenna for a satellite system.

40. The accessory system of claim 39, wherein said satellite system comprises a satellite radio system.

41. The accessory system of claim 39, wherein said satellite system comprises at least one satellite of a GPS system.

42. The accessory system of claim 37, wherein said antenna comprises an antenna for a tire pressure monitoring system; and wherein said tire pressure monitoring system comprises a control that receives signals from wheel-based sensors of the vehicle.

43. The accessory system of claim 42, wherein said accessory module accommodates said control.

44. The accessory system of claim 34, wherein one of said at least two accessories comprises a forward facing CMOS camera having a forward field of view through the windshield

49

of the vehicle and in the direction of forward travel of the vehicle and wherein another of said at least two accessories comprises a rain sensor.

45. The accessory system of claim 34, wherein said at least two accessories comprise at least three accessories, said three accessories comprising (i) an antenna, (ii) a forward facing camera and (iii) a rain sensor.

46. The accessory system of claim 45, wherein said accessory module comprises a housing and wherein said housing encompasses said antenna, said forward facing camera and said rain sensor when said accessory module is attached to said at least one accessory-module attachment element.

47. The accessory system of claim 34, wherein said mounting configuration of said interior rearview mirror assembly is at least partially enveloped by a forked portion of said accessory module.

48. The accessory system of claim 34, wherein said mounting configuration of said interior rearview mirror assembly is at least partially straddled by said accessory module.

49. The accessory system of claim 34, wherein said accessory module is detachable from said at least one accessory-module attachment element as an assembly.

50. The accessory system of claim 34, wherein said at least one accessory-module attachment element is adhesively attached to an interior surface of the windshield of the vehicle by a structural adhesive.

51. The accessory system of claim 50, wherein said at least one accessory-module attachment element comprises at least two accessory-module attachment elements.

52. The accessory system of claim 50, wherein said structural adhesive comprises at least one of an epoxy and a silicone.

53. The accessory system of claim 34, wherein said accessory module comprise a portion that extends to a roof portion of the vehicle.

54. An accessory system suitable for use in an interior cabin of a vehicle, the interior cabin having a windshield, said accessory system comprising:

at least one accessory-module attachment element adhesively attached to an interior surface of the windshield of the vehicle;

50

an accessory module, said accessory module comprising structure adapted to detachably attach to said accessory-module attachment element;

wherein said accessory module attached to said accessory-module attachment element encompasses at least (i) a rain sensor and (ii) a forward facing camera having a forward field of view through the windshield of the vehicle and in the direction of forward travel of the vehicle;

a mirror mounting button adhesively attached to the interior surface of the windshield of the vehicle;

an interior rearview mirror assembly;

wherein said interior rearview mirror assembly is detachably mounted to said mirror mounting button by a mounting configuration of said interior rearview mirror assembly, said mounting configuration comprising a support having a mirror mount configured to mount to said mirror mounting button;

wherein said mounting configuration comprises one of (a) a double pivot joint mounting configuration and (b) a single pivot joint mounting configuration; and

wherein when said interior rearview mirror assembly is mounted to said mirror mounting button and when said accessory module is attached to said at least one accessory-module attachment element, said mounting configuration of interior rearview mirror assembly is at least partially straddled by said accessory module.

55. The accessory system of claim 54, wherein said mounting configuration comprises a double pivot joint mounting configuration.

56. The accessory system of claim 55, wherein said at least two accessories comprise at least three accessories, said at least three accessories comprising (i) a rain sensor, (ii) a forward facing camera and (iii) an antenna.

57. The accessory system of claim 56, wherein said antenna comprises an antenna for a satellite system.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,728,721 B2
APPLICATION NO. : 12/276770
DATED : June 1, 2010
INVENTOR(S) : Kenneth Schofield et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 14

Line 34, "minor" should be --mirror--

Column 30

Line 20, "aim" should be --arm--

Column 34

Line 8, "minor" should be --mirror--

Column 48

Claim 42, Line 60, "system;" should be "system,"


Column 50

Claim 54, Line 13, "minor" should be "mirror"

Claim 54, Line 15, "minor" should be "mirror"

Signed and Sealed this

Twenty-sixth Day of October, 2010

A handwritten signature in black ink, reading "David J. Kappos". The signature is written in a cursive, flowing style with a large, stylized "K".

David J. Kappos
Director of the United States Patent and Trademark Office