US008788070B2

(12) **United States Patent**
Schumacher et al.

(10) **Patent No.: US 8,788,070 B2**
(45) **Date of Patent: Jul. 22, 2014**

(54) **AUTOMATIC FIELD DEVICE SERVICE ADVISER**

(75) Inventors: **Mark S. Schumacher**, Minneapolis, MN (US); **Evren Eryurek**, Melbourne, FL (US)

(73) Assignee: **Rosemount Inc.**, Eden Prairie, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 381 days.

(21) Appl. No.: **11/527,770**

(22) Filed: **Sep. 26, 2006**

(65) **Prior Publication Data**

US 2008/0125884 A1 May 29, 2008

(51) **Int. Cl.**

G05B 9/02	(2006.01)
G06F 19/00	(2011.01)
G01C 19/00	(2013.01)

(52) **U.S. Cl.**

USPC **700/79**; 700/108; 700/109; 700/114; 700/115; 700/159; 700/204; 700/104

(58) **Field of Classification Search**

USPC 700/79, 108, 109, 114, 115, 117, 159, 700/204; 702/104; 714/2; 340/7.44, 7.6; 706/21

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,096,434	A	7/1963	King	235/151
3,404,264	A	10/1968	Kugler	235/194
3,468,164	A	9/1969	Sutherland	73/343
3,590,370	A	6/1971	Fleischer	324/51
3,618,592	A	11/1971	Stewart	128/2.05 R
3,688,190	A	8/1972	Blum	324/61 R
3,691,842	A	9/1972	Akeley	73/398 C
3,701,280	A	10/1972	Stroman	73/194
3,849,637	A	11/1974	Caruso et al.	235/151
3,855,858	A	12/1974	Cushing	73/194 EM
3,948,098	A	4/1976	Richardson et al.	73/861.24
3,952,759	A	4/1976	Ottenstein	137/12
3,973,184	A	8/1976	Raber	324/51
RE29,383	E	9/1977	Gallatin et al.	137/14
4,058,975	A	11/1977	Gilbert et al.	60/39.28
4,083,031	A	4/1978	Pharo, Jr.	367/135
4,099,413	A	7/1978	Ohte et al.	73/359
4,102,199	A	7/1978	Talpouras	73/362

(Continued)

FOREIGN PATENT DOCUMENTS

CA	999950	11/1976
CN	1346435	4/2002

(Continued)

OTHER PUBLICATIONS

Emerson Proves Advancements in EDDL (Electronic Device Description Language) Technology, Apr. 2005, Emerson Process Management News, abstract.*


(Continued)

Primary Examiner — Kavita Padmanabhan
Assistant Examiner — Thomas Stevens
(74) *Attorney, Agent, or Firm* — Westman, Champlin & Koehler, P.A.

(57) **ABSTRACT**

A field device resident algorithm receives one or more diagnostic inputs and generates actionable service information. The algorithm(s) can be changed or updated after the manufacture of the field device. The actionable service information can be displayed locally or sent over a process control loop. A prediction engine can be employed to determine a period within which such service should be completed.

25 Claims, 5 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

4,122,719	A	10/1978	Carlson et al.	73/342
4,249,164	A	2/1981	Tivy	340/870.3
4,250,490	A	2/1981	Dahlke	340/870.37
4,255,964	A	3/1981	Morison	73/24.01
4,279,013	A	7/1981	Cameron et al.	340/870.37
4,337,516	A	6/1982	Murphy et al.	364/551
4,383,443	A	5/1983	Langdon	73/290
4,390,321	A	6/1983	Langlois et al.	417/15
4,399,824	A	8/1983	Davidson	128/736
4,417,312	A	11/1983	Cronin et al.	364/510
4,423,634	A	1/1984	Audenard et al.	73/587
4,446,741	A	5/1984	Sirokorad et al.	73/654
4,459,858	A	7/1984	Marsh	73/861.12
4,463,612	A	8/1984	Thompson	73/861.22
4,517,468	A	5/1985	Kemper et al.	290/52
4,530,234	A	7/1985	Cullick et al.	73/53
4,536,753	A	8/1985	Parker	340/566
4,540,468	A	9/1985	Genco et al.	162/49
4,571,689	A	2/1986	Hildebrand et al.	364/481
4,630,265	A	12/1986	Sexton	370/85
4,635,214	A	1/1987	Kasai et al.	364/551
4,642,782	A	2/1987	Kemper et al.	364/550
4,644,479	A	2/1987	Kemper et al.	364/550
4,649,515	A	3/1987	Thompson et al.	364/900
4,668,473	A	5/1987	Agarwal	422/62
4,686,638	A	8/1987	Furuse	364/558
4,696,191	A	9/1987	Claytor et al.	73/600
4,705,212	A	11/1987	Miller et al.	236/54
4,707,796	A	11/1987	Calabro et al.	364/552
4,720,806	A	1/1988	Schippers et al.	364/551
4,736,367	A	4/1988	Wroblewski et al.	370/85
4,736,763	A	4/1988	Britton et al.	137/10
4,758,308	A	7/1988	Carr	162/263
4,777,585	A	10/1988	Kokawa et al.	364/164
4,818,994	A	4/1989	Orth et al.	340/501
4,831,564	A	5/1989	Suga	364/551.01
4,833,922	A	5/1989	Frick et al.	73/756
4,841,286	A	6/1989	Kummer	340/653
4,853,693	A	8/1989	Eaton-Williams	340/588
4,866,628	A	9/1989	Natarajan	700/102
4,873,655	A	10/1989	Kondraske	364/553
4,907,167	A	3/1990	Skeirik	364/500
4,924,418	A	5/1990	Bachman et al.	364/550
4,926,364	A	5/1990	Brotherton	364/581
4,934,196	A	6/1990	Romano	73/861.38
4,939,753	A	7/1990	Olson	375/107
4,964,125	A	10/1990	Kim	371/15.1
4,988,990	A	1/1991	Warrior	340/25.5
4,992,965	A	2/1991	Holter et al.	364/551.01
5,005,142	A	4/1991	Lipchak et al.	364/550
5,025,344	A	6/1991	Maly et al.	361/88
5,043,862	A	8/1991	Takahashi et al.	364/162
5,047,990	A	9/1991	Gafos et al.	367/6
5,053,815	A	10/1991	Wendell	355/208
5,057,774	A	10/1991	Verhelst et al.	324/537
5,067,099	A	11/1991	McCown et al.	364/550
5,081,598	A	1/1992	Bellows et al.	364/550
5,089,979	A	2/1992	McEachern et al.	364/571.04
5,089,984	A	2/1992	Struger et al.	395/650
5,094,109	A	3/1992	Dean et al.	73/718
5,098,197	A	3/1992	Shepard et al.	374/120
5,099,436	A	3/1992	McCown et al.	364/550
5,103,409	A	4/1992	Shimizu et al.	364/556
5,111,531	A	5/1992	Grayson et al.	395/23
5,121,467	A	6/1992	Skeirik	395/11
5,122,794	A	6/1992	Warrior	340/825.2
5,122,976	A	6/1992	Bellows et al.	364/550
5,130,936	A	7/1992	Sheppard et al.	364/551.01
5,134,574	A	7/1992	Beaverstock et al.	364/551.01
5,137,370	A	8/1992	McCullock et al.	374/173
5,142,612	A	8/1992	Skeirik	395/11
5,143,452	A	9/1992	Maxedon et al.	374/170
5,148,378	A	9/1992	Shibayama et al.	364/551.07
5,150,289	A	9/1992	Badavas	364/154
5,167,009	A	11/1992	Skeirik	395/27
5,175,678	A	12/1992	Frerichs et al.	364/148
5,189,624	A *	2/1993	Barlow et al.	700/169
5,193,143	A	3/1993	Kaemmerer et al.	395/51
5,197,114	A	3/1993	Skeirik	395/22
5,197,328	A	3/1993	Fitzgerald	73/168
5,212,765	A	5/1993	Skeirik	395/11
5,214,582	A	5/1993	Gray	364/424.03
5,216,226	A	6/1993	Miyoshi	219/497
5,216,612	A *	6/1993	Cornett et al.	700/96
5,224,203	A	6/1993	Skeirik	395/22
5,228,780	A	7/1993	Shepard et al.	374/175
5,235,527	A	8/1993	Ogawa et al.	364/571.05
5,265,031	A	11/1993	Malczewski	364/497
5,265,222	A	11/1993	Nishiya et al.	395/3
5,267,241	A *	11/1993	Kowal	714/706
5,269,311	A	12/1993	Kirchner et al.	128/672
5,274,572	A	12/1993	O'Neill et al.	364/550
5,282,131	A	1/1994	Rudd et al.	364/164
5,282,261	A	1/1994	Skeirik	395/22
5,293,585	A	3/1994	Morita	395/52
5,303,181	A	4/1994	Stockton	365/96
5,305,230	A	4/1994	Matsumoto et al.	364/495
5,311,421	A	5/1994	Nomura et al.	364/157
5,317,520	A	5/1994	Castle	364/482
5,327,357	A	7/1994	Feinstein et al.	364/502
5,333,240	A *	7/1994	Matsumoto et al.	706/20
5,340,271	A	8/1994	Freeman et al.	415/1
5,347,843	A	9/1994	Orr et al.	73/3
5,349,541	A	9/1994	Alexandro, Jr. et al.	364/578
5,351,199	A *	9/1994	Ticcioni et al.	700/282
5,357,449	A	10/1994	Oh	364/551.01
5,361,628	A	11/1994	Marko et al.	73/116
5,365,423	A	11/1994	Chand	364/140
5,365,787	A	11/1994	Hernandez et al.	73/660
5,367,612	A	11/1994	Bozich et al.	395/22
5,369,674	A	11/1994	Yokose et al.	376/245
5,384,699	A	1/1995	Levy et al.	364/413.13
5,386,373	A	1/1995	Keeler et al.	364/577
5,388,465	A	2/1995	Okaniwa et al.	73/861.17
5,392,293	A	2/1995	Hsue	324/765
5,394,341	A	2/1995	Kepner	364/551.01
5,394,543	A	2/1995	Hill et al.	395/575
5,404,064	A	4/1995	Mermelstein et al.	310/319
5,408,406	A	4/1995	Mathur et al.	364/163
5,408,586	A	4/1995	Skeirik	395/23
5,410,495	A	4/1995	Ramamurthi	364/511.05
5,414,645	A	5/1995	Hirano	364/551.01
5,419,197	A	5/1995	Ogi et al.	73/659
5,430,642	A	7/1995	Nakajima et al.	364/148
5,434,774	A	7/1995	Seberger	364/172
5,436,705	A	7/1995	Raj	355/246
5,440,478	A	8/1995	Fisher et al.	364/188
5,442,639	A	8/1995	Crowder et al.	371/20.1
5,444,820	A *	8/1995	Tzes et al.	706/21
5,467,355	A	11/1995	Umeda et al.	364/571.04
5,469,070	A	11/1995	Koluvek	324/713
5,469,156	A	11/1995	Kogure	340/870.38
5,469,735	A	11/1995	Watanabe	73/118.1
5,469,749	A	11/1995	Shimada et al.	73/861.47
5,481,199	A	1/1996	Anderson et al.	324/705
5,481,200	A	1/1996	Voegele et al.	324/718
5,483,387	A	1/1996	Bauhahn et al.	359/885
5,485,753	A	1/1996	Burns et al.	73/720
5,486,996	A	1/1996	Samad et al.	364/152
5,488,697	A	1/1996	Kaemmerer et al.	395/51
5,489,831	A	2/1996	Harris	318/701
5,495,769	A	3/1996	Broden et al.	73/718
5,510,779	A	4/1996	Maltby et al.	340/870.3
5,511,004	A	4/1996	Dubost et al.	364/551.01
5,526,293	A	6/1996	Mozumder et al.	364/578
5,539,638	A	7/1996	Keeler et al.	364/424.03
5,548,528	A	8/1996	Keeler et al.	364/497
5,549,137	A *	8/1996	Lenz et al.	137/486
5,555,190	A	9/1996	Derby et al.	364/510
5,560,246	A	10/1996	Bottinger et al.	73/861.15
5,561,599	A	10/1996	Lu	364/164
5,570,034	A	10/1996	Needham et al.	324/763
5,570,300	A	10/1996	Henry et al.	364/551.01
5,572,420	A	11/1996	Lu	364/153

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,572,438	A	*	11/1996	Ehlers et al.	700/295
5,573,032	A		11/1996	Lenz et al.	137/486
5,578,763	A		11/1996	Spencer et al.	73/861.08
5,591,922	A		1/1997	Segeral et al.	73/861.04
5,598,521	A		1/1997	Kilgore et al.	395/326
5,600,148	A		2/1997	Cole et al.	250/495.1
5,600,791	A	*	2/1997	Carlson et al.	714/47.3
5,608,650	A		3/1997	McClendon et al.	364/510
5,623,605	A		4/1997	Keshav et al.	395/200.17
5,629,870	A		5/1997	Farag et al.	364/551.01
5,633,809	A		5/1997	Wissenbach et al.	364/510
5,637,802	A		6/1997	Frick et al.	73/724
5,640,491	A		6/1997	Bhat et al.	395/22
5,644,240	A		7/1997	Brugger	324/439
5,650,943	A		7/1997	Powell et al.	702/51
5,654,869	A		8/1997	Ohi et al.	361/540
5,661,668	A		8/1997	Yemini et al.	364/550
5,665,899	A		9/1997	Willcox	73/4
5,668,322	A		9/1997	Broden	73/756
5,671,335	A		9/1997	Davis et al.	395/23
5,672,247	A		9/1997	Pangalos et al.	162/65
5,675,504	A		10/1997	Serodes et al.	364/496
5,675,724	A		10/1997	Beal et al.	395/182.02
5,680,109	A		10/1997	Lowe et al.	340/608
5,682,317	A		10/1997	Keeler et al.	364/431.03
5,682,476	A		10/1997	Tapperson et al.	370/225
5,704,011	A		12/1997	Hansen et al.	395/22
5,705,754	A		1/1998	Keita et al.	73/861.357
5,705,978	A		1/1998	Frick et al.	340/511
5,708,211	A		1/1998	Jepson et al.	73/861.04
5,708,585	A		1/1998	Kushion	364/431.061
5,710,370	A		1/1998	Shanahan et al.	73/1.35
5,713,668	A		2/1998	Lunghofer et al.	374/179
5,731,522	A		3/1998	Sittler	73/708
5,736,649	A		4/1998	Kawasaki et al.	73/861.23
5,742,845	A		4/1998	Wagner	395/831
5,746,511	A		5/1998	Eryurek et al.	374/2
5,747,701	A		5/1998	Marsh et al.	73/861.23
5,748,883	A	*	5/1998	Carlson et al.	714/47.3
5,752,008	A		5/1998	Bowling	395/500
5,754,451	A	*	5/1998	Williams	702/185
5,764,539	A		6/1998	Rani	364/557
5,764,891	A	*	6/1998	Warrior	710/72
5,781,024	A		7/1998	Blomberg et al.	324/763
5,781,878	A		7/1998	Mizoguchi et al.	701/109
5,790,413	A		8/1998	Bartusiak et al.	364/485
5,796,006	A		8/1998	Bellet et al.	73/661
5,801,689	A		9/1998	Huntsman	345/329
5,805,442	A		9/1998	Crater et al.	364/138
5,817,950	A		10/1998	Wiklund et al.	73/861.66
5,825,664	A		10/1998	Warrior et al.	700/7
5,828,567	A		10/1998	Eryurek	364/184
5,854,993	A		12/1998	Crichnik	702/54
5,854,994	A		12/1998	Canada et al.	702/56
5,859,964	A		1/1999	Wang et al.	395/185.01
5,869,772	A		2/1999	Storer	73/861.24
5,887,978	A		3/1999	Lunghofer et al.	374/179
5,900,801	A	*	5/1999	Heagle et al.	340/286.09
5,908,990	A		6/1999	Cummings	73/861.22
5,920,016	A		7/1999	Broden	73/756
5,923,557	A		7/1999	Eidson	364/471.03
5,924,086	A		7/1999	Mathur et al.	706/25
5,934,371	A		8/1999	Bussear et al.	166/53
5,936,514	A		8/1999	Anderson et al.	340/310.01
5,940,013	A	*	8/1999	Vladimir et al.	340/945
5,940,290	A		8/1999	Dixon	364/138
5,956,663	A		9/1999	Eryurek	702/183
5,970,430	A		10/1999	Burns et al.	702/122
5,995,910	A		11/1999	Discenzo	702/56
6,002,952	A		12/1999	Diab et al.	600/310
6,006,338	A		12/1999	Longsdorf et al.	713/340
6,014,612	A		1/2000	Larson et al.	702/183
6,016,706	A		1/2000	Yamamoto et al.	9/6
6,017,143	A		1/2000	Eryurek	700/51
6,023,399	A		2/2000	Kogure	361/23
6,026,352	A		2/2000	Burns et al.	702/182
6,046,642	A		4/2000	Brayton et al.	330/296
6,047,220	A		4/2000	Eryurek	700/28
6,047,222	A		4/2000	Burns et al.	700/79
6,059,254	A		5/2000	Sundet et al.	248/678
6,061,603	A		5/2000	Papadopoulos et al.	700/83
6,072,150	A		6/2000	Sheffer	219/121.83
6,094,600	A		7/2000	Sharpe, Jr. et al.	700/19
6,104,875	A	*	8/2000	Gallagher et al.	717/168
6,112,131	A		8/2000	Ghorashi et al.	700/142
6,119,047	A		9/2000	Eryurek	700/28
6,139,180	A		10/2000	Usher et al.	374/1
6,179,964	B1		1/2001	Begemann et al.	162/198
6,182,501	B1		2/2001	Furuse et al.	73/49.2
6,199,018	B1		3/2001	Quist et al.	702/34
6,209,048	B1		3/2001	Wolff	710/62
6,237,424	B1		5/2001	Salmasi et al.	73/861.17
6,260,004	B1		7/2001	Hays et al.	702/183
6,272,438	B1		8/2001	Cunningham et al.	702/56
6,289,735	B1		9/2001	Dister et al.	73/579
6,298,454	B1	*	10/2001	Schleiss et al.	714/37
6,307,483	B1		10/2001	Westfield et al.	340/870.11
6,317,701	B1		11/2001	Pyostsia et al.	702/188
6,330,005	B1	*	12/2001	Tonelli et al.	715/735
6,347,252	B1		2/2002	Behr et al.	700/2
6,356,191	B1		3/2002	Kirkpatrick	340/501
6,360,277	B1		3/2002	Ruckley et al.	9/250
6,370,448	B1		4/2002	Eryurek et al.	700/282
6,377,859	B1		4/2002	Brown et al.	700/79
6,378,364	B1		4/2002	Pelletier et al.	73/152.47
6,396,426	B1		5/2002	Balard et al.	341/120
6,397,114	B1		5/2002	Eryurek	364/999.999
6,405,099	B1		6/2002	Nagai et al.	700/159
6,425,038	B1		7/2002	Sprecher	710/269
6,434,504	B1		8/2002	Eryurek	702/130
6,447,459	B1	*	9/2002	Larom	600/538
6,449,574	B1		9/2002	Eryurek	702/99
6,473,656	B1		10/2002	Langels et al.	700/17
6,473,710	B1		10/2002	Eryurek	702/133
6,480,793	B1		11/2002	Martin	702/45
6,492,921	B1		12/2002	Kunitani et al.	341/118
6,493,689	B2		12/2002	Kotoulas et al.	706/23
6,496,814	B1	*	12/2002	Busche	706/21
6,497,222	B2		12/2002	Bolz et al.	123/476
6,505,517	B1		1/2003	Eryurek	73/861.08
6,519,546	B1		2/2003	Eryurek	702/130
6,530,259	B1		3/2003	Kelly et al.	73/23.2
6,532,392	B1		3/2003	Eryurek	700/32
6,539,267	B1		3/2003	Eryurek	700/51
6,546,814	B1		4/2003	Choe et al.	73/862.08
6,556,145	B1	*	4/2003	Kirkpatrick et al.	340/870.17
6,561,038	B2		5/2003	Gravel et al.	73/729.2
6,564,268	B1		5/2003	Davis et al.	710/11
6,567,006	B1		5/2003	Lander et al.	340/605
6,594,603	B1	*	7/2003	Eryurek et al.	702/104
6,597,997	B2		7/2003	Tingley	702/34
6,601,005	B1	*	7/2003	Eryurek et al.	702/104
6,611,775	B1		8/2003	Coursolle	702/65
6,615,149	B1		9/2003	Wehrs	702/76
6,629,059	B2		9/2003	Borgeson	702/183
6,633,782	B1	*	10/2003	Schleiss et al.	700/26
6,637,267	B2		10/2003	Fiebelkorn et al.	73/587
6,654,697	B1		11/2003	Eryurek	702/183
6,662,120	B2		12/2003	Drahm et al.	73/861.355
6,701,274	B1		3/2004	Eryurek	702/140
6,722,185	B2		4/2004	Lawson et al.	73/40
6,727,812	B2		4/2004	Sauler et al.	340/511
6,735,549	B2	*	5/2004	Ridolfo	702/181
6,738,388	B1		5/2004	Stevenson et al.	370/465
6,751,560	B1		6/2004	Tingley et al.	702/51
6,754,601	B1	*	6/2004	Eryurek et al.	702/104
6,758,168	B2		7/2004	Koskinen et al.	122/7
6,772,036	B2		8/2004	Eryurek	700/127
6,785,592	B1	*	8/2004	Smith et al.	700/291
6,859,755	B2		2/2005	Eryurek et al.	702/183
6,889,166	B2		5/2005	Zielinski	702/183
6,892,317	B1	*	5/2005	Sampath et al.	714/4.3
6,904,476	B2		6/2005	Hedtke	710/72
6,907,383	B2		6/2005	Eryurek	702/183

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,915,364	B1	7/2005	Christensen et al.	710/104
6,970,003	B2	11/2005	Rome et al.	324/718
6,976,503	B2	12/2005	Ens et al.	137/552
7,013,185	B2 *	3/2006	Simon	700/19
7,018,800	B2 *	3/2006	Huisenga et al.	435/6
7,036,381	B2	5/2006	Broden et al.	73/708
7,040,179	B2	5/2006	Drahm et al.	73/861.356
7,058,542	B2 *	6/2006	Hauhia et al.	702/183
7,085,610	B2	8/2006	Eryurek et al.	700/29
7,099,852	B2	8/2006	Unsworth et al.	706/23
7,109,883	B2	9/2006	Trimble et al.	340/870.16
7,114,516	B2	10/2006	Ito	137/487.5
7,143,007	B2 *	11/2006	Long et al.	702/184
7,171,281	B2	1/2007	Weber et al.	700/96
7,206,646	B2 *	4/2007	Nixon et al.	700/83
7,254,518	B2	8/2007	Eryrurek et al.	702/183
7,258,021	B2	8/2007	Broden	73/756
7,262,693	B2 *	8/2007	Karschnia et al.	340/508
7,435,581	B2	10/2008	West	435/289.1
7,502,744	B2 *	3/2009	Garrow et al.	705/1.1
2002/0013629	A1	1/2002	Nixon et al.	
2002/0029808	A1	3/2002	Friend et al.	137/551
2002/0032544	A1	3/2002	Reid et al.	702/183
2002/0055790	A1 *	5/2002	Havekost	700/80
2002/0077711	A1 *	6/2002	Nixon et al.	700/51
2002/0077782	A1 *	6/2002	Fruehling et al.	702/185
2002/0121910	A1	9/2002	Rome et al.	324/718
2002/0130846	A1 *	9/2002	Nixon et al.	345/169
2002/0145568	A1	10/2002	Winter	343/701
2002/0148644	A1	10/2002	Schultz et al.	175/39
2002/0163427	A1 *	11/2002	Eryurek et al.	340/500
2002/0194547	A1	12/2002	Christenson et al.	714/43
2003/0014536	A1	1/2003	Christensen et al.	709/238
2003/0033040	A1	2/2003	Billings	700/97
2003/0041135	A1	2/2003	Keyes et al.	709/223
2003/0045962	A1	3/2003	Eryurek et al.	
2003/0083953	A1 *	5/2003	Starkey	705/26
2003/0158803	A1 *	8/2003	Darken et al.	705/36
2004/0128034	A1	7/2004	Lenker et al.	700/282
2004/0167750	A1 *	8/2004	Pagnano et al.	702/189
2004/0186927	A1 *	9/2004	Eryurek et al.	710/12
2004/0199361	A1	10/2004	Lu et al.	702/183
2004/0249583	A1	12/2004	Eryurek et al.	702/47
2005/0011278	A1	1/2005	Brown et al.	73/861.18
2005/0030185	A1	2/2005	Huisenga et al.	
2005/0055137	A1 *	3/2005	Andren et al.	700/291
2005/0072239	A1	4/2005	Longsdorf et al.	73/649
2005/0149570	A1 *	7/2005	Sasaki et al.	707/104.1
2005/0168343	A1 *	8/2005	Longsdorf et al.	340/664
2005/0284237	A1	12/2005	Henry et al.	73/861.356
2006/0075009	A1	4/2006	Lenz et al.	708/160
2006/0087402	A1 *	4/2006	Manning et al.	340/3.1
2006/0127183	A1 *	6/2006	Bishop, Jr.	405/37
2006/0229931	A1 *	10/2006	Fligler et al.	705/10
2006/0277000	A1	12/2006	Wehrs	702/183
2007/0010968	A1	1/2007	Longsdorf et al.	702/183
2007/0067725	A1 *	3/2007	Cahill et al.	715/733
2007/0079250	A1 *	4/2007	Bump et al.	715/762
2007/0168057	A1 *	7/2007	Blevins et al.	700/53
2007/0255520	A1 *	11/2007	Becker et al.	702/127
2007/0266020	A1 *	11/2007	Case et al.	707/5
2010/0138066	A1 *	6/2010	Kong	700/295
2010/0211443	A1 *	8/2010	Carrel et al.	705/14.11

FOREIGN PATENT DOCUMENTS

EP	0 122 622	A1	10/1984
EP	0 413 814	A1	2/1991
EP	0 487 419	A2	5/1992
EP	0 512 794	A2	11/1992
EP	0 594 227	A1	4/1994
EP	0 624 847	A1	11/1994
EP	0 644 470	A2	3/1995
EP	0 825 506	A2	7/1997
EP	0 827 096	A2	9/1997
EP	0 838 768	A2	9/1997
EP	0 807 804	A2	11/1997
EP	1 058 093	A1	5/1999
EP	0 965 897	A1	6/1999
EP	1 022 626	A2	7/2000
FR	2 302 514		9/1976
GB	2 310 346	A	8/1997
GB	2 342 453	A	4/2000
GB	2 347 232	A	8/2000
JP	58-129316		8/1983
JP	59-116811		7/1984
JP	59-163520		9/1984
JP	59-211196		11/1984
JP	59-211896		11/1984
JP	60-000507		1/1985
JP	60-76619		5/1985
JP	60-131495		7/1985
JP	60-174915		9/1985
JP	62-30915		2/1987
JP	64-01914		1/1989
JP	64-72699		3/1989
JP	2-05105		1/1990
JP	5-122768		5/1993
JP	5164781		6/1993
JP	06-248224		10/1994
JP	08-114638		5/1996
JP	8-136386		5/1996
JP	8-166309		6/1996
JP	8-247076		9/1996
JP	9054611		2/1997
JP	2712625		10/1997
JP	2003503784		1/2003
JP	2004021712		1/2004
JP	2004034112		2/2004
JP	2004-186445		7/2004
JP	2007507712		3/2007
WO	WO 94/25933		11/1994
WO	WO 96/11389		4/1996
WO	WO 96/12993		5/1996
WO	WO 96/39617		12/1996
WO	WO 97/21157		6/1997
WO	WO 97/25603		7/1997
WO	WO 98/06024		2/1998
WO	WO 98/13677		4/1998
WO	WO 98/14855		4/1998
WO	WO 98/20469		5/1998
WO	WO 98/39718		9/1998
WO	WO 99/19782		4/1999
WO	WO 00/41050		7/2000
WO	WO 00/55700		9/2000
WO	WO 00/70531		11/2000
WO	WO 01/02891	A2	1/2001
WO	WO 01/77766		10/2001
WO	WO 02/27418		4/2002
WO	WO 2004/044666	A2	5/2004
WO	WO 2004/048898	A1	6/2004
WO	WO 2005/033639		4/2005
WO	WO 2007100280	A1 *	9/2007

OTHER PUBLICATIONS

Eryurek et al., "Advanced Diagnostics Achieved with Intelligent Sensors and Fieldbus", 2001, Measurenment and Control vol. 34, p. 293-311.*

Rezabek, John; "Field Device Complications", 2006, 2pg.*

Reeves-T., "Optimizing Process Equipment Performance", 2005, Emerson Process Management, 5 pages.*

PlantWeb, "Improving Availability" Emerson White Paper, 2003, 15 pages.*

PlantWeb, "Reducing Operations & Maintenance Costs", 2003, 18 pages.*

The International Search Report and Written Opinion from Application No. PCT/US2007/020502, filed Sep. 21, 2007.

First Communication from corresponding European patent application No. 07838659.6, dated Nov. 24, 2009.

U.S. Appl. No. 09/257,896, filed Feb. 25, 1999, Eryurek et al.

"Survey, Applications, and Prospects of Johnson Noise Thermom-

(56) **References Cited**

OTHER PUBLICATIONS

etry," by T. Blalock et al., *Electrical Engineering Department*, 1981 pp. 2-11.
"Noise Thermometry for Industrial and Metrological Applications at KFA Julich," by H. Brixy et al., *7th International Symposium on Temperature*, 1992.
"Johnson Noise Power Thermometer and its Application in Process Temperature Measurement," by T.V. Blalock et al., *American Institute of Physics* 1982, pp. 1249-1259.
"Field-based Architecture is Based on Open Systems, Improves Plant Performance", by P. Cleaveland, *I&CS*, Aug. 1996, pp. 73-74.
"Tuned-Circuit Dual-Mode Johnson Noise Thermometers," by R.L. Shepard et al., Apr. 1992.
"Tuned-Circuit Johnson Noise Thermometry," by Michael Roberts et al., *7th Symposium on Space Nuclear Power Systems*, Jan. 1990.
"Smart Field Devices Provide New Process Data, Increase System Flexibility," by Mark Boland, *I&CS*, Nov. 1994, pp. 45-51.
"Wavelet Analysis of Vibration, Part I: Theory$_1$," by D.E. Newland, *Journal of Vibration and Acoustics*, vol. 116, Oct. 1994, pp. 409-416.
"Wavelet Analysis of Vibration, Part 2: Wavelet Maps," by D.E. Newland, *Journal of Vibration and Acoustics*, vol. 116, Oct. 1994, pp. 417-425.
"Development of a Long-Life, High-Reliability Remotely Operated Johnson Noise Thermometer," by R.L. Shepard et al., *ISA*, 1991, pp. 77-84.
"Application of Johnson Noise Thermometry to Space Nuclear Reactors," by M.J. Roberts et al., *Presented at the 6th Symposium on Space Nuclear Power Systems*, Jan. 9-12, 1989.
"A Decade of Progress in High Temperature Johnson Noise Thermometry," by T.V. Blalock et al., *American Institute of Physics*, 1982 pp. 1219-1223.
"Sensor and Device Diagnostics for Predictive and Proactive Maintenance", by B. Boynton, *A Paper Presented at the Electric Power Research Institute—Fossil Plant Maintenance Conference* in Baltimore, Maryland, Jul. 29-Aug. 1, 1996, pp. 50-1-50-6.
"Detection of Hot Spots in Thin Metal Films Using an Ultra Sensitive Dual Channel Noise Measurement System," by G.H. Massiha et al., *Energy and Information Technologies in the Southeast*, vol. 3 of 3, Apr. 1989, pp. 1310-1314.
"Detecting Blockage in Process Connections of Differential Pressure Transmitters", by E. Taya et al., *SICE*, 1995, pp. 1605-1608.
U.S. Appl. No. 10/893,144, filed Jul. 2004, Brown et al.
U.S. Appl. No. 10/675,014, filed Sep. 2003, Longsdorf et al.
U.S. Appl. No. 10/744,809, filed Dec. 2003, Brown et al.
Rezabek, John, Field Device Complications, InTech, Apr. 1, 2006, HighBeam Research online database, www.highbeam.com, 2 pages.
First Office Action from corresponding Chinese patent application No. 200780035735.6 dated Mar. 15, 2011, 4 pages.
Communication from corresponding European patent application No. 07838659.6 dated Nov. 18, 2011, 7 pages.
First Office Action from corresponding Japanese patent application No. 2009530377 dated Jun. 14, 2011.
Rejection Decision from the related Chinese patent application No. 2007800300396 dated Nov. 25, 2011, 8 pgs.
Office Action from the related Japanese patent application No. 2010519967 dated Feb. 7, 2012, 11 pgs.
Rejection Decision from the corresponding Chinese patent application No. 2007800357356 dated Mar. 28, 2012, 6 pgs.
Second Office Action from the corresponding Japanese patent application No. 2009530377 dated May 22, 2012, 5 pgs.
Summons to attend oral proceeding from the corresponding European patent application No. 07838659.6 dated Jan. 29, 2013, 6 Pages.
Decision of Rejection from corresponding European patent application No. 07838659.6 dated Jul. 3, 2013.
Decision of Reexamination dated Aug. 23, 2013 in Chinese Application No. 200780035735.6 with partial English Translation. 10 pgs, 11 pages.
Reexamination Notification dated May 3, 2013, from corresponding Chinese patent application No. 2007800357356, filed Sep. 21, 2007. 9 pgs. With English translation.
Decision of Rejection dated Apr. 30, 2013, from corresponding Japanese patent application No. 2009-530377, filed Sep. 21, 2007. 4 pgs. With English translation.

* cited by examiner




Fig. 1



I
6
I
6
44
44
42
PWR
I/O
CLK
52
PROCESS SIGNAL INPUT
46
µP
48
COMP.
62
64
D/A
76
USER I/O
54
A/D
60
66
58
68
ACT.
56
SENSOR
16
18
CONTROL ELEMENT
40

Fig. 2



140
Display/Transmit
138
Generate Service Message
Corrective Service Action
160
Prediction Engine
136
152
156
Field Device Algorithm
100
150
Loop Algorithm
110
Impulse Line Algorithm
120
122
Application
124
Process Variable
126
Process Variability
128
Field Device Env.
130
Field Device Env. △
132
Overpressure/Overtemp
Field Dev. Electronics
Sensor Drift
134
135
Model Number
137
TAG
139
144
Field Device Shunt Current
Process Loop Current
Transmitter Term. V.
146
148
Plugged Line Diag.
154

FIG. 3




FIG 4



Predicted
Relative Health Predictor
100%
0%
Actual observed degraded health value
Predicted value
t_0
t_1
Time
Relative PV Health
Inputs

FIG 5

AUTOMATIC FIELD DEVICE SERVICE ADVISER

BACKGROUND OF THE INVENTION

Field devices are used in industries to control or monitor operation of a process such as an oil refinery. A field device, such as a transmitter, is typically part of a process control or monitoring loop and is located in the field to measure and transmit a process variable such as pressure, flow or temperature, for example, to control room equipment. A field device such as a valve controller can also be part of the process control loop and controls position of a valve based upon a control signal received over the process control loop, or generated internally. Other types of controllers control electric motors or solenoids, for example. The control room equipment is also part of the process control loop such that an operator or computer in the control room is capable of monitoring the process based upon process variables received from transmitters in the field and responsively controlling the process by sending control signals to the appropriate control devices. Another field device which may be part of a process control loop is a portable communicator which is capable of monitoring and transmitting process signals on the process control loop. Typically, such devices are used to configure devices which form the process control loop.

With the advent of low-power microprocessors, field devices have undergone significant changes. Years ago, a field device would simply measure a given process variable, such as temperature, and generate an analog indication in the form of a current varying between 4 and 20 (mA) to indicate the measured temperature. Currently, many field devices employ digital communication technology as well as more sophisticated control and communication techniques. Field devices often employ low-power electronics because in many installations they are still required to run on as little as 4 mA. This design requirement prohibits the use of a number of commercially available microprocessor circuits. However, even low-power microprocessors have allowed a vast array of functions for such field devices.

One new function that is enabled by microprocessor-based smart field devices is the generation of diagnostic information. Through adaptations of hardware, software, or both, today's smart field devices are able to assess the condition of process interface elements such as sensors or solenoids, assess their own circuitry, and/or even assess the relative health of the process control loop itself. Rosemount Inc., the Assignee of the present application, has contributed in this area. See, for example, U.S. Pat. Nos. 6,047,220; 5,828,567; 5,665,899; 6,017,143; 6,119,047; 5,956,663; 6,370,448; 6,519,546; 6,594,603; 6,556,145; 6,356,191; 6,601,005; 6,397,114; 6,505,517; 6,701,274; 6,754,601; 6,434,504; 6,472,710; 6,654,697; 6,539,267; 6,611,775; 6,615,149; 6,532,292; and 6,907,383.

The result of these significant developments in the area of diagnostics for microprocessor-based smart field devices is that a wealth of information is now available relative to numerous aspects of field devices in various process installations. However, considering that a given process installation may include tens, or even hundreds of such microprocessor-based field devices, an operator or technician could easily become overwhelmed by the sheer amount of diagnostic data provided during operation.

A method of processing diagnostic data in order to better utilize the finite maintenance resources of a process installation would increase the degree to which process installations could utilize the wealth of diagnostic information available today.

SUMMARY

A field device resident algorithm receives one or more diagnostic inputs and generates actionable service information. The algorithm(s) can be changed or updated after the manufacture of the field device. The actionable service information can be displayed locally or sent over a process control loop. A prediction engine can be employed to determine a period within which such service should be completed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a simplified diagram showing a process control loop including a transmitter, controller, hand-held communicator and control room.

FIG. **2** is a block diagram of a field device with which embodiments of the present invention can be practiced.

FIG. **3** is a block diagram illustrating a number of algorithmic blocks in accordance with embodiments of the present invention.

FIG. **4** is a chart illustrating variation in a health indication over time, in accordance with an embodiment of the present invention.

FIG. **5** is an illustrative chart showing how a health indication can be predicted along a degradation curve.

DETAILED DESCRIPTION

Process variables are typically the primary variables which are being controlled or monitored in a process. As used herein, process variable means any variable which describes the condition of the process such as, for example, pressure, flow, temperature, product level, pH, turbidity, vibration, position, motor current or any other characteristic of the process. A diagnostic signal, as used herein, includes information related to operation of devices and elements in the process control loop or even the process itself. For example, diagnostic signals can include valve stem position, applied torque or force, actuator pressure, pressure of a pressurized gas used to actuate a valve, electrical voltage, current, power, resistance, capacitance, inductance, device temperature, stiction, friction, full on and off positions, travel, frequency, amplitude, spectrum and spectral components, stiffness, electric or magnetic field strength, duration, intensity, motion, electric motor back emf, motor current, loop related parameters (such as control loop resistance, voltage, or current), or any other parameter which may be detected or measured in the system.

FIG. **1** is a diagram showing an example of a process control system **2** which includes process piping **4** which carries a process fluid and two wire process control loop **6** carrying loop current I. A transmitter **8**, controller **10**, which couples to a final control element in the loop such as an actuator, valve, a pump, motor or solenoid, communicator **12**, and control room **14** are all part of process control loop **6**. It is understood that loop **6** is shown in one configuration and any appropriate process control loop may be used such as a 4-20 mA loop, **2**, **3** or **4** wire loop, multi-drop loop and a loop operating in accordance with the HART®, Fieldbus or other digital or analog communication protocol. Alternatively, the process control loop may employ various wireless communication techniques. In operation, transmitter **8** senses a process variable such as flow using sensor **16** and transmits the sensed process variable over loop **6**. The process variable may be

received by controller/valve actuator **10**, communicator **12** and/or control room equipment **14**. Controller **10** is shown coupled to valve **18** and is capable of controlling the process by adjusting valve **18** thereby changing the flow in pipe **4**. Controller **10** receives a control input over loop **6** from, for example, control room **14**, transmitter **8** or communicator **12** and responsively adjusts valve **18**. In another embodiment, controller **10** internally generates the control signal based upon process signals received over loop **6**. Communicator **12** may be the portable communicator shown in FIG. **1** or may be a permanently mounted process unit which monitors the process and performs computations. Field devices include, for example, transmitter **8** (such as a 3051S transmitter available from Rosemount Inc.), controller **10**, communicator **12** and control room **14** shown in FIG. **1**. Any of field devices **8**, **10**, **12** or **14** shown in FIG. **1** may include enhanced diagnostic signal processing in accordance with embodiments of the present invention.

FIG. **2** is a block diagram of one example of a field device **40** forming part of loop **6**. Device **40** is shown generically and may comprise any field device such as transmitter **8**, controller **10**, or communicator **12**. Control room equipment **14** may comprise, for example, a DCS system implemented with a PLC and controller **10** may also comprise a "smart" motor and pump. Field device **40** includes I/O circuitry **42** coupled to loop **6** at terminals **44**. I/O circuitry has preselected input and output impedance known in the art to facilitate appropriate communication from and to device **40**. Device **40** includes microprocessor **46**, coupled to I/O circuitry **42**, memory **48** coupled to microprocessor **46** and clock **50** coupled to microprocessor **46**. Microprocessor **46** receives a process signal input **52**. Block input is intended to signify input of any process signal such as a process variable, or a control signal and may be received from loop **6** using I/O circuitry **42** or may be generated internally within field device **40**. Field device **40** is shown with a sensor input channel **54** and a control channel **56**. Typically, a transmitter such as transmitter **8** will exclusively include sensor input channel **54** while a controller such as controller **10** will exclusively include a control channel **56**. Other devices on loop **6** such as communicator **12** and control room equipment **14** may not include channels **54** and **56**. It is understood that field device **40** may contain a plurality of channels to monitor a plurality of process variables and/or control a plurality of control elements as appropriate.

Sensor input **54** includes sensor **16**, sensing a process variable and providing a sensor output to amplifier **58** which has an output which is digitized by analog to digital converter **60**. Input **54** is typically used in transmitters such as transmitter **8**. Compensation circuitry **62** compensates the digitized signal and provides a digitized process variable signal to microprocessor **46**. In one embodiment, input **54** comprises a diagnostic channel which receives a diagnostic signal.

When field device **40** operates as a controller such as controller **8**, device **40** includes control channel **56** having control element **18** such as a valve, for example. Control element **18** is coupled to microprocessor **46** through digital to analog converter **64**, amplifier **66** and actuator **68**. Digital to analog converter **64** digitizes a command output from microprocessor **46** which is amplified by amplifier **66**. Actuator **68** controls the control element **18** based upon the output from amplifier **66**. In one embodiment, actuator **68** is coupled directly to loop **6** and controls a source of pressurized gas (not shown) to position control element **18** in response to the current I flowing through loop **6**. In one embodiment, controller **10** includes control channel **56** to control a control element and also includes sensor input channel **54** which provides a diagnostic signal such as valve stem position, force, torque, actuator pressure, pressure of a source of pressurized air, etc.

In one embodiment, I/O circuitry **42** provides a power output used to completely power other circuitry in process device **40** using power received from loop **6**. Typically, field devices such as transmitter **8**, or controller **10** are powered off the loop **6** while communicator **12** or control room **14** has a separate power source. As described above, process signal input **52** provides a process signal to microprocessor **46**. The process signal may be a process variable from sensor **16**, the control output provided to control element **18**, a diagnostic signal sensed by sensor **16**, or a control signal, process variable or diagnostic signal received over loop **6**, or a process signal received or generated by some other means such as another I/O channel.

A user I/O circuit **76** is also connected to microprocessor **46** and provides communication between device **40** and a user. Typically, user I/O circuit **76** includes a display and audio for output and a keypad for input. Typically, communicator **12** and control room **14** includes I/O circuit **76** which allows a user to monitor and input process signals such as process variables, control signals (setpoints, calibration values, alarms, alarm conditions, etc.) along with rules, sensitivity parameters and trained values. A user may also use circuit **76** in communicator **12** or control room **14** to send and receive such process signals to transmitter **8** and controller **10** over loop **6**. Further, such circuitry could be directly implemented in transmitter **8**, controller **10** or any other process device **40**.

Microprocessor **46** acts in accordance with instructions stored in memory **48**. Various instructions stored within memory **48** allow microprocessor **46** to execute one or more algorithms within the field device in accordance with embodiments of the present invention. In general, the algorithms allow the field device to obtain one or more diagnostic inputs and generate a service-related recommendation output. Diagnostic information useful as input to the algorithm(s) can include any diagnostic information that has been currently developed, or will be developed. In contrast to types of diagnostic output that have been provided in the past, the field device service advisor recommends a particular service to be performed relative to the field device, components connected to the field device, to other field devices, or to the process control loop itself.

As can be imagined, if the tens or hundreds of field devices in a given process installation were providing various types of diagnostic information over process control loops, it could inundate an operator with such a vast amount of information that he or she may not be able to adequately determine what type or quantity of corrective action should be instituted with respect to a give piece or pattern of diagnostic information. Moreover, the sheer volume of diagnostic information itself could consume valuable communication bandwidth on the process control loop thereby reducing, or degrading the ability for process variable information to be communicated timely and effectively. Embodiments of the present invention preferably include a field device-resident algorithm that is able to take one or more inputs, including diagnostic inputs, and provide a service action recommendation. In this way, the field devices themselves can make a number of decisions about what types, quantity and timing of corrective service actions should be taken. Then, this singular message can be displayed by the field device, or communicated to a control room.

FIG. **3** is a diagrammatic view of various service adviser algorithms in accordance with embodiments of the present invention. Preferably, each of algorithms **100**, **110** and **120**

are used by microprocessor **46** executing suitable instructions stored within memory **48**. While algorithms **100**, **110** and **120** are illustrated and described separately, such illustration is for clarity, and, in fact, all or any algorithms could be combined, as appropriate.

Field device algorithm **100** takes any suitable inputs related to the field device itself. Examples of suitable inputs include, but are not limited to, application input **122** (such as flow, level or pressure); process variable input **124**; process variability input **126**; field device environmental input **128**; field device environmental change input **130**; overpressure/overtemp input **132**; field device electronics input **134**; sensor drift **135**; field device model number input **137** and field device tag input **139**.

An example of process variable input **124** generally includes the value, either currently or historically, or both of the process variable of the field device. For example, if the field device is a pressure transmitter, then process variable **124** could be the actual process pressure value, history of values or any combination thereof.

Process variability input **126** is generally an indication of the variability of the process variable over a specified period. For example, process variability input may be a standard deviation calculation on an historical range of process variable values, or simply the difference between a local minima and local maxima of the process variable observed within a specified period of time.

Field device environmental input **128** includes any suitable parameter that may bear upon the operation of the field device itself. Examples of such parameters include the temperature of the field device itself, as measured by an internal temperature sensor, the relative humidity proximate the exterior of the field device, radio frequency interference that may be measured or detected by the field device, or any other external influences to the field device that can be measured, and that can bear upon the field device operation.

Input **130** is preferably based upon a mathematical operation on a history of values provided by input **128**. For example, if input **128** includes a measurement of the temperature of the field device itself, input **130** can simply be an indication of whether the temperature of the field device is changed by a specific amount within a specific time.

Input **132** is preferably a measure of whether a field device is exposed to any relative extremes of the process variable. For example, if the field device is a pressure transmitter, input **132** is an indication of whether the pressure transmitter was subjected to an overpressure event, and if so, the duration and number of such overpressure events.

Input **134** can be generated by diagnostics run on or by the field device electronics itself. While not specifically illustrated, field device algorithm **100** can include other suitable diagnostic inputs relative to the field device. Moreover, as the state of field device diagnostics advances, it is contemplated that other types of field device diagnostic information could be provided to algorithm **100**.

An example of sensor drift **135** includes an indication that the sensor, when subjected to a known characteristic, such as temperature for a temperature sensor, exhibits a reading that has changed over time. Sensor drift can occur as a sensor begins to wear, and some level of drift may be acceptable, while still indicating that service should be performed.

An example of field device model number input **137** includes data that is provided to algorithm **100** relative to the model number of the field device itself. Many field device manufacturers provide model numbers that may be parsed, at least to some degree, to provide a description of the field device. For example, a particular model code may describe the material of construction of the field device, the range of the field device, as well as any performance enhancements present in the field device. Thus, algorithm **100** may take such information into account during processing and modify the service message accordingly.

An example of field device tag input **139** is any data provided to algorithm **100** by a user, either locally or through remote means, that is an indication of a type of service performed by the field device. For example, pressure and differential pressure transmitters measure pressure, flow or level. The tagging convention may call for pressure applications to be tagged "PT", for example PT-**101**. Flow application may be tagged "FT" and level applications tagged "LT."

Field device algorithm **100** generally takes one or more of inputs **122**, **124**, **126**, **128**, **130**, **132**, **134**, **135**, **137** and **139**, and processes such inputs to generate actionable information regarding service on line **136**. The specifics of algorithm **100** can be developed via empirical means through controlled testing, and/or can include specific rules relative to conditions of one or more inputs that generate actionable information regarding service. For example, testing may show that a combination of high process variability **126** and high sensor temperature requires service in the form of "inline zero of the field device every X hours." This actionable service information can then be reported along line **136** to block **138** which may simply display or transmit the service information at block **140**.

Loop algorithm **110** takes as inputs field device shunt current diagnostic **144**; process loop current diagnostic input **146**; field device terminal voltage **148**; and potentially any output provided by field device algorithm **100**, as illustrated in phantom at line **150**.

An example of field device shunt current diagnostics **144** includes a measurement of the current consumed by field device **144** in its normal operations.

An example of process loop current diagnostics input **146** includes measurement of current able to be provided over the process communication loop to which the field device is connected.

An example of field device terminal voltage diagnostic input **148** includes measurement of the voltage across the field device terminals where the field device couples to the process communication loop.

As illustrated by the bi-directional arrows on phantom line **150**, loop algorithm **110** may provide an output that is input to field device algorithm **100**. Loop algorithm **110** takes one or more inputs **144**, **146**, **148** and **150**, and generates actionable information regarding service of the loop along line **152**.

Impulse line algorithm **120** generally receives plugged line diagnostic **154** but may receive any other information that may reasonably indicate a plugged impulse line condition. Impulse lines are conduits that convey pressure from an isolator diaphragm to a pressure sensor module. If such lines become plugged, or otherwise damaged, their ability to convey pressure from the isolation diaphragm to the sensor module may also become diminished. The ability to detect this condition is important. As illustrated in FIG. **3**, impulse line algorithm line **120** may take an input from, or provide an output to, any of field device algorithm **100** and loop algorithm **110**. Impulse line algorithm **120** provides actionable information regarding service of the impulse lines along line **156**.

Examples of actionable service information provided by algorithms **100**, **110** or **120** include: in-line zero field devices; blow down impulse lines; shop calibrate; check wiring/power supply; clear impulse lines; shop/factory calibrate; check

capillary system; or any other suitable user-defined action that may be provided by the algorithms.

In accordance with an embodiment of the present invention, the algorithms themselves can be modified or updated as appropriate. Accordingly, as new relationships between field device diagnostic information and actionable service recommendations are correlated, such new correlations between the inputs and the actionable service outputs can be updated to the field devices. These updates can take numerous forms. The local ROM of the field device may be exchanged; updated file information may be transmitted to the field device over the process control loop; or a secondary communication interface, such as a wireless communication link with a field maintenance device.

Each of lines **136**, **152** and **156** provides service information to module **138**. Module **138** may combine the information into a signal message, and/or may engage predication engine **160** to determine when such actionable service information should be effected. For example, if field device algorithm **100** provides an indication that a particular field device service action is required, prediction engine **160** may be consulted to provide a time period within which such action should be effected.

Additionally, or in the alternative, module **138** may combine, or otherwise process, the information output over one or more of lines **136**, **152** and **156** to generate an overall "health" indication or metric. This overall health indication can be displayed locally at the device, communicated over the process control loop, and/or used in conjunction with prediction engine **160** to calculate a point in the future when the health indication will reach a threshold beyond which corrective action is necessary.

Prediction engine **160** can include or utilize any known algorithmic and/or mathematical techniques to predict, based on historical data, programmatic data, empirical data, or any combination thereof, when a particular service action should be required. Examples of known techniques which can be employed in or by prediction engine **160** include the use of polynomial curve fits, neural networks, threshold circuitry, and/or fuzzy logic. Further detail regarding these techniques may be found in U.S. Pat. No. 6,701,274.

The polynomial curve fit technique employs empirical models or polynomial curve fitting in microprocessor **46**. A polynomial-like equation which has a combination of any suitable input signals as the variable terms in the polynomial, together with constants stored in memory **48** can be used for computing a future time period within which a particular service action should be effected. If field device memory **48** is limited, the constants and/or equation may be sent over process communication loop **6**.

Neural networks provide another useful technique for prediction engine **160**. In particular, the neural network can be implemented with a multi-layer neural network. Although a number of training algorithms can be used to develop a neural network model for different goals, one embodiment includes using the known back propagation network (BPN) to develop neural network modules which will capture the non-linear relationship among a set of inputs and outputs. The number of inputs to the neural network may differ depending on the complexity of the system, and any one or combination of multiple inputs can be used.

Threshold circuitry can also be used to provide important functions for prediction engine **160**. In particular, microprocessor **46** may consult with, or include such threshold circuitry. Rules resident within, or executed by microprocessor **46** may be implemented in either digital or analog circuitry. For example, the following is a sample if-then rule for spikes in pressure sensor output from a pressure sensor: if the number of spikes detected since commissioning multiplied by a value in memory **48** is greater than an upper threshold, then indicate that the pressure sensor must be replaced within X days. This is merely one illustrative example of threshold circuitry being used in conjunction with if-then rules to facilitate prediction engine **160**.

Fuzzy logic is yet another technique that can be employed for prediction engine **160**. In particular, using fuzzy logic, input data can be processed as a function of a membership function which is selected based upon a value of the input data. Such fuzzy logic techniques are well suited for inputs which fall in a non-linear or non-binary fashion.

Using prediction engine **160**, the field device can generate actionable service information augmented with an interval within which the service action should be completed. Specifically, service notifications, such as blow down impulse line can be augmented to, "blow down impulse line within X hours." These services notifications generally take the form of take "X" action within "Y" time. The time attribute can recite a specific incremental time in the future, such as "within six hours" can recite an interval such as "daily" or can recite a specific time in the future. It is also preferred that each field device be shipped with default settings in memory **48** such that the service adviser algorithm will generate an initial startup recommendation action such as "factory calibrate unit in 60 months."

As the field device gains successful runtime, it is also contemplated that the prediction algorithm can be automatically modified such that the successful runtime is taken into account. Thus, a given field device that notes a diagnostic input that has a recommended service action may not recommend the service action as urgently if the field device has run successfully for ten years, in comparison to field device that is just starting its field operation.

FIG. **4** is a chart illustrating variation in a health indication over time, in accordance with an embodiment of the present invention. Health indication **200** is compared with index **202** to determine whether the overall health necessitates corrective action. Index **202** can be established in any suitable manner, but is preferably established using High Accelerated Life Testing (HALT) with an index related thereto stored in each field device. As illustrated in FIG. **4**, the health indication experiences two excursions beyond index **202**. Such excursions may be caused by any of a variety of variables, or combinations thereof. Each field device preferably includes rules that cause the field device to report degradation if any such excursions are experienced, or the field device may report degradation after a set number or duration of excursions have occurred.

FIG. **5** is an illustrative chart showing how health indication **200** can be predicted along a degradation curve. Thus, an actual health indication observed at time to can be used to calculate that the health indication will reach a certain level at time t_1. Thus, the actionable service information can include a time in the future when one or more actions should be performed. By calculating the degradation slope, even a first order mathematical model can be used to predict when the health indication will reach a certain threshold. Prediction engine **160** can use any suitable technique, or combination of techniques listed above, implemented in software, hardware, or any combination thereof.

Embodiments of the present invention generally provide a number of advantages in the field of diagnostics for smart microprocessor-based field devices. Embodiments generally provide a user with actionable information regarding service versus ambiguous raw alarm data. Further, users are provided

with predictive information so that action may be taken before the process variable information is too bad to use for control. Further still, the various algorithms can be developed and refined empirically via a control test program. Further still, the algorithm is preferably resident in field device memory which reduces host dependency. Finally, the recommended maintenance action can be reported in any suitable manner, including via enhanced Electronic Device Description Language (EDDL) technology.

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

What is claimed is:

1. A field device comprising a process variable transmitter, comprising:

a process variable sensor configured to sense a process variable of an industrial process;

a microprocessor;

a memory operably coupled to the microprocessor;

a plurality of diagnostic inputs operably coupled to the microprocessor;

wherein the microprocessor implements field device resident algorithms based upon instructions stored in the memory including:

a plurality of diagnostic algorithms based upon the plurality of diagnostic inputs, wherein the plurality of diagnostic algorithms provide a service information output indicative of actionable service information comprising a corrective service action which should be performed based upon the plurality of diagnostic inputs;

a prediction engine implemented by a prediction algorithm configured to determine a service interval within which the corrective service action should be performed, the service interval based upon a health indication degradation curve used to predict when a health indication will reach a threshold level and wherein the prediction algorithm is modified based upon successful runtime of the process variable transmitter;

a service message module configured to generate a service message based upon the service interval and the corrective service action; and

I/O circuitry configured to transmit information related to the sensed process variable and further configured to transmit the service message including the corrective service action and an augmented service interval to another location.

2. The field device of claim **1**, including a local display coupled to the microprocessor which displays the service message including the corrective service action and wherein the corrective service action is related to at least one of the field device itself, a component coupled to the field device, a second field device, and a process control loop.

3. The field device of claim **1**, wherein the at least one of the diagnostic inputs includes a field device diagnostic input.

4. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes application information.

5. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes a process variable.

6. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes process variability.

7. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes a characteristic of an environment of the field device.

8. The field device of claim **1**, wherein the at least one of the diagnostic inputs also includes relative changes in an environment of the field device.

9. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes an indication of exposure of the field device to extremes in process variables.

10. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes a diagnostic of electronics of the field device.

11. The field device of claim **2**, wherein the at least one of the diagnostic inputs includes sensor drift.

12. The field device of claim **1**, wherein the at least one of the diagnostic inputs includes a loop diagnostic input.

13. The field device of claim **12**, wherein the at least one of the diagnostic inputs includes field device shunt current.

14. The field device of claim **12**, wherein the at least one of the diagnostic inputs includes process loop current.

15. The field device of claim **12**, wherein the at least one of the diagnostic inputs includes field device terminal voltage.

16. The field device of claim **1**, wherein the at least one of the service-related recommendation output is transmitted over a process control loop.

17. The field device of claim **16**, wherein the at least one service-related recommendation output is transmitted using enhanced Electronic Device Description Language technology.

18. The field device of claim **1**, wherein one of the plurality of diagnostic algorithms comprises a field device diagnostic algorithm.

19. The field device of claim **1**, wherein one of the plurality of diagnostic algorithms comprises a loop diagnostic algorithm.

20. The field device of claim **1**, wherein one of the plurality of diagnostic algorithms comprises an impulse line diagnostic algorithm.

21. The field device of claim **1**, wherein the prediction algorithm is implemented using a polynomial curve fit.

22. The field device of claim **1**, wherein the prediction algorithm is implemented using a neural network.

23. The field device of claim **1**, wherein the prediction algorithm is implemented using rules.

24. The field device of claim **1**, wherein the prediction algorithm is implemented using fuzzy logic.

25. The field device of claim **1**, wherein the health indication degradation curve is implemented using a mathematical model.

* * * * *