




US 20150288438A1

(19) **United States**(12) **Patent Application Publication**  
**MALTSEV et al.**(10) **Pub. No.: US 2015/0288438 A1**(43) **Pub. Date: Oct. 8, 2015**(54) **MODULAR ANTENNA ARRAY WITH RF AND  
BASEBAND BEAMFORMING****Publication Classification**(71) Applicant: **INTEL CORPORATION**, Santa Clara,  
CA (US)(72) Inventors: **ALEXANDER MALTSEV**, Nizhny  
Novgorod (RU); **ALI S. SADRI**, San  
Diego, CA (US); **RICHARD B.  
NICHOLLS**, Portland, OR (US); **REZA  
AREFI**, Great Falls, VA (US); **ALEXEI  
DAVYDOV**, Nizhny Novgorod (RU);  
**VADIM SERGEYEV**, Nizhny  
Novgorod (RU)(73) Assignee: **Intel Corporation**, Santa Clara, CA  
(US)(21) Appl. No.: **13/994,223**(22) PCT Filed: **Dec. 10, 2012**(86) PCT No.: **PCT/IB2012/003075**

§ 371 (c)(1),

(2) Date: **Jun. 14, 2013**(51) **Int. Cl.****H04B 7/06** (2006.01)**H04W 16/28** (2006.01)**H04L 27/18** (2006.01)(52) **U.S. Cl.**CPC ..... **H04B 7/0617** (2013.01); **H04L 27/18**  
(2013.01); **H04W 16/28** (2013.01)(57) **ABSTRACT**

Generally, this disclosure provides systems and methods for a modular antenna array using radio frequency (RF) and base-band (BB) beamforming. A system may include a plurality of antenna modules, each of the antenna modules further including an array of antenna elements coupled to an RF beamforming circuit, the RF beamforming circuit to adjust phase shifts associated with the antenna elements to generate an antenna beam associated with the antenna module; and a central beamforming module coupled to each of the antenna modules, the central beamforming module to control the antenna beam associated with each of the antenna modules and to generate signal adjustments relative to each of the antenna modules, wherein the arrays of antenna elements of the antenna modules combine to operate as a composite antenna beamforming array.






FIG. 1




FIG. 2




FIG. 3

400




FIG. 4

500




FIG. 5





FIG. 6



700a



700b




FIG. 7






FIG. 8




FIG. 9

1000




FIG. 10



## MODULAR ANTENNA ARRAY WITH RF AND BASEBAND BEAMFORMING

### FIELD

**[0001]** The present disclosure relates to antenna array beamforming, and more particularly, to a modular architecture for antenna arrays using radio frequency (RF) and baseband beamforming.

### BACKGROUND

**[0002]** Electronic devices, such as laptops, notebooks, netbooks, personal digital assistants (PDAs) and mobile phones, for example, increasingly tend to include a variety of wireless communication capabilities operating at increased data rates. The wireless communication systems used by these devices are expanding into the higher frequency ranges of the communication spectrum, such as, for example, the millimeter wave region and, in particular, the 60 GHz band. Propagation losses and attenuation tend to increase at these higher frequencies, however, and it can become difficult to implement antenna systems in a manner that provides the desired gain and spatial coverage.

**[0003]** Communication in this band at distances of approximately 50 meters or more, as for example outdoors or in large spaces, typically requires the use of highly directional antennas with gains of 30-40 dB or more to compensate for the attenuation losses. Additionally, there is often a requirement for relatively wide sector coverage to include other devices and stations regardless of location. Some communication systems employ phased array beamforming to steer a relatively narrow beam in a desired direction, but this approach typically requires a number of antenna elements to be coupled to an RF integrated circuit (RFIC) processing chip, where the gain of the phased array is related to the number of antenna elements. It is, however, generally difficult and expensive to couple a sufficient number of antenna elements to provide the necessary gain since the signal routing (feeding lines) between the antenna elements and the RFIC become too complex and result in increased signal attenuation. The cost of these antenna arrays typically grows disproportionately with the number of antenna elements in the array.

### BRIEF DESCRIPTION OF THE DRAWINGS

**[0004]** Features and advantages of embodiments of the claimed subject matter will become apparent as the following Detailed Description proceeds, and upon reference to the Drawings, wherein like numerals depict like parts, and in which:

**[0005]** FIG. 1 illustrates a top level system diagram of one exemplary embodiment consistent with the present disclosure;

**[0006]** FIG. 2 illustrates a block diagram of one exemplary embodiment consistent with the present disclosure;

**[0007]** FIG. 3 illustrates a block diagram of another exemplary embodiment consistent with the present disclosure;

**[0008]** FIG. 4 illustrates exemplary phase adjustments consistent with an embodiment of the present disclosure;

**[0009]** FIG. 5 illustrates exemplary phase adjustments consistent with another embodiment of the present disclosure;

**[0010]** FIG. 6 illustrates exemplary beam forming consistent with an embodiment of the present disclosure;

**[0011]** FIG. 7 illustrates exemplary beam forming consistent with another embodiment of the present disclosure;

**[0012]** FIG. 8 illustrates a block diagram of another exemplary embodiment consistent with the present disclosure;

**[0013]** FIG. 9 illustrates a flowchart of operations of an exemplary embodiment consistent with the present disclosure; and

**[0014]** FIG. 10 illustrates a platform of one exemplary embodiment consistent with the present disclosure.

**[0015]** Although the following Detailed Description will proceed with reference being made to illustrative embodiments, many alternatives, modifications, and variations thereof will be apparent to those skilled in the art.

### DETAILED DESCRIPTION

**[0016]** Generally, this disclosure provides systems and methods for antenna array beamforming using a modular architecture to synthesize larger composite antenna arrays from smaller sub-array antenna modules. A combination of RF beamforming in the sub-array antenna modules and baseband beamforming between sub-array antenna modules provides increased beamforming capability, for example, in beam width, gain, coverage and beam steering. The system may be configured to operate in the millimeter wave (mm-wave) region of the RF spectrum and, in particular, the 60 GHz region associated with the use of, for example, wireless personal area network (WPAN) and wireless local area network (WLAN) communication systems.

**[0017]** FIG. 1 illustrates a top level system diagram **100** of one exemplary embodiment consistent with the present disclosure. A modular antenna array system **102** is shown, which may be configured to transmit and/or receive data in the mm-wave region of the RF spectrum. In some embodiments the system **102** may form part of a wireless communication platform, such as, for example, a mobile phone, a laptop, a tablet or a base station. The system **102** may be configured to generate an antenna beam pattern **108**, which, in some embodiments, may be a steerable beam. The system **102** may include a plurality of RF beamforming antenna modules **104** coupled to a central beamforming module **106** through transmit (Tx) and receive (Rx) data links **112** and control links **110**, the operations of which will be explained in greater detail below. In some embodiments, the central beamforming module **106** may operate at baseband, intermediate frequency (IF) or at RF. The data to be transmitted or received by system **102** may be provided through a data port that couples the central beamforming module **106** to a processor or any other suitable system configured to generate or receive data.

**[0018]** FIG. 2 illustrates a block diagram **200** of one exemplary embodiment consistent with the present disclosure. RF beamforming antenna modules **104** are shown to include an array of antenna elements **202** coupled to an RF beamformer RFIC **212** through feed lines **204** which may be micro-strip feed lines. RFIC **212** includes an array of phase shifting circuits **208** coupled to a summer/splitter circuit **214**. The phase shifter circuits **208** are configured to adjust the phase of the RF signal received from (or transmitted to) the associated antenna element **202**. The amount of the phase shift may be determined by control signals **206** that are supplied to the phase shifter circuits. The control signals **206** may be weighting coefficients that are generated within the RFIC **212** and/or derived from signals on control links **110** received from the central beamforming module **106**. The phase shift adjustments may determine and control the beam width, gain and/or direction of the antenna beam formed by the array of antenna elements **202**. In the case of a received signal, the summer/



splitter circuit **214** sums the received phase shifted signals and provides the sum to the central beamforming module **106** over data links **112**. In the case of a transmitted signal, the summer/splitter circuit **214** splits the signal provided from the central beamforming module **106** over data links **112** and couples the split signal to each of the phase shifter circuits **208**.

[0019] The signals on control links **110** received from the central beamforming module **106**, may further adjust the weighting coefficients to cause the RF beamforming antenna modules **104** to perform as a single larger antenna array with increased beamforming capability compared to the individual RF beamforming antenna modules **104**, as will be explained in greater detail below. In some embodiments, central beamforming module **106** may divide the available RF beamforming antenna modules **104** into sub-groups where each sub-group may be individually steered to different directions and/or used for different purposes (e.g., different carrier signal frequencies). In some embodiments, the signal being transmitted or received may include multiple frequency components and the central beamforming module may be configured to apply different signal adjustments for each of the multiple frequency components of the signal.

[0020] Frequency up-conversion and down-conversion (not shown) may be performed on the transmit and receive signals (respectively) to convert between baseband (or IF) and RF. In a preferred embodiment, the up/down frequency conversion may be performed by a module included in the RFIC **212**. In some other embodiments, the frequency conversion may be performed by a module deployed between the RFIC **212** and the central beamforming module **106**.

[0021] FIG. 3 illustrates a block diagram **300** of another exemplary embodiment consistent with the present disclosure. A baseband processor **304**, which includes central beamforming module **106**, is shown coupled to a planar array **302** of RF beamforming antenna modules **104** through data links **112** and control links **110**. This example configuration, of a planar array, may be particularly advantageous for beam steering in two dimensions (e.g., azimuth and elevation).

[0022] Although only four RF beamforming antenna modules **104** are shown for simplicity, any number of such modules **104** may be employed to increase overall antenna gain and capability. Since the RF beamforming antenna modules **104** are coupled through data links **112** that may operate at lower frequencies (e.g., baseband or IF), the length of the data link signal routing is not constrained to the same extent as the feed lines for antenna elements **202**, which limits the number of antenna elements **202** in a given module array. For example, a typical antenna array RFIC may be limited to an array size of 8x8 antenna elements **202** that are capable of providing an antenna beam gain of 15-20 dB. Communications in the mm-wave region, however, may require antenna gains on the order of 30-40 dB to compensate for the higher signal attenuation associated with that frequency range. Such gains may be achieved by employing additional RF beamforming antenna modules **104**.

[0023] FIG. 4 illustrates exemplary phase adjustments **400** consistent with an embodiment of the present disclosure. In this illustration the antenna beam **108** is steered in the indicated direction. RF beamforming antenna modules **104** are configured in a linear array and each module **104** may perform a local phase adjustment to the signal to create a local phase distribution **404** in the desired beam direction. Central beamforming module **106** may provide additional inter-mod-

ule phase adjustments **406** to create a desired composite phase distribution **402** such that the signal phases across the antenna elements of the RF beamforming antenna modules **104** are aligned to create a composite antenna array having greater gain.

[0024] FIG. 5 illustrates exemplary phase adjustments **500** consistent with another embodiment of the present disclosure. This illustration is similar to that of FIG. 4, however the RF beamforming antenna modules **104** are configured in a circular array, only half of which is shown for simplicity. The antenna beam **108** is steered in the indicated direction and RF beamforming antenna modules **104** may perform a local phase adjustment to the signal to create local phase distributions **404** in the desired beam direction. Here again, central beamforming module **106** may provide additional inter-module phase adjustments **406** to create a desired composite phase distribution **402** such that the signal phases across the antenna elements of the RF beamforming antenna modules **104** are aligned to create a composite antenna array having greater gain. In some embodiments, RF beamforming antenna modules **104b**, which are physically oriented in a direction away from the desired beam direction **108**, may be controlled by central beamforming module **106** such that they are switched off or employed for another purpose.

[0025] FIG. 6 illustrates exemplary beam forming **600a** and **600b** consistent with an embodiment of the present disclosure. Shown are side views of the composite antenna array with beams pointing upward out of the plane of the array. The antenna aperture of the composite antenna array may increase in linear proportion to the number of sub-arrays (e.g., RF beamforming antenna modules **104**) being employed. A larger antenna aperture is associated with a narrower beam width and higher gain. The dashed lines of **600a** indicate example sectors **602**, **604** and **606** that are associated with possible beam directions and beam widths that may be synthesized with each of the three individual sub-arrays **104**. A composite array, formed from the three sub-arrays, may be capable of generating a beamwidth that is 3 times narrower and which may be scanned within a sector **608**, **610**, **612**. The scanning may be accomplished through adjustment of the inter-module phasing, for example, by adjustment of the weighting coefficients provided by central beamforming module **106**.

[0026] In an alternative embodiment **600b**, the composite antenna array may be configured to receive or transmit signals throughout a wide sector that is a combination of individual sectors **614**, **616** and **618**, each generated by one of the sub-arrays **104**. In this case, each sub-array **104** is configured to cover a different sector and central beamforming module **106** sums the sectors together. This may be useful, for example, when it is desirable to broadcast a signal over a wide area. Additional inter-module phase adjustments may be provided by central beamforming module **106** to generate quasi-spherical (or quasi-cylindrical) phase distribution across the composite antenna to generate a smoother antenna pattern.

[0027] FIG. 7 illustrates exemplary beam forming **700a** and **700b** consistent with another embodiment of the present disclosure. Shown are alternative configuration and form factors for the composite antenna array. A substantially spherical (or cylindrical) 360-degree pattern **702** may be achieved with parallel planes of sub-arrays **104** directed in opposite directions. A triangular arrangement **704** may also be employed to provide an omni-directional coverage mode. Additionally, and as previously described, narrow beams **706** may be



steered through any of the sectors. Changes in beam-steering and/or coverage may be accomplished by updating weighting coefficients resulting in increased speeds for mode switching and beam steering.

[0028] FIG. 8 illustrates a block diagram 800 of another exemplary embodiment consistent with the present disclosure. An alternative configuration is shown with sub-array modules 104 including end-fire antenna elements 202. This may provide a greater density of antenna elements since they are arranged linearly, rather than over a planar area, and it enables the stacking of sub-array modules 104 as shown.

[0029] The use of a composite antenna array enables an increase in signal transmission power through the deployment of an increased number of sub-array modules as opposed to an increase in the size of the power amplifier on each sub-array module. This permits a relaxation in the power level and linearity requirements of the power amplifiers and thus a relaxation in the manufacturing technology requirements of the RFIC modules. In some embodiments, therefore, the RFIC modules may be implemented in complementary metal-oxide semiconductor (CMOS) technology with a reduction in manufacturing cost.

[0030] FIG. 9 illustrates a flowchart of operations 900 of an exemplary embodiment consistent with the present disclosure. At operation 910, phase shifts associated with antenna elements are adjusted. The antenna elements are included in an array of antenna elements coupled to an RF beamforming circuit. The adjustments are performed by the RF beamforming circuit to generate an antenna beam associated with an antenna module. The antenna module includes the array of antenna elements and the RF beamforming circuit. At operation 920, a central beamforming module is coupled to a plurality of the antenna modules. At operation 920, the antenna beam associated with each of a plurality of antenna modules, coupled to a central beamforming module, is controlled by the central beamforming module. At operation 930, signal adjustments relative to each of the antenna modules are generated. The generating is performed by the central beamforming module, such that the arrays of antenna elements of the antenna modules combine to operate as a composite antenna beamforming array.

[0031] FIG. 10 illustrates a system diagram 1000 of a platform consistent with an exemplary embodiment of the present disclosure. Platform 110 may be a mobile communication device, such as, for example, a smartphone, a tablet, a laptop computing device or any other device configured to transmit or receive wireless signals. In some embodiments, platform 1010 may be a wireless base station. Platform 1010 may include a processor 1020, memory 1030, an input/output (I/O) system 1040, a wireless communication interface 1050 and a modular antenna array system 102. The modular antenna array system 102 may be configured to generate an antenna beam pattern 108 in a desired direction as described previously. Any number of platforms 1010 may transmit or receive signals through a wireless network or any suitable communication medium.

[0032] Embodiments of the methods described herein may be implemented in a system that includes one or more storage mediums having stored thereon, individually or in combination, instructions that when executed by one or more processors perform the methods. Here, the processor may include, for example, a system CPU (e.g., core processor) and/or programmable circuitry. Thus, it is intended that operations according to the methods described herein may be distributed

across a plurality of physical devices, such as processing structures at several different physical locations. Also, it is intended that the method operations may be performed individually or in a subcombination, as would be understood by one skilled in the art. Thus, not all of the operations of each of the flow charts need to be performed, and the present disclosure expressly intends that all subcombinations of such operations are enabled as would be understood by one of ordinary skill in the art.

[0033] The storage medium may include any type of tangible medium, for example, any type of disk including floppy disks, optical disks, compact disk read-only memories (CD-ROMs), compact disk rewritables (CD-RWs), digital versatile disks (DVDs) and magneto-optical disks, semiconductor devices such as read-only memories (ROMs), random access memories (RAMs) such as dynamic and static RAMs, erasable programmable read-only memories (EPROMs), electrically erasable programmable read-only memories (EEPROMs), flash memories, magnetic or optical cards, or any type of media suitable for storing electronic instructions.

[0034] “Circuitry”, as used in any embodiment herein, may comprise, for example, singly or in any combination, hardwired circuitry, programmable circuitry, state machine circuitry, and/or firmware that stores instructions executed by programmable circuitry. An app may be embodied as code or instructions which may be executed on programmable circuitry such as a host processor or other programmable circuitry. A module, as used in any embodiment herein, may be embodied as circuitry. The circuitry may be embodied as an integrated circuit, such as an integrated circuit chip.

[0035] Thus, the present disclosure provides systems, methods and platforms for antenna array beamforming using a modular architecture to synthesize larger composite antenna arrays from smaller sub-array antenna modules.

[0036] The system may include a plurality of antenna modules, each of the antenna modules including an array of antenna elements coupled to an RF beamforming circuit, the RF beamforming circuit configured to adjust phase shifts associated with each of the antenna elements to generate an antenna beam associated with the antenna module. The system of this example may also include a central beamforming module coupled to each of the antenna modules, the central beamforming module configured to control the antenna beam associated with each of the antenna modules and to generate signal adjustments relative to each of the antenna modules, and the arrays of antenna elements of the antenna modules combine to operate as a composite antenna beamforming array.

[0037] Another example system includes the forgoing components and the signal adjustments include signal magnitude adjustments and signal phase adjustments.

[0038] Another example system includes the forgoing components and the central beamforming module is a base-band processor, an intermediate frequency processor and/or an RF processor.

[0039] Another example system includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming array to generate a composite antenna beam, the composite antenna beam having a higher gain and narrower beamwidth than the antenna beams associated with the antenna modules.

[0040] Another example system includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming



array to generate a composite antenna beam, the composite antenna beam having a wider beamwidth than the antenna beams associated with the antenna modules.

[0041] Another example system includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming array to generate a composite antenna beam and to steer the composite antenna beam from a first direction to a second direction.

[0042] Another example system includes the forgoing components and the central beamforming module is further configured to segment the composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array configured to generate an independently steerable antenna beam.

[0043] Another example system includes the forgoing components and the central beamforming module is further configured to apply a plurality of signal adjustments, each of the signal adjustments associated with one of a plurality of signal frequency components.

[0044] Another example system includes the forgoing components and the antenna modules are disposed in one or more planes, the planes oriented in different directions relative to each other.

[0045] Another example system includes the forgoing components and the antenna elements and the antenna modules are arranged in a linear end-fire pattern.

[0046] Another example system includes the forgoing components and the RF beamforming circuits are RFICs and the antenna modules are configured to operate in a millimeter wave frequency range.

[0047] Another example system includes the forgoing components and the antenna elements are coupled to the RF beamforming circuit by micro-strip feeding lines.

[0048] According to another aspect there is provided a method. The method may include coupling an array of antenna elements to an RF beamforming circuit. The method of this example may also include adjusting phase shifts associated with each of the antenna elements, the adjusting performed by the RF beamforming circuit to generate an antenna beam, the antenna beam associated with an antenna module, the antenna module including the array of antenna elements and the RF beamforming circuit. The method of this example may further include coupling a central beamforming module to a plurality of the antenna modules. The method of this example may further include controlling the antenna beam associated with each of the antenna modules, the controlling performed by the central beamforming module. The method of this example may further include generating signal adjustments relative to each of the antenna modules, the generating performed by the central beamforming module, and the arrays of antenna elements of the antenna modules combine to operate as a composite antenna beamforming array.

[0049] Another example method includes the forgoing operations and the signal adjustments include signal magnitude adjustments and signal phase adjustments.

[0050] Another example method includes the forgoing operations and further includes controlling the composite antenna beamforming array to generate a composite antenna beam, the composite antenna beam having a higher gain and narrower beamwidth than the antenna beams associated with the antenna modules.

[0051] Another example method includes the forgoing operations and further includes controlling the composite

antenna beamforming array to generate a composite antenna beam, the composite antenna beam having a wider beamwidth than the antenna beams associated with the antenna modules.

[0052] Another example method includes the forgoing operations and further includes controlling the composite antenna beamforming array to generate a composite antenna beam and to steer the composite antenna beam from a first direction to a second direction.

[0053] Another example method includes the forgoing operations and further includes segmenting the composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array configured to generate an independently steerable antenna beam.

[0054] Another example method includes the forgoing operations and further includes applying a plurality of signal adjustments, each of the signal adjustments associated with one of a plurality of signal frequency components.

[0055] Another example method includes the forgoing operations and further includes disposing the antenna modules in one or more planes and orienting the planes in different directions relative to each other.

[0056] Another example method includes the forgoing operations and further includes arranging the antenna elements and the antenna modules in a linear end-fire pattern.

[0057] According to another aspect there is provided a platform. The platform may include a processor; an input/output module coupled to the processor; a memory coupled to the processor; and a wireless communication interface coupled to the processor. The wireless communication interface of this example may include a plurality of antenna modules, each of the antenna modules including an array of antenna elements coupled to an RF beamforming circuit, the RF beamforming circuit configured to adjust phase shifts associated with each of the antenna elements to generate an antenna beam associated with the antenna module. The wireless communication interface of this example may further include a central beamforming module coupled to each of the antenna modules, the central beamforming module configured to control the antenna beam associated with each of the antenna modules and to generate signal adjustments relative to each of the antenna modules, and the arrays of antenna elements of the antenna modules combine to operate as a composite antenna beamforming array.

[0058] Another example platform includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming array to generate a composite antenna beam, the composite antenna beam having a higher gain and narrower beamwidth than the antenna beams associated with the antenna modules.

[0059] Another example platform includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming array to generate a composite antenna beam, the composite antenna beam having a wider beamwidth than the antenna beams associated with the antenna modules.

[0060] Another example platform includes the forgoing components and the central beamforming module is further configured to control the composite antenna beamforming array to generate a composite antenna beam and to steer the composite antenna beam from a first direction to a second direction.

[0061] Another example platform includes the forgoing components and the central beamforming module is further



configured to segment the composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array configured to generate an independently steerable antenna beam.

**[0062]** Another example platform includes the forgoing components and the central beamforming module is further configured to apply a plurality of signal adjustments, each of the signal adjustments associated with one of a plurality of signal frequency components.

**[0063]** Another example platform includes the forgoing components and the antenna modules are disposed in one or more planes, the planes oriented in different directions relative to each other.

**[0064]** Another example platform includes the forgoing components and the antenna elements and the antenna modules are arranged in a linear end-fire pattern.

**[0065]** Another example platform includes the forgoing components and the RF beamforming circuits are RFICs and the antenna modules are configured to operate in a millimeter wave frequency range.

**[0066]** Another example platform includes the forgoing components and the platform is a smartphone, a laptop computing device or a tablet.

**[0067]** Another example platform includes the forgoing components and the platform is a wireless base station.

**[0068]** The terms and expressions which have been employed herein are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding any equivalents of the features shown and described (or portions thereof), and it is recognized that various modifications are possible within the scope of the claims. Accordingly, the claims are intended to cover all such equivalents. Various features, aspects, and embodiments have been described herein. The features, aspects, and embodiments are susceptible to combination with one another as well as to variation and modification, as will be understood by those having skill in the art. The present disclosure should, therefore, be considered to encompass such combinations, variations, and modifications.

1-32. (canceled)

**33.** A system for antenna beamforming, said system comprising:

- a plurality of antenna modules, each of said antenna modules comprising an array of antenna elements coupled to a radio frequency (RF) beamforming circuit, said RF beamforming circuit to adjust phase shifts associated with said antenna elements to generate an antenna beam associated with said antenna module; and
- a central beamforming module coupled to each of said antenna modules, said central beamforming module to control said antenna beam associated with each of said antenna modules and to generate signal adjustments relative to each of said antenna modules, wherein said arrays of antenna elements of said antenna modules combine to operate as a composite antenna beamforming array.

**34.** The system of claim **33**, wherein said signal adjustments comprise signal magnitude adjustments and signal phase adjustments.

**35.** The system of claim **33**, wherein said central beamforming module is included in a processor selected from the group consisting of a baseband processor, an intermediate frequency processor and an RF processor.

**36.** The system of claim **33**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a higher gain and narrower beamwidth than said antenna beams associated with said antenna modules.

**37.** The system of claim **33**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a wider beamwidth than said antenna beams associated with said antenna modules.

**38.** The system of claim **33**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam and to steer said composite antenna beam from a first direction to a second direction.

**39.** The system of claim **33**, wherein said central beamforming module is further to segment said composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array to generate an independently steerable antenna beam.

**40.** The system of claim **33**, wherein said central beamforming module is further to apply a plurality of said signal adjustments, each of said plurality of signal adjustments associated with one of a plurality of signal frequency components.

**41.** The system of claim **33**, wherein said antenna modules are disposed in a plurality of planes, said planes oriented in different directions relative to each other.

**42.** The system of claim **33**, wherein said antenna elements and said antenna modules are arranged in a linear end-fire pattern.

**43.** The system of claim **33**, wherein said RF beamforming circuits are RF integrated circuits (RFICs) and said antenna modules are to operate in a millimeter wave frequency range.

**44.** The system of claim **33**, wherein said antenna elements are coupled to said RF beamforming circuit by micro-strip feeding lines.

**45.** A method for antenna beamforming, said method comprising:

adjusting phase shifts associated with antenna elements included in an array of antenna elements coupled to an RF beamforming circuit, said adjusting performed by said RF beamforming circuit to generate an antenna beam, said antenna beam associated with an antenna module, said antenna module comprising said array of antenna elements and said RF beamforming circuit;

controlling said antenna beam associated with each of a plurality of said antenna modules, said antenna modules coupled to a central beamforming module, said controlling performed by said central beamforming module; and

generating signal adjustments relative to each of said antenna modules, said generating performed by said central beamforming module, wherein said arrays of antenna elements of said antenna modules combine to operate as a composite antenna beamforming array.

**46.** The method of claim **45**, wherein said signal adjustments comprise signal magnitude adjustments and signal phase adjustments.

**47.** The method of claim **45**, further comprising controlling said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a higher gain and narrower beamwidth than said antenna beams associated with said antenna modules.



**48.** The method of claim **45**, further comprising controlling said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a wider beamwidth than said antenna beams associated with said antenna modules.

**49.** The method of claim **45**, further comprising controlling said composite antenna beamforming array to generate a composite antenna beam and to steer said composite antenna beam from a first direction to a second direction.

**50.** The method of claim **45**, further comprising segmenting said composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array to generate an independently steerable antenna beam.

**51.** The method of claim **45**, further comprising applying a plurality of said signal adjustments, each of said plurality of signal adjustments associated with one of a plurality of signal frequency components.

**52.** The method of claim **45**, further comprising disposing said antenna modules in a plurality of planes and orienting said planes in different directions relative to each other.

**53.** The method of claim **45**, further comprising arranging said antenna elements and said antenna modules in a linear end-fire pattern.

**54.** A platform comprising:

a processor;

an input/output module coupled to said processor;

a memory coupled to said processor; and

a wireless communication interface coupled to said processor, said interface comprising:

a plurality of antenna modules, each of said antenna modules comprising an array of antenna elements coupled to a radio frequency (RF) beamforming circuit, said RF beamforming circuit to adjust phase shifts associated with said antenna elements to generate an antenna beam associated with said antenna module; and

a central beamforming module coupled to each of said antenna modules, said central beamforming module to control said antenna beam associated with each of said antenna modules and to generate signal adjustments relative to each of said antenna modules, wherein said

arrays of antenna elements of said antenna modules combine to operate as a composite antenna beamforming array.

**55.** The platform of claim **54**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a higher gain and narrower beamwidth than said antenna beams associated with said antenna modules.

**56.** The platform of claim **54**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam, said composite antenna beam having a wider beamwidth than said antenna beams associated with said antenna modules.

**57.** The platform of claim **54**, wherein said central beamforming module is further to control said composite antenna beamforming array to generate a composite antenna beam and to steer said composite antenna beam from a first direction to a second direction.

**58.** The platform of claim **54**, wherein said central beamforming module is further to segment said composite antenna beamforming array into a plurality of composite sub-arrays, each composite sub-array to generate an independently steerable antenna beam.

**59.** The platform of claim **54**, wherein said central beamforming module is further to apply a plurality of said signal adjustments, each of said plurality of signal adjustments associated with one of a plurality of signal frequency components.

**60.** The platform of claim **54**, wherein said antenna modules are disposed in a plurality of planes, said planes oriented in different directions relative to each other.

**61.** The platform of claim **54**, wherein said antenna elements and said antenna modules are arranged in a linear end-fire pattern.

**62.** The platform of claim **54**, wherein said RF beamforming circuits are included in one or more RF integrated circuits (RFICs) and said antenna modules are to operate in a millimeter wave frequency range.

**63.** The platform of claim **54**, wherein said platform is selected from the group consisting of a smartphone, a laptop computing device and a tablet.

**64.** The platform of claim **54**, wherein said platform is a wireless base station.

\* \* \* \* \*