



US009182244B2

(12) **United States Patent**  
**Luke et al.**

(10) **Patent No.:** **US 9,182,244 B2**  
(45) **Date of Patent:** **Nov. 10, 2015**

(54) **APPARATUS, METHOD AND ARTICLE FOR AUTHENTICATION, SECURITY AND CONTROL OF POWER STORAGE DEVICES, SUCH AS BATTERIES**

(75) Inventors: **Hok-Sum Horace Luke**, Mercer Island, WA (US); **Matthew Whiting Taylor**, North Bend, WA (US)

(73) Assignee: **Gogoro Inc.**, Hong Kong (CN)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 213 days.

(21) Appl. No.: **13/559,038**

(22) Filed: **Jul. 26, 2012**

(65) **Prior Publication Data**  
US 2013/0026973 A1 Jan. 31, 2013

**Related U.S. Application Data**

(60) Provisional application No. 61/511,900, filed on Jul. 26, 2011, provisional application No. 61/647,936, filed on May 16, 2012, provisional application No. 61/534,753, filed on Sep. 14, 2011, provisional

(Continued)

(51) **Int. Cl.**  
**H02J 7/00** (2006.01)  
**G01C 21/36** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **G01C 21/3682** (2013.01); **B60L 3/003** (2013.01); **B60L 3/0069** (2013.01); **B60L 11/005** (2013.01); **B60L 11/1822** (2013.01); **B60L 11/1824** (2013.01); **B60L 11/1838** (2013.01);

(Continued)

(58) **Field of Classification Search**  
USPC ..... 320/106  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,387,848 A 8/1921 Good  
3,664,450 A 5/1972 Udden et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 693 813 A1 1/1996  
EP 1 667 306 A1 6/2006

(Continued)

OTHER PUBLICATIONS

Chen et al., "Apparatus, Method and Article for Providing Vehicle Diagnostic Data," U.S. Appl. No. 61/601,404, filed Feb. 21, 2012, 56 pages.

(Continued)


*Primary Examiner* — Samuel Berhanu

(74) *Attorney, Agent, or Firm* — Seed IP Law Group PLLC

(57) **ABSTRACT**

A network of collection, charging and distribution machines collect, charge and distribute portable electrical energy storage devices (e.g., batteries, supercapacitors or ultracapacitors). To charge, the machines employ electrical current from an external source, such as the electrical grid or an electrical service of an installation location. By default, each portable electrical energy storage device is disabled from accepting a charge unless it receives authentication information from an authorized collection, charging and distribution machine, other authorized charging device, or other authorized device that transmits the authentication credentials. Also, by default, each portable electrical energy storage device is disabled from releasing energy unless it receives authentication information from an external device to which it will provide power, such as a vehicle or other authorization device.

**30 Claims, 7 Drawing Sheets**



**Related U.S. Application Data**

application No. 61/534,761, filed on Sep. 14, 2011, provisional application No. 61/534,772, filed on Sep. 14, 2011, provisional application No. 61/511,887, filed on Jul. 26, 2011, provisional application No. 61/647,941, filed on May 16, 2012, provisional application No. 61/511,880, filed on Jul. 26, 2011, provisional application No. 61/557,170, filed on Nov. 8, 2011, provisional application No. 61/581,566, filed on Dec. 29, 2011, provisional application No. 61/601,404, filed on Feb. 21, 2012, provisional application No. 61/601,949, filed on Feb. 22, 2012, provisional application No. 61/601,953, filed on Feb. 22, 2012.

(51) **Int. Cl.**

**G07C 5/00** (2006.01)  
**H01M 10/42** (2006.01)  
**G01C 21/34** (2006.01)  
**G06Q 30/02** (2012.01)  
**G06Q 30/06** (2012.01)  
**H02J 4/00** (2006.01)  
**E05B 81/56** (2014.01)  
**B60L 3/00** (2006.01)  
**B60L 11/00** (2006.01)  
**B60L 11/18** (2006.01)  
**G07C 5/08** (2006.01)  
**G06Q 10/02** (2012.01)  
**H01M 10/44** (2006.01)  
**H01M 10/48** (2006.01)  
**G06F 3/06** (2006.01)

(52) **U.S. Cl.**

CPC ..... **B60L 11/1846** (2013.01); **B60L 11/1861** (2013.01); **E05B 81/56** (2013.01); **G01C 21/3476** (2013.01); **G06F 3/0608** (2013.01); **G06F 3/0638** (2013.01); **G06F 3/0671** (2013.01); **G06Q 10/02** (2013.01); **G06Q 30/0253** (2013.01); **G06Q 30/0259** (2013.01); **G06Q 30/0261** (2013.01); **G06Q 30/0267** (2013.01); **G06Q 30/0639** (2013.01); **G07C 5/00** (2013.01); **G07C 5/0858** (2013.01); **H01M 10/425** (2013.01); **H01M 10/4257** (2013.01); **H01M 10/441** (2013.01); **H01M 10/482** (2013.01); **H02J 4/00** (2013.01); **H02J 7/00** (2013.01); **H02J 7/007** (2013.01); **H02J 7/0013** (2013.01); **B60L 2200/12** (2013.01); **B60L 2210/12** (2013.01); **B60L 2210/14** (2013.01); **B60L 2210/30** (2013.01); **B60L 2230/16** (2013.01); **B60L 2230/40** (2013.01); **B60L 2240/70** (2013.01); **H01M 2010/4278** (2013.01); **H01M 2220/20** (2013.01); **H01M 2220/30** (2013.01); **H02J 2007/0001** (2013.01); **H02J 2007/0098** (2013.01); **Y02E 60/12** (2013.01); **Y02T 10/705** (2013.01); **Y02T 10/7005** (2013.01); **Y02T 10/7011** (2013.01); **Y02T 10/7022** (2013.01); **Y02T 10/7044** (2013.01); **Y02T 10/7055** (2013.01); **Y02T 10/7072** (2013.01); **Y02T 10/7094** (2013.01); **Y02T 10/7225** (2013.01); **Y02T 10/7233** (2013.01); **Y02T 10/7241** (2013.01); **Y02T 10/7258** (2013.01); **Y02T 10/7291** (2013.01); **Y02T 10/92** (2013.01); **Y02T 90/121** (2013.01); **Y02T 90/124** (2013.01); **Y02T 90/127** (2013.01); **Y02T 90/128** (2013.01); **Y02T 90/14** (2013.01); **Y02T 90/16** (2013.01); **Y02T 90/161** (2013.01); **Y02T 90/163** (2013.01); **Y02T**

**90/168** (2013.01); **Y02T 90/169** (2013.01); **Y04S 30/12** (2013.01); **Y04S 30/14** (2013.01); **Y10T 70/7062** (2015.04); **Y10T 307/406** (2015.04)

(56)

**References Cited**

## U.S. PATENT DOCUMENTS

3,678,455	A	7/1972	Levey
3,687,484	A	8/1972	Cosby
3,708,028	A	1/1973	Hafer
4,087,895	A	5/1978	Etienne
4,216,839	A	8/1980	Gould et al.
5,187,423	A	2/1993	Marton
5,189,325	A	2/1993	Jarczynski
5,236,069	A	8/1993	Peng
5,339,250	A	8/1994	Durbin
5,349,535	A	9/1994	Gupta
5,491,486	A	2/1996	Welles, II et al.
5,544,784	A	8/1996	Malaspina
5,596,261	A	1/1997	Suyama
5,627,752	A	5/1997	Buck et al.
5,631,536	A	5/1997	Tseng
5,642,270	A	6/1997	Green et al.
5,815,824	A	9/1998	Saga et al.
5,839,800	A	11/1998	Koga et al.
5,898,282	A	4/1999	Drozdz et al.
5,998,963	A	12/1999	Aarseth
6,016,882	A	1/2000	Ishikawa
6,177,867	B1	1/2001	Simon et al.
6,177,879	B1	1/2001	Kokubu et al.
6,403,251	B1	6/2002	Baggaley et al.
6,429,622	B1	8/2002	Svensson
6,494,279	B1	12/2002	Hutchens
6,498,457	B1	12/2002	Tsuboi
6,515,580	B1	2/2003	Isoda et al.
6,583,592	B2	6/2003	Omata et al.
6,593,713	B2	7/2003	Morimoto et al.
6,614,204	B2	9/2003	Pellegrino et al.
6,796,396	B2	9/2004	Kamen et al.
6,822,560	B2	11/2004	Geber et al.
6,854,773	B2	2/2005	Lin
6,899,268	B2	5/2005	Hara
6,917,306	B2	7/2005	Lilja
6,952,795	B2	10/2005	O'Gorman et al.
7,010,682	B2	3/2006	Reinold et al.
7,131,005	B2	10/2006	Levenson et al.
7,392,068	B2 *	6/2008	Dayan et al. .... 455/572
7,415,332	B2	8/2008	Ito et al.
7,426,910	B2	9/2008	Elwart
7,495,543	B2	2/2009	Denison et al.
7,567,166	B2	7/2009	Bourguine De Meder
7,592,728	B2	9/2009	Jones et al.
7,617,893	B2 *	11/2009	Syed et al. .... 180/65.21
7,630,181	B2	12/2009	Wilk et al.
7,761,307	B2	7/2010	Ochi et al.
7,778,746	B2	8/2010	McLeod et al.
7,898,439	B2	3/2011	Bettez et al.
7,908,020	B2	3/2011	Pieronek
7,948,207	B2	5/2011	Scheucher
7,979,147	B1	7/2011	Dunn
7,993,155	B2	8/2011	Heichal et al.
8,006,793	B2	8/2011	Heichal et al.
8,006,973	B2	8/2011	Toba et al.
8,013,571	B2	9/2011	Agassi et al.
8,035,341	B2	10/2011	Genzel et al.
8,035,349	B2	10/2011	Lubawy
8,068,952	B2	11/2011	Valentine et al.
8,106,631	B2	1/2012	Abe
8,118,132	B2	2/2012	Gray, Jr.
8,164,300	B2	4/2012	Agassi et al.
8,229,625	B2	7/2012	Lal et al.
8,265,816	B1	9/2012	LaFrance
8,301,365	B2	10/2012	Niwa et al.
8,326,259	B2	12/2012	Gautama et al.
8,354,768	B2	1/2013	Cipriani
8,378,627	B2	2/2013	Asada et al.



(56)

**References Cited****U.S. PATENT DOCUMENTS**

8,412,401	B2	4/2013	Bertosa et al.	
8,437,908	B2	5/2013	Goff et al.	
8,614,565	B2	12/2013	Lubawy	
2001/0018903	A1	9/2001	Hirose et al.	
2001/0052433	A1	12/2001	Harris et al.	
2002/0023789	A1	2/2002	Morisawa et al.	
2002/0070851	A1	6/2002	Raichle et al.	
2003/0052796	A1	3/2003	Schmidt et al.	
2003/0141840	A1	7/2003	Sanders	
2003/0163434	A1	8/2003	Barends	
2003/0209375	A1	11/2003	Suzuki et al.	
2004/0236615	A1	11/2004	Msndy	
2004/0246119	A1	12/2004	Martin et al.	
2006/0047380	A1	3/2006	Welch	
2006/0208850	A1 *	9/2006	Ikeuchi et al.	340/5.8
2006/0284601	A1	12/2006	Salasoo et al.	
2007/0016815	A1 *	1/2007	Cooper et al.	713/322
2007/0026996	A1	2/2007	Ayabe et al.	
2007/0035397	A1	2/2007	Patenaude et al.	
2007/0090921	A1	4/2007	Fisher	
2007/0126395	A1	6/2007	Suchar	
2007/0159297	A1	7/2007	Paulk et al.	
2007/0208468	A1	9/2007	Sankaran et al.	
2007/0238164	A1	10/2007	Kim	
2008/0143292	A1	6/2008	Ward	
2008/0154801	A1	6/2008	Fein et al.	
2009/0024872	A1	1/2009	Beverly	
2009/0033456	A1	2/2009	Castillo et al.	
2009/0045773	A1	2/2009	Pandya et al.	
2009/0082957	A1	3/2009	Agassi et al.	
2009/0112394	A1	4/2009	Lepejian et al.	
2009/0198372	A1	8/2009	Hammerslag	
2009/0243539	A1 *	10/2009	Gangstoe et al.	320/106
2009/0261779	A1	10/2009	Zyren	
2009/0289784	A1 *	11/2009	Sid	340/539.3
2009/0294188	A1	12/2009	Cole	
2009/0295326	A1 *	12/2009	Daynes et al.	320/106
2010/0013433	A1	1/2010	Baxter et al.	
2010/0026238	A1	2/2010	Suzuki et al.	
2010/0051363	A1	3/2010	Inoue et al.	
2010/0052588	A1	3/2010	Okamura et al.	
2010/0089547	A1	4/2010	King et al.	
2010/0094496	A1	4/2010	Hershkovitz et al.	
2010/0114798	A1	5/2010	Sirton	
2010/0134067	A1	6/2010	Baxter et al.	
2010/0141207	A1 *	6/2010	Phillips et al.	320/114
2010/0145717	A1	6/2010	Hoeltzel	
2010/0161481	A1	6/2010	Littrell	
2010/0188043	A1	7/2010	Kelty et al.	
2010/0191585	A1	7/2010	Smith	
2010/0201482	A1	8/2010	Robertson et al.	
2010/0225266	A1	9/2010	Hartman	
2010/0235043	A1	9/2010	Seta et al.	
2010/0308989	A1	12/2010	Gasper	
2011/0025267	A1	2/2011	Kamen et al.	
2011/0029157	A1	2/2011	Muzaffer	
2011/0032110	A1	2/2011	Taguchi	
2011/0071932	A1	3/2011	Agassi et al.	
2011/0082598	A1	4/2011	Boretto et al.	
2011/0106329	A1	5/2011	Donnelly et al.	
2011/0112710	A1	5/2011	Meyer-Ebeling et al.	
2011/0114798	A1	5/2011	Gemmati	
2011/0120789	A1	5/2011	Teraya	
2011/0148346	A1	6/2011	Gagosz et al.	
2011/0153141	A1	6/2011	Beechie et al.	
2011/0160992	A1	6/2011	Crombez	
2011/0169447	A1	7/2011	Brown et al.	
2011/0200193	A1	8/2011	Blitz et al.	
2011/0202476	A1	8/2011	Nagy et al.	
2011/0224868	A1	9/2011	Collings, III et al.	
2011/0224900	A1	9/2011	Hiruta et al.	
2011/0270480	A1	11/2011	Ishibashi et al.	
2011/0279257	A1	11/2011	Au et al.	
2011/0292667	A1	12/2011	Meyers	
2011/0295454	A1	12/2011	Meyers	

2011/0303509	A1	12/2011	Agassi et al.
2012/0000720	A1	1/2012	Honda et al.
2012/0019196	A1	1/2012	Fung
2012/0038473	A1	2/2012	Fecher
2012/0062361	A1	3/2012	Kosugi
2012/0068817	A1	3/2012	Fisher
2012/0078413	A1	3/2012	Baker, Jr.
2012/0105078	A1	5/2012	Kikuchi et al.
2012/0109519	A1	5/2012	Uyeki
2012/0123661	A1	5/2012	Gray, Jr.
2012/0126969	A1	5/2012	Wilbur et al.
2012/0158229	A1	6/2012	Schaefer
2012/0194346	A1	8/2012	Tsai et al.
2012/0248868	A1	10/2012	Mobin et al.
2012/0256588	A1	10/2012	Hayashi et al.
2012/0259665	A1	10/2012	Pandhi et al.
2012/0299527	A1	11/2012	Vo
2012/0299537	A1	11/2012	Kikuchi
2012/0316671	A1	12/2012	Hammerslag et al.
2013/0024306	A1	1/2013	Shah et al.
2013/0026971	A1	1/2013	Luke et al.
2013/0026972	A1	1/2013	Luke et al.
2013/0027183	A1	1/2013	Wu et al.
2013/0030580	A1	1/2013	Luke et al.
2013/0030581	A1	1/2013	Luke et al.
2013/0030608	A1	1/2013	Taylor et al.
2013/0030630	A1	1/2013	Luke et al.
2013/0030696	A1	1/2013	Wu et al.
2013/0030920	A1	1/2013	Wu et al.
2013/0031318	A1	1/2013	Chen et al.
2013/0033203	A1	2/2013	Luke et al.
2013/0046457	A1	2/2013	Pettersson
2013/0074411	A1	3/2013	Ferguson et al.
2013/0090795	A1	4/2013	Luke et al.
2013/0093271	A1	4/2013	Luke et al.
2013/0093368	A1	4/2013	Luke et al.
2013/0093384	A1	4/2013	Nyu et al.
2013/0116892	A1	5/2013	Wu et al.
2013/0119898	A1	5/2013	Ohkura
2013/0127416	A1	5/2013	Karner et al.
2013/0132307	A1	5/2013	Phelps et al.
2013/0200845	A1	8/2013	Bito
2013/0254097	A1	9/2013	Marathe et al.
2013/0282254	A1	10/2013	Dwan et al.
2014/0028089	A1	1/2014	Luke et al.

**FOREIGN PATENT DOCUMENTS**

EP	2 101 390	A2	9/2009
EP	2 230 146	A2	9/2010
EP	2 428 939	A1	3/2012
JP	5-135804	A	6/1993
JP	7-031008	A	1/1995
JP	7-36504	U	7/1995
JP	9-119839	A	5/1997
JP	10-170293	A	6/1998
JP	10-307952	A	11/1998
JP	11-049079	A	2/1999
JP	11-51681	A	2/1999
JP	11-176487	A	7/1999
JP	11-205914	A	7/1999
JP	2000-102102	A	4/2000
JP	2000-102103	A	4/2000
JP	2000-341868	A	12/2000
JP	2001-128301	A	5/2001
JP	2002-140398	A	5/2002
JP	2003-118397	A	4/2003
JP	2003262525	A	9/2003
JP	2004-215468	A	7/2004
JP	2005-67453	A	3/2005
JP	2007-35479	A	2/2007
JP	2009171646	A	7/2009
JP	2009171647	A	7/2009
JP	4319289	B2	8/2009
JP	2010-022148	A	1/2010
JP	2010-212048	A	9/2010
JP	2010191636	A	9/2010
JP	2010200405	A	9/2010
JP	2010-269686	A	12/2010



(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

JP	2011-126452	A	6/2011
JP	2011-131631	A	7/2011
JP	2011-142704	A	7/2011
JP	2011-142779	A	7/2011
KR	1998-045020	U	9/1998
KR	2004-0005146	A	1/2004
KR	20100012401	A	2/2010
KR	10-0971278	B1	7/2010
KR	20110004292	A	1/2011
KR	20110041783	A	4/2011
TW	200836452	A	9/2008
TW	I315116	B	9/2009
TW	M371880		1/2010
TW	M379269		4/2010
TW	M379789	U1	5/2010
TW	M385047		7/2010
TW	201043986	A	12/2010
TW	201044266	A	12/2010
WO	98/21132	A1	5/1998
WO	99/03186	A1	1/1999
WO	2009/039454	A1	3/2009
WO	2010/033517	A2	3/2010
WO	2010/035605	A1	4/2010
WO	2010/143483	A1	12/2010
WO	2011/138205	A1	11/2011
WO	2012/160407	A1	11/2012
WO	2012/160557	A2	11/2012
WO	2013/024483	A2	2/2013
WO	2013/024484	A1	2/2013
WO	2013/074819	A1	5/2013
WO	2013/080211	A1	6/2013
WO	2013/102894	A1	7/2013
WO	2013/108246	A2	7/2013
WO	2013/118113	A2	8/2013
WO	2013/142154	A1	9/2013
WO	2013/144951	A1	10/2013

## OTHER PUBLICATIONS

Luke et al., "Dynamically Limiting Vehicle Operation for Best Effort Economy," U.S. Appl. No. 61/511,880, filed Jul. 26, 2011, 52 pages.

Luke et al., "Thermal Management of Components in Electric Motor Drive Vehicles," U.S. Appl. No. 61/511,887, filed Jul. 26, 2011, 44 pages.

Luke et al., "Apparatus, Method and Article for Collection, Charging and Distributing Power Storage Device, Such as Batteries," U.S. Appl. No. 61/511,900, filed Jul. 26, 2011, 73 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Power Storage Devices, Such as Batteries," U.S. Appl. No. 61/534,761, filed Sep. 14, 2011, 55 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Power Storage Devices, Such as Batteries, Based on User Profiles," U.S. Appl. No. 61/534,772, filed Sep. 14, 2011, 55 pages.

Luke et al., "Apparatus, Method and Article for Redistributing Power Storage Devices, Such as Batteries, Between Collection, Charging and Distribution Machines," U.S. Appl. No. 61/534,753, filed Sep. 14, 2011, 65 pages.

Luke et al., "Apparatus, Method and Article for Collection, Charging and Distributing Power Storage Devices, Such as Batteries," U.S. Appl. No. 61/647,936, filed May 16, 2012, 76 pages.

Luke et al., "Thermal Management of Components in Electric Motor Drive Vehicles," U.S. Appl. No. 61/647,941, filed May 16, 2012, 47 pages.

Luke et al., "Drive Assembly for Electric Device," U.S. Appl. No. 13/650,392, filed Oct. 12, 2012, 43 pages.

Taylor et al., "Apparatus, Method and Article for Physical Security of Power Storage Devices in Vehicles," U.S. Appl. No. 61/557,170, filed Nov. 8, 2011, 60 pages.

Wu et al., "Apparatus, Method and Article for Security of Vehicles," U.S. Appl. No. 61/557,176, filed Nov. 8, 2011, 37 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," U.S. Appl. No. 61/601,949, filed Feb. 22, 2012, 56 pages.

Wu et al., "Apparatus, Method and Article for a Power Storage Device Compartment," U.S. Appl. No. 61/581,566, filed Dec. 29, 2011, 61 pages.

Wu et al., "Apparatus, Method and Article for Providing Information Regarding Availability of Power Storage Devices at a Power Storage Device Collection, Charging and Distribution Machine," U.S. Appl. No. 61/601,953, filed Feb. 22, 2012, 53 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048349, mailed Feb. 18, 2013, 9 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048354, mailed Feb. 18, 2013, 11 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048366 mailed Jan. 21, 2013, 10 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048367, mailed Jan. 17, 2013, 8 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048375, mailed Jan. 23, 2013, 9 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048379, mailed Dec. 17, 2012, 9 pages.

International Search Report and Written Opinion for corresponding International Application No. PCT/US2012/048391, mailed Dec. 21, 2012, 9 pages.

International Search Report and Written Opinion of the International Searching Authority for International Patent Application No. PCT/US2012/048358, dated Feb. 25, 2013, 9 pages.

"Inrunner," retrieved from URL=<http://en.wikipedia.org/w/index.php?title=Inrunner&printable=yes> on Sep. 28, 2011, 1 page.

"Outrunner," retrieved from URL=<http://en.wikipedia.org/w/index.php?title=Outrunner&printable=yes> on Sep. 16, 2011, 2 pages.

Chen et al., "Adjusting Electric Vehicle Systems Based on an Electrical Energy Storage Device Thermal Profile," U.S. Appl. No. 61/862,854, filed Aug. 6, 2013, 74 pages.

Chen et al., "Apparatus, System, and Method for Authentication of Vehicular Components," U.S. Appl. No. 61/783,041, filed Mar. 14, 2013, 84 pages.

Chen et al., "Apparatus, System, and Method for Authentication of Vehicular Components," Office Action mailed Nov. 22, 2013, for U.S. Appl. No. 13/918,703, 35 pages.

Chen et al., "Apparatus, System, and Method for Authentication of Vehicular Components," Notice of Allowance mailed Mar. 25, 2014, for U.S. Appl. No. 13/918,703, 7 pages.

Chen et al., "Apparatus, System, and Method for Authentication of Vehicular Components," U.S. Appl. No. 13/918,703, filed Jun. 14, 2013, 84 pages.

Chen et al., "Apparatus, Method and Article for Providing Vehicle Diagnostic Data," Office Action mailed Dec. 30, 2013, for U.S. Appl. No. 14/022,134, 20 pages.

Chen et al., "Apparatus, Method and Article for Providing Vehicle Diagnostic Data," Office Action mailed Apr. 9, 2014, for U.S. Appl. No. 14/022,134, 20 pages.

Chen et al., "Apparatus, Method and Article for Providing Vehicle Diagnostic Data," U.S. Appl. No. 14/022,134, filed Sep. 9, 2013, 61 pages.

Chen et al., "Systems and Methods for Powering Electric Vehicles Using a Single or Multiple Power Cells," U.S. Appl. No. 61/862,852, filed Aug. 6, 2013, 46 pages.

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12817273.1, dated Mar. 25, 2014, 3 pages.

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12817141.0, dated Mar. 26, 2014, 3 pages.



(56)

**References Cited**

## OTHER PUBLICATIONS

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12818308.4, dated Mar. 26, 2014, 3 pages.

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12817696.3, dated Mar. 27, 2014, 3 pages.

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12817883.7, dated Mar. 27, 2014, 3 pages.

Communication pursuant to Rules 161(2) and 162 EPC, for corresponding European Patent Application No. 12818447.0, dated Mar. 27, 2014, 3 pages.

Huang et al., "Apparatus, Method and Article for Vehicle Turn Signals," U.S. Appl. No. 61/727,403, filed Nov. 16, 2012, 41 pages.

Huang et al., "Apparatus, Method and Article for Vehicle Turn Signals," U.S. Appl. No. 14/079,894, filed Nov. 14, 2013, 41 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048349, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048354, issued on Jan. 28, 2014, 7 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048358, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048366, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048367, issued on Jan. 28, 2014, 4 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048375, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048379, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048380, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048382, issued on Jan. 28, 2014, 5 pages.

International Preliminary Report on Patentability and Written Opinion for corresponding International Patent Application No. PCT/US2012/048391, issued on Jan. 28, 2014, 6 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048344, mailed Feb. 28, 2013, 9 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048347, mailed Dec. 18, 2012, 8 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048380, mailed Feb. 27, 2013, 9 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/048382, mailed Feb. 27, 2013, 9 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/063979, mailed Mar. 4, 2013, 10 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2012/058930, mailed Mar. 15, 2013, 11 pages.

International Search Report and Written Opinion for corresponding International Patent Application No. PCT/US2013/070131, mailed Feb. 19, 2014, 17 pages.

International Search Report and Written Opinion for corresponding International Application No. PCT/US2012/059931, mailed Mar. 29, 2013, 13 pages.

Luke et al., "Portable Electrical Energy Storage Device," U.S. Appl. No. 61/872,126, filed Aug. 30, 2013, 39 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Portable Charging Devices and Power Storage Devices, Such as Batteries," Office Action mailed Jan. 6, 2014, for U.S. Appl. No. 14/017,090, 19 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Portable Charging Devices and Power Storage Devices, Such as Batteries," U.S. Appl. No. 14/017,090, filed Sep. 3, 2013, 69 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Portable Charging Devices and Power Storage Devices, Such as Batteries," U.S. Appl. No. 61/773,621, filed Mar. 6, 2013, 69 pages.

Luke et al., "Apparatus, Method and Article for Providing Targeted Advertising in a Rechargeable Electrical Power Storage Device Distribution Environment," U.S. Appl. No. 61/773,614, filed Mar. 6, 2013, 77 pages.

Luke et al., "Detectible Indication of an Electric Motor Vehicle Standby Mode," Office Action for U.S. Appl. No. 13/646,320, mailed May 30, 2013, 13 pages.

Luke et al., "Detectible Indication of an Electric Motor Vehicle Standby Mode," U.S. Appl. No. 61/543,720, filed Oct. 5, 2011, 35 pages.

Luke et al., "Detectible Indication of an Electric Motor Vehicle Standby Mode," U.S. Appl. No. 61/684,432, filed Aug. 17, 2012, 41 pages.

Luke et al., "Drive Assembly for Electric Powered Device," U.S. Appl. No. 61/546,411, filed Oct. 12, 2011, 18 pages.

Luke et al., "Electric Device Drive Assembly and Cooling System," U.S. Appl. No. 61/615,144, filed Mar. 23, 2012, 43 pages.

Luke et al., "Modular System for Collection and Distribution of Electric Storage Devices," U.S. Appl. No. 61/789,065, filed Mar. 15, 2013, 76 pages.

Luke et al., "Modular System for Collection and Distribution of Electric Storage Devices," U.S. Appl. No. 14/202,589, filed Mar. 10, 2014, 76 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Power Storage Devices, Such as Batteries," Office Action mailed Feb. 25, 2014, for U.S. Appl. No. 14/023,344, 12 pages.

Luke et al., "Dynamically Limiting Vehicle Operation for Best Effort Economy," Office Action for U.S. Appl. No. 13/559,264, mailed Aug. 14, 2013, 21 pages.

Luke et al., "Dynamically Limiting Vehicle Operation for Best Effort Economy," Office Action for U.S. Appl. No. 13/559,264, mailed Feb. 12, 2014, 24 pages.

Luke et al., "Thermal Management of Components in Electric Motor Drive Vehicles," Office Action mailed Apr. 2, 2014, for U.S. Appl. No. 13/559,259, 11 pages.

Luke, "Apparatus, Method and Article for Changing Portable Electrical Power Storage Device Exchange Plans," U.S. Appl. No. 14/204,587, filed Mar. 11, 2014, 56 pages.

Luke, "Apparatus, Method and Article for Changing Portable Electrical Power Storage Device Exchange Plans," U.S. Appl. No. 61/778,038, filed Mar. 12, 2013, 56 pages.

Luke, "Apparatus, Method and Article for Providing Information Regarding a Vehicle via a Mobile Device," Office Action for U.S. Appl. No. 14/017,081, mailed Jan. 30, 2014, 36 pages.

Luke, "Apparatus, Method and Article for Providing Information Regarding a Vehicle via a Mobile Device," U.S. Appl. No. 14/017,081, filed Sep. 3, 2013, 81 pages.

Luke, "Apparatus, Method and Article for Providing Information Regarding a Vehicle via a Mobile Device," U.S. Appl. No. 61/780,781, filed Mar. 13, 2013, 80 pages.

Microchip, "AN885: Brushless DC (BLDC) Motor Fundamentals," Microchip Technology Inc., 2003, 19 pages.

Taylor et al., "Apparatus, Method and Article for Physical Security of Power Storage Devices in Vehicles," Notice of Allowance for U.S. Appl. No. 13/559,054, mailed May 30, 2013, 32 pages.



(56)

**References Cited**

## OTHER PUBLICATIONS

Taylor et al., "Apparatus, Method and Article for Physical Security of Power Storage Devices in Vehicles," Office Action for U.S. Appl. No. 13/559,054, mailed Dec. 3, 2012, 11 pages.

Taylor et al., "Apparatus, Method and Article for Physical Security of Power Storage Devices in Vehicles," U.S. Appl. No. 14/012,845, filed Aug. 28, 2013, 64 pages.

Wu et al., "Battery Configuration for an Electric Vehicle," U.S. Appl. No. 61/716,388, filed Oct. 19, 2012, 37 pages.

Wu et al., "Apparatus, Method and Article for a Power Storage Device Compartment," Office Action for U.S. Appl. No. 13/559,125, mailed Feb. 24, 2014, 28 pages.

Wu et al., "Apparatus, Method and Article for Providing Information Regarding Availability of Power Storage Devices at a Power Storage Device Collection, Charging and Distribution Machine," U.S. Appl. No. 14/022,140, filed Sep. 9, 2013, 56 pages.

Wu et al., "Apparatus, Method and Article for Providing Information Regarding Availability of Power Storage Devices at a Power Storage Device Collection, Charging and Distribution Machine," Office Action mailed Mar. 5, 2014, for U.S. Appl. No. 14/022,140, 8 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," Office Action for U.S. Appl. No. 13/559,333, mailed Jul. 3, 2013, 14 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," Office Action mailed Nov. 19, 2013, for U.S. Appl. No. 14/022,147, 10 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," Office Action mailed Nov. 27, 2013, for U.S. Appl. No. 13/559,333, 19 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," U.S. Appl. No. 14/022,147, filed Sep. 9, 2013, 56 pages.

Wu et al., "Apparatus, Method and Article for Providing Locations of Power Storage Device Collection, Charging and Distribution Machines," Office Action mailed Mar. 5, 2014, for U.S. Appl. No. 14/022,147, 12 pages.

Wu, "Battery Configuration for an Electric Vehicle," U.S. Appl. No. 14/057,405, filed Oct. 18, 2013, 38 pages.

Wu et al., "Apparatus, Method and Article for Power Storage Device Failure Safety," U.S. Appl. No. 14/071,134, filed Nov. 4, 2013, 68 pages.

Wu et al., "Apparatus, Method and Article for Power Storage Device Failure Safety," Office Action for U.S. Appl. No. 14/071,134, mailed Feb. 12, 2014, 14 pages.

Extended European Search Report dated Apr. 24, 2015, for corresponding EP Application No. 12817097.4, 9 pages.


Huang et al., "Apparatus, Method and Article for Vehicle Turn Signals," Office Action mailed May 14, 2015, for U.S. Appl. No. 14/079,894, 9 pages.

Japanese Office Action with English Translation dated Mar. 31, 2015, for corresponding JP Application No. 2014-523014, 9 pages.

Luke et al., "Apparatus, Method and Article for Redistributing Power Storage Devices, Such as Batteries, Between Collection, Charging and Distribution Machines," Office Action mailed Mar. 13, 2015, for U.S. Appl. No. 13/559,091, 33 pages.

Luke et al., "Apparatus, Method and Article for Authentication, Security and Control of Power Storage Devices, Such as Batteries, Based on User Profiles," Office Action mailed May 11, 2015, for U.S. Appl. No. 13/559,010, 26 pages.

\* cited by examiner



**FIG. 1**






FIG. 2









**FIG. 3**






**FIG. 4**



**FIG. 5****FIG. 6**

**FIG. 7****FIG. 8**



**FIG. 9****FIG. 10****FIG. 11**

## 1

**APPARATUS, METHOD AND ARTICLE FOR  
AUTHENTICATION, SECURITY AND  
CONTROL OF POWER STORAGE DEVICES,  
SUCH AS BATTERIES**

**CROSS REFERENCE TO RELATED  
APPLICATIONS**

This application claims the benefit under 35 U.S.C. 119(e) of the filing date of U.S. provisional patent application Ser. No. 61/511,900 entitled "APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES" and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/647,936 entitled "APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES" and filed May 16, 2012, U.S. provisional patent application Ser. No. 61/534,753 entitled "APPARATUS, METHOD AND ARTICLE FOR REDISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES, BETWEEN COLLECTION, CHARGING AND DISTRIBUTION MACHINES" and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/534,761 entitled "APPARATUS, METHOD AND ARTICLE FOR AUTHENTICATION, SECURITY AND CONTROL OF POWER STORAGE DEVICES SUCH AS BATTERIES" and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/534,772 entitled "APPARATUS, METHOD AND ARTICLE FOR AUTHENTICATION, SECURITY AND CONTROL OF POWER STORAGE DEVICES, SUCH AS BATTERIES, BASED ON USER PROFILES" and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/511,887 entitled "THERMAL MANAGEMENT OF COMPONENTS IN ELECTRIC MOTOR DRIVE VEHICLES" and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/647,941 entitled "THERMAL MANAGEMENT OF COMPONENTS IN ELECTRIC MOTOR DRIVE VEHICLES" and filed May 16, 2012, U.S. provisional patent application Ser. No. 61/511,880 entitled "DYNAMICALLY LIMITING VEHICLE OPERATION FOR BEST EFFORT ECONOMY" and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/557,170 entitled "APPARATUS, METHOD, AND ARTICLE FOR PHYSICAL SECURITY OF POWER STORAGE DEVICES IN VEHICLES" and filed Nov. 8, 2011, U.S. provisional patent application Ser. No. 61/581,566 entitled "APPARATUS, METHOD AND ARTICLE FOR A POWER STORAGE DEVICE COMPARTMENT" and filed Dec. 29, 2011, U.S. provisional patent application Ser. No. 61/601,404 entitled "APPARATUS, METHOD AND ARTICLE FOR PROVIDING VEHICLE DIAGNOSTIC DATA" and filed Feb. 21, 2012, U.S. provisional patent application Ser. No. 61/601,949 entitled "APPARATUS, METHOD AND ARTICLE FOR PROVIDING LOCATIONS OF POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINES" and filed Feb. 22, 2012, and U.S. provisional patent application Ser. No. 61/601,953 entitled "APPARATUS, METHOD AND ARTICLE FOR PROVIDING INFORMATION REGARDING AVAILABILITY OF POWER STORAGE DEVICES AT A POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINE" and filed Feb. 22, 2012.

## 2

**BACKGROUND**

**1. Technical Field**

The present disclosure generally relates to the charging and energy release from rechargeable electrical power storage devices (e.g., secondary batteries, supercapacitors or ultracapacitors), which may be suitable for use in a variety of fields or applications, for instance transportation and non-transportation uses.

**2. Description of the Related Art**

There are a wide variety of uses or applications for portable electrical power storage devices.

One such application is in the field of transportation. Hybrid and all electrical vehicles are becoming increasingly common. Such vehicles may achieve a number of advantages over traditional internal combustion engine vehicles. For example, hybrid or electrical vehicles may achieve higher fuel economy and may have little or even zero tail pipe pollution. In particular, all electric vehicles may not only have zero tail pipe pollution, but may be associated with lower overall pollution. For example, electrical power may be generated from renewable sources (e.g., solar, hydro). Also for example, electrical power may be generated at generation plants that produce no air pollution (e.g., nuclear plants). Also for example, electrical power may be generated at generation plants that burn relatively "clean burning" fuels (e.g., natural gas), which have higher efficiency than internal combustion engines, and/or which employ pollution control or removal systems (e.g., industrial air scrubbers) which are too large, costly or expensive for use with individual vehicles.

Personal transportation vehicles such as combustion engine powered scooters and/or motorbikes are ubiquitous in many places, for example in the many large cities of Asia. Such scooters and/or motorbikes tend to be relatively inexpensive, particular as compared to automobiles, cars or trucks. Cities with high numbers of combustion engine scooters and/or motorbikes also tend to be very densely populated and suffer from high levels of air pollution. When new, many combustion engine scooters and/or motorbikes are equipped with a relatively low polluting source of personal transportation. For instance, such scooters and/or motorbikes may have higher mileage ratings than larger vehicles. Some scooters and/or motorbikes may even be equipped with basic pollution control equipment (e.g., catalytic converter). Unfortunately, factory specified levels of emission are quickly exceeded as the scooters and/or motorbikes are used and either not maintained and/or as the scooters and/or motorbikes are modified, for example by intentional or unintentional removal of catalytic converters. Often owners or operators of scooters and/or motorbikes lack the financial resources or the motivation to maintain their vehicles.

It is known that air pollution has a negative effect on human health, being associated with causing or exacerbating various diseases (e.g., various reports tie air pollution to emphysema, asthma, pneumonia, cystic fibrosis as well as various cardiovascular diseases). Such diseases take large numbers of lives and severely reduce the quality of life of countless others.

**BRIEF SUMMARY**

Zero tail pipe pollution alternatives to combustion engines would greatly benefit air quality, and hence the health of large populations.

While the zero tail pipe emissions benefit of all-electric vehicles are appreciated, adoption of all-electric vehicles by large populations has been slow. One of the reasons appears to be the cost, particularly the cost of secondary batteries.



Another one of the reasons appears to be the limited driving range available on a single charge of a battery, and the relatively long time (e.g., multiple hours) necessary to fully recharge a secondary battery when depleted.

The approaches described herein may address some of the issues which have limited adoption of zero tail pipe emission technology, particularly in densely crowded cities, and in populations with limited financial resources.

For example, some of the approaches described herein employ collection, charging and distribution machines, which may be otherwise be termed as kiosks or vending machines, to collect, charge and distribute electrical power storage devices (e.g., batteries, supercapacitors or ultracapacitors). Such machines may be distributed about a city or other region at a variety of locations, such as convenience stores or existing gas or petrol filling stations.

The collection, charging and distribution machines may maintain a stock of fully charged or almost fully charged electrical storage devices for use by end users. The collection, charging and distribution machines may collect, receive or otherwise accept depleted electrical storage devices, for example as returned by end users, recharging such for reuse by subsequent end users.

Thus, as a battery or other electrical power storage device reaches or approaches the end of its stored charge, an end user may simply replace, exchange or otherwise swap batteries or other electrical power storage devices. This may address issues related to cost, as well as limited range and relatively long recharging times.

As previously noted, secondary batteries and other electrical power storage devices are relatively expensive. Thus, it is beneficial to stock the least number of electrical power storage devices possible, while still ensuring that demand for such is satisfied.

A portable electrical energy storage device security system for a portable electrical energy storage device may be summarized as including at least one controller; and at least one communications module coupled to the at least one controller, wherein the at least one controller is configured to: receive information regarding authentication of an external device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device, or of an external device for powering of the external device by the portable electrical energy storage device; and make a determination regarding allowing the charging from the device, or make a determination regarding allowing the powering of the device, based on the information regarding authentication.

The configured portable electrical energy storage device security system may be integrated as part of the portable electrical energy storage device. The external device may be a charging device and wherein the at least one controller may be further configured to accept the portable electrical energy storage device charge from the charging device if the charging device is authenticated based on the information regarding authentication. The accepting the portable electrical energy storage device charge may include sending a signal enabling the portable electrical energy storage device to be charged. The portable electrical energy storage device security system may further include a switch coupled to at least one terminal of the portable electrical energy storage device and to a cell the portable electrical energy storage device, the switch configured to be activated by a control signal generated by the controller of the configured portable electrical energy storage device security system, wherein the controller is configured to: send the signal in a manner enabling the portable electrical energy storage device to be charged, such

that the control signal causes the switch to close to complete a circuit such as to allow electrical current to flow from the charging device causing the portable electrical energy storage device to charge if the charging device is authenticated based on the information regarding authentication; and upon the portable electrical energy storage device being disconnected from the charging device, send the signal in a manner preventing the portable electrical energy storage from accepting a charge, such that the control signal causes the switch to break the circuit and prevent electrical current to flow from the charging device. The at least one controller may be configured to receive the information regarding authentication via a wireless signal transmitted from the external device, and wherein the wireless signal transmitted from the from the external device may not be detectable outside a specified maximum range from the portable electrical energy storage device security system communications module. The portable electrical energy storage device security system may further include a tamper-resistant housing within which the portable electrical energy storage device security system is housed, the tamper-resistant housing configured to destroy an operational condition of the portable electrical energy storage device if the tamper-resistant housing were opened in an unauthorized manner. The tamper-resistant housing may include a frangible portion configured to render an open circuit to destroy the operational condition in response to tampering or attempted tampering of the tamper-resistant housing. The frangible portion may be configured to render the open circuit by conductive paths formed in a frangible substrate of the frangible portion being configured to break in response to tampering. The controller may be further configured to: request information regarding authentication of the external device for powering of the external device by the portable electrical energy storage device; and determine how much energy to release, if any, from the portable electrical energy storage device for use by the external device, based on a response received, if any, to the requesting of information regarding authentication of the external device. The external device may be a vehicle and wherein the information regarding authentication of the external device may be information regarding the vehicle or a user associated with the vehicle. How much energy to release from the portable electrical energy storage device for use by the vehicle may be determined based on a vehicle performance profile of the vehicle. The controller may be configured to cause more energy to be released from the portable electrical energy storage device for use by the vehicle than for other vehicles having a lower vehicle performance profile than the vehicle. How much energy to release from the portable electrical energy storage device for use by the vehicle may be determined based on a profile of a user associated with the vehicle. The controller may be further configured to cause more energy to be released from the portable electrical energy storage device for use by the vehicle than for one or more other user profiles associated with a lower payment amount for portable electrical energy storage device usage than the user profile.

A method of operating a portable electrical energy storage device security system may be summarized as including receiving, by the portable electrical energy storage device security system of a portable electrical energy storage device, information regarding authentication of an external device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device or for powering of the external device by the portable electrical energy storage device; and making a determination, by the portable electrical energy storage device security system, regarding allowing the charging from the device, or making a



5

determination, by the configured portable electrical energy storage device security system, regarding allowing the powering of the device, based on the information regarding authentication.

The portable electrical energy storage device security system may be integrated as part of the portable electrical energy storage device. The external device may be a charging device and further comprising accepting the portable electrical energy storage device charge from the charging device if the charging device is authenticated based on the information regarding authentication. The accepting the portable electrical energy storage device charge may include sending a signal enabling the portable electrical energy storage device to be charged. The method may further include sending the signal in a manner enabling the portable electrical energy storage device to be charged, such that the control signal causes a switch to close to complete a circuit and allow electrical current to flow from the charging device causing the portable electrical energy storage device to charge if the charging device is authenticated based on the information regarding authentication; and once the portable electrical energy storage device is disconnected from the charging device, sending the signal in a manner preventing the portable electrical energy storage from accepting a charge, such that the control signal causes the switch to break the circuit and prevent electrical current to flow from the charging device. The method may further include receiving the information regarding authentication via a wireless signal transmitted from the from the external device, wherein the wireless signal transmitted from the from the external device is not detectable outside a specified maximum range from the portable electrical energy storage device. The method may further include destroying an operational condition of the portable electrical energy storage device if a tamper-resistant housing of the portable electrical energy storage device security system is opened in an unauthorized manner. The method may further include requesting information regarding authentication of the external device for powering of the external device by the portable electrical energy storage device; and determining how much energy to release, if any, from the portable electrical energy storage device for use by the external device, based on a response received, if any, to the requesting of information regarding authentication of the external device. The external device may be a vehicle and wherein the information regarding authentication of the external device may be information regarding the vehicle or a user associated with the vehicle. How much energy to release from the portable electrical energy storage device for use by the vehicle may be determined based on a vehicle performance profile of the vehicle. The method may further include causing more energy to be released from the portable electrical energy storage device for use by the vehicle than for other vehicles having a lower vehicle performance profile than the vehicle. How much energy to release from the portable electrical energy storage device for use by the vehicle may be determined based on a profile of a user associated with the vehicle. The method may further include causing more energy to be released from the portable electrical energy storage device for use by the vehicle than for one or more other user profiles associated with a lower payment amount for portable electrical energy storage device usage than the user profile.

A portable electrical energy storage device may be summarized as including a battery cell; and a security system operably coupled to the cell, the security system configured to allow or prevent the portable electrical energy storage device from accepting a charge; and allow or prevent energy from the cell to be released.

6

The battery cell and security system may be housed within a tamper-resistant housing of the portable electrical energy storage device, the tamper-resistant housing including a frangible portion configured to render an open circuit to destroy an operational condition of the portable electrical energy storage device in response to tampering or attempted tampering of the tamper-resistant housing. The security system may include at least one processor; at least one communications module coupled to the at least one processor; and at least one processor-readable memory that stores instructions executable by the at least one processor to cause the at least one processor to: determine whether to accept, for the portable electrical energy storage device, a portable electrical energy storage device charge from a portable electrical energy storage device charging system based on information received regarding authentication of the portable electrical energy storage device charging system; and determine how much energy to release, if any, from the portable electrical energy storage device for use by an external device, based on a response received or lack of a response received to a request from the security system for information regarding authentication of the external device. The instructions executable by the at least one processor may cause the at least one processor to accept the portable electrical energy storage device charge from the portable electrical energy storage device charging system if the portable electrical energy storage device charging system is authenticated based on the information received regarding authentication of the portable electrical energy storage device charging system. The accepting the portable electrical energy storage device charge from the portable electrical energy storage device charging system may include the at least one processor sending a signal enabling the portable electrical energy storage device to be charged by the portable electrical energy storage device charging system. The instructions executable by the at least one processor may cause the at least one processor to, if a response is received to the request for information regarding authentication, the response indicating the external device is positively not authorized to use the portable electrical energy storage device, prevent any further release of energy from the cell to the external device. The security system may be configured to allow or prevent energy from the cell to be released at particular levels according to corresponding levels of authentication by the security system of a external device intended to use the portable electrical energy storage device.

A non-transitory computer readable storage medium of a portable electrical energy storage device security system having computer executable instructions thereon may be summarized as including, when executed causing a processor of the portable electrical energy storage device security system to: receive information regarding authentication of an external device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device or for powering of the external device by the portable electrical energy storage device; and make a determination regarding allowing the charging from the device, or make a determination regarding allowing the powering of the device, based on the information regarding authentication.

The external device may be a charging device and may further include accepting the portable electrical energy storage device charge from the charging device if the charging device is authenticated based on the information regarding authentication. The accepting the portable electrical energy storage device charge may include sending a signal enabling the portable electrical energy storage device to be charged.



BRIEF DESCRIPTION OF THE SEVERAL  
VIEWS OF THE DRAWINGS

In the drawings, identical reference numbers identify similar elements or acts. The sizes and relative positions of elements in the drawings are not necessarily drawn to scale. For example, the shapes of various elements and angles are not drawn to scale, and some of these elements are arbitrarily enlarged and positioned to improve drawing legibility. Further, the particular shapes of the elements as drawn, are not intended to convey any information regarding the actual shape of the particular elements, and have been solely selected for ease of recognition in the drawings.

FIG. 1 is a schematic view of a collection, charging and distribution machine along with a number of electrical power storage devices according to one non-limiting illustrated embodiment, along with an electric scooter or motorbike, and an electrical service provided via an electrical grid.

FIG. 2 is a block diagram of the collection, charging and distribution machine of FIG. 1, according to one non-limiting illustrated embodiment.

FIG. 3 is a block diagram of the portable electrical energy storage device of FIG. 1, according to one non-limiting illustrated embodiment.

FIG. 4 is a schematic view of the portable electrical energy storage device security system controller of FIG. 3, according to one non-limiting illustrated embodiment.

FIG. 5 is a flow diagram showing a high level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment.

FIG. 6 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment, including accepting the portable electrical energy storage device charge, useful in the method of FIG. 5.

FIG. 7 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment, including sending a control signal to enable and prevent charging of the portable electrical energy storage device, useful in the method of FIG. 5.

FIG. 8 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment, including determining how much energy to release, if any, from the portable electrical energy storage device for use by the external device, useful in the method of FIG. 5.

FIG. 9 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment, including determining how much energy to release, based on a vehicle performance profile of the vehicle, useful in the method of FIG. 8.

FIG. 10 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one non-limiting illustrated embodiment, including causing more energy to be released for a certain vehicle performance profile, useful in the method of FIG. 9.

FIG. 11 is a flow diagram showing a low level method of operating the portable electrical energy storage device security system controller of FIG. 3 and FIG. 4, according to one

non-limiting illustrated embodiment, including determining how much energy to release based on a user profile, useful in the method of FIG. 8.

## DETAILED DESCRIPTION

In the following description, certain specific details are set forth in order to provide a thorough understanding of various disclosed embodiments. However, one skilled in the relevant art will recognize that embodiments may be practiced without one or more of these specific details, or with other methods, components, materials, etc. In other instances, well-known structures associated with vending apparatus, batteries, supercapacitors or ultracapacitors, power converters including but not limited to transformers, rectifiers, DC/DC power converters, switch mode power converters, controllers, and communications systems and structures and networks have not been shown or described in detail to avoid unnecessarily obscuring descriptions of the embodiments.

Unless the context requires otherwise, throughout the specification and claims which follow, the word “comprise” and variations thereof, such as, “comprises” and “comprising” are to be construed in an open, inclusive sense that is as “including, but not limited to.”

Reference throughout this specification to “one embodiment” or “an embodiment” means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, the appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment.

The use of ordinals such as first, second and third does not necessarily imply a ranked sense of order, but rather may only distinguish between multiple instances of an act or structure.

Reference to portable electrical power storage device means any device capable of storing electrical power and releasing stored electrical power including but not limited to batteries, supercapacitors or ultracapacitors. Reference to batteries means chemical storage cell or cells, for instance rechargeable or secondary battery cells including but not limited to nickel cadmium alloy or lithium ion battery cells.

The headings and Abstract of the Disclosure provided herein are for convenience only and do not interpret the scope or meaning of the embodiments.

FIG. 1 shows an environment 100 including a collection, charging and distribution machine 102, according to one illustrated embodiment.

The collection, charging and distribution machine 102 may take the form of a vending machine or kiosk. The collection, charging and distribution machine 102 has a plurality of receivers, compartments or receptacles 104a, 104b-104n (only three called out in FIG. 1, collectively 104) to removably receive portable electrical energy storage devices (e.g., batteries, supercapacitors or ultracapacitors) 106a-106n (collectively 106) for collection, charging and distribution. As illustrated in FIG. 1, some of the receivers 104 are empty, while other receivers 104 hold portable electrical energy storage devices 106. While FIG. 1 shows a single portable electrical energy storage device 106 per receiver 104, in some embodiments each receiver 104 may hold two or even more portable electrical energy storage devices 106. For example, each of the receivers 104 may be sufficiently deep to receive three portable electrical energy storage devices 106. Thus, for example, the collection, charging and distribution machine 102 illustrated in FIG. 1 may have a capacity capable of simultaneously holding 40, 80 or 120 portable electrical energy storage devices 106.



The portable electrical energy storage devices **106** may take a variety of forms, for example batteries (e.g., array of battery cells) or supercapacitors or ultracapacitors (e.g., array of ultracapacitor cells). For example, the portable electrical energy storage devices **106z** may take the form of rechargeable batteries (i.e., secondary cells or batteries). The portable electrical energy storage devices **106z** may, for instance, be sized to physically fit, and electrically power, personal transportation vehicles, such as all-electric scooters or motorbikes **108**. As previously noted, combustion engine scooters and motorbikes are common in many large cities, for example in Asia, Europe and the Middle East. The ability to conveniently access charged batteries throughout a city or region may allow the use of all-electric scooters and motorbikes **108** in place of combustion engine scooters and motorbikes, thereby alleviating air pollution, as well as reducing noise.

The portable electrical energy storage devices **106** (only visible for portable electrical energy storage device **106z**) may include a number of electrical terminals **110a**, **110b** (two illustrated, collectively **110**), accessible from an exterior of the portable electrical energy storage device **106z**. The electrical terminals **110** allow charge to be delivered from the portable electrical energy storage device **106z**, as well as allow charge to be delivered to the portable electrical energy storage device **106z** for charging or recharging the same. While illustrated in FIG. 1 as posts, the electrical terminals **110** may take any other form which is accessible from an exterior of the portable electrical energy storage device **106z**, including electrical terminals positioned within slots in a battery housing. As the portable electrical energy storage devices **106** may be lent, leased, and/or rented out to the public, it is desirable to control how and in what circumstances the portable electrical energy storage devices **106** may be charged and/or release energy, even while outside the collection, charging and distribution machine **102** or otherwise in the possession of users. This control of the portable electrical energy storage devices **106** helps to prevent theft and/or misuse and also enables control of various performance levels of various portable electrical energy storage devices **106**. Systems and methods for charging the portable electrical energy storage devices **106**, including a security system for controlling such charging and energy release, are described in more detail below with reference to FIGS. 2-7, and are useful in the overall system for collection, charging and distribution of portable electrical energy storage devices **106** described herein.

The collection, charging and distribution machine **102** is positioned at some location **112** at which the collection, charging and distribution machine **102** is conveniently and easily accessible by various end users. The location may take any of a large variety of forms, for example, a retail environment such as a convenience store, supermarket, gas or petrol station, or service shop. Alternatively, the collection, charging and distribution machine **102** may stand alone at a location **112** not associated with an existing retail or other business, for example in public parks or other public places. Thus, for example, collection, charging and distribution machines **102** may be located at each store of a chain of convenience stores throughout a city or region. Such may advantageously rely on the fact that convenience stores are often sited or distributed based on convenience to the target population or demographic. Such may advantageously rely on pre-existing leases on storefronts or other retail locations to allow an extensive network of collection, charging and distribution machines **102** to be quickly developed in a city or region.

Quickly achieving a large network which is geographically well distributed to serve a target population enhances the ability to depend on such a system and likely commercial success of such an effort.

The location **112** may include an electrical service **114** to receive electrical power from a generating station (not shown) for example via a grid **116**. The electrical service **114** may, for example, include one or more of an electrical service meter **114a**, a circuit panel (e.g., circuit breaker panel or fuse box) **114b**, wiring **114c**, and electrical outlet **114d**. Where the location **112** is an existing retail or convenience store, the electrical service **114** may be an existing electrical service, so may be somewhat limited in rating (e.g., 120 volts, 240 volts, 220 volts, 230 volts, 15 amps).

Neither the operator of the retail location **112**, nor the owner, distributor or operator of the collection, charging and distribution machine **102** may wish to bear the costs of upgrading the electrical service **114**. Yet, quick charging is desired in order to maintain an adequate supply of portable electrical energy storage devices **106** available for use by end users. The ability to quickly charge while maintaining existing or otherwise limited rated electrical service is addressed in U.S. provisional patent application Ser. No. 61/511,900, entitled "APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES" and filed Jul. 26, 2011.

Optionally, the collection, charging and distribution machine **102** may include or be coupled to a source of renewable electrical power. For example, where installed in an outside location the collection, charging and distribution machine **102** may include an array of photovoltaic (PV) cells **118** to produce electrical power from solar insolation. Alternatively, the collection, charging and distribution machine **102** may be electrically coupled to a microturbine (e.g., wind turbine) or PV array positioned elsewhere at the location **112**, for instance on a roof top or pole mounted at a top of a pole (not shown).

The collection, charging and distribution machine **102** may be communicatively coupled to one or more remotely located computer systems, such as back end or back office systems (only one shown) **120**. The back end or back office systems **120** may collect data from and/or control a plurality of collection, charging and distribution machine **102** distributed about an area, such as a city. The communications may occur over one or more communications channels including one or more networks **122**, or non-networked communications channels. Communications may be over one or more wired communications channels (e.g., twisted pair wiring, optical fiber), wireless communications channels (e.g., radio, microwave, satellite, 801.11 compliant). Networked communications channels may include one or more local area networks (LANs), wide area networks (WANs), extranets, intranets, or the Internet including the Worldwide Web portion of the Internet.

The collection, charging and distribution machine **102** may include a user interface **124**. The user interface may include a variety of input/output (I/O) devices to allow an end user to interact with the collection, charging and distribution machine **102**. Various I/O devices are called out and described in reference to FIG. 2, which follows.

FIG. 2 shows the collection, charging and distribution machine **102** of FIG. 1, according to one illustrated embodiment.



## 11

The collection, charging and distribution machine **102** includes a control subsystem **202**, a charging subsystem **204**, a communications subsystem **206**, and a user interface subsystem **208**.

The control subsystem **202** includes a controller **210**, for example a microprocessor, microcontroller, programmable logic controller (PLC), programmable gate array (PGA), application specific integrated circuit (ASIC) or another controller capable of receiving signals from various sensors, performing logical operations, and sending signals to various components. Typically, the controller **210** may take the form of a microprocessor (e.g., INTEL, AMD, ATOM). The control subsystem **202** may also include one or more non-transitory processor- or computer-readable storage media, for example read only memory (ROM) **212**, random access memory (RAM) **214**, and data store **216** (e.g., solid-state storage media such as flash memory or EEPROM, spinning storage media such as hard disk). The non-transitory processor- or computer-readable storage media **212**, **214**, **216** may be in addition to any non-transitory storage medium (e.g., registers) which is part of the controller **210**. The control subsystem **202** may include one or more buses **218** (only one illustrated) coupling various components together, for example one or more power buses, instruction buses, data buses, etc.

As illustrated, the ROM **212**, or some other one of the non-transitory processor- or computer-readable storage media **212**, **214**, **216**, stores instructions and/or data or values for variables or parameters. The sets of data may take a variety of forms, for example a lookup table, a set of records in a database, etc. The instructions and sets of data or values are executable by the controller **110**. Execution of the instructions and sets of data or values causes the controller **110** to perform specific acts to cause the collection, charging and distribution machine **102** to collect, charge, and distribute portable energy storage devices. Specific operation of the collection, charging and distribution machine **102** is described herein and also below with reference to various flow diagrams (FIGS. 5-11) in the context of being an external device to charge the portable electrical energy storage devices **106**.

The controller **210** may use RAM **214** in a conventional fashion, for volatile storage of instructions, data, etc. The controller **210** may use data store **216** to log or retain information, for example telemetric information related to collection, charging and/or distribution or collection of the portable electric power storage devices **106** and/or operation of the collection, charging and distribution machine **102** itself. The instructions are executable by the controller **210** to control operation of the collection, charging and distribution machine **102** in response to end user or operator input, and using data or values for the variables or parameters.

The control subsystem **202** receives signals from various sensors and/or other components of the collection, charging and distribution machine **102** which include information that characterizes or is indicative of operation, status, or condition of such other components. Sensors are represented in FIG. 2 by the letter S appearing in a circle along with appropriate subscript letters.

For example, one or more position sensors  $S_{P1}$ - $S_{PN}$  may detect the presence or absence of portable electrical power storage device **106** at each of the receivers **104**. The position sensors  $S_{P1}$ - $S_{PN}$  may take a variety of forms. For example, the position sensors  $S_{P1}$ - $S_{PN}$  may take the form of mechanical switches that are closed, or alternatively opened, in response to contact with a portion of a respective portable electrical power storage device **106** when the portable electrical power

## 12

storage device **106** is inserted into the receiver **104**. Also for example, the position sensors  $S_{P1}$ - $S_{PN}$  may take the form of optical switches (i.e., optical source and receiver) that are closed, or alternatively opened, in response to contact with a portion of a respective portable electrical power storage device **106** when the portable electrical power storage device **106** is inserted into the receiver **104**. Also for example, the position sensors  $S_{P1}$ - $S_{PN}$  may take the form of electrical sensors or switches that are closed, or alternatively opened, in response to detecting a closed circuit condition created by contact with the terminals **110** of a respective portable electrical power storage device **106** when the portable electrical power storage device **106** is inserted into the receiver **104**, or an open circuit condition that results from the lack of a respective portable electrical power storage device **106** in the receiver **104**. These examples are intended to be non-limiting, and it is noted that any other structures and devices for detecting the presence/absence or even the insertion of the portable electrical power storage devices **106** into receivers may be employed.

For example, one or more charge sensors  $S_{C1}$ - $S_{CN}$  may detect charge of the portable electrical power storage devices **106** at each of the receivers **104**. Charge sensors  $S_{C1}$ - $S_{CN}$  may detect the amount of charge stored by the portable electrical power storage devices **106**. Charge sensors  $S_{C1}$ - $S_{CN}$  may additionally detect an amount of charge and/or rate of charging being supplied to ones of the portable electrical power storage devices **106** at each of the receivers **104**. Such may allow assessment of current (i.e., temporal) charge condition or status of each portable electrical power storage device **106**, as well as allow feedback control over charging of same, including control over rate of charging. Charge sensors  $S_{C1}$ - $S_{CN}$  may include any variety of current and/or voltage sensors.

For example, one or more charge sensors  $S_{T1}$  (only one shown) may detect or sense a temperature at the receivers **104** or in the ambient environment.

The control subsystem **202** provides signals to various actuators and/or other components responsive to control signals, which signals include information that characterizes or is indicative of an operation the component is to perform or a state or condition in which the components should enter. Control signals, actuators or other components responsive to control signals are represented in FIG. 2 by the letter C appearing in a circle along with appropriate subscript letters.

For example, one or more engine control signals  $C_{A1}$ - $C_{AN}$  may affect the operation of one or more actuators **220** (only one illustrated). For instance, a control signal  $C_{A1}$  may cause movement of an actuator **220** between a first and a second position or change a magnetic field produced by the actuator **220**. The actuator **220** may take any of a variety of forms, including but not limited to a solenoid, an electric motor such as a stepper motor, or an electromagnet. The actuator **220** may be coupled to operate a latch, lock or other retainer mechanism **222**. The latch, lock or other retainer mechanism **222** may selectively secure or retain one or more portable electrical power storage devices **106** (FIG. 1) in the receiver **104** (FIG. 1). For instance, the latch, lock or other retainer mechanism **222** may physically couple to a complimentary structure that is part of a housing of the portable electrical power storage devices **106** (FIG. 1). Alternatively, the latch, lock or other retainer mechanism **222** may magnetically couple to a complimentary structure that is part of a housing of the portable electrical power storage devices **106** (FIG. 1). Also for instance, the latch, lock or other mechanism may open a receiver **104** (FIG. 1), or may allow a receiver **104** to be opened, to receive a partially or fully discharged portable



## 13

electrical power storage device **106** for charging. For example, the actuator may open and/or close a door to the receiver **104** (FIG. 1), to selectively provide access to a portable electrical power storage device **106** (FIG. 1) received therein. Also for example, the actuator may open and/or close a latch or lock, allowing an end user to open and/or close a door to the receiver **104** (FIG. 1), to selectively provide access to a portable electrical power storage device **106** (FIG. 1) received therein.

The control subsystem **202** may include one or more ports **224a** to provide control signals to one or more ports **224b** of the charging subsystem **206**. The ports **224a**, **224b** may provide bi-directional communications. The control subsystem **202** may include one or more ports **226a** to provide control signals to one or more ports **226b** of the user interface subsystem **208**. The ports **226a**, **226b** may provide bi-directional communications.

The charging subsystem **204** includes various electrical and electronic components to charge portable electrical power storage devices **106** when positioned or received in the receivers **104**. For example, the charging subsystem **204** may include one or more power buses or power bus bars, relays, contactors or other switches (e.g., insulated gate bipolar transistors or IGBTs, metal oxide semiconductor transistors or MOSFETs), rectifier bridge(s), current sensors, ground fault circuitry, etc. The electrical power is supplied via contacts that can take any of a variety of forms, for instance terminals, leads, posts, etc. The contacts allow electrical coupling of various components. Some possible implementations are illustrated in FIG. 2. Such is not intended to be exhaustive. Additional components may be employed while other components may be omitted.

The illustrated charging subsystem **204** includes a first power converter **230** that receives electrical power from the electrical service **114** (FIG. 1) via a line or cord **232**. The power will typically be in the form of single, two or three phase AC electrical power. As such, the first power converter **230** may need to convert and otherwise condition the electrical power received via the electrical services **114** (FIG. 1), for example for rectifying an AC waveform to DC, transforming voltage, current, phase, as well as reducing transients and noise. Thus, the first power converter **230** may include a transformer **234**, rectifier **236**, DC/DC power converter **238**, and filter(s) **240**.

The transformer **234** may take the form of any variety of commercially available transformers with suitable ratings for handling the power received via the electrical service **114** (FIG. 1). Some embodiments may employ multiple transformers. The transformer **234** may advantageously provide galvanic isolation between the components of the collection, charging and distribution machine **102** and the grid **116** (FIG. 1). The rectifier **236** may take any of variety of forms, for example a full bridge diode rectifier or a switch mode rectifier. The rectifier **236** may be operated to transform AC electrical power to DC electrical power. The DC/DC power converter **238** may be any of a large variety of forms. For example, DC/DC power converter **238** may take the form a switch mode DC/DC power converter, for instance employing IGBTs or MOSFETs in a half or full bridge configuration, and may include one or more inductors. The DC/DC power converter **238** may have any number of topologies including a boost converter, buck converter, synchronous buck converter, buck-boost converter or fly-back converter. The filter(s) **240** may include one or more capacitors, resistors, Zener diodes or other elements to suppress voltage spikes, or to remove or reduce transients and/or noise.

## 14

The illustrated charging subsystem **204** may also receive electrical power from a renewable power source, for example the PV array **118** (FIG. 1). Such may be converted or conditioned by the first power converter **230**, for example being supplied directly to the DC/DC power converter **238**, bypassing the transformer **236** and/or rectifier **236**. Alternatively, the illustrated charging subsystem **204** may include a dedicated power converter to convert or otherwise condition such electrical power.

The illustrated charging subsystem **204** may optionally include second power converter **242** that receives electrical power from one or more portable electrical power storage devices **106** (FIG. 1) via one or more lines **244**, for charging other ones of the portable electrical power storage devices **106**. As such, the second power converter **242** may need to convert and/or otherwise condition the electrical power received from portable electrical power storage devices **106**, for example optionally transforming voltage or current, as well as reducing transients and noise. Thus, the second power converter **242** may optionally include a DC/DC power converter **246** and/or filter(s) **248**. Various types of DC/DC power converters and filters are discussed above.

The illustrated charging subsystem **204** includes a plurality of switches **250** responsive to the control signals delivered via ports **224a**, **224b** from the control subsystem **202**. The switches may be operable to selectively couple a first number or set of portable electrical power storage devices **106** to be charged from electrical power supplied by both the electrical service via the first power converter **230** and from electrical power supplied by a second number or set of portable electrical power storage devices **106**. The first number or set of portable electrical power storage devices **106** may include a single portable electrical power storage device **106**, two, or even more portable electrical power storage devices **106**. The second number or set of portable electrical power storage devices **106** may include a single portable electrical power storage device **106**, two, or even more portable electrical power storage devices **106**. The portable electrical power storage devices **106** are represented in FIG. 2 as loads  $L_1, L_2, \dots, L_N$ .

The communications subsystem **206** may additionally include one or more communications modules or components which facilitate communications with the various components of a back end or back office system **120** (FIG. 1) and/or various components of the portable electrical power storage devices **106**. The communications subsystem **206** may, for example, include one or more modems **252** or one or more Ethernet or other types of communications cards or components **254**. A port **256a** of the control subsystem **202** may communicatively couple the control subsystem **202** with a port **256b** of the communications subsystem **206**. The communications subsystem **206** may provide wired and/or wireless communications. For example, the communications subsystem **206** may provide components enabling short range (e.g., via Bluetooth, near field communication (NFC), radio frequency identification (RFID) components and protocols) or longer range wireless communications (e.g., over a wireless LAN, satellite, or cellular network) with various other devices external to the collection, charging and distribution machine **102**, including the portable electrical energy storage devices **106**. The communications subsystem **206** may include one or more ports, wireless receivers, wireless transmitters or wireless transceivers to provide wireless signal paths to the various remote components or systems. The remote communications subsystem **206** may include one or more bridges or routers suitable to handle network traffic



## 15

including switched packet type communications protocols (TCP/IP), Ethernet or other networking protocols.

The user interface system **208** includes one or more user input/output (I/O) components. For example, user interface system **208** may include a touch screen display **208a**, operable to present information and a graphical user interface (GUI) to an end user and to receive indications of user selections. The user interface system **208** may include a keyboard or keypad **208b**, and/or a cursor controller (e.g., mouse, trackball, trackpad) (not illustrated) to allow an end user to enter information and/or select user selectable icons in a GUI. The user interface system **208** may include a speaker **208c** to provide aural messages to an end user and/or a microphone **208d** to receive spoken user input such as spoken commands.

The user interface system **208** may include a card reader **208e** to read information from card type media **209**. The card reader **208e** may take a variety of forms. For instance, the card reader **208e** may take the form of, or include, a magnetic stripe reader for reading information encoded in a magnetic stripe carried by a card **209**. For instance, the card reader **208e** may take the form of, or include, a machine-readable symbol (e.g., barcode, matrix code) card reader for reading information encoded in a machine-readable symbol carried by a card **209**. For instance, the card reader **208e** may take the form of, or include, a smart card reader for reading information encoded in a non-transitory medium carried by a card **209**. Such may, for instance, include media employing radio frequency identification (RFID) transponders or electronic payment chips (e.g., near field communications (NFC) chips). Thus, the card reader **208e** may be able to read information from a variety of card media **209**, for instance credit cards, debit cards, gift cards, prepaid cards, as well as identification media such as drivers licenses. The card reader **208e** may also be able to read information encoded in a non-transitory medium carried by the portable electrical energy storage devices **106**, and may also include RFID transponders, transceivers, NFC chips and/or other communication devices to communicate information to the portable electrical energy storage devices **106** (e.g., for authentication of the portable electrical energy storage devices **106** and/or authentication of the collection, charging and distribution machine **102** to the portable electrical energy storage devices **106**).

The user interface system **208** may include a bill acceptor **208f** and a validator and/or coin acceptor **208g** to accept and validate cash payments. Such may be highly useful in servicing populations who lack access to credit. Bill acceptor and validator **208f** and/or coin acceptor **208g** may take any variety of forms, for example those that are currently commercially available and used in various vending machines and kiosks.

FIG. 3 is a block diagram of the portable electrical energy storage device **106z** of FIG. 1, according to one non-limiting illustrated embodiment.

Shown is a portable electrical energy storage device housing **302**, electrical terminals **110a**, **110b**, a battery cell **304**, security system controller **306**, and a secure access panel **314**. The battery cell **304** is any rechargeable type of electrochemical cell that converts stored chemical energy into electrical energy. As described above, the electrical terminals **110a**, **110b** are accessible from an exterior of the portable electrical energy storage device **106z**. The electrical terminals **110** allow charge to be delivered from the portable electrical energy storage device **106z**, as well as allow charge to be delivered to the portable electrical energy storage device **106z** for charging or recharging the same through conductive terminal connections **312a** and **312b** to the battery cell **304**. While illustrated in FIG. 3 as posts, the electrical terminals **110a** and **110b** may take any other form which is accessible

## 16

from an exterior of the portable electrical energy storage device **106z**, including electrical terminals positioned within slots in the battery housing **302**.

Operably coupled to terminal lines **312a** and **312b** and the security system controller **308** are two switches **310a** and **310b** electronically controlled by the security system controller **306**. In a closed position, the switches **310a** and **310b** operate to complete a circuit allowing electrical current to flow from or be delivered to the portable electrical energy storage device **106z**. In an open position, the switches **310a** and **310b** operate to break the circuit, preventing electrical current from flowing from and preventing electrical current from being delivered to the portable electrical energy storage device **106z**. In some embodiments, the switches **310a** and **310b** may be any type of electronic or electromechanical switch responsive to signals received from the security system controller **308**. The switches **310a** and **310b** may include various electrical and/or electronic components including various types of actuators, contacts, relays, rectifiers, power transistors, IGBTs, and/or MOSFETs, etc.

In some embodiments, the portable electric storage device **106z** is by default in a state where it cannot accept a charge unless it receives authentication from the charging device or other external device (e.g., via a wireless signal). For example, such authentication may be made based on information received via components enabling short range (e.g., via Bluetooth, near field communication (NFC), radio frequency identification (RFID) components and protocols) or longer range wireless communications (e.g., over a wireless LAN, satellite, or cellular network) with various other devices external to the portable electric storage device **106z**. The information received on which the authentication may be based may include, but is not limited to, one or more of a code, a password, electronic credentials, electronic security certificate, encrypted data, encryption key, electronic key, etc.

The security system controller **306** is configured to send a signal to open or close the switches **310a** and **310b** based on an authentication from an external device to which the portable electric storage device **106z** is to be connected to receive a charge or to deliver energy. The portable electric storage device security system controller **306** is also configured to regulate the amount of energy to release from the portable electric storage device **106z**, if any, when both switches **310a** and **310b** are in the open position, via regulating current flowing through the portable electric storage device security system controller **306** on lines **314a** and **314b** coupled to the terminals **110a** and **110b** and the portable electric storage device security system controller **306**, and line **308** coupled to the portable electric storage device security system controller **306** and the battery cell **304**. The regulation of the energy release from the portable electric storage device **106z** may be in response to various information or other wireless signals from devices external to the portable electric storage device **106z**. For example, in some instances, a user may select a desired power or performance level of the portable electric storage device **106z** at the point of purchase, rent or exchange at the collection, charging and distribution machine **102**, and paying a premium for doing so. Also, the amount of energy released may depend on one or more of the following as indicated by information received by the portable electric storage device security system controller **306**: a user profile, a vehicle profile of a user, the subscription level of the user, particular promotions being offered related to the identified user or to general users, demographic information of the user such as (income level, gender, age, net worth, marital status, etc.).



The housing **302** is constructed of a polymer or other durable material of sufficient thickness to protect the battery cell **304** and portable electric storage device security system controller **306** from outside elements and tampering. For example the walls of the housing may be at least approximately 0.25 inch thick and completely surround the battery cell **304** and portable electric storage device security system controller **306** (except for in some embodiments a small vent hole in the housing) such that the battery cell **304** and portable electric storage device security system controller **306** cannot be accessed without a key or other specialized tool to open a locked access panel **314**.

One or more portions of the security system controller **306** may be constructed to be either tamper-proof, tamper resistant, or tamper indicative. For example, one or more portions may be frangible, and designed to render an open circuit in response to tampering or attempted tampering. For instance, one or more switches **310** or electrical leads, traces, or conductive paths may be formed in a frangible substrate, which breaks in response to tampering. The frangible substrate may take any of a large variety of forms including glasses, ceramics, or even more traditional circuit board materials if suitably thin as to tear, rip, or break if subject to forces associated or expected to be applied if tampered. In some instances, it may be sufficient if the electrical lead, trace, or conductive path is frangible, while the substrate (e.g., circuit board, housing **202**) is not frangible. For instance, such may be accomplished where the substrate is sufficiently compliant that the substrate will bend without breaking, while the bending causes a discontinuity to occur in the electrical path. Alternatively, a structure such as a blade or knife may be triggered by attempted tampering, to sever the electrical path, resulting in an open circuit condition which renders the portable electrical energy storage device **106z** inoperable.

The housing **302** may provide a protection to prevent or deter tampering, and may be formed of suitably strong and resilient materials (e.g., ABS plastic). Such may not only prevent or deter tampering, but may leave a visible indication of any tampering attempts. For example, the housing **302** may include a strong outer layer of a first color (e.g., black) within an inner layer of a second color (e.g., fluorescent orange) there beneath. Such will render attempts to cut through the housing **302** visibly apparent.

It is also noted that the housing **302** may serve as the aforementioned substrate, or a frangible substrate may be secured to an inner portion of the housing, for instance, via suitable adhesives. Thus, tampering with the housing may break or damage a circuit connection, again rendering the device inoperable.

In some embodiments, some or all of the components of the portable electric storage device security system controller **306** may be located outside of the portable electric storage device **106z** as a separate device that actuates the switches **310a** and **310b** (e.g., via a wireless control signal). Also additional or fewer switches may be used sufficient to prevent or allow the flow of current to and from the battery cell **304**.

FIG. 4 is a schematic view of the portable electrical energy storage device security system controller **306** of FIG. 1 and FIG. 3, according to one non-limiting illustrated embodiment.

The portable electric storage device security system controller **306** includes a controller **410**, a communications subsystem **406**, and a power interface/manager.

The controller **410**, for example is a microprocessor, microcontroller, programmable logic controller (PLC), programmable gate array (PGA), application specific integrated circuit (ASIC) or another controller capable of receiving sig-

nals from various sensors, performing logical operations, and sending signals to various components. Typically, the controller **410** may take the form of a microprocessor (e.g., INTEL, AMD, ATOM). The portable electric storage device security system controller **306** may also include one or more non-transitory processor- or computer-readable storage media, for example read only memory (ROM) **412**, random access memory (RAM) **414**, and other storage **416** (e.g., solid-state storage media such as flash memory or EEPROM, spinning storage media such as hard disk). The non-transitory processor- or computer-readable storage media **412**, **414**, **416** may be in addition to any non-transitory storage medium (e.g., registers) which is part of the controller **410**. The portable electric storage device security system controller **306** may include one or more buses **418** (only one illustrated) coupling various components together, for example one or more power buses, instruction buses, data buses, etc.

As illustrated, the ROM **412**, or some other one of the non-transitory processor- or computer-readable storage media **412**, **414**, **416**, stores instructions and/or data or values for variables or parameters. The sets of data may take a variety of forms, for example a lookup table, a set of records in a database, etc. The instructions and sets of data or values are executable by the controller **410**. Execution of the instructions and sets of data or values causes the controller **410** to perform specific acts to cause the portable electric storage device security system controller **306** to generate control signals to allow or prevent the portable electric storage device **106z** from accepting a charge or releasing energy, or otherwise regulate the release of energy from the portable electric storage device **106z**. Specific operation of the portable electric storage device security system controller **306** is described herein and also below with reference to various flow diagrams (FIGS. 5-11).

The controller **410** may use RAM **414** in a conventional fashion, for volatile storage of instructions, data, etc. The controller **410** may use data store **416** to log or retain information, for example, information regarding user profile information, vehicle profile information, security codes, credentials, security certificates, passwords, the subscription level of users, particular promotions being offered related to the identified user or to general users, demographic information of users such as (income level, gender, age, net worth, marital status, etc.), information regarding user vehicle locations and telematic and/or telemetric user vehicle information, information regarding portable electrical energy storage device charge capacity, information regarding route information of users, etc. The instructions are executable by the controller **410** to control operation of the portable electric storage device security system controller **306** in response to input from remote systems such as those of external devices including but not limited to: charging devices, vehicles, user identification devices (cards, electronic keys, etc.) vehicles, collection, charging and distribution machines, collection, charging and distribution machine service systems, user mobile devices, user vehicles, and end user or operator input, and using data or values for the variables or parameters.

The control subsystem **402** may also receive signals from various sensors and/or components of an external device via the communications subsystem **206** of collection, charging and distribution machine **102**. This information may include information that characterizes or is indicative of the authenticity, authorization level, operation, status, or condition of such components.

The communications subsystem **406** may include one or more communications modules or components which facilitates communications with the various components of external



devices and also the various components of the collection, charging and distribution machine **102** of FIG. 1 (e.g., such as to receive software updates or data updates of user profile, vehicle profile and/or promotional campaign information) and one or more user mobile communication devices, such that data may be exchanged between the devices for authentication purposes. The communications subsystem **406** may provide wired and/or wireless communications. The communications subsystem **406** may include one or more ports, wireless receivers, wireless transmitters or wireless transceivers to provide wireless signal paths to the various remote components or systems. The communications subsystem **406** may, for example, include components enabling short range (e.g., via Bluetooth, near field communication (NFC), radio frequency identification (RFID) components and protocols) or longer range wireless communications (e.g., over a wireless LAN, satellite, or cellular network) and may include one or more modems **452** or one or more Ethernet or other types of communications cards or components **454** for doing so. The remote communications subsystem **406** may include one or more bridges or routers suitable to handle network traffic including switched packet type communications protocols (TCP/IP), Ethernet or other networking protocols.

In some embodiments, some or all of the components of the portable electric storage device security system controller **306** may be located outside of the portable electric storage device **106z** as a separate device that actuates the switches **310a** and **310b** of the portable electric storage device **106z** (e.g., via a wireless control signal) sent via the communications subsystem **406**.

The Power Interface/Manager **420** is controllable by the controller **410** and is configured to provide power to the portable electric storage device security system controller **306** from either the battery cell **304** or external device. Also, the Power Interface/Manager **420** is configured to regulate the release of power from the portable electric storage device **106z** according to control signals received from the controller **410** and includes various components operable for doing so such as electrical transformers, converters, rectifiers, etc.

FIG. 5 shows a high level method **500** of operating the portable electrical energy storage device security system controller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment.

At **502**, the portable electric storage device **106z** receives information regarding authentication of an external device to which to connect the portable electric storage device **106z** for charging of the portable electric storage device **106z** or for powering of the external device by the portable electrical energy storage device.

At **504**, the portable electric storage device **106z** makes a determination regarding allowing the charging from the device, or makes a determination, regarding allowing the powering of the device, based on the information regarding authentication.

FIG. 6 shows a low level method **600** of operating the portable electrical energy storage device security system controller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment, including accepting the portable electrical energy storage device charge, useful in the method of FIG. 5.

At **602**, the portable electric storage device security system controller **306** accepts the portable electrical energy storage device charge from the charging device if the charging device is authenticated based on the information regarding authentication.

FIG. 7 shows a low level method **700** of operating the portable electrical energy storage device security system con-

troller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment, including sending a control signal to enable and prevent charging of the portable electrical energy storage device, useful in the method of FIG. 5.

At **702**, the portable electric storage device security system controller **306** sends the signal in a manner enabling the portable electrical energy storage device to be charged, such that the control signal causes a switch to close to complete a circuit and allow electrical current to flow from the charging device causing the portable electrical energy storage device to charge if the charging device is authenticated based on the information regarding authentication.

At **704**, once the portable electrical energy storage device is disconnected from the charging device, the portable electric storage device security system controller **306** sends the signal in a manner preventing the portable electrical energy storage from accepting a charge, such that the control signal causes the switch to break the circuit and prevent electrical current to flow from the charging device.

FIG. 8 shows a low level method **800** of operating the portable electrical energy storage device security system controller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment, including determining how much energy to release, if any, from the portable electrical energy storage device for use by the external device, useful in the method of FIG. 5.

At **802**, the portable electric storage device security system controller **306** requests information regarding authentication of the external device for powering of the external device by the portable electrical energy storage device.

At **803**, the portable electric storage device security system controller **306** determines how much energy to release, if any, from the portable electrical energy storage device for use by the external device, based on a response received, if any, to the requesting of information regarding authentication of the external device.

FIG. 9 shows a low level method **900** of operating the portable electrical energy storage device security system controller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment, including determining how much energy to release, based on a vehicle performance profile of the vehicle, useful in the method of FIG. 8.

At **902**, the portable electric storage device security system controller **306** determines how much energy to release from the portable electrical based on the vehicle performance profile of the vehicle.

FIG. 10 shows a low level method **1000** of operating the portable electrical energy storage device security system controller **306** of FIGS. 3 and 4, according to one non-limiting illustrated embodiment, including causing more energy to be released for a certain vehicle performance profile, useful in the method of FIG. 9.

At **1002**, the portable electric storage device security system controller **306** causes more energy to be released from the portable electrical energy storage device for use by the vehicle than for other vehicles having a lower vehicle performance profile than the vehicle.

FIG. 11 shows a low level method **1100** of operating the portable electrical energy storage device security system controller of FIG. 3, according to one non-limiting illustrated embodiment, including determining how much energy to release based on a user profile, useful in the method of FIG. 8.

At **1102**, the portable electric storage device security system controller **306** causes more energy to be released from the portable electrical energy storage device for use by the vehicle than for one or more other user profiles associated



with a lower payment amount for portable electrical energy storage device usage than the user profile.

For example, if the user pays a higher premium or subscription rate, then the user may qualify for an portable electric storage device 106z with higher performance characteristics, such as a higher power output.

The various methods described herein may include additional acts, omit some acts, and/or may perform the acts in a different order than set out in the various flow diagrams.

The foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of block diagrams, schematics, and examples. Insofar as such block diagrams, schematics, and examples contain one or more functions and/or operations, it will be understood by those skilled in the art that each function and/or operation within such block diagrams, flowcharts, or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. In one embodiment, the present subject matter may be implemented via one or more microcontrollers. However, those skilled in the art will recognize that the embodiments disclosed herein, in whole or in part, can be equivalently implemented in standard integrated circuits (e.g., Application Specific Integrated Circuits or ASICs), as one or more computer programs executed by one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs executed by one or more controllers (e.g., microcontrollers) as one or more programs executed by one or more processors (e.g., microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of ordinary skill in the art in light of the teachings of this disclosure.

When logic is implemented as software and stored in memory, logic or information can be stored on any non-transitory computer-readable medium for use by or in connection with any processor-related system or method. In the context of this disclosure, a memory is a nontransitory computer- or processor-readable storage medium that is an electronic, magnetic, optical, or other physical device or means that non-transitorily contains or stores a computer and/or processor program. Logic and/or the information can be embodied in any computer-readable medium for use by or in connection with an instruction execution system, apparatus, or device, such as a computer-based system, processor-containing system, or other system that can fetch the instructions from the instruction execution system, apparatus, or device and execute the instructions associated with logic and/or information.

In the context of this specification, a “computer-readable medium” can be any physical element that can store the program associated with logic and/or information for use by or in connection with the instruction execution system, apparatus, and/or device. The computer-readable medium can be, for example, but is not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus or device. More specific examples (a non-exhaustive list) of the computer readable medium would include the following: a portable computer diskette (magnetic, compact flash card, secure digital, or the like), a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM, EEPROM, or Flash memory), a portable compact disc read-only memory (CDROM), and digital tape.

The various embodiments described above can be combined to provide further embodiments. To the extent that they

are not inconsistent with the specific teachings and definitions herein, all of the U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet, including but not limited to: U.S. provisional patent application Ser. No. 61/511,900 entitled “APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES” and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/647,936 entitled “APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES” and filed May 16, 2012, U.S. provisional patent application Ser. No. 61/534,753 entitled “APPARATUS, METHOD AND ARTICLE FOR REDISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES, BETWEEN COLLECTION, CHARGING AND DISTRIBUTION MACHINES” and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/534,761 entitled “APPARATUS, METHOD AND ARTICLE FOR AUTHENTICATION, SECURITY AND CONTROL OF POWER STORAGE DEVICES SUCH AS BATTERIES” and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/534,772 entitled “APPARATUS, METHOD AND ARTICLE FOR AUTHENTICATION, SECURITY AND CONTROL OF POWER STORAGE DEVICES, SUCH AS BATTERIES, BASED ON USER PROFILES” and filed Sep. 14, 2011, U.S. provisional patent application Ser. No. 61/511,887 entitled “THERMAL MANAGEMENT OF COMPONENTS IN ELECTRIC MOTOR DRIVE VEHICLES” and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/647,941 entitled “THERMAL MANAGEMENT OF COMPONENTS IN ELECTRIC MOTOR DRIVE VEHICLES” and filed May 16, 2012, U.S. provisional patent application Ser. No. 61/511,880 entitled “DYNAMICALLY LIMITING VEHICLE OPERATION FOR BEST EFFORT ECONOMY” and filed Jul. 26, 2011, U.S. provisional patent application Ser. No. 61/557,170 entitled “APPARATUS, METHOD, AND ARTICLE FOR PHYSICAL SECURITY OF POWER STORAGE DEVICES IN VEHICLES” and filed Nov. 8, 2011, U.S. provisional patent application Ser. No. 61/581,566 entitled “APPARATUS, METHOD AND ARTICLE FOR A POWER STORAGE DEVICE COMPARTMENT” and filed Dec. 29, 2011, U.S. provisional patent application Ser. No. 61/601,404 entitled “APPARATUS, METHOD AND ARTICLE FOR PROVIDING VEHICLE DIAGNOSTIC DATA” and filed Feb. 21, 2012, U.S. provisional patent application Ser. No. 61/601,949 entitled “APPARATUS, METHOD AND ARTICLE FOR PROVIDING LOCATIONS OF POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINES” and filed Feb. 22, 2012, and U.S. provisional patent application Ser. No. 61/601,953 entitled “APPARATUS, METHOD AND ARTICLE FOR PROVIDING INFORMATION REGARDING AVAILABILITY OF POWER STORAGE DEVICES AT A POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINE” and filed Feb. 22, 2012, U.S. application Ser. No. 13/559,314, filed on Jul. 26, 2012, naming Hok-Sum Horace Luke, Matthew Whiting Taylor and Huang-Cheng Hung as inventors and entitled “APPARATUS, METHOD AND ARTICLE FOR COLLECTION, CHARGING AND DISTRIBUTING POWER STORAGE DEVICES, SUCH AS BATTERIES”, U.S. application Ser. No. 13/559,264, filed on Jul. 26, 2012 naming Hok-Sum Horace Luke and Matthew Whiting Taylor as inventors and



entitled “DYNAMICALLY LIMITING VEHICLE OPERATION FOR BEST EFFORT ECONOMY”, U.S. application Ser. No. 13/559,054, filed on Jul. 26, 2012, naming Matthew Whiting Taylor, Yi-Tsung Wu, Hok-Sum Horace Luke and Huang-Cheng Hung as inventors and entitled “APPARATUS, METHOD, AND ARTICLE FOR PHYSICAL SECURITY OF POWER STORAGE DEVICES IN VEHICLES”, U.S. application Ser. No. 13/559,390, filed on Jul. 26, 2012, naming Ching Chen, Hok-Sum Horace Luke, Matthew Whiting Taylor, Yi-Tsung Wu as inventors and entitled “APPARATUS, METHOD AND ARTICLE FOR PROVIDING VEHICLE DIAGNOSTIC DATA”, U.S. application Ser. No. 13/559,343, filed on Jul. 26, 2012, naming Yi-Tsung Wu, Matthew Whiting Taylor, Hok-Sum Horace Luke and Jung-Hsiu Chen as inventors and entitled “APPARATUS, METHOD AND ARTICLE FOR PROVIDING INFORMATION REGARDING AVAILABILITY OF POWER STORAGE DEVICES AT A POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINE”, and U.S. application Ser. No. 13/559,064, filed on Jul. 26, 2012, naming Hok-Sum Horace Luke, Yi-Tsung Wu, Jung-Hsiu Chen, Yulin Wu, Chien Ming Huang, TsungTing Chan, Shen-Chi Chen and Feng Kai Yang as inventors and entitled “APPARATUS, METHOD AND ARTICLE FOR RESERVING POWER STORAGE DEVICES AT RESERVING POWER STORAGE DEVICE COLLECTION, CHARGING AND DISTRIBUTION MACHINES” are incorporated herein by reference, in their entirety. Aspects of the embodiments can be modified, if necessary, to employ systems, circuits and concepts of the various patents, applications and publications to provide yet further embodiments.

While generally discussed in the environment and context of collection, charging and distribution of portable electrical energy storage devices for use with personal transportation vehicle such as all-electric scooters and/or motorbikes, the teachings herein can be applied in a wide variety of other environments, including other vehicular as well as non-vehicular environments.

The above description of illustrated embodiments, including what is described in the Abstract of the Disclosure, is not intended to be exhaustive or to limit the embodiments to the precise forms disclosed. Although specific embodiments and examples are described herein for illustrative purposes, various equivalent modifications can be made without departing from the spirit and scope of the disclosure, as will be recognized by those skilled in the relevant art.

These and other changes can be made to the embodiments in light of the above-detailed description. In general, in the following claims, the terms used should not be construed to limit the claims to the specific embodiments disclosed in the specification and the claims, but should be construed to include all possible embodiments along with the full scope of equivalents to which such claims are entitled. Accordingly, the claims are not limited by the disclosure.

We claim:

1. A portable electrical energy storage device security system for a portable electrical energy storage device, comprising:

at least one controller; and  
at least one communications module coupled to the at least one controller, wherein the at least one controller is configured to:

receive information regarding authentication of an external charger device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device, or of an external device

to be powered for powering of the external device to be powered by the portable electrical energy storage device; and

make a determination regarding allowing the charging from the external charger device, or make a determination regarding allowing the powering of the external device to be powered, based on the information regarding authentication, wherein how much energy to release from the portable electrical energy storage device for use by the external device to be powered is determined based on a profile of a user associated with the external device to be powered.

2. The portable electrical energy storage device security system of claim 1, wherein the configured portable electrical energy storage device security system is integrated as part of the portable electrical energy storage device.

3. The portable electrical energy storage device security system of claim 1, wherein the at least one controller is configured to make the determination regarding allowing the charging from the external charger device and wherein the at least one controller is further configured to accept the portable electrical energy storage device charge from the external charger device if the external charger device is authenticated based on the information regarding authentication.

4. The portable electrical energy storage device security system of claim 3, wherein the accepting the portable electrical energy storage device charge includes sending a signal enabling the portable electrical energy storage device to be charged.

5. The portable electrical energy storage device security system of claim 4, further comprising:

a switch coupled to at least one terminal of the portable electrical energy storage device and to a cell of the portable electrical energy storage device, the switch configured to be activated by a control signal generated by the controller of the configured portable electrical energy storage device security system, wherein the controller is configured to:

send the signal in a manner enabling the portable electrical energy storage device to be charged, such that the control signal causes the switch to close to complete a circuit such as to allow electrical current to flow from the external charger device causing the portable electrical energy storage device to charge if the external charger device is authenticated based on the information regarding authentication; and

upon the portable electrical energy storage device being disconnected from the external charger device, send the signal in a manner preventing the portable electrical energy storage from accepting a charge, such that the control signal causes the switch to break the circuit and prevent electrical current to flow from the external charger device.

6. The portable electrical energy storage device security system of claim 1, wherein the at least one controller is configured to receive the information regarding authentication via a wireless signal transmitted from the external charger device or from the external device to be powered, and wherein the wireless signal transmitted from the external charger device or from the external device to be powered is not detectable outside a specified maximum range from the portable electrical energy storage device security system communications module.

7. The portable electrical energy storage device security system of claim 1, further comprising a tamper-resistant housing within which the portable electrical energy storage device security system is housed, the tamper-resistant hous-



25

ing configured to destroy an operational condition of the portable electrical energy storage device if the tamper-resistant housing were opened in an unauthorized manner.

8. The portable electrical energy storage device security system of claim 7, wherein the tamper-resistant housing includes a frangible portion configured to render an open circuit to destroy the operational condition in response to tampering or attempted tampering of the tamper-resistant housing.

9. The portable electrical energy storage device security system of claim 8, wherein the frangible portion is configured to render the open circuit by conductive paths formed in a frangible substrate of the frangible portion being configured to break in response to tampering.

10. The portable electrical energy storage device security system of claim 1, wherein the controller is further configured to:

request information regarding authentication of the external device to be powered for powering of the external device to be powered by the portable electrical energy storage device; and

determine how much energy to release, if any, from the portable electrical energy storage device for use by the external device to be powered, based on a response received, if any, to the requesting of information regarding authentication of the external device to be powered.

11. The portable electrical energy storage device security system of claim 10, wherein the external device to be powered is a vehicle and wherein the information regarding authentication of the external device to be powered is information regarding the vehicle or a user associated with the vehicle.

12. The portable electrical energy storage device security system of claim 11, wherein how much energy to release from the portable electrical energy storage device for use by the vehicle is determined based on a vehicle performance profile of the vehicle.

13. The portable electrical energy storage device security system of claim 11, wherein the controller is configured to cause more energy to be released from the portable electrical energy storage device for use by the vehicle than for other vehicles having a lower vehicle performance profile than the vehicle.

14. The portable electrical energy storage device security system of claim 11, wherein how much energy to release from the portable electrical energy storage device for use by the vehicle is determined based on a profile of a user associated with the vehicle.

15. The portable electrical energy storage device security system of claim 11, wherein the controller is further configured to cause more energy to be released from the portable electrical energy storage device for use by the vehicle than for one or more other user profiles associated with a lower payment amount for portable electrical energy storage device usage than the user profile.

16. A method of operating a portable electrical energy storage device security system, the method comprising:

receiving, by the portable electrical energy storage device security system of a portable electrical energy storage device, information regarding authentication of an external charger device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device or for powering of an external device to be powered by the portable electrical energy storage device; and

making a determination, by the portable electrical energy storage device security system, regarding allowing the charging from the external charger device, or making a

26

determination, by the configured portable electrical energy storage device security system, regarding allowing the powering of the external device to be powered, based on the information regarding authentication, wherein how much energy to release from the portable electrical energy storage device for use by the external device to be powered is determined based on a profile of a user associated with the external device to be powered.

17. The method of claim 16, wherein the portable electrical energy storage device security system is integrated as part of the portable electrical energy storage device.

18. The method of claim 16, further comprising accepting the portable electrical energy storage device charge from the external charger device if the external charger device is authenticated based on the information regarding authentication.

19. The method of claim 18, wherein the accepting the portable electrical energy storage device charge includes sending a signal enabling the portable electrical energy storage device to be charged.

20. The method of claim 19, further comprising:

sending the signal in a manner enabling the portable electrical energy storage device to be charged, such that the control signal causes a switch to close to complete a circuit and allow electrical current to flow from the external charger device causing the portable electrical energy storage device to charge if the external charger device is authenticated based on the information regarding authentication; and

once the portable electrical energy storage device is disconnected from the external charger device, sending the signal in a manner preventing the portable electrical energy storage from accepting a charge, such that the control signal causes the switch to break the circuit and prevent electrical current to flow from the external charger device.

21. The method of claim 16, further comprising:

receiving the information regarding authentication via a wireless signal transmitted from the external charger device or from the external device to be powered, wherein the wireless signal transmitted from the external charger device or from the external device to be powered is not detectable outside a specified maximum range from the portable electrical energy storage device.

22. The method of claim 16, further comprising:

destroying an operational condition of the portable electrical energy storage device if a tamper-resistant housing of the portable electrical energy storage device security system is opened in an unauthorized manner.

23. The method of claim 16, further comprising:

requesting information regarding authentication of the external device to be powered for powering of the external device by the portable electrical energy storage device; and

determining how much energy to release, if any, from the portable electrical energy storage device for use by the external device to be powered, based on a response received, if any, to the requesting of information regarding authentication of the external device.

24. The method of claim 23, wherein the external device to be powered is a vehicle and wherein the information regarding authentication of the external device to be powered is information regarding the vehicle or a user associated with the vehicle.



## 27

25. The method of claim 24, wherein how much energy to release from the portable electrical energy storage device for use by the vehicle is determined based on a vehicle performance profile of the vehicle.

26. A portable electrical energy storage device, comprising: 5

a battery cell; and

a security system operably coupled to the battery cell, the security system configured to:

allow or prevent the portable electrical energy storage 10 device from accepting a charge; and

allow or prevent energy from the cell to be released based on information received regarding authentication of an external device, wherein how much energy to release 15 from the battery cell is determined based on a profile of a user associated with a vehicle to be powered by the portable electrical energy storage device.

27. The portable electrical energy storage device of claim 26, wherein the security system comprises:

at least one processor; 20

at least one communications module coupled to the at least one processor; and

at least one processor-readable memory that stores instructions executable by the at least one processor to cause the 25 at least one processor to:

determine whether to accept, for the portable electrical energy storage device, a portable electrical energy storage device charge from a portable electrical energy storage device charging system based on information received regarding authentication of the 30 portable electrical energy storage device charging system; and

determine how much energy to release, if any, from the portable electrical energy storage device for use by an external device, based on a response received or lack

## 28

of a response received to a request from the security system for information regarding authentication of the external device, wherein how much energy to release from the portable electrical energy storage device is determined based on a profile of a user associated with the external device.

28. A non-transitory computer readable storage medium of a portable electrical energy storage device security system having computer executable instructions thereon that, when executed cause a processor of the portable electrical energy storage device security system to:

receive information regarding authentication of an external charger device to which to connect the portable electrical energy storage device for charging of the portable electrical energy storage device or for powering of an external device to be powered by the portable electrical energy storage device; and

make a determination regarding allowing the charging from the external charger device, or make a determination regarding allowing the powering of the external device to be powered, based on the information regarding authentication, wherein how much energy to release from the portable electrical energy storage device is determined based on a profile of a user associated with the external device to be powered. 25

29. The computer readable storage medium of claim 28, further comprising accepting the portable electrical energy storage device charge from the external charger device if the external charger device is authenticated based on the information regarding authentication. 30

30. The computer readable storage medium of claim 28, wherein the accepting the portable electrical energy storage device charge includes sending a signal enabling the portable electrical energy storage device to be charged.

\* \* \* \* \*