US009197990B2

(12) **United States Patent**
Root et al.

(10) **Patent No.: US 9,197,990 B2**
(45) **Date of Patent: *Nov. 24, 2015**

(54) **INTERACTIVE ADVISORY SYSTEM**

(71) Applicant: **LOCATOR IP, L.P.**, State College, PA (US)

(72) Inventors: **Steven A. Root**, Edmond, OK (US); **Michael R. Root**, Edmond, OK (US)

(73) Assignee: **Locator IP, LP**, State College, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/156,103**

(22) Filed: **Jan. 15, 2014**

(65) **Prior Publication Data**

US 2014/0206395 A1 Jul. 24, 2014

Related U.S. Application Data

(63) Continuation of application No. 10/965,088, filed on Oct. 14, 2004, now Pat. No. 8,909,679, which is a continuation of application No. 10/667,108, filed on Sep. 19, 2003, now Pat. No. 6,826,481, which is a continuation of application No. 10/322,187, filed on Dec. 16, 2002, now Pat. No. 6,754,585, which is a continuation of application No. 09/624,668, filed on Jul. 24, 2000, now Pat. No. 6,505,123.

(51) **Int. Cl.**
G06F 17/30 (2006.01)
H04W 4/02 (2009.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04W 4/02*** (2013.01); ***G01W 1/00*** (2013.01); ***G06F 17/3087*** (2013.01); ***G06Q 30/0256*** (2013.01); ***H04L 12/1845*** (2013.01); ***H04L 12/1859*** (2013.01); ***H04L 12/1877*** (2013.01); ***H04L 12/1895*** (2013.01); ***H04L 67/04*** (2013.01); ***H04L 67/18*** (2013.01); ***H04L 67/20*** (2013.01); ***H04L 67/306*** (2013.10);
(Continued)

(58) **Field of Classification Search**
CPC G06F 17/30091
USPC 707/791
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,015,366	A	4/1977	Hall, III
4,438,439	A	3/1984	Shreve

(Continued)

FOREIGN PATENT DOCUMENTS

AU	2001277030	B2	3/2006
AU	2006204945	A1	7/2006

(Continued)

OTHER PUBLICATIONS

Boselly, III, Edward, et al., "Road Weather Information Systems vol. 2: Implementation Guide," 1993, pp. 1-82.


(Continued)

Primary Examiner — Noosha Arjomandi
(74) *Attorney, Agent, or Firm* — Blank Rome LLP

(57) **ABSTRACT**

A method for providing information to a plurality of vendors located remotely from a broadcast network. A plurality of user-defined parameters are received by a user input database with at least one of the user-defined parameters including a user profile. Each of the user profiles includes a user identifier code identifying a communicator device associated with a particular user. Real-time data indicative of the spatial locations of the communicator devices is received by a communicator location database. Search information is received independently from a plurality of vendors and a data set is generated for each vendor.

25 Claims, 2 Drawing Sheets



(51) **Int. Cl.**

G01W 1/00	(2006.01)
H04L 12/18	(2006.01)
H04W 4/20	(2009.01)
H04L 29/08	(2006.01)
G06Q 30/02	(2012.01)

(52) **U.S. Cl.**

CPC ***H04L69/329*** (2013.01); ***H04W 4/20*** (2013.01); *H04L 12/189* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,459,682	A		7/1984	Mossberg
4,473,844	A		9/1984	Klein
4,521,857	A		6/1985	Reynolds, III
4,529,982	A		7/1985	Karlstrom et al.
4,577,109	A		3/1986	Hirschfeld
4,586,827	A		5/1986	Hirsch et al.
4,755,942	A		7/1988	Gardner et al.
4,774,658	A		9/1988	Lewin
4,892,335	A		1/1990	Taft
4,901,300	A		2/1990	Van Der Zande et al.
4,945,355	A		7/1990	Blanchette
4,972,319	A		11/1990	Delorme
5,111,111	A		5/1992	Stevens et al.
5,111,391	A	*	5/1992	Fields et al. 705/7.14
5,117,353	A		5/1992	Stipanovich et al.
5,122,959	A		6/1992	Nathanson et al.
5,131,020	A		7/1992	Liebesny et al.
5,206,903	A		4/1993	Kohler et al.
5,250,955	A		10/1993	Major et al.
5,265,024	A	*	11/1993	Crabill et al. 701/538
5,298,760	A		3/1994	Fuchs et al.
5,365,290	A		11/1994	Suzuki et al.
5,398,021	A	*	3/1995	Moore 340/7.48
5,416,694	A		5/1995	Parrish et al.
5,434,565	A		7/1995	Simon et al.
5,442,147	A		8/1995	Burns et al.
5,444,444	A		8/1995	Ross
5,448,696	A		9/1995	Shimada et al.
5,467,268	A		11/1995	Sisley et al.
5,481,254	A		1/1996	Gaskill et al.
5,486,830	A		1/1996	Axline, Jr. et al.
5,493,709	A		2/1996	Duckeck et al.
5,528,678	A		6/1996	Kaplan
5,544,140	A		8/1996	Seagrave et al.
5,550,981	A		8/1996	Bauer et al.
5,555,446	A		9/1996	Jasinski
5,565,863	A	*	10/1996	Simon et al. 340/947
5,606,699	A		2/1997	De Pauw et al.
5,607,187	A		3/1997	Salive et al.
5,615,121	A		3/1997	Babayev et al.
5,615,223	A		3/1997	Carr
5,615,400	A		3/1997	Cowsar et al.
5,628,050	A		5/1997	McGraw et al.
5,634,057	A		5/1997	Dickinson
5,642,303	A		6/1997	Small et al.
5,649,182	A		7/1997	Reitz
5,671,412	A		9/1997	Christiano
5,684,476	A		11/1997	Anderson
5,689,650	A		11/1997	McClelland et al.
5,703,930	A		12/1997	Miska et al.
5,706,505	A		1/1998	Fraley et al.
5,717,589	A		2/1998	Thompson et al.
5,725,253	A		3/1998	Salive et al.
5,754,782	A		5/1998	Masada
5,757,322	A		5/1998	Ray et al.
5,764,906	A		6/1998	Edelstein et al.
5,768,577	A		6/1998	Kleewein et al.
5,790,664	A		8/1998	Coley et al.
5,790,953	A		8/1998	Wang et al.
5,794,234	A		8/1998	Church et al.
5,819,227	A		10/1998	Obuchi
5,828,843	A		10/1998	Grimm et al.
5,839,088	A		11/1998	Hancock et al.
5,845,276	A		12/1998	Emerson et al.
5,848,131	A		12/1998	Shaffer et al.
5,848,378	A		12/1998	Shelton et al.
5,864,860	A		1/1999	Holmes
5,864,875	A		1/1999	Van Huben et al.
5,867,109	A		2/1999	Wiedeman
5,867,110	A		2/1999	Naito et al.
5,867,821	A		2/1999	Ballantyne et al.
5,880,958	A		3/1999	Helms et al.
5,884,267	A		3/1999	Goldenthal et al.
5,884,309	A		3/1999	Vanechanos, Jr.
5,892,917	A		4/1999	Myerson
5,893,905	A		4/1999	Main et al.
5,913,201	A		6/1999	Kocur
5,948,041	A		9/1999	Abo et al.
5,950,161	A		9/1999	Kozuma et al.
5,963,130	A		10/1999	Schlager et al.
5,974,447	A		10/1999	Cannon et al.
5,991,735	A		11/1999	Gerace
5,999,126	A		12/1999	Ito
5,999,882	A		12/1999	Simpson et al.
6,000,285	A		12/1999	Leslie et al.
6,014,090	A		1/2000	Rosen et al.
6,018,699	A		1/2000	Baron, Sr. et al.
6,021,432	A	*	2/2000	Sizer et al. 709/217
6,023,223	A		2/2000	Baxter, Jr.
6,023,765	A		2/2000	Kuhn
6,028,514	A		2/2000	Lemelson et al.
6,031,455	A		2/2000	Grube et al.
6,040,781	A		3/2000	Murray
6,043,756	A		3/2000	Bateman et al.
6,047,236	A		4/2000	Hancock et al.
6,047,327	A		4/2000	Tso et al.
6,049,776	A		4/2000	Donnelly et al.
6,070,142	A		5/2000	McDonough et al.
6,070,143	A		5/2000	Barney et al.
6,078,260	A		6/2000	Desch
6,084,510	A		7/2000	Lemelson et al.
6,088,679	A		7/2000	Barkley
6,091,959	A		7/2000	Souissi et al.
6,094,509	A		7/2000	Zheng et al.
6,098,048	A		8/2000	Dashefsky et al.
6,100,806	A		8/2000	Gaukel
6,108,699	A		8/2000	Moiin
6,112,074	A		8/2000	Pinder
6,133,912	A		10/2000	Montero
6,134,530	A		10/2000	Bunting et al.
6,138,073	A		10/2000	Uchigaki
6,148,261	A		11/2000	Obradovich et al.
6,161,092	A		12/2000	Latshaw et al.
6,167,255	A		12/2000	Kennedy, III et al.
6,177,873	B1	*	1/2001	Cragun 340/601
6,185,427	B1		2/2001	Krasner et al.
6,199,045	B1		3/2001	Giniger et al.
6,202,023	B1		3/2001	Hancock et al.
6,209,026	B1		3/2001	Ran et al.
6,212,393	B1		4/2001	Suarez et al.
6,219,667	B1		4/2001	Lu et al.
6,233,122	B1		5/2001	Summers
6,240,369	B1		5/2001	Foust
6,252,539	B1	*	6/2001	Phillips et al. ..... 342/26 D
6,252,544	B1		6/2001	Hoffberg
6,266,612	B1		7/2001	Dussell et al.
6,266,683	B1		7/2001	Yehuda et al.
6,269,309	B1		7/2001	Buckingham
6,275,774	B1		8/2001	Baron, Sr. et al.
6,295,502	B1		9/2001	Hancock et al.
6,297,766	B1		10/2001	Koeller
6,329,904	B1		12/2001	Lamb
6,333,980	B1		12/2001	Hollatz et al.
6,334,133	B1		12/2001	Thompson et al.
6,339,744	B1		1/2002	Hancock et al.
6,339,747	B1		1/2002	Daly et al.
6,347,216	B1		2/2002	Marko et al.
6,351,218	B1		2/2002	Smith
6,356,834	B2		3/2002	Hancock et al.
6,360,172	B1		3/2002	Burfeind et al.
6,363,411	B1		3/2002	Dugan et al.
6,381,535	B1		4/2002	Durocher et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,405,134	B1	6/2002	Smith et al.	
6,408,337	B1	6/2002	Dietz et al.	
6,411,687	B1	6/2002	Bohacek et al.	
6,411,809	B1	6/2002	Haakana et al.	
6,418,371	B1	7/2002	Arnold	
6,430,562	B1	8/2002	Kardos et al.	
6,446,004	B1	9/2002	Cao et al.	
6,456,852	B2	9/2002	Bar et al.	
6,462,665	B1 *	10/2002	Tarlton et al.	340/601
6,469,664	B1	10/2002	Michaelson et al.	
6,473,692	B2	10/2002	Hancock et al.	
6,484,033	B2	11/2002	Murray	
6,490,525	B2	12/2002	Baron, Sr. et al.	
6,496,776	B1	12/2002	Blumberg et al.	
6,498,987	B1	12/2002	Kelly et al.	
6,501,392	B2	12/2002	Gremmert et al.	
6,505,123	B1	1/2003	Root et al.	
6,522,875	B1	2/2003	Dowling et al.	
6,522,888	B1	2/2003	Garceran et al.	
6,526,268	B1	2/2003	Marrah et al.	
6,531,218	B2	3/2003	Hoyt et al.	
6,542,825	B2	4/2003	Jones et al.	
6,553,317	B1	4/2003	Lincoln et al.	
6,560,456	B1	5/2003	Lohtia et al.	
6,564,143	B1	5/2003	Alewine et al.	
6,571,279	B1	5/2003	Herz et al.	
6,578,005	B1	6/2003	Lesaint et al.	
6,587,813	B1	7/2003	Whitt et al.	
6,587,831	B1	7/2003	O'Brien	
6,587,851	B1	7/2003	Ditcharo et al.	
6,590,529	B2	7/2003	Schwoegler	
6,597,983	B2	7/2003	Hancock	
6,603,405	B2	8/2003	Smith	
6,609,062	B2	8/2003	Hancock	
6,611,687	B1	8/2003	Clark et al.	
6,633,900	B1	10/2003	Khalessi et al.	
6,646,559	B2	11/2003	Smith	
6,647,257	B2	11/2003	Owensby	
6,650,902	B1	11/2003	Richton	
6,654,689	B1	11/2003	Kelly et al.	
6,675,151	B1	1/2004	Thompson et al.	
6,677,894	B2	1/2004	Sheynblat et al.	
6,680,675	B1	1/2004	Suzuki	
6,684,136	B2	1/2004	Sinex	
6,697,859	B1	2/2004	Takahashi	
6,707,905	B2	3/2004	Lenard	
6,731,940	B1	5/2004	Nagendran	
6,742,002	B2	5/2004	Arrowood	
6,745,021	B1	6/2004	Stevens	
6,751,553	B2	6/2004	Young et al.	
6,753,784	B1	6/2004	Sznaider et al.	
6,754,585	B2	6/2004	Root et al.	
6,792,615	B1	9/2004	Rowe et al.	
6,798,358	B2	9/2004	Joyce et al.	
6,812,855	B1	11/2004	Sudou et al.	
6,816,878	B1 *	11/2004	Zimmers et al.	709/200
6,823,263	B1	11/2004	Kelly et al.	
6,823,315	B1	11/2004	Bucci et al.	
6,826,481	B2	11/2004	Root et al.	
6,829,233	B1	12/2004	Gilboy	
6,829,334	B1	12/2004	Zirngibl et al.	
6,836,730	B2	12/2004	Root et al.	
6,838,998	B1	1/2005	Brown et al.	
6,845,324	B2	1/2005	Smith	
6,850,895	B2	2/2005	Brodersen et al.	
6,853,915	B2	2/2005	Hubschneider et al.	
6,892,390	B1	5/2005	Lieberman et al.	
6,909,361	B2	6/2005	McCarthy et al.	
6,909,903	B2	6/2005	Wang	
6,912,545	B1	6/2005	Lundy et al.	
6,941,126	B1	9/2005	Jordan, Jr.	
6,944,447	B2	9/2005	Portman et al.	
6,962,531	B2	11/2005	Pace et al.	
6,973,384	B2	12/2005	Zhao et al.	
6,975,942	B2	12/2005	Young et al.	
6,980,909	B2	12/2005	Root et al.	
6,985,813	B2	1/2006	Root et al.	
6,985,929	B1	1/2006	Wilson et al.	
6,988,037	B2	1/2006	Root et al.	
6,989,765	B2	1/2006	Gueziec	
6,990,458	B2	1/2006	Harrison et al.	
7,010,501	B1	3/2006	Roslak et al.	
7,016,689	B2	3/2006	Clark et al.	
7,024,205	B1	4/2006	Hose	
7,024,310	B2	4/2006	Root et al.	
7,031,724	B2	4/2006	Ross et al.	
7,047,114	B1	5/2006	Rogers	
7,058,510	B2	6/2006	Kelly et al.	
7,072,666	B1	7/2006	Kullman et al.	
7,079,631	B1 *	7/2006	Kaufman	379/88.2
7,080,018	B1	7/2006	Fox et al.	
7,084,775	B1	8/2006	Smith	
7,089,116	B2	8/2006	Smith	
7,096,276	B2	8/2006	Bodin et al.	
7,103,596	B2	9/2006	Abe et al.	
7,123,926	B2	10/2006	Himmelstein	
7,139,664	B2	11/2006	Kelly et al.	
7,171,325	B2	1/2007	Hsu et al.	
7,171,372	B2	1/2007	Daniel et al.	
7,181,345	B2	2/2007	Rosenfeld et al.	
7,184,540	B2	2/2007	Dezonno et al.	
7,184,896	B1	2/2007	Benson	
7,191,064	B1	3/2007	Myers et al.	
7,191,065	B2	3/2007	Root et al.	
7,197,308	B2	3/2007	Singhal et al.	
7,212,811	B2	5/2007	Dowling et al.	
7,212,829	B1	5/2007	Lau et al.	
7,218,938	B1	5/2007	Lau et al.	
7,219,066	B2	5/2007	Parks et al.	
7,231,657	B2	6/2007	Honarvar et al.	
7,233,781	B2	6/2007	Hunter et al.	
7,248,159	B2	7/2007	Smith	
7,254,481	B2	8/2007	Yamada et al.	
7,254,588	B2	8/2007	Sung et al.	
7,269,505	B2	9/2007	Zhao et al.	
7,283,971	B1	10/2007	Levine et al.	
7,284,000	B2	10/2007	Kuehr-McLaren et al.	
7,284,033	B2	10/2007	Jhanji	
7,289,908	B2	10/2007	Root et al.	
7,299,492	B2	11/2007	Thrash et al.	
7,315,782	B2	1/2008	Root et al.	
7,327,271	B2	2/2008	Greenstein et al.	
7,330,693	B1	2/2008	Goss	
7,366,522	B2	4/2008	Thomas	
7,400,976	B2	7/2008	Young et al.	
7,403,925	B2	7/2008	Schlesinger et al.	
7,406,382	B2	7/2008	Brulle-Drews	
7,411,493	B2	8/2008	Smith	
7,426,203	B1	9/2008	McNamara et al.	
7,502,748	B1	3/2009	Baldwin et al.	
7,557,730	B2	7/2009	Gueziec	
7,567,575	B2	7/2009	Chen et al.	
7,568,217	B1	7/2009	Prasad et al.	
7,599,795	B1	10/2009	Blumberg et al.	
7,602,285	B2	10/2009	Sznaider et al.	
7,606,663	B2	10/2009	Neef et al.	
7,647,022	B2	1/2010	Ng et al.	
7,650,633	B2	1/2010	Whitson	
7,668,832	B2	2/2010	Yeh et al.	
7,706,523	B2	4/2010	Agusta	
7,720,606	B2	5/2010	Burfeind et al.	
7,917,555	B2	3/2011	Gottumukkala et al.	
8,229,467	B2	7/2012	Root et al.	
8,483,651	B1	7/2013	Zamora et al.	
2001/0029160	A1	10/2001	Aznal	
2001/0030624	A1	10/2001	Schwoegler	
2001/0042001	A1	11/2001	Goto et al.	
2001/0049584	A1	12/2001	Jones et al.	
2001/0049636	A1	12/2001	Hudda et al.	
2001/0051888	A1	12/2001	Mayhak et al.	
2001/0053999	A1	12/2001	Feinberg	
2002/0000930	A1	1/2002	Crowson et al.	
2002/0009353	A1	1/2002	Kelsey et al.	
2002/0010615	A1	1/2002	Jacobs	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0025964	A1	2/2002	Streuff et al.	
2002/0029160	A1	3/2002	Thompson et al.	
2002/0029272	A1	3/2002	Weller	
2002/0040313	A1	4/2002	Hunter et al.	
2002/0048283	A1	4/2002	Lin	
2002/0049310	A1	4/2002	Tateishi et al.	
2002/0052674	A1	5/2002	Chang et al.	
2002/0062451	A1	5/2002	Scheidt et al.	
2002/0077876	A1	6/2002	O'Meara et al.	
2002/0091568	A1	7/2002	Kraft et al.	
2002/0095333	A1	7/2002	Jokinen et al.	
2002/0147642	A1	10/2002	Avallone et al.	
2002/0160745	A1	10/2002	Wang	
2002/0165732	A1	11/2002	Ezzeddine et al.	
2002/0173981	A1	11/2002	Stewart	
2002/0175211	A1	11/2002	Dominquez et al.	
2002/0183117	A1	12/2002	Takahashi et al.	
2002/0194366	A1	12/2002	Bodin et al.	
2003/0004780	A1	1/2003	Smith et al.	
2003/0004802	A1	1/2003	Callegari	
2003/0014297	A1	1/2003	Kaufman et al.	
2003/0028410	A1	2/2003	House et al.	
2003/0055705	A1	3/2003	Kilpatrick	
2003/0059158	A1	3/2003	Lacey	
2003/0060211	A1	3/2003	Chern et al.	
2003/0068974	A1	4/2003	Kanamaluru et al.	
2003/0100315	A1	5/2003	Rankin	
2003/0113014	A1	6/2003	Katoh	
2003/0125963	A1	7/2003	Haken	
2003/0132298	A1	7/2003	Swartz et al.	
2003/0149607	A1	8/2003	Ogasawara et al.	
2003/0169367	A1	9/2003	Ranta	
2003/0171870	A1	9/2003	Gueziec	
2003/0191765	A1	10/2003	Bargh et al.	
2003/0191795	A1	10/2003	Bernardin et al.	
2003/0198337	A1	10/2003	Lenard	
2003/0200027	A1*	10/2003	Root et al.	702/3
2004/0002348	A1	1/2004	Fraccaroli	
2004/0010372	A1	1/2004	Schwoegler	
2004/0010591	A1	1/2004	Sinn et al.	
2004/0023666	A1	2/2004	Moon et al.	
2004/0059996	A1	3/2004	Fasciano	
2004/0093265	A1	5/2004	Ramchandani et al.	
2004/0107126	A1	6/2004	Kataoka et al.	
2004/0110515	A1	6/2004	Blumberg et al.	
2004/0161097	A1	8/2004	Henry	
2004/0167813	A1	8/2004	Robertson et al.	
2004/0172343	A1	9/2004	Allibhoy et al.	
2004/0199655	A1	10/2004	Davies et al.	
2004/0203854	A1	10/2004	Nowak	
2004/0221308	A1	11/2004	Cuttner et al.	
2004/0267595	A1	12/2004	Woodings et al.	
2005/0003828	A1	1/2005	Sugar et al.	
2005/0021666	A1	1/2005	Dinnage et al.	
2005/0021806	A1	1/2005	Richardson et al.	
2005/0021980	A1	1/2005	Kanai	
2005/0027449	A1	2/2005	Marsh	
2005/0040847	A1	2/2005	Unger et al.	
2005/0050008	A1	3/2005	Root et al.	
2005/0055374	A1	3/2005	Sato	
2005/0096962	A1	5/2005	Narasimhan et al.	
2005/0136917	A1	6/2005	Taylor	
2005/0136983	A1	6/2005	Agapi et al.	
2005/0174235	A1	8/2005	Davis et al.	
2005/0181803	A1	8/2005	Weaver et al.	
2005/0192724	A1	9/2005	Hendry	
2005/0227709	A1	10/2005	Chang et al.	
2005/0228873	A1	10/2005	Tapuska et al.	
2005/0240378	A1	10/2005	Smith et al.	
2005/0243784	A1	11/2005	Fitzgerald et al.	
2005/0245243	A1	11/2005	Zuniga	
2005/0251370	A1	11/2005	Li et al.	
2006/0009155	A1	1/2006	Paalasmaa et al.	
2006/0010467	A1	1/2006	Segel	
2006/0022846	A1	2/2006	Tummala	
2006/0028400	A1	2/2006	Lapstun et al.	
2006/0046740	A1	3/2006	Johnson	
2006/0111089	A1	5/2006	Winter et al.	
2006/0123053	A1	6/2006	Scannell	
2006/0142024	A1	6/2006	Thalanany et al.	
2006/0161469	A1	7/2006	Root et al.	
2006/0164259	A1	7/2006	Winkler et al.	
2006/0178140	A1	8/2006	Smith et al.	
2006/0194595	A1	8/2006	Myllynen et al.	
2006/0200480	A1	9/2006	Harris et al.	
2006/0265228	A1	11/2006	Ando	
2006/0271560	A1	11/2006	Mitchell	
2006/0293065	A1*	12/2006	Chew et al.	455/456.3
2006/0294147	A1	12/2006	Root et al.	
2007/0005363	A1	1/2007	Cucerzan et al.	
2007/0021906	A1	1/2007	Yeh et al.	
2007/0061844	A1	3/2007	Hakusui et al.	
2007/0094071	A1	4/2007	Seraji et al.	
2007/0112511	A1	5/2007	Burfeind et al.	
2007/0112519	A1*	5/2007	Root et al.	702/3
2007/0127423	A1	6/2007	Ho	
2007/0162320	A1	7/2007	Joshi et al.	
2007/0162328	A1	7/2007	Reich	
2007/0168131	A1	7/2007	Root et al.	
2007/0168524	A1	7/2007	Chao et al.	
2007/0180119	A1	8/2007	Khivesara et al.	
2007/0192159	A1	8/2007	Root et al.	
2007/0197231	A1	8/2007	Lin	
2007/0260531	A1	11/2007	Bezancon	
2007/0260708	A1	11/2007	Beaton et al.	
2007/0260741	A1	11/2007	Bezancon	
2007/0270165	A1	11/2007	Poosala	
2007/0270166	A1	11/2007	Hampel et al.	
2007/0293240	A1	12/2007	Drennan	
2008/0020702	A1	1/2008	Jendbro et al.	
2008/0021645	A1	1/2008	Lau et al.	
2008/0070550	A1	3/2008	Hose	
2008/0082264	A1	4/2008	Hill et al.	
2008/0084857	A1	4/2008	Gorti et al.	
2008/0134043	A1	6/2008	Georgis et al.	
2008/0134258	A1	6/2008	Goose et al.	
2008/0140318	A1*	6/2008	Breed	702/3
2008/0157990	A1	7/2008	Belzer et al.	
2008/0160956	A1	7/2008	Jackson et al.	
2008/0161012	A1	7/2008	Haran et al.	
2008/0162036	A1*	7/2008	Breed	701/207
2008/0183710	A1	7/2008	Serjeantson et al.	
2008/0189028	A1	8/2008	Nair et al.	
2008/0207183	A1	8/2008	Root et al.	
2008/0271120	A1	10/2008	Parkes et al.	
2008/0275759	A1	11/2008	Parkes et al.	
2008/0294478	A1	11/2008	Joshi et al.	
2008/0313037	A1	12/2008	Root et al.	
2008/0319652	A1	12/2008	Moshfeghi	
2008/0319653	A1	12/2008	Moshfeghi	
2009/0061903	A1	3/2009	Khokhar	
2009/0073885	A1	3/2009	Jalil et al.	
2009/0083150	A1	3/2009	Mashinsky	
2009/0131080	A1	5/2009	Nadler et al.	
2009/0156161	A1	6/2009	Strahs	
2009/0176511	A1	7/2009	Morrison	
2009/0176512	A1	7/2009	Morrison	
2009/0177374	A1	7/2009	Liu	
2009/0209233	A1	8/2009	Morrison	
2009/0210441	A1	8/2009	Mercer et al.	
2009/0233575	A1	9/2009	Morrison	
2009/0233633	A1	9/2009	Morrison	
2009/0239511	A1	9/2009	Chen et al.	
2009/0240428	A1	9/2009	Shahrestani	
2009/0265099	A1	10/2009	Gottlieb	
2009/0275348	A1	11/2009	Weinreich et al.	
2009/0287587	A1	11/2009	Bloebaum et al.	
2009/0305645	A1	12/2009	Watanabe	
2010/0009657	A1	1/2010	Dingler et al.	
2010/0013629	A1	1/2010	Sznaider et al.	
2010/0036717	A1	2/2010	Trest	
2010/0042483	A1	2/2010	Hipsher	
2010/0069052	A1	3/2010	Ahomaki et al.	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2010/0069093	A1	3/2010	Morrison	
2011/0230204	A1	9/2011	Root et al.	
2013/0165070	A1*	6/2013	Hoffberg	455/404.2

FOREIGN PATENT DOCUMENTS

AU	2007207616	A1	7/2007
AU	2006202473	A1	1/2010
CA	2418268	A1	1/2002
CA	2514868	A1	8/2004
CA	2594001	A1	7/2006
CN	1230265	A	9/1999
CN	1449615	A	10/2003
CN	1659602	A	8/2005
CN	1745540	A	3/2006
CN	101083784	A	12/2007
CN	101120316	A	2/2008
EP	0436263	A1	7/1991
EP	0703463	A2	3/1996
EP	0798539	A2	10/1997
EP	1143399	A1	10/2001
EP	1303965	A2	4/2003
EP	1473684	A1	11/2004
EP	1593085	A2	11/2005
EP	1856608	A2	11/2007
EP	1912409	A1	4/2008
EP	1999665	A2	12/2008
GB	2201865	A	9/1988
GB	2216319	A	10/1989
JP	08221694	A	8/1996
JP	10065596	A	3/1998
JP	H10-65596	A	3/1998
JP	11-136365	A	5/1999
JP	2000030148	A	1/2000
JP	2000167232	A	6/2000
JP	2001126170	A	5/2001
JP	2001175718	A	6/2001
JP	2002019928	A	1/2002
JP	2002056156	A	2/2002
JP	2002140451	A	5/2002
JP	2002162478	A	6/2002
JP	2002216021	A	8/2002
JP	2002251484	A	9/2002
JP	2002255465		9/2002
JP	2002255465	A	9/2002
JP	2002269335	A	9/2002
JP	2002303527	A	10/2002
JP	2003099350	A	4/2003
JP	2003186900	A	7/2003
JP	2003196284	A	7/2003
JP	2003208367	A	7/2003
JP	200245339	A	9/2003
JP	2003272078		9/2003
JP	2003280561	A	10/2003
JP	2003281694	A	10/2003
JP	2003281694	A	10/2003
JP	2003323528	A	11/2003
JP	2003337874	A	11/2003
JP	2004505501	A	2/2004
JP	2004110496		4/2004
JP	2004127044	A	4/2004
JP	2004511836	A	4/2004
JP	2004514333	A	5/2004
JP	2004157863	A	6/2004
JP	2004529543	A	9/2004
JP	2004282610	A	10/2004
JP	2004328308	A	11/2004
JP	2004334782	A	11/2004
JP	2005073147	A	3/2005
JP	2005184065	A	7/2005
JP	2005293255	A	10/2005
JP	2005-309489	A	11/2005
JP	2006011617	A	1/2006
JP	2006107136	A	4/2006
JP	2006127144	A	5/2006
JP	2006520497	A	9/2006
JP	2007-265449	A	10/2007
JP	2009524150	A	6/2009
JP	2012083743	A	4/2012
KR	20010100635	A	11/2001
KR	20020090910	A	12/2002
KR	20030075238	A	9/2003
KR	20040010513	A	1/2004
KR	20050080370	A	8/2005
KR	20110012122	A	2/2011
WO	9607110	A1	3/1996
WO	9741654	A1	11/1997
WO	9802824	A1	1/1998
WO	9819479	A1	5/1998
WO	9923591	A1	5/1999
WO	9957700	A1	11/1999
WO	0004730	A1	1/2000
WO	0004734	A1	1/2000
WO	0004737	A1	1/2000
WO	0013047	A1	3/2000
WO	0041104		7/2000
WO	0195140	A2	12/2001
WO	0209353	A2	1/2002
WO	0221864	A1	3/2002
WO	0225964	A2	3/2002
WO	WO-02/28137	A1	4/2002
WO	0239217	A2	5/2002
WO	0239732	A1	5/2002
WO	0249310	A2	6/2002
WO	03069576	A1	8/2003
WO	2004059996	A1	7/2004
WO	2004070993	A2	8/2004
WO	2005040847	A2	5/2005
WO	2006076460	A2	7/2006
WO	2006105088	A2	10/2006
WO	2007084458	A2	7/2007

OTHER PUBLICATIONS

Myers, "Personal Digital Radio Service," IBM Technical Disclosure Bulletin, vol. 38, No. 8, p. 315, Aug. 1995.

Vantive and MDSI to Provide Enterprise Wide Wireless Field Service Solution PR Newswire, Oct. 26, 1998.

Visual Staff Scheduler Pro Version 3.0 User Guide Atlas Business Solutions, Inc. 1997.

Maxima Advantage Call Center CRM Solutions, vol. 18, No. 7, Jan. 2000.

Author Unknown, "MDSI Mobile Data Solution—Innovative and Effective Mobile Workforce Management," MDSI-Advantex.com, Feb. 1999, 19 pp.

MobileCentrex.com Web Pages, Mobile Centrex, Mar. 2003, Retrieved from Archive.orq Oct. 15, 2008.

Dispatch definition, Retrieved from Wikipedia.orq Oct. 15, 2008.

Author Unknown, "iMedeon Announces Support for Microsoft Windows CE Devices for its Wireless, Web-Based Mobile Workforce Management Applications," Business Wire, Feb. 5, 2001, 2 pp., ProQuest LLC, New York, NY, USA.

Partyka, et al., "On the Road to Service," ORMS Today, Aug. 2000, pp. 1-8, Lionheart Publishing, Inc., Marietta, GA, USA.

Author Unknown, "MobileAria and WeatherBank Announce Partnership to Avert Delays, Increase Driver Productivity," Business Wire, Jun. 26, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.

Weigel, et al., "Applying GIS and OR Techniques to Solve Sears Technician-Dispatching and Home-Delivery Problems," Interfaces, Jan.-Feb. 1999, pp. 112-130, vol. 29, No. 1, Institute for Operations Research and Management Sciences.

Feldman, W. and Feldman, P., "Making Cell Phones Indispensable for Techs," Contractor; Jul. 2004; 51, 7; ABI/INFORM Global, pp. 40 and 54.

Timmins, Annmarie, Mobile Workers Sync Up, IT Support News; Dec. 1999, pp. 28 and 30.

Bisio, R., Gavazzi, F., Malaboccia, F. and Sisto, L., "Effective Resource Scheduling in Work Force Management Context for Telecommunication Work Centers," Centro Studi E. Laboratori Telecommunicazioni, Via G. Reiss Romoli, 274, 10148 Torino, Italy; pp. 1-5.

(56) **References Cited**

OTHER PUBLICATIONS

Lesaint, et al., "Dynamic Workforce Management," AI for Network: Management Systems, Apr. 14, 1997, pp. 1-5, IEE, London, UK.
Rhinehart, Ted, "City Uses GIS to monitor snow-fighting fleet," the American City & County, Apr. 1999, vol. 144, No. 4, p. 31.
Howard County Bureau of Highways, "Web-Enabled Snowplow Tracking System," Howard County, 1999, pp. 1-11.
Kruse, John, "Snow and Ice Go Hi-Tech." Mobile Radio Technology Magazine, Oct. 1, 1999.
Ding, Jin et al., WHAM: Supporting Mobile Workforce and Applications in Workflow Environments RIDE 2000, Research Issues in Data Engineering, Feb. 2000.
Collins, J.E. and Sisley E.M., 3M Company, "Automated Assignment and Scheduling of Service Personnel," AI in Corporate Service & Support; Apr. 1994, IEEE Expert; pp. 33-39.
Ohta, et al., "Real-World Community Platform: Mobile Multi-User Communication System," Multimedia Laboratories, NTT DoCoMo, Inc., 2000, pp. 601-606.
Author Unknown, "The Nexterna Clearview Dispatch Module," 2005, 2 pp., Nexterna Limited, Burlington, Ontario, Canada.
Author Unknown, "Dispenser Services Inc. Selects Web-Based Field Resource Management Solution From Nexterna," PR Newswire, Aug. 14, 2002, 2 pp., ProQuest LLC, New York, NY, USA.
Author Unknown, "Nexterna Announces Newest Release of Nexterna Clearview," PR Newswire, Sep. 26, 2002, 2 pp., ProQuest LLC, New York, NY, USA.
Author Unknown, "Nexterna.com Web Pages Nexterna Inc. 2002-2003," retrieved from Archive. Org on May 20, 2009, 31 pp.
Author Unknown, "Motorola iRadio(TM) System Hits the Road at Consumer Electronics Show 2001," PR Newswire, Jan. 4, 2001, pp. 1-2, ProQuest LLC, New York, NY, USA.
Le Comte, "Using Your Computer—Software Review," Weatherwise, Aug. 1991, pp. 48-51, vol. 44, No. 4.
Freedman, "Pinpoint Weather," Technology Review, Jun. 2003, pp. 52-58, vol. 106, No. 5, ABI/Inform Global.
Author Unknown, "Yahoo! and Weather.com Forge Multi-National Agreement to Provide Enhanced Weather Reports," Business Wire, Jan. 7, 2002, pp. 1-3, ProQuest LLC, New York, NY, USA.
Lee, Jay et al., "Statistical Analysis with Acrview GIS," 2001, Wiley Books, pp. 1-203.
Ohbuchi, et al., "Shape-Similarity Search of Three-Dimensional Models Using Parameterized Statistics," Oct. 9-11, 2002, in the Proceedings of the 10th Pacific Conference on Computer Graphics and Applications, pp. 265-274, IEEE.
Oh et al., "A Model for Role Administration Using Organization Structure",SACMAT '02, Jun. 3-4, 2002, pp. 155-162.
Botha, R.A. et al., "Separation of duties for access control enforcement in workflow environments", IBM Systems Journal, vol. 40, No. 3, 2001, pp. 666-682.
What is Access Management?, 2AB Inc., Jan. 2004, 6 pages.
Harris, Shon, Mike Myer's Certification Passport CISSP, McGraw-Hill, 2002, ISBN 0-07-222578-5, Chapter 2, 54 pages.
Park, Joon S. et al., "Role-Based Access Control on the Web", ACM Transactions on Information and System Security, vol. 4, No. 1, Feb. 2001, pp. 37-71.
McCormick, Vickie L., "Using HR Information systems for HIPAA role-vased access compliance", Journal of Health Care Compliance, vol. 5, No. 2, Mar./Apr. 2003, pp. 31-32.
Langforn, Jeff, "Implementating Least Privilege at your Enterprise", SANS Institute, Jul. 5, 2003, 21 pages.
Cuppens, Frederick et al., "Modeling Contexts in the Or-BAC Model", ACSAC'03, 2003, pp. 1-10.
Principles of Least Privilege definition, Wikipedia.org, Reprinted Jul. 11, 2012, 5 pages.
Sakagumi et al., "ActiveTrace: Mobile Marketing Platform for Location and Behavior-Dependent Information Distribution and Analysis," Collection of Papers/Multimedia, Distribution, Collaberation and Mobile (DICOMO) Symposium, Jun. 27, 2001, vol. 2001, No. 7, pp. 501-506.
Murrary R. Barrick et al., "The Big Five Personality Dimensions and Job Performance: A Meta-Analysis"; Personnel Psychology; Spring 1991; vol. 44; No. 1, pp. 1-26.

* cited by examiner



10
14
User Input Database
22
24
30
16
12
32
20
Communicator Location Database
Weather Analysis Unit
Communication Network
26
28
21
Weather Information Database
34a
34c
34b
38a
36a
Vendor #1
38b
11
11
11
36b
Vendor #2
38c
36c
Vendor #N
8

Fig. 1




Fig. 2

INTERACTIVE ADVISORY SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Ser. No. 10/965,088, filed on Oct. 14, 2004, which is a continuation of U.S. Ser. No. 10/667,108, now U.S. Pat. No. 6,826,481, filed on Sep. 19, 2003, which is a continuation of U.S. Ser. No. 10/322,187, now U.S. Pat. No. 6,754,585, filed on Dec. 16, 2002, which is a continuation of U.S. Ser. No. 09/624,668, now U.S. Pat. No. 6,505,123, filed on Jul. 24, 2000. The entire contents of the above-referenced patent applications are hereby expressly incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

Not applicable.

BACKGROUND OF THE INVENTION

During recent years, the demand for detailed information, such as for example weather information, has risen sharply. Personal computers and communication devices have increased the demand for more information because of their power to gather, manipulate, transmit and receive data. As a result, specialized information and value-added services are in great demand. End users no longer desire to gather, manipulate and evaluate raw data. For instance, nowhere is this condition more apparent than with weather services across North America.

Years ago, radio and television broadcasters recognized an increasing demand for weather information from their audience, and thus increased the number of on-air weather segments as a means for increasing market ranking. Today, the demand for specific content in weather information has exceeded the ability of broadcasters to meet this demand. Virtually every facet of business and personal activities are continually influenced by the weather, good or bad.

In the United States as in most countries, a governmental agency (the National Weather Service in the United States), has the primary responsibility of generating weather products for the general public. These products, such as advisories, statements, and forecasts are generated and made available to third parties, such as broadcasters, newspapers, internet web sites, paging companies and others who, in turn, distribute them to the public. However, this chain of data custody is one way.

Today's lifestyles are fast-paced and sophisticated. Requests for detailed weather information for specific applications outnumber the governments' ability to process them. However, adhering to their mandated responsibility, the National Weather Service generates the general products for public consumption twice daily. This condition forces the public to interpret general and outdated advisories to meet their needs. Often, this interpretation is made erroneously. Even worse, these products are usually regional or national in scope, and may not apply to a particular location where various local activities are underway.

By way of example, weather warnings are broadcast by radio stations across the United States. These warnings identify certain weather impacts within a specified area. In most cases, the warning area includes one or more counties, covering dozens to hundreds of square miles. Most often, these threats (such as severe thunderstorms, tornadoes, etc.), only impact a very small zone within the warning area. These

threats also move rapidly. As impacts approach specific zones, they are in fact, moving away from other zones, inside the total warning area. Essentially, the existing reporting system is insufficient to specifically identify and adequately warn of personal risk. Furthermore, if the threat is imminent, the existing system cannot and does not provide preventive measures for each user near or at the threat. Thus, by default, distant or unaffected users are placed "on alert" unnecessarily when the threat may be moving away from their location.

Another common example further clarifies the problem. A family, excited to attend the championship softball game this upcoming weekend, closely monitors the local weather forecast. All week-long the forecast has advised fair to partly cloudy weather for game day. Early on game day, the forecast changes to partly cloudy, with a thirty percent chance for late afternoon showers. The family decides to attend the game, believing that the chances for rain are below their perceived risk level. Unknown to the family at midday, some clusters of showers are intensifying, and will place dangerous lightning over the game field. While the morning weather report was not completely inaccurate, the participants and spectators are exposed to risk. If later asked, it is likely the family members did not hear or remember the weather forecast. They also failed to link their limited knowledge of the weather to their own needs and risk exposure. They did not monitor changing weather events. Most likely, they had no ability to monitor developing risk at the game. Clearly, these people were forced to interpret outdated, limited information, as applied to their specific application.

Therefore, a need exists for a system to automatically and continuously provide consumer customized reports, advisories, alerts, forecasts and warnings relevant to a consumer-defined level of need or dynamic spatial location. It is to such a system that the present invention is directed.

SUMMARY OF THE INVENTION

The present invention provides an interactive advisory system and method of delivering individualized information. More specifically the present invention relates to a broadcast network for selectively transmitting individualized output signals to remote communicator devices. The broadcast network includes a user input database, a communicator location database, an analysis unit and a communication network.

The user input database contains user-defined parameters and each of the user-defined parameters desirably includes a spatial range identifier and a user profile. The user profile in each of the user-defined parameters at least identifies a communicator device associated with a particular user. The communicator location database contains real-time data indicative of the spatial locations of the communicator devices. In one preferred version of the present invention, the communicator location database is automatically and/or continuously updated by the communicator devices.

The information database contains data; such as, real-time weather data for at least the spatial locations contained in the communicator location database. The term "data" describes a wide variety of products, including but not limited to: past and current conditions of weather events; textual products, graphic products, and the like. The analysis unit receives the real-time data from the information database and automatically and continuously compares the spatial range identifier included in the user-defined parameters and the spatial locations of the corresponding communicator devices contained in the communicator location database with the real-time data and upon demand of the user, or even continuously, generates an individualized output signal, such as weather information

within the spatial range identified by the spatial range identifier for the user-defined parameters. As new locations are defined by the communicator location database, the information database is automatically updated in real-time.

The communication network transmits each individualized output signal to the particular communicator device defined in the user profile included in the user-defined parameter corresponding with the real-time data and prediction of events. Thus, a user can receive information in real-time specific to the user's immediate spatial location regardless of whether or not the user's location remains fixed or dynamic throughout time.

Other advantages and features of the present invention will become apparent to those skilled in the art when the following detailed description is read in view of the attached drawings and appended claims.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. **1** is a block diagram of an interactive weather advisory system constructed in accordance with the present invention.

FIG. **2** is a coordinate system illustrating a spatial location identifier and a spatial range identifier utilized by versions of the present invention.

DETAILED DESCRIPTION OF INVENTION

Referring now to the drawings and more particularly to FIG. **1** shown therein in block diagram form, is one embodiment of the invention in the form of an interactive weather advisory system **8**, constructed in accordance with the present invention. The weather advisory system **8** is provided with a broadcast network **10** for selectively transmitting individualized weather output signals to remote communicator devices **11**. The broadcast network **10** includes a weather analysis unit **12**, a user input database **14**, a communicator location database **16**, and a communication network **20**. The weather analysis unit **12** receives real-time weather data from a weather information database **21**. The weather information database **21** can be located at the broadcast network **10**, or remotely from the broadcast network **10**. The weather analysis unit **12**, the user input database **14**, the communicator location database **16**, the weather information database **21**, and the communication network **20**, interrelate and communicate via signal paths **22**, **24**, **26**, **28**, **30** and **32**.

The user input database **14** permits a plurality of users to input data corresponding to the weather reports, advisories or forecasts such that individualized weather reports, advisories or prediction of events can be transmitted to each individual user. The user input database **14** contains data representative of at least one user-defined parameter correlated to each one of a plurality of users. In one version of the present invention, each of the user-defined parameters includes various information related to weather output signals, such as a spatial range identifier, a user profile, one or more weather content identifiers for identifying particular weather patterns, one or more time identifiers for identifying particular times or time intervals that a user may desire a weather product, a spatial location fixed or dynamic code, and a spatial location identifier for identifying particular spatial locations of interest to the user if the spatial location fixed or dynamic code indicates that the spatial location is to be fixed. The user profile in each of the user-defined parameters includes at least a user identifier code for identifying a particular communicator device **11** associated with a particular user.

For instance, the user identifier code could be a mobile telephone number identifying one of the communicator devices **11**, which in this instance could be a mobile telephone or a pager, for example. The weather content identifier could be a computer code to identify one or a variety of weather conditions or events such as tornadoes, thunderstorms, hail storms, lightning storms, showers, snow storms, blizzards, high winds, winds aloft, rapidly rising or rapidly falling barometric pressure or other such weather patterns or conditions. The time identifier desirably could be a computer code for identifying the particular time, times, or time intervals the user desires the interactive weather advisory system **8** to communicate weather data to the user or to monitor the real-time weather data for a particular time and/or date. The spatial location identifier **26** could be a computer code identifying a particular predetermined spatial location such as, by way of example but not limitation, a longitude and latitude anywhere in the world, a town, a county, a township, address, zip code, altitude and combinations thereof.

As discussed above, the spatial location identifier identifies a particular spatial location anywhere in the world and/or altitude above sea level. The spatial range identifier identifies a particular spatial range surrounding the spatial location identifier. Each of the users can select the spatial location identifier and the spatial range identifier so as to receive weather forecasts and/or weather advisories or any other weather information for the spatial location identified by the spatial location identifier, and within the spatial range identified by the spatial range identifier.

For example, referring to FIG. **2**, shown therein is a coordinate system illustrating four spatial location identifiers and four spatial range identifiers selected by different users of the present invention. That is, one of the users selects the spatial location identifier (X1, Y1, Z1), and the spatial range identifier (R1). Another one of the users selects the spatial location identifier (X2, Y2, Z2), and the spatial range identifier (R2).

The user who selected the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X1, Y1, Z1) and the spatial range identifier R1, as predefined in his user input database. The user who selected the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2 will receive weather products and advisories concerning the spatial range identified by the spatial location identifier (X2, Y2, Z2) and the spatial range identifier R2, and as predefined in the user input database **14**. Likewise, the users who selected the spatial location identifiers (X3, Y3, Z3) and (X4, Y4, Z4) and the spatial range identifiers R3 and R4 will receive weather products and advisories concerning the spatial range identified by the spatial location identifiers (X3, Y3, Z3), (X4, Y4, Z4) and the spatial range identifier R3, R4, and as predefined in the user input database **14**.

The magnitudes of the spatial range identifiers R1, R2, R3 and R4 can be different or the same. In addition, the magnitudes of the spatial range identifiers R1, R2, R3 and R4 can vary widely and is desirably selected by the users.

Particular users can input the user-defined parameters into the user input database **14** via any suitable method. For example, the user input database **14** is desirably configured to acquire its data from a variety of optional sources preferably chosen by the user, such as verbally through a telephone customer service network, a mobile phone network equipped with wireless application protocol technology, email, a personal digital assistant, a laptop computer, or an interactive web site. Furthermore, users could mail the user-defined parameters to the broadcast network **10** and an individual at

the broadcast network **10** could input the user-defined parameters directly into the user input database **14** via a keyboard or other similar input device. In one embodiment, the user inputs the selected information into the user input database **14** via the user's communicator device **11**.

The weather information database **21** contains real-time weather data for at least the spatial locations contained in the communicator location database **16** and the spatial locations identified by the spatial location identifier in the user input database **14**. The weather analysis unit **12** generates predictions of all weather events based on the real-time weather data. The weather information database **21** desirably receives its real-time weather data from at least one of a plurality of possible resources such as, by way of example but not limitation, government weather information resources, privately operated weather information resources and other various meteorological resources. The real-time weather data could also be either inputted directly at the physical location of the weather information database **21** or inputted via a mobile phone network, a mobile phone network with wireless application protocol, the Internet, aircraft communication systems, email, a personal digital assistant, a laptop computer, regular computer, or other wireless devices.

The communicator location database **16** is an optional feature of the present invention, and is enabled via the signal path **22** when the user requests real-time weather advisories or prediction of events at the dynamic spatial location of the user's communicator device **11**. The communicator location database **16** is continuously updated such that the communicator location database **16** contains real-time data indicative of the spatial locations of the communicator devices **11**. In one embodiment, the user identifier code in the user's profile is transmitted to the communicator location database **16** via the signal path **22**. The communicator location database **16** desirably receives data from the communicator devices **11** identified by the user identifier codes via at least one of a variety of possible resources such as a mobile phone network, a mobile phone network equipped with the wireless application protocol technology, global positioning satellite technology, the Internet, loran technology, radar technology, transponder technology or any other type of technology capable of tracking the spatial location of a communicator device **11** and communicating the location of such communicator device **11** to the communicator location database **16** of the broadcast network **10**. Preferably, the communicator location database **16** is continuously and automatically updated as to the location of each of the communicator devices **11**, such as by the wireless application protocol technology.

The communication network **20** can be, by way of example but not limitation, a mobile phone network, a mobile phone network with wireless application protocol technology, the Internet, a facsimile network, a satellite network (one or two-way), a RF radio network, or any other means of transmitting information from a source to an end user.

The communicator devices **11** can be bidirectional or unidirectional communicator devices. The communicator devices **11** can be, by way of example but not limitation, a portable device, such as a mobile telephone, a smart phone, a pager, a laptop computer or a personal digital assistant or any other electronic device capable of receiving weather information data. Furthermore, the communicator device **11** can be incorporated into an object that is utilized or accessible by the user, such as a helmet, an automobile, or an airplane, for example. While only three communicator devices **11** are represented in FIG. **1** for purposes of illustration, the interactive weather advisory system **8** contemplates the utilization of a large number of communicator devices **11**.

The weather analysis unit **12** receives the data in the user input database **14**, the communicator location database **16** and the weather information database **21** from the signal paths **24**, **26**, and **28**. The weather analysis unit **12** can be, by way of example but not limitation, a computer desirably programmed to automatically and continuously compare the data in the user input database **14**, communicator location database **16** and weather information database **21** so as to generate an individualized weather output signal including weather information within the spatial range identified by the spatial range identifier for each user-defined parameter in the user input database **14**. The weather output signals are transmitted to the communication network **20** via the signal path **32**.

The weather analysis unit **12** gathers the real-time weather data from the weather information database **21**. The term "real-time weather data", as used herein, refers to weather data which is continually updated so as to indicate current or near current information. In some instances, the "real-time weather data" may be delayed by relatively small increments of five minutes, 15 minutes, or 30 minutes, for example. In other instances, the "real-time weather data" can be provided with substantially no delay. It is expected that the increments will become smaller as communication networks and weather related technology become faster.

The weather analysis unit **12** generates predictions of all weather related events and compares past and current events contained in the weather information database **21** (such as future position, strength, trajectory, etc.), to construct a four-dimensional database. Three dimensions of the database define a physical location on or above the earth's surface (the spatial location identifier (X1, Y1, Z1). The fourth dimension is time; past, present or future (identified as T1, T2, T3, T4). By employing high speed computer processors in real-time, the weather analysis unit **12** compares all events (past, current and predicted), at specific positions (X1, Y1, Z1, T1) with identical user supplied data (the user input database; X1, Y1, Z1, R1, T1), and identifies any matches (weather output signals) to the user through the communication network **20** and communication devices **11**.

The communication network **20** receives the weather output signals and the user identification codes via the signal paths **32** and **30**. In response thereto the communication network **20** transmits the individualized weather output signals to the communicator devices **11** associated with the user identification codes via the signal paths **34***a*, **34***b* and **34***c* such that each user receives the individualized weather information that was requested.

The signal paths **34***a*, **34***b* and **34***c* refer to any suitable communication link which permits electronic communications. For example, the signal paths **34***a*, **34***b* and **34***c* can be point-to-point shared and dedicated communications, infra red links, microwave links, telephone links, CATV links, satellite and radio links and fiber optic links.

Various combinations of weather information can be incorporated into the user input database **14** so as to provide the user with selected and specific weather information. For example, a user traveling in his automobile may wish to be informed by the interactive weather advisory system **8** concerning all hailstorms for an area within a 2.5 mile radius of his vehicle as he is traveling from his point of origin to his destination. The user, for example, through his smart phone (communicator device **11**) in his vehicle working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), hail (weather con-

tent identifier), 2.5 mile radius (spatial range identifier **24**) and spatial location dynamic (spatial location of the user's smart phone is then automatically and continuously monitored), and the like.

The interactive weather advisory system **8** then monitors weather information and predictions of events in the weather analysis unit **12** and transmits the individualized weather output signal to the user's smart phone if a hailstorm is detected or is highly likely to form within a 2.5 mile radius of the vehicle along the vehicle's path of travel, for the duration of travel.

The individualized weather output signal can be an audio and/or video data signal. For example, the individualized weather output signal can be a .WAV file or other suitable file containing an animated representation of a real or hypothetical individual speaking an individualized message to the user. In the example given above, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping for a short period of time so as to avoid the hailstorm. Alternatively, the individualized message may be that the hailstorm is 2.5 miles ahead of the vehicle and thus, the user should consider stopping until further notified by another individualized weather output signal so as to avoid the hailstorm. In other words, the weather analysis unit **12** may transmit another individualized weather output signal to the user via the communication network **20** and the communicator devices **11** notifying the user that the weather condition identified by the weather content identifier has passed or is beyond the spatial location identified by the spatial range identifier.

As another example, a user may desire to be informed of all real-time weather data and predictions of events within a particular spatial range of a particular dynamic spatial location. For instance, the user may be interested in whether his aircraft is at risk of icing as he flies from Oklahoma City to Tulsa, Okla. To provide a suitable level of comfort and safety, the user may wish to be informed of icing conditions within 10 miles of the dynamic spatial location of his aircraft. The user, for example, through his smart phone or other suitable avionic device (communicator device **11**) in his aircraft working in conjunction with a mobile phone network (communication network **20**) with wireless application protocol, inputs selected information into the user input database **14**; namely, the user's smart phone number (user identifier code), icing (weather content identifier), 10 mile radius (spatial range identifier **24**) and the spatial location dynamic. The spatial location of the user's smart phone or other suitable avionic device is then automatically and continuously monitored as the aircraft traverses through time and space from (X1, Y1, Z1, T1) to (X4, Y4, Z4, T4). The interactive weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather output signal to the user's smart phone or other avionic device identifying, if icing is detected or is highly likely to form relevant to a 10 mile radius of the aircraft.

As yet another example, perhaps the user is only interested in a particular weather pattern at a particular fixed spatial location and within a particular spatial range irrespective of the immediate location of the communicator device **11**. To accomplish this user's request, the broadcast network **10** does not utilize the communicator location database **16**. The user inputs selected information into the user input database **14**, namely the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier) and the spatial location in which the user is interested (spatial location identifier). The weather analysis unit **12** then monitors the real-time weather data in the weather information database **21** and the predicted events in the weather analysis unit **12** so as to transmit the individualized weather information concerning the weather pattern in the spatial location and range requested by the user.

As a further example, perhaps the user is only interested in a particular weather condition at the spatial location and within a particular spatial range at a particular time. The user inputs selected information into the user input database **14**, namely, the user's phone number (user identifier code), the code for the particular weather pattern in which the user is interested (weather content identifier), the spatial range around the spatial location in which the user is interested (spatial range identifier and the spatial location in which the user is interested spatial location identifier) and the time and date (time identifier) that the user to wishes to be informed of the weather conditions at the spatial location of interest. In response thereto, the weather analysis unit **12** monitors the real time weather data from the weather information database **21** for the spatial location and range identified by the spatial range identifier and spatial location identifier to determine the probability of the particular weather pattern occurring at the time identified by the time identifier. The weather analysis unit **12** sends, via the signal path **32**, the individualized weather output signal to the communication network **20**. The communication network **20** receives the user identifier code, via signal path **30**, from the user input database **14** and transmits the weather output signal received from the weather analysis unit **12** to the particular communicator device **11** identified by the user identifier code. Thus, the user receives the individualized weather information concerning the spatial location, spatial range and time requested by the user.

The signal paths **22**, **24**, **26**, **28**, **30** and **32** can be logical and/or physical links between various software and/or hardware utilized to implement the present invention. It should be understood that each of the signal paths **22**, **24**, **26**, **28**, **30** and **32** are shown and described separately herein for the sole purpose of clearly illustrating the information and logic being communicated between the individual components of the present invention. In operation, the signal paths may not be separate signal paths but may be a single signal path. In addition, the various information does not necessarily have to flow between the components of the present invention in the manner shown in FIG. **1**. For example, although FIG. **1** illustrates the user identifier code being transmitted directly from the user input database **14** to the communication network **20** via the signal path **30**, the user identifier code can be communicated to the weather analysis unit **12** via the signal path **24** and then communicated to the communication network **20** via the signal path **32**.

It should be understood that although the user has been described as manually inputting the user identifier code into the user input database **14**, the user identifier code could be automatically input into the user input database **14** by the communicator device **11**.

Once the user-defined parameters have been input into the user input database **14**, the user-defined parameters can be analyzed by the weather analysis unit **12** along with weather content identifiers for purposes of targeted marketing. A plurality of vendors **36** can be provided access to the weather analysis unit **12** of the broadcast network **10** via a plurality of signal paths **38***a*, **38***b*, and **38***c*. The vendors **36** can independently input search information into the weather analysis unit **12** for compiling a data set of information which is useful to the vendors **36**.

For example, a particular vendor **36***a*, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit **12** so as to request a list of all spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit **12** would then compile the data set of all spatial locations in United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, and the real-time weather data stored in the weather information database **21**. The data set is then output to the vendor **36***a*. Based on the data set, the vendor **36***a* may send advertisements or additional snow blowers to the areas identified in the data set.

As another example, the particular vendor **36***a*, who is in the business of selling snow blowers, may input a weather content identifier and time identifier into the weather analysis unit **12** so as to request a list of all user profiles identifying users who resided in spatial locations in the United States which are expected to receive at least 10 inches of snow in the next week. The weather analysis unit **12** would then compile the data set of all spatial locations in United States which is expected to receive at least 10 inches of snow in the next week based on at least one weather content identifier, the time identifier, the user profiles and the real-time weather data stored in the weather information database **21**. The data set is then output to the vendor **36***a*. Based on the data set, the vendor **36***a* may send advertisements to the users who are identified in the data set.

It is envisioned that users will subscribe to the services provided by the broadcast network **10**. In this regard, the broadcast network **10** may or may not charge a service fee to the users. In addition, some services may be provided by the broadcast network **10** for one charge and additional services may be provided at an enhanced charge.

To save processing power, the weather analysis unit **12** may periodically determine which communicator devices **11** are turned off or out of range. Once this has been determined, the weather analysis unit **12** would then not generate any individualized weather output signals for the communicator devices **11** which are turned off or out of range. Once a particular one of the communicator devices **11** is turned on or comes within range, the weather analysis unit **12** would then attempt to generate individualized weather output signals for such communicator devices **11**. In other words, to save processing power the weather analysis unit **12** may only generate individualized weather output signals for the communicator devices **11** which are active and within range.

The weather analysis unit **12** can be located at the broadcast network **10**. Alternatively, the weather analysis unit **12** can be separate from the remainder of the broadcast network **10** and provided as a service to the broadcast network **10**.

From the above description, it is clear that the present invention is well adapted to carry out the objects and to attain the advantages mentioned herein as well as those inherent in the invention. While presently preferred embodiments of the invention have been described for purposes of this disclosure, it will be readily understood that numerous changes may be made which will readily suggest themselves to those skilled in the art and which are accomplished within the spirit of the invention disclosed.

The invention claimed is:

1. A system, comprising:

a communicator location database that repeatedly receives real-time data indicative of spatial locations of a plurality of communicator devices and is updated to reflect an updated spatial location of at least one of the plurality of communicator devices;

a user input database containing a user profile, the user profile including a user identifier code identifying the at least one communicator device; and

a weather analysis unit configured to:

compare the spatial location of the at least one communicator device with weather forecast data or weather data;

generate an individualized weather output signal based on the comparison of the spatial location of the at least one communicator device with the weather forecast data or the weather data; and

output the individualized weather output signal to a communication network for transmittal to the at least one communicator device.

2. The system of claim **1**, wherein the communicator device comprises a bidirectional or unidirectional communicator device, a portable device, a mobile telephone, a smart phone, a pager, a personal digital assistant, a computer, or a laptop computer.

3. The system of claim **1**, wherein the communicator location database is updated to contain real-time data indicative of spatial locations of the plurality of communicator devices.

4. The system of claim **3**, wherein the communicator location database is automatically updated.

5. The system of claim **3**, wherein the communicator location database is automatically and repeatedly updated.

6. The system of claim **1**, wherein the communication network comprises a mobile phone network, the Internet, a facsimile network, a satellite network, or a radio frequency network.

7. The system of claim **1**, wherein the individualized weather output signal includes audio.

8. The system of claim **1**, wherein the individualized weather output signal includes video.

9. A system, comprising:

a communicator location database that repeatedly receives real-time data indicative of spatial locations of a plurality of communicator devices and is updated to reflect an updated spatial location of at least one of the plurality of communicator devices;

a user input database containing a user profile, the user profile including a user identifier code identifying the at least one communicator device; and

a weather analysis unit configured to:

output the data indicative of the spatial location of the at least one communicator device with a request to generate an individualized weather output signal based on a comparison of the spatial location of the at least one communicator device with weather forecast data or weather data;

receive the individualized weather output signal based on the comparison of the spatial location of the at least one communicator device with the weather forecast data or the weather data; and

output the individualized weather output signal to a communication network for transmittal to the at least one communicator device.

10. The system of claim **9**, wherein the communicator device comprises a bidirectional or unidirectional communicator device, a portable device, a mobile telephone, a smart phone, a pager, a personal digital assistant, a computer, or a laptop computer.

11. The system of claim 9, wherein the communicator location database is updated to contain real-time data indicative of spatial locations of the plurality of communicator devices.

12. The system of claim 11, wherein the communicator location database is automatically updated.

13. The system of claim 11, wherein the communicator location database is automatically and repeatedly updated.

14. The system of claim 9, wherein the communication network comprises a mobile phone network, the Internet, a facsimile network, a satellite network, or a radio frequency network.

15. The system of claim 9, wherein the individualized weather output signal includes audio.

16. The system of claim 9, wherein the individualized weather output signal includes video.

17. A method of outputting an individualized weather output signal, the method comprising:

receiving a user profile, the user profile including a user identifier code identifying a communicator device;

repeatedly receiving real-time data indicative of a spatial location of the communicator device;

updating the communicator location database to reflect an updated spatial location of the communicator device; and

outputting the individualized weather output signal to a communication network for transmittal to the communicator device, wherein the individualized weather output signal is generated based on a comparison of the spatial location of the communicator device with weather forecast data or weather data.

18. The method of claim 17, wherein the communicator device comprises a bidirectional or unidirectional communicator device, a portable device, a mobile telephone, a smart phone, a pager, a personal digital assistant, a computer, or a laptop computer.

19. The method of claim 17, further comprising:

storing the real-time data indicative of the spatial location of the communicator device in a communicator location database.

20. The method of claim 19, further comprising:

receiving real-time data indicative of a spatial location of a second communicator device; and

updating the communicator location database.

21. The method of claim 17, wherein the communication network comprises a mobile phone network, the Internet, a facsimile network, a satellite network, or a radio frequency network.

22. The method of claim 17, further comprising:

generating the individualized weather output signal based on a comparison of the spatial location of the communicator device with the weather forecast data or weather data.

23. The method of claim 17, further comprising:

outputting the data indicative of the spatial location of the communicator device with a request to generate the individualized weather output signal based on a comparison of the spatial location of the communicator device with the weather forecast data or weather data; and

receiving the individualized weather output signal generated based on a comparison of the spatial location of the communicator device with the weather forecast data or weather data.

24. The method of claim 17, wherein the individualized weather output signal includes audio.

25. The method of claim 17, wherein the individualized weather output signal includes video.

* * * * *