

US009407097B2

(12) **United States Patent**  
**Proud**

(10) **Patent No.:** **US 9,407,097 B2**  
(45) **Date of Patent:** **\*Aug. 2, 2016**

(54) **METHODS USING WEARABLE DEVICE  
WITH UNIQUE USER ID AND TELEMETRY  
SYSTEM**

(71) Applicant: **Hello Inc.**, San Francisco, CA (US)

(72) Inventor: **James Proud**, San Francisco, CA (US)

(73) Assignee: **Hello Inc.**, San Francisco, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-  
claimer.

(21) Appl. No.: **13/923,909**

(22) Filed: **Jun. 21, 2013**

(65) **Prior Publication Data**

US 2014/0247134 A1 Sep. 4, 2014

**Related U.S. Application Data**

(60) Provisional application No. 61/772,265, filed on Mar.  
4, 2013, provisional application No. 61/812,083, filed  
on Apr. 15, 2013.

(51) **Int. Cl.**

**G08C 19/16** (2006.01)

**H02J 5/00** (2016.01)

**H01F 38/14** (2006.01)

**A61B 5/00** (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ..... **H02J 5/005** (2013.01); **A61B 5/0002**  
(2013.01); **A61B 5/002** (2013.01); **A61B**  
**5/0015** (2013.01); **A61B 5/0022** (2013.01);  
**A61B 5/0024** (2013.01); **G06F 8/65** (2013.01);  
**G06Q 20/322** (2013.01); **G08C 17/02**  
(2013.01); **H01F 38/14** (2013.01); **H02J 7/025**

(2013.01); **H02J 17/00** (2013.01); **H04L**  
**65/403** (2013.01); **H04L 67/22** (2013.01); **A61B**  
**2560/0214** (2013.01); **A61B 2562/08** (2013.01);  
**G06F 19/3418** (2013.01); **H02J 2007/0096**  
(2013.01); **Y02B 60/183** (2013.01)

(58) **Field of Classification Search**

CPC ..... **H04L 65/403**  
USPC ..... **340/870.01; 600/534, 545**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,603,152 A 7/1986 Laurin et al.  
4,780,556 A 10/1988 Hata et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

EP 371004 A1 5/1990  
EP 1094091 4/2001



(Continued)

*Primary Examiner* — Amine Benlagsir

(57) **ABSTRACT**

A method for using telemetry data based on a user habit  
information user one or more sensors coupled to a wearable  
device that has a unique user ID, and acquire user information  
selected from of at least one of, a user's activities, behaviors  
and habit information. The wearable device includes ID cir-  
cuitry that includes ID storage, a communication system  
which reads and transmits the unique ID from the ID storage,  
a power source and a pathway system to route signals through  
the circuitry. The telemetry system communicates with the  
one or more sensors. The telemetry system includes a data-  
base of user ID's. Telemetry data is analyzed using the telem-  
etry system based on at least one of, user's activities, behav-  
iors and habit information. Personalized information about  
the user is created.

**7 Claims, 23 Drawing Sheets**



## Page 2

(51)	<b>Int. Cl.</b>				2008/0146890	A1	6/2008	LeBoeuf et al.	
	<b>G06F 9/445</b>		(2006.01)		2009/0023428	A1 *	1/2009	Behzad .....	G06F 17/30032 455/414.3
	<b>H04L 29/06</b>		(2006.01)						
	<b>H02J 7/02</b>		(2016.01)		2009/0112247	A1	4/2009	Freeman et al.	
	<b>H02J 17/00</b>		(2006.01)		2009/0119760	A1	5/2009	Hung et al.	
	<b>G08C 17/02</b>		(2006.01)		2009/0240120	A1	9/2009	Mensinger et al.	
	<b>G06Q 20/32</b>		(2012.01)		2009/0318773	A1	12/2009	Jung et al.	
	<b>H04L 29/08</b>		(2006.01)		2010/0141042	A1	6/2010	Kesler et al.	
	<b>H02J 7/00</b>		(2006.01)		2010/0153269	A1	6/2010	McCabe	
	<b>G06F 19/00</b>		(2011.01)		2010/0234695	A1	9/2010	Morris	
(56)	<b>References Cited</b>				2010/0277003	A1	11/2010	Von Novak et al.	
	<b>U.S. PATENT DOCUMENTS</b>				2011/0055132	A1	3/2011	Mahdian et al.	
	5,187,657	A	2/1993	Forbes	2011/0068935	A1	3/2011	Riley	
	5,452,274	A	9/1995	Thompson	2012/0133079	A1	5/2012	Sykes et al.	
	5,576,054	A	11/1996	Brown	2012/0146795	A1	6/2012	Margon et al.	
	5,735,887	A	4/1998	Barreras, Sr. et al.	2012/0149996	A1	6/2012	Stivoric et al.	
	5,910,544	A	6/1999	Ozawa et al.	2012/0184876	A1	7/2012	Freeman et al.	
	5,971,941	A	10/1999	Simons et al.	2012/0194419	A1	8/2012	Osterhout et al.	
	6,200,289	B1	3/2001	Hochman et al.	2012/0196832	A1	8/2012	Luria	
	6,580,356	B1	6/2003	Alt et al.	2012/0205373	A1	8/2012	Caldwell	
(57)	6,893,396	B2 *	5/2005	Schulze .....	2012/0229270	A1	9/2012	Morley et al.	
				A61B 5/0022 128/903	2012/0242501	A1	9/2012	Tran et al.	
	7,248,894	B2	7/2007	Fujieda et al.	2012/0253485	A1	10/2012	Weast et al.	
	7,616,110	B2	11/2009	Crump et al.	2012/0253489	A1	10/2012	Dugan et al.	
	7,720,855	B2	5/2010	Brown	2012/0290327	A1	11/2012	Hanlon et al.	
	7,733,224	B2	6/2010	Tran	2012/0290950	A1	11/2012	Rapaport et al.	
	8,028,905	B2	10/2011	Holberg	2012/0296156	A1	11/2012	Auphan	
	8,126,735	B2	2/2012	Dicks et al.	2012/0330109	A1	12/2012	Tran	
	8,204,786	B2 *	6/2012	LeBoeuf .....	2013/0022659	A1	1/2013	Roberts	
				A61B 5/11 128/920	2013/0030711	A1	1/2013	Korhonen	
(58)	8,251,903	B2	8/2012	LeBoeuf et al.	2013/0035785	A1 *	2/2013	MacVittie .....	B65D 83/0409 700/231
	8,587,426	B2	11/2013	Bloem	2013/0072765	A1 *	3/2013	Kahn .....	A61B 5/01 600/301
	8,663,106	B2	3/2014	Stivoric et al.	2013/0127980	A1	5/2013	Haddick et al.	
	2002/0109600	A1	8/2002	Mault et al.	2013/0144190	A1	6/2013	Bruce	
	2003/0023467	A1	1/2003	Moldovan	2013/0172691	A1 *	7/2013	Tran .....	A61B 8/488 600/301
	2003/0143113	A2	7/2003	Yuzhakov et al.	2013/0255681	A1 *	10/2013	Batch .....	A61B 5/0205 128/204.21
	2004/0172290	A1	9/2004	Leven	2013/0267794	A1 *	10/2013	Fernstrom .....	G01N 33/02 600/301
	2005/0113650	A1 *	5/2005	Pacione .....	2013/0326790	A1	12/2013	Cauwels	
				A61B 5/411 600/300	2014/0129942	A1 *	5/2014	Rathod .....	H04N 21/44222 715/720
	2005/024								






FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4





FIG. 5



**FIG. 6**







FIG. 7



**FIG. 8**




FIG. 9




FIG. 10




FIG. 11






FIG. 12




FIG. 13




FIG. 14





FIG. 15






FIG. 16B






FIG. 16C





FIG. 16D






FIG. 18




FIG. 19




FIG. 20




FIG. 21






FIG. 22




FIG. 23



# METHODS USING WEARABLE DEVICE WITH UNIQUE USER ID AND TELEMETRY SYSTEM

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. 61/772,265 filed Mar. 4, 2013 and U.S. 61/812,083 filed Apr. 15, 2013, both of which applications are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention is directed to method using wearable device telemetry devices with unique ID's, and more particularly to methods using an intelligent, wearable device with a unique ID for each user that gathers telemetry data based on a user's habits for a variety of different applications.

### 2. Description of the Related Art

Telemetry systems can be implemented to acquire and transmit data from a remote source. Some telemetry systems provide information about a user's activities.

It is becoming commonplace to use wireless packet data service networks for effectuating data sessions with. In some implementations, unique identifications (ID) need to be assigned to the devices in order to facilitate certain aspects of service provisioning, e.g., security, validation and authentication, et cetera. In such scenarios, it becomes imperative that no two devices have the same indicium (i.e., collision). Further, provisioning of such indicia should be flexible so as to maintain the entire pool of indicia to a manageable level while allowing for their widespread use in multiple service environments.

The telemetry system may incorporate a wireless technology such as wireless fidelity (WiFi); infrared (IR); or ultrasound in order to facilitate finding an object and/or data transmission. As an exemplary implementation, a medical telemetry system can be implemented to remotely monitor the cardiac electrical activity of a plurality of ambulatory patients while they remain within a predefined coverage area. The medical telemetry system may also be implemented to locate and track patients within the coverage area.

Medical telemetry systems may comprise an alarm adapted to identify high risk patients and/or patients requiring special assistance. Some medical procedures and diagnostic examinations require the removal of any telemetry system components attached directly to a patient. One problem with conventional medical telemetry systems is that the process of removing telemetry system components for purposes of performing a medical procedure or diagnostic examination can generate a false alarm. False alarms unnecessarily tax hospital resources and interfere with the working environment.

The popularity and growth of social network sites and services has increased dramatically over the last few years. Present social network sites include Facebook®, Google+®, Twitter®, MySpace®, YouTube®, LinkedIn®, Flickr®, Jaiku®, MYUBO®, Bebo® and the like. Such social networking (SNET) sites are typically web-based and organized around user profiles and/or collections of content accessible by members of the network. Membership in such social networks is comprised of individuals, or groupings of individuals, who are generally represented by profile pages and permitted to interact as determined by the social networking service.

In many popular social networks, especially profile-focused social networks, activity centers on web pages or social

spaces that enable members to view profiles, communicate and share activities, interests, opinions, status updates, audio/video content, etc., across networks of contacts. Social networking services might also allow members to track certain activities of other members of the social network, collaborate, locate and connect with existing friends, former acquaintances and colleagues, and establish new connections with other members.

Individual members typically connect to social networking services through existing web-based platforms via a computing device, tablet or smartphone. Members often share a common bond, social status, or geographic or cultural connection with their respective contacts. Smartphone and games-based mobile social networking services are examples of rapidly developing areas.

In so-called "cloud" computing, computing tasks are performed on remote computers/servers which are typically accessed via Network Systems connections. One benefit of cloud computing is that it can reduce the relative processing and storage capabilities required by user devices (e.g., a cloud computer may load a webpage accessed by a tablet device and communicate only required information back to the tablet). Accordingly, recent years have witnessed an ever-growing amount of content and application software being migrated from local or on-site storage to cloud-based data storage and management. Such software functionality/services and content are typically available on-demand via (virtualized) network infrastructures.

Transaction processing using a point-of-sale (POS) terminal is well-known. Other types of transactions may be non-financial. In the area of physical security, for example, terminals may be used by patrolmen to check in, producing evidence of their having been in the required place at the required time. Terminals may also be used in the healthcare industry, for example, to produce a record of what medical personnel have attended a patient at what times, or for myriad other purposes. Transaction processing can be used generally herein to refer to the use of a transaction terminal to read, and possibly to write, a record-bearing medium such as a credit card, an ID card, a smart card, etc. The transaction terminal may use a contact or a contactless reading mechanism. In the case of smart cards, for example, a contact-less radio interface of a type known in the art may be used.

A transaction terminal has been introduced that has a wireless modem—in particular a CDPD (cellular digital packet data) modem—that may be used to establish a connection to a CDPD network, bypassing the PSTN with its accompanying delays and charges. Such an arrangement is shown in FIG. 2. The transaction terminal connects wirelessly to a wireless network such as a CDPD network. The CDPD network includes multiple Mobile Data Base Stations (MDBS) connected to a Mobile Data Intermediate Station (MDIS). The MDIS can be connected to a transaction processor via a Frame Relay connection.

Frame Relay can be used because it is much faster than an X.25 connection. However, this transaction terminal does not scale well to meet the needs of "distributed commerce" (or "mobile commerce"). Distributed commerce may be distinguished from e-commerce by a greater element of human involvement. In e-commerce goods or services are ordered and paid for on-line, in distributed commerce, goods or services may be ordered in person and paid for by tender of a credit card or other non-cash payment medium, as opposed to the submission by the consumer (e.g., Web submission) of credit card information or the like.



Like e-commerce, underlying characteristics of distributed commerce should be user convenience, greater satisfaction of demand, and vendor efficiency.

However, various impediments hamper distributed commerce. Whereas the “plumbing” for e-commerce (i.e., the Web) has become almost universally established, the plumbing for distributed commerce remains ad hoc. A vendor must invest in terminal equipment and terminal software/firmware, enter into a subscription agreement with a wireless carrier, and, perhaps most importantly, ensure that a transaction processor is capable of receiving transactions through the wireless infrastructure, or is willing to invest to create such wireless capability. In the prior systems, for example, transaction processors are typically not equipped to handle Frame Relay traffic, requiring that a new “front end” be provided.

Furthermore, today’s hard-wired transaction terminals are relatively inefficient in their use of bandwidth.

Hence, although distributed commerce, like e-commerce, should be characterized by efficiency, flexibility and adaptability to rapid change, presently it is not.

There is a need for wearable telemetry devices, such as a wearable device, where one size fits all. There is a further need for telemetry devices configured to be used in payments. Yet there is another need for wearable telemetry devices suitable for use in social networking.

#### SUMMARY OF THE INVENTION

An object of the present invention is to methods of use that provide a wearable device, such as a wearable device, where one size fits all.

Another object of the present invention is to provide methods of use that provide a wearable device that gathers telemetry data based on a user’s habits, analyzes the data and provides the user with personalized information about their life.

A further object of the present invention is to provide methods that use a wearable device or system that measures and tracks everything from a user’s movements and activities, to habits, lifestyle choices, health and social interactions.

Yet another object of the present invention is methods that use a wearable device that creates a unique portrait of its wearer which provides personalized information and mapping of a user’s daily experience.

These and other objects of the present invention are achieved in a method for using telemetry data based on a user habit information. One or more sensors are coupled to a wearable device that has a unique user ID, and acquire user information selected from at least one of, a user’s activities, behaviors and habit information. The wearable device includes ID circuitry that includes ID storage, a communication system which reads and transmits the unique ID from the ID storage, a power source and a pathway system to route signals through the circuitry. The telemetry system communicates with the one or more sensors. The telemetry system includes a database of user ID’s. Telemetry data is analyzed using the telemetry system based on at least one of, user’s activities, behaviors and habit information. Personalized information about the user is created.

In another embodiment of the present invention, a method is provided for using telemetry data based on a user habit information. User data is acquired from one or more sensors coupled to a wearable device that has a unique user ID. The user data is selected from at least one of, a user’s activities, behaviors and habit information. Conditioning electronics for the user data are included at the wearable device. User data is communicated from the one or more sensors to a telemetry

system that includes a database of user ID’s. Telemetry data is analyzed based on at least one of a user’s, activities, behaviors and habit information.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1(a) and 1(b) illustrate one embodiment of a wearable device of the present invention, where one size fits all.

FIG. 2 illustrates one embodiment of electronics that can be included in the wearable device.

FIG. 3 illustrates one embodiment of a telemetry system of the present invention.

FIG. 4 is a diagram of the programming input schematic of the secure sensor/transmitter array of FIG. 7.

FIG. 5 is a block diagram of the system of programming the sensor/transmitter(s) comprising the secure sensor/transmitter array of FIG. 7.

FIG. 6 is a block diagram of the jam command and security/randomization bits of the secure sensor/transmitter array of FIG. 7.

FIG. 7 is a logic circuit diagram of the sensor/transmitter programming input schematic in one embodiment of the present invention.

FIG. 8 is a block diagram of an embodiment of a computer implemented system for determining the location of a remote sensor utilizing the methods of the present invention.

FIG. 9 is a block diagram illustrating one embodiment of a SNAPSHOT GPS receiver for use according to the present invention.

FIG. 10 is a block diagram of a remote sensor shown in communication with two different external communication devices.

FIG. 11 is a diagram of the active RF and RF backscatter antennas.

FIG. 12 is a diagram of the encoding scheme for the symbols in the active RF protocol.

FIG. 13 is a diagram of the packet structure in the IRDA protocol.

FIG. 14 is a diagram of the encoding scheme in the IRDA protocol.

FIG. 15 illustrates one embodiment of a wireless network that can be used with the present invention.

FIGS. 16(a)-16(d) illustrate various embodiments of the interaction of a wearable device of the present invention with an interaction engine, a transaction engine, a decoding engine, and a payment system and a third party.

FIG. 17 illustrates an embodiment of a social network circle with social devices in accordance with one embodiment of the present invention.

FIG. 18 illustrates an embodiment of a social group with a variety of members in accordance with one embodiment of the present invention.

FIG. 19 is a functional block diagram illustrating a social network infrastructure and social devices in accordance with one embodiment of the invention.

FIG. 20 illustrates a simplified block diagram of a client-server system and network in one embodiment of the present invention.

FIG. 21 illustrates a more detailed diagram of an exemplary client or server computer that can be used in one embodiment of the present invention.

FIG. 22 illustrates a system for activity collection and building a social graph including sharing activity between users in one embodiment of the present invention.



## 5

FIG. 23 illustrates a social graph with nodes representing users and edges representing sharing activity between the users in one embodiment of the present invention.

## DETAILED DESCRIPTION

As used herein, the term engine refers to software, firmware, hardware, or other component that can be used to effectuate a purpose. The engine will typically include software instructions that are stored in non-volatile memory (also referred to as secondary memory). When the software instructions are executed, at least a subset of the software instructions can be loaded into memory (also referred to as primary memory) by a processor. The processor then executes the software instructions in memory. The processor may be a shared processor, a dedicated processor, or a combination of shared or dedicated processors. A typical program will include calls to hardware components (such as I/O devices), which typically requires the execution of drivers. The drivers may or may not be considered part of the engine, but the distinction is not critical.

As used herein, the term database is used broadly to include any known or convenient means for storing data, whether centralized or distributed, relational or otherwise.

As used herein a mobile device includes, but is not limited to, a cell phone, such as Apple's iPhone®, other portable electronic devices, such as Apple's iPod Touches®, Apple's iPads®, and mobile devices based on Google's Android® operating system, and any other portable electronic device that includes software, firmware, hardware, or a combination thereof that is capable of at least receiving the signal, decoding if needed, exchanging information with a transaction server to verify the buyer and/or seller's account information, conducting the transaction, and generating a receipt. Typical components of mobile device may include but are not limited to persistent memories like flash ROM, random access memory like SRAM, a camera, a battery, LCD driver, a display, a cellular antenna, a speaker, a Bluetooth® circuit, and WIFI circuitry, where the persistent memory may contain programs, applications, and/or an operating system for the mobile device.

As used herein, the terms "social network" and "SNET" comprise a grouping or social structure of devices and/or individuals, as well as connections, links and interdependencies between such devices and/or individuals. Members or actors (including devices) within or affiliated with a SNET may be referred to herein as "nodes", "social devices", "SNET members", "SNET devices", "user devices" and/or "modules". In addition, the terms "SNET circle", "SNET group" and "SNET sub-circle" generally denote a social network that comprises social devices and, as contextually appropriate, human SNET members and personal area networks ("PANs").

As used herein, the term "wearable device" is anything that can be worn by an individual and that has a back side that in some embodiments contacts a user's skin and a face side. Examples of wearable device include but are not limited to a cap, arm band, wristband, garment, and the like.

As used herein, the term "computer" is a general purpose device that can be programmed to carry out a finite set of arithmetic or logical operations. Since a sequence of operations can be readily changed, the computer can solve more than one kind of problem. A computer can include of at least one processing element, typically a central processing unit (CPU) and some form of memory. The processing element carries out arithmetic and logic operations, and a sequencing and control unit that can change the order of operations based

## 6

on stored information. Peripheral devices allow information to be retrieved from an external source, and the result of operations saved and retrieved.

As used herein, the term "Internet" is a global system of interconnected computer networks that use the standard Internet protocol suite (TCP/IP) to serve billions of users worldwide. It is a network of networks that consists of millions of private, public, academic, business, and government networks, of local to global scope, that are linked by a broad array of electronic, wireless and optical networking technologies. The Internet carries an extensive range of information resources and services, such as the inter-linked hypertext documents of the World Wide Web (WWW) and the infrastructure to support email. The communications infrastructure of the Internet consists of its hardware components and a system of software layers that control various aspects of the architecture.

As used herein, the term "extranet" is a computer network that allows controlled access from the outside. An extranet can be an extension of an organization's intranet that is extended to users outside the organization that can be partners, vendors, and suppliers, in isolation from all other Internet users. An extranet can be an intranet mapped onto the public Internet or some other transmission system not accessible to the general public, but managed by more than one company's administrator(s). Examples of extranet-style networks include but are not limited to:

- LANs or WANs belonging to multiple organizations and interconnected and accessed using remote dial-up
- LANs or WANs belonging to multiple organizations and interconnected and accessed using dedicated lines
- Virtual private network (VPN) that is comprised of LANs or WANs belonging to multiple organizations, and that extends usage to remote users using special "tunneling" software that creates a secure, usually encrypted network connection over public lines, sometimes via an ISP

As used herein, the term "Intranet" is a network that is owned by a single organization that controls its security policies and network management. Examples of intranets include but are not limited to, The following are examples of intranet-style networks:

- A LAN
- A Wide-area network (WAN) that is comprised of a LAN that extends usage to remote employees with dial-up access
- A WAN that is comprised of interconnected LANs using dedicated communication lines
- A Virtual private network (VPN) that is comprised of a LAN or WAN that extends usage to remote employees or networks using special "tunneling" software that creates a secure, usually encrypted connection over public lines, sometimes via an Internet Service Provider (ISP)

For purposes of the present invention, the Internet, extranets and intranets collectively are referred to as ("Network Systems").

In various embodiments, the present invention provides a wearable device 10, such as a wearable device, where one size fits all. As illustrated in FIGS. 1(a) and 1(b), the wearable device 10 include a plurality of magnets 12, with adjacent magnets having opposite polarity, with a length suitable to be worn by all people. In one embodiment, the length of the wearable device 10 can be 10-12 inches. The magnets 12 are positioned along an interior of the wearable device 10 to be provided for good conformation to a user's wrist.

One or more sensors 14 are coupled to the wearable device 10. The sensors are measuring devices. As a non-limiting example, the measuring device or sensors 14 can include



RTSS devices to detect a user's activities, motions, physical parameters, and the like, including but not limited to, a heart rate monitor, a body temperature probe, a conventional pedometer, an accelerometer and the like.

Alternatively, multifunctional sensors **14** which can perform all the aforementioned functions of RTSS may be attached or embedded in wearable device **10**. In one embodiment, each sensor can be in communication and or connect electronically and/or RF to a telemetry module **16**. A variety of different sensors **14** can be utilized, including but not limited to, an accelerometer based sensor, and pressure based sensors, voltage resistance sensor, a radio frequency sensor, and the like, as recited above.

As a non-limiting example, an accelerometer, well known to those skilled in the art, detects acceleration and thus user activity. The accelerometer provides a voltage output that is proportional to the detected acceleration. Accordingly, the accelerometer senses vibration. This voltage output provides an acceleration spectrum over time; and information about loft time can be ascertained by performing calculations on that spectrum. A microprocessor subsystem, such as disclosed in U.S. Pat. No. 8,352,211, incorporated herein by reference, stores the spectrum into memory and processes the spectrum information to determine activity. Other examples of suitable accelerometer sensors are disclosed in EP 2428774 A1, incorporated herein by reference. Suitable pressure sensors are disclosed in EP 1883798 B1, incorporated herein by reference. A suitable voltage resistance sensor is disclosed in EP 1883798 B1, incorporated herein by reference. A suitable radio frequency sensor is disclosed in EP 2052352 B1, incorporated herein by reference.

Referring to FIG. 2, in various embodiments, the wearable device **10** includes a power source **24**, such a battery that can be rechargeable. The battery **24** can be put into a sleep state when not actively used in order to preserve power. A wake up feature allows the battery **24** and other electronics of the wearable device **10** to "sleep" during non-use or and is initiated into the "wake up" mode by certain predestinated events.

In one embodiment, as illustrated in FIG. 3, a telemetry system server **16** is coupled to a database **18**. Each wearable device **10** is assigned its own unique identification, ID.

The data transmitted by the wearable device **10** sensors **14** and its ID may be coded by appending a seed to digital data bits. As illustrated in FIG. 3 central processor unit **20** (CPU) validates or rejects received upon detection of the seed string appended to the digital data bits. In the alternative, the digital data bits may be coded and decoded by applying a scrambling algorithm utilizing the seed. A programming device **22** may be configured to transmit data to a sensor **14** utilizing a variety of alternative transmission means, including, for example, RF, IR, optical, and the like, or a magnetic loop/induction system.

In one embodiment, sensors **14** are configured to be shipped to users in a non-programmable mode with all programming already performed at the factory. A random seed may be communicated to the programming device **22** can a variety of different mechanisms, including but not limited to, via scanning a bar code, manual input, magnetic strip, random number generation, and the like.

Referring again to FIG. 2, in one embodiment, the wearable device **10** includes a control unit **26** that puts the wearable device **10** in a low power state. A monitoring system **28** can be included that remains active. The monitoring system **28** wakes up the electronics **30** in the wearable device **10** from a low power state. The control unit **26** can be notified of awaking of the other components by the monitoring system **28**. The control unit **26** can set a status bit on the monitoring

system **28** only when the battery **24** needs to be in a full power state. The control unit **26** then forces a power cycle.

Referring to FIG. 3, one embodiment of a telemetry system **32** is illustrated. The telemetry system **32** is in the communication with the sensors **14** and ID of the wearable device **10** and can include one or more receivers **34**, a central server **36** with the CPU **20**. The telemetry system **32** can optionally include a display **42** and an alarm **44**. The telemetry system **32** receives information from sensors **14** of a user's habits, activities, and the like, and then processes this information. Wearable device **10** with its unique ID and sensors **14** is assigned to a specific user in order to track and/or monitor that user. For illustrative purposes assume that three users A, B AND C are being tracked and monitored by the telemetry system **32**. It should, however, be appreciated that the telemetry system **32** may be implemented to track and/or monitor a much larger number of users.

In one embodiment of the present invention, radio frequency (RF) devices that are sensors **14** and/or chips may serve as the identifying devices. Each source, sensor **14**, ID and the like can carry a fixed radio frequency chip encoded with identifying data which may be correlated to the individual participants, parts or objects.

Telemetry system **32** of the present invention may include a Real-Time Location System (RTLS) **46** and Real-Time Sensing System (RTSS) **48** with RF technology. The RF technology may include active and/or passive RFID sensors **14** and an RF wireless array system as a receiver **34**. The RF technology in the RTLS **46** and RTSS **48** may include UWB technology (e.g., IEEE 802.15), WLAN technology (e.g., IEEE 802.11), SAW RFID positioning system technology, GPS technology, and the like.

The sensors **14** may communicate directly with each other and/or relay telemetry data directly to base receiving RF device(s) or base receivers **34**. The base receivers **34** may forward the telemetry data to a base computer either through a direct link or through a network. Alternatively the telemetry data may be forwarded to end user devices, including but not limited to, laptops, mobile devices and the like, either directly or through a network. The comprehensive telemetry system **32** using RF technologies such as UWB, ZigBee, Wi-Fi, GPS data system can be utilized as described above.

The readers/antennae may be interconnected using a LAN, such as Ethernet to provide a network communication infrastructure for the computers and servers. Active and passive RFID sensors **14** may be employed. The active sensors **14** (RFID) may have a two-way communication function, which allows the base computer system to dynamically manage the sensors **14**; vary update rates; send self-identification and telemetry data.

The active sensors **14** may employ dual-radio architecture. In one embodiment, active sensors **14** transmit radio pulses, which are used to determine precise two-dimensional or three-dimensional location and a conventional bi-directional radio, which is used as a control and telemetry channel with a sensor update rate.

The wearable device **10** gathers telemetry data, communicates that data to a base station, BLUETOOTH® enabled device, or smart phone and the like. From the base station, the wearable device **10** can receive firmware updates or via a BLUETOOTH® enabled device. The wearable device **10** can receive updates wirelessly. The base station can receive firmware updates from Network Systems, take telemetry data from the wearable device **10** and transfer it to Network Systems. Telemetry data received from the base station is analyzed by servers and presented to an end user. Any third party



device can receive data from the wearable device **10** wirelessly and deliver information to the servers for processing.

In one embodiment, the wearable device **10** uses an accelerometer, gyroscope, GPS sensor, a BLUETOOTH® chip, and a heart rate monitor.

As a non-limiting example, for heart monitoring, the accelerometer, sensor **14**, determines when to sample the sensors **14** and to improve the accuracy of the heart rate monitor. The gyroscope detects movement and orientation and the GPS sensor is used to determine location of the user. A BLUETOOTH® chip allows the device to connect wirelessly to other third party devices.

As a non-limiting example, a heart rate monitor **14** detects the user's heart rate in order to accurately determine the user's activity level, behavioral patterns and the like.

An Artificial Intelligence (AI) or Machine Learning-grade algorithms is used to identify the user's activities, behaviors, behaviors and perform analysis. Examples of AI algorithms include Classifiers, Expert systems, case based reasoning, Bayesian networks, and Behavior based AI, Neural networks, Fuzzy systems, Evolutionary computation, and hybrid intelligent systems. A brief description of these algorithms is provided in Wikipedia and stated below.

Classifiers are functions that can be tuned according to examples. A wide range of classifiers are available, each with its strengths and weaknesses. The most widely used classifiers are neural networks, support vector machines, k-nearest neighbor algorithms, Gaussian mixture models, naive Bayes classifiers, and decision trees. Expert systems apply reasoning capabilities to reach a conclusion. An expert system can process large amounts of known information and provide conclusions based on them.

A case-based reasoning system stores a set of problems and answers in an organized data structure called cases. A case based reasoning system upon being presented with a problem finds a case in its knowledge base that is most closely related to the new problem and presents its solutions as an output with suitable modifications. A behavior based AI is a modular method of building AI systems by hand. Neural networks are trainable systems with very strong pattern recognition capabilities.

Fuzzy systems provide techniques for reasoning under uncertainty and have been widely used in modern industrial and consumer product control systems. An Evolutionary Computation applies biologically inspired concepts such as populations, mutation and survival of the fittest to generate increasingly better solutions to the problem. These methods most notably divide into evolutionary algorithms (e.g., genetic algorithms) and swarm intelligence (e.g., ant algorithms). Hybrid intelligent systems are any combinations of the above. It is understood that any other algorithm, AI or otherwise, may also be used. Examples of suitable algorithms that can be used with the embodiments of the present invention are disclosed in, EP 1371004 A4, EP 1367534 A2, US 20120226639 and US 20120225719, all incorporated fully herein by reference.

In various embodiments, the wearable device **10** has additional features. In one embodiment, the wearable device **10** changes color, via infrared LEDs, to accurately match the wearer's skin tone. This creates a seamless and more personal integration of technology into the user's daily life. In this embodiment, there is skin contact with the wearable device **10**.

In another embodiment, the wearable device **10** remotely reminds and can be used to administer medications. As a non-limiting example, the wearable device **10** can inject

adrenalin. In one embodiment, the wearable device **10** has sleep pattern recognition based on movement and heart rate.

In various embodiments, the wearable device **10** uses algorithms to determine activity type, behavioral patterns and user habits based on collected data.

In one embodiment, the wearable device **10** uses the accelerometer information to improve the heart rate monitor. As a non-limiting example, the wearable device **10** detects movement and speed. Addition of this data improves the accuracy of the heart rate monitor and corrects for any miscalculations in vibration, noise and skin color.

In one embodiment, velocity readouts and accelerometer data are used to measure when to sample heart rate. For example, if the wearable device **10** registers zero velocity readout, the user is probably at rest or engaged in a passive activity. Thus, the wearable device **10** knows not to sample heart rate. This results in conservation of time, energy and data storage.

User activity, performance and action can be based on the acceleration and angular velocity of the wearable device **10**. In one embodiment, the wearable device **10** has a feature where the wearable device **10** authorizes third party interaction based on hand gesture, on previous interactions or patterns of behavior. As a non-limiting example, if one purchases a coke every day for the last two weeks, the wearable device **10** can "orders" the person another one based on the prior history.

In one embodiment, the wearable device **10** features nearby wearable device **10** recognition that provides for other wearable device **10** devices to be recognized within a particular vicinity and are able to share and transfer data between them. The wearable device **10**'s data analysis and feedback can be based on current or previous sensor output. The wearable device **10** can alert the user when to charge the wearable device **10** and when it is the most convenient for the user.

In one embodiment, the wearable device **10** provides feedback via color change. An outer shell of the wearable device **10** can use visual feedback, including but not limited to pigment or color changes to indicate changes in user behavior or to prompt changes in user behavior. In one embodiment, the wearable device **10** is flexible in shape. As a non-limiting example, if the user puts the wearable device **10** over their hand it can expand or contract, morphing to change size and shape.

In one embodiment, the wearable device **10** can have a sync feature for multiple bands at the same time.

In one embodiment, the wearable device **10** has data transfer to an external device that can be included or not included in system **32**. Wearable device **10** could be a data leaching device. For example, the user can relay information to someone else's device (intermediary device) to access Network Systems connected device.

In one embodiment, the wearable device **10** can disable the recording of one or more sensors **14** based on location, acceleration (or lack thereof) and the like.

In one embodiment, the wearable device **10** detects different types of transportation and activity based on sensor data.

In one embodiment, wearable device **10** can unlock doors or cars. The user can turn it on and off. As a non-limiting example, it can be turned off by having a capacitor switch on top and bottom and is placed in a way that one couldn't accidentally turn it off. As a non-limiting example, turning it off can be done by rotating the wearable device **10** once.

In one embodiment, the wearable device **10** recognizes the wearer based on biometric information, previous data, move-



## 11

ment pattern, and the like. In one embodiment, the wearable device 10 detects a new user based on an inability to match to user/usage patterns.

As non-limiting examples, a variety of different sensors 14 can be used such as, an altimeter, blood oxygen recognition, heart rate from wrist via sonar, Doppler, based on sound wave and movement, based on pressure, and the like. A pressure sensor 14 can be placed on a circulatory vessel such as a vein to detect pulse.

With the wearable device 10 of the present invention, mechanical actions of the user can be triggered, recognized and evaluated.

As a non-limiting example, with multiple users and wearable devices 10, a separate wearable device 10 ID is assigned to each of the users A, B AND C, and thereafter the assigned transmitter/monitor 14 generates user activity data and/or user tracking data. For purposes of this disclosure, monitoring data is defined to include data acquired during the process of monitoring or evaluating a predefined characteristic. The user activity data tracks data from the sensors 14 is transferred to the receivers 34 via the wireless connections 38 represented by a dashed line.

A network of receivers 34 transfers the user activity and/or tracking data to system server 16 via connection 50. System server 16 includes a processor 52 configured to process the user data in a known manner. For example, the processor 52 may convert raw user data acquired by the sensors 14 into more conveniently readable data.

As a non-limiting example, the display 42 can be implemented to graphically convey user information from system server 16 in a conveniently readable manner. As a non-limiting example, the user may be a cardiac patient with user monitoring data graphically conveyed as a conventional ECG plot comprising a sequence of P-waves, a QRS complexes and a T-waves. As another example, user tracking data may be graphically conveyed as an icon superimposed onto a map to indicate the user's relative location. Alarm 44 may be included in this embodiment.

In some embodiments, system 32 ID circuitry delivers a unique ID to the wearable device from database 18. Bluetooth chips can be coupled with other wearable devices 10 in the area. This data is then stored, as more fully explained in the following paragraph. The unique ID can be utilized for a variety of different applications including but not limited to payments, social networking and the like.

The ID circuitry of system 32 can include a number of system/components: unique ID storage, communication system, which reads and transmits the unique ID from the unique ID storage, battery 24 or power system that provides power to enable communication with the wearable device 10, a pathway system to route signals to through the circuitry, a cluster that crunches information, and a control system, to orchestrate the communication between different systems. All of these systems can be implemented in hardware, software or a combination thereof. Continuing with the telemetry system 32, sensors 14 and sensing devices are disposed on wearable devices 10 worn by users. Data, such as movement, location, speed, acceleration, and the like, can be acquired, captured and provided to system 32.

System 32 and an associated network can include an identification reference, including user activity, performance and reference information for each individual sensor 14 and location.

The user activity, performance metrics, data and the like captured by system 32 can be recorded into standard relational databases SQL server, and/or other formats and can be exported in real-time.

## 12

In various embodiments, the wearable device 10 and/or system 32 are fully sealed and have inductively charges. All communication is done wirelessly.

In one embodiment, there are no electrical contacts, physical contacts or connections with the wearable device 10. The wearable device 10 is seamless. The telemetry system 32 can include a microprocessor with CPU 20, memory, interface electronics and conditioning electronics 33 configured to receive a signal from the sensors 14. In one embodiment, all or a portion of the conditioning electronics 33 are at the wearable device 10.

In one embodiment, the CPU 20 includes a processor 52, which can be a microprocessor, read only memory used to store instructions that the processor may fetch in executing its program, a random access memory (RAM) used by the processor 52 to store information and a master dock. The microprocessor is controlled by the master clock that provides a master timing signal used to sequence the microprocessor 52 through its internal states in its execution of each processed instruction. In one embodiment, the microprocessor 52, and especially the CPU 20, is a low power device, such as CMOS, as is the necessary logic used to implement the processor design. The telemetry system 32 can store information about the user's activity in memory.

This memory may be external to the CPU 20 but can reside in the RAM. The memory may be nonvolatile such as battery backed RAM or electrically erasable programmable read only memory (EEPROM). Signals from the sensors 14 can be in communication with conditioning electronics 33 that with a filter 35, with scale and can determine the presence of certain conditions. This conditioning essentially cleans the signal up for processing by CPU 20 and in some cases preprocesses the information. These signals are then passed to interface electronics, which converts the analog voltage or currents to binary ones and zeroes understood by the CPU 20. The telemetry system 32 can also provide for intelligence in the signal processing, such as achieved by the CPU 20 in evaluating historical data.

In one embodiment, the actions of the user wearing the wearable device 10 with the unique ID can be used for different activities and can have different classifications at system 32.

The classification can be in response to the user's location, where the user spends it time, with which the user spends its time, determination of working relationships, family relationships, social relationships, and the like. These last few determinations can be based on the time of day, the types of interactions, comparisons of the amount of time with others, the time of day, a frequency of contact with others, the type of contact with others, the location and type of place where the user is at, and the like. These results are stored in database 18.

In one embodiment, the user wearing the wearable device 10 can access this information from any place where data is presented to the user, including but not limited to mobile devices, the WEB, applications program identifiers, and the like.

As a non-limiting example, the wearable device 10 communicates with a base station at system 32. The wearable device 10 can intelligently switch between data transfer and charging based on sensor readout. The wearable device 10 can represent data based on connected devices.

In one embodiment, the wearable device 10 has the capability of providing recommendations, popularity of locations or activities based on acquired data from the user.

In one embodiment, the wearable device 10 has the capability of introducing the user to other people or users based on their data and the user's data.



## 13

In one embodiment, the wearable device **10** can determine emotion of the user.

In one embodiment, the wearable device **10** uses incremental data transfer via BLUETOOTH® and the like. The wearable device **10** can transmit data through the inductive coupling for wireless charging. The user is also able to change the frequency of data transmission.

The wearable device **10** can engage in intelligent switching between incremental and full syncing of data based on available communication routes. As a non-limiting example, this can be via cellular networks, WiFi, BLUETOOTH® and the like. In one embodiment, the wearable device **10** has data storage. As a non-limiting example, storage of telemetry data on wearable device **10** can be amounts up to about 16 mg.

In one embodiment, data transferred if it's in a selected proximity of a base station of system **32** or in proximity of an associated connected network. In one embodiment, the wearable device **10** has a dynamic change of data capture frequency. The wearable device **10** can be programmed to instantly change how often it samples any sensor **14** based upon the sensor data. Intelligent data sampling is based on sensor readout.

The wearable device **10** can receive firmware updates via a base station **110** of system **32**. In one embodiment, the wearable device **10** presents analyzed data and feedback on a website. In one embodiment, the wearable device **10**'s software is based on unique human movement. The wearable device **10** is able to identify its wearer based on the unique patterns of movement, location check-ins and daily habits of the user.

In one embodiment, the app can be used on a mobile device, including but not limited to a smart phone and the like.

In one embodiment, a breakdown of recounting data that has been collecting is presented for analysis of that data. Observation or recommendations can be presented based on historical information and live information. The importance of the data can be based on past user behavior.

In one embodiment, the wearable device **10** has artificial intelligence. A wearable device processor **54** implements logic resources that exist on wearable device **10**.

In one embodiment, wearable device **10** engages in the routing of user information to third parties based on pre-defined rules, based on system **32** analysis.

In one embodiment, wearable device **10** includes one or more processors **54** that implement intelligent algorithmic processing and transfer of information to third parties. Feedback can be provided to the end user that is based on visual, tactile, gesture information and the like.

The ID can be sent from the wearable device **10** in a variety of different transmit modes, which may be provided as part of the firmware or software of an ID or sensor transmitter **14**, and which may be utilized selectively during the operation of said sensor transmitter **14**, may include "burst" transmit modes, wherein a burst of data information is transmitted, or "parcel" transmit modes, wherein timed data packets of data, which may, as desired, comprise partial data strings, are transmitted, and, if desired, repeated during time intervals. Further, the sensors **14** may have programmed therein diagnostic routines or other test modes which assist during manufacture and use, providing the operator with operational status and verification information on said sensor/transmitter **14**, as needed. Referring to FIG. 4, system **32** includes data base **18** which contains the desired transmitter, sensor, **14** personality data, as well as, the address/device ID bits for each wearable device **10**.

In one embodiment, the initial programming of the wearable device **10** for the ID, as well as optionally other personal

## 14

information of the user, is done securely, as unauthorized future alteration of same thereafter can be utilized as a means of violating system integrity.

In one embodiment, an inductive field coil is used for programming the sensors **14** and ID of wearable device **10**.

As illustrated in FIG. 4, the wearable device **10** can include a sensor **14** with an output that be received by an amplifier **56** and decoded by an I/O decoder **58** to determine I/O logic levels, as well as, both clock and data information **60**. Many such methods are commonly available including ratio encoding, Manchester encoding, Non-Return to Zero (NRZ) encoding, or the like; alternatively, a UART type approach can be used. Once so converted, clock and data signals containing the information bits are passed to a memory **62**. Any of these connections provides a logical link from the system's database **18** to the sensor **14**, ID of the wearable device **10**, as shown in FIG. 5.

In one embodiment, illustrated in FIG. 5, the system **32** chooses the necessary programmable sensor functions and stores them into database **18**. In one embodiment, in order to insure that an unauthorized user cannot connect into and program wearable device **10** the following procedure may be used:

Both the sensor **14** and receiver **34** contain an identical, repeatable pseudo randomization algorithm in ROM or in ASIC logic.

Referring to FIG. 6, the algorithm is applied to outgoing programming data **64** from system **32** and produces a number of security/randomization bits **66** that can be appended to the outgoing programming message or message **68** and sent to a sensor **14**.

Referring to FIG. 7 the sensor **14** likewise applies this pseudo randomization algorithm as the security/randomization bits **66** to the outgoing programming data, now forming the incoming programming data **70** to sensor **14** and produces a several bit result in the shift register **71**. The scrambling algorithm is devised such that a small difference in the programming bit stream causes a great difference in the pseudo randomization result. As a non-limiting example, the present invention can use a 16 bit polynomial to produce this pseudo randomization.

Optionally, in one embodiment, before a sensor **14** accepts this programming, stored in an address and personality register **73**, both the pseudo random code, stored in data in a shift register **75** from system **32** and a sensor **14**, in a shift register **71** must match via a comparator ID, **77**, indicating unauthorized acceptance use. In addition to insuring authorized access, this process also insures that the data itself is correct. The longer the polynomial sequence used, the greater the security.

In one embodiment, spread spectrum or other RF transmission is used and can include programming to determine that the frequency or spread spectrum code is unique to the area. If a spread spectrum code, system code, or frequency channel is found to be occupied at a future time of use. Re-programming of the wearable device **10** is then done with a new, unused spread spectrum code or system code or frequency channel can be selected, or, in the alternative, CPU **20**.

As illustrated in FIG. 5, step "E" would include, for example, the step of the sensor **14**, inputting the programming message and saving a seed in memory **62**; with the sensor **14** utilizing the seed to code digital data bits transmitted.

As illustrated in FIG. 8, the location of a wearable device **10** with the ID and sensors **14** can be determined. As a non-limiting example, in one embodiment the wearable device **10** includes a sensor **14** that can provide a position signal having positioning data (e.g., raw GPD data or pseudo ranges) and



15

the ID is transmitted from the wearable device **10** to system server **16**. Server **16** receives the position signal and analyzes the signal to generate information representing the location of the wearable device **10**. Server **16** transmits this location information to a client computer where the location of the wearable device **10**, allowing a user to identify the location of the remote sensor **14**.

In one embodiment, the position signal transmitted by the remote sensor **14** can also include an emergency code. For example, in the event of an emergency, such as a medical emergency or otherwise, a user may press a "panic button" that can be on the wearable device **10** or by use of a user's mobile device. Pressing the panic button may cause mobile device **74** to transmit an emergency signal to a cell site **76** where the emergency signal is relayed to server **16**. In response, server **16** can transmit Doppler information regarding in-view satellites, a fix command and a time trigger signal to the wearable device **10**.

When the location of the wearable device **10** has been determined, software running on server **16** configures server **16** such that a call or other signal is sent to a local emergency operator in the vicinity of remote sensor **14**. When the call or signal is received at the emergency operator station, the location of remote sensor **14** is transmitted and displayed. In some cases, where separate panic buttons are available for identifying medical, police, fire or other types of emergencies, the nature of the emergency is also displayed for the emergency operator. Based on this information, the emergency operator can initiate an emergency response by providing the location of remote sensor **14** to the required emergency service (police, fire department, ambulance service, etc.). In other embodiments, instead of or in addition to a position report for the remote sensor **14**, the emergency operator may also be provided with information which identifies an emergency response vehicle in close proximity to remote sensor **14**.

As illustrated in FIG. 9, a sensor **14** of the wearable device **10** can include a SNAPSHOT GPS receiver **72**. As described above, sensor **14** uses information transmitted from separately located base station **110**, mobile devices, computers, and other devices, to assist in determining the position of the remote sensor **14**, as more fully disclosed in U.S. Pat. No. 6,661,372, incorporated herein by reference.

As non-limiting examples, and as illustrated in FIG. 10, the sensors **14** can be a thermal transducer **78**, an acoustic transducer **80**, and a magnetic transducer **82**. It will be appreciated that the present invention is not limited. The transducers **78**, **80**, and **82** in the wearable device **10** can communicate with a microprocessor **84** also located in the wearable device **10**. The wearable device **10** can communicate with other devices via an RF transceiver **86**, an IRDA transceiver **88**, and/or an RF backscatter transceiver **90**. Each of the components in the wearable device **10** receives power as necessary from the battery **24**, which may include the rechargeable battery.

The acoustic transducer **80** may include a microphone, a low-pass filter, a gain amplifier, and a threshold comparator. The acoustic transducer **80** may include an omnidirectional microphone, although any other suitable acoustic transducer device would suffice. The microphone may be a surface mount MEMS device that has a frequency range of 100 Hz to 10 kHz. A single MCP602 operational amplifier is used on the acoustic sensor to amplify and low-pass filter the acoustic signal from the microphone. Another operational amplifier is used to generate a voltage reference used for single biasing and detection. The microphone output is biased to the mid-way point between the circuit supply voltage and ground to allow for both positive and negative signal swings. The biased signal is filtered with a second order low-pass Butterworth

16

filter to remove upper frequency noise. It is then amplified with an adjustable gain that is controlled by a digital resistor potentiometer. This digital resistor operates on an I2C bus and is controlled by the microprocessor **84**. Lastly, the amplified acoustic signal is threshold detected against a static voltage to detect sufficiently large acoustic signals. The digital output of the threshold detector is connected to the microprocessor **84** for processing.

The magnetic transducer **82** can include a magnetic sensor integrated circuit, a differential instrumentation amplifier, a low-pass filter, two gain amplifiers, and a threshold detector. The magnetic transducer **82** may include an NVE AA002-02 GMR (giant magneto resistive) field sensor, although any suitable magnetic sensor would suffice. This sensor has a saturation field of 15 Oe, a linear range of 0 to 10.5 Oe, and a sensitivity of 3 mV/V/Oe. Two MCP602 CMOS operational amplifiers are used on the magnetic sensor to amplify and low-pass filter the analog output signal. An INA122UA instrumentation amplifier is used as a difference amplifier for the differential output from the magnetic sensor. The magnetic sensor IC can be based on Spintronics technology. Its output includes a differential voltage pair proportional to the detected magnetic field. The differential voltage pair is amplified and converted to a single voltage by the instrumentation amplifier. The AC-coupled signal is then amplified and filtered with a low-pass filter to remove upper frequency noise and boost the low-voltage signal output. The signal is amplified a second time by an adjustable gain controlled by a digital resistor similar to the acoustic sensor. Lastly, the amplified magnetic signal is threshold detected against a static voltage, to detect sufficiently large changes in magnetic fields. The digital output of the threshold detector can be connected to the microprocessor **84** for processing.

A DS1803E-010 digitally controlled 10 kOhm variable resistor can be used in both the acoustic and magnetic sensor circuits. It is used to adjust the gain of one gain stage in each circuit. The digital resistor is controlled through an I2C interface. A LMV393IPWR comparator is also used in both the magnetic and acoustic sensor circuits for determining when a sufficiently strong sensor signal has been detected. It compares the analog sensor signal against the voltage reference and its output is tied to the microprocessor **84** for data collection.

The thermal transducer **78** may include a Burr Brown TMP 100NA/250 12-bit digital temperature sensor, although any suitable thermal sensor would suffice. The digital temperature sensor has an operating range of -55 to +120.degree. C., an accuracy of 0.5.degree. C. and a maximum resolution of 0.0625.degree. C.

Even though it is a 12-bit sensor, suitable results are achieved with only 9-bit conversions with only the 8 most significant bits used. The sensor has an I2C interface and is normally kept in sleep mode for low power operation. When directed by the microprocessor **84**, the thermal transducer can perform a 9-bit temperature conversion in 75 milliseconds.

The RF transceiver **86** may include an RF Monolithic DR3000 transceiver, although any suitable transceiver or separate transmitter and receiver **34** would suffice. This transceiver **86** allows for both digital transmission and reception. The transceiver **86** can have an operating frequency of 916.5 MHz and is capable of baud rates between 2.4 kbps and 19.2 kbps. It can use OOK modulation and has an output power of 0.75 mW. It also can use digital inputs and outputs for direct connection with the microprocessor **84**. The transceiver **86** can use an antenna **92** (FIG. 11) that may include a 17 mil thick plain steel electric guitar G-string cut to a length of 8.18 cm. It is used in a monopole over ground configuration and



can require a matching circuit of one inductor and one capacitor. Alternatively, Frequency Shift Keying (FSK), Quadrature Phase Shift Keying (QPSK), or any other suitable modulation scheme may be utilized.

The IRDA transceiver **88** may include a Sharp GP2W0110YPS infrared transceiver, although any suitable IRDA compliant infrared transceiver would suffice. This transceiver **88** can be IRDA v1.2 compliant and in one embodiment has an operating range of 0.7 meters. In one embodiment, it is capable of 115.2 kbps data speeds.

The RF backscatter transmission device **90** may include circuitry available from Alien Technology (of Morgan Hill, Calif.) for receiving and transmitting signals via RF backscatter. Battery **24** may be a 3.6 volt ½ AA lithium battery with a capacity of 1.2 amp hours. The battery **24** can be a power source **24** that can include a Texas Instruments TPS76930DBVT voltage regulator to regulate the output signal to 3 volts and with a maximum current of 100 mA. The voltage regulator can include a LDO.

The RF backscatter transceiver **86** in the wearable device **10** communicates with an RF backscatter reader **94** such as a class 3 reader from Alien Technology. The reader **94** transmits data to the backscatter transceiver **90** of the wearable device **10** by broadcasting encoded RF pulses and receives data back from the transceiver **86** by continually broadcasting RF energy to the sensor **10** and monitoring the modulated RF reflections from the sensor **10**.

The RF backscatter transceiver **90** can include a printed circuit board (PCB) patch antenna for RF reception, and RF modulation, a Schotky diode detector circuit, a comparator circuit for signal decoding, and a logic circuit for wake-up. The logic circuit monitors the incoming data, and when an appropriate wake-up pattern is detected, it triggers the microprocessor **84** so that data reception can begin. In one embodiment, the reader **94** has an operating frequency between 2402 MHz and 2480 MHz, and uses frequency hopping in this band to reduce noise interference. A modulation method used by the reader **94** can be On-Off Keying (OOK). In one embodiment, the transmission power is 1 watt. The operation of the reader **94** may be controlled by an external computer (not shown) as directed by Labview software via a RS-232 serial link.

The RF transceiver **86** can communicate with an external RF transceiver **96** such as a DR3000 transceiver from Radio Monolithics, Inc. In one embodiment, it operates at 916.5 MHz, uses OOK modulation, has a communication range of 100 meters line of sight, and a baud rate of 19.2 kbps. The active RF antenna **92** can be a quarter-wavelength monopole made from a guitar G-string and appropriate matching circuitry. Two control lines from the microprocessor **84** can be used to select the mode of operation, choosing from transmit, receive, and sleep. The active RF receiver **34** consumes the most power in receive mode compared to the other two communication links.

FIG. 6 shows the relative positioning and shape of the active RF antenna **92** and the RF backscatter antenna **98**.

The IRDA transceiver **88** of the wearable device **10** can communicate with an external IRDA transceiver **100** that may be identical to the IRDA transceiver **88**. Alternatively, the IRDA transceiver **100** can be one such as is provided in most personal digital assistants (PDA) as well as many other consumer devices. The IRDA communication link follows the standard IRDA signal and coding protocol and is modeled after a standard UART interface. In one embodiment, the IRDA transceiver **88** is capable of data speeds less than 115.2 kbps, and may only have a range of 0.7 meters for transmission. One advantage of the IRDA communication link is that

it does not require any of the RF spectrums for operation, but it typically does require line-of-sight communication.

When any one of the transceivers **86**, **88** and **90** on the wearable device **10** detect the beginning of valid data on their respective communication link, all other transceivers are disabled, thereby preventing the corruption of incoming data with the noise or partial data packets on the other communication links. However, if the data on the active transceiver proves to be erroneous, the other transceivers will be re-enabled if appropriate to allow normal operation to continue. If the data received by the active transceiver is valid, however, the other transceivers will remain disabled for several hundred milliseconds longer in the high probability that the next data packet will be transmitted on the same communication link. If, after this extended delay, no additional packets are received, then the other transceivers will be re-enabled as appropriate.

In one embodiment, the active RF protocol has no wake-up or synchronization packets, and the packets sent to and from the sensor are identical. In one embodiment, the format of an active RF packet is shown in FIG. 2. It can include a preamble to reset and spin-up the state machine of the RF receiver **34** and to properly bias the receiver's **34** data slicer/threshold detector for optimum noise rejection and signal regeneration, two framing bits to indicate the beginning and end of the data bytes, and the data bytes themselves.

Furthermore, the encoding scheme for the three symbols is shown in FIG. 12. The entire packet is DC balanced to maintain an optimal level on the data slicer/threshold detector and the receiver **34**. Data is sent most significant bit first.

The IRDA communication link can follow the standard IRDA protocol for bit encoding and UART protocol for byte transmission. Packets transmitted on the IRDA link can contain no preamble or framing bits, but they do have a header that contains two bytes. The first byte is an ASCII "I" which denotes the beginning of a valid IRDA packet. The second byte equals the number of preceding bytes in the packet. This value is used by the receiver **34** to determine when the entire packet has been received and processing of information can begin. The packet structure is shown in FIG. 13 and the IRDA/UART encoding scheme is shown in FIG. 14.

The data bytes contained in a packet transmitted to the sensor **10** through any of the communication links conform to a packet format. The CMD section of a packet is a single byte that identifies the type of packet being sent. The CMD byte appears above the beginning and end of the packet and the two must be identical. The reason for including the redundant byte is to further eliminate the chance of a packet's CMD identifier being corrupted at the receiver **34**, even if the CHECKSUM is correct.

The PAYLOAD contains all of the data that must be sent to, or returned from, the sensor. The PAYLOAD is broken down into individual bytes with the overall number of bytes and their content dependent on the type of packet being sent.

The CHECKSUM is a 16-bit CRC that is performed on all bytes in the data packet excluding the end CMD byte in packets generated by the external device. The CHECKSUM is sent most significant byte first.

The transceivers **86**, **88** and **90** may be required to communicate over a greater distance than do the components described herein. Upgrading these components to be suitable for longer distance transmission is considered to be within the spirit of this invention. The type of transducer is not limited to the specific transducer types described herein. In addition, the logic described herein for arbitrating between which communication device to use to communicate with the outside world



19

and which sensor data to provide at what time is but one possible approach to arbitration logic within such a remote sensor 10.

FIG. 15 illustrates one embodiment of an exemplary network 101 that can be used with the present invention. As shown in FIG. 15 a wireless packet data service network 102 that can be utilized with the wearable device 10. An enterprise network 104, which may be a packet-switched network, can include one or more geographic sites and be organized as a local area network (LAN), wide area network (WAN) or metropolitan area network (MAN), and the like. One or more application servers 106-1 through 106-N can be included and disposed as part of the enterprise network 104 are operable to provide or effectuate a host of internal and external services such as email, video mail, Network Systems access, corporate data access, messaging, calendaring and scheduling, information management, and the like using the unique IDs of the wearable devices 10. The wearable device 10 can be in communication with a variety of personal information devices other than the wearable device 10, including but not limited to, computers, laptop computers, mobile devices, and the like.

Additionally, system server 16 may be interfaced with the enterprise network 104 to access or effectuate any of the services from a remote location using a wearable device 10. A secure communication link with end-to-end encryption may be established that is mediated through an external IP network, i.e., a public packet-switched network such as Network Systems 108, as well as the wireless packet data service network 102 operable with a wearable device 10 via suitable wireless network infrastructure that includes a base station (BS) 110. In one embodiment, a trusted relay network 112 may be disposed between Network Systems 108 and the infrastructure of wireless packet data service network 102.

In another embodiment, the infrastructure of the trusted relay network 112 may be integrated with the wireless packet data service network 102, and the functionality of the relay infrastructure can be consolidated as a separate layer within a "one-network" environment. Additionally, as non-limiting examples, wearable device 10 may be capable of receiving and sending messages, web browsing, interfacing with corporate application servers, and the like, regardless of the relationship between the networks 102 and 112. Accordingly, a "network node" may include both relay functionality and wireless network infrastructure functionality in some exemplary implementations.

In one embodiment, the wireless packet data service network 102 is implemented in any known or heretofore unknown communications technologies and network protocols, as long as a packet-switched data service is available therein for transmitting packetized information. For instance, the wireless packet data service network 102 may be comprised of a General Packet Radio Service (GPRS) network that provides a packet radio access for mobile devices using the cellular infrastructure of a Global System for Mobile Communications (GSM)-based carrier network. In other implementations, the wireless packet data service network 102 may comprise an Enhanced Data Rates for GSM Evolution (EDGE) network, an Integrated Digital Enhanced Network (IDEN), a Code Division Multiple Access (CDMA) network, a Universal Mobile Telecommunications System (UMTS) network, or any 3rd Generation (3G) network.

Referring now to FIGS. 16(a) through 16(d), in one embodiment, the wearable device 10 is in communication with an interaction engine 120 that can be at a mobile device 74 or system 32. The interface engine can be a software application running on mobile device 74 associated with another party, including but not limited to a merchant, an

20

associate, a friend, and the like. The enables the wearable device 10 user and a merchant to interact with a transaction engine 114 to and enter into a financial transaction for the transfer of funds from a third party payment system 116 that is independent of the wearable device 10 user's financial account 118, and complete a transaction. It should be noted that the payment system 116 can be affiliated with the financial account 118 or can be a separate and non-affiliated with the financial account 118. The interaction engine 120 can take input of information related to a transfer of funds from the wearable device 10 users' financial accounts 118 as input to the transaction engine 114 to initiate and complete a financial transaction, including but not limited the purchase and payment of goods and services. In one embodiment, this input to the interaction engine 114 can include, an amount of a transaction, additional items related to the transaction, authorization and/or signature of the wearable device 10 user.

In one embodiment, the mobile device 74 receives information from the wearable device 10, e.g., the unique ID.

The interaction engine 120 can also present products or services provided by a merchant to directly to or through system 32 to the wearable device 10 user. In one embodiment, the wearable device 10 users can use the mobile device 74, the WEB, and the like, to view, text, pictures, audio, and videos, and browse through the products and services on the mobile device 74, personal computers, other communication devices, the WEB, and anything that is Bluetooth®, anything associated with Network Systems, and the like.

In one embodiment, the transaction engine 114, which can be at the mobile device 74, or external to the mobile device 74, including but not limited to wearable device 10 and the like, takes decoded financial transaction card information from a decoding engine 122, internal or external to the mobile device 74, and a transaction amount from an interaction engine 120, also internal or external to the mobile device. The transaction engine 114 then contacts the payment service 116, and or the wearable device 10 users' financial account 118, such as an acquiring bank that handles such authorization request, directly or through the payment system 116, which may then communicate with a financial transaction card issuing bank to either authorize or deny the transaction. The payment system 116 can include a user database, a transaction database, a product database, and the like. These databases can also be external to payment system 116. If the third party authorizes the transaction, then the transaction engine 114 transfers funds deducted from the account of the wearable device 10 user, or the payment system 116 can already have those funds readily available, to an account of a third party which can be another wearable device 10 user, a merchant, and the like, and provides transaction or transfer of fund results to the interaction engine 120 for presentation to a third party.

In one embodiment, the transaction engine 114 does not have the financial account or financial card information of the wearable device 10 user that is doing the transfer. In some embodiments, the transaction engine 114 keeps only selected information of the wearable device 10 user's financial accounts 118 or financial transaction cards.

In one embodiment, the wearable device communicates directly, without mobile device 74, with the payment system 116 and/or the user's financial account 118 or associated financial institution.

In one embodiment, the transaction engine 114 communicates and interacts with the financial account 118 or associated financial institution directly or through the payment system 116, through a user database, product database, and transaction database, which databases can be separate from or included in the payment system 116, over a network. The



21

network can be a communication network, as recited above, and can be based on well-known communication protocols, including but not limited to, a TCP/IP protocol.

With social networking applications, the wearable device **10**, with its unique ID, is an ID device. Information from the wearable device **10** relating to social networking, and the like, communicates with system **32**. In this manner, the wearable devices **10**, with their own unique ID's, can be recognized. This can occur at different locations, close by, distanced, and notifications can be sent to the different users wearing a wearable device **10** for a variety of social networking and other communication applications. Additionally, wearable device **10**, with its sensors **14** and ID can communicate directly to social networking sites, Network Systems, cloud services, and the like.

In one embodiment, with the current permissions given by the wearable device users, marketers, companies or individuals who wish can deliver advertisement wearable device **10** users. More particularly, system **32** can be configured to allow marketers, and the like, to deliver advertisements to consumers to buy products or services offered by the marketer. Advertisements can also be sent to wearable device **10** users with the appropriate permissions. In one embodiment, system **32** maintains the anonymity of the wearable device **10** users while allowing the marketers to have their advertisements delivered to those that fall within their defined market segment.

In one embodiment, the wearable device ID of a user provides a method of identifying and contacting users of a social networking service. The method may include the steps of signing up for a social networking service, displaying the wearable device ID, viewing another person's unique wearable device ID displayed by another user, and finding that user on a social networking service website by searching for the user using the wearable device ID viewed.

System **32** may serve a number of purposes without straying from the scope of the present invention. For example, the social networking service may allow wearable device **10** users to engage in non-romantic relationships, keep in touch with acquaintances, friends and family, professional business relationships, and romantic relationships, may allow communication between wearable device users on a message board or Network Systems forum, and may allow users to follow up on missed-connections that otherwise would not have been realized.

In one embodiment, the step of providing personal information to start an account with system **10** for different applications may be performed by a purchasing or acquiring a wearable device **10**, with a unique assigned ID, and the user can fill in an online form. This form may require users to fill in fields on the form. These fields may include: first and last name, email address, a desired password, phone number, gender, birth date, address, geographic region, education information, employment information, interests, relationship information and interests, family information, religious views, ethnicity, physical features including hair color, eye color, measurements, and the like, type of relationship being sought, living situation, answers to quiz questions, and a personal description about interesting personality traits, among other things. In addition, users may upload one or a plurality of photographs for other users to view, or for users to store the photo or photos on the server of system **32**.

In another embodiment the step of providing personal information to start an account with system **32** by wearable device **10** users may be performed automatically. In this embodiment, system **32** can access a social networking ser-

22

vice, access, via computer, contact lists or other sources of information that may include the type of information listed above.

In a further embodiment, the step of providing personal information to system **32** can be automated by importing data containing the personal information required from other social networking services including but not limited to Facebook®, LinkedIn®, MySpace®, Match.com®, eHarmony.com®, a user's email or contact list, v-card, and the like.

The unique wearable device ID may allow the user to be searched and identified by other users and potential users. Also, a computer generated email address may be provided to a user. In one embodiment, this email address may be the user's user ID followed by "@iseenya.com." In another embodiment, the email address may be the user's user ID directed to another domain name.

In one embodiment, a computer generated personal page may be provided to a wearable device **10** user. The personal page may utilize a computer to automatically import the information provided when signing up with system **32** or a social networking service. In another embodiment, the information and formatting of the personal page can be customizable.

When mobile device **74** is used, it communicates with one or more sensors **14** that are at the wearable device **10**, as more fully herein. The mobile device can **74** pull from system **32** updates from the server **16**, including but not limited to settings such as alarms, name of the wearable device wearer using the ID, a sensor **14** and the like. Sensors **14** at the wearable device **10** can send streams of information, both encrypted and non-encrypted to the mobile device and then to the server at system **32**. Server **16** sends encrypted, and can also send non-encrypted information, to mobile device **74**. Processing of this information can be achieved at the mobile device **74**, and/or server **16**. Mobile device **74** can receive raw sensor information from the wearable device **10**. This information can be compressed as well as non-compressed. A compression algorithm, at the wearable device and/or mobile device **74** or system **32**, can be used in order to minimize the amount of information that server **16** sends. System **32** can include additional encryption and/or decryption systems.

Referring now to FIG. **17**, a social network circle/group **124** (hereinafter "SNET circle") comprising social devices **126**, including wearable device **10**, is shown. Beyond traditional social networking features and services, a SNET circle **124** and associated social devices **124** according to various embodiments of the invention include numerous novel features and attributes as described more fully below with general reference to the illustration. Wearable device **10** can utilize network **101** for communication with the SNET circle, as well as with other social networking sites, or through system **32**.

Briefly, membership in the SNET circle **124** may comprise docked and undocked social devices **124** and human SNET circle members **[104] 128**, as well as proxies thereof. Further, SNET circle **124** nodes may include device services and software (e.g., applications) of various types participating as members. By way of example, SNET circle members might include artificial intelligence agents/social robots **130**, SNET security device(s) **132**, appliances, vehicles and service providers **134**, common or authorized members/functionality of other SNET circles **124**, and the like. Further, access to specific content and resources of a SNET circle **124** may be shared with members of additional SNET(s) **124**, including remote or web-based applications. Such access can be conditioned on acceptable profiling and association data. Simi-



larly, social devices or individuals may be granted temporary or ad hoc memberships, with or without restricted access.

In the illustrated embodiment, formation, maintenance and operation of SNET circle **124** is performed by standalone or distributed SNET processing circuitry and software **136**. It is noted that the “SNET processing circuitry” may comprise hardware, software, applications, or various combinations thereof, and be configurable to support various functionalities disclosed herein. Further, the SNET processing circuitry **136** may be included in a standalone server, server farm, cloud-based resources, network **101**, system **32** and/or the various types of devices described below, and incorporate authentication and security functionality **138**. In addition, specialized middleware may also be utilized by SNETs according to the invention, including standardized middleware with an associated certification process. Interactions and interdependencies within the SNET circle **124** may involve one or more of a social device association/control module **140**, a SNET circle member profiling module **142**, and an adaptive resource allocation and arbitration module **144** as described more fully below.

Distribution of internal and external SNET content/media **146** can be accomplished in a variety of ways in accordance with various embodiments of the invention. For example, media distribution may involve an adaptive or parallel network routing infrastructure involving a wide variety of communication protocols and wired and/or wireless communications channels. SNET content/media **146** may comprise, for example, various user-driven (advertising) channels, pictures, videos, links, online text, etc. Access to such content, as well as communications with and remote access to social devices **124** of the SNET circle **124**, may occur over an Network Systems backbone **148**, cellular communication system, WAN, LAN, and the like.

FIG. **18** illustrates an embodiment of a social group **150** comprising a variety of members in accordance with the present invention that can communicate through their wearable devices **10** and other devices, including but not limited to mobile devices **74**. In this embodiment, membership in the social group **150** may include a variety of novel social system members **[204]** **152** functioning in various capacities within the social group **150**. As will be understood, certain of the social system members **152** may support direct or indirect associations between the social group **150** and human members/non-members and users **154**.

In the illustrated embodiment, social system members (or nodes) **152** include one or more local or remote servers and server clusters that provide a support infrastructure for social group functionality and member operations (routing, data storage, services, etc.). Communications within the social group and with non-members may occur via dedicated or multi-function communication path devices.

Social system members **152** further include devices configured to operate as nodes within the social group **150**. Social functionality in such devices and other social system members **152** can be implemented through various means. For example, a device may have integral hardware/firmware/software to support social group access and member operations. Alternatively, a general purpose device **152a** may include social code that enables participation in the social group **150**. In a further embodiment, a device **152b** designed to include social functionality may participate in the social group **150** through a combination of non-social code and a social shim layer or driver wrapper. In yet another embodiment, a member device **152c** having a social design may utilize additional social code, including code specific to a social group **150**.

Participation in the social group **150** is supported through functionality that includes automated and member-triggered membership invitations and processing (membership management) **156**. More particularly, membership management **156** may function to invite prospective members to participate in the social group **150** through automatic, automated and member-triggered processes. For example, membership management **156** might be configured by a human user **154** to establish a social group **150** by automatically inviting/accepting social system members having certain characteristics (such as devices owned or controlled by the user or acquaintances of the user).

Processing of accepted invitations and unsolicited requests to join the social group **150** may be conditioned upon input or authorization from an existing social system member(s) **152** or human user(s) **154** (e.g., through a user interface). Similarly, membership management **156** may be configured to generate automated suggestions regarding which prospective members receive an invitation. Various other approaches, such as those described herein, can be used to establish membership in accordance with the invention.

Access to and visibility of resources of a social group **150**, including services and data, may be managed through general and member class-specific access configurations **158**. For example, if membership in the social group **150** includes family members and associated devices, a uniform access configuration (or separate device and human configurations) could be applied across the class in an automatic or automated manner. In other embodiments, access control and constraints are imposed on a per-member basis.

The social group **150** may offer a wide variety of member services **162**, including both internal and external services accessible by social system members **152**. By way of example, the social group **150** may offer email or other communication services between full members and/or authorized guest members and visitors. As with other resources of the social group **150**, access control and constraints on member services **162** may be applied to individual members or classes of members.

FIG. **19** is a functional block diagram illustrating a social network (SNET) infrastructure **164**, as more fully described and disclosed in EP 2582116, fully incorporated herein by reference.

In one embodiment, illustrated in FIG. **20**, wearable devices **10** are in communication with a distributed computer network **166** that can include networks **102**, **104**, **112**, coupled to Network Systems **108** and system **32** via a plurality of communication links **168**. Communication network **166** provides a mechanism for communication with system **16**, wearable device **10**, social media networks, mobile devices **74**, payment systems, **116**, the engines **114**, **120**, **122**, components of system **16**, and with all third parties, as described above.

The communication network **166** may itself be comprised of many interconnected computer systems and communication links. Communication links **168** may be hardwire links, optical links, satellite or other wireless communications links, wave propagation links, or any other mechanisms for communication of information. Various communication protocols may be used to facilitate communication between the various systems shown in FIG. **20**. These communication protocols may include TCP/IP, HTTP protocols, wireless application protocol (WAP), vendor-specific protocols, customized protocols, and others.

While in one embodiment, communication network **166** is the Network Systems, in other embodiments, communication network **166** may be any suitable communication network



25

166 including a local area network (LAN), a wide area network (WAN), a wireless network, an intranet, a private network, a public network, a switched network, and combinations of these, and the like.

System 32 is responsible for receiving information requests from wearable devices 10, third parties, and the like, performing processing required satisfying the requests, and for forwarding the results corresponding to the requests back to the requesting wearable device 10 and other systems. The processing required to satisfy the request may be performed by server 16 or may alternatively be delegated to other servers connected to communication network 166.

FIG. 21 shows an exemplary computer system that can be utilized with the wearable devices 10. In an embodiment, a user interfaces with system 32 using a wearable device 10 and then through a computer workstation system, such as shown in FIG. 21, a mobile device, and the like.

The communication network 166 may be the Network systems, among other things. The network may be a wireless, a wired network (e.g., using copper), telephone network, packet network, an optical network (e.g., using optical fiber), or a wireless network, or any combination of these. For example, data and other information may be passed between the computer and components (or steps) of a system of the invention using a wireless network using a protocol such as Wi-Fi (IEEE standards 802.11, 802.11a, 802.11b, 802.11e, 802.11g, 802.11i, 802.11n, and 802.11 ac, just to name a few examples), near field communication (NFC), radio-frequency identification (RFID), mobile or cellular wireless (e.g., 2G, 3G, 4G, 3GPP LTE, WiMAX, LTE, Flash-OFDM, HIPERMAN, iBurst, EDGE Evolution, UMTS, UMTS-TDD, IxRDD, and EV-DO). For example, signals from a computer may be transferred, at least in part, wirelessly to components or other computers.

FIG. 22 shows a system for activity collection and building a social graph for network wearable device 10 users. The system monitors users as they surf the Web, their activities, locations, status, interests, and other things. This can be achieved without regard to whether the wearable device users 10 are logged into a membership site, such as a social networking site.

Resources 170 and 172 gather activity data and pass this data to an activity storage server 174, typically via Network Systems 108. Partner resource 172 may be processed by a partner back end, and then this data is passed to activity storage server 174.

Wearable device 10 users can use social media sharing application or sites. Applications (e.g., a mobile device app or sites allow sharing of information with others. These can be used to collect activity data. A wearable device 10 user (sender) can share information (e.g., video, photo, link, article, or other) by posting to a site. The wearable device 10 user can post directly on the site or use an application program, such as a mobile application on a smartphone or tablet computer. When another user (recipient) clicks or vies the link, there is connection activity between the sender and recipient. This activity data is captured by system 32.

Messenger applications such as those on mobile device 74 or sites can allow Network Systems or Web messaging with others. Network Systems messaging is different from short messaging server (SMS) or text messaging. Messenger applications can be used to collect sharing activity data.

Users use messenger application to send links and other information to other users, and also achieve this using their wearable devices 10. A user (sender) can copy a link (e.g., via a clipboard) and send to one or more users via the messenger application with mobile device 74 and with its wearable

26

device 10. When a recipient user clicks on the link, there is connection activity between the sender and recipient for that link.

Sharing activity data can be captured as described above. There can be different data collectors for different devices and platforms. The activity data is transmitted to and stored at activity storage server 174, typically through Network Systems. Server 174 stores the data for further processing. There can be a significant amount of real-time data that is collected for processing. Distributed computing and processing can be used to process the data.

The activity data collected is stored at server 174, usually in a database or file systems on hard drives of server 174. There may be many terabytes of data that need are to be processed. Taking the stored activity data as input is a build-update graph component (e.g., executable code running on one or more servers or other computers). Build-update graph component 178 can run on the same server that stores the activity data, or may run on a separate server that accesses storage server 174.

In one embodiment, a build-update graph 180 builds or updates a social graph using the collected activity data. The social graph can be stored in one or more databases or file systems. In one embodiment, build-update graph 180 can include three components: (1) identify nodes and edges for social graph that need to be updated, (2) create new nodes/edges if nodes/edges are not found, and (3) update values associated with nodes and edges.

For the incoming activity data collected, identify nodes 182 scan through and find the nodes and edges of the social graph that need to be updated.

When system 32 is processing a user activity data it has the ID of the wearable device 10 user and attributes this activity to that wearable device 10 user.

When a node or edge is found, update values update the node or an edge (e.g., associated with the node). When a node or edge is not found, a new node or edge is created in the graph. The result of build/update graph is a social graph 184 with nodes modeling user profiles and edge modeling sharing activities among users.

FIG. 23 shows a sample social graph 186 where circles 188 represent nodes and lines are edges 190 representing sharing interactions between nodes 182. There can be one or more edges 190 between two nodes 182. Several edges 190 between nodes 182 can indicate sharing activities along several categories: e.g., travel, computers, sports, and others.

Nodes 182 connected together directly have one degree of separation. Nodes 182 connected through one other node have two degrees of separation. Depending on a number of intervening nodes 182 between two nodes 182, this will be a number of degrees of separation between the two nodes 182.

In a specific implementation, edges 190 between nodes 182 indicate sharing activities along several categories such as travel, computers, sports, and the like. For each additional new sharing category, an additional edge 190 is added. In a specific implementation, for each additional new sharing interest category, an additional edge 190 is added. Further, in an implementation, the sharing interaction or edges 190 between the nodes 182 can be weighted (e.g., weighting in a range from 0 to 1), so that certain types of sharing interactions are given different significance. Weight can be used to represent a relative strength of interaction related to a particular interest category.

Some types of sharing activities that are tracked for the social graph (or share graph) include: sending messages between users; sending files between users; sending videos between users; sending an e-mail (e.g., Web e-mail) with a link from one user to another such as sharing a link to various



27

social media sites; and sending instant messages between users. For mobile devices **74** the sharing activities can further include: sending SMS-type messages between users. In some embodiments, messages can be sending from wearable devices **10**.

Once two users connect, such as one wearable device **10** sending another wearable device **10** user a message containing a link concerning a topic. When the recipient user clicks on the link from the sender user, system **32** will add an edge **190** to graph **186** to represent the activity. An edge **190** is added to the graph **186** to represent this sharing activity between the two users.

In a specific implementation, two wearable device **10** users are connected when one user (sender) shares information with another user or group and the other user (recipient) consumes the information that was sent (e.g., clicked-back on the shared link, opened an attachment, opened a message). For example, simply placing a link on Facebook® wall so that all Facebook® “friends” can see this link or tweeting a link to Twitter® followers will not create a connection between the sender, or sharer, and people in the graph. This would create significant noise in the system. The connections are created between the sender and only those users who clicked back on (or otherwise consumed) the message.

In one embodiment, more recently sent messages are given a greater weight than older messages.

The foregoing description of various embodiments of the claimed subject matter has been provided for the purposes of illustration and description. It is not intended to be exhaustive or to limit the claimed subject matter to the precise forms disclosed. Many modifications and variations will be apparent to the practitioner skilled in the art. Particularly, while the concept “component” is used in the embodiments of the systems and methods described above, it will be evident that such concept can be interchangeably used with equivalent concepts such as, class, method, type, interface, module, object model, and other suitable concepts. Embodiments were chosen and described in order to best describe the principles of the invention and its practical application, thereby enabling others skilled in the relevant art to understand the claimed subject matter, the various embodiments and with various modifications that are suited to the particular use contemplated.

What is claimed is:

1. A method for using telemetry data, comprising:  
using a wearable person monitoring device that includes a microphone, an RF transmitter and sensors to determine air quality, sound level, sound quality, light quality and

28

ambient temperature near a person, the RF transmitter serving as a communication system;

using an accelerometer configured to detect a person’s movement information, the accelerometer and the wearable person monitoring device configured to assist to determine a person’s sleep information and a person’s sleep behavior information, the microphone configured to record a person’s movement sounds detected by the accelerometer, the accelerometer configured to cause the microphone to stop recording the person’s movement sounds when the person’s movement sounds are not directed to a sleep related parameter;

analyzing the person’s movement information, the person’s sleep information and the person’s sleep behavior information to calculate or derive sleep onset and wake time, sleep interruptions, and quality and depth of sleep; and

communicating between a telemetry system and the wearable person monitoring device, the telemetry system including a database of the person’s sleep information and the person’s sleep behavior information;

using ID circuitry to crunch information and a control system to orchestrate communication between different systems;

using a noise reduction element at the wearable person monitoring device to reduce signal noise; and

switching between incremental and full syncing of the sleep related parameter.

2. The method of claim 1, further comprising:

using logic resources at the wearable person monitoring device.

3. The method of claim 1, further comprising:

communicating signals from the wearable person monitoring device.

4. The method of claim 1, further comprising:

using a CPU to evaluate the sleep related parameter of the person.

5. The method of claim 1, further comprising:

using the telemetry system to create different classifications for the sleep related parameter of the person.

6. The method of claim 1, further comprising:

providing firmware updates to the wearable person monitoring device.

7. The method of claim 1, wherein streams of information relating to the wearable person monitoring device can include encrypted and non-encrypted information.

\* \* \* \* \*