US009556811B2

(12) **United States Patent**
Wagh et al.

(10) **Patent No.: US 9,556,811 B2**
(45) **Date of Patent: Jan. 31, 2017**

(54) **FIRING PATTERN MANAGEMENT FOR IMPROVED TRANSIENT VIBRATION IN VARIABLE CYLINDER DEACTIVATION MODE**

(71) Applicant: **GM Global Technology Operations LLC**, Detroit, MI (US)

(72) Inventors: **Nitish J. Wagh**, Northville, MI (US); **Randall S. Beikmann**, Brighton, MI (US)

(73) Assignee: **GM Global Technology Operations LLC**, Detroit, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 188 days.

(21) Appl. No.: **14/310,063**

(22) Filed: **Jun. 20, 2014**

(65) **Prior Publication Data**

US 2015/0369140 A1 Dec. 24, 2015

(51) **Int. Cl.**
F02D 41/00 (2006.01)
F02D 17/02 (2006.01)
F02D 13/06 (2006.01)

(52) **U.S. Cl.**
CPC ***F02D 41/0087*** (2013.01); ***F02D 13/06*** (2013.01); ***F02D 17/02*** (2013.01); ***F02D 41/008*** (2013.01)

(58) **Field of Classification Search**
CPC F02D 41/008; F02D 41/0087; F02D 2041/0012; F02D 17/00; F02D 17/02; F02D 13/06; F01D 17/00; F01D 17/02; G01M 15/12
USPC ..... 123/198 DB, 198 DC, 198 F, 481; 701/103–105
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,596,640	A	8/1971	Bloomfield
4,129,034	A	12/1978	Niles et al.
4,172,434	A	10/1979	Coles
4,377,997	A	3/1983	Staerzl

(Continued)

FOREIGN PATENT DOCUMENTS

CN	1573916	A	2/2005
CN	1888407	A	1/2007

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jun. 17, 2015 corresponding to International Application No. PCT/US2015/019496, 14 pages.


(Continued)

Primary Examiner — Lindsay Low
Assistant Examiner — Robert Werner

(57) **ABSTRACT**

A system includes a cylinder control module that determines target numbers of cylinders of an engine to be activated during a period, determines, based on the target numbers and an engine speed, N predetermined sequences for controlling the cylinders of the engine during the period, determines whether a transition parameter is associated with at least one of the N predetermined subsequences and selectively adjusts at least one of the N predetermined subsequences based on the determination of whether a transition parameter is associated with at least two of the N predetermined sequences. The system further includes a cylinder actuator module that, during the period, controls the cylinders of the engine based on the N predetermined sequence and based on the at least one selectively adjusted predetermined sequences.

14 Claims, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

4,434,767	A		3/1984	Kohama et al.
4,489,695	A		12/1984	Kohama et al.
4,509,488	A		4/1985	Forster et al.
4,535,744	A		8/1985	Matsumura
4,770,148	A		9/1988	Hibino et al.
4,887,216	A		12/1989	Ohnari et al.
4,974,563	A		12/1990	Ikeda et al.
4,987,888	A		1/1991	Funabashi et al.
5,042,444	A		8/1991	Hayes et al.
5,094,213	A		3/1992	Dudek et al.
5,226,513	A		7/1993	Shibayama
5,278,760	A		1/1994	Ribbens et al.
5,357,932	A		10/1994	Clinton et al.
5,374,224	A		12/1994	Huffmaster et al.
5,377,631	A		1/1995	Schechter
5,423,208	A		6/1995	Dudek et al.
5,465,617	A		11/1995	Dudek et al.
5,496,227	A		3/1996	Minowa et al.
5,540,633	A		7/1996	Yamanaka et al.
5,553,575	A		9/1996	Beck et al.
5,584,266	A		12/1996	Motose et al.
5,669,354	A		9/1997	Morris
5,692,471	A		12/1997	Zhang
5,720,257	A		2/1998	Motose et al.
5,778,858	A	*	7/1998	Garabedian F02D 41/1443 123/481
5,813,383	A		9/1998	Cummings
5,884,605	A		3/1999	Nagaishi et al.
5,909,720	A		6/1999	Yamaoka et al.
5,931,140	A		8/1999	Maloney
5,934,263	A		8/1999	Russ et al.
5,941,927	A		8/1999	Pfitz
5,974,870	A		11/1999	Treinies et al.
5,975,052	A		11/1999	Moyer
5,983,867	A		11/1999	Stuber et al.
6,125,812	A		10/2000	Garabedian
6,158,411	A		12/2000	Morikawa
6,244,242	B1		6/2001	Grizzle et al.
6,247,449	B1		6/2001	Persson
6,272,427	B1		8/2001	Wild et al.
6,286,366	B1		9/2001	Chen et al.
6,295,500	B1		9/2001	Cullen et al.
6,332,446	B1		12/2001	Matsumoto et al.
6,334,425	B1		1/2002	Nagatani et al.
6,355,986	B1		3/2002	Kato et al.
6,360,724	B1		3/2002	Suhre et al.
6,363,316	B1		3/2002	Soliman et al.
6,371,075	B2		4/2002	Koch
6,385,521	B1		5/2002	Ito
6,408,625	B1		6/2002	Woon et al.
6,520,140	B2		2/2003	Dreymuller et al.
6,546,912	B2		4/2003	Tuken
6,588,261	B1		7/2003	Wild et al.
6,619,258	B2		9/2003	McKay et al.
6,622,548	B1		9/2003	Hernandez
6,694,806	B2		2/2004	Kumagai et al.
6,738,707	B2		5/2004	Kotwicki et al.
6,754,577	B2		6/2004	Gross et al.
6,760,656	B2		7/2004	Matthews et al.
6,850,831	B2		2/2005	Buckland et al.
6,909,961	B2		6/2005	Wild et al.
6,978,204	B2		12/2005	Surnilla et al.
6,980,902	B2		12/2005	Nakazawa
6,981,492	B2		1/2006	Barba et al.
6,983,737	B2		1/2006	Gross et al.
7,003,390	B2		2/2006	Kaga
7,024,301	B1		4/2006	Kar et al.
7,025,041	B2		4/2006	Abe et al.
7,028,661	B1		4/2006	Bonne et al.
7,032,545	B2		4/2006	Lewis et al.
7,032,581	B2		4/2006	Gibson et al.
7,044,101	B1		5/2006	Duty et al.
7,063,062	B2		6/2006	Lewis et al.
7,066,121	B2		6/2006	Michelini et al.
7,066,136	B2		6/2006	Ogiso
7,069,718	B2		7/2006	Surnilla et al.
7,069,773	B2		7/2006	Stempnik et al.
7,086,386	B2		8/2006	Doering
7,100,720	B2		9/2006	Ishikawa
7,111,612	B2		9/2006	Michelini et al.
7,140,355	B2		11/2006	Michelini et al.
7,159,568	B1		1/2007	Lewis et al.
7,174,713	B2		2/2007	Nitzke et al.
7,174,879	B1		2/2007	Chol et al.
7,200,486	B2		4/2007	Tanaka et al.
7,203,588	B2		4/2007	Kaneko et al.
7,231,907	B2		6/2007	Bolander et al.
7,278,391	B1		10/2007	Wong et al.
7,292,231	B2		11/2007	Kodama et al.
7,292,931	B2		11/2007	Davis et al.
7,319,929	B1		1/2008	Davis et al.
7,363,111	B2		4/2008	Vian et al.
7,367,318	B2		5/2008	Moriya et al.
7,415,345	B2		8/2008	Wild
7,440,838	B2		10/2008	Livshiz et al.
7,464,676	B2		12/2008	Wiggins et al.
7,472,014	B1		12/2008	Albertson et al.
7,497,074	B2		3/2009	Surnilla et al.
7,499,791	B2		3/2009	You et al.
7,503,312	B2		3/2009	Surnilla et al.
7,509,201	B2		3/2009	Bolander et al.
7,555,896	B2		7/2009	Lewis et al.
7,577,511	B1		8/2009	Tripathi et al.
7,581,531	B2		9/2009	Schulz
7,614,384	B2		11/2009	Livshiz et al.
7,620,188	B2		11/2009	Inoue et al.
7,621,262	B2		11/2009	Zubeck
7,634,349	B2		12/2009	Senft et al.
7,685,976	B2		3/2010	Marriott
7,785,230	B2		8/2010	Gibson et al.
7,836,866	B2		11/2010	Luken et al.
7,849,835	B2		12/2010	Tripathi et al.
7,886,715	B2		2/2011	Tripathi et al.
7,930,087	B2		4/2011	Gibson et al.
7,946,263	B2		5/2011	O'Neill et al.
7,954,474	B2		6/2011	Tripathi et al.
8,050,841	B2		11/2011	Costin et al.
8,099,224	B2		1/2012	Tripathi et al.
8,108,132	B2		1/2012	Reinke
8,131,445	B2		3/2012	Tripathi et al.
8,131,447	B2		3/2012	Tripathi et al.
8,135,410	B2		3/2012	Forte
8,145,410	B2		3/2012	Berger et al.
8,146,565	B2		4/2012	Leone et al.
8,272,367	B2		9/2012	Shikama et al.
8,347,856	B2		1/2013	Leone et al.
8,402,942	B2	*	3/2013	Tripathi ..... F02D 41/0087 123/198 F
8,473,179	B2		6/2013	Whitney et al.
8,616,181	B2		12/2013	Sahandiesfanjani et al.
8,646,430	B2		2/2014	Kinoshita
8,646,435	B2	*	2/2014	Dibble ..... F02D 41/0087 123/198 DB
8,701,628	B2		4/2014	Tripathi et al.
8,706,383	B2		4/2014	Sauve et al.
8,833,058	B2		9/2014	Ervin et al.
8,833,345	B2		9/2014	Pochner et al.
8,869,773	B2		10/2014	Tripathi et al.
8,979,708	B2		3/2015	Burtch
9,020,735	B2	*	4/2015	Tripathi F02D 41/0087 701/102
9,140,622	B2		9/2015	Beikmann
9,200,575	B2	*	12/2015	Shost F02D 17/02
9,212,610	B2	*	12/2015	Chen F02D 41/0082
9,222,427	B2		12/2015	Matthews et al.
2001/0007964	A1		7/2001	Poljansek et al.
2002/0038654	A1		4/2002	Sasaki et al.
2002/0039950	A1		4/2002	Graf et al.
2002/0156568	A1		10/2002	Knott et al.
2002/0162540	A1		11/2002	Matthews et al.
2002/0189574	A1		12/2002	Kim
2003/0116130	A1		6/2003	Kisaka et al.
2003/0123467	A1		7/2003	Du et al.
2003/0131820	A1		7/2003	Mckay et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2003/0172900	A1	9/2003	Boyer et al.
2004/0007211	A1	1/2004	Kobayashi
2004/0034460	A1	2/2004	Folkerts et al.
2004/0069290	A1	4/2004	Bucktron et al.
2004/0122584	A1	6/2004	Muto et al.
2004/0129249	A1	7/2004	Kondo
2004/0138027	A1	7/2004	Rustige et al.
2004/0206072	A1	10/2004	Surnilla et al.
2004/0258251	A1	12/2004	Inoue et al.
2005/0016492	A1	1/2005	Matthews
2005/0056250	A1	3/2005	Stroh
2005/0098156	A1	5/2005	Ohtani
2005/0131618	A1	6/2005	Megli et al.
2005/0197761	A1	9/2005	Bidner et al.
2005/0199220	A1	9/2005	Ogiso
2005/0204726	A1	9/2005	Lewis
2005/0204727	A1	9/2005	Lewis et al.
2005/0205028	A1	9/2005	Lewis et al.
2005/0205045	A1	9/2005	Michelini et al.
2005/0205060	A1	9/2005	Michelini et al.
2005/0205063	A1	9/2005	Kolmanovsky et al.
2005/0205069	A1	9/2005	Lewis et al.
2005/0205074	A1	9/2005	Gibson et al.
2005/0235743	A1	10/2005	Stempnik et al.
2006/0107919	A1	5/2006	Nishi et al.
2006/0112918	A1	6/2006	Persson
2006/0130814	A1	6/2006	Bolander et al.
2006/0178802	A1	8/2006	Bolander et al.
2007/0012040	A1	1/2007	Nitzke et al.
2007/0042861	A1	2/2007	Takaoka et al.
2007/0051351	A1	3/2007	Pallett et al.
2007/0100534	A1	5/2007	Katsumata
2007/0101969	A1	5/2007	Lay et al.
2007/0107692	A1	5/2007	Kuo et al.
2007/0131169	A1	6/2007	Ahn
2007/0131196	A1	6/2007	Gibson et al.
2007/0135988	A1	6/2007	Kidston et al.
2007/0235005	A1	10/2007	Lewis
2008/0000149	A1	1/2008	Aradi
2008/0041327	A1	2/2008	Lewis et al.
2008/0066699	A1	3/2008	Michelini et al.
2008/0098969	A1	5/2008	Reed et al.
2008/0109151	A1	5/2008	Jaros et al.
2008/0121211	A1	5/2008	Livshiz et al.
2008/0154468	A1	6/2008	Berger et al.
2008/0254926	A1	10/2008	Schuseil et al.
2008/0262698	A1	10/2008	Lahti et al.
2008/0288146	A1	11/2008	Beechie et al.
2009/0007877	A1	1/2009	Raiford
2009/0013667	A1	1/2009	Winstead
2009/0013668	A1	1/2009	Winstead
2009/0013669	A1	1/2009	Winstead
2009/0013969	A1	1/2009	Winstead
2009/0018746	A1	1/2009	Miller et al.
2009/0030594	A1	1/2009	You et al.
2009/0042458	A1	2/2009	Kinoshita
2009/0042463	A1	2/2009	Kinoshita
2009/0118914	A1	5/2009	Schwenke et al.
2009/0118965	A1	5/2009	Livshiz et al.
2009/0118968	A1	5/2009	Livshiz et al.
2009/0118975	A1	5/2009	Murakami et al.
2009/0118986	A1	5/2009	Kita
2009/0177371	A1	7/2009	Reinke
2009/0204312	A1	8/2009	Moriya
2009/0229562	A1	9/2009	Ramappan et al.
2009/0241872	A1	10/2009	Wang et al.
2009/0248277	A1	10/2009	Shinagawa et al.
2009/0248278	A1	10/2009	Nakasaka
2009/0292435	A1	11/2009	Costin et al.
2010/0006065	A1	1/2010	Tripathi et al.
2010/0010724	A1	1/2010	Tripathi et al.
2010/0012072	A1	1/2010	Leone et al.
2010/0030447	A1	2/2010	Smyth et al.
2010/0036571	A1	2/2010	Han et al.
2010/0042308	A1	2/2010	Kobayashi et al.
2010/0050993	A1	3/2010	Zhao et al.
2010/0057283	A1	3/2010	Worthing et al.
2010/0059004	A1	3/2010	Gill
2010/0100299	A1	4/2010	Tripathi et al.
2010/0107630	A1	5/2010	Hamama et al.
2010/0211299	A1	8/2010	Lewis et al.
2010/0222989	A1	9/2010	Nishimura
2010/0282202	A1	11/2010	Luken
2010/0318275	A1	12/2010	Borchsenius et al.
2011/0005496	A1	1/2011	Hiraya et al.
2011/0030657	A1	2/2011	Tripathi et al.
2011/0048372	A1	3/2011	Dibble et al.
2011/0088661	A1	4/2011	Sczomak et al.
2011/0094475	A1	4/2011	Riegel et al.
2011/0107986	A1	5/2011	Winstead
2011/0118955	A1	5/2011	Livshiz et al.
2011/0144883	A1	6/2011	Rollinger et al.
2011/0178693	A1	7/2011	Chang et al.
2011/0208405	A1	8/2011	Tripathi et al.
2011/0213526	A1	9/2011	Giles et al.
2011/0213540	A1	9/2011	Tripathi et al.
2011/0213541	A1	9/2011	Tripathi et al.
2011/0251773	A1	10/2011	Sahandiesfanjani et al.
2011/0264342	A1	10/2011	Baur et al.
2011/0265454	A1	11/2011	Smith et al.
2011/0265771	A1	11/2011	Banker et al.
2011/0295483	A1	12/2011	Ma et al.
2011/0313643	A1	12/2011	Lucatello et al.
2012/0029787	A1	2/2012	Whitney et al.
2012/0055444	A1	3/2012	Tobergte et al.
2012/0103312	A1	5/2012	Sasai et al.
2012/0109495	A1	5/2012	Tripathi et al.
2012/0116647	A1	5/2012	Pochner et al.
2012/0143471	A1	6/2012	Tripathi et al.
2012/0180759	A1	7/2012	Whitney et al.
2012/0221217	A1	8/2012	Sujan et al.
2012/0285161	A1	11/2012	Kerns et al.
2013/0092127	A1	4/2013	Pirjaberi et al.
2013/0092128	A1	4/2013	Pirjaberi et al.
2013/0184949	A1	7/2013	Saito et al.
2013/0289853	A1	10/2013	Serrano
2014/0041625	A1	2/2014	Pirjaberi et al.
2014/0041641	A1	2/2014	Carlson et al.
2014/0053802	A1	2/2014	Rayl
2014/0053803	A1	2/2014	Rayl
2014/0053804	A1	2/2014	Rayl et al.
2014/0053805	A1	2/2014	Brennan et al.
2014/0069178	A1	3/2014	Beikmann
2014/0069374	A1	3/2014	Matthews
2014/0069375	A1	3/2014	Matthews et al.
2014/0069376	A1	3/2014	Matthews et al.
2014/0069377	A1	3/2014	Brennan et al.
2014/0069378	A1	3/2014	Burleigh et al.
2014/0069379	A1	3/2014	Beikmann
2014/0069381	A1	3/2014	Beikmann
2014/0090623	A1*	4/2014	Beikmann F02D 41/0087 123/350
2014/0090624	A1	4/2014	Verner
2014/0102411	A1	4/2014	Brennan
2014/0190448	A1	7/2014	Brennan et al.
2014/0190449	A1	7/2014	Phillips
2014/0194247	A1	7/2014	Burtch
2014/0207359	A1	7/2014	Phillips
2015/0240671	A1	8/2015	Nakamura
2015/0260112	A1	9/2015	Liu et al.
2015/0260117	A1	9/2015	Shost et al.
2015/0354470	A1	12/2015	Li et al.
2015/0361907	A1	12/2015	Hayman et al.

FOREIGN PATENT DOCUMENTS

CN	101220780	A	7/2008
CN	101353992	A	1/2009
CN	101476507	A	7/2009
CN	101586504	A	11/2009
CN	102454493	A	5/2012
EP	1489595	A2	12/2004
JP	2010223019	A	10/2010
JP	2011149352	A	8/2011

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

OTHER PUBLICATIONS

U.S. Appl. No. 13/798,384, filed Mar. 13, 2013, Burtch.
U.S. Appl. No. 13/798,518, filed Mar. 13, 2013, Beikmann.
U.S. Appl. No. 13/798,624, filed Mar. 13, 2013, Brennan et al.
U.S. Appl. No. 13/799,181, filed Mar. 13, 2013, Beikmann.
U.S. Appl. No. 61/952,737, filed Mar. 13, 2014, Shost et al.
Glossary of Judicial Claim Constructions in the Electronics, Computer and Business Method Arts. Public Patent Foundation. (2010).
U.S. Appl. No. 13/798,351, filed Mar. 13, 2013, Rayl.
U.S. Appl. No. 13/798,400, filed Mar. 13, 2013, Phillips.
U.S. Appl. No. 13/798,435, filed Mar. 13, 2013, Matthews.
U.S. Appl. No. 13/798,451, filed Mar. 13, 2013, Rayl.
U.S. Appl. No. 13/798,471, filed Mar. 13, 2013, Matthews et al.
U.S. Appl. No. 13/798,536, filed Mar. 13, 2013, Matthews et al.
U.S. Appl. No. 13/798,540, filed Mar. 13, 2013, Brennan et al.
U.S. Appl. No. 13/798,574, filed Mar. 13, 2013, Verner.
U.S. Appl. No. 13/798,586, filed Mar. 13, 2013, Rayl et al.
U.S. Appl. No. 13/798,590, filed Mar. 13, 2013, Brennan et al.
U.S. Appl. No. 13/798,701, filed Mar. 13, 2013, Burleigh et al.
U.S. Appl. No. 13/798,737, filed Mar. 13, 2013, Beikmann.
U.S. Appl. No. 13/798,775, filed Mar. 13, 2013, Phillips.
U.S. Appl. No. 13/799,116, filed Mar. 13, 2013, Brennan.
U.S. Appl. No. 13/799,129, filed Mar. 13, 2013, Beikmann.
U.S. Appl. No. 14/143,267, filed Dec. 30, 2013, Gehringer et al.
U.S. Appl. No. 14/211,389, filed Mar. 14, 2014, Liu et al.
U.S. Appl. No. 14/300,469, filed Jun. 10, 2014, Li et al.
U.S. Appl. No. 14/449,726, filed Aug. 1, 2014, Hayman et al.
U.S. Appl. No. 14/548,501, filed Nov. 20, 2014, Beikmann et al.
U.S. Appl. No. 14/638,908, filed Mar. 4, 2015, Shost et al.
U.S. Appl. No. 14/734,619, filed Jun. 9, 2015, Matthews.

* cited by examiner



Electric Motor
198
Hybrid Control Module
196
Transmission Control Module
194
Driver Input Module
104
Driver Input
Other Sensors
193
100
Engine Control Module
114
Boost Actuator Module
164
EGR Actuator Module
172
Phaser Actuator Module
158
Spark Actuator Module
126
Cylinder Actuator Module
120
Throttle Actuator Module
116
Fuel Actuator Module
124
Intake Phaser
102
Exhaust Phaser
148
150
140
142
122
130
128
118
Crankshaft Position
180
ECT
182
MAP
184
TPS
190
112
MAF
186
IAT
192
Air
Wastegate
EGR
Exhaust
134
162
Turbo (Hot)
160-1
170
110
Turbo (Cold)
160-2
108

FIG. 1



Engine Control Module
114
Fuel Control Module
236
232
Boost Control Module
242
240
Throttle Control Module
220
216
Spark Control Module
228
224
Phaser Control Module
237
124
164
116
126
238
158
239
120
Activation/Deactivation Sequence
248
Cylinder Control Module
244
Throttle
320
Crankshaft Position
328
Engine Speed Module
324
Engine Speed
316
Driver Input
212
Torque Request Module
204
Torque Request
208

FIG. 2



248
Activation/Deactivation Sequence
Second Sequence Setting Module
Subsequence Database
344
340
Subsequence Sequence
336
244
Cylinder Control Module
Subsequence Setting Module
332
Activated Cylinder Sequence
312
First Sequence Setting Module
Activated Cylinder Sequence Database
310
348
Target ECC
308
Target Cylinder Count Module
304
Throttle
320
Engine Speed
316
Torque Request
208

FIG. 3



Start
404
Enabling Condition(s) Satisfied?
N
Y
408
Generate Target ECC
412
Generate Activated Cylinder Sequence
416
Generate Subsequence Sequence
420
Retrieve Predetermined Cylinder Activation/ Deactivation Subsequences
424
Apply Transition Parameters?
N
Y
428
Adjusted Subsequences Based On Transition Parameters
432
Generate Target Sequence From Predetermined Cylinder Activation/ Deactivation Sequences
436
Control Engine Based On Target Activation/ Deactivation Sequence
End

FIG. 4

FIRING PATTERN MANAGEMENT FOR IMPROVED TRANSIENT VIBRATION IN VARIABLE CYLINDER DEACTIVATION MODE

FIELD

The present disclosure relates to internal combustion engines and more specifically to engine control systems and methods.

BACKGROUND

The background description provided herein is for the purpose of generally presenting the context of the disclosure. Work of the presently named inventors, to the extent it is described in this background section, as well as aspects of the description that may not otherwise qualify as prior art at the time of filing, are neither expressly nor impliedly admitted as prior art against the present disclosure.

Internal combustion engines combust an air and fuel mixture within cylinders to drive pistons, which produces drive torque. In some types of engines, air flow into the engine may be regulated via a throttle. The throttle may adjust throttle area, which increases or decreases air flow into the engine. As the throttle area increases, the air flow into the engine increases. A fuel control system adjusts the rate that fuel is injected to provide a desired air/fuel mixture to the cylinders and/or to achieve a desired torque output. Increasing the amount of air and fuel provided to the cylinders increases the torque output of the engine.

Under some circumstances, one or more cylinders of an engine may be deactivated. Deactivation of a cylinder may include deactivating opening and closing of intake valves of the cylinder and halting fueling of the cylinder. One or more cylinders may be deactivated, for example, to decrease fuel consumption when the engine can produce a requested amount of torque while the one or more cylinders are deactivated.

SUMMARY

A system includes a cylinder control module that determines target numbers of cylinders of an engine to be activated during a period, determines, based on the target numbers and an engine speed, N predetermined sequences for controlling the cylinders of the engine during the period, determines whether a transition parameter is associated with at least one of the N predetermined subsequences and selectively adjusts at least one of the N predetermined subsequences based on the determination of whether a transition parameter is associated with at least two of the N predetermined subsequences. The system further includes a cylinder actuator module that, during the period, controls the cylinders of the engine based on the N predetermined subsequences and based on the at least one selectively adjusted predetermined subsequences.

In other features, cylinder control method includes: determining target numbers of cylinders of an engine to be activated during a period, determining, based on the target numbers and an engine speed, N predetermined subsequences for controlling cylinders of the engine during the period, determining whether a transition parameter is associated with at least one transition between two of the N predetermine subsequences, selectively adjusting at least one of the N predetermine sequences based on the determination a transition parameter is associated with at least two of the N predetermine sequences s, and controlling, during the period, the cylinders of the engine based on the N predetermined sequences.

Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure will become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. **1** is a functional block diagram of an example engine system according to the present disclosure;

FIG. **2** is a functional block diagram of an example engine control system according to the present disclosure;

FIG. **3** is a functional block diagram of an example cylinder control module according to the present disclosure; and

FIG. **4** is a flowchart depicting an example method of controlling cylinder activation and deactivation according to the present disclosure.

DETAILED DESCRIPTION

Internal combustion engines combust an air and fuel mixture within cylinders to generate torque. Under some circumstances, an engine control module (ECM) may deactivate one or more cylinders of the engine. The ECM may deactivate one or more cylinders, for example, to decrease fuel consumption when the engine can produce a requested amount of torque while the one or more cylinders are deactivated. Deactivation of one or more cylinders, however, may increase powertrain-induced vibration relative to the activation of all of the cylinders.

The ECM of the present disclosure determines an average number of cylinders per sub-period to be activated during a future period including a plurality of sub-periods. Based on achieving the average number of cylinders over the future period, the ECM generates a first sequence indicating N target numbers of cylinders to be activated during the each of the plurality of sub-periods, respectively. N is an integer greater than or equal to 1. The ECM generates a second sequence indicating one or more predetermined subsequences for activating and deactivating cylinders to achieve the N target numbers of activated cylinders during each of the sub-periods, respectively. The predetermined subsequences are selected to smooth torque production and delivery, minimize harmonic vehicle vibration, minimize impulsive vibration characteristics, and minimize induction and exhaust noise.

The ECM generates a target sequence for activating and deactivating cylinders of the engine during the future period based on the predetermined subsequences. The cylinders are activated and deactivated based on the target sequence during the future period. More specifically, the cylinders are activated and deactivated based on the predetermined subsequences during each of the sub-periods, respectively. In some instances, the ECM may adjust one or more of the selected subsequences in order to reduce vibration during transition between one or more of the selected subsequences. Deactivation of a cylinder may include deactivating opening and closing of intake valves of the cylinder and halting fueling of the cylinder.

Referring now to FIG. **1**, a functional block diagram of an example engine system **100** is presented. The engine system **100** of a vehicle includes an engine **102** that combusts an air/fuel mixture to produce torque based on driver input from a driver input module **104**. Air is drawn into the engine **102** through an intake system **108**. The intake system **108** may include an intake manifold **110** and a throttle valve **112**. For example only, the throttle valve **112** may include a butterfly valve having a rotatable blade. An engine control module (ECM) **114** controls a throttle actuator module **116**, and the throttle actuator module **116** regulates opening of the throttle valve **112** to control airflow into the intake manifold **110**.

Air from the intake manifold **110** is drawn into cylinders of the engine **102**. While the engine **102** includes multiple cylinders, for illustration purposes a single representative cylinder **118** is shown. For example only, the engine **102** may include 2, 3, 4, 5, 6, 8, 10, and/or 12 cylinders. The ECM **114** may instruct a cylinder actuator module **120** to selectively deactivate some of the cylinders under some circumstances, as discussed further below, which may improve fuel efficiency.

The engine **102** may operate using a four-stroke cycle. The four strokes, described below, will be referred to as the intake stroke, the compression stroke, the combustion stroke, and the exhaust stroke. During each revolution of a crankshaft (not shown), two of the four strokes occur within the cylinder **118**. Therefore, two crankshaft revolutions are necessary for the cylinder **118** to experience all four of the strokes. For four-stroke engines, one engine cycle may correspond to two crankshaft revolutions.

When the cylinder **118** is activated, air from the intake manifold **110** is drawn into the cylinder **118** through an intake valve **122** during the intake stroke. The ECM **114** controls a fuel actuator module **124**, which regulates fuel injection to achieve a desired air/fuel ratio. Fuel may be injected into the intake manifold **110** at a central location or at multiple locations, such as near the intake valve **122** of each of the cylinders. In various implementations (not shown), fuel may be injected directly into the cylinders or into mixing chambers/ports associated with the cylinders. The fuel actuator module **124** may halt injection of fuel to cylinders that are deactivated.

The injected fuel mixes with air and creates an air/fuel mixture in the cylinder **118**. During the compression stroke, a piston (not shown) within the cylinder **118** compresses the air/fuel mixture. The engine **102** may be a compression-ignition engine, in which case compression causes ignition of the air/fuel mixture. Alternatively, the engine **102** may be a spark-ignition engine, in which case a spark actuator module **126** energizes a spark plug **128** in the cylinder **118** based on a signal from the ECM **114**, which ignites the air/fuel mixture. Some types of engines, such as homogenous charge compression ignition (HCCI) engines may perform both compression ignition and spark ignition. The timing of the spark may be specified relative to the time when the piston is at its topmost position, which will be referred to as top dead center (TDC).

The spark actuator module **126** may be controlled by a timing signal specifying how far before or after TDC to generate the spark. Because piston position is directly related to crankshaft rotation, operation of the spark actuator module **126** may be synchronized with the position of the crankshaft. The spark actuator module **126** may halt provision of spark to deactivated cylinders or provide spark to deactivated cylinders.

During the combustion stroke, the combustion of the air/fuel mixture drives the piston down, thereby driving the crankshaft. The combustion stroke may be defined as the time between the piston reaching TDC and the time at which the piston returns to a bottom most position, which will be referred to as bottom dead center (BDC).

During the exhaust stroke, the piston begins moving up from BDC and expels the byproducts of combustion through an exhaust valve **130**. The byproducts of combustion are exhausted from the vehicle via an exhaust system **134**.

The intake valve **122** may be controlled by an intake camshaft **140**, while the exhaust valve **130** may be controlled by an exhaust camshaft **142**. In various implementations, multiple intake camshafts (including the intake camshaft **140**) may control multiple intake valves (including the intake valve **122**) for the cylinder **118** and/or may control the intake valves (including the intake valve **122**) of multiple banks of cylinders (including the cylinder **118**). Similarly, multiple exhaust camshafts (including the exhaust camshaft **142**) may control multiple exhaust valves for the cylinder **118** and/or may control exhaust valves (including the exhaust valve **130**) for multiple banks of cylinders (including the cylinder **118**). While camshaft based valve actuation is shown and has been discussed, camless valve actuators may be implemented.

The cylinder actuator module **120** may deactivate the cylinder **118** by disabling opening of the intake valve **122** and/or the exhaust valve **130**. The time at which the intake valve **122** is opened may be varied with respect to piston TDC by an intake cam phaser **148**. The time at which the exhaust valve **130** is opened may be varied with respect to piston TDC by an exhaust cam phaser **150**. A phaser actuator module **158** may control the intake cam phaser **148** and the exhaust cam phaser **150** based on signals from the ECM **114**. When implemented, variable valve lift (not shown) may also be controlled by the phaser actuator module **158**. In various other implementations, the intake valve **122** and/or the exhaust valve **130** may be controlled by actuators other than a camshaft, such as electromechanical actuators, electrohydraulic actuators, electromagnetic actuators, etc.

The engine system **100** may include a boost device that provides pressurized air to the intake manifold **110**. For example, FIG. **1** shows a turbocharger including a turbine **160-1** that is driven by exhaust gases flowing through the exhaust system **134**. The turbocharger also includes a compressor **160-2** that is driven by the turbine **160-1** and that compresses air leading into the throttle valve **112**. In various implementations, a supercharger (not shown), driven by the crankshaft, may compress air from the throttle valve **112** and deliver the compressed air to the intake manifold **110**.

A wastegate **162** may allow exhaust to bypass the turbine **160-1**, thereby reducing the boost (the amount of intake air compression) of the turbocharger. The ECM **114** may control the turbocharger via a boost actuator module **164**. The boost actuator module **164** may modulate the boost of the turbocharger by controlling the position of the wastegate **162**. In various implementations, multiple turbochargers may be controlled by the boost actuator module **164**. The turbocharger may have variable geometry, which may be controlled by the boost actuator module **164**.

An intercooler (not shown) may dissipate some of the heat contained in the compressed air charge, which is generated as the air is compressed. Although shown separated for purposes of illustration, the turbine **160-1** and the compressor **160-2** may be mechanically linked to each other, placing

intake air in close proximity to hot exhaust. The compressed air charge may absorb heat from components of the exhaust system **134**.

The engine system **100** may include an exhaust gas recirculation (EGR) valve **170**, which selectively redirects exhaust gas back to the intake manifold **110**. The EGR valve **170** may be located upstream of the turbocharger's turbine **160-1**. The EGR valve **170** may be controlled by an EGR actuator module **172**.

Crankshaft position may be measured using a crankshaft position sensor **180**. A temperature of engine coolant may be measured using an engine coolant temperature (ECT) sensor **182**. The ECT sensor **182** may be located within the engine **102** or at other locations where the coolant is circulated, such as a radiator (not shown).

A pressure within the intake manifold **110** may be measured using a manifold absolute pressure (MAP) sensor **184**. In various implementations, engine vacuum, which is the difference between ambient air pressure and the pressure within the intake manifold **110**, may be measured. A mass flow rate of air flowing into the intake manifold **110** may be measured using a mass air flow (MAF) sensor **186**. In various implementations, the MAF sensor **186** may be located in a housing that also includes the throttle valve **112**.

Position of the throttle valve **112** may be measured using one or more throttle position sensors (TPS) **190**. A temperature of air being drawn into the engine **102** may be measured using an intake air temperature (IAT) sensor **192**. The engine system **100** may also include one or more other sensors **193**. The ECM **114** may use signals from the sensors to make control decisions for the engine system **100**.

The ECM **114** may communicate with a transmission control module **194** to coordinate shifting gears in a transmission (not shown). For example, the ECM **114** may reduce engine torque during a gear shift. The engine **102** outputs torque to a transmission (not shown) via the crankshaft. One or more coupling devices, such as a torque converter and/or one or more clutches, regulate torque transfer between a transmission input shaft and the crankshaft. Torque is transferred between the transmission input shaft and a transmission output shaft via the gears.

Torque is transferred between the transmission output shaft and wheels of the vehicle via one or more differentials, driveshafts, etc. Wheels that receive torque output by the transmission may be referred to as driven wheels. Wheels that do not receive torque from the transmission may be referred to as undriven wheels.

The ECM **114** may communicate with a hybrid control module **196** to coordinate operation of the engine **102** and an electric motor **198**. The electric motor **198** may also function as a generator, and may be used to produce electrical energy for use by vehicle electrical systems and/or for storage in a battery. While only the electric motor **198** is shown and discussed, multiple electric motors may be implemented. In various implementations, various functions of the ECM **114**, the transmission control module **194**, and the hybrid control module **196** may be integrated into one or more modules.

Each system that varies an engine parameter may be referred to as an engine actuator. Each engine actuator has an associated actuator value. For example, the throttle actuator module **116** may be referred to as an engine actuator, and the throttle opening area may be referred to as the actuator value. In the example of FIG. **1**, the throttle actuator module **116** achieves the throttle opening area by adjusting an angle of the blade of the throttle valve **112**.

The spark actuator module **126** may also be referred to as an engine actuator, while the corresponding actuator value may be the amount of spark advance relative to cylinder TDC. Other engine actuators may include the cylinder actuator module **120**, the fuel actuator module **124**, the phaser actuator module **158**, the boost actuator module **164**, and the EGR actuator module **172**. For these engine actuators, the actuator values may correspond to a cylinder activation/deactivation sequence, fueling rate, intake and exhaust cam phaser angles, boost pressure, and EGR valve opening area, respectively. The ECM **114** may control the actuator values in order to cause the engine **102** to generate a desired engine output torque.

Referring now to FIG. **2**, a functional block diagram of an example engine control system is presented. A torque request module **204** may determine a torque request **208** based on one or more driver inputs **212**, such as an accelerator pedal position, a brake pedal position, a cruise control input, and/or one or more other suitable driver inputs. The torque request module **204** may determine the torque request **208** additionally or alternatively based on one or more other torque requests, such as torque requests generated by the ECM **114** and/or torque requests received from other modules of the vehicle, such as the transmission control module **194**, the hybrid control module **196**, a chassis control module, etc.

One or more engine actuators may be controlled based on the torque request **208** and/or one or more other parameters. For example, a throttle control module **216** may determine a target throttle opening **220** based on the torque request **208**. The throttle actuator module **116** may adjust opening of the throttle valve **112** based on the target throttle opening **220**.

A spark control module **224** may determine a target spark timing **228** based on the torque request **208**. The spark actuator module **126** may generate spark based on the target spark timing **228**. A fuel control module **232** may determine one or more target fueling parameters **236** based on the torque request **208**. For example, the target fueling parameters **236** may include fuel injection amount, number of fuel injections for injecting the amount, and timing for each of the injections. The fuel actuator module **124** may inject fuel based on the target fueling parameters **236**.

A phaser control module **237** may determine target intake and exhaust cam phaser angles **238** and **239** based on the torque request **208**. The phaser actuator module **158** may regulate the intake and exhaust cam phasers **148** and **150** based on the target intake and exhaust cam phaser angles **238** and **239**, respectively. A boost control module **240** may determine a target boost **242** based on the torque request **208**. The boost actuator module **164** may control boost output by the boost device(s) based on the target boost **242**.

A cylinder control module **244** (see also FIG. **3**) determines a target cylinder activation/deactivation sequence **248** based on the torque request **208**. The cylinder actuator module **120** deactivates the intake and exhaust valves of the cylinders that are to be deactivated according to the target cylinder activation/deactivation sequence **248**. The cylinder actuator module **120** allows opening and closing of the intake and exhaust valves of cylinders that are to be activated according to the target cylinder activation/deactivation sequence **248**.

Fueling is halted (zero fueling) to cylinders that are to be deactivated according to the target cylinder activation/deactivation sequence **248**, and fuel is provided the cylinders that are to be activated according to the target cylinder activation/deactivation sequence **248**. Spark is provided to the cylinders that are to be activated according to the target cylinder activation/deactivation sequence **248**. Spark may be provided or halted to cylinders that are to be deactivated

according to the target cylinder activation/deactivation sequence **248**. Cylinder deactivation is different than fuel cutoff (e.g., deceleration fuel cutoff) in that the intake and exhaust valves of cylinders to which fueling is halted during fuel cutoff are still opened and closed during the fuel cutoff whereas the intake and exhaust valves are maintained closed when deactivated.

Referring now to FIG. **3**, a functional block diagram of an example implementation of the cylinder control module **244** is presented. A target cylinder count module **304** generates a target effective cylinder count (ECC) **308**. The target ECC **308** corresponds to a target number of cylinders to be activated (i.e., fired) per engine cycle on average over the next P engine cycles (corresponding to the next M possible cylinder events in a predetermined firing order of the cylinders). Where P is an integer greater than or equal to two. One engine cycle may refer to the period for each of the cylinders of the engine **102** to accomplish one combustion cycle. For example, in a four-stroke engine, one engine cycle may correspond to two crankshaft revolutions.

The target ECC **308** may be an integer or a non-integer that is between zero and the total number of possible cylinder events per engine cycle, inclusive. Cylinder events include cylinder firing events and events where deactivated cylinders would, if activated, be fired. While the example where P is equal to 10 is discussed below, P is an integer greater than or equal to two. While engine cycles and the next P engine cycles will be discussed, another suitable period (e.g., the next N sets of X number of cylinder events) may be used.

The target cylinder count module **304** generates the target ECC **308** based on the torque request **208**. The target cylinder count module **304** may determine the target ECC **308**, for example, using a function or a mapping that relates the torque request **208** to the target ECC **308**. For example only, for a torque request that is approximately 50% of a maximum torque output of the engine **102** under the operating conditions, the target ECC **308** may be a value corresponding to approximately half of the total number of cylinders of the engine **102**. The target cylinder count module **304** may generate the target ECC **308** further based on one or more other parameters, such as one or more loads on the engine **102** and/or one or more other suitable parameters.

In some implementations, the target cylinder count module **304** determines whether the torque request **208** is within one of a plurality of predetermined torque request ranges. For example, a first torque request range includes a first lower torque value and a first upper torque value. The target cylinder count module **304** determines whether the torque request **208** is between the first lower torque value and the first upper torque value (i.e., greater than the first lower torque value and less than the first upper torque value). When the target cylinder count module **304** determines the torque request value is between the first lower torque value and the first upper torque value, the target cylinder count module **304** determines the target ECC **308** corresponding to the first torque request range.

It is understood that each of the plurality of torque request ranges may correspond to a target ECC. For example, the first torque request range corresponds to a first target ECC, while a second torque request range corresponds to a second target ECC. During a calibration phase of the vehicle, torque request ranges are identified corresponding to various operating parameters of the vehicle. Similarly, target ECCs corresponding to each torque request range are identified. The target cylinder count module **304** determines a torque request range that the torque request **208** falls within. The target cylinder count module **304** determines the target ECC that corresponds to the torque request range and sets the target ECC **308** equal to the target ECC corresponding to the torque request range. In this manner, the torque request **208** may vary within a range of values while the target ECC **308** remains steady.

A first sequence setting module **310** generates an activated cylinder sequence **312** to achieve the target ECC **308** over the next P engine cycles. The first sequence setting module **310** may determine the activated cylinder sequence **312**, for example, using a mapping that relates the target ECC **308** to the activated cylinder sequence **312**.

The activated cylinder sequence **312** includes a sequence of integers that correspond to the number of cylinders that should be activated during the next P engine cycles, respectively. In this manner, the activated cylinder sequence **312** indicates how many cylinders should be activated during each of the next P engine cycles. For example, the activated cylinder sequence **312** may include an array including P integers for the next P engine cycles, respectively, such as:

$[I_1, I_2, I_3, I_4, I_5, I_6, I_7, I_8, I_9, I_{10}]$,

where P is equal to 10, I_1 is an integer number of cylinders to be activated during the first one of the next 10 engine cycles, I_2 is an integer number of cylinders to be activated during the second one of the next N engine cycles, I_3 is an integer number of cylinders to be activated during the third one of the next N engine cycles, and so on.

When the target ECC **308** is an integer, that number of cylinders can be activated during each of the next P engine cycles to achieve the target ECC **308**. For example only, if the target ECC **308** is equal to 4, 4 cylinders can be activated per engine cycle to achieve the target ECC **308** of 4. An example of the activated cylinder sequence **312** for activating 4 cylinders per engine cycle during the next P engine cycles is provided below where P is equal to 10.

[4, 4, 4, 4, 4, 4, 4, 4, 4, 4].

Different numbers of activated cylinders per engine cycle can also be used to achieve the target ECC **308** when the target ECC **308** is an integer. For example only, if the target ECC **308** is equal to 4, 4 cylinders can be activated during one engine cycle, 3 cylinders can be activated during another engine cycle, and 5 cylinders can be activated during another engine cycle to achieve the target ECC **308** of 4. An example of the activated cylinder sequence **312** for activating one or more different numbers of activated cylinders is provided below where P is equal to 10.

[4, 5, 3, 4, 3, 5, 3, 5, 4, 4].

When the target ECC **308** is a non-integer, different numbers of activated cylinders per engine cycle are used to achieve the target ECC **308**. For example only, if the target ECC **308** is equal to 5.4, the following example activated cylinder sequence **312** can be used to achieve the target ECC **308**:

[5, 6, 5, 6, 5, 6, 5, 5, 6, 5]

where P is equal to 10, 5 indicates that 5 cylinders are activated during the corresponding ones of the next 10 engine cycles, and 6 indicates that 6 cylinders are activated during the corresponding ones of the next 10 engine cycles. While use of the two nearest integers to a non-integer value of the target ECC **308** have been discussed as examples, other integers may be used additionally or alternatively.

The first sequence setting module **310** may update or select the activated cylinder sequence **312** based on one or more other parameters, such as engine speed **316** and/or a throttle opening **320**. For example only, the first sequence setting module **310** may update or select the activated

cylinder sequence **312** such that greater numbers of activated cylinders are used near the end of the next P engine cycles (and lesser numbers of activated cylinders are used near the beginning of the next P engine cycles) when the engine speed **316** and/or the throttle opening **320** is increasing. This may provide for a smoother transition to an increase in the target ECC **308**. The opposite may be true when the engine speed **316** and/or the throttle opening **320** is decreasing.

An engine speed module **324** (FIG. **2**) may generate the engine speed **316** based on a crankshaft position **328** measured using the crankshaft position sensor **180**. The throttle opening **320** may be generated based on measurements from one or more of the throttle position sensors **190**.

A subsequence setting module **332** sets a sequence of subsequences **336** based on the activated cylinder sequence **312** and the engine speed **316**. The sequence of subsequences **336** includes N indicators of N predetermined cylinder activation/deactivation subsequences to be used to achieve the corresponding numbers of activated cylinders (indicated by the activated cylinder sequence **312**) during the next P engine cycles, respectively. The subsequence setting module **332** may set the sequence of subsequences **336**, for example, using a mapping that relates the engine speed **316** and the activated cylinder sequence **312** to the sequence of subsequences **336**.

Statistically speaking, one or more possible cylinder activation/deactivation subsequences are associated with each possible number of activated cylinders per engine cycle. A unique indicator may be associated with each of the possible cylinder activation/deactivation subsequences for achieving a given number of activated cylinders. The following tables include example indicators and possible subsequences for 5 and 6 active cylinders per engine cycle with 8 cylinder events per engine cycle:

5 Cylinders Firing		6 Cylinders Firing	
Unique indicator	Subsequence	Unique indicator	Subsequence
5_01	00011111	6_01	00111111
5_02	00101111	6_02	01011111
.	.	.	.
.	.	.	.
.	.	.	.
5_10	01011101	6_10	10110111
5_11	01011110	6_11	10111011
.	.	.	.
.	.	.	.
.	.	.	.
5_28	10101011	6_28	11111100
.	.		
.	.		
.	.		
5_56	11111000		

where a 1 in a subsequence indicates that the corresponding cylinder in the firing order should be activated and a 0 indicates that the corresponding cylinder should be deactivated. While only possible subsequences for 5 and 6 active cylinders per engine cycle are provided above, one or more possible cylinder activation/deactivation subsequences are also associated with each other number of active cylinders per engine cycle.

In another implementation, subsequences having different lengths and/or subsequences with lengths that are different than the number of cylinder events per engine cycle can be used. In order to maintain a pressure within the intake manifold **110**, a subsequence may transition from activating another predetermined number of cylinders in a first number of cylinder events to activating a predetermined number of cylinders in a second number of cylinder events. For example, the subsequence may transition from activating 3 cylinders out of a potential of 8 cylinder events to activating 3 cylinders out of a potential of 7 cylinder events. The following tables include example indicators and possible subsequences for 3 active cylinders out of a potential of 8 cylinder events per engine cycle and 3 active cylinders out of a potential of 7 cylinder events per subsequence:

3 Cylinders Firing 8 Potential		3 Cylinders Firing 7 Potential	
Unique indicator	Subsequence	Unique indicator	Subsequence
3_8_01	00100101	3_7_01	0010101
3_8_02	00100110	3_7_02	0010110
.	.	.	.
.	.	.	.
.	.	.	.
3_8_10	01100010	3_7_10	0011001
3_8_11	01101000	3_7_11	0100101
.	.	.	.
.	.	.	.
.	.	.	.
3_8_28	10101000	3_7_28	1000101
.	.		
.	.		
.	.		
3_8_56	11100000		

While only possible subsequences for 3 out of 8 active cylinders and 3 out of 7 active cylinders per engine cycle are provided above, one or more possible cylinder activation/deactivation subsequences are also associated with each other number of active cylinders during each of the M cylinder events per engine cycle.

During a calibration phase of vehicle design, possible subsequences and sequences of the possible sequences producing minimum levels of vibration, minimum induction and exhaust noise, desired vibration characteristics, more even torque production/delivery, and better linkability with other possible subsequences are identified for various engine speeds. The identified subsequences are stored as predetermined cylinder activation/deactivation subsequences in a subsequence database **340**.

Further, transition parameters between the subsequences may be identified and stored in the subsequence database **340**. The transition parameters may indicate whether to truncate an outgoing subsequence and and/or to delay the start of an incoming subsequence. It is understood the outgoing subsequence may be repeated a plurality of times prior to transitioning to the incoming subsequence. The transition patterns may include a first value and a second value. The first value indicates whether to truncate an outgoing subsequence. For example, when the first value is greater than 0, the outgoing subsequence is truncated by the value of the first value. The second value indicates whether to delay the start of an incoming subsequence. For example, when the second value is greater than 0, the incoming subsequence is delayed by the value of the second value. By way of non-limiting example, a first transition pattern may be [2,5]. The outgoing subsequence is truncated by 2. In other words, the last 2 values of the outgoing subsequence are removed. The incoming subsequence is delayed by 5. In other words, the first 5 values of the incoming subsequence are removed. The outgoing subsequence and the incoming subsequence are then combined into an adjusted subsequence.

The transition parameters may be based on a length of the outgoing subsequence, a length of the incoming subsequence, an engine speed, a selected transmission gear, engine torque level, and other vehicle characteristics and operating conditions. During transition between an outgoing subsequence and an incoming subsequence, a driver and/or passenger within the vehicle may feel a vibration and/or a bump. This may be caused by a transition between subsequences of different lengths. The transition parameters truncate and/or delay the subsequences in order to reduce or remove the vibration and/or bump as felt by the driver and/or passenger.

For example, a first engine speed, a first subsequence may be selected in order to achieve a first cylinder firing pattern. As the engine speed changes, a second subsequence may be selected to achieve a second cylinder firing pattern. It is understood the first subsequence may be repeated a plurality of times prior to transitioning to the second subsequence. Transition parameters are identified that may effectively reduce or remove the vibration as a result of a transition between subsequences. In some instances, the first and second subsequence may be different sequence length. For example, the first subsequence may be a 3 out of 8 pattern. In other words, 3 cylinders are active out of 8 possible firing events. The second subsequence may be a 3 out of 7 pattern. In other words, 3 cylinders are active out of 7 possible firing events.

A transition pattern of [2,5] may effectively reduce or remove the vibration and/or bump as felt by the driver and/or passenger. Applying the transition pattern would truncate the 3 out of 8 firing pattern by 2 possible firing events and delay the start of the 3 out of 7 firing pattern by 5 possible firing events. The resulting adjusted sequence would include 8 possible firing events.

During the calibration phase of the vehicle design, all possible transitions between all identified possible subsequences are identified. Transition parameters associated with each possible transition may be identified and stored in the subsequence database **340**.

During vehicle operation, the subsequence setting module **332** sets the sequence of subsequences **336** based on the activated cylinder sequence **312** and the engine speed **316**. An example of the sequence of subsequences **336** for the example activated cylinder sequence of [5, 6, 5, 6, 5, 6, 5, 5, 6, 5] is:

[5_23, 6_25, 5_19, 6_22, 5_55, 6_01, 5_23, 5_21, 6_11, 5_29],

where 5_23 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 5 cylinders during the first one of the next P engine cycles, where 6_25 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 6 cylinders during the second one of the next P engine cycles, 5_19 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 5 cylinders during the third one of the next P engine cycles, 6_22 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 6 cylinders during the fourth one of the next P engine cycles, and so on.

In another implementation, the subsequence setting module **332** determines whether to adjust one or more predetermined cylinder activation/deactivation subsequences. For example, the subsequence **336** may include a subsequence pair comprising a first subsequence and second subsequence. The first and second subsequences may be of different subsequence lengths. Transitioning between subsequences of different lengths may be felt as a vibration and/or a bump to a driver or a passenger of the vehicle. In order to produce an acceptable transient vibration, the subsequence setting module **332** may selectively adjust one or more predetermined cylinder activation/deactivation subsequences.

For example, the subsequence setting module **332** sets the sequence of subsequences **336** based on the activated cylinder sequence **312** and the engine speed **316**. The second subsequence immediately follows the first subsequence. However, it is noted that while the identifiers first and second are used, the subsequence pair may occur anywhere within the subsequence **336**. Further, the first subsequence may be repeated multiple times prior to transitioning to the second subsequence. By repeating a subsequence the vehicle experiences less transient vibration. Further, an average target ECC per engine cycle may be when the target ECC **304** is a non-integer value. For example, as described above, the target ECC is the average number of cylinder firings per engine cycle.

A subsequence may have a subsequence length X. A sequence may repeat the subsequence Y times and include Z potential firing events, where Z=X*Y. By way of non-limiting example only, a subsequence may fire 4 cylinders out of every 7 potential firing events, the sequence repeats the subsequence 8 times, resulting in 56 potential firing events during the sequence. During the sequence, 32 cylinder firings occur of the potential 56 (i.e., 4 of every 7, or 4*8 out of 7*8). The ECC is equal to the number of cylinders that fire per engine cycle, on average, during the sequence. In the example, assuming the vehicle includes 8 cylinders, 56 firing events occurs every 7 engine cycles (i.e., Z divided by the number of cylinders). The ECC would be equal to 32 cylinder firings divided by 7 engine cycles, or 4.57 effective cylinders fired every engine cycle.

The subsequence setting module **332** may determine a transition parameter associated with a transition between the first and second subsequences. As described above, the transition parameter is stored in subsequence database **340**. The subsequence setting module **332** determines a transition parameter associated with the transition between the first and second subsequences. The subsequence setting module **332** selectively adjusts the first and second subsequence based on the transition parameter.

As described above, a subsequence may transition from activating a predetermined number of cylinders in a first number of cylinder events to activating another predetermined number of cylinders in a second number of cylinder events. For example, the subsequence may transition from activating 3 cylinders out of a potential of 8 cylinder events to activating 3 cylinders out of 7 cylinder events.

The subsequence setting module **332** sets the sequence of subsequences **336** based on the activated cylinder sequence **312** and the engine speed **316**. An example of the sequence of subsequences **336** for an example activated cylinder sequence is:

[3_8_01, 3_8_01, 3_8_01, 3_8_01, 3_7_01, 3_7_01, 37_01, 3_7_01, 37_01, 3_7_01],

where 3_8_01 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 3 cylinders during 8 potential cylinder events during a first sequence of the next P engine cycles and where 3_7_01 is the indicator of one of the predetermined cylinder activation/deactivation subsequences that is to be used to activate 3 cylinders during 7 potential cylinder events during a second sequence of the next P engine cycles.

In the example above, the subsequence **336** includes a sequence pair that includes a first subsequence (3_8_01) and a second subsequence (3_7_01) that are of different subsequence lengths. For example, 3_8_01 has a subsequence of 00100101 (i.e., a length of 8) and 3_7_01 has a subsequence of 0010101 (i.e., a length of 7). The transition between these subsequences would be to join them as 00100101:0010101. This transition may be felt as a vibration and/or a bump to the driver and/or a passenger of the vehicle. The subsequence setting module **332** selectively adjusts one or both of the subsequences based on the transition parameter associated to a transition between the 3_8_01 subsequence and the 3_7_01 subsequence.

In the example above, the transition parameter for the transition between the 3_8_01 subsequence and the 3_7_01 subsequence may be [2,3]. The transition parameter is a predetermined parameter. During calibration of the vehicle, transition parameters are identified for each possible transition between each possible subsequence pairs. In other words, each possible outgoing subsequence includes a transition into each possible incoming subsequence. A transition parameter that reduces and/or removes the vibration during the transition, for the given operating conditions, is identified and stored in the database **340**.

The subsequence setting module **332** selectively adjusts the 3_8_01 subsequence and the 3_7_01 subsequence based on the [2,3] transition parameter. For example, the subsequence setting module **332** adjusts the 3_8_01 subsequence from 00100101 to 001001 (i.e., eliminating the last two events) and adjusts the 3_7_01 subsequence from 0010101 to 0101 (i.e., eliminating the first three events).

The resulting transition would be an adjusted subsequence of 001001:0101. The adjusted subsequence may provide less transient vibration than the original transition between the 3_8_01 subsequence and the 3_7_01 subsequence. Further, the resulting subsequence activates 4 cylinders out of 10 cylinder events (i.e., 40%). Whereas the 3_8_01 subsequence activates 3 cylinders out of 8 cylinder events (i.e., 37.5%) and the 3_7_01 subsequence activates 3 cylinders out of 7 cylinder events (i.e., 42.9%). By applying the transition parameter, the resulting transition produces an output torque between the 3_8_01 subsequence and the 3_7_01 subsequence, resulting in a more gradual increase in output torque. The subsequence setting module **332** replaces the first subsequence (3_8_01) and the second subsequence (3_7_01) with the adjusted subsequence within the sequence of subsequences **336**. In this manner, the subsequence setting module **332** identifies transitions that may result in a vibration and/or bump and selective applies a transition parameter in order to reduce or remove the vibration and/or bump from the sequence of subsequences **336**.

A second sequence setting module **344** receives the sequence of subsequences **336** and generates the target cylinder activation/deactivation sequence **248**. More specifically, the second sequence setting module **344** sets the target cylinder activation/deactivation sequence **248** to the predetermined cylinder activation/deactivation subsequences indicated in the sequence of subsequences **336**, in the order specified in the sequence of subsequences **336**. The second sequence setting module **344** retrieves the predetermined cylinder activation/deactivation subsequences indicated from the subsequence database **340** and the adjusted subsequence. It is understood that the sequence of subsequences **336** may include one or more adjusted subsequences. Further, the sequence of subsequences **336** may not include any adjusted subsequences. The cylinders are activated according to the target cylinder activation/deactivation sequence **248** during the next N engine cycles.

It may be desirable to vary the activated cylinder sequence **312** from one set of P engine cycles to another set of P engine cycles. This variation may be performed, for example, to prevent harmonic vibration from being experienced within a passenger cabin of the vehicle or to maintain a random vibration characteristic. For example, two or more predetermined activated cylinder sequences may be stored in an activated cylinder sequence database **348** for a given target ECC, and predetermined percentages of use may be provided for each of the predetermined activated cylinder sequences. If the target ECC **308** remains approximately constant, the first sequence setting module **310** may select the predetermined activated cylinder sequences for use as the activated cylinder sequence **312** in an order based on the predetermined percentages.

Referring now to FIG. **4**, a flowchart depicting an example method of controlling cylinder activation and deactivation is presented. At **404**, the cylinder control module **244** determines whether one or more enabling conditions are satisfied. For example, the cylinder control module **244** determines whether a steady-state or quasi steady-state operating condition is occurring at **404**. If true, control continues at **408**. If false, control ends. A steady-state or a quasi steady-state operating condition may be said to be occurring, for example, when the engine speed **316** has changed by less than a predetermined amount (e.g., approximately 100-200 RPM) over a predetermined period (e.g., approximately 5 seconds). Additionally or alternatively, the throttle opening **320** and/or one or more other suitable parameters may be used to determine whether a steady-state or a quasi steady-state operating condition is occurring.

At **408**, the target cylinder count module **304** generates the target ECC **308**. The target cylinder count module **304** determines the target ECC **308** based on the torque request **208** and/or one or more other parameters, as discussed above. The target ECC **308** corresponds to a target number of cylinders to be activated per engine cycle on average over the next P engine cycles.

The first sequence setting module **310** generates the activated cylinder sequence **312** at **412**. The first sequence setting module **310** determines the activated cylinder sequence **312** based on the target ECC **308** and/or one or more other parameters, as discussed above. The activated cylinder sequence **312** includes a sequence of N integers that correspond to the number of cylinders that should be activated during the next P engine cycles, respectively.

The subsequence setting module **332** generates the sequence of subsequences **336** at **416**. The subsequence setting module **332** determines the sequence of subsequences **336** based on the activated cylinder sequence **312**, the engine speed **316**, and/or one or more other parameters, as discussed above. The sequence of subsequences **336** includes N indicators of N predetermined cylinder activation/deactivation subsequences to be used to achieve the corresponding numbers of activated cylinders indicated by the activated cylinder sequence **312**.

At **420**, the second sequence setting module **344** retrieves the predetermined cylinder activation/deactivation subsequences indicated by the sequence of subsequences **336**. The second sequence setting module **344** retrieves the predetermined cylinder activation/deactivation subsequences from the subsequence database **340**. Each of the predetermined cylinder activation/deactivation subsequences includes a sequence for activating and deactivating cylinders during one of the next P engine cycles.

At **424**, the subsequence setting module **332** identifies transitions between each of the retrieved, predetermined cylinder activation/deactivation subsequences. The subsequence setting module **332** determines whether to apply a transition parameter based on a determination of whether a transition has an associated transition parameter. For example, a transition may be associated with an outgoing subsequence and an incoming subsequence. The outgoing subsequence and the incoming subsequence may be of different sequence lengths. The transition between the outgoing subsequence and incoming subsequence (of different lengths) may result in a vibration and/or bump as felt by a driver or passenger within the vehicle. A transition parameter may be associated with the transition.

The transition parameter reduces and/or removes the vibration and/or bump. Further, the outgoing subsequence and the incoming subsequence may be of the same sequence length. The transition between the outgoing and incoming subsequence may include an associated transition parameter. In other words, transitioning sequences of different lengths as well as transition sequences of the same length may result in a vibration and/or bump (i.e., depending on the particular subsequences being transitioned).

If true, control continues at **428**. If false, control continues at **432**. At **428**, the subsequence setting module **332** selectively applies a transition parameter to at least one of the outgoing subsequence and the incoming subsequence based on the transition parameter. The subsequence setting module **332** communicates the adjusted subsequences to the second sequence setting module **344**. Additionally or alternatively, the subsequence setting module **332** removes the outgoing subsequence and/or the incoming subsequence. The subsequence setting module **332** includes the at least one adjusted subsequence within the sequence of subsequences **336**.

At **432**, the second sequence setting module **344** generates the target cylinder activation/deactivation sequence **248** based on the retrieved, predetermined cylinder activation/deactivation subsequences. Further, the second sequence setting module **344** may determine whether the sequence setting module **332** adjusted one or more subsequences. When the second sequence setting module **334** determines the sequencer setting module **332** adjusted at least one subsequence, the second sequence setting module **344** includes the at least one adjusted subsequence in the target cylinder activation/deactivation sequence **248**.

More specifically, the second sequence setting module **344** assembles the retrieved, predetermined cylinder activation/deactivation sequences, in the order indicated by the sequence of subsequences **336**, to generate the target cylinder activation/deactivation sequence **248**. In this manner, the target cylinder activation/deactivation sequence **248** includes a sequence for activating and deactivating cylinders during the next N engine cycles.

The engine **102** is controlled based on the target cylinder activation/deactivation sequence **248** at **436**. For example, if the target cylinder activation/deactivation sequence **248** indicates that the next cylinder in the firing order should be activated, the following cylinder in the firing order should be deactivated, and the following cylinder in the firing order should be activated, then the next cylinder in the predetermined firing order is activated, the following cylinder in the predetermined firing order is deactivated, and the following cylinder in the predetermined firing order is activated.

The cylinder control module **244** deactivates opening of the intake and exhaust valves of cylinders that are to be deactivated. The cylinder control module **244** allows opening and closing of the intake and exhaust valves of cylinders that are to be activated. The fuel control module **232** provides fuel to cylinders that are to be activated and halts fueling to cylinders that are to be deactivated. The spark control module **224** provides spark to cylinders that are to be activated. The spark control module **224** halts spark or provides spark to cylinders that are to be deactivated. While control is shown as ending, FIG. **4** is illustrative of one control loop, and a control loop may be executed, for example, every predetermined amount of crankshaft rotation.

The foregoing description is merely illustrative in nature and is in no way intended to limit the disclosure, its application, or uses. The broad teachings of the disclosure can be implemented in a variety of forms. Therefore, while this disclosure includes particular examples, the true scope of the disclosure should not be so limited since other modifications will become apparent upon a study of the drawings, the specification, and the following claims. For purposes of clarity, the same reference numbers will be used in the drawings to identify similar elements. As used herein, the phrase at least one of A, B, and C should be construed to mean a logical (A or B or C), using a non-exclusive logical OR. It should be understood that one or more steps within a method may be executed in different order (or concurrently) without altering the principles of the present disclosure.

As used herein, the term module may refer to, be part of, or include an Application Specific Integrated Circuit (ASIC); a discrete circuit; an integrated circuit; a combinational logic circuit; a field programmable gate array (FPGA); a processor (shared, dedicated, or group) that executes code; other suitable hardware components that provide the described functionality; or a combination of some or all of the above, such as in a system-on-chip. The term module may include memory (shared, dedicated, or group) that stores code executed by the processor.

The term code, as used above, may include software, firmware, and/or microcode, and may refer to programs, routines, functions, classes, and/or objects. The term shared, as used above, means that some or all code from multiple modules may be executed using a single (shared) processor. In addition, some or all code from multiple modules may be stored by a single (shared) memory. The term group, as used above, means that some or all code from a single module may be executed using a group of processors. In addition, some or all code from a single module may be stored using a group of memories.

The apparatuses and methods described herein may be partially or fully implemented by one or more computer programs executed by one or more processors. The computer programs include processor-executable instructions that are stored on at least one non-transitory tangible computer readable medium. The computer programs may also include and/or rely on stored data. Non-limiting examples of the non-transitory tangible computer readable medium include nonvolatile memory, volatile memory, magnetic storage, and optical storage.

What is claimed is:

1. A cylinder control system of a vehicle, comprising:

a cylinder control module that:

determines target numbers of cylinders of an engine to be activated during a period;

determines, based on the target numbers and an engine speed, N predetermined subsequences for controlling the cylinders of the engine during the period, where N is an integer greater than zero;

determines a transition parameter associated with at least one transition between two of the N predetermined subsequences, the two predetermined subsequences each including M indicators for the M cylinder events, each of the M indicators indicating whether to activate or deactivate a corresponding cylinder, where M is an integer greater than one,

wherein the transition parameter includes a first number (X) for truncating one of the two predetermined subsequences and a second number (Y) for truncating the other one of the two predetermined subsequences, where X and Y are integers greater than zero and less than M;

adjusts the one of the two predetermined subsequences, by removing the last X number of the M indicators of the one of the two predetermined subsequences, to produce a first adjusted predetermined subsequence; and

adjusts the other one of the two predetermined subsequences, by removing the first Y number of the M indicators of the other one of the two predetermined subsequences, to produce a second adjusted predetermined subsequence; and

a cylinder actuator module that, during the period, controls the cylinders of the engine based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

2. The cylinder control system of claim **1** wherein the cylinder control module determines the target numbers of cylinders to be activated during the period based on an engine torque request.

3. The cylinder control system of claim **1** wherein the cylinder control module generates a target sequence for activating and deactivating cylinders of the engine based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

4. The cylinder control system of claim **3** wherein the cylinder actuator module activates opening of intake and exhaust valves of first ones of the cylinders that are to be activated based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence and deactivates opening intake and exhaust valves of second ones of the cylinders that are to be deactivated based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

5. The cylinder control system of claim **1** wherein the cylinder control module retrieves the transition parameter associated with the at least one transition between the at least two of the N predetermined subsequences.

6. The cylinder control system of claim **1** wherein the cylinder control module adjusts the one of the two predetermined subsequences based on a determination that the first number X of the transition parameter is greater than 0.

7. The cylinder control system of claim **6** wherein the cylinder control module adjusts the other one of the two predetermined subsequences based on a determination that the second number Y of the transition parameter is greater than 0.

8. A cylinder control method of a vehicle, comprising:

determining target numbers of cylinders of an engine to be activated during a period,

determining, based on the target numbers and an engine speed, N predetermined subsequences for controlling cylinders of the engine during the period, where N is an integer greater than zero;

determining a transition parameter associated with at least one transition between two of the N predetermined subsequences, the two predetermined subsequences each including M indicators for the M cylinder events, each of the M indicators indicating whether to activate or deactivate a corresponding cylinder, where M is an integer greater than one,

wherein the transition parameter includes a first number (X) for truncating one of the two predetermined subsequences and a second number (Y) for truncating the other one of the two predetermined subsequences, where X and Y are integers greater than zero and less than M;

adjusting the one of the two predetermined subsequences, by removing the last X number of the M indicators of the one of the two predetermined subsequences, to produce a first adjusted predetermined subsequence;

adjusting the other one of the two predetermined subsequences, by removing the first Y number of the M indicators of the other one of the two predetermined subsequences, to produce a second adjusted predetermined subsequence; and

controlling, during the period, the cylinders of the engine based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

9. The cylinder control method of claim **8** further comprising, determining the target numbers of cylinders to be activated during the period based on an engine torque request.

10. The cylinder control method of claim **8** further comprising generating a target sequence for activating and deactivating cylinders of the engine based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

11. The cylinder control method of claim **10** further comprising activating opening of intake and exhaust valves of first ones of the cylinders that are to be activated based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence and deactivating opening of intake and exhaust valves of second ones of the cylinders that are to be deactivated based on the N predetermined subsequences, the first adjusted predetermined subsequence, and the second adjusted predetermined subsequence.

12. The cylinder control method of claim **8** further comprising retrieving the transition parameter associated with the at least one transition between the at least two of the N predetermined subsequences.

13. The cylinder control method of claim **8** wherein the adjusting the one of the two predetermined subsequences includes adjusting the one of the two predetermined subsequences based on a determination that the first number X of the transition parameter is greater than 0.

14. The cylinder control method of claim **13** wherein the adjusting the other one of the two predetermined subsequences includes adjusting the other one of the two predetermined subsequences based on a determination that the second number Y of the transition parameter is greater than 0.

* * * * *