US009867062B1

(12) **United States Patent**
Bell et al.

(10) **Patent No.: US 9,867,062 B1**
(45) **Date of Patent: Jan. 9, 2018**

(54) **SYSTEM AND METHODS FOR USING A REMOTE SERVER TO AUTHORIZE A RECEIVING DEVICE THAT HAS REQUESTED WIRELESS POWER AND TO DETERMINE WHETHER ANOTHER RECEIVING DEVICE SHOULD REQUEST WIRELESS POWER IN A WIRELESS POWER TRANSMISSION SYSTEM**

(71) Applicant: **ENERGOUS CORPORATION**, San Jose, CA (US)

(72) Inventors: **Douglas Bell**, Pleasanton, CA (US); **Michael A. Leabman**, San Ramon, CA (US)

(73) Assignee: **Energous Corporation**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/585,271**

(22) Filed: **Dec. 30, 2014**

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/337,002, filed on Jul. 21, 2014.

(51) **Int. Cl.**
H02J 50/20 (2016.01)
H04W 24/02 (2009.01)

(52) **U.S. Cl.**
CPC ***H04W 24/02*** (2013.01); ***H02J 50/20*** (2016.02)

(58) **Field of Classification Search**
CPC .. H02J 17/00; H02J 50/40; H02J 50/80; H02J 50/90; H02J 50/20
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

787,412 A 4/1905 Tesla
3,696,384 A 10/1972 Lester
(Continued)

FOREIGN PATENT DOCUMENTS

CN 203826555 U 9/2014
CN 104090265 A 10/2014
(Continued)

OTHER PUBLICATIONS

International Search Report dated Jan. 27, 2015 corresponding to International Patent Application No. PCT/US2014/037170, 4 pages.
(Continued)

Primary Examiner — Fritz M Fleming
(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

The embodiments described herein include a transmitter that transmits a power transmission signal (e.g., radio frequency (RF) signal waves) to create a three-dimensional pocket of energy. At least one receiver can be connected to or integrated into electronic devices and receive power from the pocket of energy. A wireless power network may include a plurality of wireless power transmitters each with an embedded wireless power transmitter manager, including a wireless power manager application. The wireless power network may include a plurality of client devices with wireless power receivers. Wireless power receivers may include a power receiver application configured to communicate with the wireless power manager application. The wireless power manager application may include a device database where information about the wireless power network may be stored.

21 Claims, 33 Drawing Sheets



(58) **Field of Classification Search**
USPC 307/104; 320/108
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,754,269	A	8/1973	Clavin	
4,101,895	A	7/1978	Jones, Jr.	
4,360,741	A	11/1982	Fitzsimmons et al.	
4,944,036	A	7/1990	Hyatt	
4,995,010	A	2/1991	Knight	
5,200,759	A	4/1993	McGinnis	
5,211,471	A	5/1993	Rohrs	
5,556,749	A	9/1996	Mitsuhashi et al.	
5,568,088	A	10/1996	Dent et al.	
5,646,633	A	7/1997	Dahlberg	
5,712,642	A	1/1998	Hulderman	
5,936,527	A	8/1999	Isaacman et al.	
5,982,139	A	11/1999	Parise	
6,046,708	A	4/2000	MacDonald, Jr. et al.	
6,127,799	A	10/2000	Krishnan	
6,127,942	A	10/2000	Welle	
6,289,237	B1	9/2001	Mickle et al.	
6,437,685	B2 *	8/2002	Hanaki	H02J 17/00 340/286.02
6,615,074	B2	9/2003	Mickle et al.	
6,664,920	B1	12/2003	Mott et al.	
6,798,716	B1	9/2004	Charych	
6,803,744	B1	10/2004	Sabo	
6,856,291	B2	2/2005	Mickle et al.	
6,911,945	B2	6/2005	Korva	
6,960,968	B2	11/2005	Odendaal et al.	
7,003,350	B2	2/2006	Denker et al.	
7,027,311	B2	4/2006	Vanderelli et al.	
7,068,991	B2	6/2006	Parise	
7,191,013	B1	3/2007	Miranda et al.	
7,196,663	B2	3/2007	Bolzer et al.	
7,222,356	B1	5/2007	Yonezawa et al.	
7,274,334	B2	9/2007	o'Riordan et al.	
7,274,336	B2	9/2007	Carson	
7,392,068	B2	6/2008	Dayan	
7,403,803	B2	7/2008	Mickle et al.	
7,451,839	B2	11/2008	Perlman	
7,614,556	B2	11/2009	Overhultz et al.	
7,639,994	B2	12/2009	Greene et al.	
7,643,312	B2	1/2010	Vanderelli et al.	
7,702,771	B2	4/2010	Ewing et al.	
7,786,419	B2	8/2010	Hyde et al.	
7,812,771	B2	10/2010	Greene et al.	
7,830,312	B2	11/2010	Choudhury et al.	
7,844,306	B2	11/2010	Shearer et al.	
7,868,482	B2	1/2011	Greene et al.	
7,898,105	B2	3/2011	Greene et al.	
7,925,308	B2	4/2011	Greene et al.	
8,055,003	B2	11/2011	Mittleman et al.	
8,070,595	B2	12/2011	Alderucci et al.	
8,092,301	B2	1/2012	Alderucci et al.	
8,099,140	B2	1/2012	Arai	
8,115,448	B2	2/2012	John	
8,159,090	B2	4/2012	Greene et al.	
8,159,364	B2	4/2012	Zeine	
8,180,286	B2	5/2012	Yamasuge	
8,264,101	B2	9/2012	Hyde et al.	
8,264,291	B2	9/2012	Morita	
8,276,325	B2	10/2012	Clifton et al.	
8,362,745	B2	1/2013	Tinaphong	
8,380,255	B2	2/2013	Shearer et al.	
8,410,953	B2	4/2013	Zeine	
8,432,062	B2	4/2013	Greene et al.	
8,432,071	B2	4/2013	Huang et al.	
8,446,248	B2	5/2013	Zeine	
8,447,234	B2	5/2013	Cook et al.	
8,451,189	B1	5/2013	Fluhler	
8,452,235	B2	5/2013	Kirby et al.	
8,457,656	B2	6/2013	Perkins et al.	
8,461,817	B2	6/2013	Martin et al.	
8,497,658	B2	7/2013	Von Novak et al.	
8,552,597	B2	10/2013	Song et al.	
8,558,661	B2	10/2013	Zeine	
8,621,245	B2	12/2013	Shearer et al.	
8,626,249	B2	1/2014	Kuusilinna et al.	
8,653,966	B2	2/2014	Rao et al.	
8,674,551	B2	3/2014	Low et al.	
8,712,485	B2	4/2014	Tam	
8,718,773	B2	5/2014	Willis et al.	
8,729,737	B2	5/2014	Schatz et al.	
8,772,960	B2	7/2014	Yoshida	
8,823,319	B2	9/2014	Von Novak, III et al.	
8,854,176	B2	10/2014	Zeine	
8,860,364	B2	10/2014	Low et al.	
8,897,770	B1	11/2014	Frolov et al.	
8,923,189	B2	12/2014	Leabman	
8,928,544	B2	1/2015	Massie et al.	
8,937,408	B2	1/2015	Ganem et al.	
8,946,940	B2	2/2015	Kim et al.	
8,989,053	B1	3/2015	Skaaksrud et al.	
9,000,616	B2	4/2015	Greene et al.	
9,001,622	B2	4/2015	Perry	
9,006,934	B2	4/2015	Kozakai et al.	
9,021,277	B2	4/2015	Shearer et al.	
9,030,161	B2	5/2015	Lu et al.	
9,059,598	B2	6/2015	Kang et al.	
9,077,188	B2	7/2015	Moshfeghi	
9,124,125	B2	9/2015	Leabman et al.	
9,130,602	B2	9/2015	Cook	
9,143,010	B2	9/2015	Urano	
9,225,196	B2	12/2015	Huang et al.	
9,242,411	B2	1/2016	Kritchman et al.	
9,244,500	B2	1/2016	Cain et al.	
9,252,628	B2	2/2016	Leabman et al.	
9,270,344	B2	2/2016	Rosenberg	
9,282,582	B1	3/2016	Dunsbergen et al.	
9,294,840	B1	3/2016	Anderson et al.	
9,368,020	B1	6/2016	Bell et al.	
9,401,977	B1	7/2016	Gaw	
9,444,283	B2	9/2016	Son et al.	
9,450,449	B1	9/2016	Leabman et al.	
9,461,502	B2	10/2016	Lee et al.	
9,520,725	B2	12/2016	Masaoka et al.	
9,520,748	B2	12/2016	Hyde et al.	
9,522,270	B2	12/2016	Perryman et al.	
9,537,354	B2	1/2017	Bell et al.	
9,537,357	B2	1/2017	Leabman	
9,537,358	B2	1/2017	Leabman	
9,538,382	B2	1/2017	Bell et al.	
9,544,640	B2	1/2017	Lau	
9,559,553	B2	1/2017	Bae	
9,564,773	B2	2/2017	Pogorelik et al.	
9,590,444	B2	3/2017	Walley	
9,620,996	B2	4/2017	Zeine	
2002/0028655	A1	3/2002	Rosener et al.	
2002/0034958	A1	3/2002	Oberschmidt et al.	
2002/0054330	A1	5/2002	Jinbo et al.	
2002/0072784	A1	6/2002	Sheppard et al.	
2002/0103447	A1	8/2002	Terry	
2002/0133592	A1	9/2002	Matsuda	
2003/0005759	A1	1/2003	Breed et al.	
2003/0058187	A1	3/2003	Billiet et al.	
2003/0076274	A1	4/2003	Phelan et al.	
2003/0179152	A1	9/2003	Watada et al.	
2003/0179573	A1	9/2003	Chun	
2003/0192053	A1	10/2003	Sheppard et al.	
2004/0019624	A1	1/2004	Sukegawa	
2004/0020100	A1	2/2004	O'Brian et al.	
2004/0036657	A1	2/2004	Forster et al.	
2004/0066251	A1	4/2004	Eleftheriades et al.	
2004/0119675	A1	6/2004	Washio et al.	
2004/0130425	A1 *	7/2004	Dayan	H02J 5/005 336/200
2004/0142733	A1	7/2004	Parise	
2004/0145342	A1	7/2004	Lyon	
2004/0196190	A1	10/2004	Mendolia et al.	
2004/0207559	A1	10/2004	Milosavljevic	
2004/0218759	A1	11/2004	Yacobi	
2004/0259604	A1	12/2004	Mickle et al.	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0263124 A1 12/2004 Wieck et al.
2005/0007276 A1 1/2005 Barrick et al.
2005/0030118 A1 2/2005 Wang
2005/0055316 A1 3/2005 Williams
2005/0093766 A1 5/2005 Turner
2005/0116683 A1 6/2005 Cheng
2005/0198673 A1 9/2005 Kit et al.
2005/0227619 A1 10/2005 Lee et al.
2005/0232469 A1 10/2005 Schofield
2005/0282591 A1 12/2005 Shaff
2006/0013335 A1 1/2006 Leabman
2006/0019712 A1 1/2006 Choi
2006/0092079 A1 5/2006 de Rochemont
2006/0094425 A1 5/2006 Mickle et al.
2006/0113955 A1 6/2006 Nunally
2006/0119532 A1 6/2006 Yun et al.
2006/0136004 A1 6/2006 Cowan et al.
2006/0160517 A1 7/2006 Yoon
2006/0183473 A1 8/2006 Ukon
2006/0192913 A1 8/2006 Shutou et al.
2006/0199620 A1 9/2006 Greene et al.
2006/0238365 A1 10/2006 Vecchione et al.
2006/0266917 A1 11/2006 Baldis et al.
2006/0284593 A1 12/2006 Nagy et al.
2006/0287094 A1 12/2006 Mahaffey et al.
2007/0007821 A1 1/2007 Rossetti
2007/0019693 A1 1/2007 Graham
2007/0021140 A1* 1/2007 Keyes, IV H02J 17/00 455/522
2007/0060185 A1 3/2007 Simon et al.
2007/0070490 A1 3/2007 Tsunoda et al.
2007/0097653 A1 5/2007 Gilliland et al.
2007/0103110 A1 5/2007 Sagoo
2007/0106894 A1 5/2007 Zhang
2007/0109121 A1 5/2007 Cohen
2007/0139000 A1 6/2007 Kozuma
2007/0173196 A1 7/2007 Gallic
2007/0173214 A1 7/2007 Mickle et al.
2007/0178945 A1* 8/2007 Cook H02J 17/00 455/572
2007/0182367 A1 8/2007 Partovi
2007/0191075 A1 8/2007 Greene et al.
2007/0197281 A1 8/2007 Stronach
2007/0222681 A1 9/2007 Greene et al.
2007/0257634 A1 11/2007 Leschin et al.
2007/0273486 A1 11/2007 Shiotsu
2008/0014897 A1* 1/2008 Cook H02J 17/00 455/343.1
2008/0062255 A1 3/2008 Gal
2008/0113816 A1 5/2008 Mahaffey et al.
2008/0122297 A1* 5/2008 Arai H02J 17/00 307/154
2008/0169910 A1 7/2008 Greene et al.
2008/0197802 A1 8/2008 Onishi
2008/0204342 A1 8/2008 Kharadly
2008/0211458 A1 9/2008 Lawther et al.
2008/0248758 A1 10/2008 Schedelbeck et al.
2008/0248846 A1 10/2008 Stronach et al.
2008/0278378 A1 11/2008 Chang et al.
2008/0309452 A1 12/2008 Zeine
2009/0002493 A1 1/2009 Kates
2009/0036065 A1 2/2009 Siu
2009/0047998 A1 2/2009 Alberth, Jr.
2009/0067208 A1 3/2009 Martin et al.
2009/0096412 A1 4/2009 Huang
2009/0102292 A1 4/2009 Cook et al.
2009/0102296 A1 4/2009 Greene et al.
2009/0128262 A1 5/2009 Lee et al.
2009/0157911 A1 6/2009 Aihara
2009/0200985 A1 8/2009 Zane et al.
2009/0206791 A1 8/2009 Jung
2009/0207092 A1 8/2009 Nysen et al.
2009/0219903 A1 9/2009 Alamouti et al.
2009/0243397 A1 10/2009 Cook et al.
2009/0264069 A1 10/2009 Yamasuge
2009/0284082 A1 11/2009 Mohammadian
2009/0284083 A1 11/2009 Karalis et al.
2009/0284220 A1 11/2009 Toncich et al.
2009/0284325 A1 11/2009 Rossiter et al.
2009/0286475 A1 11/2009 Toncich et al.
2009/0291634 A1 11/2009 Saarisalo
2009/0315412 A1 12/2009 Yamamoto et al.
2010/0001683 A1 1/2010 Huang et al.
2010/0007307 A1 1/2010 Baarman et al.
2010/0007569 A1 1/2010 Sim et al.
2010/0019686 A1 1/2010 Gutierrez, Jr.
2010/0026605 A1 2/2010 Yang et al.
2010/0027379 A1 2/2010 Saulnier et al.
2010/0029383 A1 2/2010 Dai
2010/0033021 A1 2/2010 Bennett
2010/0033390 A1 2/2010 Alamouti et al.
2010/0041453 A1 2/2010 Grimm, Jr.
2010/0044123 A1 2/2010 Perlman et al.
2010/0075607 A1 3/2010 Hosoya
2010/0079005 A1 4/2010 Hyde et al.
2010/0087227 A1 4/2010 Francos et al.
2010/0090656 A1 4/2010 Shearer et al.
2010/0127660 A1 5/2010 Cook et al.
2010/0142418 A1 6/2010 Nishioka et al.
2010/0142509 A1 6/2010 Zhu et al.
2010/0151808 A1 6/2010 Toncich et al.
2010/0164433 A1 7/2010 Janefalkar et al.
2010/0171461 A1* 7/2010 Baarman H02J 5/005 320/108
2010/0174629 A1 7/2010 Taylor et al.
2010/0181961 A1 7/2010 Novak et al.
2010/0194206 A1 8/2010 Burdo et al.
2010/0201201 A1 8/2010 Mobarhan et al.
2010/0201314 A1 8/2010 Toncich et al.
2010/0210233 A1 8/2010 Cook et al.
2010/0225270 A1 9/2010 Jacobs et al.
2010/0227570 A1 9/2010 Hendin
2010/0237709 A1 9/2010 Hall et al.
2010/0244576 A1 9/2010 Hillan et al.
2010/0256831 A1 10/2010 Abramo et al.
2010/0259110 A1 10/2010 Kurs et al.
2010/0264747 A1 10/2010 Hall et al.
2010/0277003 A1 11/2010 Von Novak et al.
2010/0277121 A1 11/2010 Hall et al.
2010/0295372 A1 11/2010 Hyde et al.
2010/0308767 A1 12/2010 Rofougaran et al.
2010/0309079 A1 12/2010 Rofougaran et al.
2010/0309088 A1 12/2010 Hyvonen et al.
2010/0315045 A1 12/2010 Zeine
2010/0316163 A1 12/2010 Forenza et al.
2010/0328044 A1 12/2010 Waffenschmidt et al.
2011/0031928 A1 2/2011 Soar
2011/0043047 A1 2/2011 Karalis et al.
2011/0043163 A1* 2/2011 Baarman H02J 17/00 320/108
2011/0043327 A1 2/2011 Baarman et al.
2011/0050166 A1 3/2011 Cook et al.
2011/0056215 A1 3/2011 Ham
2011/0057607 A1 3/2011 Carobolante
2011/0074342 A1 3/2011 MacLaughlin
2011/0074349 A1 3/2011 Ghovanloo
2011/0074620 A1 3/2011 Wintermantel
2011/0078092 A1 3/2011 Kim et al.
2011/0090126 A1 4/2011 Szini et al.
2011/0114401 A1 5/2011 Kanno
2011/0115303 A1 5/2011 Baarman et al.
2011/0115432 A1 5/2011 El-Maleh
2011/0127845 A1 6/2011 Walley et al.
2011/0127952 A1 6/2011 Walley et al.
2011/0133691 A1 6/2011 Hautanen
2011/0148578 A1 6/2011 Aloi et al.
2011/0154429 A1 6/2011 Stantchev
2011/0156494 A1 6/2011 Mashinsky
2011/0163128 A1 7/2011 Taguchi et al.
2011/0181120 A1 7/2011 Liu et al.
2011/0182245 A1 7/2011 Malkamaki et al.
2011/0184842 A1 7/2011 Melen
2011/0188207 A1 8/2011 Won et al.
2011/0194543 A1 8/2011 Zhao et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2011/0199046	A1	8/2011	Tsai et al.
2011/0215086	A1	9/2011	Yeh
2011/0221389	A1	9/2011	Won et al.
2011/0222272	A1	9/2011	Yeh
2011/0243050	A1	10/2011	Yanover
2011/0244913	A1	10/2011	Kim et al.
2011/0248573	A1	10/2011	Kanno et al.
2011/0248575	A1	10/2011	Kim et al.
2011/0254503	A1	10/2011	Widmer et al.
2011/0259953	A1	10/2011	Baarman et al.
2011/0273977	A1	11/2011	Shapira et al.
2011/0278941	A1	11/2011	Krishna et al.
2011/0279226	A1	11/2011	Chen et al.
2011/0281535	A1	11/2011	Low et al.
2011/0282415	A1	11/2011	Eckhoff et al.
2011/0286374	A1	11/2011	Shin et al.
2011/0302078	A1	12/2011	Failing
2011/0304216	A1	12/2011	Baarman
2011/0304437	A1	12/2011	Beeler
2012/0013196	A1	1/2012	Kim et al.
2012/0013198	A1	1/2012	Uramoto et al.
2012/0043887	A1	2/2012	Mesibov
2012/0051294	A1	3/2012	Guillouard
2012/0056741	A1	3/2012	Zhu et al.
2012/0231856	A1	3/2012	Lee et al.
2012/0080957	A1	4/2012	Cooper et al.
2012/0095617	A1	4/2012	Martin et al.
2012/0098350	A1	4/2012	Campanella et al.
2012/0098485	A1	4/2012	Kang et al.
2012/0099675	A1	4/2012	Kitamura et al.
2012/0104849	A1	5/2012	Jackson
2012/0105252	A1	5/2012	Wang
2012/0112532	A1	5/2012	Kesler et al.
2012/0119914	A1	5/2012	Uchida
2012/0132647	A1	5/2012	Beverly et al.
2012/0146426	A1	6/2012	Sabo
2012/0146576	A1	6/2012	Partovi
2012/0146577	A1	6/2012	Tanabe
2012/0147802	A1	6/2012	Ukita et al.
2012/0150670	A1	6/2012	Taylor et al.
2012/0157019	A1	6/2012	Li
2012/0161531	A1	6/2012	Kim et al.
2012/0161544	A1	6/2012	Kashiwagi et al.
2012/0169276	A1	7/2012	Wang
2012/0169278	A1	7/2012	Choi
2012/0173418	A1	7/2012	Beardsmore et al.
2012/0181973	A1	7/2012	Lyden
2012/0182427	A1	7/2012	Marshall
2012/0193999	A1	8/2012	Zeine
2012/0212072	A1	8/2012	Miyabayashi et al.
2012/0214536	A1	8/2012	Kim et al.
2012/0248886	A1	10/2012	Kesler et al.
2012/0248891	A1	10/2012	Drennen
2012/0267900	A1	10/2012	Huffman et al.
2012/0274154	A1	11/2012	DeLuca
2012/0292993	A1	11/2012	Mettler et al.
2012/0293021	A1	11/2012	Teggatz et al.
2012/0293119	A1	11/2012	Park et al.
2012/0299540	A1	11/2012	Perry
2012/0299541	A1	11/2012	Perry
2012/0299542	A1	11/2012	Perry
2012/0300588	A1	11/2012	Perry
2012/0300592	A1	11/2012	Perry
2012/0300593	A1	11/2012	Perry
2012/0306705	A1	12/2012	Sakurai et al.
2012/0309332	A1	12/2012	Liao
2012/0313449	A1	12/2012	Kurs
2012/0326660	A1	12/2012	Lu et al.
2013/0024059	A1	1/2013	Miller et al.
2013/0026982	A1	1/2013	Rothenbaum
2013/0038124	A1	2/2013	Newdoll et al.
2013/0038402	A1	2/2013	Karalis et al.
2013/0049471	A1	2/2013	Oleynik
2013/0057078	A1	3/2013	Lee
2013/0057205	A1	3/2013	Lee et al.
2013/0057210	A1	3/2013	Negaard et al.
2013/0057364	A1	3/2013	Kesler et al.
2013/0063143	A1	3/2013	Adalsteinsson et al.
2013/0069444	A1	3/2013	Waffenschmidt et al.
2013/0078918	A1	3/2013	Crowley et al.
2013/0082651	A1	4/2013	Park et al.
2013/0088090	A1	4/2013	Wu
2013/0088192	A1	4/2013	Eaton
2013/0088331	A1	4/2013	Cho
2013/0093388	A1	4/2013	Partovi
2013/0099389	A1	4/2013	Hong et al.
2013/0099586	A1	4/2013	Kato
2013/0106197	A1	5/2013	Bae et al.
2013/0119929	A1	5/2013	Partovi
2013/0120217	A1	5/2013	Ueda et al.
2013/0132010	A1	5/2013	Winger et al.
2013/0134923	A1	5/2013	Smith
2013/0137455	A1	5/2013	Xia
2013/0148341	A1	6/2013	Williams
2013/0149975	A1	6/2013	Yu et al.
2013/0154387	A1	6/2013	Lee et al.
2013/0157729	A1	6/2013	Tabe
2013/0169061	A1	7/2013	Miroshnichenko et al.
2013/0169219	A1	7/2013	Gray
2013/0169348	A1	7/2013	Shi
2013/0171939	A1	7/2013	Tian et al.
2013/0181881	A1	7/2013	Christie et al.
2013/0207604	A1	8/2013	Zeine
2013/0210357	A1	8/2013	Qin et al.
2013/0234536	A1	9/2013	Chemishkian et al.
2013/0241468	A1	9/2013	Moshfeghi
2013/0241474	A1	9/2013	Moshfeghi
2013/0249478	A1	9/2013	Hirano
2013/0254578	A1	9/2013	Huang
2013/0264997	A1	10/2013	Lee et al.
2013/0285606	A1	10/2013	Ben-Shalom et al.
2013/0288600	A1	10/2013	Kuusilinna et al.
2013/0310020	A1	11/2013	Kazuhiro
2013/0328417	A1	12/2013	Takeuchi
2013/0334883	A1	12/2013	Kim et al.
2013/0343251	A1	12/2013	Zhang
2014/0001846	A1	1/2014	Mosebrook
2014/0001875	A1	1/2014	Nahidipour
2014/0001876	A1	1/2014	Fujiwara et al.
2014/0006017	A1	1/2014	Sen
2014/0008992	A1	1/2014	Leabman
2014/0008993	A1	1/2014	Leabman
2014/0009108	A1	1/2014	Leabman
2014/0009110	A1	1/2014	Lee
2014/0011531	A1	1/2014	Burstrom et al.
2014/0015344	A1	1/2014	Mohamadi
2014/0021908	A1	1/2014	McCool
2014/0035524	A1	2/2014	Zeine
2014/0049422	A1	2/2014	Von Novak et al.
2014/0055098	A1	2/2014	Lee et al.
2014/0062395	A1	3/2014	Kwon et al.
2014/0091968	A1	4/2014	Harel et al.
2014/0113689	A1	4/2014	Lee
2014/0118140	A1	5/2014	Amis
2014/0132210	A1	5/2014	Partovi
2014/0139034	A1	5/2014	Sankar et al.
2014/0139039	A1	5/2014	Cook et al.
2014/0139180	A1	5/2014	Kim et al.
2014/0141838	A1	5/2014	Cai et al.
2014/0142876	A1	5/2014	John et al.
2014/0143933	A1	5/2014	Low et al.
2014/0159651	A1	6/2014	Von Novak et al.
2014/0159652	A1	6/2014	Hall et al.
2014/0159667	A1	6/2014	Kim et al.
2014/0175893	A1	6/2014	Sengupta et al.
2014/0177399	A1	6/2014	Teng et al.
2014/0184148	A1	7/2014	Van Der Lee et al.
2014/0184163	A1	7/2014	Das et al.
2014/0184170	A1	7/2014	Jeong
2014/0194092	A1	7/2014	Wanstedt et al.
2014/0194095	A1	7/2014	Wanstedt et al.
2014/0206384	A1	7/2014	Kim et al.
2014/0210281	A1	7/2014	Ito et al.
2014/0217967	A1	8/2014	Zeine et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0225805	A1	8/2014	Pan et al.
2014/0239733	A1	8/2014	Mach et al.
2014/0241231	A1	8/2014	Zeine
2014/0252813	A1	9/2014	Lee et al.
2014/0252866	A1	9/2014	Walsh et al.
2014/0265725	A1	9/2014	Angle et al.
2014/0265727	A1	9/2014	Berte
2014/0265943	A1	9/2014	Angle et al.
2014/0266025	A1	9/2014	Jakubowski
2014/0273892	A1	9/2014	Nourbakhsh
2014/0281655	A1	9/2014	Angle et al.
2014/0312706	A1	10/2014	Fiorello et al.
2014/0327320	A1	11/2014	Muhs et al.
2014/0327390	A1	11/2014	Park et al.
2014/0346860	A1	11/2014	Aubry et al.
2014/0354063	A1	12/2014	Leabman et al.
2014/0354221	A1	12/2014	Leabman et al.
2014/0357309	A1	12/2014	Leabman et al.
2014/0368048	A1	12/2014	Leabman et al.
2014/0375253	A1	12/2014	Leabman et al.
2014/0375255	A1	12/2014	Leabman et al.
2015/0015180	A1	1/2015	Miller et al.
2015/0015182	A1	1/2015	Brandtman et al.
2015/0015194	A1	1/2015	Leabman et al.
2015/0015195	A1	1/2015	Leabman et al.
2015/0022010	A1	1/2015	Leabman et al.
2015/0023204	A1	1/2015	Wil et al.
2015/0028688	A1	1/2015	Masaoka
2015/0035715	A1	2/2015	Kim et al.
2015/0042265	A1	2/2015	Leabman et al.
2015/0044977	A1	2/2015	Ramasamy et al.
2015/0046526	A1	2/2015	Bush et al.
2015/0061404	A1	3/2015	Lamenza et al.
2015/0091520	A1	4/2015	Blum et al.
2015/0097663	A1	4/2015	Sloo et al.
2015/0102681	A1	4/2015	Leabman et al.
2015/0102769	A1	4/2015	Leabman et al.
2015/0115878	A1	4/2015	Park
2015/0123483	A1	5/2015	Leabman et al.
2015/0123496	A1	5/2015	Leabman et al.
2015/0130285	A1	5/2015	Leabman et al.
2015/0130293	A1	5/2015	Hajimiri et al.
2015/0155737	A1	6/2015	Mayo
2015/0155738	A1	6/2015	Leabman et al.
2015/0162751	A1	6/2015	Leabman et al.
2015/0162779	A1	6/2015	Lee et al.
2015/0171656	A1	6/2015	Leabman et al.
2015/0171931	A1	6/2015	Won et al.
2015/0188352	A1	7/2015	Peek et al.
2015/0199665	A1	7/2015	Chu
2015/0207333	A1	7/2015	Baarman et al.
2015/0222126	A1	8/2015	Leabman et al.
2015/0236520	A1	8/2015	Baarman
2015/0244187	A1	8/2015	Horie
2015/0244201	A1	8/2015	Chu
2015/0249484	A1	9/2015	Mach et al.
2015/0255989	A1	9/2015	Walley et al.
2015/0263534	A1	9/2015	Lee et al.
2015/0263548	A1	9/2015	Cooper et al.
2015/0270741	A1	9/2015	Leabman et al.
2015/0288438	A1	10/2015	Maltsev et al.
2015/0318729	A1	11/2015	Leabman
2015/0326063	A1	11/2015	Leabman et al.
2015/0326068	A1	11/2015	Bell et al.
2015/0333528	A1	11/2015	Leabman
2015/0333529	A1	11/2015	Leabman
2015/0333573	A1	11/2015	Leabman
2015/0340759	A1	11/2015	Bridgelall et al.
2015/0340903	A1	11/2015	Bell et al.
2015/0340909	A1	11/2015	Bell et al.
2015/0340911	A1	11/2015	Bell et al.
2015/0341087	A1	11/2015	Moore et al.
2015/0365138	A1	12/2015	Miller et al.
2016/0005068	A1	1/2016	Im et al.
2016/0012695	A1	1/2016	Bell et al.
2016/0013656	A1	1/2016	Bell et al.
2016/0013677	A1	1/2016	Bell et al.
2016/0013855	A1	1/2016	Campos et al.
2016/0020636	A1	1/2016	Khlat
2016/0020649	A1	1/2016	Bell et al.
2016/0020830	A1	1/2016	Bell et al.
2016/0042206	A1	2/2016	Pesavento et al.
2016/0056640	A1	2/2016	Mao
2016/0065005	A1	3/2016	Won et al.
2016/0079799	A1	3/2016	Khlat
2016/0094092	A1	3/2016	Davlantes et al.
2016/0126752	A1	5/2016	Vuori et al.
2016/0126776	A1	5/2016	Kim et al.
2016/0141908	A1	5/2016	Jakl et al.
2016/0164563	A1	6/2016	Khawand et al.
2016/0191121	A1	6/2016	Bell
2016/0204622	A1	7/2016	Leabman
2016/0204642	A1	7/2016	Oh
2016/0238365	A1	8/2016	Wixey et al.
2016/0299210	A1	10/2016	Zeine
2016/0323000	A1	11/2016	Liu et al.
2016/0336804	A1	11/2016	Son et al.
2016/0339258	A1	11/2016	Perryman et al.
2016/0359367	A1	12/2016	Rothschild
2017/0005516	A9	1/2017	Leabman et al.
2017/0005530	A1	1/2017	Zeine et al.
2017/0025903	A1	1/2017	Song et al.
2017/0026087	A1	1/2017	Tanabe
2017/0043675	A1	2/2017	Jones et al.
2017/0047784	A1	2/2017	Jung et al.
2017/0085120	A1	3/2017	Leabman et al.
2017/0085437	A1	3/2017	Condeixa et al.
2017/0092115	A1	3/2017	Sloo et al.
2017/0163076	A1	6/2017	Park et al.

FOREIGN PATENT DOCUMENTS

EP	1028482	A2	8/2000
EP	1081506	A1	3/2001
EP	2346136	A1	7/2011
EP	2545635	A2	1/2013
JP	2006157586	A	6/2006
JP	2007043432	A	2/2007
JP	2008167017	A	7/2008
KR	20060061776	A	6/2006
KR	100755144	B1	9/2007
KR	20110132059	A	12/2011
KR	20110135540	A1	12/2011
KR	20120108759	A	10/2012
KR	1020130026977	A	3/2013
WO	9952173	A2	10/1999
WO	WO 200111716	A1	2/2001
WO	2004077550	A1	9/2004
WO	2003091943	A1	11/2006
WO	WO 2006122783	A2	11/2006
WO	2008156571	A2	12/2008
WO	2010022181	A1	2/2010
WO	2011112022	A2	9/2011
WO	WO 2012177283	A1	12/2012
WO	2013035190	A1	3/2013
WO	WO 2013052950	A1	4/2013
WO	WO 2013105920	A2	7/2013
WO	WO 2015097809	A1	7/2015
WO	WO 2015161323	A1	10/2015
WO	WO 2016048512	A1	3/2016
WO	WO 2016187357	A1	11/2016

OTHER PUBLICATIONS

International Search Report dated Oct. 16, 2014 corresponding to International Patent Application No. PCT/US2014/041546, 4 pages.
International Search Report dated Oct. 13, 2014 corresponding to International Patent Application No. PCT/US2014/041534, 4 pages.
International Search Report dated Nov. 12, 2014 corresponding to International Patent Application No. PCT/US2014/046956, 4 pages.
Written Opinion of the International Searching Authority dated Nov. 12, 2014 corresponding to International Patent Application No. PCT/US2014/046956, 6 pages.

(56) **References Cited**

OTHER PUBLICATIONS

International Search Report dated Sep. 12, 2014 corresponding to International Patent Application No. PCT/US2014/037072, 3 pages.
Energous Corp., Written Opinion, PCT/US2014/037170 , dated Sep. 15, 2014, 7 pgs.
Energous Corp., IPRP, PCT/US2014/037170, dated Nov. 10, 2015, 8 pgs.
Energous Corp., Written Opinion, PCT/US2014/041534, dated Oct. 13, 2014, 6 pgs.
Energous Corp., IPRP, PCT/US2014/041534, dated Dec. 29, 2015, 7 pgs.
Energous Corp., IPRP, PCT/US2014/041546, dated Oct. 16, 2014, 12 pgs.
Energous Corp., ISRWO, PCT/US2015/067242, dated Mar. 15, 2016, 9 pgs.
Energous Corp., ISRWO, PCT/US2014/041342, dated Jan. 27, 2015, 10 pgs.
Energous Corp., IPRP, PCT/US2014/041342, dated Dec. 15, 2015, 8 pgs.
Energous Corp., ISRWO, PCT/US2014/046941, dated Nov. 6, 2014, 11 pgs.
Energous Corp., IPRP, PCT/US2014/046941, dated Jan. 19, 2016, 9 pgs.
Energous Corp., ISRWO, PCT/US2014/062661, dated Jan. 27, 2015, 9 pgs.
Energous Corp., IPRP, PCT/US2014/062661, dated May 3, 2016, 10 pgs.
Supplementry European Search Report, EP Patent Application No. EP14818136-5, dated Jul. 21, 2016, 9 pgs.
L.H. Hsieh et al. Development of a Retrodirective Wireless Microwave Power Transmission System, IEEE, 2003 pp. 393-396.
B.D. Van Veen et al., Beamforming: A Versatile Approach to Spatial Filtering, IEEE, ASSP Magazine, Apr. 1988, pp. 4-24.
Leabman, Adaptive Band-Partitioning for Interference Cancellation in Communication System, Thesis Massachusetts Institute of Technology, Feb. 1997, pp. 1-70.
Panda, SIW based Slot Array Antenna and Power Management Circuit for Wireless Energy Harvesting Applications, IEEE APSURSI, Jul. 2012, 2 pgs.
Singh, Wireless Power Tranfer Using Metamaterial Bonded Micro strip Antenna for Smart Grid WSN: In Fourth International Conference on Advances in Computing and Communications (ICACC), Aug. 27-29, 2014, Abstract 299.
T. Gill et al. "A System for Change Detection and Human Recognition in Voxel Space using the Microsoft Kinect Sensor," 2011 IEEE Applied Imagery Pattern Recognition Workshop. 8 pgs.
J. Han et al. Enhanced Computer Vision with Microsoft Kinect Sensor: A Review, IEEE Transactions on Cybernetics vol. 43, No. 5. pp. 1318-1334.
Energous Corp., IPRP, PCT/US2014/046956, dated Jan. 19, 2016, 7 pgs.
Energous Corp., Written Opinion, PCT/US2014/037072, dated Sep. 12, 2014, 5 pgs.
Energous Corp., IPRP, PCT/US2014/037072, dated Nov. 10, 2015, 6 pgs.
Energous Corp., IPRP, PCT/US2015/067291, dated Jul. 4, 2017, 4 pgs.
Energous Corp., IPRP, PCT/US2015/067242, dated Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067243, dated Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067275, dated Jul. 4, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067245, dated Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2014/041546, dated Dec. 29, 2015, 9 pgs.
Energous Corp., IPRP, PCT/US2015/67250, dated Mar. 30, 2016, 10 pgs.
Energous Corp., IPRP, PCT/US2015/067325, dated Jul. 4, 2017, 8 pgs.
Energous Corp., IPRP, PCT/US2015/067249, dated Jun. 27, 2017, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067246, dated Jun. 27, 2017, 9 pgs.
Energous Corp., IPRP, PCT/US2015/067279, dated Jul. 4, 2017, 7 pgs.
Energous Corp., ISRWO, PCT/US2014/059871, dated Jan. 23, 2015, 12 pgs.
Energous Corp., IPRP, PCT/US2014/059871, dated Apr. 12, 2016, 9 pgs.
Energous Corp., ISRWO, PCT/US2014/045102, dated Oct. 28, 2014, 14 pgs.
Energous Corp., IPRP, PCT/US2014/045102, dated Jan. 12, 2016, 11 pgs.
Energous Corp., ISRWO, PCT/US2014/059340, dated Jan. 15, 2015, 13 pgs.
Energous Corp., IPRP, PCT/US2014/059340, dated Apr. 12, 2016, 11 pgs.
Energous Corp., ISRWO, PCT/US2015/067282, dated Jul. 5, 2016, 7 pgs.
Energous Corp., IPRP, PCT/US2015/067282, dated Jul. 4, 2017, 6 pgs.
Energous Corp., ISRWO, PCT/US2014/041558, dated Oct. 10, 2014, 8 pgs.
Energous Corp., IPRP, PCT/US2014/041558, dated Dec. 29, 2015, 6 pgs.
Energous Corp., ISRWO, PCT/US2014/045119, dated Oct. 13, 2014, 11 pgs.
Energous Corp., IPRP, PCT/US2014/045119, dated Jan. 12, 2016, 9 pgs.
Energous Corp., ISRWO PCT/US2014/045237, dated Oct. 13, 2014, 16 pgs.
Energous Corp., IPRP , PCT/US2014/045237, dated Jan. 12, 2016, 12 pgs.
Energous Corp., ISRWO , PCT/US2014/054897, dated Feb. 17, 2015, 10 pgs.
Energous Corp., IPRP , PCT/US2014/054897, dated Mar. 15, 2016, 8 pgs.
Energous Corp., ISRWO , PCT/US2015/067334, dated Mar. 3, 2016, 6 pgs.
Energous Corp., IPRP , PCT/US2015/067334, dated Jul. 4, 2017, 5 pgs.
Energous Corp., ISRWO , PCT/US2014/047963, dated Nov. 7, 2014, 13 pgs.
Energous Corp., IPRP , PCT/US2014/047963, dated Jan. 26, 2016, 10 pgs.
Energous Corp., ISRWO , PCT/US2014/054891, dated Dec. 18, 2014, 12 pgs.
Energous Corp., IPRP , PCT/US2014/054891, dated Mar. 15, 2016, 10 pgs.
Energous Corp., ISRWO , PCT/US2014/054953, dated Dec. 4, 2014, 7 pgs.
Energous Corp., IPRP , PCT/US2014/054953, dated Mar. 22, 2016, 5 pgs.
Energous Corp., ISRWO , PCT/US2015/067294, dated Mar. 29, 2016, 7 pgs.
Energous Corp., IPRP , PCT/US2015/067294, dated Jul. 4, 2017, 6 pgs.
Energous Corp.,ISRWO , PCT/US2014/062672 dated Jan. 15, 2015, 11 pgs.
Energous Corp., IPRP , PCT/US2014/062672 dated May 10, 2016, 8 pgs.
Energous Corp., ISRWO , PCT/US2014/044810 dated Oct. 21, 2014, 12 pgs.
Energous Corp., IPRP , PCT/US2014/044810, dated Jan. 5, 2016, 10 pgs.
Energous Corp., ISRWO , PCT/US2015/067271, dated Mar. 11, 2016, 6 pgs.
Energous Corp., IPRP , PCT/US2015/067271, dated Jul. 4, 2017, 5 pgs.

(56) **References Cited**

OTHER PUBLICATIONS

Energous Corp., ISRWO , PCT/US2014/040648, dated Oct. 10, 2014, 11 pgs.
Energous Corp., IPRP , PCT/US2014/040648, dated Dec. 8, 2015, 8 pgs.
Energous Corp., ISRWO , PCT/US2014/049673, dated Nov. 18, 2014, 10 pgs.
Energous Corp., IPRP , PCT/US2014/049673, dated Feb. 9, 2016, 6 pgs.
Energous Corp., ISRWO , PCT/US2014/068282, dated Mar. 19, 2015, 13 pgs.
Energous Corp., IPRP, PCT/US2014/068282, dated Jun. 7, 2016, 10 pgs.
Energous Corp., ISRWO, PCT/US2014/068586, dated Mar. 20, 2015, 11 pgs.
Energous Corp., IPRP, PCT/US2014/068586, dated Jun. 14, 2016, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068504, dated Mar. 30, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068495, dated Mar. 30, 2017, 9 pgs.
Energous Corp., IPRP, PCT/US2015/067287, dated Jul. 4, 2017, 6 pgs.
Energous Corp., ISRWO, PCT/US2016/068551, dated Mar. 17, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068498, dated May 17, 2017, 8 pgs.
Energous Corp., ISRWO, PCT/US2016/068993, dated Mar. 13, 2017, 12 pgs.
Energous Corp., ISRWO, PCT/US2016/068565, dated Mar. 8, 2017, 11 pgs.
Energous Corp., ISRWO, PCT/US2016/068987, dated May 8, 2017, 10 pgs.
Energous Corp., ISRWO, PCT/US2016/069316 , dated Mar. 16, 2017, 15 pgs.
European Search Report, EP Patent Application No. EP16189052.0, dated Jan. 31, 2017, 11 pgs.
European Search Report, EP Patent Application No. EP16189319-3, dated Feb. 1, 2017, 9 pgs.
European Search Report, EP Patent Application No. EP14822971, dated Feb. 1, 2017, 9 pgs.
European Search Report, EP Patent Application No. EP16189987, dated Feb. 1, 2017, 8 pgs.
European Search Report, EP Patent Application No. 16196205.5, dated Mar. 28, 2017.
European Search Report, EP Patent Application No. 16189300, dated Feb. 28, 2017, 4 pgs.
European Search Report, EP Patent Application No. 16189988.5, dated Mar. 1, 2017, 4 pgs.
European Search Report, EP Patent Application No. 16189982.5, dated Jan. 27, 2017, 9 pgs.
European Search Report, EP Patent Application No. 16189974, dated Mar. 2, 2017, 5 pgs.
European Search Report, EP Patent Application No. 16193743, dated Feb. 2, 2017, 5 pgs.
European Search Report, EP Patent Application No. 14868901.1, dated Jul. 7, 2017, 5 pgs.
Zhai, "A Practical wireless charging system based on ultra-wideband retro-reflective beamforming" 2010 IEEE Antennas and Propagation Society International Symposium, Toronto, ON 2010, pp. 1-4.
Mao: BeamStar: An Edge-Based Approach to Routing in Wireless Sensors Networks, IEEE Transactions on Mobile Computing, IEEE Service Center, Los Alamitos, CA US, vol. 6, No. 11, Nov. 1, 2007, 13 pgs.
Smolders—Institute of Electrical 1-15 and Electronics Engineers: "Broadband microstrip array antennas" Digest of the Antennas and Propagation Society International Symposium. Seattle, WA Jun. 19-24, 1994. Abstract.
Paolo Nenzi et al; "U-Helix: On-chip short conical antenna", 2013 7th European Conference on Antennas and Propagation (EUCAP), ISBN:978-1-4673-2187-7, IEEE, Apr. 8, 2013, 5 pgs.
Adamiuk G et al; "Compact, Dual-Polarized UWB-Antanna, Embedded in a Dielectric" IEEE Transactions on Antenna and Propagation, IEEE Service Center, Piscataway, NJ, US vol. 56, No. 2, ISSN: 0018-926X, abstract; Figure 1, Feb. 1, 2010, 8 pgs.
Mascarenas et al.; "Experimental Studies of Using Wireless Energy Transmission for Powering Embedded Sensor Nodes." Nov. 28, 2009, Journal of Sound and Vibration, pp. 2421-2433.

* cited by examiner

FIG. 1


100
101
102
112
104
101b
107b
103b
105b
107a
1010a
111
107c
1010c
103a
105a


RX and TX establish a connection 201
TX computes RF wave features to form energy pocket 203
TX transmits RF waves to form energy pocket 205
RX receives RF waves, rectifies energy, converts energy to DC, and charges device 207
RX determines and transmits charging data to TX 2010
TX calibrates antennas transmitting the RF waves based on data from RX 211

FIG. 2


BAT
or
CAP
I²C
326
d
cover
326
DC
Capacitor
Battery
Battery
Capacitor
332
Electronic Device
5/10V
324
326
DC
2-10V
3210
Wearable
320
342
306
306
306
306
312
3010
3010
302
340
SPI
I²C
I²C/SPI
310

FIG. 3


400
406
ANTENNA
ANTENNA
412
RFIC
MICROCONTROLLER
414
POWER
408
410
402
442
420
430
444
446
Antenna
Rectifier
Converter
Battery
424
426
428

FIG. 4


RX and TX establish a connection 501
TX establishes connection to RX 503
RX measures and transmits voltage data 505
TX Determines Power Transmission Signals 507
TX Configures Antennas 509
TX connects to second RX 511
TX reconfigures subset of antenna array for second RX 513
TX Reexamines First RX 515
TX Continues to add RXs, as detected, and alternates communication with RXs 517

FIG. 5



FIG. 6A



FIG. 6B



FIG. 7



FIG. 8


900B
902B
942B
920B
944B

FIG. 9B


900A
944A
944A
920A
902A
944A
944A
942A

FIG. 9A


1002A
1042A
1042A
1020A
1020A
1060A
1000A
1007A
1062A
1052A

FIG. 10A



FIG. 10B


1100
1132
1134
1136
Computing Device
WPM Software
USER
1102
1108
1118
PWR TX MGR APP
Device Database
1110
Third Party API (BTLE)
1112
BTLE CHIP HW
1114
Antenna MGR Software
1116
Antenna Array
1128
1120
1138
1122
PWR RX APP
Third Party API (BTLE)
BTLE CHIP HW
GUI
1130
Antenna Array
1126
Client Device
1124
1120
1128
PWR RX APP
Third Party API (BTLE)
BTLE CHIP HW
Antenna Array
Client Device
GUI
1130
1104
1106

FIGURE 11


1200
USER
1202
Wireless Power Manager (GUI)
1204
PWR TX MGRm
1208
PWR TX MGR m+1
1208
PWR RX APP
1206
ID SYS PSW
Database Records
1210
1212
Display Results
1214
Schedule
1216
Time
1218
Client Type
1220
Physical Location
1222
Messages
1224
Send Modified Database Records
1226
Share Updated Records with other Transmitters
1228
Send Command or Perform Action on Receivers
1230

FIGURE 12


1300
1316
Device Database
1302
1314
Power Transmitter Manager
Antenna Manager Software
BTLE
1308
1310
BTLE
1304
GUI
1312
Customer Device
Power Receiver
1306

FIGURE 13


1400
1402
1404
1406
1408
1410
1412
1414
1416
1418
1420
1422
1424
GUI
Customer Device
Power Receiver
Power Transmitter Manager 1
Power Transmitter Manager 2
Power Transmitter Manager n
Device Database
Device Database
Device Database
Cloud
Internet Cloud
Cloud
Business Cloud
Server
Server

FIGURE 14


1500
Start
1502
Wireless Power Transmitter Manager Scans the Network
1504
No
Wireless Power Transmitter Manager Detects a Failure
Yes
1514
1506
Wireless Power Transmitter Manager Updates Device Database
1508
Wireless Power Transmitter Manager Analyzes the Failure
1510
Wireless Power Transmitter Manager Generates a Recommendation
1512
Wireless Power Transmitter Manager Sends Recommendation
End

FIGURE 15


1600
1602
Multiple Wireless Power Transmission System
1604
Remote Information Service
1606
Internet Cloud
1608
1610
Power Receiver
1612
System Management Service
1614
Network
1616
Power Transmitter Manager
1618
Device Database
1620
GUI
Computing Device
1622
Server
1624
Remote Information Service Manager
1626
Remote Information Service Database
1628
User 1
User 2
User n
1630
GUI
1632
Non-Computing Device
1634
Server
1636
System Management Manager
1638
Devices Database
Power Transmitter 1
Power Transmitter 2
Power Transmitter N

FIGURE 16


1700
START
1702
Connect to WPTS
1704
Interact with the WPTS Interface
1706
System Information Generator Establishes Communication with a Remote Information Service
1708
Valid Credentials?
No
Yes
1710
System Information Generator Transmit the Information
1712
Stores the System Information Record into a Distributed System Database
1714
Remote Information Service Receives the Information
1716
Replies an Acknowledge Message to System Information Generator
1718
System Information Generator Deletes the Record from the Distributed System Database
1720
Client Computing Device Download the Information Coming from the Remote Information Service
1722
Client Computing Device Reports and/or, Edits the Information
END

FIGURE 17


System Architecture
1800
1802
PWR TX MGR APP
Third Party API (BTLE)
BTLE CHIP HW
1810
1812
1814
1816
Antenna MGR Software
1818
1820
PWR RX APP
Third Party API (BTLE)
BTLE CHIP HW
1812
1814
GUI
1808
1820
1822
1822
1822
PWR RX APP
Third Party API (BTLE)
BTLE CHIP HW
1814
1804
GUI
1806

FIGURE 18


1900
1902
1904
1906
1908
1910
1912
1914
1916
1918
1920
1922
1924
1926
1928
Server
Business Cloud
Remote System Manager
General Database
Internet Cloud
Network
Device Database
Power Transmitter Manager
Power Transmitter 1
Power Transmitter 2
Power Transmitter N
Power Receiver
GUI
Electronic Device

FIGURE 19


2000
START
2002
Past Status Report
2004
Check System
2006
Present Status Report
2008
Future Status Report
2010
Alert Needed?
No
Yes
2012
Send Alert
2014
Update Database
2016
Send Reports
2018
Receive Feedback
END

FIGURE 20


2100
START
2102
Generate Non-End-User Report
2104
Generate Logged Usage Report
2106
Generate Automatic Actions Report
2108
Generate Location and Movements Report
2110
Update Database
2112
Send Reports
2114
Receive Feedback
END

FIGURE 21


2200
START
System Functioning Report
2202
Online Users Report
2204
System Configuration Report
2206
Check State of Charge of Devices
2208
2210
Device in Need of Charge ?
No
Yes
2214
2212
Generate Alert
Update Database
Send Reports
2216
2218
END
Receive Feedback

FIGURE 22


2300
START
2302
Component Failure Forecast
2304
Device State of Charge Forecast
2306
System Configuration Analysis
2308
Problem Found?
No
Yes
2312
Generate Alert
Update Database
2310
2314
Send Reports
END
Receive Feedback
2318

FIGURE 23


2400
Database
2410
Web Service Software
2412
2402
Server
2416
Internet Cloud
2408
Status and Usage Information
2414
2406
2406
2406
Operator 1
Operator 2
Operator N

FIGURE 24


2500
2501
01 GLOBAL STATISTICS
Location
Devices
Devices Charging
Energy Received (Daily)
Energy Received (All time)
Transactions
Transactions Active
Energy Transmitted (Daily)
Energy Transmitted (All time)
POWER TRANSMITTED
POWER ON THE GO
DASHBOARD
DEVICES
LOCATIONS
TRANSACTIONS
ACCOUNTS
SETTINGS
WELCOME
Wattup

FIGURE 25

2600



FIGURE 26


2700
WattUp
DASHBOARD
DEVICES
LOCATIONS
TRANSMITTERS
ACCOUNTS
SETTINGS
WELCOME
everyone_demo
02 USAGE STATISTICS
Here's what your WattUp enabled devices have been up to in the past
IN THE PAST 5 DAYS
POWER RECEIVED
POWER TRANSMITTED
POWER ON THE GO
Energy Received
Energy Transmitted
Peak Incoming energy
Peak Outgoing energy
Devices Charged
2701
03 POWER UP HISTORY
Here's a record of where your devices have charged up recently

FIGURE 27

2800

FIGURE 28

FIGURE 29

2900
12:30
CURRENTLY CHARGING
Water Avenue Coffee
22%
Charged
Charge Strength:
STOP CHARGING

FIGURE 30


3000
12:30
97214
MAP
LIST
SE Alder St
SE Belmont St
SE Yamhill St
SE Taylor St
Water Avenue Coffee
SE Main St
SE Madison St
SE Hawthorne Blvd

3100



FIGURE 31


3200
WattUp
DASHBOARD
ACCOUNTS
ORGANIZATIONS
DEVICES
TRANSMITTERS
FIND LOCATION
SETTINGS
Main Locations
Secondary Locations
Satellite Locations
3201

FIGURE 32

SYSTEM AND METHODS FOR USING A REMOTE SERVER TO AUTHORIZE A RECEIVING DEVICE THAT HAS REQUESTED WIRELESS POWER AND TO DETERMINE WHETHER ANOTHER RECEIVING DEVICE SHOULD REQUEST WIRELESS POWER IN A WIRELESS POWER TRANSMISSION SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part of U.S. Non-Provisional patent application Ser. No. 14/337,002, filed Jul. 21, 2014, entitled "Systems and Methods for Communication with Remote Management Systems," which is herein fully incorporated by reference in its entirety.

This application relates to U.S. Non-Provisional patent application Ser. No. 13/891,430, filed May 10, 2013, entitled "Methodology For Pocket-forming;" U.S. Non-Provisional patent application Ser. No. 13/925,469, filed Jun. 24, 2013, entitled "Methodology for Multiple Pocket-Forming;" U.S. Non-Provisional patent application Ser. No. 13/946,082, filed Jul. 19, 2013, entitled "Method for 3 Dimensional Pocket-forming;" U.S. Non-Provisional patent application Ser. No. 13/891,399, filed May 10, 2013, entitled "Receivers for Wireless Power Transmission;" U.S. Non-Provisional patent application Ser. No. 13/891,445, filed May 10, 2013, entitled "Transmitters for Wireless Power Transmission;" U.S. Non-Provisional patent application Ser. No. 14/465,532, filed Aug. 21, 2014, entitled "Systems and Methods for Tracking the Status and Usage Information of a Wireless Power Transmission System," U.S. Non-Provisional patent application Ser. No. 14/286,129, filed May 23, 2014, entitled "System & Method for a Self-System Analysis in a Wireless Power Transmission Network," U.S. Non-Provisional patent application Ser. No. 14/272,039, filed May 7, 2014, entitled "Systems and Method For Wireless Transmission of Power," U.S. Non-Provisional patent application Ser. No. 14/272,066, filed May 7, 2014, entitled "Systems and Methods for Managing and Controlling a Wireless Power Network," U.S. Non-Provisional patent application Ser. No. 14/272,124, filed May 7, 2014, entitled "System and Method for Controlling Communication Between Wireless Power Transmitter Managers;" U.S. Non-Provisional patent application Ser. No. 14/583,625, filed Dec. 27, 2014, entitled "Receivers for Wireless Power Transmission," U.S. Non-Provisional patent application Ser. No. 14/583,630, filed Dec. 27, 2014, entitled "Methodology for Pocket-Forming," U.S. Non-Provisional patent application Ser. No. 14/583,634, filed Dec. 27, 2014, entitled "Transmitters for Wireless Power Transmission," U.S. Non-Provisional patent application Ser. No. 14/583,640, filed Dec. 27, 2014, entitled "Methodology for Multiple Pocket-Forming," U.S. Non-Provisional patent application Ser. No. 14/583,641, filed Dec. 27, 2014, entitled "Wireless Power Transmission with Selective Range," U.S. Non-Provisional patent application Ser. No. 14/583,643, filed Dec. 27, 2014, entitled "Method for 3 Dimensional Pocket-Forming," all of which are incorporated herein by reference in their entirety.

TECHNICAL FIELD

The present disclosure relates generally to wireless power transmission.

BACKGROUND

Portable electronic devices such as smart phones, tablets, notebooks and other electronic devices have become an

everyday need in the way we communicate and interact with others. The frequent use of these devices may require a significant amount of power, which may easily deplete the batteries attached to these devices. Therefore, a user is frequently needed to plug in the device to a power source, and recharge such device. This may require having to charge electronic equipment at least once a day, or in high-demand electronic devices more than once a day.

Such an activity may be tedious and may represent a burden to users. For example, a user may be required to carry chargers in case his electronic equipment is lacking power. In addition, users have to find available power sources to connect to. Lastly, users must plugin to a wall or other power supply to be able to charge his or her electronic device. However, such an activity may render electronic devices inoperable during charging.

Current solutions to this problem may include devices having rechargeable batteries. However, the aforementioned approach requires a user to carry around extra batteries, and also make sure that the extra set of batteries is charged. Solar-powered battery chargers are also known, however, solar cells are expensive, and a large array of solar cells may be required to charge a battery of any significant capacity. Other approaches involve a mat or pad that allows charging of a device without physically connecting a plug of the device to an electrical outlet, by using electromagnetic signals. In this case, the device still requires to be placed in a certain location for a period of time in order to be charged. Assuming a single source power transmission of electromagnetic (EM) signal, an EM signal gets reduced by a factor proportional to 1/r2 in magnitude over a distance r, in other words, it is attenuated proportional to the square of the distance. Thus, the received power at a large distance from the EM transmitter is a small fraction of the power transmitted. To increase the power of the received signal, the transmission power would have to be boosted. Assuming that the transmitted signal has an efficient reception at three centimeters from the EM transmitter, receiving the same signal power over a useful distance of three meters would entail boosting the transmitted power by 10,000 times. Such power transmission is wasteful, as most of the energy would be transmitted and not received by the intended devices, it could be hazardous to living tissue, it would most likely interfere with most electronic devices in the immediate vicinity, and it may be dissipated as heat.

In yet another approach such as directional power transmission, it would generally require knowing the location of the device to be able to point the signal in the right direction to enhance the power transmission efficiency. However, even when the device is located, efficient transmission is not guaranteed due to reflections and interference of objects in the path or vicinity of the receiving device.

Although the use of wireless power transmission may significantly solve the problem of using wires or pads for charging devices, when a device fails in the system, the power transfer to an electronic device may be interrupted. Different causes may exist for a failure, including a loss of power, a failure in the hardware or software of a wireless power transmitter manager, overload of the wireless power transmitter manager, and malfunction in a wireless power receiver, among others. Constant monitoring may be needed in the wireless power transmission system to avoid a breakdown in the network. For the foregoing reasons, there is a need for a system and method for a self-system analysis that may search problems in the network and when it detects a

problem, makes an analysis and at the same time makes a recommendation for enhancement or correction in the system.

SUMMARY

The embodiments described herein include a transmitter that transmits a power transmission signal (e.g., radio frequency (RF) signal waves) to create a three-dimensional pocket of energy. At least one receiver can be connected to or integrated into electronic devices and receive power from the pocket of energy. The transmitter can locate the at least one receiver in a three-dimensional space using a communication medium (e.g., Bluetooth technology). The transmitter generates a waveform to create a pocket of energy around each of the at least one receiver. The transmitter uses an algorithm to direct, focus, and control the waveform in three dimensions. The receiver can convert the transmission signals (e.g., RF signals) into electricity for powering an electronic device. Accordingly, the embodiments for wireless power transmission can allow powering and charging a plurality of electrical devices without wires.

A wireless power network may include wireless power transmitters each with an embedded wireless power transmitter manager. The wireless power transmitter manager may include a wireless power manager application, which may be a software application hosted in a computing device. The wireless power transmitter manager may include a GUI which may be used by a user to perform management tasks.

The wireless power network may include a plurality of client devices with wireless power receivers built in as part of the device or adapted externally. Wireless power receivers may include a power receiver application configured to communicate with the power transmitter manager application in a wireless power transmitter. The wireless power manager application may include a device database where information about the wireless power network may be stored.

In one embodiment, an apparatus for wirelessly providing power, comprises: a wireless power transmitter comprising a power transmitter manager, operatively coupled to the wireless power transmitter, wherein the power transmitter manager is configured to control power transmission signals to form three-dimensional pockets of energy for providing power from the wireless power transmitter to a receiver; a communication apparatus configured for communicating with a network; and a storage device operatively coupled to the wireless power transmission manager, the storage device being configured to store information for a device associated with the receiver that is registered with the network, and to communicate the information to a cloud.

In another embodiment, a method for wirelessly providing power in an apparatus, comprises: controlling, by a power transmitter manager of a wireless power transmitter, to form three-dimensional pockets of energy for providing power from the wireless power transmitter to a receiver; detecting, by the wireless power transmitter, a fault in at least one of the wireless power transmitter and the receiver; and transmitting, by a communication apparatus of the wireless power transmitter, the detected fault to a network.

In another embodiment, a system for wirelessly providing power, comprises: a server, communicatively coupled to each of a plurality of power sources via a network, wherein each of the power sources is configured to detect a fault in at least one of an associated wireless power transmitter and an associated receiver, the server being configured to receive at least one detected fault transmitted from the plurality of power sources, process the received detected fault, and provide a recommendation for correcting the received detected fault; wherein a respective one of the power sources comprises: the at least one associated wireless power transmitter; a power transmitter manager operatively coupled to the at least one associated wireless power transmitter, wherein the power transmitter manager is configured to control power transmission signals to form three-dimensional pockets of energy for providing power from the at least one associated wireless power transmitter to the associated receiver, and a communication apparatus configured for communicating with the network.

In a further embodiment, a processor-based system for managing a wireless power transmission system comprising at least one power transmitter, configured to generate pocket-forming energy in three dimensional space to at least one power receiver for charging, the processor-based system comprises: a processor; a database operatively coupled to the processor; and communications, operatively coupled to the processor, wherein the communications is operable to communicate with a network, wherein the processor is configured to receive system operation data from the at least one power transmitter via the network, wherein the system operation data comprises at least one of power transmitter status and power transmitter usage.

In another embodiment, A processor-based method for managing a wireless power transmission system comprising at least one power transmitter, configured to generate pocket-forming energy in three dimensional space to at least one power receiver for charging, the method comprises: configuring communications, operatively coupled to a processor and database, to communicate with a network; and receiving system operation data from the at least one power transmitter via the communications, wherein the system operation data comprises at least one of power transmitter status and power transmitter usage.

In a further embodiment, a processor-based system for managing a power system comprising at least one power transmitter, configured to generate pocket-forming energy in three dimensional space to at least one power receiver for charging, the processor-based system comprising: a processor; a database operatively coupled to the processor; and communications, operatively coupled to the processor, wherein the communications is operable to communicate with a network, that is further communicatively coupled to the at least one power transmitter configured with a wireless power transmitter manager, wherein the processor is configured to receive system operation data from the at least one power transmitter via the network, wherein the system operation data comprises at least one of power transmitter status and power transmitter usage.

In yet another embodiment, a wireless power transmission management system, comprises: at least one transmitter comprising an antenna array, the transmitter being configured to provide pocket-forming energy in three-dimensional space via the antenna array to at least one of a plurality of devices, the transmitter being further configured to communicate data to a network, wherein the data comprises at least one of transmitter data and device data; and a remote system manager operatively coupled to the network, wherein the remote system manager is configured to process the data communicated to the network to determine a status of the system.

In a further embodiment, a method for monitoring a wireless power system, comprises: providing, by a transmitter, pocket-forming energy in three-dimensional space to at least one of a plurality of devices, wherein the transmitter

is coupled to a respective antenna array; and communicating, by the transmitter, data from the transmitter to a network, the data comprising at least one of transmitter data and device data; wherein the data communicated to the network is processed in a remote system manager, operatively coupled to the network, to determine a status of the wireless power system.

In another embodiment, a wireless power transmission system for monitoring the distribution of pocket-forming energy in three-dimensional space, comprises: at least one transmitter, comprising: an antenna array, wherein the transmitter is configured to provide the pocket-forming energy in three-dimensional space via the antenna array to at least one of a plurality of devices, an antenna manager configured to control power and direction angle of the antenna array, a storage configured to receive and store data comprising at least one of transmitter data and device data, and communications configured to communicate the stored data to a network; wherein a remote system manager is operatively coupled to the network, the remote system manager being configured to receive and process communicated data to determine a status of the wireless power transmission system and perform an action in response to the determined status.

In a further embodiment, a processor-based system for managing a wireless power transmission system comprising at least one power transmitter, configured to generate pocket-forming energy in three dimensional space to at least one power receiver, the processor-based system comprises: a processor; a database operatively coupled to the processor; and communications, operatively coupled to the processor, wherein the communications is operable to communicate with a network, wherein the processor is configured to receive system operation data from the at least one power transmitter via the network and to communicate the system operation data to a cloud, wherein the system operation data comprises at least one of power transmitter status, power transmitter usage, power receiver status, and power receiver usage.

In another embodiment, a processor-based method for managing a wireless power transmission system comprising at least one power transmitter, configured to generate pocket-forming energy in three dimensional space to at least one power receiver for charging, the method comprises: configuring, by a processor, communications operatively coupled to the processor and a database, to communicate with a network; receiving, by the processor, system operation data from the at least one power transmitter via the communications, wherein the system operation data comprises at least one of power transmitter status, power transmitter usage, power receiver status, and power receiver usage; and communicating, by the processor, the received system operation data to a client device for display using a graphical user interface (GUI).

Additional features and advantages of an embodiment will be set forth in the description which follows, and in part will be apparent from the description. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the exemplary embodiments in the written description and claims hereof as well as the appended drawings.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting embodiments of the present disclosure are described by way of example with reference to the accompanying figures which are schematic and are not intended to be drawn to scale. Unless indicated as representing the background art, the figures represent aspects of the disclosure.

FIG. **1** illustrates a system overview, according to an exemplary embodiment.

FIG. **2** illustrates steps of wireless power transmission, according to an exemplary embodiment.

FIG. **3** illustrates an architecture for wireless power transmission, according to an exemplary embodiment.

FIG. **4** illustrates components of a system of wireless power transmission using pocket-forming procedures, according to an exemplary embodiment.

FIG. **5** illustrates steps of powering a plurality of receiver devices, according to an exemplary embodiment.

FIG. **6**A illustrates waveforms for wireless power transmission with selective range, which may get unified in single waveform.

FIG. **6**B illustrates waveforms for wireless power transmission with selective range, which may get unified in single waveform.

FIG. **7** illustrates wireless power transmission with selective range, where a plurality of pockets of energy may be generated along various radii from transmitter.

FIG. **8** illustrates wireless power transmission with selective range, where a plurality of pockets of energy may be generated along various radii from transmitter.

FIGS. **9**A and **9**B illustrate a diagram of an architecture for wirelessly charging client computing platform, according to an exemplary embodiment

FIG. **10**A illustrates wireless power transmission using multiple pocket-forming, according to an exemplary embodiment.

FIG. **10**B illustrates multiple adaptive pocket-forming, according to an exemplary embodiment.

FIG. **11** illustrates an exemplary embodiment of a wireless power network including a transmitter an wireless receivers.

FIG. **12** shows a sequence diagram of real time communication between wireless power transmitters, wireless power receivers, a wireless power manager UI and a user, according to an embodiment.

FIG. **13** shows a wireless power system using a wireless power transmitter manager, according to an embodiment.

FIG. **14** illustrates a wireless power transmission network, according to an embodiment; and

FIG. **15** is a flowchart of method for self-system analysis in a wireless power transmission network, according to an embodiment.

FIG. **16** illustrates a wireless power transmission system architecture, according to an exemplary embodiment.

FIG. **17** is a flowchart of a process to determine the status and usage information from a wireless power transmission system, according to an embodiment.

FIG. **18** shows a wireless power transmission system architecture diagram, according an exemplary embodiment.

FIG. **19** is a shows a wireless power transmission network diagram, according to an exemplary embodiment.

FIG. **20** is a flowchart of a general status report generation, according to an exemplary embodiment.

FIG. **21** is a flowchart of a past status report generation, according to an exemplary embodiment.

FIG. **22** is a flowchart of a present status report generation, according to an exemplary embodiment.

FIG. **23** is a flowchart of a future status report generation, according to an exemplary embodiment.

FIG. **24** illustrates a wireless power transmission system architecture, according to an exemplary embodiment.

FIG. **25** is a screenshot of a graphical user interface for a wireless power transmission management system, according to an embodiment.

FIG. **26** is a screenshot of a graphical user interface for a wireless power transmission management system, according to another embodiment.

FIG. **27** is a screenshot of a graphical user interface for a wireless power transmission management system, according to a further embodiment.

FIG. **28** is a screenshot of a graphical user interface for a wireless power transmission management system, according to yet another embodiment.

FIG. **29** is a screenshot of a portable electronic device graphical user interface for a wireless power transmission management system, according to an embodiment.

FIG. **30** is a screenshot of a portable electronic device graphical user interface for a wireless power transmission management system, according to another embodiment.

FIG. **31** is a screenshot of a graphical user interface for a wireless power transmission management system, according to another embodiment.

FIG. **32** is a screenshot of a graphical user interface for a wireless power transmission management system, according to a further embodiment.

DETAILED DESCRIPTION

The present disclosure is here described in detail with reference to embodiments illustrated in the drawings, which form a part here. Other embodiments may be used and/or other changes may be made without departing from the spirit or scope of the present disclosure. The illustrative embodiments described in the detailed description are not meant to be limiting of the subject matter presented here. Furthermore, the various components and embodiments described herein may be combined to form additional embodiments not expressly described, without departing from the spirit or scope of the invention.

Reference will now be made to the exemplary embodiments illustrated in the drawings, and specific language will be used here to describe the same. It will nevertheless be understood that no limitation of the scope of the invention is thereby intended. Alterations and further modifications of the inventive features illustrated here, and additional applications of the principles of the inventions as illustrated here, which would occur to one skilled in the relevant art and having possession of this disclosure, are to be considered within the scope of the invention.

I. Systems and Methods for Wireless Power Transmissions

A. Components System Embodiment

FIG. **1** shows a system **100** for wireless power transmission by forming pockets of energy **104**. The system **100** may comprise transmitters **101**, receivers **103**, client devices **105**, and pocket detectors **107**. Transmitters **101** may transmit power transmission signals comprising power transmission waves, which may be captured by receivers **103**. The receivers **103** may comprise antennas, antenna elements, and other circuitry (detailed later), which may convert the captured waves into a useable source of electrical energy on behalf of client devices **105** associated with the receivers **103**. In some embodiments, transmitters **101** may transmit power transmission signals, made up of power transmission waves, in one or more trajectories by manipulating the phase, gain, and/or other waveform features of the power transmission waves, and/or by selecting different transmit antennas. In such embodiments, the transmitters **101** may manipulate the trajectories of the power transmission signals so that the underlying power transmission waves converge at a location in space, resulting in certain forms of interference. One type of interference generated at the convergence of the power transmission waves, "constructive interference," may be a field of energy caused by the convergence of the power transmission waves such that they add together and strengthen the energy concentrated at that location—in contrast to adding together in a way to subtract from each other and diminish the energy concentrated at that location, which is called "destructive interference". The accumulation of sufficient energy at the constructive interference may establish a field of energy, or "pocket of energy" **104**, which may be harvested by the antennas of a receiver **103**, provided the antennas are configured to operate on the frequency of the power transmission signals. Accordingly, the power transmission waves establish pockets of energy **104** at the location in space where the receivers **103** may receive, harvest, and convert the power transmission waves into useable electrical energy, which may power or charge associated electrical client devices **105**. Detectors **107** may be devices comprising a receiver **103** that are capable of producing a notification or alert in response to receiving power transmission signals. As an example, a user searching for the optimal placement of a receiver **103** to charge the user's client device **105** may use a detector **107** that comprises an LED light **108**, which may brighten when the detector **107** captures the power transmission signals from a single beam or a pocket of energy **104**.

1. Transmitters

The transmitter **101** may transmit or broadcast power transmission signals to a receiver **103** associated with a device **105**. Although several of the embodiments mentioned below describe the power transmission signals as radio frequency (RF) waves, it should be appreciated that the power transmission may be physical media that is capable of being propagated through space, and that is capable of being converted into a source of electrical energy **103**. The transmitter **101** may transmit the power transmission signals as a single beam directed at the receivers **103**. In some cases, one or more transmitters **101** may transmit a plurality of power transmission signals that are propagated in a multiple directions and may deflect off of physical obstructions (e.g., walls). The plurality of power transmission signals may converge at a location in a three-dimensional space, forming a pocket of energy **104**. Receivers **103** within the boundaries of an energy pocket **104** may capture and covert the power transmission signals into a useable source of energy. The transmitter **101** may control pocket-forming based on phase and/or relative amplitude adjustments of power transmission signals, to form constructive interference patterns.

Although the exemplary embodiment recites the use of RF wave transmission techniques, the wireless charging techniques should not be limited to RF wave transmission techniques. Rather, it should be appreciated that possible wireless charging techniques may include any number of alternative or additional techniques for transmitting energy to a receiver converting the transmitted energy to electrical power. Non-limiting exemplary transmission techniques for energy that can be converted by a receiving device into electrical power may include: ultrasound, microwave, resonant and inductive magnetic fields, laser light, infrared, or other forms of electromagnetic energy. In the case of ultrasound, for example, one or more transducer elements may be disposed so as to form a transducer array that transmits ultrasound waves toward a receiving device that receives the

ultrasound waves and converts them to electrical power. In the case of resonant or inductive magnetic fields, magnetic fields are created in a transmitter coil and converted by a receiver coil into electrical power. In addition, although the exemplary transmitter **101** is shown as a single unit comprising potentially multiple transmitters (transmit array), both for RF transmission of power and for other power transmission methods mentioned in this paragraph, the transmit arrays can comprise multiple transmitters that are physically spread around a room rather than being in a compact regular structure. The transmitter includes an antenna array where the antennas are used for sending the power transmission signal. Each antenna sends power transmission waves where the transmitter applies a different phase and amplitude to the signal transmitted from different antennas. Similar to the formation of pockets of energy, the transmitter can form a phased array of delayed versions of the signal to be transmitted, then applies different amplitudes to the delayed versions of the signal, and then sends the signals from appropriate antennas. For a sinusoidal waveform, such as an RF signal, ultrasound, microwave, or others, delaying the signal is similar to applying a phase shift to the signal.

2. Pockets of Energy

A pocket of energy **104** may be formed at locations of constructive interference patterns of power transmission signals transmitted by the transmitter **101**. The pockets of energy **104** may manifest as a three-dimensional field where energy may be harvested by receivers **103** located within the pocket of energy **104**. The pocket of energy **104** produced by transmitters **101** during pocket-forming may be harvested by a receiver **103**, converted to an electrical charge, and then provided to electronic client device **105** associated with the receiver **103** (e.g., laptop computer, smartphone, rechargeable battery). In some embodiments, there may be multiple transmitters **101** and/or multiple receivers **103** powering various client devices **105**. In some embodiments, adaptive pocket-forming may adjust transmission of the power transmission signals in order to regulate power levels and/or identify movement of the devices **105**.

3. Receivers

A receiver **103** may be used for powering or charging an associated client device **105**, which may be an electrical device coupled to or integrated with the receiver **103**. The receiver **103** may receive power transmission waves from one or more power transmission signals originating from one or more transmitters **101**. The receiver **103** may receive the power transmission signals as a single beam produced by the transmitter **101**, or the receiver **103** may harvest power transmission waves from a pocket of energy **104**, which may be a three-dimensional field in space resulting from the convergence of a plurality of power transmission waves produced by one or more transmitters **101**. The receiver **103** may comprise an array of antennas **112** configured to receive power transmission waves from a power transmission signal and harvest the energy from the power transmission signals of the single beam or pocket of energy **104**. The receiver **103** may comprise circuitry that then converts the energy of the power transmission signals (e.g., the radio frequency electromagnetic radiation) to electrical energy. A rectifier of the receiver **103** may translate the electrical energy from AC to DC. Other types of conditioning may be applied, as well. For example, a voltage conditioning circuit may increase or decrease the voltage of the electrical energy as required by the client device **105**. An electrical relay may then convey the electrical energy from the receiver **103** to the client device **105**.

In some embodiments, the receiver **103** may comprise a communications component that transmits control signals to the transmitter **101** in order to exchange data in real-time or near real-time. The control signals may contain status information about the client device **105**, the receiver **103**, or the power transmission signals. Status information may include, for example, present location information of the device **105**, amount of charge received, amount of charged used, and user account information, among other types of information. Further, in some applications, the receiver **103** including the rectifier that it contains may be integrated into the client device **105**. For practical purposes, the receiver **103**, wire **111**, and client device **105** may be a single unit contained in a single packaging.

4. Control Signals

In some embodiments, control signals may serve as data inputs used by the various antenna elements responsible for controlling production of power transmission signals and/or pocket-forming. Control signals may be produced by the receiver **103** or the transmitter **101** using an external power supply (not shown) and a local oscillator chip (not shown), which in some cases may include using a piezoelectric material. Control signals may be RF waves or any other communication medium or protocol capable of communicating data between processors, such as Bluetooth®, RFID, infrared, near-field communication (NFC). As detailed later, control signals may be used to convey information between the transmitter **101** and the receiver **103** used to adjust the power transmission signals, as well as contain information related to status, efficiency, user data, power consumption, billing, geo-location, and other types of information.

5. Detectors

A detector **107** may comprise hardware similar to receivers **103**, which may allow the detector **107** to receive power transmission signals originating from one or more transmitters **101**. The detector **107** may be used by users to identify the location of pockets of energy **104**, so that users may determine the preferable placement of a receiver **103**. In some embodiments, the detector **107** may comprise an indicator light **108** that indicates when the detector is placed within the pocket of energy **104**. As an example, in FIG. **1**, detectors **107***a*, **107***b* are located within the pocket of energy **104** generated by the transmitter **101**, which may trigger the detectors **107***a*, **107***b* to turn on their respective indicator lights **108***a*, **108***b*, because the detectors **107***a*, **107***b* are receiving power transmission signals of the pocket of energy **104**; whereas, the indicator light **108***c* of a third detector **107***c* located outside of the pockets of energy **104**, is turned off, because the third detector **107***c* is not receiving the power transmission signals from the transmitter **101**. It should be appreciated that the functions of a detector, such as the indicator light, may be integrated into a receiver or into a client device in alternative embodiments as well.

6. Client Device

A client device **105** may be any electrical device that requires continuous electrical energy or that requires power from a battery. Non-limiting examples of client devices **105** may include laptops, mobile phones, smartphones, tablets, music players, toys, batteries, flashlights, lamps, electronic watches, cameras, gaming consoles, appliances, GPS devices, and wearable devices or so-called "wearables" (e.g., fitness bracelets, pedometers, smartwatch), among other types of electrical devices.

In some embodiments, the client device **105***a* may be a physical device distinct from the receiver **103***a* associated with the client device **105***a*. In such embodiments, the client device **105***a* may be connected to the receiver over a wire

111 that conveys converted electrical energy from the receiver **103***a* to the client device **105***a*. In some cases, other types of data may be transported over the wire **111**, such as power consumption status, power usage metrics, device identifiers, and other types of data.

In some embodiments, the client device **105***b* may be permanently integrated or detachably coupled to the receiver **103***b*, thereby forming a single integrated product or unit. As an example, the client device **105***b* may be placed into a sleeve that has embedded receivers **103***b* and that may detachably couple to the device's **105***b* power supply input, which may be typically used to charge the device's **105***b* battery. In this example, the device **105***b* may be decoupled from the receiver, but may remain in the sleeve regardless of whether or not the device **105***b* requires an electrical charge or is being used. In another example, in lieu of having a battery that holds a charge for the device **105***b*, the device **105***b* may comprise an integrated receiver **105***b*, which may be permanently integrated into the device **105***b* so as to form an indistinct product, device, or unit. In this example, the device **105***b* may rely almost entirely on the integrated receiver **103***b* to produce electrical energy by harvesting pockets of energy **104**. It should be clear to someone skilled in the art that the connection between the receiver **103** and the client device **105** may be a wire **111** or may be an electrical connection on a circuit board or an integrated circuit, or even a wireless connection, such as inductive or magnetic.

B. Method of Wireless Power Transmission

FIG. **2** shows steps of wireless power transmission, according to an exemplary method **200** embodiment.

In a first step **201**, a transmitter (TX) establishes a connection or otherwise associates with a receiver (RX). That is, in some embodiments, transmitters and receivers may communicate control data over using a wireless communication protocol capable of transmitting information between two processors of electrical devices (e.g., Bluetooth®, Bluetooth Low Energy (BLE), Wi-Fi, NFC, ZigBee®). For example, in embodiments implementing Bluetooth® or Bluetooth® variants, the transmitter may scan for receiver's broadcasting advertisement signals or a receiver may transmit an advertisement signal to the transmitter. The advertisement signal may announce the receiver's presence to the transmitter, and may trigger an association between the transmitter and the receiver. As described herein, in some embodiments, the advertisement signal may communicate information that may be used by various devices (e.g., transmitters, client devices, sever computers, other receivers) to execute and manage pocket-forming procedures. Information contained within the advertisement signal may include a device identifier (e.g., MAC address, IP address, UUID), the voltage of electrical energy received, client device power consumption, and other types of data related to power transmission. The transmitter may use the advertisement signal transmitted to identify the receiver and, in some cases, locate the receiver in a two-dimensional space or in a three-dimensional space. Once the transmitter identifies the receiver, the transmitter may establish the connection associated in the transmitter with the receiver, allowing the transmitter and receiver to communicate control signals over a second channel.

In a next step **203**, the transmitter may use the advertisement signal to determine a set of power transmission signal features for transmitting the power transmission signals, to then establish the pockets of energy. Non-limiting examples of features of power transmission signals may include phase, gain, amplitude, magnitude, and direction among others. The transmitter may use information contained in the receiver's advertisement signal, or in subsequent control signals received from the receiver, to determine how to produce and transmit the power transmission signals so that the receiver may receive the power transmission signals. In some cases, the transmitter may transmit power transmission signals in a way that establishes a pocket of energy, from which the receiver may harvest electrical energy. In some embodiments, the transmitter may comprise a processor executing software modules capable of automatically identifying the power transmission signal features needed to establish a pocket of energy based on information received from the receiver, such as the voltage of the electrical energy harvested by the receiver from the power transmission signals. It should be appreciated that in some embodiments, the functions of the processor and/or the software modules may be implemented in an Application Specific Integrated Circuit (ASIC).

Additionally or alternatively, in some embodiments, the advertisement signal or subsequent signal transmitted by the receiver over a second communications channel may indicate one or more power transmission signals features, which the transmitter may then use to produce and transmit power transmission signals to establish a pocket of energy. For example, in some cases the transmitter may automatically identify the phase and gain necessary for transmitting the power transmission signals based on the location of the device and the type of device or receiver; and, in some cases, the receiver may inform the transmitter the phase and gain for effectively transmitting the power transmission signals.

In a next step **205**, after the transmitter determines the appropriate features to use when transmitting the power transmission signals, the transmitter may begin transmitting power transmission signals, over a separate channel from the control signals. Power transmission signals may be transmitted to establish a pocket of energy. The transmitter's antenna elements may transmit the power transmission signals such that the power transmission signals converge in a two-dimensional or three-dimensional space around the receiver. The resulting field around the receiver forms a pocket of energy from which the receiver may harvest electrical energy. One antenna element may be used to transmit power transmission signals to establish two-dimensional energy transmissions; and in some cases, a second or additional antenna element may be used to transmit power transmission signals in order to establish a three-dimensional pocket of energy. In some cases, a plurality of antenna elements may be used to transmit power transmission signals in order to establish the pocket of energy. Moreover, in some cases, the plurality of antennas may include all of the antennas in the transmitter; and, in some cases, the plurality of antennas may include a number of the antennas in the transmitter, but fewer than all of the antennas of the transmitter.

As previously mentioned, the transmitter may produce and transmit power transmission signals, according to a determined set of power transmission signal features, which may be produced and transmitted using an external power source and a local oscillator chip comprising a piezoelectric material. The transmitter may comprise an RFIC that controls production and transmission of the power transmission signals based on information related to power transmission and pocket-forming received from the receiver. This control data may be communicated over a different channel from the power transmission signals, using wireless communications protocols, such as BLE, NFC, or ZigBee®. The RFIC of the transmitter may automatically adjust the phase and/or rela-

tive magnitudes of the power transmission signals as needed. Pocket-forming is accomplished by the transmitter transmitting the power transmission signals in a manner that forms constructive interference patterns.

Antenna elements of the transmitter may use concepts of wave interference to determine certain power transmission signals features (e.g., direction of transmission, phase of power transmission signal wave), when transmitting the power transmission signals during pocket-forming. The antenna elements may also use concepts of constructive interference to generate a pocket of energy, but may also utilize concepts of deconstructive interference to generate a transmission null in a particular physical location.

In some embodiments, the transmitter may provide power to a plurality of receivers using pocket-forming, which may require the transmitter to execute a procedure for multiple pocket-forming. A transmitter comprising a plurality of antenna elements may accomplish multiple pocket-forming by automatically computing the phase and gain of power transmission signal waves, for each antenna element of the transmitter tasked with transmitting power transmission signals the respective receivers. The transmitter may compute the phase and gains independently, because multiple wave paths for each power transmission signal may be generated by the transmitter's antenna elements to transmit the power transmission signals to the respective antenna elements of the receiver.

As an example of the computation of phase/gain adjustments for two antenna elements of the transmitter transmitting two signals, say X and Y where Y is 180 degree phase shifted version of X (Y=−X). At a physical location where the cumulative received waveform is X−Y, a receiver receives X−Y=X+X=2X, whereas at a physical location where the cumulative received waveform is X+Y, a receiver receives X+Y=X−X=0.

In a next step **207**, the receiver may harvest or otherwise receive electrical energy from power transmission signals of a single beam or a pocket of energy. The receiver may comprise a rectifier and AC/DC converter, which may convert the electrical energy from AC current to DC current, and a rectifier of the receiver may then rectify the electrical energy, resulting in useable electrical energy for a client device associated with the receiver, such as a laptop computer, smartphone, battery, toy, or other electrical device. The receiver may utilize the pocket of energy produced by the transmitter during pocket-forming to charge or otherwise power the electronic device.

In next step **209**, the receiver may generate control data containing information indicating the effectiveness of the single beam or energy pockets providing the receiver power transmission signals. The receiver may then transmit control signals containing the control data, to the transmitter. The control signals may be transmitted intermittently, depending on whether the transmitter and receiver are communicating synchronously (i.e., the transmitter is expecting to receive control data from the receiver). Additionally, the transmitter may continuously transmit the power transmission signals to the receiver, irrespective of whether the transmitter and receiver are communicating control signals. The control data may contain information related to transmitting power transmission signals and/or establishing effective pockets of energy. Some of the information in the control data may inform the transmitter how to effectively produce and transmit, and in some cases adjust, the features of the power transmission signals. Control signals may be transmitted and received over a second channel, independent from the power transmission signals, using a wireless protocol capable of transmitting control data related to power transmission signals and/or pocket-forming, such as BLE, NFC, Wi-Fi, or the like.

As mentioned, the control data may contain information indicating the effectiveness of the power transmission signals of the single beam or establishing the pocket of energy. The control data may be generated by a processor of the receiver monitoring various aspects of receiver and/or the client device associated with the receiver. The control data may be based on various types of information, such as the voltage of electrical energy received from the power transmission signals, the quality of the power transmission signals reception, the quality of the battery charge or quality of the power reception, and location or motion of the receiver, among other types of information useful for adjusting the power transmission signals and/or pocket-forming.

In some embodiments, a receiver may determine the amount of power being received from power transmission signals transmitted from the transmitter and may then indicate that the transmitter should "split" or segment the power transmission signals into less-powerful power transmission signals. The less-powerful power transmission signals may be bounced off objects or walls nearby the device, thereby reducing the amount of power being transmitted directly from the transmitter to the receiver.

In a next step **211**, the transmitter may calibrate the antennas transmitting the power transmission signals, so that the antennas transmit power transmission signals having a more effective set of feature (e.g., direction, phase, gain, amplitude). In some embodiments, a processor of the transmitter may automatically determine more effective features for producing and transmitting the power transmission signals based on a control signal received from the receiver. The control signal may contain control data, and may be transmitted by the receiver using any number of wireless communication protocols (e.g., BLE, Wi-Fi, ZigBee®). The control data may contain information expressly indicating the more effective features for the power transmission waves; or the transmitter may automatically determine the more effective features based on the waveform features of the control signal (e.g., shape, frequency, amplitude). The transmitter may then automatically reconfigure the antennas to transmit recalibrated power transmission signals according to the newly determined more-effective features. For example, the processor of the transmitter may adjust gain and/or phase of the power transmission signals, among other features of power transmission feature, to adjust for a change in location of the receiver, after a user moved the receiver outside of the three-dimensional space where the pocket of energy is established.

C. System Architecture of Power Transmission System

FIG. **3** illustrates an architecture **300** for wireless power transmission using pocket-forming, according to an exemplary embodiment. "Pocket-forming" may refer to generating two or more power transmission waves **342** that converge at a location in three-dimensional space, resulting in constructive interference patterns at that location. A transmitter **302** may transmit and/or broadcast controlled power transmission waves **342** (e.g., microwaves, radio waves, ultrasound waves) that may converge in three-dimensional space. These power transmission waves **342** may be controlled through phase and/or relative amplitude adjustments to form constructive interference patterns (pocket-forming) in locations where a pocket of energy is intended. It should be understood also that the transmitter can use the same principles to create destructive interference in a location thereby creating a transmission null—a location where

transmitted power transmission waves cancel each other out substantially and no significant energy can be collected by a receiver. In typical use cases the aiming of a power transmission signal at the location of the receiver is the objective; and in other cases it may be desirable to specifically avoid power transmission to a particular location; and in other cases it may be desirable to aim power transmission signal at a location while specifically avoiding transmission to a second location at the same time. The transmitter takes the use case into account when calibrating antennas for power transmission.

Antenna elements **306** of the transmitter **302** may operate in single array, pair array, quad array, or any other suitable arrangement that may be designed in accordance with the desired application. Pockets of energy may be formed at constructive interference patterns where the power transmission waves **342** accumulate to form a three-dimensional field of energy, around which one or more corresponding transmission null in a particular physical location may be generated by destructive interference patterns. Transmission null in a particular physical location-may refer to areas or regions of space where pockets of energy do not form because of destructive interference patterns of power transmission waves **342**.

A receiver **320** may then utilize power transmission waves **342** emitted by the transmitter **302** to establish a pocket of energy, for charging or powering an electronic device **313**, thus effectively providing wireless power transmission. Pockets of energy may refer to areas or regions of space where energy or power may accumulate in the form of constructive interference patterns of power transmission waves **342**. In other situations there can be multiple transmitters **302** and/or multiple receivers **320** for powering various electronic equipment for example smartphones, tablets, music players, toys and others at the same time. In other embodiments, adaptive pocket-forming may be used to regulate power on electronic devices. Adaptive pocket-forming may refer to dynamically adjusting pocket-forming to regulate power on one or more targeted receivers.

Receiver **320** may communicate with transmitter **302** by generating a short signal through antenna elements **324** in order to indicate its position with respect to the transmitter **302**. In some embodiments, receiver **320** may additionally utilize a network interface card (not shown) or similar computer networking component to communicate through a network **340** with other devices or components of the system **300**, such as a cloud computing service that manages several collections of transmitters **302**. The receiver **320** may comprise circuitry **308** for converting the power transmission signals **342** captured by the antenna elements **324**, into electrical energy that may be provided to and electric device **313** and/or a battery of the device **315**. In some embodiments, the circuitry may provide electrical energy to a battery of receiver **335**, which may store energy without the electrical device **313** being communicatively coupled to the receiver **320**.

Communications components **324** may enable receiver **320** to communicate with the transmitter **302** by transmitting control signals **345** over a wireless protocol. The wireless protocol can be a proprietary protocol or use a conventional wireless protocol, such as Bluetooth®, BLE, Wi-Fi, NFC, ZigBee, and the like. Communications component **324** may then be used to transfer information, such as an identifier for the electronic device **313**, as well as battery level information, geographic location data, or other information that may be of use for transmitter **302** in determining when to send power to receiver **320**, as well as the location to deliver power transmission waves **342** creating pockets of energy. In other embodiments, adaptive pocket-forming may be used to regulate power provided to electronic devices **313**. In such embodiments, the communications components **324** of the receiver may transmit voltage data indicating the amount of power received at the receiver **320**, and/or the amount of voltage provided to an electronic device **313***b* or battery **315**.

Once transmitter **302** identifies and locates receiver **320**, a channel or path for the control signals **345** can be established, through which the transmitter **302** may know the gain and phases of the control signals **345** coming from receiver **320**. Antenna elements **306** of the transmitter **302** may start to transmit or broadcast controlled power transmission waves **342** (e.g., radio frequency waves, ultrasound waves), which may converge in three-dimensional space by using at least two antenna elements **306** to manipulate the power transmission waves **342** emitted from the respective antenna element **306**. These power transmission waves **342** may be produced by using an external power source and a local oscillator chip using a suitable piezoelectric material. The power transmission waves **342** may be controlled by transmitter circuitry **301**, which may include a proprietary chip for adjusting phase and/or relative magnitudes of power transmission waves **342**. The phase, gain, amplitude, and other waveform features of the power transmission waves **342** may serve as inputs for antenna element **306** to form constructive and destructive interference patterns (pocket-forming). In some implementations, a micro-controller **310** or other circuit of the transmitter **302** may produce a power transmission signal, which comprises power transmission waves **342**, and that may be may split into multiple outputs by transmitter circuitry **301**, depending on the number of antenna elements **306** connected to the transmitter circuitry **301**. For example, if four antenna elements **306***a-d* are connected to one transmitter circuit **301***a*, the power transmission signal will be split into four different outputs each output going to an antenna element **306** to be transmitted as power transmission waves **342** originating from the respective antenna elements **306**.

Pocket-forming may take advantage of interference to change the directionality of the antenna element **306** where constructive interference generates a pocket of energy and destructive interference generates a transmission null. Receiver **320** may then utilize pocket of energy produced by pocket-forming for charging or powering an electronic device and therefore effectively providing wireless power transmission.

Multiple pocket-forming may be achieved by computing the phase and gain from each antenna **306** of transmitter **302** to each receiver **320**.

D. Components of Systems Forming Pockets of Energy

FIG. **4** shows components of an exemplary system **400** of wireless power transmission using pocket-forming procedures. The system **400** may comprise one or more transmitters **402**, one or more receivers **420**, and one or more client devices **446**.

1. Transmitters

Transmitters **402** may be any device capable of broadcasting wireless power transmission signals, which may be RF waves **442**, for wireless power transmission, as described herein. Transmitters **402** may be responsible for performing tasks related to transmitting power transmission signals, which may include pocket-forming, adaptive pocket-forming, and multiple pocket-forming. In some implementations, transmitters **402** may transmit wireless power transmissions to receivers **420** in the form of RF waves, which may include any radio signal having any frequency or wavelength. A

transmitter **402** may include one or more antenna elements **406**, one or more RFICs **408**, one or more microcontrollers **410**, one or more communication components **412**, a power source **414**, and a housing that may allocate all the requested components for the transmitter **402**. The various components of transmitters **402** may comprise, and/or may be manufactured using, meta-materials, micro-printing of circuits, nano-materials, and the like.

In the exemplary system **400**, the transmitter **402** may transmit or otherwise broadcast controlled RF waves **442** that converge at a location in three-dimensional space, thereby forming a pocket of energy **444**. These RF waves may be controlled through phase and/or relative amplitude adjustments to form constructive or destructive interference patterns (i.e., pocket-forming). Pockets of energy **444** may be fields formed at constructive interference patterns and may be three-dimensional in shape; whereas transmission null in a particular physical location may be generated at destructive interference patterns. Receivers **420** may harvest electrical energy from the pockets of energy **444** produced by pocket-forming for charging or powering an electronic client device **446** (e.g., a laptop computer, a cell phone). In some embodiments, the system **400** may comprise multiple transmitters **402** and/or multiple receivers **420**, for powering various electronic equipment. Non-limiting examples of client devices **446** may include: smartphones, tablets, music players, toys and others at the same time. In some embodiments, adaptive pocket-forming may be used to regulate power on electronic devices.

2. Receivers

Receivers **420** may include a housing where at least one antenna element **424**, one rectifier **426**, one power converter **428**, and a communications component **430** may be included.

Housing of the receiver **420** can be made of any material capable of facilitating signal or wave transmission and/or reception, for example plastic or hard rubber. Housing may be an external hardware that may be added to different electronic equipment, for example in the form of cases, or can be embedded within electronic equipment as well.

3. Antenna Elements

Antenna elements **424** of the receiver **420** may comprise any type of antenna capable of transmitting and/or receiving signals in frequency bands used by the transmitter **402**A. Antenna elements **424** may include vertical or horizontal polarization, right hand or left hand polarization, elliptical polarization, or other polarizations, as well as any number of polarization combinations. Using multiple polarizations can be beneficial in devices where there may not be a preferred orientation during usage or whose orientation may vary continuously through time, for example a smartphone or portable gaming system. For devices having a well-defined expected orientation (e.g., a two-handed video game controller), there might be a preferred polarization for antennas, which may dictate a ratio for the number of antennas of a given polarization. Types of antennas in antenna elements **424** of the receiver **420**, may include patch antennas, which may have heights from about ⅛ inch to about 6 inches and widths from about ⅛ inch to about 6 inches. Patch antennas may preferably have polarization that depends upon connectivity, i.e., the polarization may vary depending on from which side the patch is fed. In some embodiments, the type of antenna may be any type of antenna, such as patch antennas, capable of dynamically varying the antenna polarization to optimize wireless power transmission.

4. Rectifier

Rectifiers **426** of the receiver **420** may include diodes, resistors, inductors, and/or capacitors to rectify alternating current (AC) voltage generated by antenna elements **424** to direct current (DC) voltage. Rectifiers **426** may be placed as close as is technically possible to antenna elements A**24**B to minimize losses in electrical energy gathered from power transmission signals. After rectifying AC voltage, the resulting DC voltage may be regulated using power converters **428**. Power converters **428** can be a DC-to-DC converter that may help provide a constant voltage output, regardless of input, to an electronic device, or as in this exemplary system **400**, to a battery. Typical voltage outputs can be from about 5 volts to about 10 volts. In some embodiments, power converter may include electronic switched mode DC-DC converters, which can provide high efficiency. In such embodiments, the receiver **420** may comprise a capacitor (not shown) that is situated to receive the electrical energy before power converters **428**. The capacitor may ensure sufficient current is provided to an electronic switching device (e.g., switch mode DC-DC converter), so it may operate effectively. When charging an electronic device, for example a phone or laptop computer, initial high-currents that can exceed the minimum voltage needed to activate operation of an electronic switched mode DC-DC converter, may be required. In such a case, a capacitor (not shown) may be added at the output of receivers **420** to provide the extra energy required. Afterwards, lower power can be provided. For example, 1/80 of the total initial power that may be used while having the phone or laptop still build-up charge.

5. Communications Component

A communications component **430** of a receiver **420** may communicate with one or more other devices of the system **400**, such as other receivers **420**, client devices, and/or transmitters **402**. Different antenna, rectifier or power converter arrangements are possible for a receiver as will be explained in following embodiments.

E. Methods of Pocket Forming for a Plurality of Devices

FIG. **5** shows steps of powering a plurality of receiver devices, according to an exemplary embodiment.

In a first step **501**, a transmitter (TX) establishes a connection or otherwise associates with a receiver (RX). That is, in some embodiments, transmitters and receivers may communicate control data over using a wireless communication protocol capable of transmitting information between two processors of electrical devices (e.g., Bluetooth®, BLE, Wi-Fi, NFC, ZigBee®). For example, in embodiments implement Bluetooth® or Bluetooth® variants, the transmitter may scan for receiver's broadcasting advertisement signals or a receiver may transmit an advertisement signal to the transmitter. The advertisement signal may announce the receiver's presence to the transmitter, and may trigger an association between the transmitter and the receiver. As described later, in some embodiments, the advertisement signal may communicate information that may be used by various devices (e.g., transmitters, client devices, sever computers, other receivers) to execute and manage pocket-forming procedures. Information contained within the advertisement signal may include a device identifier (e.g., MAC address, IP address, UUID), the voltage of electrical energy received, client device power consumption, and other types of data related to power transmission waves. The transmitter may use the advertisement signal transmitted to identify the receiver and, in some cases, locate the receiver in a two-dimensional space or in a three-dimensional space. Once the transmitter identifies the receiver, the transmitter may establish the connection associated in the

transmitter with the receiver, allowing the transmitter and receiver to communicate control signals over a second channel.

As an example, when a receiver comprising a Bluetooth® processor is powered-up or is brought within a detection range of the transmitter, the Bluetooth processor may begin advertising the receiver according to Bluetooth® standards. The transmitter may recognize the advertisement and begin establishing connection for communicating control signals and power transmission signals. In some embodiments, the advertisement signal may contain unique identifiers so that the transmitter may distinguish that advertisement and ultimately that receiver from all the other Bluetooth® devices nearby within range.

In a next step **503**, when the transmitter detects the advertisement signal, the transmitter may automatically form a communication connection with that receiver, which may allow the transmitter and receiver to communicate control signals and power transmission signals. The transmitter may then command that receiver to begin transmitting real-time sample data or control data. The transmitter may also begin transmitting power transmission signals from antennas of the transmitter's antenna array.

In a next step **505**, the receiver may then measure the voltage, among other metrics related to effectiveness of the power transmission signals, based on the electrical energy received by the receiver's antennas. The receiver may generate control data containing the measured information, and then transmit control signals containing the control data to the transmitter. For example, the receiver may sample the voltage measurements of received electrical energy, for example, at a rate of 100 times per second. The receiver may transmit the voltage sample measurement back to the transmitter, 100 times a second, in the form of control signals.

In a next step **507**, the transmitter may execute one or more software modules monitoring the metrics, such as voltage measurements, received from the receiver. Algorithms may vary production and transmission of power transmission signals by the transmitter's antennas, to maximize the effectiveness of the pockets of energy around the receiver. For example, the transmitter may adjust the phase at which the transmitter's antenna transmit the power transmission signals, until that power received by the receiver indicates an effectively established pocket energy around the receiver. When an optimal configuration for the antennas is identified, memory of the transmitter may store the configurations to keep the transmitter broadcasting at that highest level.

In a next step **509**, algorithms of the transmitter may determine when it is necessary to adjust the power transmission signals and may also vary the configuration of the transmit antennas, in response to determining such adjustments are necessary. For example, the transmitter may determine the power received at a receiver is less than maximal, based on the data received from the receiver. The transmitter may then automatically adjust the phase of the power transmission signals, but may also simultaneously continues to receive and monitor the voltage being reported back from receiver.

In a next step **511**, after a determined period of time for communicating with a particular receiver, the transmitter may scan and/or automatically detect advertisements from other receivers that may be in range of the transmitter. The transmitters may establish a connection to the second receiver responsive to Bluetooth® advertisements from a second receiver.

In a next step **513**, after establishing a second communication connection with the second receiver, the transmitter may proceed to adjust one or more antennas in the transmitter's antenna array. In some embodiments, the transmitter may identify a subset of antennas to service the second receiver, thereby parsing the array into subsets of arrays that are associated with a receiver. In some embodiments, the entire antenna array may service a first receiver for a given period of time, and then the entire array may service the second receiver for that period of time.

Manual or automated processes performed by the transmitter may select a subset of arrays to service the second receiver. In this example, the transmitter's array may be split in half, forming two subsets. As a result, half of the antennas may be configured to transmit power transmission signals to the first receiver, and half of the antennas may be configured for the second receiver. In the current step **513**, the transmitter may apply similar techniques discussed above to configure or optimize the subset of antennas for the second receiver. While selecting a subset of an array for transmitting power transmission signals, the transmitter and second receiver may be communicating control data. As a result, by the time that the transmitter alternates back to communicating with the first receiver and/or scan for new receivers, the transmitter has already received a sufficient amount of sample data to adjust the phases of the waves transmitted by second subset of the transmitter's antenna array, to transmit power transmission waves to the second receiver effectively.

In a next step **515**, after adjusting the second subset to transmit power transmission signals to the second receiver, the transmitter may alternate back to communicating control data with the first receiver, or scanning for additional receivers. The transmitter may reconfigure the antennas of the first subset, and then alternate between the first and second receivers at a predetermined interval.

In a next step **517**, the transmitter may continue to alternate between receivers and scanning for new receivers, at a predetermined interval. As each new receiver is detected, the transmitter may establish a connection and begin transmitting power transmission signals, accordingly.

In one exemplary embodiment, the receiver may be electrically connected to a device like a smart phone. The transmitter's processor would scan for any Bluetooth devices. The receiver may begin advertising that it's a Bluetooth device through the Bluetooth chip. Inside the advertisement, there may be unique identifiers so that the transmitter, when it scanned that advertisement, could distinguish that advertisement and ultimately that receiver from all the other Bluetooth devices nearby within range. When the transmitter detects that advertisement and notices it is a receiver, then the transmitter may immediately form a communication connection with that receiver and command that receiver to begin sending real time sample data.

The receiver would then measure the voltage at its receiving antennas, send that voltage sample measurement back to the transmitter (e.g., 100 times a second). The transmitter may start to vary the configuration of the transmit antennas by adjusting the phase. As the transmitter adjusts the phase, the transmitter monitors the voltage being sent back from the receiver. In some implementations, the higher the voltage, the more energy may be in the pocket. The antenna phases may be altered until the voltage is at the highest level and there is a maximum pocket of energy around the receiver. The transmitter may keep the antennas at the particular phase so the voltage is at the highest level.

The transmitter may vary each individual antenna, one at a time. For example, if there are 32 antennas in the trans-

mitter, and each antenna has 8 phases, the transmitter may begin with the first antenna and would step the first antenna through all 8 phases. The receiver may then send back the power level for each of the 8 phases of the first antenna. The transmitter may then store the highest phase for the first antenna. The transmitter may repeat this process for the second antenna, and step it through 8 phases. The receiver may again send back the power levels from each phase, and the transmitter may store the highest level. Next the transmitter may repeat the process for the third antenna and continue to repeat the process until all 32 antennas have stepped through the 8 phases. At the end of the process, the transmitter may transmit the maximum voltage in the most efficient manner to the receiver.

In another exemplary embodiment, the transmitter may detect a second receiver's advertisement and form a communication connection with the second receiver. When the transmitter forms the communication with the second receiver, the transmitter may aim the original 32 antennas towards the second receiver and repeat the phase process for each of the 32 antennas aimed at the second receiver. Once the process is completed, the second receiver may getting as much power as possible from the transmitter. The transmitter may communicate with the second receiver for a second, and then alternate back to the first receiver for a predetermined period of time (e.g., a second), and the transmitter may continue to alternate back and forth between the first receiver and the second receiver at the predetermined time intervals.

In yet another implementation, the transmitter may detect a second receiver's advertisement and form a communication connection with the second receiver. First, the transmitter may communicate with the first receiver and re-assign half of the exemplary **32** the antennas aimed at the first receiver, dedicating only 16 towards the first receiver. The transmitter may then assign the second half of the antennas to the second receiver, dedicating 16 antennas to the second receiver. The transmitter may adjust the phases for the second half of the antennas. Once the 16 antennas have gone through each of the 8 phases, the second receiver may be obtaining the maximum voltage in the most efficient manner to the receiver.

F. Wireless Power Transmission with Selective Range

1. Constructive Interference

FIG. **6**A and FIG. **6**B show an exemplary system **600** implementing wireless power transmission principles that may be implemented during exemplary pocket-forming processes. A transmitter **601** comprising a plurality of antennas in an antenna array, may adjust the phase and amplitude, among other possible attributes, of power transmission waves **607**, being transmitted from antennas of the transmitter **601**. As shown in FIG. **6**A, in the absence of any phase or amplitude adjustment, power transmission waves **607***a* may be transmitted from each of the antennas will arrive at different locations and have different phases. These differences are often due to the different distances from each antenna element of the transmitter **601***a* to a receiver **605***a* or receivers **605***a*, located at the respective locations.

Continuing with FIG. **6**A, a receiver **605***a* may receive multiple power transmission signals, each comprising power transmission waves **607***a*, from multiple antenna elements of a transmitter **601***a*; the composite of these power transmission signals may be essentially zero, because in this example, the power transmission waves add together destructively. That is, antenna elements of the transmitter **601***a* may transmit the exact same power transmission signal (i.e., comprising power transmission waves **607***a* having the same features, such as phase and amplitude), and as such, when the power transmission waves **607***a* of the respective power transmission signals arrive at the receiver **605***a*, they are offset from each other by 180 degrees. Consequently, the power transmission waves **607***a* of these power transmission signals "cancel" one another. Generally, signals offsetting one another in this way may be referred to as "destructive," and thus result in "destructive interference."

In contrast, as shown in FIG. **6**B, for so-called "constructive interference," signals comprising power transmission waves **607***b* that arrive at the receiver exactly "in phase" with one another, combine to increase the amplitude of the each signal, resulting in a composite that is stronger than each of the constituent signals. In the illustrative example in FIG. **6**A, note that the phase of the power transmission waves **607***a* in the transmit signals are the same at the location of transmission, and then eventually add up destructively at the location of the receiver **605***a*. In contrast, in FIG. **6**B, the phase of the power transmission waves **607***b* of the transmit signals are adjusted at the location of transmission, such that they arrive at the receiver **605***b* in phase alignment, and consequently they add constructively. In this illustrative example, there will be a resulting pocket of energy located around the receiver **605***b* in FIG. **6**B; and there will be a transmission null located around receiver in FIG. **6**A.

FIG. **7** depicts wireless power transmission with selective range **700**, where a transmitter **702** may produce pocket-forming for a plurality of receivers associated with electrical devices **701**. Transmitter **702** may generate pocket-forming through wireless power transmission with selective range **700**, which may include one or more wireless charging radii **704** and one or more radii of a transmission null at a particular physical location **706**. A plurality of electronic devices **701** may be charged or powered in wireless charging radii **704**. Thus, several spots of energy may be created, such spots may be employed for enabling restrictions for powering and charging electronic devices **701**. As an example, the restrictions may include operating specific electronics in a specific or limited spot, contained within wireless charging radii **704**. Furthermore, safety restrictions may be implemented by the use of wireless power transmission with selective range **700**, such safety restrictions may avoid pockets of energy over areas or zones where energy needs to be avoided, such areas may include areas including sensitive equipment to pockets of energy and/or people which do not want pockets of energy over and/or near them. In embodiments such as the one shown in FIG. **7**, the transmitter **702** may comprise antenna elements found on a different plane than the receivers associated with electrical devices **701** in the served area. For example the receivers of electrical devices **701** may be in a room where a transmitter **702** may be mounted on the ceiling. Selective ranges for establishing pockets of energy using power transmission waves, which may be represented as concentric circles by placing an antenna array of the transmitter **702** on the ceiling or other elevated location, and the transmitter **702** may emit power transmission waves that will generate 'cones' of energy pockets. In some embodiments, the transmitter **701** may control the radius of each charging radii **704**, thereby establishing intervals for service area to create pockets of energy that are pointed down to an area at a lower plane, which may adjust the width of the cone through appropriate selection of antenna phase and amplitudes.

FIG. **8** depicts wireless power transmission with selective range **800**, where a transmitter **802** may produce pocket-forming for a plurality of receivers **806**. Transmitter **802**

may generate pocket-forming through wireless power transmission with selective range **800**, which may include one or more wireless charging spots **804**. A plurality of electronic devices may be charged or powered in wireless charging spots **804**. Pockets of energy may be generated over a plurality of receivers **806** regardless the obstacles **804** surrounding them. Pockets of energy may be generated by creating constructive interference, according to the principles described herein, in wireless charging spots **804**. Location of pockets of energy may be performed by tacking receivers **806** and by enabling a plurality of communication protocols by a variety of communication systems such as, Bluetooth® technology, infrared communication, Wi-Fi, FM radio, among others.

G. Exemplary System Embodiment Using Heat Maps

FIGS. **9**A and **9**B illustrate a diagram of architecture **900**A, **900**B for a wirelessly charging client computing platform, according to an exemplary embodiment. In some implementations, a user may be inside a room and may hold on his hands an electronic device (e.g. a smartphone, tablet). In some implementations, electronic device may be on furniture inside the room. The electronic device may include a receiver **920**A, **920**B either embedded to the electronic device or as a separate adapter connected to electronic device. Receivers **920**A, **920**B may include all the components described in FIG. **11**. A transmitter **902**A, **902**B may be hanging on one of the walls of the room right behind user. Transmitters **902**A, **902**B may also include all the components described in FIG. **11**.

As user may seem to be obstructing the path between receivers **920**A, **920**B and transmitters **902**A, **902**B, RF waves may not be easily aimed to the receivers **920**A, **920**B in a linear direction. However, since the short signals generated from receivers **920**A, **920**B may be omni-directional for the type of antenna element used, these signals may bounce over the walls **944**A, **944**B until they reach transmitters **902**A, **902**B. A hot spot **944**A, **944**B may be any item in the room which will reflect the RF waves. For example, a large metal clock on the wall may be used to reflect the RF waves to a user's cell phone.

A micro controller in the transmitter adjusts the transmitted signal from each antenna based on the signal received from the receiver. Adjustment may include forming conjugates of the signal phases received from the receivers and further adjustment of transmit antenna phases taking into account the built-in phase of antenna elements. The antenna element may be controlled simultaneously to steer energy in a given direction. The transmitter **902**A, **902**B may scan the room, and look for hot spots **944**A, **944**B. Once calibration is performed, transmitters **902**A, **902**B may focus RF waves in a channel following a path that may be the most efficient paths. Subsequently, RF signals **942**A, **942**B may form a pocket of energy on a first electronic device and another pocket of energy in a second electronic device while avoiding obstacles such as user and furniture.

When scanning the service area, the room in FIGS. **9**A and **9**B, the transmitter **902**A, **902**B may employ different methods. As an illustrative example, but without limiting the possible methods that can be used, the transmitter **902**A, **902**B may detect the phases and magnitudes of the signal coming from the receiver and use those to form the set of transmit phases and magnitudes, for example by calculating conjugates of them and applying them at transmit. As another illustrative example, the transmitter may apply all possible phases of transmit antennas in subsequent transmissions, one at a time, and detect the strength of the pocket of energy formed by each combination by observing information related to the signal from the receiver **920**A, **920**B. Then the transmitter **902**A, **902**B repeats this calibration periodically. In some implementations, the transmitter **902**A, **902**B does not have to search through all possible phases, and can search through a set of phases that are more likely to result in strong pockets of energy based on prior calibration values. In yet another illustrative example, the transmitter **902**A, **902**B may use preset values of transmit phases for the antennas to form pockets of energy directed to different locations in the room. The transmitter may for example scan the physical space in the room from top to bottom and left to right by using preset phase values for antennas in subsequent transmissions. The transmitter **902**A, **902**B then detects the phase values that result in the strongest pocket of energy around the receiver **920***a*, **920***b* by observing the signal from the receiver **920***a*, **920***b*. It should be appreciated that there are other possible methods for scanning a service area for heat mapping that may be employed, without deviating from the scope or spirit of the embodiments described herein. The result of a scan, whichever method is used, is a heat-map of the service area (e.g., room, store) from which the transmitter **902**A, **902**B may identify the hot spots that indicate the best phase and magnitude values to use for transmit antennas in order to maximize the pocket of energy around the receiver.

The transmitters **902**A, **902**B, may use the Bluetooth connection to determine the location of the receivers **920**A, **920**B, and may use different non-overlapping parts of the RF band to channel the RF waves to different receivers **920**A, **920**B. In some implementations, the transmitters **902**A, **902**B, may conduct a scan of the room to determine the location of the receivers **920**A, **920**B and forms pockets of energy that are orthogonal to each other, by virtue of non-overlapping RF transmission bands. Using multiple pockets of energy to direct energy to receivers may inherently be safer than some alternative power transmission methods since no single transmission is very strong, while the aggregate power transmission signal received at the receiver is strong.

H. Exemplary System Embodiment

FIG. **10**A illustrates wireless power transmission using multiple pocket-forming **1000**A that may include one transmitter **1002**A and at least two or more receivers **1020**A. Receivers **1020**A may communicate with transmitters **1002**A, which is further described in FIG. **11**. Once transmitter **1002**A identifies and locates receivers **1020**A, a channel or path can be established by knowing the gain and phases coming from receivers **1020**A. Transmitter **1002**A may start to transmit controlled RF waves **1042**A which may converge in three-dimensional space by using a minimum of two antenna elements. These RF waves **1042**A may be produced using an external power source and a local oscillator chip using a suitable piezoelectric material. RF waves **1042**A may be controlled by RFIC, which may include a proprietary chip for adjusting phase and/or relative magnitudes of RF signals that may serve as inputs for antenna elements to form constructive and destructive interference patterns (pocket-forming). Pocket-forming may take advantage of interference to change the directionality of the antenna elements where constructive interference generates a pocket of energy **1060**A and deconstructive interference generates a transmission null. Receivers **1020**A may then utilize pocket of energy **1060**A produced by pocket-forming for charging or powering an electronic device, for example, a laptop computer **1062**A and a smartphone **1052**A and thus effectively providing wireless power transmission.

Multiple pocket forming **1000**A may be achieved by computing the phase and gain from each antenna of transmitter **1002**A to each receiver **1020**A. The computation may be calculated independently because multiple paths may be generated by antenna element from transmitter **1002**A to antenna element from receivers **1020**A.

I. Exemplary System Embodiment

FIG. **10**B is an exemplary illustration of multiple adaptive pocket-forming **1000**B. In this embodiment, a user may be inside a room and may hold on his hands an electronic device, which in this case may be a tablet **1064**B. In addition, smartphone **1052**B may be on furniture inside the room. Tablet **1064**B and smartphone **1052**B may each include a receiver either embedded to each electronic device or as a separate adapter connected to tablet **1064**B and smartphone **1052**B. Receiver may include all the components described in FIG. **11**. A transmitter **1002**B may be hanging on one of the walls of the room right behind user. Transmitter **1002**B may also include all the components described in FIG. **11**. As user may seem to be obstructing the path between receiver and transmitter **1002**B, RF waves **1042**B may not be easily aimed to each receiver in a line of sight fashion. However, since the short signals generated from receivers may be omni-directional for the type of antenna elements used, these signals may bounce over the walls until they find transmitter **1002**B. Almost instantly, a micro-controller which may reside in transmitter **1002**B, may recalibrate the transmitted signals, based on the received signals sent by each receiver, by adjusting gain and phases and forming a convergence of the power transmission waves such that they add together and strengthen the energy concentrated at that location—in contrast to adding together in a way to subtract from each other and diminish the energy concentrated at that location, which is called "destructive interference" and conjugates of the signal phases received from the receivers and further adjustment of transmit antenna phases taking into account the built-in phase of antenna elements. Once calibration is performed, transmitter **1002**B may focus RF waves following the most efficient paths. Subsequently, a pocket of energy **1060**B may form on tablet **1064**B and another pocket of energy **1060**B in smartphone **1052**B while taking into account obstacles such as user and furniture. The foregoing property may be beneficial in that wireless power transmission using multiple pocket-forming **1000**B may inherently be safe as transmission along each pocket of energy is not very strong, and that RF transmissions generally reflect from living tissue and do not penetrate.

Once transmitter **1002**B identities and locates receiver, a channel or path can be established by knowing the gain and phases coming from receiver. Transmitter **1002**B may start to transmit controlled RF waves **1042**B that may converge in three-dimensional space by using a minimum of two antenna elements. These RF waves **1042**B may be produced using an external power source and a local oscillator chip using a suitable piezoelectric material. RF waves **1042**B may be controlled by RFIC that may include a proprietary chip for adjusting phase and/or relative magnitudes of RF signals, which may serve as inputs for antenna elements to form constructive and destructive interference patterns (pocket-forming). Pocket-forming may take advantage of interference to change the directionality of the antenna elements where constructive interference generates a pocket of energy and deconstructive interference generates a null in a particular physical location. Receiver may then utilize pocket of energy produced by pocket-forming for charging or powering an electronic device, for example a laptop computer and a smartphone and thus effectively providing wireless power transmission.

Multiple pocket-forming **1000**B may be achieved by computing the phase and gain from each antenna of transmitter to each receiver. The computation may be calculated independently because multiple paths may be generated by antenna elements from transmitter to antenna elements from receiver.

An example of the computation for at least two antenna elements may include determining the phase of the signal from the receiver and applying the conjugate of the receive parameters to the antenna elements for transmission.

In some embodiments, two or more receivers may operate at different frequencies to avoid power losses during wireless power transmission. This may be achieved by including an array of multiple embedded antenna elements in transmitter **1002**B. In one embodiment, a single frequency may be transmitted by each antenna in the array. In other embodiments some of the antennas in the array may be used to transmit at a different frequency. For example, ½ of the antennas in the array may operate at 2.4 GHz while the other ½ may operate at 5.8 GHz. In another example, ⅓ of the antennas in the array may operate at 900 MHz, another ⅓ may operate at 2.4 GHz, and the remaining antennas in the array may operate at 5.8 GHz.

In another embodiment, each array of antenna elements may be virtually divided into one or more antenna elements during wireless power transmission, where each set of antenna elements in the array can transmit at a different frequency. For example, an antenna element of the transmitter may transmit power transmission signals at 2.4 GHz, but a corresponding antenna element of a receiver may be configured to receive power transmission signals at 5.8 GHz. In this example, a processor of the transmitter may adjust the antenna element of the transmitter to virtually or logically divide the antenna elements in the array into a plurality patches that may be fed independently. As a result, 1/4 of the array of antenna elements may be able to transmit the 5.8 GHz needed for the receiver, while another set of antenna elements may transmit at 2.4 GHz. Therefore, by virtually dividing an array of antenna elements, electronic devices coupled to receivers can continue to receive wireless power transmission. The foregoing may be beneficial because, for example, one set of antenna elements may transmit at about 2.4 GHz and other antenna elements may transmit at 5.8 GHz, and thus, adjusting a number of antenna elements in a given array when working with receivers operating at different frequencies. In this example, the array is divided into equal sets of antenna elements (e.g., four antenna elements), but the array may be divided into sets of different amounts of antenna elements. In an alternative embodiment, each antenna element may alternate between select frequencies.

The efficiency of wireless power transmission as well as the amount of power that can be delivered (using pocket-forming) may be a function of the total number of antenna elements **1006** used in a given receivers and transmitters system. For example, for delivering about one watt at about 15 feet, a receiver may include about 80 antenna elements while a transmitter may include about 256 antenna elements. Another identical wireless power transmission system (about 1 watt at about 15 feet) may include a receiver with about 40 antenna elements, and a transmitter with about 512 antenna elements. Reducing in half the number of antenna elements in a receiver may require doubling the number of antenna elements in a transmitter. In some embodiments, it may be beneficial to put a greater number of antenna

elements in transmitters than in a receivers because of cost, because there will be much fewer transmitters than receivers in a system-wide deployment. However, the opposite can be achieved, e.g., by placing more antenna elements on a receiver than on a transmitter as long as there are at least two antenna elements in a transmitter **1002**B.

II. Wireless Power Software Management System

A. Systems and Methods for Managing and Controlling a Wireless Power Network (Basic)

FIG. **11** shows an exemplary embodiment of a wireless power network **1100** in which one or more embodiments of the present disclosure may operate. Wireless power network **1100** may include communication between wireless power transmitter **1102** and one or more wireless powered receivers. Wireless powered receivers may include a client device **1104** with an adaptable paired receiver **1106** that may enable wireless power transmission to the client device **1104**. In another embodiment, a client device **1104** include a wireless power receiver built in as part of the hardware of the device. Client device **1104** may be any device which uses an energy power source, such as, laptop computers, stationary computers, mobile phones, tablets, mobile gaming devices, televisions, radios and/or any set of appliances that may require or benefit from an electrical power source.

In one embodiment, wireless power transmitter **1102** may include a microprocessor that integrates a power transmitter manager app **1108** (PWR TX MGR APP) as embedded software, and a third party application programming interface **1110** (Third Party API) for a Bluetooth Low Energy chip **1112** (BLE CHIP HW). Bluetooth Low Energy chip **1112** may enable communication between wireless power transmitter **1102** and other devices such as, client device **1104**. In some embodiment, Bluetooth Low Energy chip **1112** may be utilize another type of wireless protocol such as Bluetooth®, Wi-Fi, NFC, and ZigBee. Wireless power transmitter **1102** may also include an antenna manager software **1114** (Antenna MGR Software) to control an RF antenna array **1116** that may be used to form controlled RF waves that act as power transmission signals that may converge in 3-d space and create pockets of energy on wireless power receivers. Although the exemplary embodiment recites the use of RF waves as power transmission signals, the power transmission signals may include any number of alternative or additional techniques for transmitting energy to a receiver converting the transmitted energy to electrical power.

Power transmitter manager app **1108** may call third party application programming interface **1110** for running a plurality of functions such as starting a connection, ending a connection, and sending data among others. Third party application programming interface **1110** may command Bluetooth Low Energy chip **1112** according to the functions called by power transmitter manager app **1108**.

Power transmitter manager app **1108** may also include a database **1118**, which may store database comprising identification and attribute information of the wireless power transmitter **1102**, of the receiver **1106**, and of client devices **1104**. Exemplary identification and attribute information includes identifiers for a client device **1104**, voltage ranges for a client device **1104**, location, signal strength and/or any relevant information from a client device **1104**. Database **1118** may also store information relevant to the wireless power network such as, receiver ID's, transmitter ID's, end-user handheld devices, system management servers, charging schedules (information indicative of the scheduling of a charge time for the client device **1104**), charging priorities and/or any data relevant to a wireless power network. Other examples of identification and attribute information include information indicative of level of power usage of one of the client device **1104**; information indicative of power received at the receiver **1106** that is available to the client device **1104**; and information of the duration of power usage of the client device.

Third party application programming interface **1110** at the same time may call power transmitter manager app **1108** through a callback function which may be registered in the power transmitter manager app **1108** at boot time. Third party application programming interface **1110** may have a timer callback that may go for ten times a second, and may send callbacks every time a connection begins, a connection ends, a connection is attempted, or a message is received.

Client device **1104** may include a power receiver app **1120** (PWR RX APP), a third party application programming interface **1122** (Third party API) for a Bluetooth Low Energy chip **1124** (BLE CHIP HW), and a RF antenna array **1126** which may be used to receive and utilize the pockets of energy sent from wireless power transmitter **1102**.

Power receiver app **1120** may call third party application programming interface **1122** for running a plurality of functions such as start a connection, end the connection, and send data among others. Third party application programming interface **1122** may have a timer callback that may go for ten times a second, and may send callbacks every time a connection begins, a connection ends, a connection is attempted, or message is received.

Client device **1104** may be paired to an adaptable paired receiver **1106** via a BLE connection **1128**. A graphical user interface (GUI **1130**) may be used to manage the wireless power network from a client device **1104**. GUI **1130** may be a software module that may be downloaded from any suitable application store and may run on any suitable operating system such as iOS and Android, among others. Client device **1104** may also communicate with wireless power transmitter **1102** via a BLE connection **1128** to send important data such as an identifier for the device as well as battery level information, antenna voltage, geographic location data, or other information that may be of use for the wireless power transmitter **1102**.

A wireless power manager **1132** software may be used in order to manage wireless power network **1100**. Wireless power manager **1132** may be a software module hosted in memory and executed by a processor inside a computing device **1134**. The wireless power manager **1132** may include instructions to generate outputs and to receive inputs via a Graphical User Interface (GUI), so that a user **1136** may see options and statuses, and may enter commands to manage the wireless power network **1100**. The computing device **1134** may be connected to the wireless power transmitter **1102** through standard communication protocols which may include Bluetooth®, Bluetooth Low Energy (BLE), Wi-Fi, NFC, and ZigBee®. Power transmitter manager app **1108** may exchange information with wireless power manager **1132** in order to control access and power transmission from client devices **1104**. Functions controlled by the wireless power manager **1132** may include, scheduling power transmission for individual devices, priorities between different client devices, access credentials for each client, physical location, broadcasting messages, and/or any functions required to manage the wireless power network **1100**.

FIG. **12** shows a sequence diagram **1200** for a real time communication between wireless powered transmitters and wireless powered receivers, according to an embodiment.

Sequence diagram **1200** illustrates the interactions between objects or roles in a wireless powered network. The

objects or roles described here may include, but is not limited to, a user **1202** which manages the wireless power network, a wireless power manager **1204** which serves as a front end application for managing the wireless power network, power receiver devices with corresponding power receiver apps **1206** and transmitters with corresponding power transmitter manager apps **1208**.

The process may begin when wireless power manager **1204** requests **1210** information from a power transmitter manager app **1208** hosted in a wireless transmitter. Request **1210** may include authentication security such as user name and password. Power transmitter manager apps **1208** may then verify the request **1210** and grant access to the wireless power manager **1204**.

Wireless power manager **1204** may continuously request **1210** information for different time periods in order to continue updating itself. Power transmitter manager app **1208** may then send database records **1212** to the wireless power manager **1204**. Wireless power manager **1204** may then display **1214** these records with options in a suitable GUI to a user **1202**. User **1202** may then perform different actions in order to manage the wireless power network. For example and without limitation, a user **1202** may configure powering schedules **1216** for different devices, the user **1202** may also establish priorities depending on time **1218**, type of client **1220**, physical location **1222** or may even choose to broadcast a message **1224** to client devices. The wireless power manager **1204** may then send **1226** the updated database records back to the power transmitter manager apps **1208**.

In a wireless network power grid more than one transmitter may be used. Power transmitter manager apps **1208** hosted on each transmitter may share updates **1228** to the device database. Power transmitter manager apps **1208** may then perform an action **1230** depending on the command and updates made by the user **1202** such as, charge a wireless device, send a message to the wireless devices, set a schedule to charge different devices, set power priority to specific devices, etc.

B. System and Method for a Self-system Analysis in a Wireless Power Transmission Network

FIG. **13** shows a wireless power transmission system **1300** using a wireless power transmitter manager **1302**, according to an embodiment. Wireless power transmitter manager **1302** may include a processor with computer-readable medium, such as a random access memory (RAM) (not shown) coupled to the processor. Examples of processor may include a microprocessor, an application specific integrated circuit (ASIC), and field programmable object array (FPOA), among others.

Under the control of wireless power transmitter manager **1302**, the wireless power transmission system **1300** may transmit controlled RF waves that act as power transmission signals that may converge in 3-d space and create pockets of energy on wireless power receivers. Although the exemplary embodiment recites the use of RF waves as power transmission signals, the power transmission signals may include any number of alternative or additional techniques for transmitting energy to a receiver converting the transmitted energy to electrical power.

Wireless power receiver **1304** may be paired with customer device **1306** or may be built into customer device **1306**. Examples of customer devices **1306** may include laptop computer, smartphones, tablets, music players, and toys, among other. Customer device **1306** may include a graphical user interface **1312** (GUI). Wireless power transmitter manager **1302** may receive customer device's signal strength from advertisement emitted by wireless power receiver **1304** for detecting if wireless power receiver **1304** is paired with customer device and also for the purpose of detecting if wireless power receiver **1304** is nearer to wireless power transmitter manager **1302** than to any other wireless power transmitter manager **2902** in the wireless power transmission system **1300**. Wireless power receiver **1304** may be defined as assigned to wireless power transmitter manager **1302**, which may have exclusive control and authority to change the wireless power receiver's record in device database **1316** until wireless power receiver **1304** moves to a new location closer to another wireless power transmitter manager **1302**. An individual copy of wireless power receiver's record may be stored in device database **1316** of each wireless power transmitter manager **1302** and also in each server of wireless power transmission system **1300**, through a cloud (not shown in FIG. **13**).

According to some aspects of this embodiment, one or more servers (not shown in FIG. **13**) may be a backup of device database **1316** shared by every wireless power transmitter manager **1302** in wireless power transmission system **1300**.

Under the control of wireless power transmitter manager **1302**, the wireless power transmission system **1300** may transfer power in a range up to 30 feet.

Wireless power transmitter manager **1302** may use, but is not limited to, Bluetooth low energy (BLE) to establish a communication link **1308** with wireless power receiver **1304** and a control link **1310** with customer device's graphical user interface (GUI). Wireless power transmitter manager **1302** may use control link **1310** to receive commands from and receive pairing information from customer device's graphical user interface (GUI).

Wireless power transmitter manager **1302** may include antenna manager software **1314** to track customer device **1306**. Antenna manager software **1314** may use real time telemetry to read the state of the power received by customer device **1306**.

According to some aspects of this embodiment, wireless power transmitter manager **1302** may include a device database **1316**, where device database **1316** may store three sub-dimensions of data: past, present, and future. The future data may include customer devices **1306** power schedules. The present data may include the locations and/or movements in the system, configuration, pairing, errors, faults, alarms, problems, messages sent between the wireless power devices, and tracking information, among others. With reference to FIG. **14**, the past data may include details such as the amount of power customer device **1306** used, the amount of energy that was transferred to customer device's battery, and thus sold to the customer who has or owns the device, the amount of time customer device **1306** has been assigned to a given wireless power transmitter manager. This past data includes for example information on when a customer device **1306** started pairing with graphical user interface **1312** (GUI), activities in the system, any action or event of any wireless power device in the system, errors, faults, and design problems, among others, for each customer device **1306** in wireless power transmission system **1300**. Device database **1316** may also store customer device's power schedule, customer device's status, names, customer sign-in names, authorization and authentication credentials, encrypted information, areas, details running the system, and information about all wireless power devices such as wireless power transmitter managers, wireless power receivers, end user hand-held devices, and servers, among others.

In other situations, there can be multiple wireless power transmitter managers **1302** and/or multiple wireless power receivers **1304** for powering various customer devices **1306**.

FIG. **14** illustrates a wireless power transmission network **1400**, according to an embodiment. In a wireless power transmission network **1400**, multiple wireless power transmitter managers and/or multiple wireless power receivers may be used for powering various customer devices **1402**. A wireless power receiver **1404** may be paired with customer device **1402** or may be built in customer device **1402**. Example of customer devices **1402** may include smartphones, tablets, music players, toys and others at the same time. Customer device **1402** may include a graphical user interface **1408** (GUI).

Each wireless power transmitter manager **1406** in wireless power transmission network **1400** may receive customer device's signal strength from advertisement emitted by wireless power receiver **1404** and graphical user interface **1408** (GUI) for the purpose of detecting if wireless power receiver **1404** is paired with graphical user interface **1408** (GUI) and also for detecting if wireless power receiver **1404** is nearer to wireless power transmitter manager **1406** than to any other wireless power transmitter manager **1406** in the wireless power transmission network **1400**. Wireless power receiver **1404** may be defined as assigned to wireless power transmitter manager **1406**, which may have exclusive control and authority to change the wireless power receiver's record in device database **1410** until wireless power receiver **1404** moves to a new location closer to another wireless power transmitter manager **1406**. An individual copy of wireless power receiver's record may be stored in device database **1410** of each wireless power transmitter manager **1406** and also in each server **1414** of wireless power transmission network **1400**, through a cloud **1416**.

According to some aspects of this embodiment, one or more servers **1414** may function as a backup of device database **1410** in the wireless power transmission network **1400**. Server **1414** may search devices in wireless power transmission network **1400**. Server **1414** may locate device database **1410** through UDP packets that are broadcast when a given wireless power transmitter manager **1406** boots up. The UDP packet may include the UUID of wireless power transmitter manager **1406** and also its location. To back up a specific device database **1410**, server **1414** may request access to a given wireless power transmitter manager **1406** in the network **1400**. Server **1414** may establish a connection with wireless power transmitter managers **1406** and wireless power transmitter manager **1406** may accept the connection and wait for the first amount of data from server **1414**. The first amount of data may be 128 bits UUID, once wireless power transmitter manager **1406** verifies the data, it may allow server **1414** to read a device database **1410**. Server **1414** may backup device database **1410**. Also wireless power transmitter manager **1406** may be able to reestablish its own device database **1410** from the information stored in server **1414**. For example if a given wireless power transmitter manager **1406** experience a power interruption, resulting in a software restart or system boot up, it may broadcast a UDP packet to search any server **1414** in the network **1400**. Once wireless power transmitter manager **1406** finds server **1414**, it may establish a TCP connection to restore its own device database **1410**.

Each wireless power transmitter manager in wireless power transmission network **1400** may include device database **1410**. When a record change in a given device database **1410**, this change may be distributed to all device databases **1410** in wireless power transmission network **1400**.

Device database **1410** may store three sub-dimensions of data: past, present, and future. The future data may include customer devices **1402** power schedules. The present data may include the locations and/or movements in the system, configuration, pairing, errors, faults, alarms, problems, messages sent between the wireless power devices, and tracking information, among others. The past data may include details such as the amount of power customer device **1402** used, the amount of energy that was transferred to customer device's battery, and thus sold to the customer who has or owns the device, the amount of time customer device **1402** has been assigned to a given wireless power transmitter manager **1406**, when did customer device **1402** start pairing with graphical user interface **1408** (GUI), activities in the system, any action or event of any wireless power device in the system, errors, faults, and design problems, among others, for each customer device **1402** in wireless power transmission network. Device database **1410** may also store customer device's power schedule, customer device's status, names, customer sign-in names, authorization and authentication credentials, encrypted information, areas, details running the system, and information about all wireless power devices such as wireless power transmitter managers, wireless power receivers, end user hand-held devices, and servers, among others.

Each wireless power device in wireless power transmission network **1400** may include a universally unique identifier (UUID). When a given wireless power transmitter manager **1406** boots up, and periodically thereafter, it may broadcast a user datagram protocol (UDP) packet that contains its unique UUID, and status to all devices in wireless power transmission network **1400**. The UDP packet is only distributed through the local network. Each wireless power transmitter manager **1406** and server **1414** in wireless power transmission network may establish, but is not limited to, a Wi-Fi connection **1412** to share updated device database's records between other wireless power devices in the system, including such device database information as: quality control information, wireless power device's status, wireless power device's configuration, control, logs, schedules, statistics, and problem reports, among others.

In another aspect of this embodiment, any wireless power transmitter manager, besides using UDP packets to send information through wireless power transmission network **3200**, may also use transmission control protocol (TCP) to exchange information outside the local network.

In another aspect of this embodiment, server **1414** and wireless power transmitter managers **1406** may be connected to a cloud **1416**. Cloud **1416** may be used to share between wireless power devices any device database information, among others.

According to some aspects of this embodiment, each wireless power transmitter manager **1406** and server **1414** in the network may be connected to a business cloud **1420** through an internet cloud **1418**. Business cloud **1420** may belong to a given business using a service provider to offer wireless power transfer to their users. Business cloud **1420** may be connected to a Business service provider server **1422**. Business service provider server **1422** may store marketing information, customer billing, customer configuration, customer authentication, and customer support information, among others.

Internet cloud **1418** may be also connected to a service provider cloud **1424**. Service provider cloud **1424** may store marketing and engineering information, such as less popular features, errors in the system, problems report, statistics, and quality control, among others.

Each wireless power transmitter manager **1406** may periodically establish a TCP connection with business cloud **1420** and service provider cloud **1424** to send its respective device database **1410**.

In a different aspect of this embodiment, each wireless power transmitter manager **1406** in wireless power transmission network **1400** may be able to detect failures in the network. Example of failure in the network may include overheating in any wireless power transmitter manager **1406**, malfunction, and overload, among others. If a failure is detected by any of wireless power transmitter manager **1406** in the system, then the failure may be analyzed by any wireless power transmitter manager **1406** in the system. After the analysis is completed, a recommendation may be generated to enhance or correct the system. The recommendation may be sent through cloud **1416** to business service provider server **1422** and also to service provider cloud **1424**. Service provider cloud **1424** may use the recommendation as quality control, engineering control, and to generated statistics, among others. Also the recommendation may be communicated to the person in charge of managing wireless power transmission network **1400** by text messages or E-mail. Also any device in the network with a copy of device database **1410** may be able to perform an analysis and generate a recommendation to enhance or correct the system.

In another aspect of this embodiment, each wireless power transmitter manager **1406** may send an alert message for different conditions, where wireless power transmitter manager **1406** may include a LED, which blinks for indicating under which conditions wireless power transmitter manager **1406** may be working.

In another aspect of this embodiment, wireless power transmitter manager **1406** may be able to detect failures on its own performance. If wireless power transmitter manager **1406** detects a failure, the analysis may be performed locally by wireless power transmitter manager **1406**. After the analysis is completed, a recommendation may be generated to enhance or correct the system. Then wireless power transmitter manager **1406** may send the information through cloud **1416** to business service provider server **1422** and service provider cloud **1424**. Also the recommendation may be communicated to the person in charge of managing wireless power transmission network **1400** by text messages or E-mail.

FIG. **15** is a flowchart **1500** of method for self-system analysis in a wireless power transmission network, according to an embodiment.

In a wireless power transmission network, multiple wireless power transmitter managers and/or multiple wireless power receivers may be used for powering various customer devices.

Each wireless power transmitter manager in the system may scan the wireless power transmission network, at step **1502**. Each wireless power transmitter manager in wireless power transmission network may receive customer device's signal strength from advertisement emitted by a wireless power receiver and a graphical user interface (GUI) for the purpose of detecting if wireless power receiver is paired with graphical user interface (GUI) and also for detecting if wireless power receiver is nearer to wireless power transmitter manager than to any other wireless power transmitter manager in the wireless power transmission network. Wireless power receiver may be defined as assigned to wireless power transmitter manager, which may have exclusive control and authority to change the wireless power receiver's record in device database until wireless power receiver moves to a new location closer to another wireless power transmitter manager. An individual copy of wireless power receiver's record may be stored in device database of each wireless power transmitter manager and also in each server of wireless power transmission network, through a cloud.

According to some aspects of this embodiment, one or more servers may function as a backup of the device database in the wireless power transmission network. The servers and wireless power transmitter managers in the wireless power transmission network may be connected to the cloud. The cloud may be used to share between system devices: quality control information, statistics, and problem reports, among others.

Wireless power transmitter manager may search for wireless power receivers to communicate with and send power. A wireless power receiver may be paired with customer device or may be built in customer device. Example of customer devices may include smartphones, tablets, music players, toys and others at the same time. Customer device may include a graphical user interface (GUI).

Wireless power transmitter manager may be able to detect failures in the wireless power transmission network, at step **1504**. Examples of failure may include loss of power, failure in the hardware or software of the wireless power transmitter manager, malfunction in a wireless power transmitter manager, and overload of the wireless power transmitter manager, and malfunction in a wireless power receiver, overheating or other environmental problems, and intrusion, among others.

If wireless power transmitter manager detects a failure in the wireless power transmission network, it may update its device database to register the failure, at step **1506**. Each wireless power transmitter manager in wireless power transmission network may include a device database, where device database may store three sub-dimensions of data: past, present, and future. The future data may include customer devices power schedules. The present data may include the locations and/or movements in the system, configuration, pairing, errors, faults, alarms, problems, messages sent between the wireless power devices, and tracking information, among others. The past data may include details such as the amount of power customer device used, the amount of energy that was transferred to customer device's battery, and thus sold to the customer who has or owns the device, the amount of time customer device has been assigned to a given wireless power transmitter manager, when did customer device start pairing with the graphical user interface (GUI), activities in the system, any action or event of any wireless power device in the system, errors, faults, and design problems, among others, for each customer device in wireless power transmission network. Device database may also store customer device's power schedule, customer device's status, names, customer sign-in names, authorization and authentication credentials, encrypted information, areas, details running the system, and information about all wireless power devices such as wireless power transmitter managers, wireless power receivers, end user hand-held devices, and servers, among others.

When a record changes in a given device database, this change may be distributed to all device databases in wireless power transmission network.

Subsequently, wireless power transmitter manager may analyze the failure in the wireless power transmission network, at step **1508**. In another aspect of this embodiment the failure may be analyzed by any device in the wireless power transmission network with a copy of device database.

After the analysis is completed, a recommendation may be generated to enhance or correct the system, at step **1510**.

Wireless power transmitter manager may send the recommendation to a business service provider server and also to service provider cloud, at step **1512**. Service provider cloud may use the recommendation as quality control, engineering control, and to generated statistics, among others. Also the recommendation may be communicated to the person in charge of managing wireless power transmission network by text messages or E-mail.

Else wireless power transmitter manager may continue scanning the wireless power transmission network, at step **1514**.

Examples

Example #1 is a wireless power transmission network with components similar to those described in FIG. **14**. The wireless power transmission network may be working in a school, where student may charge their electronic devices wirelessly. A student may be charging his cellphone in the science classroom. The student starts moving because he needs to take another class in a different classroom. The student arrives to the computer classroom, but he is unable to continue charging his cellphone. At the same time that the student arrives to the computer classroom the wireless power transmitter manager near to the computer classroom exceeds the amount of electronic devices to be powered. Wireless power transmitter manager may detect a failure in his performance and may start analyzing the reason performance was affected. Wireless power transmitter manager may find that an overload was the reason of its performance being affected. After the analysis is completed, a recommendation may be generated to enhance the system by installation of another wireless power transmitter manager. This recommendation may be sent to the manager of the wireless power transmission network by text messages or E-mail. Also the recommendation may be sent to the school service provider server and to the service provider cloud.

III. Status and Usage

A. Systems and Methods for Tracking the Status and Usage Information of a Wireless Power Transmission System

FIG. **16** illustrates a wireless power transmission system architecture **1600**, according to an exemplary embodiment.

According to some embodiments, wireless power transmission system architecture **1600** may include a multiple wireless power transmission systems **1602** which may be able to transmit information to a remote information service **1604** through an internet cloud **1606**. In some embodiments, a multiple wireless power transmission system **1602** may include one or more wireless power transmitters **1608**, zero or more computing device **1620** coupled with wireless power receivers **1610**, zero or more non-computing devices **1632** coupled with wireless power receivers **1610**, a system management service **1612**, and a local network **1614**. Network **1614** connections may refer to any suitable connection between computers such as intranets, local area networks (LAN), virtual private networks (VPN), wireless area networks (WAN), and the internet, among others.

According to some embodiments, each wireless power transmitter **1608** may include a wireless power transmitter manager **1616** and a distributed system database **1618**. Each wireless power transmitter **1608** may be able to manage and transmit power to one or more wireless power receivers **1610**, and each wireless power receiver **1610** may be able to charge and provide power to computing devices **1620** and/or non-computing devices **1632**. Examples of suitable computing devices **1620** may include smartphones, tablets, notebooks, and laptops, amongst others. Examples of suitable non-computing devices **1632** may include toys, toothbrushes, LED lights, game remote controls, and music players, amongst others.

Wireless power transmitter manager **1616** may be able to control the behavior of wireless power transmitters **1608**, monitoring different aspects, such as the started time of power transmission, the unique system identification of both wireless power transmitter **1608** and wireless power receiver **1610**, the amount of devices connected, the direction angle of the antennas used, as well as, the voltage at wireless power receiver **1610**'s antenna may be reported; and the real-time communication connection between wireless power transmitter **1608** and wireless power receiver **1610**, which may be used for tracking information from wireless power receiver **1610** no matter where it is located or moved; among others.

According to some embodiments, distributed system database **1618** may record relevant information from wireless power receivers **1610** within computing devices **1620**/non-computing devices **1632**, wireless power transmitter **1608**, and system management service **1612**. Information may include but is not limited to identifiers for computing devices **1620**/non-computing devices **1632**, voltage ranges for computing devices **1620**/non-computing devices **1632**, location, signal strength, wireless power receiver **1610** ID's, wireless power transmitter **1608** ID's, end-user handheld device names ID's, system management server ID's, charging schedules, charging priorities, and/or any data relevant to multiple wireless power transmission system **1602**. Additionally, wireless power transmitters **1608**, wireless power receiver **1610** within computing devices **1620**/non-computing devices **1632** and system management service **1612** may operate as system information generator.

System management service **1612** may automatically monitor the database integrity of each computing devices **1620**, and may automatically communicate with a computing devices **1620** to correct a detected error in its database. System management service **1612** may include components, such as a system management server **1634**, a system management manager **1636**, and a system management database **1638**.

Distributed system database **1618** may be implemented through known in the art database management systems (DBMS) such as, for example, MySQL, PostgreSQL, SQLite, Microsoft SQL Server, Microsoft Access, Oracle, SAP, dBASE, FoxPro, IBM DB2, LibreOffice Base, FileMaker Pro and/or any other type of database that may organize collections of data.

In some embodiments, wireless power transmitters **1608** may use network **1614** to send and receive information. Network **1614** may be a local area network, or any suitable communication system between the components of the multiple wireless power transmission system **1602**. Network **1614** may enable communication between two or more wireless power transmitters **1608**, the communication of wireless power transmitters **1608** with system management service **1612**, and may facilitate the communication between multiple wireless power transmission system **1602** and remote information service **1604** through internet cloud **1606**, amongst others.

Remote information service **1604** may be operated by the owner of the system, the manufacturer or supplier of the system, or a service provider. Remote information service **1604** may include different components, such as a back-end server **1622**, a remote information service manager **1624**, and a general remote information service database **1626**.

Back-end server **1622** and remote information service manager **1624** may be included into a single physical or virtual server. Remote information service database **1626** may include information data in a format or form discernible by remote information service **1604**, possibly in encrypted form. Additionally, wireless power transmitter **1608**, computing device **1620** and system management service **1612**, may generate usage and status information in a format or form discernible by remote information service **1604**, possibly in encrypted form. Remote information service database **1626** may be implemented through known in the art database management systems (DBMS) such as, for example, MySQL, PostgreSQL, SQLite, Microsoft SQL Server, Microsoft Access, Oracle, SAP, dBASE, FoxPro, IBM DB2, LibreOffice Base, FileMaker Pro and/or any other type of database that may organize collections of data.

Wireless power transmission system architecture **1600** may also include different authorized computing devices **1628**, which may access remote information service **1604** through internet cloud **1606** in order to collect and store information about the status and usage of multiple wireless power transmission system **1602**. The computing devices **1628** may be owned by system owner, manufacturer of system, or client for fee based distribution of status and usage information. The authorized computing devices **1628** may be operated by suitable users (e.g. clients, manufacturers or suppliers of the system) in order to determine if the multiple wireless power transmission system **1602** is operating correctly (or as expected) or has problems, as well as, to observe how the system is being used by users for marketing or customer service purposes. The collected information may be reported or edited by the authorized computing devices **1628** through a user interface **1630**, which may display different functions, and which may be a web site or other. The collected information may be provided in return for a fee.

FIG. **17** is a flowchart of a process **1700** to determine the status and usage information from a multiple wireless power transmission system. Specifically, the components included within the multiple wireless power transmission system may be a remote information service (cloud-based), a remote information service manager, a distributed system database, and client computing devices, among others. Additionally, each components in the multiple wireless power transmission system, such as wireless power transmitters, computing devices/non computing devices (coupled with wireless power receiver devices), and the system management service, may be considered as a system information generator.

The computing devices and the software modules within the multiple wireless power transmission system, may interact with each other through a suitable network connection. Network connections may refer to any suitable connection between computers such as intranets, local area networks (LAN), virtual private networks (VPN), wireless area networks (WAN), and the internet, among others.

According to one or more embodiments, process **1700** may start whenever a client computing device operated by a user, is connected to the multiple wireless power transmission system software (e.g. application software), at step **1702**. Specifically, the client computing device may initially download and install the multiple wireless power transmission system software from a public or private application store, where the application software may run on any computing device with operating system, such as iOS, Android, and Microsoft Windows, among others. Examples of computing devices may include smartphones, tablets, laptops, music players, and any other computing device.

Once the client computing device is connected to the multiple wireless power transmission system, users may interact with the multiple wireless power transmission system through a user interface displayed on the suitable client computing devices, at step **1704**. Users interface may allow users to interact with the multiple wireless power transmission system through different options, such as the selection of a computing device to be charged, monitor the status of charge of one or more wireless power receiver, and create a schedule charge for one or more wireless power receiver, report the time when transmission ended, and the total energy or power that was transmitted and received, among others.

The process may continue with step **1706**, where the system information generator may establish communication with the remote information server. Specifically, the remote information server may be located within the internet cloud or at a physical premises, and may be one or more discreet or virtual computer systems. Additionally, the system information generator may generate and store the information regarding the status and usage of the multiple wireless power transmission system within the distributed system database. Information may include but is not limited to, how all components of the system are used; the present status of the system; other categories of information including but is not limited to, errors, faults, problems, trouble reports, logs of operational events, each command issued by each user, user configurations, amount of power transmitted per power transmitter and per power receiver, metrics of all software and hardware activity, values measured or read from hardware of the system, metrics and details of every automatic operation performed by the system software, description and details of present and past location of all client computing devices and power receivers of the system, details of transmitter communications transitions (i.e. transfer of communications and/or control of power receiver from one power transmitter unit to another), all user scheduled configuration, all identifications of all system components, all software defined version labels for system components; and the present and past information for all of the above, times of occurrence, and identification of each associated system component for each of the above, among others.

The distributed system database may be implemented through known in the art database management systems (DBMS) such as, for example, MySQL, PostgreSQL, SQLite, Microsoft SQL Server, Microsoft Access, Oracle, SAP, dBASE, FoxPro, IBM DB2, LibreOffice Base, FileMaker Pro and/or any other type of database that may organize collections of data.

The software within the system information generator component that manages the distributed system database may automatically establish a secured or encrypted communication connection to verify the credentials of the remote information service, at step **1708** via ID code. If the remote information service' credentials are verified, the system information generator may transmit the information data to the remote information service, at step **1710**. However, if connection cannot be established with the remote information service, the disclosed system information generator may try again at a later time until the information data has been successfully sent to the remote information service.

Whenever the system information generator generates any information data to be stored in the distributed system database, the system information generator may create a system information record, at step **1712**, which may include information data in a format or discernible form by the remote information service, possibly in encrypted form.

Subsequently, when the information on demand is stored in the distributed system database, the remote information service may receive the information that may come from the system information generator, at step **1714**. Once the information on demand has been successfully received, remote information service replies with an acknowledgment message to system information generator, at step **1716**. The information may be stored within a remote information service database. Additionally, the remote information manager within the remote information service may be responsible to execute some actions, such as update information, receive information, store information, and send information to computing devices.

The process may continue at step **1718**, where once the information on demand has been successfully transmitted, the system information generator may delete the old disposable record of what it just sent to the remote information service from its local copy of the distributed system database in order to not overrun beyond its data storage capacity.

Finally, the authorized client computing device with the validated credentials may download the information from the remote information service, at step **1720**, and then the authorized client computing device may report and/or edit the information on demand, at step **1722** from the multiple wireless power transmission system.

The information may be used for different purposes such as for the observation or verification of past or present expected system status or operation, and system configuration; for the purpose of rapidly detecting and responding to problems, trouble, issues, errors, or faults within the system; for information including but not limited to statistics or metrics describing how the system features are in use for the purpose of increased accuracy of strategic marketing and sales focus; and for information required for billing end users, of the multiple wireless power transmission system, for power received.

Examples

Example #1 is an embodiment of a wireless power transmission system where a wireless power transmitter transmits power to a wireless power receiver to charge a client device attached to the receiver. After the transmission of power, the transmitter, also being a system information generator, establishes a communication connection with a remote information service, which may be Internet cloud based. The transmitter then communicates the detailed usage of the system in transmission of power from the transmitter through the receiver to the client device. The information service communicates an acknowledgement back to transmitter, and transmitter then deletes the usage information that was sent, to prevent transmitter's memory or database from overflowing. The information service may then distribute or provide for a fee the information to a user or computing device of another party.

The disclosed information may include, but is not limited to, the time when power transmission started, the unique system identification of both power transmitter and power receiver, the amount and direction angle of antennas used; as well as, the voltage at the power receiver's antenna reported by the power receiver to the power transmitter through the real-time communication connection between the transmitter and the receiver that is used for tracking the receiver no matter the receiver's location or movement.

B. Systems and Methods for Communication with Remote Management Systems

FIG. **18** shows a wireless power system architecture **1800**, according to an exemplary embodiment. System architecture **1800** may include one or more wireless power transmitters **1802**, and one or more wireless power receivers **1804**. In some embodiments, wireless power system architecture **1800** may include one or more electronic devices **1806**, where electronic devices **1806** may not have a built-in wireless power receiver **1804**. In other embodiments, wireless power system architecture **1800** may include electronic devices **1808** with a built-in power receiver **1804**.

Power transmitters **1802** may transmit controlled Radio Frequency (RF) waves which may converge in 3-D space. These RF waves may be controlled through phase and/or relative amplitude adjustments to form constructive and destructive interference patterns (pocket-forming). Pockets of energy may form at constructive interference patterns that may be 3-dimensional in shape whereas null-spaces may be present outside the constructive interference patterns.

According to exemplary embodiments, power transmitters **1802** may include a power transmitter manager application **1810**, a third party Bluetooth Low Energy (BLE) API **1812**, a BLE chip **1814**, an antenna manager software **1816** and an antenna array **1818** among other components. Power transmitter manager application **1810** may be an executable program loaded into a non-volatile memory within a power transmitter **1802**. Power transmitter manager application **1810** may control the behavior of power transmitter **1802**, monitor the state of charge of electronic devices **1806**, electronic devices **1808** and power receivers **1804**, may keep track of the location of power receivers **1804** and may execute power schedules, amongst others. In some embodiments, power transmitters **1802** may include a distributed wireless power transmission system database (not shown in figure) for storing information related to power receivers **1804**, electronic devices **1806**, power status, power schedules, IDs, pairing and any suitable information necessary for running the system.

Third party BLE API **1812** may enable the effective interaction between power transmitter manager application **1810** and BLE chip **1814**. Antenna manager software **1816** may process orders from power transmitter manager application **1810** and may control power and direction angle of antenna array **1818**.

Antenna arrays **1818** that may be included in power transmitters **1802** may include a number of antenna elements capable of transmitting power. In some embodiments, antenna array **1818** may include from up to 2612 antenna elements which may be distributed in an equally spaced grid. In one embodiment, antenna array **1818** may have an 8×8 grid to have a total of 64 antenna elements. In another embodiment, antenna array **1818** may have a 16×16 grid to have a total of 256 antenna elements. In another embodiment, antenna array **1818** may have a total of 512 antenna elements. However, the number of antenna elements may vary in relation with the desired range and power transmission capacity of power transmitter **1802**. Generally, with more antenna elements, a wider range and higher power transmission capacity may be achieved. Alternate configurations may also be possible including circular patterns or polygon arrangements, amongst others.

The antenna elements of antenna array **1818** may include suitable antenna types for operating in frequency bands such as 900 MHz, 2.5 GHz, 38.250 GHz, or 38.8 GHz, antenna elements may operate in independent frequencies, allowing a multichannel operation of pocket-forming.

Power transmitter **1802** may additionally include other suitable communications methods such as Wi-Fi, ZigBee and LAN amongst others.

Power receivers **1804** may include a power receiver application **1820**, a third party BLE API **1812**, a BLE chip

1814, and a power reception antenna array 1822. Power receivers 1804 may be capable of utilizing pockets of energy produced by power transmitter 1802 for charging or powering electronic devices 1806 and electronic devices 1808. Power receiver application 1820 may be an executable program loaded into a non-volatile memory within a power receiver 1804.

Third party BLE API 1812 may enable the effective interaction between power receiver application 1820 and BLE chip 1814. Antenna array 1822 may be capable of harvesting power from pockets of energy.

Electronic devices 1806 and electronic devices 1808 may include a GUI for managing the wireless power system architecture 1800. The GUI may be associated with an executable program loaded into a non-volatile memory. In some embodiments, electronic devices 1806 and electronic devices 1808 may include a distributed wireless power transmission system database (not shown in figure) for storing information related to power receivers 1804, power status, power schedules, IDs, pairing and any suitable information necessary for running the system.

In some embodiments, wireless power system architecture 1800 may include multiple power transmitters 1802 and/or multiple power receivers 1804 for charging a plurality of electronic devices 1806. In systems including multiple power transmitters 1802, the two or more power transmitters may be in constant communication using any suitable communication channel available, including Bluetooth®, BLE, Wi-Fi, ZigBee, LAN, LTE and LTE direct amongst others.

FIG. 19 illustrates a wireless power transmission system network 1900, according to an exemplary embodiment.

According to some embodiments, wireless power transmission system network 1900 may include multiple wireless power transmission systems 1902 capable of communicating with a remote management system 1904 through internet cloud 1906.

In some embodiments, wireless power transmission system 1902 may include one or more wireless power transmitters 1908, one or more power receivers 1910, one or more backup servers 1912 and a local network 1914.

According to some embodiments, each power transmitter 1908 may include a wireless power transmitter manager 1916 and a distributed wireless power transmission system database 1918. Each power transmitter 1908 may be capable of managing and transmitting power to one or more power receivers 1910, where each power receiver 1910 may be capable of charging or providing power to one or more electronic devices 1920.

Power transmitter managers 1916 may control the behavior of power transmitters 1908, monitor the state of charge of electronic devices 1920, and power receivers 1910, may keep track of the location of power receivers 1910 and may execute power schedules, run system check-ups and keep track of the energy provided to each of the different electronic devices 1920, amongst others.

According to some embodiments, database 1918 may store relevant information from electronic devices 1920 such as, identifiers for electronic devices 1920, voltage ranges for electronic devices 1920, location, signal strength and/or any relevant information from electronic devices 1920. Database 1918 may also store information relevant to the wireless power transmission system 1902 such as, receiver ID's, transmitter ID's, end-user handheld device names ID's, system management server ID's, charging schedules, charging priorities and/or any data relevant to a power transmission system network 1900.

Additionally, in some embodiments, database 1918 may store data of past and present system status.

The past system status data may include details such as the amount of power delivered to an electronic device 1920, the amount of energy that was transferred to a group of electronic devices 1920 associated with a user, the amount of time an electronic device 1920 has been associated to a wireless power transmitter 1908, pairing records, activities within the system, any action or event of any wireless power device in the system, errors, faults, and configuration problems, among others. Past system status data may also include power schedules, names, customer sign-in names, authorization and authentication credentials, encrypted information, physical areas of system operation, details for running the system, and any other suitable system or user-related information.

Present system status data stored in database 1918 may include the locations and/or movements in the system, configuration, pairing, errors, faults, alarms, problems, messages sent between the wireless power devices, and tracking information, among others.

According to some exemplary embodiments, databases 1918 within power transmitters 1908 may further store future system status information, where the future status of the system may be forecasted or evaluated according to historical data from past system status data and present system status data.

In some embodiments, records from all device databases 1918 in a wireless power transmission system 1902 may also be stored and periodically updated in server 1912. In some embodiments, wireless power transmission system network 1900 may include two or more servers 1912.

In another exemplary embodiment, wireless power transmitters 1908 may further be capable of detecting failures in the wireless power transmission system 1902. Examples of failures in power transmission system 1902 may include overheating of any component, malfunction, and overload, among others. If a failure is detected by any of wireless power transmitters 1908 within the system, then the failure may be analyzed by any wireless power transmitter manager 1916 in the system. After the analysis is completed, a recommendation or an alert may be generated and reported to owner of the power transmission system or to a remote cloud-based information service, for distribution to system owner or manufacturer or supplier.

In some embodiments, power transmitters 1908 may use network 1914 to send and receive information. Network 1914 may be a local area network, or any suitable communication system between the components of the wireless power transmission system 1902. Network 1914 may enable communication between power transmitters, the communication of power transmitters with server 1912, and may facilitate the communication between power transmission system 1902 and remote management system 1904, amongst others.

According to some embodiments, network 1914 may facilitate data communication between power transmission system 1902 and remote management system 1904 through internet cloud 1906.

Remote management system 1904 may be operated by the owner of the system, the manufacturer or supplier of the system or a service provider. Remote management system may include business cloud 1922, remote manager 1924 and backend server 1926, where the remote manager 1924 may further include a general database 1928. Functionality of backend server 1926 and remote manager 1924 can be combined into a single physical or virtual server.

General database **1928** may store additional backups of the information stored in the device databases **1918**. Additionally, general database **1928** may store marketing information, customer billing, customer configuration, customer authentication, and customer support information, among others. In some embodiments, general database **1928** may also store information, such as less popular features, errors in the system, problems report, statistics, and quality control, among others.

Each wireless power transmitter **1908** may periodically establish a TCP communication connection with remote manager **1924** for authentication, problem report purposes or reporting of status or usage details, among others.

FIG. **20** shows a flowchart of a general system status **2000** report generation process, according to an exemplary embodiment. Wireless power transmission systems may periodically send status reports to a remote management system, similar to the management systems previously described. General system status **2000** report generation process may start with past status report generation **2002**, in this step any server within a wireless power transmission system may gather information that may include details such as the amount of power delivered to each of the electronic devices in the system during a certain time period, the amount of energy that was transferred to a group of electronic devices associated with a user, the amount of time an electronic device has been associated to a wireless power transmitter, pairing records, activities within the system, any action or event of any wireless power device in the system, errors, faults, and configuration problems, among others. Past system status data may also include power schedules, names, customer sign-in names, authorization and authentication credentials, encrypted information, areas, details for running the system, and any other suitable system or user-related information.

Then, the server within the wireless power transmission system may run a system check-up **2004**. In this step, the server within the wireless power transmission system may check for any present failure, error or abnormal function of any system or subsystem components. Additionally, the server within the wireless power transmission system may check and perform an evaluation of the current system configuration.

Afterwards, the system may generate present status report **2006** and future status report **2008**. Present status report may include any present failure, error or abnormal function of any system or subsystem components; a list of presently online end-users and devices, current system configuration and power schedules, amongst others.

Future status report **2008** may include forecasts based on the extrapolation or evaluation of past and present system status reports. For example, the system may be able to extrapolate possible impending sub-system component failure based on logged past behavior of sub-system components. The system may also be able to evaluate the power schedules and determine if any device will be out of energy according to historical power consumption and current power schedule.

In some embodiments, the system may further evaluate the system configuration to check if any configuration set by an operator or end-user may cause an unwanted system behavior. Such will be reported using the same techniques described above.

Then, the wireless power transmitters may evaluate **2010** if an alert is needed. If an alert is needed, the alert may be immediately generated and sent **2012**. Depending of the type of problem detected, the alerts may be sent to the end-users, the system's owner, the service provider or any suitable combination, or to a remote system manager which can distribute a description of this urgent situation to customer service or other personnel via email, text message, or synthesized voice telephone call, according to alert configuration records stored within general database.

After the alert has been sent or if there is no alert needed, the server within the wireless power transmission system executing the report generation algorithm described in FIG. **20** may update **2014** its database with the reports and optionally back them up in a suitable server. If there are multiple servers, then only one at a time will be active for the generation of reports, while the others remain in stand-by mode, to take over if the active server goes offline. A hierarchy of priority will determine which online server is the present active (master) server.

Then, using a suitable TCP/IP connection the reports may be sent **2016** to a remote system manager for further evaluation. In some embodiments, the system may receive **2018** feedback from the remote system manager to indicate verification and storage of any received information.

FIG. **21** is a flowchart of a past status report **2100** generation process, according to an exemplary embodiment. The process for generation of a past status report **2100** may start with the generation **2102** of a non-end-user report, where non-end-user report may include logged activity, commands and configuration inputs of any non-end-user system operator.

Then, the system may generate **2104** a logged usage report which may include logged usage details and wireless energy consumption details. The wireless energy consumption details may include the amount of power delivered to each device and total amount of power delivered to the devices associated with each end user.

In some embodiments, the logged usage report may be used to compute power bills to charge end-users for the amount of wireless power received during a given time period.

Then, the system may generate **2106** an automatic actions report which may include automatic actions performed by or over any of the system components, including all power transmitters, power receivers, and any system management GUI.

Subsequently, the system may generate **2108** a location and movement report, which may include the location and movement tracking details of power receivers relative to power transmitters in the system.

After the reports have been generated the system may assemble past status report **2100** and update **2110** the database.

Then, using a suitable TCP/IP connection the reports may be sent **2112** to a remote system manager for further evaluation. In some embodiments, the system may receive **2114** feedback from the remote system manager to indicate verification and storage of any received information.

FIG. **22** is a flowchart of a present status report **2200** generation process, according to an exemplary embodiment. The process of generation of present status reports **2200** may start with the generation **2202** of a system functioning report, in which the system may evaluate the performance of each of the systems components to detect any failure, error or abnormal function of any system or subsystem component. Then the system may generate **2204** a list of all online users and devices. Afterwards, the system may generate **2206** a report of the current system configuration.

Additionally, the system may check **2208** the state of charge all the electronic devices within the system. If any

electronic device within the system is in urgent need **2210** of charge the system may generate and send **2212** an alert. The alert may be sent to the users in form of text messages, emails, voice synthesis telephone communication or any other suitable means.

In some embodiments, whenever an electronic device has a minimum amount of energy left the system may be capable of contacting the end-user to make the end user aware of the current state of charge of the electronic device.

After the reports have been generated the system may assemble present status report **2200** and update **2214** the database.

Then, using a suitable TCP/IP connection the reports may be sent **2216** to a remote system manager for further evaluation. In some embodiments, the system may receive **2218** feedback from the remote system manager to indicate verification and storage of any received information.

FIG. **23** is a flowchart of a future status report **2300** generation process, according to an exemplary embodiment. The process of generation of future status report **2300** may start with the generation **2302** of a component failure forecast in which impending sub-system component failure may be extrapolated from logged past behavior of sub-system components. Then the system may generate **2304** a device state of charge forecast, based on present rate of energy consumption of the devices, configured charging schedule, logged usage and any other suitable parameter. In this step the system may determine if any device will reach an unexpected critically low level of charge at some point in the future.

Afterwards, the system may perform **2306** a system configuration analysis, in which the system may evaluate any configuration set by the system operator or end-user to determine if it may cause any unwanted system behavior.

Then, if a problem was found **2308** in any of the first 3 steps, the system may generate a suitable alert **2310**. If an alert is sent to an end-user or system operator it may be in the form of text messages, emails, voice synthesis telephone communication or any other suitable means. In some embodiments, the system provider may be contacted by similar means.

Afterwards, the system may assemble future status report **2300** and update **2312** the database.

Subsequently, using a suitable TCP/IP connection the reports may be sent **2314** to a remote system manager for further evaluation. In some embodiments, the system may receive **2318** feedback from the remote system manager to indicate verification and storage of any received information.

Examples

In example #1 a wireless power transmission system generates a general status report as described in FIG. **20**. When checking the state of charge of the electronic devices within the system, an electronic device with critically low level of charge and no scheduled charge time is identified. In this example, the wireless power system is able to contact the owner of the electronic device via SMS message. The user schedules a charging period for the device and the device is charged before it runs out of energy.

In example #2 a wireless power transmission system generates a general status report as described in FIG. **20**. When checking the system configuration a possible unwanted behavior is identified. A device is scheduled to charge for too long without usage, which may cause overheating of some components. In this example, the power transmitter send a report to the remote management system and the remote management system sends an alert via email to the user.

In example #3 a wireless power service provider utilizes the past status reports generated by wireless power delivery system over the past 30 days to compute bills and charge end-users for their wireless power consumption.

In example #4 an end-user's electronic device requests wireless power. The wireless power transmitter utilizes a suitable TCP/IP connection to communicate with a remote system manager and authenticate the end-users credentials. The credentials of the end-user are authenticated and the electronic device is charged.

C. Status and Usage Embodiment (Graphical User Interface Demo)

Referring further to FIG. **16**, system **1600** includes a remote information service **1604**, or business cloud within Internet Cloud **1606**, with a processor (server **1622** and remote information service manager **1624**) in communication with remote information service database **1626**. The processor is configured to receive system operation data, also herein called status and usage data, from the wireless power transmission system **1602**. The system operation data can include one or more of power transmitter status, power transmitter usage, power receiver status, and power receiver usage.

Remote information service manager **1624** can generate records of the received system operation data, and can generate analyses of the system operation data. For example, the remote information service manager can generate statistics, data tables, charts, maps (e.g. local, regional, national, and international maps), financial analyses, data correlation analyses, and trend analyses. Remote information services manager **1624** can communicate records and analyses of the system operation data to client devices **1628** for display using a graphical user interface (GUI) **1630**. Client devices **1628** may include computing devices **1620** that are paired with power receivers **1610** for charging using pocket-forming energy in the wireless power transmission system, and may include workstations that are not paired with receivers.

Examples of system operation data, or status and usage data, received by the remote information service **1604** include errors, faults, trouble reports, logs of operational events, a command issued by the at least one power receiver, power receiver and power transmitter hardware configurations, amount of power transmitted per power transmitter and per power receiver, metrics of software and hardware activity, metrics of automatic operation performed by system software, location of the at least one power receiver, a transmitter communications transition, and power receiver charge scheduling configuration.

Other examples of status and usage data received by the remote information service **1604** include data pertaining to client devices (such as computing devices **1620** and non-computing device **1632**) that are registered with remote information service **1604** and that are paired with receivers **1610**. Examples of such status and usage information include battery level information, receiver antenna voltage, client device geographic location data, client device hardware configurations, metrics of client device charging activity, and client device charge scheduling.

Two functions of the wireless power management system are to track and report the status of transmitters, receivers, and devices within the network, and to track usage of the charging service by various devices and receivers. The wireless power management system collects and analyzes

the status and usage data, and provides a variety of analytics to system operators and authorized users.

An exemplary category of status and usage data involves measurement and reporting of energy harvested by a device from a wireless power receiver. In an embodiment, energy is harvested from a wireless power receiver by conversion of energy conveyed by power transmission signals such as RF waves, into electrical energy that is transmitted as direct current to a client device. This measurement in the wireless power system is analogous to an energy meter. In one embodiment, each receiver has non-volatile memory, which accumulates data on total energy harvest over time. Using BLE, receivers send response messages to the transmitter at 2200 times per second. Each time the receiver receives a BLE communication or energy wave from the transmitter, it records the spot power it harvests from the energy pocket and delivers to the device. The receiver counts number of power readings per second, and once a second sums the power transfer readings, providing a measurement of energy. The receiver IC then updates non-volatile memory with the latest energy measurement.

The wireless power management system continually uploads status and usage data from receivers, from transmitters, and from devices to the cloud-based management system. For example, as applied to energy harvest, the receiver communicates the updated energy harvest value to the transmitter, once a second. The transmitter accumulates this data for all receivers that it communicates with. Periodically, the transmitter uploads accumulated energy information to the cloud-based management system. By this means, the wireless power management system collects information on energy received by all receivers worldwide.

If given receivers move out of communication range from a transmitter, the information accumulated in non-volatile memory is available for later communication to a transmitter once in range. In addition, the information accumulated by the non-volatile memory can be made available to a user of the given device, e.g. to provide a report of his wireless energy harvest over time. Furthermore, enterprises with an information on energy harvest of all users would have access to this information collected from the respective devices.

This measurement of total energy harvest is used in the first instance to measure how much wireless power is being transferred. This data can be used to improve transmitter operation, for billing, and for other system management functions. For example, information on the energy received by assigned receivers from a given transmitter is used as feedback to the transmitter on the efficiency of power transfer. The transmitter may act on this information to adjust the phase and gain of its antennas in order to maximize the amount of harvested energy.

In the system **2400** of FIG. **24**, an operator/user may access status and usage information from graphical user interface (GUI) **2414** using a standard web browser on a computer device **2406**, such as a smartphone, a desktop computer, a laptop computer, a tablet, a PDA, and/or another type of processor-controlled device that may receive, process, and/or transmit digital data. Computer device **2406** may be configured to download the graphical user interface (GUI) **2414** from an application store to communicate with a remote information service **2402**. GUI **2414** is the Graphical User Interface between system users or operators and the software within the wireless power transmission system **2400**, and used for configuration, monitoring, command, control, reporting, and any other system management functionality. For example, users may employ GUI **2414** to view status and usage reports and analyses received from Remote Information Service **2402**, and to manage the wireless power transmission system **2400**.

Remote information service **2402** may comprise a business cloud that is accessible via through an internet cloud **2408** using web server **2416**. The operator/user may browse the specific URL or IP address associated to configuration GUI web pages provided by web service software **2412** operating within remote information service **2402**. GUI web pages may provide status and usage information stored in database **2410** of the remote information service **2402**. Web service software **2412** may use JavaScript or other suitable method for serving web pages, through embedded web, Apache, Internet Information Services (IIS), or any other suitable web server application.

The operator/user may obtain a specific URL or IP address associated to remote information service **2402** from some suitable source. The operator/user may use computer device **2406** with a suitable operating system such as Microsoft Windows, Apple iOS, Android or Linux, among others, to browse configuration GUI web pages **2414** using a standard web browser such as Chrome, Firefox, Internet Explorer, or Safari, among others, via an input device such as a touch screen, a mouse, a keyboard, a keypad, and others.

FIGS. **25-32** show exemplary graphical user interface (GUI) embodiments for status and usage reporting (graphical user interface demo). Primary display options (as seen at the left side of various display views, for example the screen shot of FIG. **25**) include dashboard, devices, locations, transmitters, accounts, and settings.

FIG. **25** shows an exemplary graphical user interface (GUI) **2500** for users to administer their account for a wireless power management system. The GUI **2500** exemplifies the scalable nature of the wireless power management system, as applied to display **2501** of statistics. Local, regional, national, or international organizations can view data and graphical depictions (e.g. the bubble charts seen here) of power transfer statistics, such as number of power transmitters, number of power receivers, volume of power transmitted, number of devices recognized, and number of devices currently charging.

FIG. **26** shows an exemplary GUI **2600** of the system displaying location and tracking within a home, office, or other facility. The user can select a room or other area within the facility, such as living room, and view status and usage metrics for transmitters (e.g. how many devices are currently being charged) and devices (charging status for each device). Data on the cloud-based management system can be viewed, as seen here, using a web portal.

FIG. **27** shows an exemplary GUI **2700** of the system displaying various types of status and usage data that is compiled by the management system, and made available to users, through the GUI **2700**, to help them analyze and manage their use of the wireless power service. The GUI **2700** show a bar chart **2701** of power received by a user's devices in each of the last five days. FIG. **28** shows an exemplary GUI **2800** of the system displaying recent usage history, i.e. a record of where and when each of a user's devices has received power, total power received and duration of power transfer.

Another format of status and usage reporting uses the form factor for PDAs and other mobile devices. FIGS. **29** and **30** show two views of a mobile phone app. These status and usage data represent a subset of the data available on using a web browser on a workstation, but are tailored to the most important status and usage categories for mobile device users. The mobile app GUI **2900** of FIG. **29** shows

the charging status and charge strength of a mobile phone. The mobile app GUI **2900** of FIG. **30** provides another example of location information, a map of a neighborhood with names and locations of businesses providing the wireless charging service.

FIG. **31** shows an example of an Accounts GUI **3100**, showing status and usage information for all transmitters that are registered to the account. This accounts screen permits an authorized user to register a new transmitter to the account. Other accounts screens permit users to register receivers and devices newly included in the management system, and to view status and usage data for such receivers and devices.

FIG. **32**, with Organizations GUI **3200**, illustrates how organizations can remotely monitor their power transfer activities at other geographic locations. Here an organization has a headquarters in Boise Id. with primary, secondary, and satellite locations in other parts of the U.S., as displayed at **3201**. A representative of the organization can select any of these locations using this screen, and monitor wireless power status and usage analytics at the selected location.

While various aspects and embodiments have been disclosed, other aspects and embodiments are contemplated. The various aspects and embodiments disclosed are for purposes of illustration and are not intended to be limiting, with the true scope and spirit being indicated by the following claims.

The foregoing method descriptions and the interface configuration are provided merely as illustrative examples and are not intended to require or imply that the steps of the various embodiments must be performed in the order presented. As will be appreciated by one of skill in the art the steps in the foregoing embodiments may be performed in any order. Words such as "then," "next," etc. are not intended to limit the order of the steps; these words are simply used to guide the reader through the description of the methods. Although process flow diagrams may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination may correspond to a return of the function to the calling function or the main function.

The various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the embodiments disclosed here may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present invention.

Embodiments implemented in computer software may be implemented in software, firmware, middleware, microcode, hardware description languages, or any combination thereof. A code segment or machine-executable instructions may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements. A code segment may be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, or memory contents. Information, arguments, parameters, data, etc. may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, etc.

The actual software code or specialized control hardware used to implement these systems and methods is not limiting of the invention. Thus, the operation and behavior of the systems and methods were described without reference to the specific software code being understood that software and control hardware can be designed to implement the systems and methods based on the description here.

When implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable or processor-readable storage medium. The steps of a method or algorithm disclosed here may be embodied in a processor-executable software module which may reside on a computer-readable or processor-readable storage medium. A non-transitory computer-readable or processor-readable media includes both computer storage media and tangible storage media that facilitate transfer of a computer program from one place to another. A non-transitory processor-readable storage media may be any available media that may be accessed by a computer. By way of example, and not limitation, such non-transitory processor-readable media may comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other tangible storage medium that may be used to store desired program code in the form of instructions or data structures and that may be accessed by a computer or processor. Disk and disc, as used here, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above should also be included within the scope of computer-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable medium and/or computer-readable medium, which may be incorporated into a computer program product.

What is claimed is:

1. A method of using a remote server to manage a wireless power transmission system, the method comprising:

at a remote server that is in communication with a plurality of power transmission managers, a first power transmission manager of the plurality of power transmission managers configured to control a first wireless power transmitter and a second power transmission manager of the plurality of power transmission managers configured to control a second wireless power transmitter:

receiving, from the first power transmission manager, information identifying a first electronic device that is associated with a first receiver, wherein the first electronic device is located closer to the first wireless power transmitter than to the second wireless power transmitter and the first electronic device has requested wireless power from the first wireless power transmitter;

receiving, from the second power transmission manager, a status report that includes information identifying a current or forecasted charge level for a second electronic device associated with a second receiver,

wherein the second electronic device is located closer to the second wireless power transmitter than to the first wireless power transmitter;

in response to receiving the information identifying the first electronic device:

determining, based at least in part on the information identifying the first electronic device, whether the first electronic device is authorized to receive power from the first wireless power transmitter; and

in accordance with a determination that the first electronic device is authorized to receive power from the first wireless power transmitter, transmitting instructions to the first wireless power transmission manager to cause the first wireless power transmitter to transmit power waves that constructively interfere proximate to the first electronic device;

in response to receiving the status report:

determining whether the information identifying the current or forecasted charge level indicates that the second electronic device requires charging; and

in accordance with a determination that the information identifying the current or forecasted charge level indicates that the second electronic device requires charging, sending, to a user associated with the second electronic device, an alert (i) indicating that the second electronic device requires charging and (ii) prompting the user to request wireless power.

2. The method of claim **1**, wherein determining that the second electronic device requires charging includes determining that no charging time is scheduled by the wireless power transmission system for the second electronic device.

3. The method of claim **2**, wherein determining that the second electronic device requires charging includes determining that the second electronic device has less than a minimum charge level remaining.

4. The method of claim **1**, wherein the forecasted charge level of the second electronic device is determined based at least in part on a present rate of energy consumption at the second electronic device.

5. The method of claim **1**, wherein the status report further includes information identifying a failure of a component of the second wireless power transmitter, and the method further comprises:

in response to receiving the status report that includes information identifying the failure of the component of the second wireless power transmitter, reporting the failure to an operator of the wireless power transmission system.

6. The method of claim **1**, wherein:

the power waves are radio frequency waves, and

the instructions that are transmitted to the first wireless power transmission manager include instructions that cause respective antenna elements of the first wireless power transmitter to transmit the radio frequency waves at respective angles so that the radio frequency waves constructively interfere proximate to the first electronic device.

7. The method of claim **1**, wherein respective locations of the first and second electronic devices relative to the first and second wireless power transmitters are determined based at least in part on respective signal strength levels for respective communication signals transmitted by the first and second electronic devices as detected by the first and second wireless power transmitter managers.

8. A system for using a remote server to manage a wireless power transmission system, the system comprising:

a remote server that is in communication with a plurality of power transmission managers, a first power transmission manager of the plurality of power transmission managers configured to control a first wireless power transmitter and a second power transmission manager of the plurality of power transmission managers configured to control a second wireless power transmitter, where the remote server is configured to:

receive, from the first power transmission manager, information identifying a first electronic device that is associated with a first receiver, wherein the first electronic device is located closer to the first wireless power transmitter than to the second wireless power transmitter and the first electronic device has requested wireless power from the first wireless power transmitter;

receive, from the second power transmission manager, a status report that includes information identifying a current or forecasted charge level for a second electronic device associated with a second receiver, wherein the second electronic device is located closer to the second wireless power transmitter than to the first wireless power transmitter;

in response to receiving the information identifying the first electronic device:

determine, based at least in part on the information identifying the first electronic device, whether the first electronic device is authorized to receive power from the first wireless power transmitter; and

in accordance with a determination that the first electronic device is authorized to receive power from the first wireless power transmitter, transmit instructions to the first wireless power transmission manager to cause the first wireless power transmitter to transmit power waves that constructively interfere proximate to the first electronic device;

in response to receiving the status report:

determine whether the information identifying the current or forecasted charge level indicates that the second electronic device requires charging; and

in accordance with a determination that the information identifying the current or forecasted charge level indicates that the second electronic device requires charging, send, to a user associated with the second electronic device, an alert (i) indicating that the second electronic device requires charging and (ii) prompting the user to request wireless power.

9. The system of claim **8**, wherein determining that the second electronic device requires charging includes determining that no charging time is scheduled by the wireless power transmission system for the second electronic device.

10. The method of claim **9**, wherein determining that the second electronic device requires charging includes determining that the second electronic device has less than a minimum charge level remaining.

11. The method of claim **8**, wherein the forecasted charge level of the second electronic device is determined based at least in part on a present rate of energy consumption at the second electronic device.

12. The method of claim **8**, wherein the status report further includes information identifying a failure of a component of the second wireless power transmitter, and the remote server is further configured to:

in response to receiving the status report that includes information identifying the failure of the component of

the second wireless power transmitter, report the failure to an operator of the wireless power transmission system.

13. The method of claim **8**, wherein:

the power waves are radio frequency waves, and

the instructions that are transmitted to the first wireless power transmission manager include instructions that cause respective antenna elements of the first wireless power transmitter to transmit the radio frequency waves at respective angles so that the radio frequency waves constructively interfere proximate to the first electronic device.

14. The method of claim **8**, wherein respective locations of the first and second electronic devices relative to the first and second wireless power transmitters are determined based at least in part on respective signal strength levels for respective communication signals transmitted by the first and second electronic devices as detected by the first and second wireless power transmitter managers.

15. A non-transitory computer-readable storage medium that includes executable instructions that, when executed by a remote server that is in communication with a plurality of power transmission managers, a first power transmission manager of the plurality of power transmission managers configured to control a first wireless power transmitter and a second power transmission manager of the plurality of power transmission managers configured to control a second wireless power transmitter, cause the remote server to:

receive, from the first power transmission manager, information identifying a first electronic device that is associated with a first receiver, wherein the first electronic device is located closer to the first wireless power transmitter than to the second wireless power transmitter and the first electronic device has requested wireless power from the first wireless power transmitter;

receive, from the second power transmission manager, a status report that includes information identifying a current or forecasted charge level for a second electronic device associated with a second receiver, wherein the second electronic device is located closer to the second wireless power transmitter than to the first wireless power transmitter;

in response to receiving the information identifying the first electronic device:

determine, based at least in part on the information identifying the first electronic device, whether the first electronic device is authorized to receive power from the first wireless power transmitter; and

in accordance with a determination that the first electronic device is authorized to receive power from the first wireless power transmitter, transmit instructions to the first wireless power transmission manager to cause the first wireless power transmitter to transmit power waves that constructively interfere proximate to the first electronic device;

in response to receiving the status report:

determine whether the information identifying the current or forecasted charge level indicates that the second electronic device requires charging; and

in accordance with a determination that the information identifying the current or forecasted charge level indicates that the second electronic device requires charging, send, to a user associated with the second electronic device, an alert (i) indicating that the second electronic device requires charging and (ii) prompting the user to request wireless power.

16. The non-transitory computer-readable storage medium of claim **15**, wherein determining that the second electronic device requires charging includes determining that no charging time is scheduled by the wireless power transmission system for the second electronic device.

17. The non-transitory computer-readable storage medium of claim **16**, wherein determining that the second electronic device requires charging includes determining that the second electronic device has less than a minimum charge level remaining.

18. The non-transitory computer-readable storage medium of claim **15**, wherein the forecasted charge level of the second electronic device is determined based at least in part on a present rate of energy consumption at the second electronic device.

19. The non-transitory computer-readable storage medium of claim **15**, wherein the status report further includes information identifying a failure of a component of the second wireless power transmitter, and the executable instructions include executable instructions that cause the remote server to:

in response to receiving the status report that includes information identifying the failure of the component of the second wireless power transmitter, report the failure to an operator of the wireless power transmission system.

20. The non-transitory computer-readable storage medium of claim **15**, wherein:

the power waves are radio frequency waves, and

the instructions that are transmitted to the first wireless power transmission manager include instructions that cause respective antenna elements of the first wireless power transmitter to transmit the radio frequency waves at respective angles so that the radio frequency waves constructively interfere proximate to the first electronic device.

21. The non-transitory computer-readable storage medium of claim **15**, wherein respective locations of the first and second electronic devices relative to the first and second wireless power transmitters are determined based at least in part on respective signal strength levels for respective communication signals transmitted by the first and second electronic devices as detected by the first and second wireless power transmitter managers.

* * * * *