



US 20190329391A1

(19) **United States**

(12) **Patent Application Publication**
HUANG et al.

(10) **Pub. No.: US 2019/0329391 A1**

(43) **Pub. Date: Oct. 31, 2019**

(54) **NAIL BLOCKING MEMBER FOR NAIL GUN**

(71) Applicant: **EVERWIN PNEUMATIC CORPORATION**, Taichung City (TW)

(72) Inventors: **WEN-SHENG HUANG**, Taichung City (TW); **WEI-JEN CHEN**, Taichung City (TW)

(21) Appl. No.: **15/967,198**

(22) Filed: **Apr. 30, 2018**


Publication Classification


(51) **Int. Cl.**
B25C 13/00 (2006.01)
B25C 7/00 (2006.01)
B25C 1/18 (2006.01)

(52) **U.S. Cl.**
CPC **B25C 13/00** (2013.01); **B25C 1/188** (2013.01); **B25C 7/00** (2013.01)

(57) **ABSTRACT**


A nail blocking member for nail gun is provided. The nail gun includes a firing portion for firing a nail. When an object is pressed upon the nail blocking member by the firing portion, the nail is fired by the firing portion to enter the object. The nail blocking member includes a main body having a contact face, with a formation groove concavely disposed on the contact face, and a guiding block convexly disposed in the formation groove. An object is pressed upon the contact face by the firing portion, and a nail is fired by the firing portion to enter the object to hit the guiding block, such that the nail is guided by the guiding block to move toward the formation groove, so as to be bent along the formation groove and reversely folded back into the object.





PRIOR ART

FIG. 1



PRIOR ART

FIG. 2




FIG. 3




FIG. 5

NAIL BLOCKING MEMBER FOR NAIL GUN

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to nail guns, and more particularly, to a nail blocking member for nail gun.

2. Description of the Related Art

[0002] In a pallet factory, a large amount of nailing operations are carried out, such that the staff apply a nail gun for executing the nailing operation.

[0003] Referring to FIG. 1 and FIG. 2, a nail gun 1 includes a firing portion 3 for firing a nail 2. The user applies the firing portion 3 to press two stacked boards 4 upon the nail blocking member 5. When the firing portion 3 fires the nail 2 to the stacked boards 4, the nail 2 passes through the stacked boards 4, so as to be bent into a J form due to the blockage of the nail blocking member 5. Therefore, the nail 2 is fixed on the stacked boards 4.

[0004] The surface 6 of a conventional nail blocking member 5 is formed in a plane shape. The stacked boards 4 are pressed upon the surface 6 of the nail blocking member 5 by the firing portion 3. However, the nail 2 is fired by the firing portion 3 along a random radial direction. When the nail 2 hits the surface 6 of the nail blocking member 5, due to the random radial firing direction, the bending angle of the nail 2 may not conform to the desired bending orientation. Therefore, the nail 2 is possibly bent into a shape other than the desired J shape.

[0005] If the nail 2 is not bent into the J shape, as a result, the stacked boards 4 are unable to be completely combined, such that the nail 2 may possibly be detached from the stacked boards 4, causing the stacked boards 4 to be not usable. In addition, with the bent nail 2 projecting from the stacked boards 4, injuries might be caused upon the transporters of the stacked boards.

SUMMARY OF THE INVENTION

[0006] For improving the issues above, an embodiment of the present invention discloses a nail blocking member for nail gun. When the nail passes through the object to hit the guiding block, the guiding block guides the nail to move along the formation groove, such that the nail is bent along the formation groove. Therefore, by use of the guiding block and the formation groove, the nail is allowed to be bent into the desired shape and fixed on the object.

[0007] For achieving the aforementioned objectives, a nail blocking member for nail gun in accordance with an embodiment of the present invention is provided. The nail gun includes a firing portion for firing a nail. When an object is pressed upon the nail blocking member by the firing portion, the nail is fired by the firing portion of the nail gun, so as to pass through the object. The nail blocking member includes:

[0008] a main body provided with a contact face, with a formation groove concavely disposed on the contact face, and a guiding block convexly disposed in the formation groove,

[0009] wherein an object is pressed upon the contact face by the firing portion, and a nail is fired by the firing portion to enter the object to hit the guiding block, such that the nail is guided by the guiding block to move toward the formation

groove, so as to be bent along the formation groove and reversely folded into the object.

[0010] With such configuration, when the nail is fired by the firing portion, the guiding block guides the nail to the formation groove, and the nail is bent along the formation groove. Therefore, the issue of the nail unable to be bent in a desired manner when hitting the plane shaped nail blocking member is resolved

[0011] In an embodiment of the present invention, a guiding face is disposed inclined to connect the guiding block and the formation groove. Therefore, the nail is able to move to the formation groove along the inclined guiding face, so as to be smoothly bent.

[0012] In an embodiment of the present invention, a transition face is disposed inclined to connect the formation groove and the contact face. Therefore, the nail is able to be folded back into the object along the transition face, so as to increase the bending effect of the nail.

[0013] In an embodiment of the present invention, the formation groove is formed in a circular shape, with the guiding block convexly disposed at the center of the formation groove. Therefore, when the nail is fired along a radial direction, with the guiding block guiding the nail to move toward the formation groove which surrounds the guiding block, the firing direction of the nail is prevented from affecting the bending direction of the nail, such that the nail is bent to form the desired shape.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 is a schematic view illustrating a conventional nail blocking member applied with a nail gun.

[0015] FIG. 2 is a schematic view illustrating a fired nail hitting the conventional nail blocking member.

[0016] FIG. 3 is a perspective view of a nail blocking member in accordance with an embodiment of the present invention.

[0017] FIG. 4 is a schematic view illustrating the nail blocking member in accordance with an embodiment of the present invention applied with a nail gun.

[0018] FIG. 5 is a schematic view illustrating a fired nail hitting the nail blocking member in accordance with an embodiment of the present invention.

[0019] FIG. 6 is a schematic view illustrating the nail blocking member in accordance with an embodiment of the present invention connected with a nail gun.

DETAILED DESCRIPTION OF THE INVENTION

[0020] The aforementioned and further advantages and features of the present invention will be understood by reference to the description of the preferred embodiment in conjunction with the accompanying drawings where the components are illustrated based on a proportion for explanation but not subject to the actual component proportion.

[0021] Referring to FIG. 3 to FIG. 6, an embodiment of the present invention provides a nail blocking member 100 for a nail gun 200. The nail gun 200 includes a gun head 201, a handle (not shown) and a nail magazine (not shown) connected with the gun head 201, a firing portion 203 disposed at one end of the gun head 201 for firing nails 202, and a trigger (not shown) disposed at one side of the gun head 201. The user grips the handle of the nail gun 200. The nail magazine contains a plurality of nails 202. The nail 202

includes a head end **202a** and a tail end **202b**. A cavity is disposed between the gun head **201** and the handle, such that the cavity is connected with a pressure source, allowing a compressed air to enter into the cavity.

[0022] When user needs to fire the nail **202** through an object **204**, the nail blocking member **100** is placed on a plane, such as a table or the ground surface which is able to hold the nail blocking member **100**, and presses the object **204** upon the nail blocking member **100** with the firing portion **203**. Then, the user controls the trigger, driving the compressed air to strike the nail **202**, such that the nail **202** is fired by the firing portion **203** to enter the object **204**. As a result, the head end **202a** of the nail **202** is stuck on the surface of the object **204**, and the tail end **202b** of the nail **202** passes through the object **204**. The object **204** is allowed to be wood boards, stacked boards, or pallets.

[0023] The nail blocking member **100** of the present invention includes a main body **10**.

[0024] The main body **10** includes a contact face **11** and a bottom face **12** disposed in opposite to the contact face **11**. The contact face **11** includes a concave formation groove **13**, with a guiding block **14** convexly disposed in the formation groove **13**. In an embodiment of the present invention, the main body **10** is formed of a metal material. The contact face **11** is formed in a plane shape. The formation groove **13** is formed in an approximate circular shape. The guiding block **14** projects at the center of the formation groove **13**, with the bottom face **12** of the guiding block **14** formed in an approximate circular shape and. In other words, the formation groove **13** is concavely formed around the guiding block **14**, and the contact face **11** is convexly formed around the formation groove **13**.

[0025] A guiding face **15** is disposed to be connected between the guiding block **14** and the formation groove **13**. Also, the guiding face **15** is disposed inclined. Also, the guiding face **15** expands from the guiding block **14** toward the formation groove **13**. The junction between the guiding face **15** and the formation groove **13** is formed in an arc shape. In an embodiment of the present invention, the junction between the guiding face **15** and the guiding block **14** is formed in an arc face, and the junction between the guiding face **15** and the formation groove **13** is formed in an arc face, wherein the arc face between the guiding face **15** and the guiding block **14** is larger than the arc face between the guiding face **15** and the formation groove **13**.

[0026] A transition face **16** is disposed to be connected between the formation groove **13** and the contact face **11**. Also, the transition face **16** is disposed inclined. Also, the transition face **16** expands from the contact face **11** toward the formation groove **13**. In an embodiment of the present invention, the formation groove **13** and the transition face **16** include an obtuse angle, and the transition face **16** and the contact face **11** include an obtuse angle.

[0027] When the object **204** is to be processed, the object **204** is pressed upon the contact face **11** by the firing portion **203**. The user controls the trigger, so as to fire the nail **202** by the firing portion **203**. The tail end **202b** of the nail **202** passes through the object **204** and hits the top face **141** of the guiding block **14**, such that the tail end **202b** of the nail **202** is guided by the guiding face **15** to slide to the formation groove **13**. Because the firing portion **203** keeps pressing the object **204**, the pressing force forces the tail end **202b** of the nail **202** to be bent according to the shape of the formation groove **13**, such that the transition face **16** forces the tail end

202b of the nail **202** to be folded back toward the object **204**. Therefore, the nail **202** is bent into a J form, as shown by FIG. 5.

[0028] In addition, a distance from the bottom face **12** to the contact face **11** is defined as a first length **L1**; a distance from the bottom face **12** to the top face **141** of the guiding block **14** is defined as a second length **L2**; the first length **L1** is larger than or equal to (not smaller than) the second length **L2**. In an embodiment of the present invention, the first length **L1** is equal to the second length **L2**. When the first length **L1** is larger than or equal to the second length **L2**, the object **204** is stably pressed upon the contact face **11** or upon the contact face **11** and the top face **141** of the guiding block **14**. Therefore, upon firing the nail **202** by the firing portion **203**, gap is prevented from being generated between the contact face **11** and the object **204**, so as to assure that the nail **202** is smoothly bent.

[0029] In another embodiment of the present invention, referring to FIG. 6, the main body **10** includes a connection portion **17** which is convexly disposed at the bottom face **12**. The connection portion **17** is connected with the clamp **205** of the nail gun **200**. The contact face **11** faces the firing portion **203** of the nail gun **200**. In an embodiment of the present invention, the main body **10** is fixed to one end of the clamp **205** of the nail gun **200** through the connection portion **17**, wherein the clamp **205** of the nail gun **200** is allowed to pivot against the firing portion **203**. When the clamp **205** moves away from the firing portion **203**, the object **204** is optionally released from or placed between the main body **10** and the firing portion **203**. When the clamp **205** move toward the firing portion **203**, the clamp **205** is allowed to clamp the object **204**.

[0030] When the object **204** is to be processed, the object **204** is clamped by the clamp **205** and the firing portion **203** of the nail gun **200**, such that the object **204** is pressed upon the contact face **11** by the firing portion **203**. Then, the user controls the trigger to fire the nail **202** by the firing portion **203**. The tail end **202b** of the nail **202** passes through the object **204** and hits the top face **141** of the guiding block **14** and further guided by the guiding face **15** to slide to the formation groove **13**. As a result, the tail end **202b** of the nail **202** is bent according to the shape of the formation groove **13**, and is further folded back toward the object **204**. Therefore, the nail **202** is bent into a J shape.

[0031] With the nail blocking member **100** of the present invention, when the nail **202** passes through the object **204** to hit the main body **10** of the nail blocking member **100**, the nail **202** efficiently slides along the inclined guiding face **15** and the arc face conjunction to the formation groove **13**, with the tail end **202b** of the nail **202** being further folded back toward the object **204** through the transition face **16**. Therefore, the nail **202** is smoothly bent into the desire J shape.

[0032] Furthermore, when the nail **202** is fired by the firing portion **203** along a radial direction, with the guiding face **15** disposed between the guiding block **14** and the formation groove **13** surrounding the guiding block **14**, the nail **202** is allowed to be bent into the J shape without being affected by the random radial firing direction.

[0033] Although particular embodiments of the invention have been described in detail for purposes of illustration, various modifications and enhancements may be made with-

out departing from the spirit and scope of the invention. Accordingly, the invention is not to be limited except as by the appended claims.

What is claimed is:

1. A nail blocking member for nail gun, the nail gun including a firing portion for firing a nail, with an object pressed upon the nail blocking member by the firing portion, and the nail fired by the firing portion of the nail gun to enter the object, the nail blocking member including:

a main body provided with a contact face, with a formation groove concavely disposed on the contact face, and a guiding block convexly disposed in the formation groove,

wherein the object is pressed upon the contact face by the firing portion, and a nail is fired by the firing portion to enter the object to hit the guiding block, such that the nail is guided by the guiding block to move toward the formation groove, so as to be bent along the formation groove and reversely folded back into the object.

2. The nail blocking member of claim 1, wherein a guiding face is disposed inclined and connected between the guiding block and the formation groove.

3. The nail blocking member of claim 2, wherein the guiding face expands from the guiding block toward the formation groove.

4. The nail blocking member of claim 2, wherein a junction between the guiding face and the guiding block is formed in an arc shape, and a junction between the guiding face and the formation groove is formed in an arc shape.

5. The nail blocking member of claim 3, wherein a junction between the guiding face and the guiding block is formed in an arc shape, and a junction between the guiding face and the formation groove is formed in an arc shape.

6. The nail blocking member of claim 1, wherein a transition face is disposed inclined and connected between the formation groove and the contact face.

7. The nail blocking member of claim 2, wherein a transition face is disposed inclined and connected between the formation groove and the contact face.

8. The nail blocking member of claim 6, wherein the transition face expands from the contact face toward the formation groove.

9. The nail blocking member of claim 7, wherein the transition face expands from the contact face toward the formation groove.

10. The nail blocking member of claim 6, wherein the formation groove is formed in a circular shape, and the guiding block is convexly disposed at a center of the formation groove.

11. The nail blocking member of claim 10, wherein a top face of the guiding block is formed in a circular shape.

12. The nail blocking member of claim 7, wherein the formation groove is formed in a circular shape, and the guiding block is convexly disposed at a center of the formation groove.

13. The nail blocking member of claim 12, wherein a top face of the guiding block is formed in a circular shape.

14. The nail blocking member of claim 1, wherein the main body includes a bottom face disposed in opposite to the contact face, with a distance between the bottom face to the contact face defined as a first length, a distance between the bottom face and a top face of the guiding block defined as a second length, the first length being not smaller than the second length.

15. The nail blocking member of claim 1, wherein the main body includes a bottom face disposed in opposite to the contact face and a connection portion, the connection portion convexly disposed at the bottom face, the connection portion connected with a clamp of the nail gun, the contact face facing the firing portion of the nail gun.

* * * * *