

(19) **United States**

(12) **Patent Application Publication**
Rafko

(10) **Pub. No.: US 2019/0330882 A1**

(43) **Pub. Date: Oct. 31, 2019**

(54) **SANITIZING DOOR HANDLE WITH
EXTERNAL FLUID CONTAINER**

(52) **U.S. Cl.**
CPC *E05B 1/0069* (2013.01); *A61L 2/18*
(2013.01); *B65D 83/20* (2013.01); *B65D*
83/267 (2013.01)

(71) Applicant: **KleanTouch LLC**, Scottsdale, AZ (US)

(72) Inventor: **Michael Rafko**, Scottsdale, AZ (US)

(21) Appl. No.: **16/000,650**

(22) Filed: **Jun. 5, 2018**

Related U.S. Application Data


(60) Provisional application No. 62/663,506, filed on Apr. 27, 2018, provisional application No. 62/663,506, filed on Apr. 27, 2018.

Publication Classification

(51) **Int. Cl.**
E05B 1/00 (2006.01)
B65D 83/26 (2006.01)
B65D 83/20 (2006.01)

(57) **ABSTRACT**

Various implementations of the invention are directed toward a sanitizing door handle and/or components of such sanitizing door handle. Some implementations of the invention are directed toward a manual sanitizing door handle while some implementations of the invention are directed toward an auto-sanitizing door handle. According to some implementations of the invention, a sanitizing fluid is dispensed directly onto an exterior surface of the sanitizing door handle in connection with an operation of the door handle to sanitize the door handle. According to some implementations of the invention, a sanitizing fluid is dispensed directly onto a user's hand(s) in connection with an operation of the door handle to sanitize the user's hand(s).






FIGURE 1





FIGURE 2






FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8

SANITIZING DOOR HANDLE WITH EXTERNAL FLUID CONTAINER

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This Application is related to the following patent applications:

[0002] 1) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1010.1), entitled “Sanitizing Door Handle,” and filed on Jun. 5, 2018;

[0003] 2) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1020.1), entitled “Sanitizing Door Handle Fluid Container Assembly,” and filed on Jun. 5, 2018;

[0004] 3) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1030.1), entitled “Method for Dispensing a Fluid during Door Operation,” and filed on Jun. 5, 2018;

[0005] 4) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1040.1), entitled “Handle-Mounted Distribution Manifold,” and filed on Jun. 5, 2018;

[0006] 5) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1050.1), entitled “Distribution Manifold with Integrated Check Valve,” and filed on Jun. 5, 2018; and

[0007] 6) U.S. patent application Ser. No. _____ (Attorney Docket No. K101 1070.1), entitled “Electronic Sanitizing Door Handle,” and filed on Jun. 5, 2018.

This Application claims priority to U.S. Provisional Patent Application No. **62/663,506**, entitled “Sanitizing Door Handle,” and filed on April 27, 2018. Each of the foregoing patent applications is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0008] The invention is generally related to door handles, and more specifically to sanitizing door handles.

BACKGROUND OF THE INVENTION

[0009] Conventional door handles suffer from actual or perceived cleanliness or sanitation issues. Such door handles may include, but are not limited to, restroom door handles, medical/hospital door handles, refrigerator or other food storage door handles, hotel/motel door handles, airplane bathroom handles, school door handles, clean room door handles, and other door handles.

[0010] In some instances, door handles with improved cleanliness and/or sanitation are needed. In some instances, door handles with fluid dispensers, such as, but not limited to sanitizing fluid dispensers, are needed.

SUMMARY OF THE INVENTION

[0011] Various implementations of the invention are directed toward a sanitizing door handle and/or components of such sanitizing door handle such that the sanitizing door handle is sanitized or cleaned in some fashion. Various implementations of the invention are directed toward a manual sanitizing door handle and/or components of such sanitizing door handle. In such implementations, a user manually operates a pump that dispenses a fluid, such as, but not limited to, a sanitizing fluid, onto a grip of the sanitizing door handle. Various implementations of the invention are

directed toward an auto-sanitizing door handle. In such implementations of the invention, the user operates the sanitizing door handle, and such operation automatically actuates the pump to dispense the fluid onto the the grip of the sanitizing door handle. In some implementations of the invention, the fluid is dispensed directly onto an exterior of the sanitizing handle. In some implementations of the invention, the fluid is dispensed into an interior of the sanitizing handle and flows through to the exterior of the sanitizing handle. In various implementations of the invention, the fluid selected for use with various implementations of the invention controls, in part, the level of “cleaning” or “sanitizing” of the door handle from sterilized to disinfected to cleaned or to some other level of cleanliness.

[0012] Various implementations of the invention are directed to a hand sanitizing dispenser that dispenses a fluid, such as a sanitizing fluid, onto hand(s) of a user when the user operates or otherwise engages a door handle, such as, but not limited to, the sanitizing door handles discussed above. In some implementations of the invention, the fluid is dispensed directly onto the hands of the user. In some implementations of the invention, the fluid is dispensed onto the exterior of the sanitizing handle and is subsequently passed onto the hands of the user through contact with the sanitizing door handle. In some implementations of the invention, the fluid is dispensed into an interior of the sanitizing handle, flows through to the exterior of the sanitizing handle, and subsequently is passed onto the hands of the user through contact with the sanitizing door handle. In various implementations of the invention, the fluid selected for use with various implementations of the invention controls, in part, the level of “cleaning” or “sanitizing” of the hands of the user from sterilized to disinfected to cleaned or to some other level of cleanliness.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 illustrates a sanitizing door handle from a first perspective in accordance with various implementations of the invention.

[0014] FIG. 2 illustrates a sanitizing door handle from a second perspective in accordance with various implementations of the invention.

[0015] FIG. 3 illustrates a sanitizing fluid assembly in accordance with various implementations of the invention.

[0016] FIG. 4 illustrates a door handle grip in accordance with various implementations of invention.

[0017] FIG. 5 illustrates a distribution manifold in accordance with various implementations of invention.

[0018] FIG. 6 illustrates a fluid pump and a keyed check valve in accordance with various implementations of the invention.

[0019] FIG. 7 illustrates a keyed check valve receiver in accordance with various implementations of the invention.

[0020] FIG. 8 illustrates a fluid container housing separate from a door handle in accordance with various implementations of the invention.

DETAILED DESCRIPTION

[0021] Various implementations of the invention are directed toward a sanitizing door handle and/or components of such sanitizing door handle such that the sanitizing door handle is sanitized or cleaned in some fashion. Various implementations of the invention are directed toward a

manual sanitizing door handle and/or components of such sanitizing door handle. In such implementations, a user manually operates a pump that dispenses a fluid, such as, but not limited to, a sanitizing fluid, onto a grip of the sanitizing door handle. Various implementations of the invention are directed toward an auto-sanitizing door handle. In such implementations of the invention, the user operates the sanitizing door handle, and such operation automatically actuates the pump to dispense the fluid onto the the grip of the sanitizing door handle. In some implementations of the invention, the fluid is dispensed directly onto an exterior of the sanitizing handle. In some implementations of the invention, the fluid is dispensed into an interior of the sanitizing handle and flows through to the exterior of the sanitizing handle. In various implementations of the invention, the fluid selected for use with various implementations of the invention controls, in part, the level of “cleaning” or “sanitizing” of the door handle from sterilized to disinfected to cleaned or to some other level of cleanliness.

[0022] Various implementations of the invention are directed to a hand sanitizing dispenser that dispenses a fluid, such as a sanitizing fluid, onto hand(s) of a user when the user operates or otherwise engages a door handle, such as, but not limited to, the sanitizing door handles discussed above. In some implementations of the invention, the fluid is dispensed directly onto the hands of the user. In some implementations of the invention, the fluid is dispensed onto the exterior of the sanitizing handle and is subsequently passed onto the hands of the user through contact with the sanitizing door handle. In some implementations of the invention, the fluid is dispensed into an interior of the sanitizing handle, flows through to the exterior of the sanitizing handle, and subsequently is passed onto the hands of the user through contact with the sanitizing door handle. In various implementations of the invention, the fluid selected for use with various implementations of the invention controls, in part, the level of “cleaning” or “sanitizing” of the hands of the user from sterilized to disinfected to cleaned or to some other level of cleanliness.

[0023] These, and other implementations and/or inventions and/or components thereof are now described.

Sanitizing Door Handle

[0024] FIG. 1 illustrates a sanitizing door handle 100 from a first perspective according to various implementations of the invention. FIG. 2 illustrates sanitizing door handle 100 from a second perspective according to various implementations of the invention. Door handle 100 includes a door handle housing 110 having a housing wall 115. Housing wall 115 may be fabricated from a variety of materials, including, but not limited to: metal, plastic, ceramic, fiberglass, wood, polymer, rubber, or other materials that may be used to fabricate housing wall 115, and/or combinations thereof, as would be appreciated. Housing wall 115 forms a hollow interior housing chamber 112 of door handle housing 110. Housing wall 115 may be formed from one or more housing wall components. In some implementations of the invention, at least one housing wall component is detachable from housing wall 115 in order to provide access to interior housing chamber 112. In some implementations of the invention, housing wall 115 is detachable from a door in order to provide access to interior housing chamber 112. Interior housing chamber 112 and its purpose is described in further detail below.

[0025] Door handle 100 may be configured as a grip, a knob, a lever, a button, a pushbar, a pullbar, a latch, or other suitable handle by which a user opens, closes, latches, unlatches, locks, unlocks, or otherwise operates door handle 100 to open or close a door to which door handle 100 is operatively attached. In some implementations of the invention, door handle 100 may be configured to push open the door. In some implementations of the invention, door handle 100 may be configured to pull open the door. In some implementations of the invention, door handle 100 may be configured to push to actuate a latch to open the door. In some implementations of the invention, door handle 100 may be configured to pull to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to rotate up to open the door. In some implementations of the invention, door handle 100 may be configured to rotate down to open the door. In some implementations of the invention, door handle 100 may be configured to rotate up to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to rotate down to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to slide left to open the door. In some implementations of the invention, door handle 100 may be configured to slide right to open the door. In some implementations of the invention, door handle 100 may be configured to slide left to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to slide right to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to be depressed to open the door. In some implementations of the invention, door handle 100 may be configured to be depressed to actuate the latch to open the door. In some implementations of the invention, door handle 100 may be configured to open the door or actuate the latch in other manners as would be appreciated.

[0026] According to various implementations of the invention, door handle 100 includes a door handle grip 120. In some implementations of the invention, door handle grip 120 may be fabricated from a variety of materials, including, but not limited to: metal (e.g., aluminum, titanium, stainless steel, etc.), plastic, polymer, ceramic, fiberglass, wood, rubber, other materials that may be used to fabricate door handle grip 120, and/or combinations thereof (e.g., polymer coated metal, etc.), as would be appreciated.

[0027] In some implementations of the invention, door handle grip 120 is operatively coupled to, for example, a door latch linkage 160 and/or a door latch actuator 170 as illustrated in FIG. 1 and FIG. 2. As would be appreciated, door latch actuator 170 operatively engages a door latch which in turn allows a door to open and/or close as would be appreciated. In some implementations of the invention, door latch linkage 160 may also be operatively coupled to a pump actuator (not otherwise illustrated) configured to, mechanically or electronically, actuate fluid pump 140 when the user operates door handle 100 via door handle grip 120 as would be appreciated.

[0028] According to various implementations of the invention, when the user operates door handle 100 via door handle grip 120, a fluid is dispensed onto door handle grip 120. In some implementations of the invention, the fluid is a sanitizing fluid that is dispensed onto door handle grip 120 to sanitize door handle grip 120. In some implementations of the invention, the sanitizing fluid is dispensed directly onto

door handle grip **120** to sanitize door handle grip **120**. In some implementations of the invention, the sanitizing fluid is dispensed into an interior of door handle grip **120** and flows through door handle grip **120** to sanitize door handle grip **120**. In various implementations of the invention, the sanitizing fluid may be dispensed onto door handle grip **120**, before, during, and/or after the operation of door handle **100** by the user.

[0029] According to various implementations of the invention, when the user operates door handle **100** via door handle grip **120**, a fluid is dispensed onto the hand(s) of the user. In some implementations of the invention, the fluid is a sanitizing fluid that is dispensed onto the hand(s) of the user to sanitize the hand(s). In some implementations of the invention, the sanitizing fluid is dispensed directly onto the hand(s) of the user to sanitize the hand(s). In some implementations of the invention, the sanitizing fluid is dispensed directly onto door handle grip **120** to sanitize the hand(s) of the user when the hand(s) come into contact with handle grip **120**. In some implementations of the invention, the sanitizing fluid is dispensed into an interior of door handle grip **120** and flows through door handle grip **120** to sanitize the hand(s) of the user when the hand(s) come into contact with handle grip **120**. In various implementations of the invention, the sanitizing fluid may come into contact with the hand(s) before, during, and/or after the operation of door handle **100** by the user.

Fluid Container Assembly

[0030] In some implementations of the invention, door handle **100** includes a fluid container assembly disposed in interior housing chamber **112**. FIG. 3 illustrates a fluid container assembly **300** according to various implementations of the invention. (Various components of fluid container assembly **300**, such as fluid container **130** and a fluid pump **140**, are also illustrated in FIG. 1 and FIG. 2 in an exemplary configuration.) In some implementations of the invention, fluid container assembly **300** may include fluid container **130**, fluid pump **140**, one or more sections of tubing **310** (illustrated in FIG. 3, for example, as tubing **310A** and tubing **310B**). In some implementations of the invention, fluid container assembly **300** may also include a distribution manifold **330**. In some implementations of the invention, fluid container assembly **300** may also include a tubing cap **320** or other termination. In some implementations of the invention, fluid container assembly **300** may also include a check valve **350**.

[0031] According to various implementations of the invention, fluid pump **140** is coupled to fluid container **130** and configured to pump a fluid (not otherwise illustrated) from inside of fluid container **130** into tubing **310**. In some implementations of the invention, tubing **310** is operatively coupled to fluid pump **140**; however, in other implementations of the invention, tubing **310** may be operatively coupled directly to fluid container **130** as would be appreciated. In some implementations of the invention such as that illustrated in the drawings, fluid pump **140** is a diaphragm pump which operates by mechanically depressing the diaphragm of fluid pump **140** to force some amount of the fluid out of fluid container **130**, through fluid pump **140**, and into tubing **310**. In some implementations of the invention, other types of pumps may be used, including various other mechanical type or electrical type pumps. In some implementations of the invention, fluid pump **140** may be

manually actuated by the user; for example, the user may depress the diaphragm of fluid pump **140** to fluid actuate pump **140**. In some implementations of the invention, fluid pump **140** may be indirectly actuated by the user; for example, fluid pump **140** may be indirectly and automatically actuated when the user operates door handle **100**, either via cams, levers, linkages, etc., to mechanically actuate fluid pump **140**, or via a switch to electrically actuate fluid pump **140**, as would be appreciated.

[0032] In some implementations of the invention, the fluid may be a sanitizing fluid, which may include any fluid having sterilizing, disinfecting, antiseptic, antimicrobial, and/or other sanitizing or cleaning properties. Active ingredients in the sanitizing fluid may include alcohol-based sanitizing fluids such as, but not limited to, isopropyl alcohol, ethyl alcohol, n-propanol, and other alcohol-based fluids; or non-alcohol-based sanitizing fluids such as, but not limited to, benzalkonium chloride (a chemical disinfectant), triclosan (an antiseptic), thymol (an organic antibacterial agent), and/or other non-alcohol-based sanitizing fluids. In some implementations of the invention, the active ingredients may be mixed with a carrier ingredient such as glycerol or other gel-like ingredient to achieve a certain amount of viscosity as would be appreciated. In some implementations of the invention, the active ingredients may be aerosolized to be sprayed onto hand(s) or door handles as would be appreciated. Sanitizing fluids are available from various manufacturers and sold under names, including, but not limited to: Purell®, Germ-X®, CleanWell™, Babyganics®, CVS®, Blum Naturals®, and other manufacturers and/or names.

[0033] In some implementations of the invention, tubing **310** facilitates transport of sanitizing fluid from fluid container **130** through distribution manifold **330** to door handle grip **120**. In some implementations of the invention, tubing **310** facilitates transport of sanitizing fluid from fluid container **130** to door handle grip **120**; in such implementations, door handle grip **120** incorporates distribution manifold **330** or door handle grip **120** functions on its own in a manner similar to distribution manifold **330**. In various implementations, tubing **310** may include, but is not limited to: nylon tubing, vinyl tubing, pvc tubing, rubber tubing, Teflon tubing, Tyron tubing, hdpe tubing, PFA tubing, FEP tubing, MFA tubing, PTFE tubing and other types of tubing as would be appreciated.

Distribution Manifold

[0034] FIG. 5 illustrates distribution manifold **330** in further detail. In some implementations of the invention, distribution manifold **330** is formed separate from and then coupled to tubing **310**. In some implementations of the invention, distribution manifold **330** is formed as part of tubing **310**. According to various implementations of the invention, distribution manifold **330** dispenses fluid from an interior of distribution manifold **330** to an exterior of distribution manifold **330** via a plurality of distribution holes, such as distribution holes **510** in FIG. 5. In some implementations of the invention, distribution holes **510** are formed around a circumference of distribution manifold **330**. In some implementations of the invention, distribution holes **510** are formed along a length of distribution manifold **330**. In some implementations of the invention, distribution holes **510** are formed along the circumference and the length of distribution manifold **330**. In some implementations of

the invention, distribution holes **510** are formed only along a portion of the circumference and/or a portion of the length of distribution manifold **330**. In some implementations of the invention, a single distribution hole **510** may be used. In some implementations of the invention, a plurality of distribution holes **510** may be used. Various numbers of distribution holes **510** may be used and configured in various patterns as would be appreciated. In some implementations of the invention, distribution manifold **330** may be terminated (i.e., closed such that no fluid may exit its end). In some implementations of the invention, distribution manifold **330** may be terminated by a tubing cap **520**.

[0035] In some implementations of the invention, distribution holes **510** are sized based on various fluid parameters of the sanitizing fluid, for example, viscosity, evaporation rate, density, and/or other various fluid parameters. In some implementations of the invention, distribution holes **510** may be “self-healing” in the sense that when the sanitizing fluid in distribution manifold **330** is under pressure (e.g., pressure created by fluid pump **140**), distribution holes **510** open, allowing sanitizing fluid to be dispensed; and when the sanitizing fluid in distribution manifold **330** is not under pressure, distribution holes **510** close, allowing little, if any, sanitizing fluid to be dispensed. Such self-healing implementations may be configured using, for example, nylon tubing, or the like, as would be appreciated. In some implementations of the invention, distribution manifold **330** is coupled to and/or disposed within door handle grip **120**.

[0036] In some implementations of the invention, fluid container assembly **300** is a replacement fluid container assembly **300** such that once the fluid is emptied from fluid container assembly **300**, such an “empty” fluid container assembly **300** may be removed from door handle **100**, and a new fluid container assembly **300** may be installed in door handle **100**. In some implementations of the invention, fluid container assembly **300** may be sold together with door handle **100**; while in some implementations of the invention, fluid container assembly **300** may be sold separately from door handle **100** as would be appreciated. In some implementations of the invention, fluid container **130** may be refillable without replacing fluid container assembly **300**.

Door Handle Grip

[0037] FIG. 4 illustrates door handle grip **120** in further detail. Door handle grip includes a distal grip end **410** and a proximal grip end **420**. In some implementations of the invention, grip wall **125** forms a hollow interior grip chamber **440** extending from proximal grip end **420** to distal grip end **410**. In some implementations of the invention, distal grip end **410** is closed and proximal grip end **420** is open. In some implementations of the invention, both ends **410**, **420** are open. While door handle grip **120** is illustrated as generally cylindrical in FIG. 4, other shapes and configurations may be used. For example, door handle grip **120** may be configured to conform with any shape of a door interface with which the user comes into contact to operate door handle **100**, including configured to conform entirely around such door interface, partially around such door interface, or simply on one or more surfaces of such door interface, as would be appreciated.

[0038] In some implementations of the invention, a plurality of grip holes (illustrated, for example, as a plurality of grip holes **430** in FIG. 4) are formed into grip wall **125**. In some implementations of the invention, grip holes **430** serve

to transfer the fluid from interior grip chamber **440** to an exterior grip surface **450** of door handle grip **120**. In this way, the fluid entering interior grip chamber **440** from proximal grip end **420** is dispensed through interior grip chamber **440**, through grip holes **430** and onto exterior grip surface **450**. In some implementations of the invention, grip holes **430** are located on door handle grip **120** in regions where the user is likely to engage door handle **100** in order to operate door handle **100**. In some implementations of the invention, grip holes **430** are formed around a circumference of door handle grip **120**. In some implementations of the invention, grip holes **430** are formed along a length of door handle grip **120**. In some implementations of the invention, grip holes **430** are formed along the circumference and the length of door handle grip **120**. In some implementations of the invention, grip holes **430** are formed only along a portion of the circumference and/or a portion of the length of door handle grip **120**. In some implementations of the invention, a single grip hole **430** may be used. In some implementations of the invention, a plurality of grip holes **430** may be used. In some implementations of the invention, grip holes **430** are formed in a length of about a hand’s width (e.g., 3-6 inches). In some implementations of the invention, grip holes **430** are formed in a length of about two hand’s width (e.g., 6-12 inches). Other lengths of grip holes **430** along door handle grip **120** may be used as would be appreciated. Various numbers of grip holes **430** may be used and configured in various patterns as would be appreciated.

[0039] In some implementations of the invention, distribution manifold **330** is operatively coupled to door handle grip **120**. In some implementations of the invention, distribution manifold **330** is disposed in interior grip chamber **440** of door handle grip **120**. In such implementations, when the fluid is dispensed through distribution manifold **330**, the fluid enters interior grip chamber **440** of door handle grip **120** and is subsequently dispensed through grip holes **430** to exterior grip surface **450** of door handle grip **120**. In some implementations of the invention, distribution holes **510** are aligned with grip holes **430** to facilitate flow of the fluid through distribution manifold **330** to exterior grip surface **450** of door handle grip **120** as would be appreciated.

[0040] In some implementations of the invention, distribution manifold **330** is integrated directly into door handle grip **120**. In such implementations, tubing **310** is operatively coupled to door handle grip **120** which in turn functions as both grip and distribution manifold as discussed above.

Check Valve

[0041] In some implementations of the invention, check valve **340** is coupled between fluid pump **140** and distribution manifold **330**. In some implementations of the invention, check valve **340** is coupled directly to fluid pump **140**. In some implementations of the invention, check valve **340** is coupled directly to distribution manifold **330**. In some implementations of the invention, check valve **340** is coupled to tubing **310** in between pump **140** and distribution manifold **330** (i.e., check valve **340** coupled between tubing **310A** and **310B** as illustrated in FIG. 3).

[0042] According to various implementations of the invention, check valve **340** is configured to allow the fluid from fluid container **130** to flow in only one direction, namely from fluid container **130** to distribution manifold **330**. When actuated, fluid pump **140** pumps (i.e., forces) the fluid from fluid container **130** into tubing **310**, through check

valve **340** and on toward distribution manifold **330**. Once pressure from fluid pump **140** subsides, check valve **340** closes to prevent the fluid from flowing back to fluid container **130** and also to maintain pressure in tubing **310** between check valve **340** and distribution manifold **330** until the fluid is dispensed.

[0043] In some implementations of the invention, check valve **340** may be shaped or “keyed” to aid in aligning or positioning various components of fluid container assembly **300** in door handle **100**. For example, FIG. **6** illustrates fluid pump **140** coupled to a keyed check valve **630** in accordance with various implementations of the invention. In some implementations of the invention, a pump seat **610** may be integrated into interior housing chamber **112** to align, orient and/or position fluid pump **140** in interior housing chamber **112**. As illustrated, pump seat **610** may include a keyed check valve receiver **620**. In some implementations of the invention, only keyed check valve **630** may fit into keyed check valve receiver **620**. FIG. **7** illustrates an example of a keyed hole **710** formed in keyed check valve receiver **620** configured to receive keyed check valve **630**. As would be appreciated, keyed hole **710** and keyed check valve **630** may have corresponding shapes different from that illustrated in FIG. **7**. For example, while keyed hole **710** (and corresponding keyed check valve **630**) is illustrated as generally hexagon and isometric in shape, keyed hole **710** may be other than generally hexagonal in shape or other than generally isometric in shape. Also for example, while keyed hole **710** is illustrated as having two semicircular protrusions, keyed hole **710** may have other numbers of protrusions or other indentations (e.g., semicircular indentations) as would be appreciated. In some implementations of the invention, keyed check valve **630** may be friction fit into keyed hole **710** as would be appreciated. In some implementations of the invention, keyed check valve **630** may be snap fit into keyed hole **710** as would be appreciated.

[0044] In some implementations of the invention (not otherwise illustrated), keyed check valve **630** may be directly coupled to distribution manifold **330**. In such implementations, keyed check valve receiver **620** may be integrated into door handle grip **120** to align, orient, and/or position distribution manifold **330** in door handle grip. In some implementations of the invention (not otherwise illustrated), keyed check valve **630** and keyed check valve receiver **630** may be disposed at various locations in door handle **100** to maintain alignment, orientation, and/or position of various components of fluid container assembly **300** as would be appreciated.

[0045] While keyed check valve **630** is described herein as a single component, it may be separated into two separate components, namely a check valve and a key, as would be appreciated. While fluid pump **140** and keyed check valve **630** are illustrated in FIG. **6** as being directly coupled to one another, in other implementations, tubing **310** may be disposed between fluid pump **140** and keyed check valve **630** as would be appreciated.

Tubing Cap

[0046] In some implementations of the invention, tubing cap **320** is shaped or “keyed” to a corresponding key hole in distal end **410** of interior grip chamber **440** of door handle grip **120**. In some implementations of the invention, tubing cap **320** is sized to friction fit or snap fit tubing cap **320** into the key hole of interior grip chamber **440** of door handle grip

120 to maintain alignment, orientation, and/or position of distribution manifold **330** within interior grip chamber **440** as would be appreciated.

Fluid Container Housing External to Door Handle

[0047] In various implementations of the invention, fluid container **130** (and associated components) are disposed externally to a door handle. FIG. **8** illustrates a fluid container housing **820**, including fluid container **130**, separate from and external to a door handle **830** in accordance with various implementations of the invention. Such implementations may be desirable in situations where space, access, clearance and/or configuration considerations do not permit installation of door handle **100**. In these implementations of the invention, fluid container housing **820** houses fluid container **130** and other components of fluid container assembly **300** (not otherwise illustrated in FIG. **8**) as would be appreciated. Fluid container **130** is operatively coupled to external tubing **840**, which in some implementations of the invention, may be covered, for example, with braided reinforcement to protect external tubing **840** as would be appreciated. In some implementations of the invention, fluid container housing is mounted on the same side of a door **810** as door handle **830**. In some implementations of the invention, fluid container housing is mounted on the opposite side of door **810** as door handle **830**. In some implementations of the invention, fluid container housing is mounted on a wall (not otherwise illustrated in FIG. **8**) near door **810** on either the same or opposite side of door **810** as door handle **830**. Depending on which side of door **810** fluid container housing **820** is mounted in relation to door handle **830**, external tubing **840** may be configured to pass through a hole **850** in door **810**, such as is illustrated in FIG. **8**. Then, in a manner similar to that described above, external tubing **840** is operatively coupled to door handle grip **120** surrounding door handle **830**. These implementations of the invention may utilize a battery-operated electrical pump disposed in or proximate to fluid container housing **820** and a switch disposed in door handle **830** or in door handle grip **120** for purposes of dispensing fluid from fluid container **130** to exterior grip surface **450** of door handle grip **120**.

[0048] While various implementations of the invention have been described herein in reference to certain door handles illustrated in the drawings, for example, other door handles and configurations thereof may be used as would be appreciated.

What is claimed:

1. A door handle comprising:

- a door handle grip comprising a grip wall, wherein the grip wall forms an interior grip chamber, wherein the grip wall also forms a plurality of grip holes that communicate the interior grip chamber of the grip wall with an exterior surface of the grip wall;
- a fluid container;
- a tubing having a first end and second end, wherein the first end of the tubing is configured to receive a fluid from the fluid container and to communicate the fluid to the second end of the tubing, wherein the door handle grip is configured to receive the fluid from the second end of the tubing;
- a pump configured to force the fluid out of the fluid container into the first end of the tubing, through the tubing to the second end of the tubing, into the interior

grip chamber of the door handle grip, through the plurality of grip holes and onto an exterior of the grip wall.

2. The door handle of claim 1, further comprising a fluid chamber housing configured to house the fluid container.

3. The door handle of claim 2, wherein the fluid chamber housing is configured separate from and external to the door handle grip.

4. The door handle of claim 3, wherein the fluid chamber housing is configured to be mounted on a same side of a door as the door handle grip.

5. The door handle of claim 3, wherein the fluid chamber housing is configured to be mounted on an opposite side of a door as the door handle grip.

6. The door handle of claim 3, wherein the fluid chamber housing is configured to be mounted on a wall near the door handle grip.

7. The door handle of claim 1, wherein the tubing comprises a braided cover.

8. The door handle of claim 1, further comprising a door latch actuator operatively coupled to the door handle.

9. The door handle of claim 8, further comprising a door latch linkage operatively coupling the door latch actuator to the door handle.

10. The door handle of claim 1, wherein the fluid container comprises a sterilizing, disinfecting, antiseptic, antimicrobial, sanitizing or cleaning fluid.

11. The door handle of claim 1, wherein the fluid container comprises an alcohol-based sanitizing fluid.

12. The door handle of claim 1, wherein the fluid container comprises a non-alcohol-based sanitizing fluid.

13. The door handle of claim 4, wherein the fluid comprises a gel-like carrier ingredient.

14. The door handle of claim 1, wherein the fluid container is refillable.

15. The door handle of claim 1, wherein the fluid container is replaceable.

16. The door handle of claim 1, further comprising a distribution manifold coupled to the second end of the tubing, wherein the distribution manifold communicates fluid from an interior of distribution manifold to an exterior of distribution manifold via a plurality of distribution holes.

17. The door handle of claim 1, further comprising a check valve disposed along the tubing between the fluid container and the second end of the tubing, the check valve configured to permit flow of the fluid through the tubing from the fluid container to the second end of the tubing and to inhibit flow of the fluid through the tubing back to the fluid container.

18. The door handle of claim 1, wherein the pump is a mechanically actuated pump.

19. The door handle of claim 1, wherein the pump is a electrically actuated pump.

20. The door handle grip, wherein the pump is actuated when a user operates the door handle.

* * * * *