US010498730B1

(12) **United States Patent**
Son et al.

(10) **Patent No.: US 10,498,730 B1**
(45) **Date of Patent: *Dec. 3, 2019**

(54) **AUTHENTICATION VIA CAMERA**

(71) Applicant: **Snap Inc.**, Venice, CA (US)

(72) Inventors: **Aaron Daniel Son**, Los Angeles, CA (US); **Matthew Koontz**, Marina Del Rey, CA (US)

(73) Assignee: **Snap Inc.**, Santa Monica, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/186,236**

(22) Filed: **Nov. 9, 2018**

Related U.S. Application Data

(63) Continuation of application No. 15/085,033, filed on Mar. 30, 2016, now Pat. No. 10,164,975.

(51) **Int. Cl.**
H04L 29/06 (2006.01)
H04N 5/225 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***H04L 63/0861*** (2013.01); ***G06K 19/06103*** (2013.01); ***H04L 63/123*** (2013.01); ***H04N 5/225*** (2013.01); *G06F 21/30* (2013.01); *G06F 21/31* (2013.01); *G06F 21/36* (2013.01); *G06F 21/44* (2013.01); *G06F 2211/003* (2013.01); *G06K 19/06* (2013.01); *H04L 9/32* (2013.01); *H04L 29/06* (2013.01); *H04L 63/0884* (2013.01)

(58) **Field of Classification Search**
CPC G06F 21/30; G06F 21/31; G06F 21/36; G06F 21/44; G06F 2211/003; H04L 9/32; H04L 63/0861; H04L 63/0884; H04L 63/123; H04L 29/06; G06K 19/06103; G06K 19/06; H04N 5/225
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,038,295 A 3/2000 Mattes
6,980,909 B2 12/2005 Root et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2887596 A1 7/2015

OTHER PUBLICATIONS


"U.S. Appl. No. 15/085,033, Final Office Action dated May 23, 2018".
(Continued)

Primary Examiner — Jayesh M Jhaveri
(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57) **ABSTRACT**

Systems and methods for authentication via camera are provided. In example embodiments, an authentication server transmits, to a mobile device, an identity verification image. The authentication server receives, from a computing device, a scanned image, wherein the computing device is different from the mobile device. The authentication server determines whether the scanned image includes data from the identity verification image. The authentication server transits, to a web server accessed by the computing device, an indication that a user's identity has been verified upon determining that the scanned image includes the data from the identity verification image.

20 Claims, 19 Drawing Sheets



(51) **Int. Cl.**

G06K 19/06	(2006.01)
G06F 21/31	(2013.01)
H04L 9/32	(2006.01)
G06F 21/44	(2013.01)
G06F 21/36	(2013.01)
G06F 21/30	(2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,173,651	B1	2/2007	Knowles	
7,411,493	B2	8/2008	Smith	
7,535,890	B2	5/2009	Rojas	
8,131,597	B2	3/2012	Hudetz	
8,199,747	B2	6/2012	Rojas et al.	
8,332,475	B2	12/2012	Rosen et al.	
8,392,975	B1 *	3/2013	Raghunath	G06F 16/58 726/7
8,718,333	B2	5/2014	Wolf et al.	
8,724,622	B2	5/2014	Rojas	
8,874,677	B2	10/2014	Rosen et al.	
8,909,679	B2	12/2014	Root et al.	
8,995,433	B2	3/2015	Rojas	
9,040,574	B2	5/2015	Wang et al.	
9,055,416	B2	6/2015	Rosen et al.	
9,100,806	B2	8/2015	Rosen et al.	
9,100,807	B2	8/2015	Rosen et al.	
9,191,776	B2	11/2015	Root et al.	
9,204,252	B2	12/2015	Root	
9,443,227	B2	9/2016	Evans et al.	
9,489,661	B2	11/2016	Evans et al.	
9,491,134	B2	11/2016	Rosen et al.	
10,164,975	B1	12/2018	Son et al.	
2007/0112968	A1 *	5/2007	Schwab	G07C 9/00079 709/229
2010/0042669	A1 *	2/2010	Cohen	G06Q 10/00 709/201
2011/0202598	A1	8/2011	Evans et al.	
2012/0209924	A1	8/2012	Evans et al.	
2013/0031623	A1	1/2013	Sanders	
2014/0282961	A1	9/2014	Dorfman et al.	
2014/0372303	A1	12/2014	Gafni	
2015/0156198	A1 *	6/2015	Sabin	H04W 4/00 713/176
2015/0310251	A1	10/2015	Wyrwas et al.	
2016/0188859	A1	6/2016	Lee et al.	
2016/0314462	A1	10/2016	Hong et al.	

OTHER PUBLICATIONS

"U.S. Appl. No. 15/085,033, Non Final Office Action dated Nov. 16, 2017", 12 pgs.

"U.S. Appl. No. 15/085,033, Notice of Allowance dated Aug. 2, 2018", 5 pgs.

"U.S. Appl. No. 15/085,033, Response filed Feb. 13, 2018 to Non Final Office Action dated Nov. 16, 2017", 12 pgs.

"U.S. Appl. No. 15/085,033, Response filed Jul. 23, 2018 to Final Office Action dated May 23, 2018", 14 pgs.

Leyden, John, "This SMS will self-destruct in 40 seconds", URL: http://www.theregister.co.uk/2005/12/12/stealthtext/, (Dec. 12, 2005), 1 pg.

* cited by examiner



100
106
THIRD PARTY SERVER(S) 120
THIRD PARTY APPLICATION(S) 122
NETWORK (E.G., THE INTERNET) 104
CLIENT DEVICE(S) 110
CLIENT APPLICATION(S) 112
CUSTOM PATTERN SYSTEM 160
SOCIAL MESSAGING SYSTEM 130
INTERFACE LAYER 124
INTERFACE MODULE(S) 140
APPLICATION LOGIC LAYER 126
APPLICATION LOGIC MODULE(S) 150
CUSTOM PATTERN SYSTEM 160
DATA LAYER 128
DATABASE SERVER(S) 132
DATABASE(S) 134

FIG. 1



200
CUSTOM PATTERN SYSTEM
160
COMMUNICATION MODULE
210
PRESENTATION MODULE
220
FINDER MODULE
230
ALIGNMENT MODULE
240
DECODER MODULE
250
ACTION MODULE
260
ENCODER MODULE
270

FIG. 2




FIG. 3A




FIG. 3B




FIG. 4



500
START
RECEIVING IMAGE DATA OF AN IMAGE
510
EXTRACTING A CANDIDATE SHAPE FEATURE OF THE IMAGE FROM THE IMAGE DATA
520
DETERMINING THE CANDIDATE SHAPE FEATURE SATISFIES A RULE
530
IDENTIFYING A CUSTOM GRAPHIC IN THE IMAGE BY COMPARING THE CANDIDATE SHAPE FEATURE TO A REFERENCE SHAPE FEATURE
540
EXTRACTING A SPATIAL ATTRIBUTE OF THE CUSTOM GRAPHIC
550
DECODING DATA ENCODED IN THE IMAGE USING THE SPATIAL ATTRIBUTE
560
END

FIG. 5



700
710
720
730
740
750
760
770

FIG. 7



530
520
DETERMINING THE CANDIDATE SHAPE FEATURE COMPRISES AN ENCLOSED LINE
610
PATH RETURNS TO A POINT?
630
NO
YES
END
DETERMINING THE CANDIDATE SHAPE FEATURE SATISFIES A PATH RULE
640
540

FIG. 6



900
902
904
906
908
910
912
914
916
918
920
Z
Y
X
REFERENCE AREA VALUE
AREA VALUE

FIG. 9



530
520
CALCULATING AN AREA VALUE OF THE CANDIDATE SHAPE FEATURE
810
DETERMINING AN AREA SCORE
820
SCORE EXCEEDS THRESHOLD?
830
NO
END
YES
DETERMINING THE CANDIDATE SHAPE FEATURE SATISFIES AN AREA RULE
840
540

FIG. 8



1100
1102
1106
1114
Z
Y
1116
1112
1104
Z
Y
X
1108
1110

FIG. 11



540
EXTRACTING A DISTINCTIVE FEATURE OF THE CUSTOM GRAPHIC
1010
DETERMINING AN ORIENTATION OF THE CUSTOM GRAPHIC
1020
GENERATING A TRANSFORMED IMAGE ACCORDING TO THE ORIENTATION
1030
DECODING THE DATA ENCODED IN THE IMAGE USING THE TRANSFORMED IMAGE
1040
END

FIG. 10




FIG. 12A




FIG. 12C



1400
1420
1430
1410

FIG. 14



1040
DETERMINING A FAILURE TO DECODE THE DATA ENCODED IN THE IMAGE
1310
GENERATING ANOTHER TRANSFORMED IMAGE
1320
DECODING THE DATA ENCODED IN THE IMAGE USING THE ANOTHER TRANSFORMED IMAGE
1330
END

FIG. 13



1600
1610
1620
7:34 AM
MUSIC FESTIVAL
EXCLUSIVE ACTIONS
GET MORE INFO
ORDER TICKETS
ADD TO CALENDAR
TELL FRIENDS
DOWNLOAD FESTIVAL DEMO
MORE...

FIG. 16



1500
1510
1520
7:34 AM
SCAN SUCCEEDED

FIG. 15



1800
1810
1820
1830
7:34 AM
GENERATE SNAPCODES
GENERATE A SNAPCODE TO
PERFORM AN ACTION
GENERATE
SAVE
SHARE

FIG. 18



1700
START
RECEIVING A REQUEST TO GENERATE
A MACHINE-READABLE IMAGE
1710
RENDERING A MACHINE-READABLE
ARRANGEMENT OF MARKS THAT
ENCODES DATA
1720
GENERATING THE MACHINE-READABLE
IMAGE WITH A CUSTOM GRAPHIC
1730
TRANSMITTING THE GENERATED
MACHINE-READABLE IMAGE
1740
END

FIG. 17




FIG. 19



2000
API CALLS 2024
MESSAGES 2026
SOFTWARE ARCHITECTURE 2002
PRESENTATION LAYER 2044
APPLICATIONS 2020
BUILT-IN 2040
THIRD PARTY 2042
MESSAGING 2043
STAND-ALONE 2045
FRAMEWORKS / MIDDLEWARE 2018
IMAGE PROCESSING 2022
IMAGE CAPTURE 2023
LIBRARIES 2016
SYSTEM 2034
API 2036
OTHER 2038
IMAGING 2039
IMAGING 2033
KERNEL 2028
SERVICES 2030
DRIVERS 2032
HARDWARE LAYER 2004
MEMORY/STORAGE 2010
INSTRUCTIONS 2008
OTHER HARDWARE 2012
PRESENTATION LAYER 2058
APPLICATIONS 2056
FRAMEWORKS 2054
LIBRARIES 2052
OS 2050
VIRTUAL MACHINE 2048
VIRTUAL MACHINE MONITOR 2046
OPERATING SYSTEM 2014
PROCESSING UNIT 2006
INSTRUCTIONS 2008

FIG. 20



2100
PROCESSORS 2110
PROCESSOR 2112
INSTRUCTIONS 2116
PROCESSOR 2114
INSTRUCTIONS 2116
MEMORY/STORAGE 2130
MEMORY 2132
INSTRUCTIONS 2116
STORAGE UNIT 2136
INSTRUCTIONS 2116
BUS 2102
I/O COMPONENTS 2150
OUTPUT 2152
VISUAL
ACOUSTIC
HAPTIC
INPUT 2154
ALPHANUMERIC
POINT BASED
TACTILE
AUDIO
BIOMETRIC 2156
EXPRESSION
BIOSIGNALS
IDENTIFICATION
MOTION 2158
ACCELERATION
GRAVITATION
ROTATION
ENVIR. 2160
ILLUMINATION
ACOUSTIC
TEMPERATURE
PRESSURE
POSITION 2162
LOCATION
ALTITUDE
ORIENTATION
COMMUNICATION 2164
WIRED
WIRELESS
CELLULAR
NEAR FIELD
BLUETOOTH
WI-FI
2172
DEVICES 2170
2182
NETWORK 2180

FIG. 21



2200
2240
2242
2244
MOBILE DEVICE
2232
2230
2234
COMPUTING DEVICE
NETWORK
2250
2210
AUTHENTICATION SERVER
2220
WEB SERVER

FIG. 22



2210
AUTHENTICATION SERVER
2305
PROCESSOR
2310
NETWORK INTERFACE
2315
MEMORY
2320
IDENTIFY VERIFICATION IMAGE GENERATOR
2325
IDENTIFY VERIFICATION MODULE
2330
IDENTIFY VERIFICATION DATA

FIG. 23



2400
TRANSMIT, TO A MOBILE DEVICE, AN IDENTITY VERIFICATION IMAGE
2410
RECEIVE, FROM A COMPUTING DEVICE, A SCANNED IMAGE
2420
2430
DOES THE SCANNED IMAGE INCLUDE DATA FROM THE IDENTITY VERIFICATION IMAGE?
YES
NO
2440
TRANSMIT, TO A WEB SERVER, AN INDICATION THAT THE USER'S IDENTITY HAS BEEN VERIFIED
TRANSMIT, TO THE WEB SERVER, AN INDICATION THAT THE USER'S IDENTITY HAS NOT BEEN VERIFIED
2450

FIG.24



2500
AUTH. SERVER 2210
WEB SERVER 2220
COMPUTING DEVICE 2230
MOBILE DEVICE 2240
2505
ACCESS EXAMPLE.COM
2510
PROVIDE EXAMPLE.COM DATA
2515
REQUEST LOGIN TO EXAMPLE.COM
2520
REQUEST SCANNED IMAGE
2525
REQUEST IDENTITY VERIFICATION IMAGE
2530
PROVIDE IDENTITY VERIFICATION IMAGE
2535
SCAN IDENTITY VERIFICATION IMAGE
2540
PROVIDE SCANNED IMAGE
2545
IDENTIFY USER BASED ON SCANNED IMAGE
2550
PROVIDE ACCESS TO ACCOUNT OF IDENTIFIED USER

FIG. 25

AUTHENTICATION VIA CAMERA

PRIORITY

This application is a continuation of and claims the benefit of priority of U.S. patent application Ser. No. 15/085,033, filed on Mar. 30, 2016, which is hereby incorporated by reference herein in its entirety

TECHNICAL FIELD

Embodiments of the present disclosure relate generally to user authentication and, more particularly, but not by way of limitation, to authentication via a camera of a computing device accessing an identity verification image.

BACKGROUND

Quick Response (QR) codes, and other optical barcodes, are a convenient way to share small pieces of information with users of mobile devices, wearable devices, and other smart devices. Typically, an optical barcode uses a finder pattern for identification of the optical barcode. Conventional finder patterns commonly use multiple generic markings conspicuously placed within the optical barcode. Such conspicuous and generic markings can be unsightly and often serve no purpose other than to function as a finder pattern.

Users typically access web-based resources by creating a username and a password with a provider of the resource. A user typically accesses a website associated with the provider and enters his/her username and password to view the resource. However, as users create more and more passwords at more and more providers, users tend to forget their passwords, reducing the security provided by the passwords and creating additional difficulty in accessing the resources. As the foregoing illustrates, a new approach to user authentication for access to a web-based resource may be desirable.

BRIEF DESCRIPTION OF THE DRAWINGS

Various ones of the appended drawings merely illustrate example embodiments of the present disclosure and should not be considered as limiting its scope.

FIG. **1** is a block diagram illustrating a networked system, according to some example embodiments.

FIG. **2** is a block diagram illustrating an example embodiment of a custom pattern system, according to some example embodiments.

FIGS. **3**A and **3**B are diagrams illustrating examples of optical barcodes employing a custom functional pattern, according to some example embodiments.

FIG. **4** is a diagram illustrating an example of identifying and decoding an optical barcode employing a custom functional pattern, according to some example embodiments.

FIG. **5** is a flow diagram illustrating an example method for identifying and decoding an optical barcode using a custom functional pattern, according to some example embodiments.

FIG. **6** is a flow diagram illustrating further example operations identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **7** is a diagram illustrating an example of identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **8** is a flow diagram illustrating further example operations for identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **9** is a diagram illustrating an example of identifying the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **10** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **11** is a diagram illustrating an example of decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIGS. **12**A, **12**B, and **12**C are diagrams illustrating various image transformations used to facilitate decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **13** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **14** is a diagram illustrating an example of decoding the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **15** is a user interface diagram depicting an example user interface for identifying the optical barcode, according to some example embodiments.

FIG. **16** is a user interface diagram depicting an example user interface for performing an action associated with the optical barcode, according to some example embodiments.

FIG. **17** is a flow diagram illustrating further example operations for generating the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **18** is a user interface diagram depicting an example user interface for generating the optical barcode using the custom functional pattern, according to some example embodiments.

FIG. **19** is a user interface diagram depicting an example mobile device and mobile operating system interface, according to some example embodiments.

FIG. **20** is a block diagram illustrating an example of a software architecture that may be installed on a machine, according to some example embodiments.

FIG. **21** is a block diagram presenting a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any of the methodologies discussed herein, according to an example embodiment.

FIG. **22** is a diagram of an example system in which web authentication via camera may be implemented, according to some example embodiments.

FIG. **23** is a block diagram of an example of the authentication server of FIG. **22**, according to some example embodiments.

FIG. **24** is a flow diagram illustrating an example method for web authentication via camera, according to some example embodiments.

FIG. **25** is a data flow diagram illustrating an example method for web authentication via camera.

DETAILED DESCRIPTION

The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of

the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

QR codes, and other optical barcodes (e.g., Universal Product Code (UPC) barcodes, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code), are a convenient way to share small pieces of information with users of mobile devices, wearable devices, and other smart devices. For instance, QR codes are two-dimensional optical barcodes that encode information readable by a device (e.g., a smart phone) equipped with a camera sensor. Typically, a QR code includes one or more functional patterns such as a finder pattern used for identification and recognition of the QR code or an alignment pattern used to facilitate decoding. Conventional finder patterns comprise multiple markings that are generic in design such as square marks placed in all corners except the bottom right corner (as is the case with a QR code). These finder patterns are absent aesthetic elements such as curves, non-uniformities, and other stylistic elements and often conform to a particular standard to promote open use of the optical barcode.

In various example embodiments, an optical barcode that uses custom patterns, or non-standard functional patterns, provides users with an aesthetically pleasing, branded barcode that allows for an exclusive experience associated with the optical barcode. For example, an entity logo (e.g., a logo of a company, organization, or individual) can be used as a finder pattern, and in some instances an alignment pattern, to create a branded and exclusive optical barcode that is machine-readable using software provided by the entity. In a specific example, a "snapcode" is an optical barcode that uses the SNAPCHAT® logo as a functional pattern. Alternatively, a "snapcode" may include an image of a face, such as a photograph of a human face or an avatar of a human face, in place of the SNAPCHAT® logo.

In an example embodiment, a custom pattern system receives image data representing an image from a user device. For example, the custom pattern system receives the image data from an optical sensor (e.g., a camera sensor) of a smart phone of the user. In various embodiments, the image data from the user device is received in response to a user-initiated image capture, a periodic monitoring of image data being detected by the optical sensor of the user device, an access of stored image data, or a combination thereof. A portion of the image data can include data representing an optical barcode employing a custom graphic for a particular functional pattern (e.g., a finder pattern). In some scenarios, the image data includes extraneous or irrelevant data along with the data pertaining to the optical barcode (e.g., an image of an optical barcode includes a background that is not pertinent to decoding the optical barcode). In a specific example, the optical sensor of the user device captures an image of a promotional poster that includes a particular optical barcode. The image of the promotional poster can include the particular optical barcode along with irrelevant portions of the promotional poster or background that surrounds the particular optical barcode.

After the custom pattern system receives the image data, the custom pattern system searches the image data of the image for the custom graphic to determine whether the image includes the optical barcode. That is to say, the custom graphic, which may be an image of a face, such as a photograph of human face or an avatar or drawing of a human face, is used as a finder pattern for recognition, identification, or detection of the optical barcode within the image. In an example embodiment, the custom pattern system searches for the custom graphic by extracting a candidate shape feature, or multiple candidate shape features, from the image data. For example, the custom pattern system performs an edge detection technique, or another image processing technique, to identify the candidate shape feature such as a contour line of the image. The custom pattern system then determines whether the candidate shape feature satisfies shape feature rules or criteria. For instance, if a particular candidate shape feature is a contour line, the custom pattern system can determine whether the contour line is an enclosed line that encircles a portion of the image. Consistent with some embodiments, the shape feature rules filter out irrelevant or extraneous candidate shape features or candidate shape features with a low probability of being the custom graphic.

In response to the candidate shape feature satisfying the shape feature rules, the custom pattern system identifies the custom graphic by comparing the candidate shape feature with a reference shape feature of the custom graphic. For example, the custom pattern system can compare an area or size of the candidate shape feature with a reference area or size of the reference shape feature. In this example, the custom pattern system identifies the custom graphic based on a match or near match (e.g., a percentage match above a threshold) between the candidate shape feature and the reference shape feature. In this way, the custom pattern system uses the custom graphic as a finder pattern to identify the presence of the optical barcode within a portion of the image.

In further example embodiments, the custom graphic or the recognized face functions as an alignment pattern to facilitate the custom pattern system decoding the data encoded in the optical barcode. In an example embodiment, the custom pattern system extracts spatial attributes of the custom graphic in the image from the image data. For example, the custom pattern system extracts a position, scale, or orientation of the custom graphic from the image data. The custom pattern system decodes data encoded in the image from the image data using the spatial attributes of the custom graphic in the image. For instance, the custom pattern system can perform an image transform using the spatial attributes (e.g., a de-skew, a rotation, a scale, or another type of image transform) to improve detectability/readability of data encoded in a portion of the image. In this way, the custom pattern system uses the custom graphic as an alignment pattern to facilitate decoding the optical barcode.

Accordingly, the custom pattern system uses the custom graphic as a functional pattern of the optical barcode without utilizing conventional functional patterns. Using the custom graphic as a functional pattern allows for an aesthetically pleasing design and can provide exclusivity to a particular software application as the functional pattern does not necessarily conform to an open standard and thus is readable exclusively by the particular software application.

Some aspects of the subject technology relate to user authentication for access to a web-based resource. Some aspects may be implemented in conjunction with a web server that hosts the web based resource and an authentication server that authenticates the user. The user may access the web-based resource through a computing device (e.g., a public computer at a library) different from the user's mobile

device. The authentication server may be associated with a service that the user accesses on his/her mobile device, such as an instant messaging program that stores some identity information (e.g., name, telephone, email, etc.) of the user.

According to some implementations, the authentication server transmits, to a mobile device of the user (e.g., via the instant messaging application) an identity verification image. The identity verification image may be transmitted in response to a request by the user either through a computing device accessing the web server or through the mobile device (e.g., through the instant messaging application of the mobile device). The authentication server transmits, to the computing device via the web server, an instruction to scan, via a camera of the computing device, the identity verification image transmitted to the mobile device. The user, in response to instructions presented via a display unit of either the mobile device or the computing device, places the display unit of the mobile device in front of the camera of the computing device for scanning. The authentication server receives, from the computing device and via the web server, a scanned image that was scanned via the camera of the computing device. The authentication server determines whether the scanned image includes data from the identity verification image. If the scanned image includes the data from the identity verification image, the authentication server transmits, to the web server, an indication that the user's identity has been verified. If the scanned image does not include the data from the identity verification image, the authentication server transmits, to the web server, an indication that the user's identity has not been verified.

As used herein, the phrase "the scanned image includes (or comprises) data from the identity verification image" encompasses its plain and ordinary meaning. The scanned image includes the data from the identity verification image if the data (e.g., dots, lines, or other markings) in the scanned image can be decoded to yield indicia that the scanned image corresponds to the identity verification image. The scanned image includes the data from the identity verification image if data from the scanned image can be decoded to yield data which was encoded into the identity verification image.

The scanned image may be said to include (or comprise) the data from the identity verification image if it includes an image of a display unit that shows the image. However, the scanned image may be blurred, tilted, rotated, or the like, relative to the original identity verification image as the scanned image is created by a user who may be inexperienced in photography, using low quality equipment, working in non-ideal lighting conditions for photography, trying to make the scan as quickly as possible, and so forth.

FIG. **1** is a network diagram depicting a network system **100** having a client-server architecture configured for exchanging data over a network, according to one embodiment. For example, the network system **100** may be a messaging system where clients communicate and exchange data within the network system **100**. The data may pertain to various functions (e.g., sending and receiving text and media communication, determining geolocation, etc.) and aspects associated with the network system **100** and its users. Although illustrated herein as client-server architecture, other embodiments may include other network architectures, such as peer-to-peer or distributed network environments.

As shown in FIG. **1**, the network system **100** includes a social messaging system **130**. The social messaging system **130** is generally based on a three-tiered architecture, consisting of an interface layer **124**, an application logic layer **126**, and a data layer **128**. As is understood by skilled artisans in the relevant computer and Internet-related arts, each module or engine shown in FIG. **1** represents a set of executable software instructions and the corresponding hardware (e.g., memory and processor) for executing the instructions. To avoid obscuring the inventive subject matter with unnecessary detail, various functional modules and engines that are not germane to conveying an understanding of the inventive subject matter have been omitted from FIG. **1**. Of course, additional functional modules and engines may be used with a social messaging system, such as that illustrated in FIG. **1**, to facilitate additional functionality that is not specifically described herein. Furthermore, the various functional modules and engines depicted in FIG. **1** may reside on a single server computer, or may be distributed across several server computers in various arrangements. Moreover, although the social messaging system **130** is depicted in FIG. **1** as a three-tiered architecture, the inventive subject matter is by no means limited to such an architecture.

As shown in FIG. **1**, the interface layer **124** consists of one or more interface modules (e.g., a web server) **140**, which receive requests from various client-computing devices and servers, such as client device(s) **110** executing client application(s) **112**, and third party server(s) **120** executing third party application(s) **122**. In response to received requests, the interface module(s) **140** communicate appropriate responses to requesting devices via a network **104**. For example, the interface module(s) **140** can receive requests such as Hypertext Transfer Protocol (HTTP) requests or other web-based Application Programming Interface (API) requests.

The client device(s) **110** can execute conventional web browser applications or applications (also referred to as "apps") that have been developed for a specific platform to include any of a wide variety of mobile computing devices and mobile-specific operating systems (e.g., IOS™, ANDROID™, WINDOWS® PHONE). In an example, the client device(s) **110** are executing the client application(s) **112**. The client application(s) **112** can provide functionality to present information to a user **106** and communicate via the network **104** to exchange information with the social messaging system **130**. Each client device **110** can comprise a computing device that includes at least a display and communication capabilities with the network **104** to access the social messaging system **130**. The client device(s) **110** comprise, but are not limited to, remote devices, work stations, computers, general purpose computers, Internet appliances, hand-held devices, wireless devices, portable devices, wearable computers, cellular or mobile phones, personal digital assistants (PDAs), smart phones, tablets, ultrabooks, netbooks, laptops, desktops, multi-processor systems, microprocessor-based or programmable consumer electronics, game consoles, set-top boxes, network personal computers (PCs), mini-computers, and the like. Users **106** can include a person, a machine, or other means of interacting with the client devices **110**. In some embodiments, the users **106** interact with the social messaging system **130** via the client device(s) **110**.

As shown in FIG. **1**, the data layer **128** has one or more database servers **132** that facilitate access to information storage repositories or databases **134**. The database(s) **134** are storage devices that store data such as member profile data, social graph data (e.g., relationships between members of the social messaging system **130**), and other user data.

An individual can register with the social messaging system **130** to become a member of the social messaging system **130**. Once registered, a member can form social network relationships (e.g., friends, followers, or contacts)

on the social messaging system **130** and interact with a broad range of applications provided by the social messaging system **130**.

The application logic layer **126** includes various application logic modules **150**, which, in conjunction with the interface module(s) **140**, generate various user interfaces with data retrieved from various data sources or data services in the data layer **128**. Individual application logic module(s) **150** may be used to implement the functionality associated with various applications, services, and features of the social messaging system **130**. For instance, a social messaging application can be implemented with one or more of the application logic module(s) **150**. The social messaging application provides a messaging mechanism for users of the client device(s) **110** to send and receive messages that include text and media content such as pictures and video. The client device(s) **110** may access and view the messages from the social messaging application for a specified period of time (e.g., limited or unlimited). In an example, a particular message is accessible to a message recipient for a predefined duration (e.g., specified by a message sender) that begins when the particular message is first accessed. After the predefined duration elapses, the message is deleted and is no longer accessible to the message recipient. Of course, other applications and services may be separately embodied in their own application logic module(s) **150**.

As illustrated in FIG. **1**, the social messaging system **130** or the client application(s) **112** includes a custom pattern system **160** that provides functionality to identify and decode optical barcodes that employ custom functional patterns. In various embodiments, the custom pattern system **160** can be implemented as a standalone system and is not necessarily included in the social messaging system **130**. In some embodiments, the client device(s) **110** includes a portion of the custom pattern system **160** (e.g., a portion of the custom pattern system **160** may be included independently or in the client application(s) **112**). In embodiments where the client device(s) **110** includes a portion of the custom pattern system **160**, the client device(s) **110** can work alone or in conjunction with the portion of the custom pattern system **160** included in a particular application server or included in the social messaging system **130**.

FIG. **2** is a block diagram **200** of the custom pattern system **160**. The custom pattern system **160** is shown to include a communication module **210**, a presentation module **220**, a finder module **230**, an alignment module **240**, a decoder module **250**, an action module **260**, and an encoder module **270**. All, or some, of the modules **210-270** communicate with each other, for example, via a network coupling, shared memory, and the like. Each module of the modules **210-270** can be implemented as a single module, combined into other modules, or further subdivided into multiple modules. Other modules not pertinent to example embodiments can also be included, but are not shown.

The communication module **210** provides various communications functionality. For example, the communication module **210** receives, accesses, or otherwise obtains image data of an image from a user device. In a specific example, the communication module **210** receives substantially real-time image data from a camera sensor of a smart phone (e.g., a single frame of image data or a continuous stream of frames captured by a camera sensor of the smart phone). The communication module **210** exchanges network communications with the database server(s) **132**, the client device(s) **110**, and the third party server(s) **120**. The information retrieved by the communication module **210** includes data associated with the user (e.g., user **106**) (e.g., member profile data from an online account or social network service data) or other data to facilitate the functionality described herein.

The presentation module **220** provides various presentation and user interface functionality operable to interactively present and receive information to and from the user. For instance, the presentation module **220** is utilizable to present user interfaces generated in response to decoding the optical barcode. In other instances, the presentation module **220** generates user interfaces that include optical barcode(s). In various embodiments, the presentation module **220** presents or causes presentation of information (e.g., visually displaying information on a screen, acoustic output, haptic feedback). The process of interactively presenting information is intended to include the exchange of information between a particular device and the user. The user may provide input to interact with the user interface in many possible manners, such as alphanumeric, point based (e.g., cursor), tactile, or other input (e.g., touch screen, tactile sensor, light sensor, infrared sensor, biometric sensor, microphone, gyroscope, accelerometer, or other sensors). The presentation module **220** provides many other user interfaces to facilitate functionality described herein. The term "presenting" as used herein is intended to include communicating information or instructions to a particular device that is operable to perform presentation based on the communicated information or instructions.

The finder module **230** provides image processing functionality to identify, recognize, or detect the custom graphic being employed as a finder pattern in the optical barcode. For example, the finder module **230** extracts and analyzes candidate shape features or candidate contour characteristics from image data of the image received from the user device (e.g., the client device(s) **110**). The finder module **230** determines satisfaction of various rules or criteria associated with the extracted candidate shape features. The finder module **230** compares the extracted candidate shape features with reference shape features of the custom graphic, or another reference image, to identify the custom graphic included in the image. The finder module **230** can employ a wide variety of schemes and techniques to extract the candidate shape features from the image data of the image and subsequently identify the custom graphic based on an analysis of the candidate shape features. Examples of those techniques are illustrated later with respect to FIGS. **5-14**.

The alignment module **240** provides image processing functionality to determine an alignment of the optical barcode using the custom graphic. The custom pattern system **160** can use the alignment to facilitate decoding of data encoded in the optical barcode. In this way, the custom graphic functions as an alignment pattern for the optical barcode. For example, the alignment module **240** extracts spatial attributes of the custom graphic in the image from the image data. In various embodiments, the spatial attributes include at least one of position, orientation, scale, or another spatial aspect of the optical barcode. The alignment module **240** determines an alignment of the optical barcode based on the spatial attributes (e.g., a particular orientation of the optical barcode). In an example, the alignment module **240** can determine an alignment including position and orientation based on the spatial attributes and generate a transformed image according to the alignment. The custom pattern system **160** can then use the transformed image to decode data encoded in a portion of the transformed image.

The decoder module **250** provides functionality to decode data encoded in the image using the spatial attributes or the determined alignment of the custom graphic in the image.

For instance, the decoder module **250** can decode the data encoded in the image from an image transformed according to the spatial attributes of the custom graphic extracted from image data. In an embodiment, the decoder module **250** detects markings (e.g., high contrast dots, squares, or other marks in the image) representing data encoded in a portion of the image from the image data. In a specific example, the decoder module **250** employs a Reed-Solomon error correction scheme (or other error correction scheme) to decode data encoded in the image. The Reed-Solomon error correction scheme (or other error correction scheme) allows for a successful or valid decoding even when a certain percentage of data could not be decoded from the optical barcode (e.g., damaged bits or incorrectly decoded bits). In some embodiments, the user or an administrator of the custom pattern system **160** configures a tolerance value for an amount of damaged or incorrectly decoded data acceptable when decoding the optical barcode. In some embodiments, the decoder module **250** also provides image processing functionality to improve decoding of the optical barcode. For instance, the decoder module **250**, as well as the alignment module **240**, can perform image transforms of the image (e.g., perform image sharpening, de-noise processing, other digital filtering, or other image processing techniques to improve decoding accuracy).

The action module **260** provides functionality to perform a variety of actions based on decoding the data encoded in the image. For example, the data encoded in a portion of the image can indicate a particular action or include information to be used in conjunction with a particular action. In a specific example, the data encoded in a portion of the image can comprise a user name, or other user identification, of a member of a social networking service and based on decoding the user name, the action module **260** can perform an action on the social networking service corresponding to the user name (e.g., sending a message to the member associated with the user name). In some embodiments, the action module **260** performs an action specific to a particular app that scans the image (e.g., a function available to a user of the app but otherwise unavailable). In some instances, the action module **260** performs the action without communicating with an external server (e.g., an action locally performed on the user device that scanned the snapcode).

The encoder module **270** provides functionality to generate and encode data into an optical barcode that employs the custom graphic as one or more functional patterns (e.g., generating snapcodes). As discussed above in connection with the decoder module **250**, in a specific example, the encoder module **270** can employ a technique such as Reed-Solomon error correction (or other error correction scheme) to encode data. In an example embodiment, the encoder module **270** renders a machine-readable arrangement of marks that represents the data to be encoded. The encoder module **270** can then generate the machine-readable optical barcode using the rendered arrangement of marks and the custom graphic to be used as a functional pattern.

FIGS. **3**A and **3**B are diagrams illustrating examples of optical barcodes employing the custom graphic for a finder pattern or an alignment pattern (e.g., snapcodes). Diagram **300** shows an example optical barcode that includes a custom graphic **310** (e.g., a company logo), and markings **320** that represent data encoded into the optical barcode. In this example, the custom graphic **310** is a company logo such as the SNAPCHAT® "ghost" logo. It will be appreciated that the SNAPCHAT® "ghost" logo is merely an example custom graphic and other graphics, icons, or symbols can be employed as a finder pattern or alignment pattern using the techniques described herein. Other example custom graphics used as a functional pattern can include designs with multiple paths, multiple polygons, multiple aesthetic elements, or other design features.

As shown in the diagram **300**, the markings **320** are dots that are arranged in a pattern with a particular spacing or positioning readable by a machine. Although the diagram **300** shows the markings **320** as dots, other shapes and marks can be employed (e.g., squares or asymmetric shapes of various geometries). The markings **320** can be arranged in a uniform pattern or a non-uniform pattern. In some instances, the marks can be of different sizes or a uniform size. Additionally, the markings **320** can be in a predetermined arrangement or an arrangement that is dynamically determinable when decoding data from the markings. In some embodiments, the custom graphic **310** and the markings **320** can be surrounded by a bounding shape, such as an outer box **325**. Although the outer box **325** of the diagram **300** is shown as a square with rounded corners, the outer box **325** can be in the form of a variety of other shapes with various geometries. Diagram **330** in FIG. **3**B shows another example optical barcode that employs the custom graphic for a finder pattern or an alignment pattern. The diagram **330** shows the optical barcode with markings excluded from within the custom graphic. In these and other embodiments, the space internal to the custom graphic may be reserved for other uses. For example, a picture, graphic, animation, annotation, or image selected by a user may be inserted.

Turning now to FIG. **4**, a diagram **400** illustrating an example of identifying and decoding the optical barcode employing the custom graphic for a finder pattern or an alignment pattern is shown. FIG. **4** is an overview of a particular example embodiment of identifying and decoding the optical barcode using the custom graphic. Additional details and alternative implementations are discussed in connection with the figures to follow. In the diagram **400**, a scene **402** illustrates a poster **404** that includes an optical barcode **406** and a user **410**. It will be appreciated that the optical barcode **406** can be displayed in a variety of manners such as on a user device display, a computer display, woven or otherwise affixed to an article of clothing or another product, or included in a variety of printed items. Callout **412** portrays an enlarged view of a portion of the scene **402**. The callout **412** includes a user device **414** of the user **410** that includes an optical sensor (e.g., a camera sensor of a smart phone) operable to detect an optical signal **408** of the optical barcode **406**.

In an example embodiment, the user device **414** captures an image of the poster **404** that includes the optical barcode **406**. The custom pattern system **160** receives the image data representing the image from the user device **414**. In this example embodiment, the custom pattern system **160** is included in the user device **414** (e.g., an application executing on a smart phone of the user **410**), although in other example embodiments, the custom pattern system **160** can reside on a server (e.g., a server of the social messaging system **130**) that is communicatively coupled with the user device **414**. Callout **416** portrays example image processing performed by the finder module **230** to identify the custom graphic in the image and use the custom graphic as an alignment pattern for decoding data included in the optical barcode **406**. In the callout **416**, the finder module **230** extracts candidate shape features from the image data of the image. Subsequently, the finder module **230** determines if the candidate features meet certain rules and criteria to filter out irrelevant shape features or shape features that have a low probability of being the custom graphic. The finder

module **230** can then compare the candidate shape features that meet the shape feature criteria or rules with reference shape features of the custom graphic. In an example, the finder module **230** identifies the custom graphic based on a match between the candidate shape features and the reference shape feature (e.g., a match score that exceeds a threshold).

Subsequent to the finder module **230** identifying the custom graphic, the custom pattern system **160** can use the custom graphic as an alignment pattern for decoding. For instance, the alignment module **240** extracts spatial attributes of the custom graphic in the image and compares the extracted spatial attributes to reference spatial attributes to determine an alignment of the custom graphic. The alignment module **240** or the decoder module **250** may then generate a transformed image of the image according to the alignment (e.g., a rotation or de-skew) as shown in callout **418**. After generating the transformed image, the decoder module **250** decodes the data encoded in a portion of the transformed image as shown in callout **420**. In the callout **420**, the dots of the optical barcode **406** are transformed into data shown as ones for dots and zeros for non-dots, although this is merely an illustrative example and other schemes can be employed. In this way, the custom pattern system **160** uses the custom graphic included in the optical barcode **406** as one or more functional patterns such as a finder pattern or an alignment pattern.

FIG. **5** is a flow diagram illustrating an example method **500** for an optical barcode (e.g., the optical barcode **406** of FIG. **4**) employing a custom functional pattern. The operations of the method **500** can be performed by components of the custom pattern system **160**, and are so described below for the purposes of illustration.

At operation **510**, the communication module **210** receives image data of an image from a user device. For example, the communication module **210** receives the image data from an optical sensor (e.g., a camera sensor) of a smart phone of the user (e.g., client device **110** or user device **414**). In various embodiments, the image data from the user device (e.g., client device **110** or user device **414**) is received in response to a user-initiated image capture, a periodic monitoring of image data being detected by the optical sensor of the user device, or a combination thereof. In some embodiments, the image data represents an image or video being captured by the user device in substantially real time (e.g., a live image feed from a camera sensor of a smart phone). In other embodiments, the image data represents an image captured by the user device, or another device and stored on the user device, from a time in the past (e.g., a still image or video stored on the user device or downloaded from a social networking service). In embodiments where the image data comprises video image data, the custom pattern system **160** can analyze individual frames of the video or a combination of multiple frames of the video to detect and decode the optical barcode. A portion of the image data can include data representing an optical barcode employing a custom graphic, custom symbol, or specific graphic for a particular functional pattern (e.g., a finder pattern or alignment pattern).

In some scenarios, the image data includes extraneous or irrelevant data along with the data pertaining to the optical barcode (e.g., an image of an optical barcode includes a background that is not pertinent to decoding the optical barcode). In a specific example, the optical sensor of the user device captures an image of a movie poster that includes a particular optical barcode. The image of the movie poster can include the particular optical barcode along with irrelevant portions of the movie poster or background that surrounds the particular optical barcode.

At operation **520**, the finder module **230** extracts a candidate shape feature or candidate characteristic of the image from the image data. The candidate shape feature can be indicative of an identification of the custom graphic (e.g., include certain traits or characteristics that indicate the custom graphic). For example, the finder module **230** performs an edge detection technique, or another image processing technique, to identify shape features such as contour lines or localized concentrations of color or shading of the image. In some embodiments, the finder module **230** extracts multiple candidate shape features from the image data. In some embodiments, the candidate shape feature includes various shape feature data such as a position of the candidate shape feature relative to a boundary of the image, a brightness of the candidate shape feature relative to the image, an average color of the candidate shape feature, and so forth.

In further example embodiments, the finder module **230** generates a low resolution copy of the image. The finder module **230** can perform various image processing on the low resolution copy of the image, such as a blur (e.g., a Gaussian blur function or another blur function) and a thresholding, to generate a modified low resolution image. The thresholding image process can include adjusting lighter colors (e.g., as determined by a threshold or threshold range) of the low resolution copy of the image to a white color and darker colors (e.g., as determined by a threshold or threshold range) of the low resolution copy of the image to a black color. The finder module **230** can then extract candidate shape features from the modified low resolution image to improve detection of the custom graphic in the image and improve computational efficiency of identifying the custom graphic in the image.

In still further example embodiments, the finder module **230** generates a high resolution copy of a portion of the image. For instance, the finder module **230** can generate the high resolution copy of a particular portion of the image corresponding to the extracted candidate shape feature. The finder module **230**, the alignment module **240**, or the decoder module **250** can use the high resolution copy for subsequent analysis, as described below, to improve detection, alignment, and decoding results.

At operation **530**, the finder module **230** determines that the candidate shape feature satisfies one or more shape feature criteria or rules. For instance, if a particular shape feature is a contour line, the finder module **230** can determine whether the contour line is an enclosed line that encircles a portion of the image. Consistent with some embodiments, the shape feature rule filters out irrelevant or extraneous features. Particular shape feature rules can be directed to or purposed for various objectives. For example, a particular shape feature rule can be purposed to filter out candidate shape features with a low probability of being the custom graphic. In this example, the particular shape feature rule can be specific to the custom graphic. In other examples, some shape feature rules can be purposed to filter out candidate shape features that are unlikely to be associated with the optical barcode. In these examples, the shape feature rule is not necessarily specific to the custom graphic.

At operation **540**, in response to the candidate shape feature satisfying the shape feature rule, the finder module **230** identifies the custom graphic or custom symbol in the image by comparing the candidate shape feature with a reference shape feature of the custom graphic or custom symbol. For example, the finder module **230** can compare an

area or size of the candidate shape feature with a reference area or size of the reference shape feature. In this example, the finder module **230** identifies the custom graphic based on a match or near match (e.g., a percentage match above a threshold) between the candidate shape feature and the reference shape feature. In this way, the finder module **230** uses the custom graphic, or at least a portion of the custom graphic, as a finder pattern to identify the presence of the optical barcode within a portion of the image.

In some embodiments, the finder module **230** extracts multiple candidate shape features from the image data. In these embodiments, the finder module **230** scores each candidate shape feature and ranks the multiple candidate shape features according to respective scores. For example, the finder module **230** determines a shape feature score for respective candidate shape features based on a count, or weighted count, of shape feature rules satisfied by the respective candidate shape feature. The finder module **230** can iterate through the ranked candidate shape features starting with the highest scoring candidate shape feature and perform further analysis (e.g., comparing the candidate shape feature to a reference shape feature) to determine that the candidate shape feature is the custom graphic.

In some embodiments, the reference shape feature is predetermined, and in other embodiments, the reference shape feature is dynamically determined. For instance, the finder module **230** can dynamically determine the reference shape feature by analyzing a reference image of the custom graphic. For example, the finder module **230** can perform analysis techniques similar to those for analyzing the image data on the reference image such as calculating the reference area value for a particular feature or characteristic of the reference image. In these embodiments, the finder module **230** dynamically determining the reference shape feature allows for dynamic use of a particular custom graphic as a functional pattern in an optical barcode. For instance, the custom pattern system **160** can be provided (e.g., received at the communication module **210**) data representing the reference image or data representing the reference features when the method **500** is performed. In this way, the custom functional patterns do not necessarily have to be fixed prior to performing the method **500**.

In further example embodiments, the finder module **230** searches for multiple custom graphics in the image data of the image (e.g., where multiple versions or different custom graphics are employed as functional patterns). In a specific example, the custom graphic can comprise a first company logo and the company may change logos to a second company logo. The custom pattern system **160** can be operable to use the first company logo as a finder pattern and the second company logo as a finder pattern and the custom pattern system **160** can search for each logo when performing the method **500**.

In further example embodiments, the finder module **230** identifies the custom graphic in the image in conjunction with other candidate shape features extracted from the image data. For example, the finder module **230** can search for both the custom graphic (e.g., a logo) and an outer box (e.g., the outer box **325**) surrounding the custom graphic. In these embodiments, the finder module **230** identifies a combination of the custom graphic and one or more additional candidate shape features extracted from the image data.

At operation **550**, in response to identifying the custom graphic, the alignment module **240** extracts a spatial attribute, geometry attribute, or spatial property of the custom graphic or custom symbol in the image from the image data. For example, the alignment module **240** extracts a position, scale, or orientation of the custom graphic from the image data. In various example embodiments, the spatial attribute is indicative of an orientation of the custom graphic in the image. The alignment module **240** or the decoder module **250** can use the spatial attribute to facilitate decoding the optical barcode.

In further embodiments, the alignment module **240** extracts a spatial attribute, geometry attribute, or spatial property of another candidate shape feature extracted from the image data of the image. For example, the alignment module **240** extracts a spatial attribute of the outer box (e.g., the outer box **325** of FIG. **3**A) surrounding the custom graphic (e.g., the custom graphic **310**) and the markings that encode data. It will be noted that throughout the discussion to follow, the alignment module **240** and the decoder module **250** can use the spatial attribute of the outer box in a same or similar way as the spatial attribute of the custom graphic to determine an alignment of the optical barcode used to facilitate decoding. For example, the alignment module **240** or the decoder module **250** can use the spatial attributes of the outer box to generate a transformed image of the image used to decode the data encoded in the image.

At operation **560**, the decoder module **250** decodes data encoded in a portion of the image from the image data using the spatial attribute of the custom graphic in the image. For instance, the decoder module **250** can perform an image transform using the spatial attributes (e.g., a de-skew, a rotation, a scale, or another type of image transform) to improve detectability or readability of data encoded in a portion of the image. In an example embodiment, the decoder module **250** decodes the data encoded in the portion of the image by detecting marking (e.g., dots, squares, or another marking) indicative of data included in the image. In this way, the decoder module **250** uses the custom graphic, or at least a portion of the custom graphic, as an alignment pattern to facilitate decoding the optical barcode. In various embodiments, the decoder module **250** employs a Reed-Solomon error correction scheme (or other error correction scheme) to decode data encoded in the image. The Reed-Solomon error correction scheme (or other error correction scheme) allows for a successful decoding of the data encoded in the image with a certain percentage of data encoded in the image being corrupt, damaged, or incorrectly decoded. In further embodiments, the decoder module **250** uses a small checksum to verify that the value decoded from the image data is a value that includes real data rather than just random data (e.g., random bits).

In further example embodiments, the decoder module **250** rejects certain results of the decoded data (e.g., results of data decoded from the image data known to be invalid as specified by an administrator of the custom pattern system **160**). For example, the decoder module **250** can reject decoded data that includes all zeros, all ones, or another specified result even though the decoded data passed other data integrity tests (e.g., error correction and checksumming). For example, this can occur when the custom pattern system **160** scans the custom graphic without any associated markings that indicate data (e.g., where the custom graphic is a logo, simply scanning the logo may yield all zeros in the decoded data and may be rejected by the decoder module **250**). In a specific example, scanning the icon associated with social messaging app **1908**, shown below in FIG. **19**, would likely yield data with all zeros and the decoder module **250** would reject the scan.

FIG. **6** is a flow diagram illustrating further example operations for identifying the optical barcode (e.g., the optical barcode **406**) using the custom functional pattern. At

operation **530**, the finder module **230** determines that the candidate shape feature satisfies the shape feature rule. In some embodiments, the operation **530** includes the operations of FIG. **6**.

At operation **610**, the finder module **230** determines that the candidate shape feature comprises an enclosed line from the image data. That is to say, the shape feature rule comprises a path rule, and the finder module **230** determines that the candidate shape feature satisfies the path rule. The finder module **230** can employ a variety of techniques to determine that the candidate shape feature satisfies the path rule.

At operation **630**, the finder module **230** determines whether the candidate shape feature is an enclosed line by determining that the candidate shape feature encircles a portion of the image by having a path that starts at a particular point and returns to the same particular point. In an example embodiment, if the candidate shape feature does not satisfy the path rule (indicated by "no" in FIG. **6**), no further analysis of the candidate shape feature is performed and the finder module **230** analyzes another candidate shape feature or performs no further operations. Alternatively, at operation **640**, if the finder module **230** determines that the candidate shape feature satisfies the path rule (indicated by "yes" in FIG. **6**), the subsequent operations of the method **500** are performed.

To illustrate the concepts of FIG. **6**, FIG. **7** is a diagram **700** illustrating an example of identifying the optical barcode using the custom functional pattern. In the diagram **700**, the image **710** is an example image that is received or accessed from the user device (e.g., the user device **414**). The image **720** is an example image portraying example candidate shape features **730**. For instance, the finder module **230** performs an edge detection image processing on the image **710** to derive the image **720**. From the image **720**, the finder module **230** identifies the candidate shape features **730**.

Callout **740** shows a particular candidate shape feature of the candidate shape features **730**. The callout **740** shows a contour line **750** (illustrated as a dotted line) of the particular candidate shape feature, a path **760**, and a point **770** of the particular candidate shape feature. In the callout **740**, the finder module **230** determines that the path rule is met if the path **760** that starts at the point **770** can follow the contour line **750** and return to the point **770**. In the diagram **700**, the particular candidate shape feature shown in the callout **740** does satisfy the path rule since the path **760** can follow the contour line **750** and return to the point **770**.

FIG. **8** is a flow diagram illustrating further example operations for identifying the optical barcode using the custom functional pattern. At operation **530**, the finder module **230** determines that the candidate shape feature satisfies the shape feature rule. In some embodiments, the operation **530** includes the operations of FIG. **8**.

At operation **810**, the finder module **230** calculates an area value or size approximation of the candidate shape feature. For example, the finder module **230** uses a proxy shape such as a polygon (e.g., a square, a rectangle, or a quadrilateral) or a non-polygonal shape (e.g., an ellipse) to approximate the shape of the candidate shape feature. The finder module **230** fits or nearly fits the proxy shape to the outer edges or outer perimeter of the candidate shape feature so that the proxy shape is representative of an area of the candidate shape feature. Subsequently, the finder module **230** calculates the area value of the proxy shape to determine the area value or size approximation of the candidate shape feature. In some embodiments, the finder module **230** employs such a technique (e.g., polygonal area approximation) to avoid a computationally expensive area calculation of the candidate shape feature in situations where the candidate shape feature is likely to be complex in shape (e.g., an area calculation for a non-uniform or irregular shaped feature is typically more computationally expensive). In some embodiments, other techniques such as pixel-based counting can be employed to determine the area value.

At operation **820**, the finder module **230** determines an area score or size score of the candidate shape feature. The finder module **230** determines the area score by comparing the area value of the candidate shape feature with a reference area value. In some embodiments, the reference area value comprises an area value of a corresponding proxy shape fitted to a reference image of the custom graphic (e.g., the area value of a proxy shape fitted to the ghost logo from a front view perspective). In other embodiments, the reference area value comprises the area value of the custom graphic (e.g., the area value of the ghost logo). The finder module **230** calculates the area score, for example, by determining a match percentage between the candidate shape feature area value and the reference area value. The finder module **230** can employ a wide variety of other schemes and techniques to calculate the area score.

At operation **830**, the finder module **230** determines whether the area score exceeds a threshold. The threshold can be predefined or dynamically determined (e.g., statistically determined based on a rolling historical average of scans).

At operation **840**, based on the area score exceeding the threshold (indicated by "yes" in FIG. **8**), the finder module **230** determines that the candidate shape feature satisfies the area rule and proceeds to subsequent operations. In another example embodiment, the finder module **230** compares the area score to an area range to satisfy the area rule (e.g., greater than a particular value and less than a particular value). If the area score does not exceed the threshold (indicated by "no" in FIG. **8**), then the finder module **230** analyzes another candidate shape feature or no further operations are performed, according to an example embodiment. In some example embodiments, the finder module **230** uses the determination of whether the candidate shape feature satisfies the shape feature rules as a filter (e.g., to remove or skip candidate shape features that are unlikely to be the custom graphic) to identify candidate shape features to be further analyzed in the process of identifying the custom graphic in the image.

To further illustrate the concepts of FIG. **8**, FIG. **9** is a diagram **900** illustrating an example of identifying the optical barcode using the custom functional pattern. In the diagram **900**, image **902** is an example image that is received from the user device. Callout **904** shows the spatial orientation of the image **902**. In this example, the image **902** is portrayed and being seen from a front right perspective. The image **902** includes optical barcode **906**. In this example, the optical barcode **906** employs the custom graphic as a functional pattern.

Callout **908** shows an enlarged portion of the image **902** that includes the candidate shape feature being analyzed by the finder module **230** to identify the custom graphic. In the callout **908**, the polygon **910** (e.g., a quadrilateral) is shown fitted to a perimeter of the candidate shape feature. Area value **912** is the area of the polygon **910**.

Callout **914** shows a reference image of the custom graphic. Callout **916** shows the spatial orientation of the reference image. In this example, the reference image is shown from the front view perspective. Polygon **918** is

shown fitted to a perimeter of the reference image. Reference area value **920** is the area of the polygon **918**. Although FIG. **9** shows polygons **910** and **918** as quadrilaterals, the finder module **230** can employ other shapes such as a square or a shape that follows or traces a contour of the candidate shape feature (e.g., an n-sided polygon or smooth fitted shape that follows contour points of the candidate shape feature).

The finder module **230** compares the area value **912** with the reference area value **920** to determine that the candidate shape feature satisfies the area rule. Another candidate shape feature of the image **902**, such as one of the musical notes of the image **902**, would not have an area value that is similar to the reference area value and therefore would not satisfy the area rule. In this way, the finder module **230** can quickly remove or skip certain candidate shape features that are unlikely to be identified as the custom graphic.

FIG. **10** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern. At operation **540**, the finder module **230** identifies the custom graphic in the image by comparing the candidate shape feature with a reference shape feature of the custom graphic. Subsequent to the operation **540**, the operations of FIG. **10** are performed in some example embodiments.

At operation **1010**, the alignment module **240** extracts a distinctive feature of the custom graphic from the image data where the distinctive feature is indicative of an alignment of the custom graphic (e.g., a particular asymmetry of the custom graphic that can be used to determine an orientation of the custom graphic). For example, the distinctive feature can comprise a distinctive point of the custom graphic, a distinctive curve, a particular asymmetry, a particular non-uniformity, or another characteristic of the custom graphic.

At operation **1020**, the alignment module **240** determines an orientation of the custom graphic in the image by comparing the distinctive feature with a reference distinctive feature of the custom graphic. For example, the alignment module **240** maps the extracted distinctive feature of the custom graphic to a reference distinctive feature to determine spatial differences between the distinctive features. In this way, the alignment module **240** can determine an alignment of the custom graphic as compared to a reference image of the custom graphic based on the determined spatial differences.

At operation **1030**, the alignment module **240** generates a transformed image by transforming the image according to the orientation of the custom graphic. For instance, the alignment module **240** can rotate, de-skew, scale, or otherwise spatially transform the image to allow for a more accurate decoding of the data in the image.

At operation **1040**, the decoder module **250** decodes the data encoded in the image using the orientation and a position of the custom graphic in the image. For example, the decoder module **250** decodes the data encoded in the image from the transformed image. In a specific scenario, the image is transformed to a front view to increase visibility and uniformity of marks in the image that represent data encoded in the image.

To assist in understanding the disclosure of FIG. **10**, FIG. **11** is a diagram **1100** illustrating an example of decoding the optical barcode using the custom functional pattern. In the diagram **1100**, similar to the FIG. **9** described above, image **1102** is an example image that is received from the user device. In this example, the image **1102** is portrayed and being seen from a front right perspective. The image **1102** includes optical barcode **1106**. In this example, the optical barcode **1106** employs the custom graphic as a functional pattern. In some examples, the image **1102** may be a two-dimensional image (e.g., on the Y-Z plane), as shown in the three-dimensional X-Y-Z coordinate system **1104**.

Callout **1108** shows an enlarged portion of the image **1102** that includes the candidate shape feature being analyzed by the alignment module **240**. Callout **1110** shows an enlarged portion of the callout **1108** showing a distinctive feature of the candidate shape feature.

Callout **1112** shows a reference image of the custom graphic. Callout **1114** shows the spatial orientation of the reference image. In this example, the reference image is shown from the front view perspective. Callout **1116** shows an enlarged portion of the callout **1112** showing a reference distinctive feature of the reference image.

The alignment module **240** compares the distinctive feature and the reference distinctive feature to determine an alignment including an orientation, scale, or position. For example, if the image that includes the custom graphic is shown from the front perspective, the distinctive feature of the custom graphic in the image should match the reference distinctive feature. The alignment module **240** can determine perspective changes based on a mismatch between the distinctive feature and the reference distinctive feature. The alignment module **240** uses the mismatch to infer or determine a perspective of the image or other spatial attributes of the image that can be utilized by the decoder module **250** to more accurately decode data from the image.

FIGS. **12**A, **12**B, and **12**C are diagrams illustrating various image transformations used to facilitate decoding the optical barcode using the custom functional pattern. In an example embodiment, the alignment module **240** or the decoder module **250** performs an image transformation such as a rotation as shown by a transition between example optical barcode **1200** and **1202**. In other embodiments, the alignment module **240** or the decoder module **250** performs a de-skewing, scale transformation, or another type of image transformation. In further example embodiments, the alignment module **240** or the decoder module **250** performs other image transformations such as a color inversion as shown by a transition between example optical barcode **1204** and **1206**. The alignment module **240** or the decoder module **250** can perform other image transformation not shown such as image sharpening, noise reduction, or other image processing.

FIG. **12**C illustrates an example of a technique to determine an alignment of the custom graphic. The example optical barcode **1208** is rotated slightly away from zero degrees. An ellipse **1210** can be fitted to the custom graphic to determine an alignment such as a rotation value of the optical barcode **1208**. The major axis **1212** of the ellipse **1210** provides an indication of a rotation value **1214** away from zero degrees (of course, the minor axis, or another axis, may similarly be used to determine a rotation value). The alignment module **240** or the decoder module **250** can perform an image transformation to adjust for the rotation value **1214** as shown by the example optical barcode **1216** being rotated from an original orientation **1218**. In this way, the alignment module **240** or the decoder module **250** can use the custom graphic to determine an alignment for the optical barcode included in the image to assist in decoding the data encoded in the image.

FIG. **13** is a flow diagram illustrating further example operations for decoding the optical barcode using the custom functional pattern. At operation **1040**, the decoder module **250** decodes the data encoded in a portion of the image from

the image data. Subsequent to the operation **1040**, the operations of FIG. **13** are performed in some example embodiments.

At operation **1310**, the decoder module **250** determines a failure to decode the data encoded in the portion of the image using the transformed image. For instance, if the data decoded from the image is corrupted, incomplete, or garbled, the decoder module **250** determines the failure to decode the data. In another instance, a portion of the data encoded in the image can be for the purposes of data validation. That is to say, a known or determinable value can be encoded into the data such that the data is valid if the value is decoded from the image. The decoder module **250** can employ a variety of other schemes and techniques to determine the failure to decode the data encoded in the portion of the image.

At operation **1320**, the alignment module **240** generates another transformed image by transforming the image according to a different orientation of the custom graphic. For example, the alignment module **240** generates a transformed image that is rotated 180 degrees, and the decoder module **250** attempts to decode the data a second time. The alignment module **240** can perform common transforms that may resolve the failure to decode such as 90 degree rotations or another transform that has frequently resolved the failure to decode in past scans. In some embodiments, the alignment module **240** performs another analysis of the image data of the image to determine another alignment to use to use when generating another transformed image. The alignment module **240** can perform other types of image transformations by applying different types of filters (e.g., orientation, color reduction, brightness manipulation, etc.) to the custom graphic.

At operation **1330**, the decoder module **250** decodes the data encoded in the portion of the image using another transformed image. The alignment module **240** and the decoder module **250** can attempt any number (e.g., a set number of attempts or an unlimited number of attempts) of iterations of alignments that ends when the data is successfully decoded from the image. In this way, the custom pattern system **160** can use the markings for self-alignment.

To further explain the discussion in connection with FIG. **13**, FIG. **14** is a diagram **1400** illustrating an example of decoding the optical barcode using the custom functional pattern. Example optical barcode **1410** shows positions for markings with empty circles. Each empty circle of optical barcode **1410** is a position for a marker. Example optical barcode **1420** shows a misalignment between marking positions and markings. Example optical barcode **1430** shows a matching alignment between the markings and the marking positions.

Turning now to FIGS. **15** and **16**, although user interfaces described herein (e.g., FIGS. **15**, **16**, and **18**) depict specific example user interfaces and user interface elements, these are merely non-limiting examples, and many other alternate user interfaces and user interface elements can be generated by the presentation module **220** and presented to the user. It will be noted that alternate presentations of the displays described herein include additional information, graphics, options, and so forth; other presentations include less information, or provide abridged information for easy use by the user.

FIG. **15** is a user interface diagram **1500** depicting an example user interface **1510** for identifying the optical barcode. In the user interface diagram **1500**, the user interface **1510** is showing a substantially real-time image captured from a camera sensor of the user device (e.g., the client device(s) **110**, the user device **414**). The user interface **1510** can include graphics and user interface elements superimposed or overlaid over the substantially real-time image being displayed underneath. For instance, user interface element **1520** is a bracket that indicates identification of an optical barcode. The user interface **1510** can indicate to the user the successful, or unsuccessful, scan of a particular optical barcode.

FIG. **16** is a user interface diagram **1600** depicting an example user interface **1610** for performing an action associated with the optical barcode. In an example embodiment, the user interface **1610** is displayed after the user interface **1510** of FIG. **15** (e.g., after a successful scan, various action options associated with the scan are displayed). The user interface **1610** can include a variety of action options associated with detecting a particular optical barcode such as user interface elements **1620**. In some embodiments, a particular action is automatically performed by the custom pattern system **160** in response to detecting and decoding a particular optical barcode.

In further example embodiments, the action is exclusive to software that provides scanning functionality for the optical barcode that uses the custom functional pattern (e.g., a snapcode). In some embodiments, the software that scans the optical barcode can perform certain exclusive actions without communicating with a server. This is due to the exclusive, branded nature of the custom functional pattern that is not necessarily openly decodable by other third-party software applications. The snapcode can specify such actions since it is likely that the software (e.g., a mobile computing software such as an app) that scans the branded optical barcode is associated with the branded optical barcode.

FIG. **17** is a flow diagram illustrating example operations for generating the optical barcode using the custom functional pattern. The operations of the method **1700** can be performed by components of the custom pattern system **160**, and are so described below for the purposes of illustration.

At operation **1710**, the communication module **210** receives a request to generate a machine-readable image such as an optical barcode that uses custom functional patterns. In some embodiments, the request includes user specified data to encode into the image.

At operation **1720**, the encoder module **270** renders a machine-readable arrangement of marks that encodes the user-specified data. For instance, the marks can comprise dots, squares, or other markings that are arranged in a predetermined pattern. In an example embodiment, the presence of a mark at a particular location in the arrangement is indicative of data.

At operation **1730**, the encoder module **270** generates the machine-readable image by positioning the machine-readable arrangement of marks in the machine-readable image with respect to a position of the custom graphic included in the machine-readable image. For example, the custom graphic can be centered in the optical barcode or positioned elsewhere (e.g., the example optical barcodes of FIGS. **3**A and **3**B).

At operation **1740**, the communication module **210** stores or transmits the machine-readable image. For instance, the communication module **210** can store the machine-readable image on the user device, a server, or another storage repository (either locally or remotely stored). In other instances, the communication module **210** transmits the machine-readable image to the user device, a server, or one or more other devices.

FIG. **18** is a user interface diagram **1800** depicting an example user interface **1810** for generating an optical barcode **1820** using the custom graphic. User interface elements **1830** provide the user with options for generating, sharing, or saving the machine-readable image. In some embodiments, the user interface diagram **1800** includes a user interface configured to receive user-specified data to encode into the machine-readable image (e.g., a social networking service member identifier, a website address, or another piece of information).

FIG. **19** illustrates an example mobile device **1900** executing a mobile operating system (e.g., IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems), consistent with some embodiments. In one embodiment, the mobile device **1900** includes a touch screen operable to receive tactile data from a user **1902**. For instance, the user **1902** may physically touch **1904** the mobile device **1900**, and in response to the touch **1904**, the mobile device **1900** may determine tactile data such as touch location, touch force, or gesture motion. In various example embodiments, the mobile device **1900** displays a home screen **1906** (e.g., Springboard on IOS™) operable to launch applications or otherwise manage various aspects of the mobile device **1900**. In some example embodiments, the home screen **1906** provides status information such as battery life, connectivity, or other hardware statuses. The user **1902** can activate user interface elements by touching an area occupied by a respective user interface element. In this manner, the user **1902** interacts with the applications of the mobile device **1900**. For example, touching the area occupied by a particular icon included in the home screen **1906** causes launching of an application corresponding to the particular icon.

Many varieties of applications (also referred to as "apps") can be executed on the mobile device **1900**, such as native applications (e.g., applications programmed in Objective-C, Swift, or another suitable language running on IOS™ or applications programmed in Java running on ANDROID™), mobile web applications (e.g., applications written in Hypertext Markup Language-5 (HTML5)), or hybrid applications (e.g., a native shell application that launches an HTML5 session). For example, the mobile device **1900** includes a messaging app, an audio recording app, a camera app, a book reader app, a media app, a fitness app, a file management app, a location app, a browser app, a settings app, a contacts app, a telephone call app, or other apps (e.g., gaming apps, social networking apps, biometric monitoring apps). In another example, the mobile device **1900** includes a social messaging app **1908** such as SNAPCHAT® that, consistent with some embodiments, allows users to exchange ephemeral messages that include media content. In this example, the social messaging app **1908** can incorporate aspects of embodiments described herein.

Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Modules can constitute either software modules (e.g., code embodied on a machine-readable medium) or hardware modules. A "hardware module" is a tangible unit capable of performing certain operations and can be configured or arranged in a certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware modules of a computer system (e.g., a processor or a group of processors) can be configured by software (e.g., an application or application portion) as a hardware module that operates to perform certain operations as described herein.

In some embodiments, a hardware module can be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware module can include dedicated circuitry or logic that is permanently configured to perform certain operations. For example, a hardware module can be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware module may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware module can include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware modules become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware module mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) can be driven by cost and time considerations.

Accordingly, the phrase "hardware module" should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. As used herein, "hardware-implemented module" refers to a hardware module. Considering embodiments in which hardware modules are temporarily configured (e.g., programmed), each of the hardware modules need not be configured or instantiated at any one instance in time. For example, where a hardware module comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware modules) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware module at one instance of time and to constitute a different hardware module at a different instance of time.

Hardware modules can provide information to, and receive information from, other hardware modules. Accordingly, the described hardware modules can be regarded as being communicatively coupled. Where multiple hardware modules exist contemporaneously, communications can be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware modules. In embodiments in which multiple hardware modules are configured or instantiated at different times, communications between such hardware modules may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware modules have access. For example, one hardware module can perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware module can then, at a later time, access the memory device to retrieve and process the stored output. Hardware modules can also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

The various operations of example methods described herein can be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors constitute processor-implemented modules

that operate to perform one or more operations or functions described herein. As used herein, "processor-implemented module" refers to a hardware module implemented using one or more processors.

Similarly, the methods described herein can be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method can be performed by one or more processors or processor-implemented modules. Moreover, the one or more processors may also operate to support performance of the relevant operations in a "cloud computing" environment or as a "software as a service" (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an API).

The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented modules can be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented modules are distributed across a number of geographic locations.

The modules, methods, applications and so forth described in conjunction with the figures above are implemented in some embodiments in the context of a machine and an associated software architecture. The sections below describe representative software architecture(s) and machine (e.g., hardware) architecture that are suitable for use with the disclosed embodiments.

Software architectures are used in conjunction with hardware architectures to create devices and machines tailored to particular purposes. For example, a particular hardware architecture coupled with a particular software architecture will create a mobile device, such as a mobile phone, tablet device, or so forth. A slightly different hardware and software architecture may yield a smart device for use in the "internet of things," while yet another combination produces a server computer for use within a cloud computing architecture. Not all combinations of such software and hardware architectures are presented here as those of skill in the art can readily understand how to implement the subject technology in different contexts from the disclosure contained herein.

FIG. **20** is a block diagram illustrating a system **2000** that implements a representative software architecture **2002**, which may be used in conjunction with various hardware architectures herein described. FIG. **20** is merely a non-limiting example of a software architecture and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture **2002** may be executing on hardware such as machine **2100** of FIG. **21** that includes, among other things, processors **2110**, memory/storage **2130**, and I/O components **2150**. A representative hardware layer **2004** is illustrated and can represent, for example, the machine **2100** of FIG. **21**. The representative hardware layer **2004** comprises one or more processing units **2006** having associated executable instructions **2008**. Executable instructions **2008** represent the executable instructions of the software architecture **2002**, including implementation of the methods, modules and so forth in the figures and description above. Hardware layer **2004** also includes memory and storage modules **2010**, which also have executable instructions **2008**. Hardware layer **2004** may also comprise other hardware as indicated by **2012** which represents any other hardware of the hardware layer **2004**, such as the other hardware illustrated as part of machine **2100**.

In the example architecture of FIG. **20**, the software architecture **2002** may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture **2002** may include layers such as an operating system **2014**, libraries **2016**, frameworks/middleware **2018**, applications **2020** and presentation layer **2044**. Operationally, the applications **2020** or other components within the layers may invoke application programming interface (API) calls **2024** through the software stack and receive a response, returned values, and so forth illustrated as messages **2026** in response to the API calls **2024**. The layers illustrated are representative in nature and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide the frameworks/middleware layer **2018**, while others may provide such a layer. Other software architectures may include additional or different layers.

The operating system **2014** may manage hardware resources and provide common services. The operating system **2014** may include, for example, a kernel **2028**, services **2030**, and drivers **2032**. The kernel **2028** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **2028** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **2030** may provide other common services for the other software layers. The drivers **2032** may be responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **2032** may include display drivers, camera drivers, BLUETOOTH® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration. In an example embodiment, the operating system **2014** includes an imaging service **2033** that can provide image processing services, such as hardware-accelerated image processing, or image capture services, such as low-level access to optical sensors or optical sensor data.

The libraries **2016** may provide a common infrastructure that may be utilized by the applications **2020** or other components or layers. The libraries **2016** typically provide functionality that allows other software modules to perform tasks in an easier fashion than to interface directly with the underlying operating system **2014** functionality (e.g., kernel **2028**, services **2030**, or drivers **2032**). The libraries **2016** may include system libraries **2034** (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **2016** may include API libraries **2036** such as media libraries (e.g., libraries to support presentation and manipulation of various media format such as Motion Picture Experts Group Layer-4 (MPREG4), H.264, Motion Picture Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Mesh Refinement (AMR), Joint Photographic Experts Group (JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework that may be used to render two-dimensional (2D) and three-dimensional (3D) in a graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **2016** may also

include a wide variety of other libraries **2038** to provide many other APIs to the applications **2020** and other software components/modules. In an example embodiment, the libraries **2016** include imaging libraries **2039** that provide image processing or image capture functionality that can be utilized by the custom pattern system **160**.

The frameworks **2018** (also sometimes referred to as middleware) may provide a higher-level common infrastructure that may be utilized by the applications **2020** or other software components/modules. For example, the frameworks **2018** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks **2018** may provide a broad spectrum of other APIs that may be utilized by the applications **2020** or other software components/modules, some of which may be specific to a particular operating system or platform. In an example embodiment, the frameworks **2018** include an image processing framework **2022** and an image capture framework **2023**. The image processing framework **2022** can provide high-level support for image processing functions that can be used in aspects of the custom pattern system **160**. Similarly, the image capture framework **2023** can provide high-level support for capturing images and interfacing with optical sensors.

The applications **2020** include built-in applications **2040** or third party applications **2042**. Examples of representative built-in applications **2040** may include, but are not limited to, a contacts application, a browser application, a book reader application, a location application, a media application, a messaging application, or a game application. Third party applications **2042** may include any of the built-in applications **2040** as well as a broad assortment of other applications. In a specific example, the third party application **2042** (e.g., an application developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or other mobile operating systems. In this example, the third party application **2042** may invoke the API calls **2024** provided by the mobile operating system such as operating system **2014** to facilitate functionality described herein. In an example embodiment, the applications **2020** include a messaging application **2043** that includes the custom pattern system **160** as part of the application. In another embodiment, the applications **2020** include a stand-alone application **2045** that includes the custom pattern system **160**.

The applications **2020** may utilize built-in operating system functions (e.g., kernel **2028**, services **2030**, or drivers **2032**), libraries (e.g., system libraries **2034**, API libraries **2036**, and other libraries **2038**), frameworks/middleware **2018** to create user interfaces to interact with users of the system **2000**. Alternatively, or additionally, in some systems, interactions with a user may occur through a presentation layer, such as presentation layer **2044**. In these systems, the application/module "logic" can be separated from the aspects of the application/module that interact with a user.

Some software architectures utilize virtual machines. In the example of FIG. **20**, this is illustrated by virtual machine **2048**. A virtual machine creates a software environment where applications/modules can execute as if they were executing on a hardware machine (such as the machine **2100** of FIG. **21**, for example). A virtual machine is hosted by a host operating system (operating system **2014** in FIG. **20**) and typically, although not always, has a virtual machine monitor **2046**, which manages the operation of the virtual machine **2048** as well as the interface with the host operating system (i.e., operating system **2014**). A software architecture executes within the virtual machine **2048** such as an operating system **2050**, libraries **2052**, frameworks/middleware **2054**, applications **2056**, or presentation layer **2058**. These layers of software architecture executing within the virtual machine **2048** can be the same as corresponding layers previously described or may be different.

FIG. **21** is a block diagram illustrating components of a machine **2100**, according to some example embodiments, able to read instructions from a machine-readable medium (e.g., a machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. **21** shows a diagrammatic representation of the machine **2100** in the example form of a computer system, within which instructions **2116** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **2100** to perform any one or more of the methodologies discussed herein can be executed. For example, the instructions **2116** can cause the machine **2100** to execute the flow diagrams of FIGS. **5**, **6**, **8**, **10**, **13**, and **17**. Additionally, or alternatively, the instructions **2116** can implement the communication module **210**, the presentation module **220**, the finder module **230**, the alignment module **240**, the decoder module **250**, the action module **260**, or the encoder module **270** of FIG. **2**, and so forth. The instructions **2116** transform the general, non-programmed machine into a particular machine programmed to carry out the described and illustrated functions in the manner described. In alternative embodiments, the machine **2100** operates as a standalone device or can be coupled (e.g., networked) to other machines. In a networked deployment, the machine **2100** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **2100** can comprise, but not be limited to, a server computer, a client computer, a PC, a tablet computer, a laptop computer, a netbook, a set-top box (STB), a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **2116**, sequentially or otherwise, that specify actions to be taken by the machine **2100**. Further, while only a single machine **2100** is illustrated, the term "machine" shall also be taken to include a collection of machines **2100** that individually or jointly execute the instructions **2116** to perform any one or more of the methodologies discussed herein.

The machine **2100** can include processors **2110**, memory/storage **2130**, and I/O components **2150**, which can be configured to communicate with each other such as via a bus **2102**. In an example embodiment, the processors **2110** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an ASIC, a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) can include, for example, processor **2112** and processor **2114** that may execute instructions **2116**. The term "processor" is intended to include multi-core processor that may comprise two or more independent processors (sometimes referred to as "cores") that can execute instructions contemporaneously. Although FIG. **21** shows multiple processors **2110**, the machine **2100** may

include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

The memory/storage **2130** can include a memory **2132**, such as a main memory, or other memory storage, and a storage unit **2136**, both accessible to the processors **2110** such as via the bus **2102**. The storage unit **2136** and memory **2132** store the instructions **2116** embodying any one or more of the methodologies or functions described herein. The instructions **2116** can also reside, completely or partially, within the memory **2132**, within the storage unit **2136**, within at least one of the processors **2110** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **2100**. Accordingly, the memory **2132**, the storage unit **2136**, and the memory of the processors **2110** are examples of machine-readable media.

As used herein, the term "machine-readable medium" means a device able to store instructions and data temporarily or permanently and may include, but is not limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)) or any suitable combination thereof. The term "machine-readable medium" should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store instructions **2116**. The term "machine-readable medium" shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., instructions **2116**) for execution by a machine (e.g., machine **2100**), such that the instructions, when executed by one or more processors of the machine **2100** (e.g., processors **2110**), cause the machine **2100** to perform any one or more of the methodologies described herein. Accordingly, a "machine-readable medium" refers to a single storage apparatus or device, as well as "cloud-based" storage systems or storage networks that include multiple storage apparatus or devices. The term "machine-readable medium" excludes signals per se.

The I/O components **2150** can include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **2150** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **2150** can include many other components that are not shown in FIG. **21**. The I/O components **2150** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **2150** can include output components **2152** and input components **2154**. The output components **2152** can include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **2154** can include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

In further example embodiments, the I/O components **2150** can include biometric components **2156**, motion components **2158**, environmental components **2160**, or position components **2162** among a wide array of other components. For example, the biometric components **2156** can include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **2158** can include acceleration sensor components (e.g., an accelerometer), gravitation sensor components, rotation sensor components (e.g., a gyroscope), and so forth. The environmental components **2160** can include, for example, illumination sensor components (e.g., a photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., a barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensor components (e.g., machine olfaction detection sensors, gas detection sensors to detect concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **2162** can include location sensor components (e.g., a Global Positioning System (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

Communication can be implemented using a wide variety of technologies. The I/O components **2150** may include communication components **2164** operable to couple the machine **2100** to a network **2180** or devices **2170** via a coupling **2182** and a coupling **2172**, respectively. For example, the communication components **2164** include a network interface component or other suitable device to interface with the network **2180**. In further examples, communication components **2164** include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, BLUETOOTH® components (e.g., BLUETOOTH® Low Energy), WI-FI® components, and other communication components to provide communication via other modalities. The devices **2170** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

Moreover, the communication components **2164** can detect identifiers or include components operable to detect identifiers. For example, the communication components **2164** can include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as a UPC bar code, multi-

dimensional bar codes such as a QR code, Aztec Code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, Uniform Commercial Code Reduced Space Symbology (UCC RSS)-2D bar codes, and other optical codes), acoustic detection components (e.g., microphones to identify tagged audio signals), or any suitable combination thereof. In addition, a variety of information can be derived via the communication components **2164**, such as location via Internet Protocol (IP) geo-location, location via WI-FI® signal triangulation, location via detecting a BLUETOOTH® or NFC beacon signal that may indicate a particular location, and so forth.

In various example embodiments, one or more portions of the network **2180** can be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a WI-FI® network, another type of network, or a combination of two or more such networks. For example, the network **2180** or a portion of the network **2180** may include a wireless or cellular network, and the coupling **2182** may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or other type of cellular or wireless coupling. In this example, the coupling **2182** can implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1×RTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard setting organizations, other long range protocols, or other data transfer technology.

The instructions **2116** can be transmitted or received over the network **2180** using a transmission medium via a network interface device (e.g., a network interface component included in the communication components **2164**) and utilizing any one of a number of well-known transfer protocols (e.g., HTTP). Similarly, the instructions **2116** can be transmitted or received using a transmission medium via the coupling **2172** (e.g., a peer-to-peer coupling) to devices **2170**. The term "transmission medium" shall be taken to include any intangible medium that is capable of storing, encoding, or carrying the instructions **2116** for execution by the machine **2100**, and includes digital or analog communications signals or other intangible medium to facilitate communication of such software.

FIG. **22** is a diagram of an example system **2200** in which web authentication via camera may be implemented. As shown, the system **2200** includes an authentication server **2210**, a web server **2220**, a computing device **2230**, and a mobile device **2240** connected to one another via a network **2250**. The network may include one or more of the Internet, an intranet, a wired network, a wireless network, a LAN, a WAN, a WiFi network, a cellular network, etc.

The mobile device **2240** is, according to some examples, a mobile phone, a tablet computer, a PDA, a digital music player, or a laptop computer. As shown, the mobile device **2240** has, among other things, a camera **2242** and a display unit **2244**. The camera **2242** is used to scan images, take photographs, record or stream videos, etc. The display unit **2244** includes, according to one or more examples, one or more screens (e.g., touchscreens), one or more monitors, or one or more projector displays. The display unit **2244** is used to display images or information. As shown, the display unit **2244** displays an identity verification image for scanning into the computing device **2230** to verify the user's identity. The camera **2242** and the display unit **2244** may be components of the mobile device **2240** or may be coupled with the mobile device **2240** via a wired or wireless connection.

The computing device **2230** is, according to some examples, a mobile phone, a tablet computer, a PDA, a digital music player, a laptop computer, or a desktop computer. As shown, the computing device **2230** has, among other things, a camera **2232** and a display unit **2234**. The camera **2232** is used to scan images, take photographs, record or stream videos, and the like. The display unit **2234** includes, according to one or more examples, one or more screens (e.g., touchscreens), one or more monitors, or one or more projector displays. The display unit **2234** is used to display images or information. According to some examples, the display unit **2234** displays instructions for the user to scan the identity verification image from the display unit **2244** of the mobile device **2240** into the camera **2232** of the computing device **2230**. The camera **2232** and the display unit **2234** may be components of the computing device **2230** or may be coupled with the computing device **2230** via a wired or wireless connection.

As shown in FIG. **22**, the camera **2232** of the computing device **2230** scans the identity verification image displayed at the display unit **2244** of the mobile device **2240**. After scanning the identity verification image, the computing device **2230** transmits the scanned identity verification image over the network for providing, to the computing device **2230**, access to a resource in response to verifying the user's identity.

The web server **2220** hosts one or more web-based secure resources (e.g., webpages or webpage content) that are accessible to users of computing devices (e.g., computing device **2230**) after verifying the identity of the user. The web-based resources include, for example, stored account information such as, messages in a messaging service, resources in a social networking service, financial institution account information, or resources (e.g., stored credit card number, shipping address, etc.) for shopping in an online store.

The authentication server **2210** verifies the identity of the user of the computing device **2230** and instructs the web server **2220** to provide, to the computing device **2230**, access to the secure resource after verifying the identity of the user of the computing device **2230**. According to some implementations, the authentication server **2210** transmits, to the mobile device **2240**, an identity verification image. The authentication server **2210** transmits, to the computing device **2230**, an instruction to scan, via the camera **2232** of the computing device, an image for verifying a user's identity. The authentication server **2210** receives, from the computing device **2230**, a scanned image. The authentication server **2210** determines whether the scanned image includes data from the identity verification image. The authentication server **2210** transmits, to the web server **2220**, an indication that the user's identity has been verified upon determining that the scanned image includes the data from the identity verification image. Operations of the authentication server **2210** are described in greater detail in conjunction with FIG. **23** and FIG. **24**.

FIG. **22** illustrates a single authentication server, a single web server, a single computing device, and a single mobile device. However, the subject technology may be implemented with two or more authentication servers, web servers, computing devices, or mobile devices. In addition, as discussed herein, the operations of the authentication server **2210** and the functions of the web server **2220** are each implemented by a single machine. However, the operations of either the authentication server **2210** or the web server **2220** may be implemented at multiple different machines working together, for example, in a server farm. In some examples, a single machine implements the functions of both the authentication server **2210** and the web server **2220**. The multiple different machines may be remote from one another and may communicate with one another over the network **2250**.

FIG. **23** is a block diagram of an example of the authentication server **2210** of FIG. **22**. As shown, the authentication server **2210** includes a processor **2305**, a network interface **2310**, and a memory **2315**. The processor **2305** executes machine instructions, which may be stored in the memory **2315**. While a single processor **2305** is illustrated, the authentication server **2210** may include multiple processors arranged into multiple processing units (e.g., CPU, GPU) etc.). The processor **2305** may include one or more processors. The network interface **2310** allows the authentication server **2210** to send and receive data via the network **2250**. The network interface **2310** may include one or more network interface cards (NICs). The memory **2315** stores data or instructions. As shown, the memory **2315** includes an identity verification image generator **2320**, an identity verification module **2325**, and identity verification data **2330**.

The identity verification image generator **2320** is configured to generate an identity verification image for a user. In some examples, the identity verification image includes a geometric shape with a custom pattern and an optical barcode within the geometric shape (for example, as illustrated in FIG. **3**A and FIG. **3**B). The identity verification image generator **2320** is configured to transmit, to the mobile device **2240**, the identity verification image. The identity verification image is transmitted over the network **2250**. In some cases, the mobile device **2240** is identified based on the mobile device **2240** having an application (e.g., an instant messaging application) and the user whose identity is to be verified being logged into the instant messaging application at the mobile device **2240**.

Any image can be the identity verification image. In some examples, the identity verification image includes encoded information (e.g., encoded in binary with dots representing 1 and blank spaces representing 0) for identifying the identity of a user. For example, the identity verification image can include a code that the authentication server **2210** maps (e.g., within a stored hash table or data repository) to the associated user's identity.

The identity verification module **2325** is configure to receive, from the computing device **2230**, a scanned image. In some cases, the scanned image is scanned, at the computing device **2230**, using the camera **2232** of the computing device **2230**. The identity verification module **2325** is configured to determine whether the scanned image includes data from the identity verification image. For example, the identity verification module **2325** reads the encoded information from the scanned image and determines whether this encoded information corresponds to the encoded information of the identity verification image that was transmitted to the mobile device **2240**. Upon determining that the scanned image includes the data from the identity verification image, the identity verification server is configured to transmit, to the web server **2220**, an indication that the user's identity has been verified. In response, the web server provides, to the computing device **2230**, access to a secure resource.

The identity verification data **2330** stores information about identity verification image(s) that were provided to mobile device(s) (e.g., mobile device **2240**) such that a scanned image, received by the authentication server **2210**, can be determined to correspond to an identity verification image. As used herein, the phrase "corresponds to" encompasses its plain and ordinary meaning. In some cases, the scanned image corresponds to the identity verification image if the same information is encoded (e.g., using dots and blank spaces) in both the scanned image and the identity verification image. In some cases, when transmitting the scanned image to the authentication server **2210**, the user of the computing device **2230** provides an indication of his/her identity (e.g., username or telephone number), and the authentication server **2210** verifies the user's identity by comparing the data from the scanned image with data corresponding to the identity verification image provided to the mobile device **2240** of the user. For example, the user enters his/her username, telephone number or other identity information (but, in some cases, not password) to identify him/herself. Based on the entered username or telephone number, the authentication server **2210** can identify a specific identity verification image that was sent to the mobile device **2240** of the user, and a scanned image corresponding to which should now be received from the computing device **2230**.

Alternatively, the user may cause the computing device **2230** to transmit, to the authentication server **2210**, the scanned image without indicating his/her identity. In accordance with this embodiment, the authentication server **2210** compares the data in the transmitted scanned image with data from all of the identity verification images that were generated by the authentication server **2210** during a predetermined time period (e.g., the last ten minutes, hour, two hours, etc.). Alternatively, in some implementations, the scanned image (created using the identity verification image) is decoded to yield both information setting forth the identity (e.g., username or telephone number) of the user and information for verifying the identity of the user.

For example, during a predetermined time period, the authentication server **2210** sends three identity verification images to mobile devices with telephone numbers 111-2222, 333-4444, and 555-6666. According to one implementation, when transmitting the scanned image, the user identifies him/herself by telephone number (e.g., 111-2222) such that the authentication server **2210** knows to which identity verification image the scanned image should correspond.

According to other implementations, the user does not specify his/her telephone number. In one case, upon receiving a scanned image from the computing device **2230**, the authentication server compares the scanned image with all three identity verification images to determine to which identity verification image, if any, the scanned image corresponds. In another case, specified bits (e.g., the top-leftmost n bits, where n is a predetermined positive integer) of the identity verification image and, therefore, also the scanned image, specify the telephone number. Upon reading the telephone number from the scanned image, the authentication server knows with which identity verification image the scanned image should be compared. The bits of the identity verification image and the scanned image can correspond to dots and blank spaces, with dots representing 1 and blank spaces representing 0.

As used herein, the term "configured" encompasses its plain and ordinary meaning. A module (e.g., identity verification image generator **2320** or identity verification module **2325**) may be configured to carry out operation(s) by storing code for the operation(s) in memory (e.g., memory **2315**). Processing hardware (e.g., processor **2305**) may carry out the operations by accessing the appropriate locations in the memory. Alternatively, the module may be configured to carry out the operation(s) by having the operation(s) hardwired in the processing hardware.

FIG. **24** is a flow diagram illustrating an example method **2400** for web authentication via camera, according to some example embodiments. The method **2400** may be implemented at the authentication server **2210**.

The method **2400** begins at step **2410**, where the authentication server **2210** transmits, to the mobile device **2240**, an identity verification image. In some cases, the identity verification image is transmitted to the mobile device **2240** in response to a request for the authentication image. The request for the authentication image comes from the mobile device **2240**. Alternatively, the request from the authentication image comes from the computing device **2230**. If the request comes from the computing device **2230**, the request includes an identification of the mobile device **2240**, which is provided as input by the user of the computing device **2230**. The identification of the mobile device may be a username in an application, such as an instant messaging application, of the mobile device, or a telephone number of the mobile device. In some examples, the identity verification image includes encoded data which is to be decoded to verify the identity of the user of the mobile device **2240**. In some examples, the identity verification image includes a geometric shape (e.g., a square or rectangle with rounded corners) with a custom pattern and an optical barcode within the geometric shape. The optical barcode includes the encoded data.

The authentication server **2210** identifies the mobile device **2240** to which to transmit the identity verification image based on a request, for the identity verification image, transmitted either by the mobile device **2240** or by the computing device **2230**. In some cases, the user of the mobile device **2240** has an account with the authentication server **2210** (which may also be used for other purposes, such as accessing an instant messaging application). If the computing device **2230** transmits the request for the identity verification image, the request, which is entered into the computing device **2230** by the user of the computing device **2230**, includes an indication of the mobile device **2240** (e.g., telephone number or username in instant messaging service) to which to transmit the identity verification image.

In some cases, the identity verification image is transmitted, from the authentication server **2210** to the mobile device **2240**, in conjunction with an indication of a validity period (e.g., 5 minutes, 10 minutes, 1 hour, 2 hours, or 24 hours) for the identity verification image. The validity period indicates for how much time the identity verification image can be used before it stops being valid for identifying the user's identity. A shorter validity period decreases the probability that the identity verification image will be compromised, for example, by a stranger who takes a photograph of the identity verification image, by the user accidentally sharing the identity verification image with a contact, or by the user losing or forgetting his/her mobile device. Upon expiration of the validity period, the authentication server **2210** removes, from the memory **2315** of the authentication server **2210** (e.g., from the identity verification data **2330**), data associated with the identity verification image. After expiration of the validity period, the authentication server **2210** foregoes transmitting an indication that the user's identity has been verified using the data associated with the identity verification image.

After the identity verification image is transmitted to the mobile device **2240**, the identity verification image is displayed on the display unit **2244** of the mobile device **2240**. The user then scans the display unit **2244** displaying the identity verification image into the computing device **2230** using the camera of the computing device **2230**, in order to authenticate the computing device **2230** to allow the computing device **2230** to access a secure web-based resource at the web server **2220**. In some cases, the authentication server **2210** transmits, for display at the computing device **2230**, an instruction for the user. The instruction instructs the user to place the display unit **2244** of the mobile device **2240**, which displays the identity verification image, in front of the camera **2232** of the computing device **2230** for scanning the identity verification image into the computing device **2230**. In some cases, the authentication server **2210** is able to identify the computing device **2230** based on the computing device **2230** requesting access to the secure web-based resource at the web server **2220**. The web server **2220** either informs the authentication server **2210** of an address of the computing device **2230** or allows the authentication server **2210** to communicate with the computing device **2230** via the web server **2220**.

The computing device **2230** generates a scanned image by scanning the display unit **2244** of the mobile device **2240** (which displays the identity verification image) into the camera **2232** of the computing device. The computing device **2230** transmits the scanned image to the authentication server **2210**.

At step **2420**, the authentication server **2210** receives, from the computing device **2230**, the scanned image. In some cases, the authentication server **2210** decodes encoded information in the scanned image.

At step **2430**, the authentication server **2210** determines whether the scanned image includes data from the identity verification image. If the identity verification image (and the scanned image generated from the identity verification image) includes the geometric shape with the custom pattern and the optical barcode, the authentication server **2210** decodes encoded information in the optical barcode within the geometric shape based on an orientation of the geometric shape identified by the custom pattern. The authentication server **2210** verifies whether the decoded information corresponds to the stored identity of the user. In some cases, determining whether the scanned image includes data from the identity verification image includes decoding data encoded in the scanned image and determining whether the decoded data corresponds to the data that was encoded into the identity verification image.

According to some aspects, the authentication server **2210** receives, from the web server **2220** or the computing device **2230**, an indication of the user's identity (e.g., a username or telephone number). In some examples, the indication of identity is entered into the computing device **2230** by the user of the computing device **2230** and provided to the authentication server **2210** by the web server **2220**. The authentication server **2210** then determines whether the scanned image includes data from the identity verification image that was transmitted to the mobile device **2240** associated with the user's identity (e.g., being logged into an application with the username of the user's identity or having the telephone number of the user's identity).

According to other aspects, prior to receiving the scanned image, the authentication server **2210** is not informed of the identity of the user sending the scanned image. However, the authentication server **2210** stores information, generated at the authentication server **2210**, about users to whom identity verification images were transmitted, and can use this information to identify the user sending the scanned image, as discussed below. In some implementations, the authentication server **2210** identifies the user by determining whether the scanned image includes data from one of multiple identity verification images provides to multiple users. For example, if the scanned image decodes to 1-0-1-1 and the authentication server **2210** provides identity verification images with the codes 0-0-1-1, 1-1-0-0, and 1-0-1-1, the scanned image corresponds to the user associated with the last identity verification image.

In other implementations, the authentication server **2210** decodes data from a first portion of the scanned image (e.g., the first n bits) to determine the user's identity. The authentication server **2210** decodes a second portion (e.g., everything after the first n bits) of the scanned image (either simultaneously with decoding the first portion or after decoding the first portion). The authentication server **2210** compares the decoded data from the second portion with data that was encoded in the identity verification image for the user to determine whether the scanned image includes data from the identity verification image. The first portion is different from the second portion.

Upon determining, at the authentication server **2210**, that the scanned image includes data from the identity verification image, the method **2400** continues to step **2440**. Upon determining that the scanned image does not include the data from the identity verification image, the method **2400** continues to step **2450**.

At step **2440**, upon determining that the scanned image includes data from the identity verification image, the authentication server **2210** transmits, to the web server **2220**, an indication that the user's identity has been verified together with an indication of the user's identity, which may correspond to a telephone number or a username (e.g., in an instant messaging service). In response, the web server **2220** provides access to the secure web-based resource to the computing device **2230**. After step **2440**, the method **2400** ends.

At step **2450**, upon determining that the scanned image does not include data from the identity verification image, the authentication server **2210** transmits, to the web server **2220**, an indication that the user's identity has not been verified. In response, the web server **2220**, does not provide access to the secure web-based resource to the computing device **2230**, and informs the computing device **2230** that access to that resource is denied. The user may then attempt to obtain access to the resource using another authentication method (e.g., entering a password or re-scanning the identity verification image). Alternatively, upon determining that the scanned image does not include data from the identity verification image, the authentication server **2210** may forego notifying the web server **2220** that the user's identity has not been verified. The web server **2220** may deny the computing device **2230** access to the secure web-based resource until the user's identity is verified using the scanned image or using another method. After step **2450**, the method **2400** ends.

FIG. **25** is a data flow diagram illustrating an example method **2500** for web authentication via camera. As shown, the method **2500** is implemented with an authentication server (auth. server) **2210**, a web server **2220**, a computing device **2230**, and a mobile device **2240**.

The method **2500** begins at step **2505**, where the computing device **2230** accesses example.com (or any other webpage stored at the web server **2220**). The computing device **2230** accesses example.com, for example, in response to the user entering the uniform resource locator (URL) example.com into a web browser.

At step **2510**, the web server **2220** provides, to the computing device **2230**, data from example.com, in response to the computing device **2230** accessing example.com. The data includes any information presented on the website example.com, such as text, images, videos, and the like.

At step **2515**, the user at the computing device **2230** requests to login to his/her account in example.com. For example, the user may wish to place a comment on an item (e.g., video, article, etc.) on example.com, and may log in to do so.

At step **2520**, in response to the user's request to log in to his/her account, the web server **2220** requests a scanned image from the user's computing device **2230**. The web server **2220** may request the scanned image as an alternative to another method for logging in (e.g., entering a password).

At step **2525**, upon noticing that the scanned image has been requested via the computing device **2230**, the user requests an identity verification image for the mobile device **2240**. As shown, the user enters the request into the mobile device **2240**, which transmits the request to the authentication server **2210**. In an alternative implementation, the user enters the request via the computing device **2230**, and provides identifying information, such as a username or a telephone number (but, in some cases, not a password) of the mobile device **2240**. The computing device then forwards the request and the identifying information of the mobile device **2240** to the web server **2220**, which forwards the request and the identifying information to the authentication server **2210**.

At step **2530**, the authentication server **2210** transmits the identity verification image to the mobile device **2240**. The identity verification image is transmitted over one or more networks. In some examples, the identity verification image is accessed, at the mobile device **2240**, via an application, such as an instant messaging application or a special-purpose application for communicating with the authentication server.

At step **2535**, after the mobile device receives the identity verification image, the user scans the identity verification image from the display unit **2244** of the mobile device **2240** to the camera **2232** of the computing device **2230**.

At step **2540**, the computing device **2230** provides the scanned image to the web server **2220** over one or more networks. The web server **2220** forwards the scanned image to the authentication server **2210** for identifying the user.

At step **2545**, the authentication server **2210** identifies the user based on the scanned image. The authentication server **2210** identifies the user by comparing information encoded (e.g., with dots and blank spaces) the scanned image with information that was encoded into the identity verification images provided to various mobile devices. Upon determining that the scanned image includes the same information as one of the identity verification images, the authentication server **2210** identifies the user as the owner of the mobile device to which that identity verification image was provided. The authentication server **2210** notifies the web server **2220** of the user's identity and confirms to the web server **2220** that the user's identity was verified.

At step **2550** upon receiving, from the authentication server **2210**, the user's identity information and a confirmation that the identity has been verified, the web server **2220** provides, to the computing device **22230**, access to the account of the identified user. After step **2550**, the method **2500** ends.

In some implementations, the web server **2220** provides a nonce to the computing device **2230** together with the request for the scanned image of step **2520** so that when the request for an identification verification image is sent to the authentication server **2210** at step **2525**, the nonce is encoded into the image. Thus, when the image is provided back to the authentication server **2210** in step **2540**, the authentication server **2210** can return the nonce back to the web server **2220** along with the user identity in step **2545**. This transmission, in step **2545**, verifies not only the user's identity but the fact that the request for verification came from the web server **2220**. This may help eliminate certain types of spoofing.

In some cases, the request **2525** contains a nonce (which is in some cases encrypted with a private key of the mobile device **2240**), and the nonce is encoded into the identity verification image provided in step **2530** in a way that cannot be decoded, for example, using the public key of the authentication server **2210**. When the scanned image is sent to the authentication server in step **2540**, the authentication server **2210** checks the nonce in the scanned image against the nonce encoded into the identity verification image. This reduces the likelihood of a replay attack or someone stealing the identity verification image and using it for authentication, since authentication using the identity verification image depends on the image (which has the encoded nonce) and the nonce itself.

In some implementations, there could be some check on the part of the authentication server **2220**, so that the authentication server **220** is satisfied that the mobile device **2240** has the right to receive an identity verification image on behalf of a particular user. In some cases, this check comes from the authentication server knowing the telephone number of the mobile device **2240** beforehand and double-checking it with the source of the request **2525**. If the source of the request **2525** can be spoofed, something else can be used to double-check the telephone number.

According to one implementation for creating the identity verification image, a user accesses a webpage, hosted at the web server **2220**, on the computing device **2230**. The user provides a telephone number or username for identifying his/her mobile device **2240** and selects a button for receiving the identity verification image at the mobile device **2240**. The web server **2220** transmits the telephone number or username to the authentication server **2210**, which generates the identity verification image and provides the identity verification image to the mobile device **2240**. The mobile device **2240** provides a user output notifying the user that it has received the identity verification image. The user opens an application on the mobile device **2240** to access the identity verification image. The user scans the identity verification image from the mobile device **2240** into the computing device **2230** via the camera **2232** of the computing device **2230**. The computing device **2230** provides the scanned image to the web server **2220**, which provides the scanned image to the authentication server **2210**. The authentication server **2210** confirms that the user's identity has been verified based on data encoded in the scanned image. After a threshold time period (e.g., one or two minutes) the identity verification image expires, and the authentication server **2210** will no longer confirm that the user's identity has been verified based on data from a scanned image corresponding to data from the generated identity verification image.

According to another implementation, to generate the identity verification image, the user accesses an application (e.g., an application for generating the identity verification image, which may also be used for other purposes, such as instant messaging) on the mobile device **2240**. Within the application, the user navigates to a workflow for generating the identity verification image and selects a button for generating the identity verification image. The mobile device **2240** sends, to the authentication server **2210**, a request for the identity verification image. The authentication server **2210** generates a new identity verification image and provides the generated identity verification image to the mobile device **2240**. The user displays the identity verification image on a display unit **2244** of the mobile device **2240** and scans the displayed identity verification image into the computing device **2230** via the camera **2232** of the computing device **2230**. The computing device **2230** provides the scanned image to the web server **2220**, for example, via an interface at a webpage. The web server **2220** forwards the scanned image to the authentication server **2210**, which verifies the identity of the user using the scanned image. After a threshold time period (e.g., one or two minutes) the identity verification image expires, and the authentication server **2210** will no longer confirm that the user's identity has been verified based on data from a scanned image corresponding to data from the generated identity verification image.

In some cases, a portion of the identity verification image encodes a user's telephone number or username (e.g., in an instant messaging application). The encoded telephone number or username is used to look up information, such as whether the user has permission to access the resource at the web server **2220** that the user is attempting to access.

Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the subject matter herein.

Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present disclosure. Such embodiments of the inventive subject matter may be referred to herein, individually or collectively, by the term "invention" merely for convenience and without intending to voluntarily limit the scope of this application to any single disclosure or inventive concept if more than one is, in fact, disclosed.

The embodiments illustrated herein are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore,

is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

As used herein, the term "or" may be construed in either an inclusive or exclusive sense. Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, modules, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present disclosure. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present disclosure as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

What is claimed is:

1. A system for user authentication using images, comprising:

hardware processing circuitry;

a hardware memory storing instructions that when executed configure the hardware processing circuitry to perform operations comprising:

receiving, at an authentication server, a request from a mobile device for a user identity verification image corresponding to a user identity of a user of the mobile device;

mapping an optical barcode to the user identity;

generating, by the authentication server, the user identity verification image to include a geometric shape with a custom pattern and the optical barcode within the geometric shape;

transmitting, from the authentication server to the mobile device, the user identity verification image in response to the request;

receiving, at the authentication server a scanned image captured by a computing device, wherein the computing device is different from the mobile device;

determining, at the authentication server, the scanned image includes data from the user identity verification image, the data including the optical barcode; and

instructing, by the authentication server, a web server accessed by the computing device, that the user identity has been verified based on the determining and the mapping between the optical barcode and the user's identity.

2. The system of claim **1**, the operations further comprising instructing, by the authentication server, the web server that a second user's identity has not been verified upon determining that a second scanned image does not include second data from a second user identity verification image.

3. The system of claim **1**, wherein determining, at the authentication server, that the scanned image includes data from the user identity verification image comprises:

decoding data encoded in the scanned image; and

determining the decoded data corresponds to data which was encoded into the user identity verification image.

4. The system of claim **1**, the operations further comprising:

receiving, at the authentication server, an indication of the user's identity from the web server or the computing device,

wherein determining, at the authentication server, the scanned image includes the data from the user identity verification image comprises comparing data from the scanned image with data from the user identity verification image transmitted to the mobile device associated with the user's identity.

5. The system of claim **1**, the operations further comprising identifying, at the authentication server, the user by determining whether the scanned image includes data from one of a plurality of user identity verification images provided to a plurality of users.

6. The system of claim **1**, the operations further comprising decoding data from a first portion of the scanned image to determine the user's identity, wherein determining the scanned image includes data from the user identity verification image comprises comparing data decoded from a second portion of the scanned image with data associated with the user identity verification image provided to the mobile device corresponding to the user's identity, wherein the first portion is different from the second portion.

7. The system of claim **1**, the operations further comprising mapping an optical barcode to the user's identity, and generating, by the authentication server, the user identity verification image to include a geometric shape with a custom pattern and the optical barcode within the geometric shape.

8. The system of claim **7**, wherein determining the scanned image includes the data from the user identity verification image comprises:

decoding encoded information in the optical barcode within the geometric shape based on an orientation of the geometric shape identified by the custom pattern; and

verifying whether the decoded information corresponds to stored identity information of the user.

9. The system of claim **1**, the operations further comprising:

transmitting, from the authentication server to the mobile device in conjunction with the user identity verification image, an indication of a validity period for the user identity verification image; and

upon expiration of the validity period, removing, from a memory of the authentication server, data associated with the user identity verification image and foregoing instructing the web server that the indication that the user's identity has been verified using the data associated with the user identity verification image.

10. The system of claim **1**, wherein the scanned image is generated by the user scanning a display unit of the mobile device into a camera of the computing device, wherein the display unit of the mobile device displays the user identity verification image.

11. A method for user authentication using images, comprising:

receiving, at an authentication server, a request from a mobile device for a user identity verification image corresponding to a user identity of a user of the mobile device;

mapping an optical barcode to the user identity;

generating, by the authentication server, the user identity verification image to include a geometric shape with a custom pattern and the optical barcode within the geometric shape;

transmitting, from the authentication server to the mobile device, the user identity verification image in response to the request;

receiving, at the authentication server a scanned image captured by a computing device, wherein the computing device is different from the mobile device;

determining, at the authentication server, the scanned image includes data from the user identity verification image, the data including the optical barcode; and

instructing, by the authentication server, a web server accessed by the computing device, that the user identity has been verified based on the determining and the mapping between the optical barcode and the user's identity.

12. The method of claim **11**, further comprising instructing, by the authentication server, the web server that a second user's identity has not been verified upon determining that a second scanned image does not include second data from a second user identity verification image.

13. The method of claim **11**, wherein determining, at the authentication server, that the scanned image includes data from the user identity verification image comprises:

decoding data encoded in the scanned image; and

determining the decoded data corresponds to data which was encoded into the user identity verification image.

14. The method of claim **11**, further comprising:

receiving, at the authentication server, an indication of the user's identity from the web server or the computing device,

wherein determining, at the authentication server, the scanned image includes the data from the user identity verification image comprises comparing data from the scanned image with data from the user identity verification image transmitted to the mobile device associated with the user's identity.

15. The method of claim **11**, further comprising identifying, at the authentication server, the user by determining whether the scanned image includes data from one of a plurality of user identity verification images provided to a plurality of users.

16. The method of claim **11**, further comprising decoding data from a first portion of the scanned image to determine the user's identity, wherein determining the scanned image includes data from the user identity verification image comprises comparing data decoded from a second portion of the scanned image with data associated with the user identity verification image provided to the mobile device corresponding to the user's identity, wherein the first portion is different from the second portion.

17. The method of claim **11**, further comprising mapping an optical barcode to the user's identity, and generating, by the authentication server, the user identity verification image to include a geometric shape with a custom pattern and the optical barcode within the geometric shape, wherein determining the scanned image includes the data from the user identity verification image comprises:

decoding encoded information in the optical barcode within the geometric shape based on an orientation of the geometric shape identified by the custom pattern; and

verifying whether the decoded information corresponds to stored identity information of the user.

18. The method of claim **11**, further comprising:

transmitting, from the authentication server to the mobile device in conjunction with the user identity verification image, an indication of a validity period for the user identity verification image; and

upon expiration of the validity period, removing, from a memory of the authentication server, data associated with the user identity verification image and foregoing instructing the web server that the indication that the user's identity has been verified using the data associated with the user identity verification image.

19. A non-transitory computer readable storage medium comprising instructions for user authentication using images, that when executed configure hardware processing circuitry to perform operations comprising:

receiving, at an authentication server, a request from a mobile device for a user identity verification image corresponding to a user identity of a user of the mobile device;

mapping an optical barcode to the user identity;

generating, by the authentication server, the user identity verification image to include a geometric shape with a custom pattern and the optical barcode within the geometric shape; transmitting, from the authentication server to the mobile device, the user identity verification image in response to the request;

receiving, at the authentication server a scanned image captured by a computing device, wherein the computing device is different from the mobile device;

determining, at the authentication server, the scanned image includes data from the user identity verification image, the data including the optical barcode; and

instructing, by the authentication server, a web server accessed by the computing device, that the user identity has been verified based on the determining and the mapping between the optical barcode and the user's identity.

20. The non-transitory computer readable storage medium of claim **19**, the operations further comprising:

receiving, at the authentication server, an indication of the user's identity from the web server or the computing device,

wherein determining, at the authentication server, the scanned image includes the data from the user identity verification image comprises comparing data from the scanned image with data from the user identity verification image transmitted to the mobile device associated with the user's identity.

* * * * *