US 20090150484A1

(19) United States

(12) Patent Application Publication

(10) Pub. No.: US 2009/0150484 A1

(43) Pub. Date: Jun. 11, 2009

Roberts

(54) MEDICAL DEVICE METADATA

(75) Inventor: **Nick Roberts**, Cumming, GA (US)

Correspondence Address:
MERCHANT & GOULD PC
P.O. BOX 2903
MINNEAPOLIS, MN 55402-0903 (US)

(73) Assignee: **Smiths Medical MD**, St. Paul, MN (US)

(21) Appl. No.: **12/189,541**

(22) Filed: **Aug. 11, 2008**

Related U.S. Application Data

(60) Provisional application No. 60/964,444, filed on Aug. 10, 2007.


Publication Classification

(51) **Int. Cl.**
G06F 15/16 (2006.01)
G06F 17/30 (2006.01)

(52) **U.S. Cl.** **709/203**; 709/206; 707/104.1; 707/E17.044

(57) **ABSTRACT**

Methods and systems of patient treatment are disclosed. The methods and systems include use of medical device informatics to modify and validate therapies and drugs used in those therapies. In certain embodiments, a medical device, such as a medical infusion pump, interfaces with a server to administer the patient treatments. In one such embodiment, a method for use of metadata on medical devices is disclosed. A method includes associating metadata with one or more medical devices, the metadata corresponding to an attribute of the medical devices. The method also includes storing the metadata on a server, the server configured to communicate with each of the medical devices by using the metadata.





104
MEDICAL DEVICE
106
PASSIVE
MEDICAL DEVICE
102
SERVER
WORKSTATION
110
114
108
MEDICAL PUMP
112
116
PORTABLE COMPUTING
SYSTEM
WIRELESS
ACCESS POINT
108
MEDICAL PUMP
108
MEDICAL PUMP
100

Fig. 1



212
Input
Device
214
Output
Device
204
RAM
206
Flash
208
EEPROM
210
Battery
System
Programmable Circuit
202
224
Patient
Interface
222
Wireless
Network
Interface
220
Wired
Network
Interface
218
Alarm
216
Display
200

Fig. 2



306
CLIENT APPLICATIONS
304
BACK-OFFICE COMPONENTS
324
ADMINISTRATIVE WEB FORMS
310
ADMINISTRATION WEB SERVICE
ADMINISTRATION 316
302
308
MEDICAL DEVICE SERVER
MEDICAL DEVICES
326
REPORTS
DATA WAREHOUSE 322
EVENT TRACKING 318
EVENT TRACKING WEB SERVICE
312
328
DASHBOARD WEB FORMS
OPERATIONS 320
330
MAINTENANCE WEB FORMS
OPERATIONS WEB SERVICE
314
332
EXTERNAL APPLICATIONS
300

Fig. 3



306
CLIENT APPLICATIONS
304
MANAGED COMPONENTS
404
FACILITY COMPONENT
324
ADMINISTRATION WEB FORMS
310
ADMINISTRATION WEB SERVICE
ADMINISTRATION 316
308
MEDICAL DEVICE SERVER
302
MEDICAL DEVICES
326
REPORTS
DATA WAREHOUSE 322
EVENT TRACKING 318
EVENT TRACKING WEB SERVICE
312
328
DASHBOARD WEB FORMS
OPERATIONS 320
330
MAINTENANCE WEB FORMS
OPERATIONS WEB SERVICE
314
332
EXTERNAL APPLICATIONS
400

Fig. 4



START
502
RECEIVE DATA FROM MULTIPLE ENTITIES AT SERVER
504
ASSOCIATE DATA WITH SPECIFIC DEVICES
506
PROGRAM DEVICES WITH DATA FROM SERVER
508
END
510
500

Fig. 5



602
START
RECEIVE STATUS INDICATOR FROM FIRST MEDICAL DEVICE
604
DETERMINE ACTION AT SERVER FOR SECOND MEDICAL DEVICE
606
PROGRAM SECOND MEDICAL DEVICE
608
END
610
600

Fig. 6



[IF IN ALRAM STATE]
[IF IN THERAPY STATE]
[IF MEDICAL DEVICE IS KNOWN]
[MEDICAL DEVICE CONNECTED]
[IF THE MEDICAL DEVICE IS NOT KNOWN]
[IF IN FAULT STATE]
[IF IN POWERED STATE]
[IF IN KNOWN STATE]
[CLEAR FAULT EVENT]
[ACTIVE FAULT EVENT]
[ACTIVE FAULT EVENT]
[CLEAR FAULT EVENT]
[BEGIN THERAPY EVENT]
[END THERAPY EVENT]
[CLEAR ALARM EVENT]
[ACTIVATE ALARM EVENT]
[ACTIVATE ALARM EVENT]
[CLEAR ALARM EVENT]
[POWER OFF EVENT]
[POWER ON EVENT]
FAULT
THERAPY
Powered
ALARM
KNOWN
NoOp
712
710
708
714
704
716
706
702
FROM ALL STATE EXCEPT KNOWN A MEDICAL DEVICE CAN TRANSITION TO THE NoOp STATE IF THE MEDICAL DEVICE SERVER CANNOT DETERMINE IF THE MEDICAL DEVICE IS ALIVE
700

Fig. 7



804
MEDICAL DEVICE SERVER
802
External Device
806
Device Server Object
808
Message Handlers
810
Data Tier Interface
Message(Soap format)
Response(OK/
WARNING/FAIL)
Message(Soap format)
Response
Processed
Message
Data Tier
Response
800

Fig. 8



902
START
904
ASSOCIATE METADATA WITH DEVICE
906
STORE METADATA ON SERVER
908
END
900

Fig. 9



1002
START
1004
ASSOCIATE METADATA WITH ALL DEVICES
1006
ASSOCIATE METADATA WITH SPECIFIC DEVICES
1008
STORE METADATA ON SERVER
1010
SELECT DEVICE
1012
COMMUNICATE WITH DEVICE USING METADATA
1014
END
1000

Fig. 10





Identity
TypeId string
DeviceId string
SessionId string
NetworkId NetworkId
AccessPoint AccessPoint
Packages Packages
NetworkId
HostName string
Domain string
Ip string
Port string
AccessPoint
Ip string
PhysicalId string
Packages
Package Package
Package
PackageId string
Name string
Version string
1102
1104
1106
1108
1100

Fig. 11




1200

Fig. 12




1300

Fig. 13




1400

Fig. 14



1500

Fig. 15



1600

Fig. 16



START
1702
Start
RECEIVE EVENTS FROM MEDICAL DEVICE(S)
1704
STORE EVENT DATA IN SERVER DATABASE
1706
2
RECEIVE REQUEST FOR SUBSET OF EVENT DATA
1708
GENERATE RESULTS
1710
END
1712
1700

Fig. 17



1802
START
1804
STORE MAINTENANCE SCHEDULE ON SERVER
1806
TRANSMIT MAINTENANCE REMAINDER TO MEDICAL DEVICE
1808
END
1800

Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24



2502
SERVER HEADER
2504
VENDER HEADER
2506
INFORMATION FOR MEDICAL DEVICE
HASH INFORMATION
2508
2500

Fig. 25



2602
START
2604
STORE INFORMATION
2606
RECEIVE MESSAGE FROM MEDICAL DEVICE
2608
INDICATE EXISTENCE OF INFORMATION
2610
RECEIVE REQUEST FOR INFORMATION
2612
DELIVER DATA PACKET
2614
END
2600

Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33



3402
START
3404
MAINTAIN SERVER TIME VALUE
3406
TRANSMIT SERVER TIME VALUE TO MEDICAL DEVICE
3408
REPLACE DEVICE TIME VALUE WITH SERVER TIME VALUE
3410
RECEIVE CONFIRMATION SIGNAL TRANSMITTED FROM MEDICAL DEVICE
3412
END
3400

Fig. 34



3502
START
3504
RECEIVE EVENT LOG DATA
3506
MODIFY EVENT LOG DATA USING TIME ZONE INFORMATION
3508
STORE EVENT LOG DATA
3510
TRACK GLOBAL EVENTS USING UNIFORM TIME ZONE INFORMATION
3512
RECEIVE REQUEST FOR LOCAL EVENT LOG
3514
CONVERT UNIFORM TIME TO LOCAL TIME
3516
END
3500

Fig. 35



«SUBSYSTEM»
ADMINISTRATION
«SUBSYSTEM»
EVENT TRACKING
«SUBSYSTEM»
OPERATIONS
- IMPLEMENTED BY
- IS IMPLEMENTED BY
1
«USES»
3602
ADMINISTRATION WEB SERVICE
+LOGIN (): STRING
+LOGOUT (): VOID
+CHANGE PASSWORD (): VOID
3606
EVENT TRACKING WEB SERVICE
3604
OPERATIONS WEB SERVICE
3600

Fig. 36



«IMPLEMENTATION CLASS»
AUTHENTICATION
+LOGIN ( )
+LOGOUT ( )
3702
«IMPLEMENTATION CLASS»
AUTHORIZATION
+CAN READ RESOURCE ( )
+CAN WRITE RESOURCE ( )
+CAN BREATE RESOURCE ( )
+CAN DELETE RESOURCE ( )
+CAN ACCESS RESOURCE ( )
3704
«IMPLEMENTATION CLASS»
ENTITY SETTINGS
+GET ENTITY SETTINGS ( )
+WRITE ENTITY SETTINGS ( )
3716
«IMPLEMENTATION CLASS»
METADATA
+INSTALL METADATA ( )
+UNINSTALL METADATA ( )
+GET ALL METADATA ( )
+GET METADATA ( )
3714
«IMPLEMENTATION CLASS»
License
+INSTALL LICENSE ( )
+UNINSTALL LICENSE ( )
+GET LICENSE ( )
+GET ALLL ICENSES ( )
3710
«IMPLEMENTATION CLASS»
USER
+CREATE USER ( )
+UPDATE USER ( )
+CHAMGE PASSWORD ( )
+DELETE USER ( )
+GET USER ( )
+GET ALL USER ROLES ( )
+GET ALL USERS ( )
+ADD USER HISTORY ( )
+GET ALL USER HISTORY ( )
+GET USER HISTORY ( )
3706
«IMPLEMENTATION CLASS»
ROLE
+CREATE ROLE ( )
+UPDATE ROLE ( )
+DELETE ROLE ( )
+GET ROLE ( )
+GET ALL ROLES ( )
+GET ALL ROLE MEMBER IDS ( )
+GET ALL ROLE ACCESS RIGHTS ( )
+GET ROLE ACCESS RIGHTS ( )
3708
«IMPLEMENTATION CLASS»
RESOURCE
+ADD RESOURCE ( )
+DELETE RESOURCE ( )
+GET ALL RESOURCES ( )
+GET RESOURCE ( )
3712
«UTILITY»
ROLE ACCESS RIGHTS
+RESOURCE ID : GUID
+READ : BOOL = FALSE
+WRITE : BOOL = FALSE
+CREATE : BOOL = FALSE
+DELETE : BOOL = FALSE
«USES»
3700

Fig. 37

Administration Tracking Event Report

Time Zone: Local
Time Periods [GMT]: All
Codes: All
Applications: All

3802 3804 3806

Date	Time	Code	Application	Message
12/14/2006	06:44:13 PM	AT001	MDS:Mds 01	Connection accepted from 192.168.1.1
12/14/2006	06:46:22 PM	AT001	MDS:Mds 02	Connection accepted from 192.168.1.2
12/14/2006	06:46:31 PM	AT002	MDS:Mds 01	Connection with 192.168.1.1 closed
12/14/2006	06:46:44 PM	AT041	MDS:Mds 02	Response transmission failed , socket closed
12/14/2006	06:46:58 PM	AT002	MDS:Mds 02	Connection with 192.168.1.2 closed

3800

Fig. 38

Security Event Report

Time Zone: Local
Time Periods [GMT]: All
Codes: All
Applications: All

3902 3904 3906

Date	Time	Code	Application	Message
12/14/2006	06:44:13 PM	AT032	Mds01	Connection from unknown medical device type
12/14/2006	06:46:22 PM	AT043	AdminWs	'absmart' failed to login
12/14/2006	06:46:31 PM	AT043	AdminWs	'absmart' failed to login
12/14/2006	06:46:44 PM	AT044	AdminWs	Lock user 'absmart' login attempted
12/14/2006	06:46:58 PM	AT047	AdminWs	'absmart' access an unauthorized resource

Fig. 39

3900



Security Event Trending Report
Time Zone: Local
Time Periods [GMT]: All
Codes: All
Applications: All
Security Event Count
0
1
2
3
4
5
6
7
8
9
Jan
Feb
Mar
Apr
May
Jun
Jul
Aug
Sep
Oct
Nov
Dec
Security Event Trending Report
Page 1 of 10
Time Zone: Local
12/20/2006 01:26 PM

Fig. 40

4000

User History Report

Time Zone: Local
Time Periods [GMT]: All
Codes: All
Users: All

4102 4104 4106 4108 4110

Date	Time	Code	User	Message	Details
12/14/2006	06:44:13 PM	HC001	medusr01	User logged in from 'ws 001'	Session Key: 0kdoewkpi2309 Location: ws001
12/14/2006	06:46:22 PM	HC001	medusr02	User logged in from 'ws 002'	Session Key: Fsjie7834jkdui Location: ws002
12/14/2006	06:46:31 PM	HC101	medusr01	Security role 'biomed' created	Name: biomed State: 'EN'
12/14/2006	06:48:12 PM	HC101	medusr01	Security role 'biomed' modified	New Members: medusr03, medusr04, medusr05
12/14/2006	06:48:40 PM	HC002	medusr01	User logged out	
12/14/2006	08:12:22 PM	HC002	medusr02	User logged out	

4100

Fig. 41



4206
4208
Metadata - Metadata Management
Install
Uninstall
Virtual Infusion Pump
Virtual Patient Monitor
Medfusion 4000
4204
4202
4200

Fig. 42





Search
Metadata
C:\test\Medfusion3600 cmdata
Browse
Install
Cancel
4300

Fig. 43




4400

Fig. 44



4500

Fig. 45


Search
Package Information
PackageDeploymentId c8416b0d-0164-444f-9c00-39a7b36ae54e
StartTime 1/11/2007 10:30:00 AM
EndTime 1/11/2007 11:15:00 AM
TargetTypeId 82bc6390-a340-45c6-93e6-03b04fde1f83
Vendor Properties
Id c8416b0d-0164-444f-9c00-39a7b36ae54e
Name Simple Infusion Pump
Version 0x00010000

4600

Fig. 46

Quarantine Report

Time Zone: Local
Date Range: 12/01/2006 – 12/11/2006
State: All

4702 4704 4706

Date	Time	State	Message
12/01/2006	01:11:11 AM	New	Soap Message error Input string was not in a correct format .Couldn't store <40.0%> in Capacity Column. Expected type is Single.
12/01/2006	02:01:31 AM	New	Unknown medical device metadata .
12/11/2006	07:09:11 PM	Released	Message validation method error
12/11/2006	07:09:11 PM	Reinserted	Soap Message error System .Web.Services.Protocols.SoapException: E10070 at WebServices.Administration.Metadata.GetMetadata(Guid MetadataId, String identity) in D:\Projects\InformaticsSystem\WebServices\WebServices.Administration\Metadata.cs:line 226 at Administration.GetMetadata(Guid metadataId, String identity)

Quarantine Report
Page 1 of 1

Time Zone: Local
12/31/2006 01:26 PM

4700

Fig. 47

Quarantine Detail Report

Timestamp : 1/1/1900 12:00:16 AM

Message Id : 3ab33e37-2e82-4fb4-b09b-094f2c31b576 4802

State : New

Message : Soap Message error Input string was not in a correct format .Couldn't store <40.0%> in Capacity Column. Expected type is Single.

SourceXml :

```
<?xml version="1.0"?>
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/" xmlns:xsi="http://www.w3.org/1999/XMLSchema-instance" xmlns:xsd="http://www.w3.org/1999/XMLSchema">
    <env:Header>
        <mds-hdr:Control xmlns:mds-hdr="mds:xml-schema:soap11-hdr">
            <Id>0</Id>
            <Timestamp>1900-01-01T00:00:05</Timestamp>
            <Response>false</Response>
        </mds-hdr:Control>
        <mds-hdr:Identity xmlns:mds-hdr="mds:xml-schema:soap11-hdr">
            <TypeId>82E9495E-EEC3-424e-81B9-C02204B2CAB5</TypeId>
            <DeviceId>00:11:22:33:44:55</DeviceId>
            <SessionId>
            </SessionId>
            <NetworkId>
                <HostName>
                </HostName>
                <Domain>medical.smgpplc.com.</Domain>
                <Ip>10.3.113.10</Ip>
                <Port>1594 </Port>
            </NetworkId>
            <Packages>
            </Packages>
        </mds-hdr:Identity>
    </env:Header>
    <env:Body>
    </env:Body>
</env:Envelope>
```

4804

Quarantine Report
Page 1 of 1

Time Zone: Local
12/31/2006 01:26 PM

4800

Fig. 48

Package Deployment Report

Time Zone: Local
Packages: All
Medical Device Types: All

Medfusion 4000 – V1.1.0 Firmware Deployment [FD9273A8-17DC-437f-B596-21C75B0AB005]

4902

Name: Head Firmware
Version: V1.1.0

Host Name (4906)	Physical Id (4908)	Notification (4910)	Transfer (4912)	Complete (4914)	
MD001	01-02-03-0A-0B-0C	12/14/2006 01:22:13 PM	12/14/2006 01:22:44 PM	12/14/2006 01:33:18 PM	4904
MD002	01-02-03-0D-0E-0F	12/14/2006 06:44:13 PM	12/14/2006 06:45:26 PM	12/14/2006 08:18:06 PM	4904
MD003	01-02-03-1A-C3-11	-	-	-	4904

Titan – C01 Configuration Deployment [2995D35A-1BF3-438a-A0E4-35E1F99EDAF3]

Name: Main Firmware
Version: V2.0.0

Host Name (4906)	Physical Id (4908)	Notification (4910)	Transfer (4912)	Complete (4914)	
T0132	0C-08-01-01-0F-03	12/14/2006 01:22:13 PM	12/14/2006 01:22:44 PM	12/14/2006 01:33:18 PM	4904
T0023	0C-08-01-06-07-21	12/14/2006 06:44:13 PM		-	4904
ERROR: Package transfer failed , medical device closed connection . (4916)					
T1765	0C-08-01-81-16-02	12/14/2006 06:44:13 PM	12/14/2006 06:45:26 PM	12/14/2006 08:18:06 PM	4904

4900

Fig. 49

Package Deployment Error Report

Time Zone: Local
Packages: All
Medical Device Types: All

5002

Titan – C01 Configuration Deployment [2995D35A-1BF3-438a-A0E4-35E1F99EDAF3]

Name: Main Firmware
Version: V2.0.0

5004 5006 5008 5010

Date	Time	Host Name	Physical Id	Message
12/14/2006	06:44:13 PM	T0023	0C-08-01-06-07-21	Package transfer failed , medical device closed connection .

5000

Fig. 50



Medical Device Maintenance Report
Time Zone : Local
Medical Devices: All
PM Periods: All
5102
Medfusion 4000
5106
5108
5110
5112
5114
5104
Host Name
Physical Id
Version(s)
Package (s)
PM Date
MD001
01-02-03-0A-0B-0C
1.0.1
1.0.0
FD9273A8-17DC-437f-B596-21C75B0AB005
2995D35A-1BF3-438a-A0E4-35E1F99EDAF3
904CC230-E26E-4846-A4E3-89F622CD8DA2
12/14/2007
MD002
01-02-03-0D-0E-0F
1.0.1
1.0.0
FD9273A8-17DC-437f-B596-21C75B0AB005
2995D35A-1BF3-438a-A0E4-35E1F99EDAF3
904CC230-E26E-4846-A4E3-89F622CD8DA2
12/14/2007
5102
Titan
5106
5108
5110
5112
5114
5104
Host Name
Physical Id
Version(s)
Package (s)
PM Date
T0132
0C-08-01-01-0F-03
1.1.0
FD9273A8-17DC-437f-B596-21C75B0AB005
2995D35A-1BF3-438a-A0E4-35E1F99EDAF3
12/14/2007
T0023
0C-08-01-06-07-21
1.1.0
FD9273A8-17DC-437f-B596-21C75B0AB005
2995D35A-1BF3-438a-A0E4-35E1F99EDAF3
12/18/2007
T1765
0C-08-01-81-16-02
1.1.0
FD9273A8-17DC-437f-B596-21C75B0AB005
2995D35A-1BF3-438a-A0E4-35E1F99EDAF3
1/22/2007
Medical Device Maintenance Report
Page 1 of 10
Time Zone : Local
12/20/2006 01:26 PM
5100

Fig. 51

Medical Device Fault Report

Time Zone: Local
Time Periods [GMT]: All
Medical Device Types: All

Medfusion 4000

Date	Time	Host Name	Physical Id	Message
12/14/2006	06:44:13 PM	MD001	0C-08-01-06-07-21	Motor rate error.
12/14/2006	06:44:13 PM	MD002	0C-08-01-06-07-21	Battery not working

Medical Device Fault Report
Page 1 of 1

Time Zone: Local
12/20/2006 01:26 PM


5200

5202 5204 5206 5208

Fig. 52

Medical Device Fault Trending Report

Time Zone: Local
Time Periods [GMT]: All
Medical Device Types: All



5300

Fig. 53



5408
ONCE A THERAPY ORDER ENETERS THE FINAL STATE IT IS KEPT FOR HISTORICAL REFERERENCE BUT CANNOT BE REACTIVATED
5406
CANCELED [CA]
5412
FAILED [FA]
5418
COMPLETE [CO]
[IF ASSISTED SETUP FAILS]
[IF ASSISTED SETUP SUCCEEDS]
5416
STARTED [ST]
[END THERAPY EVENT RECEIVED]
[THERAPY ORDER CANCELED BY USER]
5410
ASSISTED SETUP [AS]
[RECEIVE ASSISTED SETUP TRIGGER]
[BEGIN THERAPY EVENT RECEIVED]
New [NE]
[RECEIVE ASSISTED SETUP TRIGGER]
5414
SETUP [SE]
5404
5402
5400

Fig. 54



5502
«USES»
«IMPLEMENTATION CLASS»
THERAPY ORDER
«USES»
«USES»
+CREATE THERAPY ORDER ( )
+UPDATE THERAPY ORDER ( )
+CANCEL THAERAPY ORDER ( )
+EXECUTE THERAPY ORDER ( )
+GET THERAPY ORDER ( )
+GET ALL THERAPY ORDERS ( )
3604
WEB SERVICES: ADMINISTRATION
5504
«UTILITY»
THERAPY ORDER RULE
-EXPRESSION : STRING
-ACTION : THERAPY ORDER
-ACTION DATA : STRING
5506
«USES»
«ENUMERATION»
THERAPY ORDER ACTION
+ADVISORY
5500

Fig. 55



5602
5604
5606
5608
ORDER MANAGEMENT APPLICATION
OPERATIONS WEB SERVICE
MEDICAL DEVICE SERVER
«METACLASS»
MEDICAL DEVICE
5610
CREATE THERAPY ORDER
5600
RESPONSE (OK FAIL)
5612
OPERATIONS WEB SERVICE VERIFIES THERAPY INFORMATION AND STORE IN DATABASE.
5622
UPDATE/CANCEL THERAPY ORDER
5620
RESPONSE (OK FAIL)
5624
-OPERATIONS WEB SERVER VERIFIES THERAPY INFORMATION AND UPDATES ORDER.
- OR OPERATIONS WEB SERVER CANCELS ORDER.
OPERATIONS WEB SERVICE TAKE AN ORDER INDENTIFIER, LOOKS UP THE ORDER INFORMATION, AND FORWARD ALL ORDER INFORMATION TO THE MEDICAL DEVICE.
ORDER TRIGGER APPLICATION
5642
EXCECUTE THERAPY ORDER
5640
5642
EXCECUTE THERAPY ORDER
5642
EXCECUTE THERAPY ORDER
RESPONSE (OK FAIL)
5644
RESPONSE (OK FAIL)
5644
5644
RESPONSE (OK FAIL)
- OPERATIONS WEB SERVICE UPDATES THE THERAPY ORDER STATE, AS APPROPRIATE.
- EVENT TRACKING WEB SERVICE STORES THE THERAPY EVENT
5662
THERAPY BEGIN EVENT
THERAPY BEGIN EVENT
5662
EVENT TRACKING WEB SERVICE
RESPONSE (OK FAIL)
5664
5662
THERAPY BEGIN EVENT
5660
RESPONSE (OK FAIL)
5664
RESPONSE (OK FAIL)
5664

Fig. 56



5702
START
5704
RECEIVING AN ORIGINAL PARAMETER VALUE FROM A MEDICAL DEVICE
5706
RECIEVING AN UPDATED PARAMETER VALUE FROM A MEDICAL DEVICE
5708
RECEIVING A FINAL PARAMETER VALUE FROM A MEDICAL DEVICE
5710
STORING PARAMETER VALUES
5712
END
5700

Fig. 57

Medical Device History Report

Time Zone: Local
Time Periods [GMT]: All
Medical Devices: All

5802

Medfusion 4000

Date	Time	Class	Trigger	Message	Location	Drugs
5804		5806	5808	5810	5812	5814
⊞ Physical Id: 0C-08-01-06-07-21						
Hostname: MD101						
12/01/2006	06:13:01 PM	Alarm Level of Concern: Major	Warning	Battery Low PVD 3.123 TVD 4.523 PlungerPosition 3.2 Force 5.3 SyringeDiameter 1.23 AnalogSupply 5.01 FailedValue 3.5	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	
12/11/2006	07:09:11 PM	Therapy Change Parameter: Dose Original Value: 5 mg. Value Entered: 10 mg. Final Value: 10 mg.	Override	Infusing UpperHardLimit 100.00 UpperSoftLimit 102.00 LowerSoftLimit 50.00 LowerHardLimit 48.00	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Lycopene Code: LYC Strength: 10 mg.
12/01/2006	06:13:01 PM	Fault Level of Concern: Major	On	Battery not working PVD 3.123 TVD 6 PlungerPosition 3.2 Force 5.3 SyringeDiameter 1.23 AnalogSupply 5.01 FailedValue 3.5	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	
– Physical Id: AC-11-01-45-76-00						
Hostname: MD1034						

5800

Fig. 58

Therapy History Report

Time Zone: Local
Time Periods [GMT]: All
Medical Devices: All

5902

Medfusion 4000

5904 Physical Id: 0C-08-01-06-07-21

Date	Time	5906 Event Class	5908 Event Trigger	5910 Message	5912 Location	5914 Drugs
12/01/2006	01:11:11 AM	Therapy	Begin	Therapy begin .	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Dyrexetrene Code: DYR Strength: 100 mg.
12/01/2006	02:01:31 AM	Therapy	End	Therapy end .	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Dyrexetrene Code: DYR Strength: 100 mg.
12/11/2006	07:09:11 PM	Therapy	Begin	Therapy begin .	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Lycopene Code: LYC Strength: 10 mg.

5900

Fig. 59



Therapy Trending Report
Time Zone: Local
Time Periods [GMT]: All
Medical Devices: All
Therapy Count
0
1
2
3
4
5
6
7
8
9
Jan
Feb
Mar
Apr
May
Jun
Jul
Aug
Sep
Oct
Nov
Dec
Therapy Trending Report
Page 1 of 1
Time Zone: Local
12/20/2006 01:26 PM
6000

Fig. 60

Therapy Change History Report

Time Zone: Local
Time Periods [GMT]: All
Medical Devices: All

6102

Medfusion 4000

6104 Physical Id: 0C-08-01-06-07-21


Date	Time	Event Class (6106)	Event Trigger (6108)	Message (6110)	Location (6112)	Drugs (6114)
12/01/2006	01:11:11 AM	Therapy	Begin	Therapy begin.	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Dyrexetrene Code: DYR Strength: 100 mg.
12/01/2006	02:01:31 AM	Therapy	End	Therapy end.	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Dyrexetrene Code: DYR Strength: 100 mg.
12/11/2006	07:09:11 PM	Therapy	Begin	Therapy begin.	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Lycopene Code: LYC Strength: 10 mg.
12/11/2006	07:09:11 PM	Therapy Change Parameter: Dose Original Value: 5 mg. Value Entered: 10 mg. Final Value: 10 mg.	Override	Infusing	ICU – Intensive Care Unit Patient: P101 MD User: medusr01	Lycopene Code: LYC Strength: 10 mg.

6100

Fig. 61

Therapy Change Trending Report

Time Zone: Local
Time Periods [GMT]: All
Medical Device Types: All
Event Triggers: All



6200

Fig. 62



6302
START
6304
SET EXPECTED FREQUENCY OF DATA
6306
RECEIVE DATA ?
NO
6312
MEDICAL DEVICE IS OFFLINE
YES
6308
UPDATE DATA RECORDS
6310
UPDATE OUTPUT
6314
END
6300

Fig. 63



6402
6406
FAILED [FA]
6408
[IF STREAM STARTUP FAILS]
NEW [NE]
6416
TERMINATED [TE]
6404
[IF STREAM STARTUP SUCCEEDS]
[STREAM TERMINATED BY USER
OR
MEDICAL DEVICE POWER OFF EVENT]
6410
COLLECTING [CO]
[STREAM TERMINATED BY USER
OR
MEDICAL DEVICE POWER OFF EVENT]
[TELEMETRY REPORT MISSED]
[STREAM RESUMED BY USER]
[TELEMETRY REPORT RECEIVED]
[STREAM PAUSED BY USER]
OFFLINE [OL]
6412
PAUSE [PA]
6414
[STREAM TERMINATED BY USER
OR
MEDICAL DEVICE POWER OFF EVENT]
6400

Fig. 64



6502
6504
6506
6508
DASHBOARD
EVENT TRACKING WEB SERVICE
MEDICAL DEVICE SERVER
«METACLASS» MEDICAL DEVICE
6500
STARTUP
6510
START TELEMETRY STREAM
WHILE WAITING FOR MEDICAL DEVICE SERVER RESPONSE, EVENT TRACKING WEB SERVICE INITIALIZES DATABASE FOR TELEMETRY STORAGE.
RESPONSE (OK/FAIL)
6512
IF TELEMETRY STREAM STARTED COMMIT DATABASE CHANGES RETURN OK OTHERWISE ROLLBACK DATABASE CHANGES RETURN FAIL
6520
COLLECTION
-COLLECTION CONTINUES UNTIL THE MEDICAL DEVICE IS POWERED OFF OR THE STREAM IS TERMINATED BY A USER.
-SEQUENCE MAY NOT ALWAYS OCCUR IN THIS ORDER. FOREXAMPLE. MULTIPLE REQUESTS FOR TELEMETRY WINDOW COULD OCCUR BEFORE AN UPDATE IS MADE BY THE MEDICAL DEVICE SERVER
6522
ADD TELEMETRY EVENT
TELEMETRY EVENT
6524
6526
GET TELEMETRY WINDOW
6528
IF THE MEDICAL DEVICE IS POWERED OFF THE EVENT TRACKING WEB SERVICE WILL RESPONSE WITH FAIL INDICATING THE STREAM WAS TERMINATE BY THE MEDICAL DEVICE
6540
TERMINATION
EVENT TRACKING WEB SERVICE TERMINATES TELEMETRY STREAM, RELEASES ASSOCIATED RESOURCES AND CLEANS UP THE DATABASE.
6542
TERMINATE TELEMETRY STREAM
POWER OFF EVENT
6544
6562
TERMINATE TELEMETRY STREAM
TERMINATE TELEMETRY SYSTEM
6560
6564

Fig. 65



6602
≪IMPLEMENTATION CLASS≫
LATEST EVENT
+GET LATEST EVENT ()
+GET ALL LATEST EVENTS ()
≪USES≫
3604
WEB SERVICES: ADMINSITRATION
≪IMPLEMENTATION CLASS≫
TELEMETRY STREAM
6604
≪USES≫
+START TELEMETRY STREAM ()
+TERMINATE TELEMETRY STREAM ()
+PAUSE TELEMETRY STREAM ()
+GET TELEMETRY STREAM ()
+GET ALL TELEMETRY STREAMS ()
6600

Fig. 66



Medical Devices
6702
6704
6706
6708
6710
6712
Search
Hostname
Physical Id
Domain
IP Address
Port
Last Activity
MD0333
AX-06-29-00-12-03
MEDICAL
192.168.1.1
1587
12/11/2006 12:02:03 PM
MD0444
QX-06-29-13-12-BV
MEDICAL
192.168.1.2
1587
12/11/2006 3:11:03 PM
MD0524
SA-11-29-13-12-22
MEDICAL
192.168.1.3
1587
12/11/2006 4:23:11 PM
MD0324
SA-21-29-22-12-80
MEDICAL
192.168.1.11
1587
12/10/2006 6:01:39 PM
MD0988
AA-13-29-22-41-99
MEDICAL
192.168.2.2
1587
12/11/2006 10:11:28 AM
Legend
Alarm Status
Fault Status
Powered Status
Therapy Status
6700
6714
6716
Last Update : 03:44:18 pm
Pause Updates
Show Offline Medical Devices

Fig. 67

MEDICAL DEVICE METADATA

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to U.S. Provisional Patent Application No. 60/964,444, entitled "Patient Treatment Systems Employing Medical Device Informatics", and filed Aug. 10, 2007. That application is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] In general, the present disclosure relates to treatment of patients via systems for use and control of medical devices. More specifically, the present disclosure relates to software for treatment of patients using medical devices.

BACKGROUND

[0003] Patients at hospitals and other care centers require controlled therapy administration and monitoring. Hospitals and care centers use a variety of types and brands of medical devices to assist in monitoring and therapy administration. For example, medical devices used to assist in therapy administration may include medical infusion pumps, pulse oximeters, cardiopulmonary monitors, and other therapy delivery and patient monitoring equipment. The various types and brands of medical devices each generally use differing, proprietary communication standards.

[0004] The proprietary standards employed by the different devices limit interoperability among the devices, making therapy administration difficult. During use of one or more of the medical devices, a caregiver may want to perform a number of actions related to the medical device. For example, a caregiver may wish to set parameters in a medical device based on the observed characteristics of the patient. Or, the caregiver may wish to view data gathered by a monitor. Due to the proprietary standards used by various medical devices, the caregiver may use a number of types of software and hardware to access the information gathered by the medical device needed to treat the patient.

[0005] Coordinating usage of medical devices also can be difficult. A single medical device can be programmed for administering different therapies and in different locations within a hospital. Usage records of multiple medical devices of varying types and in different hospitals may need to be compared. Similarly, the status of a medical device can be difficult to monitor because the devices are often in locations other than where the caregiver is located.

SUMMARY

[0006] Methods and systems of patient treatment are disclosed. The methods and systems include use of medical device informatics to modify and validate therapies and drugs used in those therapies. In the various aspects of the present disclosure, a medical device, such as a medical infusion pump, interfaces with a server to administer treatments to patients.

[0007] In certain aspects, medical device metadata is used to define a medical device within a medical device network. In further aspects, messages are communicated between a medical device and server to define treatments and other operations to the medical device. In still other aspects, operational and historical data is communicated from medical devices to a medical device server to allow remote monitoring of the administration of a therapy to a patient. In further aspects, timing parameters dictate communication and tracking of events between a medical device and a medical device server.

[0008] In a particular aspect, a method of communication between a medical device and a server is disclosed. The method includes associating metadata with one or more medical devices, the metadata corresponding to an attribute of the medical devices. The method also includes storing the metadata on a server, the server configured to communicate with each of the medical devices by using the metadata.

[0009] In a second aspect, a system for communicating with a plurality of medical devices is disclosed. The system includes a plurality of medical devices and a server communicatively connected to the plurality of medical devices. The server includes a memory configured to store metadata describing the medical devices and a programmable circuit operatively connected to the memory. The programmable circuit is configured to execute program instructions to associate metadata with one or more medical devices, the metadata corresponding to at least one attribute of the medical devices. The programmable circuit is also configured to execute program instructions to store the metadata on a server and communicate information including the metadata with at least one of the medical devices.

[0010] In a third aspect, a method of communication between a medical device and a server is disclosed. The method includes associating metadata with each of a plurality of medical devices, the metadata corresponding to at least one attribute common to the medical devices. The method also includes associating second metadata with at least one medical device of the plurality of medical devices, the second metadata corresponding to at least one custom attribute of the medical device. The method further includes storing the metadata on a server, the server configured to communicate with each of the medical devices by using the metadata. The method also includes selecting a medical device and communicating information including the metadata with the medical device.

[0011] In a fourth aspect, a method of communication between a plurality medical devices and a server is disclosed. The method includes generating a message to a medical device server at a medical device, the message including metadata used to identify the medical device. The method further includes receiving a message from the medical device server at the medical device, the message including metadata identifying the medical device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. **1** shows an exemplary medical device network in which aspects of the present disclosure may be implemented;

[0013] FIG. **2** is a block diagram of a medical device useable in aspects of the present disclosure;

[0014] FIG. **3** is a diagram of a software architecture for a medical device network;

[0015] FIG. **4** is a diagram of a second software architecture for a medical device network;

[0016] FIG. **5** is a flowchart of methods and systems for remote management of medical devices controlled by multiple entities;

[0017] FIG. **6** is a flowchart of methods and systems for server based control of medical devices;

[0018] FIG. **7** is a state diagram of possible state for remote control of a medical device;

[0019] FIG. **8** is a functional diagram of a messaging system for use in a medical device network;

[0020] FIG. **9** is a flowchart of methods and systems for communication between a medical device and a medical device server;

[0021] FIG. **10** is a flowchart of further methods and systems for communication between a medical device and a medical device server;

[0022] FIG. **11-16** are data models including metadata useable to facilitate extensible communication systems for medical devices and medical device servers;

[0023] FIG. **17** is a flowchart of methods and systems for filtering medical device events;

[0024] FIG. **18** is a flowchart of methods and systems for managing maintenance of medical devices;

[0025] FIGS. **19-24** are data models including event metadata useable to track events occurring in medical devices;

[0026] FIG. **25** is a diagram of a data packet formatted for transmission from a medical device server to one or more medical devices;

[0027] FIG. **26** is a flowchart of methods and systems for delivery of the data packet of FIG. **25**;

[0028] FIGS. **27-32** are data models including metadata useable to facilitate delivery of data packets to medical devices from a medical device server;

[0029] FIG. **33** is a schematic diagram including metadata useable to synchronize time within a medical device network;

[0030] FIG. **34** is a flowchart of methods and systems for synchronization of medical devices in a medical device network;

[0031] FIG. **35** is a flowchart of methods and systems for time adjustment of event log data;

[0032] FIG. **36** is a block diagram of functional units of a medical device server, according to a possible embodiment of the present disclosure;

[0033] FIG. **37** is a block diagram of medical device server administration systems;

[0034] FIG. **38** is a sample medical device administration event tracking report accessible from a medical device server;

[0035] FIG. **39** is a sample security event tracking report accessible from a medical device server;

[0036] FIG. **40** is a sample security event trending report accessible from a medical device server;

[0037] FIG. **41** is a sample user history report accessible from a medical device server;

[0038] FIG. **42** is a user interface for management of medical device metadata;

[0039] FIG. **43** is a further user interface for installation of medical device metadata;

[0040] FIG. **44** is a user interface for management of data packet distribution in a medical device network;

[0041] FIG. **45** is a further user interface for deployment of data packets to medical devices in a medical device network;

[0042] FIG. **46** is a user interface confirming deployment of a data packet to a medical device;

[0043] FIG. **47** is a sample quarantine report indicating erroneous data transmission from a medical device server to a medical device;

[0044] FIG. **48** is a sample detailed quarantine report, corresponding to the quarantine report of FIG. **47**;

[0045] FIG. **49** is a sample package deployment report displaying deployments of data packets from a medical device server to medical devices;

[0046] FIG. **50** is a sample package deployment error report displaying erroneous deployments of data packets from a medical device server to medical devices;

[0047] FIG. **51** is a sample maintenance report displaying medical device maintenance events;

[0048] FIG. **52** is a sample medical device fault report displaying medical device faults communicated to a medical device server;

[0049] FIG. **53** is a sample medical device fault trending report displaying trends in medical device faults communicated to a medical device server;

[0050] FIG. **54** is a flowchart of methods and systems for communicating parameter changes from a medical device server to a medical device;

[0051] FIG. **55** is a schematic diagram including metadata useable to facilitate therapy-based programming of medical devices from a medical device server;

[0052] FIG. **56** is an exemplary messaging sequence for therapy-based programming of a medical device;

[0053] FIG. **57** is a flowchart of methods and systems for tracking changed medical device parameters communicated to a medical device server;

[0054] FIG. **58** is a sample medical device history report displaying event log data communicated from a medical device to a medical device server;

[0055] FIG. **59** is a sample therapy history report displaying therapy event log data communicated from a medical device to a medical device server;

[0056] FIG. **60** is a sample therapy trending report displaying therapy trends derived from therapy event log data communicated from a medical device to a medical device server;

[0057] FIG. **61** is a sample therapy change history report displaying changes to therapies in therapy event log data communicated from a medical device to a medical device server;

[0058] FIG. **62** is a sample therapy change trending report displaying therapy change trends derived from therapy event log data communicated from a medical device to a medical device server;

[0059] FIG. **63** is a flowchart of systems and methods for determining an on-line status of a medical device;

[0060] FIG. **64** is a flowchart of systems and methods for collecting telemetry data from a medical device;

[0061] FIG. **65** is an exemplary messaging sequence for receiving telemetry data from a medical device; and

[0062] FIG. **66** is schematic diagram including metadata useable to facilitate communication of telemetry data from medical devices to a medical device server.

DETAILED DESCRIPTION

[0063] Various embodiments of the present invention will be described in detail with reference to the drawings, wherein like reference numerals represent like parts and assemblies throughout the several views. Reference to various embodiments does not limit the scope of the invention, which is limited only by the scope of the claims attached hereto. Additionally, any examples set forth in this specification are not intended to be limiting and merely set forth some of the many possible embodiments for the claimed invention.

[0064] The logical operations of the various embodiments of the invention described herein are implemented as: (1) a

sequence of computer implemented steps, operations, or procedures running on a programmable circuit within a computer, (2) a sequence of computer implemented steps, operations, or procedures running on a programmable circuit within a medical device; and/or (3) interconnected machine modules or program engines within the programmable circuits.

[0065] The description set forth herein discusses use and programming of a variety of medical devices and a medical device server in a medical device network. One skilled in the art will realize that a wide variety of medical devices are used in administering a therapy to a user, such as medical infusion pumps, pulse oximeters, cardiopulmonary monitors, and other therapy delivery and patient monitoring equipment. These and additional medical devices may be used in the medical device network of the present disclosure. In various aspects of the present disclosure, the term medical device server refers to a computing system and a message handling and storage service used for coordination of various other components of the system. Additionally, the term "user" in the context of the medical device generally applies to the person who is receiving a therapy. In many other contexts, such as the context of usage of the medical device server, the user could also refer to any other person such as a caregiver that is operating the medical device or a computer with access to information about the medical device.

[0066] Additionally, the medical devices and interconnected computing systems considered in the present disclosure generate and present information and fields in user interfaces and reports, which are also referred to as displays. The user interfaces and reports can include fields, alpha/numeric character strings, times, and dates. The fields, also referred to as cells, prompt users to enter and/or select information. Various types of input and display devices are available on various computing systems and medical devices.

[0067] The various types of medical devices encompassed by the present disclosure execute or utilize operating parameters, which customize or personalize operation of computer implemented steps, machine modules, and programs to meet the requirements of individual medical device users. The operating parameters can be numerical values, text strings, flags, argument names, or any other aspect of medical device programming that the user or a caregiver can set to control operation of the medical device. In certain aspects of the present disclosure, metadata indicates a textual definition of the capabilities of the various operating parameters within the medical device, and to servers and other computing systems interfaced with the medical device.

I. Hardware Environment

[0068] Referring generally to FIGS. **1** and **2**, a generalized hardware environment is described. FIG. **1** shows an exemplary medical device network **100** in which aspects of the present disclosure may be implemented. The medical device network **100** provides a method by which a variety of medical devices and communication systems intercommunicate. The medical device network **100** includes a medical device server **102** interconnected with a variety of types of medical devices. The medical devices can include an active medical device **104**, a passive medical device **106**, and a plurality of exemplary medical devices shown to be medical infusion pumps **108**.

[0069] The active medical device **104** refers to any of a number of medical devices configured to assist in administering a therapy to a patient. Active medical devices include medical infusion pumps for delivery of fluidic therapies, or other therapy-providing equipment. In one embodiment, the active medical device **104** is a medical infusion device, such as the medical infusion pumps **108** shown.

[0070] The passive medical device **106** refers to any of a number of observation devices configured to monitor the status of a patient, rather than to actively assist in administering a therapy to that patient. Examples of passive medical devices include pulse oximeters, cardiopulmonary monitors, or other patient observation systems for measuring vital signs of the patient, such as breathing, heart rate and rhythm, blood oxygen levels, and other health indicators.

[0071] The medical device server **102** communicates with the medical devices, and is one or more generalized or application-specific computing systems. The medical device server **102** is configured to store and retrieve data received from the various medical devices **104**, **106**, **108**. The data received by the medical device server **102** can include event log data, programming data, and various other data transmitted to the server **102** from the medical devices **104**, **106**, **108**.

[0072] Optionally, the medical device network **100** includes additional computing devices, such as workstations **110** and portable computing systems **112**, configured to allow communicative connection to the medical device server **102**. The workstations **110** and portable computing systems **112** are generalized computing systems or thin client computing systems having a communication interface allowing access to the medical device server. The workstations **110** and portable computing systems **112** generally include input devices and displays, so as to allow a user (i.e. a caregiver) access to data about a patient when that user is not in the same location as the patient. The users may access the medical device server **102** via the workstation **110** or portable computing system **112** to retrieve data gathered from a medical device, and may instruct the medical device server **102** to communicate various messages or software packages to one or more of the medical devices.

[0073] The medical device network **100** optionally includes network infrastructure components, such as a switch **114** and a wireless access point **116**. The network infrastructure components are configured to provide the communication infrastructure between the various medical devices **104**, **106**, **108**, the medical device server **102**, and any additional computing systems **110**, **112**. Although the medical device network **100** requires a communicative conduit between the various components included in the network, the specific components included in a given medical device network will vary based upon the particular infrastructure and needs of users of the medical device network. Therefore, the switch **114** and wireless access point **116** are intended as exemplary components for implementation of a communicative interconnection between the various components of the network. Additional types of medical devices, computing systems, or networking components may be used in the network **100** as well.

[0074] FIG. **2** shows an exemplary block diagram of a medical device **200**. The medical device **200** is any of a number of types of active or passive medical devices for therapy administration or monitoring of a patient. In one possible embodiment, the medical device **200** is a medical infusion pump configured to infuse drugs and other fluidic therapies to a patient. Other types of medical devices are possible as well.

[0075] The medical device **200** includes a programmable circuit **202** interfaced to a memory subsystem, including, for example, Random Access Memory (RAM) **204**, a flash memory **206**, and an electrically erasable, programmable memory (EEPROM) **208**. The RAM **204** stores operational parameters of the medical device, as well as any non-critical storage with respect to operational data or instructions. The flash memory **206** stores instruction and/or data memory defining operation of the pump, such as pump programs, pump parameters for use in those pump programs, or other system firmware. The EEPROM **208** stores a set of initial instructions that are used by the medical device **200** and must be preserved in the event of a failure of the device, such as due to a power failure, dead battery, or other unanticipated event. The EEPROM **208** optionally includes firmware or instructions which may be read or copied into the RAM **204** or flash memory **206** for execution, as necessary.

[0076] In various embodiments of the medical device **200**, the various components of the memory subsystem used are dictated by the needs of the medical device. In certain devices, one or more of the memory system components described herein are not present. In such devices, some or all of the data and instructions stored in that device may be stored in another component of the memory subsystem present in the device. RAM may also temporarily provide storage for critical operational data or instructions. Also, alternate embodiments can be provided whereby the contents of the flash memory and the contents of the EEPROM memory previously described may be interchanged, or whereby the contents may be entirely stored in one type of non-volatile memory and none in the other. Finally, other types of non-volatile memory may be used instead, such as ferro-electric memory or others.

[0077] The medical device **200** further includes a battery system **210** configured to provide a direct current source of power to the medical device when the device cannot be plugged in to a wall power outlet or some other AC power source. In one embodiment, the battery system **210** includes a rechargeable lithium-ion smart battery system configured to provide power management and intelligent switching between DC and AC power modes depending on the presence of AC power. In further embodiments, the battery system **210** includes different types of battery systems, such as a rechargeable battery system including a nickel-cadmium battery.

[0078] The medical device **200** includes an input device **212** and an output device **214** interfaced to the programmable circuit **202**. The input device **212** allows a user at the location of the medical device to adjust the activity of the device. The input device **212** can be, for example, a mouse, keyboard, keypad, trackball, touch screen, control buttons, or other user-controllable devices. The output device **214** can be any type of audio, video, or data interface configured to provide information regarding the medical device to users and devices external to the device. In various embodiments, the output device **214** may be a data interface to a second medical device, or may be a connection to an external monitor for display of information to a user regarding the status of the medical device **200**.

[0079] The medical device **200** also includes a display device **216** and an alarm **218**. The display device **216** is a visual device capable of displaying information to a user of the device. In various embodiments of the medical device **200**, the display device **216** can be, for example, a display device, such as an LCD, CRT, or other screen. Additional types of display devices are possible as well. Furthermore, although the medical device is shown as including a display device **216**, in alternate embodiments a display device is not required. The alarm **218** can be configured to provide various types of audio indications to the user of various conditions detected in the user or the device. These conditions include a health condition detected, such as an abnormally low or high heart rate or respiration rate, or a warning related to the device, such as indicating that a supply of a drug is running low, or that maintenance may be required for the device. The alarm optionally triggers based on additional alarm conditions beyond those listed here; the alarms selected generally relate to the type of medical device implemented and conditions experienced by that device.

[0080] A wired communication interface **220** provides a data communication connection from the medical device **200** that interfaces with a medical device server or other generalized computing system. The wired communication interface **220** interfaces to the programmable circuit **202**, and sends and receives data from the medical device **200**. In various embodiments, the wired communication interface **220** can be an Ethernet or other data connection capable of communicating and receiving digital data.

[0081] A wireless communication interface **222** provides an alternative communication interface to the wired communication interface **220**, such that the medical device **200** can maintain data communications with a medical device server or other computing system when a wired communication connection is not available or convenient, based on the location of the medical device. The wireless communication interface **222** interfaces to the programmable circuit **202**, and sends and receives data wirelessly from the medical device. Usage of one or both of the wired or wireless communication interfaces is dependent upon the location of the medical device and the need for communication with a medical device server. In one embodiment, the medical device provides a constant data stream to one or both interfaces such that individuals with access to a medical device server can continuously track the status of the medical device. In further embodiments, the medical device activates and/or communicates using one or both interfaces periodically, or intermittently, so as to update the operational data or other information held by either the medical device or the medical device server.

[0082] The medical device **200** also includes a patient interface **224**. The patient interface **224** controls the mechanical component of the medical device **200** which monitors or delivers a therapy to the user. The patient interface **224** varies among the different types of medical devices based upon the function of the device. In the case where the medical device **200** is a monitor, the patient interface **224** may include a sensor or other physical detection equipment. In the case where the medical device **200** is a medical infusion pump, the patient interface may include a drive mechanism, occlusion sensor, fluid volume sensor, or other drug control or delivery interfaces. Other medical devices, and corresponding patient interfaces, are possible as well. Additional components beyond those shown may also be included in various embodiments of the medical device **200**, depending upon the particular application to which the device is directed.

II. Overall Software Environment

[0083] FIGS. **3-6** show an overall software environment for the medical device network **100** and its components, accord-

ing to various embodiments of the present disclosure. The software environment disclosed herein is discussed in two sections: (1) those aspects which relate to communications between medical devices and a medical device server, found in part III, and (2) aspects encompassing user interaction with the medical device network, such as to view data related to medical device activity, or to administer changes or additions to the medical device network, found in part IV. Both aspects relate generally to coordination of medical devices in a medical device network, of which the primary physical features are described above in FIGS. **1-2**.

[0084] The various software disclosed herein, including the metadata installation software, package deployment software, and server software described in Parts II-IV, below can be packaged in a variety of ways, and organized for a variety of different medical device networks. In a possible embodiment, the various software aspects are included in a software development kit (SDK) including some or all of the various software components described herein. In such an embodiment, the medical devices can include monitors and medical infusion pumps, and the software can include pre-packaged metadata files useable on both the medical devices and medical device server. User-readable documentation regarding the software can be included as well.

[0085] Additionally, the various software disclosed herein and claimed below can be embodied on any of a number of types of computing systems operable within the hardware environment of FIGS. **1-2**. For example, a computing device typically includes at least some form of computer-readable media. Computer readable media can be any available media that can be accessed by the computing system. By way of example, and not limitation, computer-readable media might comprise computer storage media and communication media.

[0086] Computer storage media includes volatile and non-volatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store the desired information and that can be accessed by a computing system.

[0087] Communication media typically embodies computer-readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term "modulated data signal" refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared, and other wireless media. Combinations of any of the above should also be included within the scope of computer-readable media. Computer-readable media may also be referred to as computer program product.

[0088] FIG. **3** shows a software architecture **300** in which aspects of the present disclosure are implemented. The software architecture **300** provides an operating environment in which medical device data can be stored and managed remotely from the medical devices. The software architecture **300** also provides an extensible architecture in which a variety of types of medical devices can operate. The software architecture **300** operates using one or more computing systems in communicative connection to various medical devices, and is configurable to operate across multiple locations and different business entities. The software architecture **300** operates within a medical device network including one or more medical devices and a medical device server. A possible configuration of the medical device network in which the software architecture operates is described above in FIG. **1**.

[0089] In one embodiment, aspects of the software architecture **300** are implemented using the relational and business intelligence components of Microsoft SQL Server 2005, distributed by Microsoft Corporation. In such an embodiment, various modules, such as web interfaces, may be provided using a web service, such as Microsoft Internet Information Services (IIS) platform. In further possible embodiments, aspects of the system are implemented using Microsoft SQL Server 2000, Oracle, or other database management and business intelligence products, in conjunction with various web services, such as an Apache-based or other web server.

[0090] The software architecture **300** includes one or more medical devices **302**, back office components **304**, and client applications **306**. The medical devices **302** monitor or deliver therapies to patients, as directed by a caregiver. The medical devices **302** can be any of a variety of programmable medical devices such as those discussed in conjunction with FIGS. **1-2**, above.

[0091] The back office components **304** include one or more medical device servers **308**, an administration module **310**, an event tracking module **312**, and an operations module **314**. The medical device server **308** manages communication with the various medical devices **302** associated with the back office components **304**, such as by relaying messages between the various modules **310**, **312**, **314** and the medical devices **302**. The medical device server **302** creates messages understandable to the medical devices **302** and the various modules **310**, **312**, **314** such that a variety of types of medical devices can be managed using the modules. Using the messages sent to the medical devices **302**, the medical device server **308** collects historical information from the medical devices, automates various maintenance operations, assists with therapy setup at a user's bedside, and provides medical device monitoring. In a possible embodiment, the medical device server **302** manages a metadata-based messaging system for communicating with a variety of types of medical devices, such as by using XML or some other type of metadata or markup language via SOAP or another messaging protocol.

[0092] In one possible embodiment, the medical device server **308** resides on a computing system which also hosts the additional back office components **304**. In a further embodiment, the medical device server resides on separate computing hardware from the other back office components. In such systems, the medical device server **308** may be placed at a different location from the other back office components, or may be managed by a different entity from the other back office components, as is described in FIGS. **4-5**, below. For simplicity, throughout the description of the software aspects the term medical device server is intended to encompass either the medical device server **308** or the back office components **304** as a whole, depending upon the specific implementation chosen. In certain embodiments, the medical

device server **308** can be placed on one or more physical computing platforms, resulting in the presence of multiple medical device servers.

[0093] The administration module **310** provides an interface to administration data **316**, which the medical device server **308** and client applications **306** can request for various reasons, such as to allow access to event or operational data, described below. The administration data **316** includes user validation information, such as username, password, IP authentication, or other user validation, as well as rights information defining the access rights associated with the user. For example, the administration data **316** may associate a username with a password, and require a user to provide the correct username and password to receive a validation right. The username and password information may in turn be associated with access rights information, which defines the specific categories of data, subsets of medical devices, or types of commands allowed to that user. Additional access rights may be defined in the administration data **316** and managed by the administration module **310** as well.

[0094] The administration data **316** also defines the capabilities of the various medical devices **302** managed within the environment **300**, by defining operational parameters by which the medical device server **308** interfaces with a medical device **302**. For example, a medical device configured to monitor a patient may include a variety of defined parameters relating to monitoring functions, but will not include parameters relating to therapy delivery. In allowing user-definition of a variety of possible medical device capabilities by setting operational parameters within the administration data, the environment **300** provides a user-extensible set of back office components which are configurable with a variety of medical devices having various capabilities, manufactured by different entities, and employed at different locations.

[0095] In a particular embodiment, the administration module **310** generates a web interface accessible to various client application interfaces to remotely validate users or caregivers wishing to access data held within one or more of the back office components **304**. In a further embodiment, the administration module provides an interface allowing remote applications to access the data managed by the back office components **304**.

[0096] The event tracking module **312** provides an interface to the medical device server **308**, and organizes and manages event data **318**. The event data **318** corresponds to the historical data regarding various events occurring in the medical devices **302**, which are collected and routed by the medical device server **308**. The event data **318** correlates a medical device identifier with an event identifier, and additional descriptive information regarding the event occurring in the medical device. Examples of events tracked using the event tracking module **312** include power events, alarm events, maintenance events, telemetry events, therapy events, or therapy change events in the various medical devices. Examples of various events and schema used for tracking such events are discussed below in conjunction with FIGS. **19-24**. In a particular embodiment, the event tracking module **312** generates a web interface accessible by the medical device server **308** to transfer data to a storage location of event data **318**.

[0097] The operations module **314** manages various operational characteristics of the system, such as system operational information, therapy orders, maintenance jobs, and other information used to affect operation of the various medical devices **302** associated with the environment **300**. The operations module **314** also provides a web interface to the medical device server **308** for managing the various types of operations data **320**, and to various external computing systems to allow those systems to view the operations data **320** and transmit commands within the software architecture **300**, such as to the various medical devices **302**.

[0098] An optional data warehouse **322** aggregates and coordinates the various predefined and collected data, including the administration data, the event data, and the operations data, for use by various client applications. In the embodiment shown, a reporting application receives data from the data warehouse **322**, which aggregates various data from the administration data **316**, the event data **318**, and the operations data **320**. The data warehouse **322** provides a convenient static repository useable to generate reports based on one or more of these types of data. Example reports are described in conjunction with the user to server communication systems described in Part IV, below. The data warehouse **322** can be formed using any of a number of relational or On-Line Analytical Processing products, such as SQL Server Analysis Services, Hyperion Essbase, Oracle OLAP, or other data store configured to allow querying or access to various combinations of data. For those embodiments without the optional data warehouse **322**, its functionality as described herein can be provided by the Administration, Event Tracking, Operations databases and their corresponding modules, as described herein.

[0099] The client applications **306** generally access one or more of the data sources **316**, **318**, **320**, **322** to generate user output forms indicating to caregivers or other users current or historical information about the medical devices to which that caregiver or user has access. The client applications **306** accessing the back end components **304** include administration applications **324**, reporting applications **326**, dashboards **328**, maintenance forms **330**, and various additional external applications **332**.

[0100] The administration applications **324** provide user access to the administration data **316** include a variety of administration web forms, to define usage rights for other users attempting to access the back office components **304**, as well as to define the operational parameters of the medical devices **302**. Additional administration web forms may be included as well.

[0101] The reporting applications **326** provide a number of standardized reports based on the administration data **316**, the event data **318**, and the operation data **320**. In an embodiment in which the back office components **304** include a data warehouse **322**, the reports may be based on the information in the data warehouse. Examples of reports built using the various types of data tracked in the back office components **304** include security reports, user histories, software deployment reports, medical device programming reports, maintenance reports, device history reports, therapy reports, and other reports. Additional examples of the reports are described in Part IV, below.

[0102] The dashboards **328** allow a caregiver or user to view the status of a medical device **302**. The dashboards **328** are based on operation data, and interface to the operations module **310**. The dashboards **328** available within the environment **300** correspond to the various medical devices **302** capable of frequently transmitting data to the back office components **304**. The dashboards **328** receive operational data regarding the medical devices, such as the most recent

therapy delivered by the devices. This information is reflected on the dashboard user interface, presented on a display device of a computing system accessible to a caregiver or user. In one possible embodiment, the dashboards **328** replicate the visual interface of the corresponding medical device, but in a web-portal format.

[0103] The maintenance forms **330** display maintenance information to a caregiver or other user of the medical devices **302**. The maintenance forms **330** display tracked maintenance information included in the operations data **320**, such as performed maintenance, scheduled maintenance, suggested maintenance, and maintenance trends. The maintenance forms **330** also allow the user to deploy various updates to the medical devices **302**, such as firmware updates and other software deployments. In a possible embodiment, the operations data **320** includes maintenance schedule information accessible by users via the maintenance forms. In such an embodiment, the maintenance forms **330** display a maintenance schedule to a user, including future maintenance required for various medical devices **302** as well as historical maintenance events tracked in the operations data **320**.

[0104] Various external applications **332** extend the functionality of the software environment **300** by communicating with the operations module **314**. The external applications **332** include any applications useable to extend the functionality of the software environment **300**.

[0105] FIG. **4** displays an alternative software infrastructure **400** to the one shown in FIG. **3**, and may be used in the instance in which the storage of data from the medical devices is managed by an entity other than the facility at which the medical devices operate. For example, the medical devices **302** and medical device server(s) **308** may reside at one or more hospitals or health care facilities **404**, managed by one or more healthcare entities, such as counties or private entities. However, the storage of data from those devices may be managed by a health management organization or other organization **405** contracting to manage the data of the various facilities at an off-site location. That entity can collect information from the medical device server **308** also residing at the facility, which in turn communicates data appropriately to one of the web-based modules **310**, **312**, **314** described above. Such an arrangement allows the hospital to aggregate data from its medical devices at a medical device server, but allows a third party to manage the computing infrastructure and perform the maintenance tasks related to long term storage, administration, access and/or reporting of the data.

[0106] FIG. **5** shows systems and methods for management of a software infrastructure such as the one shown in FIG. **4**, in which a third party handles the data management tasks related to the data collected from medical devices located within and controlled by various healthcare organizations at various locations, or customer sites. Operational flow within the system **500** of FIG. **5** commences at a start operation **500**, which corresponds to initialization of the system **500**, such as by operation of various medical devices connected to a medical device server.

[0107] A data receipt module **504** receives data generated by the medical devices managed by one or more entities, such as hospitals, clinics, or other health management organizations. In one embodiment, the data receipt module **504** corresponds to receipt of various administrative data, event data, or operations data from a medical device server or client applications, as shown in the back office components **304** of FIG. **4**.

[0108] An association module **506** associates the data received in the data receipt module **504** with the medical devices from which the data is received. In one possible embodiment, the association module **506** associates the data with the various locations at which the medical devices reside, or with the various entities controlling the devices, as defined in the administration data **316**. The data association can be a logical or physical relationship between the data, such as can be found in a file, table, or database.

[0109] The association module **506** prepares the data such that when a user from a particular hospital or location seeks information about medical devices, the back office components can provide to that user only information about the medical devices at that same location or within the same entity as the user, depending upon the particular implementation of the association module **506**. For example, a single hospital or ward of a hospital may have a variety of medical devices whose data is collected and managed by a third party. A doctor, nurse, or other caregiver working in that hospital or ward may access information related to the specific medical devices in that ward from a remote server, not controlled by that ward or hospital.

[0110] An optional program module **508** distributes data or instructions from the back office components to a medical device, based on the specific instructions related to that entity or location. For example, a hospital or ward can request a software upgrade to their medical devices, and the back office components will direct the specific software upgrade requested by the hospital to only that entity's devices or devices only of a specific type, excluding other devices associated with or monitored by the back office components.

[0111] In a further example, a workstation at a hospital or other healthcare location can view status information about the medical devices at that location, such as by execution of the data receipt module **504** and the association module **506**, above. In this example, the user of the workstation may optionally choose to reprogram the medical devices, and can do so by issuing a global command to all of the medical devices of a specific type at the location associated with the user. The back office components can transmit to the appropriate medical device server the specific instructions necessary to distribute to the medical devices at that location, without transmitting those instructions to the same medical devices at other locations managed by the back office components.

[0112] Operational flow terminates at an end operation **510**, which corresponds to completion of a communication session with one or more medical devices.

[0113] FIG. **6** shows systems and method executable within the medical device network of FIG. **1**, in which medical device actions are interconnected. The system **600** specifically relates to interconnection of different types of medical devices at a specific location, such as a group of medical devices all associated with a single patient. The system **600** includes a number of rules which execute on the medical device server or other back office components so as to determine any additional advisable therapy or monitoring activity using a second medical device based on observed activity of a patient with a first medical device, as received by the medical device server or back office components.

[0114] Operational flow within the system **600** commences at a start operation **602**, which corresponds to initial monitoring of a patient using a plurality of medical devices connected to a medical device network. The start operation **602**

also optionally corresponds to receipt of at least one event at the medical device server, as logged by a first medical device which is associated with a patient.

[0115] A status receipt module **604** receives a status of a patient from a first medical device used to monitor or administer a therapy to the patient. In one example, the status receipt module **604** can receive a status of a patient from a medical device associated with that patient. The status of the patient may include the heart or breath rate or regularity, an indication by the patient that he is experiencing pain, the blood glucose level of the patient, or the progress of one or more therapies administered to the patient. The status of the patient optionally also includes alarms generated by medical devices monitoring or delivering therapies to the patient.

[0116] A determination module **606** executes one or more rules based on the status of the patient received from the first medical device. The one or more rules define whether any additional action is needed with respect to that patient, such as additional or changed therapies or monitoring of the patient. The determination module **606** associates various rules with specific medical devices capable of executing the changed therapy. Only those rules are executed which correspond to active medical devices currently monitoring or delivering therapies to the patient. In one example of execution of the determination module **606**, there may exist an instance in which a monitor senses or is told that the patient is experiencing pain. In such an instance, one or more rules execute to determine whether a pain management therapy is available to that patient, and, if such a therapy is available, to determine an appropriate therapy to be administered to that patient. For example, if a medical infusion pump is associated with that patient, the determination module **606** concludes that the pump is capable of delivering a pain management therapy and calculates appropriate pump parameters for delivery of the appropriate therapy to the patient.

[0117] A program module **608** generates programming for a target medical device capable of providing the changed or additional therapy or monitoring determined in the determination module **606**. The program module **608** communicates the changes or additions to the therapy to either a workstation accessible to a caregiver of the patient, or to a medical device capable of administering the therapy. In one embodiment, the program module **608** requests that a caregiver approves the suggested therapy determined in the determination module **606**. In a further embodiment, the program module **608** directly programs the medical device capable of delivering the therapy, such that the therapy may be delivered without any additional caregiver approval or intervention.

[0118] Operational flow terminates at an end operation **610**. The end operation **610** corresponds to the medical device server completing communication of the determined therapy to a workstation or medical device.

III. Medical Device to Server Communication

[0119] FIGS. **7-35** describe generally various systems and methods for communication between the medical devices and the medical device server or other back office components, as shown in FIGS. **1-2**. The systems and method described in this section relate to coordination of medical devices in a medical device network, which may span across one or more facilities, organizations, time zones, or other logical entities. These systems can be used during user interaction with the medical device network, described in Part IV, below, in that involvement with the user relates to coordination of medical devices as well as collection and communication of data from the medical devices in the medical device network.

[0120] Referring now to FIGS. **7-8**, communications between a medical device server and a variety of types of medical devices are described. The communication methods used by the medical device server and the medical devices provides an extensible system allowing the medical device server to communicate with a variety of different types of medical devices made by a variety of different medical device manufacturers, each having different communication protocols, capabilities, and other characteristics.

[0121] FIG. **7** shows an exemplary extensible system **700** in which a medical device server associates with a remotely located medical device. The system **700** tracks the states of medical devices associated with a medical device server, and is used to associate new and existing medical devices with the medical device server to provide an extensible medical device network allowing intercommunication of a variety of types and brands of medical devices placed at a variety of different hospitals or locations within a hospital. In the system **700**, every medical device recognized by a medical device server will have an associated state held in a table on the server. Therefore, the system **700** will execute independently on the server for each medical device associated with the server. The system **700** commences at a start node **702** corresponding to connection of the medical device to a medical device network including a medical device server, such as the one shown in FIG. **1**.

[0122] Upon connection of the medical device, the medical device server must determine whether the medical device is of a known type. If the medical device is of an unknown type, operational flow proceeds to a known state **704**, which corresponds to receiving information about the capabilities of the medical device, so that the medical device is able to be added to the medical device network. The known state **704** may result from receiving user input describing the operational capabilities of the medical device, or may include communication or testing between the medical device and medical device server. When the medical device server considers a device to be in a known state corresponding to the known state **704**, the medical server treats the medical device as a recognized device, but that is not powered on or otherwise recognized by the system. If the medical device is of a known type, operational flow proceeds to a determination node **706**, which corresponds to determining the state of the medical device.

[0123] Four operational states define the operation of the medical device from the perspective of the medical device server: a powered state **708**, a therapy state **710**, a fault state **712**, and an alarm state **714**. The powered state **708** corresponds to a medical device which is powered on and experiencing normal operation, but is not currently being used to monitor or deliver a therapy to a patient. The powered state **708** is entered from the known state **704** or the determination node **706** when the medical device transmits an indication to the medical device server that it has been turned on. The powered state is entered from the remaining operational states, i.e. the therapy state **710**, the fault state **712**, and the alarm state **714**, when the medical device server receives an indication that the medical device has cleared the condition causing the server to associate the medical device with one of those states.

[0124] The therapy state **710** corresponds to a medical device communicating to the medical device server that it is currently in operation, delivering a therapy or monitoring a patient. The specific action taken by the medical device will be dictated by the characteristics of that specific medical device; however, the medical device server need only recognize that the medical device is currently in operation. The system **700** can enter the therapy state from any of the other operational states **708**, **712**, **714**, or from the determination node **706**. When the medical device successfully completes the therapy, it communicates that event to the medical device server, which returns the table entry associated with that device to the powered state **708**. If the medical device fails to complete the therapy due to a fault or alarm event, it will communicate that event to the medical device server, which changes the table entry associated with the device to the appropriate operational state.

[0125] The fault state **712** corresponds to an error occurring in the medical device, such as a malfunction in the operation of the device during monitoring or therapy delivery. The fault state **712** can be entered from either the powered state **708** or the therapy state **710**, and can also be entered from the determination node **706**. In a possible embodiment, the fault state **712** can trigger notification of a caregiver having control of the medical device that a fault has occurred. In a further embodiment, when the medical device server receives an indication which generates a fault state entry in the table, the server can determine the fault occurring in the medical device and can correct the error. Upon clearance of the fault state, the medical device transmits an indication to the medical device server that it has returned to its previous operational state, or has entered the powered state **708** if returning from the determination node **706**. The table held by the medical device server tracking the state of the medical device is updated appropriately to reflect the state of the medical device.

[0126] The alarm state **714** corresponds to the medical device server receiving an indication from the medical device of an event occurring in the medical device which requires the attention of a doctor, nurse, or other caregiver. For example, the medical device may be a medical infusion pump which has run out of medicine for delivery. In another example, the medical device is a heart rate monitor, and the event is monitoring and detection of an abnormally low or high heart rate. The alarm state **714** can be entered from either the powered state **708** or the therapy state **710**, and can also be entered from the determination node **706**. Upon clearance of the alarm event, the medical device transmits an indication to the medical device server that it has returned to its previous operational state, and the table is updated appropriately.

[0127] A nonoperative state **716** may be entered from any of the active states, including the powered state **708**, the therapy state **710**, the fault state **712**, or the alarm state **714**. The nonoperative state **716** corresponds to the server being unable to determine if the medical device is active, or what state the medical device is in. The nonoperative state **716** indicates to a user of the medical device server that attention to that medical device may be needed so as to properly associate the medical device to the medical device server.

[0128] In an example of operation of the system **700**, when a medical device is introduced into a medical device network, the medical device server may or may not know how to communicate with it. Assuming it is a known device that is not currently powered, the medical device server will eventually enter the known state **704**. When the medical device is turned on, the medical device will transmit a power on message to the server, which will update the table to indicate that the medical device is in the powered state **708**. The medical device will send to the server a message when the medical device delivers a therapy, and the medical device server will associate that medical device with the therapy state **710**. When the medical device completes delivering that therapy successfully, the medical device will send a message to the server, which will change the table entry of that device from the therapy state **710** to the powered state **708**. If the medical device fails for some reason, it will communicate a fault message to the server, which will associate the medical device with the fault state **712**.

[0129] If the medical device runs out of a drug or detects a dangerous condition of the patient, the device will communicate an alarm message to the server, which will associate the medical device with the alarm state **714**. When the device completes delivering the therapy, it sends a message to the server that delivery of the therapy is complete, and the server associates the medical device with the powered state **708**. A caregiver may then turn off the medical device, and prior to shutting down the device sends a message to the server, which in turn associates the medical device with the known state **704**.

[0130] FIG. **8** displays a diagram of an exemplary communications system **800** incorporating a medical device server and a medical device. The communications system **800** is configured for receipt, processing, and storage of input messages from external devices, such as medical devices. In one embodiment the communications system **800** uses a metadata-based communications protocol, such as the SOAP protocol. In such a system, the medical device server uses message schema files to validate messages received from medical devices.

[0131] The communications system **800** is configured such that messages sent from a medical device **802** are received by a medical device server **804**, which includes a device server object **806**, message handlers **808**, and a data tier **810**. The medical device **802** can be any of a number of medical devices capable of communication with a medical device server. Various embodiments of the medical device are described above in conjunction with FIG. **2**.

[0132] The medical device server **804** can be any of a number of generalized computing systems configured to collect information from medical devices and assist with medical device setup and monitoring. The medical device server **804** contains a device server object **806**, which handles messages sent and received from the medical device server, and parses the messages to determine that they include required information for the medical device server to act on the message. For example, the device server object can parse various metadata tags contained in the message, as well as data associated with that metadata, to verify the message type, source or destination device identification or network identification, and message data. Other components of the message may be determined as well.

[0133] Exemplary message contents describe various features of the device server object **806**, as well as for the various device handlers incorporated into the system. A sample device server object definition can read as follows:

```
<Feature>
<Id>XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX</Id>
<LicenseId>XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX</LicenseId>
<Name>Medical Device Secured Server</Name>
<Provider>MedicalDeviceServer.MedicalDeviceSoapTcpServer,
MedicalDeviceServer.MedicalDeviceSoapTcpServer.MedicalDeviceSoapSecureTcpServer</Provider>
<Description>Receives inbound connection over SSL secured TCP/IP networks.</Description>
<Type>Server</Type>
</Feature>
```

[0134] In this example, the Feature tag defines the object as a feature of the device server object. The Id tag defines the GUID, or statistically unique number used to identify the feature. The LicenseID tag identifies the license containing the features defined. The Name tag provides the name of the feature. The Provider, Description, and Type tags define the various implementation details of the object. Additional implementation details may be included as well.

[0135] One or more message handlers **808** receive the message in its original format from the device server object **806**, and process the message in a manner to convert the message to a format understandable to and stored by the data tier **810** of the medical device server **804**. The various handlers are assigned messages based on the type of message received, with each handler processing a specific type of messages in a given way. In one embodiment, the message handlers include an alarm handler, a fault handler, a maintenance handler, a power handler, a request handler, various telemetry handlers, and various therapy handlers. Additional or fewer handlers are possible, based on the variety of types of messages managed by the medical device server **804**.

[0136] A second exemplary server object definition describes various features of a message handler **808**:

```
< Feature >
<Id>XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX</Id>
<LicenseId>XXXXXXXX-XXXX-XXXX-XXXX-XXXXXXXXXXXX</LicenseId>
<Name>Medical Device Event Handler</Name>
<Provider>Informatics.BackOffice.MedicalDeviceServer</Provider>
<Description>Validates received events and stores them in the Operations database</Description>
<Type>Handler</Type>
</Feature>
```

[0137] The example for the message handler **808** is analogous to that describing the device server object **806**, but defined using a Provider tag indicating that the metadata defines a handler configured to define a feature. The message handler **808** can be associated with the device server object **806** using the following code:

```
<Handler>
...
<FeatureId>XXXXXXXXXXXXX-XXXX-XXXX-
XXXXXXXXXXXX</FeatureId>
<HandlerId>XXXXXXXX-XXXX-XXXX-XXXX-
XXXXXXXXXXXX</HandlerId>
...
</Handler>
```

[0138] By tying a feature **806** to a handler **808**, the medical device server **804** can route specific types of data to the appropriate handler.

[0139] A data tier **810** receives messages from the message handlers **808** for storage, and also responds to requests for data by providing data to the requesting message handler **808** for formation into a SOAP-based message or transmission to the medical device via the device server object **806**.

A. Metadata Programming and Communication

[0140] Referring now to FIGS. **9-16**, a programming schema is disclosed which lists metadata used to define the operational characteristics of a variety of medical devices. The metadata also allows the medical device server to communicate with a wide variety of medical devices, such as medical infusion pumps or other therapy delivery or monitoring equipment. By defining medical devices in the medical device server in terms of their operational characteristics rather than specific proprietary interfaces, the medical device server need not understand the inner workings of each type of medical device. Rather, the server will understand how to communicate with the medical device based on expected operation of that device. In general, the metadata schema disclosed operates using the XML protocol, and a SOAP based messaging system as described above in FIG. **8**. However, other standardized communication methodologies could be used as well.

[0141] FIG. **9** shows systems and methods for communication between a medical device and a medical device server. The system **900** shown is configured to provide extensibility to a variety of types and brands of medical devices, as described above in FIG. **2**. The medical device server can communicate with the medical device by defining a predetermined set of metadata and associated parameters for each medical device. The system **900** instantiates at a start operation **902**, which corresponds to communicatively connecting a medical device to a medical device server. In one embodiment, the communicative connection corresponds to introducing the medical device into a medical device network

including a medical device server, such as the network shown in FIG. **1**. In a further embodiment, the communicative connection corresponds to installation of a corresponding metadata package onto the medical device, using software for installing a metadata communication layer provided in a software development kit or otherwise provided as consistent with the present disclosure.

[0142] An association module **904** associates metadata with various medical devices in a database of a medical device server. The medical devices store corresponding metadata, so that the associated metadata corresponds to the metadata set on the device. The metadata corresponds to at least one attribute or operational characteristic common to the medical devices, and can be used to distinguish among, identify, and communicate with the various medical devices in the medical device network. In various possible embodiments, operational characteristics defined by the metadata include patient information, user or caregiver information, control information, drug information, or location information. Additional operational characteristics can be included as well, such as those described in one or more of the schema of FIGS. **11-16**. The metadata also corresponds to various events occurring in the medical device, such as power events, alarm events, maintenance events, telemetry events, therapy events, therapy change events, or other events. Additional events are described below in FIGS. **17-33**.

[0143] A storage module **906** stores the metadata on a medical device server or back office components. The medical device server is configured to communicate with each of the medical devices by using the metadata and the metadata-based messaging systems described above in conjunction with FIG. **8**. Operational flow proceeds to an end operation **908**, which corresponds to completion of establishing the communication schema between the medical device and medical device server.

[0144] FIG. **10** shows further systems and methods for communication between a medical device and a medical device server. The system **1000** of FIG. **10** stores metadata common to all medical devices in the medical device networks, and also stores information specific to a subset of the medical devices as well, allowing for customized communications between those medical devices and the medical device server. Operational flow of the system **1000** commences at a start operation **1002**, which again corresponds to communicatively connecting a medical device to a medical device server in a medical device network.

[0145] Following the start operation **1002**, operational flow proceeds to a general association module **1004**. The general association module corresponds to the association module **904** of FIG. **9**, in that it associates metadata defining the characteristics of each medical device in the medical device network by defining a predetermined set of metadata and associated parameters for each medical device. A custom metadata module **1006** associates metadata with one or more medical devices, the metadata being specific to that device. Examples of custom metadata include specific power events occurring in a particular type of medical device, specialized communication types supported by those devices, or other operational parameters which are defined for less than all of the devices included in a medical device network. A storage module **1008** generally corresponds to the storage module **906** of FIG. **9**, and stores the general metadata and the custom metadata on the server.

[0146] A device selection module **1010** selects one or more of the medical devices in the medical device network to communicate with, based on the metadata defining that device stored in the medical device server. In one embodiment, the device selection module executes upon receiving a message from the medical device(s). In a further embodiment, the medical device server selects and communicates with one or more medical devices without receiving a previous signaling communication from one of the medical devices.

[0147] A communication module **1012** transmits a message to the selected medical device determined in the device selection module **1010**. The communication module forms a SOAP-based message for transmission to the medical device, including destination information identifying the medical device as well as the data to be transmitted to the medical device. The message includes various information identified by the metadata tags defined in the schema understood by the system **1000**, such as those described in FIGS. **11-16** and **19-24**, below. Operational flow terminates at an end operation **1014**, which corresponds to completion of transmission of the message to the medical device.

[0148] FIGS. **11-16** show various schema including metadata useable to facilitate extensible communication systems for medical devices and medical device servers. The schema are used in the medical device network of FIG. **1** to identify a variety of medical devices to a medical device server, and to allow the medical device server to communicate with the devices. The schema include metadata related to various operational parameters, or attributes, common to all of the medical devices in the network or specialized to one or more of the medical devices. By using the various schema disclosed, a medical device server can identify a medical device, identify the characteristics of the device, and know how to interoperate with the device by (1) knowing the device's capabilities and limits and (2) sharing an extensible communications protocol with other medical devices.

[0149] FIG. **11** shows an identity schema **1100** used to identify various operational characteristics of each of the medical devices communicatively associated with a medical device server. The identity schema **1100** includes a main table **1102** including a variety of global parameters, as well as a network table **1104**, an access table **1106**, and one or more package tables **1108**. The main table **1102** includes metadata associated with a variety of generalized device identification characteristics, including device type, device identifier, session identifier, network identifier, access identifier, and package acceptance. The device type relates to identification of the type of the medical device such as the manufacturer and model of the device, while the device identifier is unique to each device. The session, network, and access identifiers define the connection string to allow the message to be routed correctly to the medical device. The package identifier indicates whether the medical device is configured to receive packages from the medical device server, and can link to tables indicating the current packages enabled on each device.

[0150] The remaining tables, including the network table **1104**, access table **1106**, and package tables **1108** provide additional information related to connection and capabilities of the medical device, and are linked to the main table by the network identifier, access identifier, and package identifier in the main table **1102**. The network table **1104** includes the host, domain, IP address, and port information necessary to

define a connection to the medical device over an Internet connection. The access table **1106** includes an IP address and Physical Id corresponding to the specific networking connection corresponding to the physical device to the IP address. The package tables **1108** describe additional details of the software or firmware package in use by the medical device, such as the name and version of the software package. Additional details regarding package deployment to medical devices are described below in conjunction with FIGS. **25-33**.

[0151] FIG. **12** shows a control table **1200** which includes elements describing the logistics of sending messages and tracking those elements between the medical device and medical device server. The control table **1200** shown includes message identifier, timestamp, and response metadata. The message identifier provides an identification string used to track the message, and corresponds to the identity of the medical device. The timestamp indicates a time at which the message is sent from the medical device server or medical device. The response provides a Boolean indication of whether the message is originating from a medical device or is a response from the server. Additional metadata related to message tracking can be included in the control table as well.

[0152] FIG. **13** shows a patient table **1300** used to track patient information for association with the medical device. The patient table **1300** includes an identifier and a name element. The name element holds metadata related to the patient's name, and the identifier associates to a statistically unique identifier for association with that patient. Other patient-related metadata can be included as well.

[0153] FIG. **14** shows a location table **1400** used to indicate the location of a patient. The location table **1400** includes metadata defining an alias element and a description element. The description element refers to a linguistic description of the location of a patient, such as "Hospital X, Neonatology, Room 1" or some similar entry. The alias element provides a shorthand code used to associate the location with the medical device. Additional metadata describing the location of a patient or medical device can be included in the location table **1400** as well.

[0154] FIG. **15** shows a drug table **1500** used to indicate the drug, if any, associated with the medical device. The drug table **1500** may or may not be populated for each medical device, due to the fact that only some medical devices are capable of delivering drug-based therapies to a patient. The drug table includes metadata related to a drug identifier, a drug name, and a drug concentration. Additional metadata entries can be used to further identify or describe the drug in use by the medical device.

[0155] FIG. **16** shows a user table **1600** corresponding to a doctor, nurse, or other caregiver currently controlling the medical device. The user table **1600** includes metadata related to a user identifier and user name, as well as any additional identifying characteristics of the user necessary for operation of the system.

B. Event Logging and Maintenance

[0156] Now referring to FIGS. **17-24**, systems, methods, and schema are disclosed which are used in the medical device network of FIG. **1** to track event and maintenance information for the various medical devices associated with the medical device server. These event-based schema can be used to track current and historical performance of the medical devices in the medical device network, as well as to maintain the medical devices. The schema described below define both a messaging system and an ordering of event or operational data stored by a medical device server or other back office components of a medical device network. The event logging and maintenance tracking schema define specific events or tasks occurring in the medical device network, as compared to the schema described in part II.A, above, which relate to relatively constant operational characteristics of the medical devices or server.

[0157] FIG. **17** shows methods and systems for receiving event log results from the medical device server or back office components using the various event-based message schema disclosed in FIGS. **19-24**. The system **1700** generally executes on a medical device server or other back office components of a medical device network, and provides event log data stored in one or more databases managed by those components to a caregiver or other user.

[0158] Operational flow in the system **1700** commences at a start operation **1702**, which corresponds to initial operation of the medical device network. Operational flow proceeds to an event receipt module **1704**, which receives event log data from the various medical devices associated with the medical device server. The event log data represents events occurring in the medical devices, and can be any of a number of types of events, such as power events, telemetry events, alarm events, therapy events, maintenance events, or other events such as those defined in the schema of FIGS. **19-24**.

[0159] A sample message body illustrates communication of an event from a medical device to the medical device server, such as is received by the event receipt module **1704**. In the example, the medical device is a medical infusion pump that is sending a power event to the medical device server, indicating that the pump has been turned on:

```
<env:Body><mds:PowerEvent xmlns:mds='mds:xml-schema:soap11'>
<Trigger>on</Trigger>
<Message>Normal Power Up Complete</Message>
<Timestamp>1900-01-01T00:00:08</Timestamp>
<Medfusion4000_Power>
<Source>AC</Source>
<Capacity>90.0%</Capacity>
</Medfusion4000_Power >
</mds:PowerEvent></env:Body>
```

[0160] This message portion identifies that this is the body of the message, and that it uses the SOAP 1.1 messaging protocol. The message transmitted from the pump indicates that power up process has been completed, and includes a timestamp assigned by the pump. The various power parameters correspond to those parameters included in the power event table of FIG. **19**, below, and are associated with specific values by the medical infusion pump. The message is received from the medical infusion pump by the medical device server, and the values are stored in appropriate database tables corresponding to the power event schema.

[0161] Analogous messages are sent from the medical device to the medical device server, and responses are sent from the server back to the medical device, as related to the other types of events tracked in the medical device network, as described herein.

[0162] A storage module **1706** stores the event log data in a database associated with the correct metadata as defined in the message from the medical device to the server. In one embodiment, the storage module **1706** stores event log data in the event data **318** of FIGS. **3-4**.

[0163] A request receipt module **1708** receives a request for a subset of the event log data stored in the medical device server or other back office components. The request received may come from a workstation, portable computing device, or other type of computing system. The request includes one or more narrowing parameters such as a date range, a caregiver name or identifier, a patient name or identifier, a drug name or identifier, a specific device, or other types of information associated with the event log data. In one example, the request receipt module **1708** receives a request for event log data related to delivery of a specific drug by a medical infusion pump.

[0164] A result generation module **1710** generates results based on the specific request received by the request receipt module **1708**, such as by filtering event log data held by the medical device server or back office components based on the narrowing parameters of the request. The result generation module **1710** optionally also transmits the results to the requesting computing system. Using the example described in the request receipt module **1708**, the medical device server generates a query configured to return event log data related to delivery of the identified drug by the identified pump. This query can be formed in SQL or some other database querying language, such that the database management system associated with the medical device server returns the query results.

[0165] Operational flow terminates at an end operation **1712**, corresponding to completion of generation and transmission of results to the requesting computing system.

[0166] FIG. **18** shows systems and methods for communicating preventative maintenance data to a medical device. The system **1800** uses the metadata of FIGS. **11-16**, as well as the additional event metadata of FIG. **19-24**, to track and communicate maintenance tasks to be performed on one or more of the medical devices in a medical device network. The various message transmission principles described in conjunction with FIG. **17** allow the communication to occur.

[0167] The system **1800** commences at a start operation **1802**, which corresponds to initial operation of the medical device network. Operational flow proceeds to a storage module **1804**, which stores a maintenance schedule on the medical device server associated with one or more medical devices. The maintenance schedule is stored in a database of the medical device server or back office components, and includes both a time value for the maintenance reminder events included in the schedule and for the medical device. The maintenance schedule also optionally references maintenance data, such as required operational software updates or various other configuration parameters.

[0168] In one example, the storage module **1804** stores a maintenance schedule that includes indications for suggested recalibration of a series of medical infusion pumps periodically, or for a specific medical infusion pump. In such an example, the storage module **1804** can store a maintenance schedule provided by the user or manufacturer of the medical infusion pump to provide reminders to the user of the pump when the indicated maintenance is scheduled.

[0169] A transmission module **1806** transmits a reminder to the one or more medical devices associated with the maintenance schedule when a maintenance event occurs. The reminder may be a user-readable message displayed on a display associated with the medical infusion pumps, indicating to the caregiver that recalibration is suggested. Or, the reminder may be a trigger of a user-readable message stored on the medical device.

[0170] The transmission module **1806** also optionally transmits maintenance data associated with the maintenance reminder. In one embodiment of the system **1800**, the reminder sent by the transmission module **1806** disables the medical device. In a further embodiment, the reminder allows the medical device to continue operation. In yet another embodiment, the reminder is transmitted a predetermined time prior to performance of the required maintenance of the medical device.

[0171] Continuing the example of the medical infusion pump from the storage module **1804**, above, a maintenance event is transmitted to the medical infusion pumps. The maintenance event indicates to a medical device that maintenance of that device is needed, and includes a reminder message displayed on a display device of the medical infusion pump, such as "Maintenance Required—Please Contact Manufacturer", or some other indication of required maintenance. In certain configurations, the maintenance event allows the medical device to continue operation until a caregiver contacts the manufacturer, who may have specific instructions regarding maintenance and care of the medical device.

[0172] Operational flow terminates at an end operation **1808**, which corresponds to completion of the transmission of a maintenance reminder and any corresponding maintenance data to the medical device.

[0173] FIGS. **19-24** show event-based schema for communications and responses between medical devices and a medical device server. The schema disclosed are useable in the medical device network of FIG. **1** to allow the medical device server and back office components to gather and store event log data, as well as to transmit messages to the medical devices. The medical devices and medical device server of the network transmit messages and event data using the metadata described below to identify the contents of the messages. The medical device server or back office components store the event data in correspondence with the metadata.

[0174] FIG. **19** shows a power event table **1900** and a power event response table **1910**. The tables **1900**, **1910** define metadata used to track various power events in a medical device, such as turning the device on, turning the device off, battery warnings, and other power-related events. The power event table **1900** includes metadata related to a trigger, a message, and a timestamp. The trigger corresponds to a changed event in the medical device, such as turning the device on, off, or updating the powered status of the device. The message describes the specific event that occurred in the medical device, such as a low battery warning, an occurrence of power on event, an occurrence of a power off event, or some other power-related event. The timestamp indicates the time at which the medical device experienced the power event.

[0175] The power event response table **1910** includes metadata defining various possible responses to the power events received by the medical device server. For example, when the medical device server receives a power on event, the server may respond that specific maintenance tasks are required, or that software or firmware is available to be downloaded. The power event response table includes result, message, session, interval, and package metadata. The result metadata relates to the result of the power event, such as a changed state of the medical device, or various other server-recognized results of the received event. The message metadata includes a message to be transmitted to the medical device, such as to describe the contents of the response message, for display on a display

device associated with the medical device. The session metadata includes information related to the communication session between the device and server. The interval metadata includes information related to the expected interval between communications from the medical device to the server, which is related to server detection of the on-line status of the medical device, described in Part IV, below. The package metadata provides an indication to the device as to whether new package information is available for that device, and which may be delivered via the package deployment methods and systems of FIGS. **25-33**. Additional metadata may be included in the response table **1910** and the corresponding response message.

[0176] FIG. **20** shows an alarm event table **2000** and an alarm event response table **2010**. Alarm events relate to activation or clearing of an alarm triggered in a medical device, and the corresponding messages generated by the device and communicated to the medical device server. Activation or clearing of an alarm in the medical device may relate to detection of a patient condition detected by the medical device, or may relate to the The alarm event table **2000** corresponds to the power event table **1900** in that it also includes trigger, message, and timestamp metadata. In the case of the alarm event table **2000**, the trigger metadata relates to an activate, clear, or update alarm message. The message and timestamp metadata are used analogously to the corresponding fields of the power event table **1900**.

[0177] The alarm event response table **2010** corresponds to the power event response table **1910**. Messages generated using the alarm event response table metadata are communicated to the medical device in response to receipt of an alarm event message. The alarm event response table **2010** therefore generally includes a different response than the power event response table **1910**, and communicates messages, packages or other instructions related to the alarm event.

[0178] FIG. **21** shows a maintenance event table **2100** and a maintenance event response table **2110**. Maintenance events correspond to specific reactions of the medical device to an indication that maintenance is required, such as requesting updated operational software, calibration software, or notification messages indicating the maintenance that is required. The maintenance event table **2100** corresponds to data received in a message from a medical device ready to perform maintenance in conjunction with the medical device server, for situations in which maintenance requires a software upgrade or some other remotely-controllable maintenance event. The maintenance event table **2100** corresponds to the power event table **1900** in that it also includes trigger, message, and timestamp metadata. In the case of the maintenance event table **2100**, the trigger metadata relates to an update or a package applied. The message and timestamp metadata are used analogously to the corresponding fields of the power event table **1900**.

[0179] The maintenance event response table **2110** also corresponds to the power event response table **1910**, and is generated by the medical device server or other back office components. Messages generated using the maintenance event response table metadata are communicated to the medical device in response to receipt of a maintenance event message, and relate to messages, packages or other instructions that occur response to the maintenance event, such as additional details regarding the maintenance required, maintenance schedule information, information to be displayed by the medical device about the maintenance required.

[0180] FIG. **22** shows a telemetry event table **2200** and a telemetry event response table **2210**. Telemetry refers to near-continuous streaming of event data from a medical device to the medical device server such that users with access to the medical device server can monitor operation of the medical device remotely in a near real-time fashion. The telemetry event table **2200** corresponds to the power event table **1900** in that it also includes trigger, message, and timestamp metadata. In the case of the telemetry event table **2200**, the trigger metadata relates to an update event regarding telemetry received from the medical device. The message and timestamp metadata are used analogously to the corresponding fields of the power event table **1900**.

[0181] The telemetry event response table **2210** also corresponds to the power event response table **1910**, but is generated by the server. Messages generated using the telemetry event response table metadata are communicated to the medical device in response to receipt of a telemetry event message, and communicate messages, packages or other instructions in response to the telemetry event.

[0182] FIG. **23** shows a therapy event table **2300** and a therapy event response table **2310**. Therapy events relate generally to the start and stop of therapies or monitoring processes in a medical device. The specific therapy started or stopped depends upon the type of medical device used, and can include monitoring, drug delivery, or other therapies. The therapy event table **2300** corresponds to the power event table **1900** in that it also includes trigger, message, and timestamp metadata. In the case of the therapy event table **2300**, the trigger metadata relates to a setup, begin, end or update therapy event as related to initialization or ending of a therapy by a medical device. The message and timestamp metadata are used analogously to the corresponding fields of the power event table **1900**.

[0183] The therapy event response table **2310** also corresponds to the power event response table **1910**, but is generated by the server. Messages generated using the therapy event response table metadata are communicated to the medical device in response to receipt of a therapy event message, and communicate messages, packages or other instructions in response to the therapy event.

[0184] FIG. **24** shows a therapy change event table **2400** and a therapy change event response table **2410**. Therapy change events relate generally to changes in therapies operating on a medical device, and are related to therapy events, discussed above. Therapy change events include, for example, changed parameters related to monitoring or delivering of therapies, such as changed drug delivery rates. The therapy change event table **2400** corresponds to the power event table **1900** in that it also includes trigger, message, and timestamp metadata. In the therapy change event table **2400**, the trigger metadata relates to an override, warning, abandon, or update event as related to a therapy change. The message and timestamp metadata are used analogously to the corresponding fields of the power event table **1900**.

[0185] The therapy change event response table **2410** also corresponds to the power event response table **1910**, but is generated by the server. Messages generated using the therapy change event response table metadata are communicated to the medical device in response to receipt of a therapy event message, and communicate messages, packages or other instructions in response to the therapy change event.

C. Package Deployment

[0186] Referring back to FIG. **11**, various systems and methods exist for deploying packages to medical devices

from a medical device server. The packages deployed may include firmware upgrades, maintenance information, new or changed parameters for therapies, or other software upgrades or changes to the medical devices in a medical device network. In a possible embodiment, a package can be used to reprogram the medical device to which it is sent with any of the possible types of package data. Medical devices capable of receiving package data indicate this capability in the main table **1102** and package tables **1108**. The main table **1102** indicates the capability of the device to receive a package, and the package tables **1108** include information related to the current package information stored at the medical device for use in operation of the medical device. Package delivery, as discussed in greater detail below, occurs in response to a message, and is initiated using the package data identifier in the event response tables **1910-2410** to indicate to the medical device that a package is available for delivery.

[0187] Referring now to FIG. **25**, an example structure of a package **2500** used in deployment of information to a medical device is shown. The package **2500** includes a server header **2502**, a vendor header **2504**, and information **2506** to be delivered to the medical device. The server header **2502** is the portion of the package understood by the medical device server. The server header **2502** is in a common format to all packages, and contains identification information related to the type of device configured to receive the package, as well as the source of the package. Additional information, such as package size, encryption format, or encryption key location information may be included in the server header **2502** as well. In one embodiment, the server header **2502** is a 256 byte block incorporated into the package.

[0188] The vendor header **2504** contains vendor specific information related to use of the package within the medical device receiving the package. The vendor providing the package to the medical device server is generally the manufacturer or maintenance company associated with the medical device intended to receive the package, so the vendor will format the vendor header **2504** in a manner understandable to the medical devices it manufactures. The vendor header generally includes information related to the size of the information **2506**, as well as the location of encryption information **2508** within the information. The encryption information **2508** can be used by the medical device to decrypt the information, which is generally stored in the medical device server in an encrypted form.

[0189] The information **2506** generally includes any software to be transferred from the medical device server to a medical device, such as a firmware upgrade, a file including therapy parameters, or other binary data. The package delivery system **2500** is not dependent upon the specific format of the vendor header **2504** or the information **2506**. The information **2506** is generally stored in an encrypted form on the medical device server. When transferred to a medical device, the information **2506** is decrypted by the medical device by locating the encryption information **2508** based on information in the vendor header **2504**.

[0190] FIG. **26** shows systems and methods for deploying package data from a medical device server to medical devices. The system **2600** is configured to distribute a package, such as the package **2500** of FIG. **5**, to a medical device in response to a message received from the medical device.

[0191] Operational flow within the system **2600** commences at a start module **2600**, which corresponds to receipt of package information from a vendor of a medical device, an administrator of the medical device, or another entity having familiarity with the operation of the medical device. A storage module **2604** stores the received package in the medical device server. The storage module **2604** can also set an alert or other variable for a medical device such that the next time the medical device communicates with the server, an indication of the existence of the package is included in the response to the medical device. In one embodiment, the storage module **2604** encrypts the package while stored on the medical device server or back office components, and either the medical device server or the medical device itself decrypts the message when the package is to be used or transmitted. In a further embodiment, the storage module **2604** leaves the package unencrypted when it is stored on the medical device server or back office components.

[0192] A message receipt module **2606** receives at the medical device server a message from a medical device. The message may be any of a number of types of messages, such as the power, maintenance, alarm, telemetry, therapy, or therapy change event messages described above in FIGS. **19-24**. Additional message types are possible as well.

[0193] An indication module **2608** indicates to the medical device that a package is intended for delivery to that device. In one embodiment, the indication module **2608** sets a parameter in a message response indicating the existence of a package. For example, the indication module **2608** can set a parameter in the package metadata included in the event response messages **1910-2410** of FIGS. **19-24**. Additional methods of indicating the existence of a package are possible as well, such as transmission of a specific message related to package deployment, a package request by the medical device, or other methods.

[0194] A request module **2610** receives a request from the medical device to receive the package. The request module **2610** may include one or more steps of requesting information about the package to verify at the medical device that the package should be accepted. In a possible embodiment, the request module **2610** transmits a package information request message, using metadata as shown in FIG. **27**. In such an embodiment, the request module **2610** optionally also transmits a package data request message separate from the package information request message, the package data request message transmitted following receipt of package information describing the package contents from the medical device server. In further embodiments, the request module **2610** receives a request as shown in FIG. **29** or **31**.

[0195] A delivery module **2612** delivers the requested package to the medical device. The format of the package delivery message can be as shown in FIG. **30** or **32**. Operational flow terminates at an end operation **2614**, which corresponds to completion of the package transmission to the medical device.

[0196] FIGS. **27-32** show schema including metadata used in messages and tables in a medical device network, such as the one shown in FIG. **1**, to deploy packages from a medical device server to a medical device. The schema display various request and response scenarios in which a medical device requests delivery of package information and receives the requested information in response. One or more messages may be sent between the medical device and the medical device server prior to delivery of the package and its enclosed data.

[0197] FIG. **27** shows a package information request table **2700** including metadata used to request information about a

package that is available to be deployed to a medical device. The medical device is notified of an available package based on a previous response from the medical device server, as reflecting information in the main table **1102** or package tables **1108** related to that device in the medical device server. The metadata in the table **2700** includes a package identifier, which is used by a medical device to identify the package and request information about its contents. Additional metadata related to the package may be included in the table **2700** and message from the medical device as well.

[0198] FIG. **28** shows a package information request response table **2800** including metadata used in describing a package available to be deployed to a medical device. The metadata in the table **2800** includes the package identifier, corresponding to the package identifier in the package information request table **2700**, and also includes package information metadata. The package information metadata links to a package information table **2802**, which contains name and version metadata. Values associated with the name and version metadata describe the package, such that the medical device can determine whether to request deployment of the package.

[0199] FIG. **29** shows a package data request table **2900** including metadata used in requesting package data from a medical device server. The package data request table **2900** includes package identifier and response type metadata. The package identifier represents a unique identifier for the package available for deployment to the medical device. The response type represents an identifier indicating the desired delivery format of the package data. In one embodiment, the package data can be delivered to the medical device in either a plain text format or using an xop format.

[0200] FIG. **30** shows a package data request response table **3000** including metadata used in deploying a package to a medical device. The metadata included in the package data request response table **3000** includes a package identifier and a package binary data field. The package identifier identifies the package referred to in FIG. **29**, and the package binary data field denotes the binary data representing the package being delivered to the medical device. The package binary data field can optionally link to a separate package binary data table **3002** containing the package binary data for delivery to a medical device. In one embodiment, the package delivered to the medical device is the package **2500** of FIG. **25**.

[0201] FIG. **31** shows a package request table **3100**. The package request table **3100** corresponds to the package data request table **2900** of FIG. **29** combined with the package information request table **2700** of FIG. **27**. The package request table **3100** can be used by the medical device in an instance in which the medical device does not need to validate the package information prior to downloading the package. The package request table **3100** includes a package identifier and a response type, similar to the package data request table **2900**, but indicates by requesting the entire package that package information and package data messages need not be separated.

[0202] FIG. **32** shows a package request response table **3200**, representing the schema of a message from the medical device server sent in response to a message of the form reflected by the package request table **3100** of FIG. **31**. The package request response table includes package identifier, package information, and package binary metadata. The package information metadata links to a package information table **3202** containing name and version metadata associated to the package data. The package binary metadata links to a package binary table **3204**, which includes metadata corresponding to the package to be deployed to the medical device.

D. Time Management

[0203] Referring now to FIGS. **33-35**, systems and methods for time management in a medical device network are shown. Because the medical device network can vary in size or configuration, the time management systems described are configured to extend across various business entities, various locations, and various time zones. The systems and methods described provide a uniform way to synchronize time tracking in medical devices and a medical device server located in one or more locations or time zones.

[0204] FIG. **33** shows a time messaging schema **3300** useable to track medical device time at the medical device server, and also transmit time synchronization messages between a medical device and a medical device server. The time schema **3300** includes a time request table **3302**, a time request response table **3304**, and a system time table **3306**. The time request table **3302** optionally includes no metadata, but represents a time request response sent from a medical device to the medical device server for synchronization of the medical device time with the time stored in the server or back office components. The time request response table **3304** includes system time metadata, associated with the system time value stored on the medical device server. The system time metadata optionally links to a system time table **3306**, which contains a time value useable to synchronize the time of the medical device with the time received from the medical device server. Additional metadata or other information useable to assist in time synchronization can be used as well.

[0205] FIG. **34** shows methods and systems for time synchronization of medical devices and a medical device server within a medical device network. Operational flow in the system **3400** commences at a start operation **3402**, corresponding to initial operation of the medical device network. A server time maintenance module **3404** maintains a global time value in the server that is to be used to synchronize the time values of the medical devices communicatively connected thereto.

[0206] A server time transmission module **3406** transmits the server time to one or more medical devices in the medical device network. In one embodiment, the server time transmission module **3406** transmits the server time value to a medical device in response to a request message from that medical device. In such an embodiment, the request message may be of a form shown in the time request table **3302** of FIG. **33**, above.

[0207] In a further embodiment, the transmission module **3406** converts the server time value to a localized server time value based on the time zone of the location of the medical device. This conversion may take place if the server resides in a different time zone from the medical device. The server and medical device thereby have a synchronized time value that is converted to the appropriate time zone. One possible implementation of this embodiment converts all times to the Universal Time Protocol upon transmission from the server, and the destination medical device reconverts the time value to the local time of that destination device's location. Other time zone conversions, such as from the local time of the medical device server to the local time of the medical device, are possible as well.

[0208] A replacement module **3408** replaces the device time in the medical device with the server time value received from the medical device server. The replacement module **3408** uses the time-adjusted server time value, configured to be used at the location of the medical device. An optional confirmation module **3410** sends a confirmation message to the medical device server indicating that the medical device is successfully synchronized to the server, allowing the server to track which medical devices have been successfully synchronized with the server. Operational flow terminates at an end operation **3412**, corresponding to completion of the time synchronization process.

[0209] Referring now to FIG. **35**, methods and systems for synchronizing event log data are disclosed. The system **3500** accommodates event log data received from medical devices located in different locations in a plurality of time zones. The event log data is configured such that the local time stamp of the event log data represents the time zone in which that device resides, so event logs from different time zones having the same time stamp in actuality occurred at different times. The system **3500** compensates for this discrepancy when storing event log data, and also when providing it to users for review. Operational flow within the system **3500** commences at a start operation **3502**, corresponding to initial communication of event data from medical devices to the medical device server.

[0210] A receipt module **3504** corresponds to the medical device server receiving event log data from one or more of the medical devices. As described above, the event log data includes various details regarding various types of events, such as therapy events, alarm events, maintenance events, telemetry events, or other types of events, each of which are associated with a time stamp reflecting the current time value of the medical device, reflecting the local time zone of that device. A time zone modification module **3506** converts the time stamp information from the local time zone of the medical device to a constant time zone. In one embodiment, the time zone modification module **3506** converts the time stamp to the Universal Time Protocol (UTP). A storage module **3508** stores the converted time stamp and associated event log data in the medical device server or back office components.

[0211] An optional global tracking module **3510** tracks global events using the uniform time zone information. For example, a user desiring to track events that occur at single instantaneous moment across all time zones can track global events using the Universal Time Protocol to maintain a standard time across all time zones. The user sends a request for event log data related to the global events stored on the server, and receives event log information with a time stamp having constant time zone information.

[0212] A request local event module **3512** receives a request for local event data, including types of event data associated with the time zone in which the event occurs. Examples of time zone specific events can include events timed to occur at the beginning or end of a shift at a hospital, or other local events. The request local event module **3512** generates a query for the event data requested, and returns results including event log data. A conversion module **3514** converts the uniform time zone information to local time zone information based on the location of the medical device from which the event log data was recorded. The conversion module **3514** optionally generates a report from the event log data for distributing to a requesting user, including the compensated local time event log. Operational flow within the system **3500** is terminated at an end operation **3516**, which corresponds to completion of the conversion module **3514**.

IV. Remote User to Server Communication

[0213] Referring now to FIGS. **36-66**, a generalized web service architecture is disclosed which manages user access to a medical device server in a medical device network, such as the one shown in FIG. **1**. The web service architecture allows remote user to server communication, to provide data access and programming capabilities related to medical devices in the medical device network of FIG. **1**. For example, users can perform administrative tasks, administer software updates to medical devices, access event and operational records, perform maintenance, change therapies, and view near real-time operation of the medical devices while remotely located from the devices. These functions, and others, are described below.

[0214] FIG. **36** shows an overall web service architecture **3600**, shown as a subsystem of the possible software architectures of the medical device network in FIGS. **3-4**. The web service architecture includes various web modules or services configured to validate users and provide access to data stored on the medical device server. In a possible embodiment, the web service architecture is implemented in a .NET architecture using Internet Information Server, by Microsoft Corporation.

[0215] The web service architecture **3600** includes an administrative web service **3602**, an operations web service **3604**, and an event tracking web service **3606**. The administrative web service **3602** validates users of the medical device server, and includes functional interfaces for logging in, logging out, and changing a user password. The administrative web service **3602** tracks information related to products, customers, contact information, medical devices associated with the customers, user accounts associated with a customer, and other variables. The administrative web service **3602** uses this tracked information to validate specific users, each of whom is associated with a specific health care facility, referred to in the administrative web service as a customer. A specific implementation class of the administrative web service **3602** is described in Part IV.A, below.

[0216] The operations web service **3604** provides access to operational data of the medical devices, such as operational data regarding therapy delivery or monitoring data. The operations web service **3604** tracks the various therapy states occurring in a medical device, and enables a messaging sequence that can occur to trigger or track a therapy event in a medical device. A specific implementation of the operations web service **3604** is described in Part IV.B, below.

[0217] The event tracking web service **3606** tracks various event data occurring in a medical device, such as telemetry data received by a medical device server. The event tracking web service **3606** enables users to view near-real time activity of a medical device while located remote from the medical device, and allows the user to determine the on-line status of the medical device. A specific implementation of the event tracking web service **3606** is described in Part IV.C, below.

A. Administration

[0218] Referring now to FIGS. **37-41**, systems and reports for definition and use of an administrative web service are shown. FIG. **37** shows an exemplary class structure defining an administrative web service **3700**. The administrative web

service **3700** provides a possible embodiment of the administrative web service **3602** of FIG. **36**, and is accessible via any of a number of user interfaces, such as the administration web forms **324** of FIG. **3**. The administrative web service **3700** includes an authentication class **3702**, an authorization class **3704**, a user class **3706**, a role class **3708**, a license class **3710**, a resource class **3712**, a metadata class **3714**, and an entity settings class **3716**. Each of the classes includes a number of functions remotely accessible via the internet and web-based user interfaces to perform administrative tasks. Functionality of the various classes is described below.

[0219] The authentication class **3702** provides the initial access to the administrative web service **3700**, and includes login and logout functionality. The authorization class **3704** includes a variety of resource control functions to ensure that two users are not reading from and writing to the same data concurrently, or otherwise causing data conflicts. The resource control functions incorporated into the authorization class **3704** include read, write, create, delete, and access permission functions. Other functions may be incorporated into the authorization class **3704** as well.

[0220] Each of the other classes link to the authorization class **3704**, and each requests read or write access to the data protected by the authorization class **3704**. The user class **3706** allows the system to perform various user administration tasks, such as creating new users, editing user information, changing passwords, deleting users, defining user roles, and retrieving user histories. Other functions are possible as well. The role class **3708** defines roles assignable to users, and includes the ability to create, update, delete or retrieve various roles defined in the administration data. Roles may correspond to various classes of individuals who can access data managed by the medical device server and back office components, such as doctors, nurses, or healthcare administrators. Roles may also correspond to the various entities with which the individuals are associated.

[0221] The license class **3710** defines licenses installed into the system to control the number of users able to log in at once, as well as to define usage models for various accounts. For example, a particular account may allow only a limited number of individuals to view telemetry data or to access therapy records at once, or may define a way of charging a customer for tracked usage of the medical device server or other back office components.

[0222] The resource class **3712** allows an administrator to add and delete resources, which correspond to the specific functional areas of the medical device server. The metadata class **3714** provides the underlying functionality for installing metadata into either the administration system, such as custom metadata corresponding to a newly introduced medical device, or into a newly introduced medical device itself. Exemplary interfaces for installation of metadata are shown below in FIGS. **42-43**. The entity settings class **3716** allows writing and retrieval of entity settings. Additional administrative functionality, including additional classes, may be incorporated into the administrative web service **3700** as well.

[0223] FIGS. **38-41** display sample administrative reports accessible to a user. The administrative reports of FIGS. **38-41** correspond to the reports **326** shown in FIGS. **3-4**, and are derived from information stored in the data warehouse **322** related to administrative events logged by the medical device server. In a possible embodiment of the present disclosure, the various reports are generated using SQL Server Reporting Services, by Microsoft Corporation. Other reporting and business intelligence software may be used as well.

[0224] FIG. **38** displays an administration tracking event report **3800**. The administration tracking event report displays detailed information regarding administration events, such as user access and connection to the medical device server. The number and contents of entries in the report correspond to data from the administration data **316** of FIG. **3** that match the query presented to the administrative web service. The administration tracking event report includes time and date information **3802**, application information **3804**, and message information **3806**. Additional information, such as the code information, time zone indicator, and other information can be optionally included in the report **3800**.

[0225] The time and date information **3802** display the time stamp information related to the event tracked by the administrative module. The time and date information **3802** display on the report in varying formats, depending upon whether a user chooses a local time zone option or a GMT normalized time option. In the report **3800** shown, the local time zone option is selected.

[0226] The application information **3804** indicates the service or handler accessed, and the message **3806** indicates the action taken with respect to that service or handler. In the example shown, exemplary connection events are shown for two medical device servers, labeled "MDS:Mds01" and "MDS:Mds02".

[0227] FIG. **39** displays a security event report **3900**. The security event report **3900** corresponds generally to the administration tracking event report **3800**, but includes events related to security of the medical device server rather than access to it. The security event report **3900** includes time and date information **3902**, application information **3904**, and message information **3906**, each of which have the same functionality as in the administration tracking event report **3800**.

[0228] FIG. **40** displays a security event trending report **4000**. The security event trending report **4000** displays a chart of security related events over time. In the embodiment shown, the security event trending report **4000** displays a bar chart showing the frequency of security events by month. Other configurations displaying trends in security events are possible as well.

[0229] FIG. **41** displays a user history report **4100**. The user history report displays a chronologically ordered list of events logged regarding one or more users. Each entry in the list includes time and date information **4102**, a sorting code **4104**, a username **4106** corresponding to the active user, and a message **4108** related to the action taken by that user. An optional details entry **4110** displays additional information associated with the history information, in raw form, such as the session key, location, name, location, or other activities occurring in the user history.

[0230] 1. Metadata and Package Deployment Interfaces

[0231] Referring now to FIGS. **42-50**, various methods of programming the medical device server and medical device with metadata, firmware, or other binary data are shown. FIGS. **42-46** display administrative forms useable to perform various administrative tasks in the medical device server, such as providing or removing metadata or packages, intended for configuration of the medical device server or medical devices, respectively. The administrative forms can correspond to forms generated by the administrative applica-

tions **324** of FIGS. **3-4**. FIGS. **47-50** display reports displaying the results of installation of the metadata and packages, and are a subset of the reports **326** available from the data warehouse **322** in FIGS. **3-4**.

[0232] FIGS. **42-43** display user interfaces configured to allow an administrative user to manage metadata installed into the medical device server, as described above in Parts III.A and III.B. FIG. **42** shows an initial user interface **4200** showing the metadata packages either currently installed into the medical device server or available to be installed. A listing area **4202** lists the packages, in this case displayed as "Virtual Infusion Pump", "Virtual Patient Monitor", and "Medfusion 4000". Check boxes **4204** in the listing area allow user selection of one or more of the installed packages, an install button **4206** installs the packages into the medical device server, and an uninstall button **4208** removes metadata packages from the medical device server.

[0233] FIG. **43** displays a metadata installation interface **4300** configured to allow a user to browse for a metadata file and install that file onto the medical device server. The metadata installation interface **4300** appears following selection of one of the types of medical devices present in the system in the user interface **4200**, and allows the user to select and install a metadata file associated with the previous selection of metadata using the initial user interface **4200**.

[0234] FIG. **44** displays a package deployment interface **4400** providing deployment of packages for distribution to one or more medical devices, as described above in Part III.C. The package deployment interface **4400** generally corresponds to the metadata installation interface **4200** of FIG. **42**, but relates to software to be installed onto a medical device, rather than into the medical device server. A listing area **4402** lists the packages, in this case displayed as "Simple Infusion Pump" or "TestPackage". Check boxes **4404** in the listing area allow user selection of one or more of the installed packages, a deploy button **4406** deploys the packages into the medical device server, and an uninstall button **4408** removes the packages from the medical device server.

[0235] Upon selection of the deploy button **4406**, a user interface **4500** shown in FIG. **45** is displayed. The user interface **4500** allows system administrators to enter a package deployment name into a name field **4502**, and also allows the administrator to enter a start time and end time, into start and end fields **4504**, **4506**, respectively. The user interface further allows the system administrator to select a package deployment file to use in a package deployment file selection field **4508**. The system administration presses a deploy button **4510** to deploy the package, or a cancel button **4512** to cancel deployment.

[0236] Upon selection of the deploy button **4510**, a further user interface **4600** shown in FIG. **46** is displayed to allow user verification that the correct package has been selected for download to medical devices. The user interface **4600** displays package deployment details in a package information field **4502**, including the selected start time, end time, and target type as entered in the previous user interfaces **4400**, **4500**. The user interface **4600** further displays vendor properties in a vendor field **4504**, such as the vendor identifier, name, and version of the vendor package.

[0237] FIGS. **47-50** display various reports generated from the data warehouse **322** of FIGS. **3-4**, as related to metadata-defined event messages or package deployment. FIG. **47-48** relate to message handling and debugging of faulty messages received from a medical device. FIGS. **49-50** display package deployment reports, incorporating records of successful and unsuccessful deployment of software or other binary data to medical devices.

[0238] FIG. **47** displays a quarantine report **4700**, which displays a chronological list of the quarantined messages received by the medical device server. The quarantine report **4700** includes time and date information **4702**, state information **4704**, and message information **4706**. The time and date information **4702** display the time stamp information related to the quarantine event tracked by the medical device server. The time and date information **4702** display on the report in varying formats, depending upon whether a user chooses a local time zone option or a GMT normalized time option. In the report **4700** shown, the local time zone option is selected.

[0239] The state information **4704** relates to the state of the quarantined message, such as whether it is a new message, a released message, or a reinserted message. New messages refer to newly located problematic messages, while released messages correspond to messages which cannot be resolved and must be dropped. Reinserted messages refer to those messages which are reintroduced to the message server in case the medical device is awaiting a response from the server.

[0240] The message information **4706** describes the error occurring in the message transfer. Various error messages are possible, generally relating to the ability of the medical device server to understand the message received from a medical device.

[0241] FIG. **48** displays a quarantine detail report **4800**, which is configured to display the details of a specific quarantined message received by the medical device server. The quarantine detail report includes an error field **4802** including the error information displayed on the quarantine report **4700**, and a source field **4804** which displays the metadata and values included in the message, for user debugging or correction of message activity in the medical device server. Additional information can be displayed regarding the quarantined message as well.

[0242] FIG. **49** displays a package deployment report **4900** showing package deployments known to the medical device server, with an associated list of medical devices of various types and the status of the package deployment to each of the medical devices. The package deployment report includes one or more package deployment entries **4902**, each including name and version information related to the specific package being deployed to that type of device. Each of the package entries includes device sub-entries **4904**, each of which relates to a specific device qualifying for the generalized package deployment. The sub-entries each include host name information **4906**, physical identification information **4908**, notification information **4910**, transfer information **4912**, and completion information **4914**. The host name information **4906** corresponds to the medical device server providing the package to the device. The physical identification information **4908** displays the unique identifier associated with the medical device. The notification information **4910** displays the date and time at which the medical device was notified that the package was available. The transfer information **4912** displays the date and time at which the package was successfully transferred to the medical device. The completion information **4914** displays the full date and time at which the package was successfully applied to the medical device.

[0243] Additional information can be tracked for each package deployment. For example, in an instance in which a

package fails to deploy, an error indication **4916** displays an indication of an error, and a result of the error.

[0244] FIG. **50** displays a package deployment error report **5000**. The package deployment error report **5000** provides a detailed event history for the specific packages and corresponding devices for which a package deployment fails. The package deployment error report **5000** displays a title **5002** including the target medical device type and package identifier. The title also optionally displays a name associated with the package deployment.

[0245] The package deployment error report **5000** displays time and date information **5004**, optional host information **5006**, physical identifier information **5008**, and message information **5010**. The time and date information **5004** indicate when the error in the package deployment occurred. The optional host name information **5006** displays the network name in which the medical device is located. The physical identifier information **5008** includes the identifier associated with the medical device. The message information **5010** displays the message associated with the package deployment error. Additional information regarding the deployment error may be included in the report **5000** as well.

[0246] 2. Maintenance/Faults

[0247] Referring now to FIGS. **51-53**, reports related to maintenance and faults of medical devices are shown. The reports provide user access to records of maintenance performed on the medical devices as well as information related to medical device failures and trends in those failures. Additional reports related to maintenance or faults may be incorporated as well, and correspond to the maintenance event data collected by the medical device server, as described above in Part III.B. In a possible embodiment, one or more of the reports of FIGS. **51-53** correspond to the maintenance forms **330** of FIGS. **3-4**.

[0248] FIG. **51** shows a medical device maintenance report **5100** listing maintenance records for various medical devices. The medical device maintenance report **5100** includes type entries **5102** corresponding to various types of medical devices, and device sub-entries **5104** corresponding to specific medical devices. In the embodiment shown, the type entries **5102** are the "MedFusion 4000" and "Titan" entries, while the device sub-entries **5104** are the individual rows within each type.

[0249] Within each sub-entry **5104**, there exists host name information **5106**, physical identifier information **5108**, version information **5110**, package information **5112**, and preventative maintenance date information **5114**. The host information **5106** displays the network associated with the medical device. The physical identifier **5108** displays the unique identifier associated with the medical device. The version information **5110** displays one or more version numbers associated with the medical device. The package information **5112** displays packages being used by the medical device. The preventative maintenance information **5114** displays a date at which the medical device is due for preventative maintenance. Additional information can be displayed within each sub-entry **5104** as well.

[0250] FIG. **52** shows a medical device fault report **5200**. The medical device fault report **5200** displays events related to medical device faults communicated to a medical device server, such as due to a faulty battery, motor, or other mechanical component. The medical device fault report **5200** includes time and date information **5202**, host information **5204**, physical identifier information **5206**, and message information **5208**. Use of the information **5202-5208** is analogous to the corresponding elements in the package deployment error report **5000** of FIG. **50**, but related to medical device fault events. For example, in the medical device fault report **5200**, the message information includes device fault event information, such as motor, battery, or other mechanical faults of a medical device.

[0251] FIG. **53** shows a medical device fault trending report **5300**. The medical device fault trending report **5300** displays a chart of medical device fault related events over time. The medical device fault trending report **5300** provides users with an indication of repeated errors in a medical device, or other detectable trends in medical device faults. In the embodiment shown, the medical device fault trending report **5300** displays a bar chart showing the frequency of device fault events by month. Other configurations displaying trends in device fault events are possible as well.

B. Operations Web Service: Operation and Control of Therapy States

[0252] FIGS. **54-62** disclose various aspects of the operations web service **3604** of FIG. **36**. Specifically, the figures show systems, methods, and reports for remote operation of the medical devices in a medical device network. In one possible embodiment, the systems and methods describe tracking of changed therapy parameters in a medical device by tracking original, updated, and final parameters of the medical device.

[0253] FIG. **54** shows a flowchart of methods and systems for tracking therapy order states in a medical device server. Therapy orders refer to commands to a medical device to provide a therapy to a patient. The system **5400** includes states corresponding to the various possible states experienced in the medical device during execution of the therapy order.

[0254] Operational flow within the system **5400** commences at a start node **5402**, which corresponds to introduction of a new therapy order into the medical device or medical device server. Once the therapy order is introduced, the system **5400** enters a new state **5404**, indicating that the therapy order is newly introduced and has not yet been executed by the medical device. When the system **5400** is in the new state **5404**, a user has the option to cancel the therapy order. If the user chooses to cancel the therapy order, operational flow in the system **5400** proceeds to a canceled state **5406**. From the canceled state, operational flow proceeds to an end node **5408** corresponding to completion of the therapy module. At the end node **5408**, operational flow terminates and therapy delivery events tracked using the medical device server continue to be stored for review by a user.

[0255] If the user chooses not to cancel the therapy order while the system **5400** is in the new state, operational flow proceeds to an assisted setup state **5410**. The assisted setup state **5410** attempts to assist in setting up the therapy parameters. If the assisted setup is unsuccessful operational flow branches to a failed state **5412**. The failed state **5412** stores an error message indicating that the assisted setup process failed. Operational flow proceeds from the failed state **5412** to the end node **5408**.

[0256] If the assisted setup state **5410** is successful in setting up therapy parameters, operational flow branches to a setup state **5414**. The setup state **5414** indicates that the therapy is successfully set up in the medical device, and is ready for delivery to a patient.

[0257] A begin therapy event, optionally sent from the medical device server or generated at the medical device, triggers the system **5400** to proceed to a started state **5416**, which corresponds to starting the therapy delivery in the medical device. An end therapy event received from the medical device or medical device server causes operational flow in the system **5400** to proceed to a complete state **5418**, indicating that delivery of the therapy is complete. Operational flow next proceeds to the end node **5408**.

[0258] FIG. **55** shows an exemplary class structure defining a therapy service **5500**. The therapy service **5500** illustrates a portion of the functionality of the operations web service module **3604**. The therapy service **5500** links to and uses a variety of functions from the administrative web service **3700** of FIG. **37**.

[0259] The therapy service **5500** includes a therapy order class **5502**, a therapy order rule utility **5504**, and a therapy order action enumeration **5506**. The therapy order class **5502** includes a variety of therapy order operations for starting, stopping, and defining various therapies to be delivered by medical devices in the medical device network in which the therapy service **5500** operates. The therapy order operations include therapy creation, therapy update, therapy cancel, therapy execute, and therapy retrieval operations. Additional therapy order operations can be included in the therapy order class **5502** as well.

[0260] The therapy order rule utility **5504** provides expressions and actions related to execution of the therapy order, including various parameters and commands required for execution of the therapy. The therapy order action enumeration **5506** provides advisory messages used during selection and/or execution of a therapy order.

[0261] FIG. **56** displays exemplary message exchange processes **5600**, **5620**, **5640**, and **5660** performed between a therapy order management application **5602**, an operations web service **5604** such as the one shown in FIG. **36**, a medical device server **5606** as disclosed above in FIGS. **3-4**, and a medical device **5608**, such as shown in FIG. **2**. The therapy order management application **5602** can be any application configured to interface with the operations web service to communicate therapy orders and other messages to the operations service **5604** and medical device server **5608**.

[0262] A first message exchange process **5600** illustrates the therapy order management application **5602** transmitting a create therapy order message **5610** to the operations web service **5604**. The operations web service **5604** verifies the therapy information and stores the therapy order in operations data. The operations web service **5604** also responds **5612** by indicating success or failure of the message.

[0263] A second message exchange process **5620** illustrates the therapy order management application **5602** later in time transmitting a therapy order update message or a therapy order cancellation message **5622**. The operations web service **5604** verifies the therapy information, and updates or cancels the therapy order according to the message. The operations web service **5604** also responds **5624** by indicating success or failure of the message.

[0264] A third message exchange process **5640** occurring after the first message exchange process **5600** illustrates the therapy order management application **5602** transmitting a message **5642** indicating that the therapy order should be executed. The therapy order management application **5602** transmits an execute therapy order message **5642** to the operations web service **5604**, which verifies the therapy order and in turn forwards the therapy order message **5642** to the medical device server **5606**. The medical device server **5606** relays the therapy order message **5642** to a medical device **5608**.

[0265] The medical device **5608** transmits a message **5644** indicating the success or failure of receipt of the therapy order message **5642**. The medical device server **5606** and operations web service **5604** relay the message **5644** back to the order trigger application **5602**.

[0266] At a time after the medical device transmits the message **5644**, the medical device **5608** initiates a fourth messaging process **5660** in which the medical device transmits a therapy begin message **5662** to the medical device server **5608**, indicating that the medical device has begun delivering the therapy to a patient. The medical device server **5608** transmits the message **5662** to the operations web service **5604**, which updates the therapy order state. The medical device server also relays the message **5662** to an event tracking web service **5605**, such as the one in FIG. **36**, to store a therapy delivery event in an event history log. Both the event tracking web service **5605** and the operations web service **5604** transmit response messages **5664** indicating the success or failure of receipt of the therapy begin message **5662**.

[0267] Additional events triggered by the medical device, such as a therapy completion event or alarm, transmit among the components **5602-5608** analogously to the messaging process **5660**. Further, additional messaging schema can be included as well.

[0268] FIG. **57** shows methods and systems for tracking changed parameters in a medical device, such as a medical infusion pump. The system **5700** communicates original, updated, and final parameter values used for operation of the medical device, using metadata as described herein to identify the various changes in parameters. The system **5700** commences at a start operation **5702**, which corresponds to initiation of a therapy in a medical device. The therapy initiated in the medical device includes parameters needing parameter values to define various aspects of the therapy. For example, in a therapy delivered by a medical infusion pump, various parameters include basal rates, bolus rates, thresholds, and various other parameters.

[0269] An original parameter receipt module **5704** receives an original parameter value from a medical device. The original parameter is a parameter set in a medical device prior to receipt of a different parameter by that device, and can be any type of operational parameter related to delivery of a therapy or monitoring provided by the medical device. An updated parameter receipt module **5706** receives an updated parameter value from the medical device corresponding to a change from the original parameter. The updated parameter value is a new parameter value changing the operation of the medical device. The updated parameter value relates to the same parameter as the original parameter. A final parameter receipt module **5708** receives a final parameter value from the medical device. The final parameter value is the parameter value the medical device will use for therapy and monitoring after the device is reprogrammed with the updated parameter value. The final parameter value may be the same as the updated parameter value, or may be different based on, for example, various hard and soft limits set for parameters within the medical device. In various embodiments, the receipt modules **5704-5708** may occur concurrently or sequentially, and may be included in one or more messages from the medical device to the medical device server.

[0270] A parameter storage module **5710** stores the original, updated, and final parameter values in memory of the medical device server or other back office components. Optional additional steps involved in the system **5700** can include comparing the final parameter value received in the final parameter receipt module **5708** with a hard limit or soft limit stored in the medical device server. If the final parameter value exceeds the limit, the system **5700** may trigger an alarm in the medical device server, and optionally communicate that alarm back to the medical infusion pump via a package deployment or other message. In a further embodiment, the alarm is communicated to a medical caregiver associated with the medical device.

[0271] Operational flow terminates at an end operation **5712**, which corresponds to completion of the change in pump parameter values and storage of the updated pump parameter values in the medical device server or other back office component.

[0272] FIG. **58** shows a medical device history report **5800** listing original, updated, and final operational parameter values for a medical device according to the methods and systems of FIG. **57**. The medical device history report **5800** includes a medical device label **5802**, date and time information **5804**, class information **5806**, trigger information **5808**, message information **5810**, location information **5812**, and drug information **5814**. The medical device label **5802** corresponds to the medical device name for the device whose history is displayed in the report **5800**. The date and time information **5804** correspond to the time the various events occurred that are included in the medical device history report. The class information **5806** describes the type and severity of the event. In the case of a therapy change event, the class information **5806** also includes an original value of the changed parameter, the changed value of that parameter, representing the value entered by a user, and a final value of the parameter, indicating the final set value used by the medical device.

[0273] The trigger information **5808** displays the trigger associated with the medical device event. In the example shown, an event in an alarm classification has a high level of concern, and includes a warning in the trigger information **5808**. However, an event describing a therapy change will not activate the trigger information **5808**.

[0274] The message information **5810** includes information about the status of the medical device, such as battery life, therapy delivery progress, therapy parameter limits, or physical characteristics of the device. The location information **5812** includes information related to the location of the medical device, such as the department, the facility, and the entity controlling the medical device. The drugs information **5814** includes information about the drug or therapy being delivered by the medical device, and optionally is only included in the information for a therapy change. Additional information about the medical device can be displayed in the medical device history report **5800**, based on the information tracked by the medical device server and operations web service.

[0275] FIG. **59** shows a therapy history report **5900**. The therapy history report **5900** displays the same information as is displayed in the medical device event history report **5800** of FIG. **58**, but will only display therapy event information. The therapy history report **5900** includes a medical device label **5902**, date and time information **5904**, class information **5906**, trigger information **5908**, message information **5910**, location information **5912**, and drug information **5914**, each of which operate analogously to the corresponding entries in the medical device event history report **5800**.

[0276] FIG. **60** shows a therapy trending report **6000**. The therapy trending report **6000** displays a chart of therapy related events over time. In the embodiment shown, the therapy trending report **6000** displays a bar chart showing the frequency of therapy events by month. Other configurations displaying trends in therapy events are possible as well.

[0277] FIG. **61** shows a therapy change history report **6100**. The therapy change history report **6100** also displays the same information as is displayed in the medical device event history report **5800** of FIG. **58**, but only displays therapy change event information. Therapy change events correspond to changed parameters in delivering a therapy using a medical device. The therapy change history report **6100** includes a medical device label **6102**, date and time information **6104**, class information **6106**, trigger information **6108**, message information **6110**, location information **6112**, and drug information **6114**, each of which operate analogously to the corresponding entries in the medical device event history report **5800** and the therapy history report **5900**.

[0278] FIG. **62** shows a therapy change trending report **6200**. The therapy change trending report **6200** displays a chart of therapy change events over time. In the embodiment shown, the therapy change trending report **6200** displays a bar chart showing the frequency of therapy change events by month. Other configurations displaying trends in therapy change events are possible as well.

C. Event Web Service: On-Line Status and Viewing of Device Activity

[0279] Referring now to FIGS. **63-66**, various features of the event web service of FIG. **36** are described. The event web service provides a method by which external applications collect event data from the medical device server and back office components. In particular, the event web service provides an indication of the on-line status of the medical device, and also provides user access to telemetry streams allowing near-real-time telemetry information regarding operation of a medical device in the context of a medical device network as described in FIGS. **1** and **3-4**.

[0280] FIG. **63** is a flowchart of methods and systems for determining the on-line status of a medical device. The system **6300** executes on a medical device server or other back office components, and expects communication from a medical device within a predetermined period in order to ensure accurate communication between the device and server.

[0281] Operational flow within the system **6300** commences at a start operation **6302**, which corresponds to initial communication between a medical device and a medical device server. Operational flow proceeds from the start operation **6302** to an expectation module **6304**. The expectation module **6304** sets in the medical device server and/or back office components an expected, predetermined period within which the medical device server will expect communication.

[0282] A receive data operation **6306** determines whether a message has been received by the medical device server. If data has been received by the medical device server, operational flow branches "yes" to an update module **6308**, which updates the status of the medical device to indicate that the device is on-line.

[0283] An optional output update module **6310** updates data output from the medical device server based on informa-

tion received in the message. The information received in the message can include medical device status information, event log data, telemetry data, or various other types of data. In one embodiment, the message indicates the beginning of a telemetry stream, and, in response to the message from the medical device, the medical device server and back office components update the appearance of a dashboard screen to reflect the received telemetry data. In a further embodiment, the output update module updates medical device status information in one or more of the back office components.

[0284] Operational flow proceeds through the receive data operation **6306**, the update module **6308**, and the output update module **6310** so long as the medical device continues in operation and the receive data operation **6306** determines that the medical device server continues to send messages to the medical device within the predetermined period.

[0285] If the receive data operation **6306** fails to receive data within the predetermined period, the operational flow branches "no" to an offline module **6312**, which changes the state of the medical device to offline in the medical device server and/or back office components. Operational flow proceeds to the optional output update module **6310**, which updates the output to indicate that the currently displayed data is no longer considered current by the medical device server until additional messages have been received. Operational flow terminates at an end module **6314**, corresponding to suspension of operation of the medical device network.

[0286] FIGS. **64-66** provide methods and systems for operation of telemetry streams received from a medical device. The telemetry streams described herein provide nearly-continuous communication from the medical devices to the medical device server, and are viewable on a dashboard or other web portal.

[0287] FIG. **64** shows a flowchart of systems and methods for near-real-time display of telemetry information from a medical device. Operational flow in the system **6400** commences at a start node **6402**, which corresponds to initial operation of a medical device capable of transmitting a telemetry stream in a medical device network. A new state **6404** indicates that the telemetry stream has not previously been running. After the new state, a stream startup process attempts to start the telemetry stream, as shown in FIG. **65**, below. If the stream startup process fails, operational flow proceeds to a failed state **6406**, corresponding to failure to start the telemetry stream. Operational flow then proceeds to an end node **6408**.

[0288] If the stream startup process successfully starts, operational flow proceeds to a collecting state **6410**, which corresponds to the medical device server collecting telemetry data from the medical device. In the collecting state, the telemetry data can be stored in the medical device server or other back office components, and also can be output to a dashboard or other monitoring user interface.

[0289] From the collecting state **6410**, a number of possible options affect operational flow of the system **6400**. If a message, including a telemetry stream message, is not sent from the medical device to the medical device server within an expected, predetermined time set in the medical device server or back office components, operational flow proceeds to an offline state **6412**. The offline state **6412** corresponds to the system no longer regularly receiving telemetry data. If a telemetry report is later received, the system **6400** returns to the collecting state **6410**.

[0290] If the telemetry stream is paused by a user, operational flow proceeds to a paused state **6414**, corresponding to a system which only temporarily is not receiving telemetry data. The user can resume the telemetry stream to return the system **6400** to the collecting state.

[0291] A terminated state **6416** can be reached from the collecting state **6410**, the offline state **6412**, or the paused state **6414** by the user terminating the stream or the system otherwise receiving a medical device power off event. The terminated state **6414** corresponds to ending the telemetry stream. In the terminated state, the system no longer receives information from the medical device, and the dashboard is not updated. In a possible embodiment, when the system **6400** is in the terminated state, a dashboard or other monitoring interface indicates to a user that data is not currently being collected. From the terminated state, operational flow proceeds to the end node **6408**.

[0292] FIG. **65** displays exemplary telemetry stream message sequences **6500**, **6520**, **6540**, and **6560** performed among: a dashboard **6502**, such as the one shown in FIG. **67**; an event tracking web service **6504**, such as the one shown in FIG. **36**; a medical device server **6506**, as disclosed above in FIGS. **3-4**; and a medical device **6508**, such as shown in FIG. **2**. A first telemetry stream message sequence **6500** illustrates a request to initiate a telemetry stream from a medical device to a dashboard. The message sequence **6500** starts by the dashboard **6502** sending a start telemetry stream message **6510** to the event tracking web service **6504**. The event tracking web service communicates the message **6510** to the medical device server **6506**, which in turn communicates the message **6510** to the medical device **6508**. The medical device generates a response message **6512** indicating success or failure of the message. The response message is related back to the dashboard **6502** by the medical device server **6506** and event tracking web service **6504**.

[0293] A second telemetry stream message sequence **6520** illustrates initiation of a telemetry stream by a medical device **6508**. The medical device **6508** generates a telemetry event **6522**, which includes near-continual communication of telemetry data from the medical device **6508** to the medical device server **6506**, which relays the telemetry data to the dashboard **6502** via the event tracking web service **6504**. The dashboard **6502** displays the telemetry data to the user in a near-real-time fashion. In one embodiment, the dashboard recreates the appearance of the medical device. The dashboard transmits a response message **6524** to the event tracking web service **6504**, indicating successful receipt of the telemetry stream.

[0294] The dashboard **6502** generates a get telemetry window message **6526** and transmits the message to the event tracking web service, which responds with a message **6528** indicating success or failure of the command. The telemetry window is started at this point, and the dashboard or web portal will display telemetry data.

[0295] At this point, if the medical device is powered off, the event tracking web service **6504** will respond with a fail message and will terminate the telemetry stream.

[0296] A third telemetry stream message sequence **6540** illustrates ending a telemetry stream by shutting off the medical device generating the telemetry stream. The medical device **6508** generates a power off event message **6542** and sends the message to the medical device server **6506**. The medical device server sends a terminate telemetry stream message to the event tracking web service **6504**. The event

tracking web service **6504** generates a response message **6544** indicating success or failure of receipt of the message **6542**. The medical device server **6506** relays the response message **6544** to the medical device **6508**.

[0297] A fourth telemetry stream message sequence **6560** relates to the sequence **6540** and illustrates ending a telemetry stream by discontinuing the telemetry stream at the dashboard **6502**. The dashboard **6502** generates a terminate telemetry stream message **6562**, which is communicated from the dashboard to the event tracking web service **6504**, and in turn through the medical device server **6506** to the medical device **6508**. The medical device **6508** terminates its telemetry stream and generates a response message **6564** indicating success or failure of receipt of the message **6562**. The medical device server relays the message **6564** through the event tracking web service **6504** to the dashboard **6502**. Additional messaging processes are possible in order to start and terminate telemetry streams using medical devices and dashboards according to the present disclosure.

[0298] FIG. **66** shows an exemplary class structure defining a telemetry stream class **6600**. The telemetry stream structure **6600** illustrates a portion of the functionality of the event web service module **3606**. The telemetry stream relates back to and uses a variety of functions from the administrative web service **3700** of FIG. **37**.

[0299] The telemetry stream structure **6600** includes a telemetry stream class **6602** and a latest event class **6604**. The telemetry stream class **6602** includes a variety of telemetry-related operations, including starting, terminating, pausing, and retrieving available telemetry streams. Additional telemetry stream operations can be included in the telemetry stream class **6602** as well. The latest event class **6604** includes functions for retrieving the latest events, so as to determine when the most recent event was received from the medical device and thereby determine the on-line status of the medical device, so as to determine the availability of telemetry stream data. Additional functions can be included in the latest event class **6604**, and additional classes can be added to the telemetry stream structure **6600**.

[0300] Various exemplary dashboards may be used to view telemetry data at a workstation of other computing device. One example dashboard is shown in FIG. **67**. The dashboard **6700** displays telemetry data (e.g. current or near-current operational status) relating to the pumps with which it is associated. The dashboard **6700** can be any of a number of dashboard applications configured to receive and display telemetry data to a user in a near-real-time manner, and can correspond, for example, to the dashboards logically illustrated as dashboard **328** of FIGS. **3-4**. The dashboard **6700** can be updated by a telemetry stream, such as described above in FIGS. **64-66**.

[0301] In the embodiment shown, the dashboard **6700** tracks a name **6702**, identifier **6704**, domain **6706**, address **6708**, port **6710**, and activity history **6712**, with respect to each medical device associated with the dashboard. The name **6702** corresponds to a name of a device recognizable to a user, assigned by either the device itself or the server. The identifier **6704** provides a unique identification useable by the server to verify the identity of the medical device. In various embodiments, the identifier can correspond to a globally-unique identifier (GUID), hardware address, or other identification of the medical device. The domain **6706** indicates the name of a network in which the medical device resides. The address **6708** provides connection information regarding how to communicate with the medical device from the server. In the embodiment shown, the address **6708** is shown as an IP address of the medical device. The port **6710** lists the inbound communication port for the medical device. The activity history field **6712** lists a date and time of the last event occurring on the medical device and communicated to the server.

[0302] The dashboard **6700** graphically illustrates an operational status of the pumps with which it is associated. In the embodiment shown, five medical devices are tracked in the dashboard **6700**, named "MD0333", "MD0444", "MD0524", "MD0324", and "MD0988." The first, fourth, and fifth devices (MD0333, MD0324, and MD0988) are illustrated as powered and delivering a therapy to a patient. The second device (MD0444) is shown to be in an alarm state, indicating a possible abnormal operation of the device or emergency condition related to the patient associated with that device. The third device (MD0524) is illustrated to be in a fault state, indicating a malfunction or error occurring in that medical device. Other states illustrating an operational status may be illustrated on the dashboard **6700** as well.

[0303] Optionally, additional features can be included in the dashboard **6700** that allow a user to filter or display different types of information. In the embodiment shown, a pause check box **6714** and an offline devices check box **6716** allow a user to selectably modify the dashboard. The pause check box **6714**, when selected, causes the dashboard to "freeze" temporarily halting the updating of information in the dashboard to allow a user to view the state of the dashboard at a single time. When the pause check box **6714** is unselected, the status information on the dashboard can continually update as data is received from the associated medical devices. The offline devices check box **6716** enables the dashboard to display information related to devices associated with the dashboard, but which are not online and from which the dashboard has not received recent status information. Other display features and filters can be incorporated into the dashboard as well, allowing a user to select the desired set of devices to monitor and allowing the user to view a specific portion of the telemetry data received from those users.

[0304] The various embodiments described above are provided by way of illustration only and should not be construed to limit the invention. Those skilled in the art will readily recognize various modifications and changes that may be made to the present invention without following the example embodiments and applications illustrated and described herein, and without departing from the true spirit and scope of the present invention, which is set forth in the following claims.

1. A method of communication between a medical device and a server, the method comprising:

associating metadata with one or more medical devices, the metadata corresponding to an attribute of the medical devices; and

storing the metadata on a server, the server configured to communicate with each of the medical devices by using the metadata.

2. The method of claim **1**, wherein the metadata corresponds to an attribute common to all of the medical devices.

3. The method of claim **1**, further comprising:

associating second metadata with a second medical device, different from the one or more medical devices; and

storing the second metadata on the server, the server configured to communicate with each of the medical devices

and the second medical device by using at least one of the metadata and the second metadata.

4. The method of claim **1**, wherein the one or more medical devices include medical devices from two or more medical device manufacturers.

5. The method of claim **1**, further comprising associating second metadata with at least one medical device of the plurality of medical devices, the second metadata corresponding to at least one custom attribute of the medical device.

6. The method of claim **5**, wherein the metadata and the second metadata define capabilities of the medical device.

7. The method of claim **5**, wherein storing the metadata on a server further comprises storing the second metadata on the server.

8. The method of claim **1**, wherein the metadata includes a medical device identifier.

9. The method of claim **1**, wherein the metadata includes a medical capabilities variable.

10. The method of claim **1**, wherein the metadata includes a name of the medical device.

11. The method of claim **1**, wherein the metadata corresponds to an attribute of the medical devices, the attribute selected from the group consisting of:

patient information;

user information;

control information;

drug information; and

location information.

12. The method of claim **1**, wherein the metadata corresponds to an event that is tracked by the medical device, the event selected from the group consisting of:

power events;

alarm events;

fault events;

maintenance events;

telemetry events;

therapy events;

therapy change events; and

custom events.

13. The method of claim **1**, wherein the second metadata includes an attribute of a medical infusion pump.

14. The method of claim **1**, further comprising, on the server, selecting a medical device using the metadata.

15. The method of claim **14**, further comprising sending a message to the medical device, the message including metadata.

16. The method of claim **1**, wherein the metadata is structured using XML.

17. The method of claim **1**, further comprising using the metadata to distinguish among the plurality of medical devices.

18. A system for communicating with a plurality of medical devices, the system comprising:

a plurality of medical devices;

a server communicatively connected to the plurality of medical devices, the server comprising:

a memory configured to store metadata describing the medical devices;

a programmable circuit operatively connected to the memory, the programmable circuit configured to execute program instructions to:

associate metadata with one or more medical devices, the metadata corresponding to at least one attribute of the medical devices;

store the metadata on a server; and

communicate information including the metadata with at least one of the medical devices.

19. The system of claim **18**, wherein the metadata corresponds to an attribute common to all of the medical devices.

20. The system of claim **18**, wherein the plurality of medical devices include medical devices from two or more medical device manufacturers.

21. The system of claim **18**, wherein the programmable circuit further contains program instructions to associate second metadata with at least one medical device of the medical devices, the second metadata corresponding to at least one custom attribute of the medical device.

22. The system of claim **21**, wherein the metadata and the second metadata define capabilities of the medical device.

23. The system of claim **22**, wherein the programmable circuit is further programmed to store the second metadata on the server.

24. The system of claim **23**, wherein the first metadata includes a medical device identifier.

25. The system of claim **18**, wherein at least one of the medical devices is a medical infusion pump.

26. The system of claim **25**, wherein the second metadata includes an attribute of the medical infusion pump.

27. The system of claim **18**, wherein the metadata corresponds to an attribute of medical device selected from the group consisting of:

patient information;

user information;

control information;

drug information; and

location information.

28. The system of claim **18**, wherein the metadata corresponds to an event that is tracked by the medical device, the event selected from the group consisting of:

power events;

alarm events;

fault events;

maintenance events;

telemetry events;

therapy events;

therapy change events; and

custom events.

29. A method of communication between a medical device and a server, the method comprising:

associating metadata with each of a plurality of medical devices, the metadata corresponding to at least one attribute common to the medical devices;

associating second metadata with at least one medical device of the plurality of medical devices, the second metadata corresponding to at least one custom attribute of the medical device;

storing the metadata on a server, the server configured to communicate with each of the medical devices by using the metadata;

selecting a medical device; and

communicating information including the metadata with the medical device.

30. A method of communication between a plurality medical devices and a server, the method comprising:

generating a message to a medical device server at a medical device, the message including metadata used to identify the medical device; and

receiving a message from the medical device server at the medical device, the message including metadata identifying the medical device.

31. The method of claim **30**, wherein the plurality of medical devices include medical devices from two or more medical device manufacturers.

32. The method of claim **30**, further comprising:

associating second metadata with a second medical device, different from the plurality of medical devices; and

storing the second metadata on the server, the server configured to communicate with each of the medical devices and the second medical device by using the metadata and the second metadata.

* * * * *