US010640130B2

(12) **United States Patent**
Jain et al.

(10) **Patent No.: US 10,640,130 B2**
(45) **Date of Patent: May 5, 2020**

(54) **ABERRANT DRIVER CLASSIFICATION AND REPORTING**

(71) Applicant: **Ford Global Technologies, LLC.**, Dearborn, MI (US)

(72) Inventors: **Jinesh J Jain**, San Mateo, CA (US); **Daniel Levine**, San Mateo, CA (US)

(73) Assignee: **FORD GLOBAL TECHNOLOGIES, LLC**, Dearborn, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/437,712**

(22) Filed: **Jun. 11, 2019**

(65) **Prior Publication Data**

US 2019/0291750 A1 Sep. 26, 2019

Related U.S. Application Data

(62) Division of application No. 14/842,666, filed on Sep. 1, 2015, now Pat. No. 10,358,143.

(51) **Int. Cl.**

B60W 50/14	(2020.01)
G06N 20/00	(2019.01)
G06F 16/28	(2019.01)

(52) **U.S. Cl.**

CPC ***B60W 50/14*** (2013.01); ***G06F 16/285*** (2019.01); ***G06N 20/00*** (2019.01); *B60W 2420/42* (2013.01); *B60W 2420/52* (2013.01)

(58) **Field of Classification Search**

CPC B60W 50/14; B60W 40/09; G06F 16/285; G06N 20/00; G05D 1/0088; G05D 2201/0213; H04L 67/12

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,710,249	B2	5/2010	Park	
8,554,468	B1	10/2013	Bullock	
8,977,747	B2	3/2015	Tonnesen	
2014/0236414	A1	8/2014	Droz	
2016/0163217	A1 *	6/2016	Harkness	G09B 5/06 434/65

FOREIGN PATENT DOCUMENTS

CN	104598892	A	5/2015
JP	2004206207	A	7/2004
JP	2008296682	A	12/2008

* cited by examiner


Primary Examiner — Orlando Bousono

(74) *Attorney, Agent, or Firm* — David R. Stevens; Stevens Law Group

(57) **ABSTRACT**

Methods, devices and apparatuses pertaining to aberrant driver classification and reporting are described. A method may involve receiving a message from a user of a first vehicle, the message indicating an instance of aberrant driving of a second vehicle. The method may also involve determining that the instance has occurred using one or more classifiers. The method may further involve collecting information of the second vehicle and generating a warning message based on the information.

5 Claims, 6 Drawing Sheets





100
ABERRANT DRIVING WARNING SCHEME
114
ROAD SEGMENT
128
NETWORK
130
VEHICLE
118
COMPUTING SYSTEM
124
122
HOST
DRIVER
110
ROAD
SEGMENT
126
FEATURES CLASSIFIERS
120
VEHICLE
116
VEHICLE
CLASSIFIER GENERATION SCHEME
102
SIMULATED DRIVING
SCENARIOS
106
REAL-WORLD
EXPERIMENTS
108
112
HUMAN SUBJECT
104
COMPUTING
SYSTEM

FIG. 1



104
COMPUTING SYSTEM
200
COMPUTING SYSTEM 104
PROCESSOR(S) 202
MEMORY 204
OPERATING SYSTEM 206
DATA COLLECTION MODULE 208
CLUSTERING MODULE 210
DEPLOYMENT MODULE 212
PROGRAM DATA 214

FIG. 2



300
CLUSTER 1
SAMPLE DATA SET 1
AXIS 1
AXIS 2
SAMPLE DATA SET 4
AXIS 1
AXIS 2
CLUSTER 2
SAMPLE DATA SET 2
AXIS 1
AXIS 2
SAMPLE DATA SET 5
AXIS 1
AXIS 2
CLUSTER 3
SAMPLE DATA SET 3
AXIS 1
AXIS 2
SAMPLE DATA SET 6
AXIS 1
AXIS 2
Legend:
Feature 1 =
Feature 2 =
Feature 3 =

FIG. 3



COMPUTING SYSTEM
124
400
COMPUTING SYSTEM 124
PROCESSOR(S) 402
MEMORY 404
OPERATING SYSTEM 406
WARNING GENERATION APPLICATION 408
COMMUNICATION MODULE 410
ABERRANT DRIVING DETERMINATION MODULE 412
DATA COLLECTION MODULE 414
WARNING GENERATION MODULE 416
PROGRAM DATA 418
FEATURE CLASSIFIER(S) 110

FIG. 4



500
502
PROVIDE DRIVING SCENARIO(S) INVOLVING ABERRANT DRIVING BEHAVIOR(S) TO USER
504
RECEIVE DATA OF RESPONSE(S) FROM USER
506
CLUSTER DATA TO GENERATE CLASSIFIER(S)
508
TRANSMIT CLASSIFIER(S) TO VEHICLE(S)

FIG. 5



600
602
RECEIVE MESSAGE FROM FIRST USER OF FIRST VEHICLE
604
DETERMINE PARAMETER INDICATING POSSIBLE ABERRANT DRIVING INSTANCE OF SECOND VEHICLE
606
PARAMETER GREATER THAN THRESHOLD?
NO
YES
608
DETERMINE THAT ABERRANT DRIVING INSTANCE OF SECOND VEHICLE HAS OCCURRED
610
GENERATE ERROR MESSAGE
612
RECEIVE INFORMATION OF SECOND VEHICLE
614
GENERATE WARNING MESSAGE BASED ON INFORMATION
616
TRANSMIT WARNING MESSAGE TO VEHICLE(S) IN VICINITY

FIG. 6

ABERRANT DRIVER CLASSIFICATION AND REPORTING

CROSS REFERENCE TO RELATED PATENT APPLICATION(S)

The present disclosure is part of a divisional of U.S. patent application Ser. No. 14/842,666, filed on Sep. 1, 2015, the content of which is incorporated by reference in its entirety.

TECHNICAL FIELD

The present disclosure generally relates to traffic safety and, more particularly, to methods and systems for aberrant driver classification and reporting.

BACKGROUND

Aberrant drivers are a danger to nearby pedestrians, drivers and themselves. The category of aberrant driving typically includes variously defined categories of reckless driving, careless driving, improper driving, erratic driving, and driving without due care and attention. Thus, there is a need for a solution for recognizing and mitigating the impact of aberrant driving in order to reduce motor vehicle accidents and fatalities caused by aberrant drivers.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present disclosure are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various figures unless otherwise specified.

FIG. **1** is a diagram depicting an example environment in which example embodiments of the present disclosure may be implemented.

FIG. **2** is a block diagram depicting an example computing architecture in accordance with an embodiment of the present disclosure.

FIG. **3** is a diagram of a simplified example of data clustering in accordance with the present disclosure.

FIG. **4** is a block diagram depicting an example computing architecture in accordance with another embodiment of the present disclosure.

FIG. **5** is a flowchart of an example process in accordance with an embodiment of the present disclosure.

FIG. **6** is a flowchart of an example process in accordance with another embodiment of the present disclosure.

DETAILED DESCRIPTION

In the following description, reference is made to the accompanying drawings that form a part thereof, and in which is shown by way of illustrating specific exemplary embodiments in which the disclosure may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the concepts disclosed herein, and it is to be understood that modifications to the various disclosed embodiments may be made, and other embodiments may be utilized, without departing from the scope of the present disclosure. The following detailed description is, therefore, not to be taken in a limiting sense.

Implementations herein use unsupervised and/or semi-supervised learning to build and grow a set of features of aberrant driving behaviors. These features may be processed

to build one or more classifiers. The one or more classifiers may then be deployed or otherwise transmitted to a number of vehicles to be used to identify or characterize one or more aberrant driving behaviors of one or more other vehicles in the vicinity of a vehicle. A user, e.g., a driver or a passenger, of the vehicle may report one or more perceived aberrant driving behaviors upon observing driving behavior(s) of one or more other vehicles that the user perceives to be aberrant driving behavior(s). If a perceived aberrant driving behavior is confirmed to be an aberrant driving behavior according to the one or more classifiers, a warning message may be generated and transmitted to other vehicles in vicinity of the vehicle.

FIG. **1** is a diagram depicting an example environment **100** in which example embodiments of the present disclosure may be implemented. Example environment **100** may include a classifier generation scheme **102** for the generation of classifiers for identifying and/or characterizing aberrant driving behaviors. Classifier generation scheme **102** includes a computing system **104**. Computing system **104** may include a computing apparatus, such as a server, or a collection of servers in a distributed configuration (e.g., a cloud computing service, a server farm, etc.) or a non-distributed configuration.

In accordance with various embodiments of the present disclosure, computing system **104**, in a basic configuration, may include various modules, each discussed below. Computing system **104** may collect data by way of a combination of simulations and real-world experiments, such as one or more simulated driving scenarios **106** and one or more real-world experiments **108**.

In some implementations, in the one or more simulated driving scenarios **106**, computing system **104** may simulate one or more aberrant driving behaviors in a driving simulator. Alternatively, computing system installed on the driving simulator may collect data and transmit the data to computing system **104** to build and/or train the one or more feature classifiers **110**.

In the one or more simulated driving scenarios **106**, a human subject or a user **112** may be subjected to a range of driving scenarios involving potential aberrant driving behaviors. For example, a steering wheel instrumented with push buttons may be used by user **112** to signal whether user **112** perceives a currently simulated situation as involving a potentially dangerous or aberrant driving behavior. For example, a pushed button may flag a window of time in which another vehicle in the vicinity of the vehicle that user **112** is simulated to be driving may have exhibited one or more aberrant driving behaviors. In some implementations, a monitor of a heart rate, a breath rate and/or a degree of perspiration may be placed on user **112** to measure auxiliary signals that may indicate unease of user **112** (e.g., an increase in the heart rate, breath rate and/or degree of perspiration) under one or more simulated driving scenarios **106**.

In some implementations, in one or more real-world experiments **108**, a portion of computing system **104** may be installed on a vehicle driven by user **112**. Alternatively, another computing system installed on the vehicle may collect data and transmit the data to computing system **104** to build and/or train the one or more feature classifiers **110**. For example, user **112** may drive a vehicle on a road, and the vehicle may be equipped with one or more sensors (e.g., one or more two-dimensional (2D) cameras, a Light Detection and Ranging (LIDAR) or a Radio Detection and Ranging (RADAR) system) to provide estimate data of other vehicles in the vicinity of the vehicle driven by user **112**. In some

implementations, the vehicle driven by user **112** may receive a signal from user **112** when user **112** perceives another vehicle in the vicinity to be exhibiting one or more aberrant driving behaviors. Moreover, the vehicle driven by user **112** may collect data on driving behaviors of other vehicles in the vicinity using the one or more sensors within a certain window of time. In these instances, repeating patterns of one or more aberrant driving behaviors may be procedurally re-simulated to reduce uncertainty and further train the one or more feature classifiers **110**.

Example environment **100** may further include an aberrant driving warning scheme **114** for uses of the one or more classifiers to identify and/or characterize one or more aberrant driving behaviors. Aberrant driving warning scheme **114** may include a number of vehicles including, for example, a vehicle **116**, a vehicle **118** and a vehicle **120**. The one or more feature classifiers **110** may be deployed or otherwise transmitted to any one of these vehicles. For example, the one or more feature classifiers **110** may be transmitted to vehicle **116**. A user **122**, e.g., a driver or a passenger of vehicle **116**, may report one or more perceived aberrant driving behaviors of vehicle **118** to computing system **104**, e.g., via network **130**. In these instances, user **122** may use an operation (e.g., depressing a button) similar to that described above when user **122** perceives one or more aberrant driving behaviors of vehicle **118** on a road segment **126**.

In some implementations, vehicle **116** may also be equipped with one or more sensors to allow a computing system **124** of vehicle **116** to collect data on one or more other vehicles in the vicinity of vehicle **116** (e.g., vehicle **118**). Using the one or more feature classifiers **110**, computing system **124** may assign a weight, or risk parameter, attributed to the report (e.g., a warning message) based on a classification of the vehicle in concern, e.g., vehicle **118**. In some implementations, the risk parameter may be modified (e.g., having its value increased or decreased) based on the prevalence of other reports on that same vehicle. For instance, in a situation where a malicious user spams computing system **104** with a plethora of false reports on a given vehicle, computing system **104** may decrease the value of the risk parameter attributed to the reports from the malicious user. In some implementations, the risk parameter may be a function of evaluation of and generated by one or more feature classifiers **110**, and may indicate an agreement between the evaluation of one or more feature classifiers **110** and evaluation of user **122**. In some implementations, the risk parameter may also include a measure designed to filter out false reporting from malicious user(s). This measure may avoid false reports with unacceptable frequency. In some implementations, the value of the risk parameter may be incrementally decreased by computing system **104** over a period of time so that after the passage of a predetermined amount of time the risk parameter may be zero. This way, a driver of a reported vehicle may not be labeled as an aberrant driver permanently, especially when an instance of aberrant driving by such driver may be a rare, one-time occasion and not reflective of a normal driving behavior of such driver.

The warning message may be transmitted to vehicle **120** on a road segment **128** via network **130**. For instance, vehicle **116** may transmit the warning message to vehicle **120** when vehicle **120** satisfies a user-definable metric such as, for example, being sufficiently close to vehicle **116** (e.g., within a close proximity such as 30 feet, 50 feet or 100 feet). Road segment **128** may be within any user-definable metric (e.g., a predetermined range) of road segment **126**, e.g., 100 feet, 200 feet or any user-definable distance. Network **130** may include wired and/or wireless networks that enable communications between the various computing devices described in example environment **100**. In some embodiments, network **130** may include local area networks (LANs), wide area networks (WAN), mobile telephone networks (MTNs), and other types of networks, possibly used in conjunction with one another, to facilitate communication between the various computing devices.

In some implementations, user **122** and a driver of vehicle **120** may be in a drive safety network. For example, the driver of vehicle **120** may be warned or otherwise made aware that vehicle **118** has exhibited one or more aberrant driving behaviors and may be approaching vehicle **120**, upon a determination by computing system **124** and/or user **122** of an instance of one or more aberrant driving behaviors exhibited by vehicle **118**. The driver of vehicle **120** may also determine that vehicle **118** exhibits the same or different one or more aberrant driving behaviors. The drive safety network may assign and/or aggregate a risk parameter to vehicle **118** in response to receiving a warning message regarding vehicle **118**. When a value of the risk parameter associated with vehicle **118** exceeds a risk threshold, the drive safety network may automatically report the one or more aberrant driving behaviors exhibited by vehicle **118** to a local authority.

FIG. **2** is a block diagram depicting an example computing architecture **200** in accordance with an embodiment of the present disclosure. Computing architecture **200** may be an example implementation of computing system **104**, which may be in the form of a computing apparatus having modules, kernels, data, and/or hardware.

Computing system **104** may include one or more processors **202** and memory **204**. Memory **204** may store various modules, applications, programs, or other data. Memory **204** may include one or more sets of instructions that, when executed by the one or more processors **202**, cause the one or more processors **202** to perform the operations described herein for computing system **104**. The one or more processors **202** may include one or more graphics processing units (GPU) and one or more central processing units (CPU).

Computing system **104** may have additional features and/or functionalities. For example, computing system **104** may also include additional data storage devices (removable and/or non-removable) including computer-readable media. Computer-readable media may include, at least, two types of computer-readable media, namely computer storage media and communication media. Computer storage media may include volatile and non-volatile, removable, and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, program data, or other data. The system memory, the removable storage and the non-removable storage are all examples of computer storage media. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store the desired information and which can be accessed by computing system **104**. Any such computer storage media may be part of computing system **104**. Moreover, the computer-readable media may include computer-executable instructions that, when executed by the processor(s), perform various functions and/or operations described herein.

Memory **204** may store an operating system **206** as well as various modules including, for example, a data collection

module **208**, a clustering module **210**, a transmission module **212**, and program data **214**. Operating system **206** may include one or more sets of instructions that are executable by one or more processors **202** to control operations of computing system **104**.

Data collection module **208** may be configured to present driving scenarios involving aberrant driving behaviors to user **112**, and receive data indicative of one or more responses of user **112** regarding the driving scenarios. Data collected by data collection module **208** may be stored as program data **214**.

In some implementations, computing system **104** may simulate the driving scenarios involving the aberrant driving behaviors using a simulation system. For example, user **112** may be situated or otherwise placed into the simulation system, and one or more responses of user **112** may be monitored. The one or more responses of user **112** may include signals each of which indicating an aberrant driving behavior perceived by user **112** in response to a simulated condition. In some implementations, the one or more responses may include an auxiliary signal associated with one or more physical parameters of user **112**.

In some implementations, computing system **104** may facilitate real-world experiments to user **112**. Computing system **104** may monitor one or more responses of user **112**. The one or more responses may include signals each of which indicating an aberrant driving behavior perceived by user **112** in response to a driving condition. Computing system **104** may collect real-time data including state estimates that are generated by one or more sensors of a testing vehicle and within a predetermined window of time after receiving the signals from user **122**.

Clustering module **210** may be configured to cluster the data, collected by data collection module **208**, using a nonparametric technique to generate the one or more feature classifiers **110**. For example, a set of features may include rules of road infractions such as failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary or into oncoming traffic and grossly exceeding the speed limit (e.g., by more than 10 mph). Another set of features may relate to specific absolute and relative profiles that observed vehicles may exhibit. This set of features may include, for example, swerving, skidding, oscillating laterally, deviation from a lane center for more than a threshold amount of time, lane changing without proper clearance, erratic speed control, erratic braking, and off-nominal confluence with a traffic flow.

FIG. **3** illustrates a simplified example **300** of data clustering in accordance with the present disclosure. In the simplified example **300** shown in FIG. **3**, there are data associated with three features being clustered. The three features (e.g., feature 1, feature 2 and feature 3) may pertain to, for example, (1) the speed of a vehicle, (2) an amount of deviation from the center line of a lane in which the vehicle is traveling, and (3) whether a blinker is turned on when the vehicle makes a turn. Data for each of these features may be a series of continuous numbers (e.g., speed of the vehicle and/or deviation from the center line of the lane) or discrete numbers (e.g., 0 or 1 indicative of whether the blinker is off or on when the vehicle is turning). In the simplified example **300** shown in FIG. **3**, there are six sets of unique sample data for each of the three features, and these six sets of unique sample data are grouped into three clusters (e.g., cluster 1, cluster 2 and cluster 3) each having two sets of the unique sample data. In some implementations of the present disclosure, a number of features (e.g., feature 1, feature 2 and feature 3) may be utilized for feature engineering to collect a number of sets of sample data for clustering by any suitable algorithm, e.g., executed by clustering module **210**. The result of the data clustering may be used to train classifiers such as the one or more feature classifiers **110**. Examples of an algorithm for data clustering may include, for example and not limited to, deep learning based techniques, k-means clustering, and hierarchical clustering.

Transmission module **212** may be configured to transmit the one or more feature classifiers **110** to one or more vehicles, e.g., vehicle **116**. Accordingly, user **122** of vehicle **116** may report one or more perceived aberrant driving behaviors of vehicle **118** (and/or any other vehicle), and the report may be transmitted from vehicle **116** to one or more other vehicles, e.g., vehicle **120**. For example, if one or more perceived aberrant driving behaviors of vehicle **118** are confirmed according to the one or more feature classifiers **110**, the report may be generated and transmitted to vehicle **120**, which may be in the vicinity of vehicle **116** and/or vehicle **118**.

FIG. **4** is a block diagram depicting an example computing architecture **400** in accordance with an embodiment of the present disclosure. Computing architecture **400** may be an example implementation of computing system **124**, which may be in the form of a computing apparatus having modules, kernels, data, and/or hardware.

Computing system **124** may include one or more processors **402** and memory **404**. Memory **404** may store various modules, applications, programs, or other data. Memory **404** may include one or more sets of instructions that, when executed by the one or more processors **402**, cause the one or more processors **402** to perform the operations described herein for computing system **124**. The one or more processors **402** may include one or more graphics processing units (GPU) and one or more central processing units (CPU).

Computing system **124** may have additional features and/or functionalities. For example, computing system **124** may also include additional data storage devices (removable and/or non-removable) including computer-readable media. Computer-readable media may include, at least, two types of computer-readable media, namely computer storage media and communication media. Computer storage media may include volatile and non-volatile, removable, and non-removable media implemented in any method or technology for storage of information, such as computer readable instructions, data structures, program modules, program data, or other data. The system memory, the removable storage and the non-removable storage are all examples of computer storage media. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD), or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store the desired information and which can be accessed by computing system **124**. Any such computer storage media may be part of computing system **124**. Moreover, the computer-readable media may include computer-executable instructions that, when executed by the processor(s), perform various functions and/or operations described herein.

Memory **404** may store an operating system **406** as well as various modules including, for example, a warning generation application **408**, one or more feature classifiers **110** and program data **418**. Warning generation application **408** may further include various modules such as, for example, a communication module **410**, an aberrant driving determination module **412**, a data collection module **414** and a

warning generation module **416**. Operating system **406** may include one or more sets of instructions that are executable by one or more processors **402** to control operations of computing system **124**.

Communication module **410** may be configured to receive a message from user **122** of vehicle **116**. The message may indicate an instance of an aberrant driving behavior of another vehicle, e.g., vehicle **118**, as perceived by user **122**.

Aberrant driving determination module **412** may be configured to determine whether the instance of an aberrant driving behavior has occurred using the one or more feature classifiers **110**, which may have been trained using driving scenario simulations and/or real-world experiments.

In some implementations, the one or more feature classifiers **110** may include template motion plans which may include, for example and not limited to, aberrant driving features and/or aberrant driving profiles. In these instances, the aberrant driving features are associated with driving behaviors including, for example and not limited to, at least one of the following: failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary, driving into oncoming traffics, exceeding a speed limit, tailgating and honking excessively. The aberrant driving profiles may include, for example and not limited to, at least one of swerving, skidding, oscillating laterally, prolonged deviation from a lane center, lane changing without proper clearance, erratic speed control, erratic braking, or off-nominal confluence with a traffic flow, any erratic and/or hostile and dangerous driving behaviors.

In some implementations, aberrant driving determination module **412** may determine a parameter using the aberrant driving classifiers. The parameter may indicate possibility that the instance of aberrant driving behavior has occurred within a predetermined window of time after receiving the message from user **122**. Aberrant driving determination module **412** may further determine that the instance has occurred if the value of the parameter is greater than a predetermined threshold value.

Data collection module **414** may be configured to collect information of vehicle **118**, which exhibits aberrant driving behaviors in this example. For instance, vehicle **116** may be equipped with one or more sensors (e.g., vision device(s), a LIDAR system or a RADAR system) to provide estimated data of vehicle **118** such as speed, acceleration, direction and/or any information regarding the behavior of vehicle **118**. Data collected by data collection module **414** may be stored as program data **418**.

Warning generation module **416** may be configured to generate a warning message based on the data collected by data collection module **414**. For example, the warning message may include an encoded license plate number and/or a description of vehicle **118**. Communication module **410** may transmit the warning message to one or more other vehicles, e.g., vehicle **120**, which may satisfy a user-defined metric with respect to the one or more other vehicles (e.g., when vehicle **120** is in a predetermined range of vehicle **116** such as 50 feet, 100 feet or 200 feet).

In some implementations, warning generation application **408** may receive a new warning message indicating another instance of aberrant driving behavior of vehicle **118**. The other instance may have occurred prior to the instance perceived by user **122**. In some implementations, warning generation application **408** may calculate a risk parameter of vehicle **118** based on the new warning message and the warning message previously received, and then provide information of vehicle **118** to computing system **104**, which may determine whether or not to report to an authority. For instance, warning generation application **408** may generate and transmit a report to computing system **104**, which may determine whether or not to provide the report to an authority, e.g., Department of Motor Vehicles, regarding the aberrant driving behaviors of vehicle **118**.

FIG. **5** illustrates an example process **500** implementing an embodiment in accordance with the present disclosure. Example process **500** may correspond to one of various implementation scenarios based on example environment **100**, and is provided solely for illustrative purpose so that those skilled in the art may better appreciate benefits and advantages provided by the present disclosure. Therefore, the scope of the present disclosure is not limited by example process **500**. For illustration purpose and not limiting the scope of the present disclosure, the description of example process **500** is provided below in the context of implementation using one or more processors **202** of computing system **104**. Example process **500** may begin at **502**.

At **502**, one or more processors **202** may provide one or more driving scenarios involving one or more aberrant driving behaviors to user **112**. In some implementations, one or more processors **202** may provide one or more simulations of the one or more driving scenarios involving the one or more aberrant driving behaviors through a simulation system. In other implementations, computing system **104** may facilitate real-world experiments to which user **112** is subjected. Example process **500** may proceed from **502** to **504**.

At **504**, one or more processors **202** may receive data indicative of a response of user **112** to the one or more driving scenarios. In some implementations, the one or more responses may include signals each of which indicating a response to an aberrant driving behavior from user **112** under a simulated condition. In some implementations, one or more processors **202** may monitor user **112** to collect data of the one or more responses and the one or more driving scenarios. The data of one or more responses may include, for example, a measurement of one or more auxiliary signals associated with one or more physical parameters (e.g., a heart rate, a breath rate and/or a degree of perspiration) of user **112**. Example process **500** may proceed from **504** to **506**.

At **506**, one or more processors **202** may cluster the data of one or more responses of user **112** to generate one or more feature classifier **110**. The one or more feature classifiers **110** may include, for example, one or more template motion plans or one or more actions associated with one or more aberrant driving features or one or more aberrant driving profiles. In some implementations, the one or more aberrant driving features are associated with one or more driving behaviors including at least one of the following: failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary, driving into oncoming traffics and exceeding a speed limit. The one or more aberrant driving profiles may include, for example, at least one of the following: swerving, skidding, oscillating laterally, deviation from a lane center for more than a threshold period of time (e.g., 5 seconds, 10 seconds, 15 seconds, 30 seconds or a user-definable duration), lane changing without proper clearance, erratic speed control, erratic braking and off-nominal confluence with a traffic flow. Example process **500** may proceed from **506** to **508**.

At **508**, one or more processors **202** may transmit the one or more feature classifiers **110** to one or more vehicles including vehicle **116**. Using the one or more feature classifiers **110**, user **122** may report one or more perceived

aberrant driving behaviors of vehicle **118**. If a perceived aberrant driving behaviors is confirmed according to the one or more feature classifiers **110**, a warning message may be generated and transmitted to vehicle **120**, which is in the vicinity of vehicle **118** and/or vehicle **116**.

In some implementations, the one or more classifiers may include one or more classifiers trained using either or both of a simulation driving scenarios and real-world experiments. Additionally or alternatively, the one or more classifiers may include one or more template motion plans, one or more actions associated with one or more aberrant driving features, one or more aberrant driving profiles, or a combination thereof. In some implementations, the one or more aberrant driving features may be associated with driving behaviors that include at least one of failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary, driving into oncoming traffic, or exceeding a speed limit. In some implementations, the one or more aberrant driving profiles may include at least one of swerving, skidding, oscillating laterally, deviation from a lane center for more than a threshold period of time, lane changing without proper clearance, erratic speed control, erratic braking, or off-nominal confluence with a traffic flow.

In some implementations, example process **500** may further involve transmitting the warning message to at least a third vehicle that satisfies a user-defined metric with respect to the first vehicle.

In some implementations, example process **500** may further involve a number of operations, including: receiving an additional warning message indicating an additional instance of aberrant driving of the second vehicle, the additional instance occurring prior to the instance; calculating a risk parameter of the second vehicle based on the additional warning message and the warning message; and generating a report regarding the aberrant driving of the second vehicle. In some implementations, the additional warning message may include the information of the second vehicle and one or more warning messages regarding the second vehicle.

In some implementations, in determining that the instance has occurred using the one or more classifiers, example process **500** may perform a number of operations, including: determining a parameter using the one or more classifiers, the parameter indicating a possibility that the instance of aberrant driving occurs within a predetermined window of time after receiving the message; and determining that the instance occurs in an event that the parameter is greater than a predetermined value.

In some implementations, the warning message may include an encoded license plate number of the second vehicle, a description of the second vehicle, or a combination thereof.

FIG. **6** illustrates an example process **600** implementing an embodiment in accordance with the present disclosure. Example process **600** may correspond to one of various implementation scenarios based on example environment **100**, and is provided solely for illustrative purpose so that those skilled in the art may better appreciate benefits and advantages provided by the present disclosure. Therefore, the scope of the present disclosure is not limited by example process **600**. For illustration purpose and not limiting the scope of the present disclosure, the description of example process **600** is provided below in the context of implementation using one or more processors **402** of computing system **124**. Example process **600** may begin at **602**.

At **602**, one or more processors **402** may receive a message from user **122** of vehicle **116**, e.g., a driver or a passenger sitting in vehicle **116**. The message may indicate an instance of aberrant driving of vehicle **118**. Example process **600** may proceed from **602** to **604**.

At **604**, one or more processors **402** may determine a parameter indicating a possibility that the instance of aberrant driving has occurred within a predetermined window of time after receiving the message from user **122**. In some implementations, one or more processors **402** may determine the parameter using the one or more feature classifiers **110**. Example process **600** may proceed from **604** to **606**.

At **606**, one or more processors **402** may determine whether the value of the parameter is greater than a threshold value. In an event that it is determined that the value of the parameter is greater than the threshold value (corresponding to the "YES" branch out of operation **606**), example process **600** may proceed to **608**. In an event that it is determined that the value of the parameter is less than or equal to the threshold value (corresponding to the "NO" branch out of operation **606**), example process **600** may proceed to **610**.

At **608**, one or more processors **402** may determine that the instance of aberrant driving has occurred. Example process **600** may proceed from **608** to **612**.

At **610**, one or more processors **402** may generate an error massage and provide the message to user **122**.

At **612**, one or more processors **402** may receive information of vehicle **118**. The information of vehicle **118** may be collected or obtained using one or more sensors installed on vehicle **116** (e.g., vision device(s), camera(s), a LIDAR system or a RADAR system) to provide to one or more processors **402** estimated data of vehicles in the vicinity, including vehicle **120**.

At **614**, one or more processors **402** may generate a warning message based on the received information of vehicle **118**. For example, the warning message may include an encoded license plate number or a description of vehicle **118**.

At **616**, one or more processors **402** may transmit the warning message to vehicle **120**. For example, user **122** and the driver of vehicle **120** may belong to a network, which facilitates message sharing within the network.

In some implementations, in providing the one or more driving scenarios, example process **600** may involve providing one or more simulations of the one or more driving scenarios through a simulation system.

In some implementations, in receiving the data indicative of a response of the user to the one or more driving scenarios, example process **600** may involve receiving a measurement of one or more physical parameters of the user as a response to the one or more aberrant driving behaviors under a simulated condition.

In some implementations, in the one or more classifiers may include one or more template motion plans or one or more actions associated with one or more aberrant driving features. Moreover, the one or more aberrant driving features may be associated with one or more driving behaviors that include at least one of failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary, driving into oncoming traffic, or exceeding a speed limit.

In some implementations, in the one or more classifiers may include one or more template motion plans or one or more actions associated with one or more aberrant driving profiles. Additionally, the one or more aberrant driving profiles may include at least one of swerving, skidding, oscillating laterally, deviation from a lane center for more

than a threshold period of time, lane changing without proper clearance, erratic speed control, erratic braking, or off-nominal confluence with a traffic flow.

The articles "a" and "an" are used herein to refer to one or to more than one (i.e., to at least one) of the grammatical object of the article. By way of example, "a user" means one user or more than one users. Reference throughout this specification to "one embodiment," "an embodiment," "one example," or "an example" means that a particular feature, structure, or characteristic described in connection with the embodiment or example is included in at least one embodiment of the present disclosure. Thus, appearances of the phrases "in one embodiment," "in an embodiment," "one example," or "an example" in various places throughout this specification are not necessarily all referring to the same embodiment or example. Furthermore, the particular features, structures, databases, or characteristics may be combined in any suitable combinations and/or sub-combinations in one or more embodiments or examples. In addition, it should be appreciated that the figures provided herewith are for explanation purposes to persons ordinarily skilled in the art and that the drawings are not necessarily drawn to scale.

Embodiments in accordance with the present disclosure may be embodied as an apparatus, method, or computer program product. Accordingly, the present disclosure may take the form of an entirely hardware-comprised embodiment, an entirely software-comprised embodiment (including firmware, resident software, micro-code or the like), or an embodiment combining software and hardware aspects that may all generally be referred to herein as a "circuit," "module," or "system." Furthermore, embodiments of the present disclosure may take the form of a computer program product embodied in any tangible medium of expression having computer-usable program code embodied in the medium.

The flow diagrams and block diagrams in the attached figures illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer program products according to various embodiments of the present disclosure. In this regard, each block in the flow diagrams or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It will also be noted that each block of the block diagrams and/or flow diagrams, and combinations of blocks in the block diagrams and/or flow diagrams, may be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions. These computer program instructions may also be stored in a computer-readable medium that can direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer-readable medium produce an article of manufacture including instruction means which implement the function/act specified in the flow diagram and/or block diagram block or blocks.

Although the present disclosure is described in terms of certain embodiments, other embodiments will be apparent to those of ordinary skill in the art, given the benefit of this disclosure, including embodiments that do not provide all of the benefits and features set forth herein, which are also within the scope of this disclosure. It is to be understood that other embodiments may be utilized, without departing from the scope of the present disclosure.

The invention claimed is:

1. A method, comprising:

providing, by one or more processors, one or more driving scenarios involving one or more aberrant driving behaviors to a user;

receiving, by the one or more processors, data indicative of a response of the user to the one or more driving scenarios;

clustering, by the one or more processors, the data to generate one or more classifiers; and

transmitting, by the one or more processors, the one or more classifiers to one or more vehicles,

wherein the clustering of the data to generate the one or more classifiers comprises generating the one or more classifiers using a first set of features including rules of road infractions and a second set of features including profiles exhibited by observed vehicles.

2. The method of claim **1**, wherein the providing of the one or more driving scenarios comprises providing one or more simulations of the one or more driving scenarios through a simulation system.

3. The method of claim **1**, wherein the receiving of the data indicative of a response of the user to the one or more driving scenarios comprises receiving a measurement of one or more physical parameters of the user as a response to the one or more aberrant driving behaviors under a simulated condition.

4. The method of claim **1**, wherein the one or more classifiers comprise one or more template motion plans or one or more actions associated with one or more aberrant driving features, and wherein the one or more aberrant driving features are associated with one or more driving behaviors comprising at least one of failure to signal a turn, failure to stop at an appropriate signal, proceeding without right of way, crossing a solid lane boundary, driving into oncoming traffic, or exceeding a speed limit.

5. The method of claim **1**, wherein the one or more classifiers comprise one or more template motion plans or one or more actions associated with one or more aberrant driving profiles, and wherein the one or more aberrant driving profiles comprise at least one of swerving, skidding, oscillating laterally, deviation from a lane center for more than a threshold period of time, lane changing without proper clearance, erratic speed control, erratic braking, or off-nominal confluence with a traffic flow.

* * * * *