US010640961B2

(12) **United States Patent**
Hutchinson et al.

(10) **Patent No.: US 10,640,961 B2**
(45) **Date of Patent: May 5, 2020**

(54) **WATER CONSERVATION BASED ON TOILET SEAT POSITION**

(71) Applicant: **Gmat Ventures, LLC**, Salt Lake City, UT (US)

(72) Inventors: **Steven R. Hutchinson**, Highland, UT (US); **Troy A. Holbrook**, Holladay, UT (US); **Scott A. Holbrook**, Salt Lake City, UT (US); **Christopher J. Knapp**, Salt Lake City, UT (US)

(73) Assignee: **Gmat Ventures, LLC**, Salt Lake City, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 484 days.

(21) Appl. No.: **14/135,249**

(22) Filed: **Dec. 19, 2013**

(65) **Prior Publication Data**

US 2014/0165278 A1 Jun. 19, 2014

Related U.S. Application Data

(60) Provisional application No. 61/739,395, filed on Dec. 19, 2012.

(51) **Int. Cl.**
E03D 3/12 (2006.01)
E03D 5/04 (2006.01)

(52) **U.S. Cl.**
CPC ***E03D 3/12*** (2013.01); ***E03D 5/04*** (2013.01); *Y10T 29/49428* (2015.01)

(58) **Field of Classification Search**
CPC E03D 3/12; E03D 5/04; E03D 5/10; Y10T 29/49428; A47K 13/10; A47K 13/302
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

550,006 A * 11/1895 Osborn E03D 5/04 138/28
941,895 A * 11/1909 Straw E03D 3/10 4/250

(Continued)

FOREIGN PATENT DOCUMENTS

JP 11-166258 6/1999
JP 2002-339430 11/2002

(Continued)

OTHER PUBLICATIONS

JP 2002339430 Machine Translation.*


(Continued)

Primary Examiner — Christine J Skubinna
(74) *Attorney, Agent, or Firm* — Patent Law Works LLP

(57) **ABSTRACT**

Various embodiments for conserving fluid based on the position of a toilet seat are presented. One example embodiment includes a toilet flushing system having a fluid regulation component and a position detector. The fluid regulation component is configured to regulate an amount of fluid used to flush a toilet during a flush cycle. The position detector is configured to detect whether the toilet seat is in a raised position or a lowered position. The position detector is coupled to the fluid regulation component to communicate whether the toilet seat is in the raised position or the lowered position. The fluid regulation component is further configured to regulate the amount of fluid used during the flush cycle based at least in part on whether the toilet seat is in the raised position or the lowered position.

13 Claims, 20 Drawing Sheets



(58) **Field of Classification Search**
USPC 4/324, 249–250, 335
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,080,669	A *	3/1978	Biggerstaff	E03D 1/144 4/325
5,187,818	A *	2/1993	Barrett, Sr.	E03D 5/105 4/304
5,504,947	A	4/1996	Robello et al.	
6,351,856	B1	3/2002	Browne	
6,907,621	B2	6/2005	Stemen	
8,566,970	B2	10/2013	Collignon	
8,997,268	B2 *	4/2015	Miller	E03D 5/10 4/313
2007/0056084	A1 *	3/2007	Watt	A47K 13/10 4/246.1
2007/0089223	A1	4/2007	Andersen	
2008/0178374	A1	7/2008	Abrams	
2011/0010831	A1	1/2011	Lee	

FOREIGN PATENT DOCUMENTS

JP	2002339430	A *	11/2002	
JP	2004-298275		10/2004	
KR	10-2000-0024390		5/2000	
WO	WO-2008107682	A2 *	9/2008	A47K 13/10

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2013/057719, dated Feb. 7, 2014, 14 pages.
FlusherUp Executive Summary, pictures of toilets, Aug. 22, 2012, 1 pg.
International Search Report and Written Opinion for PCT/US2013/076730, dated Apr. 14, 2014, 14 pages.

* cited by examiner




Figure 1A




Figure 1B




Figure 2A




Figure 2B




Figure 2C




Figure 2D



G
C
104a
117
116a
114a
217
218
B
220
210
230
209
234
234b
D
234a
226
228
225
227
222
P
D
224
212
E
208
234
234b
D
252
D
232
234a

Figure 3




Figure 4A




Figure 4B




Figure 4C




Figure 4D




Figure 5B




Figure 5A




Figure 6




Figure 7A




Figure 7B



764
714c
766
240
712c
710c
506c
242
756
752
756
755
754
758
752
702c

Figure 7C





Figure 8

Figure 9






Figure 10A




Figure 10C




Figure 10B




Figure 10E




Figure 10D

WATER CONSERVATION BASED ON TOILET SEAT POSITION

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit under 35 U.S.C. § 119(e) of U.S. Provisional Application No. 61/739,395, "Water Conservation Based on Toilet Seat Position", filed on Dec. 19, 2012, the entire contents of which are incorporated herein by reference.

BACKGROUND

Technical Field

The present disclosure relates to toilets. In particular, the present disclosure relates to conserving fluid used to flush a toilet during a flush cycle based on the position of the toilet seat.

Description of the Related Art

Some existing solutions for conserving water used by toilets are not satisfactorily practical solutions because each is overly complicated, expensive, ineffectual, and/or requires user courtesy and action—all factors contributing to such solutions not being used or being used inconsistently or improperly.

SUMMARY

Technology for a fluid conservation system that automatically adapts the amount of fluid used to flush a toilet during a flush cycle based on a position of the toilet seat is described. According to one innovative aspect of the subject matter described in this disclosure, a toilet flushing system includes a fluid regulation component and a position detector. The fluid regulation component is configured to regulate an amount of fluid used to flush a toilet during a flush cycle. The position detector is configured to detect whether the toilet seat is in a raised position or a lowered position. The position detector is coupled to the fluid regulation component to communicate whether the toilet seat is in the raised position or the lowered position. The fluid regulation component is further configured to regulate the amount of fluid used during the flush cycle based at least in part on whether the toilet seat is in the raised position or the lowered position.

These and other embodiments may each optionally include one or more of the following features. For instance, the toilet flushing system may include that the position detector includes a position detector that is configured to transmit the position of the toilet seat to the fluid regulation component; that the fluid regulation component is locatable downstream of a flush valve of a toilet, locatable upstream of a flush valve of the toilet, is incorporateable into a flush valve of the toilet, or is incorporated into the position detector; that the fluid regulation component includes a valve situated in a fluid regulation chamber; that the valve is configured to control the amount of fluid that passes through the fluid regulation chamber during a flush cycle based on whether the toilet seat is in the raised position or the lowered position; that the position detector includes an optical sensor; that the optical sensor is electronically coupled to the fluid regulation component and the fluid regulation component is electronically actuateable; that the position detector includes a mechanical assembly connectable to the toilet seat and connectable to the flow regulation component; that the mechanical assembly is configured to transmit a movement of the toilet seat from the toilet seat to the flow regulation component when the toilet seat is raised from the lowered position to the raised position or when the toilet seat is lowered from the raised position to the lowered position; that the position detector is coupleable to the toilet seat; the toilet includes a tank or the toilet is a tankless toilet; a flush valve of the toilet includes the flow regulation component; a toilet seat raising and lowering device for raising and the lowering the toilet seat; that the position detector is included in the toilet seat raising and lowering device and includes a sensor for sensing a position of the toilet seat.

According to another innovative aspect of the subject matter described in this disclosure, a flow regulation component includes a valve including one or more regulating components for regulating a flow of a fluid for flushing a toilet based on a position of a toilet seat of the toilet. The valve includes an input portion configured to receive an input from a position detector. The position detector communicates whether the toilet seat is located in a raised position or a lowered position.

These and other embodiments may each optionally include one or more of the following features. For instance, the flow regulation component may include that the valve is coupleable to an upstream side or downstream side of a flush valve of a toilet; that the valve is incorporated into the flush valve of the toilet; and that the input is an electronic input or a mechanical input.

According to another innovative aspect of the subject matter described in this disclosure, a method may include equipping a toilet with a flow regulation component, the flow regulation component configured to regulate the flow of a fluid for flushing the toilet based whether a toilet seat of the toilet is in the raised or lowered position; and equipping the toilet with a position detector, the position detector configured to determine whether a toilet seat of the toilet is in a raised or lowered position, the position detector configured to communicate a position of the toilet seat to the flow regulation component.

These and other embodiments may each optionally include one or more of the following features. For instance, the method may include that equipping the toilet with the position detector includes coupling the position detector proximate the toilet seat; that the position detector includes a sensor and equipping the toilet with the position detector includes attaching the position detector on a structural member included in or around the toilet in a location that gives the position detector a line of sight to a top surface of the toilet seat or to a patron using the toilet; that equipping the toilet with the flow regulation component includes attaching the flow regulation component upstream or downstream of a flush valve of the toilet; and that the toilet includes a tank or the toilet is a tankless toilet.

Other embodiments of one or more of these aspects include corresponding systems, apparatus, and methods.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure is illustrated by way of example, and not by way of limitation in the figures of the accompanying drawings in which like reference numerals are used to refer to similar elements.

FIGS. **1**A and **1**B are block diagrams of an example toilet seat raising and lowering device.

FIGS. **2**A-**2**D are perspective views of example toilets equipped with an example toilet seat raising and lowering device.

FIG. **3** is a front cross-sectional view showing the internal components of an example toilet seat raising and lowering device.

FIGS. **4**A-**4**D are top perspective, bottom perspective, left, and exploded views of an example toilet seat raising and lowering device.

FIGS. **5**A and **5**B are block diagrams of example toilet flushing fluid conservation systems.

FIG. **6** is a side perspective view of an example toilet flushing fluid conservation system.

FIGS. **7**A and **7**B are bottom perspective and top transparent perspective views of an example position unit.

FIG. **7**C is a side perspective view of a flush valve and vertical pipe equipped with another example position unit and a side view of another example position detector.

FIG. **8** is an exploded view of an example toilet seat raising and lowering device that includes a fastenable regulation device.

FIG. **9** is an example diagram showing the detection of various positions of a toilet seat or patron using an optical sensor.

FIG. **10**A is a front perspective view of an example toilet tank equipped with an example position unit.

FIGS. **10**B-**10**E are front perspective views of the example position units according to various configurations.

DETAILED DESCRIPTION

FIGS. **1**A-B are block diagrams of example toilet seat raising and lowering device **100**. In particular, FIG. **1**A is a block diagram of the example toilet seat raising and lowering device **100** that includes a movement source **104**, a movement transmission mechanism **108**, and a toilet seat **112**. The toilet seat **112** is coupled to a toilet (not shown) having a toilet bowl and can be raised from a lowered position to a raised position and lowered from the raised position to the lowered position. In some embodiments, the toilet seat **112** is pivotably connected to the toilet to move between the raised and lowered positions. In the lowered position, the toilet seat **112** may come in contact with and be situated substantially parallel to a top surface of the toilet bowl, and in the raised position, may be substantially perpendicular to the top surface of the toilet bowl. The toilet seat **112** may have a variety of shapes or sizes depending on the configuration of the toilet. For instance, the toilet seat **112** may be flat, contoured for comfort, round, elongated, padded, heated, have an open front, include contact elements situated on a toilet-bowl facing surface for contact with the toilet bowl when in a lowered position, may or may not be accompanied by a lid that is hinged for closure when the toilet is not in use, etc. The toilet seat **112** may be made of any material or combination of materials, including plastic, wood, metal, etc.

The movement source **104** is a device for generating force to automatically raise the toilet seat from a lowered position to a raised position. The movement source **104** can generate force based on an input **102**. In some embodiments, the movement source **104** may receive the input **102** to raise the toilet seat **112** responsive to the toilet being flushed. For instance, in a fluid-based embodiment, the opening of a flush valve of the toilet (not shown) may flow fluid through the movement source **104**, which is converted by the movement source **104** into force **106** that is transferred by the movement transmission mechanism **108** to the toilet seat **112** to raise it from a lowered position to a raised position. In another example, the movement source **104** may be electrically-based (e.g., an electric motor) and may receive an electrical input signal signaling it to generate force **106** to raise the toilet seat **112** when the toilet is flushed.

The input **102** can be any form of energy (e.g., kinetic, electrical, thermal, potential, electromagnetic, electrochemical, etc.) that the movement source **104** can convert into force **106**. For example, the input **102** may be one or more of a fluid flow and/or fluid pressure (e.g., hydraulic, pneumatic, etc.), an electric current, heat transfer, mass and/or velocity of a physical object (e.g., gear assembly, kinematic assembly, etc.), a combination of the foregoing, etc. In a further example, the movement source **104** may be a fluid-based actuator, such as the actuator **104**A discussed below with reference to FIGS. **2**A-**4**D, and may convert a fluid flow/pressure differential into the movement. Further non-limiting examples of a movement source **102** include an electric motor, a pneumatic actuator, a hydraulic actuator, a relay, a spring, a counterweight, one or more gears, a combustion or thermal-based engine, etc., that can be used to generate the movement.

For instance, an example embodiment of a torsion-based seat raising and lowering device **100** may include a tension spring assembly, a dampener assembly, and a clasp assembly as a movement source **104**, a lever as a movement transmission mechanism **108**, and a mounting bracket. The lever may be coupled to the mounting bracket for rotation about the longitudinal axis of the mounting bracket. The mounting bracket can attach the device proximate the toilet bowl, such as the edge of a toilet bowl proximate the rear side where the toilet seat is mounted to the toilet bowl. The lever may be configured to pivot at a base in a rotational plane parallel to that of the toilet seat and apply pressure to the toilet seat to automatically articulate the toilet seat to a raised position by force from a tension spring assembly enclosed in the base. The toilet seat lid may be articulated alone or with its lid. The device may include a clasp assembly component for retaining the toilet seat in the lowered position when first lowered until subsequent pressure is applied to the toilet seat and then removed such as where a patron sits on the toilet seat and then rises.

An example embodiment of a counter-weight-based seat raising and lowering device **100** may include a fluid-based actuator as a movement source **104** and, as a transmission mechanism **108**, may include a counter-weight mechanism held by a latch and a lever arm connected to the counter-weight mechanism. The fluid based actuator may include an inlet and outlet substantially similar to the actuator **104***a*, where, upon opening of the flush valve of the toilet, the fluid flow through the actuator can trigger the latch, thus releasing the counter-weight mechanism, which moves along a predetermined path to move the lever arm to raise the toilet seat to the raised position. In an alternative example, the movement source **104** may be electric and may be triggered by an electric signal provided by the flush valve of the toilet when the flush valve has been triggered or opened. It should be understood that numerous other variations and embodiments are also possible, contemplated and within the scope of the present disclosure.

The movement source **104** may, in some embodiments, include a regulator to control or regulate the amount of force applied to the toilet seat **112** to raise or lower it. For example, in an embodiment where the movement source **104** is fluid-based, the movement source **104** may include one or more of a pressure-reduction chamber, a bleed valve, a throttle valve, a reduction valve, a tube with adjustable inlet

and outlet orifices, and the like to adapt the force **106** (e.g., pressure) being applied to the movement transmission mechanism **108**.

The movement transmission mechanism **108** is a mechanism for transmitting/transferring/exerting the force **106** generated by the movement source **104** to the toilet seat **112** to raise it. In some embodiments, the movement transmission mechanism **108** includes a mechanical device or assembly that is coupled to the movement source **104** to receive the force/movement **106** generated thereby and connected to the toilet seat **112** to transmit the force **106** to the toilet seat **112** to raise it.

The movement transmission mechanism **108** can convert, reduce, or otherwise alter the force **106** (e.g., movement) being transmitted to raise the toilet seat **112** in a controlled manner. For instance, the movement transmission mechanism **108** may adapt the force **106** being applied to the toilet seat **112** so it does not slam into the other components of the toilet, such as a tank or a pipe, when raised.

When lowering the toilet seat **112**, the movement transmission mechanism **108**, in cooperation with the movement source **104**, can also adapt the force **106** being applied to the toilet seat **112** to prevent it from slamming onto the toilet bowl. The closure of the toilet seat **112** may be controlled by a relatively weaker counter-force simultaneously applied to the movement transmission mechanism **108** by the movement source **104**. In some embodiments, the counter force is resistance created by the movement source **104** when operated in reverse by the movement transmission mechanism **108** using the force produced by the lowering of the toilet seat **112** (e.g., the acceleration of the toilet seat produced by gravity during lowering of the toilet seat **112**).

FIG. **1**B depicts a block diagram of an example movement transmission mechanism **108**. As depicted, the movement transmission mechanism **108** may further include a lifting and lowering mechanism **114** and a seat coupling device **116** coupled together to provide the functionality of the movement transmission mechanism **108**. In some embodiments, the lifting and lowering mechanism **114** and the seat coupling device **116** may be integrated into a single component or set of components. In other embodiments, the lifting and lower mechanism **114** may be connected. For instance, the lifting and lowering mechanism **114** and the seat coupling device **116** may be fastened together using a fastener, attached via a detachable or permanent coupling, and the like. In any of the forgoing embodiments, the lifting and lowering mechanism **114** and the seat coupling device **116** are attached in such a way that force **106** (e.g., movement) may be transmitted between the movement source **104** and the toilet seat **112** to raise and lower it.

The lifting and lowering mechanism **114** may be connected to the movement source **104** to receive the force **106** generated by the movement source **104** and transmit the force **106** to the seat coupling device **116**, which then applies the force **106** to the toilet seat **112** to raise it. As a further example, the lifting and lowering mechanism **114** may be pushed along a predetermined trajectory by a pressurized fluid flowing through the movement source **104**, and in turn, may pivot the seat coupling device **116** from a lowered position to a raised position to raise the toilet seat **112**. In some embodiments, the lifting and lowering mechanism **114** may include the cable and piston assembly **114***a* discussed below with reference to at least FIGS. **3** and **4**D.

The seat coupling device **116** is a device for coupling with and lifting and lowering the toilet seat **112**. In some embodiments, the seat coupling device **116** may be positioned in a manner that allows it to contact a surface of the toilet seat **112** that faces the toilet bowl when lowered and to raise the toilet seat **112** into the raised position. The seat coupling device **116** may be adjustable to accommodate any configuration of toilet or toilet seat. In some embodiments, a proximal end of the seat coupling device **116** may be connected to a distal end of the lifting and lowering mechanism **114**, and a distal end of the seat coupling device **116** may interface with the toilet seat **112** to raise and lower it using the force **106** transmitted to the seat coupling device **116** by the seat coupling mechanism **114**.

The seat coupling device **116** may have numerous different configurations. For instance, the seat coupling device **116** may couple to the toilet seat **112** by coming in and out of contact with one or more surfaces of the toilet seat **112**, the seat coupling device **116** may be integrated with the toilet seat **112** and connect to the lifting and lowering mechanism **114** to receive and transmit force **106** (e.g. movement), the seat coupling device **116** may include one or more couplings and/or fasteners and may detachably couple the lifting and lowering mechanism **114** to the toilet seat **112**, etc. A further example of the seat coupling device **116** may include the lever arm **116***a* discussed in further detail below. In other embodiments, the seat coupling device **116** may be eliminated and the lifting and lowering mechanism **114** may be integrated with the toilet seat **112**.

In some embodiments, the intensity and/or speed used to raise or lower the toilet seat **112** may depend upon the net amount of pressure or force **106** that is transmitted via the movement transmission mechanism **108** between the toilet seat **112** and the movement source **104**. If the net amount of force **106** is high, then the movement transmission mechanism **108** may lift or close the toilet seat **112** quickly. Conversely, if the amount of force **106** is low, the movement transmission mechanism **108** may raise or lower the toilet seat **112** slowly. In some embodiments, the magnitude and/or direction of the force **106** may be adapted as discussed elsewhere herein. In these or other embodiments, the movement transmission mechanism **108**, such as the lifting and lowering mechanism **114** and/or the seat coupling device **116** may include force regulation components, such as magnets, magnetic materials (e.g., metals), regulators, springs, counter-weights, resistance elements such as grommets, washers, and the like, to adjust the force **106** being using used to raise or lower the toilet seat **112**.

FIGS. **2**A and B are perspective views of an example toilet **200**. In particular, FIGS. **2**A and B collectively show a toilet **200** including a toilet bowl **202**, the toilet seat **112**, a tank **204**, and an example toilet seat raising and lowering device **100**. The seat raising and lowering device **100** depicted in FIGS. **2**A and **2**B includes a mounting bracket **206** attached stationary to an example instance of a movement source **104** termed an actuator **104***a*. In some embodiments, the mounting bracket **206** may be attached to the actuator **104***a* using any suitable fastening means, such as fasteners, welds, and the like. In other embodiments, the mounting bracket **206** may be integrated with the actuator **104***a* or the actuator **104***a* may attach directly to and/or be integrated into the toilet bowl **202**, the toilet seat **112**, or the tank **204** without the use of the mounting bracket **206**.

In the depicted embodiment, the mounting bracket **206** attaches to the toilet bowl **202** in between the toilet seat **112** and the toilet bowl **202**. More particularly, the mounting bracket **206** can be configured to attach to the toilet **200** via one or more mounting points used to attach the toilet seat **112** to the toilet **200**. In some embodiments, the mounting bracket **206** may be about four to six inches long and about 1 to 2 inches wide and include two holes or u-shaped slots

about four to six inches apart where the mounting bracket **206** can be attached to the toilet bowl **202** via the connection points and/or fasteners that connect the toilet seat **112** to the toilet **200**. In other embodiments, the mounting bracket **206** may be configured to connect to another component of the toilet **200**, such as the tank **204**, an underside surface of the toilet bowl **202**, the toilet seat **112**, or the like.

The lever arm **116***a* can attach to the actuator **104***a* and extend out from a housing **208** of the actuator **104***a* along a surface **112***a* of the toilet seat **112**. The lever arm **116***a* can be attached to the actuator **104***a* in a fashion allowing the lever arm **116***a* to contact the toilet seat **112** and move between a lowered position B and a raised position C as indicated by arrow A. In some embodiments, the lever arm **116***a* ranges from about one to six inches long and an eighth to a half inch wide and extends from the actuator **104***a* so that it may run adjacent to, and may come in contact with, the toilet seat **112**. In some embodiments, the lever arm **116***a* may be j-shaped and may be inserted into two holes **117** of the pulley **218** for additional strength and rigidity when pressing against the toilet seat to raise or lower it, as depicted in FIG. **4**D. In some embodiments, the lever arm **116***a* may be u-shaped (not shown) and may be inserted into two or more holes **117** of the pulley **218** and extend adjacent to the toilet seat **112** to provide additional rigidity and strength when pressing against the toilet seat **112** to raise or lower it. However, while the above embodiments are provided, it should be understood that the lever arm **116***a* may have numerous different configurations. For example, the lever arm **116***a* may be or include a fastener that connects the actuator cable and piston assembly **114***a* depicted in FIG. **3** to the toilet seat **112**. Further, in some embodiments, the lever arm **116***a* may be eliminated or integrated into the toilet seat **112**.

The toilet seat **112** can be pivotably fastened to the toilet bowl **202** and may pivot (e.g., about a hinge) to positions C and B, respectively. In some embodiments, to raise the toilet seat **112** from position B to position C, the lever arm **116***a*, upon actuation, pivots in a rotational plane from position B to position C, thereby pressing against surface **112***a* of the toilet seat **112** and pivoting the toilet seat **112** about a pivot point (e.g., hinge) from position B to position C. Conversely, to lower the toilet seat **112** from position C to position B, upon actuation, the surface **112***a* of the toilet seat **112** rests against the lever arm **116***a* as it pivots in the rotational plane from position C to B, which slows the toilet seat **112**'s movement sufficiently to prevent it from slamming against the toilet bowl **202**, thus achieving a soft close.

While not depicted, in some embodiments, the lever arm **116***a* includes a tip, such as a wheel rotateably attached to the lever arm **116***a* at the distal end and configured to come into contact with and roll along the surface **112***a* when raising and lowering the toilet seat **112**. This is advantageous as it can reduce abrasions to the surface **112***a* of the toilet seat **112** caused by the lever arm **116***a* coming into contact with and rubbing against the toilet seat **112** during actuation. The lever arm **116***a* and its actuation are discussed in further detail below with reference to at least FIG. **3**.

FIG. **3** is a front cross-sectional view of an example actuator **104***a*. As depicted, the actuator **104***a* includes a bottom housing **208**, a top housing **209**, a piston housing **225**, and a regulation portion **227**, which are assembled together in a fluid-tight manner. For example, the piston housing **225** and the regulation portion **227** may be tubular in shape and are fitted in a fluid-tight manner into corresponding receiving portions of the top housing **209** and the bottom housing **208**. The bottom housing **208**, top housing **209**, and the piston housing **225** may cooperatively contain a cable and piston assembly **114***a* that forces the lever arm **116***a* to move as a result of pressurized fluid flowing through an inlet and outlet and pressing against the cable and piston assembly **114***a*. In some embodiments, the piston housing **225** may contain a piston chamber **226** and the regulation portion **227** may contain a regulation chamber **228**. The top housing **209** may include an inlet **210**, which connects to an inlet end of the piston chamber **226** and provides pressurized fluid into the piston chamber **226**, and the bottom housing **208** may include an outlet **212**, which connects to an outlet end of the piston chamber **226** and allows fluid to exit the actuator **104***a*. The piston chamber **226** and regulation chamber **228** may be connected at an inlet end via a connection pipe **230** and at an outlet end via a connection pipe **232**. The regulation portion **227** is configured to adjustably regulate the flow-rate through the regulation chamber **228** and thus the pressure P in the piston chamber **226**, as discussed in further detail below.

In the depicted embodiments, the housing **208** of the actuator **104***a* is injection molded using a polymer (e.g., thermoplastic, thermosetting plastic, elastomer, etc.) and is designed to have wall-thicknesses sufficient to withstand fluid pressures exceeding 100 psi. This is advantageous as it reduces the cost of the toilet seat raising and lowering device **100** while producing a toilet seat raising and lowering device **100** that is able to withstand fluid pressures that occur in residential and commercial applications, thus making the toilet seat raising and lowering device **100** well suited for use in a retrofit application on existing toilets **202** and toilet seat **112** assemblies. However, it should be understood that the housing **208** may be formed of any suitable materials (e.g., metal, wood, ceramic, composites, etc.) using any type of suitable manufacturing processes, including one or more of stamped, milled, cast, molded, etc. Moreover, while the actuator **104***a* is depicted as being made of distinct components, in these or other embodiments, the actuator **104***a* may be formed of a single component.

The cable and piston assembly **114***a* includes a pulley **218**, a cable **222**, and a piston **224**. As depicted, the pulley **218** is attached to one end of the cable **222** along an outer rim and is rotateably mounted to the housing **208** about a center axis. For example, as depicted in FIG. **4**D, the pulley **218** may be mounted to an axle **248** insertable into the top housing **209**. Further, the pulley **218** may be mounted to the axle **248** using a friction element that regulates the amount of force needed to rotate the pulley **218**. For example, a rubber grommet (not shown) may be inserted at a connection point between the pulley **218** and the axle **248** to increase the friction produced when rotating the pulley **218** around the axle **248**.

As depicted, the piston **224** is attached to the other end of the cable **222**. The cable **222** passes through an aperture of a seal **220**, such as an NPT O-ring plug, included in the top housing **209**. The seal **220** is situated between the pulley **218** and the piston **224** at the inlet end **210** of the piston chamber **226** and provides a fluid-tight seal between the cable **222** and the piston chamber **226** that can withstand high fluid pressures of substantially 100 psi or so and can prevent the fluid to leak out of the piston chamber **226**. The piston **224** is situated inside the piston chamber **226** and can slide along and form a circumferential seal therewith. In the depicted embodiment, the piston chamber **226**, the regulation chamber **228**, and the piston **224** are cylindrical in shape. However, it should be understood that these components may take other shapes and forms without departing from the scope of the present disclosure.

The lever arm **116***a* may be attached to the pulley **218** and rotate around the central axis **217** of the pulley **218** when the pulley **218** rotates. The pulley **218** may include a series of insertion points to receive and secure the lever arm **116***a*. This allows the lever arm **116***a* to be adjustably positioned to accommodate various different toilet and toilet seat configurations. For example, as depicted in FIG. **3**, the lever arm **116***a* may be inserted into the third of five insertion points **117** to accommodate an average-configured toilet seat. However, if the toilet **200** is instead equipped with toilet seat **112** with a larger gap between the toilet seat **112** and the toilet **200**, the lever arm **116***a* can be moved to a fourth, fifth, etc. insertion point **117** (from the left) to accommodate the larger gap or conversely the lever arm **116***a* can be moved to a first or second insertion point **117** to accommodate a smaller gap between the toilet seat **112** and the toilet **200**. In another example, the lever arm **116***a* may be u-shaped and have two ends inserted into two insertion points **117**, respectively (either directly adjacent or with one or more insertion points **117** spaced in-between). In yet another embodiment, where the lever arm **116***a* is eliminated or built into the toilet seat **112**, the various insertion points **117** in the pulley **218** may not be required and/or the pulley **218** may take other forms or be replaced by an equivalent component configured to pivot the toilet seat **112** between the lowered position and the raised position.

In the depicted embodiment, the actuator **104***a* can actuate the lever arm **116***a* to raise the toilet seat **112** as follows. When the toilet seat **112** is located in the lowered position B, the lever arm **116***a* is also in the lowered position B on an underside surface **112***a* of the toilet seat **112**, which further situates the piston **224** near the inlet end of the piston chamber **226**. A pressure differential between the inlet **210** and the outlet **212**, which can be created by the toilet **200** being flushed, causes fluid to enter through inlet **210** and flow through the chambers **226** and **228** of the actuator **104***a*, as illustrated by arrows D. By way of further illustration, in some embodiments, when the toilet **200** is flushed, water stored in the tank **204** (e.g., see FIG. **2**A) is released by a flush valve (not shown) into the bowl **202**. The tank **204** is then replenished via a fill valve (not shown) located in the tank **204** with fluid (e.g., water) supplied via inlet **214** (e.g., see FIG. **2**A). The inlet **210** is connected via a fluid line to the outlet **212** and the inlet **210** is connected to a pressurized fluid supply line (not shown). As such, when the flush valve is opened, fluid (e.g., water) flows through the actuator **104***a* thereby raising the toilet seat **112** as described above.

While some embodiments provided herein are described within the context of a toilet **200** equipped with a tank **204**, it should be understood that the seat raising and lowering device **100** is applicable to any type of toilet design including, for example, a tankless toilet. For instance, the seat raising and lower device **100** may be attached to a commercial toilet **200***a* that lacks a tank, as depicted in FIG. **2**C, and instead uses a flush valve **240** to gush a stream of fluid under high-pressure into the toilet bowl **202** to flush it. With further reference to FIG. **2**C, a vertical pipe **242** is situated between the flush valve **240** and the toilet bowl **202**, and includes a fluid supply nipple **244** and a fluid return nipple **246**, which are situated in-line (e.g., upstream or downstream of) with the flush valve **240**. The fluid supply nipple **244** is connected via a fluid supply line (not shown) to the inlet **210** of the actuator **104***a* and the outlet **212** is connected via a fluid return line (not shown) to the fluid return nipple **246**. When the toilet **200***a* is flushed by opening the flush valve **240**, pressurized fluid flows from fluid supply nipple **244** and supply line through the actuator **104***a* and back to the pipe **242** via the fluid return line and fluid return nipple **246**, thereby raising the toilet seat **112** as described above. The operation of the toilet seat **112** slow close is the same for a tankless toilet **200***a* as described herein in another embodiment of a toilet with a tank **204**.

The fluid flow through the actuator **104***a* increases the pressure P inside the piston chamber **226**, which moves the piston **224** downward as illustrated by arrow E. The downward movement of the piston **224** pulls the cable **222** downward through the seal **220** and rotates the pulley **218** in a counter-clockwise direction, as illustrated by arrow G. This counter-clockwise rotation presses the lever arm **116***a* against the toilet seat **112** and lifts it from the lowered position B to the raised position C. The bottom housing **208** may include a rest **252** which may stop the downward movement of the piston **224**. In this position, the pulley **218** and lever arm **116***a* cease rotating (provided they already haven't ceased rotating by the toilet seat **112** having reached the raised position). The rest **252** includes one or more through apertures configured to allow the fluid to flow freely from the connection pipe **232** to and through the outlet **212** (and thus through the actuator **104***a*) until the tank **204** has been replenished (and its fill valve (not shown) closes) or the fill valve **240** of the tankless toilet **200***a* closes. As the fluid flow ceases, the pressure at the inlet **210** and outlet **212** equalizes, thus equalizing the pressure P within the chambers of the actuator **104***a*.

The amount of pressure P that is generated within the piston chamber **226** when actuating the lever arm **116***a* can be regulated via the regulation portion **227** to control how much force is applied to raise the toilet seat **112**. This is advantageous because it can prevent the toilet seat **112** from slamming into the tank **204** or stressing the hinges when raised by the lever arm **116***a*, and thereby can reduce wear and tear and maintenance costs. It also allows the seat-lifting device **100** to be customized to satisfy the requirements of a variety of different toilet seat designs, as some toilets have seats that are light and open with little force, and other toilets have seats that are heavier and require more force to open.

The regulation portion **227** may include one or more regulators **234** for regulating the flow-rate of the fluid. In the depicted embodiment, the regulators **234** are two angled slots formed in the sidewall of the regulation portion **227** at locations adjacent to the connection pipes **230** and **232**, respectively. In this configuration, the regulation portion **227** is adapted to twist in place to change how the angled slots **234** align with the connection pipes **230** and **232**. This change in alignment changes the size of the openings connecting the chamber **228** to the connection pipes **230** and **232**, and thus increases or decreases the flow-rate of the fluid passing through the regulation portion **227**, and by extension, the actuator **104***a* generally. For example, a maximum flow-rate can be achieved by twisting the regulation portion/tube **227** to a position where outermost portions **234***a* of the slots **234** are aligned with the connection pipes **230** and **232**, respectively. Conversely, a minimum flow-rate can be achieved by twisting the tube **227** to a position where the innermost portions **234***b* are facing the connection pipes **230** and **232**, respectively. Further, a nearly infinite number of intermediate flow-rates may be achieved by twisting the tube **227** such that an intermediate portion of the angled slots **234** interface with the connection pipes **230** and **232**, respectively.

In other embodiments, the regulator **234** may be or include an adjustable bleed screw **235** that is insertable into the outlet end of a regulation chamber **228** to restrict flow through the regulation chamber **228** by blocking an orifice

leading to the connection pipe **232** and the outlet **212**, as depicted by FIG. **8**. In some embodiments, the insertion depth of the screw **235**, and thus, the amount by which the screw **235** restricts fluid flow through the regulation chamber **228**, can be adjusted by inserting a compatible tool (not shown) into the head of the screw **235** and rotating the screw **235**.

The more the regulator(s) **234** are configured to block the flow through the regulation chamber **228**, the higher the pressure P is during actuation of the lever arm **116***a*, and conversely, the less the regulator(s) **234** are configured to block the fluid flow through the regulation chamber **228**, the lower the pressure P during actuation of the lever arm **116***a* is during actuation.

The actuator **104***a* can cause the toilet seat **112** to close softly as follows. When a patron wishes to lower the toilet seat **112** from the upright position, the patron triggers lowering of the toilet seat **112** by moving it (e.g., pulling toward him/her). This initial movement presses the toilet seat **112** against the lever arm **116***a*, which in turn rotates the pulley **218** clockwise, pulls on the cable **222**, and begins moving the piston **224** from its resting position upward in the piston chamber **226** toward the inlet **210**. Force from the weight of the toilet seat **112** moves the lever arm **116***a* the remainder of the distance to the lowered position B. However, to prevent the toilet seat **112** from slamming against the toilet bowl **202**, the lever arm **116***a* resists against the movement of the toilet seat **112** to regulate its closure speed. This resistance is produced, at least in part, by the weight of the fluid in the piston chamber **226** above the piston **224** that is being displaced and the suction in the piston chamber **226** below the piston **224** caused by its upward movement. Resistance may also be produced by a rubber grommet (not shown) attached to the pulley **218** at the axle **248**.

The construction details of the seat raising and lowering device **100**, as shown in FIGS. **4**A-**4**D for example, are that the mounting bracket **206**, actuator **104***a*, lever arm **116***a*, regulator valve **234**, actuator cable and piston assembly **114***a*, and seal **220** may be made of plastic, rubber, metal, polymer, carbon, alloys or any combination thereof, or any other sufficiently rigid and strong material.

FIGS. **5**A and **5**B are block diagrams of example toilet flushing fluid conservation systems **500** and **550**, respectively. The systems **500** and **550** may include a toilet **502** having a flush valve **504** and a toilet seat **112**, as well as other elements that are not shown such as a tank or tankless configuration, a toilet bowl, etc., as discussed elsewhere here, such as with reference to FIG. **6**. The systems **500** and **550** also include position units **506***a* and **506***b* (also individually and collectively referred to herein as **506**). In some embodiments, the position unit **506** may be included with the toilet **502** as depicted by FIG. **5**A. In other embodiments, the position unit **506** may be included with the toilet seat raising and lowering device **100** as depicted by FIG. **5**B. The flush valve **504** may control the passage of the fluid used to flush the toilet **502**, and may be the same as or substantially similar to the flush valve **240** discussed elsewhere herein. The position unit **506** may detect what position the toilet seat **112** is in and communicate the toilet seat **112**'s position to regulate how much fluid (e.g., water) is passed by the flush valve **504** to flush the toilet **502**.

In systems **500** and **550**, if the toilet seat **112** is located in position C (see FIG. **2**B, for example), a male patron most likely deposited liquid waste (or mostly liquid waste) during his use of the toilet **502**. In contrast, if the toilet seat **112** is located in position B, the male patron likely deposited solid waste or a combination of solid and liquid waste during his use of the toilet **502**. As solid waste often requires more fluid to reliably flush, the position unit **506**, either independently or in cooperation with another component (e.g., the flush valve **504**), may permit more fluid to pass to flush the toilet **502** when the toilet seat **112** is in the lowered position B at the time the toilet **502** is flushed than when the toilet seat **112** is located in the raised position C. Conversely, the position unit **506**, either independently or in cooperation with another component, may permit less fluid to pass to flush the toilet **502** when the toilet seat **112** is in the raised position C during use than when the toilet seat **112** is located in the lowered position B. This is beneficial as significant amounts of water may be conserved over a prolonged period of use of the toilet **502**. For instance, in some embodiments, when the toilet seat **112** is in the raised position C, the system **500** or **550** may flush the toilet **502** using significantly less (e.g., 25%, 50%, or more) fluid (e.g., water) as compared to when the toilet seat **112** is located in the lowered position B. The gallons-per-flush (GPF) used by some conventional toilets can, in some cases, vary between 1 to 2 gallons. 1.1, 1.28, 1.6, are some more specific non-limiting examples of GPF rates. Equipped with the water conservation technology discussed herein, these GPS rates can be reduced by 25-50% or more, leading to significant savings in terms of cost and impact to the environment. For instance but not limitation, equipping a toilet with the position unit **506** could reduce the urine flush rate from 1.1-1.6 GPF to about 0.5-0.8 GPF.

An example method for producing or retrofitting a toilet with a position detector may include equipping a toilet with a flow regulation component and equipping the toilet with a position detector. As with other embodiments discussed herein, in this example method, the flow regulation component is configured to regulate the flow of a fluid for flushing the toilet based whether a toilet seat of the toilet is in the raised or lowered position, and the position detector is configured to determine whether a toilet seat of the toilet is in a raised or lowered position, and is configured to communicate a position of the toilet seat to the flow regulation component. In some cases, to equip the toilet with the position detector, the position detector may be coupled to the flow regulation component so the position detector can communicate the position of the toilet seat to the flow regulation component, the position detector may be coupled proximate the toilet seat. As noted elsewhere herein, the position detector may include a sensor (e.g., mechanical, electrical, optical, etc.) and equipping the toilet with the position detector may include attaching the position detector on a structural member included in or around the toilet in a location that gives the position detector a line of sight to a top surface of the toilet seat or to a patron using the toilet. In some cases to equip the toilet with the flow regulation component, the flow regulation component is attached upstream or downstream of a flush valve of the toilet.

FIG. **6** is a side perspective view of an example toilet flushing fluid conservation system **500**. As depicted in FIG. **6**, the toilet **502** may include a toilet seat **112**, a toilet bowl **202**, a flush valve **240**, a vertical pipe **242**, and a position unit **506***a* having a position detector **702** configured to interact with (e.g., connect, contact, otherwise directly or indirectly couple to) the toilet seat **112** to detect its position and communicate the position to a fluid flow regulation component, such as the regulation valve **710** depicted in FIGS. **7**A and **7**B, the flush valve **240**, or another component. In some embodiments, the position unit **506***a* may be situated proximate the toilet seat **112** along a flow path of the fluid used to flush the toilet **502**. For example, as depicted in FIG. **6**, the position unit **506***a* may be coupled to a bottom,

output end of the vertical pipe **242** so the vertical pipe **242** can pass the fluid through a restrictable fluid flow chamber **712** (see FIGS. **7**A and **7**B) of position unit **506***a* into the toilet bowl **202**.

In some embodiments, the position detector **702** may be a mechanism that physically detects the position of the toilet seat **112** through contact with it. For example, as depicted in FIG. **6**, the position detector **702** may protrude outwardly from a housing **714** of the position unit **506***a* to connect to or otherwise contact the toilet seat **112**. As a further example, the position detector **702** may be pivotably fastened to rear side of the toilet seat **112**, and may be configured to articulate in conjunction with the toilet seat **112** when the toilet seat **112** is raised or lowered, as discussed further below with reference to FIGS. **7**A and **7**B. In this way, when the toilet seat **112** is moved from a raised position to a lowered position (or vice versa), the movement triggers the position detector **702**, which in turn triggers a fluid flow regulation component, such as the regulation valve **710** depicted in FIGS. **7**A and **7**B, the flush valve **240**, or another component, to adjust how much fluid will be used when flushing the toilet **502**.

In some embodiments, the position unit **506** may be a retrofit component that is compatible with toilets that are already installed and in use. This is advantageous, as any existing toilet can be converted into one which conserves water by fitting the position unit **506** to it. In other embodiments, the toilet **502** may come pre-fitted with the position unit **506** or the position unit **506** may be integrated into the toilet **502**.

FIGS. **7**A and **7**B are bottom perspective and top transparent perspective views of an example position unit **506***a*. As illustrated, the position unit **506***a* may include a housing **714** that houses a flow regulation chamber **712**, a regulation valve **710**, and a position detector **702**. The housing **714** may be attachable to the toilet **502** via one or more fastening elements. For example, the housing **714** may include two or more holes **718** that extend through the housing **714** and the toilet **502** may include corresponding fastening elements (not shown) configured to mate with the two or more holes **718**. For instance, the toilet bowl **202** may include corresponding holes (not shown) that extend through a flange portion of the toilet bowl **202** (see FIG. **6**) located on a rear side and configured to align with holes **718** of the housing **714** and accept fasteners (e.g., various nuts and bolts, etc.) to secure the position unit **506***a* to the toilet **502**. However, it should be understood that any suitable fastening means may be used to fasten the housing **714** to the toilet **502**, including screws, clamps, clips, snaps, etc. Further, in other embodiments, the position unit **506***a* may be made integral with other components of the toilet **502**, including, for example, the vertical pipe **242**, the flush valve **240**, the toilet bowl **202**, etc.

The position detector **702** may be an assembly configured to detect the position of the toilet seat **112** and coupled to the regulation valve **710** to open or close it based on the position of the toilet seat **112**. In some embodiments, the position detector **702** may include a kinematic assembly having one end connected to the regulation valve **710** located within the flow regulation chamber **712** and another end connected to the toilet seat **112**. In some embodiments, the position detector **702** may include a first mechanical link **704** and a second mechanical link **706**. The first mechanical link **704** may be elongated and extend from the housing **714** to the toilet seat **112**. The first link **704** may have holes at its proximal and distal ends. The distal end of the first link **704** may pivotably fasten to the toilet seat **112** via a fastener (e.g., screw, bolt, rivet, etc.) inserted through the hole and secured to the toilet seat **112**. In some embodiments, the toilet seat **112** may include a post **602** (see FIG. **6**) that extends outward from a rear surface of the toilet seat **112** that faces the position unit **506***a*, and the first link **704** may pivotably fasten to the toilet seat **112** via a fastener that extends through the hole in the distal end of the first link **704** and a corresponding hole included in the post **602**.

In other embodiments, the position detector **702** may include an attachment device (not shown) configured to connect the first link **704** to the toilet seat **112**. For example, in a retrofit application where a toilet seat **112** may lack a post **602**, the attachment device (not shown) may pivotably fasten to the first link at one end via a hinge and may directly fasten to the toilet seat **112** at another end via a fastener (not shown). The fastener may include any fastening means or device capable of reliably attaching the attachment device to the toilet seat **112**, such as, but not limited to, an eye bolt. In yet other embodiments where the toilet **502** is fitted with a toilet seat raising and lowering device **100** (not shown), the position detector **702** may be attached/fastened to the seat coupling device **116** (e.g., the lever arm **116***a*), the movement transmission mechanism **108** (e.g., the pulley **218**, cable **222**, etc.), or another portion of the toilet seat raising and lowering device **100** capable of indicating/signaling/transmitting the position of the toilet seat **112** to the position detector **702**. It should be understood that the above embodiments for connecting the position detector **702** are provided by way of example, and that other equivalent ways of coupling the position detector **702** to the toilet seat **112** and/or toilet seat raising and lowering device **100** are contemplated and fall within the scope of this disclosure.

The proximal end of the first link **704** may moveably/pivotably fasten to the second link **706** at a lower end. The lower end of the second link **706** may include a hole that corresponds to the hole in the proximal end of the first link **704**. A fastener (e.g., screw, bolt, rivet, etc.) may be inserted through the holes to pivotably fasten the first link **704** and the second link **706** together. An upper end of the second link **706** may be securely fixed (e.g., fastened, welded, joined, etc.) to the regulation valve **710** to rotate the valve **710** between a restrictive position and an open position when the toilet seat **112** is respectively moved between a raised position and a lowered position. In the restrictive position, the regulation valve **710** is configured to impede the flow of the fluid released by the flush valve **240** into the flow regulation chamber **712**. In the open position, the regulation valve **710** is configured to allow the fluid released by the flush valve **240** to flow freely through the flow regulation chamber **712**.

In some embodiments, the regulation valve **710** includes a throttle valve **720** situated within the flow regulation chamber **712** to throttle the fluid flow based on the position of the toilet seat **112**. For example, the regulation valve **710** may include an axle **708** rotateably supported and secured by two diametrically opposed circular slots **722** formed in the sidewall of the flow regulation chamber **712**. A throttle member **720** may be fixed to the axle **708** along a centerline and configured to rotate within the flow regulation chamber **712** when the axle **708** is rotated by the position detector **702**. To rotate the axle **708** the second link **706** may, in some embodiments, be fixed to a proximal end of the axle **708** that extends through the circular slot **722** into a rectangular slot **716** that is formed in the housing **714** to accommodate the position detector **702**. In some embodiments, the shape of the perimeter of the throttle member **720** corresponds with/matches the cross-sectional shape of the flow regulation

chamber **712** so when the throttle member **720** is located in the restrictive position, it impedes the flow of the fluid passing through the flow-regulation chamber **712** by blocking (at least partially) the flow through the regulation chamber **712**, and thus reduces the amount of fluid used to flush the toilet **502** during a flush cycle. For example, as depicted, the throttle member **720** may be disk-shaped and configured to have a circumference that ranges between substantially 0-50% less than a circumference of the tubular flow-regulation chamber, depending on the amount of fluid that should be restricted.

While the position unit **506***a* is depicted in FIG. **6** as being situated underneath the vertical pipe **242** behind the toilet seat **112**, the position unit **506***a* may have other configurations adapted to provide the same functionality as that discussed above. For instance, in various further embodiments, the position unit **506***a* may be connected to any portion of the vertical pipe **242** or other fluid conduit associated with the toilet **500**, whether upstream, included in, or downstream of the flush valve **710**, to regulate the flow-rate of the fluid released by the flush valve **710**. For instance, in some embodiments, the position unit **506***a* may be located higher up on the vertical pipe **242**, attached to or integrated with other components of the toilet **502**, the vertical pipe **242**, the flush valve **240**, the toilet bowl **202**, a tank (e.g., see FIGS. **11**A-**11**E and corresponding description), etc., and configured to detect the position of the toilet seat **112** and communicate its position to a flow regulation component, such as the throttle valve **710**, the flush valve **240**, an electrical switch, a magnetic switch, or suitable another component for regulating the fluid flow as discussed herein. In a further example, a pipe upstream or downstream of the flush valve **240** (e.g., the vertical pipe **242**, a horizontal supply pipe upstream of the flush valve **240**, etc.) may include two separate tubes (e.g., parallel tubes) for passing fluid. One tube may be more constrictive than the other tube (e.g., have a narrower diameter, may include a diaphragm/narrower diaphragm, etc.) so as to allow less fluid to flow when the toilet seat is in a raised position, whereas the other tube would allow more fluid to flow when the toilet seat is in a lowered position. In this example, the flush valve **240**, or another suitable fluid switch, may be configured to direct to fluid to one or the other tubes depending on the position of the toilet seat **112** (e.g., in response to receiving a signal from a position detector).

In addition, in some embodiments, the position detector **702** and the valve **710** may be integrated. For example, while not depicted, the position unit **506** may have a gate valve configuration including a flat elongated rectangular gate having one end attached to the toilet seat **112** and another end that is configured to be slideably inserted into the vertical pipe **242** by the movement of the toilet seat **112** into the raised position and block (at least partially) the cross section of the vertical pipe **242**. The gate may further be configured to slide out from the vertical pipe **242** when the toilet seat **112** is moved into the lowered position, thus allowing the fluid released by the flush valve **240** to freely pass through the vertical pipe **242**.

The position unit **506** may additionally or alternatively include other components and/or assemblies for the position detector **702**. For example, the position detector **702** may include elements such as springs, gears, cables, chains, rods, magnets, etc., to transmit the position of the toilet seat **112** to the valve **710**. Moreover, the valve **710** may be a different type of valve, such as ball valve, globe valve, gate valve, needle valve, plug valve, etc., and may be mechanically or electronically activated by the position detector **702**. For instance, the position detector **702** may include electronic sensors, including, for example, optical sensors (e.g., IR proximity sensor, capacitive, Doppler effect, sonar, magnetic, camera, etc.), electronic switches, gyroscopes, etc., configured to sense the position of the toilet seat **112**. These sensors may be electronically connected to the valve **710** to transmit a signal indicating the position of the toilet seat **112** to the valve **710**. For instance, the sensor may be a gyroscope included on the toilet seat **112** that can detect the vertical and/or horizontal orientation of the toilet seat **112**, a switch located on the rim of the toilet bowl **202** that can be contacted/triggered by the toilet seat **112** when it is in a lowered position, an optical sensor placed on the toilet **502** behind or underneath the toilet seat **112** to be triggered by the toilet seat **112** when it enters/obstructs the sensors field of view, etc.

FIG. **7**C is a side perspective view of a flush valve **240** and vertical pipe **242** equipped with another example position unit **506***c* and a side view of another example position detector **702***c*. The position unit **506***c* may include a position detector **702***c*, a housing **714***c* that houses a flow regulation chamber **712***c*, and a regulation valve **710***c*. The housing **714***c*, position detector **702***c*, and associated components, may be attachable to the plumbing, a bracket, toilet bowl, other structural member, etc., of a toilet (e.g., toilet **502**) via one or more fastening elements (not shown). It should be understood that any suitable fastening means may be used to fasten these components as shown, including screws, clamps, clips, snaps, adhesive, etc. Further, in other embodiments, the position unit **506***a* may be made integral with various components associated with the toilet **502**, including, for example, the vertical pipe **242**, the flush valve **240**, toilet bowl or tank, other plumbing components, etc.

The position detector **702***c* may be an assembly configured to detect the position of the toilet seat **112** and coupled to the regulation valve **710***c* to open or close it based on the position of the toilet seat **112**. In some embodiments, the position detector **702***c* may include a kinematic, hydraulic, etc., assembly having one end that interacts with the regulation valve **710***c* located within the flow regulation chamber **712***c* and another end that interacts with the toilet seat **112**, although other movement transmission mechanisms may be used as discussed elsewhere herein, such as a cables, pulleys, gears, switches, electronic motors, etc. As depicted, the position detector **702***c* may include a pedal **755** that is depressable by the toilet seat **112** when the toilet seat is in the raised position. For instance, when substantially upright, a surface of the toilet seat **112** facing the vertical pipe **242** may come into contact with and depress the pedal **755**, which in turn depresses the piston **754** inward into the actuator housing **758**. When the toilet seat **112** is returned to the lowered position, the piston may be released back into its neutral position as depicted in FIG. **7**C.

The piston housing may contain a piston chamber into which the piston is depressably insertable. The piston may maintain a fluid-tight seal with the piston chamber included in the piston housing **754**. The hollow tubing **756** may couple to the piston chamber **758** in a fluid-tight manner and extend and couple to the valve housing **714***c* in a fluid-tight manner, so the hydraulic pressure generated by virtue of the piston **754** being depressed by the pedal **755** into the piston housing **758** is transferred via the tubing **756** to the valve **710***c* to depress the valve toward the fluid source **766** and thereby constrict the flow of the fluid allowed to pass through the valve **240** when the toilet is flushed. Alternatively, when the piston **754** is released back into its neutral position, the hydraulic pull produced thereby is transmitted

via the tubing **756** to the housing **714***c* to draws back the valve **710** from the fluid supply opening **766** and allow more fluid to pass during a subsequent flush. In the depicted example, the fluid chamber collectively formed by the piston housing **754**, tubing **756**, and the valve housing **714***c*, may be filled with a hydraulic fluid.

While in FIG. **7**C the position detector **702***c* is depicted as being located near a toilet bowl of a toilet, it should be understood that the position detector **702***c* may be located in any location or position suitable to sense/detect the position of the toilet seat **112**, including on a sidewall, on top of, or above the vertical pipe, on a bracket or other structural member protruding from a nearby structural component suitable to hold and support the position detector, etc. For instance, in further embodiments, a configuration that includes a magnetic gate valve located upstream, incorporated with, or downstream of the flush valve **240** may be used. The magnetic gate valve may be configured to constrict to allow less fluid to pass when subjected to a magnetic attraction produced by a corresponding magnetic material (e.g., rare-earth magnet(s), etc.) included in or on the toilet seat **112**. For instance, the magnetic gate valve may be constricted when the toilet seat **112** is raised in the raised position and the magnetic material included with the toilet seat is situated proximate to the flush valve **240**. Further, it should be understood that the numerous additional alternative variations and adaptations that are applicable to and discussed above with reference to the position unit **506***a* (e.g., relative to FIGS. **7**A and **7**B) are also applicable to the position unit **506***c*. However, for brevity the description of those variations and alternatives will not be repeated here.

As depicted by the dashed signal lines included in FIGS. **5**A and **5**B, in some embodiments, the throttle valve **710** may be omitted and the flush valve **504** may be configured to regulate the amount of fluid used to flush the toilet **502** based on a signal received from the position unit **506**. For example, the flush valve **504** may be mechanically or electronically coupled to the position unit **506** to receive an electronic position signal indicating whether toilet seat **112** is located in position B or position C, and the flush valve **504** may regulate the fluid that passes through it based on the flush regulation signal. For example, the position unit **506** may include a sensor (e.g., proximity sensor), as discussed elsewhere herein, that is situated in a location where it can electronically and/or optically sense what position the toilet seat **112** is in, electronically communicate the position to the flush valve **504**, and the flush valve **504** can control how much fluid is released to flush the toilet **502** (e.g., by opening more or less widely, opening for a longer or shorter period of time, a combination of the foregoing, etc.) based on the signal received from the position unit **506**.

As a further example, FIG. **9** is an example diagram showing the detection of various positions of a toilet seat **112** or patron using a sensor **902** (e.g., a form of position unit **506**). For instance, the sensor **902** may be configured to look downward toward location X. In this example, the signals (e.g., light, sound, frequency, etc.) provided by the sensor **902** to the flush valve **504** are different depending on whether the toilet seat **112** is in the raised or lowered position. The sensor **902** can determine the position of the seat **112** based on the differing signals and communicate the position to the flush valve **504**. The flush valve **504** may be configured to select the amount of fluid to flush the toilet **502** with based on the signal received from the sensor **902**. As a further example, the sensor **902** may be a proximity sensor (e.g., IR sensor) and may be capable of detecting the distance of the toilet seat **112** relative to the optical sensor (position W versus position Y). If the signal received from the optical sensor **902** indicates that the toilet seat **112** is located at location X during a use cycle of the toilet, the flush valve **504** is configured to flush the toilet with more fluid than if the signal indicates that the toilet seat **112** is located at location W.

In another example, the sensor **902** may be configured with a field of view that is substantially horizontal to the toilet seat **112**, and the sensor **902** may be capable of determining whether a patron is in front of the toilet **502** (e.g., body within range Z) or seated on the toilet **502** (torso in range Y) while using said toilet **502** (e.g., based on a variance in light, sound, frequency, heat, etc., detected by the sensor **902**). If the patron was seated at any time while using the toilet **502**, the signals received from the sensor **904** may reflect the seated position of the patron and the flush valve **504** may determine to flush the toilet **502** with a standard flush, and if the patron was standing during the entire time while using the toilet **502**, the signals received from the sensor **904** may reflect the standing position of the patron and the flush valve may determine to flush the toilet **502** with a shorter than standard flush to save fluid (e.g., water), as the presumption is that the user only deposited fluids and/or a light amount of toilet paper in the toilet **502** during his movement. In this latter example, the system can in some cases flush the toilet irrespective of the position of the toilet seat **112**.

The flush valve **504** may be an automatic (e.g., "hands free") electric flush valve, which, in some embodiments, may be controlled by the optical sensor **902** and configured to automatically flush after a patron has used the toilet based on signals received from the optical sensor **902**. In further embodiments, the optical sensor **902** may be distinct from the sensor of the automatic flush valve. Power may be provided to the optical sensor **902**, the flush valve **504**, a separate flow regulation component, or any other associated electrical components, by any conventional power source (e.g., electrical wiring in the wall **904** or premises in which the toilet is located that provides power from the power grid, batteries, solar power, etc.). In a further example, the optical sensor, flush valve **504**, and/or other associated components, may be powered by virtue of the fluid being released by the flush valve **504**. For instance, a small water-powered generator may be included in-line (e.g., on the vertical pipe or a supply pipe feeding into the flush valve, etc.) and may be propelled by the fluid released by the flush valve **504** to flush the toilet. The power produced by the water-powered generator may be stored in a storage device, such as battery that is electrically coupled to the optical sensor **902**, the flush valve **504**, and/or other associated components.

In these embodiments, the flush valve **504** and the position unit **506** may be connected wirelessly (e.g., via embedded radio transceivers, infrared transceivers, etc.), may be connected using wires, or a combination of the foregoing. The flush valve **504** may include software, circuitry, hardware, etc., to regulate the flushing of the toilet **502**. For example, the flush valve **504** may include a flush module (not shown) having logic operable by a processor (not shown) included in the toilet **502** to provide the functionality discussed herein. For instance, the flush module **504** may be stored in memory (not shown) included in the toilet **502** and operable by the processor (not shown) to perform this functionality. In further examples, may be implemented via a circuit, such as an integrated circuit (e.g., an ASIC); sets of instructions stored in one or more discrete memory devices (e.g., a PROM, FPROM, ROM) and operable by a processor; etc. In some embodiments, the flush valve **504**

and/or the position unit **506** may be coupled to an electrical power source (not shown) to receive power to operate. For instance, the flush module **504** and/or the position unit **506** may be coupled to an electricity grid, a battery, a solar cell, a fluid powered generator and power storage device that generates power from fluid flow used to flush the toilet **502**, etc.

With reference to FIG. **5**B, the system **550** may, in some embodiments, include a toilet **502** and toilet seat raising and lowering device **100** (e.g., **100***a*) having a position unit **506***b*. The position unit **506***b* may be connected to or integrated with the toilet seat raising and lowering device **100** and configured to detect whether the toilet seat **112** is in the raised position C or lowered position B. In some embodiments, the position unit **506***b* can include a sensor (e.g., proximity sensor such as an IR, light, radar, capacitive, photocell, etc., proximity sensor) placed proximate the movement transmission mechanism **108** (e.g., see FIG. **1**A) to sense its position. For example, the movement transmission mechanism **108** may move to raise the toilet seat **112** to the raised position, and during such movement, may trigger the sensor (e.g., come into contact with a physical sensor of the position unit **506***b* such as a switch, cause a change to light (obstruct, distort, etc.) being received by an optical sensor of the position unit **506***b*, etc.), thus signaling the position unit **506***b* that the toilet seat **112** is in a raised position.

FIG. **10**A is a front perspective view of an example tank **204** equipped with an example position unit **1000**, and FIGS. **10**B-**10**E are front perspective views of the example position units **1000** according to various configurations. As depicted, the tank **204** may include a conventional flushing assembly **1008** for flushing the toilet (not shown). The flushing assembly **1008** may include a base portion **1006** having a gasket that seals against the perimeter of a hole (obscured) in the bottom of the tank that leads to the bowl of the toilet. The position unit **1001** includes a cylinder **1000** that is connected to the base portion **1006** and extends vertically upward around and past the plunger **1012** of the flushing assembly **1008**. The cylinder **1000** includes two apertures **1020** and **1022**. The length of the cylinder **1000**, and the position, size, shape, and number of the apertures **1020** and **1022** in the cylinder **1000**, can be adapted to accommodate varying different sizes of toilets to achieve specific GPF depending on the position of the toilet seat **112**. As depicted, one of the apertures **1020***b* is included at the bottom of the cylinder **1000** and another of the apertures **1020***a* may be included at the top of the cylinder **1000**. The actual location of the apertures **1020***a* and *b* may be varied depending on the amount of fluid that is needed to suitably flush the toilet. The position unit **1001** may also include a sleeve portion **1012** configured to slide in a substantially fluid tight manner concentrically up and down within the cylinder **1000**. The sleeve portion **1012** may be coupled to a linkage which is configured to transmit the movement of the toilet seat **112** to the sleeve portion **1012**, thus moving the sleeve portion **1012** up or down depending on the position of the toilet seat **112**. Two different embodiments of the linkage are shown in FIG. **10**A, such as linkage **1010** and linkage **1002**, although numerous other configurations are contemplated and encompassed by the scope of this disclosure. In particular, linkage **1010** is depicted as entering the tank **204** through a hole in the base portion **1006** to raise and lower the sleeve portion **1012**. Linkage **1002** is depicted as entering the tank **204** from above the cylinder **1000**, such as a hole through the top or side of the tank (not shown), to raise and lower the sleeve portion **1012**.

As shown further in FIGS. **11**B-**11**D, the sleeve portion **1012** is raised and lowered respectively by the linkage **1002** or **1010** (as the case may be). More specifically, when the toilet seat **112** is raised to the raised position, the linkage **1002** or **1010** is configured to lower the sleeve portion **1012** to cover/seal the aperture **1020***b*. This reduces the amount of water that is permitted to flush the bowl of the toilet because any water under the aperture **1020***a* remains in the tank **240** during a flush. When the toilet seat **112** is lowered to the lowered position, the linkage is configured to raise the sleeve portion **1012** to cover the aperture **1020***a*, or in other embodiments, enough to uncover the aperture **1020***b*. This increases the amount of water that is permitted to flush the bowl of the toilet because the water previously restricted by the sleeve **1012** when it was covering/sealing the lower aperture **1020***b* is now permitted to pass through the lower aperture **1020***b*.

The advantages of the technology described herein include, without limitation, that it is small so as to be unobtrusive; simple so as to be easy to install, operate, and maintain; durable so as to provide many years of use; relatively inexpensive to own, small size so as to maintain the look and feel of the original toilet configuration, install and operate; and universal to work on all variations of toilets and toilet seats. The technology can be installed by a single individual in a matter of minutes on practically any existing toilet bowl/seat combination to provide its intended functionality. The technology can also conserve substantial amounts of fluid (e.g., water) that is used to flush the toilet, thus reducing costs and preserving the environment. The simple effectiveness and low cost of the technology help to make its use to solve a recognized problem more likely than the overly complicated and expensive related art or related art that may be relatively simple and/or inexpensive but requires user courtesy and action for embodiment.

In the foregoing description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the technology. It will be apparent, however, that the technology described herein can be practiced without these specific details. In other instances, structures and devices are shown in block diagram form in order to avoid obscuring the invention.

Reference in the specification to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the invention. The appearances of the phrase "in one embodiment" in various places in the specification are not necessarily all referring to the same embodiment.

While the foregoing written description of the invention enables one of ordinary skill to make and use what is considered presently to be the best mode thereof, those of ordinary skill will understand and appreciate the existence of variations, combinations, and equivalents of the specific embodiment, method, and examples herein. The invention should therefore not be limited by the above described embodiment, method, and examples, but by all embodiments and methods within the scope and spirit of the invention as claimed.

What is claimed is:

1. A toilet flushing system comprising:

a fluid regulation component including a regulation valve fluidly connected via a fluid line to a flush valve of a toilet and a fluid regulation chamber fluidly connected to the regulation valve, the regulation valve regulating an amount of fluid flushed by the flush valve and used to flush the toilet during a flush cycle; and

a toilet seat positioning device including a position unit, a fluid-based movement source that generates a force upon actuation, and a movement transmission mechanism configured to transfer the force to a toilet seat to raise the toilet seat from a lowered position to a raised position, the movement transmission mechanism being connected to the fluid-based movement source to receive the force, the position unit configured to detect whether the toilet seat is in the raised position or the lowered position, the position unit being movable to a position that generates a hydraulic pressure within the fluid regulation chamber of the fluid regulation component to actuate the fluid regulation chamber when the toilet seat is in the raised position, the fluid regulation chamber fluidly transmitting the generated hydraulic pressure to the regulation valve to regulate the amount of fluid that passes through the flush valve during the flush cycle.

2. The toilet flushing system of claim **1**, wherein the position unit includes a position detector that is configured to transmit a position of the toilet seat to the fluid regulation component.

3. The toilet flushing system of claim **1**, wherein the fluid regulation component is locatable downstream of the flush valve of the toilet, locatable upstream of the flush valve of the toilet, is incorporateable into the flush valve of the toilet, or is incorporated into the position unit.

4. The toilet flushing system of claim **3**, wherein the regulation valve situated in the fluid regulation chamber, the regulation valve being configured to control the amount of fluid that passes through the fluid regulation chamber during the flush cycle based on whether the toilet seat is in the raised position or the lowered position.

5. The toilet flushing system of claim **1**, wherein the position unit includes a mechanical assembly connectable to the toilet seat and connectable to the fluid regulation component, the mechanical assembly configured to transmit a movement of the toilet seat from the toilet seat to the fluid regulation component when the toilet seat is raised from the lowered position to the raised position or when the toilet seat is lowered from the raised position to the lowered position.

6. The toilet flushing system of claim **1**, wherein the position unit is coupleable to the toilet seat.

7. The toilet flushing system of claim **1**, wherein the toilet includes a tank or the toilet is a tankless toilet.

8. The toilet flushing system of claim **1**, wherein the flush valve of the toilet includes the fluid regulation component.

9. A system, comprising:

a toilet seat raising and lowering device including a fluid-based movement source that generates a force upon actuation and a seat coupling component coupled to a toilet seat of a toilet, the fluid-based movement source including a fluid inlet fluidly connected to a water supply and a fluid outlet fluidly connected to a flush valve, the fluid-based movement source being actuated by a fluid flow regulated by the flush valve during a single flush cycle to generate the force based on a pressure difference between the fluid inlet and the fluid outlet that causes the fluid flow to flow in the fluid inlet and out of the fluid outlet towards the flush valve during the single flush cycle when actuated by the flush valve, the seat coupling component configured to transfer the force to the toilet seat to raise the toilet seat from a lowered position to a raised position, wherein the single flush cycle is initiated responsive to the flush valve being actuated to flush a toilet bowl of the toilet; and

a regulation valve including an input portion configured to receive an input from the seat coupling component of the toilet seat raising and lowering device, the input indicating whether the toilet seat is located in the raised position or the lowered position, the regulation valve regulating an amount of fluid for flushing the toilet based on the input.

10. The system of claim **9**, wherein the input is a mechanical input.

11. A method comprising:

equipping a toilet with a flush valve and a flow regulation component, the flow regulation component including a regulation valve that regulates an amount of fluid for flushing the toilet based on whether a toilet seat of the toilet is in a raised position or a lowered position and a fluid regulation chamber fluidly connected to the regulation valve; and

equipping the toilet with a toilet seat raising and lowering device including a position detector, a fluid-based movement source that generates a force upon actuation, and a movement transmission mechanism configured to transfer the force to the toilet seat to raise the toilet seat from the lowered position to the raised position, the movement transmission mechanism being connected to the fluid-based movement source to receive the force, the position detector configured to determine whether the toilet seat of the toilet is in the raised position or the lowered position, the position detector being movable to a position that generates a hydraulic pressure within the fluid regulation chamber included in the flow regulation component to actuate the fluid regulation chamber when the toilet seat of the toilet is in the raised position, the fluid regulation chamber fluidly transmitting the generated hydraulic pressure to the regulation valve to regulate the amount of fluid that passes through the flush valve for flushing the toilet.

12. The method of claim **11**, wherein the position detector is coupled proximate the toilet seat.

13. The method of claim **11**, wherein the toilet includes a tank or the toilet is a tankless toilet.

* * * * *