US010641578B2

(12) **United States Patent**
Springer

(10) **Patent No.: US 10,641,578 B2**
(45) **Date of Patent: May 5, 2020**

(54) **TRIGGER-BASED ARCHERY RELEASE DEVICE AND METHOD**

(71) Applicant: **Copper John Corporation**, Auburn, NY (US)

(72) Inventor: **Eric C. Springer**, Moravia, NY (US)

(73) Assignee: **Copper John Corporation**, Auburn, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/402,873**

(22) Filed: **May 3, 2019**

(65) **Prior Publication Data**

US 2019/0285379 A1 Sep. 19, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/842,764, filed on Dec. 14, 2017, now Pat. No. 10,281,231.

(60) Provisional application No. 62/434,373, filed on Dec. 14, 2016.

(51) **Int. Cl.**
F41B 5/18 (2006.01)
F41B 5/14 (2006.01)

(52) **U.S. Cl.**
CPC ***F41B 5/1469*** (2013.01)

(58) **Field of Classification Search**
CPC F41B 5/1469
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

228,302 A 6/1880 Beard
229,089 A 6/1880 Burnham
2,133,650 A 10/1938 Baker
2,819,707 A 1/1958 Kayfes et al.
3,009,454 A 11/1961 Floyd
3,656,467 A 4/1972 Halter
3,757,763 A 9/1973 Pinti et al.
3,768,456 A 10/1973 Hansen et al.
3,853,111 A 12/1974 Stanislawski et al.
3,942,507 A 3/1976 Opal
3,965,884 A 6/1976 Killian
4,036,204 A 7/1977 Scott
4,041,926 A 8/1977 Troncosco, Jr. et al.
4,160,437 A 7/1979 Fletcher
4,424,791 A 1/1984 Muehleisen
4,509,497 A 4/1985 Garvison
4,539,968 A 9/1985 Garvison
4,567,875 A 2/1986 Fletcher
4,574,767 A 3/1986 Gazzara
4,612,907 A 9/1986 Gantt
(Continued)

OTHER PUBLICATIONS


Various prior art releases (1) downloaded from http://www.archeryhistory.com/releases/releasespics/pse.jpg, Dec. 2009.
(Continued)


Primary Examiner — John A Ricci
(74) *Attorney, Agent, or Firm* — Barclay Damn LLP

(57) **ABSTRACT**

A trigger-based archery release device and method are described herein. The archery release device, in an embodiment, includes a first housing portion, a second housing portion, and a trigger configured to be positioned at least partially between the first and second housing portions. The archery release device also includes first and second interface members. The archery release device is configured to apply a securing force to a portion of the trigger.

20 Claims, 51 Drawing Sheets





(56) **References Cited**

U.S. PATENT DOCUMENTS

4,620,523	A	11/1986	Peck
4,674,469	A	6/1987	Peck
4,854,293	A	8/1989	Roberts
4,881,516	A	11/1989	Peck
5,009,214	A	4/1991	Wilde
5,025,772	A	6/1991	Stevenson
5,096,170	A	3/1992	Albin
5,205,268	A	4/1993	Savage
5,261,581	A	11/1993	Harden
5,273,021	A	12/1993	Tepper
5,323,754	A	6/1994	Pittman et al.
5,448,983	A	9/1995	Scott
5,546,924	A	8/1996	Todd
5,595,167	A	1/1997	Scott
5,596,977	A	1/1997	Scott
5,685,286	A	11/1997	Summers
5,692,490	A	12/1997	Walker
5,694,915	A	12/1997	Summers
5,765,536	A	6/1998	Scott
5,803,068	A	9/1998	Summers
5,850,825	A	12/1998	Scott
5,937,842	A	8/1999	Summers et al.
6,032,661	A	3/2000	Goff et al.
6,205,991	B1	3/2001	Summers et al.
6,302,093	B1	10/2001	Holland
6,571,786	B2	6/2003	Summers et al.
6,631,709	B2	10/2003	Carter et al.
6,647,976	B2	11/2003	Summers et al.
6,712,060	B2	3/2004	Egusquiza
6,736,124	B2	5/2004	Carter
6,895,951	B2	5/2005	Summers et al.
6,945,241	B2	9/2005	Pellerite
6,953,035	B1	10/2005	Summers
D597,164	S	7/2009	Jones
7,654,254	B1	2/2010	Rentz et al.
8,622,051	B2	1/2014	Summers
8,746,221	B2	6/2014	Rentz
8,869,781	B2	10/2014	Jones
9,027,540	B2	5/2015	Springer
9,250,032	B2	2/2016	Kelly et al.
9,255,762	B2	2/2016	Kelly et al.
9,261,323	B2	2/2016	Springer
9,618,295	B1	4/2017	Rentz
9,625,230	B2	4/2017	Kelly et al.
9,863,736	B2	1/2018	Kelly et al.
2003/0159682	A1	8/2003	Pellerite
2004/0079351	A1	4/2004	Summers et al.
2007/0181113	A1	8/2007	Porter
2008/0149084	A1	6/2008	Whalen et al.
2009/0056689	A1	3/2009	Jones
2009/0090342	A1	4/2009	Freitag et al.
2009/0095270	A1	4/2009	Graves
2010/0108047	A1	5/2010	Jones
2011/0168146	A1	7/2011	Deceuster
2012/0192844	A1	8/2012	Springer
2012/0285431	A1	11/2012	Summers
2013/0025578	A1	1/2013	Jones
2013/0092140	A1	4/2013	Rentz
2015/0219418	A1	8/2015	Whalen

OTHER PUBLICATIONS

Various prior art releases (2) downloaded from http://www.archeryhistory.com/releases/releasespics/release4.jpg, Dec. 2009.

Prior art releases (3) downloaded from http://www.archeryhistory.com/releases on Jul. 21, 2011.

Prior art releases (4) downloaded from http://www.archeryhistory.com/releases on Jul. 21, 2011.

Longhorn Hunter (Jan. 2010).

Carter Enterprises; Carter Whisper Tech Tip Multipurpose Rope Leash; Mar. 21, 2016; retrieved from the Internet: <https://www.youtube.com/watch?v=NkpbmDUyWTM>; 7 pages.

Carter Enterprises; Whisper; on or before Dec. 31, 2011; retrieved from the Internet: <https://carterenterprises.com/releases/thumb-trigger/whisper>; 1 page.

Carter Enterprises; 2012 Carter Catalog; on or before Dec. 31, 2012; 16 pages.

T.R.U. Ball; 2012 Product Guide; on or before Dec. 31, 2012; 20 pages.




Fig. 1



11
41
19
16
6
17
39
20
24
40
94
92
34
32
37
8
15
18
63
75
54
14
6
76a, 76b
62
13
36
68
74
60
56
58
9
4
10
2

Fig. 2



11
19
6
17
16
40
20
24
94
92
32
78
15
34
8
18
14
6
75
54
13
76a, 76b
62
68
74
60
56
2
9
4
10

Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7



63
13
6
2
18
9
15
12
66
64a
44
68
32
64
60
17
6
75
74
19
34
64b
8
76a, 76b
56
62
X_T
11

Fig. 8



2
63
6
18
X_{A1}
13
15
X_H
9
17
19
4
8
34
θ1
60
11
56

Fig. 9A



2
63
6
18
13
X_{A2}
15
X_H
9
17
19
4
θ2
34
8
11
56
60

Fig. 9B




Fig. 9C



14
6
18
45
32
80
A
50
40
42
44
46
34
82
10
78
8
64a
76a, 76b
64b
68
60
56
62

Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19



13
6
18
9
15
X_B
50, 52
48
40
10
44
A
92
60
84
94
56
22
17
46
32
34
42
6
14
20
F
24
19
10
X_{E1}
16
11,28

Fig. 20




Fig. 21




Fig. 22




Fig. 23A




Fig. 23B




Fig. 23C




FIG. 24



200
204
236
238
210
229
228
216
230
209
220
224
207
246
226
218
222
202

FIG. 25



200
202
204
206
207
208
209
210
212
214
216
218
220
222
224
226
228
230
232
234
236
238
240
242
244
246
248

FIG. 26



200
212
214
Ps
S
238
232
237
234
236
202
230
216
222
240
201
207
242
242
218
220
246
226
224
209
213
203

FIG. 27



200
202
204
206
207
208
210
211
212
213
214
216
218
220
222
224
226
228
230
232
234
236
237
238
240
246
248
201
205

FIG. 28



200
202
204
205
206
207
208
209
210
211
212
213
214
215
216
218
220
222
224
226
228
229
230
231
232
233
234
235
236
237
238
240
242
246

FIG. 29



209
207
218
210
208
222
202
216, 234, 235
200
232, 220
248, 224
213
226
246
228

FIG. 30



200
202
204
207
208
209
210
211
212
213
214
216
218
220
222
224
226
228
232
234
236
238
246
248

FIG. 31




FIG. 32



250
252
254
256
258
260
262
264
266
200
202
204
207
208
210
212
214
215
216
218
220
222
226
228
246

FIG. 33



310
312
346
18
346
66
56
4
316
368
346
16

FIG. 34



310
342
314
334
318
18
326
316
346
328
332
56
346
330
344
324
336
368
346
322
320
16

FIG. 35




FIG. 36



368
56
332
330
346
318
334
316
328
326
342
376
310
18
346
344
324
322
336
320
346
348

FIG. 37



332
60
346
316
310
320
4
346
314
18

FIG. 38



60
332
330
346
310
320
328
318
322
338
316
346
400
398
340
326
342
324
344
346
18

FIG. 39



18
342
342
344
324
318
322
316
328
404
402
320

FIG. 40



18
324
342
326
344
318
338
316
332
340
400
398
320

FIG. 41



346
332
330
366
60
368
364
314
318
334
362
326
328
374
342
376
320
356
370
350
346
18
322
324
344
336
314
348
310

FIG. 42



346
332
330
314
318
316
334
328
326
342
320
376
346
322
336
18
344
314
348
310

FIG. 43



332
330
366
60
364
314
318
334
316
362
328,378
354
360
320
326
356
352
358
346
322
336
380
314

FIG. 44



(PRIOR ART)
388
387
382
384
388
390, 392

FIG. 46

(PRIOR ART)
390, 392
386
388
388
388

FIG. 45



346
332
310
60
330
394
334
318
396
320
396
396
336
326
396
396
346
328
18
346
344
324
322
348

FIG. 47




FIG. 48



346
332
330
60
334
318
316
328
326
342
336
322
18
344
346
324
348
424
406
408, 414
423
406
410, 412
4
310

FIG. 49




FIG. 50



330
332
314
364
424
423
314
318
334
362
342
374
326
376
18
344
324
322
336
348
366
320
356
328
370

FIG. 51




FIG. 52




FIG. 53

TRIGGER-BASED ARCHERY RELEASE DEVICE AND METHOD

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of, and claims the benefit and priority of, U.S. patent application Ser. No. 15/842,764 filed on Dec. 14, 2017, which is a non-provisional of, and claims the benefit and priority of, U.S. Provisional Patent Application No. 62/434,373 filed on Dec. 14, 2016. The entire contents of such applications are hereby incorporated by reference.

BACKGROUND

Archery release aids are used to hold a bowstring in the drawn position. The known release aids attach to the bowstring and pull the bowstring to the drawn position. The user activates the release aid, either by activating a trigger or by jerking the release, to cause the bowstring to slide off of the release aid's hook, thereby allowing the bowstring to fire an arrow.

There are known release aids that include a release case, a hook and one or more linkage components coupled to the hook. Some of the known release aids have triggers coupled to the linkage components, and some of the known release aids have finger extensions with some level of adjustability. All of the known release aids, however, have problems and deficiencies with respect to force transmission efficiency, reliability, ergonomics, adjustability, repeatability, ease of operation or release responsiveness. Consequently, archers can encounter a loss in desired settings, misfires, impairment of shooting performance, muscle fatigue, pain and reduced shooting accuracy.

The foregoing background describes some, but not necessarily all, of the problems, disadvantages and shortcomings related to the known archery release aids.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is an isometric side view of an embodiment of an archery release device.

FIG. **2** is another isometric side view of the archery release device of FIG. **1**.

FIG. **3** is a side view of the archery release device of FIGS. **1-2**.

FIG. **4** is a rear isometric view of the archery release device of FIGS. **1-3**.

FIG. **5** is a front isometric view of the archery release device of FIGS. **1-4**.

FIG. **6** is a front view of the archery release device of FIGS. **1-5**.

FIG. **7** is a bottom isometric view of the archery release device of FIGS. **1-6**.

FIG. **8** is a bottom isometric view of an embodiment of a release body for an archery release device.

FIG. **9**A is a sides of the archery release device of FIG. **1**, illustrating the arm member of the thumb grasp assembly extending along a first axis.

FIG. **9**B is a side view of the archery release device of FIG. **1**, illustrating the arm member of the thumb grasp assembly extending along a second axis.

FIG. **9**C is a side view of the archery release device of FIG. **1**, illustrating the arm member of the thumb grasp extending along a third axis.

FIG. **10** is a rear isometric exploded view of the release body of FIGS. **8-9**.

FIG. **11** is a rear isometric exploded view of the release body of FIGS. **8-9**C, illustrating the adjustable thumb grasp assembly in a first position.

FIG. **12** is a top isometric view of the archery release device of FIG. **8-9**C showing the adjustable thumb grasp assembly in a second position.

FIG. **13** is a top isometric view of the archery release device of FIGS. **8-9**C showing the adjustable thumb grasp assembly in a third position.

FIG. **14** is a side isometric view of an embodiment of an extension for an archery release device.

FIG. **15** is a bottom isometric view of the extension of FIG. **14**.

FIG. **16** is a top isometric view of the extension of FIGS. **14-15**.

FIG. **17** is another side isometric view of the extension of FIGS. **14-16**.

FIG. **18** is a bottom isometric exploded view of another embodiment of an extension for an archery release device.

FIG. **19** is top isometric exploded view of the extension of FIG. **18**.

FIG. **20** is a side isometric exploded view of an embodiment of an archery release device.

FIG. **21** is a side view of an embodiment of an extension for an archery release device showing securement forces.

FIG. **22** is a side view of an embodiment of an archery release device with an adjustable extension showing a variety of extension positions.

FIG. **23**A is a cross-sectional view of the archery release device of FIG. **22** with the extension in a first position.

FIG. **23**B is a cross-sectional view of the archery release device of FIGS. **22-23**A with the extension in a second position.

FIG. **23**C is a cross-sectional view of the archery release device of FIGS. **22-23**B with the extension in a third position.

FIG. **24** is a cross-sectional view of another embodiment of an archery release device, having a position adjuster.

FIG. **25** is a side isometric view of an embodiment of an extension for the archery release device of FIG. **24**.

FIG. **26** is a partially exploded side isometric view of the extension of FIG. **25**.

FIG. **27** is a partially exploded front isometric view of the extension of FIGS. **25-26**.

FIG. **28** is an exploded side isometric view of the extension of FIGS. **25-27**.

FIG. **29** is an exploded front isometric view of the extension of FIGS. **25-28**.

FIG. **30** is a side view of the extension of FIGS. **25-29** showing the internal components.

FIG. **31** is a partially exploded rear isometric view of the extension of FIGS. **25-30**.

FIG. **32** is a cross-sectional view of an embodiment of a release body housing of the archery release device of FIG. **24**.

FIG. **33** is an exploded cross-sectional view of the archery release device of FIG. **24**.

FIG. **34** is a top isometric view of yet another embodiment of the archery release device.

FIG. **35** is a fragmentary view of the archery release device of FIG. **34**, illustrating the internal components with the upper housing portion removed.

FIG. **36** is an isometric view of the lower housing portion of the archery release device of FIG. **34**.

FIG. **37** is a top isometric view of the internal components of the archery release device of FIG. **34**.

FIG. **38** is another isometric view of the lower housing portion of the archery release device of FIG. **34**.

FIG. **39** is an isometric view of the internal components of the archery release device of FIG. **34**, illustrating the bottom surfaces of the trigger, driver and other elements.

FIG. **40** is an isometric view of the internal components of the archery release device of FIG. **34**, illustrating the top surfaces of the trigger, driver and other elements.

FIG. **41** is another isometric view of the internal components of the archery release device of FIG. **34**, illustrating the bottom surfaces of the trigger, driver and other elements.

FIG. **42** is a top isometric view of the internal components of the archery release device of FIG. **34**, illustrating the top surfaces of the trigger, driver and other elements.

FIG. **43** is another top isometric view of the internal components of the archery release device of FIG. **34**, illustrating the top surfaces of the trigger, driver and other elements.

FIG. **44** is an enlarged, fragmentary, top isometric view of the internal components of the archery release device of FIG. **34**, illustrating the release force generator, the trigger, the driver and other elements.

FIG. **45** is a side diagram of a prior art compression spring, illustrating buckling and bending problems occurring during the operation of a prior art archery release aid.

FIG. **46** is a side diagram of the prior art compression spring of FIG. **45**, illustrating a different shape of the buckling and bending of the prior art archery release aid.

FIG. **47** is an isometric view of the internal components of the archery release device of FIG. **34**, illustrating the exertion of destabilization forces on the trigger, driver and other elements.

FIG. **48** is an isometric view of the archery release device of FIG. **34**, illustrating the interior housing surface of the upper housing portion.

FIG. **49** is an isometric view of the archery release device of FIG. **34**, illustrating the union of the upper and lower housing portions to receive, capture and retain the stabilizing interfaces.

FIG. **50** is an isometric view of the archery release device of FIG. **34**, illustrating the trigger motion limiter and the trigger pressurizer.

FIG. **51** is an isometric view of the archery release device of FIG. **34**, illustrating the insertion of the trigger motion limiter and the trigger pressurizer into the lower housing portion.

FIG. **52** is an isometric view of the trigger pressurizer of FIG. **51**, illustrating the insertion of the biasing member into the pressurizer body.

FIG. **53** is an isometric view of the pressurizer body of FIG. **52**, illustrating the cavity configured to partially receive the biasing member.

DETAILED DESCRIPTION

In an embodiment illustrated in FIGS. **1-7**, an archery release device **2** includes a housing **4** having a front surface **6**, a rear surface **8**, and at least two side surfaces **10**, **12**. The side surfaces **10**, **12** join the front surface **6** to the rear surface **8**. In use, the front surface **6** of the archery release device **2** faces the target and the rear surface **8** faces the archer in a direction opposite of the target. The archery release device **2** also has a top surface **9** and a bottom surface **11**. A bowstring hook, cord hook or cord holder **18** is coupled to the housing **4**, typically to the front surface **6**, and is configured to hold a bowstring, draw string or draw cord (not shown). Depending upon the embodiment, the archery release device **2** can be a triggerless release, such as a back tension release, or the archery release device **2** can be a trigger-based release. In a handheld triggerless embodiment, the archery release device **2** is configured to disengage the draw cord in response to the archer's pulling or jerking on the archery release device **2**. The spike in force resulting from the jerking or quick pull can be caused by tensing of the archer's back, arm or hand muscles. In a handheld trigger-based embodiment, the archery release device **2** has includes a trigger moveable relative to the housing **4**, a release button, release switch or other touch-responsive release controller operable to move the trigger, thereby causing the archery release device **2** to release the draw cord.

With particular reference to FIG. **2**, opposite the draw cord hook **18**, is a thumb grasp or thumb rest assembly **54**. As particularly illustrated by FIGS. **2** and **8-9**C, the thumb grasp assembly **54** includes a thumb rest body **56** having a surface **58** upon which an archer's thumb (not shown) rests or can rest during operation. In an embodiment, the surface **58** is textured to improve the grip of the surface **58**. The thumb grasp assembly **54** additionally includes an arm member **60** coupled to and extending from the thumb grasp body **56**. Depending upon the embodiment, the arm member **60** can be threadably coupled to or otherwise fastened to the thumb grasp body **56**, or the thumb grasp body **56** and the arm member **60** can be formed as a unitary member. In the embodiment shown, the thumb grasp body **56** defines a channel configured to receive a safety device **62**, such as a pin or screw. The user can remove the safety device **62** from the thumb grasp body **56** and insert the safety device **62** into the safety opening **63** (FIG. **1**). Once inserted into the safety opening **63**, the safety device **62** is operable to prevent the cord holder **18** from releasing the draw cord.

In an embodiment, the arm member **60** includes at least one bore, aperture, or opening **64** extending through the arm member **60**. In the illustrated embodiment, the arm member **60** includes a first and second bore or aperture **64***a*, **64***b* extending through the arm member **60** parallel to an axis X_T (FIG. **8**) extending through the thumb grasp body **56**.

The archery release device **2** has a thumb rest anchor or engagement member **66** (FIG. **8**) positioned within the housing **4** and at least a portion of which extends through the rear surface **8** of the housing **4**. The portion of the anchor member **66** extending through the housing **4** defines a thumb grasp engagement surface **68**. As illustrated in FIG. **8**, the engagement surface **68** has a curved profile and has a first side surface **70** and second side surface **71** joined by a perimeter surface **72**. A first guide track **74** and a second guide track **75**, each defining an opening, extend through the engagement surface **68** from the first side surface **70** to the second side surface **71**. Each guide track **74**, **75** has a curved or arc shape.

With particular reference to FIGS. **9**A-**9**C, the arm member **60** is coupled to the engagement surface **68**. In particular, the first and second bores **64***a*, **64***b* are aligned with the first and second guide track **74**, **75**, respectively, and a first and second anchor fastener **76***a*, **76***b* are inserted through the first bore **64***a* and first guide track **74** and through the second bore **64***b* and second guide track **75** to couple the arm member **60** to the engagement surface **68**. In the illustrated embodiment, the anchor fasteners **76***a*, **76***b* are screws. In this embodiment, the anchor fasteners **76***a*, **76***b* can be loosened in order to change the position of the thumb grasp assembly **54** and tightened to lock the position of the thumb grasp assembly **54** relative to the engagement member **66**.

As further illustrated by FIGS. **9**A-**9**C, the thumb grasp assembly **54** can be pivotally or rotationally adjusted relative to the housing **4**. In particular, the first and second anchor fasteners **76***a*, **76***b* can be positioned at various locations within the guide tracks **74**, **75** to change the angle of the thumb rest assembly **54** relative to the housing **4**. Referring to FIG. **9**A, an axis X_H extends longitudinally through the housing **4**. In this embodiment, the thumb rest assembly **54** is coupled to the engagement surface **68** in a first configuration in which the axis X_{A1} of the thumb grasp assembly **54** intersects the axis X_H to form a first angle θ_1. As illustrated in FIG. **9**B, the thumb rest assembly **54** is coupled to the engagement surface **68** in a second configuration in which the thumb rest assembly **54** is rotated toward the housing **4**, as compared to the configuration illustrated in FIG. **9**A. In the embodiment illustrated in FIG. **9**B, the axis X_{A2} of the thumb grasp assembly **54** intersects the axis X_H at a second angle θ_2, which is smaller than the first angle θ_1 (FIG. **9**A). As illustrated in FIG. **9**C, the thumb rest assembly **54** is coupled to the engagement surface **68** in a third configuration. In this embodiment, the axis X_{A3} of the thumb rest assembly **54** intersects the axis X_H at a third angle θ_3, which is smaller than the first angle θ_1 (FIG. **9**A) and the second angle θ_2 (FIG. **9**B). While such positions have been illustrated here, it is to be understood that the thumb rest assembly **54** can be coupled to the engagement surface **68** in a variety of configurations to achieve variable positions. The position of the thumb rest assembly **54** can be selected by the archer.

Returning to FIGS. **1-7**, the archery release device **2** can include a release body **14** and a finger extension **16** coupled to the release body **14**. As further illustrated by FIGS. **7-11**, the release body **14** includes the draw cord hook **18** and the thumb grasp assembly **54**. The release body **14** further includes concave-shaped index finger engagement surface **36** defining an index finger space **13**. As shown in FIGS. **7-11**, the release body **14** also has a concave-shaped middle finger engagement surface **37** contoured to define a middle finger space **15**. The finger extension **16** includes: (a) a concave-shaped ring finger engagement surface **39** contoured to define a ring finger space **17**; and (b) a concave-shaped pinky finger engagement surface **41** contoured to define a pinky finger space **19**. The rear surface **8** can be straight, flat or contoured or have any suitable combination thereof

As illustrated in FIGS. **10-12**, the bottom section **78** of the release body **14** defines an body mount or coupling portion **40**. In the illustrated embodiment, the body mount **40** includes a first sidewall **42** and a second sidewall **44** spaced apart from the first sidewall **42**. A first sidewall bore or aperture **50** and a second sidewall bore or aperture **52** extend through each of the first and second sidewalls **42**, **44**, respectively, and are aligned along an axis A (FIG. **11**). In this embodiment, the first sidewall **42** is joined to the second sidewall **44** by a back surface **45**, with a gap, space, or cavity **48** (FIG. **12**) extending between the first and second sidewalls **42**, **44**. A guide member **46** extends through the gap **48** between the first sidewall **42** and the second sidewall **44** and extends backward to intersect the back surface **45**. The guide or guide member **46** has a top surface **80** (FIG. **11**) and a bottom surface **82** (FIG. **12**), each of which is exposed to the gap **48**. A bore, aperture, or opening **86** (FIG. **12**) extends through the guide member **46** from the top surface **80** to the bottom surface **82** and defines a guide track or cavity **84**. In the illustrated embodiment, the guide member **46** has a curved, arc-shaped profile extending in multiple planes. It should be appreciated that, in other embodiments not shown, the guide member can have a flat profile extending in a single plane.

Referring to FIGS. **14-21**, the finger extension **16** includes a extension interface **20**. In an embodiment, as illustrated in FIGS. **19-20**, the extension interface **20** has a dimension along axis A that is less than the dimension of the grasp portion **89** along axis A. In this embodiment, when viewed in profile, the extension interface **20** has a generally triangular shape with an upper, narrower "point" section **88** and a longer lower section **90**, as illustrated in FIG. **14**. The extension interface **20** includes a horizontal bore or aperture **22**, positioned near the front surface **6**, extending through the upper section **88** of the extension interface **20** and a guide opening, space, or track **24** extending at least partially through the lower portion **90** of the extension interface **20** from the top surface **26** of the finger extension **16** toward the bottom surface **28** of the finger extension **16** to define a first portion **92** and second portion **94** of the extension interface **20**. In an embodiment, the guide track **24** has a curved or arc shape. In the illustrated embodiment, the second portion **94** of the extension interface **20** is thinner than the first portion **92** and is configured to flex or move relative to the first portion **92**. The flex zone or flex space **95**, defined by the extension interface **20**, increases the flexibility of the section portion **94**. Accordingly, the second portion **94** functions as a flexible extension member. Alternatively, both the first portion **92** and second portion **94** can be configured to flex or move relative to each other or relative to the grasp portion **89**.

A vertical bore, aperture, or opening **30** (FIG. **14**), positioned near the top surface **26**, extends through the extension interface **20**, transverse to the track **24** and the horizontal bore **22**. In an embodiment, the vertical bore **30** extends substantially perpendicularly to the track **24** and the horizontal bore **22**. In this embodiment, the vertical bore **30** extends from the rear surface **8**, through the second section portion **94**, into and through the track **24**, and at least partially into the first portion **92**.

With particular reference to FIGS. **1** and **20**, the finger extension **16** is configured to be pivotally coupled to the release body **14**. In particular, in the illustrated embodiment, the extension interface **20** of the finger extension **16** is configured to be inserted in the gap **48** of the body mount **40** so that the horizontal bore **22** aligns with the first and second sidewall bores **50**, **52**, and the guide member **46** of the body mount **40** is inserted within the guide track **24** (FIG. **19**) of the extension interface **20**. In this example, the shape of the guide track **24** corresponds to the shape of the guide member **46**. For example, the arc shape of the guide track **24** can have the same, or substantially the same, radius as the arc shape of the guide member **46**.

As illustrated by FIG. **20**, in this embodiment, a pivot member **32**, such as a pin, is positioned within the horizontal bore **22** and the first and second sidewall bores **50**, **52** along the axis A. A position adjuster, position securement, position setter, or position locking member **34**, such as a set screw and washer, is positioned in the vertical bore **30** and extends through the guide track **84** of the guide member **46**. In an embodiment, illustrated in FIG. **21**, when the position locking member **34** is tightened or advanced into the vertical bore **30**, the leg **34***a* threadably engages the first portion **92**, and the head **34***b* engages the second portion **94**. During the screwing process, the head **34***b* applies a force **96** (a first securement force) to the second portion **94** of the extension interface **20**, causing the second portion **94** to flex or move toward the first portion **92** of the extension interface **20**. At

the same time, the leg **34***a* applies a force **98** (a second securement force) to the first portion **92**. The force **98** acts to urge the first portion **92** toward the second portion **94**. As shown, the guide member **46** is positioned within the guide track **84** between the first portion **92** and second portion **94**. The forces **94**, **98** act toward each other to generate a compression force acting on the guide member **46**. This results in a squeezing and clamping of the guide member **46** to lock or secure the position of the finger extension **16** relative to the release body **14**. In this example, due to the relative positions of the vertical and horizontal bores **30**, **22**, the forces **96**, **98** and the resulting compression force are exerted along an axis F (securement axis) that intersects with the pivot plane P (FIGS. **19** and **21**), the plane in which pivot member **32** extends.

This cooperative configurations of the extension interface **20** and the body mount **40** provide several advantages and improvements. The second portion **94** is relatively flexible and facilitates the ease in locking or securing the finger extension **16** to the release body **14**. Also, the compression force, acting along axis F, is transverse to or intersects with the pivot plane P, the plane of the axis A about which the finger extension **16** pivots. Such direction of the compression force, relative to the pivoting action of the finger extension **16**, enhances the securement of the finger extension **16** to the release body **14**. Furthermore, the contact surfaces **80**, **82** of the second portion **94** have relatively large surface areas. These relatively large surface areas increase the frictional forces between the guide member **46** and the finger extension **16**. This increase in frictional force enhances the securement of the finger extension **16** to the release body **14**. In addition, these relatively large surface areas improves the stability of the finger extension **16** on the release body **14**.

Referring to FIGS. **22-23**C, when the position locking member **34** is not fully tightened in the finger extension **16**, the finger extension **16** can pivot or rotate about the pivot member **32**, causing a slide engagement between the guide member **46** and the guide track **24** in which the guide track **24** slides along the guide member **46**. In an embodiment, the guide member **46** and guide track **24** can have a corresponding curved shape to facilitate the rotational movement of the finger extension **16**.

To adjust the angular position of the finger extension **16** relative to the release body **14**, the user can partially unscrew the position locking member **34**. This results in an adjustment mode. During the adjustment mode, the finger extension **16** is coupled to the release body **14** such that the finger extension **16** can pivot or rotate relative to the release body **14**. In this embodiment, the pivot member **32** extends along axis A about which the finger extension **16** rotates or pivots. As illustrated by FIG. **22**, the finger extension **16** can rotate or pivot between a variety of positions **100***a*, **100***b*, **100***c*. In an embodiment, when the finger extension **16** is in the desired position, the user can tighten the position locking member **34** (screwing it into the finger extension **16**), securing the position of the finger extension **16** to prevent movement relative to the release body **14**. While only three positions **100***a*, **100***b*, **100***c* are illustrated here, it should be under stood that the finger extension **16** can pivot between an unrestricted quantity of positions relative to the release body **14**. In another embodiment, not illustrated, the finger extension **16** freely rotates between a variety of positions without locking into any particular position. Furthermore, while the finger extension **16** is described as moving relative to the release body **14**, it is to be understood that the reverse, in which the release body **14** moves relative to the finger extension **16**, can also occur.

As illustrated in FIG. **20**, the finger extension **16** extends along a longitudinal finger extension axis X_{E1}, and the release body **14** extends along a longitudinal release body axis X_B. In the example shown in FIG. **23**A, when the finger extension **16** is at position **100***a*, the axis X_E of the finger extension **16** intersects the axis X_B of the release body **14** at a first angle θ_{E1}. In this position **100***a*, the position locking member **34** extends through the guide member **46** at a first end **102** of the guide member **46**. In the example shown in FIG. **23**B, when the finger extension **16** is at position **100***b*, the axis X_E of the finger extension **16** intersects the axis X_B of the release body **14** at a second angle θ_{E2}, which is smaller than the first angle θ_{E1}. In this position **100***b*, the position locking member **34** extends through the guide member **46** between the first end **102** and the second end **104**. In the example shown in FIG. **23**C, when the finger extension **16** is at position **100***c*, the axis X_E of the finger extension **16** intersects the axis X_B of the release body **14** at a third angle θ_{E3}, which is smaller than the first angle θ_{E1} and the second angle θ_{E2}. In this position **100***c*, the position locking member **34** extends through the guide member **46** at the second end **104**.

In an embodiment illustrated by FIG. **19** the extension interface **20** includes a position indicator **106** to indicate the angular position of the finger extension **16** relative to the release body **14**. In this embodiment, the position indicator **106** includes a series of marks or lines equally spaced apart from each other. Depending upon the embodiment, the release body **14** can include a complimentary position indicator (not shown) positioned adjacent to the position indicator **106**. The complimentary position indicator can include an arrow, line, symbol or other mark. During the adjustment mode, the user can view the a position indicator **106**, alone or in conjunction with the complimentary position indicator, to arrive at a desired position setting for the finger extension **16**. This facilitates the process of achieving repeatable position settings for the finger extension **16**, providing an improvement in fine tuning functionality.

It is to be understood that while the body mount **40** of the release body **14** and the extension interface **20** are described as having particular respective structures, the reverse is also possible in which the release body **14** includes the structural disposition of the extension interface **20** and the finger extension **16** includes the structural disposition of the body mount **40**.

By permitting the finger extension **16** to rotate between various positions relative to the release body **14**, a variety of hand shapes can be comfortably accommodate and the release **2** can be optimized to a particular archer's hand shape, resulting in more comfort for the archer and, potentially, improved shooting accuracy.

FIGS. **24-33** illustrate another embodiment of an archery release device **250**. Similar to the archery release device **2** described above, the archery release device **250** includes a release body **252** and an extension **200**. However, as will be further described below, the archery release device **250** additionally includes a position controller **226**.

With particular reference to FIGS. **25-31**, the extension **200** includes an extension body or housing **202**. The extension housing **202** has a first side **205**, and a second side **209**, a front surface **201** , and a rear surface **203** (FIG. **26**). Joining the first and second sides **205**, **209** is a finger engagement surface **210**. As described above with regard to archery release device **2**, the finger engagement surface **210** is

shaped to accommodate one or more fingers, such as the ring finger and/or pinky finger, of an archer. An opening, aperture, or bore **207** extends through the release body **202** from the first side **205** to the second side **209**. Each side **205**, **209** has a curved or arc shape with an leg **211**, **213** extending beyond the bottom of the front surface **201**.

As particularly illustrated by FIG. **28**, a pivot interface **204**, having the shape of a hollow cylinder, protrudes from the front surface **201** of the extension body **202** with a pivot bore or opening **235** extending through the pivot interface **204** from side **205** to side **209**. A first aperture **206** extends from the front surface **201** into the release body **202**. A second aperture **208**, located below the first aperture **206**, extends through the release body **202** from the front surface **201** to the rear surface **203**. As illustrated by FIG. **29**, at least a portion of the second aperture **208** has a threaded interior surface **215**.

The extension **200** also includes an interface member **228**. The interface member **228** has a first side surface **231** and a second side surface **233** (FIG. **29**) joined by a front surface **240** and a bottom surface **244** (FIG. **27**). An aperture **230** extends through the front surface **240**. A securement aperture **242** extends through the bottom surface **244**.

Each side surface **231**, **233**, has a leg or extension member **236**, **238** extending above or beyond the front surface **240**, opposite the bottom surface **244**, and defining a gap **237** between the extension members **236**, **238**. Each side surface **231**, **233** has a molded or shaped surface in which a y-shaped protrusion **229** extends outward. Each side surface **231**, **233** includes a pivot aperture **234** extending through the protrusion **229** of each side surface **231**, **233** to the gap **237**. In addition, an anchor aperture **232** extends through each side surface **231**, **233** to the gap **237** and a brace aperture **248** extends through each side surface **231**, **233** to the gap **237**.

As illustrated by FIG. **25**, when the extension is assembly, the interface body **228** is aligned with the extension body **202** so that the pivot interface **204** is positioned within the gap **237** and the pivot bore **235** is aligned with the pivot apertures **234**. As particularly illustrated by FIG. **26**, a pivot member **216** is received or retained in the pivot aperture **235** of the extension body **202** and the pivot apertures **234** of the interface body **228**. The pivot member **216** extends along a pivot axis S, extending in a pivot plane P_S (FIG. **27**). A first washer **212** and second washer **214** are disposed on either end of the pivot member **216** between the pivot interface **204** and the sides **231**, **233**. Due to this pivot connection, the extension body **202** is able to pivot or rotate about the pivot axis S relative to the interface body **228**, or vice versa.

As illustrated by FIG. **30**, a brace member **224**, such as a pin, is retained or positioned within the brace apertures **248**, spanning the gap **237**. A position adjuster **226** is positioned within the second aperture **208** of the extension body **202**. In the illustrated embodiment, the position adjuster **226** is a set screw having a threaded surface that engages the threaded surface **215** of the second aperture **208**. The position adjuster **226** makes direct physical contact with the brace member **224**.

The extension **200** also includes a biasing member **222**, such as an extension spring, which is anchored at each end by a first anchor member **218** and a second anchor member **220**, respectively, as illustrated by FIG. **28**. As particularly illustrated by FIG. **30**, the first anchor member **218** is retained or positioned with the aperture **207** of the extension body **202** and the second anchor member **220** is retained within the anchor apertures **232**, and spanning the gap **237**, of the interface body **228**. The biasing member **222** is retained at least partially within the aperture **206**, extending into the extension body **202** and is anchored at either end to the first anchor member **218** and the second anchor member **220**. In operation, the biasing member **222** biases the interface body **228** and the extension body **202** towards each other in order to maintain physical contact between the brace member **224** and the position adjuster **226**.

In operation, the position adjuster **226** can be rotated, such as by inserting a tool (not shown) in the second aperture **208**. The rotation of the position adjuster **226** engages the threaded surface **215** of the second aperture **208**. As the position adjuster **226** is in physical contact with the brace member **224**, as maintained by the biasing member **222**, the engagement of the threaded surface **215** causes the extension body **202** to rotate about the pivot member **216**. This rotation changes the angle of the extension body **202** (or the longitudinal axis extending therein) relative to the release body **252**. For example, each revolution of the position adjuster **226** causes a designated change in the degree of such angle. This enables the user to fine tune the extension body **202** with a relatively high amount of incremental control or micro control. It should be appreciated that even a partial rotation of the position adjuster **226** will correspond to a designated change in such angle that may be desired by the user. After the user has reached the desired angle of the extension body **202** relative to the release body **252**, the user can grasp the archery release device **250** for aiming and shooting purposes. While the user is applying a grasping force to the extension body **202**, counteracting the pulling force of the draw cord, there will be physical contact between the brace member **224** and the position adjuster **226**. When the user removes the user's grasp force, for example, when temporarily disengaging the archery release device **250** from the draw cord, the biasing member **222** ensures that the extension body **202** maintains the desired angle. To achieve this, the biasing member **222** applies a constant biasing force that keeps the position adjuster **226** in physical contact with the brace member **224**. This operates to maintain the desired angle of the extension body **202** without relying upon the user's grasping force.

Referring to FIG. **32**, the release body **252** includes a housing **254**. The housing **254** has a similar overall shape to the housing **4** of the archery release device **2** described above. In this embodiment, the housing **254** includes a body interface **256** for coupling to the extension **200**. In the illustrated embodiment, the body interface **256** has a molded shape that conforms or cooperates with the shape of the interface body **228**. In this embodiment, the body interface **256** has a y-shaped cutout area that corresponds to the y-shaped protrusion **229** of the interface body **228** and a surrounding protruding area **262**. Below the protruding area **262**, a second cutout or depression area **260** corresponds to the shape of the front edge and legs **211**, **213** of the sides **205**, **209** of the extension body **202**. An interior ledge **264** separates the second cutout area **260** and the protruding area **262** from a third cutout area **266**. An aperture or bore **268** extends through the ledge **264**.

As particularly illustrated by FIG. **24**, the interface body **228** and extension body **202** are positioned within the body interface **256**. In order to secure the interface body **228**, a fastener **242**, such as a screw, is inserted, via the third cutout area **266**, through the aperture **268** and into the securement aperture **242** of the interface body **228**. When the extension **200** is secured within the body interface **256**, the position or angle of the extension body **202** can be adjusted relative to the interface body **228** and the release body **252** as described above using the position adjuster **226**. It is to be understood that while the interface body **228** has been described here as

a separate body coupled to the release body **252**, the structural features of the interface body **228** could alternatively be directly incorporated in the housing **254** of the release body **252**.

Referring to FIGS. **34-53**, in another embodiment, the archery release device **310** includes the same structure, components, elements and functionality as the archery release device **2** in addition to: (a) an upper housing portion **312**; (b) a lower housing portion **314**; (c) a trigger **316** pivotally coupled to the lower housing portion **314** through a post, boss or pivot member **318**; (d) a hammer or driver **320** pivotally coupled to the lower housing portion **314** through a post, boss or pivot member **322**; (e) a stay unit or retainer **324** pivotally coupled to the lower housing portion **314** through a post, boss or pivot member **326**; (f) a release force generator **328** coupled to the lower housing portion **314** and the driver **320** as described below; (g) a trigger motion limiter **330** threadably engaged with the lower housing portion **314** and configured to engage the trigger **316**; (h) a trigger pressurizer **332** threadably engaged with the lower housing portion **314** and configured to apply an adjustable force or pressure to the trigger **316**; (i) a plurality of stabilizing interfaces **334** and **336** engaged with the trigger **316** and the driver **320**, respectively; (j) a plurality of base biasing members **338** and **340** (FIG. **39**) positioned underneath the trigger **316** and the driver **320**, respectively; (k) a torsion spring **342** (FIG. **40**) that couples the draw cord holder **18** to the retainer **324** and applies a rotational biasing force to the draw cord holder **18**; (l) a supplemental biasing member **344** (e.g., a compression spring or coil spring) supported by the lower housing portion **314** and configured to apply a supplemental biasing force to the driver **320** or the retainer **324**; and (m) a plurality of screws, bolts or other fasteners **346** configured to secure the upper housing portion **312** to the lower housing portion **314**.

The upper and lower housing portions **312**, **314** cooperate to define an interior housing space **348**, as illustrated in FIG. **37**. In the example shown, the archery release device **310** is in the cocked position or cocked condition. In the cocked condition, the cord holder **18** would secure or hold the draw cord **350** (FIG. **42**) retracted by the user. In the embodiment illustrated in FIGS. **42-44**, the release force generator **328** includes an extension spring having a plurality of force generator ends **352**, **354**. Also, as illustrated in FIG. **44**, the driver **320** has a right driver arm **356** that defines a space, recess or notch **358**, and the archery release device **310** has a boss or post **360** extending from the lower housing portion **314**. The force generator end **352** has a hook or U-shape that fits within the notch **358** and partially wraps around the force generator end **352**. The force generator end **354** also has a hook or U-shape, and it partially encircles the post **360**. In operation, the release force generator **328** applies a spring force to the driver arm **356**, urging the driver **320** to rotate clockwise about the pivot member **322**.

In addition, the supplemental biasing member **344** can apply an additional biasing force to the driver arm **356**, as shown in FIG. **43**. In another embodiment, the archery release device **310** excludes the supplemental biasing member **344** because the release force generator **328**, alone, produces sufficient spring force on the driver arm **356**. In yet another embodiment, the supplemental biasing member **344** is configured and positioned to apply a spring force to the retainer **324**, not the driver **320**. It should be appreciated that the archery release device **310** can be fully operational with or without the supplemental biasing member **344**.

In the cocked condition, the trigger **316** blocks the rotation of the driver **320**. The blocked driver **320** immobilizes the retainer **324**, which, in turn, immobilizes the cord holder **18**. The trigger **316** has a Y-shape including a left arm **362**, a right arm **364** and a body **366**. The body **366** is coupled to the arm member **60** which, in turn, is coupled to the thumb grasp body **56**. In the cocked condition, the left arm **362** interferes with or otherwise overlaps the driver arm **356**. When ready to shoot, the user can pull the thumb grasp body **56**, causing the arm member **60** to pivot clockwise **368** (FIG. **42**). In response, the left arm **362** rotates clockwise **368** and disengages the driver arm **356**. Because of the spring forces of the release force generator **328** (and, depending upon the embodiment, the supplemental biasing member **344**) the driver **320** then rotates clockwise **368**, causing the left driver arm **370** to apply an upward force to the retainer end **372** of the retainer **324**. This causes the retainer **324** to pivot or rotate clockwise **368** about the pivot member **326**. As a result, the retainer end **374** disengages the cord holder **18**, enabling the cord holder **18** to rotate about the pivot member **376**. As the cord holder **18** rotates, the draw cord **314** slides off of the cord holder **18** to launch an arrow or projectile toward a target.

As illustrated in FIG. **44**, the release force generator **328** has an intermediate portion **378**. The intermediate portion **378** includes a plurality of loops of wire arranged in a helical or spiral shape. The intermediate portion **378** is positioned between the ends **352**, **354**. The intermediate portion **378** is configured to resist being pulled along the force axis **380**. When release force generator **328** is coupled to the right driver arm **356** and the post **360**, the release force generator **328** produces a spring force acting along the force axis **380**. The spring force acts from the right driver arm **356** toward the post **360**. In an embodiment, the loops of the intermediate portion **378** are spaced apart from each other and remain spaced apart from each other throughout the transition of the archery release device **310** from the cocked condition to a released or uncocked condition.

As illustrated in FIGS. **45-46**, prior art release aids rely substantially on or entirely on one or more compression springs (e.g., prior art compression spring **382**) to generate a release force. For example, the prior art compression spring **382** is supported by a prior art housing **384**, and the prior art compression spring **382** extends to engage a prior art hammer, such as a prior art hammer **386** or **387** of a prior art release aid. As shown in FIG. **45**, the prior art compression spring **382** tends to bend and buckle during usage. This can be caused by various factors, including, but not limited to, the geometries of the hammers **386**, **387** and the positions of the hammers **386**, **387**. For example, the hammer **386** extends in a plane that intersects with the plane in which the housing **384** extends. The intersection of these planes is associated with a cause of the bending and buckling. The bending and buckling of the prior art compression spring **382** results in a plurality of extraneous spring forces **388** other than the desired axial force **390** along axis **392**. Consequently, a substantial amount of the spring force of the prior art compression spring **382** fails to reach the intended hammer **386** or **387**. This results in a substantial inefficiency in force transmission within the prior art release aids which, in turn, impairs the release and triggering performance and responsiveness.

In contrast to the prior art compression spring **382**, the release force generator **328** produces a spring force that acts entirely or substantially entirely along the force axis **380** (FIG. **44**). This is because the release force generator **328** is operable through tension rather than compression. By avoiding compression, the release force generator **328** is not vulnerable to buckling or bending like the prior art com-

pression spring **382**. Consequently, the release force generator **328** provides substantial improvement in the efficiency of force transmission, and in release and triggering performance, reliability and responsiveness.

Referring to FIG. **47**, various destabilization forces can act upon the trigger **316** and the driver **320**, including, but not limited to, the user force **394** and other destabilization forces **396** generated by components within the archery release device **310**. These destabilization forces can urge or cause the trigger **316** and the driver **320** to become unseated, loose or out of position. The full or partial unseating of the trigger **316** or the driver **320** can substantially impair the release and triggering performance of the archery release device **310**.

The trigger **316** and the driver **320** are at least partially encased within or entrapped by the upper and lower housing portions **312**, **314**. As illustrated in FIG. **41**, the base biasing members **338** and **340** apply upward spring forces to the trigger bottom surface **398** and the driver bottom surface **400**, respectively. Depending upon the embodiment, the base biasing members **338**, **340** can include wavy washers, compression springs, elastic rings or other suitable elastic, biasing or shock-absorbing members. The base biasing members **338**, **340** are therefore operable to bias the trigger **316** and the driver **320** toward the upper housing portion **312**.

In the embodiment illustrated in FIGS. **47-49**: (a) the stabilizing interface **334** includes a ring defining a circular opening configured to receive the pivot member **318**; and (b) the stabilizing interface **336** includes a ring defining a circular opening configured to receive the pivot member **322**. Depending upon the embodiment, each of the stabilizing interfaces **334**, **336** can include a washer, disk, block or other member configured to receive the pivot member **318** or **322**, as applicable. Each of the stabilizing interfaces **334**, **336** can be constructed of any suitable material, including, but not limited to, materials associated with relatively low surface friction, such as silicon or other suitable polymers or metals. In an embodiment, the stabilizing interfaces **334**, **336** have friction reduction characteristics.

As shown in FIGS. **40** and **41**, the trigger **316** has relatively large trigger bottom and top surfaces **398**, **402**, and the driver **320** has relatively large driver bottom and top surfaces **398**, **402**. As described above, the transition from cocked condition to uncocked condition requires the rotation of the trigger **316** and the driver **320**. Once the user pulls the thumb grasp body **56**, the frictional forces acting on the surfaces **398**, **400**, **402**, **404** can impede the free movement of the trigger **316** and the driver **320** which, in turn, can impair the triggering responsiveness of the archery release device **310**. To reduce such friction, the base biasing members **338**, **340** and the stabilizing interfaces **334**, **336** isolate the trigger **316** and the driver **320** from the surfaces of the upper and lower housing portions **312**, **314**. In an embodiment, the base biasing member **338** engages less than 50% of the trigger bottom surface **398**, the base biasing member **340** engages less than 50% of the driver bottom surface **400**, the stabilizing interface **334** engages less than 50% of the trigger top surface **402**, and the stabilizing interface **336** engages less than 50% of the driver top surface **404**. This reduced physical engagement facilitates the smooth and free rotation of the trigger **316** and the driver **320** within the upper and lower housing portions **312**, **314**.

In addition, the stabilizing interfaces **334**, **336** function as spacers between the upper housing portion **312** and the trigger **316** and the driver **320**. In an embodiment illustrated in FIGS. **48-49**, the upper housing portion **312** has an interior housing surface **406** that defines: (a) a trigger stabilizer cavity **408** configured to receive part or all of the stabilizing interface **334**; and (b) a driver stabilizer cavity **410** configured to receive part or all of the stabilizing interface **336**. When the upper housing portion **312** is secured to the lower housing portion **314**, the cavity surfaces **412** and **416** apply securing forces to the stabilizing interfaces **334** and **336**, respectively, which, in turn, transfer the securing forces to the trigger top surface **402** and the driver top surface **404**, respectively. The securing forces counteract the biasing forces exerted by the base biasing members **338**, **340**. The sum of these forces on the trigger **316** and the driver **320** help to secure the proper seating of the trigger **316** and the driver **320** within the archery release device **310**. Furthermore, because the stabilizing interfaces **334**, **336** and the base biasing members **338**, **340** engage a relatively small percentage of the surface areas of the trigger **316** and the driver **320**, these securing forces have a relatively small impact on restricting the rotational movement of the trigger **316** and the driver **320**. This helps to improve the triggering responsiveness of the archery release device **310**.

In another embodiment not shown, the interior housing surface **406** of the upper housing portion **312** defines the stabilizing interfaces. In such embodiment, such stabilizing interfaces are not separate components. Instead, such stabilizing interfaces are integrated into, and unitary with, the interior housing surface **406**. For example, the interior housing surface **406** can define: (a) a peak, protrusion or raised portion of the same or similar geometry as the stabilizing interface **334**; and (b) a peak, protrusion or raised portion of the same or similar geometry as the stabilizing interface **336**. Such integrated stabilizing interfaces are configured to perform the same function as the stabilizing interfaces **334**, **336** described above.

Referring to FIGS. **42** and **50-53**, in an embodiment, the trigger motion limiter **330** is configured to be threadably engaged with the lower housing portion **314**. The trigger motion limiter **330** extends into a channel **423** defined by the upper and lower housing portions **312**, **314**. In an embodiment, the trigger motion limiter **330** includes a set screw. By adjusting or screwing the trigger motion limiter **330** relative to the lower housing portion **314**, the user or assembler can cause the trigger motion limiter **330** to engage the body **366** of the trigger **316**. By rotating the trigger motion limiter **330** clockwise, the user or assembler can decrease the extent of the engagement, overlap or interference between the trigger left arm **362** and the driver right arm **356**. By rotating the trigger motion limiter **330** counterclockwise, the user or assembler can increase the extent of the engagement, overlap or interference between the trigger left arm **362** and the driver right arm **356**. As such engagement, overlap or interference is decreased, the triggering sensitivity increases. Accordingly, the user or assembler can adjust the triggering sensitivity by rotating the trigger motion limiter **330** according to the user's preference.

As illustrated in FIGS. **51-53**, the trigger pressurizer **332** includes: (a) a pressurizer body **416** that defines a cavity **418**; and (b) a biasing member **420** that fits partially within the cavity **418**. The exterior **422** of the pressurizer body **416** is threaded and configured to threadably engage the lower housing portion **312**. The trigger pressurizer **332** extends into a threaded channel **424** defined by the upper and lower housing portions **312**, **314**. In an embodiment, the pressurizer body **416** includes a partially-hollowed set screw, and the biasing member **420** includes a compression spring. When the biasing member **420** is unrestrained, less than all of the biasing member **420** fits within the cavity **418**, as

shown in FIG. **51**. As the user screws the trigger pressurizer **332** into the threaded channel **424**, the biasing member **420** eventually reaches, and applies a spring force to, the right arm **364** of the trigger **316**. This spring forces applies a constant biasing force to the trigger **316**. The user can adjust this force, and resulting pressure, by rotating the trigger pressurizer **332** clockwise or counterclockwise. This biasing pressure can affect the triggering sensitivity and, therefore, provides the user with a another setting for fine tuning the archery release device **310**.

Additional embodiments include any one of the embodiments described above, where one or more of its components, functionalities or structures is interchanged with, replaced by or augmented by one or more of the components, functionalities or structures of a different embodiment described above.

It should be understood that various changes and modifications to the embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present disclosure and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims.

Although several embodiments have been disclosed in the foregoing specification, it is understood by those skilled in the art that many modifications and other embodiments of the disclosure will come to mind to which the disclosure pertains, having the benefit of the teaching presented in the foregoing description and associated drawings. It is thus understood that the disclosure is not limited to the specific embodiments disclosed herein above, and that many modifications and other embodiments are intended to be included within the scope of the appended claims. Moreover, although specific terms are employed herein, as well as in the claims which follow, they are used only in a generic and descriptive sense, and not for the purposes of limiting the present disclosure, nor the claims which follow.

The following is claimed:

1. An archery release device comprising:

a first housing portion;

a second housing portion;

a trigger configured to be positioned at least partially between the first and second housing portions, wherein:

the trigger comprises: (a) a first trigger surface configured to face the first housing portion; and (b) a second trigger surface configured to face the second housing portion;

the first trigger surface comprises a plurality of first surfaces, wherein the first surfaces comprise a first engagement surface; and

the second trigger surface comprises a plurality of second surfaces, wherein the second surfaces comprise a second engagement surface;

a first interface member configured to be positioned between the first trigger surface and the first housing portion, wherein the first interface member is configured to engage the first engagement surface without engaging any other first surfaces of the first trigger surface;

a second interface member configured to be positioned between the second trigger surface and the second housing portion, wherein the second interface member is configured to engage the second engagement surface without engaging any other second surfaces of the second trigger surface; and

a cord holder operatively coupled to the trigger,

wherein the trigger is configured to pivot about an axis relative to the first and second housing portions in response to a force applied to the trigger,

wherein the first and second interfaces are configured to restrict any movement of the trigger that occurs in a direction along the axis,

wherein a responsiveness of the trigger is facilitated by a lack of engagement with the other first and second surfaces during the pivoting of the trigger.

2. The archery release device of claim **1**, wherein the first trigger surface is located opposite of the second trigger surface.

3. The archery release device of claim **1**, wherein the first interface member comprises a base biasing member.

4. The archery release device of claim **3**, wherein the base biasing member comprises a ring-shaped member comprising an elastic characteristic.

5. The archery release device of claim **1**, wherein the second interface member comprises a stabilizing interface.

6. The archery release device of claim **5**, wherein the stabilizing interface comprises a ring-shaped member.

7. The archery release device of claim **1**, wherein:

the first interface member is configured to be decoupled from the first housing portion; and

the second interface member is configured to be decoupled from the second housing portion.

8. The archery release device of claim **1**, wherein:

the first housing portion integrally defines the first interface member so that the first interface member is unitary with the first housing portion; and

the second housing portion integrally defines the second interface member so that the second interface member is unitary with the second housing portion.

9. The archery release device of claim **1**, comprising a pivot member coupled to one of the first and second housing portions, wherein:

the trigger defines a passageway through which the axis extends;

the passageway extends through the first and second engagement surfaces; and

the passageway is configured to receive the pivot member.

10. The archery release device of claim **1**, wherein:

the trigger comprises an engagement portion positioned between the first and second engagement surfaces; and

the first and second housing portions and the first and second interface members are configured to cooperate to apply a securing force that acts on the engagement portion and no other portion of the trigger.

11. An archery release device comprising:

a first housing portion;

a second housing portion;

a trigger configured to be positioned at least partially between the first and second housing portions, wherein the trigger comprises an engagement portion and an other portion, wherein the engagement portion comprises first and second engagement surfaces located opposite of each other;

a first interface member configured to be positioned between the first engagement surface and the first housing portion; and

a second interface member configured to be positioned between the second engagement surface and the second housing portion,

wherein the first and second housing portions and the first and second interface members are configured to cooperate to apply a securing force,

wherein the securing force acts on the engagement portion without acting on the other portion of the trigger.

12. The archery release device of claim **11**, wherein the trigger is configured to pivot about an axis relative to the first and second housing portions in response to a force applied to the trigger.

13. The archery release device of claim **12**, wherein the first and second interfaces are configured to restrict any translational movement of the trigger that occurs in a direction along the axis.

14. The archery release device of claim **11**, wherein:

the first interface member comprises a base biasing member.

the second interface member comprises a stabilizing interface.

15. The archery release device of claim **11**, wherein:

the first interface member is configured to be decoupled from the first housing portion; and

the second interface member is configured to be decoupled from the second housing portion.

16. The archery release device of claim **11**, wherein:

the first housing portion integrally defines the first interface member so that the first interface member is unitary with the first housing portion; and

the second housing portion integrally defines the second interface member so that the second interface member is unitary with the second housing portion.

17. A method for manufacturing an archery release device, the method comprising:

configuring a first housing portion;

configuring a second housing portion;

positioning a trigger at least partially between the first and second housing portions, wherein the trigger comprises an engagement portion and an other portion, wherein the engagement portion comprises first and second engagement surfaces located opposite of each other;

positioning a first interface member between the first engagement surface and the first housing portion; and

positioning a second interface member between the second engagement surface and the second housing portion,

wherein the first and second housing portions and the first and second interface members are positioned and configured to cooperate to apply a securing force,

wherein the securing force acts on the engagement portion without acting on the other portion of the trigger.

18. The method of claim **17**, comprising:

configuring the trigger to pivot about an axis relative to the first and second housing portions in response to a force applied to the trigger; and

positioning the first and second interfaces to restrict any translational movement of the trigger that occurs in a direction along the axis.

19. The method of claim **18**, wherein the configuring of the first and second housing portions comprises:

defining the first interface member so that the first interface member is unitary with the first housing portion; and

defining the second interface member so that the second interface member is unitary with the second housing portion.

20. The method of claim **18**, comprising:

coupling the first interface member to the first housing portion so that the first interface member is configured to be decoupled from the first housing portion; and

coupling the second interface member to the second housing portion so that the second interface member is configured to be decoupled from the second housing portion.

* * * * *