US007448963B2

(12) **United States Patent**
Beach et al.

(10) **Patent No.: US 7,448,963 B2**
(45) **Date of Patent: *Nov. 11, 2008**

(54) **GOLF CLUB HEAD HAVING MOVABLE WEIGHTS**

(75) Inventors: **Todd P. Beach**, San Diego, CA (US); **Thomas Olsavsky**, Oceanside, CA (US); **Benoit Vincent**, Encinitas, CA (US); **Ian Wright**, Calgary (CA); **Kraig Willett**, Fallbrook, CA (US); **Gery Mel Zimmerman**, Fallbrook, CA (US); **Joseph Hoffman**, Carlsbad, CA (US)

(73) Assignee: **Taylor Made Golf Company, Inc.**, Carlsbad, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **11/669,900**

(22) Filed: **Jan. 31, 2007**

(65) **Prior Publication Data**

US 2007/0105652 A1 May 10, 2007

Related U.S. Application Data

(63) Continuation of application No. 11/067,475, filed on Feb. 25, 2005, now Pat. No. 7,186,190, which is a continuation-in-part of application No. 10/785,692, filed on Feb. 23, 2004, now Pat. No. 7,166,040, which is a continuation-in-part of application No. 10/290,817, filed on Nov. 8, 2002, now Pat. No. 6,773,360.

(51) **Int. Cl.**
A63B 53/04 (2006.01)
A63B 53/06 (2006.01)

(52) **U.S. Cl.** **473/337**; 473/349
(58) **Field of Classification Search** ..... None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,518,316	A	12/1924	Ellingham
1,526,438	A	2/1925	Scott
1,538,312	A	5/1925	Beat
1,592,463	A	7/1926	Marker

(Continued)

FOREIGN PATENT DOCUMENTS

DE	9012884	9/1990

(Continued)

OTHER PUBLICATIONS


Jackson, Jeff, The Modern Guide to Golf Clubmaking, Ohio: Dynacraft Golf Products, Inc., copyright 1994, p. 237.

Primary Examiner—Eugene Kim
Assistant Examiner—Alvin A. Hunter, Jr
(74) *Attorney, Agent, or Firm*—Klarquist Sparkman, LLP

(57) **ABSTRACT**

One embodiment of a golf club head having movable weights includes a body with a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt positioned around a periphery of the golf club head between the sole and the crown. Two or more weight ports are formed in the body and at least two weights are configured to be retained at least partially within the weight ports.

35 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

1,658,581	A	2/1928	Tobia
1,704,119	A	3/1929	Buhrke
1,970,409	A	8/1934	Wiedemann
D107,007	S	11/1937	Cashmore
2,214,356	A	9/1940	Wettlaufer
2,225,930	A	12/1940	Sexton
2,360,364	A	10/1944	Reach
2,460,435	A	2/1949	Schaffer
2,681,523	A	6/1954	Sellers
3,064,980	A	11/1962	Steiner
3,466,047	A	9/1969	Rodia et al.
3,556,533	A	1/1971	Hollis
3,589,731	A	6/1971	Chancellor
3,606,327	A	9/1971	Gorman
3,610,630	A	10/1971	Glover
3,652,094	A	3/1972	Glover
3,672,419	A	6/1972	Fischer
3,692,306	A	9/1972	Glover
3,743,297	A	7/1973	Dennis
3,897,066	A	7/1975	Belmont
3,976,299	A	8/1976	Lawrence et al.
3,979,122	A	9/1976	Belmont
3,979,123	A	9/1976	Belmont
4,008,896	A	2/1977	Gordos
4,043,563	A	8/1977	Churchward
4,052,075	A	10/1977	Daly
4,076,254	A	2/1978	Nygren
4,085,934	A	4/1978	Churchward
4,121,832	A	10/1978	Ebbing
4,214,754	A	7/1980	Zebelean
4,262,562	A	4/1981	MacNeill
D259,698	S	6/1981	MacNeill
4,340,229	A	7/1982	Stuff, Jr.
4,411,430	A	10/1983	Dian
4,423,874	A	1/1984	Stuff, Jr.
4,438,931	A	3/1984	Motomiya
4,530,505	A	7/1985	Stuff
D284,346	S	6/1986	Masters
4,602,787	A	7/1986	Sugioka et al.
4,607,846	A	8/1986	Perkins
4,730,830	A	3/1988	Tilley
4,736,093	A	4/1988	Braly
4,754,977	A	7/1988	Sahm
4,795,159	A	1/1989	Nagamoto
4,867,457	A	9/1989	Lowe
4,867,458	A	9/1989	Sumikawa et al.
4,869,507	A	9/1989	Sahm
4,895,371	A	1/1990	Bushner
4,962,932	A	10/1990	Anderson
4,994,515	A	2/1991	Washiyama et al.
5,039,267	A	8/1991	Wollar
5,050,879	A	9/1991	Sun et al.
5,058,895	A	10/1991	Igarashi
5,244,210	A	9/1993	Au
5,253,869	A	10/1993	Dingle et al.
D343,558	S	1/1994	Latraverse et al.
5,316,305	A	5/1994	McCabe
5,320,005	A	6/1994	Hsiao
5,328,176	A	7/1994	Lo
5,385,348	A	1/1995	Wargo
5,410,798	A	5/1995	Lo
5,421,577	A	6/1995	Kobayashi
5,429,365	A	7/1995	McKeighen
5,439,222	A	8/1995	Kranenberg
5,441,274	A	8/1995	Clay
5,447,309	A	9/1995	Vincent
5,518,243	A	5/1996	Redman
5,533,730	A	7/1996	Ruvang
5,571,053	A	11/1996	Lane
5,624,331	A	4/1997	Lo et al.
5,629,475	A	5/1997	Chastonay
5,632,694	A	5/1997	Lee
5,669,827	A	9/1997	Nagamoto
5,683,309	A	11/1997	Reimers
5,709,613	A	1/1998	Sheraw
5,718,641	A	2/1998	Lin
D392,526	S	3/1998	Nicely
5,746,664	A	5/1998	Reynolds, Jr.
5,755,627	A	5/1998	Yamazaki et al.
5,769,737	A	6/1998	Holladay et al.
5,776,011	A	7/1998	Su et al.
RE35,955	E	11/1998	Lu
D409,463	S	5/1999	McMullin
5,908,356	A	6/1999	Nagamoto
5,911,638	A	6/1999	Parente et al.
D412,547	S	8/1999	Fong
5,935,019	A	8/1999	Yamamoto
5,941,782	A	8/1999	Cook
5,947,840	A	9/1999	Ryan
5,967,905	A	10/1999	Nakahara et al.
5,997,415	A	12/1999	Wood
6,015,354	A	1/2000	Ahn et al.
6,019,686	A	2/2000	Gray
6,023,891	A	2/2000	Robertson et al.
6,032,677	A	3/2000	Blechman et al.
6,056,649	A	5/2000	Imai
6,089,994	A	7/2000	Sun
6,149,533	A	11/2000	Finn
6,162,133	A	12/2000	Peterson
6,238,303	B1	5/2001	Fite
6,270,422	B1	8/2001	Fisher
6,277,032	B1	8/2001	Smith
6,296,579	B1	10/2001	Robinson
6,299,547	B1	10/2001	Kosmatka
6,334,817	B1	1/2002	Ezawa et al.
6,348,014	B1	2/2002	Chiu
6,379,265	B1	4/2002	Hirakawa et al.
6,383,090	B1	5/2002	O'Doherty et al.
6,390,933	B1	5/2002	Galloway
6,409,612	B1	6/2002	Evans et al.
6,436,142	B1	8/2002	Paes et al.
6,440,009	B1	8/2002	Guibaud et al.
6,514,154	B1	2/2003	Finn
6,524,197	B2	2/2003	Boone
6,527,649	B1	3/2003	Neher et al.
6,530,848	B2	3/2003	Gillig
6,565,448	B2	5/2003	Cameron et al.
6,569,040	B2	5/2003	Bradstock
6,641,487	B1	11/2003	Hamburger
6,669,571	B1	12/2003	Cameron et al.
6,739,983	B2	5/2004	Helmstetter et al.
6,757,572	B1	6/2004	Forest
6,773,360	B2	8/2004	Willett et al.
6,974,393	B2	12/2005	Caldwell et al.
6,988,960	B2	1/2006	Mahaffey et al.
6,991,558	B2	1/2006	Beach et al.
7,140,974	B2	11/2006	Chao et al.
7,153,220	B2	12/2006	Lo
7,163,468	B2	1/2007	Gibbs et al.
7,166,040	B2	1/2007	Hoffman et al.
7,169,060	B2	1/2007	Stevens et al.
7,186,190	B1 *	3/2007	Beach et al. 473/335
7,223,180	B2	5/2007	Willett et al.
2001/0049310	A1	12/2001	Cheng et al.
2002/0022535	A1	2/2002	Takeda
2002/0032075	A1	3/2002	Vatsvog
2002/0072434	A1	6/2002	Yabu
2002/0137576	A1	9/2002	Dammen
2002/0160854	A1	10/2002	Beach et al.
2003/0130059	A1	7/2003	Billings
2004/0087388	A1	5/2004	Beach et al.
2004/0242343	A1	12/2004	Chao

2006/0058112 A1 3/2006 Haralason et al.

FOREIGN PATENT DOCUMENTS

EP	1001175	5/2000
GB	194823	12/1921
JP	05-317465	5/1992
JP	06-304271	4/1993
JP	5317465	12/1993
JP	06-126004	5/1994
JP	6304271	11/1994
JP	09-028844	2/1997
JP	09-327534	12/1997
JP	9308717	12/1997
JP	2773009	7/1998
JP	10-234902	8/1998
JP	10277187	10/1998
JP	2004 222911	8/2004
WO	WO 88/02642	4/1988
WO	WO 01/66199	9/2001
WO	WO 02/062501	8/2002
WO	WO 03/061773	7/2003

* cited by examiner



20
22
30
24
32
26
High
Low
Left
Right
HIGH
1 High
2
3 More Left
4 Left
5 Right
6 More Right
2 Low
10
1
10
2

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



26
48
50
40
High
1
High
3
More Left
4
Left
5
Right
40
40
6
More Right
2
Low
Low
Left
Right
52
53
10
10
2
1
2
42
HIGH
55
44
39

FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19

GOLF CLUB HEAD HAVING MOVABLE WEIGHTS

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 11/067,475, filed Feb. 25, 2005, now U.S. Pat. No. 7,186,190, which is a continuation-in-part of U.S. patent application Ser. No. 10/785,692, filed Feb. 23, 2004, now U.S. Pat. No. 7,166,040, which is a continuation-in-part of U.S. patent application Ser. No. 10/290,817 filed Nov. 8, 2002, now U.S. Pat. No. 6,773,360. These applications are incorporated herein by this reference.

FIELD

The present application is directed to a golf club head, particularly a golf club head having movable weights.

BACKGROUND

The center of gravity (CG) of a golf club head is a critical parameter of the club's performance. Upon impact, the position of the CG greatly affects launch angle and flight trajectory of a struck golf ball. Thus, much effort has been made over positioning the center of gravity of golf club heads. To that end, current driver and fairway wood golf club heads are typically formed of lightweight, yet durable material, such as steel or titanium alloys. These materials are typically used to form thin club head walls. Thinner walls are lighter, and thus result in greater discretionary weight, i.e., weight available for redistribution around a golf club head. Greater discretionary weight allows golf club manufacturers more leeway in assigning club mass to achieve desired golf club head mass distributions.

Various approaches have been implemented for positioning discretionary mass about a golf club head. Many club heads have integral sole weight pads cast into the head at predetermined locations to lower the club head's center of gravity. Also, epoxy may be added to the interior of the club head through the club head's hosel opening to obtain a final desired weight of the club head. To achieve significant localized mass, weights formed of high-density materials have been attached to the sole, skirt, and other parts of a club head. With these weights, the method of installation is critical because the club head endures significant loads at impact with a golf ball, which can dislodge the weight. Thus, such weights are usually permanently attached to the club head and are limited in total mass. This, of course, permanently fixes the club head's center of gravity.

Golf swings vary among golfers, but the total weight and center of gravity location for a given club head is typically set for a standard, or ideal, swing type. Thus, even though the weight may be too light or too heavy, or the center of gravity too far forward or too far rearward, the golfer cannot adjust or customize the club weighting to his or her particular swing. Rather, golfers often must test a number of different types and/or brands of golf clubs to find one that is suited for them. This approach may not provide a golf club with an optimum weight and center of gravity and certainly would eliminate the possibility of altering the performance of a single golf club from one configuration to another and then back again.

It should, therefore, be appreciated that there is a need for a system for adjustably weighting a golf club head that allows a golfer to fine-tune the club head to accommodate his or her swing. The present application fulfills this need and others.

SUMMARY

Disclosed below are representative embodiments that are not intended to be limiting in any way. Instead, the present disclosure is directed toward novel and nonobvious features, aspects, and equivalents of the embodiments of the golf club head having movable weights described below. The disclosed features and aspects of the embodiments can be used alone or in various novel and nonobvious combinations and sub-combinations with one another.

Briefly, and in general terms, the present application describes a golf club head having movable weights for providing enhanced golf club head performance characteristics. According to some embodiments, the golf club includes a body with a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt positioned around a periphery of the golf club head between the sole and the crown. The body also includes an interior cavity and at least two weight ports formed in the body. The golf club head also includes at least one weight that is configured to be retained at least partially within one of the weights ports.

In some embodiments, a golf club head weight port mass is between about 1 gram (g) and about 12 grams (g). In some embodiments, each golf club head weight has a mass between about 1 g and about 100 g. In some embodiments, the golf club has a total weight mass between about 5 g and about 100 g.

In some embodiments, the golf club head has a total weight port mass to body mass ratio between about 0.01 and about 2. In other embodiments, a ratio of the total weight port mass plus the total weight mass to the body mass is between about 0.044 and about 4.6.

In some embodiments, the mass of the golf club head minus the total weight mass is between about 180 g and about 215 g.

In some embodiments, the golf club head has a golf club head origin positioned on the face plate at a geometric center of the face plate. In some embodiments, the golf club head origin has an x-axis tangential to the face plate and generally parallel to the ground when the head is ideally positioned and a y-axis extending generally perpendicular to the x-axis and generally parallel to the ground when the head is ideally positioned.

In some embodiments, the golf club head center of gravity has a head origin y-axis coordinate greater than about 0 mm and less than about 50 mm where the positive y-axis extends from the head origin inwardly toward the cavity. In some embodiments, the golf club head center of gravity has a head origin x-axis coordinate greater than about −5 mm and less than about 8 mm. In some embodiments, the golf club head center of gravity has a head origin z-axis coordinate greater than 0 mm.

In some embodiments, a moment of inertia about the head center of gravity x-axis is between about 70 $kg \cdot mm^2$ and about 400 $kg \cdot mm^2$ and a moment of inertia about a head origin z-axis is between about 200 $kg \cdot mm^2$ and about 600 $kg \cdot mm^2$.

In some embodiments, the weight ports are oriented such that each weight port radial axis and a golf club head impact axis intersect to form a weight port radial axis angle between about 10 degrees and about 80 degrees.

In some embodiments, a golf club head weight port has a volume between about 0.3 cm^3 and about 15 cm^3.

In some embodiments, a ratio of the total weight port volume to the head volume is between about 0.001 and about 0.050.

In some embodiments, the weight mass multiplied by a vectorial separation distance that separates the weight center of gravity if located in the first weight port and the weight center of gravity if located in the second weight port is between about 50 g·mm and about 15,000 g·mm.

In some embodiments, the golf club head moment of inertia about the head center of gravity x-axis divided by the golf club head mass without weights is between about 800 mm^2 and about 4,000 mm^2. In some embodiments, the golf club head moment of inertia about the head center of gravity x-axis multiplied by the weight mass is between about 1.4 $g^2 \cdot mm^2$ and about 40 $g^2 \cdot mm^2$.

In some embodiments, the golf club head moment of inertia about the head center of gravity z-axis divided by the golf club head mass without weights is between about 1,500 mm^2 and about 6,000 mm^2. In some embodiments, the golf club head moment of inertia about the head center of gravity z-axis multiplied by the weight mass is between about 2.5 $g^2 \cdot mm^2$ and about 72 $g^2 \cdot mm^2$.

In some embodiments, a weight positioned on the golf club head has a head origin x-axis coordinate greater than about −40 mm and less than about −20 mm or greater than about 20 mm and less than about 40 mm. In other embodiments, the weight has a head origin x-axis coordinate less than about −40 mm or greater than about 40 mm. In some embodiments, a weight positioned on the golf club head has a head origin y-axis coordinate between about 0 mm and about 130 mm.

In some embodiments, a vectorial distance between a first weight port and a second weight port is between about 5 mm and about 200 mm. In some embodiments, a vectorial distance between the first weight port and the head origin and the second weight port and the head origin is between about 20 mm and about 200 mm.

In some embodiments, the vectorial distance between a first weight and a second weight positioned around the golf club head is between about 5 mm and about 200 mm. The vectorial distance between the first weight center of gravity and the head origin, and the second weight center of gravity and the head origin, is between about 20 mm and about 200 mm in some embodiments.

In some embodiments of a golf club with at least a first weight and a second weight, the first weight has a mass between about 1 gram and about 100 grams and the 10 second weight has a mass between about 1 gram and about 100 grams. The first weight has a head origin x-axis coordinate greater than about 0 mm and less than about 60 mm and the second weight has a head origin x-axis coordinate greater than about −60 mm and less than about 0 mm in some embodiments. In other embodiments, the first and second weights have head origin y-axis coordinates greater than about 0 mm and less than about 130 mm.

In some embodiments, the mass of a maximum weight minus the mass of a minimum weight multiplied by a vectorial distance between the maximum weight center of gravity and the minimum weight center of gravity is between about 950 g·mm and about 14,250 g·mm. In other embodiments, a separation distance between a weight when installed in a first weight port and the weight when installed in a second weight port multiplied by the weight mass is between about 50 g·mm and about 15,000 g·mm

In some embodiments, the golf club head includes a first weight positionable proximate a toe portion of the golf club head, a second weight positionable proximate a heel portion of the golf club head and a third weight positionable proximate a rear portion of the golf club head. A vectorial distance between a center of gravity of the first weight and a center of gravity of the second weight is between about 40 mm and about 100 mm, a vectorial distance between a center of gravity of the first weight and a center of gravity of the third weight, and a center of gravity of the second weight and the center of gravity of the third weight, is between about 30 mm and about 90 mm, a vectorial distance between a center of gravity of the first weight and a golf club head origin on the face plate, and a center of gravity of the second weight and the golf club head origin, is between about 20 mm and about 60 mm and a vectorial distance between a center of gravity of the third weight and a golf club head origin on the face plate is between about 40 mm and about 100 mm in some embodiments.

In some embodiments, the golf club head includes a first weight with a head origin x-axis coordinate greater than about −47 mm and less than about −27 mm and a head origin y-axis coordinate greater than about 10 mm and less than about 30 mm, a second weight with a head origin x-axis coordinate greater than about 22 mm and less than about 44 mm and a head origin y-axis coordinate greater than about 10 mm and less than about 30 mm, and a third weight with a head origin x-axis coordinate greater than about −30 mm and less than about 30 mm and a head origin y-axis coordinate greater than about 63 mm and less than about 83 mm.

In some embodiments, the golf club head has a first weight positionable proximate a front toe portion of the golf club head, a second weight positionable proximate a front heel portion of the golf club head, a third weight positionable proximate a rear toe portion of the golf club head and a fourth weight positionable proximate a rear heel portion of the golf club head. In some embodiments, the vectorial distance between a center of gravity of the first weight and a center of gravity of the second weight is between about 40 mm and about 100 mm, the vectorial distance between a center of gravity of the third weight and a center of gravity of the fourth weight is between about 10 mm and about 80 mm, the vectorial distance between a center of gravity of the first weight and a center of gravity of the third weight, and a center of gravity of the second weight and the center of gravity of the fourth weight, is between about 30 mm and about 90 mm, and the vectorial distance between a center of gravity of the first weight and a center of gravity of the fourth weight, and the vectorial distance between a center of gravity of the second weight and a center of gravity of the third weight is between about 40 mm and about 100 mm is between about 40 mm and about 100 mm. In some embodiments, the vectorial distance between a center of gravity of the first weight and a golf club head origin, and a center of gravity of the second weight and the golf club head origin, is between about 20 mm and about 60 mm. In other embodiments, the vectorial distance between a center of gravity of the third weight and a golf club head origin, and a center of gravity of the fourth weight and the golf club head origin, is between about 40 mm and about 100 mm.

In some embodiments, the golf club head has a first weight with a head origin x-axis coordinate greater than about −47 mm and less than about −27 mm and a head origin y-axis coordinate greater than about 10 mm and less than about 30 mm, a second weight with a head origin x-axis coordinate greater than about 24 mm and less than about 44 mm and a head origin y-axis coordinate greater than about 10 mm and less than about 30 mm, a third weight with a head origin x-axis coordinate greater than about −30 mm and less than about −10 mm and a head origin y-axis coordinate greater than about 63 mm and less than about 83 mm and a fourth weight with a head origin x-axis coordinate greater than about

8 mm and less than about 28 mm and a head origin y-axis coordinate greater than about 63 mm and less than about 83 mm.

In some embodiments, the golf club head can have at least a first movable weight positionable proximate a toe portion of the golf club head, a second movable weight positionable proximate a heel portion of the golf club head, a third movable weight positionable proximate a rear portion of the golf club head and a fourth movable weight positionable proximate the rear portion of the golf club head nearer the heel portion of the golf club head than the third movable weight. The first, second, third and fourth movable weights can be positionable around the skirt portion of the golf club head. The golf club head can include at least first, second, third and fourth weight ports formed in the body. The first movable weight may be configured to be retained at least partially within the first weight port, the second movable weight may be configured to be retained at least partially within the second weight port, the third movable weight may be configured to be retained at least partially within the third weight port and the fourth movable weight may be configured to be retained at least partially within the fourth weight port. A distance between the third and fourth movable weights can be smaller than a distance between the first and second movable weights.

In some embodiments, the golf club head has a weight mass to a sum of the body mass and the weight port mass ratio between about 0.05 and about 1.25.

In some embodiments, the golf club head has a face plate with a height between about 32 mm and about 59 mm, a width between about 86 mm and about 111 mm and an aspect ratio between about 0.35 and about 0.58.

In some embodiments, the golf club head has a face plate with a variable thickness face plate. The variable thickness face plate has a generally circular protrusion extending rearwardly from an interior surface of the face plate into the cavity in some embodiments. The face plate, when viewed in cross section, increases in thickness from an outer portion to an intermediate portion of the interior surface and decreases in thickness from the intermediate portion to an inner portion of the interior surface in some embodiments. In yet other embodiments, the face plate has a maximum thickness greater than about 3 mm and a minimum thickness less than about 3 mm, and a ratio of the minimum thickness to maximum thickness is less than about 0.36.

In some embodiments, the golf club head body has a sole with a thickness less than about 0.9 mm over more than about 50% of a surface area of the sole. In more specific embodiments, the skirt is made at least partially from a titanium alloy. In some embodiments, the sole has a localized zone proximate the face plate that has a thickness between about 1 mm and about 3 mm and extends rearwardly away from the face plate a distance greater than about 5 mm. In some embodiments, the golf club head has a sole areal weight less than about 0.45 g/cm^2 over more than about 50% of the sole surface area.

In still other embodiments, the golf club head body has a crown with a thickness less than about 0.9 mm over more than about 50% of a surface area of the crown. In some embodiments, the golf club head has a crown areal weight less than about 0.45 g/cm^2 over more than about 50% of the crown surface area.

In some embodiments, the golf club head body has a skirt with a thickness less than about 0.9 mm over more than about 50% of a surface area of the crown. In other embodiments, the skirt has a thickness less than about 0.8 mm over more than about 50% of a surface area of the skirt. In some embodiments, the golf club head has a skirt areal weight less than about 0.41 g/cm^2 over more than about 50% of the skirt surface area.

In some embodiments, the volume of the golf club head is between about 110 cm^3 and about 600 cm^3. In yet other embodiments, the loft of the club head is between about 6 degrees and about 30 degrees. In still other embodiments, the golf club head has a mass less than about 222 g. In some embodiments, the golf club head has a lie angle between about 55 degrees and about 65 degrees. In some embodiments, the golf club head has a coefficient of restitution greater than about 0.8.

In some embodiments, the golf club head body is made from a steel alloy, a titanium alloy or a composite material. In other embodiments, the golf club head is made using casting, forging, cold forming or other manufacturing techniques.

The foregoing and additional features and advantages of the disclosed embodiments will become more apparent from the following detailed description, which proceeds with reference to the following drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a perspective view of an embodiment of a kit for adjustably weighting a golf club head in accordance with the invention.

FIG. **2** is a bottom and rear side perspective view of a club head having four weight ports.

FIG. **3** is a side elevational view of the club head of FIG. **2**, depicted from the heel side of the club head.

FIG. **4** is a rear elevational view of the club head of FIG. **2**.

FIG. **5** is a cross sectional view of the club head of FIG. **2**, taken along line **5-5** of FIG. **4**.

FIG. **6** is a plan view of the instruction wheel of the kit of FIG. **1**.

FIG. **7** is a perspective view of the tool of the kit of FIG. **1**, depicting a grip and a tip.

FIG. **8** is a close-up plan view of the tip of the tool of FIG. **7**.

FIG. **9** is a side elevational view of a weight screw of the kit of FIG. **1**.

FIG. **10** is an exploded perspective view of a weight assembly of the kit of FIG. **1**.

FIG. **11** is a top plan view of the weight assembly of FIG. **10**.

FIG. **12** is a cross-sectional view of the weight assembly of FIG. **10**, taken along line **12-12** of FIG. **11**.

FIG. **13** is a bottom and rear perspective view of a golf club head of the present application having three weights and three weight ports.

FIG. **14** is a bottom and rear perspective view of a golf club head of the present application having two weights and two weight ports.

FIG. **15** is a front elevational view of the golf club head of FIG. **2** having four weight ports.

FIG. **16** is a top elevational view of the golf club head of FIG. **15**.

FIG. **17** is a front elevational view of the golf club head of FIG. **15** showing a golf club head origin coordinate system.

FIG. **18** is a cross-sectional view of a golf club head face plate protrusion.

FIG. **19** is a top view of a golf club face plate protrusion.

DETAILED DESCRIPTION

Disclosed below are representative embodiments that are not intended to be limiting in any way. Instead, the present

disclosure is directed toward novel and nonobvious features, aspects and equivalents of the embodiments of the golf club information system described below. The disclosed features and aspects of the embodiments can be used alone or in various novel and nonobvious combinations and sub-combinations with one another.

Now with reference to an illustrative drawing, and particularly FIG. **1**, there is shown a kit **20** having a driving tool, i.e., torque wrench **22**, and a set of weights **24** usable with a golf club head having conforming recesses, including, for example, weight assemblies **30** and weight screws **23**, and an instruction wheel **26**. In one particular embodiment, a golf club head **28** includes four recesses, e.g., weight ports **96**, **98**, **102**, **104**, disposed about the periphery of the club head (FIGS. **2-5**). In the illustrated embodiment of FIGS. **2-5**, four weights **24** are provided; two weight assemblies **30** of about ten grams (g) and two weight screws **32** of about two grams (g). Varying placement of the weights within ports **96**, **98**, **102**, and **104** enables the golfer to vary launch conditions of a golf ball struck by the club head **28**, for optimum distance and accuracy. More specifically, the golfer can adjust the position of the club head's center of gravity (CG), for greater control over the characteristics of launch conditions and, therefore, the trajectory and shot shape of the struck golf ball.

With reference to FIGS. **1-5**, weights **24** are sized to be securely received in any of the four ports **96**, **98**, **102**, **104** of club head **28**, and are secured in place using the torque wrench **22**. The instruction wheel **26** aids the golfer in selecting a proper weight configuration for achieving a desired effect to the trajectory and shape of the golf shot. In some embodiments, the kit **20** provides six different weight configurations for the club head **28**, which provides substantial flexibility in positioning CG of the club head **28**. Generally, the CG of a golf club head is the average location of the weight of the golf club head or the point at which the entire weight of the golf club head may be considered as concentrated so that if supported at this point the head would remain in equilibrium in any position. In the illustrated embodiment of FIGS. **15** and **16**, the CG **169** of club head **28** can be adjustably located in an area adjacent to the sole having a length of about five millimeters measured from front-to-rear and width of about five millimeters measured from toe-to-heel. Each configuration delivers different launch conditions, including ball launch angle, spin-rate and the club head's alignment at impact, as discussed in detail below.

Each of the weight assemblies **30** (FIGS. **10-12**) includes a mass element **34**, a fastener, e.g., screw **36**, and a retaining element **38**. In the exemplary embodiment, the weight assemblies **30** are preassembled; however, component parts can be provided for assembly by the user. For weights having a total mass between about one gram and about two grams, weight screws **32** without a mass element preferably are used (FIG. **9**). Weight screws **32** can be formed of stainless steel, and the head **120** of each weight screw **32** preferably has a diameter sized to conform to the four ports **96**, **98**, **102** and **104** of the club head **28**.

The kit **20** can be provided with a golf club at purchase, or sold separately. For example, a golf club can be sold with the torque wrench **22**, the instruction wheel **26**, and the weights **24** (e.g., two 10-gram weights **30** and two 2-gram weights **32**) preinstalled. Kits **20** having an even greater variety of weights can also be provided with the club, or sold separately. In another embodiment, a kit **20** having eight weight assemblies is contemplated, e.g., a 2-gram weight, four 6-gram weights, two 14-gram weights, and an 18-gram weight. Such a kit **20** may be particularly effective for golfers with a fairly consistent swing, by providing additional precision in weighting the club head **28**. Also, weights in prescribed increments across a broad range can be available. For example, weights **24** in one gram increments ranging from one gram to twenty-five grams can provide very precise weighting, which would be particularly advantageous for advanced and professional golfers. In such embodiments, weight assemblies **30** ranging between five grams and ten grams preferably use a mass element **34** comprising primarily a titanium alloy. Weight assemblies **30**, ranging between ten grams to over twenty-five grams, preferably use a mass element **34** comprising a tungsten-based alloy, or blended tungsten alloys. Other materials, or combinations thereof, can be used to achieve a desired weight mass. However, material selection should consider other requirements such as durability, size restraints, and removability.

Instruction Wheel

With reference now to FIG. **6**, the instruction wheel **26** aids the golfer in selecting a club head weight configuration to achieve a desired effect on the motion path of a golf ball struck by the golf club head **28**. The instruction wheel **26** provides a graphic, in the form of a motion path chart **39** on the face of instruction wheel **26** to aid in this selection. The motion path chart's y-axis corresponds to the height control of the ball's trajectory, generally ranging from low to high. The x-axis of the motion path chart corresponds to the directional control of the ball's shot shape, ranging from left to right. In the exemplary embodiment, the motion path chart **39** identifies six different weight configurations **40**. Each configuration is plotted as a point on the motion path chart **39**. Of course, other embodiments can include a different number of configurations, such as, for kits having a different variety of weights. Also, other approaches for presenting instructions to the golfer can be used, for example, charts, tables, booklets, and so on. The six weight configurations of the exemplary embodiment are listed below in Table 1.

TABLE 1

Config.		Weight Distribution			
No.	Description	Fwd Toe	Rear Toe	Fwd Heel	Rear Heel
1	High	2 g	10 g	2 g	10 g
2	Low	10 g	2 g	10 g	2 g
3	More Left	2 g	2 g	10 g	10 g
4	Left	2 g	10 g	10 g	2 g
5	Right	10 g	2 g	2 g	10 g
6	More Right	10 g	10 g	2 g	2 g

Each weight configuration (i.e., 1 through 6) corresponds to a particular effect on launch conditions and, therefore, a struck golf ball's motion path. In the first configuration, the club head CG is in a center-back location, resulting in a high launch angle and a relatively low spin-rate for optimal distance. In the second configuration, the club head CG is in a center-front location, resulting in a lower launch angle and lower spin-rate for optimal control. In the third configuration, the club head CG is positioned to induce a draw bias. The draw bias is even more pronounced with the fourth configuration. Whereas, in the fifth and sixth configurations, the club head CG is positioned to induce a fade bias, which is more pronounced in the sixth configuration.

In use, the golfer selects, from the various motion path chart descriptions, the desired effect on the ball's motion path. For example, if hitting into high wind, the golfer may choose a golf ball motion path with a low trajectory, (e.g., the second configuration). Or, if the golfer has a tendency to hit the ball to the right of the intended target, the golfer may choose a weight configuration that encourages the ball's shot

shape to the left (e.g., the third and fourth configurations). Once the configuration is selected, the golfer rotates the instruction wheel **26** until the desired configuration number is visible in the center window **42**. The golfer then reads the weight placement for each of the four locations through windows **48**, **50**, **52**, **53**, as shown in the graphical representation **44** of the club head **28**. The motion path description name is also conveniently shown along the outer edge **55** of the instruction wheel **26**. For example, in FIG. **6**, the instruction wheel **26** displays weight positioning for the "high" trajectory motion path configuration, i.e., the first configuration. In this configuration, two 10-gram weights are placed in the rear ports **96**, **98** and two 2-gram weights are placed in the forward ports **102**, **104** (FIG. **2**). If another configuration is selected, the instruction wheel **26** depicts the corresponding weight distribution, as provided in Table 1, above.

Torque Wrench

With reference now to FIGS. **7-8**, the torque wrench **22** includes a grip **54**, a shank **56**, and a torque-limiting mechanism (not shown). The grip **54** and shank **56** generally form a T-shape; however, other configurations of wrenches can be used. The torque-limiting mechanism is disposed between the grip **54** and the shank **56**, in an intermediate region **58**, and is configured to prevent over-tightening of the weights **24** into the ports **96**, **98**, **102**, and **104**. In use, once the torque limit is met, the torque-limiting mechanism of the exemplary embodiment will cause the grip **54** to rotationally disengage from the shank **56**. In this manner, the torque wrench **22** inhibits excessive torque on the weight **24** being tightened. Preferably, the wrench **22** is limited to between about twenty inch-lbs. and forty inch-lbs. of torque. More preferably, the limit is between twenty-seven inch-lbs and thirty-three inch-lbs of torque. In the exemplary embodiment, the wrench **22** is limited to about thirty inch-lbs. of torque. Of course, wrenches having various other types of torque-limiting mechanisms, or even without such mechanisms, can be used. However, if a torque-limiting mechanism is not used, care should be taken not to over-tighten the weights **24**.

The shank **56** terminates in an engagement end, i.e., tip **60**, configured to operatively mate with the weight screws **32** and the weight assembly screws **36** (FIGS. **9-11**). The tip **60** includes a bottom wall **62** and a circumferential side wall **64**. As shown in FIGS. **10** and **11**, the head of each of the weight screws **32** and weight assembly screws **36** define a socket **124** and **66**, respectively, having a complementary shape to mate with the tip **60**. The side wall **64** of the tip **60** defines a plurality of lobes **68** and flutes **70** spaced about the circumference of the tip. The multi-lobular mating of the wrench **22** and the sockets **66** and **124** ensures smooth application of torque and minimizes damage to either device (e.g., stripping of tip **60** or sockets **66**, **124**). The bottom wall **62** of the tip **66** defines an axial recess **72** configured to receive a post **74** disposed in sockets **66** and **124**. The recess **72** is cylindrical and is centered about a longitudinal axis of the shank **56**.

With reference now to FIG. **8**, the lobes **68** and flutes **70** are spaced equidistant about the tip **60**, in an alternating pattern of six lobes and six flutes. Thus, adjacent lobes **68** are spaced about 60 degrees from each other about the circumference of the tip **60**. In the exemplary embodiment, the tip **60** has an outer diameter (d_{lobes}), defined by the crests of the lobes **68**, of about 4.50 mm, and trough diameter (d_{flutes}) defined by the troughs of the flutes **70**, of about 3.30 mm. The axial recess has a diameter (d_{recess}) of about 1.10 mm. Each socket **66**, **124** is formed in an alternating pattern of six lobes **90** that complement the six flutes **70** of the wrench tip **60**.

Weights

Generally, as shown in FIGS. **1** and **9-12**, weights **24**, including weight assemblies **30** and weight screws **32**, are non-destructively movable about or within golf club head **28**. In specific embodiments, the weights **24** can be attached to the club head **28**, removed, and reattached to the club head without degrading or destroying the weights or the golf club head. In other embodiments, the weights **24** are accessible from an exterior of the golf club head **28**.

With reference now to FIG. **9**, each weight screw **32** has a head **120** and a body **122** with a threaded portion **128**. The weight screws **32** are preferably formed of titanium or stainless steel, providing a weight with a low mass that can withstand forces endured upon impacting a golf ball with the club head **28**. In the exemplary embodiment, the weight screw **32** has an overall length (L_o) of about 18.3 mm and a mass of about two grams. In other embodiments, the length and composition of the weight screw **32** can be varied to satisfy particular durability and mass requirements. The weight screw head **120** is sized to enclose one of the corresponding weight ports **96**, **98**, **102**, **104** (FIG. **2**) of the club head **28**, such that the periphery of the weight screw head **120** generally abuts the side wall of the port. This helps prevent debris from entering the corresponding port. Preferably, the weight screw head **120** has a diameter ranging between about 11 mm and about 13 mm, corresponding to weight port diameters of various exemplary embodiments. In this embodiment, the weight screw head **120** has a diameter of about 12.3 mm. The weight screw head **120** defines a socket **124** having a multi-lobular configuration sized to operatively mate with the wrench tip **60**.

The body **122** of the weight screw **32** includes an annular ledge **126** located in an intermediate region thereof. The ledge **126** has a diameter (d_{ledge}) greater than that of the threaded openings **110** defined in the ports **96**, **98**, **102**, **104** of the club head **28** (FIG. **2**), thereby serving as a stop when the weight screw **32** is tightened. In the embodiment, the annular ledge **126** is a distance (L_a) of about 11.5 mm from the weight screw head **120** and has a diameter (d_a) of about 6 mm. The weight screw body **122** further includes a threaded portion **128** located below the annular ledge **126**. In this embodiment, M5×0.6 threads are used. The threaded portion **128** of the weight screw body **122** has a diameter (d_t) of about 5 mm and is configured to mate with the threaded openings **110** defined in the ports **96**, **98**, **102**, **104** of the club head **28**.

With reference now to FIGS. **10-12**, each mass element **34** of the weight assemblies **30** defines a bore **78** sized to freely receive the weight assembly screw **36**. As shown in FIG. **12**, the bore **78** includes a lower non-threaded portion and an upper threaded portion. The lower portion is sufficiently sized to freely receive a weight assembly screw body **80**, while not allowing the weight assembly screw head **82** to pass. The upper portion of the bore **78** is sufficiently sized to allow the weight assembly screw head **82** to rest therein. More particularly, the weight assembly screw head **82** rests upon a shoulder **84** formed in the bore **78** of the mass element **34**. Also, the upper portion of the bore **78** has internal threads **86** for securing the retaining element **38**. In constructing the weight assembly **30**, the weight assembly screw **36** is inserted into the bore **78** of the mass element **34** such that the lower end of the weight assembly screw body **80** extends out the lower portion of the bore **78** and the weight assembly screw head **82** rests within the upper portion of the bore **78**. The retaining element **38** is then threaded into the upper portion of the bore **78**, thereby capturing the weight assembly screw **36** in place. A thread locking compound can be used to secure the retaining element **38** to the mass element **34**.

The retaining element **38** defines an axial opening **88**, exposing the socket **66** of the weight assembly screw head **82** and facilitating engagement of the wrench tip **60** in the socket

66 of the weight assembly screw **36**. As mentioned above, the side wall of the socket **66** defines six lobes **90** that conform to the flutes **70** (FIG. **8**) of the wrench tip **60**. The cylindrical post **74** of the socket **66** is centered about a longitudinal axis of the screw **36**. The post **74** is received in the axial recess **72** (FIG. **8**) of the wrench **22**. The post **74** facilitates proper mating of the wrench **22** and the weight assembly screw **36**, as well as inhibiting use of non-compliant tools, such as Phillips screwdrivers, Allen wrenches, and so on.

Club Head

As illustrated in FIGS. **2-5**, a golf club head **28** of the present application includes a body **92**. The body **92** can include a crown **141**, sole **143**, skirt **145** and face plate **148** defining an interior cavity **150**. The body **92** further includes a heel portion **151**, toe portion **153** and rear portion **155**.

The crown **141** is defined as an upper portion of the golf club head **28** above a peripheral outline of the head including the top of the face plate **148**.

The sole **143** includes a lower portion of the golf club head **28** extending upwards from a lowest point of the club head when the club head is ideally positioned, i.e., at a proper address position. For a typical driver, the sole **143** extends upwards approximately 15 mm above the lowest point when the club head is ideally positioned. For a typical fairway wood, the sole **143** extends upwards approximately 10 mm to about 12 mm above the lowest point when the club head is ideally positioned. A golf club head, such as the club head **28**, can be ideally positioned when angle **163** measured between a plane tangent to an ideal impact location on the face plate and a perfectly vertical plane relative to the ground is approximately equal to the golf club head loft and when the golf club head lie angle is approximately equal to an angle between a longitudinal axis of the hosel or shaft and the ground **161**. The ideal impact location is disposed at the geometric center of the face plate. The sole **143** can also include a localized zone **189** proximate the face plate **148** having a thickness between about 1 mm and about 3 mm, and extending rearwardly away from the face plate a distance greater than about 5 mm.

The skirt **145** is defined as a side portion of the golf club head between the crown and the sole that extends across a periphery of the golf club head, excluding the face plate, from the toe portion **153**, around the rear portion **155**, to the heel portion **151**.

The crown **141**, sole **143** and skirt **145** can be integrally formed using techniques such as molding, cold forming, casting, and/or forging and the face plate **148** can be attached to the crown, sole and skirt by means known in the art. Furthermore, the body **92** can be made from various metals (e.g., titanium alloys, aluminum alloys, steel alloys, magnesium alloys, or combinations thereof), composite material, ceramic material, or combinations thereof.

The face plate **148** is positioned generally at a front portion of the golf club head.

The golf club head of the present application can include one or more weight ports. For example, according to some embodiments, and as shown in FIGS. **2-5**, the golf club head **28** can include the four weight ports **96**, **98**, **102** and **104** formed in the club head. In other embodiments, a golf club head can include less or more than four weight ports. For example, in some embodiments, as shown in FIG. **13**, golf club head **130** can have three weight ports **131**. In still other embodiments, as shown in FIG. **14**, golf club head **136** can have two weight ports **137**.

Weight ports can be generally described as a structure coupled to the golf club head crown, golf club head skirt, golf club head sole or any combination thereof that defines a recess, cavity or hole on, about or within the golf club head. Exemplary of weight ports of the present application, weight ports **96**, **98**, **102**, and **104** of FIGS. **2-5** include a weight cavity **116** and a port bottom **108**. The ports have a weight port radial axis **167** defined as a longitudinal axis passing through a volumetric centroid, i.e., the center of mass or center of gravity, of the weight port. The port bottom **108** defines a threaded opening **110** for attachment of the weights **24**. The threaded opening **110** is configured to receive and secure the threaded body **80** of the weight assembly **30** and threaded body **122** of the weight screw **32**. In this embodiment, the threaded bodies **80** and **122** of the weight assembly **30** and weight screw **32**, respectively, have M5×0.6 threads. The threaded opening **110** may be further defined by a boss **112** extending either inward or outward relative to the weight cavity **116**. Preferably, the boss **112** has a length at least half the length of the body **80** of the screw **36** and, more preferably, the boss has a length 1.5 times a diameter of the body of the screw. As depicted in FIG. **5**, the boss **112** extends outward, relative to the weight cavity **116** and includes internal threads (not shown). Alternatively, the threaded opening **110** may be formed without a boss.

As depicted in FIG. **5**, the weight ports can include fins or ribs **114** having portions disposed about the ports **96**, **98**, **102** and **104**, and portions formed in the body to provide support within the club head and reduce stresses on the golf club head walls during impact with a golf ball.

In the embodiment shown in FIGS. **2-5**, the weights **24** are accessible from the exterior of the club head **28** and securely received into the ports **96**, **98**, **102**, and **104**. The weight assemblies **30** preferably stay in place via a press fit while the weights **32** are generally threadably secured. Weights **24** are configured to withstand forces at impact, while also being easy to remove.

In some embodiments, four or more weights may be provided as desired. Yet in other embodiments, a golf club head can have fewer than four weights. For example, as shown in FIG. **13**, golf club head **130** can have three weights **132** positioned around the golf club head **130** and, as shown in FIG. **14**, golf club head **136** can have two weights **138** positioned around the golf club head **136**. In some embodiments, each weight **132** and weight **138** can be a weight assembly or weight screw, such as the weight assembly **30** or weight screw **32**.

To attach a weight assembly, such as weight assembly **30**, in a port of a golf club head, such as the golf club head **28**, the threaded body **30** of the screw **36** is positioned against the threaded opening **110** of the port. With the tip **60** of the wrench **22** inserted through the aperture **88** of the retaining element **38** and engaged in the socket **66** of the screw **36**, the user rotates the wrench to screw the weight assembly in place. Pressure from the engagement of the screw **36** provides a press fit of the mass element **34** to the port, as sides of the mass element slide tightly against a wall of the weight cavity **116**. The torque limiting mechanism of the wrench prevents overtightening of the weight assembly **30**.

Weight assemblies **30** are also configured for easy removal, if desired. To remove, the user mates the wrench **22** with the weight assembly **30** and unscrews it from a club head. As the user turns the wrench **22**, the head **82** of the screw **36** applies an outward force on the retaining element **38** and thus helps pull out the mass element **34**. Low-friction material can be provided on surfaces of the retaining element **38** and the mass element **34** to facilitate free rotation of the head **82** of the weight assembly screw **36** with respect to the retaining element **38** and the mass element **34**.

Similarly, a weight screw, such as weight screws **32**, can be attached to the body through a port by positioning the threaded portion of weight **32** against the threaded opening **110** of the port. The tip of the wrench can be used to engage the socket of the weight by rotating the wrench to screw the weight in place.

A. Mass Characteristics

A golf club head of the present application has a head mass defined as the combined masses of the body, weight ports and weights. The body mass typically includes the combined masses of the crown, sole, skirt and face plate, or equivalently, the head mass minus the total weight port mass and the total weight mass. The total weight mass is the combined masses of the weight or weights installed on a golf club head. The total weight port mass is the combined masses of the weight ports and any weight port supporting structures, such as fins **114** shown in FIG. **5**.

In several embodiments, one weight port, including any weight port supporting structures, can have a mass between about 1 gram and about 12 grams. A golf club head having two weight ports may have a total weight port mass between about 2 grams and about 24 grams; a golf club head having three weight ports may have a total weight port mass between about 3 grams and about 36 grams; and a golf club head having four weight ports may have a total weight port mass between about 4 grams and about 48 grams.

In several embodiments of the golf club head, the sum of the body mass and the total weight port mass is between about 80 grams and about 222 grams. In more specific embodiments, the sum of the body mass and the total weight port mass is between about 80 grams and about 210 grams. In other embodiments, the sum of the body mass and the total weight port mass is less than about 205 grams or less than about 215 grams.

In some embodiments of the golf club head with two weight ports and two weights, the sum of the body mass and the total weight port mass can be between about 180 grams and about 222 grams. More specifically, in certain embodiments the sum of the body mass and the total weight port mass is between about 180 grams and about 215 grams or between about 198 grams and about 222 grams.

In specific embodiments of the golf club head **28**, **130** with three weight ports **132** and three weights **131** or four weight ports **96**, **98**, **102**, **104** and four weights **24**, the sum of the body mass and the total weight port mass is between about 191 grams and about 211 grams.

Each weight has a weight mass. In several embodiments, each weight mass can be between about 1 gram and about 100 grams. In specific embodiments, a weight mass can be between about 5 grams and about 100 grams or between about 5 grams and about 50 grams. In other specific embodiments, a weight mass can be between about 1 gram and about 3 grams, between about 1 gram and about 18 grams or between about 6 grams and about 18 grams.

In some embodiments, the total weight mass can be between about 5 grams and about 100 grams. In more specific embodiments, the total weight mass can be between about 5 grams and about 100 grams or between about 50 grams and about 100 grams.

B. Volume Characteristics

The golf club head of the present application has a volume equal to the volumetric displacement of the club head body. In other words, for a golf club head with one or more weight ports within the head, it is assumed that the weight ports are either not present or are "covered" by regular, imaginary surfaces, such that the club head volume is not affected by the presence or absence of ports. In several embodiments, a golf club head of the present application can be configured to have a head volume between about 110 cm^3 and about 600 cm^3. In more particular embodiments, the head volume is between about 250 cm^3 and about 500 cm^3. In yet more specific embodiments, the head volume is between about 300 cm^3 and about 500 cm^3, between 300 cm^3 and about 360 cm^3, between about 360 cm^3 and about 420 cm^3 or between about 420 cm^3 and about 500 cm^3.

In embodiments having a specific golf club head weight and weight port configuration, or thin-walled construction as described in more detail below, the golf club can have approximate head volumes as shown in Table 2 below.

TABLE 2

One Weight/Two Weight Ports (cm^3)	Two Weights/Two Weight Ports (cm^3)	Three Weights/Three Weight Ports (cm^3)	Four Weights/Four Weight Ports (cm^3)	Thin Sole Construction (cm^3)	Thin Skirt Construction (cm^3)
180-600 385-600	110-210 180-600 250-600 400-500 440-460 385-600	360-460	360-460	≦500	≧205

The weight port volume is measured as the volume of the cavity formed by the port where the port is "covered" by a regular, imaginary surface as described above with respect to club head volume. According to several embodiments, a golf club head of the present invention has a weight port with a weight port volume between about 0.9 cm^3 and about 15 cm^3.

The total weight port volume is measured as the combined volumes of the weight ports formed in a golf club head. According to some embodiments of a golf club head of the present application, a ratio of the total weight port volume to the head volume is between about 0.001 and about 0.05, between about 0.001 and about 0.007, between about 0.007 and about 0.013, between about 0.013 and about 0.020 or between about 0.020 and about 0.05.

C. Moments of Inertia

Golf club head moments of inertia are typically defined about axes extending through the golf club head CG. As used herein, the golf club head CG location can be provided with reference to its position on a golf club head origin coordinate system.

According to several embodiments, one of which is illustrated in FIGS. **16** and **17**, a golf club head origin **170** is represented on golf club head **28**. The golf club head origin **170** is positioned on the face plate **148** at approximately the

geometric center, i.e., the intersection of the midpoints of a face plate's height and width. For example, as shown in FIG. **17**, the head origin **170** is positioned at the intersection of the midpoints of the face plate height **178** and width **180**.

As shown in FIGS. **16** and **17**, the head origin coordinate system, with head origin **170**, includes an x-axis **172** and a y-axis **174** (extending into the page in FIG. **17**). The origin x-axis **172** extends tangential to the face plate and generally parallel to the ground when the head is ideally positioned with the positive x-axis extending from the origin **170** towards a heel **152** of the golf club head **28** and the negative x-axis extending from the origin to the toe of the golf club head. The origin y-axis **174** extends generally perpendicular to the origin x-axis and parallel to the ground when the head is ideally positioned with the positive y-axis extending from the origin **170** towards the rear portion **155** of the golf club. The head origin can also include an origin z-axis **176** extending perpendicular to the origin x-axis and the origin y-axis and having a positive z-axis that extends from the origin **170** towards the top portion of the golf club head **28** a negative z-axis that extends from the origin towards the bottom portion of the golf club head.

A moment of inertia about a golf club head CG x-axis **201** (see FIGS. **15** and **16**), i.e., an axis extending through the golf club head CG **169** and parallel to the head origin x-axis **172**, is calculated by the following equation

$$I_{CG_x}=\int(y^2+z^2)dm \quad (1)$$

where y is the distance from a golf club head CG xz-plane to an infinitesimal mass dm and z is the distance from a golf club head CG xy-plane to the infinitesimal mass dm. The golf club head CG xz-plane is a plane defined by the golf club head CG x-axis **201** and a golf club head CG z-axis **203** (see FIG. **15**), i.e., an axis extending through the golf club head CG **169** and parallel to the head origin z-axis **176** as shown in FIG. **17**. The CG xy-plane is a plane defined by the CG x-axis **201** and a golf club head CG y-axis (not shown), i.e., an axis extending through the golf club head CG and parallel to the head origin y-axis.

Similarly, a moment of inertia about the golf club head CG z-axis **203** is calculated by the following equation

$$I_{CG_z}=\int(x^2+y^2)dm \quad (2)$$

where x is the distance from a golf club head CG yz-plane to an infinitesimal mass dm and y is the distance from the golf club head CG xz-plane to the infinitesimal mass dm. The golf club head CG yz-plane is a plane defined by the golf club head CG y-axis and the golf club head CG z-axis **203**.

As used herein, the calculated values for the moments of inertia about the golf club head CG x-axis **201** and z-axis **203** are based on a golf club head with a body, at least one weight port coupled to the body and at least one installed weight.

1. Moments of Inertia about CG X-Axis

In several embodiments, the golf club head of the present invention can have a moment of inertia about the golf club head CG x-axis **201** between about 70 kg·mm^2 and about 400 kg·mm^2. More specifically, certain embodiments have a moment of inertia about the head CC x-axis **201** between about 140 kg·mm^2 and about 225 kg·mm^2, between about 225 kg·mm^2 and about 310 kg·mm^2 or between about 310 kg·mm^2 and about 400 kg·mm^2.

In certain embodiments with two weight ports and two weights, the moment of inertia about the head C x-axis **201** is between about 70 kg·mm^2 and about 400 kg·mm^2. In specific embodiments with two weight ports and one weight, the moment of inertia about the head CG x-axis **201** is between about 140 kg·mm^2 and about 400 kg·mm^2. Even more specifically, certain other embodiments have a moment of inertia about the head CG x-axis **201** between about 70 kg·mm^2 and about 140 kg·mm^2, between about 140 kg·mm^2 and about 400 kg·mm^2, between about 220 kg·mm^2 and about 280 kg·mm^2 or between about 220 kg·mm^2 and about 360 kg·mm^2.

In specific embodiments with three weight ports and three weights or four weight ports and four weights, the moment of inertia about the head CC x-axis **201** is between about 180 kg·mm^2 and about 280 kg·mm^2.

In some embodiments of a golf club head of the present application having a thin wall sole or skirt, as described below, a moment of inertia about the golf club head CG x-axis **201** can be greater than about 150 kg·mm^2. More specifically, the moment of inertia about the head CG x-axis **201** can be between about 150 kg·mm^2 and about 180 kg·mm^2, between about 180 kg·mm^2 and about 200 kg·mm^2 or greater than about 200 kg·mm^2.

A golf club head of the present invention can be configured to have a first constraint defined as the moment of inertia about the golf club head CG x-axis **201** divided by the sum of the body mass and the total weight port mass. According to some embodiments, the first constraint is between about 800 mm^2 and about 4,000 mm^2. In specific embodiments, the first constraint is between about 800 mm^2 and about 1,100 mm^2, between about 1,100 mm^2 and about 1,600 mm^2 or between about 1,600 mm^2 and about 4,000 mm^2.

A golf club head of the present application can be configured to have a second constraint defined as the moment of inertia about the golf club head CG x-axis **201** multiplied by the total weight mass. According to some embodiments, the second constraint is between about 1.4 g^2·mm^2 and about 40 g·mm^2. In certain embodiments, the second constraint is between about 1.4 g^2·mm^2 and about 20 g^2·mm^2, between about 2.0 g^2·mm^2 and about 10 g^2·mm^2 or between about 10 g^2·mm^2 and about 40 g^2·mm^2.

2. Moments of Inertia About CG Z-Axis

In several embodiments, the golf club head of the present invention can have a moment of inertia about the golf club head CG z-axis **203** between about 200 kg·mm^2 and about 600 kg·mm^2. More specifically, certain embodiments have a moment of inertia about the head CG z-axis **203** between about 250 kg·mm^2 and about 370 kg·mm^2, between about 370 kg·mm^2 and about 480 kg·mm^2 or between about 480 kg·mm^2 and about 600 kg·mm^2.

In specific embodiments with two weight ports and one weight, the moment of inertia about the head CG z-axis **203** is between about 250 kg·mm^2 and about 600 kg·mm^2.

In specific embodiments with two weight ports and two weights, the moment of inertia about the head CG z-axis **203** is between about 200 kg·mm^2 and about 600 kg·mm^2. Even more specifically, certain embodiments have a moment of inertia about the head CG z-axis **203** between about 200 kg·mm^2 and about 350 kg·mm^2, between about 250 kg·mm^2 and 600 kg·mm^2, between about 360 kg·mm^2 and about 450 kg·mm^2 or between about 360 kg·mm^2 and about 500 kg·mm^2.

In specific embodiments with three weight ports and three weights or four weight ports and four weights, the moment of inertia about the head CG z-axis **203** is between about 300 kg·mm^2 and about 450 kg·mm^2.

In some embodiments with a thin wall sole or skirt, a moment of inertia about a golf club head CG z-axis **203** can be greater than about 250 kg·mm^2. More specifically, the moment of inertia about head CG z-axis **203** can be between about 250 kg·mm^2 and about 300 kg·mm^2, between about 300

kg·mm^2 and about 350 kg·mm^2, between about 350 kg·mm^2 and about 400 kg·mm^2 or greater than about 400 kg·mm^2.

A golf club head can be configured to have a third constraint defined as the moment of inertia about the golf club head CG z-axis **203** divided by the sum of the body mass and the total weight port mass. According to some embodiments, the third constraint is between about 1,500 mm^2 and about 6,000 mm^2. In certain embodiments, the third constraint is between about 1,500 mm^2 and about 2,000 mm^2, between about 2,000 mm^2 and about 3,000 mm^2 or between about 3,000 mm^2 and about 6,000 mm^2.

A golf club head can be configured to have a fourth constraint defined as the moment of inertia about the golf club head CG z-axis **203** multiplied by the total weight mass. According to some embodiments, the fourth constraint is between about 2.5 g^2·mm^2 and about 72 g^2·mm^2. In certain embodiments, the fourth constraint is between about 2.5 g^2·mm^2 and about 3.6 g^2·mm^2, between about 3.6 g^2·mm^2 and about 18 g^2·mm^2 or between about 18 g^2·mm^2 and about 72 g^2·mm^2.

D. Positioning of Weight Ports and Weights

In some embodiments of the present application, the location, position or orientation of features of a golf club head, such as golf club head **28**, can be referenced in relation to fixed reference points, e.g., a golf club head origin, other feature locations or feature angular orientations. The location or position of a weight, such as weight **24**, is typically defined with respect to the location or position of the weight's center of gravity. Similarly, the location or position of a weight port is defined as the location or position of the weight port's volumetric centroid (i.e., the centroid of the cavity formed by a port where the port is "covered" by regular, imaginary surfaces as previously described with respect to club head volume and weight port volume). When a weight or weight port is used as a reference point from which a distance, i.e., a vectorial distance (defined as the length of a straight line extending from a reference or feature point to another reference or feature point) to another weight or weights port is determined, the reference point is typically the center of gravity of the weight or the volumetric centroid of the weight port.

1. Weight Coordinates

The location of a weight on a golf club head can be approximated by its coordinates on the head origin coordinate system as described above in connection with FIGS. **16** and **17**. For example, in some embodiments, weights **24** can have origin x-axis **172** coordinates and origin y-axis **174** coordinates on the coordinate system associated with golf club head origin **170**.

In some embodiments of golf club head **28** having one weight **24**, the weight can have an origin x-axis coordinate between about −60 mm and about 60 mm. In specific embodiments, the weight can have an origin x-axis coordinate between about −20 mm and about 20 mm, between about −40 mm and about 20 mm, between about 20 mm and about 40 mm, between about −60 and about −40 mm, or between about 40 mm and about 60 mm.

In some embodiments, a weight, such as weight **24**, can have a y-axis coordinate greater than about 0 mm. More specifically, in certain embodiments, the weight **24** has a y-axis coordinate between about 0 mm and about 20 mm, between about 20 mm and about 50 mm or greater than about 50 mm.

In some embodiments including a first weight and a second weight, the first weight can have an origin x-axis coordinate between about −60 mm and about 0 mm and the second weight can have an origin x-axis coordinate between about 0 mm and about 60 mm. In certain embodiments, the first weight has an origin x-axis coordinate between about −52 mm and about −12 mm, between about −50 mm and about −10 mm, between about −42 mm and about −22 mm or between about −40 mm and about −20 mm. In certain embodiments, the second weight has an origin x-axis coordinate between about 10 mm and about 50 mm, between about 7 mm and about 42 mm, between about 12 mm and about 32 mm or between about 20 mm and about 40 mm. In some embodiments, the first and second weights can have respective y-axis coordinates between about 0 mm and about 130 mm. In certain embodiments, the first and second weights have respective y-axis coordinates between about 20 mm and about 40 mm, between about 20 mm and about 50 mm, between about 36 mm and about 76 mm or between about 46 mm and about 66 mm.

In certain embodiments of the golf club head **130** having first, second and third weights **131**, the first weight can have an origin x-axis coordinate between about −47 mm and about −27 mm, the second weight can have an origin x-axis coordinate between about 22 mm and about 44 mm and the third weight can have an origin x-axis coordinate between about −30 mm and about 30 mm. In certain embodiments, the first and second weights can each have a y-axis coordinate between about 10 mm and about 30 mm, and the third weight can have a y-axis coordinate between about 63 mm and about 83 mm.

In certain embodiments of the golf club head **28** having first, second, third and fourth weights **24**, the first weight can have an origin x-axis coordinate between about −47 mm and about −27 mm, the second weight can have an origin x-axis coordinate between about 24 mm and about 44 mm, the third weight can have an origin x-axis coordinate between about −30 mm and about −10 mm and the fourth weight can have an origin x-axis coordinate between about 8 mm and about 28 mm. In certain embodiments, the first and second weights can each have a y-axis coordinate between about 10 mm and about 30 mm, and the third and fourth weights can each have a y-axis coordinate between about 63 mm and about 83 mm.

2. Distance from Head Origin to Weights

The location of a weight on a golf club head of the present application can be approximated by its distance away from a fixed point on the golf club head. For example, the positions of the weights **24** about the golf club head **28** can be described according to their distances away from the golf club head origin **170**.

In some embodiments of the golf club head **136** having a first weight **137** or a first weight and a second weight **137**, distances from the head origin **170** to each weight can be between about 20 mm and 200 mm. In certain embodiments, the distances can be between about 20 mm and about 60 mm, between about 60 mm and about 100 mm, between about 100 mm and about 140 mm or between about 140 mm and about 200 mm.

In some embodiments of the golf club head **130** having three weights **131**, including a first weight positioned proximate a toe portion of the golf club head, a second weight positioned proximate a heel portion of the golf club head and a third weight positioned proximate a rear portion of the golf club head, the distances between the head origin and the first and second weights, respectively, can be between about 20 mm and about 60 mm and the distance between the head origin and the third weight can be between about 40 mm and about 100 mm. More specifically, in certain embodiments, the distances between the head origin and the first and second weights, respectively, can be between about 30 mm and about

50 mm and the distance between the head origin and the third weight can be between about 60 mm and about 80 mm.

In some embodiments of the golf club head **28** having four weights **24**, including a first weight positioned proximate a front toe portion of the golf club head, a second weight positioned proximate a front heel portion of the golf club head, a third weight positioned proximate a rear toe portion of the golf club head and a fourth weight positioned proximate a rear heel portion of the golf club head, the distances between the head origin and the first and second weights can be between about 20 mm and about 60 mm and the distances between the head origin and the third and fourth weights can be between about 40 mm and about 100 mm. More specifically, in certain embodiments, the distances between the head origin and the first and second weights can be between about 30 mm and about 50 mm and the distances between the head origin and the third and fourth weights can be between about 60 mm and about 80 mm.

3. Distance from Head Origin to Weight Ports

The location of a weight port on a golf club head can be approximated by its distance away from a fixed point on the golf club head. For example, the positions of one or more weight ports about the golf club head **28** can be described according to their distances away from the golf club head origin **170**.

In some embodiments of the golf club head **136** having first and second weight ports **138**, distances from the head origin **170** to each weight port can be between about 20 mm and 200 mm. In certain embodiments, the distances can be between about 20 mm and about 60 mm, between about 60 mm and about 100 mm, between about 100 mm and about 140 mm or between about 140 mm and about 200 mm.

4. Distance Between Weights and/or Weight Ports

The location of a weight and/or a weight port about a golf club head of the present application can also be defined relative to its approximate distance away from other weights and/or weight ports.

In some embodiments, a golf club head of the present application has only one weight and a first weight port and a second weight port. In such an embodiment, a distance between a first weight position, defined for a weight when installed in a first weight port, and a second weight position, defined for the weight when installed in a second weight port, is called a "separation distance." In some embodiments, the separation distance is between about 5 mm and about 200 mm. In certain embodiments, the separation distance is between about 50 mm and about 100 mm, between about 100 mm and about 150 mm or between about 150 mm and about 200 mm. In some specific embodiments, the first weight port is positioned proximate a toe portion of the golf club head and the second weight port is positioned proximate a heel portion of the golf club head.

In some embodiments of the golf club head **136** with two weights **137** and first and second weight ports **138**, the two weights include a first weight and a second weight. In some embodiments, the distance between the first and second weights **137** is between about 5 mm and about 200 mm. In certain embodiments, the distance between the first and second weights **137** is between about 5 mm and about 50 mm, between about 50 mm and about 100 mm, between about 100 mm and about 150 mm or between about 150 mm and about 200 mm. In some specific embodiments, the first weight is positioned proximate a toe portion of the golf club head and the second weight is positioned proximate a heel portion of the golf club head.

In some embodiments of a golf club head having at least two weight ports, a distance between the first and second weight ports is between about 5 mm and about 200 mm. In more specific embodiments, the distance between the first and second weight ports is between about 5 mm and about 50 mm, between about 50 mm and about 100 mm, between about 100 mm and about 150 mm or between about 150 mm and about 200 mm. In some specific embodiments, the first weight port is positioned proximate a toe portion of the golf club head and the second weight port is positioned proximate a heel portion of the golf club head.

In some embodiments of the golf club head **130** having first, second and third weights **131**, a distance between the first and second weights is between about 40 mm and about 100 mm, and a distance between the first and third weights, and the second and third weights, is between about 30 mm and about 90 mm. In certain embodiments, the distance between the first and second weights is between about 60 mm and about 80 mm, and the distance between the first and third weights, and the second and third weights, is between about 50 mm and about 70 mm. In some embodiments, the first weight is positioned proximate a toe portion of the golf club head, the second weight is positioned proximate a heel portion of the golf club head and the third weight is positioned proximate a rear portion of the golf club head.

In some embodiments of the golf club head **28** having first, second, third and fourth weights **24**, a distance between the first and second weights, the first and fourth weights, and the second and third weights is between about 40 mm and about 100 mm; a distance between the third and fourth weights is between about 10 mm and about 80 mm; and a distance between the first and third weights and the second and fourth weights is about 30 mm to about 90 mm. In more specific embodiments, a distance between the first and second weights, the first and fourth weights, and the second and third weights is between about 60 mm and about 80 mm; a distance between the first and third weights and the second and fourth weights is between about 50 mm and about 70 mm; and a distance between the third and fourth weights is between about 30 mm and about 50 mm. In some specific embodiments, the first weight is positioned proximate a front toe portion of the golf club head, the second weight is positioned proximate a front heel portion of the golf club head, the third weight is positioned proximate a rear toe portion of the golf club head and the fourth weight is positioned proximate a rear heel portion of the golf club head.

5. Weight Port Axis Angular Orientations

In some embodiments of a golf club head of the present application, an angle formed between the weight port radial axis and a golf club head impact axis is between about 10 degrees and about 80 degrees. The golf club head impact axis can be defined as the origin y-axis **174** in the negative direction. In some specific embodiments, the angle is between about 25 degrees and about 65 degrees. The angled orientation of the weight port radial axis with respect to the golf club head impact axis is desirable to reduce the axial load on the weights and their associated retaining mechanism when the club head impacts a ball.

E. Distance from Head Origin to Head Center of Gravity

The location of the CG of a club head can be defined by its spatial relationship to a fixed point on the golf club head. For example, as discussed above, the location of the golf club head CG can be described according to the spatial relationship between the CG and the golf club head origin.

In some embodiments of a golf club head of having one weight, the golf club head has a CG with a head origin x-axis coordinate between about −10 mm and about 10 mm and a head origin y-axis coordinate greater than about 15 mm or less than about 50 mm. In some embodiments of a golf club

head having two weights, the golf club head has a CG with an origin x-axis coordinate between about −10 mm and about 10 mm or between about −4 mm and about 8 mm, and an origin y-axis coordinate greater than about 15 mm or between about 15 mm and about 50 mm. In some embodiments of a golf club head having three or four weights, the golf club head has a CG with an origin x-axis coordinate between about −3 mm and about 6 mm and an origin y-axis coordinate between about 20 mm and about 40 mm. In some embodiments of a golf club head having a thin sole or thin skirt construction, the golf club head has a CG with an origin x-axis coordinate between about −5 mm and about 5 mm, an origin y-axis coordinate greater than about 0 mm and an origin z-axis coordinate less than about 0 mm.

More particularly, in specific embodiments of a golf club head having specific configurations, the golf club head has a CG with coordinates approximated in Table 3 below.

TABLE 3

CG Coordinates	Two Weights	Three Weights	Four Weights	Thin Sole/Skirt Construction
origin x-axis coordinate (mm)	−3 to 8 −3 to 2 2 to 6 −2 to 1 2 to 5 −4 to 6 −4 to 4 −2 to 6	−3 to 6 −1 to 4 −3 to 3 0 to 6	−3 to 6 −1 to 4 −3 to 3	−2 to 2 −1 to 1
origin y-axis coordinate (mm)	15 to 25 25 to 35 35 to 50 30 to 40 31 to 37 20 to 30	20 to 40 23 to 40 20 to 37 20 to 38 22 to 38	20 to 40 23 to 40 20 to 37 22 to 38	12 to 15 15 to 18 >18
origin z-axis coordinate (mm)				−1 to 0 −2 to −1 <−2

F. Head Geometry and Weight Characteristics

1. Loft and Lie

According to some embodiments of the present application, a golf club head has a loft angle between about 6 degrees and about 16 degrees or between about 13 degrees and about 30 degrees. In yet other embodiments, the golf club has a lie angle between about 55 degrees and about 65 degrees.

2. Coefficient of Restitution

Generally, a coefficient of restitution (COR) of a golf club head is the measurement of the amount of energy transferred between a golf club face plate and a ball at impact. In a simplified form, the COR may be expressed as a percentage of the speed of a golf ball immediately after being struck by the club head divided by the speed of the club head upon impact with the golf ball, with the measurement of the golf ball speed and club head speed governed by United States Golf Association guidelines. In some embodiments of the present application, the golf club head has a COR greater than about 0.8.

3. Thin Wall Construction

According to some embodiments of a golf club head of the present application, the golf club head has a thin wall construction. Among other advantages, thin wall construction facilitates the redistribution of material from one part of a club head to another part of the club head. Because the redistributed material has a certain mass, the material may be redistributed to locations in the golf club head to enhance performance parameters related to mass distribution, such as CG location and moment of inertia magnitude. Club head material that is capable of being redistributed without affecting the structural integrity of the club head is commonly called discretionary weight. In some embodiments of the present invention, thin wall construction enables discretionary weight to be removed from one or a combination of the striking plate, crown, skirt, or sole and redistributed in the form of weight ports and corresponding weights.

Thin wall construction can include a thin sole construction, i.e., a sole with a thickness less than about 0.9 mm but greater than about 0.4 mm over at least about 50% of the sole surface area; and/or a thin skirt construction, i.e., a skirt with a thickness less than about 0.8 mm but greater than about 0.4 mm over at least about 50% of the skirt surface area; and/or a thin crown construction, i.e., a crown with a thickness less than about 0.8 mm but greater than about 0.4 mm over at least about 50% of the crown surface area. More specifically, in certain embodiments of a golf club having a thin sole construction and at least one weight and two weight ports, the sole, crown and skirt can have respective thicknesses over at least about 50% of their respective surfaces between about 0.4 mm and about 0.9 mm, between about 0.8 mm and about 0.9 mm, between about 0.7 mm and about 0.8 mm, between about 0.6 mm and about 0.7 mm, or less than about 0.6 mm. According to a specific embodiment of a golf club having a thin skirt construction, the thickness of the skirt over at least about 50% of the skirt surface area can be between about 0.4 mm and about 0.8 mm, between about 0.6 mm and about 0.7 mm or less than about 0.6 mm.

4. Face Plate Geometries

A height and a width can be defined for the face plate of the golf club head. According to some embodiments and as shown in FIG. **17**, a face plate **148** has a height **178** measured from a lowermost point of the face plate to an uppermost point of the face plate, and a width **180** measured from a point on the face plate proximate the heel portion **152** to a point on the face plate proximate a toe portion **154**, when the golf club is ideally positioned at address.

For example, in some embodiments of a fairway wood-type golf club head of the present application, the golf club head face plate has a height between about 32 mm and about 38 mm and a width between about 86 mm and about 92 mm. More specifically, a particular embodiment of a fairway wood-type golf club head has a face plate height between about 34 mm and about 36 mm and a width between about 88 mm and about 90 mm. In yet a more specific embodiment of a fairway wood-type golf club head, the face plate height is about 35 mm and the width is about 89 mm.

In some embodiments of a driver type golf club head of the present application, the golf club head face plate has a height between about 53 mm and about 59 mm and a width between about 105 mm and about 111 mm. More specifically, a particular embodiment of a driver type golf club head has a face plate height between about 55 mm and about 57 mm and a width between about 107 mm and about 109 mm. In yet a more specific embodiment of a driver type golf club head, the face plate height is about 56 mm and the width is about 108 mm.

According to some embodiments, a golf club head face plate can include a variable thickness faceplate. Varying the thickness of a faceplate may increase the size of a club head COR zone, commonly called the sweet spot of the golf club head, which, when striking a golf ball with the golf club head, allows a larger area of the face plate to deliver consistently high golf ball velocity and shot forgiveness. A variable thickness face plate **182**, according to one embodiment of a golf club head illustrated in FIGS. **18** and **19**, includes a generally circular protrusion **184** extending into the interior cavity

towards the rear portion of the golf club head. When viewed in cross-section, as illustrated in FIG. **18**, protrusion **184** includes a portion with increasing thickness from an outer portion **186** of the face plate **182** to an intermediate portion **187**. The protrusion **184** further includes a portion with decreasing thickness from the intermediate portion **187** to an inner portion **188** positioned approximately at a center of the protrusion preferably proximate the golf club head origin.

In some embodiments of a golf club head having a face plate with a protrusion, the maximum face plate thickness is greater than about 4.8 mm, and the minimum face plate thickness is less than about 2.3 mm. In certain embodiments, the maximum face plate thickness is between about 5 mm and about 5.4 mm and the minimum face plate thickness is between about 1.8 mm and about 2.2 mm. In yet more particular embodiments, the maximum face plate thickness is about 5.2 mm and the minimum face plate thickness is about 2 mm.

In some embodiments of a golf club head having a face plate with a protrusion and a thin sole construction or a thin skirt construction, the maximum face plate thickness is greater than about 3.0 mm and the minimum face plate thickness is less than about 3.0 mm. In certain embodiments, the maximum face plate thickness is between about 3.0 mm and about 4.0 mm, between about 4.0 mm and about 5.0 mm, between about 5.0 mm and about 6.0 mm or greater than about 6.0 mm, and the minimum face plate thickness is between about 2.5 mm and about 3.0 mm, between about 2.0 mm and about 2.5 mm, between about 1.5 mm and about 2.0 mm or less than about 1.5 mm.

For some embodiments of a golf club head of the present application, a ratio of the minimum face plate thickness to the maximum face plate thickness is less than about 0.4. In more specific embodiments, the ratio is between about 0.36 and about 0.39. In yet more certain embodiments, the ratio is about 0.38.

For some embodiments of a fairway wood-type golf club head of the present application, an aspect ratio, i.e., the ratio of the face plate height to the face plate width, is between about 0.35 and about 0.45. In more specific embodiments, the aspect ratio is between about 0.38 and about 0.42, or about 0.4. For some embodiments of a driver type golf club head of the present application, the aspect ratio is between about 0.45 and about 0.58. In more specific embodiments, the aspect ratio is between about 0.49 and about 0.54, or about 0.52.

G. Mass Ratios/Constraints

1. Ratio of Total Weight Port Mass to Body Mass

According to some embodiments of the golf club head **136** having two weight ports **138** and either one weight **137** or two weights **137**, a ratio of the total weight port mass to the body mass is between about 0.08 and about 2.0. According to some specific embodiments, the ratio can be between about 0.08 and about 0.1, between about 0.1 and about 0.17, between about 0.17 and about 0.24, between about 0.24 and about 0.3 or between about 0.3 and about 2.0.

In some embodiments of the golf club head **130** having three weight ports **132** and three weights **131**, the ratio of the total weight port mass to the body mass is between about 0.015 and about 0.82. In specific embodiments, the ratio is between about 0.015 and about 0.22, between about 0.22 and about 0.42, between about 0.42 and about 0.62 or between about 0.62 and about 0.82.

In some embodiments of the golf club head **28** having four weight ports **96**, **98**, **102**, **104** and four weights **24**, the ratio of the total weight port mass to the body mass is between about 0.019 and about 0.3. In specific embodiments, the ratio is between about 0.019 and about 0.09, between about 0.09 and about 0.16, between about 0.16 and about 0.23 or between about 0.23 and about 0.3.

2. Ratio of Total Weight Port Mass Plus Total Weight Mass to Body Mass

According to some embodiments of the golf club head **136** having two weight ports **138** and one weight **137** or two weights **137**, a ratio of the total weight port mass plus the total weight mass to the body mass is between about 0.06 and about 3.0. More specifically, according to certain embodiments, the ratio can be between about 0.06 and about 0.3, between about 0.3 and about 0.6, between about 0.6 and about 0.9, between about 0.9 and about 1.2 or between about 1.2 and about 3.0.

In some embodiments of the golf club head **130** having three weight ports **132** and three weights **131**, the ratio of the total weight port mass plus the total weight mass to the body mass is between about 0.044 and about 3.1. In specific embodiments, the ratio is between about 0.044 and about 0.8, between about 0.8 and about 1.6, between about 1.6 and about 2.3 or between about 2.3 and about 3.1.

In some embodiments of the golf club head **28** having four weight ports **96**, **98**, **102**, **104** and four weights **24**, the ratio of the total weight port mass plus the total weight mass to the body mass is between about 0.049 and about 4.6. In specific embodiments, the ratio is between about 0.049 and about 1.2, between about 1.2 and about 2.3, between about 2.3 and about 3.5 or between about 3.5 and about 4.6.

3. Product of Total Weight Mass and Separation Distance

In some embodiments of the golf club head **136** having two weight ports **138** and one weight **137**, the weight mass multiplied by the separation distance of the weight is between about 50 g·mm and about 15,000 g·mm. More specifically, in certain embodiments, the weight mass multiplied by the weight separation distance is between about 50 g·mm and about 500 g·mm, between about 500 g·mm and about 2,000 g·mm, between about 2,000 g·mm and about 5,000 g·mm or between about 5,000 g·mm and about 15,000 g·mm.

4. Product of Maximum Weight Mass Minus Minimum Weight Mass and Distance between Maximum and Minimum Weights

In some embodiments of a golf club head of the present application having two, three or four weights, a maximum weight mass minus a minimum weight mass multiplied by the distance between the maximum weight and the minimum weight is between about 950 g·mm and about 14,250 g·mm. More specifically, in certain embodiments, the weight mass multiplied by the weight separation distance is between about 950 g·mm and about 4,235 g·mm, between about 4,235 g·mm and about 7,600 g·mm, between about 7,600 g·mm and about 10,925 g·mm or between about 10,925 g·mm and about 14,250 g·mm.

5. Ratio of Total Weight Mass to Sum of Body Mass and Total Weight Port Mass

According to some embodiments of a golf club head having at least one weight and at least two weight ports, a ratio of the total weight mass to the sum of the body mass plus the total weight port mass is between about 0.05 and about 1.25. In specific embodiments, the ratio is between about 0.05 and about 0.35, between about 0.35 and about 0.65, between about 0.65 and about 0.95 or between about 0.95 and about 1.25.

H. Sole, Crown and Skirt Areal Weights

According to some embodiments of a golf club head of the present application, an areal weight, i.e., material density multiplied by the material thickness, of the golf club head sole, crown and skirt, respectively, is less than about 0.45

g/cm^2 over at least about 50% of the surface area of the respective sole, crown and skirt. In some specific embodiments, the areal weight is between about 0.15 g/cm^2 and about 0.25 g/cm^2, between about 0.25 g/cm^2 and about 0.35 g/cm^2 or between about 0.35 g/cm^2 and about 0.45 g/cm^2.

According to some embodiments of a golf club having a skirt thickness less than about 0.8 mm, the head skirt areal weight is less than about 0.41 g/cm^2 over at least about 50% of the surface area of the skirt. In specific embodiments, the skirt areal weight is between about 0.15 g/cm^2 and about 0.24 g/cm^2, between about 0.24 g/cm^2 and about 0.33 g/cm^2 or between about 0.33 g/cm^2 and about 0.41 g/cm^2.

I. EXAMPLES

1. Example A

According to one embodiment, a golf club head has two ports and at least one weight. The weight has a head origin x-axis coordinate between about −20 mm and about 20 mm and a mass between about 5 grams and about 50 grams. The golf club head has a volume between about 180 cm^3 and about 600 cm^3, and a CG with a head origin y-axis coordinate greater than or equal to about 15 mm. In a specific embodiment, the weight has a head origin y-axis coordinate between about 0 mm and about 20 mm, between about 20 mm and about 50 mm, or greater than 50 mm. In a specific embodiment, the golf club head has a CG with a head origin x-axis coordinate between about −10 mm and about 10 mm and a y-axis coordinate less than or equal to about 50 mm. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 140 kg·mm^2 and about 400 kg·mm^2, and a moment of inertia about the head CG z-axis between about 250 kg·mm^2 and about 600 kg·mm^2.

2. Example B

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −60 mm and about 0 mm and a mass between about 1 gram and about 100 grams. The second weight has a head origin x-axis coordinate between about 0 mm and about 60 mm and a mass between about 1 gram and about 100 grams. The golf club head has a volume between about 180 cm^3 and about 600 cm^3, and a CG with a head origin y-axis coordinate greater than or equal to about 15 mm. In a specific embodiment, the first and second weights each have a head origin y-axis coordinate between about 0 mm and about 130 mm. In a specific embodiment, the golf club head has a CG with a head origin x-axis coordinate between about −10 mm and about 10 mm and a y-axis coordinate between about 15 mm to about 25 mm, or between about 25 mm to about 35 mm, or between about 35 mm to about 50 mm. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 140 kg·mm^2 and about 400 kg·mm^2, a moment of inertia about the head CG z-axis between about 250 kg·mm^2 and about 600 kg·mm^2, and a head volume greater than or equal to 250 cm^3.

3. Example C

According to another embodiment, a golf club head has two ports and at least one weight. The weight has a head origin x-axis coordinate between about −40 mm and about −20 mm or between about 20 mm and about 40 mm, and a mass between about 5 grams and about 50 grams. The golf club head has a volume between about 180 cm^3 and about 600 cm^3, and a CG with a head origin y-axis coordinate greater than or equal to about 15 mm. In a specific embodiment, the weight has a head origin y-axis coordinate between about 0 mm and about 20 mm, between about 20 mm and about 50 mm, or greater than 50 mm. In a specific embodiment, the golf club head has a CG with a head origin x-axis coordinate between about −10 mm and about 10 mm and a y-axis coordinate less than or equal to about 50 mm. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 140 kg·mm^2 and about 400 kg·mm^2, and a moment of inertia about the head CG z-axis between about 250 kg·mm^2 and about 600 kg·mm^2.

4. Example D

According to another embodiment, a golf club head has two ports and at least one weight, The weight has a head origin x-axis coordinate between about −60 mm and about −40 mm or between about 40 mm and about 60 mm, and a mass between about 5 grams and about 50 grams. The golf club head has a volume between about 180 cm^3 and about 600 cm^3, and a CG with a head origin y-axis coordinate greater than or equal to about 15 mm. In a specific embodiment, the weight has a y-axis coordinate between about 0 mm and about 20 mm, between about 20 mm and about 50 mm, or greater than 50 mm. In a specific embodiment, the golf club head has a CG with a head origin x-axis coordinate between about −10 mm and about 10 mm and a y-axis coordinate less than or equal to about 50 mm. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 140 kg·mm^2 and about 400 kg·mm^2, and a moment of inertia about the head CG z-axis between about 250 kg·mm^2 and about 600 kg·mm^2.

5. Example E

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −52 mm and about −12 mm, a head origin y-axis coordinate between about 36 mm and about 76 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about 10 mm and about 50 mm, a head origin y-axis coordinate between about 36 mm and about 76 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −3 mm and about 2 mm and a head origin y-axis coordinate between about 30 mm and about 40 mm. In a specific embodiment, the golf club head has a volume between about 400 cm^3 and about 500 cm^3, and the sum of the body mass and the total port mass is between about 180 grams and about 215 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 220 kg·mm^2 and about 360 kg·mm^2 and a moment of inertia about the head CG z-axis between about 360 kg·mm^2 and about 500 kg·mm^2.

6. Example F

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −52 mm and about

−12 mm, a head origin y-axis coordinate between about 36 mm and about 76 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about 10 mm and about 50 mm, a head origin y-axis coordinate between about 36 mm and about 76 mm, and a mass between about 6 gram and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about 2 mm and about 6 mm and a head origin y-axis coordinate between about 30 mm and about 40 mm. In a specific embodiment, the golf club head has a volume between about 400 cm^3 and about 500 cm^3, and the sum of the body mass and the total port mass is between about 180 grams and about 215 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 220 $kg \cdot mm^2$ and about 360 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 360 $kg \cdot mm^2$ and about 500 $kg \cdot mm^2$.

7. Example G

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −42 mm and about −22 mm, a head origin y-axis coordinate between about 46 mm and about 66 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about 20 mm and about 40 mm, a head origin y-axis coordinate between about 46 mm and about 66 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −2 mm and about 1 mm and a head origin y-axis coordinate between about 31 mm and about 37 mm. In a specific embodiment, the golf club head has a volume between about 440 cm^3 and about 460 cm^3, and the sum of the body mass and the total port mass is between about 180 grams and about 215 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 220 $kg \cdot mm^2$ and about 280 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 360 $kg \cdot mm^2$ and about 450 $kg \cdot mm^2$.

8. Example H

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −42 mm and about −22 mm, a head origin y-axis coordinate between about 46 mm and about 66 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about 20 mm and about 40 mm, a head origin y-axis coordinate between about 46 mm and about 66 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about 2 mm and about 5 mm and a head origin y-axis coordinate between about 31 mm and about 37 mm. In a specific embodiment, the golf club head has a volume between about 440 cm^3 and about 460 cm^3, and the sum of the body mass and the total port mass is between about 180 grams and about 215 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 220 $kg \cdot mm^2$ and about 280 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 360 $kg \cdot mm^2$ and about 450 $kg \cdot mm^2$.

9. Example I

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −50 mm and about −10 mm, a head origin y-axis coordinate between about 20 mm and about 50 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about 7 mm and about 42 mm, a head origin y-axis coordinate between about 20 mm and about 50 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −4 mm and about 4 mm and a head origin y-axis coordinate between about 20 mm and about 30 mm, In a specific embodiment, the golf club head has a volume between about 110 cm^3 and about 210 cm^3, a loft between about 13 degrees and about 30 degrees, and the sum of the body mass and the total port mass is between about 198 grams and about 222 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 70 $kg \cdot mm^2$ and about 140 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 200 $kg \cdot mm^2$ and about 350 $kg \cdot mm^2$.

10. Example J

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −50 mm and about −10 mm, a head origin y-axis coordinate between about 20 mm and about 50 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about 7 mm and about 42 mm, a head origin y-axis coordinate between about 20 mm and about 50 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about −2 mm and about 6 mm and a head origin y-axis coordinate between about 20 mm and about 30 mm. In a specific embodiment, the golf club head has a volume between about 111 cm^3 and about 210 cm^3, a loft between about 13 degrees and about 30 degrees, and the sum of the body mass and the total port mass is between about 198 grams and about 222 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 70 $kg \cdot mm^2$ and about 140 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 200 $kg \cdot mm^2$ and about 350 $kg \cdot mm^2$.

11. Example K

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −40 mm and about −20 mm, a head origin y-axis coordinate between about 20 mm and about 40 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about 12 mm and about 32 mm, a head origin y-axis coordinate between about 20 mm and about 40 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −4 mm and about 4 mm and a head origin y-axis coordinate between about 20 mm and about 30 mm. In a specific embodiment, the golf club head has a volume between about 110 cm^3 and about 210 cm^3, a loft between about 13 degrees and about 30 degrees, and the sum of the body mass and the total port mass is between about 198 grams and about 222 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 70 $kg \cdot mm^2$ and about 140 $kg \cdot mm^2$ and a

moment of inertia about the head CG z-axis between about 200 kg·mm^2 and about 350 kg·mm^2.

12 Example L

According to another embodiment, a golf club head has first and second ports and corresponding first and second weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −40 mm and about −20 mm, a head origin y-axis coordinate between about 20 mm and about 40 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about 12 mm and about 32 mm, a head origin y-axis coordinate between about 20 mm and about 40 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about −2 mm and about 6 mm and a head origin y-axis coordinate between about 20 mm and about 30 mm. In a specific embodiment, the golf club head has a volume between about 110 cm^3 and about 210 cm^3, a loft between about 13 degrees and about 30 degrees, and the sum of the body mass and the total port mass is between about 198 grams and about 222 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 70 kg·mm^2 and about 140 kg·mm^2 and a moment of inertia about the head CG z-axis between about 200 kg·mm^2 and about 350 kg·mm^2.

13. Example M

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −1 mm and about 4 mm and a head origin y-axis coordinate between about 23 mm and about 40 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

14. Example N

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −1 mm and about 4 mm and a head origin y-axis coordinate between about 20 mm and about 37 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

15. Example O

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −3 mm and about 3 mm and a head origin y-axis coordinate between about 20 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

16. Example P

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about 0 mm and about 6 mm and a head origin y-axis coordinate between about 22 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams

and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

17. Example Q

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about 0 mm and about 6 mm and a head origin y-axis coordinate between about 20 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

18. Example R

According to another embodiment, a golf club head has first, second, and third ports and corresponding first, second, and third weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The third weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −3 mm and about 3 mm and a head origin y-axis coordinate between about 22 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

19. Example S

According to another embodiment, a golf club head has first, second, third, and fourth ports and corresponding first, second, third, and fourth weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 8 mm and about 28 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The fourth weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CC with a head origin x-axis coordinate between about −1 mm and about 4 mm and a head origin y-axis coordinate between about 23 mm and about 40 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

20. Example T

According to another embodiment, a golf club head has first, second, third, and fourth ports and corresponding first, second, third, and fourth weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 8 mm and about 28 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The fourth weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about −1 mm and about 4 mm and a head origin y-axis coordinate between about 20 mm and about 37 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CC x-axis between about 180 kg·mm^2 and about 280 kg·mm^2 and a moment of inertia about the head CG z-axis between about 300 kg·mm^2 and about 450 kg·mm^2.

21. Example U

According to another embodiment, a golf club head has first, second, third, and fourth ports and corresponding first, second, third, and fourth weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between

about 6 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The third weight has a head origin x-axis coordinate between about 8 mm and about 28 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The fourth weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The golf club head has a CG with a head origin x-axis coordinate between about −3 mm and about 3 mm and a head origin y-axis coordinate between about 22 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CG x-axis between about 180 $kg \cdot mm^2$ and about 280 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 300 $kg \cdot mm^2$ and about 450 $kg \cdot mm^2$.

22. Example V

According to another embodiment, a golf club head has first, second, third, and fourth ports and corresponding first, second, third, and fourth weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 3 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 gram and about 3 grams. The third weight has a head origin x-axis coordinate between about 8 mm and about 28 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 6 grams and about 18 grams. The fourth weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 6 grams and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about 0 mm and about 6 mm and a head origin y-axis coordinate between about 22 mm and about 38 mm. In a specific embodiment, the golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. In a more specific embodiment, the golf club head has a moment of inertia about the head CC x-axis between about 180 $kg \cdot mm^2$ and about 280 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 300 $kg \cdot mm^2$ and about 450 $kg \cdot mm^2$.

23. Preferred Embodiment

According to a preferred embodiment, the sole, skirt, crown, and faceplate of a golf club head are each formed from a titanium alloy. The sole has a thickness less than about 0.9 mm but greater than about 0.4 mm over at least 50% of the sole surface area; the skirt has a thickness less than about 0.8 mm but greater than 0.4 mm over at least 50% of the skirt surface area; and the crown has a thickness less than about 0.8 mm but greater than about 0.4 mm over at least 50% of the crown surface area. The areal weight of the sole, crown, and skirt, respectively, is less than about 0.45 g/cm^2 over at least 50% of the surface area of the respective sole, crown and skirt. The golf club head has first, second, third, and fourth ports and corresponding first, second, third, and fourth weights disposed in the ports. The first weight has a head origin x-axis coordinate between about −47 mm and about −27 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 grams and about 18 grams. The second weight has a head origin x-axis coordinate between about −30 mm and about −10 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 grams and about 18 grams. The third weight has a head origin x-axis coordinate between about 8 mm and about 28 mm, a head origin y-axis coordinate between about 63 mm and about 83 mm, and a mass between about 1 grams and about 18 grams. The fourth weight has a head origin x-axis coordinate between about 24 mm and about 44 mm, a head origin y-axis coordinate between about 10 mm and about 30 mm, and a mass between about 1 gram and about 18 grams. The golf club head has a CG with a head origin x-axis coordinate between about −3 mm and about 6 mm and a head origin y-axis coordinate between about 20 mm and about 40 mm. The golf club head has a volume between about 360 cm^3 and about 460 cm^3 and the sum of the body mass and the total port mass is between about 191 grams and about 211 grams. The golf club head has a moment of inertia about the head CC x-axis between about 180 $kg \cdot mm^2$ and about 280 $kg \cdot mm^2$ and a moment of inertia about the head CG z-axis between about 300 $kg \cdot mm^2$ and about 450 $kg \cdot mm^2$. The ratio of the golf club head's total weight port volume to the head volume is between about 0.001 and about 0.05, and the angle formed between the weight ports' radial axes and a golf club head impact axis is between about 10 degrees and about 80 degrees. The golf club head has a loft angle between about 6 degrees and about 16 degrees, a lie angle between about 55 degrees and about 65 degrees, and a coefficient of restitution greater than 0.8. The ratio of the golf club head's total weight port mass to the body mass is between about 0.019 and about 0.3, and a maximum weight mass minus a minimum weight mass multiplied by the distance between the maximum weight and the minimum weight is between about 950 g·mm and about 14,250 g·mm. Additionally, a ratio of the golf club head's total weight mass to the sum of the body mass plus the total weight port mass is between about 0.05 and about 1.25.

Various other designs of club heads and weights may be used, such as those disclosed in Applicant's U.S. Pat. No. 6,773,360, which is herein incorporated by reference. Furthermore, other club head designs known in the art can be adapted to take advantage of features of the present invention.

Having illustrated and described the principles of the disclosed embodiments, it will be apparent to those skilled in the art that the embodiments can be modified in arrangement and detail without departing from such principles. In view of the many possible embodiments, it will be recognized that the described embodiments include only examples and should not be taken as a limitation on the scope of the invention. Rather, the invention is defined by the following claims. We therefore claim as the invention all possible embodiments and their equivalents that come within the scope of these claims.

We claim:

1. A wood-type golf club head comprising:

a body comprising a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt posi-

tioned around a periphery of the golf club head between the sole and the crown, wherein the body defines an interior cavity;

at least two weight ports; and

at least one weight having a weight mass between about 10 grams and about 50 grams and configured to be installed at least partially within a weight port formed in the body;

wherein the head has a golf club head origin positioned on the face plate at an approximate geometric center of the face plate, the head origin including an x-axis tangential to the face plate and generally parallel to the ground when the head is ideally positioned, a y-axis generally perpendicular to the x-axis and generally parallel to the ground when the head is ideally positioned and a z-axis perpendicular to the x-axis and y-axis, and wherein an installed at least one weight has a head origin x-axis coordinate greater than about −20 mm and less than about 20 mm, and

wherein a golf club head center of gravity has a head origin y-axis coordinate greater than about 15 mm where the positive y-axis extends from the head origin inwardly toward the cavity, and

wherein a volume of the golf club head is between about 180 cm^3 and about 600 cm^3.

2. The wood-type golf club head according to claim **1**, wherein the installed at least one weight has a head origin y-axis coordinate between about 0 mm and about 20 mm.

3. The wood-type golf club head according to claim **1**, wherein the installed at least one weight has a head origin y-axis coordinate between about 20 mm and about 50 mm.

4. The wood-type golf club head according to claim **1**, wherein the installed at least one weight has a head origin y-axis coordinate greater than about 50 mm.

5. The wood-type golf club head according to claim **1**, wherein the golf club head center of gravity has a head origin y-axis coordinate less than about 50 mm.

6. The wood-type golf club head according to claim **1**, wherein the golf club head center of gravity has a head origin x-axis coordinate greater than about −10 mm and less than about 10 mm.

7. The wood-type golf club head according to claim **1**, wherein the golf club head has a moment of inertia about a head center of gravity x-axis generally parallel to the origin x-axis between about 140 $kg \cdot mm^2$ and about 400 $kg \cdot mm^2$.

8. The wood-type golf club head according to claim **1**, wherein the golf club head has a moment of inertia about a head center of gravity z-axis generally parallel to the origin z-axis between about 250 $kg \cdot mm^2$ and about 600 $kg \cdot mm^2$.

9. A wood-type golf club head comprising:

a body comprising a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt positioned around a periphery of the golf club head between the sole and the crown, wherein the body defines an interior cavity;

at least first and second weight ports formed in the body; and at least a first weight having a mass between about 1 g and about 100 g configured to be retained at least partially within the first weight port and at least a second weight having a mass between about 1 g and about 100 g configured to be retained at least partially within the second weight port;

wherein the head has a golf club head origin positioned on the face plate at an approximate geometric center of the face plate, the head origin including an x-axis tangential to the face plate and generally parallel to the ground when the head is ideally positioned, a y-axis generally perpendicular to the x-axis and generally parallel to the ground when the head is ideally positioned and a z-axis generally perpendicular to both the x-axis and the y-axis, and wherein the first weight has a head origin x-axis coordinate greater than about 0 mm and less than about 60 mm and the second weight has a head origin x-axis coordinate greater than about −60 mm and less than about 0 mm, and

wherein a golf club head center of gravity has a head origin y-axis coordinate greater than about 15 mm where a positive y-axis extends towards the cavity, and wherein a volume of the golf club head is between about 180 cm^3 and about 600 cm^3.

10. The wood-type golf club head according to claim **9**, wherein the first weight and the second weight have head origin y-axis coordinates greater than about 0 mm and less than about 130 mm.

11. The wood-type golf club head according to claim **9**, wherein the golf club head center of gravity has a head origin y-axis coordinate between about 15 mm and about 50 mm.

12. The wood-type golf club head according to claim **11**, wherein the golf club head center of gravity has a head origin y-axis coordinate between about 15 mm and about 25 mm.

13. The wood-type golf club head according to claim **11**, wherein the golf club head center of gravity has a head origin y-axis coordinate between about 25 mm and about 35 mm.

14. The wood-type golf club head according to claim **11**, wherein the golf club head center of gravity has a head origin y-axis coordinate between about 35 mm and about 50 mm.

15. The wood-type golf club head according to claim **9**, wherein the golf club head center of gravity has a head origin x-axis coordinate greater than −10 mm and less than 10 mm.

16. The wood-type golf club head according to claim **9**, wherein the golf club head has a moment of inertia about a head center of gravity x-axis generally parallel to the origin x-axis between about 140 $kg \cdot mm^2$ and about 400 $kg \cdot mm^2$.

17. The wood-type golf club head according to claim **9**, wherein the golf club head has a moment of inertia about a head center of gravity z-axis generally parallel to the origin z-axis between about 250 $kg \cdot mm^2$ and about 600 $kg \cdot mm^2$.

18. The wood-type golf club head according to claim **9**, wherein the golf club head volume is greater than about 250 cm^3.

19. A wood-type golf club head comprising:

a body comprising a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt positioned around a periphery of the golf club head between the sole and the crown, wherein the body defines an interior cavity; and

at least one weight having a weight volume and a weight mass between about 10 grams and about 50 grams, the at least one weight configured to be installed at least partially within a weight port formed in the body;

wherein the head has a golf club head origin positioned on the face plate at a geometric center of the face plate, the head origin including an x-axis tangential to the face plate and generally parallel to the ground when the head is ideally positioned, a y-axis generally perpendicular to the x-axis and generally parallel to the ground when the head is ideally positioned and a z-axis perpendicular to both the x-axis and y-axis, and

wherein the installed at least one weight has a head origin x-axis coordinate greater than about −40 mm and less than about −20 mm or greater than about 20 mm and less than about 40 mm, and

wherein the golf club head has a center of gravity with a head origin y-axis coordinate greater than about 15 mm where a positive y-axis extends inwardly toward the cavity, and

wherein the head has a golf club head volume, and wherein the golf club head volume is between about 180 cm^3 and about 600 cm^3.

20. The wood-type golf club head according to claim **19**, wherein the installed at least one weight has a head origin y-axis coordinate between about 0 mm and about 20 mm.

21. The wood-type golf club head according to claim **19**, wherein the installed at least one weight has a head origin y-axis coordinate between about 20 mm and about 50 mm.

22. The wood-type golf club head according to claim **19**, wherein the installed at least one weight has a head origin y-axis coordinate greater than about 50 mm.

23. The wood-type golf club head according to claim **19**, wherein the golf club head center of gravity has a head origin y-axis coordinate less than about 50 mm.

24. The wood-type golf club head according to claim **19**, wherein the golf club head center of gravity has a head origin x-axis coordinate greater than about −10 mm and less than about 10 mm.

25. The wood-type golf club head according to claim **19**, wherein the golf club head has a moment of inertia about a head center of gravity x-axis generally parallel to the origin x-axis between about 140 $kg \cdot mm^2$ and about 400 $kg \cdot mm^2$.

26. The wood-type golf club head according to claim **19**, wherein the golf club head has a moment of inertia about a head center of gravity z-axis generally parallel to the origin z-axis between about 250 $kg \cdot mm^2$ and about 600 $kg \cdot mm^2$.

27. A wood-type golf club head comprising:

a body comprising a face plate positioned at a forward portion of the golf club head, a sole positioned at a bottom portion of the golf club head, a crown positioned at a top portion of the golf club head and a skirt positioned around a periphery of the golf club head between the sole and the crown, wherein the body defines an interior cavity;

at least one weight having a weight volume and weight mass between about 10 grams and about 50 grams, the at least one weight being configured to be installed at least partially within a weight port formed in the body;

wherein the head has a golf club head origin positioned on the face plate at a geometric center of the face plate, the head origin including an x-axis tangential to the face plate and generally parallel to the ground when the head is ideally positioned, a y-axis generally perpendicular to the x-axis and generally parallel to the ground when the head is ideally positioned and a z-axis perpendicular to both the x-axis and y-axis, and wherein the installed at least one weight has a head origin x-axis coordinate less than about −40 mm or greater than about 40 mm, and

wherein the golf club head has a golf club head volume and a golf club head center of gravity, and wherein the golf club head center of gravity has a head origin y-axis coordinate greater than about 15 mm where a positive y-axis extends inwardly towards the cavity, and

wherein the golf club head volume is between about 180 cm^3 and about 600 cm^3.

28. The wood-type golf club head according to claim **27**, wherein the installed at least one weight has a head origin x-axis coordinate greater than about −60 mm or less than about 60 mm.

29. The wood-type golf club head according to claim **27**, wherein the installed at least one weight has a head origin y-axis coordinate between about 0 mm and about 20 mm.

30. The wood-type golf club head according to claim **27**, wherein the installed at least one weight has a head origin y-axis coordinate between about 20 mm and about 50 mm.

31. The wood-type golf club head according to claim **27**, wherein the installed at least one weight has a head origin y-axis coordinate greater than about 50 mm.

32. The wood-type golf club head according to claim **27**, wherein the golf club head center of gravity has a head origin y-axis coordinate less than about 50 mm.

33. The wood-type golf club head according to claim **27**, wherein the golf club head center of gravity has a head origin x-axis coordinate greater than about −10 mm and less than about 10 mm.

34. The wood-type golf club head according to claim **27**, wherein the golf club head has a moment of inertia about a head center of gravity x-axis generally parallel to the origin x-axis between about 140 $kg \cdot mm^2$ and about 400 $kg \cdot mm^2$.

35. The wood-type golf club head according to claim **27**, wherein the golf club head has a moment of inertia about a head center of gravity z-axis generally parallel to the origin z-axis between about 250 $kg \cdot mm^2$ and about 600 $kg \cdot mm^2$.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 7,448,963 B2
APPLICATION NO. : 11/669900
DATED : November 11, 2008
INVENTOR(S) : Todd P. Beach et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 28, line 37, "about 111 cm^3" should read --about 110 cm^3--.

Signed and Sealed this

Sixteenth Day of March, 2010

David J. Kappos
Director of the United States Patent and Trademark Office