

(12) **United States Patent**
Nix et al.

(10) **Patent No.: US 7,145,900 B2**
(45) **Date of Patent: Dec. 5, 2006**

(54) **PACKET-SWITCHED TELEPHONY CALL SERVER**

(75) Inventors: **John A. Nix**, Chicago, IL (US); **Brian C. Wiles**, Cameron Park, CA (US); **Jeffrey S. Mumma**, Chicago, IL (US)

(73) Assignee: **Go2Call.com, Inc.**, Evanston, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 777 days.

(21) Appl. No.: **09/872,904**

(22) Filed: **May 31, 2001**
(Under 37 CFR 1.47)

(65) **Prior Publication Data**
US 2006/0098619 A1 May 11, 2006

(51) **Int. Cl.**
H04L 12/66 (2006.01)

(52) **U.S. Cl.** **370/352**; 370/401; 370/466

(58) **Field of Classification Search** 370/352, 370/356, 401, 389, 466; 709/227; 379/88.17
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,966,387	A	10/1999	Cloutier	
6,014,440	A	1/2000	Melkild et al.	379/269
6,026,290	A *	2/2000	Lamkin et al.	455/405
6,049,565	A	4/2000	Paradine et al.	
6,158,010	A *	12/2000	Moriconi et al.	726/1
6,201,805	B1 *	3/2001	Strathmeyer	370/356
6,282,275	B1 *	8/2001	Gurbani et al.	379/142.06
6,339,594	B1 *	1/2002	Civanlar et al.	370/352
6,360,366	B1 *	3/2002	Heath et al.	717/178
6,490,275	B1 *	12/2002	Sengodan	370/356
6,584,093	B1 *	6/2003	Salama et al.	370/351
6,603,849	B1 *	8/2003	Lin et al.	379/221.01
6,618,761	B1 *	9/2003	Munger et al.	709/241
6,711,417	B1 *	3/2004	Gorman et al.	455/550.1

6,738,383	B1 *	5/2004	Kliland et al.	370/401
6,747,970	B1 *	6/2004	Lamb et al.	370/352
6,751,652	B1 *	6/2004	Thomas	709/204
6,775,277	B1 *	8/2004	Li et al.	370/389
6,819,664	B1 *	11/2004	Jeong	370/352
6,819,665	B1 *	11/2004	Pinard et al.	370/352
6,819,667	B1 *	11/2004	Brusilovsky et al.	370/354
6,968,385	B1 *	11/2005	Gilbert	709/229
7,002,989	B1 *	2/2006	Agrawal et al.	370/467
2002/0126654	A1 *	9/2002	Preston et al.	370/352
2002/0154755	A1 *	10/2002	Gourraud	370/219

FOREIGN PATENT DOCUMENTS

EP	0 923 211	A2	6/1999
WO	WO 00/70834		11/2000

(Continued)

OTHER PUBLICATIONS

Hamdi, L.P. et al, Voice Service Internetworking for PSTN and IP Networks, May 1999, IEEE Communications Magazine.*

(Continued)

Primary Examiner—Chau Nguyen

Assistant Examiner—Steven A Blount


(74) *Attorney, Agent, or Firm*—McDonnell Boehnen Hulbert & Berghoff LLP

(57)

ABSTRACT

A system and method for providing packet-switched telephony service. The system provides call control, signaling, and/or delivery of voice, video, and other media in substantially real time. One embodiment of the system includes a call client application on a user device, and a call server located at a packet-switched telephony service provider. The call server is preferably operable to communicate with the call client in a non-native protocol and with the gateway in a native protocol.

25 Claims, 20 Drawing Sheets



FOREIGN PATENT DOCUMENTS

WO WO 00/76107 * 12/2000

OTHER PUBLICATIONS

Hjitema, Christian et al, An Architecture for Residential Internet Telephony Service, May/Jun. 1999, IEEE Network.*

Anquetil, L.P., Media Gateway Control Protocol And Voice Over IP Gateways, Jan. 1999, Alcatel Telecommunications Review.*

"Voice over IP Signaling: H.323 and Beyond", Hong Liu et al, Oct. 2000, IEEE Communications.*

Dialpad, Technology, www.dialpad.com/company/technology.html, (printed May 7, 2001).

Dialpad.com Signs One Million Members in First 8 Weeks, dated Dec. 14, 1999, www.industry.java.sun.com/javaneWS/stories/print/0,1797,21360,00.html, (printed May 7, 2001).

Serome Technology, Introduction of Dialpad World is First in a series of premium services to be offered to customers worldwide, dated Feb. 13, 2000, www.serome.com/board_01/content_gen.asp?seq=310 (printed May 7, 2001).

Net2phone, How Net2phone Works, dated May 7, 2001, www.net2phone.com/net2phone/prodcut_info/how.html, (printed May 7, 2001).

Speak Freely for Windows, Compression modes, www.speakfreely.org/doc/compress.html, (printed Mar. 26, 2002).

Speak Freely for Windows, The Answering Machine, www.speakfreely.org/doc/answer.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Communicating with other network voice programs, , www.speakfreely.org/doc/protocol.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Voice activation, www.speakfreely.org/doc/vox.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Viewing extended status, www.speakfreely.org/doc/prop.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Broadcasting to multiple sites, www.speakfreely.org/doc/broadcast.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Multicasting to a group, www.speakfreely.org/doc/multicast.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Local loopback, www.speakfreely.org/doc/loopback.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Ring a remote user, www.speakfreely.org/doc/ring.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Sending sound files, www.speakfreely.org/doc/soundfile.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Sending live audio, www.speakfreely.org/doc/send.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Receiving sound, www.speakfreely.org/doc/recv.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Development log, Auf. 23, 1995-Mar. 12, 1996, www.speakfreely.org/doc/development_log.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Bookshelf, www.speakfreely.org/doc/bookshelf.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Why encryption?, www.speakfreely.org/doc/crypt.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Release 7.0, dated Jan. 5, 2002, www.speakfreely.org/, (printed Mar. 26, 2002).

Speak Freely for Windows, 7.1, dated Oct. 1999, www.fourmilab.ch/speakfreely.org/windows/, (printed Mar. 26, 2002).

Speak Freely for Windows, Credits, www.speakfreely.org/doc/credits.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Bugs, features, and frequently-asked questions, www.speakfreely.org/doc/bugs.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Half-duplex vs. full-duplex, www.speakfreely.org/doc/duplex.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Sampling: 8 vs 16 bit, www.speakfreely.org/doc/sampling.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Measuring computer performance, www.speakfreely.org/doc/bench.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Viewing hardware configuration, www.speakfreely.org/doc/about.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Workarounds for driver bugs, www.speakfreely.org/doc/workarounds.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Problems: compression slows down connection, www.speakfreely.org/doc/probcompslow.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Problems: random pauses in output, www.speakfreely.org/doc/probrandpause.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Problems: regular pauses in output, www.speakfreely.org/doc/probregpause.html, (printed Mar. 26, 2002).

Speak Freely for Windows, Communicating with other network voice programs, www.fourmilab.ch/speakfree/windows/doc/protocol.html, (printed Mar. 26, 2002).

Speak Freely History, dated Apr. 18, 1999, www.speakfreely.org/history.html, (printed Mar. 26, 2002).

Wiles, et al., Speak Freely, Release 7.2 for Windows 95/98/NT/2000/ME, dated Jan. 4, 2002, www.speakfreely.org/main.html, (printed Mar. 26, 2002).

Walker et al., (1995), Speak Freely Development Log, Aug. 23, 1995-Jun. 30, 1999, www.fourmilab.ch/, (printed Mar. 26, 2002).

Copy of International Search Report dated Jul. 30, 2003, from counterpart international application PCT/US02/17181.

* cited by examiner

FIGURE 1
(PRIOR ART)




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13






FIGURE 14









FIGURE 17


FIGURE 18



FIGURE 19

FIGURE 20

1

**PACKET-SWITCHED TELEPHONY CALL
SERVER**

FIELD

The present invention relates to telecommunications over packet-switched networks. More particularly, the present invention relates to a call server for use on a packet-switched network.

BACKGROUND

Public packet-switched networks have recently supported voice communications. "Internet telephony" is one example of packet-switched telephony. In packet-switched telephony, a packet-switched network, such as the Internet, serves as a transportation medium for packets carrying voice data. Voice-over-Internet-Protocol (VoIP) is one example of a collection of standards and protocols used to support voice communications over packet-switched networks such as the Internet. Others have been developed as well. A common Internet telephony scheme involves a computer or other device that is capable of connecting to the Internet. A gateway from the Internet to the Public-Switched Telephone Network (PSTN) allows a user of the computer to communicate through the Internet and PSTN to a telephone subscriber at a telephone connected to the PSTN. Other configurations are also possible.

Numerous benefits may be realized through the use of packet-switched telephony. For example, calls may be less expensive because of the utilization of a packet-switched network, such as the Internet, to traverse distances around the world. This is in contrast to conventional telephone service, which typically involves tying up telephone circuits to connect calls. Thus, a user in one location may communicate with a telephone subscriber at a second location by transmitting voice data across the Internet to a gateway that is located near a telephone subscriber's location, in order to avoid paying some or all of the long distance fees that might otherwise be associated with making such a call. Another possible advantage of packet-switched telephony service is the convenient interfaces and features that may be offered in a packet-switched telephony system. For example, volume control, a video session, or an address book application may be implemented. Many Internet Telephony Service Providers (ITSPs) have been formed in order to provide these services. Examples of ITSPs include Go2Call.com, Net2Phone, DialPad, Maxcall, AccessPower, and others. Each ITSP generally has its own calling rate and fee structure and may require a download of client software.

The download requirements vary by ITSP, but in general they require an application, such as a Java applet, and telephony gateway protocol software to be downloaded onto the device that will be interfacing with the Internet. The Java applet contains a dialing application can be used by a device equipped with a Java-capable browser, such as Internet Explorer and Netscape.

Several Internet telephony gateway protocols are available, including H.323, Session Initiation Protocol (SIP), and Media Gateway Control Protocol (MGCP). International Telecommunications Union standard H.323 is the current standard for transmitting voice over the Internet. One of the limitations of using H.323 is its large size. Downloading an H.323 stack can take up to ten minutes depending on a user's modem speed.

It is common for protocol standards to evolve quickly. As the protocol standards change, the user must typically down-

2

load an application supporting the new version of the standard, in order to be able to complete an Internet call. The user will be delayed in placing their Internet call for the time it takes to download the latest version of the telephony gateway protocol. This is an inconvenience to the user and a potential lost subscriber to the ITSP.

A user may also wish to access the Internet using a handheld device or a cellular phone. Memory in these devices is typically more limited than in personal computers. As a result, large downloads may cause memory problems, or may even be impossible. As the world becomes more mobile, the use of these devices will likely increase, which will likely further the demand for Internet telephony.

BRIEF DESCRIPTION OF THE DRAWINGS

Various embodiments are described with reference to the following drawings, wherein:

FIG. 1 is a simplified block diagram illustrating an exemplary packet-switched telephony system;

FIG. 2 is a simplified block diagram illustrating an exemplary packet-switched telephony system;

FIG. 3 is a simplified block diagram illustrating an exemplary call client system;

FIG. 4 is a simplified block diagram illustrating an exemplary Packet-switched Telephony Server Provider system;

FIG. 5 is a simplified block diagram illustrating an exemplary front end;

FIG. 6 is a simplified block diagram illustrating an exemplary call server;

FIG. 7 is a simplified block diagram illustrating an exemplary call director;

FIG. 8 is a simplified block diagram illustrating an exemplary call handler;

FIG. 9 is a simplified block diagram summarizing user device communications with a call server;

FIG. 10 is a simplified block diagram illustrating an exemplary call logger;

FIG. 11 is a simplified block diagram illustrating an exemplary proxy server;

FIG. 12 is a simplified block diagram illustrating the details of the PTSP, according to an exemplary embodiment;

FIG. 13 is a simplified block diagram illustrating an exemplary embodiment employing two data streams from a user device;

FIG. 14 is a simplified block diagram illustrating an exemplary embodiment employing a single data stream from a user device;

FIG. 15 is a simplified message flow diagram illustrating an exemplary call control sequence;

FIG. 16 is a simplified block diagram illustrating an exemplary system for allocating assets to a particular telephony protocol;

FIG. 17 is a simplified flow diagram illustrating an exemplary method for providing packet-switched telephony service;

FIG. 18 is a simplified flow diagram illustrating an exemplary method for providing packet-switched telephony service;

FIG. 19 is a simplified flow diagram illustrating an exemplary method for providing packet-switched telephony service; and

FIG. 20 is a simplified flow diagram illustrating an exemplary method for providing packet-switched telephony service.

DETAILED DESCRIPTION

I. Packet-Switched Telephony

FIG. 1 is a simplified block diagram illustrating an exemplary packet-switched telephony system 100. The system 100 includes a computer 102 from which a user wishes to place a call to a telephone subscriber located at a phone 104. The computer 102 is linked to a packet-switched network 106, such as the Internet. An Internet Telephony Service Provider (ITSP) or other packet-switched telephony service provider may operate a telephony gateway 108 between the packet-switched network 106 and a Public-Switched Telephone Network (PSTN) 110. The PSTN 110 provides service to the phone 104. The packet-switched network 106 includes network equipment that routes the individual voice data packets to a destination address identified in the individual packets.

The computer 102 contains a microphone 112 and speakers 114a,b. During a call, a user located at the computer 102 can speak into the microphone 112 to provide a voice signal input to the computer 102. A processor in the computer 102 digitizes the user's voice and assembles the data into packets according to one or more protocols, such as the Internet Protocol (IP) suite. These voice data packets are then transmitted across the packet-switched network 106 to the gateway 108. The sampling rate of the voice signal is preferably chosen to be high enough to cause the digitized voice data to sound like a continuous voice signal to a human ear. The gateway 108 converts the voice data packets back into a voice signal for further transmission on the PSTN 110. The PSTN 110 transmits the voice signals on a dedicated circuit to the phone 104. A user located at the phone 104 receives the voice signals, which may be heard through a speaker associated with the phone 104. Similarly, the user located at the phone 104 can speak into a microphone at the phone 104 to cause a voice signal to be transmitted across the PSTN 110 to the gateway 108, where the voice signal is converted into voice data packets for transmission across the packet-switched network 106 to the computer 102. The processor in the computer 102 may convert the voice data packets into a voice signal to be played on the speakers 114a,b.

Although the gateway 108 is shown as being a single device in FIG. 1, an ITSP may have several or many gateways similar to the gateway 108. The different gateways would likely be located in various locations around the world to take advantage of possible savings in long distance fees. Although the PSTN 110 may offer circuit-switched telephone service to local phone subscribers as well as to subscribers located at more distant local exchanges, long distance fees might be incurred for placing calls through the distant local exchanges. Thus, an ITSP will preferably route the call to a gateway having a connection to a PSTN that can provide local service to the phone number to be called. An ITSP gateway may be used to administer such a call routing scheme for a particular ITSP.

II. Packet-Switched Telephony Server Provider Exemplary System

FIG. 2 is a simplified block diagram illustrating an exemplary packet-switched telephony system 200. The system 200 includes a user device 202, a Packet-switched Telephony Service Provider (PTSP) 206, a gateway 208, and a target device 212. The user device 202 is linked to the PTSP 206 through a packet-switched network 204, such as the Internet. The PTSP 206 is linked to the gateway 208. The link between the PTSP 206 and the gateway 208 may be

through a packet-switched network, such as the Internet, or some other physical and/or wireless network. The gateway 208 is linked to the target device 212 through a PSTN 210 and/or some other network.

According to the exemplary system 200, a user located at the user device 202 may initiate a call to a target user located at the target device 212 by participating in a call initiation process involving the user device 202 and the PTSP 206. For example, the user device 202 may access a web-site maintained by the PTSP 206, using a web-browser, such as Microsoft Internet Explorer or Netscape Navigator. As another example, the user device 202 may execute a calling application to contact the PTSP 206 through the packet-switched network 204. The call initiation process may include choosing a phone number or address book entry to call, and may include specifying other call parameters. The PTSP 206 continues the initiation process by transmitting call initiation information to the gateway 208 so that the gateway 208 may attempt to reach the target device 212 through the public switched telephone network 210. If the call initiation process is successful, voice communications may be transmitted back and forth between the user device 202 and the target device 212. Voice data transmitted between the user device 202 and the PTSP 206 will preferably consist of packets containing voice information, as well as any other information desired by the user at the user device 202, or the PTSP 206. Data transferred between the PTSP 206 and the gateway 208 will also preferably be packetized data. Data transferred between the gateway 208 and the target device 212 via the PSTN 210 may include circuit-switched data rather than packet-switched data. Alternatively, the PSTN 210 may include one or more portions that are packet-switched and one or more portions that are circuit-switched. As a result of the various conversions and/or conveyances that occur at the PTSP 206 and gateway 208 over the packet-switched network 204 and the PSTN 210, the user device 202 is able to receive voice data transmitted by the target device 212, and vice versa.

A. User Device

The user device 202 is shown as a simple rectangular box in FIG. 2 to emphasize the variety of different forms the user device 202 might take on from one embodiment to the next. For example, the user device 202 might be any one of the following: a personal computer, a mobile phone, a wireless handheld device, or a packet-switched telephone. The user device 202 is not limited to any of these devices, and is intended to encompass future communication and information technology. Various embodiments of the system 200 will include a user device 202 having at least a link to the PTSP 206, a telephony client application, and a mechanism for user input and output. For example, the user device 202 may be a device that is capable of accessing the Internet and that is operable to execute a telephony client, such as a Java virtual machine or other "thin" client. Further details regarding the user device 202 may be found throughout this specification.

FIG. 3 is a simplified block diagram illustrating an exemplary embodiment of a call client system 300. The system 300 includes a call client 302 and a browser session 304. The call client 302 includes a software library 306 and a Java virtual machine 308. The software library 306 and the Java virtual machine 308 are linked by an interface 310. The call client 302 and the browser session 304 are linked by an interface 312. Interfaces 310 and 312 may be software links.

The software library 306 may include functionality for coding voice audio input into digital signals and for decoding digital signals into voice audio output, such as a

5

Dynamic Link Library (DLL). Other functions may also be provided. In a preferred embodiment, the software library **306** includes a Real-Time Protocol (RTP) stack, an Application Program Interface (API) (such as a Microsoft Windows API), a voice codec (such as a G.711 codec module), and a call control stack. In one embodiment, a HyperText Transfer Protocol (HTTP) stack is implemented to assist in firewall circumvention. Additionally or alternatively, a port scan module may be included to identify potential ports to use to avoid firewall interference.

The Java virtual machine **308** preferably includes an interface, such as a Graphical User Interface (GUI). According to an alternative embodiment, the Java virtual machine **308** also includes a billing system, to assist in keeping track of call time and other potential billing parameters. While the Java virtual machine **308** includes "Java" in its description, the Java language is merely one implementation, and other languages and module types are also intended to be within the scope of the present system. Java, from Sun Microsystems, is merely one possibility for implementing the Java virtual machine, and the provided functionality (e.g. GUI) is more relevant than the particular implementation of the Java virtual machine.

The browser session **304** is operable to support a Java virtual session, such as one downloaded from the PTSP **206**.

The user device components described above are merely preferred implementations, and variations may be made without departing from the intended scope of the present system. For example, one or more of the user device components described above may be combined with one or more other components. Moreover, additional components may be provided to perform other functions or to assist in performing functions described above. While the components of the user device are preferably primarily software-based, one or more components may include hardware or firmware aspects.

B. Packet-Switched Telephony Server Provider (PTSP)

FIG. **4** is a simplified block diagram illustrating at least a portion of an exemplary Packet-switched Telephony Server Provider (PTSP) system **400**. PTSP **400** may be similar to or substantially the same as the PSTP **206** of the system **200**. The PSTP **400** includes a front end **402**, a call server **404**, and a proxy server **406**. Other configurations are also possible, such as configurations with different numbers of these components, and are intended to be within the scope of the present system. In addition, while the components of PSTP **400** are shown as being co-located, this is merely for purposes of illustration, and one or more parts of the PSTP **400** may be remotely located from other parts. Similarly, the parts may be combined into one physical device.

1. Front End

FIG. **5** is a simplified block diagram illustrating an exemplary front end **500**. Front end **500** may be similar to or substantially the same as the front end **402** of the PTSP **400**. The front end **500** preferably includes a call server database **502** and a load balancer **504**. The front end **500** may be used to select a particular call server **506a-c**, if more than one call server is available. Although three call servers **506a-c** are shown in FIG. **5**, other numbers of call servers may alternatively be provided. If only one call server is provided, then load balancing would likely provide little or no performance benefit. In some embodiments, it may be possible to eliminate much or all of the front end altogether. In addition, the front end **500** is preferably only involved when a call request is first received by the PTSP **400** and possibly to maintain the call server database **502**. After any interactions the user device **202** has with the front end **500**

6

have been completed, many or all user interactions will be primarily through a call server, such as one of the call servers **506a-c**.

The front end **500** may be used as call requests are received by the PTSP **400**, to assist in handling a large number of calls. The PTSP **400** may keep information pertaining to current calls in the call server database **502**. As a result, the current number of calls on any particular server, such as any one of the call servers **506a-c**, may be monitored and used to beneficially handle new call initiations. The front end **500** may thus access current call data to select an appropriate call server for an incoming call request. For example, the front end **500** may use call density data to determine which of the call servers **406a-c** is the least busy, in order to possibly improve call performance. As another option, the front end **400** may use a round-robin selection scheme, in which the front-end **500** distributes individual call requests to the call servers **506a-c** in some ordered manner irrespective of call density. Other load balancing techniques may also be used, such as utilizing particular call servers to correspond to particular users.

It may be desirable to implement more than one call server **506a-c** at a PSTP **400** for one or more of the following reasons. The quantity of calls that may be handled by a PTSP **400** will likely be increased as the PTSP **404** adds call servers **506a-c**. For example, a call server **506a-c** may be able to handle only a limited number of concurrent calls (e.g. up to 150 calls per server) before call quality degrades to a certain threshold service level. In addition, different call servers **506a-c** may be optimized to interface with different gateways, such as the gateway **208** shown in the system **200**. Different gateways **208** often utilize network equipment provided by different equipment manufacturers. The likelihood of compatibility problems may be decreased if a call server **506a-c** is implemented on a device built by the same manufacturer as the gateway manufacturer. As an alternative to hardware-matching, a call server's software or firmware may be tweaked to increase compatibility with a particular gateway **208**. Software tweaking may address problems caused by different manufacturers implementing slightly different "flavors" (additional/alternative features, etc.) of standard protocols, for example. Another advantage of using multiple call servers **506a-c** is that different call server/gateway combinations may utilize different protocols for telephony services. For example, one call server **506a-c** may be dedicated to a gateway **208** that implements the H.323 protocol, while another call server **506a-c** may be dedicated to a gateway **208** running the Session Initiation Protocol (SIP) or the Media Gateway Control Protocol (MGCP). If a particular telephony protocol is updated, only the call server(s) **506a-c** implementing that protocol is required to implement the update.

If load balancing is provided by the PTSP **400**, then a variety of implementation techniques may be used, involving software or hardware, for example. In one embodiment, a hardware solution called the BIG-IP Controller, available from F5 Networks Inc. of Seattle, Wash., may be utilized. In another embodiment, a software solution called Resonate Central Dispatch, available from Resonate, Inc. of Sunnyvale, Calif. Other load balancing techniques are known, many of which may be used to advantage in PTSPs **400** handling large call volumes. Further details regarding the load balancer **504** and the front end **500** may be found throughout the specification.

2. Call Server

FIG. **6** is a simplified block diagram illustrating an exemplary call server **600**. Call server **600** may be similar to

or substantially the same as the call server **404** of the PTSP **400**. The call server **600** preferably includes a call director **602**, a plurality of call handlers **604a-c**, and a call logger **606**. Although three call handlers **604a-c** are shown in FIG. 6, this is merely for purposes of illustration, and other quantities of call handlers may be provided. In one alternative embodiment, only one call handler **604** is provided.

a. Call Director

FIG. 7 is a simplified block diagram illustrating an exemplary call director **700**, which may be included within the call server **600**. The call director **700** preferably includes a rules database **702** and a branding unit **704**.

Upon receiving a call request from a user device, such as the user device **202** in the system **200**, the call director **700** launches a call handler, such as one of the call handlers **604a-c** shown in FIG. 6, if the user device is authorized to make the requested call. The call director **700** may, for example, access the rules database **702** to determine an authorization status for the requested call. In an exemplary embodiment, the call director **700** parses a phone number and checks the rules database **702** to see if calls are allowed to the destination signified by the prefix of the phone number. The rules database **702** may also contain information on service agreements with users, so that the call director **700** may determine whether the user device has used up a maximum number of minutes, for example. Other authorization techniques may be implemented in addition to what has been described above, by appropriately modifying the information stored in the rules database **702** and/or the operations on the information contained in the rules database **702**. If the call director **700** determines that the user device **202** is not authorized to make a particular call, then an "unauthorized" message may be transmitted to the user device **202**, or some other action may be taken. Authorization may be determined from a user name/password login process, from an inspection of "cookies" located on the user device **202**, or from some other technique. If the call director **700** determines that the user device **202** is authorized to make a particular call, then a call handler **604a-c** may be launched, such as through the issuance of a launch command (e.g. a UNIX command).

The branding unit **704** may be included to provide branding information to the user device. For example, the branding unit **704** may transmit an audio sample to the user device to inform the user of the PTSP's **400** identity. Alternatively, advertisements for the PTSP **400** or for other commercial entities may be transmitted to the user device **202**, such as in a scheme in which the user agrees to view advertisements in exchange for receiving telephony service. The selection of which advertisements are transmitted may be based on the phone number to be called, the user device **202**, the time of day, or other parameters. Other advantages may also be realized through various embodiments. Additionally, branding may be performed at a different location in the PTSP, or it may be omitted altogether.

b. Call Handler

FIG. 8 is a simplified block diagram illustrating an exemplary call handler **800**. The call handler **800** preferably includes a call master **802** and a call slave **804**. The call master **802** is linked, such as through a packet-switched network, to a call client **810** on a user device **806**. The call slave **804** is linked to a gateway **808** through a network, such as a packet-switched network (e.g., the Internet, or a dedicated connection).

In a multiple-user environment, a call handler similar to the call handler **800** may be launched for every call. Thus, in any one call server **600**, there may be many calls at any

particular time. Each call handler **800** may be launched on a specific port that is assigned to the user device **806** that initiated the call. Call handlers **800** may communicate with each other, for example, during multiparty conference calls.

The call master **802** is configured to communicate with the call client **810** on the user device **806**. The user device **806** and the call master **802** preferably communicate according to a non-native protocol having very little overhead and providing specialized information to the PTSP **400**, such as call quality, etc. Other communications, include pings, Transmission Control Protocol (TCP) requests, and branding tones, may also be exchanged, according to exemplary embodiments. Through the use of such a non-native protocol, the PTSP need not modify the call client **810** every time a modification is made to a native telephony protocol. An example of a non-native protocol is a proprietary protocol that carries voice data and little else. In contrast, a native protocol (such as H.323, SIP, or MGCP) will typically include overhead to satisfy the expectations and requirements defined in the native protocol. Efficiency and robustness may be realized by using a streamlined non-native protocol between the user device **806** and the call master **802**. In addition, the same non-native protocol may be used regardless of what protocol (e.g. H.323, SIP, MGCP, etc.) is used by the gateway **808**. The call client **810** is therefore allowed to be small in size (e.g. around 200 kilobytes), relative to existing telephony clients that implement much or all of a standard telephony protocol used on a gateway **808**. Further details regarding the call client **810** and the non-native protocol may be found throughout the specification.

According to a preferred embodiment, the non-native protocol includes a set of data messages in a proprietary format to control basic call functionality. These messages are formatted as UDP (User Datagram Protocol), TCP (Transmission Control Protocol), or HTTP (Hyper-Text Transport Protocol) and are sent from the user device **806** to the PTSP to properly set up, monitor, and tear down calls. The messages in the non-native protocol may include information such as one or more of the following: an IP address of the user device; a port number to transmit data to the user device; an ITU E.164 telephone number; a user name for identification; a token, key, and/or password for authorization; and commands for the call handler. The messages in the native protocol may include data transferred as Packed Encoding Rules (PER), Basic Encoding Rules (BER), or ASN.1 notation for H.323 formatted messages, or Uniform Resource Locator (URL) for SIP formatted messages. Other non-native and native protocols may also be used.

The call slave **804** communicates with the gateway **808** using the native protocol of the gateway **808**. As a result, the call slave **804** preferably implements a large portion of the native protocol stack, and, in some embodiments, may implement the entire native protocol stack. This is in contrast to the call master **802**, which need only implement a skeleton non-native protocol. When updates or modifications are made to the native protocol associated with the gateway **808**, only the call slave **804** is modified, according to a preferred embodiment. The call master **802** preferably provides (through the call handler **800**) the call slave **804** with only the minimum data required to initiate, maintain, or teardown the call. This minimum data may be all that is required by all native protocols supported by all of a PTSP's call servers. As a result, the same call master **802** and call client **810** combination may be used for all call servers regardless of what native protocol is used, according to a preferred embodiment. The call handler **800** may include protocol stacks of both the native protocol and the non-

native protocol to facilitate the transfer of call data from the call master **802** to the call slave **804** in the appropriate format. The call handler **800** may translate the non-native protocol data received by the call master **802** to the native protocol used by the call slave **804** to communicate with the gateway **808**, and vice versa. Thus, in some embodiments, the call slave **804** may be obtained “off-the-shelf,” without any other modifications being made to the call handler **800**. In another embodiment, the call handler **800** may include protocol stacks for two or more different native protocols, to allow the call slave **804** to interface with more than one gateway, each running a different native protocol. Additional details regarding the call handler **800** may be found throughout the specification.

FIG. **9** is a simplified block diagram illustrating user device communications with the call server in a system **900**, according to a preferred embodiment. The system **900** includes a user device **902**, a front end **904**, and a call server **906**. The call server **906** includes a call director **908** and a call handler **910**.

A request to initiate a call **912** from the user device **902** may be received by the front end **904**, which may select the call server **906**. The call director **908** within the call server **906** will determine an authorization status for the requested call. If the call director **908** determines that the user device **902** is not authorized to make a particular call, then the call director **908** may send an “unauthorized” message **914** to the user device **902**. If the call director **908** determines that the user device **902** is authorized to make a particular call, then the call director **908** will launch the call handler **910** within the call server **906**. Once the user device **902** is authorized, the user device **902** and the call server **906** will transmit and receive messages **916** using the call handler **910**.

c. Call Logger

FIG. **10** is a simplified block diagram illustrating an exemplary call logger **1000**. The call logger **1000** preferably includes a display unit **1002** and a connection database **1004**. Other configurations, including more or fewer components, are also intended to be within the scope of the present system.

The call logger **1000** may be included in a PSTP system, such as the PTSP system **400**, in order to keep track of all active calls in a particular call server, such as the call server **600**. The call logger **1000** may also remove inactive connections, which may occur during a disconnect event or a specified idle time event, such as 30 seconds of inactivity. For example, the call logger **1000** may track at least any of the following: when a call handler **800** is launched, when a call is ringing at a target device **212**, when a call is established, and when a call is disconnected (hung up by the target device **212** or the user device **202**). Any or all of these may be stored in the connection database **1004**, and may preferably be displayed on the display unit **1002** for viewing by an administrator of the PTSP **400**. Although the call logger **1000** is shown as part of the call server **600**, this is merely a preferred embodiment, and the call logger **1000** may be situated at another location at or accessible by the PTSP **400**. As another alternative, the call logger **1000** may be omitted. This is, however, not recommended in a multiple-user setting, due to the desirability of tracking calls and equipment usage. In another embodiment the connection database **1004** is associated with (and may be included with) the call server database **502**.

3. Proxy Server

FIG. **11** is a simplified block diagram illustrating an exemplary proxy server **1100**. Proxy server **1100** may be similar to or substantially the same as the proxy server **406**

of PTSP **400**. The proxy server **1100** preferably includes a registration database **1102** and a gateway database **1104**. The proxy server **1100** may be used to select a gateway **1106a-c**, if more than one gateway is provided. Gateway selection criterion may include the number of calls the gateway **1106a-c** is handling, the location of the gateway **1106a-c**, and the type of telephony protocol the gateway **1106a-c** uses.

The registration database **1102** stores information pertaining to users and/or user devices **202**. In a preferred embodiment, every potential user must first register with the PTSP **400** prior to placing any calls over equipment maintained by the PTSP **400**. This may assist in billing, authentication, fraud control, and marketing intelligence, for example. In some embodiments, each registered user is associated with one or more proxy servers **1100**, and the association is stored in the registration database **1102**.

The gateway database **1104** stores information pertaining to the gateways **1106a-c** with which the PTSP **400** is associated, the gateway administration entity (e.g. Focal Communications, Sprint, etc.), how many calls are being handled by each gateway **1106a-c**, and other information pertaining to gateways **1106a-c** associated with the PTSP **400**.

The proxy server **1100** may access the registration database **1102** and the gateway database **1104** to select an appropriate gateway **1106a-c** for a call. The proxy server **1100** may, for example, be a gatekeeper according to the H.323 protocol. In a preferred embodiment, the proxy server **1100** is only involved during a gateway selection process. In another embodiment, only one gateway is present, and the proxy server may be omitted. (In such a case, it may be desirable to continue maintaining the registration database **1102** and/or the gateway database **1104**, for system monitoring). After the proxy server **1100** has selected an appropriate gateway **1106a-c**, the IP address of the selected gateway **1106a-c** is available to various components within the PTSP **400**, such as the call handler **800**. Although three gateways **1106a-c** are shown in FIG. **11**, this is for illustrative purposes only, and other numbers of gateways may also be provided.

In a preferred embodiment, the PTSP **400** has a plurality of proxy servers **1100** associated with a respective plurality of gateways **1106a-c**. The proxy server **1100** used for a particular call might, for example, be based on a prefix in a phone number to be called. Other proxy selection criteria may also be used.

C. Gateway

The gateway **208** is a known device that is often located on the premises of a conventional (circuit-switched) telephony provider. The gateway **208** typically serves at the point where data on a call is translated from packet-switched data to circuit-switched data. In some embodiments, the Public Switched Telephone Network (PSTN) **210** may include packet-switching network portions. For purposes of the present system, the details regarding the gateway **208** are important primarily for determining what native protocol(s) and networking equipment are in use, in order to select an appropriate call server **600** (and call slave **804**).

D. Target Device

The target device **212** is preferably a telephone having a direct or indirect connection to the PSTN **210**, or to some other network. Alternative implementations of the target device **212**, such as a mobile phone and other communication device, are also intended to be within the scope of the present system. The details regarding the target device **212** are not of particular importance for operation of the PTSP

11

400. The exact configuration of the target device 212 will likely depend on the network(s) between the gateway 208 and the target device 212. The user device 202 (or an associated user) need only know how to reach the target device 212, such as by dialing a phone number, selecting an address book entry, or entering some other target identifier.

FIG. 12 illustrates a packet-switched telephony system 1200, according to a preferred embodiment. The system 1200 is shown to include components as described above, with like reference numerals indicating like functionalities and connections. As was described above, many variations may be made from the illustrated configuration, without departing from the intended scope of the system. It should also be noted that a target device and a PSTN have been omitted from FIG. 12 to improve clarity of illustration.

III. Communication of Packet-Switched Data from the User Device

A. Call Operation: First Exemplar Embodiment

FIG. 13 is a simplified block diagram illustrating call operation in a telephony system 1300 according to a first exemplary embodiment. The system 1300 includes a user device 1302, a PTSP 1306, a gateway 1308, and a target device 1312. The user device 1302, the PTSP 1306, the gateway 1308, and the target device 1312 of system 1300 may be similar to or substantially the same as the user device 202, the PTSP 206, the gateway 208, and the target device 212 of system 200.

The user device 1302 is linked to both the PTSP 1306 and the gateway 1308 through a packet-switched network 1304, such as the Internet. The PTSP 1306 is also linked to the gateway 1308, such as through the Internet, a dedicated connection, or some other network. The gateway 1308 is linked to the target device 1312 through a PSTN 1310 and/or another network.

The user device 1302 sends call control data via the packet-switched network 1304a to the PTSP 1306. Examples of call control data include setup information (e.g. the call request, the phone number to call, etc.), ping information sent periodically (e.g. “stay alive” signals, signal strength indicators, etc.), and disconnect signals. The user device 1302 sends media data via the packet switched network 1304b to the gateway 1308. Thus, if the packet-switched network 1304a,b is an IP network, different packets from the user device 1302 may have different destination IP addresses, depending on the type of data contained in the packet.

The embodiment shown in FIG. 13 may provide performance benefits. Because media is transmitted directly to the gateway 1308, rather than through the PTSP 1306, there will likely be fewer “hops” between the user device and the target device, resulting in less delay. In addition, because an industry standard may be used to communicate media with the gateway, there will likely be fewer dropped calls, quicker ping times, and more scalability. One possible disadvantage may result from having to implement portions of a native protocol at the user device 1302. The call client 1314 may be a larger download for the user device 1302 than if all packets (including media) were transmitted by the user device 1302 to the PTSP 1306, in which a non-native protocol could be used for all packet transmissions. Because call control is still primarily handled by the PTSP 1306 in the system 1300, the call client 1314 on the user device 1302 is still likely to be smaller than it would be if call control were implemented at the gateway 1308. If call control were implemented at the gateway 1308, the user device 1302

12

would likely need to implement a more complete telephony stack in order to communicate with the gateway 1308.

Either party to the call shown in the system 1300 may initiate a disconnect procedure. If the target device 1312 initiates the disconnect procedure, the PSTN 1310 forwards the disconnect request to the gateway 1308. The gateway 1308 communicates the disconnect information to the call server of the PTSP 1306, and the call server 600 transmits a disconnect message to the user device 1302, to cause the user device 1302 to stop audio traffic transmission and return to a “ready” state. If the user device 1302 initiates the disconnect procedure, the call client 1314 on the user device 1302 transmits a disconnect message to the call server 600 of the PTSP 1306. The PTSP 1306 communicates the disconnect request to the gateway 1308 to cause the call to be disconnected.

B. Call Operation: Second Exemplary Embodiment

FIG. 14 is a simplified block diagram illustrating call operation in a telephony system 1400 according to a second exemplary embodiment. System 1400 includes a user device 1402, a PTSP 1406, a gateway 1408, and a target device 1412. The user device 1402, the PTSP 1406, the gateway 1408, and the target device 1412 of system 1400 may be similar to or substantially the same as the user device 202, the PTSP 206, the gateway 208, and the target device 212 of system 200. The user device 1402 is linked to the PTSP 1406 through a packet-switched network 1404, such as the Internet. The PTSP 1406 is linked to the gateway 1408 through a packet-switched network, such as the Internet, or some other network. The gateway 1408 is linked to the target device 1412 through the PSTN 1410.

In contrast to the first embodiment shown in FIG. 13, packets containing media and call control information are transmitted to the PTSP 1406, preferably according to a non-native protocol. The PTSP 1406 (i.e. the call handler 800) transmits the information to the gateway 1408, according to the native protocol of the gateway 1408. Similarly, media and call control packets from the gateway 1408 are transmitted to the PTSP 1410, and the PTSP 1410 transmits similar packets to the user device 1402.

In a potentially advantageous aspect of the second embodiment, the non-native protocol includes transmitting the media and/or the call control information as HTTP packets, to assist in traversing firewalls, which often block media traffic on unrecognized ports. If a port number normally associated a non-telephony application is used (e.g. ports 20, 21, 22, 23, 25, 80, 110, 119, 443, and/or 7070) is used, then a firewall is more likely to allow the media to pass through.

In another aspect of the second embodiment, conference calling may be enabled, since all media flows through the PTSP 1406. The PTSP 1406 may thus serve as a mixing entity for two or more user devices 1402 and/or target devices 1412.

FIG. 15 is a message flow diagram illustrating a method 1500 for providing packet-switched telephony service, according to an exemplary embodiment. The entities shown as transmitting and receiving messages include a user device 1502, a front end 1504, a call server 1506, a proxy server 1508, and a gateway 1510. Various messages to be set forth below may be transmitted or received by entities other than what is described. For example, the front end 1504, the call server 1506, and the proxy server 1508 may have lower level components or may be included within higher level components, some of which may be involved in the transmission of messages, according to alternative embodiments.

13

The user device **1502** transmits a call request **1512** to the front end **1504**. The call request **1512** may include a phone number and a user identification code, for example, transmitted via a TCP/IP connection. ("TCP/IP" refers to Transmission Control Protocol/Internet Protocol. TCP is described in J. Postel, ed., "Transmission Control Protocol," IETF RFC 793, and IP is described in J. Postel, ed., "Internet Protocol," IETF RFC 791, September 1981, both of which are incorporated by reference herein.)

The front end **1504** makes a call server selection **1514**. In the method **1500**, the front end **1504** has selected the call server **1506**.

The call server **1506** determines whether the call request **1512** from the user device **1502** is valid, which may include determining whether the user identification code and/or the phone number to be dialed are authorized under the user's call plan. If the call request **1512** is not valid, then the call server **1506** may transmit a rejection message **1516** to the user device **1502**. If the call request **1512** is valid, then the call server **1506** registers the user device **1502** with the proxy server **1508**, as shown in **1518**.

The proxy server **1508** makes a gateway selection **1520**, and transmits a network address (e.g. an IP address) to the call server **1506**, as shown in **1522**. In the method **1500**, the proxy server **1508** has selected the gateway **1512**.

The call server **1506** transmits branding information and an appropriate IP address (which may depend upon which embodiment is implemented) to the user device **1502**, as shown in **1524**.

The call server **1506** transmits call setup information **1526** to the gateway **1510** to initiate the call, and the gateway **1510** may transmit a call acceptance message **1528** back to the call server **1506**.

The call server **1506** may transmit a call status indicator **1530** to the user device **1502**, and a call notification **1532** may be issued from the gateway **1510** to the user device **1502**, depending on the particular embodiment implemented. A call **1534** is established. Media for the call is preferably transmitted as RTP (Real-time Transport Protocol) over UDP (User Datagram Protocol). RTP is described in Schulzrinne et al., "RTP: A Transport Protocol for Real-Time Applications," IETF RFC 1889, January 1996, and UDP is described in Postel, "User Datagram Protocol," RFC 768, August 1980, both of which are incorporated by reference herein.

While the call **1534** is in process, the call server **1506** may be in communication **1536** with the gateway **1510** to monitor the call **1534**. The call monitoring may include periodic pings, call quality, and error detection, and is preferably conducted using the native protocol of the gateway **1510**.

As was discussed above, a disconnect **1538** may be initiated by either party.

FIG. **16** is a simplified block diagram showing an exemplary system **1600** allocating assets to a particular telephony protocol. Although the SIP and H.323 protocols are illustrated in FIG. **16**, other numbers and types of protocols may alternatively be employed. The system **1600** includes a user device **1602**, assets assigned to the SIP protocol **1604**, assets assigned to the H.323 protocol **1606**, a PSTN **1608**, and a target device **1610**. The user device **1602** includes a call client **1612**. The assets assigned to the SIP protocol **1604** include a SIP call server **1614**, a SIP proxy server **1616**, and a SIP gateway **1618**. The assets assigned to the H.323 protocol **1606** include an H.323 call server **1620**, an H.323 proxy server **1622**, and an H.323 gateway **1624**.

The user device **1602** may communicate to the assets assigned to a particular protocol based on the prefix in a

14

phone number to be called. Other selection criteria may also be employed. If a particular telephony protocol is updated, only the call server(s) implementing that protocol is required to implement the update.

FIG. **17** is a flow diagram illustrating a method **1700** for providing packet-switched telephony service, according to an exemplary embodiment. The method **1700** includes receiving a call request from a user device **202**, as shown in **1702**. The call request includes a target indicator of a target device **212** that the user device **202** is attempting to call. For example, the target indicator may include a telephone number corresponding to the target device **212**. The call request received from the user device **202** is formatted and/or received according to a non-native protocol. In **1704**, a call server **600** is selected to process the call request. The call server **600** may include a call director **700** operable to determine whether the call request is authorized. In **1706**, a call handler **800** is launched upon determining that the call request is authorized. The call handler **800** may include a call master **802** and a call slave **804**, as described above. The call master **802** receives the call request in the non-native protocol, and the call handler **800** converts the call request to a native protocol. In **1708**, the call request is transmitted in the native protocol to a gateway **208**. The gateway **208** implements the native protocol, and is operable to forward the call request to the target device **212**. Other functionality may also be included as part of the method **1700**. For example, the method **1700** may further include selecting the gateway **208** from a plurality of gateways based on at least one gateway selection criterion. Similarly, functionality described above with respect to FIGS. **1–16** may also be implemented.

FIG. **18** is a flow diagram illustrating a method **1800** for providing packet-switched telephony service, according to another exemplary embodiment. In **1802**, a call request is received from a user device **202**. The call request may include a target identifier, such as a telephone number corresponding to a target device **212**. The call request is in accordance with a non-native protocol. In **1804**, a call server **600** is selected to process the call request. The call server **600** includes a call director **700** operable to determine whether the call request is authorized. In **1806**, the user device **202** is registered with a proxy server **1100** upon determining that the call request is authorized. The proxy server **1100** may include a registration data base **1102**, for example, to assist in determining authorization. In **1808**, a gateway **208** is selected by the proxy server **1100**. The proxy server **1100** may, for example, periodically obtain a gateway status, and may maintain a gateway database **1104**. In **1810**, a network address corresponding to the selected gateway **208** is sent to the call server **600** by the proxy server **1100**. In **1812**, the user device **202** is sent the network address of the selected gateway **208**. This information is preferably sent in a non-native protocol. In an alternative embodiment, branding information and/or advertising information may also be sent to the user device by the call server **600** at this time. In **1814**, the call request is transmitted in a native protocol to the gateway **208**, which operates according to the native protocol. The gateway **208** is operable to forward the call request to the target device **212**, such as via a Public-Switched Telephone Network (PSTN) **210**. At **1816**, the gateway **208** sends the call server **600** an acceptance of the call request, preferably in the native protocol. In **1818**, the call server **600** sends the user device **202** a call status indicator, preferably in the non-native protocol. In **1820**, a call is established between the user device **202** and the gateway **208**. This may include the gateway **208** notifying

15

the user device **202** (such as by notification message) that the call is established. The method **1800** may include additional functionality. For example, the call may be monitored by the call server **600** as in **1822**. As another example, disconnect service may be provided by detecting a disconnect indicator (such as a hang-up by the target device **212** or a similar notification by the user device **202**) and performing an appropriate disconnect action as in **1824**. Such a disconnect action may be performed by the gateway **208** or the PSTN **210** in the case of the target device **212**, or by the call server **600** in the case of the user device **202**.

FIG. **19** is a flow diagram illustrating a method **1900** for providing packet-switched telephony service, according to yet another exemplary embodiment. In **1902**, call control data is sent from a user device **202** to a PTSP **400**. The call control data may, for example, include a call request, ping information, and/or disconnect request information. The call control data is preferably included in at least one packet including a first network address specification, such as an IP address corresponding to the PTSP **400**. Such call control data may be sent by the PTSP **400** to a gateway **208** according to a protocol that is native to the gateway **208**. In **1904**, the user device **202** sends media to a gateway **208**, so that the gateway **208** may forward the media to a target device **212**. The media may include, but is not limited to, voice data. The media is preferably sent from the user device **202** to the gateway **208** according to a native protocol, and preferably consists of at least one packet including a network address specification such as an IP address corresponding to the gateway **208**.

FIG. **20** is a flow diagram illustrating a method **2000** for providing packet-switched telephony service, according to still yet another embodiment. In **2002**, call control data and media are sent from a user device **202** to a PTSP **400** according to a non-native protocol. In **2004**, the call control data and media are sent from the PTSP **400** to the gateway **208** according to a native protocol supported by the gateway **208**. The gateway **208** may be further operable to forward the media to a target device **212**. Much of the functionality described with reference to FIGS. **17–19** may also be included in the method **2000**. In addition, functionality described with reference to FIGS. **1–16** may also be implemented.

In view of the wide variety of embodiments to which the principles of the invention can be applied, it should be understood that the illustrated embodiments are exemplary only, and should not be taken as limiting the scope of the present invention. For example, more or fewer elements or components may be used in the block diagrams. In addition, the present invention can be practiced with hardware or a combination of software and hardware.

We claim:

1. A system for providing telephony service over the Internet, comprising in combination:

a call client downloadable to a user device located on the Internet, the call client communicating both media and first call-control data across the Internet according to a non-native protocol, the media including voice data, wherein the call client includes a port scan module to identify Internet Protocol ports open for communication;

a database for determining whether a user associated with the user device is authorized to communicate via a call with a second user accessible through a Public-Switched Telephone Network (PSTN);

16

a gateway located at an interface between the Internet and the PSTN, the gateway communicating according to a native protocol;

a Packet-switched Telephony Service Provider (PTSP) both the media and the first call-control data across the Internet with the call client according to the non-native protocol, the PTSP further communicating both the media and second call-control data across the Internet to the gateway according to the native protocol so that the call can be connected to the PSTN; and

a call logger associated with the PTSP and tracking calls.

2. The system of claim **1**, the PTSP including a call director and a plurality of call handlers, the call director receiving the first call-control data in the non-native protocol over the Internet from a plurality of user devices and distributing further call processing to the plurality of call handlers.

3. The system of claim **1**, further comprising:

a plurality of gateways; and

a proxy server associated with the PTSP, the proxy server receiving and distributing calls across the plurality of gateways according to one or more non-proprietary protocols, including the native protocol.

4. The system of claim **1**, the call client transmitting both the media and the first call control data in packets formatted according to the HTTP protocol.

5. The system of claim **1**, wherein the native protocol is selected from H.323, SIP, and MGCP, and wherein messages according to the non-native protocol are in a format selected from UDP, TCP, and HTTP.

6. The system of claim **1**, wherein the non-native protocol includes a set of data messages in a proprietary format, the set of data messages including a telephone number, a user device IP address, a port number, and a user identification token.

7. The system of claim **1**, wherein the call client receives an “unauthorized” message if by accessing the database, the PTSP determines that the user does not have a sufficient balance to place the call.

8. The system of claim **1**, wherein the call client accepts a selection of an address book entry corresponding to a target indicator.

9. The system of claim **1**, wherein the media format of the native protocol is in the G.711 codec.

10. The system of claim **1**, wherein the PTSP communicates both the media and the first call-control data with the call client over ports selected by the call client’s port scan module.

11. A system for providing telephony service over the Internet, comprising in combination:

a user device connected to the Internet and communicating call control information across the Internet according to a non-native protocol, wherein the non-native protocol provides information on call quality;

a gateway located at an interface between the Internet and the Public-Switched Telephone Network (PSTN), the gateway communicating media and call-control information according to a native protocol;

a proxy server receiving call control information according to the native protocol and selecting a gateway to the public switched telephone network;

a database for determining whether a user associated with the user device is authorized to communicate via a call with a second user accessible through the PSTN;

a call server connected to the Internet and communicating first call-control data across the Internet with the user device according to the non-native protocol, and also

17

communicating second call-control data across the Internet with a proxy server according to the native protocol; and

a call logger for tracking calls.

12. The system of claim **11**, wherein the non-native protocol provides information on call quality through pings between the user device and a PTSP associated with the call server.

13. The system of claim **11**, wherein the user device accepts a selection of an address book entry corresponding to a target indicator.

14. The system of claim **11**, wherein the user device communicates media with the gateway according to a native protocol that includes Real Time Protocol over User Datagram Protocol.

15. The system of claim **11**, wherein the user device transmits both the media and the first call-control data in packets formatted according to the HTTP protocol.

16. The system of claim **11**, wherein the native protocol is selected from H.323, SIP, and MGCP, and wherein messages according to the non-native protocol are in a format selected from UDP, TCP, and HTTP.

17. The system of claim **11**, wherein the non-native protocol includes a set of data messages in a proprietary format, the set of data messages including a telephone number, a user device IP address, a port number, and a user identification token.

18. A method for providing telephony service over the Internet, comprising in combination:

receiving a call request from a user device connected to the Internet, wherein the call request includes a telephone number corresponding to a PSTN subscriber, and wherein the call request is in accordance with a non-native protocol;

selecting a call server to process the call request, wherein the selected call server includes a call director to determine whether the user device has used up a maximum number of minutes;

18

launching a call handler, wherein the call handler receives the call request in the non-native protocol, wherein the call handler converts the call request to a native protocol, and wherein the native protocol is selected from H.323, SIP, and MGCP;

transmitting the call request in the native protocol to a gateway, wherein the gateway implements the native protocol, and forwards the call request to the PSTN subscriber;

communicating media between the user device and the gateway according to User Datagram Protocol; and logging information about calls so that call durations may be determined.

19. The method of claim **18**, wherein the user device executes a telephony client.

20. The method of claim **18**, wherein the user device receives an “unauthorized” message if the call director determines that the user does not have a sufficient balance to place the call.

21. The method of claim **18**, wherein the user device accepts a selection of an address book entry corresponding to a target indicator.

22. The method of claim **18**, wherein the user device transmits the call request in packets formatted according to the HTTP protocol.

23. The method of claim **18**, wherein messages according to the non-native protocol are in a format selected from UDP, TCP, and HTTP.

24. The method of claim **18**, further comprising selecting the gateway from a plurality of gateways based on at least one gateway selection criterion.

25. The method of claim **18**, wherein the user device is a device selected from the group consisting of a personal computer, a mobile phone, a wireless handheld, and a packet-switched telephone.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,145,900 B2
APPLICATION NO. : 09/872904
DATED : December 5, 2006
INVENTOR(S) : John A. Nix et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In claim 1, Column 16, line 4, please add -- communicating -- after the word (PTSP).

Signed and Sealed this

Fifteenth Day of April, 2008

A handwritten signature in black ink, reading "Jon W. Dudas". The signature is stylized, with a large, looped initial "J" and a cursive "Dudas".

JON W. DUDAS
Director of the United States Patent and Trademark Office