



US 20060058594A1

(19) **United States**(12) **Patent Application Publication****Ishizuka et al.**(10) **Pub. No.: US 2006/0058594 A1**(43) **Pub. Date: Mar. 16, 2006**(54) **MEASURING PROBE AND LIVING BODY
OPTICAL MEASURING DEVICE**(76) Inventors: **Takashi Ishizuka**, Kitasoma-gun (JP);
Michiyuki Fujiwara, Chiba (JP)Correspondence Address:
**ANTONELLI, TERRY, STOUT & KRAUS,
LLP
1300 NORTH SEVENTEENTH STREET
SUITE 1800
ARLINGTON, VA 22209-3873 (US)**(21) Appl. No.: **10/538,236**(22) PCT Filed: **Dec. 11, 2003**(86) PCT No.: **PCT/JP03/15880**(30) **Foreign Application Priority Data**

Dec. 12, 2002 (JP) 2002-360220

Jul. 18, 2003 (JP) 2003-276767

Publication Classification(51) **Int. Cl.****A61B 5/00** (2006.01)(52) **U.S. Cl.** **600/310**

(57)

ABSTRACT

In a measuring probe, the distal ends of an irradiation optical fiber and a detection optical fiber on the subject side are held by a holder portion which is to be mounted on a subject. The optical fibers are led out from the side surface of the holder portion. Further, the optical fibers are bent in the holder portion so that the distal ends of the optical fibers are directed towards the subject when the holder portion is mounted on the subject.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 15




FIG. 14




FIG. 16





FIG. 17



MEASURING PROBE AND LIVING BODY OPTICAL MEASURING DEVICE

TECHNICAL FIELD

[0001] The present invention relates to a measuring probe adapted to irradiate a subject with measurement light and receive light transmitted through the subject (living body passing light), and to a living body optical measuring device having the measuring probe.

BACKGROUND ART

[0002] As disclosed, for example, in JP 9-98972 A, a conventional living body optical measuring device has a measuring probe attached to a subject and a device main body connected to the measuring probe. The measuring probe has an irradiation optical fiber for irradiating the subject with measurement light generated in the device main body, a detection optical fiber for receiving the measurement light transmitted through the subject, that is, a living body passing light, and guiding it to the device main body; a fixing member for securing the distal end portions of the irradiation and detection optical fibers at predetermined positions of the subject; and a fixation belt for securing the fixing member to the subject.

[0003] However, in the case, for example, of the measurement of a newborn baby or a measurement of long duration, it is necessary to perform, apart from a measurement in a seated position or a standing position, measurement in which the subject lies down, and there is demand for a measuring probe allowing such measurement. That is, there is demand for a measuring probe which can be attached to the subject without damaging the optical fibers even when the subject lies down.

DISCLOSURE OF THE INVENTION

[0004] The present invention has been made with a view toward solving the above problem. It is accordingly an object of the present invention to provide a measuring probe and a living body optical measuring device which allow measurement with a subject lied down.

[0005] To this end, according to one aspect of the present invention, there is provided a measuring probe comprising: a holder portion attached to a subject; and an optical fiber for at least one of irradiation and detection whose distal end portion on a subject side is retained by the holder portion, wherein the optical fiber is led out from a side surface of the holder portion and is bent inside the holder portion such that the distal end portion is directed to the subject when the holder portion is attached to the subject.

[0006] According to another aspect of the present invention, there is provided a living body optical measuring device comprising a measuring probe having a plurality of optical fibers that irradiate a subject with measurement light and receive the measurement light returning from the subject, the measuring probe being attached to the subject, wherein the optical fibers are led out from a side surface of the measuring probe and are bent inside the measuring probe portion such that their distal end portions are directed towards the subject when the measuring probe is attached to the subject.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIG. 1 is a plan view of a measuring probe according to Embodiment 1 of the present invention;

[0008] FIG. 2 is sectional view of a holder portion of FIG. 1;

[0009] FIG. 3 is a plan view of FIG. 2 with a holder cover removed;

[0010] FIG. 4 is a plan view of a holder base of FIG. 2;

[0011] FIG. 5 is a side view of the holder base of FIG. 4;

[0012] FIG. 6 is a sectional view taken along the line VI-VI of FIG. 4;

[0013] FIG. 7 is a bottom view of the holder base of FIG. 4;

[0014] FIG. 8 is a sectional view of the holder cover of FIG. 2;

[0015] FIG. 9 is a bottom view of the holder cover of FIG. 7;

[0016] FIG. 10 is a block diagram schematically showing the construction of a living body optical measuring device including the measuring probe of FIG. 1;

[0017] FIG. 11 is a front view of a measuring probe according to Embodiment 2 of the present invention;

[0018] FIG. 12 is a sectional view taken along the line XII-XII of FIG. 11;

[0019] FIG. 13 is a perspective view of the measuring probe of FIG. 11 with the holder cover removed therefrom;

[0020] FIG. 14 is a perspective view of the holder portion of FIG. 11 as attached to a subject;

[0021] FIG. 15 is a perspective view of the holder portion of FIG. 14 with a fastening fixing member attached thereto from above;

[0022] FIG. 16 is a plan view of a measuring probe according to Embodiment 3 of the present invention; and

[0023] FIG. 17 is a plan view of a measuring probe according to Embodiment 4 of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

[0024] In the following, preferred embodiments of the present invention will be described with reference to the drawings.

EMBODIMENT 1

[0025] FIG. 1 is a plan view of a measuring probe according to Embodiment 1 of the present invention. In the drawing, the measuring probe of this embodiment has a probe main body 101 to be attached to a subject, a plurality of irradiation optical fibers 102 for guiding irradiation light from the main body of a measuring device to the probe main body 101, and a plurality of detection optical fibers 103 for guiding living body passing light from the subject to the main body of the measuring device.

[0026] Unlike the conventional measuring probes, the measuring probe of this embodiment has the irradiation and detection optical fibers 102 and 103 attached in advance to the probe main body 101. Thus, by attaching the probe main body 101 to the subject, the irradiation and detection optical fibers 102 and 103 are respectively arranged at desired

measurement positions. That is, by placing the probe main body **101** on the head of the subject, the irradiation and detection optical fibers **102** and **103** are respectively arranged at desired measurement positions.

[0027] One end (distal end) of each of the irradiation and detection optical fibers **102** and **103** is retained perpendicular to the surface of the subject with which the probe main body **101** is brought into contact. Also, the irradiation and detection optical fibers **102** and **103** are drawn out of a side surface of the probe main body **101**. The other end of each of the irradiation and detection optical fibers **102** and **103** is connected to the measuring device main body.

[0028] The probe main body **101** has three holder portions **104**. In each holder portion **104**, three optical fiber head portions (including an irradiation bed portion and a detection bed portion) are provided at equal intervals. The holder portions **104** are connected together at predetermined intervals by connecting portions **105**. As a result, the intervals between the holder portions **104** are maintained, and the measuring probe as a whole is reduced in weight and thickness.

[0029] Further, in order that the attachment position of the measuring probe is not shifted even if the subject moves in a horizontal position, such as a prone position, a fixing means (not shown), such as a belt, for securing the measuring probe to the head may be connected to the probe main body **101**.

[0030] Next, FIG. 2 is a sectional view of the holder portion **104** of FIG. 1, FIG. 3 is a plan view of FIG. 2 with a holder cover removed, FIG. 4 is a plan view of a holder base shown in FIG. 2, FIG. 5 is a side view of the holder base of FIG. 4, FIG. 6 is a sectional view taken along the line VI-VI of FIG. 4, FIG. 7 is a bottom view of the holder base of FIG. 4, FIG. 8 is a sectional cover of the holder cover of FIG. 2, and FIG. 9 is a bottom view of the holder cover of FIG. 7.

[0031] In the drawings, placed on a holder base **201** constituting a first member is a holder cover **202** constituting a second member. The holder base **201** is arranged on the side to be brought into contact with the subject, and the holder cover **202** is arranged on the side not to be brought into contact with the subject. The holder base **201** is formed of a material more flexible than that of the holder cover **202**. The holder cover **202** is formed of a material more rigid than that of the holder base **201**.

[0032] Between the holder base **201** and the holder cover **202**, there are retained three optical fibers **102** and **103**. A plurality of mutually independent optical fiber arranging grooves (protecting grooves) **207** in which the optical fibers **102** and **103** are accommodated are provided in the holder base **201**. Further, the optical fibers **102** and **103** are introduced into the holder portion **104** through a side surface of the holder portion **104**, and extend within the holder portion **104** in the direction in which the holder portion **104** extends, with their distal end portions being bent substantially at right angles.

[0033] Inside the holder portion **104**, there are provided a plurality of optical fiber fixing members **203** for securing the distal ends of the optical fibers **102** and **103**, a plurality of optical fiber protecting members **204** for protecting the bent portions of the optical fibers **102** and **103**, and a plurality of

height adjustment jigs **205** for adjusting the amount by which the optical fibers **102** and **103** protrude from the holder base **201**.

[0034] The optical fiber fixing members **203** retain the optical fibers **102** and **103** such that the distal end portions of the optical fibers **102** and **103** are arranged at the measurement positions of the subject. Further, the optical fiber fixing members **203** have built-in spring mechanisms (not shown) which retain the optical fibers **102** and **103** and extrude them by a minute amount from the surface of the holder base **201**.

[0035] The optical fibers **102** and **103** are arranged so as to avoid the optical fiber fixing members **203** for the other optical fibers **102** and **103**. For example, the optical fiber **103** arranged at a position nearest to the introducing portion for the optical fibers **102** and **103** passes a side near a first protrusion **402a** (described below) for fixing together the holder base **201** and the holder cover **202**, and is bent vertically by the optical fiber protecting member **204** before being retained by the optical fiber fixing member **203**. The optical fiber **102** arranged at the intermediate position passes the outer side of the optical fiber **103** closest to the introducing portion, and, after being vertically bent by the optical fiber protecting member **204**, is retained by the optical fiber fixing member **203**. Further, the optical fiber **103** arranged at the position farthest from the introducing portion of the above optical fibers **102** and **103** passes the side opposite to the above-mentioned two optical fibers **102** and **103** with respect to the first protrusion **402a**, and is bent vertically by the optical fiber protecting member **204** before being retained by the optical fiber fixing member **203**.

[0036] The above arrangement of the optical fibers **102** and **103** are effected by inserting the optical fibers **102** and **103** into the optical fiber arrangement grooves **207**. In this process, in order to make the bending rate when bending the optical fibers **102** and **103** while protecting them by means of the optical fiber protecting members **204** as low as possible, the outer peripheral coatings of the optical fibers **102** and **103** are removed, and the core portions of the optical fibers **102** and **103** are arranged in the optical fiber arrangement grooves **207**.

[0037] In the mating surface of the holder base **201** (the surface mated with the holder cover **202**), there are provided three recesses **401** with a circular section. At the bottom of each recess **401**, there is provided a through-hole **402** leading to the subject side. The distal end portions of the optical fibers **102** and **103** are protruded slightly out of the holder base **201** through the through-holes **402**.

[0038] The recesses **401** and the through-holes **402** are arranged coaxially. The diameter of the recesses **401** is larger than the diameter of the through-holes **402**. As a result, step portions are formed at the bottom of the recesses **401**. Further, the diameter of the recesses **401** is the same size as the outer peripheral diameter of the height adjustment jigs **205** and of the optical fiber fixing members **203**. The height adjustment jigs **205** and the optical fiber fixation jigs **203** are inserted into the recesses **401**.

[0039] Further, the holder base **201** has a plurality of annular protrusions **403** protruding so as to surround the distal end portions of the optical fibers **102** and **103** exposed from the holder base **201**. By adjusting the amount by which

the optical fibers **102** and **103** protrude with respect to the annular protrusions **403** by the height adjustment jigs **205**, it is possible to adjust the pressurizing force with which the distal end portions of the optical fibers **102** and **103** abut the subject. Further, due to the annular protrusions **403**, external light is prevented from entering the optical fibers **102** and **103** during measurement.

[0040] Further, the annular protrusions **403** are formed independently of each other and arranged so as to be spaced apart from each other. As a result, when the measuring probe is arranged on the subject, deformation of the holder portion **104** is allowed such that the annular protrusions **403** are in conformity with the measurement region (abutment region). As a result, it is possible for the optical fibers **102** and **103** to abut the subject at right angles or substantially at right angles. Further, due to the deformation in conformity with the configuration of the measurement region, external light is more reliably prevented from entering the optical fibers **102** and **103** during measurement.

[0041] While in this example the external configuration of the annular protrusion **403** formed at the center is circular, and the external configuration of the annular protrusion **403** arranged on either side thereof is elliptical, the configurations of the annular protrusions **403** are not restricted thereto.

[0042] The height adjustment jigs **205** prevent excessive burden on the optical fibers **102** and **103** when the moving amount of the optical fibers **102** and **103** at the time of attachment of the measuring probe to the subject exceeds the deformable range of the built-in spring mechanisms of the optical fiber fixing members **203**. This helps to prevent the optical fibers **102** and **103** from being damaged.

[0043] At the longitudinal ends of the holder base **201**, there are formed relatively large first protrusions **402a**. Further, between (in the interval) of the recesses **401** adjacent to each other, there are formed second protrusions **402b** whose section diameter and protruding amount are smaller than those of the first protrusions **402a**.

[0044] In the mating surface of the holder cover **202** facing the holder base **201**, there are formed a plurality of accommodating portions **404**, which are recesses opposed to the recesses **401**. The recesses **401** and the accommodating portions **404** define spaces for accommodating the bent portions of the optical fibers **102** and **103**. The accommodating portions **404** accommodate the bent portions of the optical fibers **102** and **103**, the optical fiber fixing members **203**, and the optical fiber protecting members **204**. The size of the accommodating portions **404** is set so as to be minimum within the range not involving damage due to the bending of the optical fibers **102** and **103**.

[0045] Further, the movement of the optical fibers **102** and **103** due to the movement of the distal end portions of the optical fibers **102** and **103** when attaching the measuring probe to the subject is absorbed by the bent portions accommodated in the accommodating portions **404**. As a result, the burden on the optical fibers **102** and **103** is substantially reduced, thereby preventing the optical fibers **102** and **103** from being damaged.

[0046] Further, the inner peripheral surfaces of the accommodating portions **404** are formed in the same size and configuration as the outer peripheral surfaces of the optical

fiber fixing members **203**. That is, the accommodating portions **404** also serve as retaining means for retaining the optical fiber fixing members **203**. As a result, when the measuring probe is attached to the subject, positional deviation of the optical fiber fixing members **203** is prevented, making it possible to obtain more accurate measurement results.

[0047] In order to make the holder cover **202** as thin as possible and to ensure a sufficient strength, protrusions are formed in those portions of the surface thereof on the opposite side of the mating surface (the portion coming into contact with a bed, etc. at the time of measurement) in which the accommodating portions **404** are formed.

[0048] In the holder cover **202**, there are formed a plurality of grooves **405** through which part of the bent optical fibers **102** and **103** pass. The grooves **405** extend from the accommodating portions **404** in the same direction as the optical fiber arrangement grooves **207**. The optical fibers **102** and **103** are partially retained in the grooves **405**, whereby the optical fibers **102** and **103** are bent in minimum spaces, and the burden on the optical fibers **102** and **103** is minimized.

[0049] Further, in the holder cover **202**, there are formed two insertion holes **406a** into which the first protrusions **402a** are inserted, and two joining recesses **406b** into which the second protrusions **402b** are fitted. By inserting the first protrusions **402a** into the insertion holes **406a** and by fitting the second protrusions **402b** into the joining recesses **406b**, the holder base **201** and the holder cover **202** are combined with each other. Further, the holder cover **202** is fixed to the holder base **201** by screws or the like.

[0050] Next, FIG. 10 is a block diagram schematically showing the construction of a living body optical measuring device including the measuring probe of FIG. 1. In the drawing, the living body optical measuring device has a probe main body **101**, a light source portion **501**, an oscillating portion **503**, a plurality of photo diodes **511**, a lock-in amplifier module **512**, an A/D converter **516**, a control portion **517**, an input/output portion **502**, and an image producing portion **521**.

[0051] The light source portion **501** has a plurality of (for example, four, as in this case) optical modules **502**. Each optical module **502** has two semiconductor lasers (not shown) respectively emitting lights of a plurality of wavelengths from the visible to the infrared wavelength region, for example, dual wavelengths of 780 nm and 830 nm.

[0052] All the semiconductor lasers included in the light source **501** are modulated by the oscillating portion **503** composed of oscillators of different oscillation frequencies. That is, in the oscillating portion **503**, the semiconductor lasers are analog-modulated by a sine wave. Further, each of the optical modules **502** is equipped with an optical fiber connector (not shown) introducing the lights of the wavelengths of 780 nm and 830 nm emitted from the semiconductor lasers into a single irradiation optical fiber **102**.

[0053] Thus, the light consisting of a mixture of lights of two wavelengths emitted from the light source portion **501** is applied to the subject constituting the object of irradiation from the distal end portions of a plurality of irradiation optical fibers **102** connected to each of the optical modules **502**. At this time, the irradiation optical fibers **102** are secured in position at the probe main body **101** as stated

above, and apply light to different positions. For example, the distal end portions of the irradiation optical fibers **102** and the detection optical fibers **103** are arranged alternately in a tetragonal-lattice-like fashion inside the probe main body **101**.

[0054] The living body passing light (the light transmitted through a light scattering reflective body) returning from the subject is detected through a plurality of (for example, five) detection optical fibers **103** arranged in the probe main body **101** by photo diodes (photo detectors) **511** connected to the other ends of the detection optical fibers **103**. As the photo diodes **511**, it is desirable to adopt well-known avalanche photo diodes which allow high sensitivity optical measurement.

[0055] The living body passing light is converted to electric signals (living body passing light intensity signals) by the photo diodes **511**. Thereafter, a modulation signal corresponding to the irradiating position and wavelength is selectively detected by a modulation signal selective detection circuit, for example, a lock-in amplifier module **512** composed of a plurality of lock-in amplifiers (not shown).

[0056] At this time, the modulation signals output from the lock-in amplifier module **512** are ones respectively separated into living body passing light intensity signals corresponding to the wavelengths and irradiating positions. In the lock-in amplifier module **512**, there are used the same number of lock-in amplifiers (not shown) as the number of signals to be measured (for example, **24**).

[0057] The living body passing light intensity signals analog-output from the lock-in amplifier module **512** are respectively converted to digital signals by an A/D converter (analog/digital converter) **516** of a plurality of (for example, **24**) channels. The digital signals are living body passing light intensity signals respectively corresponding to the wavelengths and irradiating positions.

[0058] The light source portion **501**, the oscillating portion **503**, the lock-in amplifier module **512**, and the A/D converter **516** are controlled by a control portion **517**.

[0059] The living body passing light intensity signals converted to digital signals are recorded in a storage portion **518** provided in the image producing portion **521**. The living body passing light intensity signals recorded in the storage portion **518** are read at a processing portion **519** which is also provided in the image producing portion **521**. In the case of an ordinary living body optical measurement, the processing portion **519** computes changes in oxygenated hemoglobin concentration and changes in de-oxygenated hemoglobin concentration accompanying brain activity, and hemoglobin concentration total amount, based on the living body passing light intensity signals of the detecting positions. The computation results are displayed on a display screen (not shown) of the input/output portion **520** as age-based information on a plurality of measurement positions. The age-based information is stored in the storage portion **518**. The method of computation by the processing portion **519** is well known in the art, so a detailed description thereof will be omitted.

[0060] In the living body passing light measuring device constructed as described above, the tip portions of the irradiation and detection optical fibers **102** and **103** are introduced into the probe main body **101**, and are bent inside

the probe main body **101** so as to be perpendicular to the skin of the subject. Thus, even when the subject is in a prone position, it is possible to perform living body optical measurement without damaging the measuring probe (in particular, the irradiation and detection optical fibers **102** and **103**).

[0061] As a result, it is also possible to perform a living body optical measurement which takes so long as to necessitate the subject to take a rest, such as sleep, which has been difficult in a living body optical measurement using a conventional measuring probe. Thus, it is possible to accurately identify the position of a hypnic epileptic focus or the like, which has conventionally been difficult to identify, making it possible to achieve a substantial improvement in terms of therapeutic performance.

[0062] Further, since only the core portions of the optical fibers **102** and **103** are accommodated in the holder portion **104**, it is possible to bend the optical fibers **102** and **103** at a smaller radius, making it possible to reduce the thickness of the holder portion **104**. As a result, it is possible to further reduce the burden on the subject when performing measurement with the subject lied down.

[0063] Further, since the holder base **201** is formed of a material more flexible than that of the holder cover **202**, it is possible to further reduce the burden on the subject at the time of attachment.

[0064] The number of holder portions **104** is not restricted to three but may be any other number.

[0065] Further, the number of optical fibers arranged in one holder portion **104** is not restricted to three, either, but may be any other number.

[0066] Further, the routing of the optical fibers **102** and **103** in the holder portion **104** is not restricted to the above-described one.

[0067] Furthermore, while in this embodiment the annular protrusions **403** are formed so as to protrude from the holder base **201**, this should not be construed restrictively; for example, it is also possible to form the annular recesses **403** by forming recesses extending in the minor axis direction of the holder base **201**.

[0068] The values of the wavelengths of the lights emitted from the optical modules **502** are not restricted to 780 nm and 830 nm. Further, the number of wavelengths is not restricted to two, either.

[0069] Further, while in the above example a semiconductor laser is used as the light source, this should not be construed restrictively; for example, it is also possible to use a light emitting diode.

[0070] Furthermore, the method of modulation at the oscillating portion **503** is not restricted to the analog modulation by sine wave; it may also be, for example, a digital modulation using rectangular waves of different time intervals. When thus using digital modulation, a digital filter or a digital signal processor is used as a modulated signal detecting means.

[0071] Further, the photo detectors are not restricted to photo diodes; it is also possible to use other photoelectric conversion devices, such as photomultiplier tubes, as long as they are photoelectric conversion devices.

EMBODIMENT 2

[0072] Next, FIG. 11 is a front view of a measuring probe according to Embodiment 2 of the present invention, FIG. 12 is a sectional view taken along the line XII-XII of FIG. 11, and FIG. 13 is a perspective view of the measuring probe of FIG. 11 with the holder cover removed therefrom.

[0073] In Embodiment 2, in order to match the holder portion 104 with the head configuration of the subject, a base plate 601 as a curving means is bonded to the holder portion 104. The construction of the holder portion 104 is the same as that of Embodiment 1. The base plate 601 is formed of a hard material, such as plastic. Thus, the holder portion 104 is reinforced by the base plate 601.

[0074] The base plate 601 is curved in advance. The curvature of the base plate 601 is matched with the head configuration of the subject in advance. The holder portion 104 is maintained in a configuration corresponding to the curved configuration of the base plate 601. Further, the base plate 601 is constructed so as not to interfere with the annular protrusions 403 and the distal end portions of the optical fibers 102 and 103.

[0075] By using the base plate 601 described above, it is possible to secure the holder portion 104 in position in a state in which the holder portion 104 is in close contact with the head of the subject. Thus, there is no fear of any undesired gap being generated between the head of the subject and the holder portion 104, making it possible to achieve an improvement in terms of measurement sensitivity.

[0076] Further, although not shown, it is also possible to provide rails on the subject side of the holder portion 104, holding the base plate 601 between the rails. This makes it possible to replace the base plate 601 and to combine the relatively soft holder portion 104 with base plates 601 of various configurations, making it possible to modify and attach the holder portion 104 in an optimum manner in conformity with various subject head configurations.

[0077] FIG. 14 is a perspective view of the holder portions 104 of FIG. 11 as attached to the subject, and FIG. 15 is a perspective view of the holder portions 104 of FIG. 14 with a fastening fixing member 701 attached from above.

[0078] The holder portions 104 are combined with base plates 601 of configurations corresponding to their respective attachment positions. This makes it possible for the holder portions 104 to be fixed in an optimum conformity with the head, which exhibits a fine variation in configuration from position to position.

[0079] Further, by attaching the tube-shaped fastening fixing member 701 surrounding the subject, it is possible to prevent the holder portions 104 from being detached, and to hold the holder portions 104 in close contact with the subject. As the material of the fastening fixing member 701, it is possible to use an elastic cloth, a ring-like balloon adapted to expand through injection of air, etc.

[0080] The base plates 601 are equipped with connecting portions 602 for the connection of the adjacent base plates 601. The connecting portions 602 may be, for example, of the type in which protrusions and holes are joined with each other or of the type in which attachment is effected by using magnets. This helps to prevent the individual holder portions 104 from being detached.

[0081] Further, a connection hole 603 is provided at an end of each base plate 601. It is possible to connect a chin strap or belt (not shown) for the subject to the connection hole 603 as needed.

[0082] While in Embodiment 2 the base plate 601 and the holder base 201 are separate from each other, it is also possible to mold the base plate 601 and the holder base 201 integrally with each other.

[0083] Further, the base plate may be formed of a material which allows free manual curving and maintenance of the curved state. This makes it possible to perform attachment with the holder portions deformed in an optimum fashion in conformity with various subject head configurations without having to replace the base plates. In this case, the holder portions are formed of a material more flexible than that of the base plates, and are curved in conformity with the curving of the base plates without hindering the maintenance of the curved state of the base plates.

EMBODIMENT 3

[0084] Next, FIG. 16 is a plan view of a measuring probe according to Embodiment 3 of the present invention. While in Embodiment 1 a plurality of holder portions 104 are connected by the connecting portions 105, in Embodiment 3, a plurality of holder portions 104 are previously formed into an integral unit. In this case, at least either the holder bases 201 or the holder covers 202 adopt an integral structure.

[0085] Due to this construction, it is possible to achieve a reduction in the number of parts, and to more reliably prevent mutual positional deviation of the holder portions 104.

EMBODIMENT 4

[0086] Next, FIG. 17 is a plan view of a measuring probe according to Embodiment 4 of the present invention. In this embodiment, the measuring probe as a whole is formed such that the distal end portions of the irradiation optical fibers 102 and the distal end portions of the detection optical fibers 103 are arranged alternately in both the longitudinal direction of the holder portions 104 (the horizontal direction in FIG. 17) and the direction perpendicular to the longitudinal direction of the holder portions 104. Further, a fixed distance is maintained between the adjacent holder portions 104 by the connecting portions 105.

[0087] In the measuring probe described above, the distal end portions of the optical fibers 102 and 103 are arranged in a tetragonal-lattice-like fashion, and the distal end portions of the irradiation optical fibers 102 and the distal end portions of the detection optical fibers 103 are arranged alternately in both of the two directions perpendicular to each other, whereby it is possible to realize a more effective measurement.

1. A measuring probe comprising:

a holder portion attached to a subject; and

an optical fiber for at least one of irradiation and detection whose distal end portion on a subject side is retained by the holder portion,

wherein the optical fiber is led out from a side surface of the holder portion and is bent inside the holder portion

such that the distal end portion is directed to the subject when the holder portion is attached to the subject.

2. A measuring probe according to claim 1, wherein an outer peripheral coating is removed from a bent portion of the optical fiber inside the holder portion.

3. A measuring probe according to claim 1, wherein the holder portion has a first member to be brought into contact with the subject and a second member combined with the first member.

4. A measuring probe according to claim 3, wherein the first member is more flexible than the second member, and wherein the second member is more rigid than the first member.

5. A measuring probe according to claim 3, wherein a protecting groove into which the optical fiber is inserted is formed in at least one of the first member and the second member.

6. A measuring probe according to claim 1, wherein the holder portion is provided with a through-hole through which the distal end portion of the optical fiber is exposed and an annular protrusion protruding so as to surround the distal end portion of the optical fiber.

7. A measuring probe according to claim 1, wherein a space portion for accommodating the bent portion of the optical fiber is provided inside the holder portion.

8. A measuring probe according to claim 7, wherein the holder portion has a first member to be brought into contact with the subject and a second member combined with the first member, and wherein the space portion is formed by combining recesses respectively provided in the first and second members.

9. A measuring probe according to claim 1, wherein an optical fiber fixing member for fixing the distal end portion of the optical fiber is arranged in the holder portion.

10. A measuring probe according to claim 9, wherein a space portion for accommodating the bent portion of the optical fiber and the optical fiber fixing member is provided in the holder portion, and wherein a diameter of the space portion is of the same size as an outer peripheral diameter of the optical fiber fixing member.

11. A measuring probe according to claim 8, wherein the optical fiber fixing member has a spring mechanism which extrudes the optical fiber by a minute amount to an exterior of the holder portion while retaining the optical fiber.

12. A measuring probe according to claim 1, wherein an optical fiber protecting member for protecting the bent portion of the optical fiber is arranged inside the holder portion.

13. A measuring probe according to claim 1, wherein a height adjustment jig for adjusting an amount by which the optical fiber protrudes from the holder portion is arranged inside the holder portion.

14. A measuring probe according to claim 1, further comprising a curving means provided on the holder portion, for maintaining the holder portion in a configuration curved along the subject.

15. A measuring probe according to Claim 14, wherein the curving means is mounted to the subject side of the holder portion and is a base plate curved in advance.

16. A measuring probe according to Claim 14, wherein the curving means is replaceable with respect to the holder portion.

17. A measuring probe according to Claim 14, wherein the curving means is provided with a connecting portion for connection with an adjacent curving means.

18. A living body optical measuring device comprising a measuring probe having a plurality of optical fibers that irradiate a subject with measurement light and receive the measurement light returning from the subject, the measuring probe being attached to the subject,

wherein the optical fibers are led out from a side surface of the measuring probe and are bent inside the measuring probe portion such that their distal end portions are directed towards the subject when the measuring probe is attached to the subject.

19. A living body optical measuring device according to claim 18, wherein the measuring probe has a plurality of holder portions,

wherein, in each of the holder portions, the distal end portions of the plurality of optical fibers are arranged at intervals, and

wherein the optical fibers are led out from a side surface of the holder portion.

20. A living body optical measuring device according to claim 18, further comprising a fastening fixing member which is put on the subject from above the measuring probe so as to surround the subject and which prevents the measuring probe from being detached from the subject.

* * * * *