US006736526B2

(12) **United States Patent**
Matsuba et al.

(10) **Patent No.: US 6,736,526 B2**
(45) **Date of Patent: May 18, 2004**

(54) **BULB-TYPE LAMP AND MANUFACTURING METHOD FOR THE BULB-TYPE LAMP**

(75) Inventors: **Tetsuo Matsuba**, Neyagawa (JP); **Yoshinori Kakuno**, Katano (JP)

(73) Assignee: **Matsushita Electric Industrial Co., Ltd.**, Osaka-Fu (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/100,707**

(22) Filed: **Mar. 19, 2002**

(65) **Prior Publication Data**

US 2002/0141190 A1 Oct. 3, 2002

(30) **Foreign Application Priority Data**

Mar. 27, 2001 (JP) 2001-089489

(51) **Int. Cl.**[7] **F21K 27/00**
(52) **U.S. Cl.** **362/260**; 362/373; 362/294; 313/318.02; 313/634; 315/56
(58) **Field of Search** 362/294, 373, 362/260, 26, 261, 186; 313/493, 634, 318.02; 315/56, 58

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,504,666	A	*	4/1996	Carmichael	362/294
5,545,950	A	*	8/1996	Cho	315/56
5,828,170	A	*	10/1998	Nishio et al.	313/493
5,844,357	A	*	12/1998	Iida et al.	313/493
6,153,972	A	*	11/2000	Katougi et al.	313/493
6,172,452	B1	*	1/2001	Itaya et al.	313/490
6,492,773	B2	*	12/2002	Gyoten et al.	315/56

FOREIGN PATENT DOCUMENTS

EP	704101	9/1999
JP	6196000	7/1994
JP	8511650	12/1996

* cited by examiner

Primary Examiner—John Anthony Ward

(57) **ABSTRACT**

To provide a bulb-type lamp in which a globe is fixed to a case without a tilt, and a manufacturing method for the bulb-type lamp. The globe is bonded to a connector using a thermosetting resin, in a state where a neck part of the globe is inserted in a groove of the connector without contacting the bottom of the groove. The connector is then fixed to the case by means of a fitting construction. This makes it unnecessary to perform a heating process to cure an adhesive after an envelope is formed by the globe and the case. Hence the tilting of the globe caused by the thermal expansion of air in the envelope can be prevented.

17 Claims, 10 Drawing Sheets




FIG.1




FIG.2



10
1
10a
10c
10b
113
11
113
115
31
30
302
3
300
301
302
32
200
201
20
2
21

FIG.3




FIG.4




FIG.5A




FIG.5B




FIG.5C




FIG.5D




FIG.6




FIG.7




FIG.8




FIG.9





FIG.10

PRIOR ART



BULB-TYPE LAMP AND MANUFACTURING METHOD FOR THE BULB-TYPE LAMP

This application is based on an application Ser. No. 2001-089489 filed in Japan, the content of which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a bulb-type lamp having a globe, such as a bulb-type fluorescent lamp and an electrodeless discharge lamp, and a manufacturing method for the bulb-type lamp.

2. Related Art

A bulb-type lamp is a kind of lamp in which a spherical globe, like the one used in an incandescent lamp, is fixed to a case. Examples of such a bulb-type lamp include bulb-type fluorescent lamps and electrodeless discharge lamps. The globe is usually made of glass in consideration of the heat generated in the lamp. Also, the globe is fixed to the case using an adhesive made of a thermosetting resin, such as a silicon resin, which has excellent heat resistance and sealing ability.

The following explains a construction of a bulb-type lamp and a method of fixing a globe to a case, taking a bulb-type fluorescent lamp as an example.

FIG. **10** is a partial broken front view of a conventional bulb-type fluorescent lamp.

This bulb-type fluorescent lamp has a globe **900**, a case **910**, an arc tube **920**, and a holder **930**. The globe **900** is made of glass and has one end opened. The case **910** is made of a resin and is engaged with the open end of the globe **900**. The arc tube **920** is made up of three U-shaped fluorescent tubes which are bridge-connected. The holder **930** is made of a resin, and is housed in an envelope formed by the globe **900** and case **910**. The holder **930** holds the arc tube **920** on one surface and an electric ballast **931** for illuminating the arc tube **920** on the other surface, and is fixed into an opening of the case **910**.

Here, a groove **940** is formed between the case **910** and the holder **930**, along the periphery of the case **910**. An edge part **900***a* of the globe **900** is inserted in this groove **940** and bonded to the case **910** through a thermosetting adhesive **941**.

Such a bulb-type fluorescent lamp can be manufactured as follows. First, the arc tube **920** and the electric ballast **931** are attached to the holder **930**. The holder **930** is then inserted into the case **910** with the electric ballast **931** being inserted first. Hence the electric ballast **931** is housed in the case **910**. Following this, the thermosetting adhesive **941** is injected into the groove **940** formed between the case **910** and the holder **930**, and the edge part **900***a* of the globe **900** is inserted into the groove **940**. The construction is then placed in a heating furnace and heated therein, to cure the thermosetting adhesive **941**. As a result, the globe **900** is fixed to the case **910** through the adhesive **941**.

With this manufacturing method, however, the globe **900** may be fixed to the case **910** in a tilted position. This causes a failure of holding the globe **900** in a correct position.

Prior to the heating process in the heating furnace, the globe **900** and the case **910** are substantially in tight contact with each other through the adhesive **941** and so the envelope formed by the globe **900** and case **910** is hermetically sealed. When the bulb-type fluorescent lamp in this state is heated in the heating furnace, the air in the envelope expands and the internal pressure increases. This being so, if the adhesive **941** is not hardened yet but is still soft, the internal pressure of the envelope may cause the globe **900** to be pushed up or tilted. If the adhesive **941** hardens in such a state, the globe **900** will end up being fixed to the case **910** in a tilted position (in more detail, the edge part **900***a* of the globe **900** is tilted upward on one side by about 4 mm). As a result, the globe **900** cannot be held in a correct position.

Bulb-type fluorescent lamps with tilted globes are all abandoned without being reused, because of their defective external appearances. Since these products are almost in finished form, they are costly and so abandoning them inevitably increases manufacturing costs.

To avoid the tilting of the globe, the following method may be employed instead of using a thermosetting resin as above. Which is to say, a stopper is provided to the edge part of the globe, whereas a stopper holding part is provided to the case. By engaging the stopper with the stopper holding part, the globe can be secured to the case. However, because the globe is made of glass, the stopper of the globe is not only difficult to form but also likely to break when engaged with the stopper holding part. For this reason, this type of bulb-type fluorescent lamp is not very practical.

The same problem can be found in electrodeless discharge lamps that have a construction similar to bulb-type fluorescent lamps, namely, a construction in which a globe is fixed to a case.

SUMMARY OF THE INVENTION

The present invention has an object of providing a bulb-type lamp that holds a globe in a correct position and so delivers an improved external appearance, and a manufacturing method for the bulb-type lamp.

The stated object can be achieved by a bulb-type lamp including: a globe having a constricted neck part at one end; a connector having a ring-shaped groove in which the neck part of the globe can be inserted, wherein the globe is bonded to the connector in a state where the neck part is inserted in the groove; a holder having a stand that supports an electric ballast; and a case having an opening, and holding the holder in a state where the holder is inserted in the case through the opening with the electric ballast being inserted first, wherein in the opening of the case, the connector to which the globe is bonded is fixed to one of the case and the holder by a fitting construction.

With this construction, the globe is held in place just by engaging the connector, to which the globe is bonded, with the case or the holder. This eliminates the need for the heating process which is conventionally performed after the envelope is formed by the globe and case. Accordingly, the tilting of the globe caused by the expansion of air in the envelope is prevented, with it being possible to hold the globe without a tilt relative to the case. As a result, the external appearance of the bulb-type lamp improves. This reduces the number of defective products, so that increases of manufacturing costs caused by abandoning defective products can be suppressed.

Here, the globe may be bonded to the connector in a state where the neck part which is inserted in the groove is kept from contact with a bottom of the groove.

With this construction, the tilting of the globe can be prevented more efficiently.

Here, the fitting construction may include a depression and a projection that fit together, the depression and the projection each being provided at a different one out of (a) the connector and (b) one of the case and the holder.

Here, the bulb-type lamp may be a bulb-type fluorescent lamp in which a fluorescent tube is supported by the stand of the holder, wherein the globe is a hollow spherical member having an open end at which the neck part is formed, a light diffusion film is formed on an internal surface of the globe using an adhesive, and the adhesive used for forming the light diffusion film is also used for bonding the globe to the connector.

With this construction, it becomes unnecessary to prepare another adhesive to bond the globe to the connector, since a single adhesive serves to form the light diffusion film and also to bond the globe to the connector. This contributes to lower manufacturing costs.

Here, the connector may be a ring having an inner wall and an outer wall which together form a U-shaped cross section, with the ring-shaped groove being present between the inner wall and the outer wall, and the globe is bonded to the connector using part of the adhesive which is gathered in the groove.

With this construction, an excess of low-viscosity adhesive which is used to form the light diffusion film can be gathered in the groove and put to use for bonding the globe to the connector.

Here, an arch-shaped leaf spring may be formed by cutting part of the inner wall of the connector, wherein the leaf spring presses the neck part which is inserted in the groove, to temporarily tack the connector to the globe until the adhesive gathered in the groove hardens.

With this construction, the globe and the connector can be positioned easily at the time of bonding, with it being possible to avoid displacements.

Here, the inner wall of the connector may have a smaller height than the outer wall of the connector.

With this construction, an excessive amount of adhesive in the groove overflows not from the outer wall but from the inner wall, so that the external appearance of the bulb-type lamp will not be ruined.

Here, a depression and a projection that fit together may be each provided at a facing portion of a different one of the connector and the holder, so that the connector and the holder move in conjunction with a rotation of the globe which is bonded to the connector.

With this construction, when the user installs the bulb-type lamp into a socket, the globe will be kept from becoming unattached from the case and turning freely on its own.

Here, the bulb-type lamp may be an electrodeless discharge lamp in which a core supporter is supported by the stand of the holder, and a coil form on which an induction coil is wound is supported by the core supporter.

The stated object can also be achieved by a manufacturing method for a bulb-type lamp, including: a holding step for holding a holder which has a stand supporting an electric ballast, by a case which has an opening, in a state where the holder is inserted in the case through the opening with the electric ballast being inserted first; a bonding step for bonding a globe which has a constricted neck part at one end, to a connector which has a ring-shaped groove in which the neck part of the groove can be inserted, in a state where the neck part is inserted in the groove; and a fixing step for fixing the connector to which the globe is bonded, to one of the case and the holder by a fitting construction, in the opening of the case.

With this method, the globe is held in place just by engaging the connector, to which the globe is bonded, with the case or the holder. This eliminates the need for the heating process which is conventionally performed after the envelope is formed by the globe and case. Accordingly, the tilting of the globe caused by the expansion of air in the envelope is prevented, with it being possible to hold the globe without a tilt relative to the case. As a result, the external appearance of the bulb-type lamp improves. This reduces the number of defective products, so that increases of manufacturing costs caused by abandoning defective products can be suppressed.

Here, in the bonding step a fixed distance may be maintained between a furthermost end of the connector and a furthermost end of the globe, wherein an adhesive is injected into the groove while keeping the neck part which is inserted in the groove from contact with a bottom of the groove, to bond the globe to the connector.

The globe is usually formed from glass and therefore tends to have variations in size. However, if the globe is bonded to the connector by injecting the adhesive into the groove while maintaining a fixed distance between the furthermost ends of the connector and globe and also keeping the neck part of the globe from contact with the bottom of the groove, the globe and the connector are held together without a tilt. As a result, a bulb-type lamp with a uniform height can be produced.

Here, the bulb-type lamp may be a bulb-type fluorescent lamp in which (a) the globe is a hollow spherical member having an open end at which the neck part is formed, and (b) a light diffusion film is formed on an internal surface of the globe using an adhesive in which a light diffusion material is dispersed, wherein when the adhesive is applied to the internal surface of the globe to form the light diffusion film, an excess of the adhesive drops and is gathered in the groove of the connector, the gathered adhesive being used to bond the globe to the connector in the bonding step.

With this construction, the adhesive used for forming the light diffusion film is also used for bonding the globe to the connector. This contributes to lower manufacturing costs.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, advantages and features of the invention will become apparent from the following description thereof taken in conjunction with the accompanying drawings which illustrate specific embodiments of the invention.

In the drawings:

FIG. **1** is a partial broken front view of a bulb-type fluorescent lamp to which the first embodiment of the invention relates;

FIG. **2** is a developed view of the bulb-type fluorescent lamp;

FIG. **3** is an expanded sectional view of main part of the bulb-type fluorescent lamp;

FIG. **4** is a perspective view of a connector;

FIGS. **5**A–**5**D are each a front view of the globe, in a manufacturing process of bonding the globe to the connector;

FIG. **6** is a partial broken front view of a bulb-type fluorescent lamp to which a modification to the first embodiment relates;

FIG. **7** is a partial broken front view of a bulb-type fluorescent lamp to which another modification to the first embodiment relates;

FIG. **8** is a partial broken front view of an electrodeless discharge lamp to which the second embodiment of the invention relates;

FIG. **9** is a developed view of the electrodeless discharge lamp; and

FIG. **10** is a partial broken front view of a conventional bulb-type fluorescent lamp.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

First Embodiment

The first embodiment that applies the present invention to a bulb-type fluorescent lamp is described below, by referring to drawings.

(Construction of a Bulb-type Fluorescent Lamp)

FIG. **1** is a partial broken front view of a bulb-type fluorescent lamp of the first embodiment. FIG. **2** is a developed view of the bulb-type fluorescent lamp.

This bulb-type fluorescent lamp has a power rating of 13 W. As shown in FIG. **2**, the bulb-type fluorescent lamp has a globe unit **1**, a case unit **2**, and an arc tube unit **3**. The arc tube unit **3** holds a fluorescent tube **31**, and is housed in an envelope formed by the globe unit **1** and case unit **2**.

The globe unit **1** includes a globe **10**, and a connector **11** which is bonded to an edge part **10***b* at an open end of the globe **10** using an adhesive.

The globe **10** is made of pear-shaped glass having an opening **10***a*. A narrow constricted neck part **10***c* is formed near the opening **10***a*. The internal surface of the globe **10** is coated with a light diffusion film **100** (FIG. **1**) that diffuses light emitted from the fluorescent tube **31**. The light diffusion film **100** can be formed by dispersing a light diffusion powder in a thermosetting adhesive, and applying the result to the internal surface of the globe **10** and heat-hardening it. Here, the light diffusion powder may be made of calcium carbonate, magnesium oxide, silica, titanium oxide, a phosphor, or the like, whereas the thermosetting adhesive may be made of a water-soluble acrylic emulsion, or organic nitrocellulose or ethyl cellulose. Also, to prevent damage caused by cracking, the edge part **10***b* at the opening **10***a* of the globe **10** has been heated with a burner. As a result of this, the edge part **10***b* attains a round cross section (see FIG. **3**) and also attains some variations in height along the periphery of the globe **10**. It should be noted here that the material for the globe **10** is not limited to glass, as the globe **10** may also be formed from other materials with excellent heat resistance, such as ceramic.

The connector **11** is a ring having a U-shaped cross section, and is formed by stamping an iron plate. The connector **11** is bonded to the edge part **10***b* of the globe **10** using an adhesive. Here, it is preferable to use a thermosetting adhesive with high heat resistance, but a non-thermosetting adhesive, such as an adhesive that hardens by absorbing water in the atmosphere, is applicable too. The connector **11** is engaged with a case **20** in the case unit **2**, as a result of which the globe unit **1** is fixed to the case unit **2**.

The case unit **2** is used to fix the globe unit **1**, and also house the arc tube unit **3**. The case unit **2** has the case **20** and a base **21**.

The case **20** is formed from a resin having high heat resistance, such as polybutylene terephthalate (PBT). The case **20** is a tapered cylinder with one end opened and the other end sealed with the base **21**. Here, the base **21** is an E-type base. The internal surface of the case **20** has six depressions **200** at regular intervals along the periphery, in which stoppers **113** of the connector **11** are to be caught (though only four of the depressions **200** are shown in FIG. **2**). The internal surface of the case **20** also has a projection **201** along the periphery, below the depressions **200**. The projection **201** is used to engage with a collar **301** of a holder **30** in the arc tube unit **3**. By engaging the collar **301** with the projection **201**, the arc tube unit **3** is attached securely to the case unit **2**.

The arc tube unit **3** has the holder **30**, the fluorescent tube **31**, and an electric ballast **32**. The fluorescent tube **31** is made up of three U-shaped fluorescent tube bulbs (though only two of them are shown in FIGS. **1** and **2**) which are bridge-connected. The electric ballast **32** has a construction in which circuits, such as a transistor and a capacitor, for illuminating the fluorescent tube **31** are provided on a substrate. The fluorescent tube **31** is provided on one surface of the holder **30**, whereas the electric ballast **32** is provided on the other surface of the holder **30**. Note that though the transistor, the capacitor, and the like are attached to the holder **30** in this example, they may be provided outside the bulb-type fluorescent lamp as a separate unit. In such a case, wiring for supplying power to the fluorescent tube **31** serves as the electric ballast **32**.

The holder **30** includes a cylindrical stand **300** and the collar **301** which is provided at the lower end of the cylindrical stand **300** along the periphery. The fluorescent tube **31** is mounted on top of the stand **300**, while the electric ballast **32** is mounted at the bottom of the stand **300**. The holder **30** is inserted into the case **20** with the electric ballast **32** entering first, as a result of which the collar **301** engages with the projection **201** in the case **20** and so the arc tube unit **3** is secured to the case unit **2**.

Also, three depressions **302** are provided on the upper end of the stand **300** at regular intervals (though one of them is hidden behind the U-shaped fluorescent tube bulbs in FIG. **2**). These depressions **302** and rotation prohibiting parts **115** (FIG. **4**) of the connector **11** fit together. With this fitting, even if the user holds and rotates the globe **10** while screwing the bulb-type fluorescent lamp into a socket, the holder **30** and the connector **11** are kept from sliding in the direction of rotation. Therefore, the rotational power applied by the user is transmitted to the base **21**, with it being possible to reliably install the bulb-type fluorescent lamp into the socket.

The fluorescent tube **31** is made up of the three U-shaped glass bulbs which are bridge-connected, as noted above. Each glass bulb has electrodes at both ends (not illustrated). A predetermined amount of mercury and a predetermined amount of noble gas are enclosed in each glass bulb which is coated with a phosphor film on its internal surface. Hence a crooked discharge path is formed inside the fluorescent tube **31**.

(Construction of the Connector **11**)

A construction of the connector **11** which is a characteristic component in this embodiment is described below.

FIG. **3** is an expanded sectional view of a part of the bulb-type fluorescent lamp shown in FIG. **1** which is enclosed by a dashed line.

As illustrated, the holder **30** is fixed to the case **20** by fitting the collar **301** of the holder **30** and the projection **201** of the case **20** together. The connector **11** is inserted in a groove **310** formed between the case **20** and the holder **30** along the periphery.

FIG. **4** is a perspective view of the connector **11**.

As shown in the drawing, the connector **11** is a ring with a U-shaped cross section (FIG. **3**) that has an outer wall **110** and an inner wall **111** which are connected at the bottom. For example, the size of the connector **11** is such that the outer diameter of the outer wall **110** is 44 mm (excluding the stoppers **113**), the inner diameter of the inner wall **111** is 37 mm (excluding holding parts **114** and the rotation prohibiting parts **115**), and the height of the outer wall **110** is 10 mm.

A groove **112** exists between the outer wall **110** and the inner wall **111** along the periphery. For example, the groove **112** has a width of 2 to 4.5 mm, and a depth of 8–9 mm with respect to the outer wall **110**. The connector **11** may be formed from a metal such as phosphor bronze, iron, aluminum, nickel, copper, brass, or stainless steel. As an alternative, the connector **11** may be formed from a resin such as PBT, polycarbonate (PC), polyethylene terephthalate (PET), or acrylic.

The outer wall **110** of the connector **11** is cut, on the open end side, at six portions to form the six stoppers **113** which project from the outer wall **110**. The stoppers **113** are provided with a 60° pitch along the periphery. By fitting the stoppers **113** into the depressions **200** of the case **20** as shown in FIG. **3**, the connector **11** is fixed to the case **20** without using an adhesive. In other words, the globe unit **1** is fixed to the case unit **2** by means of fitting, so that there is no need to perform the heating to cure an adhesive after the formation of the envelope. Since the heating process which is conventionally performed after the formation of the envelope is unnecessary, the tilting of the globe caused by the expansion of air in the envelope can be prevented.

Also, the inner wall **111** of the connector **11** is cut, on the open end side, at three portions with regular intervals, to form the three holding parts **114** which project from the inner wall **111**, as shown in FIG. **4**. As shown in FIG. **3**, these holding parts **114** are curved in an arch form toward the groove **112**. When bonding the globe **10** to the connector **11** using an adhesive in the manufacturing of the bulb-type fluorescent lamp, the holding parts **114** press the vicinity of the edge part **10***b* of the globe **10** so as to temporarily tack the connector **11** at an installation position until the adhesive hardens. In this way, displacements are suppressed.

The connector **11** has a U-shaped cross section. An adhesive **12** is injected into the groove **112** and stays there. Which is to say, even if the adhesive **12** has low viscosity, it remains in the groove **112**, so that a sufficient amount of adhesive can be secured to bond the globe **10** and the connector **11** to each other. By inserting the edge part **10***b* of the globe **10** into the groove **112** and then injecting the adhesive **12** into the groove **112** which allows the adhesive **12** to stay there, the globe **10** is bonded to the connector **11** at the edge part **10***b*.

Here, it is preferable to position the edge part **10***b* of the globe **10** at a distance L1 from the bottom of the groove **112**, as shown in FIG. **3**. The reason for this is given below. The edge part **10***b* of the globe **10** has been heated with a burner to prevent damage due to cracking. This being so, though cracks are fusion-bonded to each other, the edge part **10***b* becomes varied in height along the periphery, that is, the edge part **10***b* attains surface irregularities. In such a case, if the edge part **10***b* is in contact with the bottom of the groove **112**, such surface irregularities are likely to cause the globe **10** to tilt. However, if the edge part **10***b* is positioned at the distance L1 from the bottom of the groove **112**, the adhesive **12** acts as a spacer to attach the globe **10** to the connector **11** without a tilt. For the same reason, even if the height of the globe **10** has some variations, the globe unit **1** can be formed with a uniform height.

Thus, the bulb-type fluorescent lamp of this embodiment is manufactured by bonding the globe **10** to the connector **11** using the adhesive **12** and then fixing the connector **11** to which the globe **10** is bonded, to the case **20** by means of fitting. Accordingly, the globe **10** can be fixed to the case **20** without having to perform the conventional heating process after the formation of the envelope. Hence the tilting of the globe **10** and the connector **11** are bonded to each other with a gap in between, the globe unit **1** can be formed in a desired shape regardless of the shape of the globe **10**. When such a globe unit **1** is fixed to the case unit **2**, the globe **10** is held in a correct position without tilting against the case **20**. This enables a bulb-type fluorescent lamp having a uniform height to be produced.

(Manufacturing Method for the Bulb-type Fluorescent Lamp)

The following is an explanation of a method of manufacturing the above bulb-type fluorescent lamp.

A process of bonding the edge part **10***b* of the globe **10** to the connector **11** is explained first.

FIG. **5** shows the manufacturing process of bonding the edge part **10***b* to the connector **11**. The process proceeds in the order of FIGS. **5**A to **5**D.

In FIG. **5**A, the globe **10** is held by a holder **102**. The holder **102** has a support **102***a* and two arms **102***b* which are each held by the support **102***a* so as to be slidable in its facing direction. Also, each arm **102***b* is given elasticity in its facing direction. The holder **102** holds the globe **10** with the two arms **102***b*, in such a manner that the top of the globe **10** is in contact with the support **102***a* and the edge part **10***b* of the globe **10** is positioned underneath it. Here, to hold the globe **10** securely, it is more preferable for the holder **102** to have at least three arms.

In FIG. **5**B, the connector **11** is placed on a mounting stand **103** which is used for positioning the connector **11**. The mounting stand **103** is then lifted up so that the edge part **10***b* is inserted into the groove **112** of the connector **11**. Here, the mounting stand **103** is equipped, on its mounting surface, with positioning means which engages with the connector **11**, to ensure that the connector **11** is mounted at a predetermined position. The positioning means can be realized by forming, on the mounting surface, a ring-shaped depression that engages with the connector **11** or a cylindrical projection that engages with the center hole of the connector **11**. Also, the height to which the mounting stand **103** is lifted is set such that the distance between the support **102***a* and the lifted mounting stand **103**, i.e., the distance between the upper end of the globe **10** and the lower end of the connector **11**, is a predetermined distance H. Though the distance H can be determined depending on the size of the globe **10**, it is preferable to set such a distance H that allows the gap L1 to be present between the edge part **10***b* and the bottom of the groove **112**. Usually, each globe **10** is formed by putting glass in a shaping die. This being the case, when the size of the shaping die changes with use, the height of each globe **10** may vary to some degree. However, by setting such a fixed distance H that keeps the edge part **10***b* from contact with the bottom of the groove **112**, the distance between the upper end of the globe **10** and the lower end of the connector **11** is made uniform. As a result, the globe unit **1** can be formed with a uniform height.

In the state where the edge part **10***b* of the globe **10** is inserted in the groove **112** of the connector **11**, the connector **11** is temporarily tacked to the vicinity of the edge part **10***b* by the pressure from the holding parts **114** (FIGS. **3** and **4**). Accordingly, the mounting stand **103** can be detached from the connector **11**, as shown in FIG. **5**C. Following this, a spray nozzle **104** is inserted into the globe **10** through the hole of the connector **11**, and the adhesive **12** which contains a light diffusion material is discharged from the tip of the nozzle. As a result, the adhesive **12** is applied to the internal surface of the globe **10**, while an excess of the adhesive **12** drops into the groove **112** of the connector **11** and stays there (see the partial expanded sectional view of FIG. **5**C). In

other words, with the provision of this groove **112**, the adhesive **12** is gathered even if it has only low viscosity. Thus, the adhesive **12** can be used not only to form the light diffusion film **100** but also to bond the globe **10** to the connector **11**.

Here, if the adhesive **12** overflows from the groove **112** and sticks to the outside surface of the globe **10**, the external appearance of the bulb-type fluorescent lamp is spoiled. This can be prevented by setting the smallest height of the inner wall **111** to be smaller than the smallest height of the outer wall **110**. In so doing, an excessive accumulation of the adhesive **12** in the groove **112** overflows from the inner wall **111** toward the center of the connector **11**, rather than overflowing from the outer wall **110**. As a result, the adhesive **12** is kept from sticking to the outside surface of the globe **10**. In the connector **11** shown in FIG. **4**, for instance, the cuts of the inner wall **111** to form the holding parts **114** may be made deeper than the cuts of the outer wall **110** to form the stoppers **113**. In more detail, if the depth of cut for forming the holding parts **114** is about 3–5 mm and the depth of cut for forming the stoppers **113** is about 1–2 mm, the excess adhesive **12** overflows not from the outer wall **110** but from the cuts of the inner wall **111**.

After this, the connector **11** and the globe **10** are placed in a heating furnace while maintaining the distance H, and heated to cure the adhesive **12**. As a result, the light diffusion film **100** is formed on the internal surface of the globe **10**, and at the same time the globe unit **1** in which the edge part **10***b* of the globe **10** is bonded to the connector **11** is obtained, as shown in FIG. **5**D.

After this, the fluorescent tube **31** and the electric ballast **32** are mounted to the holder **30**, which is then inserted into the case **20** to engage the projection **201** of the case **20** with the collar **301** of the holder **30**, as shown in FIGS. **1–3**. Hence the case **20** and the holder **30** are held together.

The connector **11** of the globe unit **1** is then inserted into the groove **310** formed between the case **20** and the holder **30**, as shown in FIG. **3**. While doing so, the rotation prohibiting parts **115** (FIG. **4**) of the connector **11** are caught in the depressions **302** (FIG. **2**) of the holder **30**, and the stoppers **113** (FIG. **2**) of the connector **11** are caught in the depressions **200** of the case **20**. Here, means that keeps the connector **11** from being inserted to more than a predetermined depth is provided at the groove **310** between the case **20** and the holder **30**. In the example shown in FIG. **3**, a slope of the projection **201** in the case **20** serves this purpose. Which is to say, by making the bottom of the connector **11** contact with this slope, the connector **11** is kept from being inserted to more than the predetermined depth.

Lastly, the base **21** is fixed to the case **20**, to complete the bulb-type fluorescent lamp.

According to the above manufacturing method, the globe **10** is bonded to the connector **11**, and then the connector **11** to which the globe **10** is bonded is fixed into the case **20**. This allows the bulb-type fluorescent lamp to be manufactured without having to perform the heating of the hermetically sealed envelope. Accordingly, the tilting of the globe **10** caused by the heating can be avoided. Also, the globe **10** is bonded to the connector **11** while keeping the globe **10** from contact with the bottom of the groove **112** of the connector **11**. In so doing, the globe unit **1** can be formed with a uniform height. Which is to say, even if the edge part **10***b* of the globe **10** has surface irregularities, the globe **10** is bonded to the connector **11** without a tilt. Therefore, the globe **10** can be held in a correct position with respect to the case **20**. This keeps the external appearance of the bulb-type fluorescent lamp from being ruined, with it being possible to avoid increases of manufacturing costs caused by abandoning defective products.

Moreover, the adhesive **12** that is used to form the light diffusion film **100** on the internal surface of the globe **10** is also used to bond the globe **10** to the connector **11**. This not only eliminates the necessity to prepare another adhesive, but also requires only one operation to cure the adhesive **12**. Hence increases of manufacturing costs can be avoided when compared with the case where another adhesive is used. Also, the manufacturing operation can be kept from becoming complex. Furthermore, an amount of adhesive necessary for bonding the globe **10** and the connector **11** to each other can be gathered reliably and easily, in the U-shaped groove **112** of the connector **11**.

(Modifications to the First Embodiment)

(1) The above embodiment describes the case where the stoppers **113** of the connector **11** are provided on the upper end of the outer wall **110**, but the invention is not limited to such. For example, the stoppers **113** may be provided at the bottom of the connector **11**.

FIG. **6** is a partial broken front view of a bulb-type fluorescent lamp to which this modification relates. This bulb-type fluorescent lamp has the same construction as that shown in FIG. **1**, except for some differences in the shapes of the connector and case. Therefore, construction elements which are the same as those in FIG. **1** are given the same reference numerals and their explanation is omitted.

A connector **13** is formed from a resin such as PBT, polycarbonate (PC), polyethylene terephthalate (PET), or acrylic. The connector **11** is a ring with a U-shaped cross section that has an outer wall and an inner wall which are connected at the bottom. For example, the size of the connector **13** is such that the outer diameter of the outer wall is 47 mm, the inner diameter of the inner wall is 39 mm, and the height of the outer wall is 11 mm (excluding stoppers **130**). A groove **14** is provided between the inner wall and the outer wall along the periphery. As one example, the groove **14** has a width of 4 mm, and a depth of 8 mm with respect to the outer wall. The groove **14** is filled with the adhesive **12**, which bonds the globe **10** as in the above embodiment. Also, the stoppers **130** with L-shaped cross section are projected downward from the bottom of the connector **13** along the periphery. These stoppers **130** are provided at equal intervals.

Meanwhile, depressions **220** that engage with the stoppers **130** are provided on the internal surface of a case **22**. Here, a ring-shaped groove is formed between the external surface of the holder **30** and the internal surface of the case **22**. As one example, the groove has a width W1 of 2 mm (a maximum width W2 in the areas where the depressions **220** are present being about 4 mm). The stoppers **130** are inserted into this groove so as to be engaged with the depressions **220**. In this way, the connector **13** and the case **22** are held together without using an adhesive. Hence the effects described in the above embodiment can be achieved. Here, the outer wall of the connector **13** is not inserted in the gap between the holder **30** and the case **22** but is exposed to the outside. Also, the case **22** has an external shape similar to the case **20** shown in FIG. **1**, except that its total height is a few millimeters shorter than the case **20**.

Thus, the same effects as the above embodiment can still be achieved even when the stoppers of the connector are provided at different positions.

(2) The above embodiment describes the case where the connector **11** is engaged with the case **20** to hold the globe unit **1**, but the invention is not limited to such. For example, the connector **11** may be engaged with the holder **30** to hold the globe unit **1**.

FIG. **7** is a partial broken front view of a bulb-type fluorescent lamp to which this modification relates. This bulb-type fluorescent lamp has the same construction as that shown in FIG. **1**, except for some differences in the shapes of the connector and holder. Accordingly, construction elements which are the same as those shown in FIG. **1** are given the same reference numerals and their explanation is omitted. Note also that a case **23** shown in FIG. **7** has an external shape similar to the case **20** in FIG. **1**, except that its total height is a few millimeters shorter than the case **20**.

A connector **15** is made of a resin. The connector **15** is a ring with a U-shaped cross section that has an outer wall and an inner wall which are connected at the bottom. For example, the size of the connector **15** is such that the outer diameter of the outer wall is 47 mm, the inner diameter of the inner wall is 39 mm, and the height of the outer wall is 11 mm (excluding projections **151**). A groove **16** exists between the outer wall and the inner wall along the periphery. As one example, the groove **16** has a width of 4 mm, and a depth of 8 mm with respect to the outer wall. Also, the projections **151** having tapered slopes are projected downward from the bottom of the connector **15**.

Meanwhile, a holder **33** is held in the opening of the case **23** by the same fitting means as in the above embodiment, so as to leave a ring-shaped gap therebetween. Slopes **231** that engage with the tapered slopes of the projections **151** are provided around the internal surface of the case **23**. Also, projections **330** are provided around the upper end of the external surface of the holder **33**. The connector **15** is caught between the slopes **231** of the case **23** and the projections **330** of the holder **33**. As a result, the tapered slopes of the projections **151** are pushed up by the slopes **231** of the case **23** and the top **152** of the inner wall of the connector **15** is engaged with the projections **330** of the holder **33**, so that the connector **15** and the holder **33** fit together. Hence the connector **15** is held so as not to move in a direction orthogonal to a central axis X of the lamp (see FIG. **7**).

The edge part **10***b* of the globe **10** is inserted in the groove **16** of the connector **15** without contacting the bottom of the groove **16**, and is bonded to the connector **15** through the adhesive **12** as in the above embodiment.

Since the holder **33** is fixed to the case **23** through the engagement of the collar **301** as in the above embodiment, the globe **10** and the case **23** are held together without having to use an adhesive. This eliminates the necessity to perform the heating after the formation of the envelope.

Thus, the effects of the above embodiment can still be achieved even if the connector **15** and the holder **33** fit together in this way. Note here that the outer wall of the connector **15** is exposed to the outside in this modification.

(3) Though the connector is engaged with the case or the holder in the above embodiment and modifications, the same effects can still be obtained even when the connector is engaged with a component which integrates the case and the holder.

(4) The above embodiment describes the case where the bulb-type fluorescent lamp has a power rating of 13 W. However, the power rating should not be limited to such, so that the invention can be applied, for example, to a bulb-type fluorescent lamp with a power rating of 22 W.

Second Embodiment

The first embodiment describes the case when the invention is used for a bulb-type fluorescent lamp. On the other hand, the second embodiment describes the case when the invention is used for an electrodeless discharge lamp.

An application of the present invention to an electrodeless discharge lamp is explained below, with reference to drawings.

(Construction of an Electrodeless Discharge Lamp)

FIG. **8** is a partial broken front view of an electrodeless discharge lamp to which the second embodiment of the invention relates. FIG. **9** is a developed perspective view of the electrodeless discharge lamp.

As shown in these drawings, the electrodeless discharge lamp has a globe **4**, a coil unit **5**, a connector **6**, a holder **7**, and a case unit **8**. The holder **7** is inserted in the case unit **8**, and the connector **6** to which the globe **4** and the coil unit **5** are attached is fixed onto the holder **7**.

The globe **4** is a hollow spherical member made of glass, and has a constricted neck part **40** at its lower end. A cylindrical depression **41** is formed from the neck part **40** toward the center of the globe **4**, and a canalicular part **42** extends along a direction of a central axis of the depression **41**. The globe **4** is coated with a phosphor film on its internal surface, and filled with noble gas and a metal vapor of mercury or the like.

The coil unit **5** has a cylindrical coil form **50** and an induction coil **51** which is wound on the coil form **50**. A core **52** (FIG. **8**) made up of a cylindrical ferrite core, iron core, or the like is inserted in the coil form **50**. The coil unit **5** is provided in the depression **41** of the globe **4**. When power is applied to the induction coil **51**, an electric field occurs in the globe **4**, which causes the enclosed metal vapor to collide with electrons. As a result, ultraviolet light is emitted from the metal vapor. This ultraviolet light excites the phosphor film on the internal surface of the globe **4** to emit light. To attach the coil unit **5** to the connector **6**, one end of the coil form **50** is fitted into an opening **60** of the connector **6**.

The connector **6** is a cylindrical member having the opening **60** at the center, as shown in FIG. **9**. Also, a groove **61** with a U-shaped cross section is provided along the periphery of the connector **6**. Four depressions **62** are provided at regular intervals on the outer wall of the connector **6**. By engaging the depressions **62** with projections **800** of a case **80** in the case unit **8**, the connector **6** is fixed to the case **80**.

The holder **7** has a stand **70**, a core supporter **71**, and an electric ballast **72**. The cylindrical core supporter **71** for supporting the core **52** is projected from the center of one surface of the stand **70**, whereas the electric ballast **72** is provided on the other surface of the stand **70**. The electric ballast **72** is equipped with a high-frequency oscillation circuit for converting power applied from the outside into a high-frequency signal which is to be supplied to the induction coil **51**, a rectifier, and similar (both the oscillation circuit and the rectifier are not illustrated). Also, a collar **73** is provided on the side wall of the stand **70** along the periphery. By engaging the collar **73** with a projection **801** of the case **80**, the holder **7** is fixed to the case **80** and the electric ballast **72** is housed in the case **80**. Though the high-frequency oscillation circuit and the like are mounted on the holder **7** in this example, they may be provided outside the electrodeless discharge lamp as a separate unit. In such a case, wiring for supplying the high-frequency signal to the induction coil **51** serves as the electric ballast **72**.

The case unit **8** has the case **80** and a base **81**. The case **80** is a tapered cylinder. The base **81** is an E-type base which seals one end of the case **80**. The other end of the case **80** is opened. The internal surface of the case **80** has the projections **800** and the projection **801**. When the holder **7** is inserted through the opening of the case **80** with the electric ballast **72** facing the case **80**, the projections **800** and the projection **801** engage with the depressions **62** of the connector **6** and the collar **73** of the stand **70**, respectively.

(Construction of the Connector **6**)

A construction of the connector **6** which is a characteristic component in this embodiment is explained below.

As shown in FIG. **8**, the connector **6** is bonded to the neck part **40** of the globe **4** through an adhesive **400**, in the groove **61**. Here, the neck part **40** is positioned at a distance L**2** from the bottom of the groove **61**. In this way, even when the height of the globe **4** varies or the neck part **40** has surface irregularities, the globe **4** can be attached to the case **80** without a tilt, as in the first embodiment. Hence the electrodeless discharge lamp can be manufactured with a uniform height.

Here, the globe **4** and the connector **6** may be bonded to each other using a method similar to that shown in FIG. **5**. The only difference lies in that an adhesive needs to be poured into the groove **61** of the connector **6** in the step of FIG. **5**C.

The globe **4** which is bonded to the connector **6** in such a way can be fixed to the case unit **8** just by engaging the connector **6** with the case **80**. This makes it unnecessary for the globe **4** to be directly bonded to the case unit **8** using an adhesive. Accordingly, the heating to cure an adhesive after the formation of the envelope becomes unnecessary. Thus, the same effects as the first embodiment can be achieved when the present invention is applied to an electrodeless discharge lamp.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted that various changes and modifications will be apparent to those skilled in the art.

Therefore, unless such changes and modifications depart from the scope of the present invention, they should be construed as being included therein.

What is claimed is:

1. A bulb-type lamp comprising:

a globe having a constricted neck part at one end;

a connector having a ring-shaped groove in which the neck part of the globe can be inserted, wherein the globe is bonded to the connector in a state where the neck part is inserted in the groove;

a holder having a stand that supports an electric ballast; and

a case having an opening, and holding the holder in a state where the holder is inserted in the case through the opening with the electric ballast being inserted first,

wherein in the opening of the case, the connector to which the globe is bonded is fixed to one of the case and the holder by a fitting construction.

2. The bulb-type lamp of claim **1**,

wherein the globe is bonded to the connector in a state where the neck part which is inserted in the groove is kept from contact with a bottom of the groove.

3. The bulb-type lamp of claim **1**,

wherein the fitting construction includes a depression and a projection that fit together, the depression and the projection each being provided at a different one out of (a) the connector and (b) one of the case and the holder.

4. The bulb-type lamp of claim **1** being a bulb-type fluorescent lamp in which a fluorescent tube is supported by the stand of the holder,

wherein the globe is a hollow spherical member having an open end at which the neck part is formed,

a light diffusion film is formed on an internal surface of the globe using an adhesive, and

the adhesive used for forming the light diffusion film is also used for bonding the globe to the connector.

5. The bulb-type lamp of claim **4**,

wherein the connector is a ring having an inner wall and an outer wall which together form a U-shaped cross section, with the ring-shaped groove being present between the inner wall and the outer wall, and

the globe is bonded to the connector using part of the adhesive which is gathered in the groove.

6. The bulb-type lamp of claim **5**,

wherein an arch-shaped leaf spring is formed by cutting part of the inner wall of the connector, and

the leaf spring presses the neck part which is inserted in the groove, to temporarily tack the connector to the globe until the adhesive gathered in the groove hardens.

7. The bulb-type lamp of claim **5**,

wherein the inner wall of the connector has a smaller height than the outer wall of the connector.

8. The bulb-type lamp of claim **4**,

wherein a depression and a projection that fit together are each provided at a facing portion of a different one of the connector and the holder, so that the connector and the holder move in conjunction with a rotation of the globe which is bonded to the connector.

9. The bulb-type lamp of claim **1** being an electrodeless discharge lamp in which a core supporter is supported by the stand of the holder, and a coil form on which an induction coil is wound is supported by the core supporter.

10. In a light emitting bulb, the improvement comprising:

a globe having a light emitting diffusing coated surface;

a support member for mounting the globe; and

an adhesive for bonding the support member to the globe, the adhesive having a light diffusing characteristic wherein the adhesive coats the light emitting surface of the globe for diffusing the light and also provides the bonding of the globe to the support member.

11. The light emitting bulb of claim **10** wherein the support member has a ring configuration with a u-shaped cross section, an inner wall of the support member has a height lower than an outer wall to enable any overflowing adhesive to flow over the inner wall.

12. The light emitting bulb of claim **11** wherein the support member has a plurality of spring projections to hold the globe.

13. A method of assembling a light emitting bulb with a light diffusing globe comprising the steps of:

positioning the globe adjacent a support member;

coating an interior surface of the globe with an adhesive having a light diffusing characteristic; and

continuing the coating step after the interior surface of the globe is coated to provide sufficient adhesive between the globe and the adjacent support member to bond the globe to the support member with the adhesive.

14. The method of claim **14** further including drying the adhesive without heating.

15. A bulb-type lamp assembly formed by modular components, comprising:

a globe having a transparent body for transmitting light with an opening having a peripheral connector affixed to and extending about the opening, the opening of a size to receive a light emitting member, the globe connector having an exterior surface with a first fastening unit comprising one of a projecting fastener member and a fastener depression;

a holder supporting a light emitting member; and

a case member having an opening for supporting the holder, the case member having an interior surface with a second fastening unit comprising one of a projecting fastener member and a fastener depression of a configuration to cooperatively secure the first fastening unit of the globe connector to the case member by relatively forcing the globe connector exterior surface into the case member interior surface, with the holder captured between the globe connector and the case member, to enable an automatic fastening by engagement of the respective projecting fastener member with the fastener depression whereby the bulb-type lamp is provided with a fitting construction without additional fasteners.

16. The bulb-type lamp assembly of claim **15** wherein the globe connector has an interior surface with radially inward projections and the holder has complementarily depressions to receive the projections and prevent relative rotation.

17. The bulb-type lamp assembly of claim **15** wherein the transparent body of the globe is coated with a light diffusing adhesive mixture that also bonds the peripheral connector to the globe.

* * * * *