US007894801B2

(12) **United States Patent**
Zellner et al.

(10) **Patent No.: US 7,894,801 B2**
(45) **Date of Patent: *Feb. 22, 2011**

(54) **IDENTITY BLOCKING SERVICE FROM A WIRELESS SERVICE PROVIDER**

(75) Inventors: **Samuel N. Zellner**, Dunwoody, GA (US); **Mark J. Enzmann**, Roswell, GA (US); **Robert T. Moton, Jr.**, Alpharetta, GA (US)

(73) Assignee: **AT&T Intellectual Property I, LP**, Reno, NV (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/552,767**

(22) Filed: **Sep. 2, 2009**

(65) **Prior Publication Data**

US 2009/0325551 A1 Dec. 31, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/252,039, filed on Oct. 17, 2005, now Pat. No. 7,603,110.

(51) **Int. Cl.**

H04M 3/42	(2006.01)
H04M 11/04	(2006.01)
H04M 1/66	(2006.01)
H04W 24/00	(2009.01)

(52) **U.S. Cl.** **455/414.1**; 455/404.2; 455/411; 455/456.1

(58) **Field of Classification Search** 455/414.1, 455/404.2, 404.1, 411, 456.1, 456.2, 456.3, 455/456.6, 500, 517, 445

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,852,775	A *	12/1998	Hidary	455/412.1
6,208,866	B1 *	3/2001	Rouhollahzadeh et al.	455/456.5


(Continued)

Primary Examiner—George Eng
Assistant Examiner—Brandon J Miller
(74) *Attorney, Agent, or Firm*—Parks IP Law LLC; Mickki D. Murray, Esq.

(57) **ABSTRACT**

Location-blocking and identity-blocking services that can be commercially offered by a service promoter, e.g., a cellular service provider or a web advertiser. In the identity-blocking service, the service promoter may disclose the current physical location of a mobile subscriber (i.e., a cellular phone operator) to a third party (e.g., a web advertiser) subscribing to the identity-blocking service. However, the service promoter may not send any identity information for the mobile subscriber to the third party. On the other hand, in the location-blocking service, the service promoter may disclose the mobile subscriber's identity information to the third party, but not the current physical location of the mobile subscriber. Blocking of the mobile subscriber's identity or location information may be desirable for privacy reasons, to comply with a government regulation, or to implement a telecommunication service option selected by the mobile subscriber. However, in the case of the mobile subscriber requesting emergency help, the service promoter may not block identity and/or location information. Instead, the service promoter may send all such information to the emergency service provider (e.g., the police or a hospital).

20 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

6,321,092	B1 *	11/2001	Fitch et al.	455/456.5
6,505,048	B1 *	1/2003	Moles et al.	455/456.1
6,647,257	B2 *	11/2003	Owensby	455/414.1
6,662,014	B1 *	12/2003	Walsh	455/456.2
7,085,555	B2 *	8/2006	Zellner et al.	455/414.1
7,110,749	B2 *	9/2006	Zellner et al.	455/414.1
7,224,978	B2 *	5/2007	Zellner et al.	455/456.1
7,366,522	B2 *	4/2008	Thomas	455/456.1
7,509,133	B2 *	3/2009	Zellner et al.	455/456.1
7,603,110	B2 *	10/2009	Zellner et al.	455/414.1
7,664,509	B2 *	2/2010	Zellner et al.	455/456.1

* cited by examiner



28
66
10
30
34
Cell Phone
14
Shopping Mall
12
Wireless Network
Cellular
Service
Provider
16

FIG. 1



16
Cellular
Service
Provider
12
Wireless Network
24
WAP
Gateway
66
Query
Response
28
30
10
34
Cell Phone
Query
Response
INTERNET
18
Query
Response
22
Database
Query
Response
Content Server
20

FIG. 2



Mic
Audio Logic
Speaker
Display Logic
Display
Keypad Interface Logic
Keypad
GPS Receiver
GPS Receiver Antenna
Processing and Control Unit
Memory Unit
WAP Stack
WDP & Adaptation Layer
Web Browser Module
Network Interface Unit
Wireless Modem
RF Transceiver Unit
RF Antenna Unit
To wireless network
10
30
32
34
40
42
28
44
46
48
49
50
52
54
56
58
60
62
64
66

FIG. 3



72
Mobile subscriber's identity information
Cellular service provider receives cell phone location information
70
74
Any third party receiver of location information?
Yes
76
Send location information to the third party without disclosing the mobile subscriber's identity
No
82
Is location information utilized by cellular service provider for sending advertisements to the cell phone?
Third party sends location-specific advertisements to the cell phone
78
Yes
Cellular service provider sends location-specific advertisements to the cell phone
84
No
END
80

FIG. 4



Web advertiser receives cell phone location information
86
Mobile subscriber identity information available?
88
No
Yes
Any preferences registered for the mobile subscriber?
90
No
Yes
Web advertiser selects location-specific advertisements
92
Web advertiser selects location-specific advertisements based on the mobile subscriber preferences
94
Web advertiser sends the location-specific advertisements to the cell phone without sending any indication of the mobile subscriber's identity
96
END
98

FIG. 5



102
Mobile subscriber's identity information
Cellular service provider receives cell phone location information
100
Mobile subscriber's identity information blocked?
104
No
Any third party receiver of identity information?
106
No
Yes
Yes
Cellular service provider sends mobile subscriber's identity information to the third party without disclosing the physical location of the mobile subscriber
110
Third party sends user-specific advertisements to the cell phone
112
END
108

FIG. 6



114
Web advertiser receives mobile subscriber's identity information
116
Mobile subscriber location information available?
No
Yes
118
Any preferences registered for the mobile subscriber?
No
Yes
122
Web advertiser selects user-specific advertisements
Web advertiser selects user-specific advertisements based on the mobile subscriber preferences
120
Web advertiser sends the user-specific advertisements to the cell phone without sending any indication of the mobile subscriber's location
124
END
126

FIG. 7

IDENTITY BLOCKING SERVICE FROM A WIRELESS SERVICE PROVIDER

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 11/252,039, filed Oct. 17, 2005, and issued as U.S. Pat. No. 7,603,110, the entirety of which is herein incorporated by reference.

TECHNICAL FIELD

The present invention broadly relates to communication services, and more particularly, to a telecommunication service that offers information about the location of a mobile subscriber to a third party without disclosing the identity of the subscriber to the third party.

BACKGROUND

Telephone communication has seen a phenomenal growth since its inception because of its extreme usefulness in today's world. It is hard, and almost impossible, to conceive of a world without telephones. Telephones have become an integral part of a civilized society. Modern telephones include generic desk-top telephone units, cordless telephones and more advanced cellular telephones (or "cell phones"). In contrast to a cordless telephone unit, a cellular telephone allows portability in that a cell phone operator can use the cell phone many miles away from home and the use is supported by a sophisticated telecommunications system.

Because a cell phone imparts mobility to the user while on the phone, quick detection of the location of the cell phone is important in the event of fraud or when there is a need to locate a cellular telephone (and, hence, its user) that placed a phone call for emergency assistance, e.g., a "911 call." It is also desirable to locate the cell phone operator or mobile subscriber (MS) for marketing reasons, e.g., for targeting location-specific advertisements to the cell phone operator upon determining the location of the cell phone operator. For example, one or more stores in a shopping complex (e.g., a mall) may wish to inform the cell phone operator about any current promotions or offers when the cell phone operator is found to be in the vicinity of the shopping complex.

In a cellular telephone network operated by a wireless service provider (SP), a mobile switching center (MSC) may serve more than one cell-site. Therefore, to locate a cellular phone within the network, a switch engineer may need to manually visit the MSC location and identify the cell-site within which the cellular phone is operative. Such a process may not be efficient when there are a large number of cell phone operators and in the event of frequent fraudulent or "911" calls. Further, it is also possible that the cell phone operator may swiftly change cells if the detection of the cell phone location takes more than a few minutes and especially when the cell phone operator is located near a cell boundary. In such an event, the earlier cell identification may prove wrong and the whole process may be repeated to identify the new cell site to which the cell phone operator has moved.

It is known to locate a cellular telephone having a predetermined telephone number by using time difference of arrival measurements (on signals transmitted from the specific cell phone) at a multiplicity of cell-phone base-stations. However, a GPS (Global Positioning System) antenna and a corresponding GPS receiver need to be added to each base station for use in locating the cell phone in this manner.

It is also known to locate the source of radio transmissions (including cellular phone transmissions) within a multipath signal environment. A hand-held sensor unit with a built-in non-directional or omnidirectional antenna can be used to capture signal transmissions from the source of radio transmissions to be located. Phase change measurements and other calculations are performed during processing of the captured signals and the signal-emitting source (e.g., a cell phone) is then located based on the outcome of the processing.

Furthermore, the identity of the cell phone operator may already be known to the wireless service provider serving the cell phone. For example, the wireless service provider may request information about the identity of the mobile subscriber (e.g., name, gender, age, employment information, etc.) when the mobile subscriber signs up to operate the cell phone in the wireless service provider's network. In another configuration, the identity of the cell phone operator may be available to an Internet world wide web advertiser with the help of, for example, cookies. The web advertiser may employ cookies to store information about and preferences of individual mobile subscribers who access particular websites on the Internet using web browser-equipped cell phones. It is known that cookies are digital text files placed in the cell phone's memory by a web server when the cell phone operator visits a web site served by the web server. Cookies are commonly used to store registration data such as the user's (here, the mobile subscriber's) name and address, the user's preferences, and so on. Cookies make it possible for web servers to personalize information to fit the user's specific needs and preferences when the user is visiting a web site on the Internet.

A wireless service provider may wish to supply a mobile subscriber's location information to a third party (e.g., a web advertiser) as part of the service provider's marketing activity. Also, a web advertiser (or any other marketing entity) may send location-specific advertisements to a mobile subscriber upon being informed of the current location of the subscriber. Because of various reasons (e.g., privacy concerns), it may be desirable that the wireless service provider not disclose the mobile subscriber's identity to the third party when sending the subscriber's location information to the third party. It may also be desirable that the web advertiser not transmit the mobile subscriber's identity information when communicating with the mobile subscriber over the Internet.

Alternatively, it may be desirable that the wireless service provider block the mobile subscriber's location information while supplying the subscriber's identity information to a third party. For example, a cell phone operator may wish to receive operator-specific advertisements over the cell phone from the third party without having the third party know of the physical location of the operator. Similarly, it may further be desirable that the web advertiser block any reference to the mobile subscriber's current physical location when sending any subscriber-specific advertisements to the mobile subscriber over the Internet. It may also be desirable for any other (i.e., non-Internet) advertiser to not disclose the cell phone operator's current location in or through the messages communicated between the advertiser and the cell phone.

SUMMARY

The present invention contemplates a method of providing an identity-blocking service, wherein the method comprises obtaining an identity of a user operating a wireless communication device; obtaining information about a location of the user; and transferring the information about the location of the user to a third party without disclosing the identity of the

user to the third party. A wireless service provider (e.g., a cellular telephone service provider) may commercially offer the identity-blocking service to the user for a fee. The third party may be an advertiser (e.g., a web advertiser) that is desirous of sending advertisements, messages or data to the wireless communication device (and, hence, to the user of the wireless device). The identity of the user may be obtained from the user when the user signs up for a communication service that allows the user to operate the wireless communication device in the wireless service provider's telephone network. In one embodiment, the promoter of the identity-blocking service may charge a fee to the third party for supplying information about the location of the user.

The present invention further contemplates a method of sending an advertisement over a communication network to a user operating a wireless communication device, wherein the method comprises receiving first information about a location of the user; receiving second information about the identity of the user; searching a database containing a plurality of location-specific advertisements; selecting one of the plurality of location-specific advertisements based on one or more criteria pre-selected by the user; and sending the one of the plurality of location-specific advertisements to the wireless communication device over the communication network without transmitting the identity of the user therewith. The communication network may be one or more of the Internet, the PSTN (public switched telephone network), and a cellular telephone network. A web advertiser may commercially offer such an identity-blocking service to, for example, cellular phone operators (i.e., mobile subscribers).

The web advertiser may obtain identity and location information for the user by paying a fee to an information provider (e.g., a wireless service provider). Furthermore, the one of the plurality of location-specific advertisements may be sent over the communication network in the form of a TCP/IP (Transmission Control Protocol/Internet Protocol) message.

The present invention further contemplates a method of providing a location-blocking service, wherein the method comprises obtaining identity information for a user operating a wireless communication device; obtaining location information for the user; and transferring the identity information for the user to a third party without disclosing the location information for the user to the third party. As mentioned hereinbefore, the third party user may be an advertiser (e.g., a web advertiser) who is desirous of sending advertisements, messages or data to the wireless communication device (e.g., a cell phone) and, hence, to the user. A wireless service provider may offer the location-blocking service for a fee to the user. The location of the user may be obtained by monitoring and then analyzing one or more signals transmitted by the wireless communication device operated by the user. In one embodiment, the wireless communication device may be configured to supply the location information to the wireless service provider.

The present invention further contemplates a method of sending an advertisement over a communication network to a user operating a wireless communication device, wherein the method comprises receiving first information about the identity of the user; receiving second information about a location of the user; searching a database containing a plurality of user-specific advertisements; selecting one of the plurality of user-specific advertisements based on one or more criteria pre-selected by the user; and sending the one of the plurality of user-specific advertisements to the wireless communication device over the communication network without transmitting the second information about the location of the user therewith. A web advertiser may commercially offer such a location-blocking service to, for example, cellular phone operators (i.e., mobile subscribers). The web advertiser may send the one of the plurality of user-specific advertisements over the communication network in the form of a TCP/IP (Transmission Control Protocol/Internet Protocol) message.

The present invention also contemplates an unblocking option where the user may access on Internet a website for one or more service promoters to "unblock" disclosure of the user's identity and/or location information. In alternative embodiments, various identity-blocking and location-blocking services may "unblock" transmission of respective identity and/or location information when the user (or the mobile subscriber) dials an emergency phone number (e.g., "911") or indicates a desire to access an emergency service provider (e.g., a fire station, a hospital, or the police).

Blocking of a user's identity or location information may be desirable for privacy reasons, to comply with a government regulation, or to implement a telecommunication service option selected by the user. Information blocks may be implemented in hardware and/or software, and at various places in a communication arrangement. Various identity-blocking and location-blocking services require an advertiser to not disclose the user's identity and current location, respectively, in or through the messages communicated between the advertiser and the wireless communication device operated by the user.

BRIEF DESCRIPTION OF DRAWINGS

Further advantages of the present invention may be better understood by referring to the following description taken in conjunction with the accompanying drawings, in which:

FIG. **1** illustrates interaction between a wireless device, such as a cell phone, and a wireless network to determine the cell phone location when the cell phone operator approaches a location;

FIG. **2** shows an arrangement wherein the cell phone operator receives queried information or unsolicited advertisements over a combination of the wireless network and the Internet from a remote content server;

FIG. **3** is an exemplary block diagram showing circuit blocks constituting a web browser-equipped cell phone;

FIG. **4** depicts an exemplary flowchart for an identity-blocking service provided by a cellular service provider;

FIG. **5** shows an exemplary flowchart for an identity-blocking service provided by an Internet or web advertiser;

FIG. **6** is an exemplary flowchart for a location-blocking service provided by a cellular service provider; and

FIG. **7** illustrates an exemplary flowchart for a location-blocking service provided by an Internet or web advertiser.

DETAILED DESCRIPTION

FIG. **1** illustrates interaction between a wireless device, such as a cell phone **10**, and a wireless network (or a cellular telephone network) **12** to determine the cell phone location when the cell phone operator approaches a location **14**. The location **14** may be, for example, a shopping mall. It is to be understood that the cell phone **10** is powered on and is being carried by a cell phone operator or mobile subscriber (MS) approaching the location **14**. It is also noted that the arrangement shown in FIG. **1** is for illustrative purpose only. In practice, the cell phone operator may visit a number of different locations (including, but not limited to, the location **14**) carrying the cell phone **10**. The location of the cell phone **10** may then be tracked at appropriate cell sites (not shown) in the wireless network **12** that the cell phone operator visits.

As discussed in more detail hereinbelow with reference to FIG. **3**, the cell phone **10** may include a display screen **28**, a keyboard **30**, a microphone **34** and an RF (radio frequency) antenna **66**. Additional circuit blocks constituting the cell phone **10** are shown in FIG. **3**.

The location of the cell phone **10** may be determined periodically (i.e., at predetermined time intervals, e.g., every 30 seconds) by the wireless service provider or the cellular service provider (SP) **16**. Through the arrangement shown in FIG. **1**, the SP **16** may transmit user-specific or location-specific voice and/or data advertisements to the cell phone **10** as discussed hereinbelow with reference to FIG. **4**. For cell phone location determination, the SP may employ one or more of the methods discussed in U.S. Pat. No. 5,512,908 ("the '908 patent") (issued on Apr. 30, 1996) and in U.S. Pat. No. 5,625,364 ("the '364 patent") (issued on Apr. 29, 1997), both of which are incorporated herein by reference in their entireties.

In the '908 patent, a cellular telephone having a predetermined telephone number is located by using time difference of arrival measurements (on signals transmitted from the specific cell phone) at a multiplicity of cell-phone base-stations. The '364 patent discusses locating the source of radio transmissions (including cellular phone transmissions) within a multipath signal environment. In the '364 patent, a hand-held sensor unit with a built-in non-directional or omni-directional antenna is used to capture signal transmissions from the source of radio transmissions to be located. Phase change measurements and other calculations are performed during processing of the captured signals and the signal-emitting source (e.g., a cell phone) is then located based on the outcome of the processing.

Alternatively, the location determination may be made, for example, when the cell phone **10** registers with a particular cell site in the service provider's cellular network. The location data may be updated when the mobile subscriber is roaming as is known in the art.

The subscriber (carrying the cell phone **10**) may, for example, park the subscriber's vehicle near the location **14** and may approach the location **14** on foot. In that case, an interpretation of the location data from the periodic location determination may imply that the subscriber has decided to visit the location **14**. A third party advertiser (e.g., a web advertiser as discussed hereinbelow or a store in a shopping mall) or the service provider **16** itself may thus appropriately target advertisements to the cell phone **10** based on such indication of a stable location.

Alternatively, the MS may just drive around the location **14** and may not intend to park the car and visit the location **14**. In that event, an interpretation of the periodic location data may imply that the cell phone **10** (and, hence, the mobile subscriber) is in continuous motion near or around a specific location (e.g., a mall) and the cell phone operator may not visit the location **14** at all. It may therefore be desirable for the third party advertiser or the service provider **16** not to send advertisements related to the location **14** because of the high probability that the cell phone operator may not visit the location **14**.

FIG. **1** illustrates that the cell phone **10** is in wireless communication with the wireless network **12** using, for example, radio channels for voice and/or data communication. It is noted that the term "wireless network", as used herein, is contemplated to include analog or digital cellular mobile networks irrespective of the underlying transmission technology, e.g., CDMA (code division multiple access), TDMA (time division multiple access), etc., and any other radio network that employs intersystem messaging (e.g., the IS-41 based messaging scheme) as part of mobile wireless communication. The wireless network **12** may include a combination of one or more of, for example, an analog wireless network (e.g., the AMPS (Advanced Mobile Phone System) network), a digital wireless network including cellular networks (e.g., TDMA or CDMA-based wireless networks), a wireless LAN (Local Area Network) and a WLL (Wireless Local Loop) configuration. A portion of the wireless carrier network **12** may include one or more microwave links for satellite-based communication.

Furthermore, the SP **16** is shown as being part of the wireless network **12** because it is well known in the art that the wireless service provider **16** may operate in one or more of the cell sites (not shown) in the wireless network **12**. In fact, the SP **16** may operate in almost all cell sites within the wireless network **12** (e.g., in the case of a national service provider) or, alternatively, the SP **16** may have operations within a select group of cell sites within the network **12** (e.g., in the case of a regional service provider).

In addition to the determination of the MS's location, the service provider **16** may also ascertain the identity of the mobile subscriber through, for example, the cell phone data (e.g., the mobile identification number or MIN) received by the SP **16** (e.g., through a mobile switching center operated by the SP **16**) when the SP **16** authenticates the cell phone **10** as part of the cell phone registration process as is known in the art. The identity of the mobile subscriber (e.g., the subscriber's name, address, contact phone number, employment status, etc.), along with the associated MIN, may already have been previously stored in a database (e.g., the subscriber's home location register or HLR) maintained by the SP **16**. Alternatively, the mobile subscriber identity information may temporarily reside in a visitor location register (VLR) associated with the serving MSC (mobile switching center) for a roaming MS. Such identity information may be obtained by the SP **16**, for example, when the MS initially signs up for the cellular service offered by the SP **16**.

In the discussion given hereinabove, the mobile subscriber's location and identity information may be considered to reside "in the network" as opposed to "in the cell phone." In the latter situation, a GPS (global positioning system) receiver-equipped cell phone (discussed hereinbelow with reference to FIG. **3**) may monitor and record/update the cell phone location in a memory unit inside the cell phone **10**. The user of the cell phone **10** may decide whether to release the stored location information to, for example, a web advertiser. If the user decides to block the user's current location information as part of the user's query to a web advertiser for certain information (as discussed hereinbelow with reference to FIG. **2**), the web advertiser may "know" the identity of the user requesting information, but may not know where the user is located. Such an action may be necessary, for example, when the user wants to receive general information from the web advertiser on a topic of the user's choice, but without receiving location-specific advertisements.

FIG. **2** shows an arrangement wherein the cell phone operator receives queried information or unsolicited advertisements over a combination of the wireless network **12** and the Internet **18** from a remote content server **20**. The content server **20** is shown connected to the Internet **18** and may include a database **22** that stores varied information (e.g., news, weather information, shopping information, map directions, etc.). The database **22** may be physically located within the server computer **20** or, alternatively, the database **22** may be located away from the server **20**. In the latter case, the server **20** may query the remote database **22** for the requisite information. In one embodiment, some or all of the

information in the database **22** may be in a digital audio file format so as to allow the cell phone operator to listen to the information content over the speaker **32** (FIG. **3**). The data in audio file format may include file extensions such as, for example, ".WAV" (wave file), ".AIFF" (Audio Interchange File Format), ".AU" (audio file), etc. Alternatively, a portion of the information in the database **22** may be in a digital text file format, e.g., in the HTML (Hyper Text Markup Language) format, in the ASCII (American Standard Code for Information Interchange) format, etc. The digital text files may be sent over the Internet **18** to the web browser residing in the cell phone **10** so as to display the user-requested information on the display screen **28** for the cell phone **10**.

As illustrated in FIG. **2**, the cell phone operator may access the Internet **18** to request information from the content server **20**. The cell phone **10** may include a web browser (e.g., the web browser module **48** in FIG. **3**) to access the Internet **18** via the wireless network **12**. The information request may be sent (by the web browser **48**) as a query message to the remote content server **20**. The content server **20** may, in turn, forward the query to the database **22** to search and access the requested information. Upon retrieving pertinent information, the content server **20** may send the information to the cell phone **10** (i.e., to the web browser in the cell phone **10**) via a response message over the Internet **18** as illustrated in FIG. **2**. The query and response messages may include TCP/IP (Transmission Control Protocol/Internet Protocol) data packets for propagation over the Internet **18**.

A WAP (Wireless Application Protocol) proxy/server **24** is also shown as part of the data transfer arrangement in FIG. **2**. The WAP proxy/server **24** may facilitate access to the Internet **18** using the cell phone **10**. The WAP proxy/server **24** translates WAP requests/queries transmitted by the web browser module **48** (FIG. **3**) into WWW (World Wide Web) or Internet requests supported by the content server **20**. The data packets (including information queries sent to the content server **20**) generated or received by the web browser module **48** (using the WDP layer **50**) may be in a WAP-supported format, e.g., the WML (Wireless Markup Language) format. The WAP proxy/server **24** receives the WAP requests sent by the web browser module **48** in the form of WDP (Wireless Datagram Protocol) datagrams adapted to be transmitted over the underlying physical carrier networks, e.g., the PSTN (Public Switched Telephone Network) (not shown), the Internet **18**, etc. The WAP proxy/server **24** then sends appropriate WWW requests, e.g., in the HTML format, to the content server **20**.

It is noted that the term "Internet", as used herein, may be construed to include portions of traditional wireline telephone networks, e.g., the POTS (plain old telephone system) or the PSTN. Additionally, other networks, e.g., a LAN (local area network), a WAN (wide area network), etc., may also form part of the Internet **18**, as is known in the art, to propagate the query and response messages between the cell phone **10** and the content server **20**.

The content server **20** may provide the requested data or information in a specific format, e.g., in the HTML format, in the WML format, etc., depending on its design and implementation. If the content server **20** provides information in WAP content (e.g., in the WML format), then the WAP proxy/server **24** may retrieve the information directly from the content server **20** via the Internet **18** and forward the retrieved information to the web browser module **48** (FIG. **3**). However, if the content server **20** provides information in WWW content (e.g., in the HTML format), then a filter may be used to translate the WWW content into WAP content. For example, an HTML filter (not shown) placed between the WAP proxy/server **24** and the content server **20** may translate information or data received in the HTML format into that in the WML format. The WAP proxy/server **24** may receive this translated data from the HTML filter and deliver it to the web browser module **48** via the Internet **18**.

In one embodiment, the WAP proxy/server **24** may itself contain the data and information requested by the web browser module **48** (FIG. **3**). In that embodiment, instead of the content server **20**, the WAP proxy/server **24** may itself provide the requisite data and information to the web browser module **48**. Thus, the WAP proxy/server **24** may not access another content server, e.g., the content server **20**, and may, instead, directly supply the requested information in a WAP-supported format, e.g., the WML format, to the web browser module **48** via the Internet **18**. In this configuration, the WAP proxy/server **24** may function as an origin or gateway server (instead of a proxy) that responds to requests from the WAP client, i.e., the web browser module **48**, directly.

Instead of the WAP browser discussed hereinbelow with reference to FIG. **3**, the web browser module **48** may include an HTML browser (not shown). In a data transfer arrangement with the HTML browser, the WAP proxy/server **24** and the HTML filter (not shown) may not be necessary. Further, the content server **20** may be configured to transfer data in the HTML format so as to be compatible with the data format supported by the HTML browser in the web browser module **48**. All other components in the data transfer arrangement may remain the same as that illustrated in FIG. **2**. Thus, in view of the foregoing discussion of remote data transfer with a WAP browser, additional discussion of data transfer using an HTML browser is omitted to prevent repetition.

It is noted that one or more of the WAP proxy/server **24**, the content server **20** and the database **22** (if separate from the content server **20**) may be owned or operated by the cellular service provider **16**. Alternatively, an independent third party (e.g., a web banner advertiser) may own or operate these servers to store and provide various information to users or subscribers.

In one embodiment, the cell phone operator may send a query over the Internet **18** to the content server **20** by first accessing (with the help of the cell phone **10**) the web page for the content server **20** and entering the query therein. As part of the query, the cell phone operator may supply the operator's current physical location to the content server **20**. However, the operator may not supply the operator's identity to the content server **20**. In other words, the content server **20** may "know" where the operator is, but not who the operator is. For example, the cell phone operator may access the content server's **20** web site from a location on a highway to request information about nearby attractions, locations of food establishments, directions for further travel, etc. The cell phone operator may not specify his/her identity or personal choices (e.g., food preferences) to the content server **20**. Thus, the content server **20** may not supply user-specific information to the cell phone operator. Instead, the cell phone operator may receive general location-specific information from the content server **20**.

FIG. **3** is an exemplary block diagram showing circuit blocks constituting a web browser-equipped cell phone, e.g., the cell phone **10**. The cell phone **10** includes a display screen (or "display") **28**, a keypad or keyboard **30**, a speaker **32** and a microphone **34**. The keys or "buttons" on the keypad **30** may be provided as, for example, push-button keys or computer keyboard-type keys or membrane keys or any other suitable design configuration. The choice of the type of keys on the keypad **30** may thus depend on design and aesthetic considerations including, for example, the size, the weight and the desired physical contours for the cell phone **10**. The display

screen **28** may display text or graphic messages thereon. For example, when the mobile subscriber (MS) browses the Internet **18**, the display screen **28** may display the content of web pages for the MS to look at. In one embodiment, the display screen **28** may be an LCD (liquid crystal display) display. In alternative embodiments, the display screen may be, for example, a TFT (thin film transistor) active matrix display or a touch-sensitive screen.

Additional circuit elements include an audio logic unit **40**, a display logic unit **42**, a keypad interface logic unit **44**, a memory or storage unit **46**, a web browser module **48** and a network interface unit (NIU) **60**. These circuit elements are shown coupled to a processing and control unit (PCU) **52** that manages and controls various operations performed by these circuit elements. The NIU **60** may include a wireless modem **62**, an RF (radio frequency) transceiver unit **64** and an RF antenna unit **66** so as to enable the web browser module **48** to transmit and receive digital information over the Internet **18** as discussed hereinbelow.

The audio logic unit **40** may be connected to the microphone **34** and the speaker **32**. The speaker **32** may be activated by the audio logic unit **40** when, for example, the PCU **52** informs the audio logic unit **40** that the MS has initiated a telephone conversation. Voice messages may first be received by the PCU **52** (via the NIU **60**) and the PCU **52** may transmit these signals to the audio logic unit **40** to be sent to the speaker **32** for generating audible sound. Alternatively, any digital audio files (e.g., from the content server **20**) received by the cell phone **10** (using the NIU **60**) over the Internet **18** may first be sent to the web browser module **48** to retrieve the audio file data therefrom. The browser module **48** may then send the audio data to the PCU **52**, which, in turn, forwards the audio data to the audio logic unit **40** and eventually to the speaker **32** for audible playback.

The user of the cell phone **10** may speak into the microphone **34** to transmit the user's voice during, for example, a telephone conversation. The audio logic unit **40** receives the electrical audio signals from the microphone **34** and sends them to the PCU **52**, which, in conjunction with the NIU **60** transmits the user's voice to the wireless network **12**. In one embodiment, the PCU **52** may generate digital audio files from the analog audio signals received from the microphone **34**. The browser module **48** may send TCP/IP messages over the Internet **18** containing these digital audio files so as to allow the MS to carry out voice communication over the Internet **18**. The digital audio file formats may include file extensions such as, for example, ".WAV" (wave file), ".AIFF" (Audio Interchange File Format), ".AU" (audio file), etc.

The display logic unit **42** monitors and manages display functionality for the cell phone **10**. The PCU **52** may generate proper commands and signals for the display logic unit **42**, which, in turn, may control the display of visual information on the display screen **28**. The display screen **28** may display various information such as, for example, an e-mail message received over the Internet **181** any data entered via the keypad **30** or an intimation of which action is being performed by the cell phone **10**. For example, a message such as "ACCESSING THE INTERNET" may also be sent to the display logic unit **42** (to be displayed on the display screen **28**) by the PCU **52** once the PCU **52** receives an indication from the web browser module **48** that Internet access is in progress. Other messages may also be conveniently displayed on the screen **28**. For example, as soon as the user presses a key on the keypad **30**, the corresponding digit, symbol or command may be displayed on the display screen **28** by the display logic unit **42**.

The keypad interface logic **44** is coupled to the keyboard **30** and receives signals sent from the keyboard **30** when the user presses one or more keys thereon. The user may enter data such as, for example, a telephone number, a web address (e.g., the web address of the content server **20**), an e-mail message, etc., using various keys on the keypad **30**. The web browser module **48** may need a portion of such data to determine how to access the content server **20** over the Internet **18**. Furthermore, the user may also prefer to enter personal information about the user, e.g., the user's name, the address of the user's contact location, any known medical condition, etc., using keys on the keypad **30** and store that personal information in the memory unit **46**.

The keypad interface **44** transmits the signals received from the keyboard **30** to the PCU **52** for further processing. The PCU **52** decodes the received signals and accordingly instructs the appropriate circuit elements for necessary action. For example, when the user enters the user's personal information, the keypad interface logic **44** may send all the data to the PCU **52**, which may instruct the memory unit **46** to store the received data therein. The PCU **52** may store the user's personal identification information in the memory **46** using one of a number of digital text formats, e.g., HTML (Hyper Text Markup Language) format, ASCII (American Standard Code for Information Interchange) format, XML (Extensible Markup Language) text file format developed by W3C (World Wide Web Consortium), etc.

In one embodiment, the cell phone **10** may include a text-to-speech (TTS) converter (not shown). The TTS conversion functionality may be implemented with appropriate software residing in the PCU **52**. The TTS converter may work with an SGML (Standard Generalized Markup Language) format-based TTS markup language. The SGML format may be based on the ASCII text format. An example of an SGML-based TTS markup language includes the STML (Spoken Text Markup Language) developed by Lucent Technologies of Murray Hill, N.J., USA. In that embodiment, the cell phone **10** may be configured to receive an e-mail or other messages in the SGML format over the Internet **18**. The TTS converter may convert the received text file (in the SGML format) into an STML file that can be audibly played back by the audio logic unit **40**. The user of the cell phone **10** can thus hear, in a synthesized voice, the content of the message sent in a digital text format.

The memory or storage unit **46** provides memory for storage of data, such as the user's personal information as discussed hereinbefore. The data stored locally in the memory unit **46** may be text, audio or video data and may include a number of digital file formats as described hereinbefore. For example, data that may be sent over the Internet **18** may be in the HTML or the WML (Wireless Markup Language) formats. The memory unit **46** may be located inside the cell phone **10** or, alternatively, may be supplied as a memory cartridge (not shown) that may be attached to the cell phone **10** at an appropriate adapter slot (not shown) provided on the housing for the cell phone **10**.

The memory unit **46** may include volatile and/or non-volatile memory, such as RAM (Random Access Memory), ROM (Read Only Memory), EEPROM (Electrically Erasable Programmable Read Only Memory) or similar memory units. A volatile memory may lose the data stored therein if the power applied thereto is removed. The personal information about the user (as an audio file or as a text file) may be stored in the non-volatile portion of the memory **46**. On the other hand, the content of a web page accessed through the web browser **48** may be stored in the volatile portion (or temporary storage) of the memory **46**.

The web browser module **48** may include software code or routines which, when executed by the PCU **52**, perform web

browser functions upon execution. In one embodiment, the web browser module **48** may be implemented using a combination of software and hardware elements. The web browser software may include, for example, an HTML browser or a WAP (Wireless Application Protocol) browser because of the small size and portable nature of the cell phone **10** and because of the smaller display **28** and limited memory space (in the memory unit **46**) available for the cell phone **10**. The HTML browser may "read" information received or stored in the HTML format, whereas the WAP browser may be able to "read" information having WAP content (e.g., information in the WML (Wireless Mark-up Language) format). In the embodiment illustrated in FIG. **3**, the web browser module **48** includes a WAP browser that wirelessly connects the cell phone **10** to the Internet **18**.

The web browser **48** may be activated using one or more keys on the keypad **30** and may be used for surfing the world wide web portion of the Internet. The web browser module **48** interacts with the PCU **52** to execute necessary software routines for Internet access. The software routines, upon execution, activate the wireless modem **62** in the NIU **60** to accomplish dialed Internet access via the wireless network **12**. In one embodiment, the web browser module **48** (including its hardware and/or software elements) may be a part of the PCU **52** and the PCU **52** may directly perform web browsing or information delivery over the Internet **18**.

Inclusion of the web browser **48** within the cell phone **10** may result in a standardized information interface for the cell phone **10** because it dispenses with the need to have a proprietary format for information transmission, storage and display. The messages to and from the cell phone **10** need not have to be in a proprietary format, but, instead, may be in a generally available text format, e.g., the HTML format or the WML format. This allows for ease of Internet communication with the cell phone **10** because of the use of TCP/IP data packets over the Internet **18** for information exchange.

As noted hereinbefore, the web browser module **48** includes the WAP browser software represented as a WAP stack **49**. The WAP architecture provides a scaleable and extensible environment for application development for mobile communication devices such as, for example, the cell phone **10**. The WAP protocol is designed in the form of a layered architecture wherein each of the layers is accessible by the layers above, as well as by other services and applications running on the WAP platform. The WAP stack **49** has the application layer (not shown) at its top, which is successively followed by the session layer (not shown), the transaction layer (not shown), the security layer (not shown) and the transport layer, which is referred to as a WDP (Wireless Datagram Protocol) and Adaptation layer **50** in FIG. **3** (and interchangeably referred to hereinbelow as "the WDP layer" or "the adaptation layer" for the sake of clarity).

The WDP layer **50** is the lowest layer in the WAP stack that is in direct contact with a physical network carrying the WAP data. The WDP layer **50** operates above the data-capable bearer services supported by various physical networks. A bearer service is a data transport mechanism that carries the WDP protocols between two devices. Some examples of bearer services include, for example, SMS (Short Message Service), circuit switched data and packetized data. Examples of some physical networks that carry the bearer data include a GSM (Global System for Mobile Communications) or another TDMA-based (Time Division Multiple Access) wireless network, a wireline network (e.g., the PSTN or the Internet), etc. The WDP protocol can be mapped onto different bearers, with different characteristics. The adaptation layer **50** is the layer of the WDP protocol that maps the WDP protocol functions directly onto a specific bearer. Thus, operationally, the WDP layer **50** provides convergence between a given bearer service and the rest of the WAP stack **49**. The content of the adaptation layer **50** may be different for each bearer depending on, for example, specific capabilities and characteristics of that bearer service.

In the embodiment of FIG. **3**, the WDP and adaptation layer **50** in the WAP stack **49** may map WDP protocol functions onto the packetized data (i.e., the bearer service) supported by the wireless network **12** to facilitate communication between the web browser module **48** and the remote source of data (i.e., the content server **20**). The WDP layer **50** may thus adapt the datagrams transmitted and received thereby to conform to the data transmission protocol specified by the physical data carrier network, i.e., the wireless network **12**. As noted hereinbefore, the WAP browser in the web browser module **48** may communicate with the remotely-located source of data (e.g., the content server **20**) using a WAP-supported data format, e.g., the WML format. For bearer services supporting IP (Internet Protocol), the WDP protocol may be UDP (User Datagram Protocol) that provides port-based addressing (e.g., source port, destination port, etc.) which may be combined with the segmentation and reassembly features of IP-based routing to implement a connectionless datagram service between two devices.

The PCU **52** manages and controls various operations performed by different circuit elements connected thereto. The PCU **52** functions as a centralized location to send and receive various commands and information. For example, the PCU **52** may receive a signal from the keypad interface logic **44** when the MS wishes to access the Internet **18**. In response, the PCU **52** may execute the web browser software in the browser module **48** to initiate an Internet connection. The PCU **52** may receive content of a web page or an e-mail over the Internet **18** and may, in turn, instruct the display logic **42** to display the received web page or e-mail on the display screen **28**. Alternatively, the PCU **52** may instruct the TTS converter (not shown) to audibly "play" a message text using the audio logic unit **40** and the speaker **32** as described hereinbefore. During web browsing, the PCU **52** may also execute audio and video data files received from the Internet **18** using the web browser module **48** and send appropriate audio and video signals to the audio logic unit **40** and the display logic unit **42** respectively.

The cell phone **10** may include some additional optional circuit elements such as, for example, a user location identifier **54** including a GPS (Global Positioning System) receiver **56** and a GPS receiver antenna **58**. The GPS receiver antenna **58** may be provided on the cell phone **10** to continuously receive location signals from geo-stationary satellites and transfer those signals to the GPS receiver **56** to identify the current location of the cell phone **10** and, hence, the location of the user carrying the cell phone **10**. Instead of a built-in location identifier **54**, the cell phone **10** may be provided with a port (not shown) to receive an external location identifier (with or without the receiver antenna **58**) that may be attached to the port when needed. The GPS location identifier **54** may perform better in an outdoor environment, e.g., when the user is on the road. In one embodiment, the user location identifier **54** may supply the PCU **52** with the requisite location information and the PCU **52**, with the help of the web browser module **48** and the network interface unit **60** (described hereinbelow), may send the user location information over the Internet **18** to the content server **20**. Alternatively, the PCU **52** may send the MS's location information to the cellular service provider **16** via the wireless network **12**.

The network interface unit **60** provides an electrical interface for signals travelling between various circuit elements

inside the cell phone **10** and a wireless carrier network, e.g., the wireless network **12** in FIG. **3**. Data communication signals (including the TCP/IP messages) transmitted and/or received by the web browser module **48** may pass through the NIU **60** prior to reaching their appropriate destinations. The NIU **60** may provide signal amplification in, for example, a noisy signal environment.

The network interface unit **60** employs wireless devices to transfer data and information from the cell phone **10** over the Internet **18**. An antenna, e.g., an RF (radio frequency) antenna **66**, may be provided on the cell phone **10** to allow wireless data communication. Data communication may be accomplished via a wireless modem **62** using the wireless network **12**. When the wireless network **12** is a cellular network (e.g., a TDMA-based wireless network or a CDMA-based wireless network), the wireless modem **62** may be capable of data transfer using the message format supported by the given cellular network.

The web browser module **48** in the cell phone **10** may be configured to transfer data over the wireless network **12** and, hence, the web browser module **48** may be connected to the NIU **60**. The web browser module **48** in FIG. **3** includes a WAP browser, as described hereinbefore. However, a web browser module **48** with an HTML browser may be similarly configured to perform data transmission and reception operations using wireless devices. The cell phone **10** may also include a web browser module **48** with browser software that supports a content format that is different from HTML or WML such as, for example, the JavaScript scripting language. A cell phone may be conveniently designed to include such a web browser module for data communication.

The RF transceiver unit **64** sends RF signals to the RF antenna **66** for transmission to the wireless network **12** and receives RF signals from the RF antenna **66** and forwards them to the wireless modem **62** for further processing. The RF antenna **66** provides the necessary signaling interface between the wireless network **12** and the web browser module **48** that needs to access the wireless network **12**.

The wireless modem **62** may perform necessary data encoding for the data received from the WAP browser in the web browser module **48** to prepare the data (e.g., a query message) to be sent to the wireless network **12** and eventually to the content server **20** over the Internet **18**. A corresponding decoding may be performed by the wireless modem **62** upon receipt of data (e.g., a response message from the content server **20**) from the REF transceiver unit **64** prior to sending the decoded data to the WAP browser (in the web browser module **48**) for further processing. The RF transceiver unit **64** modulates data received from the wireless modem **62** to be transmitted over an RF transmission channel linking the cell phone **10** with the wireless network **12**. This modulated data is then wirelessly transmitted to the wireless network **12** (and, hence, to the Internet **18**) by the RF antenna unit **66**. Upon reception of any data or information from the wireless network **12** (e.g., an e-mail message received over the Internet **18**), the RF antenna unit **66** forwards the REF-modulated data to the RF transceiver unit **64**, which demodulates the data and sends it to the wireless modem **62** for further processing and transfer to the WAP browser in the web browser module **48**.

FIG. **4** depicts an exemplary flowchart for an identity-blocking service provided by a cellular service provider (e.g., the service provider **16** in FIGS. **1** and **2**). Initially, at block **70**, the cellular service provider **16** may periodically receive (or track) the location information for the cell phone **10** using one of the methods mentioned hereinbefore. Here, the location information can be considered to be "in the network." Alternatively, the location information may be "in the cell phone" as discussed hereinbefore. For example, a cell phone with a built-in location identifier (e.g., the cell phone **10** with the built-in GPS receiver **56** as shown in FIG. **3**) may transmit its location information to the wireless network **12** (and, hence, to the service provider **16**) periodically, for example, every 30 seconds after the cell phone **10** is activated (or powered up) by the MS. In another embodiment, the MSC (mobile switching center) (not shown) serving the cell phone **10** may be programmed to periodically "query" the cell phone **10** to extract current location information therefrom. In both cases, the PCU **52** may be configured with appropriate software which, when executed, transmits the cell phone location information via the NIU **60** to the MSC (not shown) operated by the service provider **16**.

The service provider **16** may also receive the MS's identity information (e.g., name, address, services subscribed to, etc.) at block **72** when, for example, the MS first signs up for the cellular services provided by the SP **16**. Alternatively, the MS may store subscriber's identity information in the memory unit **46** of the cell phone **10**. The browser software in the web browser module **48** may be configured to transmit MS's stored identity information to the wireless network **12** whenever, for example, the MS initially accesses the Internet **18**. The identity information received from the cell phone **10** may be temporarily stored in the MSC or any other convenient location within the cellular service provider's network.

The cellular service provider **16** may offer the cellular phone operator's location information to a third party advertiser (e.g., a web banner advertiser) for a fee, which may be fixed or based on per-delivery (of location information). In the identity-blocking service illustrated in FIG. **4**, the service provider **16** first determines at block **74** whether any third party is qualified to receive the MS's location information. The third party, as discussed hereinbefore, may be a web advertiser who is desirous of sending web banner advertisements to the web browser module **48** to be displayed on the display screen **28**. The contact data (e.g., web address, e-mail address, etc.) regarding each qualified third party receiver of location information may be stored by the SP **16** in appropriate database maintained thereby. The SP **16** may then transmit (at block **76**) MS's location information to the third party advertiser without disclosing the MS's identity to the third party. In other words, the web advertiser operating the content server **20** may only know the location of the MS, but may not know the identity of the MS, i.e., who the MS is. The SP **16** may also charge a fee to the MS for blocking MS's identity from being disclosed.

Upon receiving the location information about the MS, the third party advertiser may search the database **22** to obtain advertisements for business establishments at or near the MS's current physical location. For example, when the cell phone operator approaches the location **14**, e.g., a shopping mall (as shown in FIG. **1**), the web advertiser may select advertisements for various shops in the mall. Thereafter, at block **78**, the web advertiser may send over the Internet **18** (and via the wireless network **12**) location-specific advertisements to the web browser **48** in the cell phone **10**. The advertisements may be displayed as Internet banner advertisements on the display screen **28**. Alternatively, one or more of the advertisements may be in a digital audio format and may be heard by the cell phone operator when the digital audio file (e.g., a streaming audio file) carrying the respective advertisement is executed by the PCU **52** and the resulting audio is played through the speaker **32**. The web advertiser may continue sending different location-specific advertisements to the cell phone **10** as long as the cell phone **10** is "connected" to the Internet **18** (i.e., as long as the MS is surfing or access-

ing the Internet **18**). The web advertiser may discontinue further advertisement transmission once the cell phone **10** is "disconnected" from the Internet **18** as indicated by block **80** in FIG. **4**.

Protection of unnecessary dissemination of identity information of the cell phone operator may be desirable to prevent misuse or to preserve privacy of the operator. When the identity information is stored in the cell phone **10**, the web browser module **48** or the PCU **52** may be configured with appropriate software that gives the cell phone operator an option whether to block the transmission of the operator's stored identity information to a remote web server (e.g., the content server **20**) when the cell phone operator queries or accesses the remote server for information. In such a case, the mobile subscriber may provide an indication to the SP **16** during or prior to a phone call that the identity information may not be forwarded over the Internet **18** to the content server **20**. In one embodiment, the SP **16** may not have mobile subscriber's identity information pre-stored therewith. Here, the cell phone **10** (through, e.g., the PCU **52**) may supply the identity information to the SP **16** on a per-call basis and instruct the SP **16** to block further transmission of the identity information unless indicated otherwise by the MS.

The SP **16** decides at block **82** whether it wishes to send location-specific messages to the cell phone **10**. In one embodiment, there may not be any third party receiver of location information, but the cellular service provider **16** itself may utilize the received mobile subscriber's location information to target location-specific advertisements to the cell phone **10**. Alternatively, the SP **16** may also send location-specific advertisements or messages to the cell phone **10** even when there is a third party advertiser. For example, the content server **20** may send textual messages to the cell phone **10**, whereas the service provider **16** (through the corresponding mobile switching center) may send audio messages to the cell phone **10**. Both types of messages may be sent intermittently to the cell phone **10**. This is depicted by block **84** in FIG. **4**. When the SP **16** identifies the cell phone **10** operating in its system, the service provider **10** may target location-specific advertisements to the cell phone **10** according to a method disclosed in the U.S. Pat. No. 5,588,042 (issued on Dec. 24, 1996), which is incorporated herein by reference in its entirety. It is noted that the service provider **16** may not transmit any location-specific advertisements or messages to the cell phone **10**. In any event, the process ends at block **80**.

In the discussion given hereinabove with reference to FIG. **4**, it is noted that instead of the service provider **16** initiating transmission of location-specific messages to the cell phone **10**, the MS may "query" the SP **16** for location-specific information. For example, the MS may send a query message to a special mobile number assigned by the SP **16**. The query message may be a textual or a voice message. In case of a voice message, appropriate speech recognition software may be provided at the location processing the MS's query to identify the content of the MS's request. The SP **16** may, in response, send pre-recorded location-specific data in, for example, synthesized voice messages to the cell phone **10**. Alternatively, the query message may contain no data, but the origination of the query message to the dedicated mobile number may indicate to the SP **16** that the MS has requested location-based information. The SP **16** may offer such request-response service to mobile subscribers for additional fees.

FIG. **5** shows an exemplary flowchart for an identity-blocking service provided by an Internet or web advertiser (e.g., the web advertiser operating the content server **20**). In the identity-blocking service illustrated in FIG. **5**, the web advertiser or any other third party advertiser blocks the mobile subscriber's identity information (if available) whenever the advertiser sends any location-specific message or advertisement to the cell phone **10**. As discussed hereinbefore, the term "web advertiser" may include any third party (i.e., other than the wireless service provider **16**) advertiser or message distributor over a communication network (e.g., the Internet **18**) including, for example, the web advertiser operating the content server **20**. The message from the web advertiser may be in a text form or in a digital audio file format—both with or without images. Further, the advertisement may appear on the screen **28** as a web banner advertisement.

At block **86**, the web advertiser receives current physical location information of the cell phone **10**. The web advertiser may purchase the location information from the SP **16** for each web access by the MS. Alternatively, the web advertiser may pay a flat sum of money to receive the MS's location information during a fixed duration (e.g., six months). In one embodiment, the web advertiser may receive the location information directly from the MS. Here, the MS may transmit the MS's current physical location information to the web advertiser's server (e.g., the content server **20**) prior to or along with the query message (as shown in FIG. **2**) from the cell phone **10**. The web advertiser may also receive the IP (Internet Protocol) address for the cell phone **10** as part of the location information (from the SP **16** or from the MS). The IP address may be used to identify the MS as discussed hereinbelow. In an alternative embodiment, the web advertiser may even obtain the MS's current physical location information from another web advertiser.

The web advertiser may offer a service that provides location-specific advertisements, information or messages to the service's subscribers. In one embodiment, the MS operating the cell phone **10** may subscribe to this service, which may require the subscriber to provide its location information to the content server **20** and receive the requested location-specific data in return. For example, the MS may send a message (using the cell phone **10**) to the content server **20** informing the server **20** of the MS's current location and asking the server to provide information about nearby movie theatres and directions thereto.

It is noted that the web advertiser may require each new visitor (e.g., the MS) to its web site to register and provide basic identity information (e.g., name, address, e-mail, etc.) for the visitor. Further, the web advertiser may "capture" the IP (Internet Protocol) address of the visitor's computer (here, the IP address for the cell phone **10**) when the visitor initially visits the advertisers website. The web advertiser may correlate the MS's IP address with the MS's identity information and store them in, for example, the database **22**. Thereafter, upon receiving the cell phone location information (block **86**) containing the MS's IP address, the web advertiser determines (at decision block **88**) whether any identity information about the MS (and associated with the received IP address) is available therewith. The determination may be performed by appropriate software in, for example, the content server **20**. The software may receive the IP address from the web browser module **48** when the cell phone **10** accesses the content server **20** over the Internet. Thereafter, the software may search the database **22** to identify the MS associated with the received IP address. In one embodiment, the web advertiser may receive the MS's identity information and associated IP address for the cell phone **10** from another web advertiser under, for example, an information-sharing agreement between the web advertisers.

The software in the content server **20** may also determine whether any advertisement preferences have been stored for

the MS in the database **22** (decision block **90**). At the time of registering or at any time thereafter, the MS may enter or update the MS's identity profile to include one or more preferences. For example, the MS may indicate a preference not to receive any advertisement from an automobile dealer even when the advertisement from the automobile dealership is a qualified location-specific advertisement. In other words, using the preference option, the MS may instruct the content server **20** to not transmit any automobile-related advertisement even when the automobile merchant is in the physical vicinity of the MS. Such preferences may be specified on the web advertiser's website for selection by the user (here, the MS). Alternatively, the content server **20** may provide the MS with an option to specify a limited number (e.g., five) of preferences that the content server **20** may take into account while selecting which location-specific advertisements to be sent to the cell phone **10**. In one embodiment, the web advertiser (through the content server **20**) may transmit a questionnaire to the MS to request input from the MS regarding what type of advertisements or messages the MS would like to receive from the web advertiser.

In the absence of identity information for the MS or in the absence of any preferences registered for the MS, the web advertiser may select, at block **92**, location-specific advertisements for the MS based on the cell phone location information received at block **86**. In one embodiment, the selection of the location-specific data, messages or advertisements may be performed by specific software in the content server **20**. The software may search the database **22** and compare the received location data with the location information stored in the database **22** to identify or select appropriate messages to be sent over the Internet **18** to the cell phone **10**. When the MS has registered one or more preferences with the web advertiser, the web advertiser may optionally select location-specific advertisements based on the MS's preferences as depicted by dotted block **94**. Thus, the web advertiser may send location-specific advertisements that are also user-specific (or, user-preference-based). Alternatively, the web advertiser may send user-specific advertisements (whether based on user preferences or not) that are also location-specific.

Finally, at block **96**, the web advertiser (i.e., the content server **20** operated by the web advertiser) may send one or more of the selected location-specific advertisements to the cell phone **10** without sending any indication of the mobile subscriber's identity therewith. Similarly, the web advertiser may also send user-specific advertisements to the cell phone **10** without sending any indication of MS's identity therewith. In other words, the content server **20** may block any MS identity information from further transmission over the Internet **18**. Any interception of the location-specific advertisement or message sent from the content server **20** may serve to identify the present location of the receiver of the message, but not the identity of the receiver (i.e., who the receiver is). Protection of identity information of the MS may be useful when data packets get misdirected or intercepted over the Internet **18**. Additionally, assurance of the protection of the MS's private information may allow the MS to frequently access the web advertiser's website, thereby generating more "hits" (and, hence, more advertising revenue) to the website. The web advertiser may even charge a fee to the MS for blocking MS's identity information from further dissemination. The identity-blocking process illustrated in FIG. **5** terminates at block **98**.

As mentioned hereinbefore, the SP **16** may periodically send the MS's location information to the web advertiser (i.e., to the content server **20**). However, in one embodiment, the SP **16** may send an indication (e.g., a pre-designated digit or code) to the server **20** when the location of the MS is continuously changing, i.e., when the MS is in motion or driving a car. Here, the MS may not intend to stop by at a particular location **14** (e.g., a shopping mail) and, therefore, it may not be desirable for the web advertiser to initiate any location-specific advertising. However, the web advertiser may still send location-specific advertisements (without MS identity information) to the cell phone **10** in response to any queries initiated by the MS.

As noted hereinbefore, the MS may be moving from one location to another (e.g., from one shopping mall to another). In one embodiment, the frequency with which the web advertiser may update or change the location-specific advertisements being sent to the cell phone **10** may depend on the frequency with which the web advertiser receives updated location information from the SP **16** serving the MS. Due to limited radio frequency bandwidth, the MS location determination by the SP **16** may not be continuous. Furthermore, the frequency of location determination may depend on the number of cellular phone operators active within the cellular service provider's network and for whom location determination has to be made by the SP **16**.

In one embodiment, the identity blocking service provided by the cellular service provider **16** (as illustrated in FIG. **4**) or a similar service provided by the web advertiser (as depicted in FIG. **5**) may offer identity-blocking as a default option. However, the MS may be given an activation code (e.g., *25) that the MS may transmit from the cell phone **10** to remove the identity-blocking option. The SP **16** may even allow the MS to enter the activation code over the Internet **18** by visiting SP's website. Thus, the cellular service provider **16** may receive the activation code from the cell phone **10** at any time after the cell phone **10** is active (or, "turned ON"). Thereafter, the SP **16** may not block the MS's identity information and send the identity information along with the location information to the third party advertiser. Similarly, the web advertiser may also receive the activation code from the cell phone **10** instructing the content server **20** to release the MS's identity information with the location-specific messages. In one embodiment, the user (here, the MS) may need to enter the activation code on a per message or per website access basis. In another embodiment, the activation code may permanently remove the identity blocking option until the user revokes the user's choice.

In alternative embodiments of identity-blocking services by the cellular service provider **16** (FIG. **4**) or by the web advertiser (FIG. **5**), the identity-blocking option may be initially absent or disabled. In other words, the SP **16** or the web advertiser may not block MS's identity as a default service option. Instead, in these embodiments, the MS may be given a deactivation code (e.g., *34) that the MS may send to the SP **16** or the web advertiser to "enable" the identity-blocking option. Thus, after the MS "enables" the identity-blocking option, the SP **16** or the web advertiser may start blocking the MS's identity information as discussed hereinbefore with reference to FIGS. **4** and **5** respectively.

FIG. **6** is an exemplary flowchart for a location-blocking service provided by a cellular service provider (e.g., the service provider **16** in FIG. **2**). In the location-blocking service, the SP **16** may prevent transmission of the MS's location information to the third party advertiser, but may not block the transmission of the MS's identity information. Thus, the third party may "know" who is the receiver of the advertisements, but may not know where that receiver is located. A location-blocking option may be desirable for the MS who wants to receive only a selected group of messages regardless of the

MS's location (e.g. messages informing the MS of the prices of stocks held by the MS). Here, the data, messages or advertisements to be sent to the MS may not depend on the MS's physical location.

At block **100**, the cellular service provider **16** may receive physical location information for the cell phone **10** operated by the MS. The cellular service provider **16** may receive the location information as discussed hereinbefore with reference to block **70** in FIG. **4**. Also, the SP **16** may also receive MS's identity information at block **102** in a manner similar to that described hereinbefore with respect to block **72** in FIG. **4**. Therefore, further discussion for blocks **100** and **102** is omitted for the sake of brevity.

At decision block **104**, the SP **16** determines whether the SP **16** has implemented the option of blocking the MS's identity (e.g., to comply with a government regulation) or whether the MS has indicated to the SP **16** (using, e.g., a pre-assigned code or symbol) to block the MS's identity information from being sent to a third party receiver. The determination function at block **104** may be performed by the content server **20** or by the MSC (not shown) serving the cell phone **10**. Appropriate program code may be executed in the content server **20** or the MSC to make the determination at block **104**. The SP **16** may also determine, at block **106**, whether any third party advertiser or receiver of identity information has signed up or subscribed to receive the MS's identity information. As noted hereinbefore, the third party advertiser (e.g., a web banner advertiser) may pay predetermined fees on a per-user basis, i.e., for each new user identity information sent by the SP **16**. Alternatively, the third party advertiser may pay a fixed amount of money for a given duration (e.g., six months) irrespective of the number of user whose identity information is received thereby. Further, the SP **16** may charge a fee to the MS for blocking MS's location information from further transmission. The process depicted in FIG. **6** terminates at block **108** in the event that there is no third party receiver of the MS's identity information or when the transmission of the MS's identity information is blocked (by the MS or by the SP **16** itself).

In the absence of any blocks placed on transmission of the MS's identity information and when a third party advertiser is available to receive the MS's identity information, the SP **16** may send, at block **110**, the MS's identity information to the third party advertiser without disclosing to the third party advertiser the current physical location of the cell phone **10** being operated by the MS, thereby preventing the third party advertiser from knowing the physical location of the MS. In case of an arrangement similar to that in FIG. **2**, the SP **16** may provide the identity information to a web advertiser (i.e., to the content server **20** operated by the web advertiser) as one or more TCP/IP data packets sent over the Internet **18**. Alternatively, the SP **16** may send MS's identity information to the third party advertiser over a phone (e.g., as a voice mail) when a telephone connection (e.g., a wireline or a wireless telephone connection) exists between the SP **16** and the third party advertiser.

As noted hereinbefore, the MS's identity information may include, among other things, the MS's name, gender, age, profession, education, mailing address, etc. This information may then be used by the third party advertiser to select which advertisements or messages are to be sent to the MS. However, as noted hereinbefore, the MS may request specific information (e.g., prices of stocks held by the MS) from the third party advertiser and may also instruct the SP **16** not to disclose the MS's physical location while sending the MS's identity information to the third party advertiser. Here, the third party advertiser does not need to make any decision as to which advertisements to send to the MS. Instead, the third party advertiser may simply send the requested information from the database **22**.

Thus, upon receiving the MS's identity information, the third party advertiser (e.g., a web advertiser) may optionally send user-specific advertisements, messages or data to the cell phone **10** as indicated by the dotted block **112**. The web advertiser may have MS's user profile stored in the database **22** when, for example, the MS initially signed-up for user-specific message delivery service offered by the web advertiser. In the absence of a stored user profile, the content server **20** may search the database **22** with certain predetermined criteria (e.g., age, gender, profession, etc.) present in the identity information received from the SP **16** to select appropriate advertisements or messages to be sent to the MS. For the embodiment illustrated in FIG. **2**, the third party advertiser (here, a web advertiser) may deliver advertisements or messages to the MS as TCP/IP data packets sent over the Internet **18**. In one embodiment, the third party advertiser may dial the mobile number for the cell phone **10** and deliver audio messages to the cell phone **10**. The location-blocking service may terminate at block **108** as illustrated in FIG. **6**.

The third party advertiser may continue delivering user-specific messages, data or commercial advertisements in the location-blocking service illustrated in FIG. **6** for a fixed duration (e.g., two minutes). The length of the duration may be predetermined or may vary with user traffic. Thus, if the number of users the third party advertiser has to cater to increases, the rate at which old advertisements are replaced and new advertisements are sent to the users may decrease. In one embodiment, the third party advertiser may continue delivering user-specific advertisements to the MS until the MS turns off or deactivates the cell phone **10**, or until the cell phone **10** is "disconnected" from the Internet **18**.

FIG. **7** illustrates an exemplary flowchart for a location-blocking service provided by an Internet or web advertiser. The web advertiser receives MS's identity information at block **114**. The web advertiser may receive this identity information in one of many ways (e.g., through purchase from the SP **16** or from any other web advertiser, or from MS when MS initially signs-up or subscribes to the location-blocking message delivery service from the web advertiser, etc.) discussed in detail hereinbefore with reference to block **88** in FIG. **5**. Additional discussion therefore is omitted for the sake of brevity.

At decision block **116**, the web advertiser determines (using, e.g., the content server **20**) whether any current location information for the MS (i.e., for the cell phone **10** operated by the MS) is available in the database **22**. The web advertiser may receive the MS's current physical location information in one or many ways (e.g., from the SP **16** on a subscription-basis, from the MS's cell phone **10**, from another web advertiser, etc.) discussed in detail hereinbefore with reference to block **86** in FIG. **5**. Therefore, further discussion for block **116** is omitted for the sake of brevity. Similarly, detailed discussion for decision block **118** (regarding the web advertiser's determination whether one or more preferences are stored in the database **22** for the MS) is omitted in view of discussion hereinbefore with reference to block **90** in FIG. **5**. However, it is noted that the MS may register location-specific preferences with the web advertiser. For example, the MS may prefer to receive advertisements only from boat rental companies when the MS is present at or near a beach. Thus, the MS may qualify the MS's user preferences for specific regions or locations. In this situation (i.e., when the MS is at or near a beach), the web advertiser may not send

advertisements from the restaurants on the beach even if the MS generally accepts advertisements from restaurants when in other locations.

When the cellular phone operator's (i.e., the MS's) location information is not available with the web advertiser or when no preference for the MS is registered with the web advertiser, the web advertiser may select, at block **120**, user-specific (i.e., MS-specific) advertisements based on the identity information for the MS. Appropriate software in the content server **20** may search the database **22** to identify MS-specific advertisements. The software may use parameters such as, for example, age, employment status, gender, etc., to determine which advertisements to select from the database **22** for a given user. However, if one or more preferences for the MS are registered with the web advertiser (in, e.g., the database **22**), then the web advertiser may select (from the database **22**) MS-specific advertisements, messages or data based on those MS preferences as depicted by block **122**. In one embodiment, the preference-based message selection may be optional as indicated by the dotted block **122**. In other words, the web advertiser may ignore MS preferences in selecting user-specific advertisements from the database **22**. A similar discussion for location-specific advertisements based on MS's preferences is given hereinbefore with reference to block **94** in FIG. **5**.

At block **124**, the web advertiser sends user-specific (i.e., MS-specific) advertisements, messages or data to the cell phone **10** without sending any indication of the MS's location therewith. The function at block **124** is similar to that described hereinbefore with reference to block **96** in FIG. **5**, except that in the identity-blocking service depicted in FIG. **5**, the identity information for the MS is blocked by the web advertiser instead of the location information as at block **124** in FIG. **7**. Blocking of a cell phone operator's location information may be desirable, for example, for privacy reasons and for preventing unsolicited advertisements or messages from business establishments in the vicinity of the MS's current physical location. The web advertiser may even charge a fee to the MS for blocking MS's location information from further dissemination. The location-blocking service depicted in FIG. **7** terminates at block **126**.

It is noted that the discussion given hereinbefore (with reference to FIGS. **4** and **5**) about user-controlled activation or deactivation of identity-blocking option (using a code or a symbol) may equally apply to the location-blocking option (i.e., to block or to allow the transmission of the user's location information) described hereinbefore with reference to FIGS. **6** and **7**. Therefore, further elaboration of user-controlled activation or deactivation of location-blocking option for FIGS. **6** and **7** is not provided herein.

In one embodiment, blocking of the MS's identity and/or location may be performed by the WAP proxy/server **24** instead of the SP **16**. Here, the WAP server **24** may be configured with appropriate software that can detect and block relevant information (received from the SP **16** or from the cell phone **10**) from being transmitted to the third party advertiser. The SP **16** or the cell phone **10** may not block any MS-specific identity or location information from further transmission. Instead, the SP **16** may send an appropriate numerical code, symbol or any other indication to identify to the WAP server **24** which of the message(s) originating from the SP **16** or from the cell phone **10** contains MS's identity and/or location information. The WAP server **24** may identify the information to be blocked and prevent that information from being sent to the third party advertiser (e.g., a web advertiser).

It is noted that various identity-blocking and location-blocking services described hereinbefore with reference to FIGS. **4-7** may "unblock" transmission of respective identity and/or location information when the MS dials an emergency phone number (e.g., "911") or indicates a desire to access an emergency service provider (e.g., a fire station, a hospital or the police). For example, the SP **16** may not block the MS's identity (e.g., as shown at block **76** in FIG. **4**) when the MS dials "911". Here, the SP **16** may send location as well as identity information for the MS to the emergency service provider (e.g., police) as indicated by the dialed digits (i.e., digits "9", "1", "1"). Similarly, the WAP server **24** or the web browser module **48** (FIG. **3**) may not block the MS's identity and/or location information when the MS places an emergency phone call.

The foregoing describes exemplary embodiments of various location-blocking and identity-blocking services that may be commercially offered by a cellular service provider or by an advertiser (e.g., a web advertiser). In the identity-blocking service, the service promoter may disclose the current physical location of a mobile subscriber (i.e., a cellular phone operator) to a third party (e.g., a web advertiser) subscribing to the identity-blocking service. However, the service promoter may not send any identity information for the mobile subscriber to the third party. On the other hand, in the location-blocking service, the service promoter may disclose the mobile subscriber's identity information to the third party, but not the current physical location of the mobile subscriber. Blocking of the mobile subscriber's identity or location information may be desirable for privacy reasons, to comply with a government regulation, or to implement a telecommunication service option selected by the mobile subscriber. Information blocks may be implemented in hardware and/or software, and at various places in a communication arrangement. However, in the case of the mobile subscriber requesting emergency help, the service promoter may not block identity and/or location information. Instead, the service promoter may send all such information to the emergency service provider (e.g., the police or a hospital).

While several embodiments of the invention have been described, it should be apparent, however, that various modifications, alterations and adaptations to those embodiments may occur to persons skilled in the art with the attainment of some or all of the advantages of the present invention. It is therefore intended to cover all such modifications, alterations and adaptations without departing from the scope and spirit of the present invention as defined by the appended claims.

We claim:

1. A method for providing a feature blocking feature service, the method comprising:

obtaining, from a wireless communication device:

identity information identifying a user operating the wireless communication device;

location information indicating a location of the wireless communication device; and

a service blocking preference, wherein the service blocking preference comprises one or more of:

an indication not to block the identity information;

an indication not to block the location information; and

an indication to block the identity information; and

an indication to block the location information;

receiving, from another entity, a request for at least one of the identity information and the location information;

if the other entity comprises an emergency service provider, transmitting to the emergency service provider the at least one of the identity information and the location information; and

if the other entity does not comprise the emergency service provider, transmitting:

the identity information, if the service blocking preference indicates that the identity information is not blocked;

the location information, if the service blocking preference indicates that the location information is not blocked; and

neither of the location information and the identity information if the service blocking preference indicates that the identity information and the location information are blocked.

2. The method of claim **1**, further comprising charging a fee to the user for blocking the identity information if the service blocking preference indicates that the identity information is blocked.

3. The method of claim **1**, further comprising charging a fee to the user for blocking the location information if the service blocking preference indicates that the location information is blocked.

4. The method of claim **1**, wherein obtaining the location information comprises monitoring a signal transmitted by the wireless communication device and determining, based upon the signal, the location of the wireless communication device.

5. The method of claim **1**, wherein obtaining the service blocking preference comprises obtaining the service blocking preference submitted by the user in response to a request for the service blocking preference.

6. A network for providing a feature blocking service using data stored at a database, wherein the network is configured to:

obtain location information indicating the location of a wireless communication device and identity information indicating the identity of a user associated with the wireless communication device;

receive, from another entity, a request for the location information and the identity information;

examine a service blocking preference associated with the user, the service blocking preference being stored at the database and comprising at least one of:

an indication not to block the identity information;

an indication not to block the location information; and

an indication to block the identity information; and

an indication to block the location information;

if the other entity comprises an emergency service provider, transmitting the location information and the identity information to the other entity; and

if the other entity does not comprise the emergency service provider, transmitting one or more of:

the identity information, if the service blocking preference indicates that the identity information is not blocked;

the location information, if the service blocking preference indicates that the location information is not blocked; and

neither of the location information and the identity information if the service blocking preference indicates that the identity information and the location information are blocked.

7. The network of claim **6**, wherein the other entity comprises an advertising entity.

8. The network of claim **6**, wherein network is further configured to charge a fee to the user for blocking the identity information if the service blocking preference indicates that the identity information is blocked.

9. The network of claim **6**, wherein the network is further configured to charge a fee to the user for blocking the location information if the service blocking preference indicates that the location information is blocked.

10. The network of claim **6**, wherein the network is configured to obtain the location information by obtaining location information determined at the wireless communication device using a GPS receiver.

11. The network of claim **6**, wherein the network is configured to obtain the location information by monitoring a signal transmitted by the wireless communication device and determining, based upon the signal, the location of the wireless communication device.

12. The network of claim **6**, wherein the network is further configured to send a query to the wireless communication device, the query comprising a request for the service blocking preference.

13. The network of claim **12**, wherein the network is further configured to receive, from the wireless communication device, a response indicating the service blocking preference.

14. The network of claim **13**, wherein the network is further configured to store the service blocking preference at the database.

15. The network of claim **14**, wherein the network is further configured to retrieve, from the database, the service blocking preference.

16. A wireless communication device comprising:

a location component; and

a memory unit configured to store identity information associated with a user of the device and instructions executable by a processing and control unit to make the device operable to:

determine location information comprising an indication of the location of the device;

store the location information at the memory unit;

receive, from an entity in communication with the device, a request for the location information and the identity information;

obtain a service blocking preference, wherein the service blocking preference comprises one or more of:

an indication not to block the identity information;

an indication not to block the location information; and

an indication to block the identity information; and

an indication to block the location information;

if the entity comprises an emergency service provider, transmitting the location information and the identity information to the entity; and

if the entity does not comprise the emergency service provider, transmitting, to the entity, one or more of:

the identity information, if the service blocking preference indicates that the identity information is not blocked;

the location information, if the service blocking preference indicates that the location information is not blocked; and

neither of the location information and the identity information if the service blocking preference indicates that the identity information and the location information are blocked.

17. The device of claim **16**, wherein:

the location component comprises a Global Positioning System (GPS) receiver; and

determining the location information comprises determining, at the GPS receiver, the location information.

18. The device of claim **16**, wherein:

the service blocking preference is stored at the memory unit; and

obtaining the service blocking preference comprises retrieving the service blocking preference from the memory unit.

19. The device of claim **16**, wherein the device is configured to determine the location information at pre-determined time intervals.

20. The device of claim **16**, wherein the device is configured to transmit the service blocking preference to the network for storage at a database in communication with the network.

* * * * *