



US006115086A

[54] AUTOMOTIVE DISPLAY UNIT

[75] Inventor: John B. Rosen, Eugene, Oreg.

[73] Assignee: Rosen Products LLC, Eugene, Oreg.

[\*] Notice: This patent is subject to a terminal disclaimer.

[21] Appl. No.: 09/277,686

[22] Filed: Mar. 26, 1999

Related U.S. Application Data

[63] Continuation of application No. 08/884,445, Jun. 27, 1997, and a continuation of application No. 08/777,613, Dec. 31, 1996, and a continuation-in-part of application No. 29/083,926, Feb. 18, 1998, which is a continuation of application No. 29/058,538, Aug. 16, 1996.

[51] Int. Cl.<sup>7</sup> ..... H09H 5/64

[52] U.S. Cl. .... 348/837; 296/37.7; 307/10.1; 353/13

[58] Field of Search ..... 312/7.2, 245; 248/837, 248/918, 921, 923, 919; 224/311; 244/118.5, 1 R; 296/37.7, 37.8; 353/12, 13; 345/905; 361/682; 307/9.1, 10.1; 455/345, 347

[56] References Cited

U.S. PATENT DOCUMENTS

D. 285,684 9/1986 Akita et al. .

D. 293,579 1/1988 Davis .

D. 294,495 3/1988 Nissley .

D. 299,491 1/1989 Masuda .

D. 337,103 7/1993 Harper .

D. 356,081 3/1995 Naito et al. .

D. 366,067 1/1996 Mowrey .

D. 395,458 6/1998 Smith et al. .

4,195,431 4/1980 Neufeld .

4,383,626 5/1983 Weinblatt .

4,438,458 3/1984 Munscher .

4,504,910 3/1985 Araki et al. .

4,516,157 5/1985 Campbell .

4,620,808 11/1986 Kurtin et al. .

4,630,821 12/1986 Greenwald .

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

131 988 1/1985 European Pat. Off. .

365 290 4/1990 European Pat. Off. .

2 544 675 4/1983 France .

38 20 510 12/1989 Germany .

41 18 711 12/1992 Germany .

60-51087 3/1985 Japan .

60-51088 3/1985 Japan .

60-203526 10/1985 Japan .

61-77542 4/1986 Japan .

61-282139 12/1986 Japan .

62-231847 10/1987 Japan .

63-219440 9/1988 Japan .

1-300775 12/1989 Japan .

2-7082 1/1990 Japan .

2-31577 2/1990 Japan .

2-149083 6/1990 Japan .

3-10476 1/1991 Japan .

4-63739 2/1992 Japan .

4-185547 7/1992 Japan .

4-368245 12/1992 Japan .

5-24486 2/1993 Japan .

5-50883 3/1993 Japan .

5-131879 5/1993 Japan .

5-185878 7/1993 Japan .

6-92187 4/1994 Japan .

6-144009 5/1994 Japan .

2 276 059 9/1994 United Kingdom .

Primary Examiner—Peter M. Cuomo


Assistant Examiner—Jerry A Anderson

Attorney, Agent, or Firm—Kolisch, Hartwell, Dickinson, McCormack & Heuser

[57] ABSTRACT



A display unit is provided, the display unit including a housing configured for mounting to the ceiling of an automobile, and a screen mounted on the housing for pivot about a first axis between a stowed position wherein the screen is embedded in the ceiling and a deployed position wherein the screen projects from the housing to reveal a viewing surface of the screen. The screen also is pivotal about a second axis transverse to the first axis, promoting viewability of the screen.



29 Claims, 4 Drawing Sheets








## U.S. PATENT DOCUMENTS

4,633,323	12/1986	Haberkern et al. .	5,121,200	6/1992	Choi .
4,635,110	1/1987	Weinblatt .	5,144,290	9/1992	Honda et al. .
4,647,980	3/1987	Steventon et al. .	5,145,128	9/1992	Umeda .
4,665,430	5/1987	Hiroyasu .	5,148,282	9/1992	Sedighzadeh .
4,708,312	11/1987	Rohr .	5,161,028	11/1992	Kawata et al. .
4,735,467	4/1988	Wolters .	5,173,686	12/1992	Fujihara .
4,742,478	5/1988	Nigro, Jr. et al. .	5,177,616	1/1993	Riday .
4,749,364	6/1988	Arney et al. .	5,179,447	1/1993	Lain .
4,787,040	11/1988	Ames et al. .	5,195,709	3/1993	Yasushi .
4,814,896	3/1989	Heitzman et al. .	5,222,690	6/1993	Jeffords .
4,824,159	4/1989	Fluharty et al. .	5,233,426	8/1993	Suzuki et al. .
4,836,486	6/1989	Vossoughi et al. .	5,239,700	8/1993	Guenther et al. .
4,843,477	6/1989	Mizutani et al. .	5,243,417	9/1993	Pollard .
4,866,515	9/1989	Tagawa et al. .	5,281,985	1/1994	Chan .
4,867,498	9/1989	Delphia et al. .	5,287,191	2/1994	Suzuki et al. .
4,870,676	9/1989	Lewo .	5,289,321	2/1994	Secor .
4,883,242	11/1989	Becker et al. .	5,305,970	4/1994	Porter et al. .
4,910,591	3/1990	Petrossian et al. .	5,311,302	5/1994	Berry et al. .
4,915,461	4/1990	Kingsborough et al. .	5,333,416	8/1994	Harris .
4,947,296	8/1990	Takeuchi et al. .	5,335,076	8/1994	Reh et al. .
4,982,996	1/1991	Vottero-Fin et al. .	5,338,081	8/1994	Young et al. .
4,983,951	1/1991	Igarashi et al. .	5,359,349	10/1994	Jambor et al. .
4,988,140	1/1991	Van Order .	5,362,144	11/1994	Shioya et al. .
4,995,680	2/1991	Miruri .	5,397,160	3/1995	Landry .
5,009,384	4/1991	Gerke et al. .	5,467,106	11/1995	Salomon .
5,021,922	6/1991	Davis et al. .	5,469,298	11/1995	Suman et al. .
5,027,200	6/1991	Petrossian et al. .	5,547,248	8/1996	Marechal .
5,034,996	7/1991	Carey et al. .	5,574,443	11/1996	Hsieh .
5,061,996	10/1991	Schiffman .	5,583,735	12/1996	Pease et al. .
5,076,524	12/1991	Reh et al. .	5,743,487	4/1998	Rice .
5,096,271	3/1992	Portman .	5,775,762	7/1998	Vitito .
5,096,287	3/1992	Kakinami et al. .	5,822,023	10/1998	Suman et al. .... 348/837
5,111,289	5/1992	Lucas et al. .	5,927,784	7/1999	Vitito .
			5,946,055	8/1999	Rosen .









**AUTOMOTIVE DISPLAY UNIT****CROSS REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 08/884,445, filed Jun. 27, 1997 of John B. Rosen for a DISPLAY UNIT. This application also continues from U.S. patent application Ser. No. 08/777,613, filed Dec. 31, 1996 of John B. Rosen for PERSONAL VIDEO SYSTEM. The subject matter of these applications are incorporated herein by this reference. This application is also a continuation-in-part of U.S. Design patent application Ser. No. 29/083,926 of John B. Rosen for a CEILING-MOUNTED MONITOR SYSTEM, filed on Feb. 18, 1998, which continues from U.S. Design patent application Ser. No. 29/058,538 of John B. Rosen for a CEILING-MOUNTED MONITOR SYSTEM filed on Aug. 16, 1996.

**TECHNICAL FIELD**

The present invention relates generally to display units, and more particularly, to a display unit configured for use in presenting a viewing surface to occupants of an automobile such as a car, a truck, a sport utility vehicle (SUV), or a passenger van.

**BACKGROUND ART**

Automotive manufacturers have long sought to make passengers as comfortable as possible during travel, focusing both on physical comfort and on the passenger's entertainment. For example, vehicle sound systems have become standard accessories in most cars and trucks. In recent years, efforts have involved attempts to bring video technology into the passenger compartment, either in the form of a television, a computer, or a video game display.

Unfortunately, display units have heretofore been impractical as automotive accessories due to problems in mounting conventional display units within an automobile. One problem relates to the size of most display units, it being difficult to find space for a standard-size monitor in most automobiles. Another problem arises from difficulties in placing the display unit in a position where it may be viewed by a passenger, but will not obstruct the driver's view of the road. Still another problem involves the stowability of the display unit, and its corresponding effect on passenger safety.

Known display units also have been unable to meet consumer expectations due to difficulties in providing acceptable picture quality in a package of suitable size. However, with advancements in flat-panel display technology, picture quality of smaller display units has improved dramatically. Additionally, it has become possible to separate some of the electronic circuitry from the flat-panel display, further reducing the thickness of these displays. The present invention takes advantage of these improvements by providing a stowable display unit which is suited for mounting in an interior region of an automobile without compromising picture quality.

**DISCLOSURE OF THE INVENTION**

The aforementioned goals and objectives are met by provision of a display unit which mounts to the ceiling in an interior region of a automobile, the display unit including a screen operatively mounted on the ceiling for pivotal movement about a first axis between a stowed position wherein the screen is at least partially contained within a cavity formed in the ceiling and a deployed position wherein the

screen projects downwardly from the ceiling and into the automobile passenger compartment to reveal a viewing surface of the screen. The screen also is pivotal about a second axis transverse to the first axis. When the screen is deployed, the viewing surface typically is at an angle of between approximately 45-degrees and 90-degrees from horizontal, promoting viewability of the screen.

In one embodiment, a housing is mounted on the ceiling of the vehicle, typically near the center of the passenger compartment. The screen is mounted on the housing for pivot about a first axis which typically is defined along a predetermined edge of the screen. The screen pivots between a first orientation wherein the screen is generally horizontal (the stowed position), and a second orientation wherein the screen extends downwardly from the ceiling to present the screen's viewing surface to one or more vehicle occupants (the deployed position). The screen also is pivotal about a second axis, transverse to the first axis, so as to enhance adaptability of the screen.

A cavity of predetermined shape and size is formed in the housing, the cavity being configured to at least partially contain the screen. This reduces the profile of the display unit when the unit is not in use. The profile may be reduced further by mounting the screen's control module separately from the screen, leaving a relatively thin pivotal screen. Where the cavity is embedded in the ceiling, the screen may be configured to retract entirely into the cavity such that the viewing surface is flush with the ceiling. This eliminates any impediment to the driver's view when the screen is in its stowed position.

The housing also may include a track, and a carriage which rides along the track to provide for deployment of the screen. In such an arrangement, the screen is mounted on the carriage for deployment first, by translation of the screen along the track from a first stowed position to an intermediate position, and second, by pivot of the screen about a first axis from the intermediate position to a deployed position. Again, the first axis preferably is defined along a predetermined edge of the screen.

Safety may be enhanced by provision of a break-away hinge which pivotally couples the screen with the housing to provide for emergency collapse of the screen. Such a screen preferably is pivotal in a forward direction between the stowed position and the deployed position under a first torque so as to deploy the screen, and is further pivotal in the forward direction between the deployed position and a break-away position under a higher second torque.

These and other objects and advantages of the present invention will be more readily understood after a consideration of the drawings and the detailed description of the preferred embodiment which follows.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is an isometric view of a display unit constructed in accordance with the present invention, the display unit including a screen shown in a stowed position.

FIG. 2 is an isometric view similar to that of FIG. 1, but with the screen pivoted to a deployed position.

FIG. 3 is a side view of the display unit shown in FIGS. 1 and 2.

FIG. 4 is a somewhat simplified side view of a vehicle interior illustrating use of the display unit depicted in FIGS. 1, 2 and 3.

FIG. 5 is a sectional side view of a first alternative embodiment display unit, the display unit screen being shown in successive positions by dashed lines.

FIG. 6 is an isometric view of a second alternative embodiment display unit, the display unit including a screen in a stowed position.

FIG. 7 is a side view of the display unit of FIG. 6, but with the screen in an intermediate position.

FIG. 8 is an isometric view of the display unit of FIG. 6, but with the screen in a deployed position.

FIG. 9 is an end view of the display unit of FIG. 6, the screen being deployed to reveal a track, carriage and hinge arrangement for use in deploying the screen.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT AND BEST MODE OF CARRYING OUT THE INVENTION

Referring initially to FIGS. 1 through 4, a display unit is shown for use in an interior region of an automobile 10, such display unit being indicated generally at 12. Although the invention has broad utility, the display unit is shown mounted on the ceiling 10a of the automobile, preferably overhead and generally forward of the of the passenger seating area 14 so as to accommodate viewing thereof by one or more rear-seat passengers P.

The display unit includes a generally planar mounting frame structure in the form of a housing 20, and a corresponding screen 30, which is mounted on the housing for movement between a stowed position (FIG. 1) and a deployed position (FIG. 2). In the stowed position, the screen is contained within the housing, a viewing surface 32 thereof typically facing downward into the passenger compartment. In the deployed position, the screen projects from the housing to present the screen's viewing surface to rear-seat passenger P. The screen's viewing surface thus selectively is placed in the rear-seat passenger's line-of-sight 16.

In accordance with my teachings, housing 20 will be seen to include a perimeter structure 22 having a proximal portion closer to the passenger seating area and a distal portion more remote from the passenger seating area. The housing defines a cavity 24 configured to receive the screen when the screen is placed in its stowed position. The cavity is of predetermined shape and size, typically conforming substantially to the shape and size of the viewing screen. It will be noted in FIGS. 1 and 2, for example, that cavity 24 is configured to accommodate fitted receipt of screen 30 such that the screen is fully contained within the cavity.

The housing typically is embedded in the ceiling, the automobile being provided with a ceiling recess configured for receipt of the housing. Accordingly, the perimeter structure includes a generally planar flange 26 which may be secured to the ceiling via conventional fasteners such as screws. The flange is configured to conform to the contour of the ceiling, and preferably defines the lowermost surface of the housing. The housing thus may be flush-mounted with the ceiling. Furthermore, when the screen is in its stowed position with the screen contained within the cavity, the screen's viewing surface is flush with the flange, and correspondingly, is flush with the automobile ceiling.

In the depicted embodiment, the screen is separated from a video control module 40 which directs operation of the screen. The control module typically is mounted on the perimeter structure beside the screen and is connected to the screen via a ribbon wire 42 or the like. This keeps the display unit relatively thin. In the depicted embodiment, for example, the display unit is approximately ½-inch to 1½-inches thick.

As indicated, viewing screen 30 is hinged to the housing adjacent the distal portion thereof to accommodate revers-

ible swaying thereof in an upright plane which extends both through the housing and through the passenger seating area. The screen thus is deployed by pivot thereof about a first axis A which corresponds generally to a first edge 30a of the screen. To deploy the screen, the screen is pivoted in a rearward direction to a deployed position where the screen is at an angle  $\theta$  from horizontal. In the depicted embodiment,  $\theta$  is within a range of between approximately 45-degrees and 90-degrees. This presents the screen's viewing surface to rear-seat passenger P. The screen also may be retracted to its stowed position, again by pivot of the screen about axis A. Pivot occurs about a hinge which is shown generally at 34.

The screen also is pivotal about a second axis B which is transverse to first axis A. Accordingly, the screen is adjustable by side-to-side rotation of the screen so as to selectively face the screen's viewing surface toward a rear-seat passenger. The screen's viewing surface thus may selectively be placed in the rear-seat passenger's line of sight.

The display unit also employs a locking mechanism which selectively maintains the screen in its stowed position. The locking mechanism includes a catch 52 mounted on the housing and configured to selectively engage a corresponding recess or detent 54 in the screen's second edge 30b. The locking mechanism is operable via a lever 56 which extends (and retracts) the catch for capture (and release) by recess 54.

A first alternative embodiment display unit is shown at 112 in FIG. 5, the alternative display unit differing from display unit 12 primarily by its provision of a break-away screen 130. The screen is mounted on a display unit housing 120, typically for pivot between a stowed position and a deployed position to present a viewing surface 132 to a passenger in the passenger viewing area.

As indicated, display unit 112 is suited for use in an automobile 10, the display unit typically being embedded in the automobile ceiling 10a with housing 120 flush-mounted on the ceiling. The screen is hingedly attached to the housing via break-away hinge 134 for pivot between a generally horizontal first orientation wherein the screen is at least partially contained within cavity 124, and a second orientation wherein the screen extends downwardly from the cavity to present the screen's viewing surface to a vehicle occupant for viewing.

In its first orientation (shown in solid lines), screen 130 is in a stowed position where the screen is contained within cavity 124, the screen's viewing surface facing upwardly into the cavity so as to protect the viewing surface from damage. The screen is stowed adjacent control module 140, and may be locked in place by locking mechanism 150.

Upon deployment, the screen is pivoted under a first torque from its first orientation (shown in solid lines at 130) to its second orientation (shown in dashed lines at 130') where the screen is in a deployed position with the screen extending downwardly from the ceiling at an angle  $\alpha$  of between approximately 45-degrees and 90-degrees. The screen thus is pivoted through an angle  $\phi$  which is between approximately 90-degrees and 135-degrees. The screen's viewing surface 132' faces rearwardly and downwardly toward the automobile's rear-seat passengers.

Upon application of a second, higher torque, the screen may be pivoted from the second orientation (shown in dashed lines at 130') to its third orientation (shown in dashed lines at 130'') where the screen rests against the housing in a break-away position. This is accomplished via a two-phase hinge 134 which defines a first range of motion (between the first and second orientations) wherein the screen pivots upon



## 5

application of a first torque, and a second range of motion (between the second and third orientations) wherein the screen pivots upon application of a higher second torque. As will be appreciated by those skilled in the art, the change in torque creates a soft stop with the screen in the second orientation, a feature which provides for quick deployment of the screen.

The ability of the screen to pivot to the third orientation serves as a safety feature, the screen effectively being configured to collapse in the event of an emergency. It will be understood, for example, that the depicted screen will pivot forward from the second orientation upon contact by a rear-seat passenger who is thrown forward in a collision, but only upon application of a predetermined threshold force. Similarly, the screen is configured to pivot toward the rear of the vehicle upon application of an opposite force. In either event, the screen will yield upon application of sufficient force, and thus will not act as a hard stop of the type which may cause injury to vehicle occupants.

FIGS. 6 through 9 show a second alternative embodiment of the invented display unit at 212, such display unit being adapted for use in a vehicle having a sunroof or the like. It will be noted that the display unit includes a surface-mounted housing 220. The housing defines a cavity 224 which is configured to house a screen 230 having a viewing surface 232. The screen may be deployed to reveal the viewing surface, typically first by translation in a plane defined by the screen, and second by pivot about an axis defined by hinge 234. The screen thus typically is mounted on a carriage 236 for translation along a track 238. The hinge is positioned along a predetermined edge of the screen to provide for pivot of the screen once it has been removed from the cavity.

In FIG. 6, the screen is shown in its first position where the screen is contained within the cavity in a generally horizontal orientation. From the first position, the screen is translated along track 236 to an intermediate position with the screen still in the generally horizontal orientation. FIG. 7 shows the screen in the intermediate position. Thereafter, the screen is pivoted about a first axis A to a second position where the screen extends downwardly from the cavity to present the screen to a vehicle occupant for viewing. FIG. 8 shows the screen in the second position. The screen also may be rotatable about a second axis B which is transverse to the first axis.

The screen is configured to pass forwardly in the automobile along track 236, and then to pivot rearwardly to the deployed orientation under a predetermined first torque. The screen typically will pivot downstream to an angle of between approximately 45-degrees and 90-degrees from horizontal such that the viewing surface may be readily seen by rear-seat passengers. It is possible, however, to provide for further downstream pivot of the screen under a higher second torque to provide for emergency collapse of the screen.

While the present invention has been shown and described with reference to the foregoing operational principles and preferred embodiment, it will be apparent to those skilled in the art that other changes in form and detail may be made therein without departing from the spirit and scope of the invention as defined in the appended claims.

I claim:

1. In an automobile having a passenger seating area and a ceiling, a ceiling-mounted automotive display unit comprising;

a mounting frame structure embedded in the ceiling in the ceiling in a location overhead and generally forward of the passenger seating area in the automobile;

## 6

a screen structure mounted on the mounting frame structure, the screen structure including a viewing surface selectively viewable by a passenger in the passenger seating area; and

a video control module mounted on the mounting frame structure in a location laterally spaced from the screen structure, the video control module being electrically connected to the screen structure to direct operation of the screen structure.

2. The automotive display unit of claim 1, wherein the screen structure is configured to pivot under a first torque between the stowed position and the deployed position, and the screen structure further is configured to pivot under a second torque between the deployed position and a break-away position to provide for emergency collapse of the screen structure.

3. The automotive display unit of claim 2, wherein the second torque is higher than the first torque.

4. The automotive display unit of claim 2, wherein the screen structure is generally parallel to the ceiling when the screen structure is in the break-away position.

5. The automotive display unit of claim 2, wherein the screen structure pivots forwardly in the automobile from the stowed position to the deployed position, and further pivots forwardly in the automobile from the deployed position to the break-away position.

6. The automotive display unit of claim 2, wherein the screen structure pivots rearward in the automobile from the stowed position to the deployed position, and further pivots rearwardly in the automobile from the deployed position to the break-away position.

7. The automotive display unit of claim 1, wherein the screen structure is operatively pivotally hinged to the ceiling for pivot between a stowed position and a deployed position.

8. The automotive display unit of claim 7, wherein the screen structure is hinged for pivot about a first axis defined generally parallel to a first edge of the screen structure, and is further hinged for pivot about a second axis transverse to the first axis.

9. The automotive display unit of claim 7, wherein the screen structure projects downwardly from the ceiling to occupy a generally upright plane when the screen structure is in the deployed position.

10. The automotive display unit of claim 7, wherein the screen structure is flush with the ceiling when in the stowed position.

11. The automotive display unit of claim 1, wherein the screen structure is pivotally hinged to the mounting frame structure for pivot between a stowed position and a deployed position.

12. The automotive display unit of claim 11, wherein the mounting frame structure defines a cavity configured to receive the screen structure.

13. The automotive display unit of claim 12, wherein the viewing surface is generally flush with the ceiling when the screen structure is in the stowed position.

14. The automotive display unit of claim 13, wherein the control module and the screen structure extend in substantially the same horizontal plane when the screen structure is in the stowed position.

15. In an automobile having a passenger seating area and a ceiling, a ceiling-mounted automotive display unit comprising:

a mounting frame structure mounted to the ceiling in a location overhead and generally forward of the passenger seating area in the automobile; and

a screen structure hinged to the mounting frame structure for reversibly swaying in an upright plane which

extends through the passenger seating area, the screen structure being configured to pivot about a hinge between a stowed position wherein the screen structure lies in a plane generally paralleling the mounting frame structure and a deployed position wherein the screen structure occupies a generally upright plane at an angle relative to the mounting frame structure with a disposition overhead-viewable by a passenger seated in the passenger seating area; and

a video control module mounted on the mounting frame structure separately from the screen structure in laterally spaced relation to the screen structure, but electrically connected to the screen structure to direct operation of the screen structure.

**16.** The automotive display unit of claim **15**, wherein the screen structure is hinged for pivot about a first axis defined generally parallel to a first edge of the screen structure, and is further hinged for pivot about a second axis which bisects the screen structure and is transverse to the first axis.

**17.** The automotive display unit of claim **15**, wherein the mounting frame structure is embedded in the ceiling.

**18.** The automotive display unit of claim **17**, wherein the mounting frame structure defines a cavity configured to receive the screen structure.

**19.** The automotive display unit of claim **18**, wherein the screen structure is generally parallel to the ceiling when the screen structure is in the stowed position.

**20.** The automotive display unit of claim **19**, wherein the control module and the screen structure extend in substantially the same horizontal plane when the screen structure is in the stowed position.

**21.** The automotive display unit of claim **15**, wherein the screen structure is configured to pivot under a first torque between the stowed position and the deployed position, and the screen structure further is configured to pivot under a second torque between the deployed position and a break-away position to provide for emergency collapse of the screen structure.

**22.** The automotive display unit of claim **21**, wherein the screen structure pivots forwardly in the automobile from the stowed position to the deployed position, and further pivots forwardly in the automobile from the deployed position to the break-away position.

**23.** The automotive display unit of claim **21**, wherein the screen structure pivots rearwardly in the automobile from the stowed position to the deployed position, and further pivots rearwardly in the automobile from the deployed position to the break-away position.

**24.** The automotive display unit of claim **21**, wherein the second torque is higher than the first torque.

**25.** The automotive display unit of claim **21**, wherein the screen structure is generally parallel to the ceiling when the screen structure is in the break-away position.

**26.** In an automobile having a passenger seating area and a generally planar ceiling, an above-seat-level, ceiling-mounted automotive display unit comprising:

a generally planar mounting frame structure joined with the ceiling in a location overhead and generally forward of the passenger seating area in the automobile, the mounting frame structure being joined generally co-planarly with the ceiling and having a proximal portion closer to the passenger seating area and distal portion more remote from the passenger seating area;

a generally planar screen structure hinged to the mounting frame structure adjacent the distal portion of the mounting frame structure for reversibly swaying in an upright plane, extending both through the mounting frame structure and the passenger seating area, the screen structure being hinged to the mounting frame structure via a hinge configured to provide for pivot of the screen structure between a stowed position wherein the screen structure lies in a plane generally paralleling the mounting frame structure and a deployed position wherein the screen structure occupies a generally upright plane which lies at an angle relative to the mounting frame structure with a disposition overhead-viewable by a passenger seated in the passenger seating area; and

a video control module mounted on the mounting frame structure separately from the screen structure in laterally spaced relation to the screen structure such that the video control module and the screen structure extend in substantially the same horizontal plane when the screen structure is in the stowed position, the video control module being electrically connected to the screen structure to direct operation of the screen structure.

**27.** The automotive display unit of claim **26**, wherein the screen structure is hinged for pivot about a first axis defined generally parallel to a first edge of the screen structure, and is further hinged for pivot about a second axis which bisects the screen structure and is transverse to the first axis.

**28.** The automotive display unit of claim **26**, wherein the mounting frame structure is embedded in the ceiling, the mounting frame structure defining a cavity configured to receive the screen structure flush with the ceiling when the screen structure is in the stowed position.

**29.** The automotive display unit of claim **26**, wherein the hinge is a two-phase hinge configured to provide for pivot of the screen structure under a first torque between the stowed position and the deployed position, and configured to provide for pivot of the screen structure under a second torque, higher than the first torque, between the deployed position and a break-away position to provide for emergency collapse of the screen structure.

\* \* \* \* \*