




US 20120173048A1

(19) **United States**(12) **Patent Application Publication**
BERNSTEIN et al.(10) **Pub. No.: US 2012/0173048 A1**(43) **Pub. Date: Jul. 5, 2012**(54) **SELF-PROPELLED DEVICE
IMPLEMENTING THREE-DIMENSIONAL
CONTROL****Publication Classification**(51) **Int. Cl.**
A63H 30/04 (2006.01)
G05D 1/02 (2006.01)
B62D 63/02 (2006.01)
G06F 19/00 (2011.01)(76) Inventors: **Ian H. BERNSTEIN**, Boulder, CO
(US); **Adam Wilson**, Longmont,
CO (US); **David E. Hygh**,
Broomfield, CO (US)(21) Appl. No.: **13/342,874**(52) **U.S. Cl. 701/2; 180/167**(22) Filed: **Jan. 3, 2012**(57) **ABSTRACT****Related U.S. Application Data**(60) Provisional application No. 61/430,023, filed on Jan.
5, 2011, provisional application No. 61/430,083, filed
on Jan. 5, 2011, provisional application No. 61/553,
923, filed on Oct. 31, 2011.

A self-controlled device maintains a frame of reference about an x-, y- and z-axis. The self-controlled device processes an input to control the self-propelled device, the input being based on the x- and y-axis. The self-propelled device is controlled in its movement, including about each of the x-, y- and z-axis, based on the input.






FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4A




FIG. 4B

FIG. 4C




FIG. 5




FIG. 6




FIG. 7




FIG. 8A





FIG. 8B

**FIG. 8C**






FIG. 8D

**FIG. 9**

**FIG. 10**




FIG. 11A




FIG. 11B





FIG. 11C

**FIG. 11D**




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13C




FIG. 13B




FIG. 14A






FIG. 14B

FIG. 14C

**FIG. 16A****FIG. 16B**

SELF-PROPELLED DEVICE IMPLEMENTING THREE-DIMENSIONAL CONTROL

RELATED APPLICATIONS

[0001] This application claims priority to (i) U.S. Provisional Patent Application Ser. No. 61/430,023, entitled “Method and System for Controlling a Robotic Device,” filed Jan. 5, 2011; (ii) U.S. Provisional Patent Application Ser. No. 61/430,083, entitled “Method and System for Establishing 2-Way Communication for Controlling a Robotic Device,” filed Jan. 5, 2011; and (iii) U.S. Provisional Patent Application Ser. No. 61/553,923, entitled “A Self-propelled Device and System and Method for Controlling Same,” filed Oct. 31, 2011; all of the aforementioned priority applications are hereby incorporated by reference in their respective entirety.

FIELD OF THE INVENTION

[0002] Embodiments described herein generally relate to a self-propelled device, and more specifically, to a self-propelled device that implements three-dimensional control.

BACKGROUND

[0003] Early in human history, the wheel was discovered and human fascination with circular and spherical objects began. Humans were intrigued by devices based on these shapes: as practical transportation and propulsion, and as toys and amusements. Self-propelled spherical objects were initially powered by inertia or mechanical energy storage in devices such as coiled springs. As technology has evolved, new ways of applying and controlling these devices have been invented.

[0004] Today, technology is available from robotics, high energy-density battery systems, sophisticated wireless communication links, micro sensors for magnetism, orientation and acceleration, and widely available communication devices with displays and multiple sensors for input.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] FIG. 1 is a schematic depiction of a self-propelled device, according to one or more embodiments.

[0006] FIG. 2A is a schematic depiction of an embodiment comprising a self-propelled device and a computing device, under an embodiment.

[0007] FIG. 2B depicts a system comprising computing devices and self-propelled devices, according to another embodiment.

[0008] FIG. 2C is a schematic that illustrates a system comprising a computing device and multiple self-propelled devices, under another embodiment.

[0009] FIG. 3 is a block diagram illustrating the components of a self-propelled device that is in the form of a robotic, spherical ball, in accordance with an embodiment.

[0010] FIGS. 4A, 4B, and 4C illustrate a technique for causing controlled movement of a spherical self-propelled device, in accordance with one or more embodiments.

[0011] FIG. 5 further illustrates a technique for causing motion of a self-propelled spherical device, according to an embodiment.

[0012] FIG. 6 is a block diagram depicting a sensor array and data flow, according to an embodiment.

[0013] FIG. 7 illustrates a system including a self-propelled device, and a controller computing device that controls and interacts with the self-propelled device, according to one or more embodiments.

[0014] FIG. 8A illustrates a more detailed system architecture for a self-propelled device and system, according to an embodiment.

[0015] FIG. 8B illustrates the system architecture of a computing device, according to an embodiment.

[0016] FIG. 8C illustrates a particular feature of code execution, according to an embodiment.

[0017] FIG. 8D illustrates an embodiment in which a self-propelled device 800 implements control using a three-dimensional reference frame and control input that is received from another device that utilizes a two-dimensional reference frame, under an embodiment.

[0018] FIG. 9 illustrates a method for operating a self-propelled device using a computing device, according to one or more embodiments.

[0019] FIG. 10 illustrates a method for operating a computing device in controlling a self-propelled device, according to one or more embodiments.

[0020] FIG. 11A through FIG. 11C illustrate an embodiment in which a user interface of a controller is oriented to adopt an orientation of a self-propelled device, according to one or more embodiments.

[0021] FIG. 11D illustrates a method for calibrating a user-interface for orientation based on an orientation of the self-propelled device, according to an embodiment.

[0022] FIG. 12A and FIG. 12B illustrate different interfaces that can be implemented on a controller computing device.

[0023] FIG. 13A through FIG. 13C illustrate a variety of inputs that can be entered on a controller computing device to operate a self-propelled device, according to an embodiment.

[0024] FIG. 14A illustrates a system in which a self-propelled device is represented in a virtual environment while the self-propelled device operates in a real-world environment, under an embodiment.

[0025] FIG. 14B and FIG. 14C illustrate an application in which a self-propelled device acts as a fiducial marker, according to an embodiment.

[0026] FIG. 15 illustrates an interactive application that can be implemented for use with multiple self-propelled devices, depicted as spherical or robotic balls, under an embodiment.

[0027] FIGS. 16A and 16B illustrate a method of collision detection, according to an embodiment.

DETAILED DESCRIPTION

[0028] In an embodiment, a self-propelled device is provided, which includes a drive system, a spherical housing, and a biasing mechanism. The drive system includes one or more motors that are contained within the spherical housing. The biasing mechanism actively forces the drive system to continuously engage an interior of the spherical housing in order to cause the spherical housing to move.

[0029] According to another embodiment, a self-controlled device maintains a frame of reference about an X-, Y- and Z-axis. The self-controlled device processes an input to control the self-propelled device, the input being based on the X- and Y-axis. The self-propelled device is controlled in its movement, including about each of the X-, Y- and Z-axes, based on the input.

[0030] Still further, another embodiment provides a system that includes a controller device and a self-propelled device. The self-propelled device is operable to move under control of the controller device, and maintains a frame of reference about an X-, Y- and Z-axis. The controller device provides an interface to enable a user to enter two-dimensional control input about the X- and Y-axes. The self-propelled device processes the control input from the controller device in order to maintain control relative to the X-, Y- and Z-axes.

[0031] According to another embodiment, a self-propelled device determines an orientation for its movement based on a pre-determined reference frame. A controller device is operable by a user to control the self-propelled device. The controller device includes a user interface for controlling at least a direction of movement of the self-propelled device. The self-propelled device is configured to signal the controller device information that indicates the orientation of the self-propelled device. The controller device is configured to orient the user interface, based on the information signaled from the self-propelled device, to reflect the orientation of the self-propelled device.

[0032] According to another embodiment, a controller device is provided for a self-propelled device. The controller device includes one or more processors, a display screen, a wireless communication port and a memory. The processor operates to generate a user interface for controlling at least a directional movement of the self-propelled device, receive information from the self-propelled device over the wireless communication port indicating an orientation of the self-propelled device, and configure the user interface to reflect the orientation of the self-propelled device.

[0033] In still another embodiment, a self-propelled device includes a drive system, a wireless communication port, a memory and a processor. The memory stores a first set of instructions for mapping individual inputs from a first set of recognizable inputs to a corresponding command that controls movement of the self-propelled device. The processor (or processors) receive one or more inputs from the controller device over the wireless communication port, map each of the one or more inputs to a command based on the set of instructions, and control the drive system using the command determined for each of the one or more inputs. While the drive system is controlled, the processor processes one or more instructions to alter the set of recognizable inputs and/or the corresponding command that is mapped to the individual inputs in the set of recognizable inputs.

[0034] Still further, embodiments enable a controller device to include an object or virtual representation of the self-propelled device.

[0035] Terms

[0036] As used herein, the term “substantially” means at least almost entirely. In quantitative terms, “substantially” means at least 80% of a stated reference (e.g., quantity of shape).

[0037] In similar regard, “spherical” or “sphere” means “substantially spherical.” An object is spherical if it appears as such as to an ordinary user, recognizing that, for example, manufacturing processes may create tolerances in the shape or design where the object is slightly elliptical or not perfectly symmetrical, or that the object may include surface features or mechanisms for which the exterior is not perfectly smooth or symmetrical.

[0038] Overview

[0039] Referring now to the drawings, FIG. 1 is a schematic depiction of a self-propelled device, according to one or more embodiments. As described by various embodiments, self-propelled device **100** can be operated to move under control of another device, such as a computing device operated by a user. In some embodiments, self-propelled device **100** is configured with resources that enable one or more of the following: (i) maintain self-awareness of orientation and/or position relative to an initial reference frame after the device initiates movement; (ii) process control input programmatically, so as to enable a diverse range of program-specific responses to different control inputs; (iii) enable another device to control its movement using software or programming logic that is communicative with programming logic on the self-propelled device; and/or (iv) generate an output response for its movement and state that it is software interpretable by the control device.

[0040] In an embodiment, self-propelled device **100** includes several interconnected subsystems and modules. Processor **114** executes programmatic instructions from program memory **104**. The instructions stored in program memory **104** can be changed, for example to add features, correct flaws, or modify behavior. In some embodiments, program memory **104** stores programming instructions that are communicative or otherwise operable with software executing on a computing device. The processor **114** is configured to execute different programs of programming instructions, in order to alter the manner in which the self-propelled device **100** interprets or otherwise responds to control input from another computing device.

[0041] Wireless communication **110**, in conjunction with communication transducer **102**, serves to exchange data between processor **114** and other external devices. The data exchanges, for example, provide communications, provide control, provide logical instructions, state information, and/or provide updates for program memory **104**. In some embodiments, processor **114** generates output corresponding to state and/or position information, that is communicated to the controller device via the wireless communication port. The mobility of the device makes wired connections undesirable; the term “connection” should be understood to mean a logical connection made without a physical attachment to self-propelled device **100**.

[0042] In one embodiment, wireless communication **110** implements the BLUETOOTH communications protocol and transducer **602** is an antenna suitable for transmission and reception of BLUETOOTH radio signals. Other wireless communication mediums and protocols may also be used in alternative implementations.

[0043] Sensors **112** provide information about the surrounding environment and condition to processor **114**. In one embodiment, sensors **112** include inertial measurement devices, including a 3-axis gyroscope, a 3-axis accelerometer, and a 3-axis magnetometer. According to some embodiments, the sensors **114** provide input to enable processor **114** to maintain awareness of the device's orientation and/or position relative to the initial reference frame after the device initiates movement. In various embodiments, sensors **112** include instruments for detecting light, temperature, humidity, or measuring chemical concentrations or radioactivity.

[0044] State/variable memory **106** stores information about the present state of the system, including, for example, position, orientation, rates of rotation and translation in each axis.

The state/variable memory **106** also stores information corresponding to an initial reference frame of the device upon, for example, the device being put in use (e.g., the device being switched on), as well as position and orientation information once the device is in use. In this way, some embodiments provide for the device **100** to utilize information of the state/variable memory **106** in order to maintain position and orientation information of the device **100** once the device starts moving.

[0045] Clock **108** provides timing information to processor **114**. In one embodiment, clock **108** provides a timebase for measuring intervals and rates of change. In another embodiment, clock **108** provides day, date, year, time, and alarm functions. In one embodiment clock **108** allows device **100** to provide an alarm or alert at pre-set times.

[0046] Expansion port **120** provides a connection for addition of accessories or devices. Expansion port **120** provides for future expansion, as well as flexibility to add options or enhancements. For example, expansion port **120** is used to add peripherals, sensors, processing hardware, storage, displays, or actuators to the basic self-propelled device **100**.

[0047] In one embodiment, expansion port **120** provides an interface capable of communicating with a suitably configured component using analog or digital signals. In various embodiments, expansion port **120** provides electrical interfaces and protocols that are standard or well-known. In one embodiment, expansion port **120** implements an optical interface. Exemplary interfaces appropriate for expansion port **120** include the Universal Serial Bus (USB), Inter-Integrated Circuit Bus (I2C), Serial Peripheral Interface (SPI), or ETHERNET.

[0048] Display **118** presents information to outside devices or persons. Display **118** can present information in a variety of forms. In various embodiments, display **118** can produce light in colors and patterns, sound, vibration, music, or combinations of sensory stimuli. In one embodiment, display **118** operates in conjunction with actuators **126** to communicate information by physical movements of device **100**. For example, device **100** can be made to emulate a human head nod or shake to communicate “yes” or “no.”

[0049] In one embodiment, display **118** is an emitter of light, either in the visible or invisible range. Invisible light in the infrared or ultraviolet range is useful, for example to send information invisible to human senses but available to specialized detectors. In one embodiment, display **118** includes an array of Light Emitting Diodes (LEDs) emitting various light frequencies, arranged such that their relative intensity is variable and the light emitted is blended to form color mixtures.

[0050] In one embodiment, display **118** includes an LED array comprising several LEDs, each emitting a human-visible primary color. Processor **114** varies the relative intensity of each of the LEDs to produce a wide range of colors. Primary colors of light are those wherein a few colors can be blended in different amounts to produce a wide gamut of apparent colors. Many sets of primary colors of light are known, including for example red/green/blue, red/green/blue/white, and red/green/blue/amber. For example, red, green and blue LEDs together comprise a usable set of three available primary-color devices comprising a display **118** in one embodiment. In other embodiments, other sets of primary colors and white LEDs are used.

[0051] In one embodiment, display **118** includes an LED used to indicate a reference point on device **100** for alignment.

[0052] Power **124** stores energy for operating the electronics and electromechanical components of device **100**. In one embodiment, power **124** is a rechargeable battery. Inductive charge port **128** allows for recharging power **124** without a wired electrical connection. In one embodiment, inductive charge port **128** accepts magnetic energy and converts it to electrical energy to recharge the batteries. In one embodiment, charge port **128** provides a wireless communication interface with an external charging device.

[0053] Deep sleep sensor **122** puts the self-propelled device **100** into a very low power or “deep sleep” mode where most of the electronic devices use no battery power. This is useful for long-term storage or shipping.

[0054] In one embodiment, sensor **122** is non-contact in that it senses through the enclosing envelope of device **100** without a wired connection. In one embodiment, deep sleep sensor **122** is a Hall Effect sensor mounted so that an external magnet can be applied at a pre-determined location on device **100** to activate deep sleep mode.

[0055] Actuators **126** convert electrical energy into mechanical energy for various uses. A primary use of actuators **126** is to propel and steer self-propelled device **100**. Movement and steering actuators are also referred to as a drive system or traction system. The drive system moves device **100** in rotation and translation, under control of processor **114**. Examples of actuators **126** include, without limitation, wheels, motors, solenoids, propellers, paddle wheels and pendulums.

[0056] In one embodiment, drive system actuators **126** include two parallel wheels, each mounted to an axle connected to an independently variable-speed motor through a reduction gear system. In such an embodiment, the speeds of the two drive motors are controlled by processor **114**.

[0057] However, it should be appreciated that actuators **126**, in various embodiments, produce a variety of movements in addition to merely rotating and translating device **100**. In one embodiment, actuators **126** cause device **100** to execute communicative or emotionally evocative movements, including emulation of human gestures, for example, head nodding, shaking, trembling, spinning or flipping. In some embodiments, processor coordinates actuators **126** with display **118**. For example, in one embodiment, processor **114** provides signals to actuators **126** and display **118** to cause device **100** to spin or tremble and simultaneously emit patterns of colored light. In one embodiment, device **100** emits light or sound patterns synchronized with movements.

[0058] In one embodiment, self-propelled device **100** is used as a controller for other network-connected devices. Device **100** contains sensors and wireless communication capability, and so it can perform a controller role for other devices. For example, self-propelled device **100** can be held in the hand and used to sense gestures, movements, rotations, combination inputs and the like.

[0059] FIG. 2A is a schematic depiction of an embodiment comprising a self-propelled device and a computing device, under an embodiment. More specifically, a self-propelled device **214** is controlled in its movement by programming logic and/or controls that can originate from a controller device **208**. The self-propelled device **214** is capable of movement under control of the computing device **208**, which can be operated by a user **202**. The computing device **208** can wirelessly communicate control data to the self-propelled device **214** using a standard or proprietary wireless communication protocol. In variations, the self-propelled device **214**

may be at least partially self-controlled, utilizing sensors and internal programming logic to control the parameters of its movement (e.g., velocity, direction, etc.). Still further, the self-propelled device **214** can communicate data relating to the device's position and/or movement parameters for the purpose of generating or alternating content on the computing device **208**. In additional variations, self-propelled device **214** can control aspects of the computing device **208** by way of its movements and/or internal programming logic.

[0060] As described herein, the self-propelled device **214** may have multiple modes of operation, including those of operation in which the device is controlled by the computing device **208**, is a controller for another device (e.g., another self-propelled device or the computing device **208**), and/or is partially or wholly self-autonomous.

[0061] Additionally, embodiments enable the self-propelled device **214** and the computing device **208** to share a computing platform on which programming logic is shared, in order to enable, among other features, functionality that includes: (i) enabling the user **202** to operate the computing device **208** to generate multiple kinds of input, including simple directional input, command input, gesture input, motion or other sensory input, voice input or combinations thereof; (ii) enabling the self-propelled device **214** to interpret input received from the computing device **208** as a command or set of commands; and/or (iii) enabling the self-propelled device **214** to communicate data regarding that device's position, movement and/or state in order to effect a state on the computing device **208** (e.g., display state, such as content corresponding to a controller-user interface). Embodiments further provide that the self-propelled device **214** includes a programmatic interface that facilitates additional programming logic and/or instructions to use the device. The computing device **208** can execute programming that is communicative with the programming logic on the self-propelled device **214**.

[0062] According to embodiments, the self-propelled device **214** includes an actuator or drive mechanism causing motion or directional movement. The self-propelled device **214** may be referred to by a number of related terms and phrases, including controlled device, robot, robotic device, remote device, autonomous device, and remote-controlled device. In some embodiments, the self-propelled device **214** can be structured to move and be controlled in various media. For example, self-propelled device **214** can be configured for movement in media such as on flat surfaces, sandy surfaces or rocky surfaces.

[0063] The self-propelled device **214** may be implemented in various forms. As described below and with an embodiment of FIG. 3, the self-propelled device **214** may correspond to a spherical object that can roll and/or perform other movements such as spinning. In variations, device **214** can correspond to a radio-controlled aircraft, such as an airplane, helicopter, hovercraft or balloon. In other variations, device **214** can correspond to a radio controlled watercraft, such as a boat or submarine. Numerous other variations may also be implemented, such as those in which the device **214** is a robot.

[0064] In one embodiment, device **214** includes a sealed hollow envelope, roughly spherical in shape, capable of directional movement by action of actuators inside the enclosing envelope.

[0065] Continuing to refer to FIG. 2A, device **214** is configured to communicate with computing device **208** using network communication links **210** and **212**. Link **210** trans-

fers data from device **208** to device **214**. Link **212** transfers data from device **214** to device **208**. Links **210** and **212** are shown as separate unidirectional links for illustration; in some embodiments a single bi-directional communication link performs communication in both directions. It should be appreciated that link **210** and link **212** are not necessarily identical in type, bandwidth or capability. For example, communication link **210** from computing device **208** to self-propelled device **214** is often capable of a higher communication rate and bandwidth compared to link **212**. In some situations, only one link **210** or **212** is established. In such an embodiment, communication is unidirectional.

[0066] The computing device **208** can correspond to any device comprising at least a processor and communication capability suitable for establishing at least uni-directional communications with self-propelled device **214**. Examples of such devices include, without limitation: mobile computing devices (e.g., multifunctional messaging/voice communication devices such as smart phones), tablet computers, portable communication devices and personal computers. In one embodiment, device **208** is an IPHONE available from APPLE COMPUTER, INC. of Cupertino, Calif. In another embodiment, device **208** is an IPAD tablet computer, also from APPLE COMPUTER. In another embodiment, device **208** is any of the handheld computing and communication appliances executing the ANDROID operating system from GOOGLE, INC.

[0067] In another embodiment, device **208** is a personal computer, in either a laptop or desktop configuration. For example, device **208** is a multi-purpose computing platform running the MICROSOFT WINDOWS operating system, or the LINUX operating system, or the APPLE OS/X operating system, configured with an appropriate application program to communicate with self-propelled device **214**.

[0068] In variations, the computing device **208** can be a specialized device, dedicated for enabling the user **202** to control and interact with the self-propelled device **214**.

[0069] In one embodiment, multiple types of computing device **208** can be used interchangeably to communicate with the self-propelled device **214**. In one embodiment, self-propelled device **214** is capable of communicating and/or being controlled by multiple devices (e.g., concurrently or one at a time). For example, device **214** can link with an IPHONE in one session and with an ANDROID device in a later session, without modification of device **214**.

[0070] According to embodiments, the user **202** can interact with the self-propelled device **214** via the computing device **208**, in order to control the self-propelled device and/or to receive feedback or interaction on the computing device **208** from the self-propelled device **214**. According to embodiments, the user **202** is enabled to specify input **204** through various mechanisms that are provided with the computing device **208**. Examples of such inputs include text entry, voice command, touching a sensing surface or screen, physical manipulations, gestures, taps, shaking and combinations of the above.

[0071] The user **202** may interact with the computing device **208** in order to receive feedback **206**. The feedback **206** may be generated on the computing device **208** in response to user input. As an alternative or addition, the feedback **206** may also be based on data communicated from the self-propelled device **214** to the computing device **208**, regarding, for example, the self-propelled device's position or state. Without limitation, examples of feedback **206** include

text display, graphical display, sound, music, tonal patterns, modulation of color or intensity of light, haptic, vibrational or tactile stimulation. The feedback **206** may be combined with input that is generated on the computing device **208**. For example, the computing device **208** may output content that is modified to reflect position or state information communicated from the self-propelled device **214**.

[0072] In some embodiments, the computing device **208** and/or the self-propelled device **214** are configured such that user input **204** and feedback **206** maximize usability and accessibility for a user **202**, who has limited sensing, thinking, perception, motor or other abilities. This allows users with handicaps or special needs to operate system **200** as described.

[0073] It should be appreciated that the configuration illustrated in the embodiment of FIG. 2A is only one of an almost unlimited number of possible configurations of networks including a self-propelled device with communication connections. Furthermore, while numerous embodiments described herein provide for a user to operate or otherwise directly interface with the computing device in order to control and/or interact with a self-propelled device, variations to embodiments described encompass enabling the user to directly control or interact with the self-propelled device **214** without use of an intermediary device such as computing device **208**.

[0074] FIG. 2B depicts a system **218** comprising computing devices and self-propelled devices, according to another embodiment. In the example provided by FIG. 2B, system **218** includes two computing devices **220** and **228**, four self-propelled devices **224**, **232**, **236**, and **238**, and communication links **222**, **226**, **230**, **234** and **239**. The communication of computing device **220** with self-propelled device **224** using link **222** is similar to the embodiment depicted in network **200** of FIG. 2A; however, embodiments such as those shown enable additional communication to be established between two computing devices **220** and **228**, via network link **226**.

[0075] According to an embodiment such as provided with system **218**, the computing devices **220**, **228** may optionally control more than one self-propelled device. Furthermore, each self-propelled device **224**, **232**, **236**, **238** may be controlled by more than one computing device **220**, **228**. For example, embodiments provide that computing device **228** can establish multiple communications links, including with self-propelled devices **232** and **236**, and computing device **220**.

[0076] In variations, the computing devices **220**, **228** can also communicate with one or more self-propelled devices using a network such as the Internet, or a local wireless network (e.g., a home network). For example, the computing device **228** is shown to have a communications link **239**, which can connect the computing device to an Internet server, a web site, or to another computing device at a remote location. In some embodiments, the computing device **228** can serve as an intermediary between the network source and a self-propelled device. For example, the computing device **228** may access programming from the Internet and communicate that programming to one of the self-propelled devices.

[0077] As an alternative or variation, the computing device **228** can enable a network user to control the computing device **228** in controlling one or more of the self-propelled devices **232**, **236**, etc. Still further, the computing device **228** can access the network source in order to receive programmatically triggered commands, such as a command initiated

from a network service that causes one or more of the self-propelled devices to update or synchronize using the computing device **228**. For example, the self-propelled device **232** may include image capturing resources, and a network source may trigger the computing device **228** to access the images from the self-propelled device, and/or to communicate those images to the network source over the Internet.

[0078] In variations, such remote network functionality may alternatively be communicated directly from a network source to the self-propelled devices **224**, **232**, **236**. Thus, computing devices **220**, **228** may be optional and various applications and uses. Alternatively, computing devices **220**, **228** may be separated from the self-propelled devices **224**, **232**, **236** by a network such as the Internet. Thus, computing devices **220**, **228** can alternatively be the network source that remotely controls and/or communicates with the self-propelled devices.

[0079] It should be noted that the data communication links **210**, **212**, **222**, **226**, **230**, **234**, **239**, **242**, **246**, **248**, and **252** in FIGS. 2A, 2B, and 2C are depicted as short and direct for purposes of illustration. However, actual links may be much more varied and complex. For example, link **226** connecting two computing devices **220** and **228** may be a low-power wireless link, if devices **220** and **228** are in close proximity. However, computing devices **220** and **228** may be far apart (e.g., separated by miles or geography), so long as suitable network communication can be established.

[0080] Thus, link **226** and all of the links **222**, **230**, **234**, and **239** can employ a variety of network technologies, including the Internet, World Wide Web, wireless links, wireless radio-frequency communications utilizing network protocol, optical links, or any available network communication technology. The final connection to self-propelled devices **224**, **232**, **236** and **238** is preferably wireless so connecting wires do not restrict mobility.

[0081] In one embodiment, the communication links **222**, **226**, **230** and **234** are based on the wireless communication standard for data exchange known as BLUETOOTH. BLUETOOTH is widely available and provides a flexible communication framework for establishing data networks using short-wavelength radio transceivers and data encoding. BLUETOOTH incorporates security features to protect the data sent on the links from unauthorized observers or interference. Alternative wireless communication medium may also be employed, such as wireless USB, Wi-Fi, or proprietary wireless communications. Embodiments further contemplate that one or more of the communication links to **222**, **226**, **230** and **234** utilize short-range radiofrequency (RF) communication, and/or line-of-sight communications.

[0082] In various other embodiments, the communication links are based on other wireless communication systems. Various radio frequency data communication systems are available, including for example those known as WI-FI, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g or 802.11n. Other radio frequency data links are formed using cellular telephone service or serial communication protocols using radio modems. In other embodiments, optical communication links are employed, including modulating properties of light and LASER beams.

[0083] Any suitable communication technology can be used to form the network links, whether presently known or available in the future. The features described herein are not dependent on any particular networking technology or standard.

[0084] In some embodiments, the communication established amongst the devices, such as amongst computing device 220, 228 and/or self-propelled devices 224, 232, 236, can be temporary, flexible and reconfigurable. A resulting network of such devices can be considered an “ad-hoc” network, or alternatively a “piconet,” or “personal area network.” In this respect, some implementations provide that the computing device is 220, 228 and self-propelled devices 224, 232, 236 can be considered nodes of the network, such as an ad-hoc network. In such configurations, network components, topology and communications paths are flexible and can be readily adjusted to accommodate addition or removal of devices, changing communication requirements or channel interference. For example, self-propelled device 238 in FIG. 2B is shown with no present network connection. However, self-propelled device 238 has connected to network 218 in the past and received instructions to enable it to operate without a persistent network link.

[0085] FIG. 2C is a schematic that illustrates a system 268 comprising a computing device and multiple self-propelled devices, under another embodiment. A computing device 240 is operable to communicate with one or more self-propelled devices 244, 250, 254. The computing device 240 may communicate commands or other control data, and received feedback similar to embodiments described above. The self-propelled devices 244, 250, 254 are configured to communicate and/or be controlled by the computing device 240. Additionally, the self-propelled devices 244, 250, 254 are configured to communicate and/or control one another.

[0086] In the example shown by FIG. 2C, the computing device 240 communicates with self-propelled device 244 using communications link 242. Self-propelled device 244 communicates with self-propelled device 250 using link 246 and with self-propelled device 254 using link 248. Self-propelled devices 250 and 254 communicate using link 252. The computing device 250 can send data to any of the self-propelled devices 244, 250, or 254, using device 244 as a relay. Alternatively, the computing device 240 can communicate with the other self-propelled devices 250, 254 directly.

[0087] The system 238 may include various configurations. For example, a user may operate computing device 240 to control self-propelled device 244. Movement of the self-propelled device 244 may be communicated both to the computing device 240 and to one or more of the other self-propelled devices 250, 254. Each of self-propelled devices may be preprogrammed to react in a specific manner based on state or position information communicated from another one of the self-propelled devices. For example, self-propelled devices 244, 250 may each be operated in a repel mode, so that the movement of self-propelled device 244 (as controlled from computing device 240) results in a repel motion by the self-propelled device 250. In other variations, self-propelled devices 244, 250, 254 may be preprogrammed to maintain a specific distance apart from one another, so that movement by one device automatically causes movement by the other two devices. Still further, the devices 244, 250, 254 may be configured so as to perform a variety of activities, such as, for example, (i) one self-propelled device automatically moving when another approaches a threshold distance; (ii) one self-propelled device programmatically moving to bump another self-propelled device; (iii) the self-propelled devices automatically moving in tandem based on input received by each

of the self-propelled devices from the other self-propelled devices or from the computing device 240, and/or variations thereof.

[0088] The various systems 200, 218, 238 are illustrative of embodiments provided herein. With any of the systems described, variations include the addition of more or fewer computing devices, and/or more or fewer self-propelled devices. As described with some variations, additional sources or nodes can be provided from a remote network source. Additionally, in some operational environments, the presence of the computing device is optional. For example, the self-propelled devices can be partially or completely autonomous, using programming logic to function.

[0089] Spherical Mechanical Design

[0090] FIG. 3 is a block diagram illustrating the components of a self-propelled device 300 that is in the form of a robotic, spherical ball, in accordance with an embodiment. In one embodiment, robotic ball 300 is of a size and weight allowing it to be easily grasped, lifted, and carried in an adult human hand.

[0091] As shown, robotic ball 300 includes an outer spherical shell (or housing) 302 that makes contact with an external surface as the device rolls. In addition, robotic ball 300 includes an inner surface 304 of the outer shell 302. Additionally robotic ball 300 includes several mechanical and electronic components enclosed by outer shell 302 and inner surface 304 (collectively known as the envelope).

[0092] In the described embodiment, outer shell 302 and inner surface 304 are composed of a material that transmits signals used for wireless communication, yet are impervious to moisture and dirt. The envelope material can be durable, washable, and/or shatter resistant. The envelope may also be structured to enable transmission of light and is textured to diffuse the light.

[0093] In one embodiment, the housing is made of sealed polycarbonate plastic. In one embodiment, at least one of the outer shell 302 or inner surface 304 are textured to diffuse light. In one embodiment, the envelope comprises two hemispherical shells with an associated attachment mechanism, such that the envelope can be opened to allow access to the internal electronic and mechanical components.

[0094] Several electronic and mechanical components are located inside the envelope for enabling processing, wireless communication, propulsion and other functions (collectively referred to as the “interior mechanism”). Among the components, embodiments include a drive system 301 to enable the device to propel itself. The drive system 301 can be coupled to processing resources and other control mechanisms, as described with other embodiments. Referring again to FIG. 3, carrier 314 serves as the attachment point and support for components of the interior mechanism. The components of the interior mechanism are not rigidly attached to the envelope. Instead, the interior mechanism is in frictional contact with inner surface 304 at selected points, and is movable within the envelope by the action of actuators of the drive mechanism.

[0095] Carrier 314 is in mechanical and electrical contact with energy storage 316. Energy storage 316 provides a reservoir of energy to power the device and electronics and is replenished through inductive charge port 326. Energy storage 316, in one embodiment, is a rechargeable battery. In one embodiment, the battery is composed of lithium-polymer cells. In other embodiments, other rechargeable battery chemistries are used.

[0096] Carrier 314 can provide the mounting location for most of the internal components, including printed circuit boards for electronic assemblies, sensor arrays, antennas, and connectors, as well as providing a mechanical attachment point for internal components.

[0097] In one embodiment, the drive system 301 includes motors 322, 324 and wheels 318, 320. Motors 322 and 324 connect to wheels 318 and 320, respectively, each through an associated shaft, axle, and gear drive (not shown). The perimeter of wheels 318 and 320 are two points where the interior mechanism is in mechanical contact with inner surface 304. The points where wheels 318 and 320 contact inner surface 304 are an essential part of the drive mechanism of the ball, and so are preferably coated with a material to increase friction and reduce slippage. For example, wheels 318 and 320 are covered with silicone rubber tires.

[0098] In some embodiments, a biasing mechanism is provided to actively force the wheels 318, 320 against the inner surface 304. In an example provided, the spring 312 and end 310 can comprise a biasing mechanism. More specifically, spring 312 and spring end 310 are positioned to contact inner surface 304 at a point diametrically opposed to wheels 318 and 320. Spring 312 and end 310 provide additional contact force to reduce slippage of the wheels 318 and 320, particularly in situations where the interior mechanism is not positioned with the wheels at the bottom and where gravity does not provide adequate force to prevent the drive wheels from slipping. Spring 312 is selected to provide a small force pushing wheels 318 and 320, and spring end 310 evenly against inner surface 304.

[0099] Spring end 310 is designed to provide near-frictionless contact with inner surface 304. In one embodiment, end 310 comprises a rounded surface configured to mirror a low-friction contact region at all contact points with the inner surface 304. Additional means of providing near-frictionless contact may be provided. In another implementation, the rounded surface may include one or more bearings to further reduce friction at the contact point where end 310 moves along inner surface 304.

[0100] Spring 312 and end 310 are preferably made of a non-magnetic material to avoid interference with sensitive magnetic sensors.

[0101] Control Overview

[0102] FIGS. 4A, 4B and 4C illustrate a technique for causing controlled movement of a spherical self-propelled device 402, in accordance with one or more embodiments. In FIG. 4A, self-propelled device is at rest in a stable orientation. With an X-, Y-, Z-axes frame of reference, the center of mass 406 (or center of gravity) of the device is aligned directly below (Z axis) the center of rotation 408, causing the device to be at rest. Reference mark 404 is included in the drawing to illustrate movement (X, Y axes), but is not present on the actual self-propelled device 402.

[0103] To produce directed movement of self-propelled device 402, the center of mass 406 is displaced from under the center of rotation 408, as shown in FIG. 4B. With movement, the device 402 has an inherent dynamic instability (DIS) in one or more axes (e.g., see Y or Z axes). To maintain stability, the device uses feedback about its motion to compensate for the instability. Sensor input, such as provided from sensors 112 (see FIG. 1) or accelerometers or gyroscopes (see FIG. 6), can be used to detect what compensation is needed. In this way, the device maintains a state of dynamic inherent insta-

bility as it moves under control of sensors and control input, which can be communicated from another controller device.

[0104] The displacement 410 of center of mass 406 is caused by one or more actuators. When center of mass 406 is not aligned below center of rotation 408, a torque is created on device 402 about the center of rotation, causing device 402 to rotate to restore stability. When device 402 is in contact with a surface, rotation causes device 402 to move along the surface in the direction corresponding to the displacement 410.

[0105] FIG. 4C illustrates device 402 at rest after the movement, with reference mark 404 showing the distance device 402 has rotated from the initial position in FIG. 4A. Although the displacement of center of mass 406 and movement are shown in one dimension for illustration, the principle applies to create desired motion in any direction on a two-dimensional plane.

[0106] In some implementations, device 402 is configured with center of mass 406 being as near to the inner surface of the sphere as possible, or equivalently to arrange components so that center of mass 406 is as low as possible when the device is in a stable situation as shown in FIG. 4A.

[0107] FIG. 5 further illustrates a technique for causing motion of a self-propelled spherical device, according to an embodiment. In the FIG. 5, device 500 is shown, having center of rotation 502 and center of mass 506, and in contact with planar surface 512. The drive mechanism for robotic device 500 comprises two independently-controlled wheeled actuators 508 in contact with the inner surface of the enclosing spherical envelope of device 500. Also shown is sensor platform 504. Several components of device 500 are not shown in FIG. 5 for simplicity of illustration.

[0108] When it is desired that device 500 move at a constant velocity, the technique illustrated in FIGS. 4A, 4B and 4C can be extended as shown in FIG. 5. To achieve continuous motion at a constant velocity, the displacement of center of mass 506 relative to center of rotation 502 is maintained by action of wheeled actuators 508. The displacement of the center of mass 506 relative to center of rotation 502 is difficult to measure, thus it is difficult to obtain feedback for a closed-loop controller to maintain constant velocity. However, the displacement is proportional to the angle 510 between sensor platform 504 and surface 512. The angle 510 can be sensed or estimated from a variety of sensor inputs, as described herein. Therefore, in one embodiment, the speed controller for robotic device 500 can be implemented to use angle 510 to regulate speed for wheeled actuators 508 causing device 500 to move at a constant speed across surface 512. The speed controller determines the desired angle 510 to produce the desired speed, and the desired angle setpoint is provided as an input to a closed loop controller regulating the drive mechanism.

[0109] FIG. 5 illustrates use of angle measurement for speed control; however the technique can be extended to provide control of turns and rotations, with feedback of appropriate sensed angles and angular rates.

[0110] It can be seen from the foregoing discussion that knowledge of the orientation angles is useful, in various embodiments, for control of a self-propelled device. Measuring the orientation of the device is also useful for navigation and alignment with other devices.

[0111] FIG. 6 is a block diagram depicting a sensor array and data flow according to an embodiment. In FIG. 6, sensor array 612 provides a set of sensors for providing information to the self-propelled device, including for example, its posi-

tion, orientation, rates of translation, rotation and acceleration. Many other sensors can be included to meet requirements in various embodiments.

[0112] In one embodiment, sensor array 612 includes a 3-axis gyroscope sensor 602, a 3-axis accelerometer sensor 604, and a 3-axis magnetometer sensor 606. In one embodiment a receiver for the Global Positioning System (GPS) is included. However, GPS signals are typically unavailable indoors, so the GPS receiver is often omitted.

[0113] Due to limitations in size and cost, sensors in sensor array 612 are typically miniaturized devices employing micro-electro-mechanical (MEMS) technology. The data from these sensors requires filtering and processing to produce accurate state estimates 616. Various algorithms are employed in sensor fusion and state estimator 614. These algorithms are executed by the processor on the self-propelled device.

[0114] Those familiar with the art will understand that the signals from sensor in sensor array 612 are imperfect and distorted by noise, interference and the limited capability of inexpensive sensors. However, the sensors also provide redundant information, so that application of a suitable sensor fusion and state estimator process 614 provides an adequate state estimation 616 of the true state of the self-propelled device.

[0115] For example, in many situations, magnetometer data is distorted by stray magnetic fields and ferrous metals in the vicinity. Sensor fusion and state estimator 614 are configured to reject bad or suspect magnetometer data and rely on the remaining sensors in estimating the state 616 of the self-propelled device. In some embodiments, particular movements of the self-propelled device can be used to improve sensor data for desired purposes. For example, it can be useful to rotate self-propelled device through an entire 360 degree heading sweep while monitoring magnetometer data, to map local magnetic fields. Since the fields are usually relatively invariant over a short period of time, the local field measurement is repeatable and therefore useful, even if distorted.

[0116] Architecture

[0117] FIG. 7 illustrates a system including a self-propelled device, and a controller computing device that controls and interacts with the self-propelled device, according to one or more embodiments. In an embodiment, a self-propelled device 710 may be constructed using hardware resources such as described with an embodiment of FIG. 1. In one implementation, self-propelled device 710 is a spherical object such as described with an embodiment of FIG. 3. A computing device 750 can be a multifunctional device, such as a mobile computing device (e.g., smart phone), tablet or personal computer in device. Alternatively, computing device 750 can correspond to a specialized device that is dedicated to controlling and communicating with the self-propelled device 710.

[0118] In an embodiment, self-propelled device 710 is configured to execute one or more programs 716 stored in a program library 720. Each program 716 in the program library 720 can include instructions or rules for operating the device, including instructions for how the device is to respond to specific conditions, how the device is to respond to control input 713 (e.g., user input entered on the computing device 720), and/or the mode of operation that the device is to implement (e.g., controlled mode, versus autonomous, etc.).

[0119] The program library 720 may also maintain an instruction set that is shared by multiple programs, including

instructions that enable some user input to be interpreted in a common manner. An application program interface (API) 730 can be implemented on the device 710 to enable programs to access a library of functions and resources of the device. For example, the API 730 may include functions that can be used with programs to implement motor control (e.g., speed or direction), state transition, sensor device interpretation and/or wireless communications.

[0120] In one implementation, the device 710 receives programs and programming instructions wirelessly through use of the wireless communication port 712. In variations, the device 710 receives programs and programming instructions 782 from external sources 780 via other ports, such as expansion port 120 (see FIG. 1). The programming resources may originate from, for example, a media provided to the user of the device (e.g., SD card), a network resource or website where programs can be downloaded, and/or programs and/or instruction sets communicated via the wireless communication port 712 from the computing device 750. In one implementation, the computing device 750 can be programmatically configured to interact and/or control the self-propelled device 710 with software. Once configured, the computing device 750 communicates instructions coinciding with its programmatic configuration to the self-propelled device 710. For example, the computing device 750 may download an application for controlling or interacting with the self-propelled device 710. The application can be downloaded from, for example, a network (e.g., from an App Store), or from a website, using wireless communication capabilities inherent in the computing device 750 (e.g., cellular capabilities, Wi-Fi capabilities, etc.). The application that is downloaded by the computing device 750 may include an instruction set that can be communicated to the self-propelled device 710.

[0121] In an embodiment, the computing device 750 executes a program 756 that is specialized or otherwise specific to communicating or interacting with, and/or controlling the self-propelled device 710. In some embodiments, the program 756 that executes on the computing device 750 includes a counterpart program 716A that can execute on the self-propelled device 710. The programs 756, 716A can execute as a shared platform or system. For example, as described below, the program 756 operating on the computing device 750 may cooperate with the counterpart runtime program 716A to generate input for the self-propelled device 710, and to generate output on the computing device 750 based on a data signal from the self-propelled device 710. In an embodiment, the program 756 generates a user interface 760 that (i) prompts or provides guidance for the user to provide input that is interpretable on the self-propelled device 710 as a result of the counterpart runtime program 716A, resulting in some expected outcome from the self-propelled device 710; (ii) receives feedback 718 from the self-propelled device 710 in a manner that affects the content that is output by the program 756 operating on the computing device 750. In the latter case, for example, computer-generated content may be altered based on positioning or movement of the self-propelled device 710.

[0122] More specifically, on the computing device, the program 756 can provide a user interface 760, including logic 762 for prompting and/or interpreting user input on the computing device. Various forms of input may be entered on the computing device 750, including, for example, user interac-

tion with mechanical switches or buttons, touchscreen input, audio input, gesture input, or movements of the device in a particular manner.

[0123] Accordingly, the program 756 can be configured to utilize an inherent application program interface on the computing device 750, to utilize the various resources of the device to receive and process input. Many existing multifunctional or general purpose computing devices (e.g., smart phones or tablets) are configured to detect various kinds of input, including touchscreen input (e.g., multitouch input gesture input), optical input (e.g., camera image sensing input), audio input and device movement input (e.g., shaking or moving the entire device). The user interface 760 may include logic 762 to prompt the user for specific kinds of input (e.g., include visual markers where a user should place fingers, instruct the user or provide the user with the visual and/or audio prompt to move the device, etc.), and to interpret the input into control information that is signaled to the self-propelled device.

[0124] In some embodiments or implementations, the input generated on the computing device 750 is interpreted as a command and then signaled to the self-propelled device 710. In other embodiments or implementations, the input entered on the computing device 750 is interpreted as a command by programmatic resources on the self-propelled device 710. By interpreting user input in the form of commands, embodiments provide for the self-propelled device 710 to respond to user input in a manner that is intelligent and configurable. For example, the self-propelled device 710 may interpret user input that is otherwise directional in nature in a manner that is not directional. For example, a user may enter gesture input corresponding to a direction, in order to have the self-propelled device 710 move in a manner that is different than the inherent direction in the user input. For example, a user may enter a leftward gesture, which the device may interpret (based on the runtime program 716A) as a command to stop, spin, return home or alter illumination output, etc.

[0125] The user interface 760 may also include output logic 764 for interpreting data received from the self-propelled device 710. As described with other embodiments, the self-propelled device 710 may communicate information, such as state information and/or position information (e.g., such as after when the device moves) to the computing device 750. In one implementation, the communication from the self-propelled device 710 to the computing device 750 is in response to a command interpreted from user input on the computing device 750. In another implementation, the communication from the self-propelled device 710 may be in the form of continuous feedback generated as result of the device's continuous movement over a duration of time. As described with other implementations and embodiments, the output onto device 750 may correspond to a computing device having one of various possible form factors. The program 756 may configure the interface to graphically provide gaming context and/or different user-interface paradigms for controlling the self-propelled device 710. The program 756 may operate to directly affect the content generated in these implementations based on movement, position or state of the self-propelled device 710.

[0126] In operation, the self-propelled device 710 implements the programmatic runtime 716A using one or more sets of program instructions stored in its program library 720. The program runtime 716A may correspond to, for example, a program selected by the user, or one that is run by default or

in response to some other condition or trigger. Among other functionality, the program runtime 716A may execute a set of program-specific instructions that utilizes device functions and/or resources in order to: (i) interpret control input from the computing device 750; (ii) control and/or state device movement based on the interpretation of the input; and/or (iii) communicate information from the self-propelled device 710 to the computing device 750.

[0127] In an embodiment, the program runtime 716A implements drive control logic 731, including sensor control logic 721 and input control logic 723. The sensor control logic 721 interprets device sensor input 711 for controlling speed, direction or other movement of the self-propelled device's drive system or assembly (e.g., see FIG. 1, 3 or 8D). The sensor input 711 may correspond to data such as provided from the accelerometer(s), magnetometer(s) or gyroscope(s) of the self-propelled device 710. The sensor data can also include other information obtained on a device regarding the device's movement, position, state or operating conditions, including GPS data, temperature data, etc. The program 716A may implement parameters, rules or instructions for interpreting sensor input 711 as drive assembly control parameters 725. The input control logic 723 interprets control input 713 received from the computing device 750. In some implementations, the logic 723 interprets the input as a command, in outputting drive assembly control parameters 725 that are determined from the input 713. The input drive logic 723 may also be program specific, so that the control input 713 and/or its interpretation are specific to the runtime program 716A. The drive assembly control logic uses the parameters, as generated through sensor/input control logic 721, 723 to implement drive assembly controls 725.

[0128] In variations, the sensor/input control logic 721, 723 is used to control other aspects of the self-propelled device 710. In embodiments, the sensor/input control logic 721, 723 may execute runtime program 716A instructions to generate a state output 727 that controls a state of the device in response to some condition, such as user input our device operation condition (e.g., the device comes to stop). For example, an illumination output (e.g., LED display out), audio output, or device operational status (e.g., mode of operation, power state) may be affected by the state output 727.

[0129] Additionally, the run time program 716A generates an output interface 726 for the self-propelled device program 756 running on the computing device 750. The output interface 726 may generate the data that comprises feedback 718. In some embodiments, the output interface 726 generates data that is based on position, movement (e.g., velocity, rotation), state (e.g., state of output devices), and/or orientation information (e.g., position and orientation of the device relative to the initial reference frame). The output interface 726 may also generate data that, for example, identifies events that are relevant to the runtime program 716A. For example the output interface 726 may identify events such as the device being disrupted in its motion or otherwise encountering a disruptive event. In some embodiments, output interface 726 may also generate program specific output, based on, for example, instructions of the runtime program 716A. For example, runtime program 716A may require a sensor reading that another program would not require. The output interface 726 may implement instructions for obtaining the sensor reading in connection with other operations performed through implementation of the runtime program 716A.

[0130] According to embodiments, self-propelled device 710 is operable in multiple modes relative to computing device 750. In a controlled mode, self-propelled device 710 is controlled in its movement and/or state by control input 713, via control signals 713 communicated from the computing device 750. In some implementations, the self-propelled device 710 pairs with the computing device 750 in a manner that affects operations on the computing device as to control or feedback. In some embodiments, self-propelled device 710 is also operable in an autonomous mode, where control parameters 725 are generated programmatically on the device in response to, for example, sensor input 711 and without need for control input 713. Still further, in variations, the self-propelled device 710 can act as a controller, either for the computing device 750 or for another self-propelled device 710. For example, the device may move to affect a state of the computing device 750. The device can operate in multiple modes during one operating session. The mode of operation may be determined by the runtime program 716A.

[0131] As described by an embodiment of FIG. 7 and elsewhere in the application, the self-propelled device 710 can include a library of instruction sets for interpreting control input 713 from the computing device 750. For example, the self-propelled device can store instructions for multiple programs, and the instructions for at least some of the programs may include counterpart programs that execute on the controller device 750. According to embodiments, the library that is maintained on the self-propelled device is dynamic, in that the instructions stored can be added, deleted or modified. For example, a program stored on the self-propelled device may be added, or another program may be modified.

[0132] When executed on the computing device 750, each program may include instructions to recognize a particular set of inputs, and different programs may recognize different inputs. For example, a golf program may recognize a swing motion on the computing device 750 as an input, while the same motion may be ignored by another program that is dedicated to providing a virtual steering mechanism. When executed on the self-propelled device 710, each program may include instructions to interpret or map the control input 713 associated with a particular recognized input to a command and control parameter.

[0133] In embodiments, the self-propelled device is able to dynamically reconfigure its program library. For example, an embodiment provides that a program can be modified (e.g., through instructions received by the controller device) to process control input 713 that corresponds to a new recognized input. As another example, an embodiment provides that the self-propelled device is able to switch programs while the self-propelled device is in use. When programs are switched, a different set of inputs may be recognized, and/or each input may be interpreted differently on the self-propelled device 710.

[0134] FIG. 8A illustrates a more detailed system architecture 800 for a self-propelled device and system, according to an embodiment. As has been previously discussed herein, in various embodiments, the self-propelled device 800 comprises multiple hardware modules, including wireless communication 802, memory 804, sensors 806, displays 808, actuators 810 and an expansion port 812. Each of these modules is interfaced with a set of software known as device drivers or hardware abstraction layer (HAL) 820. HAL 820 provides isolation between specific hardware and higher layers of the software architecture.

[0135] An operating system 822 provides for support of general hardware input and output, scheduling tasks, and managing resources to perform tasks. The operating system 822 is also sometimes known as a “hypervisor” which provides for sharing of resources among tasks, for example, if two software modules request control of the actuators simultaneously, operation policy established by hypervisor 822 resolves the contention.

[0136] ORBOTIX predefined local control functions 824 comprise control loops and library routines useful to robot applications 825. In some embodiments, a set of local robot applications 825 controls some or all of the features of self-propelled device 800. In some embodiments, a set of predefined remote control functions 826 interfaces with a remote controller device such as a computing device, using wireless link 802.

[0137] In one embodiment, a Robot Application Programming Interface (API) 828 provides a documented set of functions usable to control and monitor the device hardware and functions. API functions, also known as user functions 832, can be supplied by a user or obtained from a software repository or website and downloaded to the self-propelled device. User functions 832 are stored in user function storage 830.

[0138] In one embodiment, a robot language interpreter 834 is provided. The robot language interpreter 834 processes program instructions written in a simple, easy to understand format. For example, in one embodiment, language interpreter 834 processes instructions written in a variant of the BASIC programming language with extensions for reading robot sensors 806, controlling displays 808 and actuators 810, and interfacing with other robot device hardware and features. Robot language interpreter 834 also provides protection and security against performing destructive or unwise operations. In one embodiment, language interpreter 834 understands the ORBBASIC language from ORBOTIX. Robot language code 838 is stored in dedicated robot language storage 836.

[0139] An example of user code 838, when executed by interpreter 834, causes the self-propelled device’s LED display to change color in response to the measured speed of movement of the device. Thus it can be seen that a user-supplied function can control one element of the device, such as LED display, while other elements (speed and direction) remain controlled through the wireless connection and remote control device.

[0140] Thus, multiple methods are provided for a user to add programmatic instructions to control and extend the features of the self-propelled device. API 828 provides a powerful interface for a sophisticated user, while language interpreter 834 provides a simple and safer interface for a novice that can also negate time lags in communication with a controller device.

[0141] FIG. 8B illustrates the system architecture of a computing device 840, according to an embodiment. As previously described herein, computing devices useful in networks with self-propelled devices typically provide a wireless communication interface 841, a user interface 845, with other hardware and features 846.

[0142] Device 840 typically provides an operating system 848, for example iOS for an APPLE IPHONE and ANDROID OS for ANDROID computing devices. Also provided is an API 850 for applications. ORBOTIX application base 852 provides basic connectivity to device API 850 and device OS 848 with higher layers of application software.

[0143] ORBOTIX controller application programs, or “apps” **854** and **858**, provide user experiences and interaction with self-propelled devices. For example, in various embodiments, apps **854** and **858** provide control of a self-propelled device using touch-sensing control or a simulated joystick controller. Apps **854** and **858** can also provide a solo or multi-player game experience using self-propelled or robotic devices.

[0144] In some embodiments, controller apps **854** and **858** use sensors on device **840** to allow gestural control of a physical device in a real world environment, controlling a self-propelled or robotic device. For example, a user can make a gesture used in a sports game—a tennis swing or golf swing. The gesture is sensed on device **840** and processed by a software app to cause corresponding motion of the self-propelled device.

[0145] ORBOTIX API/SDK (Software Development Kit) **856** provides a documented set of interface functions useful to a user desiring to create custom applications **858** on a controller device for use with a self-propelled robotic device.

[0146] App **854** differs from app **858** in that app **854** is built directly on the application base layer **852**, while app **858** is built on ORBOTIX controller API/SDK **856**.

[0147] FIG. 8C illustrates a particular feature of code execution according to an embodiment. Shown are two computing devices **842** and **846**. Device **842** is not necessarily the same type as device **846**. One device may be an IPHONE and one an ANDROID phone. Each device has an associated memory storage area, memory **849** for device **846** and memory **844** for device **842**. Robot code **847** is loaded into both memories **844** and **849**, and is subsequently available to transfer to robot API **850**.

[0148] A notable feature in this embodiment is that code module **847** is stored and transferred into robot API **850** using an intermediate computing device **842** or **846**, and the type of the computing device does not matter. This makes it possible for computing devices to store various code modules or “helper apps” that can be downloaded to robotic devices as needed, for example to expedite a particular task.

[0149] It should be appreciated that the embodiments and features discussed in relation to FIGS. 8A, 8B and 8C provide a highly flexible distributed processing platform, wherein tasks can be readily moved between a controller and controlled device.

[0150] Control Systems

[0151] According to at least some embodiments, a self-propelled device such as described by various examples herein moves in accordance with a three-dimensional reference frame (e.g., X-, Y- and Z-axes), but operates using input that is received from a device that uses a two-dimensional reference frame (e.g., X-, Y-axes). In an embodiment, the self-propelled device maintains an internal frame of reference about the X-, Y- and Z-axes. The self-propelled device is able to receive control input from another device, in which the control input is based on a two-dimensional reference frame and further controls the movement of the self-propelled device about the X-, Y- and Z-axes.

[0152] FIG. 8D illustrates an embodiment in which a self-propelled device **800** implements control using a three-dimensional reference frame and control input that is received from another device that utilizes a two-dimensional reference frame, under an embodiment. The self-propelled device **800** (assumed to be spherical) includes a control system **882** that includes a three-axis controller **880** and an inertial measure-

ment unit (IMU) **884**. The IMU **884** uses sensor input to provide feedback that the controller **880** can use to independently determine a three-dimensional frame of reference for controlling a drive system **890** (e.g., see FIG. 3) of the self-propelled device. Specifically, the three-axis controller **880** operates to implement control on motors **892** (or wheels **894**) of the drive system **890**. For example, the three-axis controller **880** operates to determine the speeds at which each of two parallel wheeled motors **894**, **894** are to spin. It should be appreciated that the two motors **892**, **892**, which can be operated in varying degrees of cooperation and opposition, are capable of moving the sphere **800** in many rotational and translational motions to achieve a desired movement. In one embodiment, the motors **892**, **892** are capable of rotating at varying speeds in both forward and reverse directions to affect the movement of the corresponding wheels **894**, **894**. In another embodiment, each motor **892**, **892** speed is varied from zero to a maximum in one direction.

[0153] The controller **880** and IMU **884** can be implemented through separate hardware and/or software. In one implementation, the controller **880** and IMU **884** are implemented as separate software components that are executed on, for example, processor **114** (see FIG. 1).

[0154] More specifically, the controller **880** measures or estimates the present state of the self-propelled device **800**, including pitch, roll, and yaw angles based on feedback **895**. The feedback **895** may originate from, for example, one or more accelerometers **896A**, gyroscope **896B**, magnetometer **896C**, and/or other devices (e.g., GPS), which determine the feedback when the device is in motion.

[0155] In one embodiment, controller **880** receives feedback **895** from the IMU **884** as to the motion of the device along three axes, including a desired pitch input, a desired roll input and a desired yaw input. In one variation, the feedback **895** includes desired orientation angles. Still further, the feedback can correspond to desired rates of angular rotation.

[0156] In one embodiment, the desired pitch angle is calculated by an additional control loop configured to maintain forward speed. As described in conjunction with FIG. 5, speed and pitch angle are related by the physics of a rolling sphere.

[0157] In addition to feedback **895**, the controller uses control input **885** from the controller device to implement control on the drive system **890**. The control input **885** may originate from a device that utilizes a two-dimensional reference frame (e.g., X and Y). In one implementation, the control input **885** is determined by, for example, processing resources of the self-propelled device **800** that interpret control data from the controller **880** as commands that specify one or more parameters, such as parameters that specify position (e.g., move to a position), distance, velocity or direction. Thus, some embodiments provide that the control input **885** is based on control data that is (i) generated in accordance with a two-dimensional reference frame, and (ii) interpreted as one or more commands that specify parameters such as distance, position or velocity. For example, a desired speed is provided by way of control input **885** to the controller **880**. In an embodiment, the controller **880** implements control **888** on the drive system **890** using control parameters **898**, which account for the control input **885** and the feedback **895**. The control **888** may cause individual components of the drive system **890** to compensate for instability, given, for example, parameters specified in the control input (e.g., command input). In other words, the controller **882** may implement

control **888** in a manner that causes the drive system **890** to adjust the motion of the device based on feedback **885**, in order to effectively implement the control parameters (e.g., distance to travel) specified in the command input. Furthermore, the control **888** enables the device to maintain control with presence of dynamic instability when the device is in motion.

[0158] In some embodiments, the controller **880** is able to determine, from feedback **895**, the present state of the self-propelled device **800** in conjunction with desired angles. As mentioned, the controller **880** can use the feedback **895** to implement control parameters, particularly as to compensating for the dynamic instability (see also FIG. 4B) that is inherent in about one or more axes when the self-propelled device is in motion. The errors can be determined for each axis (e.g., pitch, roll and yaw). This uses a technique of feedback where the actual angle is compared to the desired angle, in each axis, to calculate an error or correction signal.

[0159] According to embodiments, the controller **880** uses the feedback **895** to establish multiple control loops. In one embodiment, the controller **880** computes an estimated set of state variables, and uses the estimated state variables in a closed loop feedback control. This allows the multiple feedback control loops to be implemented, each of which control or provide feedback as to a state, such as, for example, a position, rate, or angle. The controller **880** can implement feedback control using estimated states, so as to provide for controlled movement of the self-propelled device, both along a surface and in device rotation about axes. The controlled movement can be achieved while the device is inherently unstable during movement.

[0160] In addition, incorporating feedback input **895** using sensors and estimation of present state variables enables feedback control **898** for device stability in both static and dynamic conditions. It can be appreciated that actuators in embodiments of a self-propelled device will not respond consistently or cause identical command response, due to disturbances such as variations in actuators, environment, noise and wear. These variations would make stable, controlled movement difficult without feedback control **898**. Feedback control **898** can also provide stability augmentation to a device that can be inherently unstable and allows movement in a controlled and stable manner.

[0161] Now the controller has calculated three correction signals and the signals must be combined into command signals to each of the two motors. For reference, the two motors are termed “left” and “right”, although it should be understood the assignment of these terms is arbitrary. It can be appreciated that the assignment of labels affects the sign conventions in roll and yaw.

[0162] Then, the following equations are used to combine the correction terms into left and right motor commands.

[0163] First, the pitch and yaw corrections are combined into intermediate variables. In one embodiment, the pitch correction is limited to prevent the motors from being driven at full speed to create forward motion, which would prevent response to roll or yaw correction inputs.

$$\text{left_motor_intermediate} = \text{pitch correction} + \text{yaw correction}$$

$$\text{right_motor_intermediate} = \text{pitch correction} - \text{yaw correction}$$

[0164] Next, the roll correction is included appropriately into the left and right motor variables. If the roll correction is positive, roll correction is subtracted from the left motor command:

$$\text{left_motor_output} = \text{left_motor_intermediate} - \text{roll correction}$$

$$\text{right_motor_output} = \text{right_motor_intermediate}$$

[0165] Alternatively, if the roll correction is not positive, roll correction is added to the right motor variable:

$$\text{left_motor_output} = \text{left_motor_intermediate}$$

$$\text{right_motor_output} = \text{right_motor_intermediate} + \text{roll correction}$$

[0166] Thus the controller produces an output variable for each motor that includes the desired control in three axes.

[0167] In this way, a controller can use a two-dimensional reference frame to provide input for the self-propelled device (which utilizes a three-dimensional reference frame). For example, the controller can implement a graphic user interface to enable the user to input that is based on two-dimensional input. For example, FIG. 11B illustrates a graphic control mechanism that can be implemented on a controller device to enable the user to provide directional input about the X and Y axes (see also FIG. 12A).

[0168] Methodology

[0169] FIG. 9 illustrates a method for operating a self-propelled device using a computing device, according to one or more embodiments. Reference may be made to numerals of embodiments described with other figures, and with FIG. 7 in particular, for purpose of illustrating suitable components or elements that can be used to perform a step or sub-step being described.

[0170] According to an embodiment, when a session is initiated between the self-propelled device **710** and computing device **750** (e.g., self-propelled device is turned on and the self-propelled device program **756** is launched on the computing device **750**), the two devices calibrate their respective orientation (**910**). In one implementation, the self-propelled device **710** obtains its orientation and/or position relative to the initial reference frame, then signals the information to the computing device **750**.

[0171] In an embodiment in which the self-propelled device **710** is spherical (e.g., a ball), the self-propelled device **710** can base its orientation determination on the location of the device marker. The device marker may correspond to a predetermined feature on the device. The location of the feature relative to an initial reference frame is obtained and communicated to the computing device **750**. The computing device **750** may include a user-interface that includes an orientation that is based on the orientation information communicated from the self-propelled device **710**. For example, the user interface **760** of computing device **750** may generate a graphic steering mechanism that is calibrated to reflect the orientation of the self-propelled device **710** (e.g., based on the predetermined marker on the self-propelled device **710**).

[0172] Control input is received on the self-propelled device from the computing device running the self-propelled device program **756** (**920**). The control input may be in the form of a command, or otherwise be in the form of data that is interpretable on the self-propelled device **710** (through use of programming). The control input may include multiple components, including components from different input or

interface mechanisms of the computing device 750 (e.g., touchscreen and accelerometer of the computing device 750). Accordingly, implementations provide for control input to be based on touchscreen input (922), mechanical switch or button inputs (924), device motion or position input (926), or combinations thereof (928). In variations, other forms of input can be entered on the computing device 750 and processed as control input. For example, the computing device 750 may communicate to the self-propelled device 710 one or more of (i) audio input from the user speaking, (ii) image input from the user taking a picture, and/or (iii) GPS input.

[0173] In an embodiment, the control input is interpreted on the self-propelled device 710 using programming (930). Thus, the self-propelled device 710 may receive different forms of input from the computing device 750, based on the program executed on the self-propelled device 710 and/or the computing device 750. Moreover, self-propelled device 710 and/or the computing device 750 implement different processes for how input of a given type is to be interpreted. For example, self-propelled device 710 can interpret touchscreen inputs differently for different programs, and the response of the self-propelled device may be determined by which program is executing when the input is received.

[0174] In using programming to interpret input, self-propelled device 710 may be capable of different forms of responses to input. Based on the program that is executed on the self-propelled device 710 and/or the computing device 750, the input of the user may be interpreted as directional input (932), non-directional input (934), and/or a multi-component command input (936). More specifically, the device may be correlated to input that is directional in nature by interpreting user actions or input data that includes an inherent directional aspect. For example, a user may operate a graphic steering wheel to control the direction of the self-propelled device 710. The device may also process input non-directionally. For example some forms of user input or action may have inherent directional characteristics (e.g., the user swinging computing device 750 in a particular direction, the user providing some directional input on the steering wheel mechanism that is graphically displayed on the computing device, etc.), but the manner in which the input is processed on the self-propelled device 710 may not be directional, or least directional in a manner that is similar to the inherent directional characteristic of the user action.

[0175] In variations, action performed by the user on the computing device 750 may also be interpreted as a command. The input from the user on the computing device 750 may be correlated (either on the computing device 750 or the self-propelled device 710) with instructions that signify an action by the device. The correlation between input and action can be program-specific, and configurable to meet the requirements or objects of the particular program that is being executed. As an example, the self-propelled device 710 can interpret a single user action (e.g., gesture input on computing device) as a command to perform a series of actions, such as actions to perform a combination of movement, state changes, and/or data outputs.

[0176] The device performs one or more actions that are responsive to the user action or actions (940). The response of the self-propelled device 710 may be dictated by the program that is executing on the device (as well as the computing device 750) when the control input is received. Thus, the action or actions performed by the self-propelled device 710

may be complex, and multiple actions can be performed based on a single command or series of user actions.

[0177] For example, the self-propelled device 710 and the computing device 750 may combine to enable the user in simulating a game in which a ball (such as a tennis ball) is struck against the wall. To simulate the game, the user may swing computing device 750 in a given direction (e.g., like a racquet), causing the self-propelled device 710 to move in a direction that is related to the direction of the user's motion. However, without further input from the user, the self-propelled device 710 may return or move in a substantially opposite direction after the initial movement, so as to simulate the ball striking a wall or another racquet and then returning. Thus, the return of the self-propelled device 710 would be non-directional in its relation to the inherent directional characteristic of the original action.

[0178] The same example also illustrates the use of command input, in that one input on the computing device 750 (user swinging device) is interpreted into multiple actions that are taken by the self-propelled device 710. Moreover, based on programming, the self-propelled device 710 and/or the computing device 750 may interpret multiple kinds of user input or action as a command, resulting in performance of one action, or a series of actions. For example, in the ball example described above, the user may also be required to place his finger on the touchscreen of the computing device 750, while swinging the device in a particular direction. The combination of the touchscreen input and the motion input of the computing device 750 can be interpreted as a command for multiple actions to be performed by the self-propelled device 710. In the example provided, the self-propelled device performs the following in response to multi-component user action: determine a velocity and direction based on the user action (e.g., user places finger and touchscreen while swinging computing device 750); move based on the determined velocity and direction; determine when to stop based on the simulated presence of a wall; estimate return velocity and direction; and then move in the return direction.

[0179] Additionally, each action or output from the self-propelled device 710 may incorporate several independent sub actions, involving independently operable aspects of the self-propelled device 710. For example, self-propelled device 710 may include multiple motors that comprise the drive assembly. A command input may dictate whether one or both motors are used. Likewise, command input may determine if other hardware resources of the device are used in response to user input. For example, the command input can correlate a user input on the computing device with a series of actions on the self-propelled device 710, which include communicating an output of a magnetometer to the computing device 750.

[0180] Other types of command input that can be interpreted from a user action include, for example, altering the state of the self-propelled device 710 based on a particular input from the user. For example, the user may perform a double tap on the touchscreen of the computing device 750 as a form of input. A first program on the self-propelled device 710 may interpret the double tap as a command to spin. A second program on the same self-propelled device 710 may interpret the double tap as a command to illuminate.

[0181] In some embodiments, the self-propelled device 710 signals back information (e.g., feedback 718) to the computing device 750 (950). The feedback 718 may correspond to the updated position information (952), information about the device's movement or orientation (954) (e.g., velocity or

direction), device state information (956), or other information (e.g., sensor input from the device based on specific programming request). As described with some embodiments, the feedback 718 may be used to generate content on the computing device 750. For example, the feedback 718 may affect a virtual representation of the self-propelled device 710 generated on the computing device 750. With, for example, movement of the self-propelled device 710, the corresponding virtual representation of the self-propelled device on the computing device 750 may also be moved accordingly. Numerous examples are provided herein for user feedback 718 to generate and/or after content on the computing device 750.

[0182] FIG. 10 illustrates a method for operating a computing device in controlling a self-propelled device, according to one or more embodiments. Reference may be made to numerals of embodiments described with other figures for the purpose of illustrating suitable components or elements for performing a step or sub-step being described.

[0183] The computing device 750 may include a contextual user interface (1010). For example, the user interface generated on the computing device 750 may include a graphic interface that provides features for implementing the game or simulation. The features may include use of a graphic object that is virtually moved in accordance with movement of the self-propelled device 710. Specific examples of user interfaces include, for example: (i) a user interface having a circle, and an orientation marker that the user can move about the circle, where the orientation marker represents the orientation of the self-propelled device; (ii) a golfing or bowling interface showing a virtualized ball that represents the self-propelled device; or (iii) a dynamic and interactive gaming content in which an object representing the self-propelled device 710 is moved in the context of gaming or simulation content.

[0184] A user may operate the computing device 752 to enter one or more inputs. The input may be either discrete (in time) or continuous. Discrete input may correspond to a specific user action that is completed, and results in the self-propelled device 710 moving and/or performing other actions. Examples of discrete inputs include simulated golf swings or bowling strokes (e.g., where the user swings his handset and the action is interpreted as a golf or bowling ball movement). Continuous input requires the user to be engaged while the self-propelled device moves. Examples of continuous input include the user operating a virtual steering feature or joy stick as a mechanism for controlling the self-propelled device in its movement. As mentioned with some other embodiments, the user input may correspond to multiple actions performed by the user, including actions that include the use of different input interfaces or mechanisms on the computing device 750. For example, the user input can correspond to user actions on the touchscreen display, the user moving the computing device about the gesture, the user interacting with the camera to the computing device, the user providing speech input from a microphone of the computing device, and/or the user operating buttons and/or mechanical switches on the computing device.

[0185] The user input is communicated to the self-propelled device (1030). In one embodiment, the computing device 750 interprets the input of the user, and then signals interpreted input to the self-propelled device 710. In variations, the self-propelled device 710 interprets the input of the user, based on data signals received from the computing device 750.

[0186] The self-propelled device 710 may respond to the user input, by, for example, moving in a direction and/or in accordance with the velocity specified by the user input (1040). Other actions, such as spinning, performing other movements, changing state of one or more devices, etc. can also be performed, depending on the interpretation of the user input.

[0187] The computing device 750 may receive the feedback from the self-propelled device 710 (1050). The nature and occurrence of the feedback may be based on the programmatic configuration of the self-propelled device 710 and the computing device 750. For example, the feedback communicated from the self-propelled device 710 to the computing device 750 may include information that identifies position, orientation and velocity of the self-propelled device, either at a particular instance or over a given duration of time. As an alternative or addition, the feedback may include or state information about the self-propelled device 710, and/or readings from one or more sensors on the self-propelled device. Furthermore, depending on the implementation, the feedback may be communicated either continuously or discretely. In the latter case, for example, the self-propelled device 710 may perform an action, such as moving to a particular position, and then communicate its position and orientation to the computing device 750. Alternatively, the self-propelled device 710 may continuously update the computing device 750 on this orientation and/or position and/or velocity, as well as state other information. Numerous variations are possible, depending on the programmatic configuration of the self-propelled device 710.

[0188] In response to receiving the feedback, the computing device 750 updates, modifies or generates new contextual user interfaces that reflects a change in the representation of the self-propelled device (1060). Specifically, once the self-propelled device 710 moves, its representation of the user interface on the computing device 750 may reflect the movement. For example, the contextual user interface of the computing device may reflect the movement of the self-propelled device 710 in a manner that is not video (or at least not solely video), but rather computer-generated (e.g., animated, graphic, etc.). As an addition or alternative, other information communicated with the feedback (e.g., the state of the self-propelled device 710) may also be reflected in the user interface of the computing device 750. For example, if the self-propelled device 710 is illuminated, its virtual representation of the user interface of the computing device 750 may change to reflect that illumination.

[0189] FIG. 14A through FIG. 14C, discussed below, provide further examples and extensions of embodiments in which the self-propelled device is represented in a virtual context on the controller device.

[0190] User Control Orientation

[0191] FIG. 11A through FIG. 11C illustrate an embodiment in which a user interface of a controller is oriented to adopt an orientation of a self-propelled device, according to one or more embodiments. In embodiments shown, a self-propelled device 1102 maintains a pre-determined reference frame that indicates, for example, a forward facing direction. With reference to FIG. 11A, the self-propelled device 1102 is shown to be spherical, although other form factors may be adopted (including crafts or vehicles). As a spherical device, however, self-propelled device 1102 is relatively featureless and lacks structure that would otherwise indicate to the observer what the device's frame of reference is, such as what

the forward-facing direction of the device is. In order to identify the frame of reference, the self-propelled device **1102** can optionally include an outwardly visible marker **1104** or surface feature that identifies the frame of reference. For example, the marker **1104** can correspond to a light-emitting component that illuminates to mark a forward-facing surface **1106** of the device. The light-emitting component can, for example, correspond to a light emitting diode (LED) that resides with the exterior of the device, or alternatively, within the interior of the device so as to illuminate the forward-facing surface **1106** from within the (e.g., the exterior of the device may be translucent).

[0192] The device **1102** can maintain its own frame of reference, using resources that reside on the device. For example, device **1102** may utilize sensors such as a magnetometer (determine north, south, east west), an IMU (see FIG. **8D**), a GPS, and/or stored position or state information in order to determine its frame of reference.

[0193] FIG. **11B** illustrates a controller device **1120** for controlling the self-propelled device **1102**. The controller device **1120** includes a display screen **1121** on which a user-interface feature **1122** is provided to enable control of the self-propelled device **1102**. The user-interface feature **1122** may enable the user to enter, for example, directional input in order to steer the self-propelled device **1102**. According to embodiments, the orientation of the user-interface feature **1122** is calibrated to match the orientation of the self-propelled device **1102**, based on the frame of reference maintained on the self-propelled device **1102**. For example, the user-interface feature **1122** may include a marker **1124** that serves as a point of contact for interaction with the user. The relative orientation of the marker **1124** on the user-interface feature **1122** may be set to match the orientation of the marker **1104** of the self-propelled device **1102**. Thus, in the example provided, the forward-facing orientation of the self-propelled device **1102** may be directed west, and the user may maintain the forward-direction by keeping the marker **1124** in the west direction.

[0194] According to embodiments, the orientation of the self-propelled device **1102** with respect to the device's internal frame of reference dictates the orientation of the user-interface **1122** (e.g., the direction of the marker **1124**). For example, FIG. **11C** can serve as an illustration of the controller **1120** being rotated (e.g., the user moves the controller while holding it) relative to the self-propelled device **1102**. The marker **1124** of the user-interface **1122** may be set to the orientation of the marker **1104** on the self-propelled device **1102**, so that, for example, the west direction remains forward-facing.

[0195] FIG. **11D** illustrates a method for calibrating a user-interface for orientation based on an orientation of the self-propelled device, according to an embodiment. While reference is made to elements of FIG. **11A** through FIG. **11C** for purpose of illustrating suitable elements or components for performing a step or sub-step being described, an embodiment such as described by FIG. **11D** may be readily employed with other forms of devices.

[0196] The self-propelled device **1102** operates to determine its orientation, relative to an internal frame of reference that is determined from resources of the device (**1150**). The self-propelled device **1102** can determine its orientation in response to events such as the self-propelled device **1102** (i) being switched on, (ii) being connected wirelessly to the controller device **1120**, (iii) after a set duration of time, (iv)

after user input or command, and/or (v) after a designated event, such as a bump that makes the device "lost".

[0197] The self-propelled device **1102** signals information to the controller **1120** that indicates the orientation of the self-propelled device **1102** relative to the device's frame of reference (**1160**). The information may be signaled wirelessly through, for example, BLUETOOTH or other forms of wireless communication mediums.

[0198] The controller **1120** may initiate a program or application to control the self-propelled device **1102** (**1170**). For example, a control program may be operated that initiates the controller **1120** in connecting with the self-propelled device **1102**. The program may generate a user-interface **1122** that displays content in the form of a virtual controller for the self-propelled device **1102**. The virtual controller can include a marker or orientation that indicates front/back as well as left/right.

[0199] Based on the information received from the self-propelled device **1102**, the controller **1120** configures the user-interface **1122** so that the marker or orientation is aligned or otherwise calibrated with the orientation maintained on the device (**1180**). For example, as a result of the calibration or alignment, both the self-propelled device **1102** and the controller **1120** recognize the frontal direction to be in the same direction (e.g. north or west).

[0200] Numerous variations may be provided to the examples provided. For example, the user-interface **1122** can include alternative steering mechanisms, such as a steering wheel or virtual joystick (see also FIG. **12A**). The manner in which the user-interface **1122** can be configured to provide directional input can also be varied, depending on, for example, the virtual model employed with the user-interface (e.g., steering wheel or joystick).

[0201] Controller Interface and Usage Scenarios

[0202] FIG. **12A** and FIG. **12B** illustrate different interfaces that can be implemented on a controller computing device. In FIG. **12A**, content corresponding to a steering mechanism is illustrated to control the velocity and direction of a self-propelled device. In FIG. **12B**, content corresponding to a gaming interface (e.g., golf) is depicted that shows a representation of the self-propelled device in the form of a golf ball. The user can interact with the devices shown (e.g., take golf swing with the controller/computing device) to direct the self-propelled device to move. In turn, the content generated on the computing device can be reconfigured or altered. In particular, the representation of the self-propelled device can be affected. For example, the golf ball may be depicted as moving when the self-propelled device moves.

[0203] FIG. **13A** through FIG. **13C** illustrate a variety of inputs that can be entered on a controller computing device to operate a self-propelled device, according to an embodiment. In FIG. **13A** and FIG. **13B**, the user can be prompted by graphic features **1302** to place fingers on a given area of a display screen **1304**. For example, two finger positioning can be used for a golf example, and three finger positioning can be used for a bowling example. With fingers placed, the device **1300** can be moved in an arc motion to simulate a golf stroke or bowler arm motion (FIG. **13C**). The examples illustrate cases in which multiple types of input are combined and interpreted as a set of commands with one or more parameters (e.g., parameters dictating direction and velocity or position of the self-propelled device). For example, a guided touch screen input (first type of input) performed concurrently with movement of the controller device (second type of input) in an

arc fashion can be interpreted as a command to move the self-propelled device in a given direction for a designated distance (e.g., for golfing or bowling examples).

[0204] Virtual Object Representation and Interaction

[0205] Some embodiments enable the self-propelled device to be virtually represented on an interface of the controller device. In such embodiments, the degree to which the self-propelled device and its virtual representation are linked may vary, depending on desired functionality and design parameters. For example, in gaming applications, some events that occur to the self-propelled device (e.g., bumps) may be conveyed and represented (e.g., virtual bump) with the device representation.

[0206] With reference to FIG. 14A, the self-propelled device 1400 may be operated in a real-world environment, and virtually represented by a graphic object 1412 that is part of the user-interface of the controller device 1402. The implementation may be provided by executing a corresponding program or instruction set on each of the self-propelled device 1400 and controller device 1402 (e.g., a game). Based on the implemented instruction set, a relationship can be established between the self-propelled device 1400 and the virtual representation 1412. The relationship can be established by way of the self-propelled device 1400 signaling state information 1405 to the controller device 1402, and the controller device signaling control information 1415 based on user-input and virtual events.

[0207] As described with other embodiments, the self-propelled device 1400 may operate in a three-dimensional reference frame and the controller device 1402 may operate in a two-dimensional reference frame. The self-propelled device 1400 can include a three-dimensional controller that processes two-control information 1415 (e.g., user input and virtual events) in its three-dimensional reference frame. The three-dimensional environment of the self-propelled device 1400 may be represented two-dimensionally on the controller device 1402.

[0208] Examples of the relationships can include: (i) the self-propelled device 1400 communicates its state (e.g., position information) to the controller device 1402, which reflects a corresponding change in the position of the virtual object 1412—for example, both the self-propelled device and the controller device 1402 may trace a similarly shaped path; (ii) the user can enter input that moves or changes position of the virtual representation 1412, and this change is reflected by real-world movement of the self-propelled device 1400; (iii) an event that occurs to the self-propelled device 1400 is conveyed and/or represented in the virtual environment of the virtual representation 1412—for example, the self-propelled device may collide with an object, causing lateral movement or stoppage, and this event may be communicated virtually with the object 1412 being bumped, stopped or even made to change color to reflect the event; and (iv) an event that occurs to the virtual environment of the virtual representation 1412 is conveyed to the self-propelled device—for example, a virtual collision between the virtual representation 1412 and another virtual object (e.g., wall, zombie, etc. in gaming environment) may result in the movement of the virtual object 1412 being changed, and this change may be communicated as control input to the self-propelled device 1402 which can shake, stop or move unexpectedly to simulate the virtual collision). Numerous variations may be implemented with respect to the manner in which the self-propelled device is linked to a virtual environment.

[0209] FIG. 14B and FIG. 14C illustrate an application in which a self-propelled device acts as a fiducial marker, according to an embodiment. In the example shown, a gaming environment is provided in which the user can steer the self-propelled device through, for example, tilting or movement of the controller computing device 1430. While the self-propelled device is moved, the controller computing device displays content that includes both virtual objects 1432 and the representation 1434 of the self-propelled device. Based on the rules and object of the game, the user can steer the self-propelled device and cause the virtual representation 1434 to move on the screen in a manner that reflects the real movement of the self-propelled device. As noted in FIG. 14A, events such as collisions between the self-propelled device 1430 and its environment, can be communicated and represented with the virtual representation 1434 and its environment. Likewise, events that occur between the virtual representation 1434 and the virtual environment (e.g., wall or zombie collision) can be communicated and implemented on the self-propelled device 1402 (e.g., the device may veer left).

[0210] FIG. 15 illustrates an interactive application that can be implemented for use with multiple self-propelled devices, depicted as spherical or robotic balls, under an embodiment. In FIG. 15, system 1500 creates an ad-hoc network to arrange a number of self-propelled robotic balls into a desired pattern on a planar surface 1515. For example, the balls may be automatically arranged into a character, word, logo, or other meaningful or visually interesting arrangement. Five robotic balls 1510, 1512, 1514, 1516, and 1518 are shown for illustration, but this does not imply any limit to the number of robotic ball devices that can be included.

[0211] Video camera 1502 captures images of the robotic balls on surface 1515 and relays the image to computer/controller 1506 using data link 1504. Computer/controller 1506 executes an application designed to identify the robotic balls and instruct each robotic ball in moving to its desired position. Computer controller 1506 forms an ad-hoc network via link 1506 with robotic balls 1510, 1512, 1514, 1516, and 1518 to send instructions to each ball. Link 1506 can, in one embodiment, be a link to a single ball, and each ball is communicated with in turn. In another embodiment, link 1506 connects to two or more of the robotic balls, or is a broadcast channel to all robotic balls.

[0212] One task controller 1506 performs is identification of each ball and its location. To perform this task, in one embodiment controller 1506 sequentially instructs each ball to emit a unique signal detectable by camera 1502 in conjunction with controller 1506 and associated application software. The signal may be detectable by a human or not. For example, a ball 1510 emits a certain color or pattern of light. In one embodiment, the ball's light pattern is modulated in a manner detectable by video camera 1502 and controller 1506. In another embodiment, every ball in the array is instructed to simultaneously emit its own unique identification signal or light pattern.

[0213] Once every robotic ball on surface 1515 has been identified and located by controller 1506, controller 1506 issues a set of movement instructions to each robotic ball to move it into the desired location.

[0214] FIGS. 16A and 16B illustrate a method of collision detection, according to an embodiment. In FIG. 16A, collision event 1600 occurs when self-propelled device 1602 collides with fixed object 1604. A collision event causes a sudden negative acceleration in self-propelled device 1602. Device

1601, in one embodiment, is equipped with multi-axis accelerometers for sensing acceleration. The data from the accelerometer sensors shows a distinctive pattern indicating a collision event has occurred. In one embodiment, collision detection occurs in onboard processing of device **1602**. If self-propelled device **1602** has established a network connection with another device, either a controller or another self-propelled device, then collision detection can occur in any connected device.

[0215] FIG. 16B shows a more complex case of a collision event **1620** between two self-propelled devices **1622** and **1624**. In the event of a collision between two self-propelled devices, it may be the case that one was in motion or that both were in motion, prior to the collision. Detection of a collision between two self-propelled devices requires that a processor receive data from both devices, and that the data be tagged to allow time-correlation of collision events. If two collision events occur at the nearly the same time in two self-propelled devices, it is inferred that the two devices were involved in a collision event—they collided with each other. Further filtering is possible, for example to determine if the two devices were in close proximity, or if either was moving toward the other at the time the collision event was detected. Filtering increases the probability of accurately detecting a collision event from acceleration data. Collision detection can be useful in games and in applications that require detection of walls and obstacles.

CONCLUSION

[0216] One or more embodiments described herein provide that methods, techniques and actions performed by a computing device are performed programmatically, or as a computer-implemented method. Programmatically means through the use of code, or computer-executable instructions. A programmatically performed step may or may not be automatic.

[0217] One or more embodiments described herein may be implemented using programmatic modules or components. A programmatic module or component may include a program, a subroutine, a portion of a program, or a software component or a hardware component capable of performing one or more stated tasks or functions. As used herein, a module or component can exist on a hardware component independently of other modules or components. Alternatively, a module or component can be a shared element or process of other modules, programs or machines.

[0218] Furthermore, one or more embodiments described herein may be implemented through the use of instructions that are executable by one or more processors. These instructions may be carried on a computer-readable medium. Machines shown or described with FIGs below provide examples of processing resources and computer-readable mediums on which instructions for implementing embodiments of the invention can be carried and/or executed. In particular, the numerous machines shown with embodiments of the invention include processor(s) and various forms of memory for holding data and instructions. Examples of computer-readable mediums include permanent memory storage devices, such as hard drives on personal computers or servers. Other examples of computer storage mediums include portable storage units (such as CD or DVD units), flash memory (such as carried on many cell phones and personal digital assistants (PDAs)), and magnetic memory. Computers, terminals, network enabled devices (e.g., mobile devices such as cell phones) are all examples of machines and devices that

utilize processors, memory and instructions stored on computer-readable mediums. Additionally, embodiments may be implemented in the form of computer-programs, or a computer usable carrier medium capable of carrying such a program.

[0219] Although illustrative embodiments have been described in detail herein with reference to the accompanying drawings, variations to specific embodiments and details are encompassed by this disclosure. It is intended that the scope of the invention is defined by the following claims and their equivalents. Furthermore, it is contemplated that a particular feature described, either individually or as part of an embodiment, can be combined with other individually described features, or parts of other embodiments. Thus, absence of describing combinations should not preclude the inventor(s) from claiming rights to such combinations.

[0220] While certain embodiments of the inventions have been described above, it will be understood that the embodiments described are by way of example only. Accordingly, the inventions should not be limited based on the described embodiments. Rather, the scope of the inventions described herein should only be limited in light of the claims that follow when taken in conjunction with the above description and accompanying drawings.

What is claimed is:

1. A method for operating a self-propelled device, the method comprising:
 - maintaining, on the self-propelled device, a frame of reference about an x-, y- and z-axis;
 - processing an input to control the self-propelled device, wherein the input is based on the x- and y-axis;
 - controlling the self-propelled device in its movement, including controlling the self-propelled device about each of the x-, y- and z-axis, based on the input.
2. The method of claim 1, wherein the self-propelled device is dynamically unstable when in movement about one or more of the x-, y- or z-axis, and wherein controlling the self-propelled device includes processing feedback from movement of the self-propelled device to compensate for the self-propelled device's instability about the z-axis.
3. The method of claim 1, wherein processing the feedback includes processing input from a gyroscope.
4. The method of claim 1, wherein processing the feedback includes processing input from an accelerometer.
5. The method of claim 1, wherein processing the feedback includes processing input from an inertial measurement unit.
6. The method of claim 1, wherein the self-propelled device is spherical.
7. The method of claim 1, wherein the input is received wirelessly from a controller device.
8. The method of claim 7, wherein the input is generated from a user interaction with a two-dimensional user interface provided on the controller device.
9. The method of claim 8, wherein the two-dimensional user interface is a graphic user interface that is generated on a display screen of the controller device.
10. The method of claim 9, wherein the graphic user interface includes a steering mechanism.
11. A system comprising:
 - a controller device;
 - a self-propelled device, operable to move under control of the controller device, the self-propelled device maintaining a frame of reference about an x-, y- and z-axis;

wherein the controller device provides an interface to enable a user to enter two-dimensional control input about the x- and y-axes; and

wherein the self-propelled device processes the control input from the controller device in order to maintain control relative to the x-, y- and z-axes.

12. The system of claim **11**, wherein the self-propelled device is dynamically unstable when in movement about one or more of the x-, y- or z-axes, and wherein the self-propelled device includes processing feedback from movement of the self-propelled device to compensate for the self-propelled device's instability about the one or more of the x-, y- or z-axes.

13. The system of claim **12**, wherein the self-propelled device processes feedback from a gyroscope.

14. The system of claim **12**, wherein the self-propelled device processes feedback from an accelerometer.

15. The system of claim **12**, wherein the self-propelled device processes feedback from an inertial measurement unit.

16. The system of claim **11**, wherein the self-propelled device is spherical.

17. The system of claim **11**, wherein the controller device is a multifunctional wireless device.

18. The system of claim **17**, wherein the controller device is a smart phone or a tablet.

19. The system of claim **11**, wherein the controller device generates the input from a user interaction with a two-dimensional user interface provided on the controller device.

20. The system of claim **19**, wherein the two-dimensional user interface is a graphic user interface that is generated on a display screen of the controller device.

21. The system of claim **20**, wherein the graphic user interface includes a steering mechanism.

22. A self-propelled device comprising:

a drive system to move the self-propelled device; and
a control system to:

maintain a frame of reference about an x-, y- and z-axes;
process a control input from a controller device that is specific to the x- and y-axes;

use the control input to implement control on the drive system relative to the x-, y- and z-axes in moving the device.

23. The self-propelled device of claim **22**, wherein the control system processes feedback from movement of the self-propelled device to compensate for the self-propelled device's instability about one or more of the x-, y- or z-axes.

24. The self-propelled device of claim **23**, wherein the control system implements an inertial measurement unit to generate the feedback based on input from a set of sensors.

25. The self-propelled device of claim **23**, wherein the set of sensors include one or more of a gyroscope and/or accelerometer.

26. The self-propelled device of claim **22**, wherein the self-propelled device includes a spherical housing.

* * * * *