



US 20130005512A1

(19) **United States**(12) **Patent Application Publication****Joseph et al.**(10) **Pub. No.: US 2013/0005512 A1**(43) **Pub. Date:****Jan. 3, 2013**

(54) **SYSTEM AND METHOD FOR IMPROVING A BASKETBALL PLAYER'S SHOOTING INCLUDING A DETECTION AND MEASUREMENT SYSTEM**

**Publication Classification**(51) **Int. Cl.***A63B 69/40*

(2006.01)

(52) **U.S. Cl.****473/431**

(57)

**ABSTRACT**

A system and method for improving a player's efficiency in shooting by providing a player with various shooting challenge routines at which a player makes either a total number of shots or a total number shots in a row. Statistics regarding the player's performance are stored, printed and/or evaluated and the player can use the information to improve his or her efficiency at one or more of the plurality of different locations where the player shoots the basketball. In another embodiment, a measuring or detection system is used in combination with or separate from a ball launcher. The system is adapted to measure at least one of a distance of a player from the a launcher, height of a shot made by the player after catching a basketball, release angle, release time, or arc of a shot; entry angle of the basketball into a goal; hold or release time; or shot arc.

(75) Inventors: **John G. Joseph**, Upper Sandusky, OH (US); **Troy David Geiser**, Findlay, OH (US); **Albert Charles Abnett**, Nevada, OH (US)


(73) Assignee: **SHOOT-A-WAY, INC.**, Upper Sandusky, OH (US)


(21) Appl. No.: **13/529,917**


(22) Filed: **Jun. 21, 2012**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/420,122, filed on Apr. 8, 2009, now Pat. No. 8,206,246.









**FIG. 3**



FIG. 3A






FIG. 3C

**STEP 3** Number of S

Select the number of shots per location.

Enter 000 for in

**To Challenge Shooting Accuracy**

For advanced shooters, no. of shots must be NEXT SPOT. For example, if 5 shots selected & the shooter must make 5 shots before 8000 series

**For Guns Equipped with SHOT T**

S2

USER

S1

PRINT

Press USER BUTTON then enter your 3 Digit Code using balls numbered 0-9 around the 3 Point arch in Step 1. Code shows in Step 3. Press Pre Program Drill Button to finish. If EEE shows, code is wrong or doesn't exist. Press USER, then Pre Program Drill button to clear SHOT TRACKING for next shooter.

Press Print Button to Print Workout Rcpt, which includes USERS current workout, USERS yearly workout totals, and USERS career workout totals.

A

POWER

Shoot-

1-800-

www.sho





FIG-4

45

USER NAME: JOHN SMITH - USER DEFINED PERIOD					11-1-09 3-2-10
SHOT	MAKES	TOTAL ATTEMPTS	MAKES IN A ROW	TOTAL MAKES	PERCENTAGE TOTAL MAKES/ TOTAL ATTEMPTS
55		56	50	58	60

FIG-5



**Fig. 6: Example Printout**

Shooting Workout Printout

User: Joe Thomas

User defined Time Period: 1/1/09 to 3/26/09

Spot	Makes	Total Shots	Percentage
0	453	634	71.5%
1	200	234	85.5%
2	100	243	41.2%
3	121	323	37.5%
4	123	232	53.0%
5	105	234	44.9%
6	178	343	51.9%
7	186	343	54.2%
8	543	1006	54.0%
9	66	132	50.0%
10	80	232	34.5%
11	109	343	31.8%
12	243	545	44.6%
13	116	343	33.8%
14	298	545	54.7%
15	100	232	43.1%
16	180	423	42.6%
TOTAL	3201	6387	50.1%

FIG. 7

CHALLENGE SHOOTING ACCURACY – MAIN PROCEDURE




FIG. 8  
CHALLENGE SHOOTING ACCURACY - PROCEDURE A







FIG. 9

Challenge Shooting Accuracy - Procedure B

Multi Shots which MUST BE MADE at 1 or Each Spot






FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13A




FIG. 13B






FIG. 13C



COMPUTE ENTRY ANGLE  $\theta_e$  TO BASKET

Fig. 13D



AT ANY POINT P:

$$(1) Y = V_{oy}T - \frac{1}{2} g T^2$$


$$(2) X = V_{ox}T \quad \text{OR} \quad T = X / V_{ox}$$

Y IS VERTICAL POSITION

X IS HORIZONTAL POSITION

 $V_{oy}$  IS VERTICAL VELOCITY COMPONENT, UPON SHOOTING $V_{ox}$  IS HORIZONTAL VELOCITY COMPONENT, UPON SHOOTING

FIG. 13E



$$\text{COMBINE EQUATIONS (1) AND (2): } Y = (X v_{oy} / v_{ox}) - 1/2 g (X^2 / v_{ox}^2) \quad (3)$$

SUBSTITUTE VALUES OF X AND Y AT BASKET:

$$D_B = (D v_{oy} / v_{ox}) - 1/2 g (D^2 / v_{ox}^2) \quad (3A)$$

MULTIPLY BY  $v_{ox}^2$  AND RE-ARRANGE

$$v_{oy} = (D_B v_{ox}^2 + 1/2 g D^2) / D v_{ox} \quad (4)$$

FIG. 13F





Fig. 13G



FOR A GENERALIZED BODY TRAVELLING VERTICALLY, TO A HEIGHT H  
 $(1/2) M V^2 = M g H$  WHERE M IS MASS, g IS ACCELERATION OF GRAVITY  
 AND V IS VERTICAL VELOCITY.

THAT IS, THE BODY INITIALLY HAD ONLY KINETIC ENERGY  
 AND ALL THAT IS CONVERTED INTO POTENTIAL ENERGY.

SOLVE FOR H:  $H = V^2 / 2g$

SUBSTITUTE  $D_A$  FOR H AND  $v_{oy}$  FOR V:  $D_A = v_{oy}^2 / 2g$  (5)

Fig. 13H




Fig. 13I




FIG- 14







FIG. 15A






FIG. 15A1





FIG. 15A2

FIG. 15B







FIG. 15B1

FIG. 15B2



**FIG. 15C**

FIG. 15D






FIG. 16 (OVERALL)




FIG. 17

## Procedures and Methods for a Coach to Register the Gun




FIG. 18

## Procedure to Create a Roster on Website for Download




FIG. 19

## Procedure to Download Rosters to the Gun




FIG. 20




FIG. 21

Procedure to Calibrate The Gun Shooting Machine for  
Accurate Data Collection




FIG. 22




FIG. 23A

NOT DEPENDANT ON DOPPLER

Procedure to select Shooting workout for Shooter and for the Gun to collect & save made shots & total shots at each shooting location






FIG. 23B




FIG. 24A




FIG. 24B




FIG. 25




FIG. 26

Procedure to upload shooting sessions to Website




FIG. 27

NOT DEPENDENT ON DOPPLER OR DOPPLER DEPENDENT  
Procedure to Create Customized Reports on Website




FIG. 28A

NOT DEPENDENT ON DOPPLER  
PROCEDURE TO USE REAL TIME CHALLENGE MODE ON THE GUN FOR  
TWO PLAYERS TO LOG INTO THE SAME GUN AND SHOOT AGAINST EACH OTHER





FIG. 28B





## SHOOTING CHALLENGE FOR PLAYERS FROM DIFFERENT TEAMS AT DIFFERENT LOCATIONS

FIG. 29




FIG. 30




FIG. 31

268

270

THE GUN SHOT TRACKER by Shoot-A-Way

Email and Auth Code Accepted

### Create an Account

First Name

Last Name

Username

Password

Confirm Password


REMEMBER YOUR USER NAME and PASSWORD. You will need it along with your Username whenever you log into the Gun to spread shooting sessions, review shooting totals and export team changes to your CLUB.

E-Mail Address


Confirm E-Mail Address

FIG. 32

272



324



Hi Tom, Please click the link below and enter your username. That's all along with your password. It might be a good idea to add this link to your internet favorites as it will allow you to log on to and manage your GUN SHOT TRACER account. Again write down your username and password for future use.

100

## General Overview of Case Study Package system

Surround Your Team to the USGS Flood Drive.

Now you may add your players (up to 27 per team). Each player will be assigned a 3-digit code that they will enter each time they shoot on the Gun. Once this roster has been entered here on the Gun Shot Tracker Website, you will be prompted to export it to a HANK thumb drive. Then, simply take this HANK drive to the Gun and download it with the Gun powered up, using the "import" button. If the Gun's control board shows FFF when you import the file, a bit not read correctly and you will have to try saving it to your thumb drive again. If FFF's are not displayed, you may remove the USB Flash Drive and have your players begin and begin shooting, while the Gun Tracks their shooting data.

Two T-man officers with the Sheriff's Commission can be contacted by the Gun Shot Tracker

The Gun Shot Tracker site will allow for two groups (teams) to be tagged to 1 Gun's Serial Number. For example, if a High School boys and girls team purchased the Gun together, the Gun Shot Tracker site will allow for two groups (teams) to be tagged to 1 Gun's Serial Number. It will be important that each team has created an account tied to the Gun's Serial Number and Authenticity Code, and for them to input their roster onto the Gun through the above process.

NOTE: Once two users register to 1 Gsm, no other users will be able to register to that Gsm unless 1 of the other registered users is deleted.

Learn to Love Your Shingles


Long the way, however, remember that you and your players (up to 27) will be allowed to log onto the Gun by pressing the USER button; enter their 5 digit code, press the Pre-Programmed Data button. If their 5 digit code shows up on the front scoreboard for 2 seconds, the Gun has recognized them and it is ready to track their shooting totals.


You will no longer need to use the "insert" button unless you need to edit your team. Now, your players' shots are ready to be tracked.

Continued from p. 10

Insert your USB Flash Drive into the USB port on the Gun. Press the Export Nits to Computer button. Log onto your Gun Shot Tracker account and upload revisions by using the Import tab at the top of the Gun Shot Tracker website.

FIG. 34







80







FIG. 37



39




FIG. 39





FIG. 40



455

FIG. 41




FIG. 42

Individual Shooting Report for Kevin Curtis




FIG. 43










FIG. 46

730

Not Dependant on Doppler Player/Team or USA the World Rankings		Sorting variables to create custom charts
Headings	Quantifiers	Explanation of Quantifiers
1 Choose Player	Roster List	Chose any player on your roster or entire team
2 Minimum Age	Any	range from 1 - 150 <= Maximum Age
3 Maximum Age	Any	range from 1 - 150 >= Minimum Age
4 Beginning Date	All	Beginning date <= Ending date
5 Ending Date	All	Ending date >= Beginning date
6 Gender	Both, M, F	Male, Female or include all shooters
7 Enter Shooting Locations	All	0 through 17
8 Chart Type	Makes/Total Shots/%	Sort based on makes, total shots or shooting %
9 City	All	Choose City
10 County	All	Choose County
11 State	All	Choose State
12 Country	All	Choose Country

FIG. 47

## Example #1

(Example 1 INPUT Information)

1 Choose Player	John Drew
2 Minimum Age	14
3 Maximum Age	25
4 Beginning Date	6/1/2009
5 Ending Date	12/15/2010
6 Gender	M
7 Enter Shooting Locations	All
8 Chart Type	Total Shots
9 City	All
10 County	All
11 State	All
12 Country	United States

732



FIG. 48

730

(Example #1 Custom Created Report)

Player/Team or USA vs the World Rankings				
Total Shots from all shooting locations from 6/1/09 to 12/15/10 for males age range 14-25 for John Drew				
Rank	Name	State	School	Total
1	Ted Robinson	AR	Rison	623,567
2	Mike Johnson	TN	Cordova	511,343
3	Tim Worley	KS	Kansas University	198,565
4	Ron Jeffersson	NM	Gallup HS	191,233
5	Ted Jackson	NC	UNCC	190,343
6	Mary Fredrick	TN	Memphis HS	185,343
7	Heather Jones	CA	Jackson	183,232
8	Frank Tedford	AZ	Hanie Skills	180,232
9	Robert Ele	OH	Upper Defense	177,656
10	Tiffany Robinson	CA	Point Arena HS	165,454
11	Tom Watson	CA	FootHill HS	161,232
12	Mike Jackson	TX	Alto HS	160,334
13	John Drew	CO	Sangre	155,343
14	Tim Whenton	GE	Wilwood	154,343
15	Mak Ames	FL	Florida Gator's	150,232
16	Joetta Cooley	AZ	Scottsdale AZ	145,343
17	Joe Drew	CO	Sangre de Cristo	141,223
18	Mike Watson	MI	St. Louis HS	139,343
19	Heather Johnson	OH	Lima HS	135,354
20	Kevin Curtis	CA	USC	134,232
21	Jeff George	MN	St. Paul West HS	131,232
22	Jermaine Watson	SC	Myrtle Beach HS	129,434
23	Avery Elliot	NC	Durham HS	128,343
24	Christy Robinson	TX	Union City HS	125,324
25	Michael Drew	SD	Howard	119,232

FIG. 49

## Example #2

(Example #2 INPUT Information)

1 Choose Player	TEAM Sangre
2 Minimum Age	all
3 Maximum Age	all
4 Beginning Date	all
5 Ending Date	all
6 Gender	M
7 Enter Shooting Locations	spot 8
8 Chart Type	Total Makes
9 City	All
10 County	All
11 State	Colorado
12 Country	United States

FIG. 50

740

(Example #2 Custom Created Report)

Player/Team or USA vs the World Rankings		
Total Makes for all dates from shooting location 8 for Colorado Male teams.		
Rank	Team	Total
1	Alamosa	623,567
2	Sangre	511,343
3	Sargent	198,565
4	Stratton	191,233
5	Pagosa	190,343
6	Centauni	185,343
7	Creed	183,232
8	Center	180,232
9	Monte Vista	177,656
10	Buna Vista	165,454
11	Denver East	161,232
12	Denver West	160,334
13	Pueblo East	155,343
14	Sierra Grande	154,343
15	Mt. Valley	150,232
16	Grand Junction	145,343
17	Wray	141,223
18	Eads	139,343
19	Swink	135,354
20	Simila	134,232
21	La Junta	131,232
22	Lamar	129,434
23	John Mall	128,343
24	La Veta	125,324
25	Sanford	119,232

FIG. 51

Doppler Dependant Player/Team or USA the World Rankings			Sorting variables to create custom charts
Headings		Quantifiers	Explanation of Quantifiers
1 Choose Player	Roster List	Chose any player on your roster	
2 Minimum Age	Any	range from 1 - 150 <= Maximum Age	
3 Maximum Age	Any	range from 1 - 150 >= Minimum Age	
4 Beginning Date	All	Beginning date <= Ending date	
5 Ending Date	All	Ending date >= Beginning date	
6 Gender	Both, M, F	Male, Female or include all shooters	
7 Enter Shooting Locations	All	0 through 17	
8 Shooting Distance	All	13, 14, 15, 16, 17, 18, 19, 20, 21+, all	
9 Chart Type	Makes/Total Shots/%	Sort based on makes, total shots or shooting %	
10 City	All	Choose City	
11 County	All	Choose County	
12 State	All	Choose State	
13 Country	All	Choose Country	

742

FIG. 52

## Example #1

(Example #1 INPUT Information)

1 Choose Player	John Drew
2 Minimum Age	14
3 Maximum Age	25
4 Beginning Date	6/1/2009
5 Ending Date	12/15/2010
6 Gender	M
7 Enter Shooting Locations	All
8 Shooting Distance	20 feet away
9 Chart Type	Total Shots
10 City	All
11 County	All
12 State	All
13 Country	United States



FIG. 53

743

(Example #1 Custom Created Report)

Player/Team or USA vs the World Rankings				
Total Shots from all shooting locations from 6/1/09 to 12/15/10 for males age range 14-25 at a distance of 20 feet for John Drew				
Rank	Name	State	School	Total
1	Ted Robinson	AR	Rison	623,567
2	Mike Johnson	TN	Cordova	511,343
3	Tim Worley	KS	Kansas University	198,565
4	Ron Jeffersson	NM	Gallup HS	191,233
5	Ted Jackson	NC	UNCC	190,343
6	Mary Fredrick	TN	Memphis HS	185,343
7	Heather Jones	CA	Jackson	183,232
8	Frank Tedford	AZ	Hanie Skills	180,232
9	Robert Ele	OH	Upper Defense	177,656
10	Tiffany Robinson	CA	Point Arena HS	165,454
11	Tom Watson	CA	FootHill HS	161,232
12	Mike Jackson	TX	Alto HS	160,334
13	John Drew	CO	Sangre	155,343
14	Tim Whenton	GE	Wilwood	154,343
15	Mak Ames	FL	Florida Gators	150,232
16	Joetta Cooley	AZ	Scottsdale AZ	145,343
17	Joe Drew	CO	Sangre de Cristo	141,223
18	Mike Watson	MI	St. Louis HS	139,343
19	Heather Johnson	OH	Lima HS	135,354
20	Kevin Curtis	CA	USC	134,232
21	Jeff George	MN	St. Paul West HS	131,232
22	Jermaine Watson	SC	Myrtle Beach HS	129,434
23	Avery Elliot	NC	Durham HS	128,343
24	Christy Robinson	TX	Union City HS	125,324
25	Michael Drew	SD	Howard	119,232

FIG. 54

## Example #2

(Example #2 INPUT Information)

1 Choose Player	TEAM Sangre
2 Minimum Age	all
3 Maximum Age	all
4 Beginning Date	all
5 Ending Date	all
6 Gender	M
7 Enter Shooting Locations	spot 8
8 Shooting Distance	15 feet
9 Chart Type	Total Makes
10 City	All
11 County	All
12 State	Colorado
13 Country	United States

FIG. 55

744

(Example #2 Custom Created Report)

Player/Team or USA vs the World Rankings		
Total Makes for all dates from shooting location 8 for Colorado Male teams at a distance of 15 feet		
Rank, Team	State	Total
1 Alamosa	CO	623,567
2 Sangre	CO	511,343
3 Sargent	CO	198,565
4 Stratton	CO	191,233
5 Pagosa	CO	190,343
6 Centauri	CO	185,343
7 Creed	CO	183,232
8 Center	CO	180,232
9 Monte Vista	CO	177,656
10 Buna Vista	CO	165,454
11 Denver East	CO	161,232
12 Denver West	CO	160,334
13 Pueblo East	CO	155,343
14 Sierra Grande	CO	154,343
15 Mt. Valley	CO	150,232
16 Grand Junction	CO	145,343
17 Wray	CO	141,223
18 Eads	CO	139,343
19 Swink	CO	135,354
20 Simila	CO	134,232
21 La Junta	CO	131,232
22 Lamar	CO	129,434
23 John Mall	CO	128,343
24 La Veta	CO	125,324
25 Sanford	CO	119,232

FIG. 56

(This chart is a list of top 20 rankings for shooters using the Gun on a given day)

**Top 20 National Rankings for Team Upper Sandusky, Ohio**

**Date: December 15, 2011**

<i>Ranking</i>	<i>Total Shots Taken</i>	<i>State</i>	<i>School</i>	<i>Number</i>
1	M. Johnson	PA	East HS	8,543
<b>2</b>	<b>T. Tedford</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>7,644</b>
3	H. Mikelson	TX	Wattford	6,445
4	J. Johnson	IL	Sangre	5,434
5	L. Berry	CA	Monte Vista	5,344
6	M. Terry	CA	West HS	5,000
7	M. Robinson	MD	Metford	4,567
8	S. Adams	WA	Johnson	4,322
9	M. Curtis	NE	Eastbay	3,400
10	K. Prior	MO	Sandusky	3,000
11	T. Allen	ND	St. Pats	2,545
12	K. Clair	FL	Jefferson	2,400
13	B. Brown	CA	Pueblo West	2,234
14	S. Heard	CO	Denver East	2,112
15	M. Lopez	TN	Knoxville	2,000
16	T. Vandouk	TX	Austin Central	1,923
17	B. Simpson	OR	Medford	1,901
18	M. Leach	TX	Lubbock	1,899
19	J. Crawford	MN	St. Paul	1,823
20	M. Eddy	OH	Carey	1,800
<b>643</b>	<b>M. Jones</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>543</b>
<b>822</b>	<b>T. Whenton</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>344</b>
<b>12,500</b>	<b>H. Duncan</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>123</b>
<b>21,356</b>	<b>J. Dudley</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>100</b>
<b>40,343</b>	<b>M. Anderson</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>70</b>
<b>59,943</b>	<b>T. Martinez</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>65</b>
<b>123,134</b>	<b>M. Davis</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>0</b>

750

750a

FIG. 57A

<i>Ranking</i>	<i>Total Shots Made</i>	<i>State</i>	<i>School</i>	<i>Number</i>
1	M. Johnson	PA	East HS	6,407
2	<b>T. Tedford</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>5,733</b>
3	H. Mikelson	TX	Wattford	4,834
4	J. Johnson	IL	Sangre	4,076
5	L. Berry	CA	Monte Vista	4,008
6	M. Terry	CA	West HS	3,750
7	M. Robinson	MD	Metford	3,425
8	S. Adams	WA	Johnson	3,242
9	M. Curtis	NE	Eastbay	2,550
10	K. Prior	MO	Sandusky	2,250
11	T. Allen	ND	St. Pats	1,909
12	K. Clair	FL	Jefferson	1,800
13	B. Brown	CA	Pueblo West	1,676
14	S. Heard	CO	Denver East	1,584
15	M. Lopez	TN	Knoxville	1,500
16	T. Vandouk	TX	Austin Central	1,442
17	B. Simpson	OR	Medford	1,426
18	M. Leach	TX	Lubbock	1,424
19	J. Crawford	MN	St. Paul	1,367
20	M. Eddy.	OH	Carey	1,350
643	M. Jones	OH	Upper Sandusky	407
822	T. Whenton	OH	Upper Sandusky	258
12,500	H. Duncan	OH	Upper Sandusky	92
21,356	J. Dudley	OH	Upper Sandusky	75
40,343	M. Anderson	OH	Upper Sandusky	53
59,943	T. Martinez	OH	Upper Sandusky	49
123,134	M. Davis	OH	Upper Sandusky	0

752

752a

FIG. 57B

<i>Ranking</i>	<i>Percentage</i>	<i>State</i>	<i>School</i>	<i>Number</i>
1	H. Brown	PA	East HS	99.90%
2	<b>M. Watson</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>99.85%</b>
3	S. Terry	TX	Wattford	99.00%
4	M. Applewood	IL	Sangre	97.65%
5	H. Jacobson	CA	Monte Vista	97.50%
6	.....			
7	.....			
8	.....			
9	.....			
10	.....			
11	.....			

754

FIG. 58

(This chart is a list of top 20 rankings for shooters using the Gun for a given AGE range)

**Top 20 National Rankings for Team Upper Sandusky, Ohio**

Age range of Shooters in the Ranking

Min Age: 16

Max Age 18

<i>Ranking</i>	<i>Total Shots Taken</i>	<i>State</i>	<i>School</i>	<i>Number</i>
1	M. Johnson	PA	East HS	1,122,233
2	<b>T. Tedford</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>993,343</b>
3	H. Mikelson	TX	Wattford	894,343
4	J. Johnson	IL	Sangre	785,454
5	L. Berry	CA	Monte Vista	734,469
6	.....			
7	.....			
8	.....			
9	.....			
10	.....			
11	.....			

756

FIG. 59

(This chart is a list of top 20 rankings for shooters using the Gun for a given DATE range)

**Top 20 National Rankings for Team Upper Sandusky, Ohio**

**Date Range: December 23, 2011 - December 22, 2012**

<i>Ranking</i>	<i>Total Shots Taken</i>	<i>State</i>	<i>School</i>	<i>Number</i>
1	M. Johnson	PA	East HS	1,122,233
2	<b>T. Tedford</b>	<b>OH</b>	<b>Upper Sandusky</b>	<b>993,343</b>
3	H. Mikelson	TX	Wattford	894,343
4	J. Johnson	IL	Sangre	785,454
5	L. Berry	CA	Monte Vista	734,469
6	.....			
7	.....			
8	.....			
9	.....			
10	.....			
11	.....			

758



FIG. 60

760

(Not Dependant on Doppler - This chart shows rankings from a shooting area)

Player/Team vs the Nation Shooting Report for Kevin Curtis, Team Upper Sandusky, OH

December 15, 2011

**Shooting Location 8** (could also be on locations 0-16)

Local Shooting (Team Upper Sandusky) Rankings for Kevin Curtis

760a

<b>RANKINGS</b>	<b>Today</b>	<b>Week</b>	<b>Month</b>	<b>Year</b>	<b>Lifetime</b>
<i>Total Shots</i>	1st	1st	1st	1st	1st
<i>Total Shots Made</i>	1st	1st	1st	2nd	2nd
<i>Shooting %</i>	1st	1st	1st	1st	1st
<b>Total Upper Sandusky Shooters</b>	6	12	14	55	132

Regional Shooting (Wyandot County) Rankings for Kevin Curtis

760b

<b>RANKINGS</b>	<b>Today</b>	<b>Week</b>	<b>Month</b>	<b>Year</b>	<b>Lifetime</b>
<i>Total Shots</i>	1st	1st	1st	1st	1st
<i>Total Shots Made</i>	1st	1st	1st	2nd	2nd
<i>Shooting %</i>	1st	2nd	1st	1st	1st
<b>Total Wyandot Shooters</b>	864	1,432	5,345	15,343	34,766

Statewide Shooting (Ohio) Rankings for Kevin Curtis

760c

<b>RANKINGS</b>	<b>Today</b>	<b>Week</b>	<b>Month</b>	<b>Year</b>	<b>Lifetime</b>
<i>Total Shots</i>	4th	1st	9th	5th	543rd
<i>Total Shots Made</i>	3rd	1st	9th	4th	342nd
<i>Shooting %</i>	2nd	5th	2nd	2nd	434th
<b>Total Ohio Shooters</b>	12,121	25,344	33,434	49,343	85,434

National Shooting (USA) Rankings for Kevin Curtis

760d

<b>RANKINGS</b>	<b>Today</b>	<b>Week</b>	<b>Month</b>	<b>Year</b>	<b>Lifetime</b>
<i>Total Shots</i>	28th	1st	21st	10th	123231st
<i>Total Shots Made</i>	9th	1st	17th	8th	9,384th
<i>Shooting %</i>	3rd	29th	5th	3rd	7,855th
<b>Total United States Shooters</b>	50,123	112,123	123,323	213,432	987,433

International Shooting (World) Rankings for Kevin Curtis

760e

<b>RANKINGS</b>	<b>Today</b>	<b>Week</b>	<b>Month</b>	<b>Year</b>	<b>Lifetime</b>
<i>Total Shots</i>	32nd	1st	23rd	12th	232,234th
<i>Total Shots Made</i>	11th	1st	18th	9th	11,232nd
<i>Shooting %</i>	3rd	34th	5th	3rd	8,453rd
<b>Total International Shooters</b>	65,434	132,332	155,234	244,002	1,323,323

FIG. 61

(Not dependant on Doppler)

Player/Team vs the Nation Shooting Report for Kevin Curtis, Team Upper Sandusky

December 15, 2011

770

770a

Local Shooting (Team Upper Sandusky) Rankings for Kevin Curtis

RANKINGS	Today	Percentile	Week	Percentile	Month	Percentile	Year	Percentile	Lifetime	Percentile
Total Shots	1	83.3%	1	91.7%	1	92.9%	1	98.2%	1	99.2%
Total Shots Made	1	83.3%	1	91.7%	1	92.9%	2	96.4%	1	99.2%
Shooting %	1	83.3%	1	91.7%	1	92.9%	1	98.2%	1	99.2%
Total Upper Sandusky Shooters	6		12		14		55		132	

770b

Regional Shooting (Wyandot County) Rankings for Kevin Curtis

RANKINGS	Today	Percentile	Week	Percentile	Month	Percentile	Year	Percentile	Lifetime	Percentile
Total Shots	1	99.9%	1	99.9%	1	100.0%	1	100.0%	1	100.0%
Total Shots Made	1	99.9%	1	99.9%	1	100.0%	2	100.0%	2	100.0%
Shooting %	1	99.9%	2	99.9%	1	100.0%	1	100.0%	1	100.0%
Total Wyandot Shooters	864		1,432		5,345		15,343		34,766	

770c

Statewide Shooting (Ohio) Rankings for Kevin Curtis

RANKINGS	Today	Percentile	Week	Percentile	Month	Percentile	Year	Percentile	Lifetime	Percentile
Total Shots	4	100.0%	1	100.0%	9	100.0%	5	100.0%	543	99.4%
Total Shots Made	3	100.0%	1	100.0%	9	100.0%	4	100.0%	342	99.6%
Shooting %	2	100.0%	5	100.0%	2	100.0%	2	100.0%	434	99.5%
Total Ohio Shooters	12,121		25,344		33,434		49,343		85,434	

770d

National Shooting (USA) Rankings for Kevin Curtis

RANKINGS	Today	Percentile	Week	Percentile	Month	Percentile	Year	Percentile	Lifetime	Percentile
Total Shots	28	99.9%	1	100.0%	21	100.0%	10	100.0%	123,231	86.7%
Total Shots Made	9	100.0%	1	100.0%	17	100.0%	8	100.0%	9,384	99.0%
Shooting %	3	100.0%	29	100.0%	5	100.0%	3	100.0%	7,855	99.1%
Total United States Shooters	50,123		112,123		123,323		213,432		923,434	

770e

International Shooting (World) Rankings for Kevin Curtis

RANKINGS	Today	Percentile	Week	Percentile	Month	Percentile	Year	Percentile	Lifetime	Percentile
Total Shots	32	100.0%	1	100.0%	23	100.0%	12	100.0%	232,234	82.5%
Total Shots Made	11	100.0%	1	100.0%	18	100.0%	9	100.0%	11,232	99.2%
Shooting %	3	100.0%	34	100.0%	5	100.0%	3	100.0%	8,453	99.4%
Total International Shooters	65,434		132,332		155,234		244,002		1,323,323	

FIG. 62

(Doppler Dependant - this chart would be a comparison of shots take from 15 ft. Could in fact be done at different distances for example 19.9 ft. or 22ft etc.)

Player/Team vs the Nation Shooting Report for Kevin Curtis, Team Upper Sandusky, OH

December 15, 2011

Distance: 15 Feet (could also be from 15-18 feet, or 19.9+ feet)

Local Shooting (Team Upper Sandusky) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	1st	1st	1st	1st	1st
Total Shots Made	1st	1st	1st	2nd	2nd
Shooting %	1st	1st	1st	1st	1st
Total Upper Sandusky Shooters	6	12	14	55	132

Regional Shooting (Wyandot County) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	1st	1st	1st	1st	1st
Total Shots Made	1st	1st	1st	2nd	2nd
Shooting %	1st	2nd	1st	1st	1st
Total Wyandot Shooters	864	1,432	5,345	15,343	34,766

Statewide Shooting (Ohio) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	4th	1st	9th	5th	543rd
Total Shots Made	3rd	1st	9th	4th	342nd
Shooting %	2nd	5th	2nd	2nd	434th
Total Ohio Shooters	12,121	25,344	33,434	49,343	85,434

National Shooting (USA) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	28th	1st	21st	10th	123231st
Total Shots Made	9th	1st	17th	8th	9,384th
Shooting %	3rd	29th	5th	3rd	7,855th
Total United States Shooters	50,123	112,123	123,323	213,432	987,433

International Shooting (World) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	32nd	1st	23rd	12th	232,234th
Total Shots Made	11th	1st	18th	9th	11,232nd
Shooting %	3rd	34th	5th	3rd	8,453rd
Total International Shooters	65,434	132,332	155,234	244,002	1,323,323

FIG. 63  
Doppler Dependent Report

(Doppler Dependent - This chart shows rankings from a shooting area along with distance)  
Player/Team vs the Nation Shooting Report for Kevin Curtis, Team Upper Sandusky, OH  
December 15, 2011

**Shooting Location 8, from 15-19 feet** (could also be on locations 0-16 & other distance range)

774a Local Shooting (Team Upper Sandusky) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	1st	1st	1st	1st	1st
Total Shots Made	1st	1st	1st	2nd	2nd
Shooting %	1st	1st	1st	1st	1st
Total Upper Sandusky Shooters	6	12	14	55	132

774b Regional Shooting (Wyandot County) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	1st	1st	1st	1st	1st
Total Shots Made	1st	1st	1st	2nd	2nd
Shooting %	1st	2nd	1st	1st	1st
Total Wyandot Shooters	864	1,432	5,345	15,343	34,766

774c Statewide Shooting (Ohio) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	4th	1st	9th	5th	543rd
Total Shots Made	3rd	1st	9th	4th	342nd
Shooting %	2nd	5th	2nd	2nd	434th
Total Ohio Shooters	12,121	25,344	33,434	49,343	85,434

774d National Shooting (USA) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	28th	1st	21st	10th	123231st
Total Shots Made	9th	1st	17th	8th	9,384th
Shooting %	3rd	29th	5th	3rd	7,855th
Total United States Shooters	50,123	112,123	123,323	213,432	987,433

774e International Shooting (World) Rankings for Kevin Curtis

RANKINGS	Today	Week	Month	Year	Lifetime
Total Shots	32nd	1st	23rd	12th	232,234th
Total Shots Made	11th	1st	18th	9th	11,232nd
Shooting %	3rd	34th	5th	3rd	8,453rd
Total International Shooters	65,434	132,332	155,234	244,002	1,323,323

**SYSTEM AND METHOD FOR IMPROVING A  
BASKETBALL PLAYER'S SHOOTING  
INCLUDING A DETECTION AND  
MEASUREMENT SYSTEM**

**CROSS-REFERENCE TO RELATED  
APPLICATION**

[0001] This application is a continuation-in-part of U.S. patent application Ser. No. 12/420,122, filed Apr. 8, 2009, which is incorporated herein by reference and made a part hereof.

**BACKGROUND OF THE INVENTION**

[0002] 1. Field of the Invention

[0003] This invention relates to a system and method for improving a player's shooting and includes a detection and measurement system for detecting, measuring or calculating shooting statistics (such as made shots, entry angle and release angle, get-off or release speed, measurements of distance, hold time or release time, degree of arc and the like) and data regarding a player's shooting.

[0004] 2. Description of the Related Art

[0005] In the past, various devices have been used to throw basketballs at a player so that the player can practice shooting the basketballs from a location and toward a basketball hoop on a basketball backboard. Several devices are offered by the assignee of the present application and marketed under the trademark THE GUN. For example, The Gun 6000 Series available from the assignee hereof provides a player with a high performance gun or ejector that a player and his or her coach can use during shooting practice. Other ball throwing devices are also available, such as the Dr. Dish™ product available from Airborne Athletics, Inc. of Belle Plaine, Minn., that are used during basketball practice.

[0006] One problem or deficiency of the prior art devices is that while they can be programmed to eject basketballs toward a player at a particular location, they were not capable of challenging the shooter's accuracy by, for example, making the shooter successfully shoot a number of shots, either consecutively or non-consecutively, at one location before the gun or ejector caused balls to be ejected or thrown to the next spot or location. Moreover, the devices fail to simulate a playing environment wherein a player feels pressure or a pressure-simulated is provided.

[0007] In shooting systems of the past, a launcher may launch balls to various positions on the basketball floor for shooting by a player. The player would then shoot the balls. In general, there were no means or devices for recording data associated with the shots and passes to the player, such as the distance from the launcher that the player was positioned, the arc of the player's shot after the player received the basketball and whether the player made the shot or missed the shot. There was also no means provided for recording the time it took to launch the ball to the player, a time that it took the player to get the shot off and then the time it took for the shot to travel to the basket, all of which can be important data and statistics for improving the player's shooting.

[0008] Moreover, there have been no means or systems or methodologies in the past for providing an automated system for repeating the same shot to the same player, multiple players from the same team or even players from different teams and then comparing the shooting data and statistics for the players.

[0009] The basketball practice systems of the prior art also lack the ability to track, measure or record the shooting distance and/or a shooting location (such as a shooting location along a vector associated with a basketball hoop) and, therefore, are incapable of providing comparable measurements or statistics for comparison.

[0010] There is, therefore, a need for a system and method for not only improving the player's efficiency in shooting the basketball, but also for providing a system and method for repeatedly launching the same shot to the same or different players so that data and statistics, such as data and statistics relative to the shots that the player made, misses and the like, and to provide the player, coaches and other interested persons the ability to compare statistics by the same player, by different players on the same team or by different players from different teams.

**SUMMARY OF THE INVENTION**

[0011] One object of an embodiment is to provide a system and process for improving a player's shooting ability.

[0012] Another object is to provide a system and method for challenging a shooter.

[0013] Still another object is to provide a system and method for monitoring a player's shooting performance, such as shots made in a row and/or total cumulative shots made.

[0014] Another object of the invention is to provide a system and method for determining when a basketball that has been shot by a player has been made or has been missed.

[0015] Another object of the invention is to provide a system and method for comparing statistics regarding shots by a player.

[0016] Still another object of the invention is to provide a system and method for gathering data and statistics regarding shots from different players on the same team, the same player, or different players from different teams.

[0017] Yet another object of the invention is to provide a system and method for comparing data generated by at least one or a plurality of players, regardless of whether those players are on the same or different teams and/or providing means for accessing that comparison data over the internet.

[0018] Still another object of the invention is to provide means for downloading, exporting, saving (on a permanent or portable storage device, such as a USB drive) the data and statistics, including the comparison data and statistics, for at least one or a plurality of players.

[0019] Still another object is to provide a radar or a Doppler measurement system to measure or capture a distance or location from a basketball hoop or launcher that a player caught the ball from.

[0020] Still another object is to provide a detection or measurement system that measures not only the distance the ball was caught from that is also adapted to measure, detect or calculate at least one or a plurality of a release time of the ball, an arc of the shot, a release angle, an entry angle or a horizontal or vertical velocity of the ball.

[0021] In one aspect, this invention comprises an apparatus for assisting basketball practice, comprising a launcher for launching a basketball into a flight path, a measuring system which measures speed of the basketball after a player shoots the basketball, ascertains elapsed time of the flight path, and using a formula which incorporates the speed and the elapsed time, computes a distance from which the player shot the basketball.

**[0022]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0023]** an apparatus in which the measuring system measures the speed based on Doppler shift of reflected radiation which is reflected from the launched basketball;

**[0024]** an apparatus in which the measuring system ascertains a time T1 when the flight path begins; uses a radar gun to ascertain speed of the basketball; ascertains a time T2 when the measured speed of the basketball falls below a limit; and computes the elapsed time based on T1 and T2; and

**[0025]** an apparatus in which the speed is measured when the basketball exits the launcher.

**[0026]** In another aspect, this invention comprises an apparatus for assisting basketball practice, comprising a launcher for launching a basketball along a flight path, and a radar gun which detects speed of the basketball when launched, and continues to measure speed along the flight path.

**[0027]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0028]** an apparatus further comprising a system which computes elapsed time of the flight path;

**[0029]** an apparatus further comprising a system which computes a distance based on the elapsed time and the detected speed;

**[0030]** an apparatus further comprising a basketball goal which includes a backboard, a rim attached to the backboard, and a net attached to the rim; a system for detecting whether a player scores a goal; and a data system which records conditions of the flight path and whether the basketball on the flight path scored a goal;

**[0031]** an apparatus in which the apparatus launches a succession of basketballs along a succession of flight paths, and the data system records conditions of each flight path; and whether the basketball launched on each flight path was subsequently shot by the player successfully through the rim;

**[0032]** an apparatus in which the data system records in a data file conditions for each of multiple flight paths presented to the player and whether the player scored a goal with each basketball of each respective flight path; and

**[0033]** an apparatus in which the data system makes the data file available to remote parties.

**[0034]** In another aspect, this invention comprises an apparatus for assisting in basketball practice of a player, comprising a launcher which launches a basketball pass at a time T1, a detector which measures speed S of the basketball upon launch, and a control which knows time T1, identifies a time T2, when the speed S measured by the detector falls below a first threshold, detects a time T3, occurring after time T2, when speed measured by the detector rises above a second threshold, learns that the basketball scored a goal at time T4 after a shot by the player, computes at least one of the following a pass flight time PFT, based on the equation  $PFT = T2 - T1$ , a distance D based on the equation  $D = PFT \times S$ , a hold time H based on the equation  $H = T3 - T2$ , or a shot flight time SFT based on the equation  $SFT = T4 - T3$ .

**[0035]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0036]** an apparatus wherein the detector is coupled to the launcher and moved in response to movement of the launcher.

**[0037]** In still another aspect, this invention comprises an apparatus for assisting basketball practice by measuring speed of a basketball, comprising a radar transmitter which transmits a radar signal at a time T to the basketball, a radar receiver which receives a transmitted radar signal after reflection by the basketball, an amplifier which applies amplification to the received radar signal, and progressively increases the amplification as elapsed time since time T increases.

**[0038]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0039]** an apparatus in which an amplification at time T3 is greater than an amplification at time T2, the amplification at time T2 is greater than an amplification at time T1, and the time T1 follows the time T, the time T2 follows time T1, and the time T3 follows the time T2; and

**[0040]** an apparatus in which the amplification applied for the basketball having a higher speed is increased faster than the amplification applied for the basketball having a lower speed.

**[0041]** In still another aspect, this invention comprises an apparatus for assisting basketball practice by measuring speed of a basketball, comprising a radar transmitter which transmits a radar signal to the basketball, a radar receiver which receives reflection of the transmitted radar signal from the basketball after a delay, and an amplifier which applies amplification to a received radar signal, such that the amplification is relatively small when the delay is relatively small, and the amplification is relatively large when the delay is relatively large.

**[0042]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0043]** an apparatus in which the delay represents time taken for the signal to travel from the basketball to the radar receiver, after reflection.

**[0044]** In still another aspect, this invention comprises an apparatus for assisting basketball practice by measuring speed of a moving basketball, comprising a radar transmitter which transmits radar to the moving basketball as it moves away from the radar transmitter, a radar receiver which receives radar reflections from the moving basketball, which reflections decrease in amplitude as the moving basketball moves farther away, and a compensation system which maintains the received radar reflections relatively constant.

**[0045]** In still another, this invention comprises a system, comprising a launcher for launching a basketball into a trajectory selected from a collection of possible trajectories, a detection system which detects when a player catches the basketball and terminates the trajectory, computes a flight

distance of the trajectory, detects whether a shot of the basketball made by the player scores a goal, and records the flight distance or location from which the basketball was shot, computed and whether the goal was scored.

**[0046]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0047]** an apparatus wherein the detection system records the location at which the player shot the basketball and a percentage of shots made.

**[0048]** In another aspect, this invention comprises a system for practicing or improving shooting basketballs, comprising at least one launcher, which is programmable to make a series of passes to a player, a measurement system which generates data associated with a player's shooting, the data including at least one of the following measurements or calculations: a distance from a basketball hoop from which the player shot a basketball, a release time, a release arc of the basketball when the player shoots it or an entry arc of the basketball entering the basketball hoop, determines or records a total number of shots the player took and whether the player made the shots, and stores the shots made by the player at each location.

**[0049]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0050]** a system wherein the data includes the distance and the measurement system further comprises a measuring device that measures a distance from the basketball hoop that the player took a shot, with the distance being stored on the at least one launcher;

**[0051]** a system wherein the measurement system is adapted to measure distance data for a plurality of distances extending along a plurality of vectors that project from the at least one launcher;

**[0052]** a system wherein the plurality of vectors extend over a plurality of shooting locations that generally correspond to a plurality of selected shooting locations that were selected by a user;

**[0053]** a system wherein the plurality of selected shooting locations generally correspond to a plurality of buttons, respectively, arranged in an arc on a user interface associated with the at least one launcher;

**[0054]** a system wherein the measuring device is a Doppler system having a plurality of amplifiers for amplifying a signal relating to movement of the basketball as it travels away from the at least one launcher;

**[0055]** a system wherein the system further comprises a tracking system for tracking the player's shots and for generating reports showing the player's shooting success at each distance from which a shot was taken by the player;

**[0056]** a system wherein the tracking system is located on a server associated with a website so that it is accessible by an interested user, such as at least one of a coach, the player or other interested users;

**[0057]** a system wherein the tracking system is adapted to receive data associated with a plurality of players who shot basketballs using the at least one launcher, wherein the data

was initially captured by the at least one launcher and uploaded to the tracking system;

**[0058]** a system wherein the system comprises a plurality of launchers, the tracking system further comprising the tracking system being adapted to receive data associated with a plurality of players who shot basketballs using the plurality of launchers, wherein the data was initially captured by the plurality of launchers and uploaded to the tracking system; the tracking system comprising a chart/report generator for generating charts or reports showing the data;

**[0059]** a system wherein the plurality of launchers are located at different locations;

**[0060]** a system wherein the plurality of launchers are used at the same time;

**[0061]** a system wherein the plurality of launchers are used at different times;

**[0062]** a system wherein the chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from at least one of the plurality of players;

**[0063]** a system wherein the charts or reports further comprise a ranking and a listing of at least one of the measurements or calculations;

**[0064]** a system wherein the charts or reports comprises a shooting measurement or calculation for a plurality of distances which are shown or listed on the charts or reports;

**[0065]** a system wherein the shooting measurement or calculation is a number of makes or percentage calculation based upon or using the number of made shots;

**[0066]** a system wherein the charts or reports further comprise a comparative ranking and a listing of at least one of the measurements or calculations for a plurality of players;

**[0067]** a system wherein the plurality of players are from the same team and use the same launcher;

**[0068]** a system wherein the plurality of players are from different teams and use the same launcher;

**[0069]** a system wherein the plurality of players are from a plurality of different teams, the plurality of different teams using a plurality of launchers, respectively, that are located at a plurality of different locations;

**[0070]** a system wherein the plurality of different locations are located in different countries;

**[0071]** a system wherein the plurality of different locations are located in different states or counties within the United States;

**[0072]** a system wherein the tracking system further comprises a tracking website having an associated server for storing shooting data and statistics for the player; a plurality of graphical user interfaces that are presented to a user after logging onto the tracking website, the tracking website being adapted to track and store data and statistics regarding a plurality of players' shooting performance over a predetermined period of time;

**[0073]** a system wherein the predetermined period of time is a lifetime of each of the plurality of players;

**[0074]** a system wherein the tracking system and graphical user interfaces are further adapted to permit the user to create and store a roster or team of players and assign them to the at least one launcher;

**[0075]** a system wherein the at least one launcher is adapted to receive the roster or team of players to enable the at least one launcher to capture and store shooting statistics and data for each player;

**[0076]** a system wherein the tracking system is further adapted to permit the shooting data and statistics to be uploaded from the at least one launcher to the tracking website;

**[0077]** a system wherein the tracking website comprises a chart/report generator for generating charts or reports showing the shooting statistics and data;

**[0078]** a system wherein the chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from a plurality of players that use the at least one launcher;

**[0079]** a system wherein the charts or reports further comprise a ranking and a listing of at least one of the measurements or calculations;

**[0080]** a system wherein at least one of the reports comprises a mapping report or scatter diagram showing a shooting accuracy for a plurality of distances along a vector extending from the at least one launcher; and

**[0081]** a system wherein the chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from a plurality of players that use different launchers.

**[0082]** In another aspect, this invention comprises an apparatus which enables a player to practice basketball, comprising a display or interface which indicates several different types of available basketball passes, accepts input from a user which selects a sequence of the basketball passes, a basketball launcher which launches the sequence of the available basketball passes for the player to catch, a detector which estimates, for some or all of the available basketball passes, a distance between point of catching each pass by the player and a reference location, a transmitter for transmitting data indicating the sequence of the available basketball passes to a remote location, which enables a second launcher to launch the sequence of the basketball passes.

**[0083]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0084]** an apparatus in which the reference location is a basketball goal;

**[0085]** an apparatus in which the detector estimates the distance by measuring velocity  $V$  and flight time  $T$  of the basketball, and multiplying velocity  $V$  times flight time  $T$ ; and

**[0086]** an apparatus in which the detector estimates the distance by measuring horizontal velocity component  $V_h$  of a basketball shot by the player and time of flight  $T$  of the basketball, and then multiplying velocity  $V$  times flight time  $T$ .

**[0087]** In another aspect, this invention comprises an apparatus which enables a player to practice basketball, comprising a launcher which launches a basketball for the player to catch, and a detector which makes an estimate at least one of distance of the player from the launcher, height of a shot made by the player after catching the basketball, release angle by the player, or entry angle of the basketball into a goal.

**[0088]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0089]** an apparatus in which the detector uses only detected speeds of the basketball, time of flight of the shot and time of flight of a launched basketball pass, to compute the distance, height, release angle, and entry angle;

**[0090]** an apparatus in which a detected speed includes speed of the basketball when leaving the launcher;

**[0091]** an apparatus in which a time of flight of the basketball is that between time of launch of the basketball and time at which detected speed of the basketball reaches a lower limit;

**[0092]** an apparatus in which the lower limit is zero; and

**[0093]** an apparatus wherein the detector makes an estimate of each of the distance of the player from the launcher; the height of a shot made by the player after catching the basketball; the release angle by the player; or the entry angle of the basketball into the goal.

**[0094]** In another aspect, this invention comprises a system for players to practice basketball, comprising a first launching system which includes a first launcher which launches a predetermined sequence of basketball passes for a first player to catch, a first detector which, for each pass, produces performance data which includes distance of the first player from the first launcher, height of a shot made by the first player after catching a basketball, release angle by the first player, and entry angle of the basketball into a goal, and a first communication system which posts on a web site a description of the predetermined sequence of basketball passes selected of the performance data of the first player, a second launching system, located remote from the first launching system, which obtains a description of the predetermined sequence of basketball passes, either from the first launching system or the web site; and includes a second launcher which launches the predetermined sequence of basketball passes for a second player to catch, a second detector which, for each pass, produces performance data which includes distance of the second player from the second launcher, height of a shot made by the second player after catching the basketball, release angle by the second player, and entry angle of the basketball into a goal and a second communication system which posts on the web site selected of the performance data for each pass to the second player.

**[0095]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0096]** a system in which the first communication system posts, on the web site, distance of the first player from the first launcher; height of a shot made by the first player after catching the basketball; release angle by the first player; and entry angle of the basketball into a goal for every pass to the first player;

**[0097]** a system in which the second communication system posts, on the web site, distance of the second player from the second launcher; height of a shot made by the second player after catching the basketball; release angle by the second player; and entry angle of the basketball into a goal for every pass to the second player;

**[0098]** a system in which the performance data for the first and second players are presented at the web site in a manner which allows comparison between the first and second players;



**[0099]** a system wherein the system creates reports from criteria selected by a user;

**[0100]** a system wherein the reports comprise relative compromises and rankings for a plurality of either players or teams; and

**[0101]** a system wherein the reports are for players on different teams.

**[0102]** In another aspect, this invention comprises a basketball tracking system comprising a launcher for launching a basketball to a plurality of locations on a basketball floor, a distance sensor for measuring a distance from which the basketball is shot from at least one of the plurality of locations, at least one sensor for sensing at least one of whether a shot was made or missed, a database for storing statistics at each distance for each shot taken.

**[0103]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0104]** a basketball tracking system wherein the system further comprises an interface for use in causing the launcher to throw the basketballs along a plurality of different vectors;

**[0105]** a basketball tracking system wherein the distance sensor senses where a player caught the basketball and determines at least one of a location or distance from a rim where the player released the basketball toward the rim;

**[0106]** a basketball tracking system wherein the distance sensor is adapted to determine a release angle or arch at which the player shot the basketball;

**[0107]** a basketball tracking system wherein the database receives the distance measurements and the statistics at each distance, the statistics comprising statistics of made shots at the distance;

**[0108]** a basketball tracking system wherein the plurality of different vectors is sixteen or less;

**[0109]** a basketball tracking system wherein the interface comprises the plurality of different vectors laid out on the interface for selection by a user;

**[0110]** a basketball tracking system wherein the distance sensor comprises a Doppler measurement system;

**[0111]** a basketball tracking system wherein the tracking system further comprises a plurality of graphical user interfaces for enabling a user to view the distance measurements and the statistics in the database;

**[0112]** a basketball tracking system wherein the plurality of graphical user interfaces enables the user to at least one of edit, view, print, copy and create reports using the distance measurements and the statistics stored in the database; and

**[0113]** a basketball tracking system wherein the system further comprises a report generator for generating at least one report in response to a selection of a plurality of criteria selected by the user using at least one of the plurality of graphical user interfaces.

**[0114]** In another aspect, this invention comprises an apparatus for assisting basketball practice of a player, comprising a launcher which launches a basketball for the player to (1) catch and then (2) make a shot toward a goal, a device which measures distance D between the player and the goal, a detector which measures horizontal velocity  $V_{ox}$  of the shot, a control which computes time-of-flight of the shot by dividing the distance D by the horizontal velocity  $V_{ox}$ .

**[0115]** In another aspect, this invention comprises an apparatus for assisting in basketball practice of a player, comprising a launcher for launching a pass for the player to catch and then make a shot and a detector for detecting a maximum height, DA, which the shot reaches.

**[0116]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0117]** an apparatus in which the maximum height DA is measured with respect to the player's release point of a basketball;

**[0118]** an apparatus in which the detector ascertains an initial vertical component of velocity,  $V_{yi}$ , of a basketball upon shooting by the player, and the detector computes the maximum height DA based on an initial vertical component of velocity  $V_{yi}$  and an acceleration of gravity, g;

**[0119]** an apparatus in which the shot is made toward a goal, and a height, DB, of the goal above the player's release point is known, and further comprising a sensing system which senses distance D between a location where the player makes the shot and the goal; senses an initial horizontal component of velocity,  $V_{xi}$ , of the shot; computes an initial vertical component of velocity,  $V_{yi}$ , of the shot upon release by the player, based on the horizontal component of velocity  $V_{xi}$ , the distance D, the height DB, and an acceleration of gravity, g;

**[0120]** an apparatus in which the player makes the shot toward a goal, and in which the initial vertical component of velocity  $V_{yi}$  is computed based on a height DB of a goal above the player's release point, an initial horizontal velocity  $V_{xi}$  of the shot, a distance D between the player and the goal, and an acceleration of gravity g;

**[0121]** an apparatus further comprising a sensor which senses an initial vertical velocity  $V_{yi}$  and an initial horizontal velocity  $V_{xi}$  of the player's shot, a system which computes a release angle,  $\text{THETA}_r$ , of the player's shot, based on the initial vertical velocity  $V_{yi}$  and the initial horizontal velocity  $V_{xi}$ ;

**[0122]** an apparatus in which the release angle  $\text{THETA}_r$  is computed based on an arctangent of the initial vertical velocity  $V_{yi}$  divided by the initial horizontal velocity  $V_{xi}$  ( $V_{yi}/V_{xi}$ );

**[0123]** an apparatus further comprising a sensor which senses a final vertical velocity,  $V_{yf}$ , and a final horizontal velocity,  $V_{xf}$ , of the player's shot when it reaches the goal, and a system which computes an entry angle,  $\text{THETA}_e$ , of the player's shot at the goal, based on the final vertical velocity  $V_{yf}$  and the final horizontal velocity  $V_{xf}$ ;

**[0124]** an apparatus further comprising a sensor which senses a final vertical velocity,  $V_{yf}$ , and a final horizontal velocity,  $V_{xf}$ , of the player's shot when it reaches the goal, and a system which computes an entry angle,  $\text{THETA}_e$ , of the player's shot at the goal, based on the final vertical velocity  $V_{yf}$  and the final horizontal velocity  $V_{xf}$ ; and

**[0125]** an apparatus according to claim 95, in which the entry angle,  $\text{THETA}_e$ , is computed based on an arctangent of the final vertical velocity  $V_{yf}$  divided by the final horizontal velocity  $V_{xf}$  ( $V_{yf}/V_{xf}$ ).

**[0126]** In another aspect, this invention comprises an apparatus for assisting in basketball practice of a player, comprising a launcher for launching a pass for the player to catch and

then make a shot, and a detector for detecting an initial vertical component of velocity,  $V_{yi}$ , of the shot, upon release by the player.

[0127] In another aspect, this invention comprises an apparatus for assisting in basketball practice of a player, comprising a launcher for launching a pass for the player to catch and then make a shot, and a detector for detecting an initial horizontal component of velocity,  $V_{xi}$ , of the shot, upon release by the player.

[0128] In another aspect, this invention comprises an apparatus for assisting practice of a basketball player who makes a shot toward a goal, comprising a sensor which senses a final vertical velocity  $V_{yf}$  and a final horizontal velocity  $V_{xf}$  of the basketball player's shot when it reaches the goal, and a system which computes an entry angle,  $\text{THETA}_e$ , of the basketball player's shot at the goal, based on the final vertical velocity  $V_{yf}$  and the final horizontal velocity  $V_{xf}$ .

[0129] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0130] an apparatus in which the entry angle,  $\text{THETA}_e$ , is computed based on an arctangent of the final vertical velocity  $V_{yf}$  divided by the final horizontal velocity  $V_{xf}$  ( $V_{yf}/V_{xf}$ ).

[0131] In another aspect, this invention comprises an apparatus for assisting practice of a basketball player who makes a shot toward a basketball goal, comprising a launcher which launches a basketball for the basketball player to catch, and then make the shot, a first sensing system which computes a distance  $D$  between the basketball player and the goal, based on flight characteristics of the basketball; and a second sensing system which measures initial horizontal velocity  $V_{xi}$  of the shot by the player, and estimates time-of-flight  $T_p$  of the shot, based on the distance  $D$  and the initial horizontal velocity  $V_{xi}$ .

[0132] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0133] an apparatus in which the flight characteristics comprise initial velocity of the basketball as it leaves the launcher, and time-of-flight of the basketball from the launcher to the player;

[0134] an apparatus in which the distance  $D$  is computed based partly on initial velocity of the basketball as it leaves the launcher;

[0135] an apparatus in which a reduction in velocity of the basketball due to air drag is ignored;

[0136] an apparatus in which the distance  $D$  is computed based partly on initial velocity of the basketball, and a reduction in velocity due to air drag is accounted for by a weighting factor;

[0137] an apparatus in which the weighting factor is a percentage of initial velocity; and

[0138] an apparatus in which the percentage is less than one percent.

[0139] In another aspect, this invention comprises an apparatus for assisting practice of a basketball player who makes a shot toward a basketball goal, which is a known height  $DB$  above the player's release point of the shot, comprising a

launcher which launches a basketball for the player to catch, and then make the shot, a sensing system which senses distance  $D$  between the player and the basketball goal, senses horizontal velocity  $V_x$  of the shot, computes vertical velocity,  $V_y$ , of the shot based on (1) the distance  $D$ , (2) the horizontal velocity  $V_x$ , (3) a height  $DB$ , and (4) an acceleration of gravity  $g$ .

[0140] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0141] an apparatus in which the sensing system further computes maximum height reached by the shot;

[0142] an apparatus in which the sensing system further computes an entry angle,  $\text{THETA}_e$ , of the basketball at the basketball goal;

[0143] an apparatus in which the maximum height is computed based on vertical velocity  $V_y$  and acceleration of gravity  $g$ ; and

[0144] an apparatus in which the entry angle  $\text{THETA}_e$  is computed as an arctangent of the vertical velocity  $V_y$  divided by the horizontal velocity at the goal, wherein the vertical velocity  $V_y$  is the vertical component of velocity of the basketball and the horizontal velocity  $V_x$  is the horizontal component of velocity.

[0145] In another aspect, this invention comprises an apparatus for assisting practice of a basketball player who makes a shot toward a basketball goal, comprising a launcher which launches a ball for the basketball player to catch, and then make the shot, an estimation system which estimates two or more of the following parameters, distance travelled by the launched basketball to the player, release angle,  $\text{THETA}_r$ , of the shot, maximum height which the shot reaches, entry angle,  $\text{THETA}_e$ , of the shot into the basketball goal, whether the shot scores a goal, and if the shot scores a goal, whether the goal is a swisher or not.

[0146] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0147] an apparatus in which the estimation system estimates four or more of the parameters; and

[0148] an apparatus in which the estimation system estimates five or more of the parameters.

[0149] In another aspect, this invention comprises a method for assisting in basketball practice of a player, comprising launching a pass for the player to catch and then make a shot, and detecting a maximum height  $DA$  which the shot reaches.

[0150] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0151] a method in which a maximum height  $DA$  is measured with respect to the player's release point of the basketball;

[0152] a method in which the detector ascertains the initial vertical component of velocity,  $V_{yi}$ , of the basketball upon shooting by the player, and the detector computes the maxi-

maximum height  $DA$  based on the initial vertical component of velocity  $V_{yi}$  and acceleration of gravity,  $g$ ;

[0153] a method in which the shot is made toward a goal, and height  $DB$  of the goal above the player's release point is known, and further comprising sensing distance  $D$  between a location where the player makes the shot and the goal; sensing an initial horizontal component of velocity,  $V_{xi}$ , of the shot; computing an initial vertical component of velocity,  $V_{yi}$ , of the shot upon release by the player, based on the initial horizontal component of velocity  $V_{xi}$ , the distance  $D$ , the height  $DB$ , and acceleration of gravity,  $g$ ;

[0154] a method in which the player makes the shot toward the goal, and in which the initial vertical component of velocity  $V_{yi}$  is computed based on the height  $DB$  of the goal above the player's release point, initial horizontal component of velocity  $V_{xi}$  of the shot, distance  $D$  between the player and the goal, and acceleration of gravity  $g$ ;

[0155] a method and further comprising sensing the initial vertical component of velocity  $V_{yi}$  and the initial horizontal component of velocity  $V_{xi}$  of the player's shot, computing a release angle,  $THETA_e$ , of the shot, based on the initial vertical component of velocity  $V_{yi}$  and the initial horizontal component of velocity  $V_{xi}$ ;

[0156] a method in which the release angle  $THETA_e$  is computed based on an arctangent of the initial vertical component of velocity  $V_{yi}$  divided by the initial horizontal component of velocity  $V_{xi}$  ( $V_{yi}/V_{xi}$ );

[0157] a method further comprising sensing a final vertical velocity,  $V_{yf}$ , and the final horizontal velocity,  $V_{xf}$ , of the player's shot when it reaches the goal, and computing entry angle,  $THETA_e$ , of the player's shot at the goal, based on the final vertical velocity  $V_{yf}$  and the final horizontal velocity  $V_{xf}$ ;

[0158] a method in which the entry angle,  $THETA_e$ , is computed based on an arctangent of the final vertical velocity  $V_{yf}$  divided by the final horizontal velocity  $V_{xf}$  ( $V_{yf}/V_{xf}$ ); and

[0159] a method in which the final horizontal velocity  $V_{xf}$  used in computing entry angle is equal to initial horizontal velocity  $V_{xi}$  of a basketball when shot by the player.

[0160] In another aspect, this invention comprises a method for assisting in basketball practice of a player, comprising launching a pass for the player to catch and then make a shot, and detecting an initial vertical component of velocity,  $V_{yi}$ , of the shot, upon release by the player.

[0161] In another aspect, this invention comprises a method for assisting in basketball practice of a player, comprising launching a pass for the player to catch and then make a shot, and detecting an initial horizontal component of velocity,  $V_{xi}$ , of the shot, upon release by the player.

[0162] In another aspect, this invention comprises a method for assisting practice of a basketball player who makes a shot toward a goal, comprising sensing a final vertical velocity  $V_{yf}$ , and a final horizontal velocity  $V_{xf}$  of the player's shot when it reaches the goal, and computing entry angle,  $THETA_e$ , of the player's shot at the goal, based on the final vertical velocity  $V_{yf}$  and the final horizontal velocity  $V_{xf}$ .

[0163] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0164] a method in which the entry angle,  $THETA_e$ , is computed based on an arctangent of the final vertical velocity  $V_{yf}$  divided by the final horizontal velocity  $V_{xf}$  ( $V_{yf}/V_{xf}$ ).

[0165] In another aspect, this invention comprises a method for assisting practice of a basketball player who makes a shot toward a basketball goal, comprising launching a basketball for the basketball player to catch, and then make the shot, computing distance  $D$  between the basketball player and the goal, based on flight characteristics of the basketball, and measuring initial horizontal velocity  $V_{xi}$  of the shot by the basketball player, and estimating time-of-flight  $T_p$  of the shot, based on the distance  $D$  and the initial horizontal velocity  $V_{xi}$ .

[0166] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0167] a method in which the flight characteristics comprise initial velocity of the basketball as it leaves a launcher, and time-of-flight of the basketball from the launcher to the player;

[0168] a method in which the distance  $D$  is computed based partly on initial velocity of the basketball as it leaves the launcher;

[0169] a method in which reduction in velocity of the basketball due to air drag is ignored;

[0170] a method in which distance  $D$  is computed based partly on initial velocity of the basketball, and reduction in velocity due to air drag is accounted for by a weighting factor;

[0171] a method in which the weighting factor is a percentage of initial velocity; and

[0172] a method in which the percentage is less than one percent.

[0173] In another aspect, this invention comprises a method for assisting practice of a basketball player who makes a shot toward a basketball goal, which is a known height  $DB$  above the basketball player's release point of the shot, comprising launching a basketball for the basketball player to catch, and then make the shot, sensing distance  $D$  between the basketball player and the goal, horizontal velocity  $V_x$  of the shot, and computing vertical velocity,  $V_y$ , of the shot based on (1) the distance  $D$ , (2) the horizontal velocity  $V_x$ , (3) the height  $DB$ , and (4) acceleration of gravity  $g$ .

[0174] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0175] a method further computing maximum height reached by the shot;

[0176] a method further computing entry angle,  $THETA_e$ , of the basketball at the goal;

[0177] a method in which the maximum height is computed based on vertical velocity  $V_y$  and acceleration of gravity  $g$ ; and

[0178] a method according to claim 136, in which the entry angle  $THETA_e$  is computed as an arctangent of the vertical velocity  $V_y$  divided by the horizontal velocity  $V_x$  at the goal, wherein the vertical velocity  $V_y$  is the vertical component of velocity of the basketball and the horizontal velocity  $V_x$  is the horizontal component of velocity.

**[0179]** In another aspect, this invention comprises a method for assisting practice of a basketball player who makes a shot toward a basketball goal, comprising launching a basketball for the basketball player to catch, and then make the shot, estimating two or more of the following parameters, distance travelled by the launched basketball to the basketball player, release angle,  $\text{THETA}_r$ , of the shot, maximum height which the shot reaches, entry angle,  $\text{THETA}_e$ , of the shot into the goal, whether the shot scores a goal, and if the shot scores the goal, whether the goal is a swisher or not.

**[0180]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0181]** a method in which an estimation system estimates four or more of the parameters; and

**[0182]** a method in which an estimation system estimates five or more of the parameters.

**[0183]** In another aspect, this invention comprises an apparatus for assisting practice of a basketball player who makes a shot toward a basketball goal, comprising a launcher which launches a ball for the basketball player to catch, and then make the shot, a receiver which receives a radar signal which indicates speed of the ball, and a variable-gain amplifier which receives the radar signal, and applies variable gain to the radar signal, to maintain amplitude of the amplified radar signal within predetermined limits.

**[0184]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0185]** an apparatus further comprising a radar gun which transmits a radar signal to the ball, for reflection to the receiver; and a system which progressively increases gain of the variable-gain amplifier after launch of the ball;

**[0186]** an apparatus in which the received radar signal experiences weakening as distance between the ball and the receiver increases, and increasing the gain by the variable amplifier compensates for the weakening;

**[0187]** an apparatus further comprising a microprocessor which receives a signal derived from the variable-gain amplifier, and uses the signal to compute at least one of the following parameters speed of the ball, time when the player catches the ball, time when the player makes the shot, distance between the player and the launcher, maximum height of the shot, and entry angle of the shot into the goal;

**[0188]** an apparatus in which the microprocessor computes at least two of the parameters;

**[0189]** an apparatus in which the microprocessor computes at least four of the parameters;

**[0190]** an apparatus in which the microprocessor computes at least five of the parameters; and

**[0191]** an apparatus in which the microprocessor computes all of the parameters.

**[0192]** In another aspect, this invention comprises a method of assisting practice of a basketball player who makes a shot toward a basketball goal, comprising launching a ball for the basketball player to catch, and then make the shot, receiving a radar signal which indicates speed of the ball, and delivering the radar signal to a variable-gain amplifier which applies

variable gain to the radar signal, to maintain amplitude of the radar signal within predetermined limits.

**[0193]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0194]** a method further comprising using a radar gun to transmit a radar signal to the ball, for reflection to a receiver; and progressively increasing gain of the variable-gain amplifier after launch of the ball;

**[0195]** a method in which the received radar signal experiences weakening as distance between the ball and the receiver increases, and increasing the gain by the variable amplifier compensates for the weakening;

**[0196]** a method further comprising using a microprocessor to receive a signal derived from the variable-gain amplifier, and compute at least one of the following parameters based on the signal: speed of the ball, time when the player catches the ball, time when the player makes the shot, distance between the player and the launcher, maximum height of the shot, and entry angle of the shot into the goal;

**[0197]** a method in which the microprocessor computes at least two of the parameters;

**[0198]** a method in which the microprocessor computes at least four of the parameters;

**[0199]** a method in which the microprocessor computes at least five of the parameters; and

**[0200]** a method in which the microprocessor computes all of the parameters.

**[0201]** In another aspect, this invention comprises an apparatus for assisting practice of a basketball player, comprising a launcher for launching a pass for the basketball player to catch, and then make a shot toward a goal, computation system which measures velocity  $V$  and time-of-flight  $T$  of the pass, computes distance  $D$  to the basketball player, measures a horizontal component  $V_x$  of the velocity of the shot, computes a vertical component  $V_y$  of the velocity of the shot, computes maximum height  $DA$  reached by the shot, and computes entry angle  $\text{THETA}_e$ , of a ball at the goal.

**[0202]** The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

**[0203]** an apparatus in which the distance  $D$  is computed based on the velocity  $V$  and the time-of-flight  $T$ ;

**[0204]** an apparatus in which the vertical component  $V_y$  is computed based on the horizontal component  $V_x$ , the distance  $D$ ; a height  $DB$  of the goal above the basketball player, and acceleration of gravity,  $g$ ; and

**[0205]** an apparatus in which the maximum height  $DA$  is computed based on the vertical component  $V_y$  and acceleration of gravity  $g$ .

**[0206]** In another aspect, this invention comprises a method for assisting practice of a basketball player, comprising launching a pass for the basketball player to catch, and then make a shot toward a goal, using a computation system, measuring velocity  $V$  and time-of-flight  $T$  of the pass, computing distance  $D$  to the basketball player, measuring a horizontal component  $V_x$  of a velocity of the shot, computing a vertical component  $V_y$  of a velocity of the shot, computing a

maximum height DA reached by the shot; and computing an entry angle THETA, of a ball at the goal.

[0207] The above mentioned aspects and the embodiments shown and described herein could be used alone or together and/or in combination with one or more of the features covered by one or more of the claims set forth herein, including but not limited to one or more of the following features or steps:

[0208] a method in which the distance D is computed based on the velocity V and the time-of-flight T;

[0209] a method in which the vertical component Vy is computed based on the horizontal component Vx, the distance D; the height DB of the goal above the basketball player, and acceleration of gravity, g; and

[0210] a method in which the maximum height DA is computed based on the vertical component Vy and acceleration of gravity g.

[0211] These and other objects and advantages of the invention will be apparent from the following description, the accompanying drawings and the appended claims.

#### BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWINGS

[0212] FIG. 1 is a perspective view of a system in accordance with one embodiment of the invention where a player is shooting a basketball from a first position at a playing area;

[0213] FIG. 2 is a view similar to FIG. 1 after the player has successfully performed one or more shooting accuracy routines at a first position (such as FIG. 9 and FIG. 1) and after a gun or ejector has automatically pivoted to eject or throw a basketball to another position, such as position 16 in the illustration;

[0214] FIG. 3 is a view showing the layout of FIGS. 3A-3D;

[0215] FIGS. 3A-3D are views of a user interface or display in accordance with one embodiment of the invention;

[0216] FIG. 4 is an enlarged view showing details of a display shown in FIG. 1;

[0217] FIG. 5 is a simplified view of a plurality of basketballs made in a row in the simplified illustration;

[0218] FIG. 6 is a view of various statistics and data and a printout for the player over a preselected period, illustrating the player's percentage of made shots relative to total shots at one or more of each of the plurality of different locations;

[0219] FIG. 7 is a schematic of a challenge shooting accuracy main procedure routine;

[0220] FIG. 8 is a schematic of a challenge shooting accuracy routine wherein multiple shots must be made in a row;

[0221] FIG. 9 is a schematic of a challenge shooting accuracy routine wherein multiple shots must be made at a particular location, but not necessarily in a row;

[0222] FIG. 10 is a perspective view of a system in accordance with another embodiment of the invention where a basketball is launched to a player and the player shoots the basketball from a position on the basketball floor;

[0223] FIG. 11 is a partial fragmentary view showing a throwing arm and vibration limit sensor in the embodiment shown in FIG. 10 and the player shoots from a distance;

[0224] FIGS. 12A-12C illustrate a Doppler procedure or algorithm for generating various Doppler statistics;

[0225] FIGS. 13A-13I are various formulas, calculations and algorithms used to generate Doppler measurements in the embodiment being illustrated;

[0226] FIG. 14 is a simplified schematic of the Doppler circuit shown in FIGS. 15A-15D;

[0227] FIGS. 15A-15D are one form of a Doppler circuit used in the embodiment shown in FIG. 10;

[0228] FIG. 16 is an overall view of the use of the embodiment shown in FIG. 10;

[0229] FIG. 17 is a general procedure and method for a coach to register the gun or ejector;

[0230] FIG. 18 is an illustrative procedure for creating a roster on a website for downloading to the gun or ejector;

[0231] FIG. 19 is a illustrative procedure for downloading the rosters created relative to FIG. 18 to the gun or ejector;

[0232] FIG. 20 is a general use of the embodiment shown in FIG. 10;

[0233] FIG. 21 is an illustrative procedure for calibrating the gun or ejector;

[0234] FIG. 22 is a general illustrative procedure for players to log onto the gun or ejector in the embodiment shown in FIG. 10;

[0235] FIGS. 23A-23B illustrate a general procedure for a shooting workout in accordance with another embodiment of the invention wherein the procedure is not dependent upon Doppler measurements;

[0236] FIGS. 24A-24B is similar to the procedure shown in FIGS. 23A-23B, but includes Doppler measurements and statistics;

[0237] FIG. 25 is a general procedure for uploading statistics and measurements to a local or non-local computer or website;

[0238] FIG. 26 is a general procedure for uploading shooting session data and statistics to a website in accordance with one embodiment;

[0239] FIG. 27 is a general procedure for creating customized reports;

[0240] FIGS. 28A-28B is another illustrative challenge mode, which is a real-time challenge in the illustration;

[0241] FIG. 29 is another illustrative challenge for different players on different teams at different locations using different guns or ejectors;

[0242] FIGS. 30-41 are illustrative graphical user interfaces or screenshots in accordance with one embodiment of the invention;

[0243] FIG. 42 is a scatter diagram or matrix illustrating various Doppler statistics and shooting percentages for various distances along various vectors corresponding to the shooting locations selected by a user;

[0244] FIG. 43 is a table illustrating the data visually shown in the scatter diagram in FIG. 42;

[0245] FIG. 44 is an example of a "SESSIONS" file for uploading from the gun or ejector;

[0246] FIG. 45 is an example of the "SESSIONS" file from the gun or ejector to the website WS;

[0247] FIG. 46 is an example of various sorting variables or selection criteria for use by a user;

[0248] FIG. 47 is an illustrative input selected criteria in one example;

[0249] FIG. 48 is an illustrative chart resulting from the selections made and shown in FIG. 47;

[0250] FIG. 49 is another example of input selection criteria or information selected by a user in the example;

[0251] FIG. 50 is the report or chart shown from the selections made and shown in FIG. 49;

[0252] FIG. 51 is a listing of the sorting variables or selection criteria that a user may use, which in the embodiment shown includes Doppler measurements;

[0253] FIG. 52 is another illustrative example of selected criteria or input information, including Doppler measurement of shooting distance;

[0254] FIG. 53 is a chart or report created by the website WS in response to the selected criteria in FIG. 52;

[0255] FIG. 54 is still another example of selected input information or criteria;

[0256] FIG. 55 is a chart or report created by the website WS in response to the criteria or information selected in FIG. 54; and

[0257] FIGS. 56-63 are various charts and reports showing illustrative comparisons and rankings of players and teams, where such players are from the same or different teams, same or different regions, skill levels and the like.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0258] Referring back to FIG. 1, the system 10 comprises a user interface 40 and a front display 42. The user interface 40 in the illustration being described is shown in more detail in FIGS. 3A-3D and will be described later herein. For ease of illustration, FIG. 3 illustrates the interface 40 with various portions of the interface shown in FIGS. 3B-3D. The system 10 further comprises a storage device 44, such as an electronic storage device or other electronic storage, for storing data relative to the player's efficiency, such as data regarding the player's performance during one or more of the shooter challenge routines 32a and even historical or cumulative information regarding a player's performance over a predetermined period or even a player's career in shooting using the system 10.

[0259] The gun or ejector 20 is a conventional ball ejecting machine and comprises a frame 24 having a plurality of wheels 26. The gun or ejector 20 has a conventional ball ejector 28 that is pivotally mounted on the frame 24 and can throw or eject basketballs 12 in the direction A. The gun or ejector 20 comprises a drive motor and linkage 30 for pivotally driving the ball ejector 28 in the direction of double arrow B in FIG. 1 so that a direction of thrown balls can be changed. The system 10 comprises a circuit board (not shown) having the controller 32 that is coupled to and controls the operation of the drive motor and linkage 30, gun or ejector 20 as shown.

[0260] Note that the gun or ejector 20 also comprises a ball retrieval or net system 34 which facilitates gathering basketballs 12 that are thrown toward the hoop 14 in a manner conventionally known. As also illustrated, the gun or ejector 20 may further comprise a shoot or guide 36 for facilitating guiding basketballs 12 into an inlet 38 where they can be ejected by the gun or ejector 20 through the outlet 39 and toward a basketball player P.

[0261] A photo sensor 33 is coupled to the hoop 14 and electronically coupled to the controller 32. The photo sensor 33 senses when the player P has successfully shot the basketball through the hoop 14.

[0262] In the embodiment being described several conventional guns/ejectors 20 may be used, including The Gun 6000 Series available from Shoot-a-Way, Inc. of Upper Sandusky, Ohio. An alternative gun or ejector 20 may be the Dr. Dish™ product available from Airborne Athletics, Inc. of Belle Plaine, Minn.

[0263] In the illustration being described, the controller 32 comprises a plurality of routines or algorithms for improving the player P's shooting efficiency. The routines include a shooter challenge routine 32a for challenging the player P in

shooting a basketball 12 towards the at least one or a plurality of different areas 22. The shooter challenge routine 32a facilitates improving a player's efficiency in that they provide a player P with feedback as to his or her shooting accuracy. With the feedback, the player P can focus his or her shooting practice on those areas where the player's efficiency is below a predetermined or preselected efficiency percentage. In the illustration being described, the predetermined efficiency may be any desired or selected shooting efficiency, such as 30% or 40%. For example, if a player's shooting efficiency falls below the predetermined threshold, such as 40% in the illustration being described, the player P may force his or her practice on the areas where the player P needs to improve his or her shooting efficiency.

[0264] Referring back to FIG. 1, the controller 32 further comprises means or apparatus for calculating the shooting efficiency using a shooting efficiency calculator 32b. The shooting efficiency calculator 32b calculates a shooting efficiency of the player P at the at least one or a plurality of the plurality of different positions 22 where the player P shot the basketball 12. The shooting efficiency calculator 32b may provide shooting efficiency statistics and data during one or more of the shooter challenge routines 32a mentioned later herein, but it is also capable of providing historical or cumulative data regarding a player's lifetime or career shooting statistics at each of the plurality of different locations 22. Again, the player P or a coach (not shown) may use the information, statistics or data as feedback in order to improve the player's efficiency in shooting the basketball 12 at the one or more of the plurality of different locations 22.

[0265] Referring back to FIG. 1, the system 10 comprises a user interface 40 and a front display 45. The user interface 40 in the illustration being described is shown in more detail in FIG. 3 and will be described later herein. The system 10 further comprises a storage device 44, such as an electronic storage device or other electronic storage, for storing data relative to the player's efficiency, such as data regarding the player's performance during one or more of the shooter challenge routines 32a and even historical or cumulative information regarding a player's performance over a predetermined period or even a player's career in shooting using the system 10.

[0266] As further illustrated in FIG. 1, the system 10 further comprises a ticket printer 46 which is coupled to the controller 32 and which is capable of printing a ticket 48 (FIG. 6). In the illustration being described, the ticket 48 comprises a plurality of information fields 50. In the illustration being described, the information fields 50 may include a player's name 52, time and date or period the player P practiced which could be a single day or date or could be a date span over a period of time during which the player P used the system 10. Note in the illustration being described, the ticket 48 comprises information fields 50 that also include information relevant to the player P's shooting performance. In the illustration being described, the ticket 48 comprises a spot column 55 which identifies the at least one or a plurality of predetermined locations 22 at which the player P shot the basketball 12. A total shots column 56 which identifies the number of shots attempted at the associated spot listed in the spot column 55. The ticket 48 information fields 50 also comprises a number of shots made column 58. Finally, a percentage column 60 is provided so that a player P can view the percentage of shots made at a given spot relative to the total number of shots taken over the time period 54 selected by the player P.

[0267] As mentioned earlier, a predetermined or desired efficiency threshold, such as 40% in the illustration being described, may be selected. The player P can use the information fields 50, such as the percentage column 60, and identify those spots where the player P's shooting efficiency dropped below the predetermined or desired efficiency threshold. In the illustration shown in FIG. 6, note that the highlighted areas 62 each identify spots, such as spots 3, 10, 11, and 13, at which the player P's efficiency dropped below 40%. Using this information, the player P or his or her coach (not shown) may then program the controller 32 using the user interface 40 (FIGS. 3A-3D) to direct one or more respected shots to those particular spots where the player P's efficiency dropped below the predetermined threshold. In a manner conventionally known, the player P may select a number of shots to shoot at the one or more of predetermined plurality of different locations 22 or alternatively, the player P may select initially or after reviewing his or her efficiency percentages to shoot a number of shots at each of the plurality of different locations 22 where the player P's performance efficiency was deficient using one or more of the shooter challenge routines 32a. These routines will not be described relative to FIGS. 7-9.

[0268] In the illustration being described, the shooter challenge routines 32a are programs stored in a read only memory (not shown) on the board (not shown) and under control of the controller 32.

[0269] Before beginning the shooter challenge routines 32a, the player P or the coach uses the interface 40 to program the controller 32. In this illustration, the controller 32 is programmed in multiple steps. First, the user selects one or more of the plurality of different locations 22 (0-16, in the illustration being described) during a first step or does not select a location thus the Gun will throw to the direction it is pointing. Note that the interface 40 may have the steps labeled for easy access. During a second step, the user programs the controller 32 and selects a time delay between passes or the time between which the gun or ejector 20 ejects basketballs 12. In one embodiment, the time delay is predetermined and set to at least one second. The third conventional step is programming the controller 32 with the number of shots for each of the plurality of different locations 22 selected in Step 1. Again, the player P can start the shooting by pressing the start button 70 and can stop shooting by pressing the stop button 72 (FIG. 3D).

[0270] The player P or a coach may select a challenge shooting accuracy button 74 (FIGS. 3A-3D) whereupon the controller 32 will begin the shooter challenge routines 32a. A multiple shots in a row routine requires the player P to make the number of shots consecutively before the gun/ejector 20 is caused to throw basketballs 12 at the next programmed spot. A total number of shots routine requires the player P to make the total number of shots before the gun/ejector 20 begins throwing basketballs 12 at the next programmed spot. During this routine, the player P does not have to make the number of shots consecutively. In this regard, if the player P selects the challenge shooting accuracy button 74, then the controller 32 prompts the user using the screen 76 to determine whether the player P desires to make multiple shots in a row or multiple shots at each spot before the gun/ejector 20 is caused to pivot and throw basketballs 12 to the next position, without the requirement that the shots be made in a row.

[0271] A main routine will now be described. If the challenge shooter accuracy button 74 is not pressed and the player

P or his or her coach presses the start button 70, the controller 32 begins at block 78 (FIG. 7) by starting to throw basketballs 12 toward the player P at one of the plurality of different locations 22 as selected by the player P during step 1 (FIGS. 3A-3D). The routine continues to block 79 where the controller 32 assigns a TSPOTS variable to the number of locations selected in step 1. The routine continues to block 80 where the controller 32 assigns a NUM variable to the number of shots per spot selected by the player P in step 3. At decision block 82, it is determined whether the challenge shooting mode was enabled by the player P by pressing button 74 (FIGS. 3A-3D). If it was not, then the controller 32 energizes the gun/ejector 20 to output one shot for each spot selected by the player P. In another embodiment, the controller 32 energizes the gun/ejector 20' to output the total number of shots selected in step 3 to each location before the gun/ejector 20' moves to the next location. If a decision at block 82 was affirmative, then it is determined at decision block 83 whether the player P selected the multiple shots must be made in a row routine where the player P must make the selected number of shots in a row at each of the plurality of different locations 22 selected by the player P in step 1. If the decision at block 83 was negative, then the routine continues (block 84) to the multiple shots which must be made at one or each of the plurality of different locations 22 selected by the player P in step 1 which is illustrated in FIG. 9. If the decision at decision block 83 was affirmative, then the routine continues (block 86) to the multiple shots which must be made in a row at the at least one or each of the plurality of different locations 22 selected by the player P in step 1, which is illustrated in FIG. 8 and which will now be described.

[0272] If the player P selected challenge shooter accuracy routine in which the player P must make multiple shots in a row at the least one or a plurality of different locations 22 selected by the player P, then the controller 32 begins the routine illustrated in FIG. 8 (block 88) and the routine continues to block 90 where the controller 32 energizes the gun or ejector 20 to throw a basketball 12 toward the first spot selected by the player P during step 1.

[0273] The photo sensor 33 senses when a basketball 12 passes through the hoop 14 (FIG. 5) and therefore when a shot by a player P has been made. At decision block 92 (FIG. 8), the photo sensor 33 determines whether the shot was made by the player P and if it was not then the routine loops back to block 88 as shown. If the shot was made, the controller 32 increments the count by one (block 94) and it is determined at decision block 96 whether or not the total number, which is the number that the player P has programmed during step 3 using the interface 40. It should be understood that if the player P has selected the challenge shooting accuracy button 74 and been prompted to enter during step 3 the number of shots that must be made in a row using the buttons 77 (FIGS. 3A-3D), with the total number of shots displayed in the display 76. If the controller 32 determines that the total number of shots made, as represented by the COUNT variable, is equal to the predetermined number of shots to be made as selected by the player P at decision block 96, then the routine continues to decision block 98, otherwise it loops back to block 90 as shown.

[0274] Thereafter, the controller 32 determines (block 98) whether or not the total number of spots (TSPOTS) equals one or zero. If the decision at decision block 98 is negative, then the player P has made the number of shots in a row at the location which the player P is shooting the ball, so the con-

troller 32 energizes drive motor and linkage 30 to pivotally drive the gun or ejector 20 so that it will eject basketballs 12 toward the next spot which was selected by the player P in step 1. If the decision at decision block 98 is affirmative then the routine exits to a standby mode as shown.

[0275] Another shooter challenge routine 32a (FIG. 1) may be selected by the player P as mentioned earlier. During this routine, a player must shoot multiple shots at the at least one or at each of the plurality of different locations 22 that are selected by the player P, without the limitation or qualification that the shots be made in a row. If this shooter challenge routine 32a is selected, controller 32 starts the routine in FIG. 9 wherein it sets a COUNT equal to zero at block 100. The controller 32 energizes the gun or ejector 20 to throw a basketball 12 (block 102) toward the first of the at least one or a plurality of the plurality of different locations 22 selected by the player P at block 102. At decision block 104, it is determined whether the shot is made and if it is not it loops back to block 102 as shown. If the shot is made, the controller 32 increments the COUNT by one (block 106) and then proceeds to decision block 108 where it is determined whether the total number of shots made is equal to the COUNT. If it is not, then the routine loops back to block 102 where another basketball 12 is thrown. If the decision at decision block 108 is affirmative, then the routine proceeds to decision block 110 where it is determined if the TSPOTS equals one or is TSPOTS equals zero. Thus, it is determined at decision block 110 if TSPOTS equals one or is TSPOTS equals zero which signify that player P has only selected one spot or the direction the gun or ejector 20 is currently pointing (zero spots) to shoot his number of makes at this spot (i.e. there is no other locations selected so the gun goes in standby mode). If it is not, then the controller 32 energizes the drive motor and linkage 30 to pivotally drive the gun or ejector 20 so that it throws a basketball 12 to the next spot selected by the player P at block 112 and the routine then proceeds back to block 100 as shown. If the decision at decision block 110 is affirmative, then the routine exits to standby mode as shown.

[0276] After the player P has used the system 10, it may output the shooting efficiency statistics to the ticket printer 46 by selecting the print button 114 (FIG. 3C). The user can display shooting statistics either by the ticket printer or by exporting them to a secondary device like a computer and see them there.

[0277] In the illustration being described, the controller 32 may be programmed with one or more player's names, such as the players P on any given team and their information stored in the electronic storage device 44. When a particular player P is using the system 10 he can retrieve his user information using the user button 116 (FIGS. 3A-3D) which the controller 32 could cause a directory of players to be displayed so that the user can select the player P that will be using the system 10. In one illustration, each player will have a 3 digit code tied to his name which will be initially set up on a computer and dropped down on the gun/ejector 20 by an import button 118 (FIGS. 3A-3D). When player P wants to use the system 10, he will enter his three digit code. This code will be displayed on the front scoreboard display 45 (FIGS. 1 and 4) when the system 10 is in standby mode and for a set time, such as at least 4 seconds, in the STEP 3 (76 in FIGS. 3A-3D) three digit display. Although not shown, the system 10 may include the ability to load/enter the shooter's number or name at the gun/ejector 20 and have it displayed on the front board and/or on the control board, thus not having to

import it from a computer. The statistics relative to a player P may also be imported and stored using the button 118 (FIG. 3D), which a coach uses to load players into the system each tagged with a 3 digit code or if the coach has to edit a certain player's shooting data on a given workout. Moreover, the user can export data associated with one or more players P using the export stats button 120 (FIG. 3D). In this regard, the controller 32 may have an input/output interface that enables, for example connection to permanent or portable storage devices, such as CD, DVD, USB interface for smart drives, flash drives and the like. The information can then be loaded onto other computers (not shown) for evaluation and use by other users, such as coaches, trainers and the like.

[0278] During use of the system 10, it may be desirable to provide a display 45 (FIGS. 1 and 3A-3D) which can be wired or wireless and in communication with the controller 32 so as to enable a player P or his or her coach to view the performance and efficiency during the player P's use of the system 10.

[0279] In general, the system 10 comprises the user interface 40 that enables the user to select the shooting practice that the user desires. During the first step, the user turns the power to the gun or ejector 20 and the controller 32 on and selects either the pre-programmed drills or the user can select at least one or a plurality of different locations 22 at which the player P will shoot the basketball 12. In the illustration being described, for example, the user would select the various positions by depressing one or more of the buttons 41 (FIG. 3A) which are arranged on the interface 40 to generally correspond to the positions 22 labeled in FIG. 1. The controller 32 receives the selected positions information and stores it in memory (not shown). During a second step, labeled as step 2 on the user interface 40, the user selects the time delay between passes using the buttons 43 and display 45. The time delay represents the amount of time that the gun or ejector 20 allows to lapse before ejecting basketballs 12.

[0280] During the third step, the user uses the button 77 and display 47 to select the number of shots at each of the locations selected during step 1. The user may begin a practice by depressing the start button 70 and may end the practice by depressing the stop button 72.

[0281] During this third step, the user may also elect to challenge the shooting accuracy. The shooter challenge routines 32a are stored in the electronic storage device 44. It should be understood that the shooter challenge routines 32a facilitate improving the player P's shooting efficiency by providing a number of shooting challenges to the player P at one or more of the plurality of different locations 22. By challenging the shooter accuracy and then evaluating a shooter's statistics during the challenges, the shooter's performance can be evaluated. If the shooter's shooting efficiency is below a predetermined threshold or is deficient as determined by the player P or his or her coach, then during the player P's next shooting practice the player P can use the information and program the system 10 to throw basketballs 12 at one or more of the plurality of different locations 22 where the player P's performance was deficient, thereby improving the player P's shooting accuracy in general and also improving the player P's accuracy at one or more of the plurality of different locations 22.

[0282] Advantageously, this system 10 and method provide means for improving the player P's efficiency at shooting the basketball 12 at one or more of the plurality of different locations 22.



[0283] The system and method enables a player to select S number of shots and N number of positions at which the player will shoot at least one basketball.

[0284] The system and method further permits repeating the throwing, sensing and causing steps until the player has shot S number of shots at each of N number of position, wherein S is at least one of a total number of shots made at each of N number of positions or a total number of shots made in a row at each of N number of positions.

[0285] Referring now to FIGS. 10-63, other embodiments of the invention will now be presented and described. An overview of these embodiments will now be described. In the embodiments, like parts are identified with the same part numbers, except a prime ("'") has been added to the parts described in this embodiment. Notice in FIG. 10 some additional components relative to the embodiment of FIG. 1 are shown. In this embodiment, a system 200 is provided for training players from the same or different teams and for training players or teams practicing at the same or different locations. In one embodiment shown in FIGS. 10-62, the system 200 comprises a Doppler measuring system 800 and means for measuring or calculating various measurements, such as a player's release time, a player's distance between a position from which the player shoots to the rim 14', a release arc associated with the player's release of the ball 12', and an entry arc are associated with the angle at which the ball 12' enters the hoop 14', as will be described later herein.

[0286] In another embodiment, the system and methods described herein provides means, procedure and tracking system for calculating, comparing and tracking shooting statistics and data of players from the same team or different teams regardless of whether those players or teams are located at the same shooting location or at different shooting locations and regardless of whether the players or teams are shooting at the same time or at different times. In other words, the system allows, for example, a player, a coach or other interested person on one team of players to view that player's shooting statistics and also to compare those statistics against other shooters' statistics on the same team or comparing that shooter's statistics against statistics of shooters from different teams.

[0287] In the examples shown, it is important to note that the players on the different teams could be, for example, in the same league, in different leagues, of the same age group or different age groups or could be different skill levels (e.g., high school vs. college, college vs. pros, high school vs. pros). The comparisons and reports or chart, can be created using various criteria, such as age (e.g., comparison of a player age fifteen to a comparison of shooting statistics from other players of the same age or in the same age group.) It is also envisioned that gender could also be a criterion for comparison so, for example, girls or women could be compared against other girls or women from other teams in the same or different age groups. Moreover, the female shooter statistics could be compared against male shooter statistics.

[0288] In FIG. 10, a player P identifies himself to the computer 202 and then a computer 202 initiates a series of drills for the player P. During the drills, the gun or ejector 20' selects at least one spot, area or position 22' on the basketball floor and causes the ball launcher, gun or ejector 20', described earlier herein, to pass basketball(s) 12' to one or more spots or locations selected by the user or that are part of the pre-programmed drills. A measurement system, such as a Doppler measurement system 800 described earlier measures

various Doppler data described later herein, such as a speed of the basketball 12' as it leaves the gun or ejector 20'. The player P responds by moving to one of the spots or positions 22' and catches the basketball 12'. The ball launcher, gun or ejector 20' and other components may be the same or similar to the gun or ejector 20 and other parts described earlier and may have feature of the embodiment described earlier.

[0289] In short, the system and methods described herein permit a player, coach or other interested person or user to compare a shooter's statistics based on a number of selected or predetermined criteria which will be described later herein. For ease of description, the term "user" will be used herein and refers to any interested person, such as a player, trainer, coach, scout, family member or any other interested user.

[0290] Referring back to FIG. 10, the method and system 200 also provides means and apparatus for uploading and downloading information and data between the gun or ejector 20' and a website WS using a computer (such as computer 202 or 204) via the internet, wirelessly, or using other devices (e.g., computer 204). The website WS has an associated server 206 that permits the user to upload and download information to and from the website WS using the computer 202 in the manner described later herein.

[0291] The system comprises the computer 202 which is coupled to the local server or storage device 44' which was described earlier herein relative to FIG. 1. In the example, the computer 202 is used by a first user and a second computer, such as computer 204, could be used by a second user so that the second user could also access the website WS via the internet. Of course, multiple users could access and use the website WS from other computers (not shown) or devices, such as smart devices like iPad, iPhone, Blackberry and the like. For ease of illustration, the second user is shown in FIG. 10 as being associated with a remote or second system 204, but it should be understood that the second user could also be utilizing the computer 204 directly, wirelessly or via the internet. Note also that the first user could access the computer 202 directly or via the internet as shown. It is also important to understand that the second user could be utilizing the system 200 located at the same geographic location and same system 200 that is used by the first user. Alternatively, the second user could be utilizing a different launcher 20' with a different backboard 14' at a different geographic location remote from the first location of the system 200 and computer 202 that the first user is using. For ease of description, the second system comprising the same components as the system 200 will be collectively referred to as system 208 (FIG. 10).

[0292] In the illustration being described, the first and second systems 200 and 208, respectively, are calibrated as described herein so that shooting positions and statistics gathered from the various shooting positions using the first and second systems 200 and 208 can be compared. For example, a player A using system 200 and shooting at a location, such as at location 8 (FIG. 10), as identified by button 8 shown in the interface 40 in FIG. 3, will be shooting from location 8 at the basketball playing area shown. The gun or ejector 20' will shoot or launch balls to the position 8 as selected, the shooter A will shoot from that position and the system 200 will measure and calculate statistics and data, described later herein, relating to player A's shooting at the position 8. A player B using the second system 208, which can be at the same or different geographic location, that has been programmed to launch balls or that launches ball to the same position 8, the system 200 will measure, calculate and gen-

erate data and statistics relative to the second player B's shooting efficiency at the position 8. In one illustrative embodiment that the players could be shooting at the same time or at different times and that the system 200 and second system 208 could be located at the same or different geographic locations. Thus, the players may not know that they are competing against each other, whereas in other illustrative embodiments, the players may desire a competition and use the systems 200 and 208 to compete directly against each other at the same or different times or locations.

[0293] As mentioned, one embodiment includes the Doppler measurement system for generating various data and statistics to be described herein. The general measurements will be described relative to FIGS. 12A-12C and 13A-13G. Features of a Doppler system and circuit will be described later herein relative to FIGS. 15A-15D.

[0294] FIGS. 12A-12C are flow charts which illustrate processes undertaken by one form of the invention showing a general operation of the Doppler system 800.

[0295] In FIG. 12A, execution begins at block 801. Block 802 then inquires whether the motor which launches the basketball 12 is running. If not, the NO branch is taken, and the logic idles in the NO branch until the motor is detected as running.

[0296] When the running motor is detected, the YES branch is taken, and the logic reaches block 803, which inquires whether a throwing arm TA (FIG. 11) in the gun or ejector 20', powered by the motor 30' (FIG. 10), has struck its limiting stop, which is a rubber limit bumper RB (FIG. 11). If not, the NO branch is taken, and the logic idles in the NO branch until a strike of the limit-bumper is detected by a proximity sensor PS (FIG. 11) having a proximity pickup PP. Note in FIG. 15C, the microprocessor pin labeled RC4 obtains signal from proximity sensor PS from connector J2.

[0297] It is pointed out that at least some of the idling in the NO branch occurs during the travel of the throwing arm from its rest position en route to the limit-bumper RB.

[0298] When striking of the rubber limit-bumper RB is detected, the YES branch is taken from block 803, and block 804 is reached. Block 804 inquires whether a pulse is detected from the proximity sensor LBS, which indicates that the throwing arm TA has struck the limit-bumper, indicating that the ball 12' has been launched. If no pulse is detected, the NO branch is taken, and the logic idles in the NO branch until the pulse is detected.

[0299] When the pulse is detected, indicating that the arm TA has struck the limit-bumper RB, the YES branch is taken, which leads to block 805 in FIG. 12B. In block 805, a flight timer is started in microprocessor 910 (FIG. 14) described later herein. To repeat: the pulse of block 804 in FIG. 12A indicates that the launching arm has reached the limit of its travel, and thus a ball has been launched. The flight timer is now started at this initiation of the launch, as indicated in block 805 of FIG. 12B.

[0300] Next, block 806 is reached, in which the duration of X number of pulses is measured. This allows computation of the time interval T between adjacent pulses to be measured, which allows determination by microprocessor 910 of the pulse frequency, which is the inverse of T, or 1/T. This is an indicator of the Doppler frequency, although in the digital domain.

[0301] Next, the logic reaches block 807 in FIG. 12B, which inquires whether the measured speed of the ball 12' has reached zero. If not, the NO branch is taken, and the logic reaches block 808, which inquires whether the gain of the amplifiers described later herein which amplify the Doppler

signal should be increased. If not, because the amplification is sufficient, the NO branch is taken from block 808 and leads to block 806.

[0302] If block 808 indicates that amplification must be increased, the YES branch is taken, leading to block 811, where an amplifier gain is increased. The logic returns to block 806.

[0303] If, in block 807, the ball velocity is detected as zero, indicating that the player has caught the ball 12', then the YES branch is taken. Block 809 is reached, wherein the Doppler frequency, mentioned in connection with block 806, is actually computed. Also, a release timer is triggered.

[0304] At this time, it is assumed that the player has caught the ball, because the measured velocity of the ball is zero. It is desired to now learn how fast the player can get off a shot, also referred to herein as release time, so a release timer RT is initiated in microprocessor 910 described later herein.

[0305] The logic then proceeds to block 810, which asks whether pulses are received which indicate that a Doppler frequency has resumed. To repeat: during the flight of the ball to the player, the Doppler pulses dropped to zero when the player caught the ball 12'. Now, as the player holds the ball 12' momentarily, block 810 waits for the pulses to resume, indicating that the player has made a shot. The logic idles in the NO branch of block 810 until ball 12' motion, indicating a shot is detected.

[0306] When the pulses are detected, the YES branch is taken from block 810, and block 812 is reached. That block ascertains the count value of the release timer which was initiated in block 809. The count value indicates the time delay between (1) the time when the player caught the ball and (2) the time the player makes a shot.

[0307] Next, block 813 is reached, which measures the speed of the shot made by the player in the manner of block 806.

[0308] Next, block 815 in FIG. 12C is reached, which computes a distance of the player from the hoop or rim 14', based on the measured speed of the ball and the time of flight of the ball.

[0309] Next, block 816 calculates the release angle, entry angle to the basket, and the arc height, or peak altitude, of the ball.

[0310] Next, block 817 displays, or prints, or both, the five indicated parameters which were computed, and stores those values.

[0311] Next, block 820 inquires whether the ball throwing motor is active. If not, the NO branch is taken, and the processing ends, as indicated by block 821. If so, the YES branch is taken, and the logic returns to block 803 in FIG. 12A.

[0312] FIGS. 13A, 13B and 13C provide an overview of the computations used to gather various Doppler measurements referred to herein. These algorithms are programmed into microprocessor 910 (FIG. 14) described later herein. FIGS. 13D-13H provide greater detail referred to in the description relative to FIGS. 14 and 15A-15C and elsewhere herein.

[0313] In FIG. 13A, the ball 12' travels toward the player. The following equations are used:

$$D = V_{GUN} \times T_d \quad A1$$

[0314] A2  $V_{GUN}$  is velocity of ball

$$V_{GUN} = (C \times \Delta F) / (2 \times F) \quad A3$$

[0315] C = Speed of Light

[0316] F = Radar Frequency (24.15 GHz)

[0317]  $\Delta F$  = Doppler Shifted Frequency

$$V_{GUN} = \Delta F / 161 \text{ m/sec} \quad A4$$

[0318] A5  $T_d$  = Time of Flight

[0319] In FIG. 13A, the ball B travels toward the player. The distance to the player is given by equation A1, and is the standard equation of distance equaling velocity multiplied by time. The time  $T_d$  is defined in equation A5.

[0320]  $V_{GUN}$  is the velocity of the ball, as indicated by equation A2. Equation A3 gives a standard Doppler equation. Equation A4 is a simplification of equation A3, in which the constants F and C have been inserted. It is seen that velocity, in meters per second, equals the measured frequency shift divided by 161.

[0321] In FIG. 13B, the arc height  $D_A$  (or  $D_{Arch}$ ) is computed using the following equations:

[0322] B1 measure horizontal velocity of player's shot,  $V_h$

[0323] B2 compute assumed time of flight to basket,  $T_p$

$$T_p = D/V_h \text{ (D from FIG. 13A)}$$

[0324] In FIG. 13B, the arch height  $D_A$  (or  $D_{Arch}$ ) is computed.  $D_A$  is the height above the point at which the player releases the ball, as shown in FIG. 13E, and not the height of the arch above the ground.

[0325] In equation B1 in FIG. 13B, the horizontal velocity component,  $V_h$ , is measured by the radar gun, as described herein. Equation B2 computes the assumed time of flight,  $T_p$ , to the basket.  $V_h$  becomes  $V_{ox}$  later.  $V_v$  becomes  $V_{oy}$  later.

[0326] The vertical velocity in that equation,  $V_v$ , is computed in FIG. 13E, equation 4. It is preferred to compute  $D_A$  as shown in equation 5, which is explained later with reference to FIG. 13G.

[0327] In FIG. 13C, the entry angle theta,  $\theta_e$  is computed, as is the release angle theta,  $\theta_r$ . The following equations are used:

[0328] C1 compute  $V_v$  based on kinetic energy of ball at basket

$$\theta_e = \arctan V_v/V_h \quad C2$$

[0329] Phrase C1 indicates that the vertical component,  $V_v$ , of the ball's velocity is computed. Equation C2 then computes theta,  $\theta_e$ . Theta,  $\theta_e$ , is computed in a similar way.  $V_v$  ("v" for vertical) is a generalized variable, and a specific instance later will be  $V_{by}$  ("y" for y-axis). Similarly,  $V_h$  ("h" for horizontal) in FIG. 13C is a generalized variable, and a specific instance later will be  $V_{bx}$  ("x" for x-axis).

[0330] FIGS. 13D-H will provide details of the computations just outlined.

[0331] In FIG. 13D, an x-y coordinate system is shown, wherein x represents horizontal distance and y represents height. For any point P on the path of the ball B, equations 1 and 2 apply.

[0332] Equation 1 is the difference between (1) the vertical distance covered because of the initial velocity of the ball, namely,  $V_{oy}T$  and (2) the deceleration of the ball due to gravity, namely,  $\frac{1}{2}gT^2$ . From another point of view, equation 1 is the sum of (1) distance travelled upward at any given time T, plus the superposition of (2) the distance travelled downward at that same time T. Equation 1 gives the y-coordinate of the ball.

[0333] Equation 2 gives the x-coordinate of the ball, and is the simple velocity-multiplied-by-time function.

[0334] In FIG. 13E, equation 3 is the result of combining equations 1 and 2 of FIG. 13D. In equation 3A, the known values of x and y are substituted for the condition where point P is located at the basket. That is, at the basket, the value of x is D and the value of y is  $D_B$  (or  $D_{Basket}$ ). Those values are substituted into equation 3, to produce equation 3A, as indicated.

[0335] Equation 4 is a reduction, in which equation 3A is multiplied by  $V_{ox}^2$ , and re-arranged, as indicated. Equation 4 allows computation of  $V_{oy}$ , which is the vertical component of the ball's velocity.

[0336] FIG. 13F is a further illustration of the content of Equation 4, which is repeated in the Figure.  $V_{oy}$ , the vertical component of velocity of the ball, is computed from  $D_B$ ,  $V_{ox}$ , D, and g.  $D_B$  is the height of the ball, at the basket, above the player's release height. The player enters  $D_B$  into the system upon initialization. Of course,  $D_B$  will, in general, be larger for a player who is short of stature, compared to a taller player.

[0337]  $V_{ox}$  is the x-component of velocity of the ball, and is measured by the Doppler shift. D is the distance between the player and the basket. The parameter g is the acceleration due to gravity.

[0338] FIG. 13G produces equation 5, which allows computation of  $D_A$ , the arch height, based on  $V_{oy}$ . Equation 5 results from solving the equation  $(\frac{1}{2})MV^2 = MgH$  for H, and making the substitution indicated.

[0339] FIG. 13H uses the preceding values computed to obtain the angle theta, the entry angle of the ball into the basket. Equation A indicates the potential energy of the ball at the top of the arch, that is, at height  $D_A$  (or  $D_{Arch}$ ). Equation B indicates the total energy (kinetic plus potential, in the y-direction) of the ball at the basket, at height  $D_B$  (or  $D_{Basket}$ ). It is assumed that  $V_{bx} = V_{ox}$ , since air drag is ignored. This assumption is considered tenable, since at a typical ball velocity of 13 feet per second, the speed reduction due to drag is about 0.9 percent, that is, less than one percent.

[0340] Another embodiment for determination of arch height is shown in FIG. 13I. In this embodiment, the distance to the player is known and whether the player is at R1 or R2. So, in advance, a player makes a series of shots at each of R1 and R2, with different arch heights. The shot for each different arch height will have a different flight time. A look-up table may be created and stored in memory on the gun. Then, during play, for each shot, the distance (R1 or R2 in the illustration) and the flight time is ascertained. An arch height for that type of shot is "looked-up" in the look-up table, which eliminates the need to compute the value. This is illustrated in FIG. 13I.

[0341] The total energy of the ball (in the y-direction) at the basket equals the potential energy at the peak of the arch, that is, at the height  $D_A$ . Thus, equation A is set equal to equation B, and solved for  $V_{by}$ , producing equation 6.  $V_{by}$  is the vertical component of velocity at the basket.

[0342] Equation 7 then uses  $V_{by}$  and  $V_{bx}$  to compute the entry angle of the ball at the basket.

[0343] An exemplary calculation using typical values will now be given. The following assumptions are made:

[0344] 1. Velocity of ball as shot from the gun,  $V_{gun}$ , is 20 feet per second.

[0345] 2. The distance D from gun to player is 18 feet.

[0346] 3. The hold time by the player is 0.45 seconds, that is, slightly less than one-half second.

[0347] 4. The horizontal velocity of the player's shot,  $V_{ox}$ , is 13 feet per second.

[0348] 5. The height of the basket above the player's release height,  $D_b$ , is 3 feet.

[0349] The following calculations are thus made.

[0350] A. The flight time to the player is 18 feet/(20 feet/second), or 0.9 second. Thus,  $T=0.9$  second.

[0351] B. From Equation 4 in FIG. 13E,  $V_{oy} = [(D_B)(V_{ox}^2) + \frac{1}{2}gD^2]/D V_{ox}$ . In this example,  $V_{ox}=13$  feet/

second,  $D_B=3$  feet,  $D=18$  feet, and  $g=32.2$  feet/second<sup>2</sup>. Thus,  $V_{oy}$ , vertical velocity of the player's shot, equals 24.46 feet per second.

[0352] C. From Equation 5 in FIG. 13G,  $D_A=(V_{oy}^2/2g)=9.29$  feet. Since the height of the basket is known to be ten feet, the ball release height is seven feet. The arch is thus 6.29 feet above the basket (i.e.,  $9.29-3.0$ ).

[0353] D. The entry angle, theta, in FIG. 13H is calculated from Equation 6 in that Figure.  $V_{by}=8.02$  SQRT  $(D_A-D_B)=20.1$  feet per second. Theta is  $\text{ARCTAN}(V_{by}/V_{bx})=\text{ARCTAN}(20.1/13)=57.1$  degrees.

[0354] The system 200 and Doppler system 800 comprise a Doppler circuit for capturing and/or calculating the various Doppler measurements that will now be described.

[0355] FIG. 14 is a high-level diagram of a circuit which detects the speed of the ball 12' as it exits the launcher. FIGS. 15A-15D are more detailed diagrams of the circuit.

[0356] Horn 900 in FIGS. 10, 11 and 14 is mounted adjacent an exit port on the gun, ejector or launcher 20'. Horn 900 in FIG. 14 generically represents a radar gun having a Gunn diode (not shown) in the illustration. It should be understood that a conventional radar gun may be used.

[0357] Horn 900 includes (1) a radar transmitter which transmits bursts of energy at 24 GHz, (2) a receiver, or detector, which detects reflected radar energy, and (3) a mixer (also called a multiplier or heterodyne circuit) which produces a signal which indicates the difference in frequency, due to Doppler shift, between the transmitted signal and the received signal.

[0358] The difference signal, indicated as waveform DS in FIG. 14, will most often lie in the range of about 200 to 1200 Hz. The difference signal DS will probably be contaminated with low frequency noise N.

[0359] A variable gain amplifier 902 amplifies the difference signal DS. Waveform 904 represents the amplified signal. The amplifier is represented as an amplifier 906 symbolically followed by a variable potentiometer 908. The latter operates as a voltage divider and picks off a signal which is a percentage of the output signal produced by the amplifier 906. Thus, as a hypothetical example, if the gain of amplifier 906 is 10, and potentiometer 908 picks off 80 percent of the amplified signal, the net amplification is 8.

[0360] The gain of the variable gain amplifier 902 is controlled by microprocessor 910, as indicated by dashed line 912. One reason for using variable gain is that the strength of the reflected signal received by horn 900 will depend on the distance to the object (the basketball 12' in this context) causing the reflection.

[0361] For example, if the object is located ten feet from the horn, the reflected signal received by the horn will have a certain strength. If the object is located twenty feet from the horn, the reflected signal received by the horn will have a smaller strength because the reflected signal travelled a longer distance.

[0362] In order to compensate for this reduced signal strength due to distance, the gain of amplifier 902 is adjusted during the flight of the radar pulse. The following simplified Table 1 illustrates some principles involved in this compensation. All units are arbitrary for simplicity.

TABLE 1

Row 100	Distance to Object	Time of Flight of Radar Pulse	Strength of Received Signal	Gain of Amplifier
1	10	1	5	1
2	20	2	4	5/4
3	30	3	3	5/3
4	40	4	2	5/2

[0363] As Table 1 indicates, the time of flight of the radar pulse (that is, the round-trip time which includes the time of flight to the object, plus the time of flight back to the horn 900) is proportional to the distance to the object. The strength of the received signal is arbitrarily indicated as the sequence 5, 4, 3, 2.

[0364] It is pointed out that the flight time of the ball-pass described earlier is not the time of flight in Table 1, but is one-half of the time of flight of Table 1.

[0365] The gain of the amplifier 902 is adjusted so that the signal strength produced by the amplifier 906 remains at unity. For example, for the object at 10 distance units, the received signal strength is 5, and the gain is unity.

[0366] For the object at 20 distance units, the gain is 5/4, or 1.25. When this gain is applied to the received signal strength of 4, the resulting signal strength is  $4 \times 5/4$ , or 5, making the received signal strength, after amplification, the same as the signal strength for the object at 10 distance units.

[0367] Further, the sequence of operation is significant. Row 1 represents an elapsed time of 1 unit after transmission of a radar burst. The gain is 1 at this time. If a reflected signal is received at this time, it is amplified by this gain.

[0368] Row 2 represents an elapsed time of 2 units after transmission of this radar burst. The gain is 5/4 at this time. If a reflected signal is received at this time, it is amplified by this gain.

[0369] Row 3 represents an elapsed time of 3 units after transmission of this radar burst. The gain is 5/3 at this time. If a reflected signal is received at this time, it is amplified by this gain, and so on.

[0370] Thus, for each radar pulse transmitted, the microprocessor 910 in FIG. 14 adjusts the gain of amplifier 902 according to the sequence listed in the Table above, based on the time elapsed since the pulse was transmitted. At time 1, the gain is 1; at time 2, the gain is 5/4; at time 3, the gain is 5/3, and so on. This sequence is repeated for each successive pulse.

[0371] In the immediately preceding discussion, a single speed of the ball-pass. However, if a faster pass is made, then, at any given time after launch, the ball will be farther away than the same ball passed at a slower speed.

[0372] To repeat: at any given time after launch, such as Y milliseconds, the reflected radar signal from the faster ball, when received, will be smaller than the reflected radar signal from the slower ball, when received. The reason is that, after Y milliseconds, the faster ball is farther away.

[0373] Accordingly, Table 1 above can be modified. The progressive reduction of signal strength in the received burst will depend on the distance which the burst traveled (that is, the total distance to the basketball, plus the return distance). That distance will equal (1) the speed of the basketball multiplied by (2) the time of travel of the basketball.

[0374] The basketball's speed is known to the microprocessor 910 in FIG. 14. The time of travel is also known

because that is simply the time elapsed since the launch of the basketball, called the pass flight time above.

[0375] Therefore, the distance to the basketball 12', in the second column of Table 1, in principle, will be known by multiplying the speed of the basketball 12' times the time elapsed since the radar pulse was transmitted. A radar pulse will travel twice this distance. The attenuation of the radar signal will depend on this distance.

[0376] Consequently, the time elapsed since the launch of the basketball is used to determine the gain of variable gain amplifier 902 in FIG. 14.

[0377] This can be illustrated by Table 2.

TABLE 2

Row	Speed of Ball	Distance to Object	Time of Flight of Radar Pulse
1	20	10	1
2	20	20	2
3	20	30	3
4	20	40	4

[0378] Assume that the speed of the ball 14' is 20, as indicated. In Row 1, the time of flight represents a trip to the ball, plus the return trip, for a distance of 20. Since the speed is 20, the time of flight is 1, as indicated.

[0379] In row 2, the speed is still 20, but the total distance is 40, corresponding to the time shown of 2, and so on.

[0380] In another embodiment, the gain selected for each time instant after launch of the basketball 12' need not be a linear function of time.

[0381] Therefore, the distance to the ball 12' is, in principle, used to adjust the gain of the amplifier 902 in FIG. 14. That distance can be inferred based on speed of the ball, and time elapsed since the ball was launched. Thus, for a given ball launch speed, a given sequence of gains is computed, or retrieved from memory. One gain is used at each time interval, as indicated by the Tables above. For another ball launch speed, another sequence of gains is computed, or retrieved from memory, and so on.

[0382] In one form of one embodiment of the invention, the goal is to maintain the signal received by horn 900 as constant as possible. The gain required at each instant can be determined experimentally in a simple manner, since the distances involved are not large. For example, if the basketball is launched for different distances of 5 feet, then 6 feet, then 7 feet, and then in one foot increments up to 100 feet, and the signal attenuation measured for each launch, that represents 96 launches, which can be done in a short time. The necessary signal gain is immediately apparent for each launch, based on the signal received for each.

[0383] After the gain is adjusted in pursuit of maintaining a constant received amplitude, the signal is filtered. In FIG. 14, the output of variable amplifier 902 is fed to a block 914, which represents components, later described, which perform multiple functions. One function is that block 914 extracts the amplified difference signal DS, and suppresses low frequency noise N. A second function is that block 914 performs amplification.

[0384] The output of block 914 is indicated as waveform 916, which represents the extracted difference signal DS.

[0385] The output of block 914 is fed to a comparator 918, which compares this output to a threshold voltage THRESH, which is produced by a potentiometer 920. Potentiometer 920

is manually adjustable. The adjustable voltage THRESH determines the trip point of the comparator 918.

[0386] Each time the voltage THRESH is exceeded, comparator 918 produces a pulse, thereby producing a pulse train 922 having a frequency identical to that of waveform 916, which frequency is identical to the difference frequency DS. This frequency indicates the speed of the object which reflected the radar pulse produced by horn 900

[0387] Microprocessor 910 counts the number of pulses occurring in pulse train 922 per second, and thereby deduces the frequency of the pulse train 922.

[0388] Switch 923 is controlled by the microprocessor 910, as indicated by dashed line 925. Switch 923 turns the transmitter within horn 900 on and off periodically.

[0389] One reason is that the transmitter utilizes a Gunn diode to generate radar energy. Gunn diodes can draw significant amounts of current, and the current can cause heating of the Gunn diode, which will increase the temperature of the Gunn diode. The increase in temperature can cause a drift in frequency of the Gunn diode.

[0390] Therefore, in one form of one embodiment of the invention, the microprocessor 910 turns on the Gunn diode, through switch 923, only just prior to transmission of a radar burst, and shuts down the Gunn diode immediately afterward.

[0391] FIGS. 15A-15C are more detailed circuit diagrams of the speed measuring circuitry of FIG. 14. Horn 900 in FIG. 15A corresponds to the transmitter/receiver horn 900 of FIG. 14 described above.

[0392] In FIG. 15A, and other figures, resistors are labeled with the symbol "R," followed by another symbol, such as "7," as in "R7" adjacent, and to the right of, horn 900. These symbols are not used as reference indices for explanations given in the text of this Specification for the functions provided by the associated resistors. Instead, the symbols are used for internal consistency in the drawings. For example, if R7 appears in two different places in the drawings, the symbol R7 indicates that the same resistor is shown in those two places. A similar comment applies to capacitors and other elements.

[0393] In FIG. 15A, a first stage amplifier 924 (not individually indicated in FIG. 14) receives the signal from horn 900. The amplifier is AC coupled, and has a gain of 100.

[0394] The symbolic variable gain amplifier 902 of FIG. 14 is indicated in FIG. 15A as amplifier 902A. The variable gain is provided by a digitally variable resistor 908A, which alters the feedback network of individual amplifier 926, which alters the overall gain of the amplifier stage 902A.

[0395] Digitally variable resistor 908A in FIG. 15A functions as the symbolic potentiometer 908 in FIG. 14, and is under control of the microprocessor 910 in FIG. 14. Digitally variable resistors are known in the art, and one suitable version is model number MCP 4013, available from Microchip Technologies, Inc.

[0396] In FIG. 15A, filter 914A is contained in block 914 in FIG. 14. The output line 928 in FIG. 15A leads to the same line 928 in FIG. 15B.

[0397] Lines 909 represent power lines which receive voltages from sources external to the components of FIG. 15A. The voltages are delivered to those components, via lines which are not shown. Item 909A in FIG. 15B and item 909B in FIG. 15C represent similar power lines.

[0398] Circuit 910 supplies reference voltages which are used throughout FIG. 15. It includes a precision shunt voltage reference 911, such as model number LTC 1634, available

from Linear Technologies, Inc., which feeds an operational amplifier 912, such as model number TL074, available from Texas Instruments Corporation.

[0399] In FIG. 15B, amplifier stages 920 amplify the signal on line 928. The eight diodes D (only two of them are labeled) act as clippers to eliminate low level noise when no signal is received on line 928, as when no ball-pass has been made by the ball launcher, which is shown in other figures.

[0400] Comparator 922 determines when the output of amplifiers 920 exceed a threshold and, if so, feeds a signal to transistor 924. The signal is indicated by LED 926.

[0401] The signal on line 930 is fed to microprocessor 915 in FIG. 15C, which is an industry standard PIC 18F9140. An RS232 converter 931 enables serial communication with the processor 910. LEDs 935 are used for diagnostic purposes.

[0402] FIG. 15D illustrates a power supply PS which powers the circuits described above. Twelve volts DC are applied to lines 950. Lines 950 deliver power to voltage regulator 944, which is an industry standard model 7805 regulator, which delivers five volts, regulated, on terminal 960. A shut-down switch 968 is activated by a signal on line 969.

[0403] Terminals 950 also power a DC/DC converter circuit 970, which contains the industry standard LT1931 DC/DC converter 972, which produces negative 8 volts on line 975. Other embodiments of the invention may utilize 12 volts on this line 975, and yet other voltages in other cases.

[0404] A significant feature of one form of the invention is that the microprocessor 910 in FIGS. 14, 15A makes the computations described herein based, in essence, on only two external inputs. One external input is the pulse train 922 of FIG. 14, which, after processing, appears on the line labeled SigA in FIG. 15C. That line SigA is a single line, carrying a single pulse train.

[0405] That pulse train 922 indicates the Doppler shift of the radar signal, which is Delta-F in equation A3 in FIG. 13A. That Doppler shift is used to compute the parameters of (1) distance to the player, (2) arch height  $D_a$  in FIGS. 13B and 13E, and (3) release angle and entry angle in FIG. 13D.

[0406] The other external data used is  $T_p$ , elapsed time of the player's shot, as in equation B2 in FIG. 13B. This is computed as the time interval between (1) the time of initiation of the shot, as indicated by resumption of the Doppler signal, and (2) the arrival of the ball at the basket, which is detected as described herein.

[0407] So long as the user has entered  $D_b$  (the difference between the height of the ball at the release point and the loft rim), the only external values used by the microprocessor are (1) the Doppler shift and (2) the flight time of the player's shot,  $T_p$ .

[0408] Another time,  $T_d$  in equation A1 in FIG. 13A is used, namely, the time of flight of the pass to the player. But  $T_d$  is an internally computed value, using the internal clock of the microprocessor 910 or using another device associated with the microprocessor 910. The beginning of the time interval  $T_d$  is known to the microprocessor 910 because the microprocessor 910 initiates the pass. The end of the time interval  $T_d$  is known from the time when the Doppler shift drops to zero. This is sensed by the proximity sensor LBS in FIG. 11, when the arm TA hits the stop RB.

[0409] To recapitulate: the Doppler shift, indicated in pulse train 922 in FIG. 14, is used to measure the initial speed of the launched ball. When the Doppler shift indicates that the speed

of the launched ball falls to zero, it is assumed that the player has caught the ball. The time between launch and catch,  $T_d$  is then computed.

[0410] When the Doppler shift indicates that the ball is again in motion, it is assumed that the player has shot the ball. The Doppler shift is then taken as indicating the horizontal velocity  $V_h$  in FIG. 13D. When the ball reaches the basket, the time of flight of the ball,  $T_p$  can be computed.

[0411] The Doppler shift and  $T_p$ , the time of flight of the player's shot, are values determined by external events. The flight time of the pass to the player,  $T_d$  is computed internally, as the interval between (1) initiation of the launch of the ball, which is under control of the microprocessor 910, and (2) the drop of the Doppler shift to zero, indicating zero speed in the ball. In one embodiment of the Doppler, the signal is continuous. It transmits a continuous 24 GHz signal. The signal it receives back from a moving target is slightly shifted in frequency above or below 24 GHz according to the velocity of the target. When mixed together (transmitted and received signal), a difference signal results. The frequency of this difference signal is proportional to target speed. The difference signal is what is input to the first amplifier stage of the gun or ejector 20' circuit. So the changes in amplification occur as a function of time from an event, the Gun throwing the ball in the first case, and the player shooting the ball in the second case.

[0412] In one embodiment, the gun or ejector 20' which launches a basketball pass at a time  $T_1$ , a radar gun which measures speed S of the basketball upon launch and a control which knows time  $T_1$ , identifies a time  $T_2$ , when the speed measured by the radar gun falls below a first threshold, detects a time  $T_3$ , occurring after time  $T_2$ , when speed measured by the radar gun rises above a second threshold, learns that the basketball scored a goal at time  $T_4$  after a shot by the player, computes a pass flight time PFT, based on the equation  $PFT = T_2 - T_1$ , computes a distance D based on the equation  $D = PFT \times S$ , computes a hold time H based on the equation  $H = T_3 - T_2$ , and computes a shot flight time SFT based on the equation  $SFT = T_4 - T_3$ . In another embodiment, SFT can be computed by dividing the Distance, D (already computed) by the Player's horizontal velocity,  $V_{ox}$ . It should be understood that SFT could be measured by the means written if every shot was a make.

[0413] Thus, to repeat, the computations of FIGS. 13A through 13G are based on only two variables whose values depend on external events, and those variables are (1) DELTA-F in equation A3 in FIG. 13A and (2)  $T_p$  in equation B2 in FIG. 13B, which is the flight time of the player's shot.

[0414] The use of the measurements and calculations (e.g., in customized comparison reports) is described later herein.

[0415] Referring back to FIG. 10, as with the embodiment shown relative to FIG. 1, note that the gun or ejector 20' has the storage device 44' for storing information, data and statistics regarding the player's shooting. As with the embodiment described earlier herein, a portable storage device 210, such as a USB drive, flash drive or other memory or storage device may be used to enable the user to port to a USB port (not shown) on the gun or ejector 20' and download information, such as a player roster, upload the statistics and data from the gun or ejector 20' to the computer 202. The first user or users may then access the website WS via the internet using the computer 202 and upload those statistics to a server 206 associated with the website WS for use as described herein. Alternatively, the gun or ejector 20' may include a conven-

tional wireless communication device **145'** to enable the user to wirelessly transmit the data and statistics from the gun or ejector **20'** directly to the computer **202** or other device or directly to the website WS. Similarly, the second computer **204** may upload data and statistics from the second system **208**, for example, using another portable storage device **210** and the remote computer or server **204** (or wirelessly) to the website WS and the computer **206** associated therewith.

[0416] After the data and statistics from one or more players, such as Players A and B, is captured or measured and has been uploaded to the website WS and its associated server **206**, the first and second users can elect to make the data and statistics public so that they can be used by others, elect to keep the data and statistics private for use only by themselves or some combination thereof. The first and second users may also view, save (locally or on a remote server, such as the website WS server, or portable storage device), create and print customized reports, use customized reports regarding a player using the data and statistics. Comparison reports and charts of players' data, statistics and rankings from the same or different teams, the same or different geographic territories or other criteria, such as gender, age or skill level may also be created, viewed, stored, printed and used as described and shown later herein.

[0417] Advantageously, therefore, the system according to another embodiment enables a user to improve the player's shooting efficiency by, among other things, comparing shooting statistics and rankings of players, regardless of whether the players are using the same gun or ejector **20'**, using different guns or ejectors **20'**, shooting at the same or different times, shooting at the same or different geographic locations, or the like.

[0418] Referring now to FIG. 16, an overall schematic view of the methodology and process for using the system **200** is shown. Initially, the user registers (block **220**) the gun or ejector **20'** by accessing the website WS, which will be described later herein relative to FIG. 17. The user creates and stores team information (block **222**) using by accessing the website WS using, for example, computer **202** and such process is described later herein relative to FIGS. 35 and 18. The user creates and stores a team roster and its players, and that data for players of the team is stored on the website WS (block **224**), which is described later herein relative to FIGS. 36, 37 and 18. After the user has stored the information and data on the website WS, the team and player data information may be downloaded (block **226** in FIG. 16) to the gun or ejector **20** and this procedure is described relative to FIG. 19.

[0419] In order to utilize and compare statistics or data from shooters using multiple guns or ejectors **20'** which are situated at the same or different geographic locations, it is necessary to calibrate each gun or ejector **20'** (block **228**), and this procedure is described in more detail relative to FIG. 21. After the gun or ejector(s) **20'** is/are calibrated, the players, teams, coaches and other users may use the gun or ejector **20'** (block **230**). In this regard, the players, teams and coaches may use the gun or ejector **20'** in a traditional manner, as described earlier herein relative to FIGS. 1-9, including utilizing the shooter challenge routines **32a'**, the other shooting challenges, or the gun or ejector **20'** may be used by the same or different teams. In general, the use of the gun or ejector **20'** is described later herein relative to FIG. 20.

[0420] Returning to the overview description in FIG. 16, after the gun or ejector **20'** as described is used, shooting statistics and data are captured by the gun or ejector **20'** (block

**232** in FIG. 16), those statistics or data may then be used, uploaded to the portable storage device **210**, computer **202**, transmitted or uploaded to website WS server **206** in a manner described later herein relative to the procedure shown in FIG. 26. After the statistics and data described earlier herein are captured and uploaded to the website WS server **206**, the user (such as players, coaches or other interested users or persons) may create, view, download, save them on a local server or storage associated with the computers **202**, **204**, remote server or portable storage device (such as a flash drive), publish, share and/or print customized reports using the data and statistics. The creation and use of customized reports and use is described in more detail herein relative to FIGS. 27, 28A-28B and use the customized reports created to improve the players' shooting and basketball playing ability and skills (block **234**). The overall procedure and use of the system then ends. More detailed descriptions of the foregoing will now be provided.

[0421] Referring now to FIGS. 17-19, a process and procedure for registering a gun or ejector **20'** and for creating and downloading a team roster of players to the gun or ejector **20'**, along with a plurality of associated graphical user interfaces, shown in FIGS. 30-41, will now be described. Referring to FIG. 17, the coach or user accesses the website WS, which is shown in the illustration as being the website located at the domain name www.shootaway.com. The screen shots or graphical user interfaces in FIGS. 30-41 are presented to the user when he or she accesses the website WS. Once the website WS is accessed (block **250** in FIG. 17), the user is presented with and uses the graphical user interface **260** (FIG. 30) and enters the serial number of the gun or ejector **20'** and an authentication number at the locations **262** and **264** on the graphical user interface as illustrated in FIG. 30 (block **252** in FIG. 17). In the illustration being described, the authorization code inserted in the area **264** in FIG. 30 is provided by the manufacturer of the gun or ejector **20'**. In this regard, each individual gun or ejector **20'** has a unique serial number and has the authorization code associated with it. The user is provided this authorization code as a means of securely accessing the website WS. The user may be assigned and be required to enter a user name and a password for the user to access their account in the future. This user name and password may be communicated or provided to the user, for example, in an email message **266** (FIG. 33) communicated to the user. In a conventional manner, the website WS presents the user with a graphical user interface **268** (FIG. 31) after the serial number and authorization code are accepted by the website WS whereupon the user can enter his or her name, create a user name and password and have an assigned email address as illustrated in the FIG. 31. In this regard, at using the graphical user interface **268**, the user can enter his or her first and last name, user name, password and an email address and then create and account at the website WS by actuating the electronic "create account" button **270** in FIG. 31. Once the information is entered, the user can create the account by clicking the electronic "create account" button **270** in FIG. 31 whereupon the website WS creates a user account for the user.

[0422] In response to this input, the website WS generates a message, which is illustrated in FIG. 32 on the graphical user interface **272**, which informs the user to check his or her email address, one illustrative email confirmation or notice is shown in the FIG. 33 (block **254** in FIG. 17) which informs the user of the general overview of the system **200** as well as provides an electronic link **267** in FIG. 32 (block **256** in FIG.

17) for enabling the user to log on to the account that the website WS created and associated with the user.

[0423] Once an account is created, the user may go to the website WS (block 258 in FIG. 17) and log in using their newly created user name and password. The first time the user accesses the website WS he or she is directed to a “create roster” procedure or routine which will now be described relative to FIG. 18 (block 259 in FIG. 17).

[0424] In one illustrative embodiment and after registering the gun or ejector 20', the user is enabled to create rosters and add teams and players, for example, up to twenty-seven players per team, although the number of players could be more or fewer, using the website WS. Each player is assigned a digital or numeric code that they will use to enter each time they use the gun or ejector 20'. Once the roster has been entered by the user on the website WS, the user will be prompted to and may export it (or save it) to a portable storage device 210, such as a USB drive, thumb drive, flash drive or the like. The gun or ejector 20' comprises a port or interface (not shown) that receives the portable storage device 210 so that the data thereon can be downloaded to the gun or ejector 20' using the import button 118 mentioned earlier herein relative to FIG. 3.

[0425] In one illustrative embodiment, two groups or teams of players within, for example, a school or organization can be tracked by one gun or ejector 20', and the website WS will allow for at least two groups or teams to be tagged to each gun or ejector 20' that was entered into the area 262 on the website WS associated with the gun or ejector 20'. For example, if a high school boys and girls teams purchased a single gun or ejector 20' together, the gun or ejector 20' will track twenty-seven players for the boy's team and twenty-seven players for the girl's team. In this regard, the system 200 contemplates that each of the boys and girls teams has created an account tied to the gun or ejector 20' serial number and authentication code that was provided as mentioned earlier herein. In one illustrative embodiment, only two individuals, such as coaches, may be registered or associated with one gun or ejector 20' when accessing the website WS. A third or other user may be associated with the gun or ejector 20', but only if one of the prior two users has been deleted or disassociated with the gun or ejector 20' serial number.

[0426] In the manner described later herein, once the gun or ejector 20' is registered using the procedure in FIG. 17 and the roster is created using the website WS, including team and players (for example, up to twenty-seven players in one illustrative embodiment), the user(s) will be allowed to log onto and use the gun or ejector 20' by using the interface 40 (FIGS. 3-3D) and input the roster onto the gun or ejector 20'. In this regard, it is important to note that once the team or player information and data is stored by the user on the website WS, it may be imported into the gun or ejector 20'. Individual players can be selected by using the digital code that is assigned to each player at the time the roster is created in the manner described later herein. In this regard, the user uses the interface 40 and depresses a button such as the pre-programmed drills button 278 (FIG. 3B) which is a button used for both selecting pre-programmed drills and selecting the player who is shooting. Once the pre-programmed drills button 278 is depressed, a player's three-digit code will appear on the display 45'. If necessary, the user may toggle the pre-programmed drills button 278 to scan through and select one digital number assigned to the desired player. In the illustration being described, the digital code is displayed on the display 45' and if the user scrolls through the digital code

and leaves the digital code on the front scoreboard display 45' for two or more seconds, the gun or ejector 20' will recognize the player and will begin tracking and storing that player's shooting statistics and data. After the gun or ejector 20' recognizes the player, the pre-programmed drills button 278 may be used in a conventional manner to select one or more pre-programmed drills that are stored on the gun or ejector 20'.

[0427] As will be described in more detail later herein, after a shooting session, the statistics and data associated with the team or one or more players may be uploaded to the website WS. In this regard, the portable storage device 210 mentioned earlier herein, such as a USB flash drive, may be inserted into the port, such as a conventional USB port (not shown) on the gun or ejector 20', and the export button 120 on interface 40 may be actuated so that the shooting statistics and data associated with a shooting session may be downloaded or exported to the portable storage device 210. The portable storage device 210 may then be ported to a storage device or computer, such as computers 202 or 204 (FIG. 10), and the shooting statistics and data uploaded to the user's account at the website WS. In this regard, a session file, which is a comma delimited file containing the data and shooting statistics associated with a session of shooting, may then be uploaded to the website WS using an import button 280 (FIG. 35) on the graphical user interface 292.

[0428] Having described the procedure for registering the gun or ejector 20' and provided a general overview of the tracking system and features of the embodiment being described, a more detailed description of various features of embodiments will now be described. As mentioned earlier, it is necessary to create a roster of teams and players on the website WS and that roster of teams and players may then be downloaded to the gun or ejector 20'. Again, after the gun or ejector 20' is used during a shooting session, the data and statistics may be uploaded to the website WS, for example, using the import button 280 (FIG. 3) which is provided in the graphical user interface 292 (FIG. 35). The user logs onto the website WS (block 282-FIG. 18) using the graphical user interface 284 (FIG. 34) which is provided by the website WS after the user has created his user account as will now be described. After the gun or ejector 20' is registered, a roster is created using the procedure to create a roster of team(s) and players, which will now be described relative to FIG. 18.

[0429] As illustrated in FIG. 18, the user enters his user-name and password in the areas 286 (FIG. 34) and 288, respectively, and then actuates the login button 290. The user will be presented first with the ability to add a team (block 294 in FIG. 18) and create a roster link using the graphical user interface 292 (FIG. 35) presented by the website WS. After log in, the user uses the graphical user interface 292 and enters a team or group name (“SPUTS” in the example) at area 296 and identifies an associated gender using the electronic buttons 298. The website WS also asks the user to identify a team number from 0-9 in the area 300 of the graphical user interface 292. It is important to note that this single-digit number will appear as the first digit of the digital code assigned by system 200 to each shooter who will be using the shot tracking system in accordance with the illustration being described. The digital code in the illustration associated with each player is a three digit code in the embodiment being described, but it could be another alphanumeric or digital code of longer or shorter length.

[0430] Once the team, gender and team number is assigned by the user, the user actuates (block 294 in FIG. 18) the



electronic submit button **302** (FIG. **35**) whereupon the team is created. Once a team has been created, the user may select a players link button **304**, which is the electronic link labeled "Players" in the top banner portion of the graphical user interface **306** (FIG. **36**). Whereupon the user is presented with the graphical user interface **306** which enables the user to link or associate players with the team that was created using the graphical user interface **292** in FIG. **35**. Thus, at block **295** (FIG. **18**), the user chooses the add player link **304** (FIG. **36**) whereupon the user is presented with area **223** (FIG. **36**) containing the gun login number area **308**, first name area **310**, last name area **312** and a drop down menu **314** for selecting the team. Note that a gun login number entered in the area **308** of interface **306** is a number associated with the player and that player will use when logging onto and using the gun or ejector **20'** to collect data and shooting statistics during a shooting session. In the illustration being described, the gun login number will be assigned by the user by selecting a number from 0-99, which will be combined with the team number prefix digit, mentioned earlier relative to area **300** in FIG. **35**, to create the three-digit code. In one illustrative embodiment, the number of players associated with a team is limited to 27, but it is to be understood that more or fewer players may be assigned to a team if desired.

**[0431]** The information is submitted to the website WS by actuating the electronic submit button **316** (FIG. **36**). In response, the website WS presents the user with a graphical user interface **318** illustrated in FIG. **37** which shows the team and the players that are associated with the team in the area **320** of the graphical user interface **318**.

**[0432]** Referring back to FIG. **18**, after the user enters the players name, assigns a login number, birth date and associates the player with a team (block **297** in FIG. **18**), it is determined at decision block **299** whether the player wishes to add another player. If yes, then the routine loops back to block **297** as shown, but if not, the routine proceeds to block **301** in FIG. **18** where the roster of players is stored on the website WS as a comma delimited file in the illustration being described. In this regard, the information or data associated with the roster may be stored on the local computer **202**, **204** and/or the remote server **206** associated with the website WS. Alternatively, the data may be stored on a portable storage device **210** of the type mentioned and described earlier herein.

**[0433]** After the roster is created as described relative to FIG. **18**, the roster may be downloaded to the gun or ejector **20'** which will now be described relative to FIG. **19**.

**[0434]** Referring now to FIG. **19**, the rosters are downloaded to the gun or ejector **20'** after the rosters are created and the procedure for downloading will now be described. The procedure begins by the user logging onto the website WS using the graphical user interface **284** (FIG. **34**) and actuating the electronic button **290** (block **330** in FIG. **19**). At decision block **332**, it is determined whether the user has entered a roster to download to the gun **20'**, if not then the user uses the procedure described relative to FIG. **18** to create a roster on the website WS (block **334** in FIG. **19**). If the decision at decision block **332** is affirmative, then the user selects the export link **293** (FIG. **35**) at block **336** in FIG. **19**. Once the user selects the export link **293** in the graphical user interface **292**, the user is presented with a graphical user interface **300** (FIG. **38**) by the website WS. The user is provided with the ability to export or save the play list file of the roster which includes the data and information relating to a team and its

players, onto a storage device **210** (FIG. **10**). In this regard, the player is provided with the graphical user interface **340** (FIG. **39**) showing storage areas on his or her computer, such as computer **202** or **204**, or other device the user uses to access the website WS. The user selects the player list file (identified in the FIG. **39** as "plyrlist") and saves it out using the electronic button **342** (FIG. **38**) onto the portable storage device **210** of the type mentioned earlier herein. The "plyrlist" file, which comprises the information regarding the team, the players identification code, name, and the like, are imported to the gun or ejector **20'** using the USB port (not shown) using the import button **118** (FIG. **3**) mentioned earlier herein. Although the embodiment being described herein discusses or utilizes the portable storage device **210** for importing and exporting data and statistics to and from, respectively, the gun or ejector **20'**, it is important to understand that these functions and features could be done wirelessly with conventional wireless technology. Also, it is envisioned that the gun or ejector **20'** could comprise means and apparatus for uploading and downloading information directly to the website WS to the computers **202** or **204** and the like using conventional wired or wireless technology, thereby reducing or eliminating the need for the use of the portable storage device **210**. It is also important to note that the computers **202** and **204** may be stand alone computers, portable computers or smart phones or devices, such as an Apple iPhone, Android, iPad, BlackBerry, smart phone or other similar smart device that is capable of receiving and transmitting information to and from the website WS.

**[0435]** In the illustration using portable storage device **210**, the user inserts the device to a port (not shown) on the gun or ejector **20'** and actuates the import button **118** (FIG. **3D**), which causes the "plyrlist" data to be downloaded onto the gun **20'** This is done at block **338** in FIG. **19**.

**[0436]** After the rosters are downloaded to the gun or ejector **20'**, the routine in FIG. **19** ends. It is important to understand that once the gun or ejector **20'** has been programmed with the roster(s) of teams and/or player(s), the gun or ejector **20'** is ready to use and collect statistics as provided herein. A general description of use will now be described relative to FIG. **20**.

**[0437]** The procedure starts at block **350** (FIG. **20**) where the gun or ejector **20'** is calibrated at the geographic location where it is located, such as a gymnasium or basketball floor. The calibration procedure is described later herein relative to FIG. **21**. The calibration procedure is important so that the data and statistics captured or collected regarding a shooting session for one or more players using the same or different guns or ejectors **20'** will be comparable. For example, the data and statistics associated with a player shooting at a particular position, such as along a vector associated with the position **8** (FIGS. **2** and **10** and the button labeled **8** in FIG. **10**) will be comparable to a second player B who is shooting from that same position, position **8** in the example.

**[0438]** Once the gun or ejector **20'** is calibrated, then shooting data and statistics may be compared with reasonable reliability and relatively low margin of error. As mentioned earlier, the players A and B may be on the same team shooting at the same location, may be on the same team shooting at different locations, may be on the same team shooting at the same time, may be on the same or different teams using the same gun or ejector **20'**, on different teams using different guns or ejectors **20'**, may be on different teams using different guns or ejectors **20'** at the same or different times, and the like.

[0439] Returning to FIG. 20, the player selects at least one or a plurality of positions from which to shoot (block 354), which is described later herein relative to FIGS. 23A, 23B, 24A and 24B. The player shoots until the selected routine, whether it be a pre-programmed drill routine or a user-programmed drill routine, ends at block 356. In one embodiment, the gun or ejector 20' may be programmed to eject balls 12' in the order in which the buttons 41 (FIG. 3A) are selected. In other words, the controller 32' on the gun or ejector 20' will cause the balls to be ejected from the gun or ejector 20' in the order in which the buttons were selected. The system 200 stores the plurality of positions selected and then the gun or ejector 20' ejects the correct number of balls to those locations in the order they were programmed. It may also eject the balls in order from left to right as viewed on the interface 40 as far as the plurality of the positions no matter the order they were programmed. For example, if the user selected or actuated buttons 0, 11, 5 and 16 (FIGS. 3A-3B) on interface 40 in this order, then the controller 32' would cause the balls to be ejected from the gun or ejector 20' to the corresponding location 0, 11, 5 and 16 (FIG. 10) in the order in which the buttons 41 (FIG. 3A) were selected, thereby enabling the user to program the positions in a non-serial order which enables the gun or ejector 20' to accurately simulate game-playing situations. This programming ability enables the user to create millions of possible shooting drills or routines.

[0440] After the shot selection is determined and the player shoots until the routine ends (FIGS. 23A, 23B and 24A, 24B), it is determined whether or not a new shooter, the same shooter or whether the shooter(s) are done shooting. If they are the same or if there are new shooters, then the routine loops back to block 354 as shown, but if the shooting is done, then the user may export the data and statistics regarding the shooting session (block 360), which is described later herein relative to FIG. 25. At decision block 362 (FIG. 20), the user who is exporting, uploading or saving the data or statistics may decide to make the data or statistics public or available for use or to view by others at decision block 362. If the decision is not to make them available, then the routine proceeds to block 364, but if the decision is to make them available, then the procedure enables the data and statistics to be made available for use by others at block 366, and this procedure is described later herein relative to FIG. 25.

[0441] It is then determined whether the user wants to view and/or make local, regional, national or international comparisons of the data or statistics from a shooting session at decision block 368. If the user does not, then the procedure ends, but if the user does wish to view, print and/or make local, regional, national or international comparisons, then the routine proceeds to block 370 (FIG. 20) wherein the system proceeds to block 434 in FIG. 25.

[0442] As referenced in FIG. 20, block 350 and for the reasons mentioned earlier, the gun or ejector 20' is preferably calibrated and the procedure to calibrate the gun or ejector 20' is shown in FIG. 21, which will now be described. The calibration procedure starts by the user positioning the gun or ejector 20' underneath the net or rim 14' adjacent to the backboard 16'. The gun or ejector 20' is centered lengthwise (baseline to baseline) on the basketball playing area or court with a center line of the basket (end to end) and thus is equidistant from each of sidelines and side edges of the backboard, all of which is shown in block 371. Calibrating the gun or ejector 20' in this manner facilitates ensuring that all shots taken from, for example, a shooting location such as the

shooting location associated with the button labeled 8 (FIG. 3A) associated with the position 8 (FIG. 10), will be on a dead-center line of the court as it bisects a baseline where the gun or ejector 20' is located to the opposing baseline at the opposite end of the court. Accurately positioning the gun or ejector 20' also assures accurate measurements by the Doppler System 800 (FIG. 10) and comparisons.

[0443] As shown in block 352 in FIG. 20, after the gun or ejector 20' is calibrated, the player may log in and use the gun or ejector 20' and the procedure for log in will now be described relative to FIG. 22. The player starts by using the pre-programmed drills button 278 on the interface 40. In the example, the user enters his 3 digit code by first pressing the user button 116 in FIG. 3C the pressing the number of balls in FIGS. 3A and 3B until he/she has entered the complete code. The user then presses the Pre-Programmed Drills button 278 (FIG. 3B) to enter that code. The user could also depress and hold the user button in FIG. 3C for 4 seconds, for example. If this is done, the system 200 enables the user to scroll through all the user codes using the up/down arrows 43 (FIG. 3B). When they see their code, the user actuates or presses the Pre-Programmed Drills button to enter it. Thereafter, it is determined at block 372 (FIG. 22) whether the player logged in with a code that exists (as downloaded and stored to the gun or ejector 20' by the user) or that has been programmed into the gun or ejector 20' at decision block 374. If he or she has not logged in properly, then the gun displays an error code, which in one embodiment is the three letters "EEE" on the interface 40' on the display 42' (FIG. 10) at decision block 376.

[0444] If the decision at decision block 374 (FIG. 22) is affirmative, then the gun or ejector 20' is ready to use and collect data and statistics (block 378) for the player regarding the player's makes and total shots for the player at each shooting location from where the player shot at block 378. Thereafter the routine ends.

[0445] It is important to understand that once the gun or ejector 20' has been calibrated and the player has logged in, the player may begin a shooting session and shoot until the shooting session ends, as mentioned earlier relative to block 356 in FIG. 20. For ease of description and illustration, it is to be understood that the Doppler System 800 described earlier herein may be used during a shooting session, although it is not mandatory. Thus, measurement and calculations from the Doppler System 800 may be used alone or in combination with other features of other embodiments described herein. For ease of description, various procedures will be described herein as being Doppler dependent, which means that the procedures are conducted using the Doppler System 800 and measurements sensed and calculated therefrom. Some of the features or embodiments of the invention will be repeated, but without use of the Doppler System 800. Accordingly, it should be understood that while some of the embodiments utilize the Doppler System 800 and its calculations or measurements, it is not mandatory and there are features of various embodiments that are not dependent on the measurements performed by the Doppler System 800. For further ease of illustration and description, some of the procedures and embodiments described herein will be first described as without the use of the Doppler System 800, followed by a description of a similar embodiment but using the Doppler System 800.

[0446] Referring now to FIGS. 23A and 23B, a process is shown for the user to select a shooting workout for the gun or ejector 20' to collect and save statistics and data relative to the

workout, such as the number of shots made, number of total shots taken and the like at each of the predetermined or preselected shooting locations (e.g., the locations associated with the buttons 0-16 and labeled 41 in FIGS. 3 and 3A-3D and the associated positions or locations 22' (FIG. 10). The routine starts at block 380 (FIG. 23A) wherein the shooter chooses his shooting locations 0-16 on the interface 40 (FIGS. 3 and 3A-3D) by actuating one or more of the plurality of buttons 41. Alternatively, the user may select the pre-programmed drills button 278 (FIG. 3B) to cause the gun or ejector 20' to run through one or more pre-programmed drills that are stored on the gun or ejector 20'. If no locations are selected by the user, the gun or ejector 20' will treat the shooting session as an "open" session during which the gun 20' will fire balls in the direction it is pointing set physically by the user pointing the gun to the left corner or top of the key. There is no random shooting to different spots.

[0447] The routine proceeds to block 382 (FIG. 23A) wherein the shooter chooses the time delay between the pass by using the area of the interface 40 (FIG. 3A) labeled step two with the plurality of buttons 43. Time between passes can be from approx 1.5 seconds to 99 seconds. The shooter then chooses the number of balls 12' to be passed to each location before the gun or ejector 20' moves to the next shooting location (block 384). The shooter actuates the up and down arrow button 77 (FIG. 3D) to enter the total number of shots to be passed to each of the shooting locations before the gun or ejector 20' moves to the next shooting location. In one illustrative embodiment, the shooter or user may choose (block 386) if he or she wants to require shots to make or made in a row before the gun or ejector 20' moves to the next shooting location by actuating the button 74 (FIG. 3C). Once the gun or ejector 20' is programmed, the user may press the start button 70 (FIG. 3D), as indicated at block 388 in FIG. 23A.

[0448] At block 390 in FIG. 23A, the shooter begins shooting at a first one of the selected shooting locations and the gun or ejector 20' saves or records each made shot at each shooting location on the storage device 44' (FIG. 10). The gun or ejector 20' will also save a total number of shots at each shooting location. If no spots or shooting locations were initially selected by the user at block 380 (FIG. 23A), the gun or ejector 20' will throw passes in the direction it is pointing and save the makes and misses in the "open" shooting location in the memory or storage device 44'.

[0449] The routine proceeds to block 392 (FIG. 23B) where the shooting session or workout ends when the player either presses button 72 (FIG. 3D) or the workout has come to an end. For example, a workout or shooting session may come to an end after the gun or ejector 20' has ejected or launched the total number of shots to each of the locations selected, the pre-determined drill selected has been performed, or a shooting goal or one of the shooting challenges described earlier herein has been achieved. The routine proceeds to decision block 394 (FIG. 23B) where it is determined if the player has finished shooting. If the player has, then the player or user powers off the gun or ejector 20' or logs off by pressing (block 396) the user button 116 (FIG. 3C). Thereafter, it is determined whether another player is desirous of shooting at decision block 398 and if he is, then the routine proceeds back to block 380 (FIG. 23A) as shown. If the decision at decision block 398 is negative, then it is determined whether or not an interested user, such as a coach or other user, desires to upload the shooting session data or statistics to a remote computer or

server or website (block 400 in FIG. 23B). If he does not, then the routine ends, but if he does, then the routine proceed to the upload shooting sessions data and statistics routine (block 402), described later herein relative to FIG. 26, which will be described later herein.

[0450] If the decision at decision block 394 is negative, then the routine proceeds to decision block 404 where it is determined whether or not the player wants to continue the current shooting session or workout. If he does, then the routine loops back to block 388 (FIG. 23A) as shown. If not, then the routine loops back to block 380 as shown.

[0451] Having described the general procedure for one embodiment that is not dependent on the Doppler System 800, now the procedure for selecting a shooting work out and for collecting data and statistics relative to the shooting session that utilizes the Doppler System 800 and its measurement or calculations will now be described relative to FIGS. 24A and 24B.

[0452] In FIG. 24A the routine begins at block 406 wherein the shooter chooses his shooting locations 0-16 on the interface 40 (FIG. 3 and FIGS. 3A-3D) by actuating one or more of the plurality of buttons 41 as described earlier. Alternatively, the user may select the pre-programmed drills button 278 (FIG. 3B) to cause the gun or ejector 20' to run through one or more pre-programmed drills that are stored on the gun or ejector 20'. If no locations are selected by the user the gun or ejector 20' will treat the shooting session as an "open" session during which the gun or ejector 20' will fire balls in the direction it is pointing set physically by the user pointing the gun say to the left corner or top of the key.

[0453] The routine proceeds to block 408 (FIG. 24A) wherein the shooter chooses the time delay between the pass by using the area of the interface 40' (FIGS. 3 and 3A-3D) labeled step two with the plurality of buttons 43. In the illustration, the shooter can choose between 15 seconds up to 60 seconds between passes from the gun or ejector 20'. The shooter then chooses the number of balls to be passed to each location before the gun or ejector 20' moves to the next shooting location (block 410). The shooter actuates the up and down arrow button 77 to enter the total number of shots to be passed to each of the shooting locations before the gun or ejector 20' moves to the next shooting location. In one illustrative embodiment, the shooter or user may choose (block 412) if he or she wants to require shots to made or made in a row before the gun or ejector 20' moves to the next shooting location by actuating the button 74 (FIG. 3C). Once the gun or ejector 20' is programmed, the user may press the start button 70 (FIG. 3D) as indicated at block 414 in FIG. 24A.

[0454] At block 416 in FIG. 24A, the shooter begins shooting at a first one of the selected shooting locations and the gun or ejector 20' saves or records each made shot at each shooting location on the storage device 44'. The gun or ejector 20' will also save a total number of shots at each shooting location. If no spots or shooting locations were initially selected by the user at block 406 (FIG. 24A), the gun or ejector 20' will throw passes in the direction it is pointing and save the makes and misses in the "open" shooting location in the memory or storage device 44'. The routine proceeds to block 418 (FIG. 24B) where the shooting session or workout ends when the player either presses button 72 (FIG. 3D) or the workout has come to an end. For example, a workout or shooting session may come to an end after the gun or ejector 20' has ejected or launched the total number of shots to each of the locations selected, the pre-determined drill selected has been per-

formed or a shooting goal or one of the shooting challenges described earlier herein has been achieved. The routine proceeds to decision block **420** (FIG. 24B) where it is determined if the player has finished shooting. If the player has, then the player or user powers off the gun or ejector **20'** or logs off by pressing (block **422**) the user button **116** (FIG. 3C). Thereafter, it is determined whether another player is desirous of shooting at decision block **424** and if he is, then the routine proceeds back to block **406** (FIG. 24A) as shown. If the decision at decision block **424** is negative, then it is determined whether or not an interested user, such as a coach or other user, desires to upload the shooting session data or statistics to a remote computer or server or website (block **428** in FIG. 24B). If he does not, then the routine ends, but if he does, then the routine proceed to the upload shooting sessions data and statistics routine, described later herein relative to FIG. 26, which will be described later herein.

[0455] After the decision block **420**, it is determined whether or not the player wants to continue to work the current shooting session or workout (block **420**). If the decision at decision block **420** is negative, then the routine proceeds to decision block **432** where it is determined whether or not the player wants to continue the current shooting session or workout. If he does, then the routing loops back to block **414** (FIG. 24A) as shown. If not, then the routine loops back to block **406** as shown.

[0456] It is extremely important to note a difference between the procedure described and shown in FIGS. 24A and 24B relative to the procedure in FIGS. 23A and 23B. The procedure in FIGS. 24A and 24B, the system **200** and Doppler system **800** includes Doppler data and statistics. As mentioned earlier herein, these Doppler data, statistics, measurements or calculations include measurements and calculations of distance between the player and the gun or ejector **20'**, the shooter's release time (i.e., the time it takes from when the shooter receives the ball and then shoots the ball towards the hoop **14'**), the arc or angle of the shooter's release, and the arc or entry angle of the shot as the shot enters the hoop **14'**. In the manner described later herein, this Doppler data and statistics may also be used for comparisons, creating reports and the like as described later in. The user holds spot **0** button **41** (FIG. 3A) for 4 seconds to disable or to turn on the Shot Tracker feature. In the illustration being described, the gun or ejector **20'** is always in an "on" state (unless the user has turned off the Shot Tracker feature) so that gun or ejector **20'** is always collecting Doppler data and statistics, but collecting and using this data is not mandatory.

[0457] Referring back to FIG. 24B, If the decision at decision block **424** is affirmative, then the new shooter logs onto the gun or ejector **20'** using the log in procedure described earlier herein relative to FIG. 22, as shown at block **426** in FIG. 24B. Thereafter, the routine loops back to decision block **406** as shown. If the decision at decision block **424** is negative, then the routine proceeds to decision block **428**.

[0458] If the decision at decision block **424** (FIG. 24B) is negative, then it is determined whether or not an interested user, such as a coach, desires to upload the shooting session data or statistics to a remote computer or server or website (block **428**). If he does not, then the routine ends, but if he does, then the routine proceed to the upload shooting sessions data and statistics routine (block **430**) described later herein relative to FIG. 26.

[0459] After the decision block **420** (FIG. 24B), it is determined whether or not the player wants to continue to work the

current shooting session or workout. If the decision at decision block **420** is negative, then the routine proceeds to decision block **432** where it is determined whether or not the player wants to continue the current shooting session or workout. If he does, then the routine loops back to block **414** (FIG. 23A) as shown. If not, then the routine loops back to block **406** as shown.

[0460] The user may power off the Gun by pressing the POWER SWITCH button in FIG. 3C (bottom left corner of interface **40**) the machine is powered down and the procedures in FIGS. 23B and 24B will automatically go to END and the shooting data is stored.

[0461] After shooting is complete and the normal data and statistics and Doppler data and statistics are gathered, calculated and stored, for example, by controller **32'** (FIG. 10) on the storage device **44'**, the statistics may be uploaded and stored to a local or remote computer, such as computer **202** or **204**, or on a remote server or computer, such as the server **206** associated with the website WS. FIG. 25 addresses this feature of one embodiment.

[0462] In FIG. 25, it is determined at decision block **434** whether the user wants to upload data and statistics and store them on the local computer associated with the user, such as a computer **202** or remote server or computer **204**, in the example. If he does, then the routine proceeds to block **436** whereupon the statistics are saved on the local computer **202**, **204** or other storage device so that they may be viewed locally using a conventional program such as Windows Internet Explorer or Windows Explorer both of which are available from Microsoft Corporation of Redmond, Wash., Safari available from Apple Computers of Cupertino, Calif. or other program capable of viewing html files. Note that the data and statistics may be exported from the gun or ejector **20'** using the export button **120** (FIG. 3D) mentioned and described earlier herein. As mentioned earlier herein, the data and statistics may be exported using the portable storage device **210** (FIG. 10), such as the thumb drive or flash drive mentioned earlier herein, may be downloaded to the computer using a wired (e.g., RS232 cable) or wirelessly transmitted (e.g., through a Wi-Fi connection) from the gun or ejector **20'** as mentioned earlier using conventional wireless technology.

[0463] As illustrated in FIG. 25, block **436**, one or more of the following data or statistics may be saved, used, displayed on, printed into report and the like using the local computer **202**, **204**:

[0464] Total shots on gun

[0465] Total shots per player

[0466] Total make per player

[0467] Total shots at each location per player

[0468] Total makes at each location per player

[0469] Team rankings and comparisons

[0470] Two on two vs. Records

[0471] Print graphs and shooting reports

[0472] (Comparisons can be adjusted based on date data was collected from gun or ejector **20'**)

[0473] If Doppler System **800** is used, collect Doppler measured data (arch, distance, release time, release angle, entry angle).

[0474] A user may also wish to not only store, use and print data on the local computer, such as computers **202** or **204**, but may also wish to upload the data and statistics to, for example, a remote site or server, such as server **206** in FIG. 10, or remote website WS. The user would then proceed to block **438** in FIG. 25 to export and upload the saved statistics and

data that are saved on the gun or ejector **20'** for all or only selected ones of the shooters who were shooting during a shooting session to a computer, such as computers **202** and **204** or to the remote website WS and the server **206** associated therewith. Again, the data could be uploaded using the internet, or wirelessly, such as through a Wi-Fi connection or other data connection. As mentioned earlier herein, the portable storage device **210** (FIG. **10**) may also be used to store the data and statistics so that they can be accessed using a computer which can be used to upload the statistics to the website WS, for example.

[**0475**] In one illustrative embodiment, it is important to note that if the statistics and data are uploaded to the website WS, the system **200** comprises a tracking system that is adapted to enable and permit a collection of measured and comparison statistics and data to be generated, stored, saved, viewed, published and used. For example, regional rankings and comparisons may be performed to rank and compare players who perform during the shooting session to other players in the region. Similar rankings and comparisons could be made on a state-wide basis (e.g., all players within the state of Ohio), a nationwide, basis, or international rankings and comparison comparing all players throughout the United States of America, Italy, China, Japan and the like. The system **200** and method described herein provide means and device for generating and using comparisons that can be adjusted based upon numerous various parameters described later herein, such as a shooting date or date range when a shooting session occurred, age of players, gender of players and the like. As illustrated in block **440** (FIG. **25**), the statistics and data that may be gathered, calculated, saved and stored:

[**0476**] Total shots on gun  
 [**0477**] Total shots per player (pp)  
 [**0478**] Total make pp  
 [**0479**] Total shots at each location pp  
 [**0480**] Total makes at each location pp  
 [**0481**] Team rankings and comparisons  
 [**0482**] Two on Two vs. Records  
 [**0483**] Print graphs and shooting reports  
 [**0484**] Regional rankings and comparisons  
 [**0485**] State rankings and comparisons  
 [**0486**] National rankings and comparisons  
 [**0487**] World rankings and comparisons  
 [**0488**] (Again, comparisons can be adjusted based on the date the data was collected from gun or ejector **20'**) It should be understood that the graphs and shooting reports could be printed by using, for example, a ticket printer **46'** or any other printer, such as a local or remote printer associated with computer or server **202**, **204**, server **208** or website WS.

[**0489**] If Doppler System **800** is used, Doppler measured data (arc, distance, release time, release angle  $\theta_r$ , entry angle  $\theta_e$  is also collected) in the manner described earlier relative to FIGS. **13A-13B**, **14** and **15A-15D**.

[**0490**] The procedure for uploading the shooting sessions to the website WS will now be described relative to FIG. **26**. The procedure for uploading shooting sessions data and statistics begins in FIG. **26** at block **442** wherein the user powers up the gun or ejector **20'** into standby mode which may be manually selected by actuating the stop or standby button **72** (FIG. **3**). If the data and statistics are to be uploaded non-wirelessly or without a hardware connection to, for example, a computer **202**, **204** or to the website WS, then in one illustration this may be done using the portable storage device **210**

(FIG. **10** as mentioned earlier). In this event, the user inserts the portable storage device **210** (FIG. **10**) which in the illustration being described could be a USB thumb drive into the USB port (not shown) of the gun or ejector **20'**. Once the portable storage device **210** is inserted into the port (not shown) of the gun or ejector **20'** control board or controller **32'**, the user may actuate the export data button **120** (FIG. **3D**) to save the sessions file (block **442** in FIG. **26**).

[**0491**] It is important to understand that in one illustrative embodiment, the sessions data and statistics file includes all shooters' dates and statistics and data associated with all shooting sessions they completed since the last export of data, their nametag to the three digit player code described earlier herein, number of makes and total shots in each session they shot each time from each shooting location. If the user wants to export the data without the use of the portable storage device **210**, then the user may do so, for example, wirelessly. For example, the user would power up the computer **202** and use a wireless communication device **145'** (FIG. **10**), which in the illustration being described is coupled to the controller **32'** and mounted on the gun or ejector **20'**. In the illustration being described, the wireless communication device **145'** may comprise conventional Bluetooth technology or other dedicated wireless or wired internet connection. If Gun is equipped with wireless communication device **145'** that includes a wireless receiver and transmitter (FIG. **10**), which is optional, the user would press the import or export buttons **118**, **120** to effect the import or export of data (FIG. **3D**). Alternatively, a hard wire connection between an RS232 port on the gun or ejector **20'** may be used.

[**0492**] In the illustration shown in FIG. **26**, it is contemplated that the portable storage device **210** is used and the user takes the portable storage device **210** to the computer **202** (block **444** in FIG. **26**), inserts it, logs into the website WS using the graphical user interface **284** described earlier herein relative to FIG. **34**. The user then selects the link to import button **280** (block **445** in FIG. **26**). In response to the user actuating the import button **280** (FIG. **35**), the user is prompted with another graphical user interface **446** (FIG. **41**) and with a browse button **448** which, when actuated, presents the user with view(s) of their computer so they can import the file. Screen shot **450** (FIG. **40**) is illustrative. The illustrative file is shown as "SESSIONS" and labeled as **453** in FIG. **40**. After it is selected, the user may actuate the button **455** in FIG. **40** whereupon the file is imported from the portable storage device **210** or computer **202** and linked to the import sessions user interface **446** as illustrated in FIG. **41**. The user may then actuate the upload stats button **457** (FIG. **41**) whereupon the system **10** causes the file to be uploaded to the website WS and the server **206** associated therewith.

[**0493**] As mentioned, the data is stored in a database **206a** (FIG. **10**) associated with the server **206**. It is important to note that the database **206a** is updated and retains cumulative shooting statistics for each shooter on a team or roster. Thus, for example, if only two of ten shooters on a team shot during a shooting session, their data could be uploaded as described, but the database **206a** maintains cumulative data for all members of the team regardless of when shooting occurred. This is useful for generating the comparison reports described later herein, some of which utilize lifetime shooting statistics.

[**0494**] Advantageously and as described, graphical user interface **450** (FIG. **40**) shows the sessions file as stored on the portable storage device **210**, which is shown in the illustration as "removable disk (K)". The user selects the "SESSIONS"

file shown on the portable storage device **210** and actuates the open button **455** in FIG. **40** whereupon the sessions file data and statistics are uploaded to the website WS and in the illustration being described, stored on the server **206** associated with the website WS. In the illustration being described, the “SESSIONS” file includes all the information and data captured and referenced relative to the data mentioned earlier herein relative to FIG. **25**. The website WS receives the information and data and updates the database **206a** (FIG. **10**) that maintains a continuous cumulative database for each player and all the statistics and data associated with the player for all the shooting statistics that were captured. In the illustration being described, the database **206a** is set up that each session is tagged to a unique number which happens the date and time to the minute that it was started. Thus the files can continuously be updated and added to.

[0495] Returning to FIG. **26**, it is important to note that if the Doppler statistics and measurements that were gathered and/or calculated during an embodiment that used the Doppler System **800**, then at the block **442**, the sessions file referenced therein would also include the Doppler measurements and statistics which include distance of the shot, the release time for the shot, the release arc of the shot and entry angle or arc of the shot. The Doppler measurement and statistics are embodied and included in the sessions file and uploaded in the manner described herein. As mentioned earlier herein relative to FIG. **16**, once the data and statistics are captured and uploaded to the server **206** (FIG. **10**) associated therewith, the users may create, view, save, use and/or print customized reports and use the customized reports. The creation of the reports, use of the reports and the reports themselves will now be described.

[0496] As mentioned earlier herein relative to block **234** in FIG. **16**, after the data and statistics are captured, measured and/or calculated, they can be viewed, stored, saved and used. In the embodiment being described, customized reports can be created and used. For example, the customized reports can be viewed by a user, such as a coach, trainer or player, to improve the player's basketball playing skills. For example, if a player learns and understands that his shooting efficiency at one location or area on the basketball floor is below a predetermined desired shooting efficiency, then the player can program the gun or ejector **20'** to increase the frequency of practice shots at that position in order to improve the player's efficiency. The procedure for creating the customized reports will now be described relative to FIG. **27**.

[0497] After the player has tracked their shooting data and statistics and the user uploads the “SESSIONS” file containing the data and statistics to the website WS, the user goes to the website WS login graphical user interface **284** (FIG. **34**) and logs into the website WS using his or her username and password (block **450** in FIG. **27**). The user may then actuate the player's button **304** in the graphical user interface **306** (FIG. **36**) and is then presented with the listing of the players in area **320**, as illustrated in FIG. **37** described earlier herein. At block **452** in FIG. **27**, the user selects a particular shooter or shooters or even a team for which they would like an in-depth report.

[0498] The routine continues to decision block **454** wherein the user determines whether or not it wants to do a chart type comparing to other shooters. If not, the routine continues to decision block **456** where it is determined whether the chart type for an individual shooter is a progression chart. If it is not, the routine proceeds to block **458** and the user selects

chart type; Made/total Shots, Shots, Percentage, Percentile at each Shooting Location and/or Doppler data of statistics.

[0499] If the decision at decision block **456** is yes, then the routine proceeds to block **460** whereupon the user selects the date range they would like the chart to include. For example, a beginning date, an ending date or total shots in a career which covers all dates is selected (block **460**). After the procedures in block **458** and **460**, the routine proceeds to allowing the user to select the rankings/chart at block **468** described later herein.

[0500] If the decision at decision block **454** is affirmative, then the user wishes to do comparisons to other shooters and the routine proceeds to block **462** where the user selects the location they would like to include which could be shooters from the local team only, the local county only, the state (e.g., all shooters in the state of Ohio), the country (e.g., all shooters in the U.S.A., France, Italy or China), or shooters from around the world. At block **464**, the user selects the minimum and maximum age so that the report includes other shooters in the age range. Alternatively, the user may select all ages so that the report will compare the player, such as player A, to one or more other players of all ages. The routine continues where the user then selects (block **466**) the shooting locations they wish to include in the chart or report. In the illustration being described, the shooting locations correspond to the buttons labeled **0-16** in FIG. **3** and the shooting locations **0-16** in FIG. **10**. It should be understood that the selections mentioned in blocks **462-466** do not necessarily have to occur in any particular sequence.

[0501] The routine proceeds to block **468** where the user selects the rankings or chart type so that the chart or report is displayed on a screen, terminal or display, such as a monitor (not shown) coupled to the computer **202** or **204** or other display that the user is using to access the website WS. As mentioned earlier herein, the display may be associated with a computer, such as computers **202**, **204**, or other smart device, such as an iPad, iPhone, Android, Blackberry or other device that has the capability of allowing a user to access, view and use the website WS. Note that when the user selects which shooting locations they wish to include, they proceed to block **460** where the user selects the date range they would like the chart to include, including the beginning date, ending date or the total shots in a career which covers all dates as explained earlier herein relative to block **460**. After block **460**, the routine proceeds to block **468** where the user selects “show rankings” chart or report. As mentioned earlier herein relative to blocks **458** and **460**, which concerns creating a chart or report when a comparison is not desired, after the user makes the selections referred to in block **458** and **460**, the user selects the show rankings/chart at block **468** as shown. It should be understood that the order of selection in blocks **462-466** is not strict, and a user can select criteria in any order as described herein.

[0502] After block **468**, the routine continues to block **470** where the user views the rankings chart or report and then proceeds to decision block **472** where it is determined whether or not the user wishes to print the chart or report created. If he does, then the chart or report is printed (block **474**), and thereafter or if the decision at decision block **472** is negative, then the user determines (block **476**) whether or not he desires to email or publish the newly-created chart or ranking. If he does, then the routine proceeds to block **478** or the user is provided with a graphical user interface in which the user can elect to email the chart or report or ranking or

otherwise publish it. In this regard, the website WS provides process and means for conventionally publishing the chart or report on website WS or using conventional social media, such as Twitter®, Facebook®, YouTube® or the like.

**[0503]** If the decision at decision block 476 is negative or after the publication referred to in block 478, the user determines at decision block 479 (FIG. 27) whether or not he wishes to create another chart or report. If he does not, then the procedure ends, but if he does, then the procedure proceeds to block 452 where the user may again select the shooter, shooters or team they would like an in-depth report on. It is important to note that the general procedure and steps referred to in FIG. 27 are shown in the order mentioned, but they do not have to occur in this exact order and the user may create reports for an individual player, group of players or team and also create comparison reports using the graphical user interface and the criteria described herein which may be selected in any order. In one form of the invention, the sorting variables may be presented on website WS as shown in FIGS. 46 and 51 with selection buttons or boxes (not shown) next to the variables for selection.

**[0504]** It should also be noted that the procedure for creating the customized reports on the website WS relative to FIG. 27 is useful for creating reports that have data and statistics that are not dependent on or that do not utilize or list Doppler measurements of the type mentioned earlier. Alternatively and in another embodiment of the invention, the charts and reports may also comprise Doppler data and statistics that include the Doppler measurements and calculations provided by the Doppler System 800 described earlier herein. If this is the case, then at blocks 458 and 460, the user can also select the specific Doppler data measurements or calculations, such as the distance from the basket from each shot, the player's release time, the release angle and the entry angle or arc at which the ball is being received in the hoop 14', that will be included in the chart or report.

**[0505]** After the user selects the chart or report criteria referred to in block 458 and 460 and/or the Doppler data or statistics, then the routine proceeds to block 468 as described earlier herein. Thus, it should be appreciated that reports or charts including the Doppler data and statistics are optional and may be selected by the user when creating the charts or reports for comparison or for an individual player or team of players. As mentioned earlier herein relative to FIG. 25 and blocks 436 and 440 in that figure, note that all of the variables mentioned earlier therein may be picked in any combination or permutation and the system 200 provides means for doing so. As mentioned earlier, in one form of the invention, the sorting variables may be presented on website WS as shown in FIGS. 46 and 51 with selection buttons or boxes (not shown) next to the variables for selection.

**[0506]** Advantageously, the system 200 and method described herein provides means, apparatus and methods adapted to enable shooting games and challenges, including the challenges mentioned and described earlier herein, as well as real-time or non real-time challenges between or among players of the same team or players of different teams and regardless of where those players are located or the time when they are shooting or the like. The system 200 and procedures and methods described herein also permit real-time competition and non real-time competitions between players of the same or different teams and regardless of where those players are located. By calibrating the gun or ejector 20' in the manner described earlier herein and providing the means and appa-

ratus for saving, viewing and printing reports, including comparison reports, the user can compare himself or herself to others.

**[0507]** FIGS. 28A, 28B and 29 provide two illustrative shooting challenges or routines. It should be understood, however, that other shooting challenges are contemplated and the system 200 and methods described herein enable users to develop customized shooting challenges for use by players on the same team or players on different teams, regardless of the geographic location of the players or the time which the players shoot. In an alternative embodiment, the system 200 and method provide a procedure for real-time challenge for two players who may use the same gun or ejector 20' at the same location. This procedure will now be described relative to FIGS. 28A-28B.

**[0508]** This procedure starts at block 500 wherein the first player or shooter, such as Player A, logs onto the gun or ejector 20' using the shooting logon procedure described earlier herein relative to FIG. 22. It is then determined whether one or more other players or shooters, such as Player B, wishes to challenge the first player and if not, then the routine proceeds to block 502. Then, the routine proceeds to block 504 where the user proceeds to login and use the gun or ejector 20'. If the decision at decision block 502 is affirmative, then there is at least one or more other players or shooters who wish to challenge the first shooter, and so, the routine proceeds to block 506 where the second shooter also logs into the gun or ejector 20' using the procedure described earlier herein relative to FIG. 22, as shown at block 506 in FIG. 28A. The shooters choose their shooting locations (block 508), the time delay using the buttons 43 (FIG. 3B) on the interface 40 as described earlier herein (block 510 in FIG. 28A) and the shooter(s) choose the number of balls (block 512) that they want passed to each selected location or pre-programmed location (if a pre-programmed drill was selected). The Players A and B alternate shooting in the illustration. Player A first shoots at a location, then Player B and so on. After shooting is complete at a location, the gun or ejector 20' passes the number of balls to the next shooting location where Player A shoots, then Player B and so on. After Players A and B have shot at the second location, the gun or ejector 20' launches balls to the next selected location. Thus, the system 200 has the players alternate after shooting the number of shots at each location. It should be understood however, that the system 200 could have player A go through the entire program and then have player B shoot or it could have them alternate every shot.

**[0509]** As mentioned earlier herein, one feature of the embodiment being described is that the shooters can select any arrangement or order of the positions by actuating one or more of the plurality of buttons 41 (FIG. 3A). The controller 32' stores the selected locations and in the order in which the buttons 41 (FIG. 3A) were actuated, thereby giving the users the ability to customize the shooting locations and the order in which the gun or ejector 20' will eject or launch balls to the shooting locations. This has been found to be very advantageous when simulating a game condition. For example, a shooter may shoot the ball from the top of the key at position 8 (illustrated in FIG. 10) and then immediately move to another position, such as a position along a vector along the "0". This simulates a game condition when the basketball 12' hits a side of the rim 14' when a shot is missed and is deflected after a shot from the top of the key, straight toward a sideline. It may be important for the player to practice shooting at both



positions in that order and the system 200 and method described herein enable the players or shooters to select positions along imaginary vectors, lines or direction extending from the gun or ejector 20' in the directions identified by the numbers or locations 0-16 in FIG. 10 in the illustration. For example, actuating the button 41 labeled "8" in FIG. 3A and then actuate the button 41 labeled "0" on the interface 40, the gun or ejector 20' launches basketballs along the vectors toward the position 8 (FIG. 10) and then toward the position 0. As mentioned earlier, in one embodiment, the gun or ejector 20' launches the number of balls programmed to each position in the order that the positions were selected using the interface 40.

[0510] At block 514 in FIG. 28A, the user presses the start button 70' (FIG. 3D) to begin the routine. At block 516 (FIG. 28A), the gun or ejector 20' begins launching basketballs 12' to the first shooter who shoots the preselected "n" number of shots programmed at block 512 at the first of the shooting locations selected at block 508. The gun or ejector 20' saves each shot that it senses being made using the sensor 33' at each shooting location on the controller or board 32', which stores the information in the storage device 44'. Note that the gun or ejector 20' also saves and stores the total number of shots taken on the storage device 44'.

[0511] When the first shooter is done shooting at each of the locations selected at block 508, then the second shooter begins shooting "n" number of balls selected at block 512 at the various shooting locations programmed at block 508. The gun or ejector 20' again saves this data along with the shots made as sensed by the sensor 33' and the total number of shots taken at each of the shooting locations programmed at block 508. When the next or other shooters is/are finished, the gun or ejector 20' begins ejecting balls to the first shooter at the next location that was programmed at block 508. Again, Player A shoots shots at a spot 1, then Player B shoots shots at spot 1, then Player A shoots shots at the next spot, then Player B shoots shots at the next spot and so on.

[0512] Note that the gun or ejector 20' delays the time between each pass at a shooting location in accordance with that which the user programmed at block 510. An additional delay time may also be used as in the first embodiment described earlier herein to delay the time between which the shooter begins shooting basketballs when changing from one location to the next location. For example, an additional delay time of five seconds may be required for a player or the first shooter to move to the next shooting location and the delay time that the user selected at block 510 may not be sufficient to enable the player to get to the next position. Accordingly, the gun or ejector 20' controller 32' may comprise an additional pre-programmed delay time for ejecting basketballs 12' when the location of shooting changes.

[0513] The routine continues to block 518 (FIG. 28B) where after the selected shooting workout is accomplished by the first shooter, second shooter . . . to the nth shooter, the gun or ejector 20' enters a standby mode. The winner of the challenge may be displayed on the display 45' (FIG. 10) by the user code or number assigned to the player. At block 520 (FIG. 28B), the gun or ejector 20' displays the winner of the challenge as being the player with the most makes, thus the highest percentage of makes from the selected or programmed locations. Again, the controller 32' of the gun or ejector 20' causes the number associated with the shooter/player to be displayed along with his or her percentage of makes compared to the other shooter's percentages.

[0514] The routine proceeds to decision block 522 (FIG. 28B) wherein it is determined whether the same shooters want to do another shooting challenge, and if they do, then the routine returns to block 506 as shown. If they do not, then it is determined (decision block 524) whether other shooters want to challenge one another to a shooting challenge. If they do, then the routine proceeds to block 500 wherein other shooters can perform the shooting challenge. If they do not, then the procedure ends.

[0515] It should be understood that the procedure is not dependent on Doppler statistics or measurements or data provided by the Doppler System 800, but such Doppler data or statistics may also be incorporated into the shooting challenge. The system 200 can detect where ball is being shot from within a certain accuracy and require the second player or shooter, to retake said shot until he takes the shot from "about" (e.g., within a foot in the illustration) of the first shooter's general shot distance. The system 200 notifies shooter of this by flashing timing lights or other notice on Display 45' (FIG. 10) to make shooter aware that last shot did not count.

[0516] It should be understood that the procedure described in FIGS. 28A-28B is a real-time challenge mode during which two or more players are competing against each other using the same gun or ejector 20'. In another illustrative embodiment shown in FIG. 29, a shooting challenge is provided for players from different teams at different locations. For ease of description, it will be assumed that at least one gun or ejector 20' is located at two or more geographically distinct locations and they have been calibrated (as described relative to FIG. 21) for a first team, such as team A in the illustration, and a second team, such as team B, that is using a different or second gun or ejector 20' at a different geographic location. One or more players on team A shoot until the routine ends (block 528). The data associated with one or more players from team A shooting at the various positions are uploaded and stored on the website WS server 206 (block 530) in the manner described earlier herein.

[0517] The second system 208 having a gun or ejector 20' launches balls to the same or different positions that were pre-programmed or user-programmed positions for the players on team B (block 532 in FIG. 29). One or more players shoot until the routine ends (block 534) and then data and statistics for the one or more players from the second team B shooting at the various positions are uploaded and stored on the website WS server 206 as shown in block 536. It should be understood that the players from each of the teams A and B may shoot at the same time or at different times. It should also be understood that in one embodiment, the players at the second location of team B may program the gun or ejector 20' with the exact same pattern of programmed locations that were programmed by team A. Alternatively, the teams may program their gun or ejector 20' so that they shoot at totally different locations or where only a few locations overlap, the statistics and data for each of the locations is gathered and stored cumulatively for each location by the system 208 so that shooting data for various distance and locations are stored cumulatively and comparisons may be made over a period of time using data captured over a period of time.

[0518] Thus, the system 200 enables the users to compete in real-time or in non real-time because it is capable of collecting and storing data and statistics, including Doppler data, associated with one or more shooting sessions and then accumulating and storing the data over time and storing it on the



website WS system and/or server 206. This is particularly useful when using the Doppler data and statistical measurements provided by the Doppler System 800 described earlier herein. In this regard, the Doppler measurements are captured, measured and/or calculated by the microprocessor 910 (FIGS. 14 and 15A) and schematically shown as 32' in FIG. 10 and may be stored on the website WS. Thereafter, a player's percentage of makes at numerous distances and positions, may be stored, viewed, published, printed and the like. For example, FIG. 42 illustrates a scatter or mapping diagram and FIG. 43 shows a report 600, both of which may be stored on the server 206 and used for competitions and comparisons as described herein.

[0519] Returning to the illustration in FIG. 29, recall that it is presumed that the players of team A are using a first gun or ejector 20' at a first geographic location and the players from team B are using the second system 208 (FIG. 10) having second gun or ejector 20' at a second geographic location. At decision block 538 (FIG. 29), it is determined whether more players from team A and/or team B are shooting in addition to the first players that have shot from those teams. If they are, then the routine loops back to block 526 where the second and subsequent players may shoot from the pre-programmed positions. If not, then the shooting challenge is complete for the teams A and B and the routine proceeds to block 540 where it is determined whether other players from other teams (i.e., teams other than A and B) are shooting. If they are, then a gun or ejector 20' which may be the first gun or ejector 20', second gun or ejector 20' or a third gun or ejector 20' located at a third geographic location launches balls to the pre-programmed or user programmed position for the next team (block 542 in FIG. 29). The players shoot until the routine ends (block 544).

[0520] Thereafter, data and statistics from the one or more players from the subsequent team(s) at the various positions are uploaded and stored on the website WS server 206 (block 546). If the decision at decision block 540 is negative or after the data and statistics are uploaded and stored as described relative to block 546, the system 200 enables users, such as teams, players, coaches and other interested parties, to view and compare player and team statistics of one team, such as team A, against the player and team statistics for another team, such as team B or other teams, as shown at block 548. The shooting challenge is then complete. Reports may be created and printed and the like as described herein.

[0521] As mentioned earlier herein relative to FIG. 20, FIG. 27, FIG. 29 and the like, the system 200 provides means for saving, viewing, printing, publishing the reports comprising data and statistics, comparisons, competitions and the like. The user may access the website WS with a conventional internet connection using a computer (e.g., computers 202, 204), smart phone or other smart device, such as an iPad, iPhone, Blackberry or the like. The user logs onto their account to access, publish, view and print out multiple detailed reports comparing local shooters' statistics and data, including but not limited to the number of made shots, number of shots taken, percentage of made shots relative to number of shots taken and comparisons of such statistics to a local, regional, national or international bank or data base of other shooters across the region, state, country or the world. The comparison reports and charts may be created on a cumulative basis, average basis and/or percentile basis and can be

sorted in any particular arrangement using a plurality of criteria, such as age, date, time, gender, distance or other criteria as mentioned earlier herein.

[0522] The system 200 also enables the players' statistics and data to be stored in the storage device 44' (FIG. 10) coupled to the controller 32' and located on the gun or ejector 20' so that when a user uses the gun or ejector 20', the controller 32' can cause the shooting statistics and data for the positions being selected to be displayed on display 45' during a shooting session. For example, if a first player in Ohio has programmed the gun or ejector 20' to shoot one or more balls to the location 8 before beginning the shooting session, the controller 32' will cause the gun or ejector 20' to eject or launch balls to the position 8. The gun or ejector 20' may cause the display 45' to display the position number (i.e., "8"), the historical percentage of made shots at the position 8 by the local player, the shooting percentage for that position based on either average, median totals or total shots for a work out depending on what the user prefers. Alternatively, the controller 32' may cause a percentage of made shots at a position or location on a team-wide, regional, state-wide, national and international basis.

[0523] With the Doppler measurement capability provided by the Doppler System 800, it should be understood that each of the positions 0-16 (FIG. 10) in the example may be viewed as imaginary vectors having an originating point associated with the gun or ejector 20' and which extend outwardly away from hoop 14' in the direction of the locations or spots 0-16. One vector is illustrated in FIG. 10 and labeled  $V_{13}$  for position 13. The Doppler measurement system 800 enables Doppler measurements and data to be captured at any position along the vector. For example, the Doppler System 800 enables the Doppler data and measurements to be captured along the base line vector position 0 at any distance from the gun or ejector 20', such as three feet, three-and-a-half feet, four feet, . . . twenty feet, etc. Typically, the Doppler will cease providing precise measurement data at about 35 feet. It should also be understood that the Doppler measurement system 800 rounds the measurements to the nearest foot so that, for example, if the Doppler System measures a shot taken at ten feet, seven inches, it rounds the measurement to eleven feet for ease of simplicity in comparisons.

[0524] As mentioned earlier herein, the server 206 (FIG. 10) comprises the database 206a on which the data and statistics have been uploaded to the website WS are saved. The user may access the website WS in the manner described earlier herein and then may generate the various reports, charts, comparisons and the like as described herein relative to FIG. 27. Some of these reports and charts will now be illustrated.

[0525] One illustrative report is shown in FIG. 42 wherein the individual shooting statistics report, scatter or mapping diagram for a particular shooter, Kevin Curtis in the illustration, is shown. Note the shooting positions 0-16 in the report and the Doppler data or statistics associated with the player's shooting. Thus, notice in the illustrative report shown in FIG. 42 that distance data measurements or calculations for a plurality of locations have been rounded off to the nearest foot, which are shown and labeled 602 in the illustration. The system 200 and the controller 32' and shooting efficiency calculator 32b' (FIG. 10) uses the Doppler measurement system 800 which measures, senses and/or calculates the measurements of the various distances and the sensor 33' is used to capture the number of made shots at each distance. The

controller **32'** and shooting efficiency calculator **32b'** can then calculate a makes percentage which is associated with each distance along the vectors as shown. Again, one should understand that the various positions or shooting locations **0-16** may be considered as vectors along which the ball is ejected or launches by the gun or ejector **20'** and the Doppler System **800** captures the measurement from where the player caught the ball and shot the ball from. As mentioned earlier herein, the Doppler System **800** also enables the calculation of the player's release time, which is the time between the point in time when the player captures the basketball and then shoots it toward the rim **14'**. Other Doppler statistics, such as an arc of the shot as released by the player and the entry arc of the ball **12'** as it approaches the hoop or rim **14'** are calculated by the Doppler System **800** as described herein.

[0526] The report **600** (FIG. **42**) may be visually displayed on a display associated with the computer **202** or **204** or other device in the form shown. Of course, the unique layout of the scatter diagram **600** provides the user with the means and ability to quickly view a player's performance at the various distances and positions on the basketball playing area. Note that the report **600** has the percentages **604** listed for each of the distance positions measured by the Doppler System **800**. The report **600** may also be provided in a table format, such as a table **606** in FIG. **43**. Note that the percentages are shown in the table along with the shooting area and the distance in feet as measured by the Doppler System **800** herein. For example, as illustrated in FIGS. **42** and **43**, the shooter's percentage when shooting from fifteen feet along an imaginary vector  $V_{13}$  (FIG. **10**) is 74%, as illustrated by the data labeled **608** in FIGS. **42** and **43**. In contrast, the percentage from fifteen feet along vector or location **4** is 77% as shown by the data labeled **609**.

[0527] Advantageously, the system **200** provides a convenient and easy means and process for gathering, calculating, displaying, printing or publishing shooting data and statistics regarding a player's shooting ability at one or more of the shooting locations. The Doppler measurements provide accurate shooting measurements and comparisons because the player shooting, for example, along the vector  $V_{13}$  (FIG. **10**) associated with different shooting positions **13**. This is valuable and important because players may shoot along a common vector, but not at the same distance along that vector. For example, one player may be shooting from sixteen feet, while an opposing player or subsequent player or even the same player may be shooting along the same vector  $V_{16}$ , but at a shorter or longer distance. Thus, unless the player was shooting from the exact same distance along a vector  $V_{0-16}$  from the gun or ejector **20'**, the comparisons could be inaccurate.

[0528] Advantageously, the Doppler System **800** provides accurate measurements of the distances where the player(s) shoot the basketball from, and the system **200** collects statistics associated with each of those positions and the controller **32'/microprocessor 910** (FIGS. **10**, **14** and **15C**) measures, calculates and stores the data and statistics associated with each shot and its associated distance for use in creating the reports, comparisons and the like described herein. This feature of the embodiment provides for accurate analysis and comparisons of a player's efficiency in shooting and also accurate comparisons of a player's shooting efficiency and statistics when compared to one or more other players from the same or different teams.

[0529] The report **600** in FIG. **42** and table **606** in FIG. **43** may be displayed and viewed by the user using conventional

means such as the user's computer **202**, **204** or other device that the user uses to access the website WS. The report **600** and table **606** may be printed out and/or published in the manner described herein for use by the user.

[0530] It should also be understood that the reports for a team may also be generated in the same format or in a different desired format. Also, shooting percentage comparisons may be made, for example, for a region, state, nation or the world and may be created by the user using the website WS. The system, means and process for accomplishing this will now be described.

[0531] If the user desires to upload sessions data, it will follow the upload routine described earlier herein relative to FIG. **25**. A representation or example of the "SESSIONS" file that is uploaded is shown in a format that is illustrated in FIG. **44**. Note that the file format comprises the player's identification number in the column **700**, the player's name **702**, the date the session occurred in column **703** and then the shooting results from any of the shooting locations selected by the player or user. Note that the table is broken out by showing each location (**0-16** in the illustration) being described and the total number of shots taken and made at each shooting of the shooting locations **0-16** in the illustration being described. For example, the report shows that the player Kevin Curtis (identified as "P214" in column **700**) had a shooting session on May 20, 2010, that lasted for 58.04 seconds. At position or shooting location **7**, the player took seven shots, as indicated by the data **706** in FIG. **44** and made five of those shots as indicated by data **708** in FIG. **44**. Note that the player took a total number of nineteen shots and made twelve of those shots, as indicated by the data **710** and **712**, respectively. The last column in the sessions data file identified by the part number **714** refers to the specific player number that differentiates each player in the data base no matter the team. In other words, **700** is the player number on that team and every team (Gun user) could have a **223** as a log in number for their Gun; but when it is uploaded to the internet, it is the number in column **714** that relates to this player and in the case of Joe Jones P223, his specific number tagged in the database is 19 in the illustration. In the illustration being described, the "SESSIONS" data file is a comma separated value file and will not have the actual first six rows illustrated in FIG. **44**.

[0532] If the "SESSIONS" data includes Doppler measurements or calculations generated by the Doppler System **800**, then the "SESSIONS" data file will include additional data as illustrated as shown in the FIG. **45**. Note that in this "SESSIONS" data file the gun or ejector **20'** collects or calculates six data points or facts including: 1) the shooting location, 2) the distance of the shot taken, 3) whether the shot was a make or miss, 4) the player's release time, 5) the player's release angle and 6) the entry angle into the hoop **14'**. In the illustration being described, note that the player P223, Joe Jones, had a shooting session on May 20, 2010, and that his first shot, indicated by the column **720** in FIG. **45**, shows that the shooting location was 0, corresponding to a base line shot identified by the location number **0** in FIG. **10**. The column of data **720** also shows that the distance of his shot in feet was fifteen feet and that he made the shot, identified by the number **1** which represents a made shot (the number **0** represents a miss). The report shows the player's release time for the shot was 0.301 seconds, his release angle was 55° and the entry angle of the ball to hoop **14'** was 45°.

[0533] Advantageously, a user, such as a coach, may note that the release angle, which represents the angle at which the

player released the ball **12'** toward the hoop **14'**, was  $55^\circ$ , but the entry angle was much shallower in that it was  $45^\circ$ . It may be a coach's desire to improve the player's entry angle to increase the probability that the basketball will approach the hoop **14'** at a desired angle and thereby improve the player's probability of making the shot.

**[0534]** Note that the "SESSIONS" data represented in FIG. **45** shows the data for each and every shot taken by the player with the last column identified by the arrow **722** representing the last position of the last shooting location. Note that during any shooting session, the player may shoot from different positions. In the illustration shown in FIG. **45**, Joe Jones shot in a serial order from shooting location **0, 1, 2, 3, 4** to the last shot taken, whereas in comparison, the player, Kevin Curtis, who had a shooting session on the same day, but he took all shots from the shooting location **8** in the illustration being described. Note also that the Doppler System **800** enabled the measurement and calculation of distances, release time, release arc or angle and entry arc or angle as shown. For example, Joe Jones shot at shooting location **0** from fifteen feet whereas at the shooting location **2** he shot from sixteen feet, as shown in FIG. **45**. His corresponding release time, release angle and entry angle are different as well. Obviously, the Doppler measurements provide a user, such as a coach or trainer, extremely useful data in training a player to play basketball and to score.

**[0535]** As described earlier, once the sessions data is uploaded from the gun or ejector **20'** or a computer, such as computer **202, 204**, to the website WS server **206**, the information can be used, evaluated, saved, viewed, stored, printed, published and the like. The following are some representative charts or reports that are selectively generated by the system **200** for use by the user.

**[0536]** FIG. **46** is a listing of the sorting variables that are presented to the user using drop down menus (not shown) in a graphical user interface. For example, all could be drop down decision boxes so if they were sorting on age, and did not want any above 10 years old, they would enter **10** in the box instead of "Any" and so on for the others. In the embodiment in FIG. **46**, the sorting variables include:

Headings	Quantifiers	Explanation of Quantifiers
1 Choose Player	Roster List	Chose any player on your roster or entire team
2 Minimum Age	Any	range from 1-150 $\leq$ Maximum Age
3 Maximum Age	Any	range from 1-150 $\geq$ Minimum Age
4 Beginning Date	All	Beginning date $\leq$ Ending date
5 Ending Date	All	Ending date $\geq$ Beginning date
6 Gender	Both, M, F	Male, Female or include all shooters
7 Enter Shooting Locations	All	0 through 17
8 Chart Type	Makes/Total Shots/%	Sort based on makes, total shots or shooting %
9 City	All	Choose City
10 County	All	Choose County
11 State	All	Choose State
12 Country	All	Choose Country

**[0537]** Once the user accesses the website and selects one or more of the sorting variables to be used in the report, the report accesses the website and is created in the manner described earlier relative to FIG. **27**.

**[0538]** FIG. **47** illustrates an example where a user has selected various criteria for John Drew the website WS cre-

ated the report **730** shown in FIG. **48**. Thus, in the illustration, the user selected the player John Drew, the minimum age and the maximum age, 14 years and 25 years, respectively. The beginning and ending dates indicated in the example in FIG. **47** and the rest of the variables or criteria as illustrated in FIG. **47**. In response, either the computer **202, 204** or and the website WS generated and displayed the chart or report **730** (FIG. **48**). As mentioned earlier herein, the user may elect to publish this report or chart or may save it or print it out for use by him or others.

**[0539]** In the illustration in FIG. **48**, the total shots for the criteria entered show the player John Drew to be ranked thirteenth when compared to other shooters around the world. In the illustration being described, the total shots shown in this report represent the total number of shots taken by a player at all shooting locations, which are the shooting locations **0-16** in the illustration being described. In this regard and as mentioned earlier, while the description herein has identified **0-16** locations, it should be understood that more or fewer locations may be provided on the interface **40** (FIG. **3**) and programmed into the system **200** so that there are more or fewer identified shooting locations, respectively.

**[0540]** FIGS. **49** and **50** illustrate another example where a user has selected criteria including the entire team "Sangre" and identified all ages and a beginning date and an ending date. The user selected the shooting location **8** and identified the chart type as total makes, and the state and geographic territory as being All Cities and Counties within the State of Colorado. Note the resultant report **740** (FIG. **50**) ranks the Sangre team second in total number of made shots at location **8** for the Colorado male teams. In this regard, note that the input information also includes gender, as illustrated in FIGS. **47** and **49** so that the data can be further sorted and organized based upon gender, as well as player, team and the other variables shown in the illustrations.

**[0541]** The examples illustrated in FIGS. **47, 48, 49** and **50** were not dependent upon or include Doppler measurements. In another embodiment of the invention, Doppler dependent measurements are provided and some illustrative examples of the input variables and reports generated will now be described.

**[0542]** It should be appreciated, again, that any number of reports and combinations of reports using one or more of the variables or criteria shown in the preceding and subsequent illustrations can be used. In other words, reports and charts may be created using any number of combinations or permutations of the input criteria or variables described in FIGS. **46** and **51**. FIG. **51** illustrates the plurality of variables or criteria **742**, which include Doppler measurements that may be presented to the user from the website WS and made available for selection. Note that the criteria or variables include:

Headings	Quantifiers	Explanation of Quantifiers
1 Choose Player	Roster List	Chose any player on your roster
2 Minimum Age	Any	range from 1-150 $\leq$ Maximum Age
3 Maximum Age	Any	range from 1-150 $\geq$ Minimum Age
4 Beginning Date	All	Beginning date $\leq$ Ending date
5 Ending Date	All	Ending date $\geq$ Beginning date
6 Gender	Both, M, F	Male, Female or include all shooters
7 Enter Shooting Locations	All	0 through 16
8 Shooting Distance	All	13, 14, 15, 16, 17, 18, 19, 20, 21+, all

-continued

Headings	Quantifiers	Explanation of Quantifiers
9 Chart Type	Makes/Total Shots/%	Sort based on makes, total shots or shooting %
10 City	All	Choose City
11 County	All	Choose County
12 State	All	Choose State
13 Country	All	Choose Country

[0543] Thus, the criteria or variable entries are provided to the user and the user can select the variables to create any type of chart desired based upon the variables selected. For example, FIG. 52 shows and illustrative selection of variables. In this example, John Drew was selected with the minimum/maximum ages indicated in the FIG. 52, and the other variables or criteria shown and described were selected. In response, the computer, such as computer 202, 204 or website WS created and generated the chart or report 743 which system 200 (FIG. 10) generated in response to the variables or criteria selected. Note in the illustration being described, the user-selected input criteria, shown in FIG. 52, that a shooting distance of twenty feet away from the hoop 14' was selected and a total shots taken at all locations (one or more of the locations identified 0-16 in FIG. 10 and on the interface 40 in FIG. 3). Note that the player chosen in the example was John Drew and in the report, it shows that John Drew of the Sangre school or team was thirteenth in total shots taken from all shooting locations of a distance of 20 feet between the dates Jun. 1, 2009 to Dec. 15, 2010 for males ages 14-25 in the illustration being described.

[0544] Another example is shown in FIGS. 54 and 55. Notice the input information shown in this example of FIG. 54 identifies a team, "Sangre", the position 8 and the distance of fifteen feet. The chart type was identified as "Total Makes" in the drop-down menu screen. The resulting chart or report 744 created by a computer, such as computer 202, 204 or website WS in response to this input information of FIG. 54 is illustrated in FIG. 55. Again, it shows the Sangre team's total makes for all dates for the shooting location or position 8 at a distance of fifteen feet along the vector defined by a line between the gun or ejector 20' and the position 8 shown in FIG. 10. In the illustration being described, the position 8 is at the center of the top of the key or an imaginary line bisecting and radially extending from a center axis of the basketball hoop 14' perpendicular to the backboard 16'.

[0545] Thus, it should be understood that the user can identify and select any combination or permutation of criteria or variables and the computer, such as computer 202, 204 or website WS will generate the corresponding report or chart for display, viewing, saving, printing, exporting, publishing and the like.

[0546] FIG. 56 illustrates a comparison chart or report showing a list of the top twenty rankings for shooters using a gun or ejector 20' on a given day. In the illustration being described, the day was Dec. 15, 2011, and the chart shows the top twenty national rankings. In the illustration being described, the team Upper Sandusky, Ohio generated this chart using the system 200. Note that its player identified at row 2 of the ranking was identified as T. Tedford of Upper Sandusky, Ohio who had a total number of shots taken of 7,644 as illustrated in the chart 750 in FIG. 56.

[0547] FIG. 57A illustrates a chart or report based on total shots made by the player and also illustrates player T. Tedford

being ranked second among all shooters in the nation as illustrated in the report 752 shown in FIG. 57A. Note in the examples being described in FIGS. 56 and 57A-57B, the user of the system 200 identified or selected to show the national rankings for the team Upper Sandusky, Ohio. The top twenty players are indicated in the reports 750 (FIG. 56) and 752 (FIG. 57A), while the rest of the Upper Sandusky, Ohio team players and their associated ranking are identified as 750a (FIG. 56) and 752a (FIG. 57A) of the reports.

[0548] FIGS. 57B and 58 illustrate additional exemplary reports. FIG. 57B illustrates the ranking based upon percentage of shots made, indicating that M. Watson, for example, of the team Upper Sandusky, Ohio shot 99.85% and was second in the national ranking as illustrated in the chart or report 754 in FIG. 57B. Another exemplary report 756 is shown in FIG. 58 wherein a top twenty national rankings for the team Upper Sandusky, Ohio is shown. This illustration in FIG. 58 shows the list of rankings using the gun or ejector 20' for a given age range, minimum age sixteen and maximum age eighteen in the illustrative chart shown in FIG. 58. Note that the player T. Tedford of the Upper Sandusky, Ohio team ranked second with total shots taken of 993,343.

[0549] In still another example shown in FIG. 59, another report 758 is shown as being generated based upon the top twenty rankings for shooter's using the gun or ejector 20' during a particular date range. In the illustration being described, the date range selected by user was Dec. 23, 2011-Dec. 22, 2012. Note that for that year and date range, T. Tedford of the Upper Sandusky, Ohio team was also ranked second with the identified number of shots, total shots taken being the same as in the illustration shown in FIG. 58.

[0550] Advantageously, the system and method, again, permits sorting and comparisons based upon using Doppler measurements and without Doppler measurements and using any number of combinations or permutations of selected criteria or variables. In the illustration being described, several pre-programmed standard reports or chart formats are provided or generated by the website WS. In this regard, the following charts or reports are provided for use by the user:

Type of Chart	Description
Total Makes	provides a chart based on total number of shots made at a location or distance (with or without Doppler measurements)
Total Shots Taken	provides a chart based on total number of shots taken at a location or distance (with or without Doppler measurements)
Percentage of Shots Made	provides a ranking and comparison based upon the shooting accuracy of the player, namely, the total shots made over the number of shots taken (with or with Doppler measurements)

[0551] Again, as mentioned earlier herein, the comparisons can be made on a player basis, on a team basis and such comparisons can be made versus other players on the same or different teams, other geographic regions, such as city, county, state, national, international, age range, date range, gender and the other variables mentioned earlier herein relative to FIGS. 46 and 51.

[0552] The system 200 may provide other formats of charts as well. FIGS. 60-63 illustrate various examples of such charts. In FIG. 60, a chart showing the rankings for a particular shooting area was generated by the user. In the illustration

shown, the chart was generated for a player, namely Kevin Curtis of the team Upper Sandusky, Ohio, and it shows his ranking compared to various geographic areas such as on his local team in the area **760a**, regional compared to his ranking regionally (e.g., in the county in which his team is located) at area **760b** in the chart or report **760**. His statewide rankings, national shooting rankings and international shooting rankings are also shown in the areas **760c**, **760d** and **760e**, respectively. Note that the charts in each area **760a-760e** show the total shots made and the shooting percentage and his relative ranking based upon those criteria for the day (Dec. 15, 2011 in the illustration), week, month, year and even lifetime as shown in the columns indicated in report **760** in FIG. **60**.

[0553] FIG. **61** illustrates still another exemplary report or chart **770**. In this report, the player or team shooting percentages are presented for comparison to the local teams, regional teams, statewide teams, national teams and international teams as illustrated. Similar to the chart **760** in FIG. **60**, the chart **770** shows the rankings for total shots, total shots made, shooting percentages for the day, week, month, year and lifetime for the player when compared to a local shooting team (area **770a** in FIG. **61**), a regional team (such as all teams in a particular geographic county in area **770b** in FIG. **61**), statewide (area **770c**), nationwide within a nation, such as the United States of America (area **770d**) and internationally in area **770e** of chart **770** in FIG. **61**.

[0554] FIGS. **62** and **63** illustrate yet another exemplary embodiment of charts that may be generated using the system **200**. In this embodiment, a chart **772** is shown. In the embodiment shown in FIGS. **62** and **63** one of the variables used for comparison is one or more Doppler measurements. In the illustrative chart **772**, which was created by the user using statistics website WS, the chart **772** shows the player or team versus the national shooting report. Note in top area of the chart **772a**, the chart identifies a particular distance which could also be any distance measured by the Doppler System **800**. Thus, at the distance of fifteen feet, the chart or report **772** was created for the player Kevin Curtis. Note that at a distance of fifteen feet, his statistics or rankings are shown in areas **772b** of the chart **772**. Likewise, in the area **772c** his regional rankings or statistics are shown, and his statewide statistics are shown in the area **772d**. The national rankings or statistics for the player are shown in the area **772e** and the international data or statistics are shown in the area **772f** as shown.

[0555] Thus, in this illustrative chart **772** in FIG. **62**, the player Kevin Curtis' ranking was first on his team for total shots made from a distance of fifteen feet for the date Dec. 15, 2011, the week, the month of December, but he was ranked second for both the year 2011 and over his lifetime in comparison to other players on the team. Similar rankings and statistics are shown in the other areas **772c-772f**.

[0556] Still another exemplary chart or report **774** is shown in FIG. **63**. In this illustrative embodiment, the shooter selected a single shooting location, shooting location **8** in the illustration being described, and the Doppler measured distances of fifteen to nineteen feet. Again, the user selected a player, Kevin Curtis in the illustration, and his rankings are listed in the chart or reports **774**. In this regard, note that his local shooting statistics compared to other shooters on his team is shown in the area **774a**, regional shooting rankings or statistics in the area **774b**, statewide shooting rankings or statistics in the area **774c**, nationwide shooting rankings or statistics in the area **774d** and international shooting rankings

or statistics in the area **774e** of the chart **774**. Again, the preceding charts and reports are illustrative, and it should be understood that other shooting locations (**0-16** in the illustration being described), distances or other criteria could be selected to generate other reports or charts.

[0557] Advantageously, the system and method described herein enable the user to gather, collect and analyze shooting data and use that shooting data to compare a player or a team's shooting efficiency and ranking versus other players or teams on a local, regional, statewide, national or even international basis. Using the information, a coach can focus the player on practicing shooting on different areas and with different techniques to improve the player's efficiency. The generation of these reports will greatly improve a shooter's efficiency based on two primary, but different reasons. First, the actual data can be studied and a user (both coach and shooter) can find areas that need improvement, whether it be more or less shots at that giving location or if the user is struggling on a certain side of the court, a coach may devise a game plan that would keep the user from shooting from those locations. Secondly, a player or coach will be able to see what others are doing and compare his body of work to theirs. This becomes a competition between users and thus more and more shots are taken and tracked since typically users of this machine are competitive. This collection of data can then be reviewed at a later time by users, including the player P, the coaches who advise the player P or other third parties in order to assess and improve the performance of the player P. In this regard, the collection of data can be made available to select other interested parties, such as players and coaches on other teams of a basketball league with which the player is affiliated, for example. Each individual player or a collection of players on a team or at a given school or club can maintain the website WS on which the statistics and data described above are posted. This posting allows a world-wide comparison of the performances of the players among themselves, their coaches, associates, and rivals. The system **200** also permits competitions among players, teams and the like.

[0558] Advantageously, the system and method permit gathering and configuring shooting statistics of the shooter and team across any territory, such as the United States, via the website WS and various graphical user interface showing graphical tables, charts and illustrations (not shown), on the website WS, with the data and statistics being downloadable, printable and/or visible for comparison. For example, the computer **202** (FIG. **10**) may communicate with the remote computer or server **206** or a computer associated with a remote launcher **204** to cause players at remote locations to shoot the same shots. The data and statistics from those shots are collected and stored on, for example, computers **202** and server **206** and may be uploaded and stored on the server **206** associated with the website WS. Players, coaches and other interested parties may then view the data and statistics for comparison by visiting the website WS. For example, Player A from University X may compare his statistics to Player B from University Y. This enables virtual play, practice and comparison among at least one or a plurality of players on the same team or different teams and thereby enables a team to compare their data and statistics to one or more other teams.

[0559] Comparisons can be done in real-time, thereby allowing a plurality of players at remote locations, for example, to directly compete against each other in real-time if desired. For example, a given pass (in terms of speed, direction, and inclination angle) in FIG. **10** is made to Player A,

who catches it and shoots. His performance data is recorded on the gun or ejector 20' or by computer 202 associated with that gun or ejector 20' on storage device 44'. The computer 202 or controller 32' controlling the gun or ejector 20' which launched the pass to Player A informs (e.g., wirelessly, directly or via website WS) the remote launcher 20' in a remote system, such as system 200 in FIG. 10, of the characteristics of that pass. The remote computer 204 then makes an identical pass to Player B using the remote gun or ejector 20', and the two computers 202, 204 and website WS allow an immediate comparison of the performances of the two players on those computers or on the remote website WS. For example, guns at different locations could be online and a prompt (not shown) on each machine allowing a shooter to challenge a remote shooter on another machine. When the challenge is accepted, the challenger programs his Gun and that program automatically programs (via the Internet) the remote Gun. The challenger then starts his gun and the real time challenge begins. The results may be displayed on display 45' (FIG. 10).

#### ADDITIONAL ADVANTAGES OR CONSIDERATIONS

[0560] 1. It is contemplated that the data can be made available on other networks as well. For example, an intra-net can, in effect, be established, either by direct communication lines, or by using the Internet for communication, but by restricting access, as by using passwords. In this case, the data is not made available publicly, but to a limited audience. As a specific example, the data can be held in a remote or local server and made available through a dial-up line or other conventional communication link, such as a wireless link, to specific parties, such as members of a player's P league, members of other teams in any league, across the United State or anywhere around the world. In effect, the server 206 or website WS may deliver a display via a graphical user interface (not shown), an electronic or hard copy reprint of the data, although extensive, on demand to a limited audience.

[0561] 2. In one embodiment, the data and statistics can be presented visually, such as by the scatter diagram 600 (FIG. 42) superimposed over a bird's eye view of a basketball court. The scatter diagram 600 indicates the area at each point where a shot 604 was taken, and indicates the distance, number of shots taken, the percentage of shots which scored and the like percentage which scored as swishers.

[0562] The statistics, data, reports and charts, or a selected subset of them, can be stored and printed for the player P when he finishes a practice session.

[0563] 3. It was stated above that, after a launch of the basketball 12' by gun or ejector 20', the speed of the basketball 12' is computed and when the speed drops to zero, it is concluded that the player P has caught the basketball 12' at that time. However, if the player P is moving when the basketball 12' is caught, the speed may not drop to zero. Therefore, in one embodiment of the invention, the basketball 12' catch is concluded when the speed of the basketball 12' drops below a threshold. That threshold can be based on an average running speed of a player P, under the reasoning that a basketball in flight has a significantly higher speed than that running speed. Then, when a player P catches such a basketball 12', the speed of the basketball 12' will abruptly be constrained to conform to the player's P running speed. Thus, when the flight speed of the basketball 12' changes to the running speed of a player P, a catch may be concluded.

[0564] 4. The speed of the basketball 12' along its flight path running from the gun or ejector 20' to the player P need not be constant. Thus, a more accurate computation of distance will (1) break the flight path into segments, (2) compute a speed S for each segment, (3) assign a time T to each segment, (4) compute a distance for each segment as  $S \times T$ , and (5) compute a total distance as the sum of the distances for all segments.

[0565] 5. In one embodiment of the invention, the actual, precise distance occurring between a player P and the gun or ejector 20' is not necessarily always the most important variable. Rather, the response of the player P at a given location to a given pass is considered a paramount consideration. The player's P location is deduced from measured data. In a precise technical sense, the basketball 12' in FIG. 10 which is launched by the gun or ejector 20' will not maintain a constant speed. Further, the flight path followed by the basketball 12' will usually, but not always, resemble a parabola, but will not be a precise parabola because of the changing speed. Therefore, multiplying the measured speed of the basketball 12' by the time of flight will only give an approximation of the length of the flight path. This length is not the same as the distance from the gun or ejector 20' to the player P, although a good approximation of distance can probably be derived from the measured speed and time. The algorithms presented and described relative to FIGS. 13A-13I enable calculations of such distances.

[0566] Nevertheless, one embodiment of the invention is not necessarily concerned with precise measurement of these parameters. Rather, one embodiment of the invention is concerned with repeatability of the challenge presented to the player P by each pass. That is, the invention knows the release angle,  $\theta$ , at which the basketball 12' is launched, together with the compass direction of the launch. In addition, the invention knows the initial speed of the basketball 12'. These three parameters (ball speed, inclination angle, and compass direction) allow a given launch, or pass, to be repeated accurately. Thus, the same pass can be presented to the same player at different times and to different players at the same or different times and/or at the same or different places. The players' responses to the challenges can be measured, in terms of hold times and accuracy of their shots, recorded and then compared as mentioned earlier.

[0567] In regard to comparisons, because the players' responses are determined as provided herein, the player(s) responses can be compared in a meaningful way. This is despite the fact that the actual distance from the player P to the gun or ejector 20' may not be known with high precision.

[0568] From another perspective, the flight distance of the pass made by the gun or ejector 20' can be considered secondary data. The flight distance is computed, based on measured data, but the more relevant information lies in the detailed characteristics of the pass made by the gun or ejector 20'.

[0569] One goal or use of another embodiment may be to reproduce a given type of pass, for a given player or for comparison between multiple players. This reproduction can be made by repeating the gun's or ejector's 20' performance, in terms of (1) ball speed, (2) entry angle, (3) release direction, and so on. It is not necessary to work backward from the computed travel distance of a given pass in order to reproduce that pass.

[0570] Thus, from this other perspective, the measured information, such as distance of a pass delivered by the gun or ejector 20', is a useful approximation to the player P from the gun or ejector 20'.

[0571] 6. Another consideration is that there are significant differences between the system 200 and prior art ball throwers, such as a baseball or tennis ball throwers. These differences include:

[0572] a) A typical women's basketball weighs about 20 ounces and a men's 22 ounces. Tennis balls weigh about 2 and 2 $\frac{1}{16}$  ounces and a baseball weighs about 5.13 ounces. One form of the invention launches a basketball with a velocity of about 30 feet per second at maximum spring setting. A baseball pitch traveling 100 miles per hour travels roughly 150 feet per second, as does a similar tennis ball. Because the basketball 12' travels at a significantly lower speed, compared to a baseball or tennis ball thrower, for example, from a baseball or tennis ball thrower machine (not shown), the basketball player can make reliable and repeatable catches of a launched basketball 12' in a bare-handed manner. As one specific example, the player can reliably and repeatably catch, bare-handed, the basketball 12' pass every ten seconds for ten minutes. That is not possible with a high speed baseball pitch, for example.

[0573] b) The basketball player catches and holds, at least momentarily, the launched basketball 12', and then makes a shot. That is not intended with baseball pitches and tennis ball guns.

[0574] c) The basketball launcher has associated equipment which calculates the distance of the player from the launcher 20, 20'. That is not done with the other prior art launchers that throw other balls, nor is there a reason to do so.

[0575] d) The basketball player does not use a bat, racket, or other instrument to strike the ball.

[0576] e) The basketball gun or ejector 20, 20' can require the player to move to different pre-programmed locations, to catch the ball. An automated tennis ball gun may require the player to move, but that is not done in baseball pitching, and, again, the player is not catching the ball, shooting and the ball launcher is not monitoring and measuring the distance from where the ball is shot to a hoop 14, 14'.

[0577] f) The basketball gun or ejector 20, 20' does not impose side spin on the ball, in order to cause deviations in the ball's path, as is done in tennis or in a baseball "curve ball."

[0578] 7. Under one embodiment of the invention, a detection of (1) the speed of the launched basketball, (2) the entry angle, and (3) the release angle of the launched pass are all done without human intervention. This is different from having a database of basketball statistics that is kept and used. For example, the database may indicate that, in a given game, player X caught a pass from player Z who was positioned at a certain location, and then player X scored a three-point shot. Again, system 200 stores this information and allows one to re-construct the pass using the gun or ejector 20' in FIG. 10 and without human intervention.

[0579] A similar comment applies to the detection of whether a shot scores a goal.

[0580] 8. In Table V a listing of each component in the circuits shown in the FIGS. 15A-15D is provided. It should be understood that these are merely representative and other values and arrangement of components could be used and the invention is not limited precisely thereto:

TABLE V

Component	Type	Value	Available From
C1, C2, C200, C201, C205, C207, C217	ceramic	.001	Digi-Key Corporation of Thief River Falls, MN
C3, C4, C202, C203, C204, C206	ceramic	.1	Digi-Key Corporation of Thief River Falls, MN
C5, C8, C212, C213, C214, C215, C216	tantalum	1.0u	Digi-Key Corporation of Thief River Falls, MN
C6, C7	ceramic	.047	Digi-Key Corporation of Thief River Falls, MN
C9, C16, C17, C218, C219, C308, C303	tantalum	4.7u	Digi-Key Corporation of Thief River Falls, MN
C301	COG	2.0u	Digi-Key Corporation of Thief River Falls, MN
C302	COG	1.0u	Digi-Key Corporation of Thief River Falls, MN
C304	aluminum	20u	Digi-Key Corporation of Thief River Falls, MN
C305	aluminum	47u	Digi-Key Corporation of Thief River Falls, MN

TABLE V-continued

Component	Type	Value	Available From
C306	200 uF	Cap	Digi-Key Corporation of Thief River Falls, MN
C307, C311	tantalum	10u	Digi-Key Corporation of Thief River Falls, MN
C309	ceramic	330 pf	Digi-Key Corporation of Thief River Falls, MN
C310	ceramic	.22u	Digi-Key Corporation of Thief River Falls, MN
C312	ceramic	.01u	Digi-Key Corporation of Thief River Falls, MN
D1	160-1087	LED-RED	Digi-Key Corporation of Thief River Falls, MN
D4, D2	diode	1N4148	Digi-Key Corporation of Thief River Falls, MN
D3	160-1089	GRN LED	Digi-Key Corporation of Thief River Falls, MN
D5	160-1088	YEL LED	Digi-Key Corporation of Thief River Falls, MN
D205, D206, D207, D208, D209, D210, D211, D212, D300	Schottky	1N5711	Digi-Key Corporation of Thief River Falls, MN
L300, L301	308-1486	47 uH	Digi-Key Corporation of Thief River Falls, MN
Q1	PNP	2N3906	Digi-Key Corporation of Thief River Falls, MN
Q2, Q3, Q4, Q5, Q301	NPN	2N3904	Digi-Key Corporation of Thief River Falls, MN
Q300	Pchan	IRFR5305	Digi-Key Corporation of Thief River Falls, MN
R1	1% metal film	39.2k	Digi-Key Corporation of Thief River Falls, MN
R2	1% metal film	43.2k	Digi-Key Corporation of Thief River Falls, MN
R3	1% metal film	1.0k	Digi-Key Corporation of Thief River Falls, MN
R4, R13, R16, R17, R25, R209, R214	1% metal film	100k	Digi-Key Corporation of Thief River Falls, MN



TABLE V-continued

Component	Type	Value	Available From
R5	1% metal film	750	Digi-Key Corporation of Thief River Falls, MN
R6	1% metal film	2.49k	Digi-Key Corporation of Thief River Falls, MN
R7, R302	1% metal film	2k	Digi-Key Corporation of Thief River Falls, MN
R8, R9, R10, R20, R22, R26, R204, R205, R207, R212, R303,	1% metal film	10K	Digi-Key Corporation of Thief River Falls, MN
R11	1% metal film	33k	Digi-Key Corporation of Thief River Falls, MN
R12, R14	1% metal film	8.45k	Digi-Key Corporation of Thief River Falls, MN
R15	1% metal film	1 meg	Digi-Key Corporation of Thief River Falls, MN
R18, R19	1% metal film	249	Digi-Key Corporation of Thief River Falls, MN
R21	1% metal film	3.01k	Digi-Key Corporation of Thief River Falls, MN
R23, R28, R31, R317	1% metal film	4.99k	Digi-Key Corporation of Thief River Falls, MN
R27, R203, R208, R213, R301, R305	1% metal film	1k	Digi-Key Corporation of Thief River Falls, MN
R29, R32	1% metal film	15k	Digi-Key Corporation of Thief River Falls, MN
R202	1% metal film	6.65k	Digi-Key Corporation of Thief River Falls, MN
R206	1% metal film	4.9k	Digi-Key Corporation of Thief River Falls, MN
R210, R211	1% metal film	374k	Digi-Key Corporation of Thief River Falls, MN
R216, R215	1% metal film	1.82k	Digi-Key Corporation of Thief River Falls, MN
R304	1% metal film	9.09k	Digi-Key Corporation of Thief River Falls, MN
R310	1% metal film	30.1k	Digi-Key Corporation of Thief River Falls, MN

TABLE V-continued

Component	Type	Value	Available From
OSC1	CTX306CT	20 MHz	Digi-Key Corporation of Thief River Falls, MN
U1	microprocessor	18F2520	Digi-Key Corporation of Thief River Falls, MN
U4, U201	opamp	TL074	Digi-Key Corporation of Thief River Falls, MN
U5	digital pot	MCP4013	Digi-Key Corporation of Thief River Falls, MN
U6	Gunn	MAC7801	MAcom available from Richardson RFPD, Inc. of LaFox, IL
U8	regulator	MC7805D2	Digi-Key Corporation of Thief River Falls, MN
U200	reference	LTC1634smt	Digi-Key Corporation of Thief River Falls, MN
U204	serial driver	MAX232A	Digi-Key Corporation of Thief River Falls, MN
U300	neg voltage	LT1931AES5	Digi-Key Corporation of Thief River Falls, MN

**[0581]** While the system, procedure and methods constitute preferred or illustrative embodiments, it is to be understood that the invention is not limited to these precise methods, and that changes may be made in either without departing from the scope of the invention, which is defined in the appended claims.

What is claimed is:

1. An apparatus for assisting basketball practice, comprising:

- a) a launcher for launching a basketball into a flight path;
- b) a measuring system which
  - i) measures speed of said basketball after either a player shoots said basketball or said launcher launches said basketball;
  - ii) ascertains elapsed time of said flight path; and
  - iii) using a formula which incorporates the speed and the elapsed time, computes a distance from which said player shot said basketball.

2. The apparatus according to claim 1, in which said measuring system measures said speed based on Doppler shift of reflected radiation which is reflected from said launched basketball.

3. The apparatus according to claim 1, in which said measuring system

- i) ascertains a time T1 when said flight path begins;
- ii) uses a radar gun to ascertain speed of said basketball;
- iii) ascertains a time T2 when said measured speed of said basketball falls below a limit; and
- iv) computes the elapsed time based on T1 and T2.

4. The apparatus according to claim 1, in which said speed is measured when said basketball exits said launcher.

5. An apparatus for assisting basketball practice, comprising:

- a) a launcher for launching a basketball along a flight path; and
- b) a radar gun which detects speed of said basketball when launched, and continues to measure speed along said flight path.

6. The apparatus according to claim 5, and further comprising:

- c) a system which computes elapsed time of said flight path.

7. The apparatus according to claim 6, and further comprising:

- d) a system which computes a distance based on the elapsed time and the detected speed.

8. The apparatus according to claim 7, and further comprising:

- e) a basketball goal which includes a backboard, a rim attached to said backboard, and a net attached to said rim;
- f) a system for detecting whether a player scores a goal; and
- g) a data system which records
  - i) conditions of said flight path and
  - ii) whether said basketball on said flight path scored a goal.

9. The apparatus according to claim 8, in which said apparatus launches a succession of basketballs along a succession of flight paths, and said data system records

- i) conditions of each flight path; and
- ii) whether said basketball launched on each flight path was subsequently shot by said player successfully through said rim.

10. The apparatus according to claim 8, in which said data system records in a data file (1) conditions for each of multiple flight paths presented to said player and (2) whether said player scored a goal with each basketball of each respective flight path.

11. The apparatus according to claim 10, in which said data system makes said data file available to remote parties.

12. An apparatus for assisting in basketball practice of a player, comprising:

- a) a launcher which launches a basketball pass at a time T1;
- b) a detector which measures speed S of said basketball upon launch; and
- c) a control which
  - i) knows time T1,
  - ii) identifies a time T2, when said speed S measured by said detector falls below a first threshold,
  - iii) detects a time T3, occurring after time T2, when speed measured by said detector rises above a second threshold,
  - iv) learns that said basketball scored a goal at time T4 after a shot by said player,
  - v) computes at least one of the following:
    - a pass flight time PFT, based on the equation  $PFT = T2 - T1$ ,
    - a distance D based on the equation  $D = PFT \times S$ ,
    - a hold time H based on the equation  $H = T3 - T2$ ,
    - a shot flight time SFT based on the equation  $SFT = T4 - T3$ , or
    - an arc of a shot.

13. The apparatus according to claim 12, wherein said detector is coupled to said launcher and moved in response to movement of said launcher.

14. A system, comprising:

- a) a launcher for launching a basketball into a trajectory selected from a collection of possible trajectories;
- b) a detection system which
  - i) detects when a player catches said basketball and terminates said trajectory;
  - ii) computes a flight distance of said trajectory;
  - iii) detects whether a shot of said basketball made by said player scores a goal; and
  - iv) records said flight distance or location from which said basketball was shot, computed and whether said goal was scored.

15. The system according to claim 14, wherein said detection system records said location at which said player shot said basketball and a percentage of shots made.

16. A system for practicing or improving shooting basketballs, comprising:

- at least one launcher, which is programmable to make a series of passes to a player;
- a measurement system which:
  - i) generates data associated with a player's shooting, said data including at least one of the following measurements or calculations: a distance from a basketball hoop from which said player shot a basketball, a release time, a release arc of said basketball when said player shoots it or an entry arc of said basketball entering said basketball hoop;
  - ii) determines or records a total number of shots said player took and whether said player made the shots; and

- iii) stores the shots made by said player at each location.

17. The system as recited in claim 16, wherein said data includes said distance and said measurement system further comprises:

- a measuring device that measures a distance from said basketball hoop that said player took a shot, with said distance being stored on said at least one launcher.

18. The system as recited in claim 17 wherein said measurement system is adapted to measure distance data for a plurality of distances extending along a plurality of vectors that project from said at least one launcher.

19. The system as recited in claim 18 wherein said plurality of vectors extend over a plurality of shooting locations that generally correspond to a plurality of selected shooting locations that were selected by a user.

20. The system as recited in claim 19 where said plurality of selected shooting locations generally correspond to a plurality of buttons, respectively, arranged in an arc on a user interface associated with said at least one launcher.

21. The system as recited in claim 17 wherein said measuring device is a Doppler system having a plurality of amplifiers for amplifying a signal relating to movement of said basketball as it travels away from said at least one launcher.

22. The system as recited in claim 16 wherein said system further comprises:

- a tracking system for tracking said player's shots and for generating reports showing said player's shooting success at each distance from which a shot was taken by said player.

23. The system as recited in claim 22 wherein said tracking system is located on a server associated with a website so that it is accessible by an interested user, such as at least one of a coach, said player or other interested users.

24. The system as recited in claim 22 wherein said tracking system is adapted to receive data associated with a plurality of players who shot basketballs using said at least one launcher, wherein said data was initially captured by said at least one launcher and uploaded to said tracking system.

25. The system as recited in claim 22 wherein said system comprises a plurality of launchers, said tracking system further comprising:

- said tracking system being adapted to receive data associated with a plurality of players who shot basketballs using said plurality of launchers, wherein said data was initially captured by said plurality of launchers and uploaded to said tracking system;
- said tracking system comprising a chart/report generator for generating charts or reports showing said data.

26. The system as recited in claim 25 wherein said plurality of launchers are located at different locations.

27. The system as recited in claim 25 wherein said plurality of launchers are used at the same time.

28. The system as recited in claim 25 wherein said plurality of launchers are used at different times.

29. The system as recited in claim 25 wherein said chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from at least one of said plurality of players.

30. The system as recited in claim 29 wherein said charts or reports further comprise a ranking and a listing of at least one of said measurements or calculations.

31. The system as recited in claim 29 wherein said charts or reports comprises a shooting measurement or calculation for a plurality of distances which are shown or listed on said charts or reports.

32. The system as recited in claim 31 wherein said shooting measurement or calculation is a number of makes or percentage calculation based upon or using the number of made shots.

33. The system as recited in claim 29 wherein said charts or reports further comprise a comparative ranking and a listing of at least one of said measurements or calculations for a plurality of players.

34. The system as recited in claim 33 wherein said plurality of players are from the same team and use the same launcher.

35. The system as recited in claim 33 wherein said plurality of players are from different teams and use the same launcher.

36. The system as recited in claim 33 wherein said plurality of players are from a plurality of different teams, said plurality of different teams using a plurality of launchers, respectively, that are located at a plurality of different locations.

37. The systems as recited in claim 36 wherein said plurality of different locations are located in different countries.

38. The systems as recited in claim 36 wherein said plurality of different locations are located in different states or counties within the United States.

39. The system as recited in claim 22 wherein said tracking system further comprises:

a tracking website having an associated server for storing shooting data and statistics for said player;

a plurality of graphical user interfaces that are presented to a user after logging onto said tracking website, said tracking website being adapted to track and store data and statistics regarding a plurality of players' shooting performance over a predetermined period of time.

40. The system as recited in claim 39 wherein said predetermined period of time is a lifetime of each of said plurality of players.

41. The system as recited in claim 39 wherein said tracking system and graphical user interfaces are further adapted to permit said user to create and store a roster or team of players and assign them to said at least one launcher.

42. The system as recited in claim 41 wherein said at least one launcher is adapted to receive said roster or team of players to enable said at least one launcher to capture and store shooting statistics and data for each player.

43. The system as recited in claim 42 wherein said tracking system is further adapted to permit said shooting data and statistics to be uploaded from said at least one launcher to said tracking website.

44. The system as recited in claim 39 wherein said tracking website comprises a chart/report generator for generating charts or reports showing said shooting statistics and data.

45. The system as recited in claim 44 wherein said chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from a plurality of players that use said at least one launcher.

46. The system as recited in claim 45 wherein said charts or reports further comprise a ranking and a listing of at least one of said measurements or calculations.

47. The system as recited in claim 44 wherein at least one of said reports comprises a mapping report or scatter diagram showing a shooting accuracy for a plurality of distances along a vector extending from said at least one launcher.

48. The system as recited in claim 44 wherein said chart/report generator generates charts or reports that includes at least one of a comparison of shooting statistics or data from a plurality of players that use different launchers.

49. An apparatus which enables a player to practice basketball, comprising:

a) a display or interface which

i) indicates several different types of available basketball passes;

ii) accepts input from a user which selects a sequence of said basketball passes;

b) a basketball launcher which launches said sequence of said available basketball passes for said player to catch;

c) a detector which estimates, for some or all of said available basketball passes, a distance between (i) point of catching each pass by said player and (ii) a reference location;

d) a transmitter or system for transmitting or uploading data indicating said sequence of said available basketball passes to a remote location, which enables a second launcher to launch said sequence of said basketball passes.

50. The apparatus according to claim 49, in which said reference location of paragraph (c) is a basketball goal.

51. The apparatus according to claim 49, in which said detector estimates said distance by measuring velocity  $V$  and flight time  $T$  of the basketball, and multiplying velocity  $V$  times flight time  $T$ .

52. The apparatus according to claim 49, in which said detector estimates said distance by measuring (i) horizontal velocity component  $V_h$  of a basketball shot by said player and (ii) time of flight  $T$  of said basketball, and then multiplying velocity  $V$  times flight time  $T$ .

53. An apparatus which enables a player to practice basketball, comprising:

a) a launcher which launches a basketball for said player to catch; and

b) a detector which makes an estimate at least one of:

i) distance of said player from said launcher;

ii) a release time;

iii) an arc of a shot;

iv) height of a shot made by said player after catching said basketball;

v) release angle by said player; or

vi) entry angle of said basketball into a goal.

54. The apparatus according to claim 53, in which said detector uses only (i) detected speeds of said basketball, (ii) time of flight of said shot and (iii) time of flight of a launched basketball pass, to compute the distance, height, release angle, and entry angle of paragraph (b).

55. The apparatus according to claim 53, in which a detected speed includes (i) speed of said basketball when leaving said launcher.

56. The apparatus according to claim 53, in which a time of flight of said basketball is that between (i) time of launch of said basketball and (ii) time at which detected speed of said basketball reaches a lower limit.

57. The apparatus according to claim 56, in which said lower limit is zero.

58. The apparatus according to claim 53, wherein said detector makes an estimate or measurement of a plurality of:

i) said distance of said player from said launcher;

ii) said release time;

iii) said arc of said shot;

iv) said height of a shot made by said player after catching said basketball;

v) said release angle by said player; or

vi) said entry angle of said basketball into said goal.

59. A system for players to practice basketball, comprising:

a) a first launching system which includes

i) a first launcher which launches a predetermined sequence of basketball passes for a first player to catch;

- ii) a first detector which, for each pass, produces performance data which includes at least one of:
  - A) distance of said first player from said first launcher;
  - B) height of a shot made by said first player after catching a basketball;
  - C) release angle, release time, or arc of a shot by said first player; and
  - D) entry angle of said basketball into a goal;
  - E) hold or release time; or
  - F) shot arc;
- iii) a first communication system which posts on a web site (1) a description of said predetermined sequence of basketball passes (2) selected of said performance data of said first player;
- b) a second launching system, located remote from said first launching system, which obtains a description of said predetermined sequence of basketball passes, either from said first launching system or said web site; and includes
  - i) a second launcher which launches said predetermined sequence of basketball passes for a second player to catch;
  - ii) a second detector which, for each pass, produces performance data which includes at least one of:
    - A) distance of said second player from said second launcher;
    - B) height of a shot made by said second player after catching said basketball;
    - C) release angle, release time or arc of a shot by said second player; and
    - D) entry angle of said basketball into a goal;
    - E) hold or release time; or
    - F) shot arc;
  - iii) a second communication system which posts on said web site selected of said performance data for each pass to said second player.
- 60. The system according to claim 59, in which said first communication system posts, on said web site, a plurality of:
  - A) distance of said first player from said first launcher;
  - B) height of a shot made by said first player after catching said basketball;
  - C) release angle, release time or arc of a shot by said first player; and
  - D) entry angle of said basketball into a goal for every pass to said first player.
- 61. The system according to claim 59, in which said second communication system posts, on said web site, a plurality of:
  - A) distance of said second player from said second launcher;
  - B) height of a shot made by said second player after catching said basketball;
  - C) release angle, release time or arc of a shot by said second player;
  - D) entry angle of said basketball into a goal for every pass to said second player;
  - E) hold or release time; or
  - F) shot arc;

62. The system according to claim 59, in which the performance data for said first and second players are presented at said web site in a manner which allows comparison between said first and second players.

63. The system according to claim 59, wherein said system creates reports from criteria selected by a user.

64. The system according to claim 63, wherein said reports comprise relative compromises and rankings for a plurality of either players or teams.

65. The system according to claim 64, wherein said reports are for players on different teams.

66. A basketball tracking system comprising:

a launcher for launching a basketball to a plurality of locations on a basketball floor;

a distance sensor for measuring a distance from which said basketball is shot from at least one of said plurality of locations;

at least one sensor for sensing at least one of whether a shot was made or missed;

a database for storing statistics at each distance for each shot taken.

67. The basketball tracking system as recited in claim 66 wherein said system further comprises:

an interface for use in causing said launcher to throw said basketballs along a plurality of different vectors.

68. The basketball tracking system as recited in claim 66 wherein said distance sensor senses where a player caught said basketball and determines at least one of a location or distance from a rim where said player released said basketball toward said rim.

69. The basketball tracking system as recited in claim 68 wherein said distance sensor is adapted to determine a release angle or arc at which said player shot said basketball.

70. The basketball tracking system as recited in claim 66 wherein said database receives said distance measurements and said statistics at each distance, said statistics comprising statistics of made shots at said distance.

71. The basketball tracking system as recited in claim 67 wherein said plurality of different vectors is sixteen or less.

72. The basketball tracking system as recited in claim 67 wherein said interface comprises said plurality of different vectors laid out on said interface for selection by a user.

73. The basketball tracking system as recited in claim 66 wherein said distance sensor comprises a Doppler or radar measurement system.

74. The basketball tracking system as recited in claim 66 wherein said tracking system further comprises a plurality of graphical user interfaces for enabling a user to view said distance measurements and said statistics in said database.

75. The basketball tracking system as recited in claim 74 wherein said plurality of graphical user interfaces enables said user to at least one of edit, view, print, copy and create reports using said distance measurements and said statistics stored in said database.

76. The basketball tracking system as recited in claim 74 wherein said system further comprises a report generator for generating at least one report in response to a selection of a plurality of criteria selected by said user using at least one of said plurality of graphical user interfaces.

\* \* \* \* \*