

(10) **Patent No.:** US 8,368,648 B2
(45) **Date of Patent:** Feb. 5, 2013

- | | | | |
|-----------|---|---------|---------|
| 2,902,023 | A | 9/1959 | Waller |
| 3,135,512 | A | 6/1964 | Taylor |
| 3,395,920 | A | 8/1968 | Moe |
| 3,454,920 | A | 7/1969 | Mehr |
| 3,456,134 | A | 7/1969 | Ko |
| 3,474,241 | A | 10/1969 | Kuipers |
| D220,268 | S | 3/1971 | Kliwer |

- (Continued)

- FOREIGN PATENT DOCUMENTS

- | | | |
|----|---------|--------|
| CN | 1032246 | 4/1989 |
| CN | 1338961 | 3/2002 |

- (Continued)

- ## OTHER PUBLICATIONS

- Richard Borovoy et al., "Groupwear: Nametags That Tell About Relationships," *Chi* 98, Apr. 1998, pp. 329-330.

- (Continued)

Primary Examiner — Abbas Abdulsalam

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear LLP

- (57) **ABSTRACT**

(Continued)

- circuitry and/or command circuitry for generating control signals and/or an effects generator and associated control circuitry to enable the input device to selectively generate at least one visual, aural or tactile effect comprising sound, lighting or vibration. The input device can include a wireless transceiver for providing two-way wireless communication with the wireless-compatible game console. An optional display screen displays short text messages received through wireless communications with the wireless-compatible game console.


- ## 45 Claims, 44 Drawing Sheets

- See application file for complete search history.

- (56) **References Cited**

U.S. PATENT DOCUMENTS

1,661,058	A	2/1928	Theremin
1,789,680	A	1/1931	Gwinnett
2,752,725	A	7/1956	Unsworth



Related U.S. Application Data

Oct. 30, 2008, now Pat. No. 8,089,458, which is a division of application No. 10/954,025, filed on Sep. 29, 2004, now Pat. No. 7,445,550, which is a continuation-in-part of application No. 10/397,054, filed on Mar. 25, 2003, now Pat. No. 7,500,917, which is a continuation-in-part of application No. 09/792,282, filed on Feb. 22, 2001, now Pat. No. 6,761,637.

- (60) Provisional application No. 60/184,128, filed on Feb. 22, 2000.

References Cited

(56)

U.S. PATENT DOCUMENTS

3,660,648 A	5/1972	Kuipers	4,862,165 A	8/1989	Gart
3,707,055 A	12/1972	Pearce	4,891,032 A	1/1990	Davis
3,795,805 A	3/1974	Swanberg et al.	4,904,222 A	2/1990	Gastgeb et al.
3,949,364 A	4/1976	Clark et al.	4,910,677 A	3/1990	Remedio et al.
3,973,257 A	8/1976	Rowe	4,914,598 A	4/1990	Krogmann
3,978,481 A	8/1976	Angwin et al.	4,918,293 A	4/1990	McGeorge
3,997,156 A	12/1976	Barlow et al.	4,924,358 A	5/1990	VonHeck
4,009,619 A	3/1977	Snymann	4,957,291 A	9/1990	Miffitt
4,038,876 A	8/1977	Morris	4,961,369 A	10/1990	McGill
4,055,341 A	10/1977	Martinez	4,964,837 A	10/1990	Collier
4,063,111 A	12/1977	Dobler et al.	4,967,321 A	10/1990	Cimock
4,166,406 A	9/1979	Maughmer	4,969,647 A	11/1990	Mical et al.
4,171,737 A	10/1979	McLaughlin	4,980,519 A	12/1990	Mathews
4,205,785 A	6/1980	Stanley	4,988,981 A	1/1991	Zimmerman et al.
4,231,077 A	10/1980	Joyce et al.	4,994,795 A	2/1991	MacKenzie
4,240,638 A	12/1980	Morrison et al.	5,011,161 A	4/1991	Galphin
4,282,681 A	8/1981	McCaslin	5,036,442 A	7/1991	Brown
4,287,765 A	9/1981	Kreft	5,045,843 A	9/1991	Hansen
4,296,929 A	10/1981	Meyer et al.	5,048,831 A	9/1991	Sides
4,303,978 A	12/1981	Shaw	D320,624 S	10/1991	Taylor
4,318,245 A	3/1982	Stowell et al.	5,058,480 A	10/1991	Suzuki et al.
4,321,678 A	3/1982	Krogmann	5,059,958 A	10/1991	Jacobs et al.
4,325,199 A	4/1982	McEdwards	5,062,696 A	11/1991	Oshima
4,337,948 A	7/1982	Breslow	5,068,645 A	11/1991	Drumm
4,342,985 A	8/1982	Desjardins	D322,242 S	12/1991	Cordell
4,402,250 A	9/1983	Baasch	5,076,584 A	12/1991	Openiano
4,412,205 A	10/1983	Von Kemenczky	D325,225 S	4/1992	Adhida
4,425,488 A	1/1984	Moskin	5,114,155 A	5/1992	Tillery et al.
4,443,866 A	4/1984	Burgiss	5,114,344 A	5/1992	Fumagalli et al.
4,450,325 A	5/1984	Luque	5,124,938 A	6/1992	Algrain
4,503,299 A	3/1985	Henrard	5,127,657 A	7/1992	Ikezawa et al.
4,514,600 A	4/1985	Lentz	5,128,671 A	7/1992	Thomas, Jr.
4,514,798 A	4/1985	Lesche	D328,463 S	8/1992	King et al.
4,540,176 A	9/1985	Baer	5,136,222 A	8/1992	Yamamoto
4,546,551 A	10/1985	Franks	5,138,154 A	8/1992	Hotelling
4,558,604 A	12/1985	Auer	5,145,446 A	9/1992	Kuo
4,561,299 A	12/1985	Orlando	D331,058 S	11/1992	Morales
4,575,621 A	3/1986	Dreifus	5,166,502 A	11/1992	Rendleman
4,578,674 A	3/1986	Baker et al.	5,170,002 A	12/1992	Suzuki et al.
4,595,369 A	6/1986	Downs	5,175,481 A	12/1992	Kanno
4,623,887 A	11/1986	Welles	5,177,311 A	1/1993	Suzuki et al.
4,623,930 A	11/1986	Oshima	5,178,477 A	1/1993	Gambaro
4,627,620 A	12/1986	Yang	5,181,181 A	1/1993	Glynn
4,672,374 A	6/1987	Desjardins	5,184,830 A	2/1993	Okada et al.
4,678,450 A	7/1987	Scolari et al.	5,192,082 A	3/1993	Inoue et al.
4,695,058 A	9/1987	Carter, III et al.	5,192,823 A	3/1993	Suzuki et al.
4,695,953 A	9/1987	Blair et al.	5,194,006 A	3/1993	Zaenglein, Jr.
4,699,379 A	10/1987	Chateau et al.	5,194,048 A	3/1993	Briggs
4,739,128 A	4/1988	Grisham	5,202,844 A	4/1993	Kamio
4,761,540 A	8/1988	McGeorge	5,207,426 A	5/1993	Inoue et al.
4,776,253 A	10/1988	Downes	5,212,368 A	5/1993	Hara
4,787,051 A	11/1988	Olson	5,213,327 A	5/1993	Kitaue
4,816,810 A	3/1989	Moore	5,223,698 A	6/1993	Kapur
4,817,950 A	4/1989	Goo	5,231,568 A	7/1993	Cohen et al.
4,819,182 A	4/1989	King et al.	D338,242 S	8/1993	Cordell
4,839,838 A	6/1989	LaBiche et al.	5,232,223 A	8/1993	Dornbusch
4,846,568 A	7/1989	Usui	5,236,200 A	8/1993	McGregor et al.
4,849,655 A	7/1989	Bennett	5,247,651 A	9/1993	Clarisse
4,851,685 A	7/1989	Dubgen	D340,042 S	10/1993	Copper et al.
4,858,390 A	8/1989	Kenig	5,259,626 A	11/1993	Ho
4,858,930 A	8/1989	Sato	5,262,777 A	11/1993	Low et al.
			D342,256 S	12/1993	Payne et al.
			5,277,645 A	1/1994	Kelley et al.
			5,279,513 A	1/1994	Connelly
			5,280,744 A	1/1994	DeCarlo
			D345,164 S	3/1994	Grae
			5,290,964 A	3/1994	Hiyoshi et al.
			5,292,124 A	3/1994	Carpenter
			5,292,254 A	3/1994	Miller et al.
			5,296,871 A	3/1994	Paley
			5,299,967 A	4/1994	Gilbert
			5,307,325 A	4/1994	Scheiber
			5,310,192 A	5/1994	Miyake
			5,317,394 A	5/1994	Hale
			5,319,548 A	6/1994	Germain
			5,320,358 A	6/1994	Jones
			5,320,362 A	6/1994	Bear et al.
			5,329,276 A	7/1994	Hirabayashi
			5,332,322 A	7/1994	Gambaro

US 8,368,648 B2

Page 3

5,339,095 A	8/1994	Redford	5,605,505 A	2/1997	Han
D350,736 S	9/1994	Takahashi et al.	5,606,343 A	2/1997	Tsuboyama
D350,782 S	9/1994	Barr	5,611,731 A	3/1997	Bouton et al.
D351,430 S	10/1994	Barr	5,613,913 A	3/1997	Ikematsu et al.
5,354,057 A	10/1994	Pruitt et al.	5,615,132 A	3/1997	Horton
5,356,343 A	10/1994	Lovetere	5,621,459 A	4/1997	Ueda
5,357,267 A	10/1994	Inoue	5,623,581 A	4/1997	Attenberg
5,359,321 A	10/1994	Ribic	5,624,117 A	4/1997	Ohkubo et al.
5,359,348 A	10/1994	Pilcher et al.	5,627,565 A	5/1997	Morishita et al.
5,363,120 A	11/1994	Drumm	D379,832 S	6/1997	Ashida
5,365,214 A	11/1994	Angott et al.	5,640,152 A	6/1997	Copper
5,366,229 A	11/1994	Suzuki	5,641,288 A	6/1997	Zzenglein, Jr.
5,369,580 A	11/1994	Monji	5,642,931 A	7/1997	Gappelberg
5,369,889 A	12/1994	Callaghan	5,643,087 A	7/1997	Marcus et al.
5,372,365 A	12/1994	McTeigue et al.	5,645,077 A	7/1997	Foxlin
5,373,857 A	12/1994	Travers et al.	5,645,277 A	7/1997	Cheng
5,378,197 A	1/1995	Briggs	5,647,796 A	7/1997	Cohen
5,382,026 A	1/1995	Harvard et al.	5,649,867 A	7/1997	Briggs
5,393,074 A	2/1995	Bear et al.	5,651,049 A	7/1997	Easterling et al.
5,396,227 A	3/1995	Carroll et al.	5,655,053 A	8/1997	Renie
5,396,265 A	3/1995	Ulrich et al.	5,662,332 A	9/1997	Garfield
5,403,238 A	4/1995	Baxter et al.	5,662,525 A	9/1997	Briggs
5,405,294 A	4/1995	Briggs	5,666,138 A	9/1997	Culver
5,411,269 A	5/1995	Thomas	5,667,217 A	9/1997	Kelly et al.
5,421,590 A	6/1995	Robbins	5,667,220 A	9/1997	Cheng
5,422,956 A	6/1995	Wheaton	5,670,845 A	9/1997	Grant
5,429,361 A	7/1995	Raven et al.	5,670,988 A	9/1997	Tickle
5,430,435 A	7/1995	Hoch	5,672,090 A	9/1997	Liu
5,432,864 A	7/1995	Lu et al.	5,674,128 A	10/1997	Holch et al.
5,435,561 A	7/1995	Conley	5,676,450 A	10/1997	Sink et al.
5,435,569 A	7/1995	Zilliox	5,676,673 A	10/1997	Ferre et al.
D360,903 S	8/1995	Barr et al.	5,679,004 A	10/1997	McGowan et al.
5,440,326 A	8/1995	Quinn	5,682,181 A	10/1997	Nguyen et al.
5,443,261 A	8/1995	Lee et al.	5,685,776 A	11/1997	Stambolic et al.
5,453,053 A	9/1995	Danta et al.	5,694,340 A	12/1997	Kim
5,453,758 A	9/1995	Sato	5,698,784 A	12/1997	Hotelling et al.
D362,870 S	10/1995	Oikawa	5,701,131 A	12/1997	Kuga
5,459,489 A	10/1995	Redford	5,702,305 A	12/1997	Norman et al.
5,469,194 A	11/1995	Clark et al.	5,702,323 A	12/1997	Poulton
5,481,957 A	1/1996	Paley	5,703,623 A	12/1997	Hall et al.
5,482,510 A	1/1996	Ishii et al.	5,716,216 A	2/1998	O'Loughlin et al.
5,484,355 A	1/1996	King	5,716,281 A	2/1998	Dote
5,485,171 A	1/1996	Copper et al.	5,724,106 A	3/1998	Autry et al.
5,488,362 A	1/1996	Ullman et al.	5,726,675 A	3/1998	Inoue
5,490,058 A	2/1996	Yamasaki	5,734,371 A	3/1998	Kaplan
5,498,002 A	3/1996	Gechter	5,734,373 A	3/1998	Rosenberg
5,502,486 A	3/1996	Ueda	5,734,807 A	3/1998	Sumi
5,506,605 A	4/1996	Paley	D393,884 S	4/1998	Hayami
5,509,806 A	4/1996	Ellsworth	5,736,970 A	4/1998	Bozeman
5,516,105 A	5/1996	Eisenbrey et al.	5,739,811 A	4/1998	Rosenberg et al.
5,517,183 A	5/1996	Bozeman	5,741,182 A	4/1998	Lipps et al.
5,523,800 A	6/1996	Dudek	5,741,189 A	4/1998	Briggs
5,524,637 A	6/1996	Erickson	5,742,331 A	4/1998	Uomori
5,528,265 A	6/1996	Harrison	5,745,226 A	4/1998	Gigioli
5,531,443 A	7/1996	Cruz	D394,264 S	5/1998	Sakamoto et al.
5,533,933 A	7/1996	Garnjost et al.	5,746,602 A	5/1998	Kikinis
5,541,860 A	7/1996	Takei et al.	5,751,273 A	5/1998	Cohen
5,550,721 A	8/1996	Rapisarda	5,752,880 A	5/1998	Gabai et al.
5,551,701 A	9/1996	Bouton et al.	5,752,882 A	5/1998	Acres et al.
5,554,033 A	9/1996	Bizzi et al.	5,757,305 A	5/1998	Xydis
5,554,980 A	9/1996	Hashimoto et al.	5,757,354 A	5/1998	Kawamura
5,561,543 A	10/1996	Ogawa	5,757,360 A	5/1998	Nitta et al.
5,563,628 A	10/1996	Stroop	D395,464 S	6/1998	Shiibashi et al.
5,569,085 A	10/1996	Igarashi et al.	5,764,224 A	6/1998	Lilja et al.
D375,326 S	11/1996	Yokoi et al.	5,769,719 A	6/1998	Hsu
5,573,011 A	11/1996	Felsing	5,770,533 A	6/1998	Franchi
5,574,479 A	11/1996	Odell	5,771,038 A	6/1998	Wang
5,579,025 A	11/1996	Itoh	5,772,508 A	6/1998	Sugita et al.
D376,826 S	12/1996	Ashida	D396,468 S	7/1998	Schindler et al.
5,580,319 A	12/1996	Hamilton	5,775,998 A	7/1998	Ikematsu et al.
5,581,484 A	12/1996	Prince	5,785,317 A	7/1998	Sasaki
5,585,584 A	12/1996	Usa	5,785,592 A	7/1998	Jacobsen
5,586,767 A	12/1996	Bohland	5,786,626 A	7/1998	Brady et al.
5,587,558 A	12/1996	Matsushima	D397,162 S	8/1998	Yokoi et al.
5,587,740 A	12/1996	Brennan	5,791,648 A	8/1998	Hohl
5,594,465 A	1/1997	Poulachon	5,794,081 A	8/1998	Itoh
5,598,187 A	1/1997	Ide et al.	5,796,354 A	8/1998	Cartabiano et al.
5,602,569 A	2/1997	Kato	5,803,740 A	9/1998	Gesink et al.
5,603,658 A	2/1997	Cohen	5,803,840 A	9/1998	Young

5,806,849 A	9/1998	Rutkowski	5,991,085 A	11/1999	Rallison et al.
5,807,284 A	9/1998	Foxlin	5,996,033 A	11/1999	Chiu-Hao
5,810,666 A	9/1998	Mero et al.	5,999,168 A	12/1999	Rosenberg
5,811,896 A	9/1998	Grad	6,001,014 A	12/1999	Ogata
5,819,206 A	10/1998	Horton et al.	6,001,015 A	12/1999	Nishiumi et al.
5,820,462 A	10/1998	Yokoi et al.	6,002,394 A	12/1999	Schein
5,820,471 A	10/1998	Briggs	6,009,458 A	12/1999	Hawkins et al.
5,820,472 A	10/1998	Briggs	D419,199 S	1/2000	Cordell et al.
5,822,713 A	10/1998	Profeta	D419,200 S	1/2000	Ashida
5,825,298 A	10/1998	Walter	6,010,406 A	1/2000	Kajikawa et al.
5,825,350 A	10/1998	Case, Jr. et al.	6,011,526 A	1/2000	Toyoshima et al.
D400,885 S	11/1998	Goto	6,012,980 A	1/2000	Yoshida et al.
5,830,065 A	11/1998	Sitrick	6,012,984 A	1/2000	Roseman
5,831,553 A	11/1998	Lenssen et al.	6,013,007 A	1/2000	Root et al.
5,833,549 A	11/1998	Zur et al.	6,016,144 A	1/2000	Blonstein
5,835,077 A	11/1998	Dao et al.	6,019,680 A	2/2000	Cheng
5,835,156 A	11/1998	Blonstein et al.	6,020,876 A	2/2000	Rosenberg
5,835,576 A	11/1998	Katz	6,024,647 A	2/2000	Bennett et al.
5,836,817 A	11/1998	Acres et al.	6,024,675 A	2/2000	Kashiwaguchi
5,838,138 A	11/1998	Henty	6,025,830 A	2/2000	Cohen
5,841,409 A	11/1998	Ishibashi et al.	6,037,882 A	3/2000	Levy
D402,328 S	12/1998	Ashida	6,044,297 A	3/2000	Sheldon
5,847,854 A	12/1998	Benson, Jr.	6,049,823 A	4/2000	Hwang
5,850,624 A	12/1998	Gard	6,052,083 A	4/2000	Wilson
5,851,149 A	12/1998	Xidos et al.	6,057,788 A	5/2000	Cummings
5,853,332 A	12/1998	Briggs	6,058,342 A	5/2000	Orbach
5,854,622 A	12/1998	Brannon	6,059,576 A	5/2000	Brann
5,855,483 A	1/1999	Collins et al.	6,060,847 A	5/2000	Hettema et al.
D405,071 S	2/1999	Gambaro	6,066,075 A	5/2000	Poulton
5,865,680 A	2/1999	Briggs	6,069,594 A	5/2000	Barnes et al.
5,867,146 A	2/1999	Kim et al.	6,072,467 A	6/2000	Walker
5,874,941 A	2/1999	Yamada	6,072,470 A	6/2000	Ishigaki
5,875,257 A	2/1999	Marrin et al.	6,075,443 A	6/2000	Schepps et al.
D407,071 S	3/1999	Keating	6,075,575 A	6/2000	Schein et al.
D407,761 S	4/1999	Barr	6,076,734 A	6/2000	Dougherty et al.
5,893,562 A	4/1999	Spector	6,077,106 A	6/2000	Mish
5,897,437 A	4/1999	Nishiumi	6,078,789 A	6/2000	Bodenmann
5,898,421 A	4/1999	Quinn	6,079,982 A	6/2000	Meador
5,900,867 A	5/1999	Schindler et al.	6,080,063 A	6/2000	Khosla
5,901,246 A	5/1999	Hoffberg et al.	6,081,819 A	6/2000	Ogino
5,902,968 A	5/1999	Sato et al.	6,084,315 A	7/2000	Schmitt
5,906,542 A	5/1999	Neumann	6,084,577 A	7/2000	Sato et al.
D410,909 S	6/1999	Tickle	6,085,805 A	7/2000	Bates
5,908,996 A	6/1999	Litterst et al.	6,087,950 A	7/2000	Capan
5,911,634 A	6/1999	Nidata et al.	6,089,987 A	7/2000	Briggs
5,912,612 A	6/1999	DeVolpi	D429,718 S	8/2000	Rudolph
5,913,019 A	6/1999	Attenberg	6,102,406 A	8/2000	Miles et al.
5,913,727 A	6/1999	Ahdoot	6,110,039 A	8/2000	Oh
5,919,149 A	7/1999	Allen	6,110,041 A	8/2000	Walker et al.
5,923,317 A	7/1999	Sayler et al.	6,115,028 A	9/2000	Balakrishnan
5,924,695 A	7/1999	Heykoop	6,127,990 A	10/2000	Zwern
5,926,780 A	7/1999	Fox et al.	6,129,549 A	10/2000	Thompson
5,929,782 A	7/1999	Stark et al.	6,132,318 A	10/2000	Briggs
5,929,841 A	7/1999	Fujii	6,137,457 A	10/2000	Tokuhashi
5,929,848 A	7/1999	Albukerk et al.	D433,381 S	11/2000	Talesfore
D412,940 S	8/1999	Kato et al.	6,142,870 A	11/2000	Wada
5,931,739 A	8/1999	Layer et al.	6,142,876 A	11/2000	Cumbers
5,942,969 A	8/1999	Wicks	6,144,367 A	11/2000	Berstis
5,944,533 A	8/1999	Wood	6,146,278 A	11/2000	Kobayashi
5,946,444 A	8/1999	Evans et al.	6,148,100 A	11/2000	Anderson et al.
5,947,789 A	9/1999	Chan	6,149,490 A	11/2000	Hampton
5,947,868 A	9/1999	Dugan	6,150,947 A	11/2000	Shima
5,955,713 A	9/1999	Titus	6,154,723 A	11/2000	Cox et al.
5,955,988 A	9/1999	Blonstein	6,155,926 A	12/2000	Miyamoto et al.
5,956,035 A	9/1999	Sciammarella	6,160,405 A	12/2000	Needle
5,961,386 A	10/1999	Sawaguchi	6,160,540 A	12/2000	Fishkin et al.
5,963,136 A	10/1999	O'Brien	6,160,986 A	12/2000	Gabai et al.
5,964,660 A	10/1999	James et al.	6,162,122 A	12/2000	Acres et al.
5,967,898 A	10/1999	Takasaka et al.	6,162,123 A	12/2000	Woolston
5,967,901 A	10/1999	Briggs	6,162,191 A	12/2000	Foxin
5,971,270 A	10/1999	Barna	6,164,808 A	12/2000	Shibata
5,973,757 A	10/1999	Aubuchon et al.	6,171,190 B1	1/2001	Thanasack et al.
5,980,254 A	11/1999	Muehle et al.	6,174,242 B1	1/2001	Briggs et al.
5,982,356 A	11/1999	Akiyama	6,176,837 B1	1/2001	Foxlin
5,984,785 A	11/1999	Takeda et al.	6,181,253 B1	1/2001	Eschenbach et al.
5,984,788 A	11/1999	Lebensfeld et al.	6,181,329 B1	1/2001	Stork et al.
5,986,570 A	11/1999	Black et al.	6,183,364 B1	2/2001	Trovato
5,986,644 A	11/1999	Herder	6,183,365 B1	2/2001	Tonomura et al.
5,989,120 A	11/1999	Truchsess	6,184,862 B1	2/2001	Leiper

6,184,863	B1	2/2001	Sibert	6,347,998	B1	2/2002	Yoshitomi et al.
6,186,902	B1	2/2001	Briggs	6,350,199	B1	2/2002	Williams et al.
6,191,774	B1	2/2001	Schena	6,352,478	B1	3/2002	Gabai et al.
6,196,893	B1	3/2001	Casola et al.	6,356,867	B1	3/2002	Gabai et al.
6,198,295	B1	3/2001	Hill	6,361,396	B1	3/2002	Snyder
6,198,470	B1	3/2001	Agam et al.	6,361,507	B1	3/2002	Foxlin
6,198,471	B1	3/2001	Cook	D456,410	S	4/2002	Ashida
6,200,216	B1	3/2001	Peppel	6,364,735	B1	4/2002	Bristow et al.
6,200,219	B1	3/2001	Rudell et al.	6,368,177	B1	4/2002	Gabai et al.
6,200,253	B1	3/2001	Nishiumi	6,368,217	B2	4/2002	Kanno
6,201,554	B1	3/2001	Lands	6,369,794	B1	4/2002	Sakurai et al.
6,206,745	B1	3/2001	Gabai et al.	6,369,908	B1	4/2002	Frey et al.
6,206,782	B1	3/2001	Walker et al.	6,371,375	B1	4/2002	Ackley et al.
6,210,287	B1	4/2001	Briggs	6,371,853	B1	4/2002	Borta
6,211,861	B1	4/2001	Rosenberg et al.	6,375,566	B1	4/2002	Yamada
6,214,155	B1	4/2001	Leighton	6,375,569	B1	4/2002	Acres
6,217,450	B1	4/2001	Meredith	6,375,572	B1	4/2002	Masuyama et al.
6,217,478	B1	4/2001	Vohmann	6,375,578	B1	4/2002	Briggs
6,220,171	B1	4/2001	Hettema et al.	6,377,793	B1	4/2002	Jenkins
6,220,964	B1	4/2001	Miyamoto	6,377,906	B1	4/2002	Rowe
6,220,965	B1	4/2001	Hanna et al.	D456,854	S	5/2002	Ashida
6,222,522	B1	4/2001	Mathews	6,383,079	B1	5/2002	Takech et al.
D442,998	S	5/2001	Ashida	6,386,538	B1	5/2002	Mejia
6,224,486	B1	5/2001	Walker et al.	6,392,613	B1	5/2002	Goto
6,224,491	B1	5/2001	Hiromi et al.	6,394,904	B1	5/2002	Stalker
6,225,987	B1	5/2001	Matsuda	6,400,480	B1	6/2002	Thomas
6,226,534	B1	5/2001	Aizawa	6,400,996	B1	6/2002	Hoffberg et al.
6,227,966	B1	5/2001	Yokoi	6,404,409	B1	6/2002	Solomon
6,231,451	B1	5/2001	Briggs	6,409,379	B1	6/2002	Gabathuler et al.
6,234,803	B1	5/2001	Watkins	6,409,604	B1	6/2002	Matsuno
6,238,289	B1	5/2001	Sobota et al.	6,409,687	B1	6/2002	Foxlin
6,238,291	B1	5/2001	Fujimoto et al.	D459,727	S	7/2002	Ashida
6,239,806	B1	5/2001	Nishiumi et al.	D460,787	S	7/2002	Nishikawa
RE37,220	E	6/2001	Rapisarda et al.	6,414,589	B1	7/2002	Angott et al.
6,241,611	B1	6/2001	Takeda et al.	6,415,223	B1	7/2002	Lin
6,243,491	B1	6/2001	Andersson	6,421,056	B1	7/2002	Nishiumi
6,243,658	B1	6/2001	Raby	6,424,333	B1	7/2002	Tremblay
6,244,987	B1	6/2001	Ohsuga et al.	6,426,719	B1	7/2002	Nagareda
6,245,014	B1	6/2001	Brainard et al.	6,426,741	B1	7/2002	Goldsmith et al.
6,248,019	B1	6/2001	Mudie et al.	6,438,193	B1	8/2002	Ko
6,254,101	B1	7/2001	Young	D462,683	S	9/2002	Ashida
6,254,394	B1	7/2001	Draper et al.	6,445,960	B1	9/2002	Borta
6,261,180	B1	7/2001	Lebensfeld et al.	6,452,494	B1	9/2002	Harrison
6,264,202	B1	7/2001	Briggs	6,456,276	B1	9/2002	Park
6,264,558	B1	7/2001	Nishiumi et al.	D464,052	S	10/2002	Fletcher
6,265,984	B1	7/2001	Molinarioli	D464,950	S	10/2002	Fraquelli et al.
6,267,673	B1	7/2001	Miyamoto et al.	6,462,769	B1	10/2002	Trowbridge et al.
6,273,425	B1	8/2001	Westfall et al.	6,463,257	B1	10/2002	Wood
6,273,819	B1	8/2001	Strauss et al.	6,463,859	B1	10/2002	Ikezawa
6,280,327	B1	8/2001	Leifer et al.	6,466,198	B1	10/2002	Feinstein
6,280,328	B1	8/2001	Holch et al.	6,466,831	B1	10/2002	Shibata
6,283,862	B1	9/2001	Richter	6,473,070	B2	10/2002	Mishra et al.
6,283,871	B1	9/2001	Briggs	6,473,713	B1	10/2002	McCall
6,290,565	B1	9/2001	Galyean, III et al.	6,474,159	B1	11/2002	Foxlin et al.
6,290,566	B1	9/2001	Gabai et al.	6,482,067	B1	11/2002	Pickens
6,293,684	B1	9/2001	Riblett	6,484,080	B2	11/2002	Breed
6,297,751	B1	10/2001	Fadavi-Ardekani	6,490,409	B1	12/2002	Walker
6,301,534	B1	10/2001	McDermott	6,492,981	B1	12/2002	Stork et al.
6,302,793	B1	10/2001	Fertitta, III et al.	6,494,457	B2	12/2002	Conte et al.
6,302,796	B1	10/2001	Lebensfeld et al.	6,496,122	B2	12/2002	Sampsel
6,304,250	B1	10/2001	Yang	6,509,217	B1	1/2003	Reddy
6,311,982	B1	11/2001	Lebensfeld et al.	6,512,511	B2	1/2003	Willner
6,315,673	B1	11/2001	Kopera	6,517,438	B2	2/2003	Tosaki
6,320,495	B1	11/2001	Sporgis	6,518,952	B1	2/2003	Leiper
6,322,365	B1	11/2001	Shechter et al.	6,525,660	B1	2/2003	Surintrspanont
6,323,614	B1	11/2001	Palaxxolo	6,526,158	B1	2/2003	Goldberg
6,323,654	B1	11/2001	Needle	6,527,646	B1	3/2003	Briggs
6,325,718	B1	12/2001	Nishiumi et al.	6,530,838	B2	3/2003	Ha et al.
6,328,648	B1	12/2001	Walker et al.	6,530,841	B2	3/2003	Bull et al.
6,328,650	B1	12/2001	Fukawa et al.	6,538,675	B2	3/2003	Aratani
6,329,648	B1	12/2001	Delatorre	D473,942	S	4/2003	Motoki et al.
6,330,427	B1	12/2001	Tabachnik	6,540,607	B2	4/2003	Mokris et al.
6,331,841	B1	12/2001	Tokuhashi	6,540,611	B1	4/2003	Nagata
6,331,856	B1	12/2001	VanHook	6,544,124	B2	4/2003	Ireland
6,332,840	B1	12/2001	Nishiumi et al.	6,544,126	B2	4/2003	Sawano
6,337,954	B1	1/2002	Soshi	6,545,661	B1 *	4/2003	Goschy et al. 345/158
6,342,010	B1	1/2002	Slifer	6,551,165	B2	4/2003	Smirnov
6,346,047	B1	2/2002	Sobota	6,551,188	B2	4/2003	Toyama et al.
6,347,993	B1	2/2002	Kondo et al.	6,554,707	B1	4/2003	Sinclair et al.

6,554,781 B1	4/2003	Carter et al.	6,773,325 B1	8/2004	Mawle et al.
D474,763 S	5/2003	Tozaki et al.	6,773,344 B1	8/2004	Gabai et al.
6,565,438 B2	5/2003	Ogino	6,785,539 B2	8/2004	Hale
6,567,536 B2	5/2003	McNitt et al.	6,786,877 B2	9/2004	Foxlin
6,572,108 B1	6/2003	Bristow	6,796,177 B2	9/2004	Mori
6,575,753 B2	6/2003	Rosa et al.	6,796,908 B2	9/2004	Weston
6,577,350 B1	6/2003	Proehl	6,797,895 B2	9/2004	Lapstun
6,579,098 B2	6/2003	Shechter	6,811,489 B1	11/2004	Shimizu
6,582,299 B1	6/2003	Matsuyama et al.	6,811,491 B1	11/2004	Levenberg et al.
6,582,380 B2	6/2003	Kazlauskys et al.	6,812,881 B1	11/2004	Mullaly et al.
6,583,783 B1	6/2003	Dietrich	6,813,525 B2	11/2004	Reid
6,585,596 B1	7/2003	Leifer et al.	6,813,574 B1	11/2004	Yedur
6,589,120 B1	7/2003	Takahashi	6,813,584 B2	11/2004	Zhou et al.
6,590,536 B1	7/2003	Walton	6,816,151 B2	11/2004	Dellinger
6,591,677 B2	7/2003	Rothoff	6,821,204 B2	11/2004	Aonuma et al.
6,592,461 B1	7/2003	Raviv et al.	6,821,206 B1	11/2004	Ishida et al.
6,595,863 B2	7/2003	Chamberlain et al.	6,836,705 B2	12/2004	Hellmann
6,597,342 B1	7/2003	Haruta	6,836,751 B2	12/2004	Paxton
6,597,443 B2	7/2003	Boman	6,836,971 B1	1/2005	Wang
6,599,194 B1	7/2003	Smith	6,842,991 B2	1/2005	Levi
6,605,038 B1	8/2003	Teller et al.	6,846,238 B2	1/2005	Wells
6,608,563 B2	8/2003	Weston et al.	6,850,221 B1	2/2005	Tickle
6,609,969 B1	8/2003	Luciano et al.	6,850,844 B1	2/2005	Walters
6,609,977 B1	8/2003	Shimizu	6,852,032 B2	2/2005	Ishino
6,616,452 B2	9/2003	Clark et al.	6,856,327 B2	2/2005	Choi
6,616,535 B1	9/2003	Nishizak	D502,468 S	3/2005	Knight et al.
6,616,607 B2	9/2003	Hashimoto	6,868,738 B2	3/2005	Moscip
6,626,728 B2	9/2003	Holt	6,872,139 B2	3/2005	Sato et al.
6,628,257 B1	9/2003	Oka	6,873,406 B1	3/2005	Hines
6,629,019 B2	9/2003	Legge et al.	D503,750 S	4/2005	Kit et al.
6,632,142 B2	10/2003	Keith	6,878,066 B2	4/2005	Leifer
6,633,155 B1	10/2003	Liang	6,882,824 B2	4/2005	Wood
6,634,949 B1	10/2003	Briggs et al.	D504,677 S	5/2005	Kaminski et al.
6,636,826 B1	10/2003	Abe et al.	D505,424 S	5/2005	Ashida et al.
6,641,482 B2	11/2003	Masuyama et al.	6,890,262 B2	5/2005	Oishi
6,650,029 B1	11/2003	Johnston	6,891,526 B2	5/2005	Gombert
6,650,313 B2	11/2003	Levine	6,894,686 B2	5/2005	Stamper et al.
6,650,345 B1	11/2003	Saito	6,897,845 B2	5/2005	Ozawa
6,651,268 B1	11/2003	Briggs	6,897,854 B2	5/2005	Cho et al.
6,654,001 B1	11/2003	Su	6,902,483 B2	6/2005	Lin
6,672,962 B1	1/2004	Ozaki et al.	6,903,725 B2	6/2005	Nacson
6,676,520 B2	1/2004	Nishiumi et al.	6,905,411 B2	6/2005	Nguyen et al.
6,676,524 B1	1/2004	Botzas	6,906,700 B1	6/2005	Armstrong
6,677,990 B1	1/2004	Kawahara	6,908,386 B2	6/2005	Suzuki et al.
6,682,074 B2	1/2004	Weston	6,908,388 B2	6/2005	Shimizu
6,682,351 B1	1/2004	Abraham-Fuchs et al.	6,918,833 B2	7/2005	Emmerson et al.
6,684,062 B1	1/2004	Gosior et al.	6,921,332 B2	7/2005	Fukunaga
D486,145 S	2/2004	Kaminski et al.	6,922,632 B2	7/2005	Foxlin
6,686,954 B1	2/2004	Kitaguchi	6,925,410 B2	8/2005	Narayanan
6,692,170 B2	2/2004	Abir	6,929,543 B1	8/2005	Ueshima et al.
6,693,622 B1	2/2004	Shahoian et al.	6,929,548 B2	8/2005	Wang
6,702,672 B1	3/2004	Angell et al.	6,932,698 B2	8/2005	Sprogis
6,709,336 B2	3/2004	Siegel et al.	6,932,706 B1	8/2005	Kaminkow
6,712,692 B2	3/2004	Basson	6,933,861 B2	8/2005	Wang
6,716,102 B2	4/2004	Whitten et al.	6,933,923 B2	8/2005	Feinstein
6,717,573 B1	4/2004	Shahoian et al.	6,935,864 B2	8/2005	Shechter et al.
6,717,673 B1	4/2004	Janssen	6,939,232 B2	9/2005	Tanaka et al.
6,718,280 B2	4/2004	Hermann	6,948,999 B2	9/2005	Chan
6,725,107 B2	4/2004	MacPherson	6,954,980 B2	10/2005	Song
6,725,173 B2	4/2004	An	6,955,606 B2	10/2005	Taho et al.
D489,361 S	5/2004	Mori et al.	6,956,564 B1	10/2005	Williams
6,729,934 B1	5/2004	Driscoll et al.	6,965,374 B2	11/2005	Villet et al.
6,733,390 B2	5/2004	Walker et al.	6,966,775 B1	11/2005	Kendir et al.
6,736,009 B1	5/2004	Schwabe	6,967,563 B2	11/2005	Bormaster
D491,924 S	6/2004	Kaminski et al.	6,967,566 B2	11/2005	Weston et al.
D492,285 S	6/2004	Ombao et al.	6,982,697 B2	1/2006	Wilson et al.
6,743,104 B1	6/2004	Ota et al.	6,983,219 B2	1/2006	Mantyjarvi
6,746,334 B1	6/2004	Barney	6,984,208 B2	1/2006	Zheng
6,747,632 B2	6/2004	Howard	6,990,639 B2	1/2006	Wilson
6,747,690 B2	6/2004	Molgaard	6,993,451 B2	1/2006	Chang et al.
6,749,432 B2	6/2004	French et al.	6,995,748 B2	2/2006	Gordon et al.
6,752,719 B2	6/2004	Himoto et al.	6,998,966 B2	2/2006	Pedersen
6,753,849 B1	6/2004	Curran et al.	7,000,469 B2	2/2006	Foxlin et al.
6,753,888 B2	6/2004	Kamiwada	7,002,591 B1	2/2006	Leather
6,757,068 B2	6/2004	Foxlin	7,029,400 B2	4/2006	Briggs
6,757,446 B1	6/2004	Li	7,031,875 B2	4/2006	Ellenby et al.
6,761,637 B2	7/2004	Weston et al.	7,040,986 B2	5/2006	Koshima
6,765,553 B1	7/2004	Odamura	7,040,993 B1	5/2006	Lovitt
D495,336 S	8/2004	Andre et al.	7,040,998 B2	5/2006	Jolliffe et al.

US 8,368,648 B2

Page 7

7,052,391	B1	5/2006	Luciano, Jr.	7,428,499	B1	9/2008	Philyaw
7,055,101	B2	5/2006	Abbott et al.	7,435,179	B1	10/2008	Ford
7,066,781	B2	6/2006	Weston	7,441,151	B2	10/2008	Whitten et al.
D524,298	S	7/2006	Hedderich et al.	7,442,108	B2	10/2008	Ganz
7,081,033	B1	7/2006	Mawle	7,445,550	B2	11/2008	Barney et al.
7,081,051	B2	7/2006	Himoto et al.	7,465,212	B2	12/2008	Ganz
7,086,645	B2	8/2006	Hardie	7,488,231	B2	2/2009	Weston
7,090,582	B2	8/2006	Danieli et al.	7,489,299	B2	2/2009	Liberty et al.
7,094,147	B2	8/2006	Nakata	7,492,268	B2	2/2009	Ferguson et al.
7,098,891	B1	8/2006	Pryor	7,492,367	B2	2/2009	Mahajan et al.
7,098,894	B2	8/2006	Yang	7,500,917	B2	3/2009	Barney et al.
7,102,615	B2	9/2006	Marks	7,502,759	B2	3/2009	Hannigan et al.
7,102,616	B1	9/2006	Sleator	7,519,537	B2	4/2009	Rosenberg
7,107,168	B2	9/2006	Oystol	7,524,246	B2	4/2009	Briggs et al.
D531,228	S	10/2006	Ashida et al.	7,535,456	B2	5/2009	Liberty et al.
7,115,032	B2	10/2006	Cantu et al.	7,536,156	B2	5/2009	Tischer
7,118,482	B2	10/2006	Ishihara et al.	7,564,426	B2	7/2009	Poor
7,126,584	B1	10/2006	Nishiumi et al.	7,568,289	B2	8/2009	Burlingham et al.
7,127,370	B2	10/2006	Kelly	7,572,191	B2	8/2009	Weston et al.
D531,585	S	11/2006	Weitgasser et al.	7,582,016	B2	9/2009	Suzuki
7,133,026	B2	11/2006	Horie et al.	7,596,466	B2	9/2009	Ohta
7,136,674	B2	11/2006	Yoshie et al.	7,614,958	B2	11/2009	Weston et al.
7,136,826	B2	11/2006	Alsafadi	7,623,115	B2	11/2009	Marks
7,137,899	B2	11/2006	Hiei	7,627,451	B2	12/2009	Vock
7,139,983	B2	11/2006	Kelts	7,662,015	B2	2/2010	Hui
7,140,962	B2	11/2006	Okuda et al.	7,663,509	B2	2/2010	Shen
7,142,191	B2	11/2006	Idesawa et al.	7,674,184	B2	3/2010	Briggs et al.
7,145,551	B1	12/2006	Bathiche	7,704,135	B2	4/2010	Harrison
7,149,627	B2	12/2006	Ockerse	7,749,089	B1	7/2010	Briggs et al.
7,154,475	B2	12/2006	Crew	7,774,155	B2	8/2010	Sato et al.
7,155,604	B2	12/2006	Kawai	7,775,882	B2	8/2010	Kawamura et al.
7,158,116	B2	1/2007	Poltorak	7,789,741	B1	9/2010	Fields
7,158,118	B2	1/2007	Liberty	7,796,116	B2	9/2010	Salsman et al.
7,173,604	B2	2/2007	Marvit	7,850,527	B2	12/2010	Barney et al.
7,176,919	B2	2/2007	Drebin	7,878,905	B2	2/2011	Weston et al.
7,180,414	B2	2/2007	Nyfelt	7,883,420	B2	2/2011	Bradbury
7,180,503	B2	2/2007	Burr	7,896,742	B2	3/2011	Barney et al.
7,182,691	B1	2/2007	Schena	7,927,216	B2	4/2011	Ikeda
7,183,480	B2	2/2007	Nishitani et al.	7,942,745	B2	5/2011	Ikeda
7,184,059	B1	2/2007	Fouladi	8,021,239	B2	9/2011	Weston et al.
D538,790	S	3/2007	Okada et al.	8,089,458	B2	1/2012	Barney et al.
D543,246	S	5/2007	Ashida et al.	8,164,567	B1	4/2012	Barney et al.
7,220,220	B2	5/2007	Stubbs et al.	8,169,406	B2	5/2012	Barney et al.
7,223,173	B2	5/2007	Masuyama et al.	8,184,097	B1	5/2012	Barney et al.
7,225,101	B2	5/2007	Usuda et al.	8,226,493	B2	7/2012	Briggs et al.
7,231,063	B2	6/2007	Naimark	2001/0010514	A1	8/2001	Ishino
7,233,316	B2	6/2007	Smith et al.	2001/0015123	A1	8/2001	Nishitani et al.
7,236,156	B2	6/2007	Liberty et al.	2001/0024973	A1	9/2001	Meredith
7,239,301	B2	7/2007	Liberty et al.	2001/0031662	A1	10/2001	Larian
7,261,690	B2	8/2007	Teller et al.	2001/0034257	A1	10/2001	Weston et al.
7,262,760	B2	8/2007	Liberty	2001/0039206	A1	11/2001	Peppel
RE39,818	E	9/2007	Slifer	2001/0049302	A1	12/2001	Hagiwara et al.
D556,201	S	11/2007	Ashida et al.	2001/0054082	A1	12/2001	Rudolph et al.
7,291,014	B2	11/2007	Chung et al.	2002/0005787	A1	1/2002	Gabai et al.
7,292,151	B2	11/2007	Ferguson et al.	2002/0024500	A1	2/2002	Howard
7,297,059	B2	11/2007	Vancura et al.	2002/0024675	A1	2/2002	Foxlin
7,301,527	B2	11/2007	Marvit	2002/0028071	A1	3/2002	Molgaard
7,301,648	B2	11/2007	Foxlin	2002/0032067	A1	3/2002	Barney
D556,760	S	12/2007	Ashida et al.	2002/0038267	A1	3/2002	Can et al.
7,307,617	B2	12/2007	Wilson et al.	2002/0052238	A1	5/2002	Muroi
D559,847	S	1/2008	Ashida et al.	2002/0058459	A1	5/2002	Holt
D561,178	S	2/2008	Azuma	2002/0068500	A1	6/2002	Gabai et al.
7,331,857	B2	2/2008	MacIver	2002/0072418	A1	6/2002	Masuyama et al.
7,335,134	B1	2/2008	LaVelle	2002/0075335	A1	6/2002	Relimoto
D563,948	S	3/2008	d-Hoore	2002/0090985	A1	7/2002	Tochner et al.
7,339,105	B2	3/2008	Eitaki	2002/0090992	A1	7/2002	Legge et al.
7,345,670	B2	3/2008	Armstrong	2002/0098887	A1	7/2002	Himoto et al.
D567,243	S	4/2008	Ashida et al.	2002/0103026	A1	8/2002	Himoto et al.
7,359,121	B2	4/2008	French et al.	2002/0107069	A1	8/2002	Ishino
7,359,451	B2	4/2008	McKnight	2002/0107591	A1	8/2002	Gabai et al.
7,361,073	B2	4/2008	Martin	2002/0118147	A1	8/2002	Solomon
RE40,324	E	5/2008	Crawford	2002/0123377	A1	9/2002	Shulman
7,379,566	B2	5/2008	Hildreth	2002/0126026	A1	9/2002	Lee et al.
7,387,559	B2	6/2008	Sanchez-Castro et al.	2002/0128056	A1	9/2002	Kato
7,395,181	B2	7/2008	Foxlin	2002/0137427	A1	9/2002	Peters
7,398,151	B1	7/2008	Burrell et al.	2002/0137567	A1	9/2002	Cheng
7,414,611	B2	8/2008	Liberty	2002/0140745	A1	10/2002	Ellenby
7,419,428	B2	9/2008	Rowe	2002/0158751	A1	10/2002	Bormaster
7,424,388	B2	9/2008	Sato	2002/0158843	A1	10/2002	Levine

2002/0183961	A1	12/2002	French et al.	2005/0130739	A1	6/2005	Argentar
2002/0193047	A1	12/2002	Weston	2005/0134555	A1	6/2005	Liao
2003/0013513	A1	1/2003	Rowe	2005/0143173	A1	6/2005	Barney et al.
2003/0022736	A1	1/2003	Cass	2005/0156883	A1	7/2005	Wilson et al.
2003/0027634	A1	2/2003	Matthews, III	2005/0162389	A1	7/2005	Obermeyer
2003/0036425	A1	2/2003	Kaminkow et al.	2005/0164601	A1	7/2005	McEachen
2003/0037075	A1	2/2003	Hannigan	2005/0170889	A1	8/2005	Lum et al.
2003/0038778	A1	2/2003	Noguera	2005/0172734	A1	8/2005	Alsio
2003/0052860	A1	3/2003	Park et al.	2005/0174324	A1	8/2005	Liberty
2003/0057808	A1	3/2003	Lee et al.	2005/0176485	A1	8/2005	Ueshima
2003/0063068	A1	4/2003	Anton	2005/0179644	A1	8/2005	Alsio
2003/0069077	A1	4/2003	Korienek	2005/0210418	A1	9/2005	Marvit
2003/0095101	A1	5/2003	Jou	2005/0210419	A1	9/2005	Kela
2003/0096652	A1	5/2003	Siegel et al.	2005/0212749	A1	9/2005	Marvit
2003/0106455	A1	6/2003	Weston	2005/0212750	A1	9/2005	Marvit
2003/0107178	A1	6/2003	Weston	2005/0212751	A1	9/2005	Marvit
2003/0107551	A1	6/2003	Dunker	2005/0212752	A1	9/2005	Marvit
2003/0134679	A1	7/2003	Siegel et al.	2005/0212753	A1	9/2005	Marvit
2003/0144047	A1	7/2003	Sprogis	2005/0212754	A1	9/2005	Marvit
2003/0144056	A1	7/2003	Leifer et al.	2005/0212755	A1	9/2005	Marvit
2003/0166416	A1	9/2003	Ogata	2005/0212756	A1	9/2005	Marvit
2003/0171145	A1	9/2003	Rowe	2005/0212757	A1	9/2005	Marvit
2003/0171190	A1	9/2003	Rice	2005/0212758	A1	9/2005	Marvit
2003/0193572	A1	10/2003	Wilson et al.	2005/0212759	A1	9/2005	Marvit
2003/0195037	A1	10/2003	Vuong et al.	2005/0212760	A1	9/2005	Marvit
2003/0195041	A1	10/2003	McCauley	2005/0212764	A1	9/2005	Toba
2003/0195046	A1	10/2003	Bartsch	2005/0212767	A1	9/2005	Marvit
2003/0204361	A1	10/2003	Townsend	2005/0215295	A1	9/2005	Arneson
2003/0214259	A9	11/2003	Dowling et al.	2005/0215322	A1	9/2005	Himoto et al.
2003/0216176	A1	11/2003	Shimizu	2005/0217525	A1	10/2005	McClure
2003/0222851	A1	12/2003	Lai	2005/0233808	A1	10/2005	Himoto et al.
2003/0234914	A1	12/2003	Solomon	2005/0239548	A1	10/2005	Ueshima et al.
2004/0028258	A1	2/2004	Naimark	2005/0243061	A1	11/2005	Liberty
2004/0033833	A1	2/2004	Briggs et al.	2005/0243062	A1	11/2005	Liberty
2004/0034289	A1	2/2004	Teller et al.	2005/0253806	A1	11/2005	Liberty
2004/0048666	A1	3/2004	Bagley	2005/0256675	A1	11/2005	Kurata
2004/0063480	A1	4/2004	Wang	2005/0266907	A1	12/2005	Weston et al.
2004/0070564	A1	4/2004	Dawson	2005/0277465	A1	12/2005	Whitten et al.
2004/0075650	A1	4/2004	Paul	2005/0278741	A1	12/2005	Robarts
2004/0077423	A1	4/2004	Weston et al.	2006/0007115	A1	1/2006	Furuhashi
2004/0081313	A1	4/2004	McKnight et al.	2006/0028446	A1	2/2006	Liberty
2004/0092311	A1	5/2004	Weston et al.	2006/0030385	A1	2/2006	Barney et al.
2004/0095317	A1	5/2004	Zhang	2006/0040720	A1	2/2006	Harrison
2004/0102247	A1	5/2004	Smoot et al.	2006/0092133	A1	5/2006	Touma
2004/0119693	A1	6/2004	Kaemmler	2006/0094502	A1	5/2006	Katayama et al.
2004/0121834	A1	6/2004	Libby et al.	2006/0122474	A1	6/2006	Teller et al.
2004/0134341	A1	7/2004	Sandoz	2006/0123146	A1	6/2006	Wu et al.
2004/0140954	A1	7/2004	Faeth	2006/0148563	A1	7/2006	Yang
2004/0143413	A1	7/2004	Oystol	2006/0152487	A1	7/2006	Grunnet-Jepsen
2004/0147317	A1	7/2004	Ito et al.	2006/0152488	A1	7/2006	Salsman
2004/0152499	A1	8/2004	Lind et al.	2006/0152489	A1	7/2006	Sweetser
2004/0152515	A1	8/2004	Wegmuller et al.	2006/0178212	A1	8/2006	Penzias
2004/0174287	A1	9/2004	Deak	2006/0205507	A1	9/2006	Ho
2004/0193413	A1	9/2004	Wilson	2006/0231794	A1	10/2006	Sakaguchi et al.
2004/0198158	A1	10/2004	Driscoll et al.	2006/0252475	A1	11/2006	Zalewski
2004/0198517	A1	10/2004	Briggs	2006/0252477	A1	11/2006	Zalewski et al.
2004/0203638	A1	10/2004	Chan	2006/0256081	A1	11/2006	Zalewski
2004/0204240	A1	10/2004	Barney	2006/0258452	A1	11/2006	Hsu
2004/0218104	A1	11/2004	Smith	2006/0264258	A1	11/2006	Zalewski et al.
2004/0222969	A1	11/2004	Buchenrieder	2006/0264260	A1	11/2006	Zalewski
2004/0227725	A1	11/2004	Calarco	2006/0267935	A1	11/2006	Corson
2004/0229693	A1	11/2004	Lind	2006/0273907	A1	12/2006	Heiman
2004/0229696	A1	11/2004	Beck	2006/0282873	A1	12/2006	Zalewski
2004/0236453	A1	11/2004	Szoboszlai	2006/0284842	A1	12/2006	Poltorak
2004/0239626	A1	12/2004	Noguera	2006/0287030	A1	12/2006	Briggs et al.
2004/0252109	A1	12/2004	Trent et al.	2006/0287085	A1	12/2006	Mao
2004/0254020	A1	12/2004	Dragusin	2006/0287086	A1	12/2006	Zalewski
2004/0259651	A1	12/2004	Storek	2006/0287087	A1	12/2006	Zalewski
2004/0268393	A1	12/2004	Hunleth	2007/0015588	A1	1/2007	Matsumoto et al.
2005/0017454	A1	1/2005	Endo et al.	2007/0021208	A1	1/2007	Mao et al.
2005/0020369	A1	1/2005	Davis	2007/0049374	A1	3/2007	Ikeda et al.
2005/0032582	A1	2/2005	Mahajan et al.	2007/0050597	A1	3/2007	Ikeda et al.
2005/0047621	A1	3/2005	Cranfill	2007/0052177	A1	3/2007	Ikeda et al.
2005/0054457	A1	3/2005	Eyestone	2007/0060391	A1	3/2007	Ikeda et al.
2005/0060586	A1	3/2005	Burger	2007/0066394	A1	3/2007	Ikeda et al.
2005/0076161	A1	4/2005	Albanna	2007/0066396	A1	3/2007	Weston et al.
2005/0085298	A1	4/2005	Woolston	2007/0072680	A1	3/2007	Ikeda et al.
2005/0116020	A1	6/2005	Smolucha et al.	2007/0091084	A1	4/2007	Ueshima et al.
2005/0125826	A1	6/2005	Hunleth	2007/0093291	A1	4/2007	Hulvey

2007/0159362	A1	7/2007	Shen	JP	07-044315	2/1995
2007/0173705	A1	7/2007	Teller et al.	JP	07-107573	4/1995
2007/0252815	A1	11/2007	Kuo	JP	07-115690	5/1995
2007/0257884	A1	11/2007	Taira	JP	07-146123	6/1995
2007/0265075	A1	11/2007	Zalewski	JP	07-200142	8/1995
2007/0265076	A1	11/2007	Lin	JP	07-262797	10/1995
2007/0265088	A1	11/2007	Nakada et al.	JP	07-302148	11/1995
2008/0014835	A1	1/2008	Weston et al.	JP	07-318332	12/1995
2008/0015017	A1	1/2008	Ashida et al.	JP	08-095704	4/1996
2008/0039202	A1	2/2008	Sawano et al.	JP	08-106352	4/1996
2008/0119270	A1	5/2008	Ohta	JP	08-111144	4/1996
2008/0121782	A1	5/2008	Hotelling et al.	JP	08-114415	5/1996
2008/0174550	A1	7/2008	Laurila	JP	08-122070	5/1996
2008/0183678	A1	7/2008	Weston	JP	08-152959	6/1996
2008/0273011	A1	11/2008	Lin	JP	08-191953	7/1996
2008/0278445	A1	11/2008	Sweester	JP	08-211993	8/1996
2009/0009294	A1	1/2009	Kupstas	JP	08-221187	8/1996
2009/0033621	A1	2/2009	Quinn	JP	08-305355	11/1996
2009/0124165	A1	5/2009	Weston	JP	08-335136	12/1996
2009/0156309	A1	6/2009	Weston et al.	JP	09-149915	6/1997
2009/0215534	A1	8/2009	Wilson et al.	JP	09-164273	6/1997
2009/0305799	A1	12/2009	Weston et al.	JP	09-34456	7/1997
2009/0326851	A1	12/2009	Tanenhau	JP	09-230997	9/1997
2010/0056285	A1	3/2010	Weston et al.	JP	09-237087	9/1997
2010/0105475	A1	4/2010	Mikhailov	JP	09-274534	10/1997
2010/0144436	A1	6/2010	Marks et al.	JP	09-319510	12/1997
2010/0203932	A1	8/2010	Briggs et al.	JP	10-021000	1/1998
2010/0273556	A1	10/2010	Briggs et al.	JP	10-033831	2/1998
2010/0289744	A1	11/2010	Cohen	JP	10 043349 A	2/1998
2011/0081969	A1	4/2011	Ikeda	JP	10-099542	4/1998
2011/0081970	A1	4/2011	Barney et al.	JP	10-154038	6/1998
2011/0177853	A1	7/2011	Ueshima	JP	10-235019	8/1998
2011/0190052	A1	8/2011	Takeda	JP	10-254614	9/1998
2011/0300941	A1	12/2011	Weston et al.	JP	11-053994	2/1999
2012/0034980	A1	2/2012	Weston et al.	JP	11-099284	4/1999
FOREIGN PATENT DOCUMENTS				JP	11-114223	4/1999
				JP	2000-33184	2/2000
CN	1559644	1/2005		JP	2000-176150	6/2000
DE	3930581	3/1991		JP	2000-270237	9/2000
DE	19701374	7/1997		JP	2000-300839	10/2000
DE	19632273	2/1998		JP	2000-308756	11/2000
DE	19648487	6/1998		JP	2000-325653	11/2000
DE	19814254	10/1998		JP	2001-038052	2/2001
DE	19937307	2/2000		JP	2001-058484	3/2001
DE	10029173	1/2002		JP	2001-104643	4/2001
DE	10219198	11/2003		JP	U20009165	4/2001
EP	0322825 A2	7/1898		JP	2001-175412	6/2001
EP	0264782 A2	4/1988		JP	2001-251324	9/2001
EP	0570999	12/1988		JP	2001-265521	9/2001
EP	0 546 844	6/1993		JP	2001-306245	11/2001
EP	0546844	6/1993		JP	2002-07057	1/2002
EP	0695565 A1	2/1996		JP	2002-062981	2/2002
EP	0835676	4/1998		JP	2002-78969	3/2002
EP	0848226	6/1998		JP	2002-082751	3/2002
EP	0852961	7/1998		JP	2002-091692	3/2002
EP	1062994	12/2000		JP	2002-126375	5/2002
EP	1279425	1/2003		JP	2002-136694	5/2002
EP	1293237	3/2003		JP	2002-153673	5/2002
EP	0993845	12/2005		JP	2002-202843	7/2002
FR	2547093 A1	12/1984		JP	2002-224444	8/2002
GB	2244546	12/1991		JP	2002-233665	8/2002
GB	2284478	6/1995		JP	2002-298145	10/2002
GB	2307133	5/1997		JP	2003-053038	2/2003
GB	2310481	8/1997		JP	2003-140823	5/2003
GB	2316482	2/1998		JP	2003-208263	7/2003
GB	2319374	5/1998		JP	2003-236246	8/2003
GB	2325558 A	11/1998		JP	2003-325974	11/2003
GB	2388418	11/2003		JP	2004-062774	2/2004
JP	62-14527	1/1987		JP	2004-313429	11/2004
JP	63-186687	8/1988		JP	2004-313492	11/2004
JP	03-210622	9/1991		JP	2005-040493	2/2005
JP	06-50758	2/1994		JP	2005-063230	3/2005
JP	06-050758	2/1994		JP	2006-113019	4/2006
JP	06-154422	6/1994		JP	2006-136694	6/2006
JP	06-190144	7/1994		JP	2006-216569	8/2006
JP	06-198075	7/1994		JP	2007-083024	4/2007
JP	H0677387	10/1994	NL	9300171	8/1994	
JP	06-308879	11/1994	RU	2077358 C1	4/1997	
JP	07-028591	1/1995	RU	2125853	2/1999	

RU	2126161	2/1999
WO	WO 94/02931	3/1994
WO	WO 95/11730 A1	5/1995
WO	WO 96/05766	2/1996
WO	WO 96/14115	5/1996
WO	WO 96/14121	5/1996
WO	WO 97/09101	3/1997
WO	WO 97/12337	4/1997
WO	WO 97/17598	5/1997
WO	WO 97/20305	6/1997
WO	PCT/US97/01811	8/1997
WO	WO 97/28864	8/1997
WO	WO 97/32641	9/1997
WO	WO 98/11528	3/1998
WO	WO 98/36400	8/1998
WO	WO 99/58214	11/1999
WO	WO 00/33168	6/2000
WO	WO 00/35345	6/2000
WO	WO 00/61251	10/2000
WO	WO 00/63874	10/2000
WO	WO 00/67863	11/2000
WO	WO 01/87426	11/2001
WO	WO 01/91042	11/2001
WO	WO 02/17054	2/2002
WO	WO 02/34345	5/2002
WO	WO 02/47013	6/2002
WO	WO 03/015005	2/2003
WO	WO 03/043709	5/2003
WO	WO 03/044743	5/2003
WO	WO 03/088147	10/2003
WO	WO 03/107260	12/2003
WO	WO 2004/039055	5/2004
WO	WO 2004/051391	6/2004

OTHER PUBLICATIONS

Jonathan Green et al., "Camping in the Digital Wilderness: Tents and Flashlights As Interfaces to Virtual Worlds," *Chi* 2002, Apr. 2002, pp. 780-781.

Mitchel Resnick et al., "Digital Manipulatives: New Toys to Think With," *Chi* 98; Apr. 1998; pp. 281-287.

Vanessa Colella et al., "Participatory Simulations: Using Computational Objects to Learn about Dynamic Systems," *Chi* 98; Apr. 1998, pp. 9-10.

R. Borovoy et al., "Things that Blink: Computationally Augmented Name Tags," *IBM Systems Journal*, vol. 35, Nos. 3 & 4, 1996; pp. 488-495.

Allison Druin et al., "Robots for Kids: Exploring New Technologies for Learning," Academic Press, 2000; Chap. 1, 27 pages.

Badler et al., "Multi-Dimensional Input Techniques and Articulated Figure Positioning by Multiple Constraints," *Interactive 3D Graphics*, Oct. 1986; pp. 151-169.

Cheok et al., "Micro-Accelerometer Based Hardware Interfaces for Wearable Computer Mixed Reality Applications," 6th International Symposium on Wearable Computers (ISWC'02), 8 pages.

James H. Clark, "Designing Surfaces in 3-D," *Graphics and Image Processing-Communications of the ACM*, Aug. 1976; vol. 19; No. 8; pp. 454-460.

James H. Clark, "Three Dimensional Man Machine Interaction," *Siggraph '76*, Jul. 14-16 Philadelphia, Pennsylvania, 1 page.

Michael F. Deering, "HoloSketch A Virtual Reality Sketching Animation Tool," *ACM Transactions on Computer-Human Interaction*, Sep. 1995; vol. 2, No. 3; pp. 220-238.

Robert E. Drzymala et al., "A Feasibility Study Using a Stereo-Optical Camera System to Verify Gamma Knife Treatment Specification," *Proceedings of 22nd Annual EMBS International Conference*, Jul. 2000; pp. 1486-1489.

Hunter G. Hoffman, "Physically Touching Virtual Objects Using Tactile Augmentation Enhances the Realism of Virtual Environments," *IEEE Virtual Reality Annual International Symposium '98*, Atlanta, Georgia, 1998, 5 pages.

D.W. Kormos et al., "Intraoperative, Real-Time 3-D Digitizer for Neurosurgical Treatment and Planning," 1993; 1 page.

Nintendo Tilt Controller Ad, *Electronic Gaming Monthly*, 1994, 1 page.

Interfax Press Release, "Tsinghua Tongfang Releases Unique Peripheral Hardware for 3D Gaming," 2002, 1 page.

New Strait Times Press Release, "Microsoft's New Titles," 1998, 1 page.

"Ollivanders: Makers of Fine Wands." Dec. 2, 2002. [online] [retrieved on Mar. 30, 2005], Retrieved from Internet <URL: <http://www.cim.mcgill.edu/~jer/courses/hci/assignments/2002/www.ece.mcgill.ca/%7Eeuryd>>.

Digital ID Cards The next generation of 'smart' cards will have more than a one-track mind. *Wall Street Journal*, Jun. 25, 2001.

Tech Designers Rethink Toys: Make Them Fun. *Wall Street Journal*, Dec. 17, 2001.

PCT International Search Report and Written Opinion mailed Aug. 26, 2004, App. No. PCT/US04/08912, 7 pages.

Pajama Sam: No Need to Hide When It's Dark Outside Infogrames, Sep. 6, 2002.

"Raise High the 3D Roof Beam: Kids shape these PC games as they go along," by Anne Field, article as featured in *Business Week* 2001.

"212 Series of Decoders" HT12D/HT12F by HOLTEK—Product Specification (Nov. 2002).

"212" Series Encoders HT12A/HT12E by HOLTEK—Product Specification (Apr. 2000).

"Enchanted Spell-Casting Sorcerers Wand" by Ken Holt as featured on www.inventionconnection.com online advertisement (Dec. 2002).

"Micro Tilt Switch" D6B by Omron® Product Specification.

"Owl Magic Wand and Owl Magic Orb" Press Release by Emerald Forest Toys (Nov. 2001).

"Serial-in Parallel-out Shift Register" SN54/74LS164 by Motorola—Product Specification.

"The Magic Labs Conjure Wands" as featured on www.magic-lab.com Product Specification Dec. 2002.

"Tilt Switch" by Fuji & Co. as featured on www.fuji-piezo.com online advertisement May 2001.

"Toy Wand Manufacturer Selects MEMSIC Sensor: Magic Labs cuts costs with MEMSIC sensor" Press Release by MEMSIC, Inc. as featured on www.memsic.com May 2002.

"Get Bass," Videogame by Sega, The International Arcade Museum and the KLOV (accessed at http://www.arcade-museum.com/game_detail.php?game_id=7933 on Jul. 29, 2011).

"Glove-based input interfaces" Cyberglove/Cyberforce, <http://www.angelfire.com/ca7/mellott124/glove1.htm> (accessed on Jul. 29, 2011).

"Kirby Tilt 'n' Tumble 2" <http://www.unseen64.net/2008/04/08/koro-koro-kirby-2-kirby-tilt-n-tumble-2-gc-unreleased/>, Apr. 8, 2008 (accessed on Jul. 29, 2011).

Kirby Tilt 'n' Tumble (GCN-GBA Spaceworld 2001, You Tube Video, uploaded by adonjfv on Sep. 5, 2006 (accessed at <http://www.youtube.com/watch?v=5rLhlwp2iGk> on Sep. 7, 2011; digital video available upon request).

"MEMS enable smart golf clubs," *Small Times*, Jan. 6, 2005, accessed at <http://dpwsa.electroiq.com/index/display/semiconductors-article-display/269788/articles/small-times/consumer/2005/01/mems-enable-smart-golf-clubs.html> on Jul. 29, 2011.

"Miacomet and Interact Announce Agreement to Launch Line of Reel Feel™ Sport Controllers", PR Newswire (May 13, 1999), accessed at http://www.thefreelibrary.com/_print/PrintArticle.aspx?id=54621351 on Sep. 7, 2011.

"Emerald Forest Toys" [online] [retrieved on Sep. 14, 2005], retrieved from Internet <URL: http://www.pathworks.net/print_eft.html>.

"Gatemaster Features", internet article, Jul. 9, 1997; <http://web.archive.org/web/10070709135000/www.gatemaster.com/gmfeat.htm> (accessed on Dec. 11, 2008).

"Nintendo Wii Controller Invented by Americans: Midway Velocity Controller Technology Brief," You Tube Video presentation dated Jun. 28, 2000; uploaded by drjohnniefever on Sep. 8, 2007 (accessed at <http://www.youtube.com/watch?v=wjLhSrSxFNw> on Jun. 30, 2010; digital video available upon request).

ACT Labs, Miacomet Background, Jan. 27, 2001, http://web.archive.org/web/200101271753/http://www.act-labs.com/realfeel_background.htm, (accessed on Sep. 7, 2011).

- Agard, "Advances in Strapdown Inertial Systems," Agard Lecture Series No. 133, Advisory Group for Aerospace Research and Development, Neuilly-Sur-Seine (France) (1984).
- Santiago, "Extended Kalman filtering applied to a full accelerometer strapdown inertial measurement unit," M.S. Thesis, Massachusetts Institute of Technology, Dept. of Aeronautics and Astronautics, Santiago (1992).
- Ang, et al., "Design and Implementation of Active Error Canceling in Hand-held Microsurgical Instrument," Paper presented at 2001 IEEE/RSJ International Conference on Intelligent Robots and Systems (2001).
- Azuma et al., "Improving Static and Dynamic Registration in an Optical See-Through HMD," Paper Presented at SIGGRAPH '94 Annual Conference in Orlando, FL (1994).
- Azuma, et al., "A Frequency-Domain Analysis of Head-Motion Prediction," Paper Presented at SIGGRAPH '95 Annual Conference in Los Angeles, CA (1995).
- Bachmann et al., "Inertial and Magnetic Posture Tracking for Inserting Humans into Networked Virtual Environments," Virtual Reality Software and Technology archive, Paper Presented at ACM Symposium on Virtual Reality Software and Technology in Banff, Alberta, Canada (2001).
- Bachmann et al., "Orientation Tracking for Humans and Robots Using Inertial Sensors" Paper Presented at 199 International Symposium on Computational Intelligence in Robotics & Automation (CIRA '99) (1999).
- Ballagas, et al., "iStuff: A Physical User Interface Toolkit for Ubiquitous Computer Environments," Paper presented at SIGCHI Conference on Human Factors in Computing Systems (2003).
- Radica Legends of the Lake™ Instruction Manual (2003).
- BBN Report No. 7661, "Virtual Environment Technology for Training (VETT)," The Virtual Environment and Teleoperator Research Consortium (VETREC), pp. III-A-27 to III-A-40 (Mar. 1992).
- Behringer, "Improving the Registration Precision by Visual Horizon Silhouette Matching," Paper presented at First IEEE Workshop on Augmented Reality (1998).
- Behringer, "Registration for Outdoor Augmented Reality Applications Using Computer Vision Techniques and Hybrid Sensors," Paper presented at IEEE Virtual Reality (VR '99) Conference in Houston, TX (1999).
- Benbasat, et al., "An Inertial Measurement Framework for Gesture Recognition and Applications," Paper Presented at International Gesture Workshop on Gesture and Sign Languages in Human-Computer Interaction (GW '01), London, UK (2001).
- Bianchi, "A Tailless Mouse, New cordless Computer Mouse Invented by ArcanaTech," Inc.com, Jun. 1, 1992 (accessed at <http://www.inc.com/magazine/19920601/4115.html> on Jun. 17, 2010).
- Skien, Mike, "Nintendo Announces Wireless GBA Link", Bloomberg, Sep. 25, 2003 (accessed at <http://www.nintendoworldreport.com/news/9011>).
- Bona, et al., "Optimum Reset of Ship's Inertial Navigation System," IEEE Transactions on Aerospace and Electronic Systems, Abstract only (1965) (accessed at <http://oai.dtic.mil/oai/oai?verb=getRecord&metadataPrefix=html&identifier=AD0908193> on Jun. 17, 2010).
- Boser, "3-Axis Accelerometer with Differential Sense Electronics," Berkeley Sensor & Actuator Center, available at <http://www.eecs.berkeley.edu/about.boser/pdf/3axis.pdf> (1997).
- Boser, "Accelerometer Design Example: Analog Devices XL-05/5," Berkeley Sensor & Actuator Center, available at <http://www.eecs.berkeley.edu/about.boser/pdf/xl05.pdf> (1996).
- Britton et al., "Making Nested Rotations Convenient for the User," SIGGRAPH '78 Proceedings of the 5th Annual Conference on Computer Graphics and Interactive Techniques, vol. 12, Issue 3, pp. 222-227 (Aug. 1978).
- Brownell, Richard, Review: Peripheral-GameCube-G3 Wireless Controller, gamesarefun.com, Jul. 13, 2003 (accessed at <http://www.gamesarefun.com/gamesdb/perireview.php?perireviewid=1> on Jul. 29, 2011).
- Buchanan, Levi: "Happy Birthday, Rumble Pak," IGN.com, Apr. 3, 2008 (accessed at <http://retro.ign.com/articles/864/864231p1.html> on Jul. 29, 2011).
- Business Wire, "Feature/Virtual reality glasses that interface to Sega channel, Time Warner, TCI; project announced concurrent with COMDEX," Nov. 14, 1994 (accessed at http://findarticles.com/p/articles/mi_m0EIN/is_1994_Nov_14/ai_15923497/?tag=content;col.1 on Jul. 7, 2010).
- Business Wire, "Free-space 'Tilt' Game Controller for Sony Playstation Uses Scenix Chip; SX Series IC Processes Spatial Data in Real Time for On-Screen," Dec. 6, 1999 (accessed at http://findarticles.com/p/articles/mi_m0EIN/is_1999_Dec_6/ai_58042965/?tag=content;col.1 on Jul. 7, 2010).
- Business Wire, "Logitech MAGELLAN 3D Controller," Apr. 14, 1997 (accessed at http://www.thefreelibrary.com/_/print/PrintArticle.aspx?id=19306114 on Feb. 10, 2011).
- Business Wire, "Mind Path Introduces GYROPOINT RF Wireless Remote," Jan. 27, 2000 (accessed at <http://www.allbusiness.com/company-activities-management/operations-office/6381880-1.html> on Jun. 17, 2010).
- Business Wire, "Pegasus' Wireless PenCell Writes on Thin Air with ART's Handwriting Recognition Solutions," Business Editors/High Tech Writers Telecom Israel 2000 Hall 29, Booth 19-20, Nov. 7, 2000 (accessed at <http://www.highbeam.com/doc/1G1-66658008.html> on Jun. 17, 2010).
- Business Wire, "RPI ships low-cost pro HMD Plus 3D Mouse and VR PC graphics card system for CES," Jan. 9, 1995 (accessed at <http://www.highbeam.com/doc/1G1-16009561.html> on Jun. 17, 2010).
- Buxton et al., "A Study in Two-Handed Input," Proceedings of CHI '86, pp. 321-326 (1986) (accessed at <http://www.billbuxton.com/2hands.html> on Jul. 29, 2011).
- Buxton, Bill, A Directory of Sources for Input Technologies (last updated Apr. 19, 2001), <http://web.archive.org/web/20010604004849/http://www.billbuxton.com/InputSources.html> (accessed on Sep. 8, 2011).
- "Imp Coexists With Your Mouse," Byte, p. 255 (Jan. 1994).
- Canaday, "R67-26 The Lincoln Wand," IEEE Transactions on Electronic Computers, vol. EC-16, No. 2, p. 240 (Apr. 1967) (downloaded from IEEE Xplore on Jul. 7, 2010).
- Caruso et al., "A New Perspective on Magnetic Field Sensing," Sensors Magazine, Dec. 1, 1998 (accessed at <http://www.sensorsmag.com/sensors/electric-magnetic/a-new-perspective-magnetic-field-sensing-855> on Jun. 17, 2010).
- Caruso et al., "Vehicle Detection and Compass Applications using AMR Magnetic Sensors", Paper presented at 1999 Sensors Expo in Baltimore, Maryland (May 1999), available at <http://masters.donntu.edu.ua/2007/kita/gerus/library/amr.pdf>.
- Caruso, "Application of Magnetoresistive Sensors in Navigation Systems," Sensors and Actuators, SAE SP-1220, pp. 15-21 (Feb. 1997); text of article accessed at <http://www.ssec.honeywell.com/position-sensors/datasheets/sae.pdf>.
- Caruso, "Applications of Magnetic Sensors for Low Cost Compass Systems," Honeywell, SSEC, Paper presented at IEEE 2000 Position Location and Navigation Symposium (2000), accessed at <http://www.ssec.honeywell.com/magnetic/datasheets/lowcost.pdf>.
- Cheng, "Direct interaction with Large-Scale Display Systems using Infrared Laser Tracking Devices," Paper presented at Australasian Symposium on Information Visualisation, Adelaide, Australia (2003).
- CNET News.com, "Nintendo Wii Swings Into Action," May 25, 2006 (accessed at http://news.cnet.com/2300-1043_3-6070295-4.html on Aug. 5, 2011).
- Cutrone, "Hot products: Gyration GyroPoint Desk, GyroPoint Pro gyroscope-controlled wired and wireless mice," Results from the Comdex Show Floor, Computer Reseller News, Dec. 4, 1995 (accessed from LexisNexis research database on Feb. 17, 2011; see pp. 8 and 9 of reference submitted herewith).
- Immersion, "Immersion Ships New Wireless CyberGlove(R) II Hand Motion-Capture Glove; Animators, Designers, and Researchers Gain Enhanced Efficiency and Realism for Animation, Digital Prototyping and Virtual Reality Projects," Business Wire, Dec. 7, 2005 (available at <http://ir.immersion.com/releasedetail.cfm?releaseid=181278>).
- Deruyck, et al., "An Electromagnetic Position Sensor," Polhemus Navigation Sciences, Inc., Burlington, VT (Nov. 1973) (Abstract from DTIC Online).

- Dichtburn, "Camera in Direct3D" Toymaker (Feb. 6, 2005), <http://web.archive.org/web/20050206032104/http://toymaker.info/games/html/camera.html> (accessed on Jul. 29, 2011).
- Donelson, et al., "Spatial Management of Information", Proceedings of 1978 ACM SIGGRAPH Conference in Atlanta, Georgia, pp. 203-209 (1978).
- Ewalt, David M., "Nintendo's Wii is a Revolution," Review, Forbes.com, Nov. 13, 2006 (accessed at http://www.forbes.com/2006/11/13/wii-review-ps3-tech-media-cx_de_1113wii.html on Jul. 29, 2011).
- Fielder, Lauren "E3 2001: Nintendo unleashes GameCube software, a new Miyamoto game, and more," GameSpot, May 16, 2001 (accessed at http://www.gamespot.com/news/2761390/e3-2001-nintendo-unleashes-gamecube-software-a-new-miyamoto-game-and-more?tag=gallery_summary%3Bstory on Jul. 29, 2011).
- Foxlin, "Motion Tracking Requirements and Technologies," Chapter 7, from Handbook of Virtual Environment Technology, Kay Stanney, Ed., Lawrence Erlbaum Associates (2002) (extended draft version available for download at <http://www.intersense.com/pages/44/119/>).
- Frankle, "E3 2002: Roll O Rama," Roll-o-Rama GameCube Preview at IGN, May 23, 2002 (accessed at <http://cube.ign.com/articles/360/360662p1.html> on Sep. 7, 2011).
- Friedmann, et al., "Device Synchronization Using an Optimal Linear Filter," SI3D'92: Proceedings of the 1992 symposium on Interactive 3D graphics, pp. 57-62 (1992).
- Furniss, Maureen, "Motion Capture," posted at http://web.mit.edu/m-i-t/articles/index_furniss.html on Dec. 19, 1999; paper presented at the Media in Transition Conference at MIT on Oct. 8, 1999 (accessed on Sep. 8, 2011).
- gamecubicle.com News Article, Nintendo WaveBird Controller, http://www.gamecubicle.com/news-Nintendo_gamecube_wavebird_controller.htm, May 14, 2002 (accessed on Aug. 5, 2011).
- Heath, "Virtual Reality Resource Guide AI Expert," v9 n5 p. 32(14) (May 1994) (accessed at <http://ftp.hitl.washington.edu/scivw-ftp/commercial/VR-Resource-Guide.txt> on Jun. 17, 2010).
- HiBall-3100—"Wide-Area, High-Precision Tracker and 3D Digitizer," www.3rdtech.com/HiBall.htm (accessed on Jul. 29, 2011).
- Hinckley, "Synchronous Gestures for Multiple Persons and Computers," Paper presented at ACM UIST 2003 Symposium on User Interface Software & Technology in Vancouver, BC, Canada (Nov. 2003).
- Hinckley, et al., "A Survey of Design Issues in Spatial Input," Paper presented at 7th Annual ACM Symposium on User Interface Software and Technology (1994).
- Zowie Playsets, <http://www.piernot.com/proj/zowie/> (accessed on Jul. 29, 2011).
- Intersense, "InterSense Mobile Mixed Reality Demonstration," YouTube Video dated Oct. 2006 on opening screen; uploaded by InterSenseInc on Mar. 14, 2008 (accessed at http://www.youtube.com/watch?v=daVdzGK0nUE&feature=channel_page on Sep. 8, 2011; digital video available upon request).
- Intersense, "IS-900 Precision Motion Trackers," Jun. 14, 2002, <http://web.archive.org/web/20020614110352/http://www.isense.com/products/prec/is900/> (accessed on Sep. 8, 2011).
- Intersense, Inc., "Comparison of Intersense IS-900 System and Optical Systems," Whitepaper, Jul. 12, 2004., available at <http://www.jazdtech.com/techdirect/research/InterSense-Inc.htm?contentSetId=60032939&supplierId=60018705>.
- "Interview with Pat Gschy, the 'Real' Nintendo Wii Inventor," YouTube video uploaded by agbulls on Jan. 14, 2008 (accessed at <http://www.youtube.com/watch?v=oKtZysYGDLE> on Feb. 11, 2011; digital video available upon request).
- Jacob, "Human-Computer Interaction—Input Devices," ACM Computing Surveys, vol. 28, No. 1, pp. 177-179 (Mar. 1996); link to text of article provided at <http://www.cs.tufts.edu/~jacob/papers/>.
- Ju, et al., "The Challenges of Designing a User Interface for Consumer Interactive Television Consumer Electronics Digest of Technical Papers," IEEE 1994 International Conference on Volume , Issue , Jun. 21-23, 1994 pp. 114-115 (Jun. 1994) (downloaded from IEEE Xplore on Jul. 13, 2010).
- Kessler, et al., "The Simple Virtual Environment Library: an Extensible Framework for Building VE Applications," Presence, MIT Press (2000).
- Kohlhase, "NASA Report, The Voyager Neptune travel guide," Jet Propulsion Laboratory Publication 89-24, (Jun. 1989).
- Kormos, D.W., et al., "Intraoperative, Real-Time 3-D Digitizer for Neurosurgical Treatment and Planning," IEEE (1993) (Abstract only).
- Krumm et al., "How a Smart Environment can Use Perception," Paper presented at UBICOMP 2001 Workshop on Perception for Ubiquitous Computing (2001).
- Laser Tag: General info: History of Laser Tag, <http://lasertag.org/general/history.html> (accessed on Mar. 13, 2008; historical dates start on Mar. 1984).
- Laser Tag: Lazer Tag Branded Gear; last update Sep. 26, 2006, http://home.comcast.net/~ferret1963/Lazer_Tag_Brand.HTML (accessed on Mar. 13, 2008; historical dates start in 1986).
- Liu, et al., "Enhanced Fisher Linear Discriminant Models for Face Recognition," Paper presented at 14th International Conference on Pattern Recognition (ICPR'98), Queensland, Australia (Aug. 1998).
- Logitech's WingMan Cordless RumblePad Sets PC Gamers Free, Press Release, Sep. 2, 2001 (accessed at <http://www.logitech.com/en-us/172/1373> on Aug. 5, 2011).
- Louderback, J. "Nintendo Wii", Reviews by PC Magazine, Nov. 13, 2006 (accessed at <http://www.pcmag.com/article/print/193909> on Sep. 8, 2011).
- Maclean, "Designing with Haptic Feedback," Paper presented at IEEE Robotics and Automation (ICRA '2000) Conference in San Francisco, CA, Apr. 22-28, 2000.
- Marrin, "Possibilities for the Digital Baton as a General Purpose Gestural Interface," Late-Breaking/Short Talks, Paper presented at CHI97 Conference in Atlanta Georgia, Mar. 22-27, 1997 (accessed at <http://www.sigchi.org/chi97/proceedings/short-talk/tm.htm> on Aug. 5, 2011).
- Marrin, Teresa et al., "The Digital Baton: A Versatile Performance Instrument," Paper presented at International Computer Music Conference, Thessaloniki, Greece (1997) (text of paper available at <http://quod.lib.umich.edu/cgi/p/od/dod-idx?c=icmc;idno=bbp2372.1997.083>).
- Marrin, Teresa, "Toward an Understanding of Musical Gesture: Mapping Expressive Intention with the Digital Baton," Masters Thesis, Massachusetts Institute of Technology, Program in Media Arts and Sciences (1996).
- Marti et al., "Biopsy navigator: a smart haptic interface for interventional radiological gestures" Proceedings of the Computer Assisted Radiology and Surgery (CARS 2003) Conference, International Congress Series, vol. 1256, pp. 788-793 (2003) (e-copy of text of paper available at <http://infoscience.epfl.ch/record/29966/files/CARS03-GM.pdf>).
- Masliah, "Measuring the Allocation of Control in 6 Degree of Freedom Docking Experiment," Paper presented at SIGCHI Conference on Human Factors in Computing Systems, The Hague, Netherlands (2000).
- Maybeck, "Stochastic Models, Estimation and Control," vol. 1, Chapter 1, Introduction (1979).
- Mizell, "Using Gravity to Estimate Accelerometer Orientation," Proceedings of the Seventh IEEE International Symposium on Wearable Computers (ISWC '03), IEEE Computer Society (2003).
- Moser, "Low Budget Inertial Navigation Platform (2000)," www.tmoser.ch/typo3/11.0.html (accessed on Jul. 29, 2011).
- Mulder, "Human movement tracking technology," Technical Report, NSERC Hand Centered Studies of Human Movement project, available through anonymous ftp in fas.sfu.ca/pub/cs/graphics/vmi/HMTT.pub.ps.Z, Burnab, B.C., Canada: Simon Fraser University (Jul. 1994).
- "The N.I.C.E. Project," YouTube video uploaded by evltube on Nov. 20, 2007 (accessed at <http://www.youtube.com/watch?v=ihGXa21qLms> on Sep. 8, 2011; digital video available upon request).
- Naimark, et al., "Encoded LED System for Optical Trackers," Paper presented at Fourth IEEE and ACM International Symposium on Mixed and Augmented Reality (ISMAR 2005), Oct. 5-8, 2005, Vienna Austria (2005) (electronic version of text of paper available for download at <http://www.intersense.com/pages/44/129/>).

- Navarrete, et al., "Eigenspace-based Recognition of Faces: Comparisons and a new Approach," Paper Presented at 11th International Conference on Image Analysis and Processing (2001).
- News Article, "New Game Controllers Using Analog Devices' G-Force Tilt to be Featured at E3", Norwood, MA (May 10, 1999) (accessed at http://www.thefreelibrary.com/_/print/PrintArticle.aspx?id=54592268 on Jun. 17, 2011).
- PR Newswire, "Five New Retailers to Carry Gyration's Gyropoint Point and Gyropoint Pro," Jul. 8, 1996 (accessed at http://www.thefreelibrary.com/_/print/PrintArticle.aspx?id=54592268 on Jun. 18, 2010).
- PR Newswire, "Three-Axis MEMS-based Accelerometer From STMicroelectronics Targets Handheld Terminals," Feb. 18, 2003 (accessed at http://www.thefreelibrary.com/_/print/PrintArticle.aspx?id=54592268 on Jun. 3, 2011).
- Nintendo, Game Boy Advance SP System Instruction Booklet (2003).
- Nintendo, Nintendo Game Boy Advance System Instruction Booklet (2001-2003).
- Nintendo, Nintendo Game Boy Advance Wireless Adapter.
- Odell, "An Optical Pointer for Infrared Remote Controllers," (1995) (downloaded from IEEE Xplore on Jul. 7, 2010).
- Ojeda, et al., "No GPS? No Problem!" University of Michigan Develops Award-Winning Personal Dead-Reckoning (PDR) System for Walking Users, available at http://www.engine.umich.edu/research/mrl/urpr/In_Press/P135.pdf, (2004 or later).
- Ovaska, "Angular Acceleration Measurement: A Review," Paper presented at IEEE Instrumentation and Measurement Technology Conference, St. Paul, MN, May 18-21, 1998.
- Pai, et al., "The Tango: A Tangible Tangoreceptive Whole-Hand Interface," Paper presented at Joint Eurohaptics and IEEE Symposium on Haptic Interfaces for Virtual Environment and Teleoperator Systems, Pisa, Italy, Mar. 18-20, 2005.
- Paley, W. Bradford, "Interaction in 3D Graphics," SIGGRAPH Computer Graphics Newsletter, col. 32, No. 4 (Nov. 1998) (accessed at <http://www.siggraph.org/publications/newsletter/v32n4/contributions/paley.html> on Aug. 2, 2011).
- Paradiso, Joseph A., "The Brain Opera Technology: New Instruments and Gestural Sensors for Musical Interaction and Performance" (Nov. 1998) (available at http://pubs.media.mit.edu/pubs/papers/98_3_JNMR_Brain_Opera.pdf).
- PC World, "The 20 Most Innovative Products of the Year," Dec. 27, 2006 (accessed at <http://www.pcworld.com/printable/article/id,128176/printable.html> on Aug. 2, 2011).
- PCTracker, Technical Overview, available at http://www.est-kl.com/fileadmin/media/pdf/InterSense/PCTracker_Tech_Overview.pdf (date unknown).
- Perry, Simon, "Nintendo to Launch Wireless Game Boy Adaptor," Digital Lifestyles, <http://digital-lifestyles.info/2003/09/26/nintendo-to-launch-wireless-game-boy-adaptor/>, Sep. 26, 2003 (accessed on Jul. 29, 2011).
- Phillips, "TECHWATCH: On the Right Track: A unique optical tracking system gives users greater freedom to explore virtual worlds," Computer Graphics World, vol. 23, Issue 4 (Apr. 2000).
- Pierce et al., "Image Plane Interaction Techniques in 3D Immersive Environments," Paper presented at 1997 symposium on Interactive 3D graphics, Providence, RI (1997).
- Piyabongkarn, "The Development of a MEMS Gyroscope for Absolute Angle Measurement," Dissertation, Univ. Minnesota, Nov. 2004 (Abstract only).
- Polhemus, "Polhemus 3Space Fastrak devices" (image) (2001).
- PowerGlove product Program Guide, Mattel, 1989 (Text of Program Guide provided from http://hiwaay.net/~lkseitz/cvtg/power_glove.shtml; the text was typed in by Lee K. Sietz; document created Aug. 25, 1988; accessed on Aug. 2, 2011).
- Rekimoto, "Tilting Operations for Small Screen Interfaces," Tech Note presented at 9th Annual ACM Symposium on User Interface Software and Technology (UIST'96) (1996) (available for download at <http://www.sonycs.jp/person/rekimoto/papers/uist96.pdf>).
- Roberts, "The Lincoln Wand," 1966 Proceedings of the Fall Joint Computer Conference (1966), available for electronic download at <http://www.computer.org/portal/web/csdl/doi/10.1109/AFIPS.1966.105>.
- Roetenberg, "Inertial and magnetic sensing of human motion," Thesis, University of Twente (2006).
- Roetenberg, et al., "Inertial and Magnetic Sensing of Human Movement Near Ferromagnetic Materials," Paper presented at Second IEEE and ACM International Symposium on Mixed and Augmented Reality, Mar. 2003 (available at <http://www.xsens.com/images/stories/PDF/Inertial%20and%20magnetic%20sensing%20of%20human%20movement%20near%20ferromagnetic%20materials.pdf>).
- Rolland, et al., "A Survey of Tracking Technology for Virtual Environments," University of Central Florida, Center for Research and Education in Optics Lasers (CREOL) (2001).
- Satterfield, Shane, "E3 2002: Nintendo announces new GameCube games," GameSpot, <http://www.gamespot.com/gamecube/action/rollorama/news/2866974/e3-2002-nintendo-announces-new-gamecube-games>, May 21, 2002 (accessed on Aug. 11, 2011).
- Schofield, Jack et al., Games reviews, "Coming up for airpad," The Guardian (Feb. 3, 2000) (accessed at <http://www.guardian.co.uk/technology/2000/feb/03/online-supplement5/print> on Jun. 18, 2010).
- Shoemake, Ken, "Quaternions," available online at <http://campar.in.tum.de/twiki/pub/Chair/DwarfTutorial/quatu.pdf> (date unknown).
- Smartswing, "SmartSwing: Intelligent Golf Clubs that Build a Better Swing," <http://web.archive.org/web/20040728221951/http://www.smartswinggolf.com/> (accessed on Sep. 8, 2011).
- Smartswing, "The SmartSwing Learning System Overview," Apr. 26, 2004, <http://web.archive.org/web/2004426215355/http://www.smartswinggolf.com/tls/index.html> (accessed on Jul. 29, 2011).
- Smartswing, "The SmartSwing Learning System: How it Works," 3 pages, Apr. 26, 2004, http://web.archive.org/web/20040426213631/http://www.smartswinggolf.com/tls/how_it_works.html (accessed on Jul. 29, 2011).
- Smartswing, "The SmartSwing Product Technical Product: Technical Information," Apr. 26, 2004, http://web.archive.org/web/20040426174854/http://www.smartswinggolf.com/products/technical_info.html (accessed on Jul. 29, 2011).
- Sulic, "Logitech Wingman Cordless Rumblepad Review," Gear Review at IGN, Jan. 14, 2002 (accessed at <http://gear.ign.com/articles/317/317472p1.html> on Aug. 1, 2011).
- Sutherland, "A Head-Mounted Three Dimensional Display," Paper presented at AFIPS '68 Fall Joint Computer Conference, Dec. 9-11, 1968, electronic paper available at www.cise.ufl.edu/~lok/teaching/dcvef05/papers/sutherland-headmount.pdf.
- Sutherland, Ivan E., "Sketchpad: A Man-Machine Graphical Communication System," Proceedings of the AFIPS Spring Joint Computer Conference, Detroit, Michigan, May 21-23, 1963, pp. 329-346 (source provided is reprinting of text accessed at <http://www.guidebookgallery.org/articles/sketchpadamanmachinegraphicalcommunicationsystem> on Sep. 8, 2011).
- Timmer, "Modeling Noisy Time Series: Physiological Tremor," International Journal of Bifurcation and Chaos, vol. 8, No. 7 (1998).
- Timmer, et al., "Pathological Tremors: Deterministic Chaos or Non-linear Stochastic Oscillators?" Chaos, vol. 10, No. 1 pp. 278-288 (Mar. 2000).
- Timmer, et al., "Cross-Spectral Analysis of Tremor Time Series," International Journal of Bifurcation and Chaos, vol. 10, No. 11 pp. 2595-2610 (2000); electronic text available at http://www.fdmold.uni-freiburg.de/groups/timeseries/tremor/pubs/cs_review.pdf.
- Timmer, et al., Cross-Spectral Analysis of Physiological Tremor and Muscle Activity: II Application to Synchronized Electromyogram, Biological Cybernetics, vol. 78 (1998) (obtained from <http://arxiv.org/abs/chao-dyn/9805012>).
- Titterton et al., "Strapdown Inertial Navigation Technology," Peter Peregrinus Ltd., pp. 1-56 and pp. 292-321 (1997).
- Ulanoff, Lance, "Nintendo's Wii is the Best Product Ever," PC Magazine, Jun. 21, 2007 (accessed at http://www.pcmag.com/print_article2/0,1217,a=210070,00.asp?hidPrint=true on Aug. 1, 2011).
- UNC Computer Science Department, "News & Notes from Sitterson Hall," UNC Computer Science, Department Newsletter, Issue 24, Spring 1999 (Apr. 1999) (accessed at <http://www.cs.unc.edu/NewsAndNotes/Issue24/> on Jun. 18, 2010).

- Urban, "BAA 96-37 Proposer Information," DARPA/ETO (1996) (accessed at [http://www.fbodaily.com/cbd/archive/1996/08\(August\)19-Aug-1996/Aso1001.htm](http://www.fbodaily.com/cbd/archive/1996/08(August)19-Aug-1996/Aso1001.htm) on Jul. 27, 2010).
- Villoria, Gerald, "Hands on Roll-O-Rama Game Cube," Game Spot, http://www.gamespot.com/gamecube/action/rollorama/news.html?sid=2868421&com_act=convert&om_clk=newsfeatures&tag=newsfeatures;title;l&m, May 29, 2002 (accessed on Jul. 29, 2011).
- Wang, et al., "Tracking a Head-Mounted Display in a Room-Sized Environment with Head-Mounted Cameras," Paper presented at SPIE 1990 Technical Symposium on Optical Engineering and Photonics in Aerospace Sensing (1990).
- Ward, et al., "A Demonstrated Optical Tracker With Scalable Work Area for Head-Mounted Display Systems," Paper presented at 1992 Symposium on Interactive 3D Graphics (1992).
- Welch et al., "Complementary Tracking and Two-Handed Interaction for Remote 3D Medical Consultation with a PDA," Paper presented at Trends and Issues in Tracking for Virtual Environments Workshop at IEEE Virtual Reality 2007 Conference (2007), available at http://www.cs.unc.edu/~welch/media/pdf/Welch2007_TwoHanded.pdf.
- Welch et al., "Motion Tracking: No Silver Bullet, but a Respectable Arsenal," IEEE Computer Graphics and Applications, vol. 22, No. 6, pp. 24-38 (2002), available at http://www.cs.unc.edu/~tracker/media/pdf/cga02_welch_tracking.pdf.
- Welch, "Hawkeye Zooms in on Mac Screens with Wireless Infrared Penlight Pointer," MacWeek, May 3, 1993 (excerpt of article accessed at <http://www.accessmylibrary.com/article/print/1G1-13785387> on Jun. 18, 2010).
- Welch, et al., "SCAAT: Incremental Tracking with Incomplete Information," Paper presented at SIGGRAPH 97 Conference on Computer Graphics and Interactive Techniques (1997), available at <http://www.cs.unc.edu/~welch/media/pdf/scaat.pdf>.
- Welch, et al., "The HiBall Tracker: High-Performance Wide-Area Tracking for Virtual and Augmented Environments," Paper presented at 1999 Symposium on Virtual Reality Software and Technology in London, Dec. 20-22, 1999, available at http://www.cs.unc.edu/~welch/media/pdf/VRST99_HiBall.pdf.
- Wiley, M., "Nintendo Wavebird Review," Jun. 11, 2002, <http://gear.ign.com/articles/361/361933p1.html> (accessed on Aug. 1, 2011).
- Williams, et al., "Physical Presence: Palettes in Virtual Spaces," Society of Photo-Optical Instrumentation Engineers (SPIE) Conference Series, vol. 3639, No. 374-384 (May 1999), available at http://www.fakespacelabs.com/papers/3639_46_LOCAL.pdf.
- Wilson, "Wireless User Interface Devices for Connected Intelligent Environments," <http://research.microsoft.com/en-us/um/people/awilson/publications/old/ubicomp%202003.pdf> (2003).
- Wilson "WorldCursor: Pointing in Intelligent Environments with the World Cursor," <http://www.acm.org/uist/archive/adjunct/2003/pdf/demos/d4-wilson.pdf> (2003).
- Wilson et al., "Gesture Recognition Using the Xwand," http://www.ri.cmu.edu/pub_files/pub4/wilson_daniel_h_2004_1/wilson_daniel_h_2004_1.pdf (2004).
- Wilson et al., "Xwand: UI for Intelligent Spaces," Paper presented at CHI 2003 Conference, Ft. Lauderdale, FL, Apr. 5-10, 2003, available at <http://research.microsoft.com/en-us/um/people/awilson/publications/WilsonCHI2003/CHI%202003%20XWand.pdf> (2003).
- Wormell et al., "Advancements in 3D Interactive Devices for Virtual Environments," Presented at the Joint International Immersive Projection Technologies (IPT)/Eurographics Workshop on Virtual Environments (EGVE) 2003 Workshop, Zurich, Switzerland, May 22-23, 2003 (available for download at <http://www.intersense.com/pages/44/123/>) (2003).
- Wormell, "Unified Camera, Content and Talent Tracking in Digital Television and Movie Production," Presented at NAB 2000, Las Vegas, NV, Apr. 8-13, 2000 (available for download at <http://www.intersense.com/pages/44/116/>) (2003).
- You, et al., "Hybrid Inertial and Vision Tracking for Augmented Reality Registration," <http://graphics.usc.edu/cgit/pdf/papers/Vr1999.PDF> (1999).
- You, et al., "Orientation Tracking for Outdoor Augmented Reality Registration," IEE Computer Graphics and Applications, IEEE, vol. 19, No. 6, pp. 36-42 (Nov. 1999).
- Zhai, "User Performance in Relation to 3D Input Device Design," Computer Graphics 32(4), pp. 50-54, Nov. 1998; text downloaded from <http://www.almaden.ibm.com/u/zhai/papers/siggraph/final.html> on Aug. 1, 2011.
- Immersion CyberGlove product, Immersion Corporation, <http://www.cyberglovesystem.com> (2001).
- Intersense, "InterSense Inc., The New Standard in Motion Tracking," Mar. 27, 2004, <http://web.archive.org/web/2004040500550Z/http://intersense.com> (accessed on May 19, 2009).
- PowerGlove product Program Guide, Mattel, 1989.
- VTI, Mindflux-Vti CyberTouch, <http://www.mindflux.com/au/products/vti/cybertouch.html> (1996).
- Sega/Sports Sciences, Inc., "Batter Up, It's a Hit," Instruction Manual, Optional Equipment Manual (1994).
- Sega/Sports Sciences, Inc., "Batter Up, It's a Hit," Photos of baseball bat (1994).
- Briefs, (New & Improved), (Brief Article), PC Magazine, Oct. 26, 1993.
- Foremski, T., "Remote Control Mouse Aims at Interactive TV" Electronics Weekly, Mar. 9, 1994.
- Ji, H. "Study on the Infrared Remote-Control Lamp-Gesture Device," Yingyong Jiguang/Applied Laser Technology, v. 17, n. 5, p. 225-227, Language: Chinese-Abstract only, Oct. 1997.
- "At-home fishing," <http://www.virtualpet.com/vp/media/fishing/homef.jpg> (accessed on Jan. 14, 2010).
- Traq 3D, "Healthcare," <http://www.traq3d.com/Healthcare/Healthcare.aspx> (accessed on Jan. 21, 2010).
- Reunert, "Fiber-Optic Gyroscopes: Principles and Applications," Sensors, Aug. 1993, pp. 37-38.
- Yun et al., "Recent Developments in Silicon Microaccelerometers," Sensors, 9(10) University of California at Berkeley, Oct. 1992.
- Link, "Field-Qualified Silicon Accelerometers from 1 Milli g to 200,000 g," Sensors, Mar. 1993.
- Laughlin et al., "Inertial Angular Rate Sensors: Theory and Applications," Sensors Magazine Oct. 1992.
- Kennedy, P.J. "Hand-held Data Input Device," IBM Technical Disclosure Bulletin, vol. 26, No. 11, pp. 5826-5827, Apr. 1984.
- Hind, Nicholas, "Cosmos: A composition for Live Electronic Instruments Controlled by the Radio Baton and Computer Keyboard (Radio Baton and Magic Glove)," A Final Project Submitted to the Department of Music of Stanford University in Partial Fulfillment of the Requirements for the Degree of Doctor Musical Arts/UMI Microform 9837187, Jan. 1998.
- Jiang, "Capacitive position-sensing interface for micromachined inertial sensors," Dissertation at Univ. of Cal. Berkeley, 2003.
- Lee et al., "Innovative Estimation Method with Measurement Likelihood for all-Accelerometer Type Inertial Navigation System," IEEE Transactions on Aerospace and Electronic Systems, vol. 38, No. 1, Jan. 2002.
- Maggioni, C., "A novel gestural input device for virtual reality," IEEE Virtual Reality Annual International Symposium (Cat. No. 93CH3336-5), 118-24, 1993.
- Morgan, C., "Still chained to the overhead projector instead of the podium," (TV Interactive Corp's LaserMouse Remote Pro infrared mouse) (clipboard) (brief article) (product announcement) Government Computer News, Jun. 13, 1994.
- Business Wire, "InterSense Inc. Launches InertiaCube2—The World's Smallest Precision Orientation Sensor with Serial Interface," Aug. 14, 2001 (accessed at <http://www.highbeam.com/doc/1G1-77183067.html/print> on Sep. 7, 2011).
- Sayed, "A Framework for State-Space Estimation with Uncertain Models," IEEE Transactions on Automatic Control, vol. 46, No. 7, Jul. 2001.
- Richard Marks. (Jan. 21, 2004) (Windows Media v7). EyeToy: A New Interface for Interactive Entertainment, Stanford University (accessed at <http://lang.stanford.edu/courses/ee380/2003-2004/040121-ee380-100.wmv> on Sep. 7, 2011; digital video available upon request).
- "Eyeto demo from 2000—3d motion cap with a hand-held wand," YouTube Video uploaded by MuchRockness on Mar. 14, 2010 (accessed at <http://www.youtube.com/watch?NR=1&v=mheOtyWNjV0> on Sep. 6, 2011; digital video available upon request).

- "Sony PS2 Motion Controller 5 years ago (2004)," YouTube Video uploaded by r1oot on Jul. 8, 2009 (accessed at <http://www.youtube.com/watch?v=JbSzmRt7HhQ&feature=related> on Sep. 6, 2011; digital video available upon request).
- Durlach, et al., "Virtual Reality: Scientific and Technological Challenges," National Academy Press (1995).
- Gelmis, J., "Ready to Play, The Future Way," Buffalo News, Jul. 23, 1996 (accessed from LexisNexis research database on Sep. 6, 2011).
- Virtual Fishing, Operational Manual, 2 pages, Tiger Electronics, Inc. (1998).
- "ASCII Entertainment releases the Grip," ASCII Entertainment Software—Press News—Coming Soon Magazine, May 1997 (electronic version accessed at http://www.csoon.com/issue25/p_ascii4.htm on Sep. 6, 2011).
- Analog Devices, "ADXL150/ADXL250, ± 5 g to ± 50 g, Low Noise, Low Power, Single/Dual Axis iMEMS® Accelerometers," Data Sheet, Rev. 0 (1998).
- Rothman, Wilson, "Wii-mote Prototype Designer Speaks Out, Shares Sketchbook," Gizmodo.com, Aug. 30, 2007 (accessed at <http://gizmodo.com/gadgets/exclusive/wii+mote-prototype-designer-speaks-out-shares-sketchbook-295276.php> on Aug. 31, 2011).
- Rothman, Wilson, "Unearthed: Nintendo's Pre-Wiimote Prototype," gizmodo.com, Aug. 29, 2007 (accessed at <http://gizmodo.com/gadgets/exclusive/unearthed-nintendo-2001-prototype-motion+sensing-one+headed-controller-by-gyration-294642.php> on Aug. 31, 2011).
- Miller, Ross, "Joystiq interview: Patrick Goschy talks about Midway, tells us he 'made the Wii'," Joystiq.com, Jan. 16, 2008 (accessed at <http://www.joystiq.com/2008/01/16/joystiq-interview-patrick-goschy-talks-about-midway-tells-us-h/> on Aug. 31, 2011).
- "Wii Mailbag," IGN.com, Jan. 26, 2006 (accessed at <http://uk.wii.ign.com/mail/2006-01-26.html> on Aug. 31, 2011).
- Kosak, Dave, "Mind-Numbing New Interface Technologies," Gamespy.com, Feb. 1, 2005 (accessed at <http://www.gamespy.com/articles/584/584744p1.html> on Aug. 31, 2011).
- "The Big Ideas Behind Nintendo's Wii," Business Week, Nov. 16, 2006 (accessed at http://www.businessweek.com/technology/content/nov2006/tc20061116_750580.htm on Aug. 31, 2011).
- Crecente, Brian, "Motion Gaming Gains Momentum," kotaku.com, Sep. 17, 2010 (accessed at <http://kotaku.com/5640867/motion-gaming-gains-momentum> on Aug. 31, 2011).
- Miller, Paul, "Exclusive shots of Goschy's prototype 'Wiimote' controllers," Engadget, Jan. 15, 2008 (accessed at <http://www.engadget.com/2008/01/15/exclusive-shots-of-goschys-prototype-wiimote-controllers/> on Aug. 31, 2011).
- ASCII, picture of one-handed controller, 2 pages, Feb. 6, 2006.
- Airpad Motion Reflex Controller for Sony Playstation—Physical Product, (AirPad Corp. 2000).
- AirPad Controller Manual, (AirPad Corp. 2000).
- "Harry Potter Magic Spell Challenge," Tiger Electronics, 2001.
- Acar, et al., "Experimental evaluation and comparative analysis of commercial variable-capacitance MEMS accelerometers," Journal of Micromechanics and Microengineering, vol. 13 (1), pp. 634-645, May 2003.
- Achenbach, "Golf's New Measuring Stick," Golfweek, Jun. 11, 2005.
- Algrain, "Estimation of 3-D Angular Motion Using Gyroscopes and Linear Accelerometers," IEEE Transactions on Aerospace and Electronic Systems, vol. 27, No. 6, pp. 910-920 (Nov. 1991).
- Algrain, et al., "Accelerometer Based Line-of-Sight Stabilization Approach for Pointing and Tracking system," Second IEEE Conference on Control Applications, Sep. 13-16, 1993 Vancouver, B.C., pp. 159-163 (1993).
- Algrain, et al., "Interlaced Kalman Filtering of 3-D Angular Motion Based on Euler's Nonlinear Equations," IEEE Transactions on Aerospace and Electronic Systems, vol. 30, No. 1 (Jan. 1994).
- Allen, et al., "A General Method for Comparing the Expected Performance of Tracing and Motion Capture Systems," {VRST} '05: Proceedings of the ACM Symposium on Virtual Reality Software and Technology, Nov. 7-9, 2005 Monterey, California (2005).
- Allen, et al., "Tracking: Beyond 15 Minutes of Thought," SIGGRAPH 2001 Course 11 (2001).
- Analog Devices "ADXL202E Low-Cost ± 2 g Dual-Axis Accelerometer with Duty Cycle Output" Data Sheet, Rev. A (2000).
- Analog Devices "ADXL50 Single Axis Accelerometer" Data Sheet, Rev. B (1996), available at <http://www.analog.com/en/obsolete/adxl50/products/product.html>.
- Analog Devices "MicroConverter®, Multichannel 12-Bit ADC with Embedded Flash MCU, ADuC812" Data Sheet (2003), available at http://www.analog.com/static/imported-files/data_sheets/ADUC812.pdf.
- Analog Devices "ADXL330 Small, Low Power, 3-Axis ± 2 g iMEMS Accelerometer" Data Sheet, Rev. PrA (2005).
- Analog Devices "ADXL50 Monolithic Accelerometer with Signal Conditioning" Data Sheet (1996).
- Analog Devices "ADXRS150 $\pm 150^\circ/\text{s}$ Single Chip Yaw Rate Gyro with Signal Conditioning" Data Sheet, Rev. B (2004).
- Analog Devices "ADXRS401 $\pm 75^\circ/\text{s}$ Single Chip Yaw Rate Gyro with Signal Conditioning" Data Sheet, Rev. O (2004).
- Ang, et al., "Design of All-Accelerometer Inertial Measurement Unit for Tremor Sensing in Hand-held Microsurgical Instrument," Proceedings of the 2003 IEEE International Conference on Robotics & Automation, Sep. 14-19, 2003, Taipei, Taiwan, pp. 1781-1786 (2003).
- Apostolyuk, Vladislav, "Theory and Design of Micromechanical Vibratory Gyroscopes," MEMS/NEMS Handbook, Springer, vol. 1, pp. 173-195 (2006).
- Ascension Technology, 6D Bird Class B Installation and Operation Guide (2003).
- Ator, "Image-Velocity Sensing with Parallel-Slit Reticles," Journal of the Optical Society of America, vol. 53, No. 12, pp. 1416-1422 (Dec. 1963).
- Azarbayejani, et al., "Real-Time 3-D Tracking of the Human Body," M.I.T. Media Laboratory Perceptual Computing Section Technical Report No. 374, Appears in Proceedings of Image'Com 96, Bordeaux, France, May 1996.
- Azarbayejani, et al., "Visually Controlled Graphics," M.I.T. Media Laboratory Perceptual Computing Section Technical Report No. 374, Appears in IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 15, No. 6, pp. 602-605 (Jun. 1993).
- Azuma et al., "Making Augmented Reality Work Outdoors Requires Hybrid Tracking," Proceedings of the International Workshop on Augmented Reality, San Francisco, CA, Nov. 1, 1998.
- Azuma, "Predictive Tracking for Augmented Reality," Ph.D. Dissertation, University of North Carolina at Chapel Hill, Department of Computer Science (1995).
- Azuma, et al., "A motion-stabilized outdoor augmented reality system," Proceedings of IEEE Virtual Reality '99, Houston, TX, Mar. 13-17, 1999, pp. 252-259.
- Bachmann, "Inertial and Magnetic Angle Tracking of Limb Segments for Inserting Humans into Synthetic Environments," Dissertation, Naval Postgraduate School, Monterey, CA (Dec. 2000).
- Baker et al., "Active Multimodal Control of a 'Floppy' Telescope Structure," Proc. SPIE, vol. 4825, pp. 74-81 (2002).
- Balakrishnan, "The Rockin' Mouse: Integral 3D Manipulation on a Plane," Published in Proceedings of 1997 ACM Conference on Human Factors in Computing Systems (CHI'97), pp. 311-318, (1997).
- Baraff, "An Introduction to Physically Based Modeling: Rigid Body Simulation I—Unconstrained Rigid Body Dynamics," SIGGRAPH 97 Course Notes, Robotics Institute, Carnegie Mellon University (1997).
- Baudisch, et al., "Soap: a Pointing Device that Works in Mid-air," Proc. UIST'06, Oct. 15-18, 2006, Montreux, Switzerland (2006).
- BEI Gyrochip™ Model QRS11 Data Sheet, BEI Systron Donner Inertial Division, BEI Technologies, Inc., (Sep. 1998).
- Benbasat, "An Inertial Measurement Unit for User Interfaces," Massachusetts Institute of Technology Masters Thesis, (Sep. 2000).
- Bhatnagar, "Position trackers for Head Mounted Display systems: A survey" (Technical Report), University of North Carolina at Chapel Hill (Mar. 1993).
- Bishop, "The Self-Tracker: A Smart Optical Sensor on Silicon," Ph.D. Dissertation, Univ. of North Carolina at Chapel Hill (1984).
- Borenstein, et al., "Where am I? Sensors and Methods for Mobile Robot Positioning" (1996).


- Bowman, et al., "An Introduction to 3-D User Interface Design," MIT Presence, vol. 10, No. 1, pp. 96-108 (Feb. 2001).
- Britton, "A Methodology for the Ergonomic Design of Interactive Computer Graphic Systems, and its Application to Crystallography" Ph.D. Dissertation, University of North Carolina at Chapel Hill, Dept. of Computer Science (1977).
- Buxton, Bill, "Human input/output devices," In M. Katz (ed.), *Technology Forecast: 1995*, Menlo Park, CA: Price Waterhouse World Firm Technology Center, pp. 49-65 (1994).
- Cho et al., "Magic Wand: A Hand-Drawn Gesture Input Device in 3-D Space with Inertial Sensors," Proceedings of the 9th Intl Workshop on Frontiers in Handwriting Recognition (IWFHR-9 2004), IEEE (2004).
- Cooke, et al., "NPSNET: Flight simulation dynamic modeling using quaternions," Presence, vol. 1, No. 4, pp. 404-420, (Jan. 25, 1994).
- CSIDC Winners—"Tablet-PC Classroom System Wins Design Competition," IEEE Computer Society Press, vol. 36, Issue 8, pp. 15-18, IEEE Computer Society, Aug. 2003.
- Emura, et al., "Sensor Fusion based Measurement of Human Head Motion," 3rd IEEE International Workshop on Robot and Human Communication (1994).
- Foxlin et al., "An Inertial Head-Orientation Tracker with Automatic Drift Compensation for Use with HMD's," Proceedings of the 1994 Virtual Reality Software and Technology Conference, Aug. 23-26, 1994, Singapore, pp. 159-173 (1994).
- Foxlin et al., "Miniature 6-DOF Inertial System for Tracking HMDs," SPIE vol. 3362, Helmet and Head-Mounted Displays III, AeroSense 98, Orlando, FL, Apr. 13-14, 1998.
- Foxlin et al., "WearTrack: A Self-Referenced Head and Hand Tracker for Wearable Computers and Portable VR," Proceedings of International Symposium on Wearable Computers (ISWC 2000), Oct. 16-18, 2000, Atlanta, GA (2000).
- Foxlin, "Head-tracking Relative to a Moving Vehicle or Simulator Platform Using Differential Inertial Sensors," Proceedings of Helmet and Head-Mounted Displays V, SPIE vol. 4021, AeroSense Symposium, Orlando, FL, Apr. 24-25, 2000.
- Foxlin, "Inertial Head Tracker Sensor Fusion by a Complementary Separate-bias Kalman Filter," Proceedings of the IEEE 1996 Virtual Reality Annual International Symposium, pp. 185-194, 267 (1996).
- Foxlin et al., "FlightTracker: A Novel Optical/Inertial Tracker for Cockpit Enhanced Vision, Symposium on Mixed and Augmented Reality," Proceedings of the 3rd IEEE/ACM International Symposium on Mixed and Augmented Reality (ISMAR 2004), Nov. 2-5, 2004, Washington, D.C.
- Foxlin, "Generalized architecture for simultaneous localization, auto-calibration, and map-building," IEEE/RSJ Conf. on Intelligent Robots and Systems (IROS 2002), Oct. 2-4, 2002, Lausanne, Switzerland.
- Foxlin, "Pedestrian Tracking with Shoe-Mounted Inertial Sensors," IEEE Computer Graphics and Applications, vol. 25, No. 6, pp. 38-46, (2005).
- Foxlin, et al., "Constellation™: A Wide-Range Wireless Motion-Tracking System for Augmented Reality and Virtual Set Applications," ACM SIGGRAPH 98, Orlando, Florida, Jul. 19-24, 1998.
- Foxlin, et al., "Miniaturization, Calibration & Accuracy Evaluation of a Hybrid Self-Tracker," IEEE/ACM International Symposium on Mixed and Augmented Reality (ISMAR 2003), Oct. 7-10, 2003, Tokyo, Japan.
- Foxlin, et al., "VIS-Tracker: A Wearable Vision-Inertial Self-Tracker," IEEE VR2003, Mar. 22-26, 2003, Los Angeles, CA.
- Friedmann, et al., "Synchronization in virtual realities," M.I.T. Media Lab Vision and Modeling Group Technical Report No. 157, Jan. 1991 to appear in Presence, vol. 1, No. 1, MIT Press, Cambridge, MA.
- FrontSide Field Test, "Get This!" Golf Magazine, Jun. 2005, p. 36.
- Fuchs, Eric, "Inertial Head-Tracking," MS Thesis, Massachusetts Institute of Technology, Dept. of Electrical Engineering and Computer Science (Sep. 1993).
- Geen et al., "New iMEMS® Angular-Rate-Sensing Gyroscope," Analog Dialogue 37-03, pp. 1-3 (2003).
- Grimm, et al., "Real-Time Hybrid Pose Estimation from Vision and Inertial Data," Proceedings of the First Canadian Conference on Computer and Robot Vision (CRV'04), IEEE Computer Society (2004).
- Gyration Ultra Cordless Optical Mouse, User Manual, Gyration, Inc., Saratoga, CA (2003).
- Gyration, "Gyration MicroGyro 100 Developer Kit Data Sheet," <http://web.archive.org/web/19980708122611/www.gyration.com/html/devkit.ht-ml> (Jul. 1998).
- Gyration, Inc., GyroRemote GP240-01 Professional Series (2003).
- Harada et al., "Portable Absolute Orientation Estimation Device with Wireless Network Under Accelerated Situation" Proceedings of the 2004 IEEE International Conference on Robotics & Automation, New Orleans, LA, Apr. 2004, pp. 1412-1417.
- Harada et al., "Portable orientation estimation device based on accelerometers, magnetometers and gyroscope sensors for sensor network," Proceedings of IEEE International Conference on Multisensor Fusion and Integration for Intelligent Systems (MFI 2003), pp. 191-196, (2003).
- Haykin, et al., "Adaptive Tracking of Linear Time-Variant Systems by Extended RLS Algorithms, IEEE Transactions on Signal Processing," vol. 45, No. 5, pp. 1118-1128 (May 1997).
- Hinckley, et al., "Sensing Techniques for Mobile Interaction," Proceedings of the 13th Annual ACM Symposium on User Interface Software and Technology (ACM UIST), San Diego, CA, (2000).
- Hinckley, et al., "The VideoMouse: A Camera-Based Multi-Degree-of-Freedom Input Device" ACM UIST'99 Symposium on User Interface Software & Technology, CHI Letters vol. 1 No. 1, pp. 103-112 (1999).
- Hinckley, Ken "Haptic Issues for Virtual Manipulation," Ph.D. Dissertation University of Virginia, Dept. of Computer Science (1997).
- Holden, Maureen K. et al., "Use of Virtual Environments in Motor Learning and Rehabilitation," Department of Brain and Cognitive Sciences, Handbook of Virtual Environments: Design, Implementation, and Applications, Chap. 49, pp. 999-1026, Stanney (ed), Lawrence Erlbaum Associates (2002).
- Holloway, Richard Lee, "Registration Errors in Augmented Reality Systems," Ph.D. Dissertation, University of North Carolina at Chapel Hill, Dept. of Computer Science (1995).
- Intersense, "InterSense InertiaCube2 Manual for Serial Port Model" (2001).
- Jakubowski, et al., "Increasing Effectiveness of Human Hand Tremor Separation Process by Using Higher-Order Statistics," Measurement Science Review, vol. 1, No. 1 (2001).
- Keir et al., "Gesture-recognition with Nonreferenced Tracking," IEEE Symposium on 3D User Interfaces, pp. 151-158, Mar. 25-26, 2006.
- Kindratenko, "A Comparison of the Accuracy of an Electromagnetic and a Hybrid Ultrasound-Inertia Position Tracking System," MIT Presence, vol. 10, No. 6, pp. 657-663, Dec. 2001.
- Klein et al., "Tightly Integrated Sensor Fusion for Robust Visual Tracking," British Machine Vision Computing, vol. 22, No. 10, pp. 769-776, 2004.
- Kuipers, Jack B., "SPASYN—An Electromagnetic Relative Position and Orientation Tracking System," IEEE Transactions on Instrumentation and Measurement, vol. 29, No. 4, pp. 462-466 (Dec. 1980).
- Kunz, Andreas M. et al., "Design and Construction of a New Haptic Interface," Proceedings of DETC '00, ASME 2000 Design Engineering Technical Conferences and Computers and Information in Engineering Conference, Baltimore, Maryland, Sep. 10-13, 2000.
- La Scala, et al., "Design of an Extended Kalman Filter Frequency Tracker," IEEE Transactions on Signal Processing, vol. 44, No. 3 (Mar. 1996).
- Lee et al., "Tilta-Pointer: the Free-Space Pointing Device," Princeton COS 436 Project (Fall 2004); retrieved from Google's cache of <http://www.milyehuang.com/cos436/project/specs.html> on May 27, 2011.
- Lee et al., "Two-Dimensional Position Detection System with MEMS Accelerometer for Mouse Applications," Design Automation Conference, 2001, Proceedings, 2001 pp. 852-857, Jun. 2001.
- Leganchuk et al., "Manual and Cognitive Benefits of Two-Handed Input: An Experimental Study," ACM Transactions on Computer-Human Interaction, vol. 5, No. 4, pp. 326-259, Dec. 1998.
- Liang, et al., "On Temporal-Spatial Realism in the Virtual Reality Environment," ACM 1991 Symposium on User Interface Software and Technology (Nov. 1991).

- Lobo et al., "Vision and Inertial Sensor Cooperation Using Gravity as a Vertical Reference," *IEEE Trans. on Pattern Analysis and Machine Intelligence*, vol. 25, No. 12, pp. 1597-1608, Dec. 2003.
- Logitech, "Logitech Tracker—Virtual Reality Motion Tracker," downloaded from <http://www.vrealities.com/logitech.html> on Jun. 18, 2010.
- Logitech, Inc. "3D Mouse & Head Tracker Technical Reference Manual," 1992.
- Luinge, "Inertial sensing of human movement," Thesis, University of Twente, Twente University Press, 2002.
- Luinge, et al., "Estimation of orientation with gyroscopes and accelerometers," *Proceedings of the First Joint BMES/EMBS Conference*, 1999., vol. 2, p. 844 (Oct. 1999).
- Luethi, P. et al., "Low Cost Inertial Navigation System" (2000); downloaded from <http://www.electronic-engineering.ch/study/ins/ins.html> on Jun. 18, 2010.
- Mackenzie et al., "A two-ball mouse affords three degrees of freedom," *Extended Abstracts of the CHI '97 Conference on Human Factors in Computing Systems*, pp. 303-304. New York: ACM (1997).
- Mackinlay, "Rapid Controlled Movement Through a Virtual 3D Workspace," *ACM SIGGRAPH Computer Graphics archive*, vol. 24, No. 4, pp. 171-176 (Aug. 1990).
- Merians, et al., "Virtual Reality-Augmented Rehabilitation for Patients Following Stroke," *Physical Therapy*, vol. 82, No. 9, Sep. 2002.
- Merrill, "FlexiGesture: A sensor-rich real-time adaptive gesture and affordance learning platform for electronic music control," Thesis, Massachusetts Institute of Technology, Jun. 2004.
- Meyer et al., "A Survey of Position Tracker," *MIT Presence*, vol. 1, No. 2, pp. 173-200, (1992).
- Morris, "Accelerometry—a technique for the measurement of human body movements," *J Biomechanics* vol. 6, pp. 729-736 (1973).
- Myers et al., "Interacting at a Distance: Measuring the Performance of Laser Pointers and Other Devices," *CHI 2002*, Apr. 2002.
- Naimark et al., "Circular Data Matrix Fiducial System and Robust Image Processing for a Wearable Vision-Inertial Self-Tracker," *IEEE International Symposium on Mixed and Augmented Reality (ISMAR 2002)*, Darmstadt, Germany (2002).
- Nishiyama, "A Nonlinear Filter for Estimating a Sinusoidal Signal and its Parameters in White Noise: On the Case of a Single Sinusoid," *IEEE Transactions on Signal Processing*, vol. 45, No. 4, pp. 970-981 (Apr. 1997).
- Nishiyama, "Robust Estimation of a Single Complex Sinusoid in White Noise— H_∞ Filtering Approach," *IEEE Transactions on Signal Processing*, vol. 47, No. 10, pp. 2853-2856 (Oct. 1999).
- Omelyan, "On the numerical integration of motion for rigid polyatomics: The modified quaternion approach" *Computers in Physics*, vol. 12 No. 1, pp. 97-103 (1998).
- Paradiso, et al., "Interactive Therapy with Instrumented Footwear," *CHI 2004*, Apr. 24-29, 2004, Vienna, Austria.
- Park, *Adaptive control strategies for MEMS gyroscopes* (Dissertation), Univ. Cal. Berkley (Dec. 2000).
- Phillips, "Forward/Up Directional Incompatibilities During Cursor Placement Within Graphical User Interfaces," *Ergonomics*, vol. 48, No. 6, May 15, 2005.
- Phillips, "LPC2104/2105/2106, Single-chip 32-bit microcontrollers; 128 kB ISP/IAP Flash with 64 kB/32 kB/16 kB RAM," Dec. 22, 2004.
- Pilcher, "AirMouse Remote Controls," *IEEE Conference on Consumer Electronics* (1992).
- Pique, "Semantics of Interactive Rotations," *Interactive 3D Graphics*, *Proceedings of the 1986 workshop on Interactive 3D graphics*, pp. 259-269 (Oct. 1986).
- Pryor et al., "A Reusable Software Architecture for Manual Controller Integration," *IEEE Conf. on Robotics and Automation*, Univ of Texas, pp. 3583-3588 (Apr. 1997).
- Raab, et al., "Magnetic Position and Orientation Tracking System," *IEEE Transactions on Aerospace and Electronic Systems*, vol. AES-15, No. 5, pp. 709-718 (Sep. 1979).
- Regan, "Smart Golf Clubs," baltimoresun.com, Jun. 17, 2005.
- Ribo, et al., "Hybrid Tracking for Outdoor Augmented Reality Applications," *IEEE Computer Graphics and Applications*, vol. 22, No. 6, pp. 54-63, Nov./Dec. 2002.
- Riviere, et al., "Adaptive Canceling of Physiological Tremor for Improved Precision in Microsurgery," *IEEE Transactions on Biomedical Engineering*, vol. 45, No. 7, pp. 839-846 (Jul. 1998).
- Robinett et al., "Implementation of Flying, Scaling, and Grabbing in Virtual Worlds," *ACM Symposium* (1992).
- Robinett et al., "The Visual Display Transformation for Virtual Reality," University of North Carolina at Chapel Hill (1994).
- Sakai, et al., "Optical Spatial Filter Sensor for Ground Speed," *Optical Review*, vol. 2, No. 1, pp. 65-67 (1995).
- Sawada, et al., "A Wearable Attitude-Measurement System Using a Fiberoptic Gyroscope," *MIT Presence*, vol. 11, No. 2, pp. 109-118, Apr. 2002.
- Saxena, et al., "In Use Parameter Estimation of Inertial Sensors by Detecting Multilevel Quasi-Static States," Berlin: Springer-Verlag, pp. 595-601 (2005).
- Selectech Airmouse, "Mighty Mouse," *Electronics Today International*, p. 11 (Sep. 1990).
- Sorenson, et al., "The Minnesota Scanner: A Prototype Sensor for Three-Dimensional Tracking of Moving Body Segments," *IEEE Transactions on Robotics and Animation*, vol. 5, No. 4 (Aug. 1989).
- Stovall, "Basic Inertial Navigation," *NAWCWPNS TM 8128*, Navigation and Data Link Section, Systems Integration Branch (Sep. 1997).
- Templeman, James N., "Virtual Locomotion: Walking in Place through Virtual Environments," *Presence*, vol. 8, No. 6, pp. 598-617, Dec. 1999.
- Timmer, et al., "Characteristics of Hand Tremor Time Series," *Biological Cybernetics*, vol. 70, No. 1, pp. 75-80 (1993).
- Toy Designers Use Technology in New Ways as Sector Matures, *WSJ.com*, Dec. 17, 2001.
- US Dynamics Corp, "Spinning Mass Mechanical Gyroscopes," Aug. 2006.
- US Dynamics Corp, "The Concept of 'Rate', (more particularly, angular rate pertaining to rate gyroscopes) (rate gyro explanation)," Aug. 2006.
- US Dynamics Corp, "US Dynamics Model 475 Series Rate Gyroscope Technical Brief," Dec. 2005.
- US Dynamics Corp, "US Dynamics Rate Gyroscope Interface Brief (rate gyro IO)" Aug. 2006.
- Van Den Bogaard, Thesis, "Using linear filters for real-time smoothing of rotational data in virtual reality application," dated Aug. 2, 2004, available at <http://www.science.uva.nl/research/ias/alumni/m.sc.theses/theses/RobvandenBogaard.pdf>.
- Van Laerhoven et al., "Using an Autonomous Cube for Basic Navigation and Input," *Proceedings of the 5th International Conference on Multimodal interfaces*, Vancouver, British Columbia, Canada, pp. 203-210, Nov. 5-7, 2003.
- Van Rheeden, et al., "Noise Effects on Centroid Tracker Aim Point Estimation," *IEEE Trans. on Aerospace and Electronic Systems*, vol. 24, No. 2, pp. 177-185 (Mar. 1988).
- Vaz, et al., "An Adaptive Estimation of Periodic Signals Using a Fourier Linear Combiner," *IEEE Transactions on Signal Processing*, vol. 42, No. 1, pp. 1-10 (Jan. 1994).
- Verplaetse, "Inertial Proprioceptive Devices: Self-Motion Sensing Toys and Tools," *IBM Systems Journal*, vol. 35, Nos. 3&4 (Sep. 1996).
- Verplaetse, "Inertial-Optical Motion-Estimating Camera for Electronic Cinematography," *Masters Thesis*, MIT, Media Arts and Sciences (1997).
- Vorozcovs et al., "The Hedgehog: A Novel Optical Tracking Method for Spatially Immersive Displays," *MIT Presence*, vol. 15, No. 1, pp. 108-121, Feb. 2006.
- Watt, Alan, *3D Computer Graphics*, Chapter 1: "Mathematical fundamentals of computer graphics," 3rd ed. Addison-Wesley, pp. 1-26 (2000).
- Welch, "Hybrid Self-Tracker: An Inertial/Optical Hybrid Three-Dimensional Tracking System," *Tech. Report TR95-048*, Dissertation Proposal, Univ. of North Carolina at Chapel Hill, Dept. Computer Science, Chapel Hill, N.C. (1995).

- Welch, et al., "High-Performance Wide-Area Optical Tracking: *The HiBall Tracking System*," MIT Presence: Teleoperators & Virtual Environments (Feb. 2001).
- Widrow, et al., "Fundamental Relations Between the LMS Algorithm and the DFT," IEEE Transactions on Circuits and Systems, vol. CAS-34, No. 7 (Jul. 1987).
- Williams et al., "Implementation and Evaluation of a Haptic Playback System," vol. 3, No. 3, Haptics-e, 2004.
- Williams et al., "The Virtual Haptic Back Project," presented at the IMAGE 2003 Conference, Scottsdale, Arizona, Jul. 14-18, 2003.
- Wilson et al., "Demonstration of the Xwand Interface for Intelligent Spaces," UIST '02 Companion, pp. 37-38 (2002).
- Worringham, et al., "Directional Stimulus-Response Compatibility: A Test of Three Alternative Principles," Ergonomics, vol. 41, Issue 6, pp. 864-880 (Jun. 1998).
- Yang et al., "Implementation and Evaluation of 'Just Follow Me': An Immersive, VR-Based, Motion-Training System," MIT Presence: Teleoperators and Virtual Environments, vol. 11, No. 3, at 304-23 (MIT Press), Jun. 2002.
- Youngblut, et al., "Review of Virtual Environment Interface Technology," Institute for Defense Analyses (Mar. 1996).
- Zhai, "Human Performance in Six Degree of Freedom Input Control," Ph.D. Thesis, University of Toronto (1995).
- Zhou et al., "A survey—Human Movement Tracking and Stroke Rehabilitation," Technical Report: CSM-420, ISSN 1744-8050, Dept. of Computer Sciences, University of Essex, UK, Dec. 8, 2004.
- Zhu et al., "A Real-Time Articulated Human Motion Tracking Using Tri-Axis Inertial/Magnetic Sensors Package," IEEE Transactions on Neural Systems and Rehabilitation Engineering, vol. 12, No. 2, Jun. 2004.
- May 3, 2010 Response to Feb. 5, 2010 Office Action for U.S. Appl. No. 12/222,787, filed Aug. 15, 2008, now U.S. Pat. No. 7,774,155 (including Rule 1.132 Declaration by Steve Mayer).
- Boulanger et al., "The 1997 Mathews Radio-Baton and Improvisation Modes," Music Synthesis Department, Berklee College of Music (1997).
- Exintaris, et al., "Ollivander's Magic Wands : HCI Development," available at <http://www.cim.mcgill.ca/~jer/courses/hci/project/2002/www.ece.mcgill.ca/%257Eurydice/hci/notebook/final/MagicWand.pdf> (2002).
- Paradiso, et al., "Musical Applications of Electric Field Sensing", available at http://pubs.media.mit.edu/pubs/papers/96_04_cmj.pdf (1996).
- U.S. Appl. No. 60/214,317, filed Jun. 27, 2000.
- U.S. Appl. No. 60/730,659, filed Oct. 25, 2005 to Marks.
- Response to Office Action dated Sep. 18, 2009 for U.S. Appl. No. 11/404,844.
- Expert Report of Nathaniel Polish, Ph.D. On Behalf of Respondents Nintendo of America, Inc. and Nintendo Co., Ltd., dated Nov. 3, 2011.
- Expert Report of Kenneth Holt on Behalf of Respondents Nintendo of America, Inc. and Nintendo Co., Ltd., dated Nov. 3, 2011.
- Respondents Nintendo Co., Ltd. and Nintendo of America Inc.'s Objections and Supplemental Responses to Complainants Creative Kingdoms, LLC and New Kindoms, LLC's Interrogatory Nos. 35, 44, 47, 53, and 78, dated Oct. 13, 2011.
- International Preliminary Examination Report, International App. No. PCT/US00/09482; dated Apr. 24, 2001; 4 pages.
- International Search Report and Written Opinion; International Appl. No. PCT/US2006/043915; mailed Mar. 9, 2007; 8 pages.
- International Search Report and Written Opinion, International App. No. PCT/US05/34831; mailed Jul. 2, 2008; 11 pages.

* cited by examiner

FIG. 1






FIG. 2A




FIG. 2B




FIG. 3A




FIG. 4A




FIG. 3B




FIG. 4B




FIG. 5A




FIG. 5B





FIG. 6

FIG. 7






FIG. 8




FIG. 9




FIG. 10




FIG. 11

FIG. 12





FIG. 13







FIG. 14A




FIG. 14B





FIG. 15B




FIG. 15A




FIG. 15C




FIG. 15D




FIG. 16B




FIG. 16A




FIG. 16C




FIG. 16D




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A








FIG. 18B






FIG. 19G




FIG. 19H




FIG. 19I




FIG. 19J




FIG. 19K




FIG. 19L




FIG. 19M




FIG. 19N




FIG. 19O










FIG. 19P













FIG. 21C








FIG. 25




FIG. 26






FIG. 27








FIG. 28





FIG. 29






FIG. 31A




FIG. 31B







FIG. 32A






FIG. 33D

FIG. 33C

FIG. 33B

FIG. 33A





FIG. 34A

FIG. 34B



810

810

FIG. 35A



**FIG. 35B****FIG. 35C**



FIG. 35D






FIG. 35E

**FIG. 35F****FIG. 35G**




FIG. 36A




FIG. 36B




FIG. 36C




FIG. 36D

1

PORTABLE INTERACTIVE TOY WITH RADIO FREQUENCY TRACKING DEVICE

RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 13/312,916, filed Dec. 6, 2011, which is a continuation of U.S. patent application Ser. No. 13/231,813, filed Sep. 13, 2011, now U.S. Pat. No. 8,169,406, which is a continuation of U.S. patent application Ser. No. 12/261,864, filed Oct. 30, 2008, now U.S. Pat. No. 8,089,458, which is a divisional of U.S. patent application Ser. No. 10/954,025, filed Sep. 29, 2004, now U.S. Pat. No. 7,445,550, which is a continuation-in-part of U.S. patent application Ser. No. 10/397,054, filed Mar. 25, 2003, now U.S. Pat. No. 7,500,917, which is a continuation-in-part of U.S. patent application Ser. No. 09/792,282, filed Feb. 22, 2001, now U.S. Pat. No. 6,761,637, issued Jul. 13, 2004, which claims priority under 35 U.S.C. §119(e) to U.S. Provisional Application No. 60/184,128, filed Feb. 22, 2000, each of which is hereby incorporated herein by reference in its entirety to be part of this specification.

BACKGROUND

1. Field

The present invention generally relates to children's games and, in particular, to magic wands and interactive games and play systems utilizing wireless transponders and receivers for providing a magical interactive play experience. The present invention also relates particularly to interactive toys, games and play systems utilizing radio frequency transponders and transceivers to provide a unique interactive game play experience.

2. Description of the Related Art

Games, toys, play structures and other similar entertainment systems are well known for providing play and interaction among children and adults. A variety of commercially available play toys and games are also known for providing valuable learning and entertainment opportunities for children, such as role playing, reading, memory stimulation, tactile coordination and the like.

Magic and wizardry are classic play themes that continue to capture imaginations and entertain new generations of children and adults alike. Magic and the seemingly limitless possibilities of fun and exciting things brought to life through magic challenge children's imaginations, creativity and social interactivity.

While there are many games and toys that specifically target magic and wizardry as a central play theme, most offer only a superficially engaging play experience, particularly for older children. Very few offer a fully immersive play experience that allows participants to carry out and immerse themselves in a realistic fantasy experience of practicing, performing and mastering "real" magic. In any event, there is always demand for more exciting and entertaining games and toys that increase learning and entertainment opportunities for children and stimulate creativity and imagination.

SUMMARY

Embodiments of the present invention provide a unique play experience carried out utilizing an interactive "wand" and/or other seemingly magical actuation/tracking device. The wand or other actuation device allows play participants to electronically and "magically" interact with their surround-

2

ing play environment(s), thereby giving play participants the realistic illusion of practicing, performing and mastering "real" magic.

Embodiments of the invention may be carried out in association with virtually any suitable play environment, play structure, play area or other area (either commercial or residential), as desired. It can also be carried out in non-physical play environments, such as television, radio, virtual reality, computer games and the like. The play environment may be simply a themed play area, or even a multi-purpose area such as a restaurant dining facility, family room, bedroom or the like. The play environment may either be real or imaginary (i.e., computer/TV generated), and either local or remote, as desired. Optionally, multiple play participants, each provided with a suitable "wand" and/or other actuation/tracking device, may play and interact together, either within or outside one or more compatible play environments, to achieve desired goals, master certain magical spells and/or produce desired seemingly magical effects within the play environment.

In accordance with one embodiment the present invention provides a toy wand or other seemingly magical object which provides a basic foundation for a complex, interactive entertainment system to create a seemingly magic interactive play experience for play participants who possess and learn to use the magical wand toy.

In accordance with another embodiment, the present invention provides an interactive play system and seemingly magical wand toy for enabling a trained user to electronically send and receive information to and from other wand toys and/or to and from various transceivers distributed throughout a play facility and/or connected to a master control system. The toy wand or other seemingly magical object is configured to use a send/receive radio frequency communications protocol which provides a basic foundation for a complex, interactive entertainment system to create a seemingly magic interactive play experience for play participants who possess and learn to use the magical wand toy.

In accordance with another embodiment the present invention provides a "magic" training facility wherein play participants can select and/or build and then learn to use a "real" magic wand. The wand allows play participants to electronically and "magically" interact with their surrounding play environment simply by pointing, touching or using their wands in a particular manner to achieve desired goals or produce desired effects within the play environment. Various wireless receivers or actuators are distributed throughout the play facility to facilitate such interaction and to facilitate full immersion in the fantasy of practicing, performing and mastering "real" magic.

In accordance with another embodiment the present invention provides a wand actuator device for actuating various interactive play effects within a compatible play environment. The wand comprises an elongated hollow pipe or tube having a proximal end or handle portion and a distal end or transmitting portion. An internal cavity may be provided to receive one or more batteries to power optional lighting, laser or sound effects and/or to power long-range transmissions such as via an infrared LED transmitter device or RF transmitter device. The distal end of the wand may be fitted with an RFID (radio frequency identification device) transponder that is operable to provide relatively short-range RF communications (<60 cm) with one or more receivers or transceivers distributed throughout a play environment. A magnetic tip may also be provided for actuating various effects via one or more magnetically operated reed switches. The handle portion of the wand may be fitted with an ornamental knob that is

3

selected by play participants from an available assortment. Knobs may be fitted with an optional rotary switch that may be selectably rotated to indicate different spells, commands or combinations of spells and commands for activating or controlling various associated special effects.

In accordance with another embodiment the present invention provides a wand having an RFID transponder or tag. The transponder contains certain electronics comprising a radio frequency tag pre-programmed with a unique person identifier number ("UPIN"). The UPIN may be used to identify and track individual play participants and/or wands within the play facility. Optionally, each tag may also include a unique group identifier number ("UGIN"), which may be used to match a defined group of individuals having a predetermined relationship. The RFID transponder or other identifying device is preferably used to store certain information identifying each play participant and/or describing certain powers or abilities possessed by an imaginary role-play character. Players advance in a magic adventure game by finding clues, casting spells and solving various puzzles presented. Players may also gain (or lose) certain attributes, such as magic skills, magic strength, fighting ability, various spell-casting abilities, combinations of the same or the like. All of this information is preferably stored on the RFID transponder and/or an associated database indexed by UPIN so that the character attributes may be easily and conveniently transported to other similarly-equipped play facilities, computer games, video games, home game consoles, hand-held game units, and the like. In this manner, an imaginary role-play character is created and stored on a transponder device that is able to seamlessly transcend from one play environment to the next.

In accordance with another embodiment, the present invention provides an RFID card or badge intended to be affixed or adhered to the front of a shirt or blouse worn by a play participant while visiting an RF equipped play facility. The badge comprises a paper, cardboard or plastic substrate having a front side and a back side. The front side may be imprinted with graphics, photos, or any other information desired. The front side may include any number of other designs or information pertinent to its application. The obverse side of the badge contains certain electronics comprising a radio frequency tag pre-programmed with a unique person identifier number ("UPIN"). The UPIN may be used to identify and track individual play participants within the play facility. Optionally, each tag may also include a unique group identifier number ("UGIN") which may be used to match a defined group of individuals having a predetermined relationship.

In accordance with another embodiment, the present invention provides an electronic role-play game utilizing specially configured electronically readable character cards. Each card is configured with an RFID or a magnetic "swipe" strip or the like, that may be used to store certain information describing the powers or abilities of an imaginary role-play character that the card represents. As each play participant uses his or her favorite character card in various play facilities the character represented by the card gains (or loses) certain attributes, such as magic skill level, magic strength, flight ability, various spell-casting abilities, etc. All of this information is preferably stored on the card so that the character attributes may be easily and conveniently transported to other similarly-equipped play facilities, computer games, video games, home game consoles, hand-held game units, and the like. In this manner, an imaginary role-play character is created and stored on a card that is able to seamlessly transcend from one play medium to the next.

4

In accordance with another embodiment the present invention provides a trading card game wherein a plurality of cards depicting various real or imaginary persons, characters and/or objects are provided and wherein each card has recorded or stored thereon in an electronically readable format certain selected information pertaining to the particular person, character or object, such as performance statistics, traits/powers, or special abilities. The information is preferably stored on an RFID tracking tag associated with each card and which can be read electronically and wirelessly over a predetermined range preferably greater than about 1 cm when placed in the proximity of a suitably configured RF reader. Optionally, the RFID tag may be read/write capable such that the information stored thereon may be changed or updated in any manner desired. Alternatively, a magnetic strip, bar code or similar information storage means may be used to store relevant information on the card.

For purposes of summarizing the invention and the advantages achieved over the prior art, certain objects and advantages of the invention have been described herein above. Of course, it is to be understood that not necessarily all such objects or advantages may be achieved in accordance with any particular embodiment of the invention. Thus, for example, those skilled in the art will recognize that the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other objects or advantages as may be taught or suggested herein.

All of these embodiments are intended to be within the scope of the invention herein disclosed. These and other embodiments of the present invention will become readily apparent to those skilled in the art from the following detailed description of the preferred embodiments having reference to the attached figures, the invention not being limited to any particular preferred embodiment(s) disclosed.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus summarized the general nature of the invention and its essential features and advantages, certain preferred embodiments and modifications thereof will become apparent to those skilled in the art from the detailed description herein having reference to the figures that follow, of which:

FIG. 1 is a schematic illustration of one embodiment of an interactive wand toy having features and advantages in accordance with the present invention;

FIGS. 2A and 2B are schematic illustrations of a mercury tilt switch for use in accordance with one embodiment of the present invention and being shown in the OFF and ON conditions, respectively;

FIGS. 3A and 3B are schematic illustrations of a micro-ball tilt switch (normally closed configuration) for use in accordance with one embodiment of the present invention and being shown in the ON and OFF conditions, respectively;

FIGS. 4A and 4B are schematic illustrations of a micro-ball tilt switch (normally open configuration) for use in accordance with one embodiment of the present invention and being shown in the ON and OFF conditions, respectively;

FIGS. 5A and 5B are schematic illustrations of the interactive wand toy of FIG. 1 in upward and downward orientations, respectively;

FIG. 6 is a partial perspective view of a user waving the interactive wand toy of FIG. 1 in such a way to produce actuation thereof;

5

FIG. 7 is a schematic illustration of an alternative embodiment of an interactive wand toy including an optional RF/IR module and having features and advantages in accordance with the present invention;

FIG. 8 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an optional magnetic inductance energy source having features and advantages in accordance with the present invention;

FIG. 9 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an optional piezo generator energy source having features and advantages in accordance with the present invention;

FIG. 10 is a schematic illustration of a piezo armature for use in a piezo generator having features and advantages in accordance with the present invention;

FIG. 11 is a schematic circuit diagram of the piezo generator and power supply of FIG. 9 having features and advantages in accordance with the present invention;

FIG. 12 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an RF/IR module and optional RFID transponder having features and advantages in accordance with the present invention;

FIG. 13 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an RF/IR module and optional RFID transponder having features and advantages in accordance with the present invention;

FIG. 14A is a schematic illustration of a further alternative embodiment of an interactive wand toy including optional orientation sensors having features and advantages in accordance with the present invention;

FIG. 14B is a detail transverse cross-sectional view of the handle portion of the interactive wand toy of FIG. 14A, illustrating the preferred placement and orientation of the optional orientation sensors and having features and advantages in accordance with the present invention;

FIG. 15A is a schematic illustration of a further alternative embodiment of an interactive wand toy including optional rotary switch having features and advantages in accordance with the present invention;

FIG. 15B is a detail transverse cross-sectional view of the handle portion of the interactive wand toy of FIG. 15A illustrating one preferred embodiment of a rotary switch having features and advantages in accordance with the present invention;

FIG. 15C is a partial perspective view of a user rotating the knob of the interactive wand toy of FIG. 15A in such a way to produce a desired wand operation or effect;

FIG. 15D is a detail view of the handle portion and rotatable knob of the interactive wand toy of FIGS. 15A and 15B;

FIG. 16A is a schematic illustration of a further alternative embodiment of an interactive wand toy including optional touch sensor elements having features and advantages in accordance with the present invention;

FIG. 16B is a detail view of one embodiment of a touch sensor element of FIG. 16A having features and advantages in accordance with the present invention;

FIG. 16C is a partial perspective view of a user operating the touch-sensor-enabled interactive wand toy of FIG. 15A in such a way to produce a desired wand operation of effect;

FIG. 16D is a detail view of the handle portion and touch sensor contact elements of the interactive wand toy of FIGS. 16A and 16C;

FIGS. 17A-17B are time-sequenced illustrations of one embodiment of a wand-actuated effect using the interactive wand toy of FIG. 16 with optional magnetic tip and a magnetic reed switch having features and advantages in accordance with the present invention;

6

FIG. 17C is an alternative embodiment of a wand-actuated effect using the interactive wand toy of FIG. 16 with optional magnetic tip, a magnetic reed switch and an optional RF/IR receiver having features and advantages in accordance with the present invention;

FIGS. 18A and 18B are schematic illustrations showing one preferred method for fabricating, assembling and finishing an interactive wand toy having features and advantages in accordance with the present invention;

FIGS. 19A-19P are schematic illustrations showing various possible constructions, configurations and finishes of interactive wand toys having features and advantages in accordance with the present invention;

FIGS. 20A and 20B are schematic illustrations showing two alternative preferred embodiments of an RFID-enabled wand toy having features and advantages in accordance with the present invention;

FIGS. 20C and 20D are front and back views, respectively, of a preferred embodiment of an RFID-enabled trading card having features and advantages in accordance with the present invention;

FIGS. 20E and 20F are front and back views, respectively, of a preferred embodiment of an RFID-enabled key chain trinket having features and advantages in accordance with the present invention;

FIG. 21A is a partial cross-section detail view of the distal end of the interactive wand toy of FIG. 1, illustrating the provision of an RFID transponder device therein;

FIG. 21B is a schematic illustration of an RFID read/write unit for use with the interactive wand toy of FIG. 1 having features and advantages in accordance with the present invention;

FIG. 21C is a simplified circuit schematic of the RFID read/write unit of FIG. 21B having features and advantages in accordance with the present invention;

FIG. 22A is a simplified schematic block diagram of an RF transmitter module adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 22B is a simplified schematic block diagram of an IR transmitter module adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 23A is a simplified schematic block diagram of an RF receiver module and controller adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 23B is a simplified schematic block diagram of an RF receiver module and controller adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 24 is a simplified schematic diagram of an alternative embodiment of a portion of the RF receiver module of FIG. 23A adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 25 is a detailed electrical circuit schematic of the RF transmitter module of FIG. 22A adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 26 is a detailed electrical circuit schematic of the RF receiver module of FIG. 23A adapted for use in accordance with one preferred embodiment of the present invention;

FIG. 27 is a simplified illustration of an interactive play system usable with light-activation in accordance with one preferred embodiment of the present invention;

FIG. 27A is a simplified illustration of another embodiment of an interactive play system usable with light-activation;

FIG. 27B is a simplified illustration of another embodiment of an interactive play system usable with light-activation;

FIG. 28 is a perspective illustration of one preferred embodiment of a wand-actuated play effect comprising a

player piano controlled at least in part by the output of an RF receiver and/or magnetic reed switch having features and advantages in accordance with the present invention;

FIG. 29 is a perspective illustration of another preferred embodiment of a wand-actuated play effect comprising bookshelves with simulated levitating books controlled at least in part by the output of an RF receiver and/or magnetic reed switch having features and advantages in accordance with the present invention;

FIG. 30 is a perspective illustration of another preferred embodiment of a wand-actuated play effect comprising a water fountain effect controlled at least in part by the output of an RF receiver and/or magnetic reed switch having features and advantages in accordance with the present invention;

FIGS. 31A and 31B are time-sequenced perspective views of a magic training center comprising various wand-actuated play effects controlled at least in part by the output of one or more RF receivers and/or magnetic reed switches having features and advantages in accordance with the present invention;

FIG. 32A is a perspective illustration of one preferred embodiment of a wand-actuated game comprising a grid of lighted squares that are controlled at least in part by one or more RF receivers and/or magnetic reed switches having features and advantages in accordance with the present invention;

FIGS. 32B-32D are time-sequenced top plan views of the wand-actuated game of FIG. 32A, illustrating the preferred operation thereof and having features and advantages in accordance with the present invention;

FIGS. 33A-33D are front views of various role-play character cards for use within an interactive play structure;

FIGS. 34A and 34B are front and rear views, respectively, of an alternative embodiment of a role-play character card for use with a specially configured interactive game and/or game play facility having features and advantages in accordance with the present invention;

FIGS. 35A-35G are various illustrations of a role-play adventure game configured to be utilized with the role-play character card of FIGS. 34A and 34B and having features and advantages in accordance with the present invention;

FIGS. 36A and 36B are front and rear views, respectively, of a trading or playing card having features and advantages in accordance with the present invention; and

FIGS. 36C and 36D are front views of several alternative embodiments of trading or playing cards having features and advantages in accordance with the present invention.

DETAILED DESCRIPTION

For convenience of description and for better clarity and understanding of the invention similar elements to those previously described may be identified with similar or identical reference numerals. However, not all such elements in all embodiments are necessarily identical as there may be differences that become clear when read and understood in the context of each particular disclosed preferred embodiment.

Interactive Wand

A wand is provided that allows play participants to electronically and “magically” interact with their surrounding play environment simply by pointing or using their wands in a particular manner to achieve desired goals or produce desired effects within the play environment. Use of the wand may be as simple as touching it to a particular surface or “magical” item within a suitably configured play environment or it may be as complex as shaking or twisting the wand a predetermined number of times in a particular manner and/

or pointing it accurately at a certain target desired to be “magically” transformed or otherwise affected.

For example, various wand-compatible receivers may be distributed throughout a play facility that will allow wand users to activate various associated play effects and/or to play a game using the wand. As play participants play and interact within each play environment they learn more about the “magical” powers possessed by the wand and become more adept at using the wand within various game contexts to achieve desired goals or desired play effects. Optionally, play participants may collect points or earn additional magic levels or ranks for each play effect or task they successfully achieve. In this manner, play participants may compete with one another to see who can score more points and/or achieve the highest magic level.

FIG. 1 illustrates the basic construction of one preferred embodiment of an interactive “magic” wand toy 100 having features and advantages in accordance with the present invention. While a magic wand is specifically contemplated and described herein as the most preferred embodiment of the invention, those skilled in the art will readily appreciate from the disclosure herein that the invention is not limited to wands, but may be carried out using any number or variety of other objects and toys for which it may be desirable to imbue special “magic” powers or other functionalities described herein. Other suitable magical objects and toys may include, for example and without limitation, ordinary sticks, tree branches, flowers, swords, staffs, scepters, whips, paddles, nunchuks, cricket bats, baseball bats, various sporting balls, brooms, feather dusters, paint brushes, wooden spoons, chop sticks, pens, pencils, crayons, umbrellas, walking canes, candy canes, candle sticks, candles, tapers, musical instruments (e.g., flutes, recorders, drum sticks), books, diaries, flashlights, telescopes, kaleidoscopes, laser pointers, ropes, tassels, gloves, coats, hats, shoes and other clothing items, fishing rods and simulated fishing rods, dolls, action figures, stuffed animals, rings, bracelets necklaces and other jewelry items, key chain trinkets, lighters, rocks, crystals, crystal balls, prisms, and various simulated play objects such as apples, oranges, bananas, carrots, celery and other fruits/vegetables. However, magic wands are particularly preferred because they are highly versatile, can transcend a wide variety of different play themes and play environments, and wands can be customized and personalized in their fabrication, assembly and finish as will be described herein in more detail.

As illustrated in FIG. 1, the wand 100 essentially comprises an elongated hollow pipe or tube 110 having a proximal end 112 and a distal end 114. An internal cavity 116 is preferably provided to receive and safely house various circuitry for activating and operating the wand and various wand-controlled effects (described later). Batteries, optional lighting, laser or sound effects and/or the like may also be provided and housed within cavity 116, if desired, as will be described in more detail later. An optional button may also be provided, if desired, to enable particular desired functions, such as sound or lighting effects or longer-range transmissions. While a hollow metal or plastic tube 110 is preferred, it will be appreciated that virtually any other mechanical structure or housing may be used to support and contain the various components and parts described herein, including integrally molded or encapsulated containment structures such as epoxy resins and the like. If a metal tube is selected, care must be taken to ensure that it does not unduly interfere with any of the magnetic, RFID or RF/IR devices described herein. Thus, for example, any RF antennas should preferably be mounted near

or adjacent an end opening and/or other opening of the tube **110** to ensure adequate operating range and desired directionality.

The proximal end **112** of tube **110** is preferably adapted to secure the tube **110** to an optional handle **120**. The handle **120** may further include securement means, such as threaded stud **121**, snap latches, mating magnets or the like, for receiving and securing an optional decorative knob **123**. For example, knobs **123** may be purchased, selected and/or earned by play participants as they advance in a game and/or when they play different games. The distal end **114** of the wand is preferably fitted with an RFID (radio frequency identification) transponder or tag **118** that is operable to provide relatively short-range RF communications (less than about 200 cm) using one or more RFID reader units or reader/writer units (sometimes referred to herein as “receivers” or “transceivers,” respectively), described in more detail later. The transponder **118** contains certain electronics comprising a radio frequency tag pre-programmed with a unique person identifier number (“UPIN”). The UPIN may be used to identify and track individual wands and/or play participants. Optionally, each tag may also include a unique group identifier number (“UGIN”) which may be used to match a defined group of individuals having a predetermined or desired relationship.

The RFID transponder is preferably used to store certain information identifying each play participant and/or describing certain powers or abilities possessed by an imaginary role-play character. For example, players may advance in a magic adventure game by finding clues, casting spells and solving various puzzles presented. Players may also gain (or lose) certain attributes, such as magic skills, magic strength, fighting ability, various spell-casting abilities, combinations of the same or the like, based on game play, skill-level and/or the purchase of collateral play objects. Some or all of this information is preferably stored on the RFID transponder **118** so that the character attributes may be easily and conveniently transported to various compatible play facilities, games, video games, home game consoles, hand-held game units, and the like. Alternatively, only the UPIN and/or UGIN are stored on the transponder **118** and all other desired information is stored on a computer-accessible database indexed by UPIN and/or UGIN.

Operation of the transponder **118** (and/or other wireless communication devices described later) is preferably controlled by internal activation circuitry **115** comprising, in the particular embodiment illustrated, a pair of series-connected mercury tilt sensors **122** and **124** (represented in the corresponding schematic diagram as switches S1 and S2, respectively). As illustrated in FIGS. 2A and 2B each mercury tilt sensor **122**, **124** comprises a sealed, evacuated glass bulb **130** within which is contained a small ball of liquid mercury. A pair of electrical leads **134** extends through the glass bulb **130** at the sealed end thereof and form closely spaced contacts **136**. In one orientation (e.g., FIG. 2B) the ball of mercury **132** is drawn by gravity to cover or envelope the contacts **136**, thus completing the electrical circuit and closing the switch S1/S2 (ON state). In all other orientations (e.g., FIG. 2A) the ball of mercury **132** does not contact or envelope both contacts **136** and, thus, the circuit remains open (OFF state). The particular orientation and tilt angle required to trigger either ON or OFF conditions will depend on the size of the glass bulb **130**, amount of contained mercury **132** and the size and spacing of contacts **136**. If mercury sensors are used, preferably they are encased in a metal and/or epoxy jacket so as to ensure against breakage and possible health and environmental hazards. Preferably, each mercury sensor is encased in epoxy within a sealed stainless steel ferule.

Alternatively, one or more micro-ball tilt sensors **136** or **138** may be used instead of or in addition to mercury switches **122**, **124**. For example, FIGS. 3A and 3B are schematic illustrations of a micro-ball tilt switch **136** (normally closed configuration) that may be adapted for use in accordance with an alternative embodiment of the invention. The tilt switches **136**, **138** generally comprise upper and lower conductive enclosures **142**, **146**, respectively, separated by a suitable insulating material **144** and a conductive ball **140** that is free to move within. In one orientation (e.g., FIG. 3A) the internally contained conductive ball **140** rests within an annular groove completing the electrical circuit between the top conductive enclosure **142** and bottom conductive enclosure **146** (ON state). But, when the sensor **136** is tilted by an amount greater than angle α (FIG. 3B), the ball **140** rolls away from the lower conductive enclosure **141** and, thus, the circuit is opened (OFF state).

FIGS. 4A and 4B are schematic illustrations of another embodiment of a micro-ball tilt switch **138** (normally open configuration) that may also be adapted for use in accordance with a further alternative embodiment of the present invention. In this case, in a first orientation (e.g., FIG. 4A) an internally contained conductive ball **140** rests within a central conical pocket formed in the lower conductive enclosure **146** and is thereby prevented from contacting and completing electrical connection to the upper conductive enclosure **142** (OFF state). But, when the sensor **138** is tilted by an amount greater than angle α (FIG. 4B) the ball **140** rolls out of the conical pocket, touching and completing the circuit with the upper conductive enclosure **142** (ON state). The particular orientation and range of tilt angles required to trigger either ON or OFF conditions of micro-ball sensors **136**, **138** can be varied and/or adjusted to meet varying needs and skill levels of wand users.

Referring to FIGS. 5A and 5B tilt sensors **122** and **124** are preferably oppositely oriented and spaced apart between opposite ends of the tube **110**, as illustrated. Those skilled in the art will appreciate from the disclosure herein that in virtually any static position of the wand **100** at least one of tilt sensors **122**, **124** will be in the OFF state. Thus, the transponder **118** can essentially only be activated when the wand is in a non-static condition or, in other words, when the wand is in motion. More specifically, the placement and orientation of the tilt sensors **122**, **124** is preferably such that different accelerations or motions are required at the proximal and distal ends **112** and **114** in order to trigger both tilt sensors **122**, **124** to their ON positions (or OFF positions, as the case may be) and, thus, to enable or activate transponder **118** (or other wireless communication devices described later).

As illustrated in FIG. 5A, when the wand **100** is held in an upright orientation, tilt sensor **122** (S1) is in its ON state (Static-ON) and tilt sensor **124** (S2) is in its OFF state (Static-OFF). Because the sensors are wired in series, the activation circuit **115** is OFF (open circuit) and the transponder **118** is disabled. Of course, those skilled in the art will readily appreciate from the disclosure herein that if transponder **118** requires a short circuit to disable, then the sensors **122** and **124** would preferably be wired in parallel and, in the orientation shown, the activation circuit **115** would be shorted through S1. On the other hand, when the wand **100** is held in an upside down orientation (FIG. 5B), tilt sensor **122** (S1) is in its OFF state (Static-OFF) and tilt sensor **124** (S2) is in its ON state (Static-ON) such that the activation circuit **115** remains OFF (open circuit) and the transponder **118** remains disabled. Again, if transponder **118** requires a short circuit to disable, then the sensors **122** and **124** would preferably be

11

wired in parallel and, in the orientation shown, the activation circuit **115** would be shorted through **S2**.

Advantageously, the wand activation circuit **115** in accordance with the above-described preferred embodiment is essentially only activated (and transponder **118** is only enabled) when a user actively moves the wand **100** in such particular way as to impart different transient acceleration forces on the distal and proximal ends of the wand **100** (or wherever the sensors are located if not at the distal and proximal ends). In particular, the transient acceleration forces must be sufficient enough at one end of the wand to overcome the gravitational forces acting on the upper sensor (Static-OFF), but not sufficient enough at the other end to overcome the gravitational forces acting on the lower sensor (Static-ON). This transient condition is illustrated in FIG. 6.

The wand activation circuit **115** (and, thus, transponder **118**) is activated by holding the wand tilted slightly upward in one hand while gently and smoothly waving it so that the distal end **114** of the wand follows an upward-cresting arcing pattern while the proximal end **112** remains relatively steady or follows a smaller, more gentle arcing pattern. The acceleration forces caused by the upward arcing motion at the distal end **114** counteract gravitational forces on the tilt sensor **124** and cause it to switch from its OFF state to its ON state. At the same time, the smaller arcing motion and acceleration forces at the proximal end **112** are not sufficient to counteract the gravitational forces on the tilt sensor **122** and, thus, it remains in its ON state. The result is that both sensors **122** and **124** are momentarily in their ON state and the wand activation circuit **115** thereby momentarily activates the transponder **118**. The complexity and learnability of the described motion is similar to a golf swing. Only with this particular motion (or other similar learned motions) executed in a precise and repeatable fashion will the transient conditions be satisfied to cause both sensors **122** and **124** to switch to their ON state, thereby momentarily activating transponder **118**. If the arcing motion is too fast or too pronounced, the lower sensor **122** will switch to its OFF state. On the other hand, if the arcing motion is too slow or too shallow, the upper sensor **124** will not switch to its ON state. Thus, successful operation of the wand **100** requires real skill, patience and training.

Those skilled in the art will readily appreciate and understand from the disclosure herein that various additional and/or alternative wand activation circuits can be designed and configured so as to respond to different desired wand activation motions. For example, this may be achieved by adding more sensors and/or by changing sensor positions and orientations. For example, one wand motion may trigger a first wand activation circuit (and a first wand effect) while a different wand motion may trigger a second wand activation circuit (and a second wand effect). The number, type and complexity of wand motions and corresponding wand activation circuits are limited only by design and cost considerations and user preferences. Most desirably 6-12 unique wand activation motions and corresponding wand activation circuits are provided. Of course, those skilled in the art will recognize from the disclosure herein that multiple wand activation circuits may share one or more sensors and/or other supporting circuitry and components, as required or desired. Alternatively, a single, multi-mode wand activation circuit may be provided that can respond to multiple wand motions.

The degree of difficulty and skill required to master each wand motion can preferably be adjusted to suit the age and skill-level of each user. Generally speaking, selecting tilt sensors **122, 124** having narrow activation ranges increases the difficulty level of the wand, as it makes it more difficult to satisfy the transient conditions required to turn each sensor to

12

its ON or active state. Similarly, adding more sensors also increases the difficulty level, as it decreases the probability that all required transient conditions can be satisfied in a given moment. Placement and orientation of the sensors **122** and **124** (and any other sensors) can also make a difference in the degree of difficulty and skill required. For example, spacing the sensors closer together (e.g., 3-5 cm apart) generally makes it more difficult to operate the wand as it becomes harder and harder to create different transient conditions relative to each sensor location. Conversely, spacing sensors farther apart (e.g., 10-35 cm apart) makes it easier. An optimal sensor spacing is about 8-12 cm. Optionally, some or all of these degree-of-difficulty parameters can be adjusted or changed as skill-levels increase or as other circumstances warrant.

Of course, those skilled in the art will appreciate from the disclosure herein that the wand activation circuitry **115** is not limited to those including mercury or micro-ball tilt sensors, as illustrated, but may be practiced using a wide variety of other motion and/or tilt sensors and/or other supporting circuitry elements and components that are selected and adapted to the purposes described herein. These include, without limitation, impact sensors, micro-sensors, gyro-sensors, force sensors, micro-switches, momentum sensors, vibration sensors, gravity sensors, accelerometers, and all variety of reed switches (gravity, momentum, magnetic or otherwise). Moreover, any one or more of these and/or other similar sensor devices may also be used in conjunction with other supporting circuitry elements or components (either internal or external to the wand **100**) as desired, including microprocessors, computers, controller boards, PID circuitry, input/output devices, combinations of the same and the like. Mercury and micro-ball tilt sensors as illustrated and described above are particularly preferred as they are relatively inexpensive and reliable.

FIG. 7 is a schematic illustration of an alternative embodiment of an interactive wand **100a** including an optional RF/IR module adapted for long-range wireless communications (up to about 100 meters). Wand **100a** is essentially the same as wand **100** illustrated and described above in connection with FIG. 1, except longer-range wand operation is achieved by replacing the RFID transponder **118** in wand **100** (FIG. 1) with an auxiliary RF/IR transmitter **150** (see FIGS. 22 and 25 accompanying discussion for circuit schematic and other details). If line of sight or directional actuation is desired, an infrared LED transmitter of the type employed in standard television remote controls may be provided instead of or in addition to the RF transmitter **118**, as those skilled in the art will readily appreciate. In the latter case, a hole (not shown) would preferably be provided in the distal end **114** of the wand to accommodate the transmitting LED of the IR transmitter circuit. Of course, a wide variety of other wireless communications devices, as well as various optional sound and lighting effects may also be provided, as desired.

RF/IR transmitter module **150** and/or any other desired optional effects may be actuated using the wand activating circuit **115** substantially as illustrated and described above in connection with FIGS. 1-6. As illustrated in FIG. 7, tilt sensors **122, 124** (**S1/S2**) are wired in series with the RF/IR module, between batteries **152** (voltage source **V+**) and ground (all or part of tube **110**). Thus, RF/IR module **150** is powered when sensors **122** and **124** are both in their ON state (switches **S1** and **S2** are both closed). Again, this transient state can essentially only be achieved when a skilled user actively moves the wand **100a** in such particular way as to impart different transient acceleration forces on the distal and proximal ends of the wand **100a**, as illustrated and described

13

above in connection with FIG. 6. Other than as noted above it will be understood that the wand **100a** is in all other material respects essentially the same as wand **100** illustrated and described in connection with FIGS. 1-5. Note that the handle **120a** and knob **123a** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

Furthermore, the wand activation circuitry **115** may advantageously comprise a microprocessor that communicates with the sensors **122**, **124** and the transmitter module **150**. In one embodiment, the microprocessor receives at least one signal from the sensors **122**, **124** indicative of the state of the sensors. For instance, the microprocessor may determine when each of the sensors **122**, **124** are in an ON or an OFF state or when one of the sensors **122**, **124** switches states. Based on the states of the sensors **122**, **124**, the microprocessor then outputs a signal to the transmitter module **150** that causes activation or deactivation of the transmitter module **150**.

In another embodiment, the microprocessor is capable of measuring a duration of time related to the operational states of the sensors **122**, **124**. For example, the microprocessor may use a clock signal or an external timer to determine the duration of time during which at least one of the sensors **122**, **124** is in an ON state. The microprocessor may then use this duration of time when outputting a signal to the transmitter module **150**. For example, the microprocessor may correlate the duration of time that a sensor **122**, **124** is activated (e.g., in an ON state) with an intensity, level, or type of a "spell" being cast by the user. For instance, if the user, while "casting a spell," is able to move the wand **100** so as to keep at least one of the sensors **122**, **124** activated for a certain period of time, the microprocessor may assign a particular level or intensity to the spell being cast. Thus, the microprocessor may output different signals, which represent different spells or spell intensities, to the transmitter module **150** based on the length of time of the sensor activation. In one embodiment, the microprocessor may associate longer durations of sensor activation with higher intensity spells.

In yet other embodiments, the microprocessor calculates the duration of time between successive activations, or triggering, of the sensors **122**, **124**. For example, the microprocessor may determine how much time passes between the activation of the sensor **122** and the activation of the sensor **124**, which are caused by the user's operation of the wand **100**. For instance, the microprocessor may associate simultaneous or shorter durations of time between the activations of the two sensors **122**, **124** with a more advanced, or higher-level, spell. Thus, the user that operates the wand **100** so as to activate each of the sensors **122**, **124** within a relatively short period of time is able to cast higher-level spells. On the other hand, if there is a greater delay between the activations of the sensors **122**, **124**, the microprocessor assigns a lower intensity level to the spell being cast. In yet other embodiments, the time during or between the sensor activations is used by the microprocessor to determine which of a variety of spells is achieved by the user.

In other embodiments, the microprocessor may compare the duration of time of sensor activation or time between successive activations, to a predetermined time. For example, if the duration of time between successive activations is less than the predetermined time, the "spell" may be assigned a higher intensity level. If the duration of time between successive activations is greater than the predetermined time, the "spell" may be assigned a higher lower level. In addition, in some embodiments, the microprocessor does not calculate

14

the specific value of the duration of time but determines if the duration of time exceeds or does not exceed a predetermined time.

In yet other embodiments of the invention, the duration of time during or between activation of the sensors **122**, **124** is output to a receiver external to the wand **100**. The receiver then processes the duration of time in determining which effect, or which level of an effect, is caused by the particular wand activation motions and associated duration(s) of time. In yet other embodiments, the foregoing microprocessor may be used in a wand **100** comprising a transponder **118** instead of, or in combination with, the transmitter module **150**.

In another embodiment, the microprocessor accesses a look-up table that associates specific durations of time, or ranges of durations of time, with the intensity or the type of the spell being cast. For example, the look-up table may associate durations of time less than 0.1 seconds between successive sensor activations with a higher level spell, durations of time from 0.1 to 0.2 seconds with a mid-level spell, and durations of time greater than 0.2 seconds with a lower level spell. In one embodiment, the look-up table is stored in a memory, such as for example a read-only memory (ROM), on the wand **100**. The look-up table may be internal or external to the microprocessor. In yet other embodiments, the look-up table may be accessible by the receiver of the signal from the wand **100**.

FIG. 8 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an optional magnetic inductance energy source. Wand **100b** is essentially the same as wand **100** illustrated and described above in connection with FIG. 1, except that batteries **152** are replaced with a magnetic inductance energy generator **162**. The magnetic inductance energy generator **162** comprises an inductance coil **L1** sized and arranged such that when it is exposed to a fluctuating magnetic field (e.g., a moving permanent magnet **164** rubbed back and forth and/or an externally generated electromagnetic field) an alternating current is generated. This generated current is rectified by diode **D1** or, alternatively, a full wave bridge rectifier (not shown), and charges preferably an electrolytic capacitor **C1** until it reaches a predetermined operating voltage **V+**. If desired, a voltage regulator device, such as a zener diode (not shown) and/or active regulation circuitry may be added to stabilize and increase the efficiency of the magnetic inductance energy generator **162**.

Alternatively, those skilled in the art will appreciate from the disclosure herein that a various magnetic field effect sensors, such as Wiegand sensors and the like, may readily be used in place of or in addition to inductor **L1** where, for example, it is desired to increase the energy-generating efficiency of the circuit **162**. For example, U.S. Pat. No. 6,191,687 to Dlugos discloses a Wiegand effect energy generator comprising a Wiegand wire that changes its magnetic state in response to being exposed to an alternating magnetic field. The Wiegand wire has core and shell portions with divergent magnetic properties. The magnetic properties of the wire are such that it produces an output power signal that corresponds to the strength and rate of change of a magnetic field to which the Wiegand wire is exposed. Such energy pulses generally are between about 5 and 6 volts and 10 microseconds in width. Such energy pulses have sufficient voltage and duration to power a low power transmitter such as RF/IR module **150**. One suitable Wiegand sensor that may be utilized in accordance with the present invention is the series 2000 sensor sold by EHD Corp. The Series 2000 Wiegand sensor produces pulses in response to alternating magnetic fields or permanent magnets that pass near the sensor.

15

The energy generating circuit **162** is preferably such that the wand **100b** has no movable parts and requires no maintenance such as replacing batteries or the like over its anticipated life. All energy is generated and stored by rubbing the wand back and forth with a permanent magnet and/or by placing the wand within an externally generated electromagnetic field. Preferably, the inductor **L1** (or Wiegand wire) and capacitor **C1** are selected such that 5-10 seconds of exposure to an external fluctuating magnetic field will fully charge the capacitor **C1**, thus enabling the wand RF/IR transmitter to be activated at least once and preferably 5-20 times without having to recharge. Advantageously, the absence of replaceable batteries or other visible electronic technology significantly increases the reality and full immersion experience of the magical fantasy and gives users the feeling of practicing, performing and mastering “real” magic using a “real” magic wand **100b**. Optionally, a non-replaceable permanent rechargeable battery and/or a factory replaceable battery (not shown) may be provided in place of or in addition to the energy generating circuit **162** where it is desired to provide long-term energy storage. Other than replacing batteries **152** with magnetic inductance energy generator **162**, the wand **100b** is in all other material respects essentially the same as wand **100a** illustrated and described above in connection with FIG. 7. Note that the handle **120b** and knob **123b** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

FIG. 9 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an optional piezoelectric generator. Wand **100c** is essentially the same as wand **100b** illustrated and described above in connection with FIG. 8, except that magnetic inductance energy generator **162** has been replaced with a piezo generator **166** and power supply **168**.

Piezoelectricity refers to a unique property of certain materials such as quartz, Rochelle salt, and certain solid-solution ceramic materials such as lead zirconate-titanate ($\text{Pb}(\text{ZrTi}1-x)\text{O}_3$) (“PZT”) that causes induced stresses to produce an electric voltage or, conversely, that causes applied voltages to produce an induced stress. In a “generator” mode, electricity is developed when a piezoelectric (“piezo”) crystal is mechanically stressed. Conversely, in a “motor” mode, the piezo crystal reacts mechanically when an electric field is applied.

PZT is one of the leading piezoelectric materials used today. It can be fabricated in bimorph or unimorph structures (piezo elements), and operated in flexure mode. These structures have the ability to generate high electrical output from a source of low mechanical impedance (conversely, to develop large displacement at low levels of electrical excitation). Typical applications include force transducers, spark pumps for cigarette lighters and boiler ignition, microphone heads, stereophonic pick-ups, etc.

It is known that piezo elements can be used to generate small amounts of useful energy from motion. For example, U.S. Pat. No. 3,456,134 to Ko, incorporated in its entirety by reference herein, discloses a piezoelectric energy converter for electronic implants, wherein body motion is converted into electrical energy using a piece of piezoelectric PZT in the form of a resonant cantilever beam. See also, U.S. Pat. No. 6,438,193 to Ko et. al, which discloses a similar piezo generator for self-powered tire revolution counter. Such piezo generators have particular application and benefit to batteryless toys and wands of the type disclosed and described herein.

16

FIG. 10 is a cross-sectional view of such a piezo generator **166** comprising a “bimorph” piezo element **170** rigidly mounted at one end forming a cantilever beam. A “bimorph” is a flexing-type piezoelectric element, which has the capacity for handling larger motions and smaller forces than single piezoelectric plates. The bimorph piezo element **170** comprises two planar piezo crystals secured together face-to-face with a shim or vane therebetween. Mechanical bending of the element **170** causes it to produce a corresponding voltage between output electrodes **176, 178**.

The piezoelectric element **170** is mounted and enclosed within the distal end of tube **110** (FIG. 9) and its free end is loaded with a small weight **174** selected to resonate at a suitable frequency corresponding to the likely or anticipated movement of the wand **100c**. A typical measured oscillation frequency is on the order of 10-100 Hz. As the wand is moved periodically, the piezo element **170** vibrates back and forth producing electrical pulses. These electrical pulses are then rectified by a full wave bridge rectifier **180** (FIG. 11), are filtered by a filter circuit comprising capacitors **C1, C2** and resistors **R0, R1** and are stored in an energy storage capacitor **C3**, preferably a low-voltage electrolytic capacitor.

In order to draw maximum power from the piezo element **170**, the power supply circuit **168** “load” impedance preferably is selected to match the output impedance of the piezo element **170**. In order to minimize the ripple effect (peak-to-peak magnitude of rippling imposed on the nominal DC voltage level) energy storage capacitor **C3** is preferably selected to be as large as possible, given available space constraints. To improve the stability of the power-supply an optional voltage regulator **182** may be added. For example, an LM185 IC band-gap voltage regulator may be chosen.

The piezo generator and power supply circuits **166, 168** preferably have sufficient power output under normal operating conditions such that the wand **100c** requires no other internal energy sources such as replaceable batteries or the like. All energy is generated and stored by normal motion of the wand during use, e.g. during spell casting or during normal walking or running while carrying the wand **100c**. Preferably, the energy storage capacitor **C3** is selected such that when fully charged, it provides sufficient stored energy to enable the wand to be activated at least once and preferably 50-100 times without having to recharge.

Advantageously, the absence of replaceable batteries or other visible electronic technology significantly increases the reality and full immersion experience of the fantasy and gives users the feeling of practicing, performing and mastering “real” magic using a “real” magic wand **100c**. Optionally, a non-replaceable permanent rechargeable battery and/or a factory replaceable battery (not shown) may be provided in place of or in addition to the energy generating circuit **166** where it is desired to provide long-term energy storage. The wand **100c** in all other material respects is essentially the same as wand **100b** illustrated and described above in connection with FIG. 8. Note that the handle **120c** and knob **123c** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

FIG. 12 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an RF/IR module and optional RFID transponder. Wand **100d** is essentially the same as wand **100b** illustrated and described above in connection with FIG. 8, except for the addition of optional RFID transponder **118d**.

As with the RFID transponder **118** illustrated and described above in connection with FIG. 1, RFID transponder **118d** is operable to provide relatively short-range RF com-

17

munications (less than about 200 cm) using one or more RFID reader units or reader/writer units, described in more detail later. The transponder **118d** also preferably contains certain electronics comprising a radio frequency tag pre-programmed with a unique person identifier number ("UPIN"). The UPIN may be used to identify and track individual wands and/or play participants. Optionally, each tag **118d** may also include a unique group identifier number ("UGIN") which may be used to match a defined group of individuals having a predetermined or desired relationship.

The RFID transponder is preferably used to store certain information identifying each play participant and/or describing certain powers or abilities possessed by an imaginary role-play character. For example, players may advance in a magic adventure game by finding clues, casting spells and solving various puzzles presented. Players may also gain (or lose) certain attributes, such as magic skills, magic strength, fighting ability, various spell-casting abilities, combinations of the same or the like, based on game play, skill-level and/or the purchase of collateral play objects. Some or all of this information is preferably stored on the RFID transponder **118d** so that the character attributes may be easily and conveniently transported to various compatible play facilities, games, video games, home game consoles, hand-held game units, and the like. Alternatively, only the UPIN and UGIN are stored on the transponder **118** and all other desired information is stored on a computer-accessible database indexed by UPIN and/or UGIN.

If desired, RFID transponder **118d** may be electronically interlocked and controlled by a corresponding wand activation circuit such as illustrated and described above in connection with FIG. 1. More preferably, however, the RFID tag **118d** is not interlocked, but is always activated. In this manner, transponder **118d** can be easily read at short range using an RFID reader/writer (described later) to sense and track play participants and/or to activate various simple wand effects. Longer range RF communications via RF/IR module **150** are preferably only enabled when an appropriate wand activation motion is executed as described above in connection with FIGS. 1-6. The wand **100d** in all other material respects is essentially the same as wand **100b** illustrated and described above in connection with FIG. 8. Note that the handle **120d** and knob **123d** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

FIG. 13 is a schematic illustration of a further alternative embodiment of an interactive wand toy including an RF/IR module and optional RFID transponder. Wand **100e** is essentially the same as wand **100d** illustrated and described above in connection with FIG. 12, except for the location and placement of the RFID transponder **118e**.

As with the RFID transponder **118d** illustrated and described above in connection with FIG. 12, RFID transponder **118e** provides relatively short-range RF communications using one or more RFID reader units or reader/writer units, described in more detail later. The transponder **118e** also preferably contains certain electronics comprising a radio frequency tag pre-programmed with a unique person identifier number ("UPIN") and unique group identifier number ("UGIN"). Preferably, RFID tag **118e** is always activated so that it can be easily read at short range using an RFID reader/writer (described later) to sense and track play participants and/or to activate various simple wand effects. Placing the RFID tag **118e** in the handle **120e**, allows for modular construction and functionality of a wand **100e** as auxiliary handles may be interchanged having other unique RFID tags

18

with unique stored information. Optionally, the tag-containing handle **120e** and knob **123e** may be omitted altogether in the case, for example, where a less expensive wand is desired.

As described above, longer range RF communications via RF/IR module **150** are preferably enabled only when an appropriate wand activation motion is executed as described above in connection with FIGS. 1-6. The wand **100e** in all other material respects is essentially the same as wand **100d** illustrated and described above in connection with FIG. 12. Note that the handle **120e** and knob **123d** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

In certain advanced applications, it is desirable to wirelessly communicate specific data and commands to achieve different or varied wand effects. For example, it may be desirable to wirelessly send one command signal that turns a certain object (e.g., a lamp) "OFF" and another command signal that turns an object "ON". As described above in connection with FIGS. 1-6, this functionality may be achieved using multiple wand activation circuits (or a single multi-mode circuit) responsive to various unique wand motions whereby each wand motion, if executed successfully, causes a different RF or IR signal to be transmitted to control or activate the desired effect (e.g., turning a light ON or OFF or simulating the levitation of an object).

Another convenient way to achieve similar functionality is to load data bits representing specific desired commands directly into a data buffer of RF/IR module **150f** (FIG. 14A) and then, using only a single wand activation circuit and a single learned wand motion, cause an RF or IR signal to be transmitted, thereby carrying the command signal and data to an RF or IR receiver and associated effect. Thus, for example, one or more tilt sensors **192**, **194** (illustrated schematically as switches S3/S4) may be provided in a convenient location within the wand **100f** (e.g., within the handle **120**). These sensors are preferably mounted and oriented such that axial rotation of the wand shaft **110** and/or wand handle **120f** causes the sensors to alternately switch from their ON to their OFF state. As illustrated in the circuit schematic accompanying FIG. 14A, each sensor controls one data input bit of the RF/IR module data bus (e.g., S3, S4).

Preferably, sensors **192**, **194** are disposed at an angle of between about 60 and 120 degrees (most preferably about 90 degrees) from one another within a transverse plane of the wand (see, e.g., FIG. 14B). Those skilled in the art will readily appreciate that in this manner, four possible wand orientations are possible resulting in four unique sensor pair states as follows: ON/ON; OFF/OFF; ON/OFF and OFF/ON. These four sensor states can represent, for example, four unique command signals sent using the RF/IR module **150f**. The wand **100f** in all other material respects is essentially the same as wand **100b** illustrated and described above in connection with FIG. 8. Note that the handle **120f** and knob **123f** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

Where it is desired to send a larger number of unique command signals, various combinations of additional orientation sensors and/or wand activation circuits may be added, as desired. Alternatively, various dials, switches and/or other inputs may be provided for selecting from a number of unique wand commands or "spells." For example, in one preferred embodiment illustrated in FIGS. 15A-C a wand **100g** is provided including a knob-actuated rotary switch **202** which directly loads up to 4 data bits (up to 16 possible unique

19

codes) representing specific desired commands directly into a data buffer of RF/IR module **150g** (FIG. **15A**).

As illustrated in FIG. **15C** a user rotates the knob **123g** and sets it to the desired spell represented by magic symbols **204** (FIG. **15D**). Then, using only a single wand activation circuit and a single learned wand motion, the user causes an RF or IR signal to be transmitted, carrying the unique command signal/data to an RF or IR receiver, thereby controlling or activating an associated effect. Alternatively, a potentiometer may be used in conjunction with an ND converter circuit instead of rotary switch **202** for selecting wand functions/spells. The wand **100g** in all other material respects is essentially the same as wand **100h** illustrated and described above in connection with FIG. **8**. Note that the handle **120g** and knob **123g** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

FIG. **16A** is a schematic illustration of a further alternative embodiment of an interactive wand toy including optional touch sensor elements for selecting one or more wand spell commands. Wand **100h** is essentially the same as wand **100f** illustrated and described above in connection with FIGS. **14A** and **14B**, except for the substitution of touch sensor elements **208**, **210**, **212** for tilt sensors **192**, **194**.

Touch sensor elements **208**, **210**, **212** (represented in the accompanying schematic as **S3**, **S4**, **S5**) comprise solid-state electronic switches (no buttons or moving parts) that are activated by the simple touch of a finger. Most preferably, these are solid state touch switches of the type illustrated and described in U.S. Pat. No. 4,063,111 to Dobler et al., the entire contents of which are incorporated herein by reference. As illustrated in FIG. **16B**, each touch switch contact element **208**, **210**, **212** is preferably formed from a pair of conductive electrodes **211** surrounded by, and preferably flush with, an insulating material **213**. If desired, the electrodes **211** may be shaped in the form of magic symbols or other shapes consistent with a desired magic theme, as illustrated. During use, the user's finger **217** is placed over the pair of electrodes **211** and thereby forms a portion of an electronic circuit to change the state of a corresponding solid state electronic switching device **Q1**, **Q2**, **Q3** in communication therewith, such as a MOSFET or PNP transistor. The touch sensor is thereby actuated.

Each touch sensor preferably controls one data input bit of the RF/IR module data bus (e.g., **S3**, **S4**, **S5**). One or more touch switches may be activated during a single wand transmission. Thus, those skilled in the art will readily appreciate that eight possible combinations of touch switch activations are possible corresponding to eight unique command input data sets as follows: ON/ON/ON; OFF/OFF/ON; ON/OFF/ON; OFF/ON/ON; ON/ON/OFF; OFF/OFF/OFF; ON/OFF/OFF; and OFF/ON/OFF. These eight sensor states can represent, for example, eight unique command signals sent using the RF/IR module **150h**.

As illustrated in FIGS. **16C** and **16D**, a user may select a spell by touching one or more selected magic symbols. Then, while holding the fingers over the selected magic symbols and using only a single wand activation circuit and a single learned wand motion, the user causes an RF or IR signal to be transmitted, carrying the unique command signal/data to an RF or IR receiver, thereby controlling or activating an associated effect.

Optionally, wand **100h** includes a magnetic tip **216**, as illustrated in FIG. **16A**. This can be especially useful and entertaining for close-range activation of various play effects, such as turning lights on/off, triggering special sound and/or lighting effects. For example, FIGS. **17A-17B** are time-se-

20

quenced illustrations of one embodiment of a magnetically actuated lighting effect using the interactive wand toy **100h** with optional magnetic tip **216**. A magnetic reed switch **218** is provided in series between the desired lighting effect **220** and a power source (**V+**). The reed switch is constructed in the normal fashion. Contacts **222**, **224** are normally open and, thus, the lighting effect **220** is in its OFF state. But, when the magnetic tip **216** of wand **100h** is brought into relatively close proximity (2-3 cm) with the reed switch **218**, contact elements **222**, **224** are magnetized by the magnetic field lines and are drawn toward each other. This causes the contacts **222**, **224** to immediately attract, closing the gap and completing the circuit to turn on the lighting effect **220**. Of course, those skilled in the art will appreciate from the disclosure herein that various relays, power controllers and the like may be required or desirable to provide adequate control of larger, more complex effects. But all such effects, no matter how small/simple or large/complex, may be triggered with a simple reed switch **218** and a wand **100h** having a magnetic tip **216**, as described above.

The magnetic tip **216** is especially useful and synergistic in combination with the other disclosed functions and features of wand **100h**. Thus, for example, as illustrated in FIG. **17C**, a desired lighting effect is controlled by RF/IR receiver **250**, which is adapted to receive an RF and/or IR command signal from wand **100h**. The RF/IR receiver **250** (and/or the lighting effect **220**) is also controlled by series-connected magnetic reed switch **218**, as illustrated and described above (FIGS. **17A**, **17B**). Desirably, this allows a user to use the wand **100h** and the magnetic tip **216** thereof to select one or more effects he or she wishes to control or activate. For example, the closure of the magnetic reed switch **218** sends an activation signal to RF/IR receiver **250**. In response, the receiver initiates a timer (e.g., 5-10 seconds) wherein its RF and/or IR receiver circuitry is activated and ready to receive one or more transmitted commands for controlling the associated effect **220**. Thus, a user may select to control the lighting effect **220** by activating the reed switch **218** with the magnetic tip **216** of wand **100h**. Then the user may cast a spell (cause the wand **100h** to transmit an RF or IR command signal) that commands the RF/IR receiver **250** to turn the lighting effect ON or OFF, to change the lighting effect (e.g., change its color or intensity), and/or launch a related effect (e.g., simulated levitation of the lighting source or other desired effects). In this manner, users can maintain direct and precise control over any number of individual play effects as may be desired. The wand **100h** in all other material respects is essentially the same as wand **100f** illustrated and described above in connection with FIG. **14**. Note that handle **120h** and knob **123h** are slightly modified, as these elements are preferably uniquely customized/personalized for each wand and/or wand user as will be discussed in more detail later.

While it is particularly preferred to provide batteryless RF-enabled, RFID-enabled or IR-enabled wand **100**, those skilled in the art will recognize from the disclosure herein that the invention may be carried out in a variety of other ways that incorporate some or all of the inventive features disclosed and described herein. For example, wand activation circuit **115** may be implemented in a variety of other gaming and entertainment applications such as, for example, a wireless or hard-wired wand input device for a video game, computer game or home game console, an arcade or redemption challenge device, home-operated amusement device using simple bells and buzzers, or the like. Alternatively, some or all of the various circuitry and components described herein above may be externally implemented such that the wand **100** may not be entirely self-contained, but may rely on certain external

components and circuitry for some or all of its functionality. Alternatively, some or all of the various circuitry and components described herein can be implemented in a user-wearable format such that various interactive play effects and the like, as described herein, may be actuated through particular hand or arm motions without the use of a wand.

Additional optional circuitry and/or position sensors may be added, if desired, to allow the “magic wand” **100** to be operated by waving, shaking, stroking and/or tapping it in a particular manner. If provided, these operational aspects would need to be learned by play participants as they train in the various play environments. The ultimate goal, of course, is to become a “grand wizard” or master of the wand. This means that the play participant has learned and mastered every aspect of operating the wand to produce desired effects within each play environment. Of course, additional effects and operational nuances can (and preferably are) always added in order to keep the interactive experience fresh and continually changing. Optionally, as shown and discussed in more detail in connection with FIG. **19G**, the wand **100** may be configured such that it is able to display 50 or more characters on a LTD or LCD screen. The wand may also be configured to respond to other signals, such as light, sound, or voice commands as will be readily apparent to those skilled in the art.

Proximity Sensor

In yet another embodiment, the wand **100** further comprises a proximity sensor usable to provide a “hover” effect that is indicative of the initialization of a control interlock. When the proximity sensor in the wand **100** is moved within a particular distance of a receiver, such as the RF/IR receiver **150**, and/or an effects controller, a “hover” effect occurs, such as, for example, the turning on of a light, the movement or vibration of an object, or any other perceptible signal (visual or audible) that notifies the user that a play effect may be initiated.

For instance, one embodiment of the invention may include a play effect that comprises the moving of a book. When the user brings the wand **100** within a predetermined distance from the book (e.g., one meter), the proximity sensor in the wand **100** causes the wand to output a command signal to a receiver and/or effects controller near the book to initiate a control interlock and to generate a “hover” effect, such as the turning on of a light. At this point, the user is notified that he or she may then cast the appropriate spell, such as by appropriately motioning the wand **100**, which causes the book to move. If the user attempts to cast the spell outside of the predetermined distance, the book does not move. This is because the appropriate control interlock is not initiated between the wand **100** and the receiver and/or effects controller.

Furthermore, the foregoing described “hover” effect may be used with passive RFID technology to conserve energy or battery power of the wand **100**. In one embodiment, the wand **100** comprises a passive RFID circuit in addition to an activation circuit (e.g., activation circuit **115** of FIG. **1**) and may operate in an “active” or a “sleep” mode. During the sleep mode, the activation circuit does not engage in significant activity, which reduces the energy consumption of the wand **100**. In addition, during the “sleep” mode, the user may not be able to cast spells with the wand **100**. When the passive RFID circuit of the wand **100** is brought within a certain range of an RF transmitter, such as positioned near the effects controller, the passive RFID circuit receives the transmitted RF signal and “awakens” the wand activation circuit into the “active” state. At this point, the user is able to engage in spell casting, such as by motioning the wand, as is described herein. In

further embodiments, a perceptible signal, such as a light or a noise, alerts the user when the wand **100** awakens to an “active” mode.

Although disclosed with reference to particular embodiments, a skilled artisan will recognize from the disclosure herein a wide variety of methods and/or devices usable to cause a “hover” effect. For example, the user may use certain voice commands, such as a particular magic word or phrase, to cause the “hover” effect and to initiate a control interlock. In other embodiments, an RFID tag in the wand **100**, the receiver, and/or the effects controller is used to initiate the “hover” effect. In yet other embodiments, the proximity sensor is located remote to the wand **100**, such as near or in the receiver and/or effects controller.

Wand Operation

A magic wand as disclosed and described herein may be used to cast an infinite possibility of “spells” or commands based on a single wand activation circuit, a single learned wand motion and only a few unique wand command signals selected using any of the various circuits and structures described above in connection with FIGS. **14-16** (of course more complex operations are also possible and desirable). For example, using the wand **100g** illustrated and described in connection with FIGS. **16A-16D** a user can easily transmit three distinct command codes selected by each of the three touch sensors **108**, **110**, **112**. Touching either the “+” or the “-” symbols and waving the wand in the required motion triggers the internal wand activation circuit and causes the wand to transmit a radio frequency (RF) or infrared (IR) signal corresponding to an “ON/CAST” or “OFF/BLOCK” command or spell, respectively. This can be useful, for example, for turning on/off various play effects over long distances (up to 100 meters) and for basic game play such as spell casting competitions, target practice, and the like.

If it is desired to provide signal directionality so that the command signal or spell can be aimed or cast at various particular selected play effects or objects, then a directional signal source such as IR and/or directionalized RF is preferably selected. Alternatively, a combination of directional (e.g., IR) and omni-directional (e.g., RF) signal sources may be used effectively to provide a desired directional spell-casting capability. For example, a momentum-actuated switch or accelerometer (not shown) internally disposed within the tip of wand **100** can be used to activate a directional signal source (e.g., a light bulb or L.E.D. shining a beam or cone of light) when a predetermined momentum force or acceleration is reached. Such a wand with internal wand activation circuitry and/or a directional signal source may replace, for example, a gun or a rifle in a conventional shooting gallery or target game such as disclosed in U.S. Pat. No. 4,296,929 to Meyer et al. and U.S. Pat. No. 5,785,592 to Jacobsen, both of which are incorporated by reference herein in their entireties.

Waving and activating the wand while touching the “*” symbol preferably initiates the beginning of a “complex” spell comprising multiple combinations of the first two (base-2 coding) or all three wand motions (base-3 coding). Of course, those skilled in the art will appreciate that with three touch sensors, up to base-8 coding is possible by including combinations of simultaneously activated sensors. Thus, various spell “recipes” or incantations can be described and carried out using a sequence of individual commands and corresponding wand motions as represented, for example, by the three distinct magic symbols. Table 3, below, illustrates some examples of complex spells/commands that are possible using base-3 coding.

TABLE 1

Spell Formula Effect	
+	"on" or "cast spell"
-	"off" or "block spell"
*	"start complex spell"
*+	"move object"
*-	"stop object"
+	"start/increase levitation"
-	"stop/decrease levitation"
++	"unlock/open door"
**+*	"lock/close door"
*++	"Fire Spell"
*+-	"Block Fire spell"
*+++	"Ice Spell"
*++-	"Block Ice Spell"

Using up to 6 combinations of 2 wand motions (base-2), wand users can produce 126 different spells. Using up to 6 combinations of 3 wand motions (base-3), wand users can produce 1092 different spells. Using up to 6 combinations of 8 wand motions (base-8) produces 299,592 different possible spells. There is virtually no limit to the number of different spells that can be created and executed in this fashion. Preferably, once a complex spell is initiated and during each further step thereof a timer is initiated by the associated active receiver module and/or effects controller. If an additional command signal is not received within a predetermined time period (e.g. 0.5-3 seconds) the complex spell is considered "completed" and the effects controller actuates the appropriate relay to trigger whatever appropriate effect(s) correspond to the complex spell received. If the spell is incomplete or is inaccurate in any way, preferably only a "swoosh" or similar sound effect is triggered indicating that a spell was cast but did not work.

If desired, the active receiver module or associated effects controller can also be configured to give users audible and/or visual cues as each complex spell is being cast. This is in order to help users cast complex spells and help them identify when they have made a mistake or if they are about to cast the wrong or an unintended spell. For example, various themed feedback effects such as glowing lights, halo effects or escalating sound effects can be provided as each step in a complex spell is successfully completed. Again, this helps users learn the spells and understand where they perhaps went wrong in casting a particular spell. It also helps users discover and learn new spells by trial and error experimentation and by memorizing various spell sequences/commands that are observed to produce desired effects.

Preferably, users participate and advance in an interactive magic experience or game over time (e.g., weeks, months or years) according to a predetermined progression of gaming levels, wand levels and/or experience levels. For example, the various RF receivers disposed within a compatible play space could be programmed so that users of Level-1 wands may only be able to cast spells by actually touching their wands to whatever object they wish to control/actuate. Users of Level-2 wands would be able to cast simple (e.g., on/cast and off/block) spells over short and medium range distances, but not complex spells. Users of Level-3 wands would be able to cast simple spells (e.g., on/cast and off/block) and some complex spells (e.g., spells requiring up to 3 wand motions) over short, medium and long range distances, but not more complex spells requiring 4 or more wand motions. Users of Level-4 wands would be able to cast all types and varieties of simple and complex spells over short, medium and long distances using any number of wand motions as desired. Certain "master" level users may also be able to program or define

their own spells and share them with other users. There is no limit to the number and complexity of spells and corresponding special effects that may be created.

Wand levels can easily be set and changed, for example, by accessing the internal circuitry of each wand and flipping various dip switches to change the address or coding of the internal RF/IR transmitter. Alternatively, within a play facility wand levels may be set and stored at the receiver/controller level by tracking each wand unique ID code (UPIN/UGIN) and using a computer and an indexed data-base to look up the corresponding wand level and any other relevant gaming information associated with each unique UPIN/UGIN. Preferably, when a user reaches the appropriate number of points or experience for advancement to the next level, a special congratulatory effect is actuated and the user is thereby notified that he or she has earned additional magic powers. If desired, a short graduation ceremony may be presided over by a "Grand Wizard" while the user's wand is upgraded with new magic powers (e.g., insertion of new electronics and/or adjustment of various dip switches, circuit jumpers, combinations of the same or the like).

Wand Fabrication, Assembly and Detailing

One particularly exciting and rewarding aspect of an immersive interactive magic experience in accordance with the present invention is providing users with an opportunity to select, build and/or decorate their own magic wands. Accordingly, preferably all or most of the wand components are standardized, modularized and interchangeable so that various prefabricated wand components and starting materials can be stocked (e.g., in a "wizards workshop") and individually purchased by users to create an endless variety of unique and individualized finished wands having evolving powers, abilities and/or aesthetics.

For the most fully immersive experience possible it is most desirable that users are not distracted by the underlying technology that makes the wand work, but simply enjoy the immersive fantasy experience of practicing, performing and mastering "real" magic using a "real" magic wand. Thus, preferably most, if not all, of the wand components are simple in outward appearance and preferably contain no conspicuous outward manifestations (or have only minimal outward manifestations) of the technology within. Wand materials and components fabricated from natural or simulated natural materials, such as wood, bone leather, minerals (metals) and crystals are particularly preferred, although certainly not required.

The base wand component comprises the wand shaft 110. This may be a hollow plastic, wood or metal shaft provided in various materials and colors. For beginners or entry level users, a finished wand may be constructed by simply selecting a wand shaft 110 and then fitting it with one or more magnetic end caps 216, as illustrated. This provides a entry level wand (Level-1) that can be used to activate a variety of simple effects such as illustrated and described above in connection with FIGS. 17A-17C. If desired, a small wood lathe 230 can be used to create a custom wand handle 120 fabricated from a selected wood stock and a user's choice of any one of a number of available template patterns. If further desired, the end of the handle may be center-drilled to accommodate a threaded stud 121, bolt or other means for removably securing a selected decorative metal, wood and/or crystal knob 123a-123f. Such knobs may comprise, for example, any one of a number of standard, internally threaded cabinet knobs or drawer-pulls such as available from Emtek Products Inc. A Level-1 wand constructed in this fashion preferably facilitates basic game play within a compatible play facility, but is

not fully functional and, therefore, may not be capable of achieving some of the more desirable play effects or play experiences available.

The next level wand (Level-2) would preferably include, in addition, a simple passive RFID transponder **118** inserted and secured at one end thereof. The transponder **118** provides relatively short-range RF communications and also stores a unique person identifier number ("UPIN") and an optional unique group identifier number ("UGIN"). The UPIN and UGIN may be used to identify and track individual wands and play participants. The RFID transponder **118** also stores certain information identifying each play participant and/or describing certain powers or abilities possessed by an imaginary role-play character represented by the wand. These stored character attributes may be easily and conveniently transported with the wand to various compatible play facilities, games, video games, home game consoles, hand-held game units, and the like. If desired, the transponder **118** may be encapsulated in a colored epoxy, Lucite or the like and thereby disguised as a natural crystal or mineral/stone. A Level-2 wand preferably facilitates basic and intermediate game play within a compatible play facility. It has more functionality than a Level-1 wand, but is still not fully functional and, therefore, may not be capable of achieving some of the most desirable play effects or play experiences available.

The next level wand (Level-3) would preferably include, in addition, an active RF/IR module and associated wand activation circuitry for wirelessly casting a simple spell (e.g., ON/OFF) over longer distances. For example, this would be similar to the wand **100d**, illustrated and described above in connection with FIG. 12. Preferably, the wand would be self powered, requiring no batteries or other replaceable internal power source. However, if replaceable batteries are desired, they may optionally be encapsulated in a colored epoxy, Lucite or the like and thereby disguised and sold in the form of a natural "energy crystal" or mineral/stone. A Level-3 wand preferably facilitates basic, intermediate and some advanced game play within a compatible play facility. It has more functionality than a Level-1 and Level-2 wand and can cast simple spells over long distances, but is not able to cast more complex spells. Therefore, it may not be capable of achieving some of the most advanced and desirable play effects or play experiences available.

The highest level wand (Level-4) would preferably include, in addition, circuitry and/or structure(s) for selecting and casting more advanced and/or complex spells (e.g., ON/OFF, increase/decrease, UP/DOWN, change colors, simulated levitation, or the like). For example, this would be similar to the wands **100f/100h**, illustrated and described above in connection with FIGS. 14-16. Preferably, the wand would be self powered, requiring no batteries or other replaceable internal power source. A Level-4 wand preferably facilitates basic, intermediate and all advanced game play within a compatible play facility. It has more functionality than a Level-1, Level-2 and Level-3 wand and can cast a variety of simple or complex spells over long distances to achieve the most advanced and spectacular magical play effects.

Preferably, in all cases described above, the wand shaft **110**, handle **120** and/or knob **123** may be further decorated and/or individualized, as desired, with various monograms, engravings, stickers, stains, custom paint and the like, to suit the tastes of each individual user. For example, various assembly and fabrication stations may preferably be provided within a dedicated "workshop" area whereby wand purchasers may personally attend to the selection, fabrication, assembly and final detailing of their personal wands. Similarly,

wand "kits" may also be selected, packaged and sold whereby purchasers can assemble and decorate their own wands in the convenience of their own home using the wand components, materials and decorative elements illustrated and described above. FIGS. 19A-19P illustrate various examples of wands, wand handles or grips, wand add-ons, and wand knobs that have been fabricated, assembled and detailed in a manner as described above.

RFID Tags/Transponders

Many of the preferred embodiments of the invention illustrated and described above are RFID-enabled—that is, they utilize RFID technology to electrically store and communicate certain relevant information (e.g., UPIN and UGIN, game levels, points, combinations of the same or the like) and/or to wirelessly actuate or control various magical play effects. RFID technology provides a universal and wireless medium for uniquely identifying objects and/or people and for wirelessly exchanging information over short and medium range distances (10 cm to 10 meters). Commercially available RFID technologies include electronic devices called transponders or tags, and reader/writer electronics that provide an interface for communicating with the tags. Most RFID systems communicate via radio signals that carry data either uni-directionally (read only) or, more preferably, bi-directionally (read/write).

Several examples of RFID tags or transponders particularly suitable for use with the present invention have been illustrated and described herein. For example, in the particular preferred embodiments illustrated and described above, a 134.2 kHz/123.2 kHz, 23 mm glass transponder is preferably selected, such as available from Texas Instruments, Inc. (<http://www.tiris.com>, e.g., Product No. RI-TRP-WRHP). As illustrated in FIG. 21A, this transponder basically comprises a passive (batteryless) RF transmitter/receiver chip **240** and an antenna **245** provided within an hermetically sealed vial **250**. A protective silicon sheathing **255** is preferably inserted around the sealed vial **250** between the vial and the inner wall of the tube **110** to insulate the transponder from shock and vibration. If desired, the RFID transponder **118** may be modified to provide an optional external interrupt/disable line **260**, such as illustrated in FIG. 21A and as described in more detail above in connection with FIGS. 1 and 5.

However, those skilled in the art will readily appreciate from the disclosure herein that the invention is not limited to the specific RFID transponder devices disclosed herein, but may be implemented using any one or more of a wide variety of commercially available wireless communication devices such as are known or will be obvious from the disclosure herein to those skilled in the art. These include, without limitation, RFID tags, EAS tags, electronic surveillance transmitters, electronic tracking beacons, Wi-Fi, GPS, bar coding, and the like.

Of particular interest for purposes of practicing the present invention is the wide variety of low-cost RFID tags that are available in the form of a printed circuit on a thin, flat adhesive-backed substrate or foil. For example, the 13.56 MHz RFID tag sold under the brand name Tag-it™ and available from Texas Instruments, Inc. (<http://www.tiris.com>, Product No. RI-I03-110A) has particular advantages in the context of the present invention. Paper thin and batteryless, this general purpose read/write transponder is placed on a polymer tape substrate and delivered in reels. It fits between layers of laminated paper or plastic to create inexpensive stickers, labels, tickets and badges. Tag-it™ inlays have a useful read/write range of about 25 cm and contain 256 bits of on-board memory arranged in 8×32-bit blocks which may be programmed (written) and read by a suitably configured read/

write device. Such tag device is useful for storing and retrieving desired user-specific information such as UPIN, UGIN, first and/or last name, age, rank or level, total points accumulated, tasks completed, facilities visited, etc. If a longer read/write range and/or more memory is desired, optional battery-powered tags may be used instead, such as available from AXCESS, Inc. and/or various other vendors known to those skilled in the art.

Another RFID tagging technology of particular interest for purposes of practicing the present invention are the so-called "chipless" RFID tags. These are extremely low-cost RFID tags that are available in the form of a printed circuit on a thin, flat adhesive. These tags are similar in size, shape and performance to the Tag-it™ inlays described above, except that these tags require no on-board integrated circuit chip. Chipless RFID tags can be electronically interrogated to reveal a pre-encoded unique ID and/or other data stored on the tag. Because the tags do not contain a microchip, they cost much less than conventional RFID tags. An adhesive-backed chipless RFID tag with up to 10 meters range and 256 bits of data, can cost one tenth of their silicon chip equivalents and typically have a greater physical performance and durability. For example, a suitable chipless RFID tag is being made available from Checkpoint Systems under its ExpressTrak™ brand. Very inexpensive chipless RFID tags (and/or other types of RFID tags) may also be directly printed on paper or foil substrates using various conductive inks and the like, such as are available from Parelec Inc. under its Parmod VLT™ brand.

In the context of carrying out an interactive gaming experience, play experience or entertainment experience, such as the type generally disclosed and described herein, such adhesive-backed tag devices and the like are highly advantageous. They are inexpensive, disposable, and may be easily secured or applied to virtually any play object, wand, wristband, badge, card or the like, for electronically storing and retrieving desired user-specific or object-specific information. Such information may include, for example, UPIN, UGIN, object type/size/shape/color, first and/or last name, age, rank or level, total points accumulated, tasks completed, facilities visited, combinations of the same or the like. For example, FIG. 20A illustrates one preferred embodiment of a wand toy **100i** having an adhesive-backed RFID tag **322** secured thereon for enabling the wand **100i** to interact with various play effects located within an RFID-enabled play facility or play environment. FIG. 20B illustrates a second preferred embodiment of a wand toy **100j** having an adhesive-backed RFID tag **322** secured thereon for enabling the wand **100j** to interact with various play effects located within an RFID-enabled play facility or play environment. Similar RFID tags may also be applied to any of the other wands **100a-h** disclosed and described herein or any other toys, play objects, jewelry, trinkets, action figures, collectibles, trading cards and generally any other items desired to be incorporated as part of an RFID-enabled gaming experience.

FIGS. 20E and 20F illustrate one possible preferred embodiment of a key chain trinket **321** incorporating an RFID tag **322** suitable for use in various RFID-enabled gaming and entertainment experiences as disclosed herein. Such RFID-enabled items not only make the overall gaming and entertainment experience more exciting and enjoyable, but they can create unique branding opportunities and additional lucrative revenue sources for a play facility owners/operators. Moreover, and advantageously, character attributes developed during a play a participant's visit to a local play facility are stored on the tag **322**. When the play participant then revisits the same or another compatible play facility, all of the

attributes of his character are "remembered" on the tag so that the play participant is able to continue playing with and developing the same role-play character. Similarly, various video games, home game consoles, and/or hand-held game units can be and preferably are configured to communicate with the tag in a similar manner as described above and/or using other well-known information storage and communication techniques. In this manner, a play participant can use the same role play character he or she has developed with specific associated attributes in a favorite video action game, role-play computer game or the like.

Trading cards incorporating RFID tags are also particularly advantageous in the context of an interactive role-playing game such as disclosed herein. For example, FIGS. 20C and 20D are front and rear views, respectively, of an optional RFID-enabled trading card **325** for use within an interactive gaming experience as described herein. For example, such RFID-enabled trading cards may be used instead of or as an adjunct to the wand **100** with RFID transponder **118** as illustrated and described above in connection with FIG. 1. Each card **325** preferably comprises a paper, cardboard or plastic substrate having a front side **328** and a back side **330**. The front **328** of the card **325** may be imprinted with graphics, photos, or any other information as desired. In the particular embodiment illustrated, the front **328** contains an image of a magical wizard character **332** in keeping with an overall magic or wizard theme. In addition, the front **328** of the card may include any number of other designs or information **334** pertinent to its use and application in the game. For example, the character's special magic powers, skills and experience level may be indicated, along with any other special powers or traits the character may possess.

The obverse side **330** of the card preferably contains the card electronics comprising an RFID tag **336** pre-programmed with the pertinent information for the particular person, character or object portrayed on the front of the card. The tag **336** generally comprises a spiral wound antenna **338**, a radio frequency transmitter chip **340** and various electrical leads and terminals **342** connecting the chip to the antenna. If desired, the tag may be covered with an adhesive paper label **344** or, alternatively, the tag may be molded directly into a plastic sheet substrate from which the card is formed. Preferably, the tag **336** is passive (requires no batteries) so that it is inexpensive to purchase and maintain. The particular tag illustrated is the 13.56 MHz tag sold under the brand name Tag-it™ available from Texas Instruments, Inc. (<http://www.tiris.com>, Product No. RI-I03-110A). The tag may be "read/write" or "read only", depending on its particular gaming application. Optionally, less expensive chipless tags may also be used with equal efficacy.

Those skilled in the art will readily appreciate from the disclosure herein that a variety of trading card designs having features and advantages as disclosed herein may be used to play a wide variety of unique and exciting games within an RFID-enabled play facility and/or using an RFID-enabled gaming device or game console. Alternatively, persons skilled in the art will appreciate from the disclosure herein that such games may be carried out using a conventional computer gaming platform, home game console, arcade game console, hand-held game device, internet gaming device or other gaming device that includes an RFID interface. Advantageously, play participants can use trading cards **325** to transport information pertinent to a particular depicted person, character or object to a favorite computer action game, adventure game, interactive play facility or the like. For example, a suitably configured video game console and video game may be provided which reads the card information and recreates

the appearance and/or traits of particular depicted person, character of object within the game. If desired, the game console may further be configured to write information to the card in order to change or update certain characteristics or traits of the character, person or object depicted by the card **325** in accordance with a predetermined game play progression.

Advantageously, RFID-enabled character trading cards and character traits, including special powers, and the like, need not be static in the game, but may change over time according to a central story or tale that unfolds in real time (e.g., through televised shows or movies released over the course of weeks, months or years). Thus, a character trading card that may be desirable for game play this week (e.g., for its special magic powers or abilities), may be less desirable next week if the underlying character is injured or captured in the most recent episode of the story. Another significant and surprising advantage of RFID-enabled trading cards is that multiple cards can be stacked and simultaneously read by a single RFID reader even where the cards are closely stacked on top of one another and even though the reader may be hidden from view. This feature and ability creates limitless additional opportunities for exciting game complexities, unique game designs and gaming strategies heretofore unknown.

FIGS. **33A-33D** are front views of various alternative embodiments of possible role-play character cards for use within a Harry Potter/Hogwarts interactive play structure. See, for example, U.S. Pat. No. 6,761,637 to Weston, incorporated herein by reference, which describes an interactive play structure in the theme of a "magic" training center for would-be wizards in accordance with the popular characters and storylines of the children's book series "Harry Potter" by J. K. Rowling. Role play cards **600** are preferably constructed substantially the same as the card **325** illustrated and described above in connection with FIGS. **20C**, **20D**, except with different character illustrations and/or graphics. For example, each card **600** may include a different character from a Harry Potter storyline representing a role-play character desired to be imagined by a play participant. The obverse side (not shown) includes an RFID tag, such as illustrated and described above in connection with FIG. **20D**. Alternatively, a magnetic "swipe" strip and/or other well known information storage means may be used with efficacy, so long as it is relatively compact, durable and inexpensive.

The particular size, shape and theme of the cards **600** is relatively unimportant. In the particular embodiment illustrated, the cards **600** are shaped and themed so as to be used as bookmarks for Harry Potter series books. These may be packaged and sold together with each Harry Potter book, or they may be sold separately as novelty items or the like. If desired, a hole or eyelet **610** may be provided at the top of each card **600** so as to facilitate wearing the card **600** as a pendant on a necklace **620** or as key-chain trinket. Smaller, pocket-sized cards and/or other similar RFID or magnetic transponder devices may also be used where convenience and market demand dictates. Such transponder devices are commercially available, such as from Texas Instruments, Inc. (<http://www.tiris.com>, e.g., Prod. Nos. RI-TRPW9WK, RI-TRP-R9QL, RI-TRP-WFOB).

Of course, those skilled in the art will readily appreciate from the disclosure herein that the underlying concept of an RFID-enabled card **325** and card game is not limited to cards depicting fantasy characters or objects, but may be implemented in a wide variety of alternative embodiments, including conventional playing cards, poker cards, board game cards and tokens, sporting cards, educational cards and the

like. If desired, any number of other suitable collectible/tradable tokens, coins, trinkets, simulated crystals or the like may also be provided and used with a similar RFID tag device for gaming or entertainment purposes in accordance with the teachings of the present invention.

For example, RFID tag devices may be included on "magic articles" that may be purchased or acquired in a gaming or interactive play system. For instance, a user may purchase an invisibility cloak, magic beads, belts, and the like during an interactive play experience. The RFID tags may be used to communicate to a central database that a certain person has purchased or is possession of the tagged item. The central database may then track the tagged items and/or may cause those in possession of the tagged items to have increased "magical" skills or powers, such as additional protection from the spells "cast" by opposing players.

RFID Readers/Writers

In accordance with another preferred embodiment of the invention various RFID readers and associated play effects are distributed throughout an entertainment facility and are able to read the RFID tags described herein and to actuate or control one or more effects in response thereto. For example, the UPIN and UGIN information can be conveniently read and provided to an associated computer, central network, display system or other tracking, recording or display device for purposes of interacting with an associated effect and/or creating a record of each play participant's experience within the play facility. This information may be used for purposes of interactive game play, tracking and calculating individual or team scores, tracking and/or locating lost children, verifying whether or not a child is inside a facility, photo capture and retrieval, and many other useful purposes as will be readily obvious and apparent from the disclosure herein to those skilled in the art.

FIG. **21B** is a simplified schematic diagram of one embodiment of an RFID reader/writer **300** for use with the wand and RFID transponder **118** of FIG. **21A**. A preferred reader/writer device is the Series 2000 Micro Reader available from Texas Instruments, Inc. (<http://www.tiris.com>, e.g., Product No. RI-STU-MRD1). As illustrated, the reader/writer **300** basically comprises an RF Module **302**, a Control Unit **304** and an antenna **306**. When the distal end of wand **100** and its internally contained transponder **118** comes within a predetermined range of antenna **306** (about 20-200 cm) the transponder antenna **245** is excited by the radiated RF fields **308** and momentarily creates a corresponding voltage signal which powers RF transmitter/receiver chip **240**. In turn, the RF transmitter/receiver chip **240** outputs an electrical signal response which causes transponder antenna **245** to broadcast certain information stored within the transponder **235** comprising, for example, 80 to 1000 bits of information stored in its internal memory. This information preferably includes a unique user ID (UPIN/UGIN), magic level or rank and/or certain other items of information pertinent to the user, the wand and/or the game or play experience.

A carrier signal embodying this information is received by antenna **306** of RFID reader/writer **300**. RF Module **302** decodes the received signal and provides the decoded information to Control Unit **304**. Control Unit **304** processes the information and provides it to an associated logic controller, PID controller, computer or the like using a variety of standard electrical interfaces (not shown). Thus, the information transmitted by transponder **118** and received by reader/writer **300** may be used to control one or more associated play effects through a programmable logic controller, for example. In one embodiment, the information transmitted includes data relating to the activation of the sensors **122**, **124** of the

31

wand **100**. In other embodiments, the transmitted information may include timing information, such as the duration of time that a sensor is activated and/or the duration of time between successive activations of the sensors **122**, **124**. Play effects, may include, for example, lighting effects, sound effects, various mechanical or pneumatic actuators and the like.

Preferably, RFID reader/writer **300** is also configured to broadcast or "write" certain information back to the transponder **118** to change or update information stored in its internal memory, for example. The exchange of communications occurs very rapidly (about 70 ms) and so, from the user's perspective, it appears to be virtually instantaneous. Thus, the wand **100** may be used to "magically" actuate and/or communicate with various associated effects by simply touching or bringing the tip of the wand **100** into relatively close proximity with the antenna **306** of a reader/writer unit **300**.

As indicated above, communication of data between a tag and a reader is by wireless communication. As a result, transmitting such data is always subject to the vagaries and influences of the media or channels through which the data has to pass, including the air interface. Noise, interference and distortion are the primary sources of data corruption that may arise. Thus, those skilled in the art will recognize that a certain degree of care should be taken in the placement and orientation of readers **300** so as to minimize the probability of such data transmission errors. Preferably, the readers are placed at least 30-60 cm away from any metal objects, power lines or other potential interference sources. Those skilled in the art will also recognize that the write range of the tag/reader combination is typically somewhat less (~10-15% less) than the read range and, thus, this should also be taken into account in determining optimal placement and positioning of each reader device **300**.

Typical RFID data communication is asynchronous or unsynchronized in nature and, thus, particular attention should be given in considering the form in which the data is to be communicated. Structuring the bit stream to accommodate these needs, such as via a channel encoding scheme, is preferred in order to provide reliable system performance. Various suitable channel encoding schemes, such as amplitude shift keying (ASK), frequency shift keying (FSK), phase shift keying (PSK) and spread spectrum modulation (SSM), are well known to those skilled in the art and will not be further discussed herein. The choice of carrier wave frequency is also important in determining data transfer rates. Generally speaking the higher the frequency the higher the data transfer or throughput rates that can be achieved. This is intimately linked to bandwidth or range available within the frequency spectrum for the communication process. Preferably, the channel bandwidth is selected to be at least twice the bit rate required for the particular game application.

FIG. **21C** is a simplified circuit schematic of the reader/writer unit **300** of FIG. **21B**. The read or write cycle begins with a charge (or powering phase) lasting typically 15-50 ms. During this phase, the RF Module **302** causes the antenna **306** to emit an electromagnetic field at a frequency of about 134.2 kHz. The antenna circuit is mainly formed by the resonance capacitor **C1** and the antenna coil **306**. A counterpart resonant circuit of the transponder **118** is thereby energized and the induced voltage is rectified by the integrated circuit **240** and stored temporarily using a small internal capacitor (not shown).

The charge phase is followed directly by the read phase (read mode). Thus, when the transponder **118** detects the end of the charge burst, it begins transmitting its data using Frequency Shift Keying (FSK) and utilizing the energy stored in the capacitor. The typical data low bit frequency is 134.2 kHz

32

and the typical data high bit frequency is 123.2 kHz. The low and high bits have different duration, because each bit takes 16 RF cycles to transmit. The high bit has a typical duration of 130 μ s, the low bit of 119 μ s. Regardless of the number of low and high bits, the transponder response duration is generally less than about 20 ms.

The carrier signal embodying the transmitted information is received by antenna **306** and is decoded by RF module **302**. RF Module **302** comprises integrated circuitry **312** that provides the interface between the transponder **118** and the Control Module **304** (data processing unit) of the Reader/Writer Unit **300**. It has the primary function and capability to charge up the transponder **118**, to receive the transponder response signal and to demodulate it for further digital data processing.

A Control Unit **304**, comprising microprocessor **314**, power supply **316** and RS232 Driver **318**, handles most data protocol items and the detailed fast timing functions of the Reader/Writer Module **300**. It may also operate as interface for a PC, logic controller or PLC controller for handling display and command input/output functions, for example, for operating/actuating various associated play effects.

Long Range Transmitter and Receiver

If desired, the wand **100** may also be configured for long range communications with one or more of the transceivers **300** (or other receivers) disposed within a play environment. For example, one or more transceivers **300** may be located on a roof or ceiling surface, on an inaccessible theming element, or other area out of reach of play participants. Such long-range wand operation may be readily achieved using an auxiliary battery powered RF transponder, such as available from Axxess, Inc., Dallas, Tex. If line of sight or directional actuation is desired, a battery-operated infrared LED transmitter and receiver of the type employed in television remote controls may be used, as those skilled in the art will readily appreciate. Of course, a wide variety of other wireless communications devices, as well as various sound and lighting effects may also be provided, as desired.

In many of the preferred embodiments of the invention as illustrated and described herein it is disclosed to use a radio frequency (RF) and/or infrared (IR) transmitter to send wand command signals over relatively long range distances (e.g., 10-100 meters or more). For example, wand **100A** illustrated and described in connection with FIG. **7** includes an internal RF/IR Module **150** for communicating various command signals to one or more remote RF/IR receivers and associated effects. Command signal receivers may be located, for example, on a remote roof or ceiling surface of a compatible play facility, a retail mall, restaurant, destination resort facility or even an outdoor public play area. Internal RF/IR Module **150** can comprise any number of small, inexpensive RF transmitters such as are commercially available from Axxess, Inc., of Dallas, Tex. If directionality is desired, any number of small, inexpensive infrared LED transmitters may be used, such as the type commonly employed in television remote controls, keyless entry systems and the like.

FIG. **22A** is a schematic block diagram of a particularly preferred transmitter module **150** adapted for use in accordance with the present invention. The transmitter module **150** generally comprises an RF transmitter **358** driven and controlled by a microprocessor or ASIC **350**. ASIC **350** includes address storage module **352**, data storage module **354** and shift register **356**. Address storage module **352** includes a stored address or coded value, for example, in parallel bit format, that is a preselected coded value that may be uniquely associated with a particular transmitter module **150**. Address storage module **352** applies the address coded value to an encoder, such as shift register **356** which, when enabled,

encodes the coded value by converting it from parallel bit format to serial bit format which is applied to radio frequency (RF) transmitter 358. Similarly, data storage module 354 may include coded data or commands provided by a user (e.g., via any of the various command input circuits and structures described above in connection with FIGS. 14-16). Data storage module 354 applies the coded data values to shift register 356 which, when enabled, encodes the coded data by converting it from parallel bit format to serial bit format which is also applied to radio frequency (RF) transmitter 358. Radio frequency transmitter 358 modulates the coded address and data values which is encoded in serial bit format onto a radio frequency carrier signal which is transmitted as an RF output signal (RF_{Out}) such as via a simple loop antenna.

Application of electrical power from an internal battery source 152 (or one or more self-generating power sources as described herein) is preferably controlled via wand activation circuitry 115 such as illustrated and described above in connection with FIGS. 1-6. Thus, transmitter module 150, address storage module 352, data storage module 354, shift register 356 and/or RF transmitter 358, are preferably only powered for a short period of time when the wand circuitry 115 is successfully actuated and a corresponding command signal is to be transmitted. Those skilled in the art will recognize from the disclosure herein that transmitter module 150 may be implemented in a variety of known electrical technologies, such as discrete electronic circuits and/or integrated circuits. An implementation employing an integrated microprocessor or an application specific integrated circuit (ASIC) 350 is shown diagrammatically in FIG. 22A. Preferably, integrated circuitry technology and/or surface mount componentry is used to reduce the physical size of the circuit 150 such that it is able to fit within the relatively small cavity 116 of wand shaft 110 or handle 120 (see FIG. 1).

FIG. 23A is a schematic block diagram of receiver module 362 which operates in conjunction with transmitter module 150 previously described. Radio frequency command signals transmitted by transmitter module 150 are provided as input signals (RF_{In}) to RF receiver 363 which may comprise a simple tuned circuit with loop antenna (not shown). Command signals received by RF receiver 363 are applied to a decoder, such as shift register 364 which converts the coded value therein from a serial bit format to a parallel bit format. Address comparator 366 receives at one input the transmitter module coded address value in parallel bit format from shift register 364 and at its other input a preselected fixed or dynamically stored coded value from address storage 368. The preselected coded value from address storage 368 corresponds to the preselected coded value of the transmitter module 150 with which receiver module 362 is associated or compatible. In other words, the preselected coded value stored in transmitter address storage 352 of transmitter module 150 is the same as or compatible with a preselected coded value as is stored in address storage 368 of receiver module 362 with which it is associated or compatible. If the coded address value in the received command signal matches all or a predetermined portion of the preselected fixed or dynamic coded value stored in address storage 368, this coincidence is detected by address comparator 370 and is applied to restart or reset receive timer 372. Receive timer 372 preferably has a time-out period of, for example, 0.5-3 seconds and, if it is not restarted or reset within this time period, it produces a command termination signal which tells an associated controller 374 to process the received command signals(s) and to actuate one or more corresponding play effects such as lighting effects 376, sound effects 377 and motorized actuators 378. In other embodiments, the receive timer 372 may determine the

type and/or intensity of the play effect based on the amount of time between command signals. For example, shorter durations of time between command signals may cause higher-intensity play effects, and longer durations of time may cause lower-intensity play effects. Each of the functional elements of receiver module 362 and controller 374 receive electrical power from a suitable power source 380, as illustrated.

In operation, a user activates circuitry 150 by appropriately waving or moving the wand. This causes electrical voltage from battery 150 to be applied across the RF transmitter module 150, thereby causing the RF transmitter module 150 to transmit a desired command signal (RF_{Out}) including coded address and optional coded data information. This signal is received and decoded by receiver module 362 as input signal (RF_{In}). The decoded transmitter address information is compared to a fixed or dynamically stored coded value from address storage 368. Preferably, an immediate effect such as a pulsing light or sound is actuated by controller 374 in order to provide visual and/or aural cues that a command signal was received. Receive timer 372 is initiated and the RF receiver module 362 awaits the next command signal. If no further signal is received before the time times out, then the spell is assumed to be complete and the controller 374 is instructed to process the received command signal(s) and actuate the appropriate relay(s) thereby triggering whatever appropriate effect(s) correspond to the spell received. Preferably, as noted above, if the spell is incomplete or is inaccurate only a "swoosh" or similar sound effect is triggered indicating that a spell was cast but did not work. For simple spells, a fixed coded value may be stored in address storage 368. For complex spells, the stored coded value may be dynamically changed to match an expected or required series or progression of command signals. Alternatively, address storage 368 may be fixed and command signals may be carried and communicated to controller 374 as decoded data corresponding to data stored in data storage module 354 (FIG. 22A).

For applications supporting multiple wands (i.e., multiple RF transmitter modules 150) within a single play space, the address comparator 366 of receiver module 362 is preferably configured to accept either: (1) a range of valid "compatible" addresses from the set of RF transmitter modules 150; or (2) any valid address from a list of valid addresses stored in address storage module 368. In the first case, each transmitter module 150 within a defined group of transmitter modules (e.g., all Level-1 wands) would preferably be configured to have a coded address value having a portion of address bits that are identical and a portion of address bits that may be unique, but unique data bits as selected by each user. The receiver module 362, upon detecting a compatible address bit sequence, decodes the data bits thereof and sets a latch selected by those particular data bits. A number of such latches, may be provided, for example, for recognizing and distinguishing further such command signals originating from multiple users and/or wands. In the second case, the receiver module 362 stores a list of specific coded values, i.e. valid addresses, in a memory, such as memory 368, and as transmitted addresses are received, they are compared to the valid addresses in this list. Thus, only signals transmitted by RF transmitter modules that are on the list of valid addresses are accepted by receiver module 362. In this manner, for example, command signals sent by Level-1 wands can be distinguished from command signals sent by Level-2 wands, which can be distinguished from Level-3 wands, etc.

Although the transmitter module 150 of FIG. 22A and the receiver module 362 of FIG. 23A are described with reference to RF technology, a skilled artisan will recognize from the disclosure herein that other types of wireless technology may

35

also be used. For example, FIG. 22B depicts an IR transmitter module 150' having an IR transmitter 358' that may be used to transmit signals such as the type commonly employed in television remote controls, keyless entry systems and the like. The other components of the IR transmitter module 150' may also be modified such that the IR transmitter module 150' is capable of functioning similarly to the RF transmitter module 150 discussed with reference to FIG. 22A. In addition, FIG. 23B illustrates an IR receiver module 362' having an IR receiver 363' usable to operate with the IR transmitter module 150' of FIG. 22B. The other components of the IR receiver module 362' may also be modified such that the IR receiver module 363' is capable of functioning similarly to the RF receiver module 363 discussed with reference to FIG. 23A.

FIG. 24 is a schematic block diagram of a portion of a receiver module 362" including an embodiment of address comparator 370' and of address storage 368' particularly suited for operating with a plurality of simultaneously operating transmitter modules 150 or 150'. For example, blocks in FIG. 24 that are the same as blocks in FIG. 23A and described above are shown in phantom and are identified by the same numeric designation as in FIG. 23A. Address storage 368' includes addressable registers or memory 386 in which are stored the preselected coded identification values corresponding to the preselected coded identification value of each of a plurality of compatible RF transmitter modules 150 desired to be operably associated with receiver 362". Address selector 388 repetitively generates a sequence of addresses including the addresses of all the registers of addressable register 386 within a relatively short time period less than about 50-100 milliseconds. Thus the complete set of preselected stored coded values are applied to one input of coded value comparator 390 whereby the received coded identification value received and decoded at the output of shift register 364 and applied to the other input of coded value comparator 390 is compared to each one of the stored coded values of the set thereof stored in addressable register 386.

Although the receiver module 362" of FIG. 24 is disclosed with reference to particular embodiments, a skilled artisan will recognize from the disclosure herein a wide variety of alternative structures and uses for the receiver module 362". For example, the receiver module 362" may be capable of receiving an IR signal and structured similarly to the IR receiver module 362' of FIG. 23B.

Comparator 370' preferably includes a latch circuit 392 having an addressable latch corresponding to each register in addressable register 386 and that is addressed by the same address value generated by address selector 388 to address register 386. When there is a match at the inputs of coded value comparator 390 between the received coded value and the then produced stored coded value, the occurrence of the match is stored by setting the designated corresponding latch in latch circuit 392. If received coded identification values corresponding to all of the stored fixed coded values are received and properly decoded, then all of the latches in latch circuit 392 will be set, thereby making a "true" condition at the inputs of AND gate 294 and causing its output to become "true". This "true" signal from AND gate 294 resets receive timer 372, as described above in connection with FIG. 23A, and also activates a reset circuit 296 to reset all the latches of latch circuit 392 so that the comparison sequence of received coded identification values to the set of stored fixed coded values begins again. If all of the preselected received coded values are not received, then all of the latches in latch circuit 392 are not set, the output of AND gate 294 does not become "true", and receive timer 372 times out and issues the command termination signal discussed above.

36

FIG. 25 is a detailed electrical schematic diagram of an exemplary embodiment of transmitter module 150 illustrated and discussed above. Electrical power is provided by one or more batteries 152 and/or other power sources as illustrated and described herein. This power is preferably switched by wand activation circuit 115 and/or optional timer module 402. Electrical power is provided via diode D2 to the transmit timer U1, such as an integrated circuit one-shot multivibrator type LM555 available from National Semiconductor Corporation. The time-out interval of multivibrator U1 is established by resistors R2, R3 and capacitor C1 which need not be high precision components. When wand activation circuit 115 is activated, a voltage is applied through resistor R1 to the gate of a transistor Q1. This causes electrical power to be applied from battery 152 to a five-volt voltage regulator U4 such as a type LM78L05 also available from National Semiconductor Corporation. Alternatively, the periodic output from U1 may be applied to the gate of a transistor Q1 to the same effect (e.g., for sending periodic "beacon" transmissions).

Regulated voltage from regulator U4 is applied to shift register 356 (pin 18) and RF transmitter 358. Shift register 356 is implemented by an encoder integrated circuit U2 such as a 212 series encoder type HT12E available from Holtek Microelectronics in Hsinchu, Taiwan, R.O.C. Non-volatile address storage 352 is implemented by twelve single pole switches in switch packages SW1 and SW2 which are set to produce a twelve-bit coded value which is applied in parallel bit format to encoder integrated circuit U2 of shift register 356. Once set by the manufacturer or the user, the preselected coded value stored in address storage 352 is fixed and will not change absent human intervention. However, in alternative embodiments SW2 may be replaced in whole or in part by wand command selection circuitry such as touch switches, mercury tilt switches and the like illustrated and described above in connection with FIGS. 14-16. Such circuitry enables users to actively select and change the coded data impressed upon address lines 8-10 of encoder integrated circuit U2. Integrated circuit U2 reproduces the coded address and data values in pulse-width modulated serial-bit format and applies it through diode D1 to RF transmitter 358. RF transmitter 358 includes a class B biased transistor Q2 in an L-C tuned RF oscillator transmitter coupled to a loop antenna 406 for transmitting the command signal coded values (address bits coded by SW1 and data bits coded by SW2) produced by encoder U2.

Transmitter module 150 need only employ a small antenna such as a small loop antenna and is not required to have optimum antenna coupling. In a typical embodiment, with a transmitter frequency of about 915 MHZ, a transmitter peak power output of less than or equal to one milliwatt produces a transmission range R of about 20-30 meters. Other frequencies and power levels may also be employed. The low transmitter power is particularly advantageous in that it allows the size of transmitter module 150 to be made very small.

FIG. 26 is an electrical schematic diagram of an exemplary embodiment of receiver module 362 illustrated and discussed above. Power is supplied by a voltage source 410 which can be either a battery or a DC power supply. Voltage from voltage source 410 is regulated by voltage regulator circuit U3 such as type LM78L05 to produce a regulated +5 volt power supply for the functional blocks of receiver module 362. In operation, command signals transmitted from transmitter modules are received at loop antenna 412 and applied to RF receiver 363 including a receiver sub-circuit integrated circuit U8 such as type RX-2010 available from RF Monolithics in Dallas, Tex. The identification signal, including the twelve bit coded

37

value in serial-bit format is coupled from the output of receiver sub-circuit U8 to shift register decoder and address comparator 364/366 which are implemented in an integrated circuit U5, such as a 212 series decoder type HT12D also available from Holtek Microelectronics. Decoder U5 converts the coded value in serial-bit format to parallel-bit format and compares that received coded value to the preselected stored coded fixed reference value in parallel bit format determined, for example, by the positions of the twelve single pole switches in switch packages SW3, SW4 of address storage module 368.

Receive timer 372 is implemented by one-shot timer integrated circuit U6a such as type 74123N and D-flip flop U7a such as type 74HC74D, both of which are available from National Semiconductor Corporation of Santa Clara, Calif. When comparator 366 detects a match between the received coded value from transmitter module 150 and the coded value stored in address storage 368 it resets one-shot timer U6a. If one-shot timer U6a is not again reset within the time determined by timing resistor R8 and timing capacitor C9, U6a then sets flip-flop U7a and its Q output becomes low thereby applying a voltage input to controller 374 signifying the end of a transmitted simple or complex spell. Controller 374 then processes the received command signal or signals (e.g., stored in a stack register) and appropriately operates one or more associated play effects 376.

Those skilled in the art will appreciate that the switch positions of the twelve switches SW1, SW2 of transmitter module 150 correspond to the switch positions of the corresponding twelve switches SW3, SW4 of receiver module 362. These preset values may be fixed or dynamic, as discussed above. The twelve-bits available for storing coded values may be apportioned in a convenient way, for example, into an address portion and into a data portion. For example, the twelve-bit coded value can be apportioned into a ten-bit address portion (1024 possible combinations) and a two-bit data portion, which would accommodate up to four different transmitter command signals. If desired, the ten-bit address portion can be further divided into various logical portions representing, for example, the designated wand level (e.g., 1, 2, 3 or 4), special acquired magic powers or skills, experience levels and the like. This coded data would preferably be shared and coordinated between all transmitter modules 150 and receiver modules 362 such that each wand effectively would have its own unique powers and abilities as represented and identified by the coded address data. Thus, certain receivers and associated play effects would not be actuated by certain wands unless the address coding of the transmitter module thereof is coded with the appropriate matching data. In addition, the timing between received signals may be used to determine the appropriate play effect or intensity of a play effect caused by operation of the wand 100. Persons skilled in the art will recognize also that recoding of transmitter modules is a convenient way to provide for advancement of game participants within an interactive gaming experience. For example, this can be accomplished manually (e.g., by flipping dip switches SW1/SW2) or automatically/wirelessly (e.g., via RF programmable code latching circuitry, not shown).

While the foregoing embodiments have been described in terms of a radio frequency (RF) transmission between a transmitter module 150 and receiver module 362, various alternative embodiments could also readily be implemented such as, for example, replacing (or complementing) RF transmitter and receiver set (358, 363) with an appropriately selected infrared (IR) transmitter and receiver set or a laser or light system. The IR or laser system would have particular advantage where, for example, it is desired to provide directional

38

control of a transmitted command signal such as may be useful for directional spell casting, target practice, and wand-based shooting galleries.

Light-Activated Interactive Play System

For example, FIG. 27 illustrates an exemplary embodiment of a light-activated interactive play system 414 for use with embodiments of the invention utilizing laser technology. As shown in FIG. 27, the interactive play system 414 comprises the magic wand 100 having a light emitting module 416, a display device 418, an image preparation device 420, a camera 422, and a control system 423.

The light emitting module 416 of the wand 100 advantageously emits a directional signal, such as, for example, visible or infrared light. In one embodiment, the light emitting module 416 comprises a semiconductor laser. The signal output from the light emitting module 416 is emitted from an end opening of the wand 100 in a direction substantially parallel to the wand body. The signal may be generated from particular motions of the wand 100, as described herein, or from other input from the user.

In one embodiment, the user operates the wand 100 such that the signal emitted from the light emitting module 416 is directed to the display device 418. The display device 418 may comprise any device, apparatus or medium usable to intercept, reflect, and/or capture the signal emitted from the light emitting module 416 at an arbitrary position on the display device. In one embodiment, the display device 418 comprises a screen. In other embodiments, the display device 418 may comprise a wall, a mist, a door, a transparent surface, or the like.

Furthermore, the illustrated interactive play system 414 comprises the image preparation device 420, which operates to cause at least one image to appear on the display device 418. In one embodiment, the image preparation device 420 projects a video image and/or a still image onto the display device 418. For example, the image preparation device 420 may comprise a video projector, an LCD projector, or the like. In other embodiments, the image preparation device 420 may comprise multiple devices usable to project or to cause an image to appear on the display device 418. A skilled artisan will recognize from the disclosure herein a wide variety of objects, characters, and/or images that may be projected on the display device 418. For instance, the image preparation device 420 may project the image of mythical creatures, such as a dragon or a unicorn; magical objects, such as a flying carpet; or fantasy characters, such as a wizard or an elf; combinations of the same or the like.

In the illustrated embodiment, the display device 418 comprises a translucent material and is arranged in front of the image preparation device 420. In such an arrangement, the user's view of the image preparation device 420 may be partially or entirely obstructed by the display device 418. In other embodiments, the image preparation device 420 may be located near, to the side of, or in front of the display device 418 so long as an image may appear on the display device 418. In yet other embodiments, the image preparation device 420 is electrically coupled to the display device 418 through a wired or wireless transmission medium so as to cause images to appear on the display device.

In an embodiment, the camera 422 is directed at the display device 418 and advantageously captures, detects and/or records the arbitrary position of the signal emitted from the light emitting module 416 as the signal is intercepted by the display device 418. For example, the camera 422 may comprise a high-speed still camera or a specialized video camera used to take periodic or continuous photographs of a surface of display device 418. In an embodiment of the invention in

which the light emitting module **416** outputs an infrared signal, the camera **422** is configured to record the infrared signal as it is intercepted by the display device **418**. The camera **422** advantageously outputs a signal based on the captured image data to the control system **423**, which captured image data includes information indicative of the position of the signal output by the light emitting module **416**. In yet other embodiments, multiple cameras **422** are used in the interactive play system **414** to capture, detect, or record the position of the light emitting module signal as it is intercepted by the display device **418**. For example, multiple cameras **422** may be directed at different sections of the display device **418** and/or may record or capture data from different angles.

In one embodiment, the control system **423** advantageously communicates with at least the image preparation device **420** and the camera **422**. For example, the control system **423** may comprise a general purpose or a special purpose processor. However, an artisan will recognize that the control system **423** may comprise an application-specific integrated circuit (ASIC) or one or more modules configured to execute on one or more processors.

The control system **423** receives and processes the image data received from the camera **422**. In one embodiment, the control system **423** analyzes the position and/or movement of the signal from the light emitting module **416** to determine modifications to be made to the subsequent images to be produced by the image preparation device **420**. For example, the control system **423** may determine from the image data that a user has cast a certain "spell" by motioning the wand **100**, and therefore the light emitting module **416**, in a particular recognizable pattern. The control system **423** may make this determination by tracking the movement(s) of the light emitting module signal across the display device **418**, which movement is recorded in the image data output from the camera **422**.

For example, the control system **423** may initially command the image preparation device **420** to project an image of a brick wall onto the display device **418**. The user, who sees the image of the brick wall, points his or her wand **100** toward the brick wall such that the light emitting module **416** outputs a signal, such as a red dot caused by a laser, onto the brick wall (and the display device **418**). The user then motions the wand in a particular pattern, such as is described herein, to cause a desired motion of the red dot across the display device **418**. The camera **422** records this movement in its image data, which is output to the control system **423** for processing. If the control system **423** determines from the image data that a certain spell has been cast, such as a "move wall" spell, the control system **423** causes the image preparation device **420** to project an image of the wall disappearing or moving out of the path or view of the user.

Although the interactive play system **414** is disclosed with reference to particular embodiments, a skilled artisan will recognize from the disclosure herein a wide variety of alternatives usable with the system **414**. For example, the display device **418** may comprise a large liquid crystal display (LCD) screen coupled to an image preparation device **420** comprising a digital video source, such as a memory. Furthermore, sensors, such as optical or infrared sensors, usable to detect the position and/or movement of the light emitting module signal may be used in place of, or in combination with, the camera **422**.

In yet another embodiment, the control system **423** may be in communication with a central system or database and/or various receivers capable of causing one or more play effects. Thus, the control system **423** may, in response to the signal emitted from the light emitting module **416**, control or cause

play effects other than modifications to the image on the display device **418**. For example, the control system **423** may command a light to turn on or a book to open based on the signal captured by the camera **422**.

FIG. 27A depicts yet another embodiment of an interactive system for use with light-activation. As shown, a light-activated interactive play system **414'** includes similar components as the interactive play system **414** of FIG. 27. In particular, the illustrated interactive play system **414'** includes the camera **422** that advantageously captures, detects and/or records the position of a signal emitted from the light emitting module **416** of the wand **100**. In one embodiment, the camera **422** is located within a substantially enclosed area, such as, for example, a room, and detects the signal emitted from the light emitting module **416** within the room and/or directed at objects or effects within the room. In other embodiments, multiple cameras **422** are located within a single room.

The camera **422** communicates with a control system **423'**. Similar to the control system **423** of FIG. 27, the control system **423'** receives and processes the image data received from the camera **422**. For example, the control system **423'** may analyze the position and/or movement of the signal from the light emitting module **416** within a room. In one embodiment, the control system **423'** advantageously communicates with one or more effects, such as through wired or wireless communications, to control or trigger the effects based on the image data from the camera **422**. For example, as illustrated in FIG. 27A, the interactive play system **414'** includes effects such as a chair **424**, a bookshelf **425** having at least one book **426**, and a magic hat **427** with flowers **428**.

An embodiment of a method for interactive game play will now be described with reference to FIG. 27A. A user or game participant enters a room having the interactive system **414'**. The user then maneuvers his or her wand **100** such that the light emitting module **416** emits its signal in a certain direction and/or pattern, which signal is captured by the camera **422**. The control system **423'** then receives image data from the camera **422** that includes information relating to the position and/or movement of the signal within the room. Using this image data, the control system **423'** triggers and/or controls at least one special effect.

For example, in one embodiment, if the user directs the signal from the light emitting module **416** toward the chair **424**, the control system **423'** causes the chair to "levitate" or to move. If the user directs the signal from the light emitting module **416** toward the bookshelf **425**, the control system **423'** may cause the book **426** to move or to open. If the user directs the signal from the light emitting module **416** toward the magic hat **427**, the control system **423'** may cause the flowers **428** to appear. Each of these described special effects may be controlled by associated effects controllers, such as motors and/or processors, that are in communication with the control system **423'**. In addition, a skilled artisan will recognize from the disclosure herein a wide variety of special effects usable with the interactive system **414'**. For example, the control system **423'** may trigger a cuckoo clock, a light to turn on, an inanimate object to speak, and so forth.

In yet other embodiments of the invention, such as illustrated in FIG. 27B, the user performs a predetermined pattern or movement of the wand **100** to initiate a "magic spell." The movement of the wand **100** causes a corresponding movement of the signal emitted by the light emitting module **416**, which signal is captured by the camera **422**. The control system **423'** then processes the image data received from the camera **422** to determine which "spell" was cast and to cause or trigger the special effect(s) associated with the particular spell.

Competitive Games and Play Effects

It will be apparent to those skilled in the art from the disclosure herein that the invention disclosed and described herein facilitates a plethora of new and unique gaming opportunities and interactive play experiences heretofore unknown in the entertainment industry. In one embodiment the invention provides a unique play experience that may be carried out within a compatible play facility, retail space and/or other facility utilizing a wand as disclosed and described herein. With a wand or other similarly enabled device, play participants can electronically and “magically” interact with their surrounding play environment(s) to produce desired play effect, thereby fulfilling play participants’ fantasies of practicing, performing and mastering “real” magic.

For example, FIG. 28 illustrates one preferred embodiment of a wand-actuated play effect comprising a player piano 429 that is adapted to be responsive to or controlled by an RF command signal transmitted by magic wand toy 100. Those skilled in the art will readily appreciate that an RF receiver and associated controller, such as disclosed and described herein, can easily be concealed within the piano 429 and/or in the vicinity thereof such that it electronically interfaces with and directs various selected control circuitry associated with the piano 429. These may include, for example, circuitry for controlling: power on/off, song selection, playing speed and volume, instrument selection and special sound effects, sound sampling, combinations of the same or the like. In operation, user 430 would wave the wand 100 in accordance with one or more specific learned motions selected by the user to achieve a desired effect (e.g., piano on/off, play next song, speed-up/slow down, change piano sound, combinations of the same or the like). Most preferably, the wand 100 contains internal activation circuitry, such as described herein, such that the wand may be activated by the motion induced thereon by a user and so that actuation and control of the special effect appears to be, and has the feeling to user 430 of being, created by “real” magic.

FIG. 29 illustrates another preferred embodiment of a wand-actuated play effect comprising magical or “enchanted” bookshelves 436. The bookshelves contain multiple shelves of simulated or real books 438 that are controlled by one or more concealed actuators. The actuators are preferably positioned and arranged such that, when actuated, they cause one or more selected books to move, vibrate or levitate. Again, those skilled in the art will readily appreciate that an RF receiver and/or associated controller, such as disclosed and described herein, can easily be concealed within the bookshelves 436 and/or in the vicinity thereof. Movement and vibration of selected books can be provided, for example, by various linear stepper-motor actuators associated with one or more of the books 438. Each actuator may be controlled, for example, by a magnetic reed switch closure hidden behind the binder of each book. As a user 430 lightly touches the binder of each book with a magnetically-tipped wand 100 the associated reed switch (not shown) is closed, connecting power to an associated vibrator/actuator. Then, as the user 430 waves the wand 100 in one or more particular ways the selected book appears to vibrate or move as if it is being lifted or controlled by the magic wand 100. More spectacular effects may include, for example: (i) an effect that causes all or some of the books 438 to vibrate or move violently, randomly and/or in a rhythmic pattern (e.g., as if dancing); (ii) an effect that causes one or more books to appear as if floating or levitating; (iii) an effect that causes all or some of the books to magically rearrange themselves; (iv) an effect that causes one or more selected books to talk or tell stories; and (v) an effect that causes two or more books to appear to have a quarrel,

argument or debate (e.g., about an interesting historical fact or event). Some or all of these larger, more spectacular effects may be, and preferably are, restricted to only users 430 who possess and have learned to use, for example, a Level-3 wand or above. Thus, for example, a goal-oriented or object-driven, interactive game may be provided wherein play participants compete with one another to learn and master certain game tasks in order to achieve successively more challenging goals or objectives and to thereby earn additional powers, spells, abilities, points, special recognition and/or other rewards within the context of an overall game experience. Preferably, in each case and regardless of the level of wand used, actuation and control of the special effect appears to be, and has the feeling to user 430 of being, created by “real” magic. Of course, many other possible fun and/or exciting special effects will be readily apparent and obvious from the disclosure herein to persons skilled in the art.

FIG. 30 illustrates another preferred embodiment of a wand-actuated play effect comprising a water fountain 440 having one or more associated water features 442 responsive to or controlled by an RF command signal transmitted by one or more wands 100. An RF receiver and associated controller, such as disclosed and described herein, can easily be placed within an associated fountain control system or panel, electronically interfacing therewith to direct or control various selected fountain features or functions. These may include, for example, on/off control of water flow, fountain lighting, special water features 442, combinations of the same or the like. In operation, one or more users 430 would wave their wands 100 in accordance with one or more specific learned motions selected by each user to achieve a desired effect (e.g., fountain on, next water feature, increase/decrease water feature, change lighting intensity/color, or the like). Most preferably, each wand 100 contains internal activation circuitry, such as described herein, such that each wand may be activated by the motion induced thereon by each user and so that actuation and control of the special effect appears to be, and has the feeling to users 430 of being, created by “real” magic.

FIGS. 31A and 31B are time-lapsed schematic illustrations of a preferred embodiment of a play facility or play center constructed in accordance with the present invention. The play facility may comprise a family entertainment center, retail entertainment space, arcade, theme park, destination resort, restaurant, or the like, themed as a magic training center or any variety of other suitable themes as may be desired. The play facility preferably comprises multiple wand-actuated play effects 400, such as talking animals 452, magic hats 454, crystal balls 456, enchanted books 458, and various shooting-gallery-style pop-up target effects 460, 462. These may be physical play objects configured with special effects, as illustrated, and/or they may be graphical or computer-generated images displayed, for example, on one or more associated computer monitors, TV monitors, DVD display monitors, or computer gaming consoles and the like, such as illustrated in FIG. 27B. Those skilled in the art will readily appreciate from the disclosure herein that all of these effects and many other possible play effects may be actuated or controlled by wand 100 using one or more RF receivers, RFID reader/writers and/or magnetic reed switches, as disclosed and described above.

Some interactive play effects 400 may have simple or immediate consequences, while others may have complex and/or delayed consequences and/or possible interactions with other effects. Some play effects 400 may local (short range) while other effects may be remote (long range). Each play participant 430, or sometimes a group of play participants working together, preferably must experiment with the

various play effects using their magic wands **100** in order to discover and learn how to create one or more desired effect(s). Once one play participant figures it out, he or she can use the resulting play effect to surprise and entertain other play participants. Yet other play participants will observe the activity and will attempt to also figure it out in order to turn the tables on the next group. Repeated play on a particular play element can increase the participants' skills in accurately using the wand **100** to produce desired effects or increasing the size or range of such effects.

Most preferably, a live-action object-oriented or goal-oriented, interactive game is provided whereby play participants compete with one another (and/or against themselves) within a compatible play space to learn and master certain play effects and game tasks in order to achieve successively more challenging goals or game objectives and to thereby earn additional powers, spells, abilities, points, special recognition and/or other rewards within the context of an overall game experience. For example, play participants can compete with one another to see which participant or group of participants can create bigger, longer, more accurate or more spectacular effects. Other goals and game objectives may be weaved into an entertaining story, such as a magical quest or treasure hunt in which play participants immersed. The first task may be to build a magic wand. The next task may be to learn to use the magic wand to locate and open a secret treasure box filled with magical secrets (e.g., various spell formulas or magical powers). The ultimate goal may be to find and transform a particular frog (identified by, e.g., secret markings or other secret characteristics) into a prince/princess. Of course, many other gaming and theming possibilities are possible and desirable. Optionally, various "take home" play effects can also be provided for the purpose of allowing play participants to continue the magical experience (and practice their skills) at home.

In one preferred embodiment, a user **430** would preferably point and/or wave the wand **100** in accordance with one or more specific learned motions or "spells" selected to achieve a desired effect on one or more selected objects. For example, as illustrated in FIG. **31B**, one spell may cause rabbit **452** to talk; another spell may cause hat **454** to magically sprout flowers **464**; another spell may cause book **458** to open with a frog **466** jumping out; another spell may cause an image of a wizard **468** to magically appear (with optional sound and lighting effects) within crystal ball **456**; another spell may cause candle **462** to magically light itself with a pop-up flame **470**. Most preferably, wand **100** contains internal activation circuitry, such as described herein, such that the wand may be activated by the motion induced thereon by user **430** and so that actuation and control of the special effect appears to be, and has the feeling to users **430** of being, created by "real" magic. To provide added mystery and fun, certain effects **400** may be hidden such that they must be discovered by play participants. If desired, various clues can be provided such as, for example, part of a magical mystery game.

In each of the play effects described above, it is possible, and in many cases desirable, to provide additional control interlocks so that multiple input signals are required to actuate a given desired effect. For example, a proximity sensor may be provided associated with a given effect and electronically interlocked with the effect controller such that the effect cannot be operated if the proximity sensor is not also actuated. This could help reduce inadvertent or random actuation of the various effects. Similarly, voice activated controls and voice recognition software could also be implemented and interlocked with the effect controller so that, for example, a

user **430** would need to say a particular "magic" word or phrase while waving the magic wand **100** in order to actuate a desired effect.

As mentioned, the proximity sensor may be used to provide a "hover" effect that is indicative of the initialization of a control interlock. For example, when a proximity sensor in the wand **100** is moved within a particular distance of a receiver and/or effects controller, a "hover" effect occurs, such as, for example, the turning on of a light, the movement or vibration of an object, or any other perceptible signal (visual or audible) that notifies the user that a play effect may be initiated. This "hover" effect may notify the user that a spell may be cast so as to cause one or more effects.

In other embodiments, an RFID reader is preferably interlocked with one or more effects controllers in order to provide more precise control of various effects and also improved tracking of game progress, points, or the like. For example, one or more objects or targets **452**, **454**, **456**, **458**, **462** can be selected at close range using an RFID transponder and associated RFID reader. Once all such desired objects have been selected, the long range RF capabilities of the wand **100** can be used to control all of the selected objects/effect simultaneously. Those skilled in the art will readily appreciate from the disclosure herein that similar functionality can be easily provided with various magnetic reed switches and the like provided in association with each object or target. If desired, various pop-up targets **462** and the like may be arranged in a shooting gallery **460** whereby a user **430** can practice aiming the wand **100** and casting various spells at one or more desired targets **462**. In this case the wand **100** preferably is adapted to send directional signals, such as infrared or laser, instead of or in addition to RF signals as described herein.

FIGS. **32A-D** illustrate one preferred embodiment of a wand-actuated game **500** having unique features and benefits in accordance with the present invention. The game **500** basically comprises a 3x7 grid of lighted squares (including optional visual graphics and/or sound effects) that are controlled by a game effects controller (not shown) and one or more RF receivers (not shown). Those skilled in the art will readily appreciate and understand from the disclosure herein how to set up and program a game controller and/or one or more RF receivers as disclosed and described herein so as to achieve the game functionality and various effects as will be described herein below. Preferably, one RF receiver (or IR receiver, RFID receiver, or the like) is provided for each play participant **430** so that command signals from each player can be distinguished. For example, multiple RF receivers may be directionally focused or range-adjusted so as to receive RF command signals only from a selected corresponding player **430a** or **430b**.

Individual squares within a defined playing field **504** are preferably lit or dimmed in a timed sequence in response to one or more predetermined RF command signals ("spells") received from one or more RF-enabled wands **100**. Preferably, special 3x1 arrays of squares **510a**, **510b** (labeled 1-2-3) are provided at opposite ends of a playing field **504** and are adapted to respond to a signal imposed by, for example, the presence, proximity or weight of play participants **430a**, **430b**, as they stand on each square. These special squares may be raised or otherwise differentiated, as desired, to indicate their special function within the game **500**. Actuating individual squares within arrays **510a** and **510b** (e.g., by stepping or standing on them) allows play participants **430a**, **430b** to select a corresponding column of squares in the playing field **504** in which they may desire to launch an attack, counterattack or defense using various learned spells or incantations. Spells may be actuated, for example, by waving wand **100** in

one or more particular learned motions selected to produce a desired play effect or spell. An infinite variety of such spells are possible as described above.

Preferably, when a spell is successfully cast by a player **430a** or **430b**, the first square immediately in front of the player lights up or is otherwise controlled to produce a special effect indicating that a spell has been cast. Other squares in the same column are then preferably lit in a timed sequence or progression moving toward the opposing player (see, e.g., FIGS. **32B** and **32C**). Most preferably, the lighting effects for each square and/or other associated special effects are controlled or varied in a way to indicate the type of spell cast (e.g., a fire ball spell, ice spell, transforming spell, or the like). For example, various colors or patterns of lights may be used to indicate each spell. Alternatively, various graphic images and/or associated sound effects may be used to indicate each spell. These may be displayed, for example, on an overhead TV or associated computer monitor (not shown).

When an opposing player perceives that a spell has been cast and is moving toward him, that player (e.g., player **430b** in FIG. **32B**) attempts to quickly identify the type of spell and to cast in the same column a counter-measure or "blocking spell" in an attempt to neutralize or block the advancing spell (see, e.g., FIG. **32C**). The blocking spell may be cast, for example, using the same particular wand motion or series of wand motions used to cast the "forward spell", except with a "block" command added. Thus, a blocking spell is launched toward the advancing spell, as indicated by a progression of lighted squares and/or other effects controlled in a similar fashion as described above. If the blocking spell is effective (i.e., properly selected and executed), then the advancing spell is neutralized and the lighted column of squares is cleared (see, e.g., FIGS. **32C** and **32D**). If the blocking spell is ineffective, then the advancing spell continues until it reaches the end of the column. Preferably, whenever a spell reaches the opposing side, points and/or other gaming advancements are awarded to the successful player. These may vary, for example, depending upon the difficulty level of the spell, the experience level of the opposing player, and the like. In one particularly preferred embodiment, successful players are rewarded (and unsuccessful players are punished) by allowing certain spells to "capture" or disable the opposing player's special square in each corresponding column (see, e.g., FIG. **32D**). Once all of a player's special squares **510a**, **510b** have been captured or disabled the game is ended.

Preferably, the speed of game play progresses and becomes faster and faster as game play continues (e.g., spells move faster). In this manner, the game **500** continually challenges game participants to improve their reaction speed and spell accuracy. The game also encourages players to learn and master more difficult or complex spells, as these will be typically be harder and take longer for an opponent to successfully block. Certain additional spells or advanced commands may also be provided for speeding up a spell or slowing down an advancing spell. Any infinite variety and possibility of other spells and game play nuances are possible and desirable in accordance with the fundamental aspects of the invention disclosed and described herein.

Those skilled in the art will also recognize from the disclosure herein that the game **500** is not limited to use with RF-enabled input devices, such as wands, cards, tokens and the like, as described herein. Alternatively, the game **500** may be readily adapted and used with a wide variety of other input devices, including, without limitation, RFID tracking, magnetic actuators, joysticks, push-buttons, computer mouse or keypad, foot pedals, motion sensors, virtual-reality gloves and the like, proximity sensors, weight sensors, or the like.

Similarly, the game **500** is not limited to use with a magic theme, but may be implemented in a wide variety of other suitable themes such as, without limitation, war games, martial arts, "shoot-out" games, alien invasion, memory games, board games, educational games, trivia games, strategy games, and the like. It is also specifically contemplated that the game **500** may be expanded or modified to accommodate 3 or more players. For example, a six-sided game field accommodating up to six different players may easily be implemented using a similar playing field made up of hexagonal "squares".

Master System

In addition, a skilled artisan will recognize from the disclosure herein that the foregoing competitive games and/or play effects may use a central or master system to coordinate, control, and/or monitor the status of the games or effects in a particular area. For example, a central database may be used to monitor the skill levels of all those who are participating in the competitive game in a particular location. In other embodiments, the central system may comprise a centralized computer network that monitors the operation of each wand **100** (e.g., the play effects caused by operation of the wand) within a particular area. In yet other embodiments, the wands **100** may automatically download information from the central system.

If a master system is utilized, preferably each wand **100** and/or RFID card **325** is configured to electronically send and receive information to and from various receivers or transceivers **300** distributed throughout a play environment using a send receive radio frequency ("SRRF") communication protocol. This communications protocol provides the basic foundation for a complex, interactive entertainment system which creates a seemingly magic interactive play experience for play participants who possess and learn to use the magic wand. In its most refined embodiments, a user may electronically send and receive information to and from other wands and/or to and from a master control system located within and/or associated with any of a number of play environments, such as a family entertainment facility, restaurant play structure, television/video/radio programs, computer software program, game console, web site, etc. This newly created network of SRRF-compatible play and entertainment environments provides a complex, interactive play and entertainment system that creates a seamless magical interactive play experience that transcends conventional physical and temporal boundaries.

SRRF may generally be described as an RF-based communications technology and protocol that allows pertinent information and messages to be sent and received to and from two or more SRRF compatible devices or systems. While the specific embodiments described herein are specific to RF-based communication systems, those skilled in the art will readily appreciate that the broader interactive play concepts taught herein may be realized using any number of commercially available 2-way and/or 1-way medium range wireless communication devices and communication protocols such as, without limitation, infrared-, digital-, analog, AM/FM-, laser-, visual-, audio-, and/or ultrasonic-based systems, as desired or expedient.

The SRRF system can preferably send and receive signals (up to 40 feet) between tokens and fixed transceivers. The system is preferably able to associate a token with a particular zone as defined by a token activation area approximately 10-15 feet in diameter. Different transceiver and antenna configurations can be utilized depending on the SRRF requirements for each play station. The SRRF facility tokens and transceivers are networked throughout a play environment.

These devices can be hidden in or integrated into the environmental infrastructure, such as walls, floors, ceilings and play station equipment. Therefore, the size and packaging of these transceivers is not particularly critical.

In a preferred embodiment, an entire entertainment facility may be configured with SRRF technology to provide a master control system for an interactive entertainment play environment using SRRF-compatible magic wands and/or tracking devices. A typical entertainment facility provided with SRRF technology may allow 300-400 or more users to more-or-less simultaneously send and receive electronic transmissions to and from the master control system using a magic wand or other SRRF-compatible tracking device.

In particular, the SRRF system uses a software program and data-base that can track the locations and activities of up to a hundred or more users. This information is then used to adjust the play experience for each user based on "knowing" where the user/player has been, what objectives that player has accomplished and how many points or levels have been reached. The system can then send messages to the user throughout the play experience. For example, the system can allow or deny access to a user into a new play area based on how many points or levels have been reached by that user and/or based on what objectives that user has accomplished or helped accomplish. It can also indicate, via sending a message to the user the amount of points or specific play objectives necessary to complete a "mission" or enter the next level of play. The master control system can also send messages to the user from other users.

The system is preferably sophisticated enough that it can allow multiple users to interact with each other adjusting the game instantly. The master system can also preferably interface with digital imaging and/or video capture so that the users activities can be visually tracked. Any user can locate another user either through the video capturing system or by sending a message to another device. At the end of a visit, users are informed of their activities and the system interfaces with printout capabilities. The SRRF system is preferably capable of sending and receiving signals up to 100 feet. Transmitter devices can also be hidden in walls or other structures in order to provide additional interactivity and excitement for play participants.

Suitable embodiments of the SRRF technology described above may be obtained from a number of suitable sources, such as AXCESS, Inc. and, in particular, the AXCESS active RFID network system for asset and people tracking applications. In another preferred embodiment the system comprises a network of transceivers **300** installed at specific points throughout a facility. Players are outfitted or provided with a reusable "token"-a standard AXCESS personnel tag clipped to their clothing in the upper chest area. As each player enters a specific interactive play area or "game zone" within the facility, the player's token receives a low frequency activation signal containing a zone identification number (ZID). The token then responds to this signal by transmitting both its unique token identification number (TID) along with the ZID, thus identifying and associating the player with a particular zone.

The token's transmitted signal is received by a transceiver **300** attached to a data network built into the facility. Using the data network, the transceiver forwards the TID/ZID data to a host computer system. The host system uses the SRRF information to log/track the guest's progress through the facility while interfacing with other interactive systems within the venue. For example, upon receipt of a TID/ZID message received from Zone 1, the host system may trigger a digital camera focused on that area, thus capturing a digital image of

the player which can now be associated with both their TID and the ZID at a specific time. In this manner the SRRF technology allows the master control system to uniquely identify and track people as they interact with various games and activities in a semi-controlled play environment. Optionally, the system may be configured for two-way messaging to enable more complex interactive gaming concepts.

In another embodiment, the SRRF technology can be used in the home. For enabling magic at the home, a small SRRF module is preferably incorporated into one or more portable toys or objects that may be as small as a beeper. The SRRF module supports two-way communications with a small home transceiver, as well as with other SRRF objects. For example, a magic wand **100** can communicate with another magic wand **100**.

The toy or object may also include the ability to produce light, vibration or other sound effects based on signals received through the SRRF module to complement the operation of the wand and/or the effects achieved. In a more advanced implementation, the magical object may be configured such that it is able to display preprogrammed messages of up to 50 characters or more on a LCD screen when triggered by user action (e.g. button) or via signals received through the SRRF module. This device is also preferably capable of displaying short text messages transmitted over the SRRF wireless link from another SRRF-compatible device. For example, FIG. **19G** shows a toy wand **100** having an LCD screen **113** for displaying short text messages.

Preferably, the SRRF transceiver **300** is capable of supporting medium-to-long range (10-40 feet) two-way communications between SRRF objects and a host system, such as a PC running SRRF-compatible software. This transceiver **300** has an integral antenna and interfaces to the host computer through a dedicated communication port using industry standard RS232 serial communications. It is also desirable that the SRRF transmission method be flexible such that it can be embedded in television or radio signals, videotapes, DVDs, video games and other programs media, stripped out and re-transmitted using low cost components. The exact method for transposing these signals, as well as the explicit interface between the home transceiver and common consumer electronics (i.e. TVs, radios, VCRs, DVD players, A/V receivers, etc.) is not particularly important, so long as the basic functionality as described above is achieved. The various components needed to assemble such an SRRF system suitable for use with the present invention are commercially available and their assembly to achieve the desired functionality described above can be readily determined by persons of ordinary skill in the art. If desired, each SRRF transceiver may also incorporate a global positioning ("GPS") device to track the exact location of each play participant within one or more play environments.

Most desirably, a SRRF module can be provided in "chip" form to be incorporated with other electronics, or designed as a packaged module suitable for the consumer market. If desired, the antenna can be embedded in the module, or integrated into the toy and attached to the module. Different modules and antennas may be required depending on the function, intelligence and interfaces required for different devices. A consumer grade rechargeable or user replaceable battery may also be used to power both the SRRF module and associated toy electronics.

Interactive Game Play

Embodiments of the present invention may be carried out using a wide variety of suitable game play environments, storylines and characters, as will be readily apparent to those skilled in the art. The following specific game play examples

are provided for purposes of illustration and for better understanding of the invention and should not be taken as limiting the invention in any way:

EXAMPLE 1

An overall interactive gaming experience and entertainment system is provided (called the "Magic" experience), which tells a fantastic story that engages children and families in a never-ending adventure based on a mysterious treasure box filled with magical objects. Through a number of entertainment venues such as entertainment facilities, computer games, television, publications, web sites, and the like, children learn about and/or are trained to use these magical objects to become powerful "wizards" within one or more defined "Magic" play environments. The play environments may be physically represented, such as via an actual existing play structure or family entertainment center, and/or it may be visually/aurally represented via computer animation, television radio and/or other entertainment venue or source.

The magical objects use the SRRF communications system allowing for messages and information to be received and sent to and from any other object or system. Optionally, these may be programmed and linked to the master SRRF system. Most preferably, the "magic wand" **100** is configured to receive messages from any computer software, game console, web site, and entertainment facility, television program that carries the SRRF system. In addition, the magic wand can also preferably send messages to any SRRF compatible system thus allowing for the "wand" to be tracked and used within each play environment where the wand is presented. The toy or wand **100** also preferably enables the user to interact with either a Master system located within a Magic entertainment facility and/or a home-based system using common consumer electronic devices such as a personal computer, VCR or video game system.

The master control system for a Magic entertainment facility generally comprises: (1) a "token" (gag, toy, wand **100** or other device) carried by the user **430**, (2) a plurality of receivers or transceivers **300** installed throughout the facility, (3) a standard LAN communications system (optional), and (4) a master computer system interfaced to the transceiver network (optional). If a Master computer system is used, preferably the software program running on the Master computer is capable of tracking the total experience for hundreds of users substantially in real time. The information is used to adjust the play for each user based on knowing the age of the user, where the user has played or is playing, points accumulated, levels reached and specific objectives accomplished. Based on real-time information obtained from the network, the system can also send messages to the user as they interact throughout the Magic experience.

The Master system can quickly authorize user access to a new play station area or "zone" based on points or levels reached. It can also preferably indicate, via sending a message to the user, the points needed or play activities necessary to complete a "mission." The Master system can also send messages to the user from other users. The system is preferably sophisticated enough to allow multiple users to interact with each other while enjoying the game in real-time.

Optionally, the Master system can interface with digital imaging and video capture so that the users' activities can be visually tracked. Any user can then locate another user either through the video capturing system or by sending a message to another device. At the end of a visit, users are informed of their activities and other attributes related to the Magic experience via display or printout.

For relatively simple interactive games, the Master system may be omitted in order to save costs. In that case, any game-related information required to be shared with other receivers or transceivers may be communicated via an RS-232 hub network, Ethernet, or wireless network, or such information may be stored on the wand itself and/or an associated RFID card or badge carried by the play participant. For retrofit applications, it is strongly preferred to provide substantially all stand-alone receivers or transceivers that do not communicate to a master system or network. This is to avoid the expense of re-wiring existing infrastructure. For these applications, any information required to be shared by the game system is preferably stored on the wand or other RFID device(s) carried by the play participants. Alternatively, if a more complex game experience is demanded, any number of commercially available wireless networks may be provided without requiring rewiring of existing infrastructure.

EXAMPLE 2

A computer adventure game is provided in which one or more play participants assume the role of an imaginary character "Pajama Sam" from the popular series of computer games published by Humongous Entertainment, Inc. of Woodinville, Wash. A Pajama Sam adventure character card **700**, such as illustrated in FIGS. **34A**, **34B**, is provided to each play participant. The card may be packaged and sold together with the game software, and/or it may be sold separately, as convenience and market demands dictate.

The card **700** may be constructed substantially the same as the cards **325**, **600** illustrated and described above in connection with FIGS. **20C-D** and **33**, except with different character illustrations and/or graphics. For example, each card **700** may include a different character from the Pajama Sam computer game series representing a role-play character desired to be imagined by a play participant. The obverse side (FIG. **34B**) includes an RFID tag **720**, such as illustrated and described above in connection with FIG. **20D**. Preferably, the tag **720** is covered with an adhesive paper label **725**. Alternatively, the tag **720** may be molded directly into a plastic sheet substrate from which the card **700** is then formed. Alternatively, a magnetic "swipe" strip and/or other well-known information storage means may be used with efficacy, so long as it is relatively compact, durable and inexpensive.

The particular size, shape and theme of the card **700** is relatively unimportant. In the particular embodiment illustrated, the card **700** is shaped and themed similar to a baseball trading card so that they may be collected and stored conveniently in any baseball card album or the like. If desired, a hole or eyelet (not shown) may be provided at the top of the card **700** so as to facilitate wearing the card **700** as a pendant on a necklace or as key-chain trinket. Of course, smaller, pocket-sized cards and/or other similar RFID or magnetic transponder devices may also be used where convenience and market demand dictates. Such alternative suitable transponder devices are commercially available, such as from Texas Instruments, Inc. (<http://www.tiris.com>, e.g., Prod. Nos. RI-TRP-W9WK, RI-TRP-R9QL, RI-TRP-WFOB).

A specially configured computer, video game, home game console, hand-held gaming device or similar gaming device is provided with a reader, and more preferably a reader/writer such as described above, that is able to communicate with the tag **720** or other information storage means associated with the card **700**. As each play participant plays his or her favorite Pajama Sam game the Pajama Sam character represented by the card **700** gains (or loses) certain attributes, such as speed, dexterity, and/or the possession of certain tools or objects

51

associated with the game play. All of this information is preferably stored on the card **700** so that the character attributes may be easily and conveniently transported to other similarly-equipped computer games, video games, home game consoles, hand-held game units, play facilities, and the like. In this manner, an imaginary role-play character is created and stored on a card that is able to seamlessly transcend from one play medium to the next.

For example, in the course of playing a typical Pajama Sam game, players must “find” certain objects or tools that they will use to solve certain puzzles or tasks presented by the game. Players “pick up” these objects or tools by clicking their mouse on the desired object. The computer game software then keeps a record of which objects have been collected and displays those objects on the computer screen when requested by the player. This is illustrated by FIG. **35A**, which is a screen shot from the computer game, “Pajama Sam, in No Need to Hide When It’s Dark Outside,” published by Humongous Entertainment, Inc. © 1996. The game begins in Pajama Sam’s bedroom, and the player is asked to find and click on certain objects **810** that Pajama Sam needs to begin his adventure—namely his flashlight, PajamaMan lunch box and PajamaMan mask. As these objects are located and collected, they are displayed on the bottom of the computer screen, as illustrated in FIG. **35A**.

FIG. **35B** is a screen shot from the same game where the player faces his first challenge or puzzle to solve. He or she must somehow make Pajama Sam operate the elevator **815** to take Pajama Sam up into the tree house **820** where his arch-enemy “Darkness” resides. To solve the puzzle the player explores the scene with his mouse and clicks on objects that might be useful to solve the puzzle. Eventually, the player will discover a pile of rocks **825** which Pajama Sam picks up and tosses into the basket **830** to operate the elevator. In the next scene (FIG. **35E**) Pajama Sam is inside the tree house and the player must decide which of three possible paths to take representing doors **840**, **845** and **850**. Doorway **850** leads to the scene illustrated in FIG. **35D** in which Pajama Sam (and the player) is challenged to a trivia game by a pair of talking doors. The player chooses from different categories of questions and attempts to choose correct answers from a multiple choice list provided by the game (see FIG. **35E**). Ultimately, the player is challenged with a question specific to the game (see FIG. **35F**) and which requires the player to have visited a particular location within the game where the information is contained. If the player has not completed that portion of the computer game, he or she cannot answer the question posed and Pajama Sam cannot advance in the adventure game (see FIG. **35G**).

If the player were to quit the game at this point, he or she could save the game on the host computer and return to the same computer later to complete the adventure. But the Pajama Sam character itself, its attributes, experiences and accomplishments are not portable and cannot presently be transferred from one game or gaming environment to another. However, the Pajama Sam adventure card **700** in accordance with the present invention enables a play participant to continue the adventure somewhere else (e.g. at a friend’s house, or a video arcade facility) without having to restart the game and repeat the steps that the player has already accomplished. With the Pajama Sam adventure card **700**, relevant details of the game experience and the Pajama Sam character are stored on the card **700** so that the player can take the card to another computer, game console, hand-held game device or a designated Pajama Sam play facility, to continue the adventure in a new and exciting play environment.

52

For example, the Pajama Sam play facility could be configured as a physical play space having theming and game play that parallels that of one or more of the Pajama Sam computer adventure games. Now our computer game player who has a Pajama Sam adventure card **700** can visit this play facility and the facility would be able to read the information on the card and determine that this particular player has already completed the first puzzle in the first Pajama Sam computer adventure game. If the player desires, he or she will be allowed to advance automatically in the game play within the Pajama Sam play facility so that the player can work on a new puzzle. If the player successfully solves a new puzzle at the play facility, this information will be recorded on the Pajama Sam adventure card **700**. The next time he or she plays the computer game the card can be automatically read and the computer experience can be modified or updated in accordance with the new information recorded on the card. In this manner, the character role-play experience becomes portable, personal and long-term. This, in turn, facilitates the development of even more sophisticated and complex role-play characters and longer, more enjoyable role play experiences as players are able to continue playing with and developing the same role-play character(s) over long periods of time and in different and varied play environments.

Similarly, various other video games, home game consoles, and/or hand-held game units can be and preferably are configured to communicate with the Pajama Sam adventure card **700** in a similar manner as described above and/or using other well-known information storage and communication techniques. In this manner, a play participant can use the Pajama Sam adventure card **700** and the role play character he or she has developed with specific associated attributes in a favorite video action game, role-play computer game, internet adventure game or the like.

EXAMPLE 3

A trading card game is provided wherein a plurality of cards depicting various real or imaginary persons, characters and/or objects are provided and wherein each card has recorded or stored thereon in an electronically readable format certain selected information pertaining to the particular person, character or object, such as performance statistics, traits/powers, or special abilities. The information is preferably stored on an RFID tracking tag associated with each card and which can be read electronically and wirelessly over a predetermined range preferably greater than about 1 cm when placed in the proximity of a suitably configured RF reader. Optionally, the RFID tag may be read/write capable such that it the information stored thereon may be changed or updated in any manner desired. Alternatively, a magnetic strip, bar code or similar information storage means may be used to store relevant information on the card.

FIGS. **36A** and **36B** depict one preferred embodiment of a trading card **900** having features and advantages in accordance with the present invention. The particular trading card illustrated in FIG. **36A** is provided in the theme of the popular Pokemon characters and, in particular, the character Pikachu. FIGS. **36C** and **36D** illustrate several other possible Pokemon themed trading cards which may be provided in accordance with the present invention. Each card preferably comprises a paper, cardboard or plastic substrate having a front side **905** and a back side **910**. The front **905** of the card **900** may be imprinted with graphics, photos, or any other information as desired. In the particular embodiment illustrated, the front **905** contains an image of the Pikachu character **925** in keeping with the Pokemon theme. In addition, the front **905** of the

53

card **900** may include any number of other designs or information **930** pertinent to its application. For example, the character's type, size and evolution may be indicated, along with any special powers or traits the character may possess.

The obverse side **910** of the card **900** preferably contains the card electronics comprising a radio frequency tag **920** pre-programmed with the pertinent information for the particular person, character or object portrayed on the front of the card. The tag **920** generally comprises a spiral wound antenna **950**, a radio frequency transmitter chip **960** and various electrical leads and terminals **970** connecting the chip **960** to the antenna. If desired, the tag **920** may be covered with an adhesive paper label (not shown) or, alternatively, the tag may be molded directly into a plastic sheet substrate from which the card **900** is formed.

Preferably, the tag **920** is passive (requires no batteries) so that it is inexpensive to purchase and maintain. Such tags and various associated readers and other accessories are commercially available in a wide variety of configurations, sizes and read ranges. RFID tags having a read range of between about 10 cm to about 100 cm are particularly preferred, although shorter or longer read ranges may also be acceptable. The particular tag illustrated is the 13.56 MHz tag sold under the brand name Tag-it™ available from Texas Instruments, Inc. (<http://www.tiris.com>, Product No. RI-I03-110A). The tag **920** has a useful read/write range of about 25 cm and contains 256-bits of on-board memory arranged in 8x32-bit blocks which may be programmed (written) and read by a suitably configured read/write device. If a longer read/write range and/or more memory is desired, optional battery-powered tags may be used instead, such as available from AXCESS, Inc. and/or various other vendors known to those skilled in the art.

Cards **900** may be collected or traded and/or they may be used to play various games, such as a Pokemon arena competition using an electronic interface capable of reading the card information. Such games may be carried out using a specially configured gaming device or, alternatively, using a conventional computer gaming platform, home game console, arcade game console, hand-held game device, internet gaming device or other gaming device that has been modified to include an RF reader or magnetic "swipe" reader device as illustrated and described above. Advantageously, play participants can use the trading cards **900** to transport information pertinent to a particular depicted person, character or object to a favorite computer action game, adventure game, interactive play structure or the like. For example, a suitably configured video game console and video game may be provided which reads the card information and recreates the appearance and/or traits of particular depicted person, character of object within the game. If desired, the game console may further be configured to write information to the card in order to change or update certain characteristics or traits of the character, person or object depicted by the card **900** in accordance with a predetermined game play progression.

Of course, those skilled in the art will readily appreciate that the underlying concept of an RFID trading card **900** and card game is not limited to cards depicting fantasy characters or objects, but may be implemented in a wide variety of alternative embodiments, including sporting cards, baseball, football and hockey cards, movie character cards, dinosaur cards, educational cards and the like. If desired, any number of other suitable collectible/tradable tokens or trinkets may also be provided with a similar RFID tag device in accordance with the teachings of the present invention as dictated by consumer tastes and market demand.

54

Although this invention has been disclosed in the context of certain preferred embodiments and examples, it will be understood by those skilled in the art that the present invention extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. Thus, it is intended that the scope of the present invention herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

What is claimed is:

1. A portable wireless interactive toy for amusing or entertaining one or more game participants playing a game in conjunction with a wireless-compatible gaming system in which at least a portion of the game is represented through one or more computer animations displayed on an associated display device and wherein game progress or performance for each individual game participant is simultaneously tracked in accordance with a unique identification number associated with said wireless interactive toy, said wireless interactive toy comprising:

an elongated body sized and configured to be held and moved freely in the air using a single hand to play said game at least in part by moving the elongated body in free space, said elongated body having an axis of elongation extending from a first end adapted to be held or gripped by a single hand of a game participant to a second end protruding from said first end and being in substantial coaxial alignment therewith;

an effects generator configured to display or produce one or more light, vibration or sound effects; and

a wireless radio frequency (RF) communication device storing a unique identification number for uniquely identifying said wireless interactive toy within said game and for distinguishing said wireless interactive toy from other wireless devices that may be operated by other game participants, said RF communication device comprising a wireless RF transceiver adapted to provide two-way wireless RF communications with a wireless-compatible gaming system and wherein said two-way wireless RF communications include communication of at least said unique identification number;

wherein said portable wireless interactive toy is configured and adapted to automatically establish a wireless communication link with said wireless-compatible gaming system when said wireless interactive toy is operated within a wireless communication range of said wireless-compatible gaming system, further configured to establish said wireless communication link at least in part by: i) receiving from said wireless-compatible gaming system a first wireless communication that includes a first identification number identifying said wireless-compatible gaming system, and ii) responding to said first wireless communication by transmitting a second wireless communication that includes said first identification number and a second identification number comprising said unique identification number of said wireless RF communication device.

2. The wireless interactive toy of claim 1 further comprising at least one motion sensor configured to sense one or more waving or shaking motions of said elongated body.

3. The wireless interactive toy of claim 2 wherein said at least one motion sensor is configured to sense and distinguish one or more waving, shaking, stroking or tapping motions of said elongated body.

4. The wireless interactive toy of claim 1 wherein said RF transceiver comprises a medium range wireless RF trans-

55

ceiver configured and adapted to wirelessly and electronically exchange information over a communication range of at least 10 feet.

5. The wireless interactive toy of claim 1 further comprising a global positioning system (GPS) device configured to determine the global position of said wireless interactive toy.

6. The wireless interactive toy of claim 1 wherein said effects generator is configured to selectively display or produce said one or more light, vibration or sound effects based on one or more wireless communications received from said wireless-compatible gaming system.

7. The wireless interactive toy of claim 1 further comprising a display screen configured to display game-relevant information based on one or more wireless communications received from said wireless-compatible gaming system.

8. The wireless interactive toy of claim 7 wherein said wireless RF transceiver is further adapted to wirelessly communicate game-relevant information to and from a second wireless interactive toy.

9. The wireless interactive toy of claim 1 in combination with said wireless-compatible gaming system configured and adapted to execute game software for carrying out said game.

10. The combination of claim 9 in further combination with said game software, said game software including program instructions for instructing said wireless-compatible gaming system to: i) conduct an interactive game in which a virtual play environment is visually and aurally represented through computer animation; ii) track game progress or performance of each game participant playing said game based at least in part on identifying and distinguishing one or more wireless input signals from each said game participant; and iii) adjust the play experience for each said game participant based on said tracked game progress or performance.

11. An interactive game for entertaining multiple play participants wherein at least a portion of said game is physically represented in a physical play environment through one or more physical play objects and wherein at least a portion of said game is virtually represented in a virtual play environment through one or more computer animations, said interactive game comprising:

at least one physical play object configured to be manipulated by one or more play participants in a physical play environment to produce one or more physical effects;

at least one gaming system configured to be operated by one or more play participants to produce in a virtual play environment one or more computer-animated visual, aural or tactile effects;

at least one wireless receiver adapted to receive wireless input signals from one or more associated portable wireless devices;

at least one portable wireless device sized and configured to be held and moved freely in the air by a play participant and operated to play said game at least in part by moving or transporting said portable wireless device within said physical play environment, said at least one portable wireless device comprising a wireless tracking device storing a unique identification number for uniquely identifying said portable wireless device within said game and for distinguishing said portable wireless device from other wireless devices, said tracking device comprising a wireless transmitter adapted to provide wireless communications with said at least one wireless receiver and wherein said wireless communications include communication of at least said unique identification number; and

a game control system configured to actuate or control one or more physical effects in said physical play environ-

56

ment and one or more computer-animated effects in said virtual play environment so as to provide an overall interactive game in which game progress or performance of multiple play participants playing said game in both said physical play environment and said virtual play environment are individually tracked according to said received wireless input signals, and wherein said game control system is further configured to adjust a game experience for each said play participant in said physical play environment and/or said virtual play environment based on said tracked game progress or performance.

12. The interactive game of claim 11 wherein said at least one physical play object comprises a portable toy.

13. The interactive game of claim 11 wherein said at least one gaming system comprises a personal computer, video gaming system, home-based gaming system, or web-based gaming system.

14. The interactive game of claim 11 wherein at least one said wireless receiver and said wireless transmitter comprise medium range wireless communication devices configured and adapted to wirelessly and electronically exchange information over a communication medium selected from the group consisting of: RF, infrared, laser, visual, audio, and ultrasonic.

15. The interactive game of claim 14 wherein said at least one wireless receiver comprises a first wireless radio frequency (RF) transceiver adapted to send and receive wireless signals to and from one or more associated wireless devices and wherein said wireless tracking device comprises a second wireless RF transceiver adapted to provide two-way wireless RF communications with said first wireless RF transceiver over a communication range of at least 10 feet and wherein said two-way wireless RF communications include communication of at least said unique identification number.

16. The interactive game of claim 11 wherein said at least one portable wireless device comprises an elongated body sized and configured to be held and moved freely in the air using a single hand to play said game at least in part by moving the elongated body in free space, said elongated body having an axis of elongation extending from a first end adapted to be held or gripped by a single hand of a play participant to a second end protruding from said first end and being in substantial coaxial alignment therewith.

17. The interactive game of claim 16 wherein said at least one portable wireless device further comprises at least one motion sensor configured to sense one or more waving or shaking motions of said elongated body.

18. The interactive game of claim 17 wherein said at least one motion sensor is configured to sense and distinguish one or more waving, shaking, stroking or tapping motions of said elongated body.

19. The interactive game of claim 11 wherein said at least one portable wireless device further comprises a global positioning system (GPS) device configured to determine the global position of said portable wireless device.

20. The interactive game of claim 11 wherein said at least one portable wireless device further comprises an effects generator configured to display or produce one or more light, vibration or sound effects.

21. The interactive game of claim 11 wherein said at least one portable wireless device further comprises a display screen configured to display game-relevant information.

22. The interactive game of claim 11 wherein said game control system is further configured and adapted to actuate or control said one or more physical effects in said physical play environment or said one or more computer-animated effects

57

in said virtual play environment so as to teach or train a play participant how to move said at least one portable wireless device to wirelessly actuate or control said one or more physical effects or computer-animated visual, aural or tactile effects.

23. The interactive game of claim 11 wherein said game control system is further configured and adapted to adjust a play experience for a play participant by allowing or denying access to one or more different game areas or game levels in said physical or virtual play environment based on said tracked game progress or performance.

24. The interactive game of claim 11 further comprising an image capture system configured to automatically capture one or more digital images of a play participant while said play participant is playing said game.

25. The interactive game of claim 24 further comprising an image storage and retrieval system configured to store, retrieve and display said one or more digital images.

26. An entertainment system for entertaining one or more game participants playing a game in which at least a portion of the game is produced through one or more computer animations displayed on an associated display device and wherein game progress or performance for each individual game participant is tracked simultaneously as said game is played, said entertainment system comprising:

at least one computer-animated gaming system comprising a computing device configured and adapted to produce one or more computer-animated visual, aural or tactile effects in accordance with a game played by said one or more game participants;

a first radio frequency (RF) wireless transceiver configured to communicate with said at least one computer-animated gaming system adapted to provide two-way wireless RF communications with one or more wireless input devices over a wireless communication range of at least 10 feet;

at least one wireless motion-sensitive input device sized and configured to be held and moved freely in the air and operated by a game participant using a single hand to play said game at least in part by moving substantially the entire input device in free space, said at least one input device comprising:

an elongated body having an axis of elongation extending from a first end adapted to be gripped by a single hand of a game participant to a second end extending coaxially from said first end;

a unique identification number for uniquely identifying said at least one input device within said game and for distinguishing said at least one input device from other wireless input devices that may be operated by other game participants;

a second RF wireless transceiver adapted to provide two-way wireless RF communications with said first transceiver, wherein said two-way wireless communications include communication of at least said unique identification number; and

an effects generator for selectively producing one or more light, vibration or sound effects based on one or more wireless communications received from said at least one computer-animated gaming system;

a game control system configured and adapted to actuate or control said one or more computer-animated effects in accordance with said game; and

game software configured and adapted to be executed by said game control system, said game software including program instructions for instructing said game control system to: i) conduct an interactive game in which a

58

virtual play environment is represented through one or more computer animations displayed on an associated display device; ii) simultaneously track game progress or performance of each game participant playing said game based at least in part on identifying or distinguishing each said wireless communication in accordance with said unique identification number; and iii) adjust a play experience for each said game participant based on said tracked game progress or performance.

27. The entertainment system of claim 26 wherein said at least one computer-animated gaming system comprises a personal computer, video gaming system, home-based gaming system, or web-based gaming system.

28. The entertainment system of claim 27 wherein said at least one computer-animated gaming system comprises multiple gaming systems provided in one or more play environments, said multiple gaming systems configured to communicate selected game-relevant data between said multiple gaming systems, wherein said game-relevant data comprises tracked game progress or performance for multiple game participants playing said game substantially simultaneously.

29. The entertainment system of claim 26 wherein said at least one wireless motion-sensitive input device comprises at least one motion sensor configured to sense one or more waving or shaking motions.

30. The entertainment system of claim 29 wherein said at least one motion sensor is configured to sense and distinguish one or more waving, shaking, stroking or tapping motions of said elongated body.

31. The entertainment system of claim 26 wherein said at least one wireless motion-sensitive input device comprises a global positioning system (GPS) device configured to determine the global position of said portable wireless device.

32. The entertainment system of claim 26 wherein said at least one wireless motion-sensitive input device further comprises a display screen configured to display game-relevant information.

33. The entertainment system of claim 26 wherein said game software further comprises program instructions for instructing said game control system to teach or train a game participant how to move said at least one input device to wirelessly actuate or control said one or more computer-animated visual, aural or tactile effects in accordance with said game.

34. The entertainment system of claim 26 wherein said game software further comprises program instructions for instructing said game control system to adjust a play experience for a game participant by allowing or denying access to one or more different game levels in said game based on said tracked game progress or performance.

35. The entertainment system of claim 26 wherein said at least one wireless motion-sensitive input device comprises a first wireless motion-sensitive input device and a second wireless motion-sensitive input device, and wherein said second input device is adapted to wirelessly communicate with said first input device.

36. The entertainment system of claim 26 further comprising an image capture system adapted to be triggered at least in part by said game control system for capturing one or more digital images of a game participant playing said game.

37. The entertainment system of claim 36 further comprising an image storage-retrieval-display system configured to selectively store, retrieve and display said one or more captured digital images.

38. An amusement attraction for entertaining multiple play participants playing a game wherein at least a portion of said game is physically represented in a physical play environ-

ment and wherein at least a portion of said game is virtually represented in a virtual play environment through one or more computer animations, said amusement attraction comprising:

a physical play environment comprising a play structure, themed play space or entertainment facility configured and arranged to produce one or more physical effects in accordance with a game, said physical play environment configured to support simultaneous use by multiple play participants;

a virtual play environment comprising at least one gaming system comprising an associated computing device configured and adapted to produce one or more computer-animated visual, aural or tactile effects in accordance with said game;

at least one wireless receiver adapted to receive wireless input signals from one or more associated portable wireless devices and to communicate said wireless input signals to said physical play environment and/or said virtual play environment;

at least one portable wireless device sized and configured to be held and moved freely in the air by a play participant and operated to play said game at least in part by moving or transporting said portable wireless device within said physical play environment, said at least one portable wireless device comprising a wireless tracking device storing a unique identification number for uniquely identifying said portable wireless device within said game and for distinguishing said portable wireless device from other wireless devices, said tracking device comprising a wireless transmitter adapted to provide wireless communications with said at least one wireless receiver and wherein said wireless communications include communication of at least said unique identification number; and

a game control system for actuating or controlling one or more physical effects in said physical play environment and one or more computer-animated effects in said virtual play environment so as to provide an overall interactive game in which game progress or performance of multiple play participants playing said game in both said physical play environment and said virtual play environment are tracked according to said received wireless input signals, and wherein said game control system is further configured to adjust a game experience for each said play participant in both said physical play environ-

ment and said virtual play environment based on said tracked game progress or performance.

39. The amusement attraction of claim **38** wherein said at least one gaming system comprises a personal computer, video gaming system, home-based gaming system, or web-based gaming system.

40. The amusement attraction of claim **38** wherein said wireless receiver and said wireless transmitter comprise medium range wireless communication devices configured and adapted to wirelessly and electronically exchange information over a communication medium selected from the group consisting of: RF, infrared, laser, visual, audio, and ultrasonic.

41. The amusement attraction of claim **38** wherein said at least one wireless receiver comprises a first wireless radio frequency (RF) transceiver adapted to send and receive wireless signals to and from one or more associated wireless devices and wherein said wireless tracking device comprises a second wireless RF transceiver adapted to provide two-way wireless RF communications with said first wireless RF transceiver over a communication range of at least 10 feet and wherein said two-way wireless RF communications include communication of at least said unique identification number.

42. The amusement attraction of claim **38** wherein said at least one portable wireless device comprises an elongated body sized and configured to be held and moved freely in the air using a single hand to play said game at least in part by moving the elongated body in one or more particular motions, said elongated body having an axis of elongation extending from a first end adapted to be held or gripped by a single hand of a play participant to a second end protruding from said first end and being in substantial coaxial alignment therewith.

43. The amusement attraction of claim **38** wherein said at least one portable wireless device further comprises an effects generator configured to display or produce one or more light, vibration or sound effects.

44. The amusement attraction of claim **38** wherein said at least one portable wireless device further comprises a display screen configured to display game-relevant information.

45. The amusement attraction of claim **38** wherein said game control system is further configured and adapted to adjust a play experience for a play participant by allowing or denying access to one or more different game areas or game levels in said physical or virtual play environment based on said tracked game progress or performance.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,368,648 B2
APPLICATION NO. : 13/475824
DATED : February 5, 2013
INVENTOR(S) : Barney et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Specification

In column 19 at line 10, Change "ND" to --A/D--.

Signed and Sealed this
Nineteenth Day of November, 2013

A handwritten signature in cursive script, appearing to read "Teresa Stanek Rea".

Teresa Stanek Rea
Deputy Director of the United States Patent and Trademark Office