



US 20130278201A1


(19) **United States**(12) **Patent Application Publication**
Retti(10) **Pub. No.: US 2013/0278201 A1**(43) **Pub. Date: Oct. 24, 2013**(54) **MULTIPLE LAYER SOLAR ENERGY
HARVESTING COMPOSITION AND
METHOD, SOLAR ENERGY HARVESTING
BUCKYBALL, INDUCTIVE COUPLING
DEVICE; VEHICLE CHASSIS;
ATMOSPHERIC INTAKE HYDROGEN
MOTOR; ELECTRICAL ENERGY
GENERATING TIRE; AND MECHANICAL
ENERGY HARVESTING DEVICE****Publication Classification**(51) **Int. Cl.**
H01L 31/058 (2006.01)
H02J 7/00 (2006.01)
(52) **U.S. Cl.**
CPC **H01L 31/0583** (2013.01); **H02J 7/0052**
(2013.01)
USPC **320/101**; 136/206; 136/244; 136/252(71) Applicant: **Kahr! L Retti**, Parkville, MD (US)(72) Inventor: **Kahr! L Retti**, Parkville, MD (US)(21) Appl. No.: **13/673,595**(22) Filed: **Nov. 9, 2012****Related U.S. Application Data**

(63) Continuation of application No. 11/498,759, filed on Aug. 4, 2006, now abandoned.

(60) Provisional application No. 60/705,484, filed on Aug. 5, 2005, provisional application No. 60/810,162, filed on Jun. 2, 2006.

(57) **ABSTRACT**

A multiple layer composition and method for deposition of a solar energy harvesting strip onto a driving surface that will allow electric cars to charge by an inductive coupling is provided. The multiple layer composition includes at least one magnetic material for generating a magnetic field, wherein at least one of the multiple layers comprises the magnetic material. Further, the a multiple layer composition includes at least one solar energy harvesting material for converting at least one of thermal and photonic energy into electrical energy, wherein at least one of the multiple layers comprises the at least one solar energy harvesting material and wherein the at least one solar energy harvesting material is located within a magnetic field generated by the at least one magnetic material. One of the layers may also include a thermal energy harvesting material for converting thermal energy into electrical energy.






FIG. 1






FIG. 2






FIG. 4D




FIG. 4A




FIG. 4E




FIG. 4B




FIG. 4F




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 8






FIG. 7






FIG. 11




FIG. 12




FIG. 13
(Prior Art)




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG. 19





FIG. 20

**MULTIPLE LAYER SOLAR ENERGY
HARVESTING COMPOSITION AND
METHOD, SOLAR ENERGY HARVESTING
BUCKYBALL, INDUCTIVE COUPLING
DEVICE; VEHICLE CHASSIS;
ATMOSPHERIC INTAKE HYDROGEN
MOTOR; ELECTRICAL ENERGY
GENERATING TIRE; AND MECHANICAL
ENERGY HARVESTING DEVICE**

**CROSS-REFERENCE TO RELATED
APPLICATION**

[0001] This application claims the benefit under 35 U.S.C. §119(e) of Provisional Patent Application No. 60/705,484, filed Aug. 5, 2005, Provisional Patent Application No. 60/810,162, filed Jun. 2, 2006, and is a continuation under 35 U.S.C. §120 of patent application Ser. No. 11/498,759, filed Aug. 4, 2006, the entire disclosures of which are hereby incorporated by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to the generation of electrical energy from solar energy for applications such as powering electric vehicles by inductive coupling. More particularly, the present invention relates to a multiple layer solar energy harvesting composition and method used to form a solar energy harvesting strip along a road surface that allows passing electric vehicles to be powered by an inductive coupling thereto. Further, the present invention relates to a solar energy harvesting buckyball. Still further, the present invention relates to an inductive coupling device. Even further, the present invention relates to a vehicle chassis for storing electrical energy. Additionally, the present invention relates to an atmospheric intake hydrogen motor. Also, the present invention relates to an electrical energy generating tire. Further, the present invention relates to a mechanical energy harvesting device.

[0004] 2. Description of the Related Art

[0005] As expanding energy use and environmental concerns have become of greater importance, interest has grown in available energy sources that are alternatives to fossil fuels, hydroelectric power and nuclear power. In today's alternate energy market, there are a number of different alternative energy systems being used. There are solar cells, known in the industry as photovoltaic cells, wind turbines which generate electricity using electrical generators driven by blades that catch the wind, solar furnaces which generate electricity using electrical generators driven by steam that is produced by catching and magnifying heat from the sun, hydrogen fuel cells which derive hydrogen from gasoline or methane, straight hydrogen motors for vehicles which burn hydrogen that is stored thereon, and electric cars which rely on batteries to power them. All of these technologies have significant hurdles to overcome.

[0006] A significant problem with solar cell technology is that large areas of land are needed to establish solar fields with a high enough yield to be practical. Solar cells have been improved over the years to be more effective at converting sunlight into electricity, but even the best solar cells are only about 20% efficient at conversion. Further, solar cells have limited wave length efficiency and on cloudy or rainy days, there is little or no generation of electricity. This means that in

order to compete with other methods of electrical generation, large numbers of solar arrays must be directed at the sun during the daylight hours. It is very expensive to build these arrays and they require extensive amounts of land.

[0007] Like solar energy, wind fields are constructed to take advantage of a natural process to generate electricity. The disadvantages of wind generation are the amount of land required, costs of construction, and inconsistent nature of wind. These disadvantages all add up to, as with solar cell technology, relying on natural processes that are undependable.

[0008] Solar furnaces also rely on the sun to fuel them. At night and on cloudy days they become ineffective. Thus the generation of electricity during a rainstorm becomes substantially impossible. As with solar energy and wind fields, solar furnaces are inefficient because they only generate energy for a part of a day.

[0009] Much has been written about the conversion of vehicles to burn hydrogen or other natural gases to help curb the use of oil. Hydrogen fuel cell vehicles are now being constructed by every major car manufacturer. Hydrogen's major drawbacks are production and storage. In a hydrogen fuel cell vehicle the range is only about 90 miles at best. Hydrogen fuel cells require hydrogen which when produced generates greenhouse gases. Additionally, storing hydrogen for consumption on a vehicle is complicated due to the nature of hydrogen in its gaseous state. Thus, liquefying hydrogen creates the problem of putting cold storage tanks in vehicles which would vastly increase the cost of the vehicle. Also, a cold storage tank would occupy a significant amount of space within a vehicle so as to store enough hydrogen to get near the number of miles per tank the average car gets now.

[0010] Electric vehicles which rely solely on batteries to power them suffer from problems such as limited range, and this has forced most auto producers to abandon the purely electric car as an alternative to the internal combustion engine. Even when electric vehicles are coupled with solar cell technology, most solar cells are inefficient because of a number of limiting factors, including wave refraction and reflection, weather problems, and so forth, and therefore fall short of delivering enough energy. Hybrid cars combine an internal combustion engine with a generator, electric motors and batteries. However, such cars still produce greenhouse gases, and other harmful pollutants.

[0011] In addition to the growing interest in alternative energy sources, interest is growing in an energy economy of increased efficiency. In a conventional energy economy, an open loop consumption process is practiced. In the open loop energy consumption process energy is purchased as it is utilized from a centralized energy system. However, the open loop system is inefficient as the energy consumer never generates and adds energy to the system. On the other hand, in a closed loop consumption process, the inefficiencies of the open loop system can be avoided by having the consumer generate and add energy to the energy system. By way of example, in the context of vehicles, if 20 million of the 100 million vehicles in the U.S. operated to supplement one hour of electricity to the centralized energy system, that would total 20 million hours a day of usable electricity.

[0012] Accordingly, a need exists for an improved means to generate energy where the generated energy could be used for a vehicle. Additionally, a need exists for a system that allows for a practical closed loop energy consumption process.

SUMMARY OF THE INVENTION

[0013] An aspect of the invention is to provide a multiple layer solar energy harvesting composition and method used to form a solar energy harvesting strip on a road surface that allows passing electric vehicles to be powered by an inductive coupling thereto. Solar energy includes at least thermal and/or photonic energy.

[0014] Another aspect of the present invention is to provide a solar energy harvesting buckyball for use in a solar energy harvesting strip and an electric vehicle for use with the solar energy harvesting strip.

[0015] A further aspect is to provide a method for harvesting solar energy comprising depositing a plurality of layers onto a surface area that is incident to solar energy, wherein at least one of the plurality of layers comprises at least one solar energy harvesting material and at least one of the plurality of layers comprises at least one magnetic material. Further, the method comprises converting at least one of thermal and photonic energy into electrical energy by the at least one solar energy harvesting material, wherein the at least one solar energy harvesting material is located within a magnetic field generated by the at least one magnetic material.

[0016] A still further exemplary embodiment of the present invention provides a multiple layer solar energy harvesting composition for deposition onto a surface area that is incident to solar energy, comprising at least one magnetic material for generating a magnetic field, wherein at least one of the multiple layers comprises the magnetic material. Further, the composition comprises at least one solar energy harvesting material for converting at least one of thermal and photonic energy into electrical energy, wherein at least one of the multiple layers comprises the at least one solar energy harvesting material and wherein the at least one solar energy harvesting material is located within a magnetic field generated by the at least one magnetic material.

[0017] A yet further exemplary embodiment of the present invention provides a method for harvesting solar energy, comprising depositing a plurality of layers onto a surface area that is incident to solar energy, wherein at least one of the plurality of layers comprises thermal energy harvesting material and at least one of the plurality of layers comprises a photonic energy harvesting material. Further, the method comprises converting thermal and photonic energy into electrical energy by the thermal and photonic energy harvesting materials, respectively.

[0018] An additional exemplary embodiment of the present invention provides a multilayer solar energy harvesting composition for deposition onto a surface area that is incident to solar energy, comprising a thermal energy harvesting material for converting thermal energy into electrical energy, wherein at least one layer comprises the thermal energy harvesting material. Further, the composition comprises a photonic energy harvesting material for converting photonic energy into electrical energy, wherein at least one layer comprises the thermal energy harvesting material.

[0019] Another exemplary embodiment of the present invention provides a carbon buckyball for harvesting solar energy, comprising a thermal energy harvesting material on at least a portion of the exterior of the buckyball for converting thermal energy into electrical energy. Further, the buckyball comprises a photonic energy harvesting material on at least a portion of the exterior of the buckyball for converting photonic energy into electrical energy.

[0020] Still another exemplary embodiment of the present invention provides an inductive coupling device for a vehicle, said vehicle being at least partially powered by electrical energy, the inductive coupling device comprises a spherical inductive coupler for inducing current in a magnetic field.

[0021] A further exemplary embodiment of the present invention provides a vehicle chassis for storing electrical energy for use in a vehicle that is at least partially powered by electrical energy, the vehicle chassis comprises a first conductor; a second conductor; and a material for energy storage disposed between the first and second conductors, wherein the chassis supports a body of the vehicle.

[0022] An additional exemplary embodiment of the present invention provides an atmospheric intake hydrogen motor that obtains hydrogen fuel from condensed atmospheric water vapor, the atmospheric intake hydrogen motor comprises an atmospheric intake for intaking air; at least one sensor for sensing at least one characteristic of the intaken air; a condensation bladder for condensing water from the air; and a cooling and/or heating device for cooling or heating the condensation bladder according to the sensed at least one characteristic of the intaken air, wherein the cooling and/or heating device cools or heats the condensation bladder to condensate the water from the air.

[0023] Yet an additional exemplary embodiment of the present invention provides an electrical energy generating tire for a vehicle, the electrical energy generating tire comprises a first reinforcement strip formed circumferentially on the tire, the first reinforcement strip comprising a conductive material and forming as a positive conductor; a second reinforcement strip formed circumferentially on the tire, formed circumferentially on the tire, the second reinforcement strip comprising the conductor material and forming as a negative conductor; an annular strip comprised of piezo ceramic material and/or thermal harvesting material that is disposed between the first and second reinforcement strip; and at least one sidewall conductor coupled to at least one of the first and second reinforcement strips.

[0024] Still another exemplary embodiment of the present invention provides a mechanical energy harvesting device for converting mechanical motion into electrical current for use in a vehicle, the mechanical energy harvesting device comprises an electrical winding; a magnetic travel rod surrounded by the winding and moveable relative to the winding; wherein electrical current is induced when the magnetic travel rod moves relative to the winding.

[0025] Other aspects, advantages, and salient features of the invention will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses exemplary embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0026] The above and other objects, features, and advantages of certain embodiments of the present invention will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0027] FIG. 1 illustrates a solar energy harvesting strip according to an exemplary embodiment of the present invention;

[0028] FIG. 2 illustrates a first exemplary embodiment of the solar energy harvesting strip in elemental form;

[0029] FIG. 3A illustrates a detailed view of the bonding layer and magnetic layer;

[0030] FIG. 3B illustrates a detailed view of the bonding layer and magnetic layer in an exemplary embodiment where the bonding layer and magnetic layer are used to convey information;

[0031] FIGS. 4A-4C illustrate cross sectional views of alternative embodiments for the conductive layer;

[0032] FIGS. 4D-4F illustrate perspective views of the alternative embodiments for the conductive layer illustrated in FIGS. 4A-4C;

[0033] FIG. 5A depicts a cross sectional view of the first exemplary embodiment of the solar energy harvesting strip;

[0034] FIG. 5B depicts the magnetic field of the first exemplary embodiment of the solar energy harvesting strip from a top view;

[0035] FIG. 6 illustrates a cross sectional view of the first exemplary embodiment of the solar energy harvesting strip including the effects of soft iron deposits on the magnetic field;

[0036] FIG. 7 illustrates the magnetic fields for each of the layers of the first exemplary embodiment of the solar energy harvesting strip;

[0037] FIG. 8 illustrates a second exemplary embodiment of the solar energy harvesting strip in elemental form;

[0038] FIG. 9 illustrates an exploded view of a first exemplary embodiment of a buckyball for use with the second exemplary embodiment of the solar energy harvesting strip;

[0039] FIG. 10 illustrates an exploded view of a second exemplary embodiment of a buckyball for use with the second exemplary embodiment of the solar energy harvesting strip;

[0040] FIG. 11 illustrates a detailed view of the second exemplary embodiment of the buckyball illustrated in FIG. 10;

[0041] FIG. 12 illustrates an electric vehicle according to an exemplary embodiment of the present invention;

[0042] FIG. 13 illustrates a conventional induction coupling device;

[0043] FIG. 14 illustrates an induction coupling device according to an exemplary embodiment of the present invention;

[0044] FIG. 15 illustrates an induction coupling device according to another exemplary embodiment of the present invention;

[0045] FIG. 16 illustrates conduction lines on the body panels of the electric vehicle according to an exemplary embodiment of the present invention;

[0046] FIG. 17 illustrates the body panels and chassis of the electric vehicle in elemental form according to an exemplary embodiment of the present invention.

[0047] FIG. 18 illustrates an exemplary embodiment of an atmospheric intake hydrogen motor in elemental form.

[0048] FIG. 19 illustrates a shock absorber for converting linear mechanical motion into electrical energy according to an exemplary embodiment of the invention.

[0049] FIG. 20 illustrates an electrical energy generating tire according to an exemplary embodiment of the invention.

[0050] Throughout the drawings, the same drawing reference numerals will be understood to refer to the same elements, features, and structures.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0051] The matters defined in the description such as a detailed construction and elements are provided to assist in a comprehensive understanding of the embodiments of the

invention and are merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the embodiments described herein can be made without departing from the scope and spirit of the invention. Also, descriptions of well-known functions and constructions are omitted for clarity and conciseness.

[0052] Exemplary embodiments of the present invention include apparatuses, systems and methods for harvesting solar energy. Solar energy includes both thermal and photonic energy. Preferably, a multiple layer solar energy harvesting composition is embodied as a strip provided on a driving surface that allows electric vehicles to inductively receive energy as they traverse the driving surface. FIG. 1 illustrates a solar energy harvesting strip according to an exemplary embodiment of the present invention. In FIG. 1, a solar energy harvesting strip 110 between about 1" to about 24" wide is provided at the center of driving surface 120. The position at the center of the driving surface 120 is presented as an example only, and the solar energy harvesting strip 110 could be positioned at any suitable position on the driving surface 120. Further, the width of about 1" to about 24" is merely exemplary, and in other exemplary embodiments of the present invention the width can be varied as required by the application or location. Additionally, while solar energy harvesting strip 110 is shown in FIG. 1 as being provided on the driving surface 120, the solar energy harvesting composition could be provided on any other permanent surface and could be embodied in any form, as required by the application or location. For example, the solar energy harvesting composition could be applied to roadways, barrier walls, lampposts, rooftops, curbs, and so forth and be formed according to the surface it is applied on.

[0053] According to an exemplary embodiment of the present invention, a method of application for the solar energy harvesting strip 110, described in greater detail below, comprises the steps of spraying multiple coats in rapid succession onto the driving surface 120. However any number of methods of deposition, such as hand application, film deposition, and so forth, can be used for any one or all of the constituent components of the solar energy harvesting composition.

[0054] The above solar energy harvesting strip 110, according to exemplary embodiments of the present invention, merges solar harvesting and linear magnetic generation technologies. In exemplary embodiments of the present invention, photonic harvesting materials could be used for the conversion of photonic energy into electrical energy. However, in other embodiments of the present invention, thermal harvesting materials could be used to convert thermal energy into electrical energy. The solar energy harvesting composition may comprise only one or both of the photonic and thermal harvesting materials. When using both photonic and thermal energy to generate electricity, embodiments of the present invention are up to 50% more efficient than conventional solar cells. Conventional solar cells become less efficient as they heat up, whereas embodiments of the present invention using both photonic and thermal energy become more efficient.

[0055] In exemplary embodiments of the present invention, a solar energy harvesting strip 110 comprises a linear magnetic field generator for generating electrical flow. A linear magnetic field generator requires great distances in order to create a magnetic field capable of generating any appreciable current. Such distances could be achieved by the placement of the solar energy harvesting strip 110 on a length of driving

surface **120** so as to produce a linear magnetic field generator. In this case, since the magnetic fields could be created over long distances, very little current would be needed from the solar harvesting materials. Even weak current flow creates magnetic fields of sufficient strength. Further, since magnetic fields are unaffected by ice, snow, dirt and so forth, keeping the surface clean and well maintained is of less importance. According to an exemplary embodiment of the present invention a vehicle passes over the solar energy harvesting strip **110** to power the vehicle. The vehicle receives power by having an inductive coupling device affixed thereto that passes through the magnetic field thereby producing electrical flow.

First Exemplary Embodiment of the Solar Energy Harvesting Strip:

[0056] A first exemplary embodiment of the solar energy harvesting strip **110** in elemental form is illustrated in detail in FIG. 2. The solar energy harvesting strip **110** comprises a multiple layer solar energy harvesting composition comprised of a bonding layer **210**, magnetic layer **220**, a thermal harvesting layer **230**, a conductive layer **240**, a photonic harvesting layer **250**, and a sealing layer **260**. These components are shown and arranged as one example, and in other embodiments of the present invention, components can be combined, added, removed and/or rearranged as required by the application or location. Further, all of the layers may be formed having the same width or the layers may be formed such that each layer positioned on top of another layer is narrower than the layer beneath it. Still further, the edged of any of the layers may be squared, rounded, or tapered. In FIG. 2, the energy harvesting composition is embodied as a strip, but may be formed in any configuration as required by the application or location.

[0057] In operation, the thermal harvesting layer **230** and/or photonic harvesting layer **250** convert thermal and/or photonic energy into electrical energy. The electrical energy migrates across and/or between the layers of the energy harvesting composition. In one embodiment, the electrical energy migrates along conductive traces on any of the layers and/or conductive ladders between any of the layers. In another embodiment, electrical energy flows through and between the layers of the energy harvesting composition without any conductive traces or ladders.

[0058] When a conductive layer **240** is included, the electrical energy migrates to the conductive layer **240** under the influence of a magnetic field generated by the magnetic layer **220** and/or bonding layer **210**. Conductive layer **240** stores the electrical energy and generates an electric field which augments the magnetic field. Further, conductive layer **240** may be attached to an electrical energy consumption, transmission and/or storage device. When the energy harvesting composition is embodied as a strip and conductive layer **240** is attached to an electrical energy consumption, transmission and/or storage device, one or more attachments may occur along the strip.

[0059] When a conductive layer **240** is not included, electrical flow occurs within and/or between the layers and generates an electric field which augments the magnetic field. With or without conductive layer **240**, the augmented magnetic field couples the energy harvested by the thermal harvesting layer **230** and/or photonic harvesting layer **250** to an electric vehicle and/or other remote devices. In another embodiment, the electrical energy is used to energize inductive coils that are used to couple the energy harvested by the

thermal harvesting layer **230** and/or photonic harvesting layer **250** to an electric vehicle and/or other remote devices. A better understanding of the first exemplary embodiment of the solar energy harvesting strip **110** will be achieved through the following detailed discussion.

[0060] Bonding layer **210** is preferably comprised of a rubber or asphalt type adhesive and functions as a bonding agent between a surface on which the solar energy harvesting strip is applied and a subsequent layer. Further, the bonding layer **210** may additionally function to fill any cracks and/or fissures in the surface it is applied to, such as driving surface **120**. In an exemplary embodiment of the present invention, bonding layer **210** comprises a soft ferromagnetic material suspended in a rubberized material. When bonding layer **210** comprises the soft ferromagnetic material, the bonding layer **210** additionally functions to generate a magnetic field that becomes magnetized by magnetic layer **220**. Further, bonding layer **210** may function to electrically insulate the other layers from the surface it is applied to. Exemplary soft ferromagnetic materials include iron, soft iron, steel and magnetite. However, any magnetic material may be used.

[0061] Magnetic layer **220** is comprised of a permanent magnetic material. The magnetic layer **220** has a magnetic field that is perpendicular to the field in place, such as the field generated by the bonding layer **210** when the bonding layer **210** includes a soft ferromagnetic material. Magnetic layer **220** functions to generate a magnetic field, which will be described in greater detail below. The permanent magnetic material of magnetic layer **220** may be a permanent hard ferromagnetic material. Exemplary hard ferromagnetic materials include strontium ferrite, strontium ferrite powder, strontium ferrite powder in a polymer base, steel, iron, nickel, cobalt, suspensions of magnetite, soft iron in epoxy, iron nickel alloy, ceramic, alnico, and rare earth magnetic materials. However, any permanent magnetic material may be used.

[0062] Thermal harvesting layer **230** is comprised of a thermal electric and/or thermionic material. The thermal harvesting layer **230** converts thermal energy into electrical energy. It is not necessary for the thermal energy to originate as solar energy. Thermal harvesting layer **230** may be combined with one or both of the bonding layer **210** and magnetic layer **220**. Exemplary thermal electric and/or thermionic materials include strontium and barium strontium titanates. Barium strontium titanates is a material that when heated causes electrical current to flow. Beside the above exemplary thermal electric and/or thermionic materials, any thermal electric and/or thermionic materials may be used.

[0063] Conductive layer **240** is comprised of at least two conductors separated by a dielectric or insulative material. The conductors collect the electrical energy from the thermal harvesting layer **230** and the photonic harvesting layer **250**. When used with a dielectric, the conductors form a parallel plate discharge capacitor. One of the conductors functions as a positively charged plate whereas the other functions as a negatively charged plate. Preferably, if thermal harvesting layer **230** is comprised of a thermionic material and is positioned adjacent to conductive layer **240**, the conductor closest to the thermal harvesting layer **230** may function as the positively charged plate. Exemplary materials for the conductors include aluminum oxide, aluminum dioxide, indium tin oxide, indium tin oxide laced with graphite, any conducting metal, and thin film mono pole plastics such as a polyamide. Additionally, the conductor may be comprised of carbon modified epoxies or silicate modified crynoacrylates, which

have been developed to cope with strength and durability issues. The conductors may be comprised of the same material or may each be comprised of different materials. Exemplary dielectric materials include graphite, carbon and activated carbon. Further, it is preferred that conductive layer **240** is attached to an electrical energy consumption, transmission and/or storage device so as to be part of a complete circuit. Examples of which includes street lights, power grids and batteries, respectively. Attachments to the conductive layer **240** for the purpose of drawing energy from it may occur at one or more positions. Further, one of the plates of the conductors may be coupled to earth ground.

[0064] Photonic harvesting layer **250** is comprised of a photonic harvesting material and converts photonic energy into electrical energy. The photonic harvesting material may be a photovoltaic material that comprises solid state junction diodes which comprise an NPN type diode of purified silicon, doped with impurities such as germanium. However, other impurities may be used as a dopant in addition to or instead of germanium. In addition, the photonic harvesting material may be MgZn oxides that are dye sensitized, dirty silicates, polymer films laced with nanocrystals, and organic based films such as phenylene. Moreover, the photonic harvesting material may comprise a film deposition of the photonic harvesting material on a plastic that supports monopole charges. In such an arrangement the film can then be bonded to the conductive layer **240**. In yet another example, the photonic harvesting material may be comprised of conventional type solar cells that are bonded to the conductive layer **240** and which have an N layer of silicon applied by spray or film deposition. Alternatively, the photonic harvesting material may be a composition that makes use of dye sensitized zinc oxide enriched with magnesium. This composition pushes the useable wavelength to 800 nanometers, thereby allowing energy to be harvested from the infrared spectrum. Furthermore, photonic harvesting layer **250** may comprise a fractal lens structure or include clear N layers to allow for the transmission of photons through the substrate to be used again on a second NPN type diode and so forth.

[0065] Sealing layer **260** is comprised of a sealing material. Exemplary sealing materials include PTFEE which is a member of the Teflon family. However, certain epoxies modified by silicates or carbon may be used as well. Additionally, a combination of cyanoacrylates and silicates may be used as well.

[0066] The layers described above with reference to FIG. 2 are merely one exemplary arrangement. In other embodiments of the present invention, components can be combined, added, removed and/or rearranged as required by the application or location. For instance, the use of strontium as a magnetic as well as thermal electrical material may eliminate the need for the application of a separate thermal harvesting layer. In other words, by using a material that functions as both a magnetic as well as thermal electrical material, the structures and/or functions of two or more of the bonding layer **210**, magnetic layer **220** and a thermal harvesting layer **230** may be combined. Additionally, it is not necessary for the thermal harvesting layer **230** to be located between the magnetic layer **220** and the thermal harvesting layer **230**, as the thermal harvesting layer **230** may be located at any point in the layered structure of the solar energy harvesting composition which forms the solar energy harvesting strip **110**. Furthermore, the structure and/or function of one or more of the bonding layer **210**, magnetic layer **220**, thermal harvesting

layer **230**, conductive layer **240**, photonic harvesting layer **250**, and sealing layer **260** may be omitted or combined. Additionally, other layers with redundant and/or additional functions and/or structures may be added.

Exemplary Structure of Bonding Layer and Magnetic Layer:

[0067] A better understanding of the bonding layer **210** and magnetic layer **220** will be achieved through the following detailed discussion with reference to FIGS. 3A and 3B. FIG. 3A shows the structure of bonding layer **210** and magnetic layer **220** in greater detail, in accordance with an exemplary embodiment of the present invention. In FIG. 3A, bonding layer **210** comprises a soft ferro magnetic material and magnetic layer **220** comprises a hard ferro magnetic material. The soft ferro magnetic material of bonding layer **210** generates a magnetic field **310**. Preferably, the hard ferro magnetic material of magnetic layer **220** is deposited on top of the soft ferro material of bonding layer **210**. However, the hard ferro magnetic material of magnetic layer **220** may be positioned beneath or within the soft ferro material of bonding layer **210**. The hard ferro magnetic material is illustrated on the bonding layer **210** as magnetic surfaces **340** and **350** that resemble bar magnets whose polar regions lie in a substantially perpendicular state with regards to the outer edge of the solar energy harvesting strip **110**. In other words, the magnetic field of the hard anisotropic ferro magnetic material lies substantially perpendicular to the magnetic field of the soft ferro magnetic material. While it is preferred that the polar regions of the magnetic surfaces **340** and **350** lie in a substantially perpendicular state with respect to the outer edge of the solar energy harvesting strip **110**, the magnetic surfaces **340** and **350** may be applied so that their polar regions align in a direction parallel to the solar energy harvesting strip **110**. Preferably, the polar regions of adjacent magnetic surfaces **340** and **350** are oriented in opposite directions as shown in FIG. 3A. However, the polar regions of adjacent magnetic surfaces **340** and **350** may be oriented in the same direction. Further, while only magnetic surfaces **340** and **350** are illustrated, it is preferred that the hard ferro magnetic material be applied along most of length of solar energy harvesting strip **110**.

[0068] The hard ferro magnetic material of magnetic layer **220** generates magnetic fields **320** and **330**. The magnetic field strength of the hard ferro magnetic material correlates to the mass of the magnetic material. Accordingly, by way of example, a magnetic field **330** of half strength, as compared to magnetic field **320**, is generated at magnetic surface **350** by using a hard ferro magnetic material that is half as thick. Accordingly, any thickness of hard ferro magnetic material may be utilized as required by the application or location. An image charge **360** is generated as a result of the hard ferro magnetic material being in proximity of the soft ferro magnetic material. By way of example, image charge **360** is depicted for the hard ferro magnetic material of magnetic surface **340**. The polar regions of the image charge **340** are opposite of the polar regions for the hard ferro magnetic material of magnetic surface **340**.

[0069] In an exemplary embodiment, as shown in FIG. 3B, in place of the hard ferro material **340**, a diamagnetic material **370** such as bismuth may be substituted. Areas of the soft ferro material **210** that are covered with diamagnetic material **370** significantly decrease the coercive and inductive forces of the magnetic field **380** generated by the soft ferro material **210** in those areas. Use of these magnetic field modifiers in certain patterns along the length of the strip

allow information to be encoded in a pattern. Devices that are able to sense the variations of the magnetic field along the length of the strip will thereby be able to ascertain the information. By way of example, for an electric vehicle traveling along the length of the strip, the encoded information may comprise traffic signals, speed limits, driver assist programs, and so forth.

Exemplary Structure of Conductive Layer:

[0070] A better understanding of the conductive layer 240 will be achieved through the following detailed discussion with reference to FIGS. 4A, 4B, 4C, 4D, 4E and 4F which illustrate exemplary structures of the conductive layer 240. FIGS. 4A, 4B and 4C illustrate cross-sectional views of the exemplary structures of the conductive layer 240. FIGS. 4D, 4E and 4F illustrate perspective views of the exemplary structures of the conductive layer 240. In FIGS. 4A-4C and 4D-4F, a first conductor 410A, 410B and 410C is spaced apart from a second conductor 420A, 420B and 420C with a dielectric or insulative material 430A, 430B, 430C formed between. When used with a dielectric, the conductors form a parallel plate discharge capacitor. One of the first conductor 410A, 410B and 410C and second conductor 420A, 420B and 420C functions as an electrically positive plate while the other functions as an electrically negative plate. Additionally, dielectric or insulative material may additionally be formed adjacent to any combination of the top, bottom, left or right side of the structures shown in FIGS. 3A-3B. Moreover, any number of the bonding layer 210, magnetic layer 220, thermal harvesting layer 230, conductive layer 240, photonic harvesting layer 250, and sealing layer 260 may be formed between the first conductor 410A, 410B and 410C and second conductor 420A, 420B and 420C instead of or in addition to the dielectric or insulative material 430A, 430B and 430C, and may have a cross sectional width that is less than, greater than or equal to the insulative material 430A, 430B and 430C. The cross sectional height for each of the first and second conductors 410A, 410B and 410C and 420A, 420B and 420C and dielectric or insulative material 430A, 430B and 430C are shown as being the same. However, the height of each can vary according to the application. FIGS. 4A and 4B are similar in that first conductors 410A and 410B are situated below the dielectric or insulative material 430A and 430B which is below the second conductor 420A and 420B. FIGS. 4D and 4E are similar for the same reasons as FIGS. 4A and 4B. FIGS. 4B and 4C are similar in that the first conductor 410B and 410C and second conductor 420B and 420C are parallel, spaced apart and at least one of the first conductor 410B and 410C and second conductor 420B and 420C has a cross sectional width less than the width of the strip. FIGS. 4E and 4F are similar for the same reasons as FIGS. 4B and 4C. While FIGS. 4A-4C show particular exemplary structures of the conductive layer 240, conductive layer 240 may be formed in other ways as the application requires.

[0071] FIGS. 4A and 4D illustrates conductive layer 240 formed so as to have the second conductor 420A formed on top of the dielectric or insulative material 430A which is formed on top of the first conductor 410A. Each of the first and second conductors 410A and 420A and dielectric or insulative material 430A are substantially planar, with each lying in different planes, and each have substantially the same cross sectional width. However, the first and second conductors 410A and 420A and dielectric or insulative material 430A may also be formed so that dielectric or insulative material

430A is narrower than the first conductor 410A but wider than the second conductor 420A.

[0072] FIGS. 4B and 4E illustrates conductive layer 240 having parallel spaced apart first and second conductors 410B and 420B formed side by side with the dielectric or insulative material 430B formed in between. Second conductor 420B is formed on top of the dielectric or insulative material 430B which is formed on top of the first conductor 410B. First and second conductors 410B and 420B at least partially lie in different planes. Dielectric or insulative material 430B is continuous and may have a cross sectional width equal to or less than width of the strip. In an alternative implementation, the first conductor 410B may be positioned over the dielectric or insulative material 430B with the second conductor 420B positioned beneath the dielectric or insulative material 430B. The cross sectional width of at least one of the first and second conductors 410B and 420B is less than the cross sectional width of the strip.

[0073] FIGS. 4C and 4F illustrates conductive layer 240 having parallel spaced apart co-planar first and second conductors 410C and 420C formed side by side with a co-planar dielectric or insulative material 430C formed in between. The cross sectional width of each of the first and second conductors 410C and 420C and dielectric or insulative material 430C is less than the cross sectional width of the strip.

[0074] FIGS. 4A-4F illustrate particular exemplary structures of the conductive layer 240, however, conductive layer 240 may be formed in other ways as the application requires.

Exemplary Embodiment of Operation of Solar Energy Harvesting Strip:

[0075] In order to better understand the operation of the solar energy harvesting strip 110, a study of the magnetic fields of the individual elements is in order. FIGS. 5A and 5B depict the magnetic field lines of solar energy harvesting strip 110 when the layers of the solar energy harvesting composition are in place.

[0076] In FIG. 5A, a cross sectional view of the solar energy harvesting strip 110 formed on surface 530 is shown. The magnetic poles of the solar energy harvesting strip 110 are shown in the cross sectional view. Upper magnetic field lines 510 are shown oriented in direction A. Further, lower magnetic field lines 520 are shown passing through surface 530.

[0077] In FIG. 5B the orientation of the magnetic field from a top view is shown. As can be seen in this view, the magnetic moments 550 are aligned parallel to the outer edge of the strip and have a magnetic orientation such that their north pole points in direction B. As a result of this method of polarization, a number of small anisotropic regions are created whose net field effect emulates that of a bar magnet. Further, a net field effect of the combined components of the solar energy harvesting strip 110 along the length of the solar energy harvesting strip 110 is a helical field 540 along the length of the solar energy harvesting strip 110. The helical field 540 orientation resembles a torus and the net effect on an unbounded electron is torisoidal. This torisoidal effect influences electron flow in the solar energy harvesting strip 110.

[0078] The magnetic fields depicted in FIGS. 5A and 5B are merely exemplary and are shown in the absence of any magnetic interference. However, as is exemplified in FIG. 6, soft iron deposits 610 may be located beneath the surface 530 that interfere with the magnetic fields of the solar harvesting strip 110. These soft iron deposits form image charges 620

above the anisotropic permanent magnetic material. As a result, spike lines **630** are created above the magnetic field that are random modifiers of the field at large. In order to facilitate an ease of understanding, the effects of the soft iron deposits **610** located beneath the surface **530** will be omitted from further discussions.

[0079] The individual magnetic fields of the components of solar harvesting strip **110** will now be discussed. FIG. 7 depicts the magnetic field lines for each successive layer including alternative embodiments for conductive layer **240** that are exemplified in FIGS. 4A-4D and 4C-4E. The magnetic field lines for the conductive layers **240** exemplified in FIG. 4B are substantially similar to the magnetic field lines illustrated with respect to FIG. 4C, and therefore a discussion thereof is omitted.

[0080] The magnetic field **320** generated by bonding layer **210** and/or magnetic layer **220** has been discussed above with reference to FIG. 3 and therefore any further discussion will be omitted for the sake of brevity. The thermal harvesting layer **230** alters the magnetic field generated by bonding layer **210** and/or magnetic layer **220** and results in altered magnetic field lines **710**.

[0081] The conductive layer **240** generates a magnetic field when current flows through the conductors. However, the current flow is affected by conductive layer **240** being located within the magnetic field generated by the bonding layer **210** and/or magnetic layer **220**. The net effect on electron flow due to the magnetic field generated by the bonding layer **210** and/or magnetic layer **220** is to force the electrons to the outer edges of the conductors. This phenomenon is known in the art as magnetic field line fringing and becomes important when using mono-pole plastics because many of the available electrons become trapped by the atoms of the other constituent elements. The use of an external magnetic field to force electron flow out to the edge of the conductors overcomes the tendency of electrons to be randomized in their migration. The magnetic field generated by the conductive layer **240** increases the net magnetic field strength due to the electromagnetic force in the conductors. Thereby, the potential of the magnetic inductance field is increased.

[0082] The magnetic fields generated around the conductors of the conductive layer **240** vary according to the structure of the conductive layer **240**. By way of example, exemplary conductive layers **240** of the embodiments shown in FIGS. 4A-4D and 4C-4E are depicted in FIG. 7.

[0083] In the conductive layer **240** of the type exemplified in FIGS. 4A and 4D, magnetic field lines **720** follow a circular pattern around the flat conductors. A spike in the magnetic field strength occurs at the midpoint of the separation between the two conductors. However, when saturation occurs, the spike collapses at the meridian and forms in the direction of the current flow in the conductors.

[0084] In the conductive layer **240** of the type exemplified in FIGS. 4C and 4E, magnetic field lines **730** reach a max spike at the center of the max distance between the two conductors that are separated by a dielectric. A secondary field spike occurs between the anisotropic and dielectric material at the midpoint between the two conductors.

[0085] The dielectric of the conductive layer **240** further results in a modified magnetic field **740** which is a magnetic field of the bonding layer **210** and/or magnetic layer **220** which has been modified by the thermal harvesting layer **230**.

[0086] When all the layers of energy harvesting strip **110** are in place, the magnetic fields of the various conductors and

the magnetic layers produce a linear magnetic field **750** that follows the right hand rule of field direction when there is a current present in the conductors.

Second Exemplary Embodiment of Solar Energy Harvesting Strip:

[0087] A second exemplary embodiment of the solar energy harvesting strip **110** in elemental form is illustrated in detail in FIG. 8. The solar energy harvesting device, according to the second exemplary embodiment, comprises a second multiple layer solar energy harvesting composition comprising a bonding layer **210**, a magnetic layer **220**, a conductive layer **240**, a thermal-photonic harvesting layer **810**, and a sealing layer **260**. When the components of the thermal-photonic harvesting layer **810** are combined as shown in FIG. 8, they form N type solid state junction diodes. These components are shown and arranged as one example, and in other embodiments of the present invention, components can be combined, added, removed and/or rearranged as required by the application or location. In FIG. 8, the energy harvesting strip **110** is embodied as a strip, but may be formed in any configuration as required by the application or location. Further, all of the layers may be formed having the same width or the layers may be formed such that each layer positioned on top of another layer is narrower than the layer beneath it. Still further, the edged of any of the layers may be squared, rounded, or tapered. In the second exemplary embodiment, bonding layer **210**, magnetic layer **220**, conductive layer **240**, and sealing layer **260** are identical to their respective layer in the first exemplary embodiment, and a description thereof will be omitted. It is further noted that thermal harvesting layer **230** and/or photonic harvesting layer **250**, as described with respect to the first exemplary embodiment, may be provided in the second exemplary embodiment.

[0088] In operation, the thermal-photonic harvesting layer **810** converts thermal and/or photonic energy into electrical energy. When a conductive layer **240** is included, the electrical energy migrates to the conductive layer **240** under the influence of a magnetic field generated by the magnetic layer **220** and/or bonding layer **210**. Conductive layer **240** stores the electrical energy and generates an electric field which augments the magnetic field. Further, conductive layer **240** may be attached to an electrical energy consumption, transmission and/or storage device. When the energy harvesting composition is embodied as a strip and conductive layer **240** is attached to an electrical energy consumption, transmission and/or storage device, one or more attachments may occur along the strip.

[0089] When a conductive layer **240** is not included, electrical flow occurs within and/or between the layers and generates an electric field which augments the magnetic field. With or without conductive layer **240**, the augmented magnetic field couples the energy harvested by the thermal harvesting layer **230** and/or photonic harvesting layer **250** to an electric vehicle and/or other remote devices. In another embodiment, the electrical energy is used to energize inductive coils that are used to couple the energy harvested by the thermal-photonic harvesting layer **810** to an electric vehicle and/or other remote devices. A better understanding of the first exemplary embodiment of the solar energy harvesting strip **110** will be achieved through the following detailed discussion.

[0090] As shown in FIG. 8, thermal-photonic harvesting layer **810** comprises a doped silicate barrier solution layer

830, a clear N type silicate barrier layer **840** and a plurality of nanostructures. In an exemplary embodiment of the present invention, the nanostructures are 60 sided carbon buckyballs **820**. Preferably, at least a portion of the lower hemisphere of the buckyballs **820** is suspended within the doped silicate barrier solution layer **830** and at least a portion of the upper hemisphere of the buckyballs **820** is suspended within clear N type silicate barrier layer **840**. Buckyballs **820** carry a structurally negative charge, and therefore are preferable for forming solid state junction diodes of the NPN type.

[0091] The buckyballs **820** are situated in the thermal-photon harvesting layer **810** such that electrical fields generated by the buckyballs **820** align in a perpendicular manner with respect to the magnetic field produced by the magnetic layer **220** and/or bonding layer **210**. The individual buckyball structures generate electrical flow, behaving like parallel plate discharge capacitors in series. Because electrical fields generate magnetic fields, the field strength of the solar energy harvesting strip **110** will be augmented.

[0092] The buckyballs **820** have had solid state junction diodes formed on the facets of their exterior structure for the conversion of thermal and/or photonic energy into electrical energy which is discharged into the solar harvesting strip **110**. In order to convert the thermal and/or photonic energy into electrical energy, thermal and/or photonic energy harvesting materials are deposited on the facets of the buckyball **820**. The thermal and photonic energy harvesting materials could be any of the material discussed above with respect to the thermal harvesting layer **230** and photonic harvesting layer **250** of FIG. 2. Further, the photonic energy harvesting material could include doping the facets of the buckyball **820** with nanocrystals that are doped by any number of dopants, such as germanium, phosphorous and boron, and the like. Preferably, a lower hemisphere of the buckyballs **820** comprises the thermal harvesting material and an upper hemisphere of the buckyballs **820** comprises the photonic energy harvesting material. However, the thermal and photonic energy harvesting materials may be comprised on any of, and include any number of, the facets of the buckyballs **820**. Moreover, buckyballs **820** may comprise only thermal or photonic energy harvesting materials. Additionally, any combination of thermal only, photonic only and mixed thermal-photon buckyballs **820** may be utilized. The buckyballs **820** are prepared by conventional methods known to the art.

[0093] Preferably, the facets of the buckyballs **820** comprise spacing between the applications of thermal and/or photonic harvesting material so as to provide excellent electron path migration. The advantages of cutting channels in silicon for electron migration occurs naturally in this structure.

[0094] The structure of the buckyballs **820** are advantageous in that when applied to the solar harvesting strip **110**, they have up to 30 facets that face the sky at every angle to catch sunlight from dusk to dawn, thereby eliminating the need to constantly reorient solar cells. While embodiments of the present invention are described utilizing 60 sided carbon buckyballs **820**, epoxy and carbon microballs could be substituted for the buckyballs **820**. For example, hollow carbon microballs with a dielectric having poles formed from nanotubes would substantially perform the same function as the buckyballs.

First Exemplary Embodiment of a Buckyball:

[0095] FIG. 9 illustrates a first exemplary construction of a buckyball **820** of the thermal-photon harvesting layer **810**

according to an exemplary embodiment of the present invention. In FIG. 9, a carbon nanotube **910** is located in the upper hemisphere **920** of the buckyball **820** and functions as an electrode for the buckyball **820**. The nanotube **910** comprises a hollow interior and may contain silicon nanocrystals and/or a magnetic material within its hollow interior. FIG. 9 further illustrates a second electrode **930** at a lower hemisphere of the buckyball **820**. Depending on the composition of the buckyballs **820** they may operate as either a nanobattery or a nanocapacitor.

[0096] When buckyballs **820** are formed as a nanobattery the buckyballs are filled with an electrical energy storing chemical and are provided with the carbon nanotubes **910** and **940** to form a nanobattery. These nanobatteries use thermal and/or photonic energy to produce electricity, which is discharged into solar energy harvesting strip **110**, then recharged and discharged repeatedly. In an exemplary embodiment of the invention, the rate of discharge and recharge is on the order of millions of times a second.

[0097] When the buckyballs **820** are formed as nanocapacitors, the buckyballs **820** comprise the tuned carbon nanotubes **910** and **940** and a dielectric material introduced to the interior of the hollow carbon structure. Exemplary dielectric materials include tantalum pentoxide (Ta_2O_5) and manganese dioxide (MnO_2). However, any other dielectric material may be used. When tantalum pentoxide (Ta_2O_5) and/or manganese dioxide (MnO_2) is used as the dielectric material, the buckyball **820** is formed as a nanoelectrolytic nanocapacitor. When buckyballs **820** are formed as a nanocapacitor they use thermal and/or photonic energy to produce electricity, which is then discharged into the solar harvesting strip **110**.

Second Exemplary Embodiment of a Buckyball:

[0098] FIG. 10 illustrates a second exemplary structure of carbon buckyball **820**, which is illustrated in a partially exploded view. In FIG. 10, a tuned carbon nanotube **1010** is located at the upper pole of an upper hemisphere **1020** of the buckyball **820**. Further, a tuned carbon nanotube **1050** is located at a lower pole in the lower hemisphere **1040** of the buckyball **820**. Additionally, a carbon barrier **1030** is equatorially placed within the hollow center of the buckyball **820**. Carbon barrier **1020** preferably comprises a coating of a dielectric material that serves as a collection medium for electrons flowing into the solar energy harvesting strip **110**.

[0099] FIG. 11 illustrates a comprehensive exploded view of the second embodiment from FIG. 10 shown in greater detail. A dielectric coating **1120**, is located on the upper side of barrier **1030**. An exemplary dielectric coating includes tantalum pentoxide, however any other dielectric material could alternatively be used. Barrier **1030** further comprises a dielectric coating **1130** on the bottom of the barrier **1030**. Dielectric coating **1120**, barrier **1030** and dielectric coating **1130** perform the function of a parallel plate discharge capacitor with a high leakage rate.

[0100] As illustrated in FIG. 11, tuned carbon nanotube **1010** functions as an electrode with anode and cathode termination points. The nanotube **1010** exits the carbon structure of buckyball **820** at the upper pole and includes a protruding portion **1110** with a cathode termination point. Further, carbon nanotube **1010** includes an anode termination point located at dielectric coating **1120**. Protruding portion **1110** illustrates an exemplary length for the portion of nanotube **1010** exiting the buckyball **820**. Likewise, tuned carbon nanotube **1050** functions as an electrode with anode and cathode

termination points. The nanotube **1050** exits the carbon structure of buckyball **820** at the lower pole and includes a protruding portion **1110** with an anode termination point. Further, carbon nanotube **1050** includes a cathode termination point located at dielectric coating **1130**. Protruding portion **1150** illustrates an exemplary length for the portion of nanotube **1050** exiting the buckyball **820**.

[0101] In operation, electrical field charges migrate to the exterior of the buckyball **820**. Alignment of electrical field lines occurs at the dielectric coating **1120** which functions as a collection plate for the anode termination point of nanotube **1010** and thereby carries a net negative charge which saturates the barrier **1030**. The barrier **1030** is also saturated by dielectric coating **1130** which functions as a collection plate for the cathode termination point of nanotube **1050** and thereby carries a net positive charge.

[0102] A magnetic material **1140**, whose field is opposite of the magnetic field of the magnetic layer **220** and/or bonding layer **210**, is shown filling the hollow portion of the lower hemisphere of the buckyball **820**. The purpose of the magnetic material **1140**, according to an exemplary embodiment of the present invention, is to orient the buckyball **820** so that facts comprising the photonic harvesting material are oriented upward. For example, if the nanostructure **820** is being sprayed upon a surface, the magnetic material **1170** within the sphere is attracted to the magnetic material in bonding layer **210** and/or magnetic layer **220** and rotates the sphere to a proper or desired orientation. Magnetic material may also be deposited in the hollow anode as well. To further ensure alignment, a diamagnetic material may be placed in the cathode.

[0103] As noted above, the individual buckyballs **820** generate electrical flow, behaving like parallel plate discharge capacitors in series. Because electrical fields generate magnetic fields, the magnetic field strength of the solar energy harvesting strip is augmented for inductance. The electrons flow to the conductive layer **140** which itself acts as a parallel plate capacitor.

First Exemplary Embodiment of a Method of Application of a Solar Energy Harvesting Composition

[0104] In another exemplary embodiment of the present invention, the solar energy harvesting strip comprises a solar energy harvesting composition for use with an applicator to spray apply the layers of the solar energy harvesting composition on a driving surface. The solar energy harvesting composition comprises about 10% to about 20% rubber type adhesive to act as bonding agent between the driving surface and subsequent applications, about 20% to about 60% magnetic material, about 20% to about 40% specially prepared solid state junction diodes, a conduction material where used comprise about 20% to about 30% graphite/epoxy and about 20% to about 30% of a metallic conductor such as Aluminum Dioxide. The film is then sealed by a type of transparent material, such as a transparent TEFLON material. These layers can be configured and arranged in a number of manners. For example, a permanent magnet rubber bonding strip can be applied, followed by a first and second conductor application, an epoxy/graphite dielectric conduction strip, a thermal electric converter, a photonic energy harvesting material conduction film, and completed with a clear topcoat. In another example, an aluminum dioxide plate conductor can be applied, followed by a graphite/epoxy dielectric, an aluminum dioxide plate conductor, barium strontium titanates, a

photonic energy harvesting material conduction film, and completed with a clear nonstick topcoat. In the above examples, thermal energy harvesting materials may be substituted for any of materials or be separately applied.

Second Exemplary Embodiment of a Method of Application of a Solar Energy Harvesting Composition

[0105] Use of an apparatus such as the one disclosed in U.S. Pat. No. 5,605,251 of Retti entitled "Pulseless Pump Apparatus", the entire disclosure of which is incorporated herein by reference, is preferable for applying the chemical coating of yet another embodiment of the present invention, in three somewhat simultaneous overcoatings. In the first application, a rubber-based, asphalt cement which combines permanently magnetized material, preferably about 75% magnetic material to about 25% cement, is applied to the surface providing electrical insulation as well as a bonding agent for the subsequent overcoatings. In a somewhat simultaneous application, graphite, preferably in a solution of 65% graphite 65%, and 35% epoxy or ACC (superglue), is applied to the bonding agent in two separate but parallel lines to form conductors representing the positive and negative leads in a circuit. In the third application of material, specially formed solid state junction diodes are deposited by air jet onto the surface of the magnetic-graphite strip, forming a solid overcoating of the base materials producing photovoltaic strips on the surface of the road. A final deposition comprised of PFTEE can then be achieved by direct spray onto the surface of the strips, so as to protect the composition from the effects of the elements. In the above example, thermal energy harvesting materials may be substituted for any of materials or be separately applied.

Exemplary Short Capture Energy System:

[0106] In yet another embodiment of the present invention, an energy system can be provided and is referred to for purposes of discussion as a short capture energy system. The short capture energy system comprises installing a solar energy harvesting strip in a road surface under a protective coating that electric vehicles may use to recharge onboard batteries by means of an inductive coupling. The solar cells used in the short capture energy system, according to yet another embodiment of the present invention, are basically the same PNP gates formed on silicon wafers that are in use today. The short capture energy system is different in that after the formation of the gates, the product is bonded with a rubberized magnetic material and then ground or broken up so as to be air blasted onto a rubber based adhesive strip previously applied to a driving surface. A magnet is then passed over the solution so as to "flip" the cells so that the gates are upward and form a fractal surface pointed skyward.

[0107] After the cells are oriented correctly, a PFTEE coating is liquid applied to the surface creating a protective coating that passes more sunlight in the coned spectrum than does glass. No conductor is needed since the cells will only capture the current for a short period before release to the onboard auto batteries by means of induction. Given the expansion rates of concrete as well as asphalt, the normal fissuring of these surfaces will harmlessly translate to the strip surface without effect as there is no need to maintain a continuous conductor. The gates may be broken, cut, or ground to any shape with the embodiment being triangular shaped silicon gates bonded to rubberized magnetic material. In the above example, thermal energy harvesting materials may be substituted for any of materials or be separately applied.

tuted for any of materials or be separately applied. Alternatively, the materials, layers, and/or composition of the first and second exemplary embodiments of solar energy harvesting strip may be formed and/or operate according the small capture energy system.

Exemplary Small Capture Energy System:

[0108] In yet another embodiment of the present invention, an energy systems can be provided and is referred to for purposes of discussion as a small capture energy system. The small capture energy system involves the use of a material similar to that describe above with respect to the solar energy harvesting strip **110**. However, instead of a driving surface, the solar energy harvesting composition is applied to the separation walls found on highways. Further, it utilizes a continuous conductor that will allow the photonic and/or thermionic energy harvesting materials to pass and store electricity for a variety of uses. The electricity of a 6 inch solar energy harvesting strip on all of the existing driving surfaces as well as on the barrier walls, would out produce all the current solar capture devices in use today.

[0109] In the small capture energy system, a rubber type cement is applied, for example, to the surface of barrier walls on the highway. However, the composition could alternatively be applied to rooftops, bridges, light poles, and so forth, onto which a conductor could be applied. Over the conductor, a coating of an electrolytic epoxy is sprayed while receiving a somewhat simultaneous application of the solar cells. Like the short capture energy system, a magnet is used to orient the PNP gates skyward. The strips of cells could be linked together to run a variety of applications. Alternatively, the materials, layers, and/or composition of the first and second exemplary embodiments of solar energy harvesting strip may be formed and/or operate according the small capture energy system.

Exemplary Use of Small and Short Capture Energy Systems:

[0110] Exemplary embodiments of the present invention could be used to charge vehicle batteries. For example, solar harvesting strips **110** can be installed in parking lots. The solar harvesting strips **110** could be laid out in a parking lot on space dividers to determine field generation strength as well as basic durability. These strips could be comprised of the small capture energy system embodiment, having continuous conductors tied to collection batteries. Vehicles having electric batteries could charge at these stations. Further, solar harvesting strips **110** could be applied on major highways. Additionally, solar harvesting strip **110** could be applied to the separation wall, that is, the concrete barrier between lanes, and tied to a continuous conductor including collection batteries to run highway lights, lighting for signs, and so forth. Once in place and operating, the small and short capture energy systems can be utilized to augment the solar harvesting strip **110**.

Third Exemplary Embodiment of the Method of Application of Solar Energy Harvesting Material

[0111] In yet another exemplary embodiment of the present invention, any ferris metal capable of magnetization can be ground to the consistency of iron filings. Preferably, ferris metal is comprised primarily of reclaimed recyclables. These metals can be generally magnetized by field polarization in this process. Once magnetized, the material can be combined

with an electrolytic substance while receiving a somewhat simultaneous overcoating of thermal and/or photonic harvesting materials. Encasement can be finalized by an application of a film. Flow of current through the solar energy harvesting composition would augment the field produced by the already magnetized layer. Since there is a layer of magnetic material, times of little or no sunshine, ice, dirt, and nighttime, would have less of an affect on the system than they would on conventional photovoltaic cell systems. The solar harvesting strips of this composition can receive field augmentation in the energy system. In an exemplary system, the same type of laminations can be used, with the exception of providing a continuous conductor, so that the current flow could be directed to either collection batteries or directed to the roadway strips. Further electrical energy from the collection batteries and/or electric grid may add electricity of the conductors so as to augment the magnetic field.

[0112] In such applications, the thermal and/or photonic harvesting materials are basically applied in a suspended solution. In an exemplary embodiment, the application to the road surface can be a four step process that can be accomplished simultaneously from a truck bearing the proper equipment. The application can be much like painting lines on the road. The conducting strips can be applied in much the same way, except that conductors for collection are used. Possible uses for this composition would be barrier walls, the inside of guard rails, jackets for over head wires, and so forth. Since the substrate may be dyed or colored, the lines dividing the lanes on a road could be "repainted" with the material and be made to be conducting or nonconducting.

[0113] A use of the above embodiments further comprises uses on rooftops. The same materials for the road can be used to coat existing rooftops. Further, instead of collecting voltage from a dense concentration of cells, collection of the magnetic field is possible to drive a small generator by magnetic inductance.

Further Exemplary Embodiments

[0114] In yet other embodiments of the present invention, an indestructible solar cell can be designed to be embedded in the roadway and provide a system and method of power generation for electrical vehicles by use of electrical inductance principles, whereby the vehicles passing over the cells may draw current from them for onboard charging of fuel cells. The embodiments can further comprise a system and method for a digital, as well as a fiber optic network, allowing the concurrent construction of a global communications network. Also, the embodiments can comprise a system and method for recharging and discharging the related network so as to produce an electrical surplus, which may be used to power any and all foreseeable technologies which use electricity. The thermal and/or photonic harvesting materials of the embodiments may also be used in general housing construction applications, as the surface of these solar cells may be constructed to resemble any surface such as shingles, bricks, siding, glass films, and so forth. Further, the embodiment can comprise a method of photo nonreluctant dying so that the solar cells may be dyed without consequence to the cells electrical conducting properties. Also, the embodiments can further comprise a method of photoluminescence magnification to multiply the net effect of the charging cycle by a factor of 4 to produce ultra efficient charging, and include a system and method for lighting the roadway at night with little consequential discharge of the network.

[0115] An application of an embodiment of the present invention can entail installation of conventional photovoltaics on the surface of barrier walls, guard rails, and so forth. Methods of doing this have been devised so as to be able to transfer electrical current to ferris bearing substrates attached to the road surfaces via electrical coils to create magnetic fields. Electric cars can then be provided having an inductive coupling device attached to the subframe, and which are tied electrically through diodes to an onboard charging device. Since the charging medium is a long range magnetic field, having an inductive coupling device that is maintained at certain heights with regards to the charging medium is not as necessary as it is for a short distance charging system, such as buried electrical cable in the roads.

[0116] In another exemplary embodiment of the present invention, the introduction of thermal and/or photonic harvesting materials bonded to any type of magnetic material via the use of electrolytic material such as certain epoxies, can occur. Like the first application, a film of rubber and a Ferris substrate would precede the application of an electrolytic and photovoltaics covered over by a film of PFTEE that passes more of the correct wavelength than does glass. Provisions can then be made to use augmentation by photovoltaics. Application of the photovoltaics to the substrate can yield a Fractal surface, proven to be more effective at wave length capture than a flat or parabolic conformity.

[0117] In yet another exemplary embodiment of the present invention, the composition could be air blasted onto a quick setting solution that would contain all conductors and/or magnetic material in the solution. Magnetic field orientation could be a one time process by passing a magnet over the solar harvesting strips. If the gates are bonded to a magnetic material on the negative side of the gates, positive gate orientation could be accomplished by passing a magnet over the semi-viscous strip to orient the gates upwards.

Exemplary Embodiment of the Inductively Coupled Electric Vehicle

[0118] In FIG. 12, an electric vehicle 1200 is illustrated that is operable with the solar energy harvesting strip 110, according to an exemplary embodiment of the present invention. Electric vehicle 1200 may comprise a number of features that increase its efficiency. For instance, electric vehicle 1200 may comprise a regenerative braking system 1210. A regenerative braking system 1210 generates electrical energy by converting breaking force into electrical energy that may be used to power the electric vehicle 1200. Further, electric vehicle 1200 may incorporate independent electric motors 1220 at each wheel. The configuration of having one electric motor at each wheel minimizes the vehicle's weight thereby reducing the amount of energy needed to propel the vehicle. The body panels 1230 may be constructed to function as parallel plate discharge capacitors. Further, a solar energy harvesting material that converts photonic and/or thermal energy into electricity may be used for the finish coating on all body panels 1230. Additionally, all of the window glass 1240 may be coated with a clear or tinted photonic and/or thermal energy harvesting material. Further, electric vehicle 1200 includes an inductive coupling device 1250 which uses a sphere-type inductive coupling device for induction instead of a conventional plate-type inductive coupling device. Preferably, electric vehicle 1200 includes ancillary or backup electrical generation devices. Such ancillary or backup electrical generation devices may covert mechanical motion associated

with the electric vehicle 1200 into electricity. For example, when you open the door, a magnetic rod travels through a series of windings which produces electrical current. In addition, the regenerative braking system 1210 described above is another example of an ancillary or backup electrical generation device. Further, electric vehicle 1200 may be provided with a hydrogen motor 1260 that generates electricity. Electric vehicle 1200 may further include channels to collect rain water stored and used by hydrogen motor 1260. Still further, electric vehicle 1200 may be provided with photonic harvesting material underneath the chassis to allow for the conversion into electricity of photonic energy received from lights sources that are coupled to solar energy harvesting strip 110. The light sources may be embedded in the driving service 120 and/or solar energy harvesting strip 110. While electric vehicle 1200 may include all of the above features, electric vehicle 1200 may alternatively include any combination of any number of the above features as well as other features that increase its efficiency.

[0119] A conventional plate-type inductive coupling device is illustrated in FIG. 13. In operation, the conventional plate-type inductive coupling device uses flat metal plates 1310 that must be lowered from a raised position 1330 to a lowered position 1340 so as to be placed in the field 1350 of charging medium 1320 in order to cause current flow across the surface of the plates 1310. This configuration has a number of disadvantages, including potential damage to the plates due to snow, ice, debris or the like. This configuration is further problematic in that the plates 1310 must be centered over the charging medium 1320 for maximum inductive coupling.

[0120] A sphere-type inductive coupling device 1250 according to an exemplary embodiment is shown in FIG. 14. The inductive coupling device 1250 includes an inductance sphere 1410 that does not need to be raised or lowered and so may be fixed at a permanent height well above the charging medium. A sphere-type inductive coupling device is beneficial in that it has a far greater surface area than a plate-type inductive coupling device. The inductance sphere 1410 may be made of a great range of materials including any, or any combination of, soft or hard magnetic materials, dielectric materials and electro-conductive materials. Further, any type of motor, including a hydrogen motor or small internal combustion engine, may be used to spin the inductance sphere 1410 for the generation of electrical energy. When the inductance sphere 1410 is spun in the field 1420 over the solar energy harvesting strip 110, the inductance sphere 1410 accumulates a charge on its surface which in turn is transferred to the battery/storage area 1450. The inductance sphere 1410 accumulates a charge on its surface by inductance through the coil of conductors 1440 around its center. Thus, if the battery storage areas 1450 are low in charge and the vehicle is not moving, the inductance sphere 1410 may be spun to charge its batteries.

[0121] The use of multiple spheres of the same size or of different sizes results in the ability to multiply the charge effect over a large area no matter what the vehicle's position is in relation to the solar harvesting strip 110. In one exemplary embodiment illustrated in FIG. 15, a large sphere 1510 comprised of magnetic material is surrounded by several smaller spheres 1520 comprised of a dielectric material. The larger sphere 1510 may be attached to motorized or mechanical movements causing them to spin. In yet another exemplary embodiment, several large spheres may be used instead

of a single large sphere. When the storage capacity of the vehicle is saturated, a super corona discharge may reintroduce charge to the solar harvesting strip **110**. Thus, a vehicle **1200** coated with a solar energy harvesting material, sitting in the sun will collect a charge up to its storage capacity. The excess charge will be discharged to the solar energy harvesting strip **110**. Furthermore, electrical current will be introduced across the surface of the small inductance spheres when the large sphere **1510** is spun. The net effect on the small dielectric spheres **1520** will be to cause a predominate charge on the faces that will discharge into the solar energy harvesting strip **110**, causing a point of charge accumulation that will increase the overall electric charge on the conducting layer **130**. This in turn will increase the overall magnetic field of the solar energy harvesting strip **110** that is available for charging. This arrangement provides a means for vehicle charge sharing. For example, a vehicle sitting in a traffic jam with a full charge may increase the magnetic field available for the motorist in front or behind him who may not have a full charge.

[0122] The spheres will preferably be constructed as part of a permanent chassis of the vehicle **1200**. The chassis will be formed like a parallel plate discharge capacitor with positive **1530** and negative **1540** plates and a dielectric or electrolyte material **1550** in between. Positive plate **1530** and negative plate **1540** are connected to the primary storage batteries **1450** as well as capacitors in the body panels **1230**. Additionally, any backup or ancillary electrical generation devices could be electrically coupled to the chassis for providing electrical charge to the chassis. For example, an electrical generating tire **1560**, discussed below, could be electrically coupled to the chassis. In an exemplary embodiment of the chassis, the chassis is a carbon fiber filament enclosure surrounding the negative plate **1540**. As the spheres **1510** and **1520** accumulate charge, the positive charges will be attracted to the negative plate **1540**, and the negative charges will flow to the positive plate **1530**. Excess charges will accumulate across the dielectric material and migrate to the negative electrode of the battery **1430** creating a current. When all the storage systems reach saturation, the current will flow to ground, in this case, the solar harvesting strip **110**.

[0123] Preferably, the entire body of the vehicle **1200** is constructed to capture, convert and use thermal and photonic energy to either charge the vehicle **1200** or add charge to the solar harvesting strip **110**. Therefore, when the vehicle is parked over a solar harvesting strip **110**, the parked vehicle is adding charge to the solar harvesting strip **110**. The body panels will be described with reference to FIGS. **16** and **17**. The chassis and the body panels are first constructed of a carbon fiber sheet **1700**, followed by a honeycomb structure **1710** and then topped off by a carbon fiber sheet **1720**. The honeycomb structure **1710** may be filled with an electrolyte suspended in a polymer creating a gel type rechargeable battery or may contain a dielectric material. This composition creates a thin, lightweight structure that is much stronger than steel. It also creates five times the charging area found in a conventional electric vehicle, while decreasing the overall weight of the vehicle. The body panels **1230** of the vehicle **1200** further comprise preformed conduction areas including, but not limited to, electrical feeder lines **1610**, graphite feeder lines **1620**, preformed graphite conduction areas **1630** and preformed feeder lines **1640**. Any of the conduction areas may be used for one or more of the headlights, side lamps, electric motors or the like. The use of preformed conduction

areas to connect various components and charging devices drastically reduces the weight and cost of the vehicle. Further, the use of preformed conduction areas eliminates the need for a costly wiring harness, and allows for a completely modular construction of the vehicle. The body panels will simply plug into the electrical system in case of replacement and may be recycled.

[0124] The body panels **1230** will further be finished in a series of steps. The first coat will be a conductor material **1730** which functions as a negative conductor for the panel. Exemplary materials for the conductive material **1730** include graphite or powered metal. However, other materials may be used including the materials used for the conductors of conductive layer **240** of the solar harvesting strip **110**. The next coat is comprised of a thermal harvesting material **1740**. The thermal harvesting material may be the same material used for thermal harvesting layer **230** of the solar harvesting strip. The next coat is a dielectric material **1750**, such as activated carbon or any other suitable dielectric material. Further, dielectric material **1750** may be the same material used as the dielectric material utilized in the conducting layer **240** of solar harvesting strip **110**. Further, a conductive material **1760** will be applied over the thermal harvesting material and functions as a positively biased conductor. The conductive material **1760** may be the same material as conductor material **1730** or may be a different material. The conductor material **1730**, dielectric material **1750** and conductor material **1760** form a parallel plate discharge capacitor. A photonic harvesting material **1770** is applied next. The photonic harvesting material **1770** could be any known photovoltaic material such as titanium or zinc oxides or dye sensitized photovoltaic materials. Dye sensitized photovoltaic materials could give the vehicle its color. Additionally, photonic harvesting material **1770** may comprise any of the materials used in photonic harvesting layer **250** or thermal-photonic harvesting layer **810** of the solar harvesting strip **110**. Further, photonic harvesting material **1770** may be an amorphous thin film deposition of silicates. Next, a clear conductor **1780**, such as indium tin oxide or mono-pole plastic, is applied having a negative bias. The final sealer **1790** is applied next, thereby completing the body of the electric vehicle **1200** that is a battery, a giant discharge capacitor and an electrical generator. The final sealer **1790** may be comprised of the same materials used for sealing layer **260** of the solar harvesting strip **110** or any other suitable material. These components are shown and arranged as one example, and in other embodiments of the present invention, components can be combined, added, removed and/or rearranged as required by the application or location.

Exemplary Embodiment of the Hydrogen Motor

[0125] FIG. **18** illustrates an exemplary embodiment of an atmospheric intake hydrogen motor in elemental form. The atmospheric intake hydrogen motor according to the exemplary embodiment uses a condensation electrolysis system to glean water from the atmosphere to be used as a source of hydrogen. By using atmosphere as the source of water, large heavy water stores are not required. While it is preferred that the atmospheric intake hydrogen motor be used as hydrogen motor **1260**, hydrogen motor **1260** may be any other type of hydrogen motor. Further, while it is preferred that the atmospheric intake hydrogen motor **1260** be used for driving a charging system of an electric vehicle, the atmospheric intake hydrogen motor **1260** may be used in any other application

requiring a motor. For example, the atmospheric intake hydrogen motor **1260** could be used for the generation of electricity at the utilities level.

[0126] The atmospheric intake hydrogen motor **1260** intakes atmosphere through an atmospheric intake. When used with electric vehicle **1200**, atmosphere is introduced to a venting **1805** at the front of the generator. It is preferred but not required that atmospheric intake occur at a predetermined rate. It is further preferable that the atmospheric intake occur through a small intake fan (not shown) at the venting **1805** in front of the motor **1260**. When the air travels through the venting **1805** the air is sampled by one or more sensors **1810** including air temperature, air speed, vacuum pressure, and barometric pressure sensors. The air temperature sensor determines the outside air temperature and/or temperature of the air passing through the vent **1805** for regulating the temperature of a bladder **1815**. The air speed intake sensor determines the speed of incoming air. The vacuum pressure sensor determines the backflow pressure of the motor **1260**. Preferably, the atmospheric intake hydrogen motor **1260** is controlled by a microprocessor (not shown) located on replaceable computer boards. However, the atmospheric intake hydrogen motor **1260** may be controlled by other means, including manual, mechanical, and other control means. The microprocessor receives signals from the sensors and controls any of the heating and cooling systems **1820**, fan, and ignition **1845**.

[0127] The atmospheric intake vent **1805** is constructed so as to confine the atmosphere inside of a bladder **1815**. The bladder **1815** includes a cooling and/or heating system **1820** that heats and/or cools the bladder **1815** based on the sensed temperature and barometric pressure of the atmosphere. The heated or cooled bladder **1815**, when in contact with the atmosphere, causes condensation to form in the bladder **1815**. Preferably, the cooling system **1820** is operative to sonically cool the atmosphere, but any conventional cooling system may be used. The heating system **1820** may be any conventional heating system. The condensation is accumulated inside of a collection bladder **1815**.

[0128] The water is then collected by gravity into an electrolysis chamber, preferably using a gravity valve **1825**. In the electrolysis chamber, the water is placed on an electrolysis screen **1830** having alternating positive and negative conductors. On the electrolysis screen **1830** water droplets are electrolyzed by an electrical current which causes the separation of the hydrogen from the oxygen in the water. When atmospheric intake hydrogen motor **1260** is used with electric vehicle **1250**, it is preferred that the electrical energy needed to separate the hydrogen from the oxygen is generated using electrical generation means imbedded in the tires **1560** of the electric vehicle **1250**. The tires **1560** of the electric vehicle **1250** will be discussed in greater detail below. However, the electrical energy may also come from the batteries or a progressive discharge generator geared to the moving wheels. Moreover, after the atmospheric intake hydrogen motor **1260** begins generating electrical energy, part of or all of the electrical energy required to separate the hydrogen from the oxygen may be generated by the atmospheric intake hydrogen motor **1260**.

[0129] After the hydrogen is separated from the oxygen, the hydrogen is collected at the top of a holding bladder **1825** and induced under vacuum pressure to an intake chamber **1840** to be used as a fuel. In the intake chamber **1840** the hydrogen is ignited by photon excitation or other ignition means. Prefer-

ably, the combustion is vectored along a vectored blast ridge to a rotating conical piston. In one embodiment, the combustion chamber **1850** of the engine houses a conically shaped piston which is attached to the stator of the alternator. After combustion, the conically shaped piston spins and thereby causes the alternator to generate electricity. In an alternative embodiment, the combustion chamber includes a conically shaped piston located within conically shaped piston receiver, wherein the conically shaped piston and conically shaped piston receiver each have a magnetic orientation that is out of phase with the other. Here, once the hydrogen is ignited, the conically shaped piston spins inside the conically shaped piston receiver, thereby generating electricity. The alternative embodiment is advantageous in that efficiency is increased as the rotational speed is increased.

[0130] For either of the above embodiments, the exhaust of the combustion comprises water vapor and may be chambered via exhaust **1860** to a pressurized tank of salt water **1865** so as to add water to the tank. The tank of salt water **1865** is not required, but is preferred. The tank of salt water **1865** may be used to increase the efficiency of the electrolysis by introducing sodium to the electrolysis screen **1830**. Further, the tank of salt water **1865** may be used as an initial and/or backup supply of water for the atmospheric intake hydrogen motor **1260** via supply line **1870**. In addition the tank of salt water **1865** may function as a collection reservoir for collected rain water.

[0131] Preferably, the generated electricity is stored in one or more large discharge capacitors until said capacitors are completely charged. Once the discharge capacitors are completely charged they could be discharged into an electrical energy storage device. Exemplary electrical energy storage devices include battery/storage area **1430** of electric vehicle **1250**, the chassis of electric vehicle **1250** and a large hydrid electrocell. An exemplary hydrid electrocell gleans the NOX₂ from the fuel source and absorbs this emission which is a by product of the combustion of hydrogen.

[0132] The atmospheric intake hydrogen motor **1260** is advantageous for numerous reasons. When the atmospheric intake hydrogen motor **1260** is used in a vehicle charging system, the electrical energy storage device of the vehicle charging system can maintain a lower level of charge than is usually maintained in conventional electrical vehicles. Also, the motor **1260** should prove to be almost maintenance free since it contains a small number of moving parts. Additionally, all of the functions are controlled by computer boards that are easily replaceable. Moreover, it weighs far less than the conventional motors since it is constructed mainly of high impact plastic with ceramics being used in the high heat areas. Also, the atmospheric intake hydrogen motor **1260** does not require onboard vehicle storage of highly combustible gases. Further, no special batteries or expensive hydride reclamation units are required. In addition, the motor **1260** requires no petroleum products for lubrication. The motor **1260** has zero emissions, including zero oxides since the burning of atmospheric hydrogen results in only a small amount of water vapor emissions with pure, clean, oxygen as the main byproduct. Preferably, the motor **1260** is used simply as a charging unit and not as a means to propel the vehicle. The motor **1260** requires no mufflers, catalytic converters, or liquid fuels as do vehicles powered by internal combustion motors. The atmospheric intake hydrogen motor **1260** is far quieter than conventional engines. In a production assembly scenario, the atmospheric intake hydrogen motor **1260** is far easier to con-

struct since it has about only twenty or so total parts, with only about three or so requiring mechanical motion. Because the atmospheric intake hydrogen motor **1260** is much smaller than conventional power plants, it can be used in multiples if necessary to facilitate charging of an electrical system. For example, more than one atmospheric intake hydrogen motor **1260** may be used on electric vehicle **1200**.

Exemplary Embodiment of a Mechanical Energy Harvesting Device

[0133] As mentioned above with respect to electric vehicle **1200**, ancillary or backup electrical generation devices may be included with the vehicle to generate electricity. One such device is a linear mechanical energy harvesting device for converting linear mechanical motion into electrical energy. An exemplary embodiment of the mechanical energy harvesting device is a shock absorber **1900** for use in the suspension of electric vehicle **1250**. FIG. **19** illustrates a shock absorber for converting mechanical motion into electrical energy, according an exemplary embodiment of the invention.

[0134] The shock absorber **1900** includes an electrical winding **1910** surrounding a travel rod **1920**. The electrical winding **1910** may be covered by a housing **1930** and includes a first mount **1940** located on the end opposite the travel rod **1920**. The electrical winding **1910** further includes positive and negative electrical connections **1950** and **1960**. The travel rod **1920** is made of a magnetic material and is preferably made of magnetic stainless steel. The travel rod includes a second mount **1970** located on the end opposite the series of windings **1910**. When the travel rod moves up or down along path C in either direction there is a current introduced in the winding **1910** by inductance. Preferably, path C is a linear path. A diode bridge (not shown) is used to orient the generated current with respect to movement of the travel rod along path C in either direction. The shock absorber **1900** further includes a thermal harvesting material to convert thermal energy generated in the mechanical energy harvesting device into electrical energy. The thermal harvesting material may be any of the thermal harvesting materials discussed above with respect to solar harvesting strip **110**.

[0135] While the mechanical energy harvesting device has been described as a shock absorber **1900** in the above exemplary embodiment, in other embodiments, similar devices and methods are utilized to convert mechanical motion into usable electricity. Additional devices that may include a mechanical energy harvesting device include doors, hoods, hatchbacks, break and accelerator pedals, knobs, switches or any other arrangement in which a travel rod **1920** and a series of windings **1910** surrounding the travel rod **1920** are moveable relative to each other.

Exemplary Embodiment of an Electrical Energy Generating Tire

[0136] Another ancillary or backup electrical generation device that may be included with the electric vehicle **1250** to generate electricity is an electrical energy generating tire **1560**. FIG. **20** illustrates an electrical energy generating tire according an exemplary embodiment of the invention.

[0137] An electrical energy generating tire **1560** generates electricity as it rolls along a driving surface, such as driving surface **120**. The tire has a preformed cavity which houses a piezo ceramic strip and/or thermal harvesting strip **2010** that is sandwiched between two reinforcement strips **2020** that are

coated with a conductor material forming positive and negative conductors above and below the piezo ceramic strip and/or thermal harvesting strip **2010**. Piezo ceramic strip comprises a Piezo ceramic material. Thermal harvesting strip comprises a thermal harvesting material, such as any of the thermal harvesting materials discussed above with respect to solar harvesting strip **110**.

[0138] The exterior of the tire includes tire tread **2030**. As the tire **1560** contacts the driving surface, the piezo ceramic strip is compressed and emits electrons that flow to the positive conductor. Likewise, the tire **1560** contacts the driving surface heat is generated in the tire from which thermal harvesting strip converts heat energy into electrical energy. Included in the tire is a sidewall conductor **2040**. The electricity flows to the sidewall and up to the rib of the tire via sidewall conductor **2040**. The rib contacts the inner portion of the rim, passing the electricity to the vehicle. The rim is separated into two halves that are electrically insulated from each other. Preferably, the outer portion of the rim functions as the positive side and the inner portion functions as the negative side. However, the polarity of the sides may be switched. Further, it is preferred that the electricity generated by the tires will be used to provide electricity for the atmospheric intake hydrogen motor **1260**. By using the electricity generated by the tires for the hydrogen generator, the overall charge of the vehicle will not be affected by hydrogen production.

[0139] While the invention has been shown and described with reference to certain embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention as defined by the appended claims and their equivalents.

1. A method for harvesting solar energy, the method comprising:

depositing a plurality of layers onto a surface area that is incident to solar energy, wherein at least one of the plurality of layers comprises at least one solar energy harvesting material bonded to the surface area and at least one of the plurality of layers comprises at least one magnetic material bonded to the surface area; and

converting at least one of thermal and photonic energy into electrical energy by the at least one solar energy harvesting material, wherein the at least one solar energy harvesting material is located within a magnetic field generated by the at least one magnetic material.

2. The method according to claim 1, wherein at least one discharge capacitor is comprised by one or among more than one of the plurality of layers, the discharge capacitor comprising at least two conductors that are spaced apart and substantially parallel and at least one dielectric material between the conductors, wherein the at least one discharge capacitor is charged by the electrical energy and augments the magnetic field.

3. The method according to claim 1, wherein the depositing of the plurality of layers onto a surface area comprises depositing one or more of the plurality of layers by spraying, hand application, or film deposition.

4. The method according to claim 1, wherein the at least one magnetic material is deposited as a line array of a plurality of adjacent magnet portions substantially parallel to the surface area and substantially parallel to each other, wherein opposing polar regions of each of the plurality of magnet portions are oriented such that a line between the opposing

polar regions of each of the plurality of magnet portions is perpendicular to the line array, further wherein each of the plurality of magnet portions have a substantially similar or opposite magnetic field orientation.

5. The method of claim 1, wherein the magnetic material is at least partially used for retaining and conveying information by staggering or eliminating portions of the magnetic material, or by adding diamagnetic material to the magnetic material to act as a magnetic field modifier.

6. The method according to claim 1, wherein the at least one solar energy harvesting material is a thermal harvesting material for converting thermal energy into electrical energy and a photonic energy harvesting material for converting photonic energy into electrical energy, wherein the thermal harvesting material and photonic energy harvesting material are comprised by different layers of the plurality of layers.

7. The method of claim 1, wherein one of the plurality of layers comprises a basecoat on which the magnetic material is deposited and another one of the plurality of layers comprises a transparent sealant material.

8. The method according to claim 1, wherein the surface area that is incident to solar energy is one of a driving surface and a body panel of a vehicle.

9. A multiple layer solar energy harvesting composition for deposition onto a surface area that is incident to solar energy, the composition comprising:

at least one magnetic material bonded to the surface area, for generating a magnetic field, wherein at least one of the multiple layers comprises the magnetic material; and at least one solar energy harvesting material bonded to the surface area, for converting at least one of thermal and photonic energy into electrical energy, wherein at least one of the multiple layers comprises the at least one solar energy harvesting material and wherein the at least one solar energy harvesting material is located within a magnetic field generated by the at least one magnetic material.

10. The multiple layer solar energy harvesting composition according to claim 9, wherein at least one discharge capacitor is comprised by one or among more than one of the multiple layers, the discharge capacitor comprising at least two conductors that are spaced apart and substantially parallel and at least one dielectric material between the conductors, wherein the at least one discharge capacitor is charged by the electrical energy and augments the magnetic field.

11. The multiple layer solar energy harvesting composition according to claim 10, wherein the deposition of the multiple layers onto a surface area comprises depositing one or more of the plurality of layers by spraying, hand application, or film deposition.

12. The multiple layer solar energy harvesting composition according to claim 9, wherein the at least one magnetic material is deposited as a line array of a plurality of adjacent magnet portions substantially parallel to the surface area and substantially parallel to each other, wherein opposing polar regions of each of the plurality of magnet portions are oriented such that a line between the opposing polar regions of each of the plurality of magnet portions is perpendicular to the line array, further wherein each of the plurality of magnet portions have a substantially similar or opposite magnetic field orientation.

13. The multiple layer solar energy harvesting composition of claim 9, wherein the magnetic material is at least partially

used for retaining and conveying information by staggering or eliminating portions of the magnetic material, or by adding diamagnetic material to the magnetic material to act as a magnetic field modifier.

14. The multiple layer solar energy harvesting composition according to claim 9, wherein the at least one solar energy harvesting material is a thermal harvesting material for converting thermal energy into electrical energy and a photonic energy harvesting material for converting photonic energy into electrical energy, wherein the thermal harvesting material and photonic energy harvesting material are comprised by different layers of the plurality of layers.

15. The multiple layer solar energy harvesting composition of claim 9, wherein one of the plurality of layers comprises a basecoat on which the magnetic material is deposited and another one of the plurality of layers comprises a transparent sealant material.

16. The multiple layer solar energy harvesting composition according to claim 9, wherein the surface area that is incident to solar energy is one of a driving surface and a body panel of a vehicle.

17. A method for harvesting solar energy, the method comprising:

depositing a plurality of layers onto a surface area that is incident to solar energy such that the plurality of layers are adhesively bonded to the surface area, wherein at least one of the plurality of layers comprises thermal energy harvesting material and at least one of the plurality of layers comprises a photonic energy harvesting material; and

converting thermal and photonic energy into electrical energy by the thermal and photonic energy harvesting materials, respectively.

18. The method according to claim 17, wherein the depositing of the plurality of layers onto a surface area comprises depositing one or more of the plurality of layers by spraying, hand application, or film deposition.

19. The method according to claim 17, wherein at least one of the plurality of layers comprises a magnetic material for generating a magnetic field, the magnetic material being deposited as a line array of a plurality of adjacent magnet portions substantially parallel to the surface area and substantially parallel to each other, wherein opposing polar regions of each of the plurality of magnet portions are oriented such that a line between the opposing polar regions of each of the plurality of magnet portions is perpendicular to the line array, further wherein each of the plurality of magnet portions have a substantially similar or opposite magnetic field orientation.

20. The method according to claim 19, wherein at least one discharge capacitor is comprised by one or among more than one of the plurality of layers, the discharge capacitor comprising at least two conductors that are spaced apart and substantially parallel and at least one dielectric between the conductors, wherein the at least one discharge capacitor is charged by the electrical energy and augments the magnetic field.

21-67. (canceled)

* * * * *