US008755839B2

(12) **United States Patent**
Parkulo et al.

(10) **Patent No.: US 8,755,839 B2**
(45) **Date of Patent: Jun. 17, 2014**

(54) **PERSONAL MULTIMEDIA COMMUNICATION SYSTEM AND NETWORK FOR EMERGENCY SERVICES PERSONNEL**

(75) Inventors: **Craig Michael Parkulo**, Concord, NC (US); **Wesley McChord Barbee**, Oakboro, NC (US); **Jerald Robert Malin**, Matthews, NC (US); **Jeffrey Lynn Landis**, Waxhaw, NC (US); **Matthew Shannon**, Troutman, NC (US)

(73) Assignee: **STI Licensing Corp.**, Beachwood, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 682 days.

(21) Appl. No.: **12/126,640**

(22) Filed: **May 23, 2008**

(65) **Prior Publication Data**

US 2009/0023421 A1 Jan. 22, 2009

Related U.S. Application Data

(63) Continuation of application No. 11/890,663, filed on Aug. 7, 2007, now Pat. No. 7,377,835, which is a continuation of application No. 11/744,901, filed on Dec. 23, 2003, now Pat. No. 7,263,379.

(60) Provisional application No. 60/436,038, filed on Dec. 23, 2002.

(51) **Int. Cl.**
H04M 1/00 (2006.01)

(52) **U.S. Cl.**
USPC **455/557**; 455/556.1; 455/404.2; 455/521; 455/456.1; 455/423; 455/424; 455/456.5; 455/403; 455/457; 340/501; 340/506; 340/539.13; 340/572.1; 340/825.36

(58) **Field of Classification Search**
USPC 455/557, 404.2, 556.1; 340/573.1, 340/539.13, 539.32, 539.11
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,468,656 A 8/1984 Clifford et al.
4,906,972 A 3/1990 Spencer

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1379026 1/2004
GB 2372892 9/2002
WO WO 03/050689 6/2003

OTHER PUBLICATIONS

Radio Frequency & Communications Planning Unit, "Requirement No. MG-41 (Issue 1): A Cardinal Points Requirement for a Radio Telemetry System for Use by the Fire Service."


(Continued)

Primary Examiner — Edward F. Urban
Assistant Examiner — Ganiyu A Hanidu
(74) *Attorney, Agent, or Firm* — The Small Patent Law Group LLC

(57) **ABSTRACT**

A personal multimedia communication system and network for emergency services personnel includes a plurality of personal communication systems linked together and to a base station in a network. Each personal communication system includes a PDA device mounted on a PASS control console, a video camera mounted on the PDA device, a GPS unit, a microphone, and other electronic devices. The various electronic devices are all communicatively connected to the PDA device. Data from the various devices may be collected in the PDA device and wirelessly transmitted to any other node or device in the network, including other personal communication devices. Each personal communication device may serve as a repeater, thus providing a wireless communications link between a device located out of range of the base station.

34 Claims, 15 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

5,392,771	A		2/1995	Mock et al.
5,552,772	A		9/1996	Janky et al.
5,564,429	A		10/1996	Bonn et al.
5,568,121	A		10/1996	Lamensdorf
5,596,652	A		1/1997	Piatek et al.
5,689,234	A		11/1997	Stumberg et al.
5,738,092	A		4/1998	Mock et al.
5,793,882	A		8/1998	Piatek et al.
5,815,417	A		9/1998	Orr et al.
5,864,481	A		1/1999	Gross et al.
5,878,819	A	*	3/1999	Denoize et al. 169/53
5,943,922	A		8/1999	Rolfe
5,946,618	A		8/1999	Agre et al.
5,950,133	A		9/1999	Bledsoe
5,959,423	A	*	9/1999	Nakanishi et al. 318/568.12
5,977,913	A		11/1999	Christ
5,990,793	A		11/1999	Bieback
6,031,454	A		2/2000	Lovejoy et al.
6,072,396	A		6/2000	Gaukel
6,091,331	A		7/2000	Toft et al.
6,100,806	A		8/2000	Gaukel
6,127,968	A	*	10/2000	Lu 342/357.31
6,169,497	B1		1/2001	Robert
6,198,394	B1	*	3/2001	Jacobsen et al. 340/573.1
6,201,475	B1		3/2001	Stumberg et al.
6,219,346	B1		4/2001	Maxemchuk
6,243,039	B1		6/2001	Elliott
6,268,798	B1		7/2001	Dymek et al.
6,285,857	B1		9/2001	Javitt
6,310,552	B1		10/2001	Stumberg
6,325,283	B1		12/2001	Chu et al.
6,333,694	B2		12/2001	Pierce et al.
6,364,026	B1	*	4/2002	Doshay 169/47
6,472,988	B1		10/2002	Feld et al.
6,504,794	B2	*	1/2003	Haase et al. 367/119
6,522,531	B1		2/2003	Quintana et al.
6,538,623	B1		3/2003	Parnian et al.
6,549,845	B2		4/2003	Eakle et al.
6,606,993	B1		8/2003	Wiesmann et al.
6,653,937	B2		11/2003	Nelson
6,675,091	B2		1/2004	Navab
6,703,930	B2		3/2004	Skinner
6,824,065	B2		11/2004	Boone et al.
6,826,117	B2	*	11/2004	Haase et al. 367/119
6,850,844	B1		2/2005	Walters et al.
6,853,303	B2		2/2005	Chen et al.
6,859,725	B2		2/2005	Challoner et al.
6,894,610	B2		5/2005	Schubert et al.
6,899,101	B2		5/2005	Haston et al.
6,930,608	B2		8/2005	Grajales et al.
6,965,344	B1		11/2005	Halsey et al.
6,999,441	B2		2/2006	Flammer
7,005,980	B1	*	2/2006	Schmidt et al. 340/539.13
7,034,678	B2		4/2006	Burkley et al.
7,079,831	B2		7/2006	Schwartzman et al.
7,089,930	B2		8/2006	Adams et al.
7,091,852	B2		8/2006	Mason et al.
7,113,089	B2		9/2006	Ho
7,126,951	B2		10/2006	Belcea et al.
7,148,803	B2		12/2006	Brandy
7,498,980	B2	*	3/2009	Kagawa et al. 342/357.04
2001/0034793	A1		10/2001	Madruga et al.
2001/0036832	A1	*	11/2001	McKay 455/456
2001/0048364	A1		12/2001	Kalthoff et al.
2001/0049837	A1	*	12/2001	Slack 2/6.2
2002/0008625	A1	*	1/2002	Adams et al. 340/573.1
2002/0058508	A1		5/2002	Pallas et al.
2002/0065594	A1		5/2002	Squires et al.
2002/0065868	A1		5/2002	Lunsford et al.
2002/0081970	A1		6/2002	Wingren
2002/0098843	A1		7/2002	Struhsaker
2002/0135488	A1		9/2002	Hibbs et al.
2002/0159409	A1		10/2002	Wolfe et al.
2002/0188402	A1		12/2002	Huang et al.
2003/0078029	A1		4/2003	Petite
2003/0152061	A1		8/2003	Halsey et al.
2003/0165128	A1		9/2003	Sisodia et al.
2003/0214397	A1		11/2003	Perkins et al.
2004/0001442	A1		1/2004	Rayment et al.
2004/0004537	A1		1/2004	Flick
2004/0004547	A1		1/2004	Appelt et al.
2004/0008663	A1		1/2004	Srikrishna et al.
2004/0070515	A1		4/2004	Burkley et al.
2004/0087316	A1		5/2004	Caci
2004/0088584	A1		5/2004	Shacher et al.
2004/0105399	A1		6/2004	Robertazzi et al.
2004/0185822	A1		9/2004	Tealdi et al.
2004/0223469	A1		11/2004	Bahl et al.
2005/0001720	A1		1/2005	Mason et al.
2005/0065678	A1		3/2005	Smith et al.
2005/0124377	A1		6/2005	Shih et al.
2005/0152396	A1		7/2005	Pichna et al.
2005/0165616	A1		7/2005	Ellis et al.
2005/0185606	A1		8/2005	Rayment et al.
2005/0239451	A1		10/2005	Periyalwar et al.
2005/0245272	A1		11/2005	Spaur et al.
2006/0023681	A1		2/2006	A'Rafat
2006/0079180	A1		4/2006	Sinivaara
2006/0087993	A1		4/2006	Sengupta et al.
2006/0120370	A1		6/2006	Ginchereau et al.
2006/0158329	A1		7/2006	Burkley et al.
2006/0216011	A1		9/2006	Godehn
2006/0265664	A1		11/2006	Simons et al.
2006/0273894	A1		12/2006	Goehler
2007/0129045	A1		6/2007	Aerrabotu
2011/0196651	A1	*	8/2011	Delin et al. 702/178

OTHER PUBLICATIONS

Survivair Pant®her®, Panther, 6 pgs.

A Fire Service User Requirement for Telemetry at Incidents: JCDD/40—Issue 02; Jun. 9, 1997, 23 pages.

Personnel Accountability System Technology Assessment; United States Fire Administration; Federal Emergency Management Agency; 86 pages.

Personnel Accountability System Technology Assessment; United States Fire Administration; Federal Emergency management Agency; Dec. 1999, 86 pgs.

Radio Frequency & Communication Planning Unit, Requirement No. MG-41 (Issue 1): A Cardinal Points Requirement for a Radio Telemetry System for Use by the Fire Service; Jan. 12, 1994; 51 pages.

Survivair Pant®her®, Panther, Mar. 2003, 6 pgs.

* cited by examiner



05
OTHER LANS
70
BASE GPS
65
WAN
80
Satellite
68
LAN
70
15
104
28
15
104
28
15
104
28

Fig. 1




Fig. 2



28
107
HUD
TO/FROM
LAN 70
60
CAMERA
15
FROM GPS
SAT. 68
10
PDA
104
50
PASS
CONTROL
CONSOLE
30
PASS UNIT
20

Fig. 3



130
40
BATTERY
31
MOTION SENSOR
32
HEADS UP DISPLAY
41
PERSONAL BIOMETRICS SENSORS
42
ENVIRONMENTAL SENSORS
43
MICRO-CONTROLLER
35
RIGHT BACKUP LED
33
RIGHT PIEZO
34
LEFT PIEZO
36
LEFT BACKUP LED
FROM "CYLINDER IN" SWITCH
37
39
TO/FROM PASS
38
CONTROL CONSOLE
FROM TANK
PRESSURE SENSOR

Fig. 4




Fig. 5



150
IR Rx/Tx
59
57
55
TO/FROM
PASS UNIT
58
LED's
52
PUSH BUTTONS
53

Fig. 6




Fig. 7



110
19
LCD
12
122
121
22
23
GPS ANTENNA
GPS
MAIN BATTERY
111
123
ALTIMETER
24
MEMORY BACKUP BATTERY
07
FUNCTION BUTTONS
MICRO-PROCESSOR
16
AUDIO I/O
113
112
LAN ANTENNA
NIC
21
KEYPAD
11
VIDEO INPUT
17
IR Rx/Tx
13

Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13



190
IR Rx/Tx
196
191
97
PIEZO
197
BATTERY
192
MOTION SENSOR
98
LED's
PUSH BUTTONS
195

Fig. 14




Fig. 15

PERSONAL MULTIMEDIA COMMUNICATION SYSTEM AND NETWORK FOR EMERGENCY SERVICES PERSONNEL

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. application Ser. No. 11/890,661 filed Aug. 7, 2007 and entitled "PERSONAL MULTIMEDIA COMMUNICATION SYSTEM AND NETWORK FOR EMERGENCY SERVICES PERSONNEL" which is a continuation of U.S. application Ser. No. 10/744,901, filed Dec. 23, 2003 and entitled "PERSONAL MULTIMEDIA COMMUNICATION SYSTEM AND NETWORK FOR EMERGENCY SERVICES PERSONNEL", which was entitled to the benefit of, and claims priority to, provisional U.S. patent application Ser. No. 60/436,038 filed Dec. 23, 2002 and entitled "HANDHELD MULTIMEDIA COMMUNICATION SYSTEM FOR FIREFIGHTERS," of which the entirety of each is incorporated herein by reference.

BACKGROUND OF THE PRESENT INVENTION

1. Field of the Present Invention

The present invention relates to communication systems for firefighters, and, in particular, to handheld devices carried by firefighters and other emergency services personnel for collecting, displaying, wirelessly transmitting, and wirelessly receiving multimedia data in hazardous environments.

2. Background

Traditionally, the equipment carried into fires and other hazardous environments by firefighters and other emergency services personnel (generally referred to herein as "firefighters") has been primarily mechanical, with the most important piece of equipment being a self-contained breathing apparatus ("SCBA") for providing the wearer with breathable air. Conventional SCBA's generally include a facepiece, one or more pressurized cylinder or tank, and a hose. The facepiece, which covers the wearer's nose, mouth and eyes and includes a lens for external viewing, is supplied with air from the tanks via the hose. The tanks are secured to the wearer's body by a harness or backpack. One or more gauges are typically supplied to tell the user how much air remains in the tank.

More recently, firefighters have begun carrying a variety of auxiliary equipment on their backpacks or their headgear. Of this additional equipment, one of the most important items is a personal alarm safety system ("PASS") device. This device typically includes a motion sensor for monitoring whether the wearer has become motionless, thus indicating a potential injury or other debilitating condition for the wearer which may be signaled with audible or visual alarms or alert signals. The PASS device may also be integrated with a pressure gauge, thus serving multiple functions. The pressure gauge portion of the PASS device may be separated from the motion sensor portion to permit the user to look at the gauge when desired while positioning the motion sensor on the backpack. However, most PASS devices or systems are incapable of alerting personnel other than the wearer using any method other than the audible or visible alert signals generated by the PASS devices themselves, which has been a serious shortcoming of such devices.

This problem was partially solved with the development of an advanced PASS device which was capable of transmitting data from the PASS device back to a central location. The Scott Emergency Management System ("SEMS"), manufactured by Scott Health & Safety of Monroe, N.C., uses transmitting PASS devices, each carried by an individual firefighter, to transmit PASS data back to a central base station. However, the SEMS devices use a point-to-point protocol, wherein data received from the PASS device may only be transmitted as full duplex radio data directly to a dedicated base station. This technology limits the range of the Scott SEMS device. This limitation can be overcome by deploying repeaters to allow greater effective transmission distances from individual transmitting PASS devices. Unfortunately, using repeaters to relay the information has shortcomings in firefighting environments. First, time must be taken to place the repeaters in key locations in and around the burning building or other firefighting environment in order to have the ability to have at least one repeater within range of every firefighter and the base station. In addition, the repeaters are not mobile, and each will remain in a single location until it is physically moved to another one, which is also time consuming. Further, in a building fire it is not always possible to retrieve the repeater if dropped inside the building due to changes in the building environment. Thus, a more flexible and effective transmitting PASS system is needed.

In addition, there has been an increased emphasis in recent years on the development of other electronic devices to be carried by firefighters. These include heads up displays ("HUDs") for displaying tank pressure or other information to a user directly in his line of sight; video cameras, and particularly thermal imaging cameras, for capturing visual data or for use in seeing through dense smoke, recognizing areas of thermal stress, and the like; GPS devices for giving a firefighter information about his location, and many other devices. In addition, additional onboard sensors have been developed or are being developed for monitoring biometric conditions of the firefighter, environmental conditions, additional equipment information, and many other conditions and data. Still further, firefighters continue to carry audio communications devices such as radios and the like to facilitate communications between firefighters or to a command center located outside the immediate area of danger.

Unfortunately, until now there has been no effort to consolidate all of this information in a single location, or to communicate multiple different types of data from one firefighter to another or from one firefighter to a command center using a single device. This; means that there is no central location or device carried by a firefighter on which he may view or otherwise receive multiple different types of data, thereby avoiding the problem of having to check or consult different devices to receive different types of data. Moreover, it has been impossible to correlate data of one type with data of another type without going through a tedious manual process, if such a correlation is possible at all. For example, it is difficult if not impossible with current systems and devices to correlate GPS data captured over time by a firefighter's GPS device with video data captured by a thermal imaging camera carried by the same firefighter. Likewise, it has been difficult or impossible to correlate audio signals, video signals or data, positional data, biometric data, environmental data, SCBA status information and other data using either the firefighter's current equipment or at the command center using data transmitted from the firefighter thereto.

Thus, a convenient, robust, handheld solution to all of these problems is needed in order to improve the effectiveness of firefighters and other emergency services personnel.

SUMMARY OF THE PRESENT INVENTION

The present invention comprises a personal multimedia communication system and network for firefighters and other

emergency services personnel. The communication system and network may include a PDA device, a PASS system and a video camera, where the PDA device includes a GPS subsystem, a PASS interface, a video input, and a wireless network interface for communicating with a wireless LAN. Broadly defined, the present invention according to one aspect is a method of communicating multimedia data from a personal communication system carried by a firefighter to a base station including: gathering multimedia data at a first personal communication system carried by a first firefighter in a hazardous environment; wirelessly broadcasting at least some of the data using _a standard protocol; receiving, at a second personal communication system carried by a second firefighter, the data broadcast by the first personal communication system; upon receiving the, data at the second personal communication system, wirelessly broadcasting the data using the standard protocol; and receiving, at a base station, the data broadcast by the second personal, communication system.

The present invention, according to another aspect of the present invention, includes a personal communication system for use by a firefighter in a hazardous environment, including: a PASS system, the PASS system including a PASS unit to be carried directly on a firefighter's backpack and a PASS control console to be hung from the backpack, the PASS control console being connected to the PASS unit by at least a communications interface; and a PDA device, releasably mounted on the PASS control console and electrically connected to the PASS control such that data from the PASS unit may be transmitted to the PDA device via the PASS control console.

In features of this aspect, the personal communication system further includes a video camera releasably mounted on the PDA device and electrically connected to the PDA device such that video data from the video camera may be transmitted to the PDA device; and the video camera is a thermal imaging camera.

The present invention, according to another aspect of the present invention; includes a personal communication system for use by a firefighter in a hazardous environment, including: a support apparatus to be worn by a firefighter in a hazardous environment; a first onboard data source carried by the support apparatus; a second onboard data source carried by the support apparatus; and a PDA device communicatively connected to both the first onboard data source and the second onboard data source.

In feature of this aspect, the first onboard data source is a PASS system; the PDA device has a display adapted to display data from both the first onboard data source and the second onboard data source; the PDA device has a wireless transmitter adapted to transmit data from both the first onboard data source and the second onboard data source; the second onboard data source is a video camera, a microphone, a GPS device, a biometric sensor for measuring the body temperature, pulse rate or CO2 level of the firefighter, or an environmental sensor: for measuring the environmental temperature or sensing gas.

The present invention, according to another aspect of the present invention, includes a method of communicating at least two types of multimedia data from a personal, communication system carried by a firefighter to a remote location, including: gathering a first stream of multimedia data of a first data type; communicating the first stream of multimedia data of the first data type to a computer device in a personal communication system carried by a firefighter; gathering a second stream of multimedia data of a second data type; communicating the second stream of multimedia data of the second data type to the computer device; wirelessly transmitting the first and second streams of data from the computer device to a remote location; receiving the first and second streams of data from the computer device at the remote location; and correlating the first stream of data with the second stream of data.

In features of this aspect, the correlating step takes place in the computer device before transmission: the correlating step takes place at the remote location after receiving the first and second streams of data; the first data type is a reading of a motion sensor in a PASS system, the first stream of multimedia data is a set of such readings, and the second data type is a physical location reading, a video image, or an audio signal; the first data type is a physical location reading (such as a GPS reading), the first stream of multimedia data is a set of such readings, and the second data type is a video image or an audio signal; and the first and second streams of data are gathered at sequential points in time, and correlating the first stream of data with the second stream of data includes time-synchronizing the two streams of data.

The present invention, according to another aspect of the present invention, includes a method of communicating positional data from a personal communication system carried by a firefighter to a remote location, including: providing a personal communication system, the personal communication system including at least a positional data gathering device and a wireless transmitter; gathering, via the positional data gathering device, positional data indicative of the physical location of the personal communication system; and transmitting the positional data to a remote location via the wireless transmitter.

In features of this aspect, the positional data gathering device is a GPS unit; the positional data gathering device is a dead reckoning device; and the method further includes providing, at the remote location, a base GPS unit, receiving, at the remote location, the positional data transmitted from the personal communication system, comparing the received positional data with positional data from the base GPS unit, generating data indicative of the comparison, and wirelessly transmitting the comparison data to the personal communication system.

The present invention, according to another aspect of the present invention, includes a communications network for emergency personnel, including: a plurality of personal communication systems, each carried by a firefighter in a hazardous environment, wherein each personal communication system including a PDA device connected to at least one onboard data gathering device carried by the firefighter and having a wireless transceiver, and wherein each personal communication system is adapted to send and receive signals from at least some of the other personal communication systems; and a base station adapted to send and receive wireless signals from at least some of the personal communication systems.

In features of this aspect, the at least one onboard data gathering device in each personal communication system includes a PASS system; the at least one onboard data gathering device in each personal communication system includes a positional data gathering device; the positional data gathering device in each personal communication system is a GPS unit; the at least one onboard data gathering device in each personal communication system includes a video camera; and the video camera in each personal communication system is a thermal imaging camera.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodi-

ment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features, embodiments, and advantages of the present invention will become apparent from the following detailed description with reference to the drawings, wherein:

FIG. **1** is a block diagram of a personal multimedia communication system and network in accordance with a preferred embodiment of the present invention:

FIG. **2** is a perspective view of equipment carried by a firefighter or another emergency services worker in accordance with a preferred embodiment of the present invention;

FIG. **3** is a block diagram of one of the personal communications systems of FIG. **1**;

FIG. **4** is a block diagram of the internal computer hardware system of the PASS unit of FIGS. **2** and **3**;

FIG. **5** is a perspective view of the PASS control console of FIGS. **2** and **3**;

FIG. **6** is a block diagram of the internal computer hardware system of the PASS control console of FIG. **5**;

FIG. **7** is a perspective view of the PDA device of FIGS. **2** and **3**;

FIG. **8** is a block diagram of the internal computer hardware system of the PDA device of FIG. **7**;

FIG. **9** is a perspective view illustrating the interconnection of the PDA device of FIG. **7** to the PASS control console of FIG. **5**;

FIG. **10** is a perspective view of an alternative embodiment of the PDA device of FIG. **1**;

FIG. **11** is a perspective view of an alternative embodiment of the PASS control console of FIG. **1**;

FIG. **12** is a perspective view illustrating the interconnection of the PDA device of FIG. **10** to the PASS control console of FIG. **11**;

FIG. **13** is a perspective view of a mini-PASS unit;

FIG. **14** is a block diagram of the internal computer hardware system of the mini-PASS unit of FIG. **13**; and

FIG. **15** is a perspective view illustrating the interconnection of the PDA device of FIG. **10** to the mini-PASS unit of FIG. **13**.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings, in which like numerals represent like components throughout the several views, a handheld multimedia communication system for firefighters and other emergency services personnel is hereby described. FIG. **1** is a block diagram of a personal multimedia communication system and network **05** in accordance with a preferred embodiment of the present invention. As illustrated therein, the system and network **05** may include one, and typically a plurality, of personal communication systems **15** interlinked with a truck-based global positioning system ("GPS") unit **65**, the GPS satellite constellation **68**, a local area network ("LAN") **70**, and a wide area network ("WAN") **80**: Other LANS **70** may likewise be linked to the system and network **05** via the WAN **80**, but in order to simplify the discussion, only one LAN **70** will generally be discussed and illustrated herein.

Each personal communication system **15** is designed to be carried by an individual firefighter or other emergency services personnel as part of his equipment **28**. As shown in FIG. **1**, firefighters and many other emergency services personnel that enter a dangerous environment typically carry an air tank **104** as part of a self-contained breathing apparatus ("SCBA"), but the equipment **28** may include a number of other components as well. FIG. **3** is a perspective view of equipment **28** carried by a firefighter or another emergency services worker in accordance with a preferred embodiment of the present invention. As illustrated therein, the equipment **28** may include a collection of conventional firefighting or safety equipment mounted on a backpack **101**, as well as headgear **105**, worn on the user's head and connected to the air tank **104** by a first pressure line **102**, for supplying breathable air from the air tank **104** to the user's mouth and nose.

FIG. **3** is a block diagram of one of the personal communications systems **15** of FIG. **1**. As shown, each personal communications system **15** may include a Personal Alert Safety System ("PASS") system **20**, a personal digital assistant ("PDA") device **10**, a video camera **60** and a "heads-up" display ("HUD") **107**. Like many conventional PASS systems, the PASS system **20** of the present invention preferably includes both a PASS unit **30** and a separate PASS control console **50**, and the PASS unit **30** may be carried conventionally in a recess in the user's backpack **101**, while the PASS control console **50** preferably hangs from the end of a second pressure line **106**, connected via a pressure reducer to the air tank **104**, and a reinforced electronics cable sheath **103**. The HUD **107** may be of conventional design, connected to the other electronic components via an electronics cable which is preferably integral with the second pressure line **106** but may also be separate if necessary. The PDA device **10** may be communicatively coupled to the PASS control console **50**, and the camera **60** may be communicatively coupled to the PDA device **10**.

FIG. **4** is a block diagram of the internal computer hardware system **130** of the PASS unit **30** of FIGS. **2** and **3**. The internal computer hardware system **130** for each PASS unit **30** preferably includes a microcontroller **43**, a motion sensor module **31**, a HUD interface **32**, one or more piezo alarms **33**, **34**, one or more LED's **35**, **36**, an input **37** from a "cylinder in" switch, a PASS control console interface **38**, a tank pressure sensor input **39** and a battery **40**.

The motion sensor module **31** preferably includes a tri-axial magnetometer and a tri-axial accelerometer to provide an inertial guidance system as well as being operative with the microcontroller **43** to provide an indication as to whether the PASS unit **30** has been motionless for a predetermined period of time. However, a simple motion sensor function (without the inertial guidance feature) may likewise be provided by a simple mechanical sensor of conventional design.

The HUD interface **32** enables data, signals or the like to be communicated between the PASS unit **30** and the HUD unit **107** located on headgear worn by the user carrying the PASS unit **30**. The piezo alarms **33**, **34**, which preferably include a right side piezo alarm **33** and a left-side piezo alarm **34**, are sound generators that may be used to create a variety of sound patterns and are activated in a variety of circumstances, such as when the motion sensor module **31** indicates that the PASS unit **30** has been motionless for the predetermined period of time, when an air tank is installed or removed, when air pressure is low, when radio communications have been lost, or in order to alert the user that he should look at the display. Piezo alarms such as these are included on PASS systems sold by Scott Health and Safety of Monroe, N.C. The LED's **35**, **36**, which preferably include a right-side LED **35** and a left-side LED **36**, are backup lights that are activated when the motion sensor module **31** indicates that the PASS unit **30** has been motionless for the predetermined period of time. The "cylinder in" input **37** receives an indication from a SCBA as to whether an air tank **104** has been installed therein or not.

The PASS control console interface **38** provides communication between the PASS unit **30** and the PASS control console **50**. This interface **38** may be an IC2, CAN, RS-232, RS-485 or the like communication bus. The tank pressure sensor input **39** receives input from a pressure sensor, located on the air tank **104**, as to the amount of air remaining in the air tank **104** based on the amount of pressure or other related variable. The PASS unit **30** may be any conventional PASS unit having the functionality described above. One PASS unit **30** suitable for use with the present invention is the standard PASS unit manufactured by Scott Technologies of Monroe, N.C.

The PASS unit **30** may also include other sensor devices and interfaces. These may include, but are not limited to, personal biometric sensors **41**, for monitoring physiological characteristics of the wearer and the like, and environmental sensors **42**, for monitoring environmental characteristics such as temperature, the presence of gas, and the like. Biometric sensors **41** may be IC's for measuring the body temperature of the firefighter, the firefighter's pulse rate or CO2 levels and the like and are preferably located inside the housing of the PASS unit **30**. The environmental sensors **42** are also circuits and may be located inside or outside the housing. One commercially-available module having such environmental sensor is an external module, available from Scott Health & Safety of Lancaster, N.Y., that communicates with the microcontroller **43** via IC2, CAN, RS-232. RS-485 or the like.

FIG. **5** is a perspective view of the PASS control console **50** of FIGS. **2** and **3**. The PASS control console **50** includes a housing **51**, a pressure gauge **52**, one or more pushbuttons **53**, a docking interface **54**, a PASS unit interface **55**, a pressure line input **56**, an internal computer hardware system **150**, illustrated in FIG. **6**, and a corresponding software system. The housing **51** is designed to accommodate the other components and is preferably of heavy-duty, hardened construction, the design of which would be apparent to one of ordinary skill in the art. The pressure gauge **52**, which is preferably an analog gauge and display, although other gauge and display technologies may be suitable as well, provides an indication as to the amount of air remaining in the air tank **104** based on the amount of pressure detected at the pressure line input **56**, which is connected to the second pressure line **106** to the air tank **104**, or other related variable. The pushbuttons **53**, which preferably include at least a reset button and a manual alarm, may be disposed in any convenient location in the housing **51** and, may be of conventional heavy-duty construction. The docking interface **54** is preferably located on the back of the PASS control console **50** in order to provide a mounting and connection location for the PDA device **10**, as described herein below, and includes an appropriately-shaped surface or surfaces in the housing **51**, and one or more latches (not shown) for releasably locking the PDA device **10** to the PASS control console **50**. The latches, which preferably each include a quick release mechanism, may be disposed, for example, on the sides or back of the PASS control console **50**. To assemble the PDA device **10** to the PASS control console **50**, the user may simply align the two devices **10**, **50** and push them together, causing the latches to lock the PDA device **10** in place automatically. To release the PDA device **10**, the same latches may simply be depressed, preferably at the same time. The PASS unit interface **55** provides communication between the PASS control console **50** and the PASS unit **30**.

FIG. **6** is a block diagram of the internal computer hardware system **150** of the PASS control console **50** of FIG. **5**. The internal computer hardware system **150** for each PASS control console **50** preferably includes a microcontroller **57**, the PASS unit interface **55**, an interface to the pressure gauge **52**, the pushbuttons **53** described previously, one or more visual indicators **58**, such as LED's, and an infrared transceiver **59**. Briefly described, the interface to the pressure gauge **52** permits pressure data to be communicated to the microcontroller **57**, and the infrared transceiver **59** is mounted externally to permit line-of-sight infrared communication with a PDA device **10** when the PASS control console **50** and the PDA device **10** are docked together. Many of the components of the internal computer hardware system **150** may be conventional components such as those found in the standard PASS control console manufactured by Scott Technologies of Monroe, N.C.; however, modifications apparent to one of ordinary skill in the art, must be made to a conventional PASS control console to make it suitable for use with the present invention.

FIG. **7** is a perspective view of the PDA device **10** of FIGS. **2** and **3**. As used herein, the term "PDA device" is generally understood to mean any user device having a microprocessor, a display, and a user interface for controlling the operation of the device, and shall include any device having the components and general functionality of any conventional PDA device, but it will be understood that the PDA device **10** of the present invention may further include additional components and functionality as described hereinbelow. The PDA device **10** includes a housing **06**, a display **19**, one or more pushbuttons **07**, a keypad **21** (shown only in FIG. **8**), a docking station **08**, an internal computer hardware system **110** (illustrated in FIG. **8**), and a corresponding software system. The housing **06** is designed to accommodate the other components and is preferably of heavy-duty, hardened construction, the design of which would be apparent to one of ordinary skill in the art. The display **19** is preferably a liquid crystal display ("LCD") with backlight of a type found generally on conventional PDA's; however, other displays, including displays using conventional, organic or polymer LED technology, may be suitable as well. The pushbuttons **07** may be disposed in any convenient location in the housing **06** and may be of conventional heavy-duty construction, while the keypad **21** may be hidden from view when the PDA device **10** is docked with the PASS control console **50** in order to better protect it. The docking station **08** is preferably located at the bottom of the PDA device **10** in order to permit it to be mounted on the PASS control console **50**, as described hereinbelow, and includes an appropriately-shaped recess in the housing **06**, one or more electrical contacts **09** and one or more latches (not shown) for releasably locking the PDA device **10** and at least a portion of a corresponding PASS system **20** together.

FIG. **8** is a block diagram of the internal computer hardware system **110** of the PDA device **10** of FIG. **7**. Each PDA device **10** includes a microprocessor **111**, a wireless network interface **11**, a GPS subsystem **12**, an infrared transceiver **13**, audio I/O **16**, a video input **17**, a keypad **21** and a battery system **22**. To minimize expense, the microprocessor **111** is preferably a commercially available reduced instruction set computing ("RISC")-based microprocessor such as the SA **110** "StrongARM®"-type microprocessor available from Intel. The wireless network interface **11** preferably includes a network interface card ("NIC") **112** and an antenna **113**. In a preferred embodiment, the wireless network interface **11** utilizes the: IEEE 802.11b standard communications protocol for data transmissions at 11 Gbits/sec in the 2.4 GHz frequency range.

The keypad **21** and pushbuttons **07** together enable a user to input data, select options, and otherwise control the operation of the PDA device **10**. Generally, the keypad **21** provides full operational control of the PDA device **10**, while the pushbuttons **07** serve as "shortcut" keys to enable certain functions to be carried out with a minimum of effort and time. The battery

system **22** preferably includes both a main general use battery **23** and a second battery **24**, which may be a coin cell, for backing up the memory. The battery, system **22** may be recharged using the electrical contracts **09** illustrated in FIG. **7**.

The GPS subsystem **12** includes a GPS device **121** and a dedicated antenna **122**. The GPS device **121** may utilize any known GPS technology, including differential GPS ("DGPS"), whereby positional errors are corrected through the use of ground references having known coordinates; assisted GPS ("A-GPS"), whereby data is collected from multiple sources to improve precision; or the like. For indoor use, the GPS device **121** may utilize the GL-16000 32-bit bus indoor chip set or the GL-HSRF serial interface chipset, both from Fujitsu. For outdoor use, the GPS device **121** may utilize the onboard MLOC GPS receiver chipset.

Although many GPS units are capable of measuring position in the Z-direction (i.e., elevation), the GPS subsystem **12** may also include a separate altimeter **123** for making or supplementing this measurement. The altimeter **123**, which may be an atmospheric pressure device or any other suitable device, preferably IC-based, may be incorporated in the PDA device **10** as shown or may be disposed elsewhere in the user's equipment **28**.

It will be apparent to those of ordinary skill in the art that other types of positioning systems may be substituted for the GPS subsystem **12** described herein. For example, positioning systems utilizing ultra-wide band ("UWB") technologies are currently being developed, and other wireless technologies may likewise be used or developed for use in determining precise location data. As used herein, the term "GPS" should generally be understood to encompass or anticipate the use of such technologies, and the selection and implementation of a device or system making use of such a technology will likewise be apparent to one of ordinary skill in the art.

The infrared transceiver **13** is mounted to permit external line-of-sight infrared communication with a PASS system **20** when the PDA device **10** and at least a portion of the PASS system **20** are docked together. The infrared transceiver **13** permits data to be relayed from the PASS system **20** to the LAN **70**, as described herein below.

The audio I/O **16** includes connections for input from a microphone and output to a speaker, each of which are preferably located in the headgear **105**. Using appropriate software, the microphone and speaker provide either full- or half-duplex, radio communication and permit radio communications to be carried out with other common radios such as those from Motorola and Harris Corp. In one preferred embodiment, the software is off-the-shelf software such as conventional Microsoft or JoySoft Voip software. In another preferred, embodiment, proprietary software may be developed that utilizes data compression algorithms.

The video input **17** permits the interconnection of a video data source, such as a video camera **60**, to the PDA device **10**, as described below. Preferably, the video input **17** includes an RS-170 standard video connector/interface or another standard video connector/interface together with a communications interface such as Springboard, Compact Flash, USB, or the like, the selection of which would be apparent to one of ordinary skill in the art based on the PDA device **10** being used, the camera **60** being used, and the like. The video input **17** permits data to be relayed from the video data source to the LAN **70**, as described herein below.

FIG. **9** is a perspective view illustrating the interconnection of the PDA device **10** of FIG. **7** to the PASS control console **50** of FIG. **5**. As illustrated therein, the housing **51** of the PASS control console **50** is guided into place in the recess of the docking station **08** such that the pressure gauge **52** on the PASS control console **50** remains visible. Once in place, the latches may be used to releasably lock the PDA device **10** and the PASS control console **50** together. When properly latched, the infrared transceiver **59** of the PASS control console **50** is aligned with the infrared transceiver **13** of the PDA device **10**, thus permitting line-of-sight communication between the two devices. It should also be noted that the docking process does not interfere with the pushbuttons **07**, **53** on either device or the PASS unit interface **55** and the pressure line input **56** on the PASS control console **50**.

Because firefighters and other personnel must frequently work in environments having low light or occluded surroundings, the video camera **60** is preferably an infrared or thermal imaging camera in order to add thermal awareness and enhanced visibility in such environments. By interfacing the video camera **60** with the PDA device **10**, visual images generated by the video camera **60** may be displayed on the PDA display **19**, thus potentially eliminating the need for a dedicated monitor on the video camera **60** itself. The video camera **60** is preferably mounted directly on the PDA device **10** as shown in FIG. **2** in order to enable the user to point the camera **60** in any desired direction. However, the camera **60** may alternatively be mounted elsewhere on the backpack **101**, such as on the shoulder straps supporting the backpack **101**, at or below shoulder height and oriented to face forward. Still further alternatively, the camera **60** may be mounted on the headgear **105**, but this mounting location is less desirable because of the extra weight that is thus added to the headgear **105**. Such extra weight may be uncomfortable for the wearer, and in addition may cause the weight of the headgear **105** to exceed specified limits.

If the camera **60** is to be mounted on the PDA device **10**, then the camera may be provided with an electrical connector disposed in a location and at an orientation such that it may be electrically coupled to the video input **17** of the PDA device **10** when the camera **60** is docked to the PDA device **10**. A latching system (not shown) may be provided to retain the camera **60** in this position on the PDA device **10**. The latching system may include one or more latches/quick release mechanisms located on the top or back of the PDA device **10** with corresponding mechanisms on the back or sides of the camera **60**. Advantageously, this direct connection between the camera **60** and the PDA device **10** minimizes delay in capturing data from the camera **60** on the PDA device **10** and avoids the risk of an extra cable becoming entangled in other equipment **28** or with the wearer's surroundings. It also may permit the use of a shared battery system between the PDA device **10** and the camera **60**, thereby enhancing power efficiency.

In operation, the PDA device **10** enables a variety of data to be transmitted to and from the PDA device **10**, thus providing the firefighter or other user carrying the PDA device **10** with a considerably greater tool set with which to work. To use the PDA device **10**, the battery system in the PDA device **10** is first recharged using the electrical contacts **09**. Once charged, the PDA device **10** is attached to the PASS control console **50**, by latching the PASS control console **50** to the PDA device **10** as described hereinabove. The docking procedure triggers an automatic boot procedure and provides onscreen instructions and, options to the user. Also, if desired, a video camera **60** may be attached to the PDA device **10** such that the video camera output is connected to the video input **17** of the PDA device **10**. The presence of a video camera **60** is also preferably detected automatically by the PDA device **10**. Once connected, digital images may be captured by the video camera **60** and transferred to the, PDA device **10** via the video input **17** of the PDA device **10**. The operating components of

a thermal imaging camera suitable for use with the present invention are available in the Eagle **160** camera available from Scott Health & Safety of Monroe, N.C.

Once the PDA device **10** is operational, it begins gathering data from a variety of sources. For example, on a periodic basis, the GPS subsystem **12** makes a positional determination using the GPS satellite constellation **68**, in accordance with conventional GPS operations. If the GPS subsystem **12** includes a separate altimeter **123**, then the microprocessor **111** may derive an additional vertical elevation measurement in conjunction with the X, Y and optional Z data developed by the GPS device **121**. When considered in the sequence in which they were determined, preferably in conjunction with an indication of the time at which they were determined, these readings form a "bread crumb" trail that reflects the path taken by the PDA device **10** as it was carried along by its owner.

Also, the PDA device **10** preferably receives data from the PASS system **20** via the-infrared transceiver **13**. The data may be received on a periodic basis, or the data may be received continuously. If received continuously, the PDA device **10** may ignore some of the data or may process all of it, as desired. The data received may include any data available to the PASS system **20**. Preferably, the data received includes at least an indication of the amount of air remaining in the air tank **104** and status information derived from the motion sensor module **31**. The data may also include other status information, environmental data gathered by the PASS unit **30**, biometric data gathered by the PASS unit **30**, and the like. Preferably, all information or data received from the PASS system **20** is time-coordinated with the GPS data so that at least some of the GPS readings are aligned in time with at least some of the PASS data.

At any time, the PDA device **10** may also receive other data input by the firefighter or other user carrying the PDA device **10**. For example, the PDA device may receive voice data and other ambient noise data from the microphone, or may receive data input by the user via the keypad **21** or pushbuttons **07**. Preferably, all of this data is coordinated with GPS data and PASS data.

In addition, if a video camera **60** is connected to the PDA device **10**, the PDA device **10** may receive, at any time, video data (which may include audio data) from the video camera **60** via the video input **17**. Video data from the camera **60** may be displayed on the PDA display **19** for viewing by various emergency personnel to assist in locating thermally intense zones, to see through dense smoke, or to locate victims or other emergency personnel.

Other data may be gathered in the PDA device **10** using a variety of other peripheral devices and interfaces. Preferably, the PDA device **10** is further equipped with a variety of standard I/O and interfaces for this purpose. For example, each PDA device **10** preferably further includes one or more USB ports, one or more PCMCIA slots, and/or other connectors and interfaces.

As various types of data are received by the PDA device **10**, the data is processed by the microprocessor **111**, and some or all of the data may be buffered in a memory that is preferably at least 128 MB in size. In addition, at least some of the data is transmitted via the wireless network interface **11** to the user's wireless LAN **70**. Thus, not only may a firefighter's PASS system **20**, may be monitored remotely to determine the status of his air tank **104** or whether the firefighter may be injured or otherwise debilitated, but position data (GPS, dead reckoning or both), audio data from the microphone, video data from the camera **60**, stored or user-input data from the PDA device **10**, and environmental or biometric data gathered by the PASS unit **30** may all likewise be transmitted as well.

The data is preferably transmitted in such a way that data received from the various sources at the same time is transmitted together (or in close proximity) so that a maximum amount of data for each point in time is grouped together. This enables a fuller "snapshot" of an emergency worker's situation in a dangerous area to be made available, using appropriate software, to personnel located at a command center. Thus, for example, if a firefighter's motion sensor indicates that his PASS system **20** has been motionless for more than the predetermined maximum period of time, then the positional data (GPS, dead reckoning or both) corresponding in time to the motion sensor data may be consulted to determine where the firefighter was when the PASS system **20** stopped moving. If desired, the complete "bread crumb" trail left by the firefighter's GPS subsystem **12** may be studied in order to determine how to each the firefighter. Preferably, the bread crumb trail may then be downloaded directly from the wireless LAN **70** into another firefighter's PDA device **10** for direct, on-the-scene use without having to exit the building or return to the truck. Similarly, video data may be coordinated with positional data to provide information to a command center as to the precise location of a particular situation captured by the video camera **60**, or audio data may be combined with PASS data to provide information about what a firefighter was saying or doing when his PASS unit **30** indicated that he became motionless. Of course, it will be apparent to those of ordinary skill in the art that a wide variety of useful combinations of data may be provided by the system of the present invention.

Because of the large amounts of bandwidth required to transmit video data, certain concessions may be necessary with regard to such transmissions. For example, in one embodiment, if video data is being transmitted, then audio data from the, user's microphone is not transmitted. In another approach, video images from the camera **60** may be compressed using MPEG or similar methods before being stored and/or transmitted.

The command center preferably further includes the truck-based GPS unit **65**. The truck-based GPS unit **65** includes a GPS device, a dedicated antenna, a controller, and a GPS almanac. Because the truck-based GPS unit **65** is located in relatively close proximity to each firefighter or other worker and his GPS-equipped PDA device **10**, small errors in the GPS data derived by a particular PDA device **10** may be accounted for using the readings from the truck-based GPS unit **65**.

In addition to transmitting data gathered from various onboard subsystems, each PDA device **10** is preferably capable of receiving data, from other personal communication systems **15** and other points or nodes in the LAN **70**. Incoming data may be received at the antenna **113** and relayed to the microprocessor **111** via the NIC **112**. Such data may include any data transmitted from another personal communication system **15** as well as similar data transmitted from a command center or similar node in the LAN **70**. Thus, for example, video data from the camera **60** of the personal communication system **15** of a first user may be transmitted via the PDA device **10** of that system **15** to a second user's personal communication system **15**, where it may be processed and displayed on the display **19** of the second system's PDA device **10**. This would permit several team members to see video captured by another team member acting as a scout. Similarly, positional data, audio data and the like may likewise be shared. In addition, data such as text messages, map or floor plan data, and the like may be transmitted from a command

center to the personal communication systems **15** of one or more personnel and displayed to them via the displays **19** of their respective PDA devices **10**.

In another feature of the present invention, each PDA device **10** may operate as a repeater unit for relaying data from other PDA devices **10** located in relatively close proximity. However, unlike previous systems that use deployable, dedicated repeaters to increase effective transmission distances, the system of the present invention, instead utilizes a peer-to-peer mesh network technology to achieve greater transmission distance. The PASS control console **50** of each individually-issued PASS system **20** is capable of full duplex transmissions with other PASS consoles **50**, using the 802.11 standard protocol, to form a mesh network architecture that does not rely on a central base station, router or access point to relay the data transmissions to the other client devices. All PASS control consoles **10** within the network act as repeaters, transmitting data (including voice, PASS data, dead reckoning and GPS coordinate data, video, and the like) from one device to the next device until the data packet has reached its final destination. Thus, for example, one firefighter may be in an area of a building from which direct communication with his wireless LAN **70** is impossible or unreliable, but because each PDA device **10** may be used to relay data from other PDA devices **10**, data from the firefighter's PDA device **10** may be relayed to the wireless LAN **70** by another PDA device **10** in the area. Thus, a PDA device **10** may also be used or modified to serve as a GPS location beacon, a data packet repeater, a "camera on a stick," an unmanned drop sensor for sensing and relaying data, a personal In unit, and the like.

It will be apparent that locating and tracking individual devices in a mesh network is also possible without requiring the use of GPS. However, the degree of accuracy may vary, and the use of a combination of dead reckoning with GPS, as described previously, can increase the accuracy to within +/−5 meters.

The peer-to-peer 802.11 mesh networking technology creates a mobile network without the need of any existing infrastructure. This mobile wireless LAN **70** may further be wirelessly interfaced with the WAN **80** (or a cell network) to facilitate communication and distribution of data over a larger area. Tie in may be provided through a base station, typically residing on a fire truck, since existing networks require interface hardware to address different network protocols. The WAN **80** may connect together other LAN's **70** on the scene; battalion equipment, including maintenance and support elements as well as equipment from the next higher echelon; land line communications, including to a GPS almanac service; the internet; hospitals, local government and other emergency agencies; and the like.

FIG. **10** is a perspective view of an alternative embodiment of a PDA device **210** for use in the system and network **05** of FIG. **1**. The PDA device **10** includes a housing **206**, a display **19**, one or more pushbuttons **07**, a keypad **21** (shown only in FIG. **8**) a docking station **08**, an internal computer hardware system **110**, illustrated in FIG. **8**, and a corresponding software system. The components are generally similar to that of the first described PDA device **10**, except that the housing **206** utilizes a different design in order to incorporate a "landscape"-type display **219**. The docking station **08** is likewise modified relative to the first-described PDA device **10** because of the different dimensions and shape of the rest of the housing **206**.

FIG. **11** is a perspective view of an alternative embodiment of a PASS control console **250** for use in the system and network **05** of FIG. **1**. The alternative PASS control console **250** includes a housing **251**, a pressure gauge **52**, one or more pushbuttons **53**, a docking interface **254**, a PASS unit interface **55**, a pressure line input **56**, an internal computer hardware system **150**, illustrated in FIG. **6**, and a corresponding software system. The components are generally similar to that of the first-described PASS control console **50**, except that the housing **251** utilizes a different design in order to accommodate the different design of the housing **206** of the alternative PDA device **210** illustrated in FIG. **10**.

FIG. **12** is a perspective view illustrating the interconnection of the PDA device **210** of FIG. **10** to the PASS control console **250** of FIG. **11**. As illustrated therein, the housing **251** of the alternative PASS control console **250** is guided into place in the recess of the docking station **208** such that the pressure gauge **52** on the alternative PASS control console **250** remains visible. Once in place, the latches may be used to releasably lock the alternative PDA device **210** and the alternative PASS control console **250** together. When properly latched, the infrared transceiver **59** of the alternative PASS control console **250** is aligned with the infrared transceiver **13** of the alternative PDA device **210**, thus permitting line-of-sight communication between the two devices **250**, **210**. It should also be noted that the docking process does not interfere with the pushbuttons **07**, **53** on either device or the PASS unit interface **55** and the pressure line input **56** on the alternative PASS control console **250**.

In an alternative embodiment, any PASS system **20** may instead include only a unitary mini-PASS unit **90**, thus dispensing with a PASS unit that is separate from the PASS control console. Mini-PASS units **90** are typically utilized by workers who are not equipped with an SCBA and thus do not require the full functionality of a; conventional PASS unit **30**. FIG. **13** is a perspective view of a mini-PASS unit **90**. The mini-PASS unit **90** includes a housing **91**, one or more pushbuttons **93**, a docking interface **94**, one or more visual indicators **98**, such as LED's, a electronics input **96**, a piezo alarm **97**, an internal computer hardware system **190**, illustrated in FIG. **14**, and a corresponding software system. As illustrated, the housing **91**, pushbuttons **93** and docking interface **94** are generally similar to the housing **51**, pushbuttons **53** and docking interface **54**, respectively, of the alternative PASS control console **250** of FIG. **11**, but it will be apparent that the various components could also be applied to the first-described PASS control console **50** illustrated in FIG. **5** as well. The piezo alarm **97** is a sound generator that is activated when a motion sensor **192** (shown in FIG. **14**), disposed within the mini-PASS unit **90**, indicates that the mini-PASS unit **90** has been motionless for a predetermined period of time. The LED's include a backup light that is likewise activated when the motion sensor **192** indicates that the PASS unit **90** has been motionless for the predetermined period of time. Because the mini-PASS unit **90** includes only a single component, there is no need for an interface such as the PASS unit interface **55** illustrated in FIG. **11**. However, an electronics input **96** may be provided to provide a means for receiving data from other onboard electronic devices similar to those referenced in the description of the PASS unit **30** of the first embodiment.

FIG. **14** is a block diagram of the internal computer hardware system **190** of the mini-PASS unit **90** of FIG. **13**. The internal computer hardware system **190** for each mini-PASS unit **90** preferably includes a microcontroller **191**, the motion sensor **192** described previously, a connection to the piezo alarm **97**, a connection to each visual indicator **98**, connections to the pushbuttons **93**, an infrared transceiver **196** and a battery **197**. Briefly described, the motion sensor **192** is operative with the microcontroller **191** to provide an indication as to whether the mini-PASS unit **90** has been motionless for a predetermined period of time; the piezo alarm **193** is a

sound generator that is activated when the motion sensor **192** indicates that the mini-PASS unit **90** has been motionless for the predetermined period of time; the LED's include lights that are activated when the motion sensor **192** indicates that the PASS unit **90** has been motionless for the predetermined period of time; and the infrared transceiver **196** is mounted externally to permit line-of-sight infrared communication with the alternative PDA device **210** when the mini-PASS unit **90** and the alternative PDA device **210** are docked together. Many of the components of the internal computer hardware, system **190** may be conventional components such as those found in the standard mini-PASS unit manufactured by Scott Technologies of Monroe, N.C.; however, modifications to a conventional mini-PASS unit, apparent to one of ordinary skill in the art, may be necessary to make it suitable for-use with the present invention.

FIG. **15** is a perspective view illustrating the interconnection of the alternative PDA device **210** of FIG. **10** to the mini-PASS unit **90** of FIG. **13**. The housing **91** of the mini-PASS unit **90** may be guided into place in the recess of the docking station **208** such that the pressure gauge **92** on the mini-PASS unit **90** remains visible. Once in place, the latches may be used to releasably lock the PDA device **210** and the mini-PASS unit **90** together. When properly latched, the infrared transceiver **196** of the mini-PASS unit **90** is aligned with the infrared transceiver **13** of the PDA device **210**, thus permitting line-of-sight communication between the two devices **90**, **210**. It should also be noted that the docking process does not interfere with the pushbuttons **07**, **93** on either device or the pressure line input **96** on the mini PASS unit **90**. Further, although the mini-PASS unit **90** is only shown docked with the alternative PDA device **210**, it should be apparent that the mini-PASS unit **90** may likewise be used with the first PDA device **10** described previously.

As noted previously, mini-PASS units **90** are typically used by personnel who are not carrying SCBA equipment and thus do not have an air tank **104** to be monitored. However; their operation is otherwise similar to that of conventional PASS units **30** in that data provided by a mini-PASS unit **90** may be relayed by the PDA device **10** in a manner similar to that of conventional PASS units **30** and PASS control consoles **50**.

Based on the foregoing information, it is readily understood by those persons skilled in the art that the present invention is susceptible of broad utility and application. Many embodiments and adaptations of the present invention other than those specifically described herein, as well as many variations, modifications, and equivalent arrangements, will be apparent from or reasonably suggested by the present invention and the thereof, without departing from the substance or scope of the present invention. Accordingly, while the present invention has been described herein in detail in relation to its preferred embodiment, it is to be understood that this disclosure is only illustrative and exemplary of the present invention and is made merely for the purpose of providing a full and enabling disclosure of the invention. The foregoing disclosure is not intended to be construed to limit the present invention or otherwise exclude any such other embodiments, adaptations, variations, modifications or equivalent arrangements; the present invention being limited only by the claims appended hereto and the equivalents thereof. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for the purpose of limitation.

What is claimed is:

1. A communications network for emergency personnel, comprising:

first and second personal communication systems (PCS) to be carried by first and second emergency personnel, the first PCS and second PCS each including an onboard data gathering device and at least one wireless transceiver, the transceivers of the first PCS and second PCS being configured to communicate with one another over a broadcasting network, the onboard data gathering devices collecting PASS data from a PASS system carried by the emergency personnel, the transceiver of the first PCS broadcasting PCS transmission signals including the PASS data associated with the first emergency personnel over the broadcasting network;

a display, carried by the second emergency personnel, the display presenting information based on the PCS transmission signal from the transceiver of the first PCS to assist the second emergency personnel in at least one of tracking and locating the first PCS; and

an imaging camera, carried by the second emergency personnel, the imaging camera detecting images of an environment where the second emergency personnel is located, wherein the imaging camera is at least one of a video camera and a thermal imaging camera and wherein the imaging camera includes a transceiver that broadcasts the images for reception at least one of another PCS or a base station.

2. The communications network of claim **1**, wherein the PCS transmission signal includes positional data, the information, that is presented on the display, being based on the positional data.

3. The communications network of claim **1**, wherein the PCS transmission signal includes positional data, the first PCS determining the positional data based on at least one of ultra-wide band related information, GPS related information and dead reckoning related information.

4. The communications network of claim **1**, wherein the second PCS includes memory storing at least one of map data and floor plan data associated with a hazardous environment surrounding the first emergency personnel, the display displaying at least one of a map and floor plan associated with the hazardous environment.

5. The communications network of claim **4**, further comprising a base station storing the at least one of map data and floor plan data such that the base station and the second PCS display a common map or floor plan data.

6. The communications network of claim **1**, wherein the first PCS broadcasts at least one of PASS and SCBA data that is received by the second PCS and wherein the second PCS rebroadcasts the at least one of PASS and SCBA data received.

7. A portable device for use in a hazardous environment to determine how to reach an emergency personnel carrying a personal communications system (PCS), the PCS including an onboard data gathering device and at least one wireless transceiver, the onboard data gathering device collecting PASS data from a PASS system carried by the emergency personnel, the transceiver broadcasting a PCS transmission signal, including the PASS data associated with the emergency personnel, over a broadcasting network, the portable device comprising:

a wireless receiver, carried by a user, the receiver receiving the PCS transmission signal from the transceiver of the PCS over the broadcasting network;

a display, coupled to the wireless receiver, the display being carried by the user and presenting information based on the PCS transmission signal from the transceiver of the PCS; and

an imaging camera, carried by the user, the imaging camera detecting images of an environment where the user is located based on a direction in which the imaging camera is pointed, wherein the imaging camera is at least one of a video camera and a thermal imaging camera and wherein the imaging camera includes a transceiver that broadcasts the images for reception at least one of another PCS or a base station.

8. The portable device of claim **7**, wherein the user is a firefighter carrying a PASS system and a PDA device, the receiver being housed in the PDA device that is releasably mounted on a PASS control console of the PASS system and electrically connected to the PASS control console such that data from a PASS unit may be transmitted to the PDA device via the PASS control console.

9. The portable device of claim **7**, wherein the PCS transmission signal includes positional data and the information presented on the display is based on the positional data.

10. The portable device of claim **7**, wherein the PCS transmission signal includes positional data, the positional data being determined at the PCS based on at least one of ultra-wide band related information, GPS related information and dead reckoning related information.

11. The portable device of claim **7**, further comprising a memory storing at least one of map data and floor plan data associated with the hazardous environment, the display displaying the at least one of a map and floor plan associated with the hazardous environment.

12. The portable device of claim **10**, wherein the display presenting information representative of a location of the firefighter based on the position data in the PCS transmission signal from the transceiver of the PCS.

13. The portable device of claim **7**, wherein the PCS transmission signal is rebroadcast between multiple PCS before being received by the receiver.

14. A method of communicating data from a first personal communication system carried by an emergency personnel while in a hazardous environment to a remote location, the method comprising:

providing a first personal communication system (PCS), the first PCS including at least a positional data gathering device and a wireless transmitter;

gathering, via the positional data gathering device, positional data indicative of at least one of a relative location of, and a path taken by, the first PCS;

transmitting the positional data to the remote location via the wireless transmitter over a broadcasting network; and

detecting images at a camera of the hazardous environment where the first PCS is located as video data, and transmitting the video data with the positional data over the broadcasting network to at least one of the remote location or another PCS.

15. The method of claim **14**, wherein the first PCS transmits the positional data over a broadcasting network to the remote location.

16. The method of claim **14**, further comprising collecting PASS data from a PASS system carried by the emergency personnel carrying the first PCS and transmitting the PASS data and the positional data over the broadcasting network to the remote location.

17. The method of claim **14**, wherein the positional data gathering device is a GPS unit.

18. The method of claim **14**, wherein the positional data gathering device is a dead reckoning device.

19. The method of claim **14**, further comprising:

providing, at the remote location, a base GPS unit;

receiving, at the remote location, the positional data transmitted from the first PCS;

comparing the received positional data with positional data from the base GPS unit;

generating data indicative of the comparison; and

wirelessly transmitting the comparison data to the first PCS.

20. The method of claim **14**, further comprising repeating the gathering operation over time to obtain over time, the positional data representative of a path taken by the first PCS as the first PCS is carried by an emergency personnel.

21. The method of claim **20**, further comprising obtaining timing information and transmitting the positional data with the timing information to the remote location.

22. The method of claim **20**, transmitting motion sensor data from a PASS system with the positional data; and utilizing the motion sensor data and corresponding positional data to determine how to reach the first PCS.

23. The method of claim **14**, further comprising receiving the positional data at a second PCS, and presenting the positional data at the second PCS for direct, on-the-scene use to determine how to reach the first PCS.

24. The method of claim **14**, further comprising displaying one of a map and a floor plan on a display of at least one of the remote location or another PCS.

25. The method of claim **14**, further comprising displaying one of a map and a floor plan in combination with the positional data in a manner to assist in determining where the first PCS is located.

26. The method of claim **14**, further comprising displaying the video data at the at least one of the remote location or another PCS to provide information regarding a situation captured by the camera.

27. The method of claim **14**, further comprising coordinating the video data with the positional data.

28. The method of claim **14**, further comprising providing an unmanned drop sensor within the hazardous environment, the drop sensor relaying the positional data over the broadcasting network from the first PCS to at least one of another PCS and or the remote location.

29. The method of claim **14**, further comprising providing a location beacon device within the hazardous environment, transmitting from the location beacon device a signal to the first PCS, and presenting information, at the first PCS, based on the signal transmitted from the location beacon device to assist the emergency personnel to locate the location beacon device.

30. The method of claim **14**, further comprising conveying the positional data between at least one intermediate PCS over the broadcasting network to at least one of a remote PCS and or the remote location; and displaying a floor plan of the hazardous environment at the at least one of the remote PCS or the remote location in combination with information indicative of the positional data to track and locate the first PCS.

31. The method of claim **14**, further comprising coupling a sound generator to the first PCS that produces a predetermined sound pattern indicating that a radio communications link has been lost between the first PCS and another PCS.

32. The communications network of claim **1**, further comprising an unmanned drop sensor placed within a hazardous environment surrounding the first emergency personnel, the drop sensor relaying the PCS transmission signal over the broadcasting network from the first PCS to at least one of the second PCS or the base station, wherein the drop sensor is at

least one of dropped by the first emergency personnel within the hazardous environment or positioned on at least one of a floor or the ground within the hazardous environment.

33. The method of claim **14**, further comprising providing an unmanned drop sensor within the hazardous environment, the drop sensor relaying the positional data over the broadcasting network from the first PCS to at least one of another PCS or the remote location, wherein the drop sensor is positioned on at least one of a floor or the ground within the hazardous environment.

34. The method of claim **14**, further comprising providing an unmanned drop sensor within the hazardous environment, the drop sensor relaying the positional data over the broadcasting network from the first PCS to at least one of another PCS or the remote location, wherein the drop sensor is dropped by the emergency personnel within the hazardous environment.

* * * * *