



US008062403B2

(12) **United States Patent**
Goode

(10) **Patent No.:** **US 8,062,403 B2**
(45) **Date of Patent:** **Nov. 22, 2011**

(54) **FILTER ELEMENTS FOR CIRCULATING AIR SYSTEMS**

(76) Inventor: **Jim Goode**, Dallas, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 589 days.

(21) Appl. No.: **12/250,399**

(22) Filed: **Oct. 13, 2008**

(65) **Prior Publication Data**

US 2009/0094952 A1 Apr. 16, 2009

Related U.S. Application Data

(60) Provisional application No. 60/998,772, filed on Oct. 12, 2007.

(51) **Int. Cl.**
B01D 50/00 (2006.01)

(52) **U.S. Cl.** **55/485**; 55/482; 55/486; 55/487;
55/488; 55/489; 55/490; 55/491; 55/492;
55/501; 55/522; 55/524; 55/525; 55/528

(58) **Field of Classification Search** 55/482,
55/485–489, 490, 491–492, 501, 522, 524–525,
55/528, 495, DIG. 31

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,597,927	A *	5/1952	Endres	96/17
3,364,661	A *	1/1968	Manherz et al.	55/418.1
3,399,516	A *	9/1968	Hough, Jr. et al.	55/487
3,727,769	A *	4/1973	Scholl	210/484
3,793,692	A *	2/1974	Tate et al.	29/896.62
4,141,703	A *	2/1979	Mulchi	96/132
4,610,705	A *	9/1986	Sarnosky et al.	96/135
4,902,306	A *	2/1990	Burnett et al.	95/69
4,904,288	A *	2/1990	d'Augereau	55/485

5,037,455	A *	8/1991	Scheineson et al.	96/17
5,108,470	A *	4/1992	Pick	96/58
5,336,299	A *	8/1994	Savell	95/70
5,453,116	A *	9/1995	Fischer et al.	95/278
5,454,845	A *	10/1995	Anahara et al.	55/482.1
5,525,136	A *	6/1996	Rosen	55/486
5,807,425	A *	9/1998	Gibbs	96/66
5,989,320	A *	11/1999	Rutkowski	96/55
6,152,978	A *	11/2000	Lundquist	55/385.1
6,156,089	A *	12/2000	Stemmer et al.	55/467
6,231,646	B1 *	5/2001	Schweizer et al.	96/17
6,372,004	B1 *	4/2002	Schultink et al.	55/382
6,464,761	B1 *	10/2002	Bugli	96/135
6,478,858	B2 *	11/2002	Angermann et al.	96/143
6,524,360	B2 *	2/2003	Cox et al.	55/382
6,764,533	B2 *	7/2004	Lobiondo, Jr.	96/66
6,811,588	B2 *	11/2004	Niakin	55/385.3
6,923,911	B1 *	8/2005	Beier et al.	210/273
7,255,838	B2 *	8/2007	Yuan et al.	422/177
7,686,859	B2 *	3/2010	Barratt	55/423
2001/0042361	A1 *	11/2001	Cox et al.	55/382
2002/0088214	A1 *	7/2002	Sherwood	55/486
2004/0083697	A1 *	5/2004	Niakin	55/486

(Continued)


Primary Examiner — Jason M Greene

Assistant Examiner — Dung H Bui

(57) **ABSTRACT**

An improvement to a reusable filtering assembly used in circulating air systems for residential or commercial heating and air conditioning systems. A series of layers consisting of filtering materials disposed between two framing units are comprised of the following: expanded metal lath, a layer of small fiber material, a layer of large fiber material, a layer of small crimp wire cloth, a layer of small fiber material, and a last layer of expanded metal lath. The present invention further comprises a stage loaded series of layers wherein the direction of air flow is from the first layer to the sixth layer comprising: Expanded Metal Lath, Small Fiber, Large Fiber, Small Crimp Wire Cloth, Small Fiber, and Expanded Metal Lath.

12 Claims, 2 Drawing Sheets



US 8,062,403 B2

Page 2

U.S. PATENT DOCUMENTS				
2004/0148913	A2 *	8/2004	Engel et al.	55/428
2004/0154273	A1 *	8/2004	Stephan	55/495
2004/0250683	A1 *	12/2004	Soane et al.	96/226
2007/0020156	A1 *	1/2007	Kraft et al.	422/177
2007/0062168	A1 *	3/2007	Adamini et al.	55/486
2007/0175192	A1 *	8/2007	Niakan et al.	55/486
2007/0251200	A1 *	11/2007	Volo et al.	55/482
2008/0168754	A1 *	7/2008	Frey et al.	55/488
				* cited by examiner






Fig. 1



1

FILTER ELEMENTS FOR CIRCULATING AIR SYSTEMS**CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the benefit of the priority date of provisional application 60/998,772, filed on Oct. 12, 2007.

FEDERALLY SPONSORED RESEARCH

Not Applicable

SEQUENCE LISTING OR PROGRAM

Not Applicable

STATEMENT REGARDING COPYRIGHTED MATERIAL

Portions of the disclosure of this patent document contain material that is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by any one of the patent document or the patent disclosure as it appears in the Patent and Trademark Office file or records, but otherwise reserves all copyright rights whatsoever.

BACKGROUND

Novelty filtering systems comprising multiple layers are known in the prior art, as are filtering elements for circulating air.

For example U.S. Pat. No. 4,904,228 to d'Augereau discloses a reusable filtering element for residential or commercial heating and air conditioning systems. Although this invention comprises a filtering means for large and small particles separation, the placement order of the various layers plug up the filters catch cell. Furthermore, it impairs the ability for cleaning the system with respect to hair, lint, or grease applications. The prior art consists of further drawbacks in the means of bracing the corners of the filtering system, particularly with rivets. Bracing the corners this way exhausts the possibility of disassembling the system, using it in highly corrosive environments, and the ability to clean each layer separately.

The d'Augereau reference also comprises HERSITE coated paint, and rejects the usage of filtering systems in food grade applications. Particularly, this paint has previously chipped off during high pressure cleaning, which has then entered air streams.

Therefore, it is the objective of the present invention to address the need for a novel and more effective filtering system comprising: efficient filter layer arrangements, rivetless corner connections, and a powder coated grids.

SUMMARY

The present invention comprises a reusable air filter assembly for circulating air systems. The assembly contains sandwiched materials comprising filtering layers. Each layer comprises a filtering feature which contributes to removing airborne particles in a circulating air system. The layered arrangement of the assembly is stage loaded, in the direction of airflow, as follows: expanded metal lath, small fiber, large fiber, small crimp wire cloth, small fiber, and expanded metal lath.

2

The air filter assembly contains support brackets at the junction of the framing means and further comprising stainless steel screws to improve the rigidity of the frame. In one preferred embodiment the support brackets are made of aluminum, comprising an "L" shape with two holes disposed thereon for fastening.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a perspective cut away view of the filter assembly. FIG. 2 is a front view of the filter assembly. FIG. 3 is a side view of the filter assembly.

DESCRIPTION

Referring to FIG. 1, an improvement on a reusable air filter assembly is shown and described. The filter assembly 10, comprises a framing means 12, for housing multiple filtering layers. In one preferred embodiment, the frame comprises four members connected to and disposed around the periphery of the filter. In another preferred embodiment, the framing means 12, comprises a sandwiched top frame unit and bottom frame unit, each of which is capable of sandwiching a number of layers of filtering materials. Each frame unit comprises a feature that overlaps the other, wherein a single screw can be disposed through the overlap to secure the framed units relative to each other.

A series of layers of filter material is sandwiched in the frame, comprising a first layer of expanded metal lath 18, a second layer of small fiber material 20, a third layer of large fiber material 22, a fourth layer of small crimp wire cloth 24, a fifth layer of small fiber material 26, and a sixth layer of expanded metal lath 28, wherein the direction of air flow is from the first layer to the sixth layer. In one preferred embodiment, small fiber material comprises warp and fill 12 mil monofil polypropylene, 4.5 oz/sq yd, honeycomb weave, 29×26 threads per inch; and large fiber material comprises warp and fill 20 mil monofil polypropylene, 10.2 oz/sq yd, honeycomb weave, 26×18 threads per inch.

Referring to FIG. 2, the filter assembly 10 comprises a framing means 12 held in a substantially rectangular shape and rigid at the corner junctions 34. The corner junctions further comprise support brackets 32 (shown in FIG. 3) for holding the framing means 12 in a static position from the interiors of the corner junctions 34.

Referring to FIG. 3, the filter assembly 10 comprises support brackets 32 on the interior of the framing means 12 wherein stainless steel screws 30 extend through the support brackets 32. The stainless steel screws 30 also extend through the framing means 12 at a point of overlap between the framing means 12 and the support brackets 32. In one preferred embodiment the support brackets 32 are made of aluminum and comprise an "L" shape, with two arms, wherein each arm is 40 mm in length and 16 mm in width. Yet in the illustrative embodiment, the support bracket 32 comprises two holes on each arm, wherein each hole is spaced 4 cm apart.

Referring again to FIG. 1, a preferred embodiment of the filter assembly 10 comprising a sixth layer of an expanded metal lath 28 layer comprising steel. In another preferred embodiment the expanded metal lath 28 comprises galvanized steel. In yet another preferred embodiment, the expanded metal lath 28 comprises powder coated galvanized steel. In a particular preferred embodiment, the stainless steel screws 30 comprise an 8×½ inch modified truss head self drilling screw.

3

All features disclosed in this specification, including any accompanying claims, abstract, and drawings, may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features.

Any element in a claim that does not explicitly state “means for” performing a specified function, or “step for” performing a specific function, is not to be interpreted as a “means” or “step” clause as specified in 35 U.S.C. §112, paragraph 6. In particular, the use of “step of” in the claims herein is not intended to invoke the provisions of 35 U.S.C. §112, paragraph 6.

Although preferred embodiments of the present invention have been shown and described, various modifications and substitutions may be made thereto without departing from the spirit and scope of the invention. Accordingly, it is to be understood that the present invention has been described by way of illustration and not limitation.

What is claimed is:

1. A reusable air filter assembly for circulating air systems, comprising:

- a. a frame, comprising two frame units capable of sandwiching a number of layers of material, and each comprising a feature that overlaps the other, wherein a single screw can be disposed through the overlap to secure the frames relative to each other;
- b. a series of material disposed in the frame, containing a first layer of expanded metal lath, a second layer of small fiber material, a third layer of large fiber material, a fourth layer of small crimp wire cloth, a fifth layer of small fiber material, and a sixth layer of expanded metal

4

lath, arranged in this order, wherein the direction of air flow is from the first layer to the sixth layer;

- c. screws anchoring the frame units in position; and
- d. support brackets for holding the frame units in position at corners of the frame units, wherein the screws extend through the support brackets and overlapping portions of the frame units.

2. The assembly of claim 1, wherein the support brackets comprise aluminum.

3. The assembly of claim 2, wherein the support brackets comprise “L” shaped members, with two arms, and wherein each arm is 40 mm in length and 16 mm in width.

4. The assembly of claim 3, wherein two holes are disposed on each arm.

5. The assembly of claim 4, wherein the holes are spaced 4 cm apart.

6. The assembly of claim 1, wherein the expanded metal lath comprises steel.

7. The assembly of claim 6, wherein the expanded metal lath comprises galvanized steel.

8. The assembly of claim 7, wherein the expanded metal lath comprises powder coated galvanized steel.

9. The assembly of claim 1, wherein the screws comprise stainless steel.

10. The assembly of claim 9, wherein the stainless steel screws comprise 8×½ modified tress drilling screws.

11. The assembly claim 1, wherein the small fiber material comprise warp and fill 12 mil monofil polypropylene, 4.5 oz/sq yd, honeycomb weave, 29×26 threads per inch.

12. The assembly of claim 1, wherein the large fiber material comprises warp and fill 20 mil monofil polypropylene, 10.2 oz/sq yd, honeycomb weave, 26×18 threads per inch.

* * * * *