



US 20140362565A1

(19) **United States**

(12) **Patent Application Publication**
YAO et al.

(10) **Pub. No.: US 2014/0362565 A1**

(43) **Pub. Date: Dec. 11, 2014**

(54) **LIGHT EMITTING DEVICE**

Publication Classification

(71) Applicant: **EPISTAR CORPORATION**, Hsinchu (TW)

(72) Inventors: **Chiu-Lin YAO**, Hsinchu (TW);
Min-Hsun HSIEH, Hsinchu (TW);
Been-Yu LIAW, Hsinchu (TW);
Wei-Chiang HU, Hsinchu (TW);
Po-Hung LAI, Hsinchu (TW);
Chun-Hung LIU, Hsinchu (TW);
Shih-An LIAO, Hsinchu (TW); **Yu-His SUNG**, Hsinchu (TW); **Ming-Chi HSU**, Hsinchu (TW)

(21) Appl. No.: **14/301,060**

(22) Filed: **Jun. 10, 2014**

(30) **Foreign Application Priority Data**

Jun. 11, 2013 (TW) 102120893

(51) **Int. Cl.**

H01L 33/38 (2006.01)

F21K 99/00 (2006.01)

(52) **U.S. Cl.**


CPC **H01L 33/38** (2013.01); **F21K 9/135** (2013.01)

USPC **362/223**; 257/88

(57)

ABSTRACT

This disclosure discloses a light-emitting device. The light-emitting device comprises: a first electrode part; a second electrode part; a third electrode part, spaced apart from the first electrode part and the second electrode part; and a light-emitting unit partially covering the first electrode part and the second electrode part and fully covering the second electrode part, the light-emitting unit having a conductive structure contacting the second electrode part.






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B




FIG. 7C






FIG. 7D






FIG. 8C




FIG. 8D




FIG. 8E




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 11E




FIG. 11F




FIG. 11G




FIG. 11H




FIG. 11I




FIG. 11J




FIG. 12




FIG. 12A




FIG. 12B

FIG. 12C




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 13D




FIG. 13E

LIGHT EMITTING DEVICE

BACKGROUND

Technical Field

[0001] The present disclosure relates to a light-emitting device, and in particular to a light-emitting device with an omnidirectional light pattern.

REFERENCE TO RELATED APPLICATION

[0002] This application claims the right of priority based on TW application Serial No. 102120893, filed on Jun. 11, 2013. The entire content of the application is hereby incorporated by reference.

DESCRIPTION OF THE RELATED ART

[0003] The light-emitting diodes (LEDs) of the solid-state lighting elements have the characteristics of low power consumption, low heat generation, long operational life, shock-proof, small volume, quick response and good opto-electrical property like light emission with a stable wavelength so the LEDs have been widely used in household appliances, indicator light of instruments, and opto-electrical products, etc. As the opto-electrical technology develops, the solid-state lighting elements have great progress in the light efficiency, operation life and the brightness, and LEDs are expected to become the main stream of the lighting devices in the coming future. However, in some application, there is a need to have a light-emitting apparatus with an omnidirectional light pattern which is not available using the conventional light emitting apparatus.

[0004] It is noted that the LEDs can be further connected to other components in order to form a light emitting apparatus. For example, the LEDs is disposed on a submount, and then on a carrier. Alternatively, a solder or an adhesive is formed between the LEDs and the carrier to form the light emitting apparatus. In addition, the carrier can further include electrode for electrically connecting to the LEDs.

SUMMARY OF THE DISCLOSURE

[0005] The present disclosure provides a light-emitting apparatus with an omnidirectional light pattern.

[0006] This disclosure discloses a light-emitting device. The light-emitting device comprises: a first electrode part; a second electrode part; a third electrode part, spaced apart from the first electrode part and the second electrode part; and a light-emitting unit partially covering the first electrode part and the second electrode part and fully covering the second electrode part, the light-emitting unit having a conductive structure contacting the second electrode part.

BRIEF DESCRIPTION OF THE DRAWING

[0007] The accompanying drawings are included to provide easy understanding of the application, and are incorporated herein and constitute a part of this specification. The drawings illustrate the embodiments of the application and, together with the description, serve to illustrate the principles of the application.

[0008] FIGS. 1A and 1B illustrate a perspective view of a light-emitting device in accordance with one embodiment of the present disclosure.

[0009] FIG. 1C illustrates a perspective view of a light-emitting device in accordance with another embodiment of the present disclosure, showing a conductive connecting connector formed on a side of a carrier.

[0010] FIG. 2A illustrates a top view of a light-emitting device in accordance with one embodiment of the present disclosure.

[0011] FIG. 2B illustrates a cross-sectional view taken along from line I-I' of FIG. 2A.

[0012] FIG. 3A illustrates a top view of a light-emitting device in accordance with one embodiment of the present disclosure.

[0013] FIG. 3B illustrates a cross-sectional view taken along from line II-II' of FIG. 3A.

[0014] FIG. 4A illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0015] FIG. 4B illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0016] FIG. 4C illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0017] FIG. 4D illustrates a bottom view of the light-emitting device of FIG. 4C.

[0018] FIG. 4E illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0019] FIG. 4F illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0020] FIG. 4G illustrates an equivalent circuit of the FIG. 4F.

[0021] FIG. 5A illustrates a cross-sectional view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0022] FIG. 5B illustrates a top view of the light-emitting device of FIG. 5A.

[0023] FIG. 5C illustrates a bottom view of the light-emitting device of FIG. 5A.

[0024] FIG. 5D illustrates a cross-sectional view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0025] FIG. 5E illustrates a top view of the light-emitting device of FIG. 5D.

[0026] FIGS. 6A and 6B illustrate cross-sectional views of a light-emitting device in accordance with another embodiment of the present disclosure.

[0027] FIG. 6C illustrates a top view of the light-emitting device of FIGS. 6A and 6B.

[0028] FIGS. 6D and 6E illustrate top and bottom views of an electrical plate embodied in the light-emitting device of FIGS. 6A and 6B.

[0029] FIG. 7A illustrates a cross-sectional view of a light-emitting diode unit in accordance with one embodiment of the present disclosure.

[0030] FIG. 7B illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0031] FIG. 7C illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0032] FIG. 7D illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0033] FIG. 8A illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0034] FIG. 8B illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0035] FIG. 8C illustrates a partial cross-sectional view of the light-emitting diode unit of FIG. 8A embodied in FIG. 5A.

[0036] FIG. 8D illustrates a cross-sectional view of a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0037] FIG. 8E illustrates a correlated color temperature spatial distribution of light emitted from a light-emitting diode unit in accordance with another embodiment of the present disclosure.

[0038] FIG. 9 illustrates a cross-sectional view of a light-emitting device in accordance with another embodiment of the present disclosure.

[0039] FIG. 10A illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0040] FIG. 10B illustrates a top view of a circuit board on which a light-emitting device is mounted in accordance with one embodiment of the present disclosure.

[0041] FIG. 11A illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0042] FIG. 11B illustrates a top view of FIG. 11A.

[0043] FIG. 11C illustrates a top view of a circuit board on which a light-emitting device is mounted in accordance with one embodiment of the present disclosure.

[0044] FIG. 11D illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0045] FIG. 11E illustrates a top view of FIG. 11D without a cover.

[0046] FIG. 11F illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0047] FIG. 11G illustrates a flexible carrier in a non-bending state.

[0048] FIG. 11H illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0049] FIG. 11I illustrates a flexible carrier in a non-bending state.

[0050] FIG. 11J illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure.

[0051] FIG. 12 illustrates a cross-sectional view of an LED tube in accordance with one embodiment of the present disclosure.

[0052] FIGS. 12A~12C illustrating a method of making the LED tube of FIG. 12.

[0053] FIGS. 13A~13D are views illustrating a method of making a light-emitting device in accordance with another embodiment of the present disclosure.

[0054] FIG. 13E illustrate a cross-sectional view of a light-emitting device of FIG. 13D.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0055] To better and concisely explain the disclosure, the same name or the same reference number given or appeared in different paragraphs or figures along the specification should have the same or equivalent meanings while it is once defined anywhere of the disclosure. In addition, these drawings are not necessarily drawn to scale. Likewise, the relative sizes of elements illustrated by the drawings may differ from the relative sizes depicted.

[0056] The following shows the description of embodiments of the present disclosure in accordance with the drawings.

[0057] FIGS. 1A and 1B illustrate a perspective view of a light emitting device 100 in accordance with one embodiment of the present disclosure. The light-emitting device 100 includes an oblong carrier with a top surface 101 and a bottom surface 102 opposite to the top surface 101, a plurality of light-emitting units 11 disposed on the top surface 101, a top electrode 20 formed on the top surface 101, a bottom electrode 30 formed on the bottom surface 102, and a transparent body 103 covering the top electrode 20 and the light-emitting units 11. In this embodiment, the carrier 10 has a length of 18 mm~30 mm and a width smaller than 3 mm, and the light-emitting unit 11 has a width of 0.5 mm~1.5 mm and a length of 1 mm~3 mm. Referring to FIG. 1A, the top electrode 20 includes two top electrode pads 201, 202 and a top electrode connector 203. Referring to FIG. 1B, the bottom electrode 30 is formed on the bottom surface 102 and includes two bottom electrode pads 301, 302 and a bottom electrode connector 303. The bottom electrode connector 303 can be a straight line, and is physically and electrically connected to the two electrode pads 301, 302. As shown in FIG. 1C, a conductive connecting connector 208 is optionally formed on a side of the carrier 10 for electrically connecting the top electrode pad 202 with the bottom electrode pad 302. Alternatively, a via hole (not shown) is formed within and penetrating the carrier 10, and a conductive material is fully or partly filled with the via hole for electrically connecting the top electrode pad 202 with the bottom electrode pad 302. In operation, when the light-emitting device 100 is connected to an external source (power supply) and when the conductive connecting connector 208 is not provided, the two top electrode pads 201, 202 can be respectively connected to a positive node and a negative node of the external source such that the light-emitting units 11 can emit light, that is, the external source is connected to the carrier 10 at the same surface (top surface) but at two opposite sides. In one embodiment, when the conductive connecting connector 208 is further provided for electrically connecting the top electrode pad 202 with the bottom electrode pad 302, a positive node and a negative node of the external source can be respectively connected to the top electrode pad 201 and the bottom electrode pad 301 such that the light-emitting units 11 can emit light, that is, the external source is connected to the carrier 10 at the different surfaces (top surface and bottom surface) but at the same side. By virtue of the top electrode 20, the bottom electrode 30 and/or the conductive connecting connector 208, the light-emitting device 100 can be connected to the external source at the different surfaces but the same side or at the same surface but two opposite sides for different application of the light-emitting device.

[0058] The transparent body 103 can include a single layer or a multilayer structure. When the transparent body 103 is a

multilayer structure (not shown), it sequentially includes a first transparent layer, a wavelength conversion layer, and a second transparent layer. The first transparent layer and the second transparent layer can include, e.g. epoxy, polyimide, BCB, PFCB, SU8, acrylic resin, PMMA, PET, PC, polyetherimide, fluorocarbon polymer, glass, Al_2O_3 , SINR, SOG, poly(tetrafluoroethene) or combinations thereof. The wavelength conversion layer includes aluminum oxide (such as YAG or TAG), silicate, vanadate, alkaline-earth metal silicate, alkaline-earth metal sulfide, alkaline-earth metal selenide, alkaline-earth metal gallium silicate, metal nitride, metal nitride oxide, a mixture of tungstate and molybdate, a mixture of oxide, or combinations thereof. In this embodiment, the light-emitting unit **11** can emit a blue light with a peak wavelength of 430 nm~480 nm, and some of the blue light is converted by the wavelength conversion layer to emit a yellow light with a peak wavelength of 570 nm~590 nm or a yellowish green light with a peak wavelength of 540 nm~570 nm. Furthermore, the yellow light or the yellowish green light is mixed with the unconverted blue light to produce a white light.

[0059] FIG. 2A is a top view of the light-emitting device as shown in FIG. 1A without showing the transparent body **103**. Referring to FIGS. 1A and 2A, the top electrode connector **203** is patterned and includes a plurality of electrode blocks **2031**. In this embodiment, the electrode blocks **2031** are arranged in a straight line along a length direction of the carrier **10** (X) and physically spaced apart from each other. Each of the electrode blocks **2031** includes a first end **2032** and a second end **2033**. In one embodiment, a distance (d_1) between the two adjacent light-emitting units **11** is 0.5 mm~1.2 mm, and each of the distances between the two adjacent light-emitting units **11** can be the same or different depending on actual requirements. FIG. 2B is a cross-sectional view taken along line I-I' of FIG. 2A with the transparent body **103** included. Referring to FIG. 2B, each of the light-emitting units **11** has a first connecting pad **111** (for example, p pad) and a second connecting pad **113** (for example, n pad). The first connecting pad **111** and the second connecting pad **113** are at positions corresponding to the first end **2032** of one electrode block **2031** and the second end **2033** of adjacent one electrode block **2031** for physically and electrically connecting therebetween. Accordingly, the light-emitting units **11** are electrically connected in series with each other on the carrier **10**. The transparent body **103** is provided to cover portions of the top electrode **20** and the light-emitting units **11**.

[0060] FIG. 3A is a top view of a light-emitting device in accordance with another embodiment of the present disclosure, but without showing the transparent body. FIG. 3B is a cross-sectional view taken along line II-II' of FIG. 3A with the transparent body included. Referring to FIGS. 3A and 3B, a top electrode connector **204** includes a first electrode region **2041** and a second electrode region **2042**. The first electrode region **2041** and the second electrode region **2042** are parallel and alternately arranged along the length direction of the carrier **10** (X) and physically spaced apart from each other. The light-emitting units **11** are arranged along the length direction of the carrier **10** (X), and the first connecting pad **111** and the second connecting pad **113** are at positions corresponding to the first electrode region **2041** and the second electrode region **2042** for physically and electrically connecting therebetween. For example, the first connecting pad **111** of the light-emitting unit **11A** is corresponding to the first electrode region **2041A** and the second connecting pad **113** of

the light-emitting unit **11A** is corresponding to the second electrode region **2042A**; the first connecting pad **111** of the light-emitting unit **11B** is corresponding to the second electrode region **2042A** and the second connecting pad **113** of the light-emitting unit **11B** is corresponding to the first electrode region **2041B**. The second connecting pad **113** of the light-emitting unit **11A** and the first connecting pad **111** of the light-emitting unit **11B** are both disposed on the second electrode region **2042A** for electrically connecting therebetween. Accordingly, the light-emitting units **11** are electrically connected in series with each other on the carrier **10**. In this embodiment, the second connecting pad **113** of the light-emitting units **11A** and the first connecting pad **111** of the light-emitting units **11B** are at the same side of the carrier **10**; the first connecting pad **111** of the light-emitting units **11A** and the second connecting pad **113** of the light-emitting units **11B** are at another side of the carrier **10**. The light-emitting device further includes a transparent body **103** covering the top electrode **20** and the light-emitting units **11**.

[0061] FIG. 4A is a top view of a light-emitting device in accordance with another embodiment of the present disclosure. Referring to FIG. 4A, a top electrode connector **205** includes a plurality of electrode zones **2051** arranged along the length direction of the carrier **10** at a first oblique angle to the length direction. Each of the electrode zones **2051** has a first end **2052** and a second end **2053**. The light-emitting units **11** are arranged along the length direction of the carrier **10** and at a second oblique angle with respect to the electrode zones **2051**. The first oblique angle can be the same or different from the second oblique angle. Each of the light-emitting units **11** has a first connecting pad (not shown) and a second connecting pad (not shown). The first connecting pad and the second connecting pad are respectively at positions corresponding to the first end **2052** of one electrode zone **2051** and the second end **2053** of adjacent one electrode zone **2051** for physically and electrically connecting therebetween. Accordingly, the light-emitting units **11** are electrically connected in series with each other on the carrier **10**. In this embodiment, all the second connecting pads of the light-emitting units **11** are at the same side of the carrier **10** and all the first connecting pads of the light-emitting units **11** are at another side of the carrier **10**.

[0062] FIG. 4B is a top view of a light-emitting device in accordance with another embodiment of the present disclosure. Referring to FIG. 4B, a top electrode connector **206** includes a first electrode bar **2061** and a second electrode bar **2062**. The top electrode pad **201** is merely connected to the first electrode bar **2061** and the top electrode pad **202** is merely connected to the second electrode bar **2062**. Each of the light-emitting units **11** has a first connecting pad (not shown) and a second connecting pad (not shown). The first connecting pad and the second connecting pad are respectively at positions corresponding to the first electrode bar **2061** and second electrode bar **2062** for physically and electrically connecting therebetween. Accordingly, the light-emitting units **11** are electrically connected in parallel with each other on the carrier **10**.

[0063] FIG. 4C is a top view of a light-emitting device in accordance with another embodiment of the present disclosure. Referring to FIG. 4C, the top electrode **20** includes a top electrode pad **201** and a top electrode connector **209** formed on the top surface **101** of the carrier **10**. The top electrode connector **209** includes a first electrode strip **2091** and the second electrode stripe **2092**. The first electrode stripe **2091**

and the second electrode stripe **2092** are physically spaced apart from each other. The first electrode stripe **2091** includes a first region **20911**, a first stripe **20912** electrically connecting to and extending from the first region **20911** along the length direction of the carrier **10** ($-X$), and a plurality of first branches **20913** electrically connecting to and extending from the first stripe **20912** along the width direction of the carrier **10** ($-Y$). The second electrode stripe **2092** includes a second stripe **20921** electrically connecting to and extending from the top electrode pad **201** along the length direction of the carrier **10** ($-X$); and a plurality of second branches **20922** electrically connecting to and extending from the second stripe **20921** along the width direction of the carrier **10** (Y). The first stripe **20912** and the second stripe **20921** are parallel with each other; and the first branches **20913** and the second branches **20922** are alternately and parallelly arranged with each other. Each of the light-emitting units **11** has a first connecting pad (not shown) and a second connecting pad (not shown) which are at positions respectively corresponding to the first branches **20913** and the second branches **20922** for electrically connecting therebetween.

[0064] FIG. 4D illustrates a bottom view of the light-emitting device in FIG. 4C. The bottom electrode **30** includes a bottom electrode pad **301** and a bottom electrode connector **310** formed on the bottom surface **102** of the carrier **10**. The bottom electrode line **310** includes a third electrode stripe **3101** and the fourth electrode stripe **3102**. The third electrode stripe **3101** and the fourth electrode stripe **3102** are physically spaced apart from each other. The third electrode stripe **3101** includes a second region **31011**, a third stripe **31012** electrically connecting to and extending from the second region **31011** along the length direction of the carrier **10** ($-X$), and a plurality of third branches **31013** electrically connecting to and extending from the third stripe **31012** along the width direction of the carrier **10** ($-Y$). The fourth electrode stripe **3102** includes a third region **31021**, a fourth stripe **31022** electrically connecting to and extending from the bottom electrode pad **301** along the length direction of the carrier **10** ($-X$); and a plurality of fourth branches **31023** extending from and electrically connecting to the fourth stripe **31022** along the width direction of the carrier **10** (Y). The third stripe **31012** and the fourth stripe **31022** are parallel with each other; and the third branches **31013** and the fourth branches **31023** are alternately and parallelly arranged with each other. Each of the light-emitting units **11** has a first connecting pad (not shown) and a second connecting pad (not shown) which are at positions respectively corresponding to the fourth branches **31023** and the third branches **31013** for electrically connecting therebetween. Referring to FIGS. 4C and 4D, the first region **20911** is at the position corresponding to the third region **31021** and a hole **211** penetrates through the carrier **10** at the first region **20911** and the third region **31021**; the second region **31011** is at the position corresponding to the top electrode pad **201** and a hole **212** penetrates through the carrier **10** at the second region **31011** and the top electrode pad **201**. The holes **211**, **212** can include a conductive material fully or partly filled therewithin for electrically connecting the opposite surfaces of the carrier **10** with each other. To be more specific, when a positive node and a negative node of the external source are electrically connected to the top electrode pad **201** and the bottom electrode pad **301**, respectively, the top electrode pad **201** is electrically connected to the second region **31011** through the hole **212** for further electrically connecting to the third stripe **31012** and the third branches

31013. In other words, the top electrode pad **201**, the second electrode stripe **2092** and the third electrode stripe **3101** are electrically connected to the positive node of the external source. Likewise, the first region **20911** is electrically connected to the third region **31021** through the hole **211**. Since the third region **31021** is electrically connected to the bottom electrode pad **301**, the bottom electrode pad **301** can be electrically connected to the first stripe **20912** and the first branches **20913**. In other words, the bottom electrode pad **301**, the first electrode stripe **2091** and the fourth electrode stripe **3102** are electrically connected to the negative node of the external source. Accordingly, the light-emitting units **11** on the top surface **101** and the bottom surface **102** are all electrically connected in parallel with each other for emitting light. In this embodiment, with the hole **211**, the first stripe **20912** and the fourth stripe **31022** are electrically connected to each other. In other embodiment, instead of forming the first stripe **20912**, the first regions **20911** and the hole **211**, a plurality of individual holes is formed corresponding to each of the first branch **20913** for electrically connecting the first branch **20913** with the fourth stripe **31022**.

[0065] FIG. 4E illustrates a top view of the light-emitting device in accordance with another embodiment of the present disclosure. The top electrode connector **207** includes a first electrode region **2071**, a second electrode region **2072**, and a third electrode region **2073**. The first electrode region **2071**, the second electrode region **2072**, and the third electrode region **2073** are all rectangle. The long sides of the first electrode region **2071** and the third electrode region **2073** are parallel with the short side (width) of the carrier; the short side of the second electrode region **2072** is parallel with the long side (length) of the carrier. A plurality of the light-emitting units is disposed on the carrier **10** and electrically connected to each other in a bridge configuration by the arrangement of the top electrode connector **207**. The light-emitting units have the first connecting pad and the second connecting pad. It is noted that from the top view of FIG. 4E, the first connecting pad and the second connecting pad cannot be clearly viewed. However, for clarifying this embodiment the first connecting pad and the second connecting pad are labeled in FIG. 4E. To be more specific, the first connecting pad **111C** of the light-emitting unit **11C** is at the first electrode region **2071** for electrically connecting therebetween; the second connecting pad **113C** of the light-emitting unit **11C** is at the second electrode region **2072A** for electrically connecting therebetween; the first connecting pad **111D** of the light-emitting unit **11D** is at the third electrode region **2073** for electrically connecting therebetween; the second connecting pad **113D** of the light-emitting unit **11D** is at the second electrode region **2072A** for electrically connecting therebetween; the first connecting pad **111E** of the light-emitting unit **11E** is at the second electrode region **2072A** for electrically connecting therebetween; the second connecting pad **113E** of the light-emitting unit **11E** is at the second electrode region **2072B** for electrically connecting therebetween; the first connecting pad **111F** of the light-emitting unit **11F** is at the second electrode region **2072B** for electrically connecting therebetween; the second connecting pad **113F** of the light-emitting unit **11F** is at the first electrode region **2071** for electrically connecting therebetween; and the first connecting pad **111G** of the light-emitting unit **11G** is at the second electrode region **2072B** for electrically connecting therebetween; the second connecting pad **113G** of the light-emitting unit **11G** is at the third electrode region **2073** for electrically connecting therebetween.

such that the light-emitting units 11C, 11D, 11E, 11F, 11G are electrically connected to each other in the bridge configuration. Therefore, the light-emitting device can be directly connected to an alternately current (AC) power supply. FIG. 4G is an equivalent circuit of FIG. 4E. In the positive cycle of the alternately current power supply, a positive-cycle current passes through the light-emitting units 11C, 11E, 11G; and in the negative cycle of the alternately current power supply, a negative-cycle current passes through the light-emitting units 11D, 11E, 11F. In this embodiment, only one bridge configuration is described, however, there can be a plurality of bridge configurations formed on the carrier 10 for electrically connecting to each other. In addition, the quantity of the bridge configurations is adjustable depending on a desired voltage (for example, 110V, 120V, 220V or 240V). FIG. 4F illustrates a top view of a light-emitting device in accordance with another embodiment of the present disclosure. The light-emitting device in FIG. 4F is similar with that in FIG. 4E, except that the second electrode region 2072 can include a plurality of sub electrode regions 2072C between the sub electrode regions 2072A, 2072B. A plurality of light-emitting units 11E is arranged on the sub electrode regions 2072A, 2072C, 2072B for electrically connecting in series to each other. In other embodiment, the light-emitting units 11E can be connected to each other in parallel or in series-parallel.

[0066] FIG. 5A illustrates a cross-sectional view of the light-emitting device 200 in accordance with another embodiment of the present disclosure. FIGS. 5B and 5C are a top view and a bottom view without showing the light-emitting units, respectively. Referring to FIGS. 5A~5C, the light-emitting device 200 includes a carrier 10' having a top surface 101' and a bottom surface 102' opposite to the top surface 101', a plurality of light-emitting units 12A, 12B respectively disposed on the top surface 101' and the bottom surface 102', a top electrode 20' on the top surface 101', a bottom electrode 30' formed on the bottom surface 102', and a transparent body 103 covering the top electrode 20', the bottom electrode 30', and the light-emitting units 12A, 12B. As shown in FIG. 5B, the top electrode 20' includes a top electrode pad 201', a plurality of first electrode parts 2011' and a plurality of second electrode parts 2012'. The first electrode part 2011' and the second electrode part 2012' are arranged in a straight line along a length direction of the carrier 10' (X), and physically and alternately spaced apart from each other. The second electrode part 2012' includes a plurality of sub electrode part 20121' spaced apart from each other. In this embodiment, the first electrode part 2011' between two adjacent second electrode parts 2012' has a length smaller than that of the second electrode part 2012'. A distance between two adjacent light-emitting units is smaller than a length of one of the light-emitting units. In this embodiment, the second electrode part 2012' includes three sub electrode parts 20121' which are spaced apart from each other by a distance. Referring to FIGS. 5A and 5B, the light-emitting unit 12A has a first connecting pad (not shown) at a position corresponding to the first electrode part 2011' for electrically connecting therebetween, and the light-emitting unit 12A has a second connecting pad (not shown) at a position corresponding to adjacent one first electrode part 2011' for electrically connecting therebetween, such that the light-emitting unit 12A partially covers the first electrode part 2011' and the adjacent first electrode part 2011', and fully covers the second electrode part 2012'. The second electrode part 2012' contacts the light-emitting unit 12A but is not electrically connected to the

light-emitting unit 12A for dissipating heat from the light-emitting unit 12A to the ambient (air). It is noted that the "contact" means directly contact or indirectly contact. The indirectly contact indicates a conductive material (for example: solder) or a non-conductive material (for example: adhesive) formed between the light-emitting unit 12A and the second electrode part 2012'. In another embodiment, the second electrode part 2012' can also be electrically connected to the light-emitting unit 12A. Referring to FIG. 5C, the bottom electrode 30' includes a bottom electrode pad 301', a plurality of third electrode parts 3011' and a plurality of fourth electrode parts 3012'. The bottom electrode 30' has a pattern similar with that of the top electrode 20'. The third electrode parts 3011' and the fourth electrode parts 3012' are arranged in a straight line along a length direction of the carrier 10' (X), and physically and alternately spaced apart from each other. The fourth electrode part 3012' includes three sub electrode parts 30121' spaced apart from each other. Referring to FIGS. 5A and 5C, the light-emitting unit 12B has a first connecting pad (not shown) at a position corresponding to the third electrode part 3011' for electrically connecting therebetween, and the light-emitting unit 12B has a second connecting pad (not shown) at a position corresponding to adjacent third electrode part 3011' for electrically connecting therebetween. The fourth electrode part 3012' contacts the light-emitting unit 12B but is not electrically connected to the light-emitting unit 12B for dissipating heat from the light-emitting unit 12B to the ambient (air). In another embodiment, the fourth electrode part 3012' can also be electrically connected to the light-emitting unit 12B. It is noted that the first electrode part 2011' and the fourth electrode part 3012' are respectively formed on the top surface 101' and the bottom surface 102' at the position corresponding to each other, and the second electrode part 2012' and the third electrode part 3011' are respectively formed on the top surface 101' and the bottom surface 102' at the position corresponding to each other. Accordingly, the light-emitting units 12A on the top surface 101' and the light-emitting units 12B on the bottom surface 102' are alternately arranged, and the light-emitting units 12A does not fully overlap the light-emitting units 12B. The quantity, the shape, and the length of the sub electrode parts can be varied. The distance between the sub electrode parts can also be varied. Moreover, the quantity, the shape, and the length of the first electrode part 2011', the second electrode part 2012', the third electrode part 3011', the fourth electrode part 3012' can also be varied. In this embodiment, like FIG. 1C, a conductive connecting connector 208 is optionally formed on a side of the carrier 10' for electrically connecting the first electrode part 2011' at the end position with the third electrode part 3011' at the end position. Alternatively, a hole (not shown) is optionally formed to penetrate through the carrier 10' and a conductive material is fully or partly filled with the hole for electrically connecting the first electrode part 2011' with the third electrode part 3011'. Therefore, in operation, when the light-emitting device is connected to the external source, a positive node and a negative node of the external source can be electrically connected to the top electrode pad 201' and the bottom electrode pad 301' such that the light-emitting units 12A, 12B are electrically connected in series to each other for emitting light, that is, the external source is connected to the carrier 10 at the different surfaces (top surface and bottom surface) but at the same side.

[0067] FIG. 5D illustrates a cross-sectional view of the light-emitting device 200' in accordance with another

embodiment of the present disclosure. FIG. 5E illustrates a cross-sectional view of the light-emitting device 200' in accordance with another embodiment of the present disclosure. The light-emitting device 200' has a structure similar with the light-emitting device 200. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting device 200' further includes a dam 35 formed on the top surface 101' and/or the bottom surface 102' to surround the light-emitting units 12A, 12B (as shown in FIG. 5E). Subsequently, a transparent body 103 is formed on the light-emitting units 12A, 12B and the dam 35. In this embodiment, the dam 35 has a height (0.3 mm~0.75 mm) lower than that of the light-emitting units 12A, 12B (0.8 mm~1 mm), thereby a coverage range of the transparent body 103 can be substantially limited by the dam 35. Using the same amount of transparent body 103, compared to the light-emitting device without the dam 35, the transparent body 103 of the light-emitting device with the dam 35 has a smooth top surface for improving a uniformity of the emitting angle of the light-emitting device. The dam 35 is made of a material the same or different from the transparent body 103 and including silicone, epoxy, polyimide, BCB, PFCB, SU8, acrylic resin, PMMA, PET, PC, polyetherimide, fluorocarbon polymer, glass, Al₂O₃, SINR, SOG, Poly(tetrafluoroethylene) or combinations thereof.

[0068] FIGS. 6A and 6B illustrate cross-sectional views of the light-emitting device 300 in accordance with another embodiment of the present disclosure. FIG. 6C illustrates a top view of the light-emitting device 300 without showing an electrical plate 25. The light-emitting device 300 includes a carrier 10" having a top surface 101" and a bottom surface 102" opposite to the top surface 101", a plurality of light-emitting units 13 disposed on the top surface 101", a top electrode 20" on the top surface 101", an electrical plate 25, and a transparent body 103 covering the top electrode 20", the light-emitting units 13 and part of the electrical plate 25. As shown in FIG. 6C, the top electrode 20" includes a first electrode pad 201", a second electrode pad 202", a plurality of first electrode parts 2011", a plurality of second electrode parts 2012", and a third electrode part 2013". The first electrode pad 201" and the second electrode pad 202" are arranged at the same side and the same surface (the top surface). The first electrode part 2011" and the second electrode part 2012" are arranged in a straight line along a length direction of the carrier 10" (X), and physically and alternately spaced apart from each other. The third electrode part 2013" is a straight line and parallel with the first electrode part 2011" and the second electrode part 2012". The top electrode 20" further includes a bended part 2014" which has an end arranged in a straight line with and spaced apart from the second electrode part 2012" while the other end is physically and electrically connected to the third electrode part 2013". The second electrode part 2012" includes a plurality of sub electrode part 20121" spaced apart from each other. In this embodiment, the second electrode part 2012" includes three sub electrode parts 20121" spaced apart from each other by a distance. Referring to FIG. 6A, the light-emitting unit 13 has a first connecting pad (not shown) at a position corresponding to the first electrode part 2011" for electrically connecting therebetween, and the light-emitting unit 13 has a second connecting pad (not shown) at a position corresponding to adjacent first electrode part 2011" for electrically connecting therebetween. The second electrode part 2012" contacts the light-emitting unit 13 but is not electrically connected to the

light-emitting unit 13 for dissipating heat from the light-emitting unit 13 to the ambient (air). In another embodiment, the second electrode part 2012" can also be electrically connected to the light-emitting unit 13. As shown in FIGS. 6A, 6B, 6D, and 6E, the electrical plate 25 includes a board 250 having a top surface 251 and a bottom surface 252 opposite to the top surface 251, a first electrode block 253 formed on the top surface 251 and a second electrode block 254 formed on the bottom surface 252. Referring to FIG. 6D, the first electrode block 253 has a first section 2531 and a second section 2532 connecting to the first section 2531. Referring FIG. 6E, the second electrode block 254 has a third section 2541, and a fourth section 2542 without physically connecting to the third section 2541. The second section 2532 and the fourth section 2542 are respectively formed on the top surface 251 and the bottom surface 252 at the position corresponding to each other. A hole 255 penetrates through the board 250 at the second section 2532 and the fourth section 2542 (as shown in FIG. 6A), and a conductive material can be fully or partly filled within the hole 255 for electrically connecting the second section 2532 with the fourth section 2542. The electrical plate 25 is disposed at a position corresponding to the top electrode 20" of the carrier 10", the fourth section 2542 is physically and electrically connected to the first electrode pad 201", the third section 2541 is physically and electrically connected to the second electrode pad 202", and the fourth section 2542 is electrically connected to the first electrode block 253 through the conductive material filled within the hole 255. In operation, a positive node and a negative node of the external source can be electrically connected to the first section 2531 of the first electrode block 253 and the third section 2541 of the second electrode block 254 such that the light-emitting units 13 can emit light. Specifically, the first electrode block 253 is electrically connected to the fourth section 2542 through the conductive material filled within the hole 255, and the fourth section 2542 is physically and electrically connected to the first electrode pad 201", thus the positive node of the external source can be electrically connected to the first electrode pad 201". Likewise, the negative node of the external source can be electrically connected to the second electrode pad 202" through the third section 2541. Since the positive node and the negative node of the external source can be electrically connected to the first electrode block 253 and the second electrode block 254, respectively, and the first electrode block 253 and the second electrode block 254 are respectively arranged on the top surface 251 and the bottom surface 252 of the electrical plate 25, the external source is connected to the electrical plate 25 at the different surfaces (top surface 251 and bottom surface 252) but at the same side. By virtue of the hole 255, the first section 2531 is connected to the first electrode pad 201" such that the positive node and the negative node of the external source can be electrically connected to the first electrode pad 201" and the second electrode pad 202", respectively, and the first electrode pad 201" and the second electrode pad 202" are formed on the top surface 101" of the carrier 10", therefore, the external source is connected to the carrier 10" at the same surface (top surface 101") and at the same side. In another embodiment, the first electrode block and the second electrode block can be designed to form on the top surface of the electrical plate and a hole is formed at the first electrode block and the second electrode block. With the conductive material filled within the hole, the first electrode block and the second electrode block are electrically connected to the first elec-

trode pad and the second electrode pad, respectively, therefore, the external source is connected to the electrical plate at the same surface (top surface 101) and at the same side.

[0069] It is noted that the sub electrode parts described in FIG. 5A can also be formed in FIGS. 2A, 3A 4A~4E. In other words, there are sub electrode parts formed between the electrode blocks 2031 in FIG. 2A; there are sub electrode parts formed between the first electrode region 2041 and the second electrode region 2042 in FIG. 3A; there are sub electrode parts formed between the electrode zones 2051 in FIG. 4A; there are sub electrode parts formed between the first electrode bar 2061 and the second electrode bar 2062 in FIG. 4B; there are sub electrode parts formed between the first branch 20913 and the second branch 20922 in FIG. 4C; there are sub electrode parts formed between the third branch 31013 and the fourth branch 31023 in FIG. 4D; and there are sub electrode parts formed between the first electrode region 2071, the second electrode region 2072, and the third electrode region 2073. The sub electrode parts contacts the light-emitting unit but is not electrically connected to the light-emitting unit for dissipating heat from the light-emitting unit to the ambient (air). In another embodiment, the sub electrode parts can also be electrically connected to the light-emitting unit.

[0070] FIG. 7A illustrates a cross-sectional view of a light-emitting diode unit 1000 in accordance with one embodiment of the present disclosure, which can be used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A. The light-emitting diode unit 1000 includes a substrate 7000, a first-type semiconductor layer 7001, an active layer 7002, and a second-type semiconductor layer 7003. The first-type semiconductor layer 7001 and the second-type semiconductor layer 7003, for example a cladding layer or a confinement layer, respectively provide electrons and holes such that electrons and holes can be combined in the active layer 7002 to emit light. A first conductive portion 7004 and a second conductive portion 7005 are formed on the second-type semiconductor layer 7003 and the first-type semiconductor layer 7001, respectively. The light-emitting diode unit 1000 is a flip-chip light-emitting diode unit. In another embodiment, the light-emitting diode unit 1000 can further include a wavelength conversion material (not shown) formed on the substrate 7000 to convert light emitted by the active layer 7002. In another embodiment, the light-emitting diode unit 1000 is a thin-film light-emitting diode structure without the substrate 7000. Therefore, a wavelength conversion material (not shown) is directly formed on the first-type semiconductor layer 7001. It is noted that when the light-emitting diode unit 1000 is used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A, the first conductive portion 7004 acts as the previously described first connecting pad or the second connecting pad, and the second conductive portion 7005 acts as the previously described second connecting pad or the first connecting pad. Accordingly, a connection configuration between the first conductive portion 7004, the second conductive portion 7005, the top electrode or/and the bottom electrode is the same as the connection configuration between the first (second) connecting pad, the second (first) connecting pad, the top electrode or/and the bottom electrode. The light-emitting diode unit 1000 further includes a protective layer 7006 made of a transparent insulation material with a high thermal conductivity coefficient (for example, diamond like carbon) and formed to cover the first-type semiconductor layer 7001, the second-type semiconductor layer

7003, and the active layer 7002. Therefore, when the light-emitting diode unit 1000 is used as the light-emitting units 12A, 12B, 13 in FIGS. 5A and 6A, the protective layer 7006 can contact the electrode part 2012', 3012', 2012" for dissipating heat from the light-emitting diode unit 1000 to the ambient (air). Furthermore, the protective layer 7006 can also include a reflective material therein (for example, TiO_2 , SiO_2 , Al_2O_3 , ZrO_2 , ZnS , ZnO , or MgO).

[0071] FIG. 7B illustrates a cross-sectional view of a light-emitting diode unit 1001 in accordance with one embodiment of the present disclosure. The light-emitting diode unit 1001 has a structure similar with the light-emitting diode unit 1000, and can also be used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, and 6A. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting diode unit 1001 further includes a reflective layer 7007 to cover the first-type semiconductor 7001, the second-type semiconductor 7003, and the active layer 7002. Accordingly, the light emitted from the active layer 7002 is able to be reflected toward the substrate 7000. The light-emitting diode unit 1001 can also include a protective layer 7006 formed on the reflective layer 7007 that is made of a transparent insulation material with a high thermal conductivity coefficient (for example, diamond like carbon). When the light-emitting diode unit 1001 is used as the light-emitting units 12A, 12B, 13 in FIGS. 5A and 6A, the protective layer 7006 can contact the electrode part 2012', 3012', 2012" for dissipating heat from the light-emitting diode unit 1001 to the ambient (air). The reflective layer 7007 comprises insulating material, such as SiO_2 , Al_2O_3 , TiO_2 or combinations thereof.

[0072] FIG. 7C illustrates a cross-sectional view of a light-emitting diode unit 1002 in accordance with one embodiment of the present disclosure. The light-emitting diode unit 1002 has a structure similar with the light-emitting diode unit 1000 and can also be used as any one of the light-emitting unit 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, and 6A. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting diode unit 1000 merely includes a light-emitting diode; however, the light-emitting diode unit 1002 includes a plurality of light-emitting diodes commonly formed on a common substrate 7010. The light-emitting diodes are physically spaced apart from each other on the common substrate 7010 and a conductive structure 7015 is provided to electrically connect the light-emitting diodes with each other in series, in parallel or in series-parallel such that the light-emitting diode unit 1002 is capable of operating in a high voltage (an operating voltage (such as 6V, 12V, 24V, 36V, or 45V) is larger than the forward voltage of a light-emitting diode (about 3V)). In this embodiment, the light-emitting diode unit 1002 includes three light-emitting diodes and has an operating voltage of about 9V ($3\text{V} \times 3 = 9\text{V}$). An insulation layer 7016 formed between the light-emitting diodes and the conductive structure 7015 for avoiding an undesired electrical path. In another embodiment, as shown in FIGS. 7A and 7B, the light-emitting diode unit 1002 can include a protective layer (not shown) for covering the first-type semiconductor 7001, the second-type semiconductor 7003, the active layer 7002 and the conductive structure 7015. Alternatively, a reflective layer (not shown) is provided to cover the first-type semiconductor 7001, the second-type semiconductor 7003, and the active layer 7002. Accordingly, the light emitted from the active layer 7002 is able to be reflected toward the sub-

strate 7000. Likewise, when the light-emitting diode unit 1002 is used as the light-emitting unit 12A, 12B, 13 in FIGS. 5A and 6A, the protective layer 7006 can contact the electrode part 2012', 3012', 2012" for dissipating heat from the light-emitting diode unit 1002 to the ambient (air). It is noted that the light-emitting diode unit 1002 merely has one first conductive portion 7004' formed on the second-type semiconductor layer 7003 of one light-emitting diode and one second conductive portion 7005' are formed on the first-type semiconductor layer 7001 of another light-emitting diode. When the light-emitting diode unit 1002 is used as the light-emitting unit 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A, the first conductive portion 7004' acts as the previously described first connecting pad or the second connecting pad, and the second conductive portion 7005' acts as the previously described second connecting pad or the first connecting pad. Accordingly, a connection configuration between the first conductive portion 7004', the second conductive portion 7005', the top electrode or/and the bottom electrode is the same as the connection configuration between the first (second) connecting pad, the second (first) connecting pad, the top electrode or/and the bottom electrode. By connecting the first conductive portion 7004' and the second conductive portion 7005' to the external source, all the light-emitting diodes can emit light. The reflective layer 7007 includes an insulating material, such as SiO_x , Al_2O_3 , TiO_2 or combinations thereof.

[0073] FIG. 7D illustrates a cross-sectional view of a light-emitting diode unit 1003 in accordance with one embodiment of the present disclosure. The light-emitting diode unit 1003 has a structure similar with the light-emitting diode unit 1000 and can also be used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, and 6A. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting diode unit 1003 further includes a first expansion electrode portion 7024 that is physically and electrically connected to the first conductive portion 7004, and that has an area greater than that of the first conductive portion 7004; and a second expansion electrode portion 7025 that is physically and electrically connected to the second conductive portion 7005 and that has an area greater than that of the second conductive portion 7005. Likewise, when the light-emitting diode unit 1003 is used as the any one of light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A, the first expansion electrode portion 7024 acts as the previously described first (second) connecting pad, and the second expansion electrode portion 7025 acts as the previously described second (first) connecting pad. Accordingly, a connection configuration between the first expansion electrode portion 7024, the second expansion electrode portion 7025, the top electrode or/and the bottom electrode is the same as the connection configuration between the first (second) connecting pad, the second (first) connecting pad, the top electrode or/and the bottom electrode. In this embodiment, the first expansion electrode portion 7024 and the second expansion electrode portion 7025 are provided for facilitating a subsequent alignment process.

[0074] FIG. 8A illustrates a cross-sectional view of a light-emitting diode unit 2000 in accordance with one embodiment of the present disclosure, which can be used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A. The light-emitting diode unit 2000 has a structure similar with the light-emitting diode unit 1003.

The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting diode unit 2000 includes a substrate 7000, a first-type semiconductor layer 7001, an active layer 7002 and a second-type semiconductor layer 7003. The first-type semiconductor layer 7001 and the second-type semiconductor layer 7003, for example a cladding layer or a confinement layer, respectively provide electrons and holes such that electrons and holes can be combined in the active layer 7002 to emit light. A first conductive portion 7004 and a second conductive portion 7005 are formed on the second-type semiconductor layer 7003 and the first-type semiconductor layer 7001, respectively. The light-emitting diode unit 2000 is a flip-chip light-emitting diode unit. A space 7008 is formed between the first conductive portion 7004 and the second conductive portion 7005. The first conductive portion 7004 has a contact surface 70041 and the second conductive portion 7005 has a contact surface 70051 substantially coplanar with the contact surface 70041. A transparent substance covers the substrate 7000, the first-type semiconductor layer 7001, the active layer 7002 and the second-type semiconductor layer 7003 and further fully fills into the space 7008 to form a first transparent structure 7026. In another embodiment, the transparent substance does not fully fill the space 7008, and there may have air between the first conductive portion 7004 and the second conductive portion 7005. The first transparent structure 7026 has a surface 70261 substantially coplanar with the contact surface 70041, 70051. Subsequently, the protective layer 7006 formed on a surface of the first transparent structure 7026 to expose the first conductive portion 7004 and the second conductive portion 7005. A first expansion electrode portion 7024 and a second expansion electrode portion 7025 formed on and electrically connected to the first conductive portion 7004 and the second conductive portion 7005, respectively, and further formed on the protective layer 7006. In this embodiment, the first expansion electrode portion 7024 has a sidewall 70241 not coplanar with a sidewall 70061 of the protective layer 7006; the second expansion electrode portion 7025 has a sidewall 70251 not coplanar with another sidewall 70062 of the protective layer 7006. In other embodiment, the sidewall 70241 of the first expansion electrode portion 7024 can be coplanar with a sidewall 70061 of the protective layer 7006; the sidewall 70251 of the second expansion electrode portion 7025 can be coplanar with the another sidewall 70062 of the protective layer 7006. The light-emitting diode unit 2000 further includes a second transparent structure 7027 formed on the first transparent structure 7026. The first transparent structure 7026 includes silicone, epoxy, polyimide (PI), BCB, perfluorocyclobutane (PFCB), SU8, acrylic resin, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), polycarbonate (PC), polyetherimide, fluorocarbon polymer, Al_2O_3 , SINR, or spin-on-glass (SOG). The second transparent structure 7027 can include sapphire, diamond, glass, epoxy, quartz, acryl resin, SiO_x , Al_2O_3 , ZnO, silicone, and/or any combination thereof.

[0075] FIG. 8B illustrates a cross-sectional view of a light-emitting diode unit 2001 in accordance with one embodiment of the present disclosure, which can be used as any one of the light-emitting units 11, 12A, 12B, 13 in FIGS. 1A, 3A, 4A~4F, 5A, 5D, and 6A. The light-emitting diode unit 2001 has a structure similar with the light-emitting diode unit 2000. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The

light-emitting diode unit **2000** merely includes a light-emitting diode; however, the light-emitting diode unit **2001** includes a plurality of light-emitting diodes. In this embodiment, each of the light-emitting diodes has a respective substrate, but in another embodiment, as shown in FIG. 7C, the light-emitting diodes can be commonly formed on a substrate. The light-emitting diodes are electrically connected to each other (in series, in parallel or in series-parallel) through a conductive structure **7015'**. In this embodiment, the conductive structure **7015'** physically and electrically connects the second conductive portion **7005** of one light-emitting diode with the first conductive portion **7004** of adjacent light-emitting diode in series. The transparent structure **7026** covers the light-emitting units. It is noted that when the light-emitting diode unit **2001** is used as any one of the light-emitting units **11**, **12A**, **12B**, **13** in FIGS. 1A, 3A, 4A-4F, 5A, 5D, and 6A, the first expansion electrode portion **7024** acts as the previously described first (second) connecting pad, and the second expansion electrode portion **7025** acts as the previously described second (first) connecting pad. Accordingly, a connection configuration between the first expansion electrode portion **7024**, the second expansion electrode portion **7025**, the top electrode or/and the bottom electrode is the same as the connection configuration between the first (second) connecting pad, the second (first) connecting pad, the top electrode or/and the bottom electrode. By connecting the first expansion electrode portion **7024** and the second expansion electrode portion **7025** to the external source, the light-emitting diodes can emit light. FIG. 8C is a partially cross-sectional view where the light-emitting diode unit **2001** is applied in the light-emitting device of FIG. 5. In this embodiment, only one light-emitting diode unit **2001** is shown to be disposed on the carrier **10**. The light-emitting diode unit **2001** includes four light-emitting diodes **12A1**, **12A2**, **12A3**, **12A4**. The first expansion electrode portion **7024** merely covers partial of the first electrode part **2011'A** and the second expansion electrode portion **7025** and merely cover partial of the first electrode part **2011'B**. The conductive structure **7015'** includes a plurality of sub conductive structures **70151'** which all are not physically connected to the first electrode parts **2011'A**, **2011'B**. The first electrode part **2011'A** is merely physically connected to the light-emitting diodes **12A1**, the second electrode part **2012'** is physically connected to the light-emitting diodes **12A1**, **12A2**, **12A3**, **12A4**, and the first electrode part **2011'B** is merely physically connected to the light-emitting diodes **12A4**. The first transparent structure **7026** merely cover partial of the first electrode part **2011'A**, **2011'B** but cover full of the second electrode part **2012'**. A protective layer **7006** is formed between the conductive structure **7015'** and the first transparent structure **7026**. The conductive structure **7015'** can be physically connected to the electrode part **2012'** (**3012'**) for dissipating heat from the light-emitting diode unit **2001** to the ambient (air). Similarly, the light-emitting diode unit **2001** can also be used as the light-emitting unit **13** in FIG. 6A. Alternatively, when the light-emitting device of the aforesaid embodiments further has sub electrode parts, the light-emitting diode unit **2001** can still be used as any one of the light-emitting unit of these light-emitting devices. In this embodiment, the conductive structure **7015'** includes Au, Al, Cu, or Pt, and is electrically connected to the electrode part **2012'** (**3012'**, **2012''**). The conductive structure **7015'** has a shape or area as the same as that of the electrode part **2012'** (**3012'**, **2012''**). Referring to FIGS. 5A, 8C (6A), the electrode part **2012'** (**3012'**, **2012''**)

has three sub electrode parts **20121'** (**30121'**, **20121''**) and the conductive structure **7015'** has three sub conductive structures **70151'**, that is, the amount of the sub electrode parts is equal to (corresponding to) the sub conductive structures. In other embodiment, the sub conductive structure **70151'** has an area smaller than that of the corresponding sub electrode part.

[0076] FIG. 8D illustrates a cross-sectional view of a light-emitting diode unit **2002** in accordance with one embodiment of the present disclosure, which can be used as any one of the light-emitting units **11**, **12A**, **12B**, **13** in FIGS. 1A, 3A, 4A-4F, 5A, 5D, and 6A. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting diode unit **2001** includes a plurality of light-emitting diodes commonly formed on a common substrate **7000**. The light-emitting diodes are physically spaced apart from each other on the common substrate **7000** and a conductive structure **7015** is provided to electrically connect the light-emitting diodes with each other in series, in parallel or in series-parallel such that the light-emitting diode unit **2002** is capable of operating in a high voltage (an operating voltage (such as 6V, 12V, 24V, 36V, or 45V) larger than the forward voltage of a light-emitting diode (about 3V)). In this embodiment, the light-emitting diode unit **2002** includes four light-emitting diodes and has an operating voltage of about 12V ($3V \times 4 = 12V$). An insulation layer **7016** is formed between the light-emitting diodes and the conductive structure **7015** for avoiding an undesired electrical path. It is noted that the light-emitting diode unit **2002** merely has one first conductive portion **7004** formed on the second-type semiconductor layer **7003** of one light-emitting diode and one second conductive portion **7005** formed on the first-type semiconductor layer **7001** of another light-emitting diode. When the light-emitting diode unit **2002** is used as any one of the light-emitting units **11**, **12A**, **12B**, **13** in FIGS. 1A, 3A, 4A-4F, 5A, 5D, and 6A, the first conductive portion **7004** acts as the previously described first connecting pad or the second connecting pad, and the second conductive portion **7005** acts as the previously described second connecting pad or the first connecting pad. Accordingly, a connection configuration between the first conductive portion **7004**, the second conductive portion **7005**, the top electrode or/and the bottom electrode is the same as the connection configuration between the first (second) connecting pad, the second (first) connecting pad, the top electrode or/and the bottom electrode. By connecting the first conductive portion **7004** and the second conductive portion **7005** to the external source, all the light-emitting diodes can emit light. The first transparent structure **7026** covers all the light-emitting units.

[0077] The aforesaid light-emitting diode units **1000**, **1001**, **1002**, **2000**, **2001**, **2002** having the protective layer or/and the reflective layer can emit light from the light-emitting diode unit toward the substrate which is substantially defined as a five-surface light-emitting diode unit. When the light-emitting units **11**, **13** are merely arranged on the top surface **101**, **101''** of the carrier **10**, **10''** (shown in FIGS. 1A, 3A, 4A-4F, 6A) and includes a transparent body **103** having the wavelength conversion layer dispersed in and formed on the light-emitting units **11**, **13** and portion of the carrier, portion of the light (ex. blue light) emitted from the light-emitting unit is converted to another light (ex. yellow or yellowish-green light) by the wavelength conversion layer. The blue light is mixed with the yellow light (or yellowish-green light) to form a white light. In other embodiment, the light-emitting diode unit includes a wavelength conversion material for converting

the light emitted by the active layer, thus the transparent body **103** does not include the wavelength conversion layer. In this embodiment, the carrier is a transparent or semi-transparent. Portions of the white light can be scattered or reflected by the particles within the wavelength conversion layer (or the wavelength conversion material) to be incident on the transparent or semi-transparent carrier such that the white light not only emits outwardly through a side (top surface) of the transparent carrier on which the light-emitting unit is arranged, but also emits outwardly through a side surface and a bottom surface of the transparent carrier, which indicates the white light can emit outwardly through all surfaces of the carrier (defined as a six-surface light-emitting device). In addition, a diffusing powder (ex. TiO_2) is optionally added into the wavelength conversion layer (or the wavelength conversion material) for increasing the possibility in which the white light progresses downward. In short, in this embodiment, an approximately uniform light distribution (can be seen from a six-surface light-emitting device) can be achieved by using a non-uniform light source (such as five-surface light-emitting diode). Furthermore, the white light at the side of the transparent carrier on which the light-emitting unit is arranged (top surface) has a first average correlated color temperature (CCT); the white light at another side of the transparent carrier (bottom surface) has a second average correlated color temperature less than the first average correlated color temperature. A difference of the first average correlated color temperature and the second average correlated color temperature is not smaller than 50K and not greater than 300K. To be specific, the light-emitting device is disposed on a black base with the top surface facing upward and is electrically connected to the external source. When the light-emitting device emits light, a Chroma Meter (for example, UPRtek, MK350) is used to measure the correlated color temperature to obtain the first average correlated color temperature. Hereinafter, the light-emitting device is provided with its bottom surface facing upward and is electrically connected to the external source. When the light-emitting device emits light, the second average correlated color temperature is measured. Alternatively, a goniophotometer is used to obtain the correlated color temperature of the white light at any point in a space. For example, the light-emitting device is viewed as a central point, and a correlated color temperature spatial distribution of the light emitted from the light-emitting device is shown in FIG. 8E ($0^\circ\sim 360^\circ$). The spatial angle at the top surface of the carrier (with the light-emitting unit) is defined as $0^\circ\sim 180^\circ$ and the spatial angle at the bottom surface of the carrier (without the light-emitting unit) is defined as $180^\circ\sim 360^\circ$. In the range of $0^\circ\sim 180^\circ$, the correlated color temperature at any angle is measured to obtain a first correlated color temperature; in the range of $180^\circ\sim 360^\circ$, the correlated color temperature at any angle is measured to obtain a second correlated color temperature; the first correlated color temperature is greater than the second correlated color temperature and a difference of the first correlated color temperature and the second correlated color temperature is not smaller than 50K and not greater than 300K. As shown in FIG. 8E, within the range of $180^\circ\sim 360^\circ$, the correlated color temperature in the range of $210^\circ\sim 225^\circ$ and $315^\circ\sim 300^\circ$ is higher. In addition, the average correlated color temperature at the top surface ($0^\circ\sim 180^\circ$) is greater than that at the bottom surface ($180^\circ\sim 360^\circ$).

[0078] FIG. 9 illustrates a cross-sectional view of a light-emitting device **400** in accordance with another embodiment

of the present disclosure. The light-emitting device **400** includes a transparent carrier **10''**, a plurality of light-emitting diode units **1004** disposed on the transparent carrier **10''**, a first electrode pad **201''** and a second electrode pad **202''**. The light-emitting diode unit **1004** includes a substrate **140**, a first-type semiconductor layer **141**, an active layer **142** and a second-type semiconductor layer **143**. The first-type semiconductor layer **141** and the second-type semiconductor layer **143**, for example a cladding layer or a confinement layer, respectively provide electrons and holes such that electrons and holes can be combined in the active layer **142** to emit light. The light-emitting diode unit **1004** further includes a first bonding pad **144** formed on the first-type semiconductor layer **141** and a second bonding pad **145** formed on the second-type semiconductor layer **143**. The light-emitting diode unit **1004** includes a reflective structure **146** formed between the substrate **140** and the carrier **10''** for reflecting the light from the light-emitting diode unit **1004** toward the bonding pad, which is substantially defined as a five-surface light-emitting diode unit. A wire **147** connects the first bonding pad **144** of one light-emitting diode unit **1004** with the second bonding pad **145** of adjacent light-emitting diode unit **1004** in series. Moreover, the wire **147** further connects the light-emitting diode unit **1004** with the first electrode pad **201''** and the second electrode pad **202''**. When the light-emitting device **400** is connected to the external source (power supply), a positive node and a negative node of the external source is electrically connected to the first electrode pad **201''** and the second electrode pad **202''**, respectively, such that the light-emitting diode unit **1004** can emit light. Similarly, since a transparent body **103** including a wavelength conversion layer (not shown) can be formed on the light-emitting diode unit **1004** and portions of the transparent carrier **10''**. Portion of the light (ex. blue light) emitted from the light-emitting diode unit **1004** is converted to another light (ex. yellow or yellowish-green light) by the wavelength conversion layer. The blue light is mixed with the yellow light (or yellowish-green light) to form a white light. Portions of the white light can be scattered or reflected by the particles within the wavelength conversion layer to be incident on the transparent carrier such that the white light not only emits outwardly through a side (top surface) of the transparent carrier on which the light-emitting unit is arranged, but also emits outwardly through side surface and a bottom surface of the transparent carrier, which indicates the white light can emit outwardly through all surfaces (defined as a six-surface light-emitting device). In addition, a diffusing powder (ex. TiO_2) is optionally added into the wavelength conversion layer (or the wavelength conversion material) for increasing the possibility in which the white light progresses downward. In short, in this embodiment, an approximately uniform light distribution (can be seen from a six-surface light-emitting device) can be achieved by using a non-uniform light source (such as five-surface light-emitting diode). In other embodiment, a wavelength conversion material is directly formed on the second-type semiconductor layer **143** for converting the light emitted by the active layer, thus the transparent body **103** does not include the wavelength conversion layer. The reflective layer can be a single layer or a multilayer structure made of one or more conductive material or insulating material. The conductive material includes Ag, Al, Ni, Cu, Au, Ti, or combinations thereof. The insulating material includes epoxy, SiO_x , Al_2O_3 , TiO_2 , silicone, resin or combinations thereof.

[0079] It is noted that the carrier 10, 10', or 10'' is transparent or non-transparent to the light emitted by the light-emitting units 11, 12A, 12B, 13 depending on actual requirements. When the carrier is transparent, it can be glass (n (refractive index)=1.4~1.7), SiC, diamond, epoxy, quartz, acryl resin, SiO_x, Al₂O₃, ZnO, silicone or combinations thereof. The glass can include Soda-Lime Glass, Alumino Silicate Glass, or low alkaline glass. When the carrier is non-transparent, it can be circuit board with a core board made of a metal, a thermoplastic material, a thermosetting material or a ceramic material. The metal includes Al or Cu. The thermosetting material includes phenetic, epoxy, bismaleimide triazine, or combinations thereof. The thermoplastic material includes polyimide resin, or polytetrafluorethylene. The ceramic material includes Al₂O₃, AlN, or AlSiC. The top electrode and the bottom electrode can include Au, Al, Cu, Ag or combinations thereof. In another embodiment, the carrier is made of a flexible material such as polyimide. The transparent body 103 is transparent or semi-transparent to the light emitted by the light-emitting units 11, 12A, 12B, 13.

[0080] FIG. 10A illustrates a perspective view of an LED bulb 500 in accordance with an embodiment of the present disclosure. The LED bulb 500 includes a cover 50, a light-emitting device 100, a circuit board 52, a heat sink 54, and an electrical connector 56. The light-emitting device 100 can be replaced by the light-emitting device 200, 300 and the light-emitting device 200, 300 can be applied in the light-emitting bulb 500. The light-emitting device 100 can be viewed as a light filament. When the light-emitting device 100 is mounted on the circuit board 52, the carrier 10 is connected to the circuit board 52 through the same side but different surfaces (see FIG. 1C) thereof. Alternatively, by the electrical plate 25, the external source is connected to the carrier 10 at the same surface but at two opposite sides (see FIGS. 6A~6E). The circuit board 52 is mounted on the heat sink 54 for dissipating heat generated by the light-emitting device 100 away therefrom in a conduction, convection or radiation method. The electrical connector 56 is connected to the heat sink 54, and also connected to the external source. In this embodiment, the light-emitting devices are substantially disposed on the circuit board 52 in a vertical direction (Z) and arranged in a triangular pattern (from the top view). In other embodiment, the light-emitting devices can be arranged in a rectangular pattern, a polygonal pattern or an approximate circle pattern. FIG. 10B illustrates a top view of a circuit board on which the light-emitting devices are mounted in accordance with an embodiment of the present disclosure. The light-emitting devices 100 are arranged in a quadrangular pattern while the top surfaces 101 of each carrier (with the light-emitting units) face outwardly and the bottom surfaces of each carrier (without the light-emitting units) face each other. The LED bulb 501 further includes a light-emitting unit 15 disposed in an interior space defined by the quadrangular pattern and surrounding by the light-emitting devices 100. The light-emitting unit 15 substantially emits light along the Z direction (see FIG. 10A). It is noted that the light-emitting device 100 emits white light and the light-emitting unit 15 emits red light so this configuration can improve the color rendering (CRI≥90) or the Color Quality Scale (CQS≥85). Any one of the light-emitting diode unit 1000, 1001, 1002, 1003, 2000, 2001, 2002 can be used as the light-emitting unit 15.

[0081] FIG. 11A illustrates a perspective view of an LED bulb 502 in accordance with another embodiment of the present disclosure. FIG. 11B illustrates a top view of FIG.

11A. The LED bulb 502 is similar with the LED bulb 501. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. The light-emitting devices 100 are substantially disposed on the circuit board 52 in a vertical direction (Z) and arranged in a quadrangular pattern (from the top view). The light-emitting device 200, 300 can also be applied in this embodiment. In other embodiment, the light-emitting devices can be arranged in a rectangular pattern, a polygonal pattern or an approximate circle pattern. Referring to FIG. 11B, the light-emitting devices 100A, 100B are arranged along the first direction (A) in a straight line with a width direction parallel with the first direction. The light-emitting devices 100C, 100D are arranged along the second direction (B) in a straight line with a width direction parallel with the second direction. The first direction is, but not limited to, substantially perpendicular to the second direction. An angle between the first direction and the second direction can be 30°, 45° or 60°. Each top surface 101 (with the light-emitting unit) of the light-emitting units 100A, 100B has a normal vector perpendicular to the first direction (A) and the two normal vectors point in opposite directions from each other (see arrow). Likewise, each top surface 101 (with the light-emitting unit) of the light-emitting units 100C, 100D has a normal vector perpendicular to the second direction (B) and the two normal vectors point in opposite directions from each other (see the arrow). Furthermore, the emitting direction (see the arrow) of the light-emitting devices 100A, 100B, 100C, 100D can be viewed in a clockwise direction (or anticlockwise). The top surface 101 of the light-emitting device 100A faces the bottom surface 102 of the light-emitting device 100D. FIG. 11C illustrates a top view of a circuit board on which the light-emitting devices are mounted in accordance with an embodiment of the present disclosure. It is different from that of FIG. 11B that a light-emitting unit 15 is further disposed in a space between two adjacent light-emitting devices 100. The light-emitting unit 15 substantially emits light along the Z direction (see FIG. 10A). It is noted that the light-emitting device 100 emits white light and the light-emitting unit 15 emits red light so this configuration can improve the color rendering (CRI≥90) or the Color Quality Scale (CQS≥85).

[0082] FIG. 11D illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure. The LED bulb includes a cover 50, four light-emitting devices 100, a circuit board 52, a heat sink 54, and an electrical connector 56. The detail structure of the light-emitting device 100 can be referred to the aforesaid embodiments. In this embodiment, the carrier of each of the light-emitting devices 100 is made of a flexible material, such as polyimide. The four light-emitting devices 100 are alternately arranged over each other on the circuit board 52. Specifically, the carrier of the bottom light-emitting device 100E is bent to have an arc shape and the top surface of the carrier faces outwardly so the light-emitting units 11 emit outwardly. Similarly, the carrier of each of the first middle light-emitting device 100F, the second middle light-emitting device 100G and the top light-emitting device 100H is bent to have an arc shape and the top surface of the carrier faces outwardly so the light-emitting units 11 emit outwardly[?]. By this configuration, light can emit toward different directions such that an LED bulb with an omnidirectional direction light pattern can be obtained. FIG. 11E illustrates a top view of FIG. 11D without the cover 50. Each of the light-emitting devices 100E~100H extends in different directions (for example, the

bottom light-emitting device **100E** extends from point **1** to point **2**; the top light-emitting device **100H** from point **3** to point **4**).

[0083] FIG. 11F illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure. The LED bulb includes a cover **50**, a post **57**, a light-emitting device **100'**, a circuit board **58**, a heat sink **54**, and an electrical connector **56**. The light-emitting device **100'** includes a flexible carrier **10** and a plurality of light-emitting units **11** on the carrier **10**. In this embodiment, the post **57** is a solid cylinder and has a circuit for electrically connecting to the light-emitting units **11**. Alternatively, the post **57** can be a hollow cylinder. FIG. 11G illustrates the flexible carrier **10** in a non-bending state. The flexible carrier **10** has a first portion **107** and a second portion **108**. In this embodiment, a plurality of light-emitting units **11** is arranged on the first portion **107** in an array and one light-emitting unit **11** is arranged on the second portion **108**. When the flexible carrier **10** is attached to the post **57**, the first portion **107** is bent to wind along the contour of a side surface of the post **57**. Subsequently, the second portion **108** is bent in a direction toward a center of the post **57**. After winding on the post **57**, the second portion **108** is substantially perpendicular to the first portion **107**. By this configuration, the light-emitting units **11** on the first portion **107** emit light toward a side direction and the light-emitting unit **11** on the second portion **108** emits light in an upward direction, thereby an LED bulb with an omnidirectional direction light pattern can be obtained. In addition, an enclosing structure **59** is optionally provided to fully enclose the light-emitting device **100'** and the post **57**. The enclosing structure **59** is transparent and can be made of a material like silicone or epoxy.

[0084] FIG. 11H illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure. The LED bulb of FIG. 11H has a structure similar to that of FIG. 11F. The LED bulb is a type A bulb and includes a cover **50**, a pedestal **581**, a post **57**, a light-emitting device **100''**, a heat sink **54**, and an electrical connector **56**. The light-emitting device **100''** includes a flexible carrier **10** and a plurality of light-emitting units **11** on the carrier **10**. In this embodiment, the post **57** is a hollow cylinder and has a circuit for electrically connecting to the light-emitting units **11**. FIG. 11I illustrates the flexible carrier **10** in a non-bending state. Different from the light-emitting device **100'**, the light-emitting device **100''** includes four second portions **108** each of which has one light-emitting unit **11** is arranged thereon[?]. By this configuration, the light-emitting units **11** on the first portion **107** emit light toward a side direction and the light-emitting units **11** on the second portions **108** emit light in an upward direction, thereby an LED bulb with an omnidirectional direction light pattern can be obtained.

[0085] FIG. 11J illustrates a perspective view of an LED bulb in accordance with one embodiment of the present disclosure. The LED bulb of FIG. 11J has a structure similar to that of FIG. 11H. In this embodiment, the LED bulb does not include a heat sink and the cover **50** is directly connected to the electrical connector **56**. The LED bulb is also the light-emitting bulb with an omnidirectional direction light pattern. It is noted that the aforesaid "omnidirectional direction light pattern" means the light pattern complying with the definition by Energy Star.

[0086] FIG. 12 illustrates a cross-sectional view of a light-emitting tube in accordance with one embodiment of the present disclosure. The light-emitting tube includes a light-

emitting device, a holder **80** and a cover **81**. The aforesaid light-emitting devices can be combined with each other to apply in this light-emitting tube. In another embodiment, the cover **81** can be made of a flexible material such as polyimide (PI). In this embodiment, taking the light-emitting device of FIGS. 4A and 4B for example, the holder **80** includes a first clamp portion **801**, a second clamp portion **802**, and a penetrating hole **803**. The first clamp portion **801** and the second clamp portion **802** are spaced apart from each other and define a space therebetween. The light-emitting device has a part passing through the space and further through the penetrating hole **803** to expose the top electrode pad **201** and the bottom electrode pad **301** for electrically connecting to the external source. With the clamp portions **801**, **802** tightly clamping the light-emitting device, the light-emitting device can be mounted on the holder **80**. In another embodiment, the space between the clamp portions **801**, **802** is larger than a width of the light-emitting device and does not directly contact the light-emitting device so an adhesive substance (not shown) is filled within the space between the clamp portions **801**, **802** for firmly mounting the light-emitting device on the holder. The holder **82** substantially divides the light-emitting device into two sides wherein one is with the light-emitting units **11** and the other is with the top electrode pad **201** and the bottom electrode pad **301**. The cover **81** merely covers the side with light-emitting units **11** but does not cover the side with top electrode pad **201** and the bottom electrode pad **301**. In addition, the cover **81** is spaced apart from the light-emitting device by a shortest distance (d_2) smaller than 2 mm for efficiently dissipating heat from the light-emitting device to ambient (air) through the cover. Alternatively, a filler can be filled between the cover **81** and the light-emitting device and includes a transparent substance, a wavelength conversion layer or a diffusing layer (not shown). The filler directly contact the light-emitting device for conducting heat from the light-emitting device to ambient (air) therethrough. Moreover, because of the filler, the light-emitting device has a better hot/cold ratio. To be more specific, when the light-emitting device is connected to the external source, in an initial state, a cold-state lighting efficiency (light output (lumen)/watt) is measured, hereinafter, in every period of time (ex. 30 ms), the lighting efficiency is measured. When a difference between the adjacent measured light emitting efficiencies is smaller than 0.5%, the latter light efficiency is defined as a hot-state lighting efficiency. The hot/cold ratio is a ratio of the hot-state lighting efficiency to the cold-state lighting efficiency. In this embodiment, when the filler is filled between the light-emitting device and the cover, the hot/cold ratio of the light-emitting device is R_1 , and when the filler is not filled between the light-emitting device and the cover, the hot/cold ratio of the light-emitting device is R_2 , wherein a difference of R_1 and R_2 is larger than 20%. The adhesive substance can be made of a material the same as the transparent substance. The cover **81** includes diamond, glass, epoxy, quartz, acrylic resin, SiO_2 , Al_2O_3 , ZnO or silicone. The transparent substance includes silicone, epoxy, polyimide (PI), BCB, perfluorocyclobutane (PFCB), SU8, acrylic resin, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), polycarbonate (PC), polyetherimide, fluorocarbon polymer, Al_2O_3 , SINR, spin-on-glass (SOG).

[0087] FIGS. 12A~12C illustrate drawings of a method making the light-emitting tube of FIG. 12. Referring to FIG. 12A, a carrier **10** is provided and a plurality of light-emitting units **11** disposed on the top surface **101** and the bottom

surface **102** of the carrier **10** to form a light-emitting device. Referring to FIG. **12B**, a hollow cover **81** is provided and has an open end and a closed end. A transparent substance **811** (which can include a wavelength conversion material and/or a diffusing powder) is filled into the cover **81** from the open end. Referring to FIG. **12C**, a portion of the light-emitting device is embedded into the transparent substance **811** such that the top electrode pad **201** and the bottom electrode pad **301** are exposed from the open end. It is noted that, in the embedded step, gas (air, bubble) may be generated, and a degas step can be performed to remove the gas. Alternatively, the gas is not entirely removed so there is gas existing in the transparent substance **811**. Subsequently, the transparent substance **811** can be solidified by heating or lighting. Optionally, before the solidification, a holder is provided and the light-emitting device passes through the penetrating hole of the holder and is mounted on the holder (as shown in FIG. **12**) such that the side with the light-emitting units is fully sealed by the cover to expose the top electrode pad **201** and the bottom electrode pad **301** for electrically connecting to the external source.

[0088] FIGS. **13A~13D** illustrate drawings of a method making the light-emitting device **600** in accordance with one embodiment of the present disclosure. The light-emitting device **600** is similar with the light-emitting device **100**. The devices, elements or steps with similar or the same symbols represent those with the same or similar functions. Referring to FIG. **13A** and FIG. **13B**, a carrier **10** is provided and the top electrode **20**, the bottom electrode **30** and a temporary electrode **220** are formed on the carrier **10** using printing. A hole **221** is formed and a conductive material is fully or partly filled with the hole **221** for electrically connecting the top electrode **20** with the bottom electrode **30**. The temporary electrode **220** can be electrically connected to the top electrode **20**. Furthermore, a scribe line **222** is formed on the bottom surface **102** of the carrier at a position corresponding to the temporary electrode **220**. The light-emitting units **11** are mounted on the top electrode **20** (or/and the bottom electrode, as shown in FIG. **5A**) of the carrier **10** by surface mounted technology or wiring bonding. Referring to FIGS. **13C** and **13D**, a first transparent layer **1032** is formed to cover the light-emitting units **11** along its contour; a wavelength conversion layer **1033** is formed to cover the first transparent layer **1032** along its contour; and a second transparent layer **1034** is formed to cover the wavelength conversion layer **1033** without having the same contour as the wavelength conversion layer **1033**. During test, the positive node and the negative node of the external source are connected to the top electrode **20** and the temporary electrode **220**, respectively, so the light-emitting units **11** emit light. Hereinafter, the temporary electrode **220** and portions of the carrier **10** are removed along the scribe line **222**. In this embodiment, the temporary electrode **220** is removed using breaking, laser dicing, or diamond dicing that such methods can cause a side **121** of the carrier **10** with a rough, unsmooth, or irregular surface. On the contrary, another side **122** of the carrier has a smooth surface. Therefore, the side **121** and another side **122** have different roughness. The wavelength conversion layer can be a single layer or a multilayer structure. FIG. **13E** is a cross-sectional view of FIG. **13D** (along X direction). The light-emitting unit **11** has a height (H_2), a maximum distance between the second transparent layer **1034** and the carrier is H_1 ; $H_2 \geq 0.5H_1$. It is noted that when the light-emitting unit **11** includes the first transparent structure (the light-emitting diode units **2000**, **2001** or **2002** in FIG. **8A**,

FIG. **8B** to FIG. **8D**), and the first transparent structure **7026** is made of a material the same as the first transparent layer **1032**, an interface formed therebetween is vague under the electrical microscopy or the interface does not exist between the first transparent structure **7026** and the first transparent layer **1032**.

[0089] While the aforesaid light-emitting device is applied in an alternating current (AC) power supply or a direct current (DC) power supply with a root mean square voltage of 120V, the light-emitting device can be designed to have an operating voltage of $140V \pm 10\%$; while the light-emitting device is applied in an alternating current (AC) power supply or a direct current (DC) power supply with a root mean square voltage of 100V, the light-emitting device can be designed to have an operating voltage of $115V \pm 10\%$; while the light-emitting device is supplied with an alternating current (AC) power supply or a direct current (DC) power supply with a root mean square voltage of 220V, the light-emitting device can be designed to have an operating voltage of $280V \pm 10\%$. The alternating current (AC) power supply is rectified to a direct current (DC) power supply. Furthermore, the light-emitting device can also be supplied with a direct current power supply with a substantially constant voltage (ex. battery) and the light-emitting device can be designed to have an operating voltage smaller than 15V. In addition, a plurality of light-emitting devices is disposed in a support and the light-emitting devices are electrically connected to each other in series, in parallel, in series-parallel for increasing the applications. Moreover, the aforesaid light-emitting device or light tube can also be applied in U-shape lamp, spiral lamp, bulb, and candle lamp.

[0090] It is noted that, besides the light-emitting diode unit (FIGS. **7A~7D**, **8A~8B** and **8D**) described in the present disclosure can be used as any one of the light-emitting units. However, the conventional package structure (for example, 3014 or 5630 package) can be used as any one of the light-emitting units.

[0091] It is noted that the foregoing description has been directed to the specific embodiments of this invention. It will be apparent to those having ordinary skill in the art that other alternatives and modifications can be made to the devices in accordance with the present disclosure without departing from the scope or spirit of the disclosure. In view of the foregoing, it is intended that the present disclosure covers modifications and variations of this disclosure provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. An light-emitting device, comprising:

- a first electrode part;
- a second electrode part;
- a third electrode part, spaced apart from the first electrode part and the second electrode part; and
- a light-emitting unit partially covering the first electrode part and the second electrode part and fully covering the second electrode part, the light-emitting unit having a conductive structure contacting the second electrode part.

2. The light-emitting device of claim 1, wherein the conductive structure does not contact the first electrode part and the third electrode part.

3. The light-emitting device of claim 1, wherein the light-emitting unit further comprises a first light-emitting diode

and a second light-emitting diode, and the first light-emitting unit is connected to the second light-emitting diode through the conductive structure.

4. The light-emitting device of claim 1, wherein the light-emitting unit further comprises a first transparent structure covering the first light-emitting diodes and the second light-emitting diode.

5. The light-emitting device of claim 1, wherein the light-emitting unit further comprises a connecting pad partially covering the first electrode part.

6. The light-emitting device of claim 1, wherein the light-emitting unit further comprises a first light-emitting diode and a second light-emitting diode, and wherein the first electrode part merely contacts the first light-emitting diode the second part contacts the first light-emitting diode and the second light-emitting diode, and the third electrode part merely contacts the second light-emitting diode.

7. The light-emitting device of claim 1, wherein the light-emitting unit further comprises a first transparent structure that partially covers the first electrode part and the third electrode part, and fully covers the second electrode part.

8. The light-emitting device of claim 7, further comprising a protective layer formed between the conductive structure and the first transparent structure.

9. The light-emitting device of claim 1, further comprising a carrier and a transparent layer, wherein the light-emitting unit is formed on the carrier and the transparent layer covers the light-emitting unit; and a longest distance between the transparent layer and the carrier is H_1 ; and the light-emitting unit has a height (H_2); $H_2 \geq 0.5H_1$.

10. The light-emitting device of claim 1, further comprising a transparent layer fully covering the light-emitting unit and the second electrode part and partially covering the first electrode part.

11. A light-emitting tube comprising (filament tube):

a cover having a first end;

a light-emitting device, enclosed by the cover, having two electrode pads exposed from the first end of the cover; and

a transparent substance formed between the light-emitting device and the cover.

12. The light-emitting tube of claim 11, wherein the cover comprises diamond, glass, epoxy, quartz, acrylic resin, SiO_x , Al_2O_3 , ZnO or silicone.

13. The light-emitting tube of claim 11, wherein the transparent substance includes silicone, epoxy, polyimide (PI), BCB, perfluorocyclobutane (PFCB), SU8, acrylic resin, polymethyl methacrylate (PMMA), polyethylene terephthalate (PET), polycarbonate (PC), polyetherimide, fluorocarbon polymer, Al_2O_3 , SINR, spin-on-glass (SOG).

14. The light-emitting tube of claim 11, wherein the light-emitting device further comprises:

a carrier having a top surface and a bottom surface opposite to the top surface; and

a light-emitting unit arranged on the top surface.

15. The light-emitting tube of claim 14, wherein the two electrode pads are formed on the top surface.

16. The light-emitting tube of claim 14, wherein the two electrode pads are formed on the same side of the carrier.

17. The light-emitting tube of claim 11, wherein the transparent substance comprises a wavelength conversion material.

* * * * *