US 20150261727A1

(19) United States

(12) Patent Application Publication

Davis

(10) Pub. No.: US 2015/0261727 A1

(43) Pub. Date: Sep. 17, 2015

(54) **SYSTEM, METHOD, AND COMPUTER PROGRAM PRODUCT FOR PROCESSING A MARKUP DOCUMENT**

(71) Applicant: **e-Numerate Solutions, Inc.**, Great Falls, VA (US)

(72) Inventor: **Russell T Davis**, Bethesda, MD (US)

(21) Appl. No.: **14/724,792**

(22) Filed: **May 28, 2015**

Related U.S. Application Data

(60) Continuation-in-part of application No. 12/222,751, filed on Aug. 15, 2008, which is a division of application No. 09/573,778, filed on May 18, 2000, now Pat. No. 7,421,648.

(60) Provisional application No. 60/183,152, filed on Feb. 17, 2000, provisional application No. 60/135,525, filed on May 21, 1999.

Publication Classification

(51) **Int. Cl.**

G06F 17/21 (2006.01)

G06F 17/22 (2006.01)

(52) **U.S. Cl.**

CPC *G06F 17/218* (2013.01); *G06F 17/2252* (2013.01)

(57) **ABSTRACT**

A system, method, and computer program product are provided for identifying a first markup document including first numerical values and first tags reflecting first characteristics of the first numerical values associated with a first unit of measure, and a second markup document including second numerical values and second tags reflecting second characteristics of the second numerical values associated with a second unit of measure. The first characteristics of the first numerical values associated with the first unit of measure are different from the second characteristics of the second numerical values associated with the second unit of measure. At least a portion of the numerical values of at least one of the first markup document or the second markup document are automatically transformed, so that the at least some of the first numerical values of the first markup document and at least some of the second numerical values of the second markup document have a common unit of measure. Further, at least a part of the first markup document and at least a part of the second markup document are processed, resulting in a single markup document, for display.




Views
108
Chart
Spreadsheet
Treeview
Report
Documentation
Export (many file formats)
RDML
Data Viewer
100
RDML Data Document
102
RMML Macro Document
104
RDSL Style Document
106

FIG. 1


203
Web Server
232
Disk Array
234
Database Server
236
Database Storage
238
Network 214
Main Memory 204
Data Viewer 100
RDML Document 102
RMML Macro Document 104
RDSL Style Sheet 106
RDML Document Formatter 216
RDML Document Server 218
RDML Document Editor 220
RDSL Style Sheet Editor 222
RDML/XML Search Engine 224
RDML Plug-In Applications 225
Views 108
CPU 202
Secondary Storage 206
Image Database 226
Existing Database 230
RMML Macro Software Development Kit 228
Display 210
Input 212
200
201

FIG. 2


Main components
222
220
RDML Document Editor
RDSL Style Sheet Editor
230
Existing Database (SQL Server, Oracle, etc.)
216
RDML Document Formatter
106
102
RDML Document
RDSL Style Sheet
226
218
RDML Image Database
RDML Document Server
228
104
100
RMML Macro Software Development Kit
RMML Macro Document
RDML Data Viewer
224
225
RDML/XML Search Engine
Various RDML Plug-In Applications

FIG. 3


RDML Data Formatter
File
View
Tools
Help
Open File
Fill All Defaults
Fill Column Defaults
Copy Down
Select an Att/Element:
LI Title
LI Category
Y Axis Title
Level
Format
Relation to Parent
LI Footnotes
LI Description
Precision
Unit
Magnitude
Modifier
Measure
Scale
Select an Option:
#,##0;(#,##0)
[#,##0;(#,##0)]
[0.0]
[;(0.00)]
[0.0]
[%,(0.00%)]
[0.0]
[%,(0%)]
Format Template for how this line items numbers will appear in treeview, reports, spreadsheets. Also y-axis label formatting. Required
Mark up the Table:
li ID
li title
format
y axis title
2.0 Environmental Protection Ag... #,##0; (#,##0) $ in Thousands
4.0 Pollution control and abate... #,##0; (#,##0) $ in Thousands
6.0 Discretionary #,##0; (#,##0) $ in Thousands
8.0 Nongrant #,##0; (#,##0) $ in Thousands
10.0 Science and technology #,##0; (#,##0) $ in Thousands
12.0 Pollution control and abate... #,##0; (#,##0) $ in Thousands
14.0 Grant #,##0; (#,##0) $ in Thousands
16.0 Office of the Inspector Gener... #,##0; (#,##0) $ in Thousands
18.0 Nongrant #,##0; (#,##0) $ in Thousands
20.0 Payment to the hazardous s... #,##0; (#,##0) $ in Thousands
22.0 Revolving fund for certificatio... #,##0; (#,##0) $ in Thousands
24.0 Mandatory #,##0; (#,##0) $ in Thousands
26.0 Hazardous substance supe... #,##0; (#,##0) $ in Thousands
28.0 Nongrant #,##0; (#,##0) $ in Thousands
30.0 Leaking underground stora... #,##0; (#,##0) $ in Thousands
32.0 Oil spill response #,##0; (#,##0) $ in Thousands
34.0 Inspector General (trust fun... #,##0; (#,##0) $ in Thousands
36.0 Licensing fees for pesticide... #,##0; (#,##0) $ in Thousands
38.0 Discretionary #,##0; (#,##0) $ in Thousands
40.0 Recoveries, Hazardous sub... #,##0; (#,##0) $ in Thousands
42.0 Miscellaneous contributed f... #,##0; (#,##0) $ in Thousands
Databases
LineItemSet
LineItems
Middle Status
Left Status
402
404
406
408
216

FIG. 4

FIG. 5


RDML Data Formatter
File View Tools Help
Open File
Fill All Defaults
Fill Column Defaults
Copy Down
Documentation URL:
jdbc:odbc:JFormat1
506
Documentation Table:
rdmidoc_header
508
LI Data URL:
jdbc:odbc:JFormat1
510
Click to Update
RDML Documents to work on...
doc title
status
RDMLDoc ID
Sallie Mae – Income Statement Done rdml_sima_is1
Dept. of Energy Done rdml_omb_energy_1
Peak Mortgage Company Done rdml_mf_1
Des Moines Water & Sewer Done rdml_desmoines_1
University Business Office – Cash Flow Done rdml_sima_bursar1
Sallie Mae – Asset Management Stratification Done rdml_sima_asset1
Dept. of Commerce Done rdml_omb_commerce_1
Executive Office of the President Done rdml_omb_eop_1
General Services Administration Done rdml_omb_gsa_1
Dept. of Housing and Urban Development Done rdml_omb_hud_1
Judicial Branch Done rdml_omb_judicial_1
Dept. of Labor Done rdml_omb_labor_1
National Aeronautic and Space Administrati... Done rdml_omb_nasa_1
Governmental Receipts Done rdml_omb_receipts_1
Social Security Administration Done rdml_omb_ssa_1
Dept. of Energy Done rdml_omb_transportation_1
Dept. of Veteran's Administration Done rdml_omb_va_1
504
Databases
LineItemSet
LineItems
502
Middle Status
Left Status
216


START
User submits data request to web server and RDML data server via the viewer
602
RDML server queries the databases
604
The databases return the results to the server
606
The server creates an RDML document
608
The server returns the RDML document to the web server and on to the viewer
610
END

FIG. 6


Chart Data
715
Chart Manager
714
Chart
716
TreeView
720
Tree View Manager
718
Spreadsheet
724
Spreadsheet Manager
722
Footnote
728
Footnote Manager
726
Macro Panel
732
Macro Manager
730
Graphical User Interface
734
HTML Browser
736
XSL Processor
752
Style Manager
750
RDSL Document (Style Sheet)
106
Primary Data Store (DOM objects)
712
Custom Math Processor
754
RDML XPointer Reader
756
RDML Processor
708
X-Value Transformer
710
Macro Adapter
760
RDML Document Type Definition ("DTD")
702
RDML Document
102
RDML Reader
704
XML Parser
706
Macro Interface
758
RMML Document
104
RMML Document
104
RMML Document
104
etc.

FIG. 7A


Text Document
Object / Process
Output Application ("View")
Object Storage
Graphical User Interface ("GUI")
Third-Party Software Component
Input/ Output Process
Program Flow

FIG. 7B


START
802
Document reader finds and receives document
804
XML parser parses text
806
RDML processor processes the text into an object
808
X-value transformer 810 type checks and manipulates x-values
810
Primary data store 812 stores active objects of the same type for display
812
Views display active objects stored in primary data store
END

FIG. 8


rdmldoc
902
rdmldoc_header
904
line_item_set
906
data_source
908
formatting_source
910
rdmldoc_source
912
license_terms
914
contact_info
918
contact_info
918
contact_info
918
contact_info
918
linkset
916
link
922
linkset
916
data_x
924
li_class_set
926
li_class
930
linkset
916
line_item
928
link
922
data_x
938
data_y
932
linkset
920
link
922
note_set
934
note
936
702

FIG. 9


Start
Locate Documents
1002
Select Document to be Transformed
1004
Access Line Item
1006
Determine Desired Transformation
1008
Access Unit, Magnitude, Modifier, Scale, Measure, and Adjustment Attributes
1010
Determine Conversion Factors for Each Attribute
1012
Multiply the Conversion Factors to Manipulate the numbers of the Document or Line Item
1014
Display Transformed Document on Line Item
1016
Another Line Item to be Transformed?
1018
Yes
No
Another Document to be Transformed?
1020
Yes
No
End

FIG. 10


START
1102
X-value transformer receives a new document
1104
Determines type of active documents in primary data store
1106
New object is same type as active documents
Yes
1108
Add to currently active documents
No
1110
Notify user
1112
User chooses to reject object?
Yes
1114
Reject the document
No
1116
User chooses to erase current active?
Yes
1118
Erase current active documents
1120
Store new document
No
1122
Insert new document as standby object
END

FIG. 11

FIG. 12A


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
XY Maximum
Open Close Copy Screen Add Remove Erase Type Back Forward Stop Home
URL of Data Document File:/C:\Rdml/RdmlBrowser\files\xy_test1.rdm
Global Warming
As of 10/1/1999
Humidity
30.00
20.00
10.00
0.00
38 39 40 41 42 43 44 45 46 47
Temperature
XY Test1
Line Item
Table Name XY Test1
As of 10/1/1999
As of 10/1/1999
Clarity Index
Units Point 0 Point 1 Point 2 Links Sum Average Row
Humidity 25.40 26.60 26.64 2 276.41 27.64 27
Pounds per sq inch 235.40 226.60 236.64 2 2,486.41 248.64 28
Index 235.40 226.60 236.64 2 2,486.41 248.64 29
HTML Browser Chart/Tree Footnotes Spreadsheet
0:3
XY Plot
Done
1202
720
1204
1206

FIG. 12B


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
XY Maximum
URL of Data Document File:C:/Rdml/RdmlBrowser/files/test4_xy.rdm
Global Warming
As of 10/1/1999
300.00
200.00
100.00
0.00
40
50
60
70
80
90
100
XY Test1
Line Item
Table Name: XY Test1
As of 10/1/1999
As of 10/1/1999
Clarity Index
Units Point 0 Point 1 Point 2 Links Sum Average Row
Humidity 25.40 26.60 26.64 2 276.41 27.64 1
Pounds per sq inch 235.40 226.60 236.64 2 2,486.41 248.64 2
Index 235.40 226.60 236.64 2 2,486.41 248.64 3
HTML Browser
Chart Tree
Spreadsheet
Footnotes
1:3
XY Plot
Done
1204
1206
1202
720

FIG. 12C


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
XY Maximum
URL of Data Document File:C:/Rdml/RdmlBrowser/files/test4_xy.rdm
Clarity Index
Global Warming
300.00
200.00
100.00
0.00
40
50
60
70
80
90
100
XY Test1
Line Item
Table Name: XY Test1
As of 10/1/1999
As of 10/1/1999
Clarity Index
Units Point 0 Point 1 Point 2 Links Sum Average Row
Humidity 25.40 26.60 26.64 2 276.41 27.64 1
Pounds per sq inch 235.40 226.60 236.64 2 2,486.41 248.64 2
Index 235.40 226.60 236.64 2 2,486.41 248.64 3
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
2:3
XYPlot
Done
1202
1204
1206
720



FIG. 13

FIG. 14A


RDML Data Viewer
File Edit View Chart Favorites Tools Help
Start Period: 1940
URL of Data Document: http://localhost/rdml_omb_hist1_table1_1.rdm
Total Surplus or Deficit (-)
US Gov't Budget
$ in Millions
90,000
0
(90,000)
(180,000)
(270,000)
(360,000)
1940
1950
1960
1970
1980
1990
2000
Line Item
Units
1996
1997
1998
Sum
Row
1 Tables Open:
Table #1: Table 1.1 – Summary of Receipts, Outlays
Summary of Receipts, Outlays
Summary of Receipts, Outlays
Total Receipts
Total Outlays
Total Surplus or Deficit (-)
On-Budget
Off-Budget
$ in Millions 1,579,292 1,601,235 (21,943) 0 0 0 1,657,858 1,667,815 (9,957) 0 0 0 1,742,736 1,733,217 9,519 0 0 0 33,364,998 36,855,937 (3,490,942) 0 0 0
TreeView
Footnotes
DataSheet
Macros
HTML Browser
1402
1404
1420
1206
1418
1410
1416
1414
1406
716
720
1422

FIG. 14B


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
URL of Data Document File:C:/Rdml/RdmlBrowser/files/dml_eu_mexico1.rdm
TS Start Period 1980
Total foreign debt
Total debt/exports of G and S
Mexico
Y1 Axis: Total foreign debt; Y2 Axis: Total debt/exports of G and S
EIU - Mexico Statistics
Line Item
Units
1993
1994
1995
Links
Sum
Average
Row
short term $ in millions 36,257 39,323 37,300 1 509,265 22,142 3
interest arrears $ in millions 0 0 0 1 78 3 3
interest arrears owed to official creditors $ in millions 0 0 0 1 0 0 3
interest arrears owed to private creditors $ in millions 0 0 0 1 77 3 3
Ratios (%) 0.00 0.00 0.00 1 0.00 0.00 4
total debt/exports of G and S Ratio 195.12 179.43 174.39 1 4,532.83 197.08 4
total debt/GDP Ratio 32.63 33.20 58.17 1 1,023.43 44.50 4
international reserves/total debt Ratio 19.08 4.48 10.10 1 263.30 11.45 4
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
TimeSeries
175,184:318
Done
1406
1408
1402
1404
1206
1410
1212
716
720

FIG. 14C


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
URL of Data Document File:C:/Rdml/RdmBrowser/files/rdml_eiu_mexico1.rdm
Start Period 1980 TS
Total foreign debt
Total debt/exports of G and S
Mexico
Y1 Axis: Total foreign debt; Y2 Axis: Total debt/exports of G and S
EIU - Mexico Statistics
Line Item
short term
interest arrears
interest arrears owed to official creditors
interest arrears owed to private creditors
Ratios (%)
total debt/exports of G and S
total debt/GDP
international re
Series Description
View Links
Units 1993 1994 1995 Links Sum Average Row
$ in millions 36,257 39,323 37,300 1 509,265 22,142 3
$ in millions 0 0 0 1 78 3 3
$ in millions 0 0 0 1 0 0 3
$ in millions 0 0 0 1 77 3 3
$ in millions 0.00 0.00 0.00 1 0.00 0.00 4
Ratio 195.12 179.43 174.39 1 4,532.83 197.08 4
Ratio 32.63 33.20 58.17 1 1,023.43 44.50 4
Ratio 19.08 4.48 10.10 1 263.30 11.45 4
HTML Browser Chart/Tree Footnotes Spreadsheet TimeSeries
Done
175,184:318
1406
1408
1402
1410
1412
1424
1206
716
720

FIG. 14D


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
URL of Data Document
File:C:/Rdml/RdmBrowser/files/dml_eu_mexico1.rdm
Total foreign debt
Total debt/exports of G and S
Start Period 1980
TS
Total debt/exports of G and S
File Edit Help Ctrl + H
LINE ITEM:
Legend: Total debt/exports of G and S
Title: Mexico
Units: Ratio
Magnitude: 0
Level: 3
PARENT DOCUMENT:
Document ID: rdml_eiu_mexico1.rdm
STATISTICAL SUMMARY:
# of Points: 23
# of Nulls: 1
Sum: 4,533 Ratio
Average: 197 Ratio
Maximum: 340 Ratio
Minimum: 91 Ratio
FOOTNOTES:
Source: Derived from IMF, International Financial S
OK
Cancel
EIU - Mexico Statistics
Line Item
short term
interest arrears
interest arrears owed to official creditors
interest arrears owed to private creditors
Ratios (%)
total debt/exports of G and S
total debt/GDP
international reserves/total debt
Sum Average Row
509,265 22,142
1,023.43 44.50
263.30 11.45
4,532.83 197.08
Y1 Axis: Total debt/exports of G and S
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
TimeSeries
Done
175,184:318
Start
JBuilder
RDML Data Viewer
ScreenUpdates12_13.doc
5:30 PM
1402
1426
1206
1406
716
720

FIG. 14E


Numerator Lite 1.0 – Composite REIT Inc.
File Edit View Chart Favorites Tools Window Help
Open Save Export Print Screen Back Forward Stop Home X-Axis Y-Axis Clear Type
URL Address file://localhost/D:/may/files/rdml_mf_1.roll
Composite REIT Inc. – Valuation Strategies
$ in Thousands
30,000
22,500
15,000
7,500
0
CMBS
DESwap
Hold
REIT
Refi
SellLoan
Syndicate
Resolution Strategy
Dundalk Liberty Cornwall
Cross Creek Apts
Bristol House Apts
Oak Grove Apts
Line Item
Units
OMBS
Syndicate
Refi
Links
Sum
Avg
Composite REIT Inc. Co.
Aberdeen
Annapolis
Baltimore
DUNDALK LIBERTY CORNWALL
CROSS CREEK APTS
BRISTOL HOUSE APTS
OAK GROVE APTS
DUTCH VILLAGE APTS
Shipyard Apartments
Park Crescent Apartments
HAMLET WEST APARTMENTS
LONDON and HAMPSHIRE HOUSE APTS
WELLINGTON GATE APTS
$ In Thousands
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
Macro
RDL Docs Open =1
Category
Done.
720
1450

FIG. 14F


1432
1430
Numerator Lite 1.0
File Edit View Chart Favorites Tools Window Help
Open Save Export Print Screen Back Forward Stop Home X-Axis Y-Axis Clear Type
URL Address: file://localhost/D:/NumeratorLite/files/rdml_omb_energy_1a.rdm
Outlays – Dept. of Energy
URLs for Currently Selected Elements
Original Data Sources:
Links for Line Item: Original Data Sources
RDML Formatted Source Table text here
Department Web Site text here
$ in Thousands
20,000,000
15,000,000
10,000,000
5,000,000
0
Fiscal Year
Dept. of Energy
Line Item
Units
2001
2002
2003
Links
Sum
Avg
Department of Energy
Department of Energy
Atomic Energy Defense Activities
Energy Programs
Power Marketing Administration
Departmental Administration
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
RDL Docs Open =1
Time Series


START
1502
Select Line Item
1504
Get the ID of the Line Item
1506
Undo any old macros
1508
Delete the last Series
B

FIG. 15A


B
1512
Remove existing data
1514
Get RDMLDoc from PDS
1516
Get RDMLLineItem
1518
Normalize X data
1520
Fill X Axis with data
1522
Fill Y Axis with data
1524
Mark Which Y Axis This Series is on
1526
Y2 Axis?
Yes
1528
Add Axis
No
1530
Set number formats for axis labels
1532
Set the number precision
1534
Update the footnotes
1536
Run any macros that are applied
C

FIG. 15B


C
1538
Set Y1 Title
1540
Set Y2 Title
1542
Update the Series Styles
1544
Update the Chart Title
1546
Update the Legend
1548
Update the X Axis
1550
Update the Number Precision
1552
Update the Y Axis
1554
Update the Chart Type
1556
Update the Footer
1558
Set the maximum X value
1560
Repaint the Graphical Chart
END

FIG. 15C



	A	B	C	D	E	F
1		1962	1963	1964	1965	1966
2	Military Personnel	16330694	16255836	17421684	17912624	20009255
3	Operation and Maintenance	11593929	11873616	11932040	12348718	14709815
4	Procurement	14532033	16631555	15350826	11839339	14338537
5	Research, Development, Test, and Evaluation	6318612	6375564	7021448	6236216	6259083
6	Military Construction	1347129	1143518	1026292	1006908	1333564
7						

FIG. 16

FIG. 17


RDML Data Viewer
File Edit View Chart Favorites Tools Help
Start Period: 1962
URL of Data Document: File:/M:\RdmlBrowser\files\rdml_omb_education_1.rdm
Outlays – Dept. of Education
Office on Postsecondary Education
Office of Elementary and Secondary Education
Office of Special Education and Rehabilitative Services
Office of Vocational and Adult Education
Department Management
$ in Thousands
44,088,000
36,740,000
29,392,000
22,044,000
14,696,000
7,348,000
0
1970
1980
1990
2000
Note: Series #1 (Office of Potsecondary Education):
Note: Series #2 (Office of Elementary and Secondary Education):
Note: Series #3 (Office of Special Education and Rehabilitative Services):
Note: Series #4 (Office of Vocational and Adult Education):
Note: Series #5 (Departmental Management):
TreeView
Footnotes
DataSheet
Macros
HTML Browser
Done.
1402
716
728
1702


RMML Document Type Definition
1800
1810
macro_source
918
contact_info
1804
macro_header
1812
license_terms
918
contact_info
1802
macro_doc
916
linkset
1816
macro_description
922
link
1814
documentation
1818
help_page
1806
macro_code
1820
code
1822
instructions
1824
gui
926
1826
qualifiers
li_class_set
930
1828
error_handling
li_class
1830
testing
1808
macro_references
1802
macro_doc
1834
data_docs

FIG. 18


104
RMML Document
1910
RMML Doc Reader
1908
RMML_Lib
1906
RMML Doc
1912
Macro Factory
758
Macro
760
Macro Adapter
1926
Macro Library
1918
Macro_TSL
1920
Macro_CT
1922
Macro_XY
1924
Macro_OVER

FIG. 19A


Parameter Panel
1960
Description Panel
1958
New MacroPanel
732
J Panel
1842
Macro GUI
1948
Macro GUI Default
1950
M Variable
1946
Macro Assumption Group
1944
Macro Libary
1926
Macro GUI_Vector
1856
Macro GUI_ Radio
1854
Macro GUI_List
1852

FIG. 19B


Macro Manager
730
Chart Data
715
Macro Library
1926
Macro GUI
1948
Evaluator
1984
Function Resolver
1988
Variable Resolver
1986
Tokenizer
1994
Formula Node
1992
Formula
1990
Formula Exception
1996
RMML Interpreter
1980

FIG. 19C

FIG. 20A


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
TS Start Period 1962
URL of Data Document File:/C:\Rdml\RdmlBrowser\files/rdml_omb_justice_1.rdm
Department of Justice
Outlays – Dept. of Justice
$ in Thousands
20,000,000
15,000,000
10,000,000
5,000,000
0
1970
1980
1990
2000
Parameters:
Select a Destination Currency
US - Dollars
Britian - Pounds
Germany - Deutschmarks
Canada - Dollars
France - Francs
Italy - Lira
Mexico - Pesos
Macro:
Change Currency
Description:
Converts US dollars to another currency.
U.S. Economic Statistics
Applicable
Invert value (negative/positive/absolute)
Average
Sum
Minimum/Maximum
Sort
Multiply
Change Currency
Test Variables
Moving Average
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
Macros
TimeSeries
: 129
MacroScreenShots.doc - ...
RDML Data Viewer
Done
Start
11:14AM
1960
1958
2002
1926
732

FIG. 20B


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen Back Forward Stop Home Add Remove Erase Type
TS Start Period 1962
URL of Data Document File:/C:\Rdml\RdmlBrowser\files/rdml_omb_justice_1.rdm
Department of Justice
Outlays – Dept. of Justice
$ in Thousands
20,000,000
15,000,000
10,000,000
5,000,000
0
1970
1980
1990
2000
Parameters:
Select a Parameter:
Full average
Disregard nulls
Disregard zeros
[No Change]
Original Values
Macro:
Average
Description:
Produces the average of a data series, according to the parameters
U.S. Economic Statistics
Applicable
Invert value (negative/positive/absolute)
Average
Sum
Minimum/Maximum
Sort
Multiply
Change Currency
Test Variables
Moving Average
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
Macros
TimeSeries
RDML Data Viewer
MacroScreenShots.doc - ...
Done
Start
11:13 AM
1960
1958
2002
1926
732

FIG. 20C


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen
Back Forward Stop Home
Add Remove Erase Type
TS Start Period 1962
URL of Data Document File:/C:\Rdml\RdmlBrowser\files/rdml_omb_justice_1.rdm
Department of Justice
Outlays – Dept. of Justice
$ in Thousands
20,000,000
15,000,000
10,000,000
5,000,000
0
1970
1980
1990
2000
Macro: Adjust for US Inflation
Parameters:
Description: Converts line items to inflation-adjusted values (GDP Deflater, 1997 = 100)
Deflators
5.24
5.19
5.12
5.06
4.98
4.84
4.69
4.50
U.S. Economic Statistics
Macros
Applicable
Invert value (negative/positive/absolute)
Average
Sum
Minimum/Maximum
Sort
Multiply
Change Currency
Test Variables
Moving Average
Adjust for US Inflation
Library
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
Macros
TimeSeries
RDML Data Viewer
Done
Start
MacroScreenShots.doc - ...
11:25AM
1960
1958
2002
1926
732

FIG. 20D


RDML Data Viewer
File Edit View Chart Favorites Tools Window Help
Open Close Copy Screen
Back Forward Stop Home
Add Remove Erase Type
TS Start Period
1962
URL of Data Document File:/C:\Rdml\RdmlBrowser\files/rdml_omb_justice_1.rdm
Department of Justice
Outlays – Dept. of Justice
$ in Thousands
200,000,000
150,000,000
100,000,000
50,000,000
0
1970
1980
1990
2000
U.S. Economic Statistics
Applicable
Invert value (negative/positive/absolute)
Average
Sum
Minimum/Maximum
Sort
Multiply
Change Currency
Test Variables
Moving Average
Parameters:
Macro:
Multiply
Description
Multiplies each number is each series by the parameter.
Modify a parameter
Multiply by 10
HTML Browser
Chart/Tree
Footnotes
Spreadsheet
Macros
TimeSeries
RDML Data Viewer
Done
: 129
Start
MacroScreenShots.doc - ...
11:18 AM
1960
1958
2002
1926
732


START
2102
User puts data in table form
2104
Open and initialize dialog box
2106
User fills in default values for attributes
2108
User clicks "OK" to create attribute columns
2110
Open and initialize dialog box
2112
Create each element, nesting as necessary
2114
Save to file
END

FIG. 21

FIG. 22A

Microsoft Excel – b_84.xls

File Edit View Insert Format Tools Data Window Help

A1 = li_legend

2202

	A	B	C	D	E	F	G	H	I	J	K	L	M
1	li_legend	1927	1932	1934	1936	1938	1940	1942	1944	1946	1948	1950	1952
2	Total general revenues by source	7271	7267	7678	8395	9228	9609	10418	10908	12356	17250	20911	25181
3	Property taxes	4730	4487	4076	4093	4440	4430	4537	4604	4986	6126	7349	8652
4	Sales and gross receipts taxes	470	752	1008	1484	1794	1982	2351	2289	2986	4442	5154	6357
5	Individual income taxes	70	74	80	153	218	224	276	342	422	543	788	998
6	Corporation net income taxes	92	79	49	113	165	156	272	451	447	592	593	846
7	Revenue from Federal Govern-me	116	232	1016	948	800	945	858	954	855	1861	2486	2566
8	All other[3]	1793	1643	1449	1604	1811	1872	2123	2269	2661	3685	4541	5763
9	Total general expenditures by fur	7210	7765	7181	7644	8757	9229	9190	8863	11028	17684	22787	26098
10	Education	2235	2311	1831	2177	2491	2638	2586	2793	3356	5379	7177	8318
11	Highways	1809	1741	1509	1425	1650	1573	1490	1200	1672	3036	3803	4650
12	Public welfare	151	444	889	827	1069	1156	1225	1133	1409	2099	2940	2788
13	All other[4]	3015	3269	2952	3215	3547	3862	3889	3737	4591	7170	8867	10342

Staging Sheet 1 Sheet 2

Ready NUM

Start b_84.xls Microsoft Visual Basic ScreenShot_Wizard.doc - 11:42AM

2204

FIG. 22B


Microsoft Excel – b_84.xls
File Edit View Insert Format Tools Data Window Help
A13
All others
(Place cursor on top left cell of data block, fill out this dialog, then click "OK")
Default Values
Chart Title
History of Government Budgets
Y Axis Title
$ Millions
Format
#,##0;(#,##0)
Footnote
Source: www.whitehouse.gov
Unit
Select One: (Default is blank)
Currency
$US
Pounds UK
Yen Japanese
Length
Magnitude
Millions
OK
Cancel
Help
2206

FIG. 22C

Microsoft Excel – b_84.xls

File Edit View Insert Format Tools Data Window Help

R1 = li_legend

	A	B	C	D	E	F	G	H	I	J	
1	li_ID	li_legend	li_title	li_cat	y_axis_title	level	format	relation	li_notes	li_desc	li_p
2	1	Total general revenues by source	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
3	2	Property taxes	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
4	3	Sales and gross receipts taxes	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
5	4	Individual income taxes	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
6	5	Corporation net income taxes	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
7	6	Revenue from Federal Govern-ment	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
8	7	All other[3]	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
9	8	Total general expenditures by function	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
10	9	Education	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
11	10	Highways	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
12	11	Public welfare	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		
13	12	All other[4]	History of Government Budgets		$ in Millions	1	#,##0;(#,##0)	Parent	Source: www.whitehous		

Staging Sheet 1 Sheet 2

Ready NUM

Start b_84.xls Microsoft Visual Basic-Ta... ScreenShots_Wizard.doc - ... 11:45AM

2208 2208 2208 2208 2208 2208 2208 2208

FIG. 22D


2210
2212
Microsoft Excel - b_84.xls
File Edit View Insert Format Tools Data Window Help
Create RDML Document
Input
Data Block Range
Sheet2!A1:BW13Sheet2!$BK
Default RDML File
D:\default1.rdm
Use non-file defaults
Browse
Output
Directory
D:\
Filename
out.rdm
Browse
Commonly Changed Elements
Document Title
Government Receipts and Expenditures
Line Item Type
TimeSeries
X Axis Title
Year
OK
Cancel
Help
Edit
Sum=65175772
Staging
Sheet 1
Sheet 2
Ready
Start
Microsoft Visual Basic-Ta...
ScreenShots_Wizard.doc - ...
11:46AM

SYSTEM, METHOD, AND COMPUTER PROGRAM PRODUCT FOR PROCESSING A MARKUP DOCUMENT

RELATED APPLICATIONS

[0001] This application is a continuation-in-part (for the purposes of providing a glossary in accordance with the Glossary Pilot Program) of application Ser. No. 12/222,751, filed Aug. 15, 2008 which, in turn, is a divisional of application Ser. No. 09/573,778, filed May 18, 2000, now U.S. Pat. No 7,421,648, which, in turn, claims priority to Provisional U.S. Patent Application No. 60/135,525, filed on May 21, 1999, and Provisional U.S. Patent Application No. 60/183,152, filed on Feb. 17, 2000, which are all incorporated herein by reference.

[0002] The following identified U.S. patent applications are also relied upon and are incorporated by reference in this application.

[0003] U.S. patent application Ser. No. 09/573,780 (now U.S. Pat. No. 7,650,355) entitled "Reusable Macro Markup Language," filed on May 18, 2000.

[0004] U.S. patent application Ser. No. 09/573,419 (now U.S. Pat. No. 7,249,328), entitled "Tree View for Reusable Data Markup Language," filed on May 18, 2000.

[0005] U.S. patent application Ser. No. 09/573,413 (now U.S. Pat. No. 6,920,608), entitled "Chart View for Reusable Data Markup Language," filed on May 18, 2000.

FIELD OF THE INVENTION

[0006] The present invention relates generally to data processing systems and, more particularly, to a computer markup language for use in a data browser and manipulator.

SUMMARY

[0007] A system, method, and computer program product are provided for identifying a first markup document including first numerical values and first tags reflecting first characteristics of the first numerical values associated with a first unit of measure, and a second markup document including second numerical values and second tags reflecting second characteristics of the second numerical values associated with a second unit of measure. The first characteristics of the first numerical values associated with the first unit of measure are different from the second characteristics of the second numerical values associated with the second unit of measure. At least a portion of the numerical values of at least one of the first markup document or the second markup document are automatically transformed, so that the at least some of the first numerical values of the first markup document and at least some of the second numerical values of the second markup document have a common unit of measure. Further, at least a part of the first markup document and at least a part of the second markup document are processed, resulting in a single markup document, for display.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. **1** depicts a high level diagram of a Reusable Data Markup Language (RDML) data viewer, its inputs and outputs in accordance with methods and systems consistent with the present invention;

[0009] FIG. **2** depicts a data processing system suitable for use with methods and systems consistent with the present invention;

[0010] FIG. **3** depicts a diagram of the interrelation of various RDML software and hardware components shown in FIG. **2**;

[0011] FIG. **4** depicts the use of an RDML formatter shown on FIGS. **2** and **3** to add markup tags to data;

[0012] FIG. **5** depicts a screen shot of a database/document tab and management screen of the RDML formatter depicted in FIGS. **2** and **3**;

[0013] FIG. **6** depicts a flowchart of the steps performed when accessing the RDML document server depicted in FIGS. **2** and **3**;

[0014] FIG. **7**A depicts internal architecture of the RDML data viewer depicted in FIGS. **2** and **3**;

[0015] FIG. **7**B depicts a legend of the meaning of the symbols depicted in FIG. **7**A;

[0016] FIG. **8** depicts a flowchart of the steps performed by the RDML data viewer in a method for downloading, processing and displaying an RDML document in accordance with methods and systems consistent with the present invention;

[0017] FIG. **9** illustrates elements of an RDML Document Type Definition in accordance with methods and systems consistent with the present invention;

[0018] FIG. **10** depicts a flowchart of steps used to automatically manipulate an RDML document for display using line item attributes in accordance with methods and systems consistent with the present invention;

[0019] FIG. **11** depicts a flowchart of the steps performed by the x-value transformer depicted in FIG. **7**A to store a new document in the primary data store;

[0020] FIGS. **12**A-**12**C depicts X-Y plots and tree views in accordance with methods and systems consistent with the present invention;

[0021] FIG. **13** depicts a primary data store of the RDML data viewer as shown in FIG. **7**A;

[0022] FIGS. **14**A-**14**F depict a chart view and tree view of the RDML data viewer as depicted in FIG. **7**A in accordance with methods and systems consistent with the present invention;

[0023] FIGS. **15**A-**15**C depict flowcharts of the steps performed by a graphical user interface, chart manager and chart data object for adding a line item to a chart view upon selection of the line item in a tree view in accordance with methods and systems consistent with the present invention;

[0024] FIG. **16** depicts a spreadsheet view and a chart view of the data viewer in accordance with methods and systems consistent with the present invention; and

[0025] FIG. **17** depicts a footnote view of the data viewer and a chart view in accordance with methods and systems consistent with the present invention;

[0026] FIG. **18** illustrates elements of a Reusable Macro Markup Language (RMML) Document Type Definition in accordance with the present invention;

[0027] FIGS. **19**A-**19**C depict RMML document handling, an RMML graphical interface, and an RMML macro interpreter, respectively, in accordance with the present invention;

[0028] FIGS. **20**A-**20**D illustrates screen shots of RMML macro panels in accordance with the present invention.

[0029] FIG. **21** shows a flowchart illustrating steps used in a method for tagging information from spreadsheets in accordance with the present invention; and

[0030] FIGS. **22**A-**22**D depicts exemplary screen shots of the tagging of spreadsheet information tagging to create a document in accordance with the present invention.

DETAILED DESCRIPTION

Glossary

[0031] HTML=HyperText Markup Language

[0032] Measurement=characteristics necessary to describe the measurement aspects of the domain the number is taken from

[0033] Structure=structuring of the data in within a table

[0034] Tagging=adding metadata

[0035] RDML=Reusable Data Markup Language

[0036] XML=Extensible Markup Language

[0037] Methods and systems in accordance with the present invention provide a markup language, referred to as Reusable Data Markup Language ("RDML"), that permits the browsing and manipulation of numbers and provide a related data viewer that acts as a combination Web browser and spreadsheet/analytic application that may automatically read numbers from multiple online sources and manipulate them without human intervention. Using the markup language, users may browse online sources using numerical-based queries, and the data viewer may automatically combine and manipulate multiple documents on a single display.

[0038] In accordance with an implementation consistent with the present invention, a method in a data processing system is provided that receives a first markup document and a second markup document, both the first markup document and the second markup document containing numerical values and tags reflecting characteristics of the numerical values. The method automatically combines the first markup document and the second markup document into a single data set and displays the single data set.

[0039] In accordance with another implementation, a method in a data processing system is provided that receives a document containing numerical values, and receives indications of characteristics of the numerical values, the characteristics including a unit and a magnitude. Further, it adds the received indications into the document as tags associated with the numerical values to create a markup document.

[0040] In accordance with yet another implementation, a method in a data processing system is provided that receives a markup document having a set of numerical values and tags indicating characteristics of the numerical values and determines a transformation for the set of numerical values to reflect new characteristics. The method then accesses a plurality of the tags of the set of numerical values, the plurality of the tags indicating magnitude, scale, modifier, units, measure, adjustment and aggregation. Furthermore, the method determines conversion factors for the magnitude, scale, modifier, units, measure, adjustment and aggregation tags to accomplish the transformation to the new characteristics and multiplies the set of numerical values by the determined conversion factors to transform the set of numerical values to reflect the new characteristics.

[0041] Methods and systems in accordance with the present invention provide a chart view that automatically manipulates and graphically displays numerical data. The manipulation and display is based on attributes associated with the numerical data describing characteristics of the numerical data. The chart view facilitates the simultaneous display of different series of numerical values of different types on a single chart and automatically displays appropriate descriptive textual components (e.g., axis labels, axis titles, chart titles, number precision, legends, footnotes, axis scales, etc.) The chart view allows single click transformations of series of numerical values and provides automatic formatting of descriptive textual components in response.

[0042] In accordance with an implementation of the present invention, a method in a data processing system having a display showing a chart is provided that receives a series of numerical values with tags indicating characteristics of the numerical values and displays the numerical values on the chart. Further, the method automatically determines a title for the numerical values based at least one of the tags and displays the determined title on the chart.

[0043] In accordance with another implementation of the present invention, a method in a data processing system having a display showing a chart is provided that receives a first series of numerical values having tags indicating characteristics of the numerical values and displays the first series of numerical values on the chart, the first series of numerical values corresponding to a first axis on the chart. The method further receives a second series to be added to the chart, the second series of numerical values having tags indicating characteristics of the second series of numerical values and automatically generates a second axis on the chart. Finally, the method displays the second series of numerical values on the chart corresponding to the second axis while the first series is displayed on the chart.

[0044] In accordance with yet another implementation of the present invention, a method in a data processing system having a display showing a chart is provided that receives an instruction to display a series of numerical values on the chart on the display, the numerical values having tags indicating characteristics of the numerical values, and displays the series of numerical values on the chart in response to the received instruction. The method then automatically formats the chart based on at least one of the tags in response to the received instruction.

[0045] In accordance with another implementation of the present invention, a data processing system is provided comprising a memory storing a charting application configured to manipulate and display numerical data, the memory having a selected series of numerical values having a tag indicating text information associated with the numerical values. The data processing system further comprises a display showing a chart having a legend that displays the text information associated with the selected series of numerical values. The legend word-wraps and scrolls the text information associated with the series of numerical data when the text information does not fit on the legend on the chart. The system further comprises a processor for running the charting application.

[0046] Methods and systems in accordance with the present invention provide a tree view that automatically manipulates and graphically displays numerical data. The tree view facilitates the simultaneous display of different series of numerical values of different types on a single display and automatically displays descriptive textual components. The tree view allows single click transformations of series of numerical values and provides automatic formatting of descriptive textual components in response. It further visually displays the relationship between series of numerical data for a user while supplying the user with hyperlinks associated with a given series of numerical data.

[0047] In accordance with an implementation of the present invention, a method in a data processing system is provided that receives a first and a second series of numerical values, and determines the relationship between the first and second

series of numerical values. The method then displays an icon depicting the relationship between the first and second series of numerical values based on the determined relationship.

[0048] In accordance with another implementation of the present invention, a method in a data processing system is provided that receives a series of numerical values and a link associated with the series of numerical values, the link having a list of associated hyperlinks. The method displays the series of numerical values and the associated link, and receives an instruction to activate the link. Further, the method displays the list of hyperlinks associated with the link in response to the received instruction.

[0049] In accordance with yet another implementation of the present invention, a method in a data processing system having a display showing a chart is provided that receives a series of numerical values having associated metadata documentation. The method further receives an instruction to select the series of numbers and displays the series of numerical values on the chart while displaying the metadata documentation associated with the series of numerical values.

[0050] In accordance with another implementation of the present invention, a data processing system is provided that comprises a memory having a program for manipulating numerical values, and storing a first series of numerical values and a second series of numerical values. The data processing system further comprises a display that displays the first and second series of numerical values and a relationship icon depicting the relationship between the first series of numerical values and the second series of numerical values. Finally, the data processing system further comprises a processor for running the program.

[0051] Methods and systems in accordance with the present invention provide a markup language, referred to as Reusable Macro Markup Language ("RMML"), for producing and utilizing macros which are reusable numerical analysis routines which can be written quickly, cheaply, and in a form usable by a broad range of data documents in RDML, the platform upon which the macros are run.

[0052] RMML allows reusable spreadsheet type macros to be posted as web documents, to be, searched by search engines, to be combined into more complex programs, and to be reused with many data documents. RMML brings to spreadsheet manipulation routines the economic and productivity benefits of (1) standardization, (2) interchangeable parts, (3) specialization and assembly-line techniques in creation, and (4) economies of scale in creation and deployment. In addition, RMML brings to spreadsheet macros and numerical programming, some of the benefits of the World Wide Web: (1) widespread accessibility on demand, (2) ability to search for documents (in this case, search for capabilities and behavior of routines instead of text or data), and (3) the ability to hyperlink documents (including the ability of macros to call each other remotely).

[0053] In accordance with an implementation of the present invention, a data processing system method is provided that receives a macro defined to perform an operation on a series of numerical values and receives a series of numerical values having tags indicating characteristics of the numerical values. The method then performs an operation defined by the macro on the series of numerical values using the indicated characteristics.

[0054] In accordance with another implementation of the present invention, a data processing system method is provided that receives a macro defining an operation on a set of numerical values and receives a vector or matrix of numerical values. The method then performs an operation defined by the macro using the vector or matrix as a variable in the operation.

[0055] In accordance with yet another implementation of the present invention, a data processing system is provided that includes a memory containing a numerical analysis program having a macro defined to perform an operation on a series of numerical values, and a series of numerical values having tags indicating characteristics of the numerical values. It further comprises a processor for running the program such that the program performs an operation defined by the macro on the series of numerical values using the indicated characteristics, and a display for displaying results of the operation.

[0056] Because of the length of the detailed description, the following table of contents is provided.

Topic	Section
Reusable Data Markup Language Overview	I
Reusable Macro Markup Language Overview	I.A
System Hardware Components	II
System Overview	III
System Details	IV
Internal Data Viewer Architecture	IV.A
Document Type Definition	IV.A.1
Reader, Parser and Processor	IV.A.2
X-value Transformer and Line Item Set Types	IV.A.3
Primary Data Store	IV.A.4
Chart View	IV.A.5
Tree View	IV.A.6
Spreadsheet View	IV.A.7
Footnote View	IV.A.8
Tagging Wizard	IV.A.9
Aspects of RDML Documents	IV.A.IO
Graphical User Interface and HTML browser	IV.B
Reusable Macro Markup Language	IV.C
RMML Macro Package	IV.C1

I. RDML Overview

[0057] Methods and systems consistent with the present invention provide a markup language, referred to as Reusable Data Markup Language ("RDML"), and a data viewer referred to as the RDML data viewer that is used to retrieve, manipulate and view documents in the RDML format. Generally, RDML permits the browsing and manipulation of numbers, and allows the viewer to act as a combination Web browser and spreadsheet/analytic application that may automatically read numbers from multiple online sources, understand their meaning, and manipulate them without human intervention. The RDML data viewer may use the Internet to obtain requested sets of numbers like HTML does for text. Using RDML, it is possible to form a search on the Internet that is a true query of numbers. One such request is the creation of a list of quarterly revenues from 1996 to 1997 pertaining to companies with sales growth greater than 10 percent and no taxable income. After receiving any requested sets of numerical data, the data viewer may automatically transform and combine them even if they are in different formats (i.e., one in thousands of U.S. dollars and another in hundreds of French francs) on a single graphical display without requiring the user to make manual adjustments. The user may then make single-click adjustments to the display (e.g., adjust for inflation, currencies, time periods, number precision, etc.) to see different aspects of the received infor-

mation. RDML generally facilitates numerical browsing by associating numbers with attributes describing the meaning of the numbers.

[0058] Although the preferred embodiment of RDML is a markup language that is a fully compliant implementation of XML version 1.0, other implementations are possible. XML is described in detail in "XML Bible," Elliotte Rusty Harold, IDG Books Worldwide, 1999, which is incorporated herein by reference. The RDML data viewer is a data browser, data manipulator, data viewer (in the form of charts, spreadsheets, etc.) and general user interface for data documents. It greatly extends the capabilities provided by current spreadsheet and database management programs. In addition to extended capabilities, it lowers costs to businesses by permitting efficient reuse of data, functions, and report formats.

[0059] The RDML data viewer works with RDML-formatted data documents, which are files that may be stored locally, over a network, including the Internet, or in any combination of sources. The structure of the RDML data files allows the RDML data viewer to act as a combination browser and analytic program, such as a spreadsheet, which can automatically read, interpret and manipulate numbers in its integrated analytic program. The RDML data viewer also provides a "macro" development and management scheme which allows users to create custom routines for the manipulation, transformation and display of RDML-formatted data. Macros and related aspects are described in greater detail below.

[0060] FIG. **1** depicts a high-level diagram of an RDML data viewer **100**, its inputs and its outputs in accordance with methods and systems consistent with the present invention. Generally, data viewer **100** may be software that resides in the memory of a computer and accepts several types of input **102**, **104** and **106**, one of which is the RDML data document **102**. The RDML data document **102** may be an ASCII text document formatted with RDML tags which are compliant with XML version 1.0. In one implementation consistent with the present invention, the tags of an RDML data document **102** are advantageously structured to include documentation of the data and arrange data in "line items," a collection of data values that is similar to a "record" or "row" in a relational database (discussed below). In RDML, the line item is generally the basic unit of calculation, as opposed to a single data value or cell as is typical with most conventional databases or spreadsheets. RDML documents **102** contain sets of line items, such sets being analogous to "tables" in relational databases, and documentation ("metadata") regarding the "line item sets." The RDML data document **102** is read by the RDML data viewer **100** which stores the data internally, making it available to a number of "views" **108**, which present the data in different ways (charts, tables, etc.) to a user (not shown). The views **108** are also referred to as programs or applications, as they can be standalone software programs that receive their data from the RDML data viewer **100**.

[0061] Analysis routines can be developed for data and placed in their own documents referred to as Reusable Macro Markup Language ("RMML") Macro Documents **104** which are another input to the data viewer **100** and are optional. These routines are reusable; they can be applied to virtually any data document meeting the requirements set forth in the RMML document **104**. For example, an RMML document **104** may contain routines for converting RDML data to different currencies, and any data denominated in currency can use the RMML currency conversion macro. The preferred embodiment of RMML is also a fully compliant implementation of XML version 1.0, although other embodiments are possible.

[0062] Similarly, Reusable Data Style Language ("RDSL") style sheets **106**, another optional input to the data viewer **100**, can be applied to data documents to create specially-formatted output reports. A RDSL is a fully compliant implementation of Extensible Style Language ("XSL") which is described in detail in "XML Bible," Elliotte Rusty Harold, IDG Books Worldwide, 1999. These RDSL documents **106** are XSL-compliant style sheets which essentially act as report writers for RDML data documents **102**. A typical use would be for data documents containing corporate financial statements. A single RDML data document **102** may contain a set of financial statements, but several different style sheets could be applied: one to show the data in annual columns, one to show it in a quarterly breakdown, one to show it in European format, and so forth. The RDML data viewer **100** automatically combines data documents **102** and style documents **106** to create reports.

[0063] RDML dramatically reduces the expense, time, and complexity of data manipulation by addressing the aforementioned problems of documentation of data, non-standardization of analytic routines, and low conceptual-level calculations of data. RDML addresses the problem of the separation of data and its documentation by encapsulating data and its documentation together in machine-readable form that can be used interactively. This differs from the approach of conventional relational databases in which data is kept in the computer and the documentation typically kept in a three-ring binder or other printed document. The separation of data and its documentation often ensures the need for high-priced database programmers every time the data must be accessed, used or transferred. Documentation in RDML also differs from that of spreadsheets, which tend to be personal in that the documentation is in the head and personal notes of the creator. Iii one implementation consistent with the present invention, RDML encapsulates machine-readable documentation with the data. The data and its documentation (metadata) are used together by the data viewer **100** to interpret what the numbers mean, how they are to be used, and how they are to be displayed. The small up-front investment in refining the raw data pays off in the lessened need for human labor to access and reuse the data in the future. RDML incorporates several important types of metadata: sources, contacts, license requirements, expirations and update information, data types, data classes, handling instructions (e.g., what to do with nulls, missing values, etc.), units and measurements, and other information needed to produce the various presentations.

[0064] Use of RDML addresses the problem of non-standardization by defining standards for both data characteristics and analytic routine interfaces. Standardization leads to component reuse, automation of production, and more rapid development of product enhancements. While the computer industry has developed standards for file formats and function-level interfaces, it has not developed general data format or content-analysis standards. For example, once data is input to an application (whether spreadsheet, database or other), the user may want to manipulate the data and see basic statistics for the different line items (sums, averages, % changes, variances, and so forth), adjustments for standard changes (adjustments for inflation, conformance to industry indexes, % of stock market averages, etc.), or standard ratios (debt/equity, price/earnings, etc.) Because there is neither a standard gen-

eral data format, nor a standard analytic routine interface, users currently create each of these manipulation routines from primitive coding. In spreadsheets, they must input formulas and conversion factors number by number, and in databases, they must write SQL queries or other programming routines to manipulate the data.

[0065] RDML provides both the data standard and the function interface for manipulation routines. This means that a routine can be written to apply to any line item that meets the conditions it imposes, and these routines are reusable. Currently, conventional spreadsheet macros (one analogue to RDML macros **104**) are typically only used in the spreadsheet for which they were designed. The macros cannot typically be used in another spreadsheet where the numbers may be in different cells or in different units. RDML macros **104** are not dependent on cell position, or human intervention to conform data: they can be directly used by others for other data sets. If a user writes a routine which, for instance, calculates and graphs a moving average of a time series, it can be used by any time series in any RDML document **102**.

[0066] While solving documentation and standardization problems, use of RDML also addresses the problem of calculations occurring at too low a conceptual level by creating data "objects" at the line item and document levels, whereas conventional spreadsheets operate only at the cell (single number) level. For instance, calculations that may be common to a set of data, i.e., a line item, may operate more efficiently because they can be applied once, as opposed to being applied individually to many different single numbers or cells. Furthermore, analytic routines (macros) can be combined, applied successively, or used by inheritance to create new routines. The line item orientation dramatically reduces the number of formulas that need to be written (one per line instead of one per number). It also increases the readability of program code, because the user can review the logic at a higher level of abstraction.

[0067] In addition to solving these problems, RDML reduces costs, time, and complexity for operations on the side of the data consumer, the data publisher and the program developer. To utilize and manipulate data, typically, a user retrieving data over the Internet views a text version of the data, prints the data (in HTML, ASCII or PDF format), and then types the numbers into a spreadsheet or database program. The RDML data viewer **100** automates this process by making the data immediately available to other programs as interpretable data: the user does not need to retype it. Upon locating numerical sets of data from multiple online sources, the data viewer **100** automatically normalizes, collates, transforms, and formats the data.

[0068] Some conventional systems make data available for download as data in either a common spreadsheet format (such as Lotus or Excel), or in a comma-delimited or other common text format. This at least saves the user the necessity of retyping certain numbers, but creates a new problem of manipulating the data to get it into a more usable form (e.g., normalized, standardized).

[0069] As such, RDML (and its related data viewer) "normalizes" data for added efficiency. Normalizing data is primarily a matter of conforming key fields, including matching dissimilar fields, resolving conflicts in categories, resolving the handling of duplicates, etc. In order to be useful, data should be conformed to a format that can be read by an application (such as a graphing routine, or calculation routine). For example, the application may expect data aggregated by year, whereas the incoming data may be aggregated by month. The user must manipulate the input to make it conform to the form expected by the application. RDML performs these tasks automatically, using embedded documentation regarding the input data to make any necessary conforming changes to the input. In the time series example above, RDML would aggregate the monthly data into yearly data, using embedded documentation to determine whether the aggregation should be a sum, an average, etc.

[0070] Additionally, comparing data is a primary use of spreadsheets. Examples include comparing the financial statements of different companies, comparing the statistics from different states, and comparing different economic time series. When these data categories come from different sources, they are usually not directly compatible: the user must lay out the data items on a spreadsheet or similar program in a manner similar to assembling a jigsaw puzzle. As with normalization, RDML uses documentation embedded in the various input files to determine how different line items and values should be collated.

[0071] Once data is normalized and collated, the RDML data viewer **100** transforms the data automatically. Conventionally, users typically make a series of adjustments to the numbers in the data set. The input data may be, for example, denominated in "millions of dollars," while output is desired in "billions of yen." RDML provides a set of indicators for the most common transformations, permitting automatic machine translation of the numbers from their input state to the state desired by the user.

[0072] A conventional method of formatting data for output on a PC is to cut-and-paste the data to a formatting application (word processor, graph generator, spreadsheet or other), and then mark up the data to change the format to the desired output. This is time consuming and not repeatable—if the data is input again with a slight change, the whole formatting process must be repeated. The RDML data viewer **100** avoids the cut-and-paste approach by saving the original data in a central storage object (described below) in the data viewer **100** and applying separate formatting instructions to create different views **108**. The user can switch among views **108** with a single mouse click and the program handles all format and numerical conversions for the user.

[0073] In some of the more advanced database management systems, a "report-writer" approach is used. Like the RDML data viewer **100**, this approach applies a template to a centrally stored dataset. The problem is that the data sets are not standardized; a report writer template written for one dataset cannot typically be used for another. RDML, however, provides for reuse of style sheets in the same manner it provides reuse of data and macros.

[0074] In addition to the above-mentioned problems, RDML solves problems relating to "live" connections of numerical data involving multiple sources that typically require programming expertise. Whether the aim is to draw numbers from multiple sources over a wide area network (e.g., the Internet) or over a corporate LAN, incorporating remote data is complicated by many issues: connection protocols, programming language dependencies, data type inconsistencies, error handling, data transformations, etc. Programmers can surmount these problems at a certain expense, but not in a flexible way that permits reuse, and users again rely on custom programming. In response to the cost, time requirements, and inflexibility of the custom programming approaches, casual users resort to labor-based solutions.

In a typical case, a financial spreadsheet is created with, for example, ten assumptions related to interest rates. Every time the spreadsheet is used, the creator looks the numbers up in the newspaper and types the results into the appropriate cells, and any necessary transformations are made by hand. RDML removes the need for custom programming and manual input by providing a way to include numbers from remote RDML documents **102** in normal formulas. The RDML data viewer **100** automatically looks to the specified address on the web to retrieve the numbers, makes any necessary transformations (for example, from yen to current dollars) and places the result in the correct formula. In this way, an RDML document **102** or macro **104** can draw on multiple documents at once. Because its documentation is machine-readable, it can be read by multiple systems, none of which need be aware of the physical layout or data types of the others.

[0075] Lastly, the use of RDML enables client-side processing using Internet-supplied data thereby realizing a number of advantages. After data is retrieved, analytic routines (macros) are performed on the client side, as opposed to the conventional approach in web-based data analysis, in which the analytic routines are performed on the server side. Whereas sensitive data and calculations can remain local in the RDML data viewer **100**, the user need not fear that sensitive data is being misused by a company running a server, or that data is being misappropriated over the web. Additionally, it increases speed because updates to graphs, reports and spreadsheets can be near instantaneous because there is no need for the round-trip Internet transmission, or the loading and execution of a routine on a busy server. Users may also prefer local copies of data that they control and to which they have immediate access.

I.A. RMML Overview

[0076] Methods and systems in accordance with the present invention provide macros and RMML, which allow numerical analysis routines to be written quickly, cheaply, and in a form that is usable by a broad range of data documents in RDML. RMML macros provide reusable user-defined calculations for use in conjunction with RDML that automatically manipulate and display numerical data contained in RDML markup documents. RMML also allows spreadsheet type macros to be posted as web documents, to be searched by search engines, to be combined into more complex programs, and to be reused with many data documents.

[0077] For example, a user viewing a chart having a series of data in an RDML data viewer may apply, with one mouse click, a macro to that chart and see an instantaneous (or nearly instantaneous) transformation of the charted series of data. Not only is the data changed, but the titles, legends, footnotes, axis scales and other properties are also changed. As a further example, a user may be looking at a time series trend of automobile sales in millions of dollars. By clicking on a macro entitled "% change", the chart recalculates itself according the percentage change from period to period. The y-axis title changes from "$ millions" to "% annual change", etc. Table manipulation macros may perform such functions as combining two tables into one, sorting a table, searching for certain line items and other database-like tasks. Other transformation macros may perform other functions such as word translation, data format translation, and report-writing.

[0078] RMML macros are highly reusable because they are made available in a cross-platform, text-based, searchable, XML-compliant format. Because the macros are portable, they have much greater marketability. RMML also builds into its language tags for many types of documentation so that a macro may be reused and understood by the original macro writer as well as other users.

[0079] Conventional spreadsheet programs typically base references on physical locations, a problem RMML avoids by referring to numbers by their position in a chart or formula, or by tag names, thus allowing the numbers themselves to be anywhere in a document. RMML macros also use the measurement and the meaning of numbers because RDML-tags contain standard vocabularies to identify the measure, magnitude, scale, unit, precision, class, etc. of the numbers, and the RMML interpreter handles differences for the user.

[0080] Additionally, RMML builds error handling into its interpreter and makes available automated testing tools to help increase the quality of the code. Users may also graphically change parameters for the macros using check boxes, slider bars, input boxes, and selection lists, and RMML makes it easy for the author of a macro to add those visual components.

[0081] Below is a detailed description of RDML, the platform upon which RMML macros run, followed by a detailed description of RMML.

II. System Hardware Components

[0082] FIG. **2** depicts a data processing system **200** that is suitable for use with methods and systems consistent with the present invention. Data processing system **200** comprises a computer **201** and a server computer **203** interconnected via a network **214**, such as the Internet, where the server computer **203** may provide RDML documents **102** to computer **201**. Computer **201** includes a central processing unit (CPU) **202**, a main memory **204**, a secondary storage device **206**, a display **210** and an input device **212**.

[0083] The main memory **204** may include the RDML data viewer **100** which may be a personal computer-based program, although one skilled in the art will appreciated that the data viewer may reside elsewhere. In addition to the data viewer **100** which includes views **108** for display, the main memory **204** includes related software components that may be used to input RDML documents **102**, macro documents **104**, and style sheets **106** to the data viewer. It may include the RDML document formatter **216** which a user uses to apply tags to numerical data, and/or an RDML document server **218** which provides RDML documents **102** to the data viewer **100**. The main memory **204** may also comprise an RDML document editor **220** used to edit the files of RDML documents **102** and RDSL style sheet editor **222** for creating style sheets **106**. The RDML/XML search engine **224**, which searches RDML documents in response to queries, may also reside in memory **204** along with any additional plug-in applications **225**. Each of these components and their interactions are described below in greater detail.

[0084] The memory **204** may include various software components of the data viewer **100** and related components which may be programmed in object-oriented languages such as the Java™ programming language. The Java™ programming language is described in further detail in "The Java Programming Language," 2nd Ed., Ken Arnold, James Gosling, Addison-Wesley, 1998, which is incorporated herein by reference. For further description of the Java Language, reference should be made to "The Java Language Specification," James Gosling, Bill Joy, Guy Steele, Addison-Wesley, 1996 which is also incorporated herein by reference. However, one

skilled in the art will appreciate that other programming languages may be used. The RDML data viewer **100** may download RDML data documents **102** from many different sources such as a local storage disk or from a server over network **214**.

[0085] The secondary storage **206** may include the RDML image database **226** which stores documentation tag data regarding RDML document **102**, and the RMML macro software development kit **228** for developing macros. The secondary storage may also store existing databases **230** for holding original data from which RDML documents **102** are created. These components may also be stored in main memory or on another remote computer and are also described in greater detail below.

[0086] FIG. **2** also depicts a web server **232** on computer **203** that interacts with the computer **201** via network **214**. In one system consistent with the present invention, the web server **232** sends RDML documents **102** over the network **214** and may be connected to a disk array **234** which holds RDML data documents **102**. This disk array **234** may receive data documents **102** from the database server **236** which may receive data from database storage **238**. Protocols used in the transmission of information between the server **232** and the computer **201** include, but are not limited to, HTTP and FTP.

[0087] One skilled in the art will appreciate that aspects of methods and systems consistent with the present invention may be stored on or read from other computer readable media besides memory like secondary devices, such as hard disks, floppy disks, and CD ROM, or a carrier wave from a network (such as the Internet). Additionally, one skilled in the art will also appreciate that the data processing system may contain additional or different components.

III. System Overview

[0088] FIG. **3** illustrates an RDML system consistent with the present invention and the relationships between the various components. These various components may reside in a memory **204** on a computer such as computer **201**. Existing databases **230** store data that can be used to create RDML documents **102**, and generally the data is extracted into either a "flat file" format (e.g., comma-delimited, or fixed-width fields) or a form readable by Java Database Connectivity ("JDBC"). RDML documents **102** may be structured to model flat files so that a single RDML document **102** encapsulates a set of rows and columns. Examples of databases include SQL server by Microsoft and Oracle **8** server.

[0089] The RDML document formatter **216** is a graphical tool used by the user to reduce the amount of manual labor required to combine data and its documentation. The contents of an existing database **230** may not be enough to create an RDML document **102**, because in one system consistent with the present invention, RDML uses documentation of the contents. Such documentation often may be found in a printed volume and hence must be manually input and manually combined with the data. The RDML formatter **216** allows a user (or data publisher) to map data fields from a relational database, flat file, spreadsheet file or text document to RDML data documents **102**. It also allows a data publisher to add documentation to the data file (RDML data document **102**) itself.

[0090] The RDML image database **226** is a relatively small database maintained by the RDML formatter **216** to hold information necessary to recreate an RDML document **102** should the underlying data change. It eliminates the need for the user to manually input the documentation again because the RDML image database **226** stores it.

[0091] An RDML document server **218** functions when RDML documents **102** are being created dynamically. The server **218** queries the existing database **230** for the desired line items, queries the image database **226** for documentation items and instructions for constructing the RDML document **102**, and finally creates a valid, well-formed RDML document.

[0092] The RDML document editor **220** allows users to edit RDML documents **102** which typically are ASCII text files (which may contain UNICODE data). As such, they may be edited by any text-oriented editor or word processor. This is, however, a time-consuming and error-prone approach to marking up an RDML (or any XML) file. A specialized RDML document editor **220** allows a user to quickly make changes, check for errors, and view information on the data and metadata. The document editor **220** may operate over the Internet: users possessing the correct permissions to modify a file can make updates or changes to the underlying RDML data document **102** by issuing commands from the RDML data viewer **100**.

[0093] An RDML document **102** may be an ASCII/UNICODE text file used to transmit data and metadata to the RDML Data Viewer **100**. It can be stored locally, or can be transmitted over network **214** such as a corporate LAN or the Internet (using HTTP, FTP, email, etc.). To be a valid RDML document **102**, the file conforms to the RDML Document Type Definition ("DTD") which is described in detail below. The DTD describes required and optional data elements, their ordering, syntax, and the controlled vocabulary for use in certain data elements. DTDs in general are also described in "XML: Extensible Markup Language," Elliotte Rusty Harold, IDG Books Worldwide, **1998**.

[0094] The RDML data viewer **100** functions as a combination RDML and HTML browser, object-oriented spreadsheet, report-writer, and application platform. The browser functions read HTML or RDML documents **102**; HTML documents are rendered immediately in a browser window, while RDML documents are first cached in an internal data object (conforming to the DOM—"Document Object Model"—standard discussed below) and then rendered in views **108** selected by the user. The default view is typically a chart and a tree listing, although several other default views are available. The RDML data viewer **100** uses the cached RDML data objects to create views **108**, employing a variety of transformation and manipulation objects to get the data to match either the form expected by the view, or to match the form of other data objects with which it is being combined.

[0095] The RDML Macro Software Development Kit ("SDK") **228** allows a function designer to create functions that can be applied generally to any data document that contains the types of data necessary for the function. The SDK is a collection of macro-writing tools, including an IDE ("Integrated Development Environment"), an editor, an object browser, and a validation tester.

[0096] RDML generally separates the form of data from general calculation routines that operate on that data. By separating format from functions, both the data and the functions can be made reusable. In conventional spreadsheets, for example, numbers can be placed in arbitrary cells selected by the creator. If a second developer decides to create an analytic function, that developer must know what row and column

each number is in. That routine will then not work with another spreadsheet unless the exact same row and column structure is followed.

[0097] Applying functions generally creates one form of software reuse: users need not tell the function where their data is (the approach of "wizards" in traditional spreadsheets). A second form of reuse is that gained by inheritance: function developers can choose the existing function that most closely matches what they are trying to do, and simply make the necessary edits to create the desired new function. The SDK **228** permits a third type of reuse in the ability to attach to remote data documents and remote macros on the web to take advantage of these extra resources and to provide real-time updating of data and functions.

[0098] RMML macro documents **104** are text documents that contain routines just as RDML data is contained in a text document. This document contains the heart of the calculation: the specification of operations on numbers, such as a formula, an ordered list of other macros to perform, or list of instructions.

[0099] RDSL style sheets **106** act as templates for output reports. The RDML data object (discussed below) in the RDML data viewer **100** can be placed into a report using one or more different style sheets. RDSL, a fully compliant implementation of XSL, allows a data publisher to provide multiple report formats for its data. They are reusable in that a style sheet written for one RDML data document **102** can be used for another if the specified restrictions are met. For example, a style sheet for a time-series data set can be used for another time series data set. The style sheet editor **222** is basically a report-writer because the user can graphically compose a report from a sample document, specify the types of RDML data documents **102** that this report can apply to, automatically create a style sheet **106** when the result is acceptable, and then use the resulting style sheet to create a report from any qualifying RDML data document **102**.

[0100] The RDML search engine **224** searches RDML documents **102** similarly to the way HTML search engines search HTML documents. HTML search engines pick up key words, but can only tell a user that a particular document contains the requested word(s). They cannot, however, provide query services. For example, a user may wish to search the Internet for "all financial statements of computer services companies which have revenue growth >10%," and the RDML search engine **224** provides this capacity. The RDML Search Engine **224**, however, does not index only keywords like the HTML approach, but also the element names and key attributes. This permits searching for numerical values, or posing complex queries regarding the content and/or context of the data. The RDML search engine **224** thus acts as a generalized query processor for RDML data document **102**, RMML macros **104**, and RDSL stylesheets **106**. Some aspects of the search engine **224** are described in greater detail in co-pending U.S. Provisional Patent Application Ser. No. 60/183,152, filed on Feb. 17, 2000.

[0101] As mentioned earlier, each view **108** in the RDML data viewer **100** is essentially a separate application denoted on FIG. **3** as various RDML Plug-in applications **225**. The chart view, for example, is a separate charting application that has been "plugged in" to the RDML data viewer's basic infrastructure of Internet browser, XML parser/processor, RDML transformation and manipulation objects, internal object management architecture, interfaces to other applications, and graphical user interface (described below). For example, a mapping component can be plugged into the panel in which the chart is seen. Subsequently, when a user clicks on a line item, the colors of the different countries or states will change to show a thematic map, or different dots will appear, etc. The RDML data viewer **100** may be designed in modular fashion to permit changing or adding component applications to leverage off the common components.

IV. System Details

[0102] With further reference to FIG. **3**, several of the components (excluding RMML and RDSL components) are described in greater detail below. The existing databases **230** may be relational databases, object-oriented databases, or any other type of database. RDML tags in RDML documents **102** add documentation to the types of pure data found in relational databases. Since the data that already exists in relational databases can be used to create RDML documents **102**, the data may be made available to either the RDML formatter **216** or the RDML server **218** and be in a flat file format (rows and columns).

[0103] For connections, both the RDML formatter **216** and the RDML server **218** read Open Database Connectivity ("ODBC") and JDBC database sources. The flat file aspect is based on the idea that RDML documents **102** effectively model a basic row and column matrix. To produce an RDML document **102**, therefore, the original data source may provide a single table, or create one with a query. Relational linking is possible with RDML documents **102**, through a server to a relational database, or indirectly through hyperlinks to other RDML documents or hyperlinks to RDML document servers **218**. This is similar to many database applications: data is collected from various underlying tables to create a single table or screen to show the user. The data table to be used as a source for an RDML document **102** may be oriented to have the fields be one of three basic exemplary RDML data table types: time series, category, or X-Y plot described below.

[0104] With reference to the RDML formatter **216**, once there is a flat file data table of data points in the existing database **230**, an RDML document **102** can be created by adding tags that contain documentation regarding the data table. The information contained in these tags are maintained in a separate data table from the original data points. The RDML formatter **216** is an application that assists a user in selecting the proper documentation tags, saves the tags in a separate database (the RDML image database **226**), and creates the actual RDML document **102**.

[0105] FIG. **4** is a screen shot that shows how the RDML formatter **216** assists the user in "tagging" data, i.e., adding metadata that applies to the line items. In one implementation consistent with the present invention, for each line item of data, there are at least 18 different potential attributes (described in detail below) applied using the radio buttons **402**. When a user selects a radio button **402**, the formatter **216** supplies a description **404** of the selected attribute. Upon selection of a radio button **402** from the left-most box, the user is presented with a list of the possible values in the middle option box **406**. The user may either double click one of the options to add it as an attribute of the selected line item, or type in a new value in the text box at the top of the middle option box **406**. The formatter **216** automatically updates the line item table **408** which, in this instance, displays the line items' ID, title, format and Y-axis title (attributes which are discussed below).

[0106] FIG. **5** shows a screen shot of the database tab and document management screen accessed by a tab **502** on the RDML formatter **216**. This screen manages RDML documents **102** that can be created from a relational database **230**. The user can specify a list **504** of data tables in a relational database and have the RDML formatter **216** create RDML documents **102** for each using default properties. From that point, the RDML formatter **216** is used to modify the defaults. The user may use the RDML formatter **216** to select tags from scratch (as shown in FIG. **4**) for a document **102**, but this puts an unnecessary burden on the user to remember which properties are appropriate.

[0107] The formatter **216** references a database **230** (shown on FIG. **3**) specified by the documentation URL **506**. The database **230** holds a list of data tables, and the formatter **216** inserts a table **504** that holds stores information regarding the data tables into the database **230** for later reference. This table **504** is referenced by the documentation table name **508**. Similarly, the formatter **216** stores a list of line item attributes **408** for the database **230** in the database which are referenced by the li_data URL **510**.

[0108] The RDML image database **226** contains documentation that relates to a separate set of data records in the existing database **230**. The RDML formatter **216** creates and maintains the RDML image database **226**. The RDML image database **226** standardizes the process of documenting data documents, and provides a controlled vocabulary for the metadata. The RDML image database **226** also performs document management and tracking, update and version control, error checking, input validation, and the creation of status reports.

[0109] The image database **226** contains a list of RDML documents **102** that it can produce. The original data may be in flat files, relational tables, or a table that results from a query on a relational database. The image database **226** contains document metadata that references the original document table or flat file in the original database **230**. Documentation information contained in the image database **226** is added to this data. It further includes line item set metadata for the set of line items, documentation that is typically of a more technical nature and applies to the line item set as a whole. Examples of such information is table types, field definitions ("x values") and hyperlinks that apply to the line item set as a whole. (A line item set may be generally analogous to a table; it is a collection of line items, which are analogous to records in the database world.)

[0110] The image database **226** also includes line item metadata that references the individual records of the original document table or flat file in the original database **230**. There may be a pointer from each line item's metadata record to the corresponding record in the original data table. Each line item includes the fields of the original record, plus, in one implementation consistent with the present invention, at least 18 additional fields that contain "attribute" documentation: object types, unit designators, hyperlinks, footnotes, and so forth. A listing of exemplary attributes of a line item is described below.

[0111] FIG. **6** illustrates steps used by the data viewer **100** when accessing the RDML document server **218**. The RDML server **218** occupies a middle position between a database server **230** and a user's data viewer **100** or web browser. Although one architecture for RDML is to have RDML documents **102** served from disk-based text files, users may sometimes wish to create RDML documents dynamically in response to queries. The tasks of executing the query and delivering a result in RDML document form are performed by the RDML server **218**. To do so, a user submits the data request to the server **218** via the data viewer **100** (step **602**). The RDML Server **218** is a server application called by a web server (not shown) which fields the user's request. The RDML server **218** queries the database **230** using known techniques (step **604**), and the database returns the results to the RDML server (step **606**). The server **218** then creates an RDML document **102** (step **608**) and returns the RDML document to the web server which transmits the results to the viewer **100** (step **610**).

[0112] The RDML document editor **220** permits users to edit the actual elements and attributes of an RDML, RMML, or RDSL document (**102**, **104** and **106**). The documents may be presented in a tree view for selection and direct editing. A text-based window may display the contents of the selected document for editing. Besides basic editing, it performs a number of utility functions: (1) search and replace, (2) validation, (3) well-formedness testing, (4) hyperlink validation, (5) cut-and-paste of elements, and (6) replacement of elements with defaults.

IV.A. Internal Data Viewer Architecture

[0113] FIG. **7**A depicts a schematic diagram of the internal architecture and program flow of the RDML data viewer **100**, and FIG. **7**B depicts the meaning of each symbol type in FIG. **7**A. For each numbered component, a description is given which provides further details on that component's input and output, internal decision process, storage format, object architecture, and program flow.

[0114] Before fully describing FIG. **7**A, however, it is important to understand an overview of the steps involved, which is depicted in FIG. **8** and discussed in conjunction with FIG. **7**A. FIG. **8** is a flowchart describing steps in a method for downloading, processing and displaying a RDML document **102** in accordance with the present invention. FIG. **8** describes an overview of the steps involved, and each related component is subsequently described in further detail with relation to FIG. **7**A. First, the RDML reader **704** finds and receives an RDML document **102** in text form formatted according to the structure of the RDML DTD **702** (step **802**). The RDML Reader **704** may be a class that runs in a separate thread and has methods for checking the RDML document **102** type (Time Series, Category, XY) and handling errors. The RDML Reader **704** then calls the XML parser **706** which parses the text (step **804**). The RDML processor **708** receives the parsed text from the XML parser **706**, error checks it and creates an object based on the data and structure in the received text. (step **806**).

[0115] The RDML processor **708** transfers the resulting object to the X-value transformer **710** which performs type-checking and manipulates the fields (x-values) of the data so that it may be displayed and stored coherently and simultaneously with other active objects of the same type (step **808**). The X-value transformer **710** makes sure that the data values to be graphed against the x-axis are in common units. For example, if document A is an annual time series and document B is a quarterly time series, the X-value transformer **710** in this case would use the "li_aggregation" attributes of the line items in document B to aggregate four quarters at a time into annual data. As a second example, if document A is a category document with x-values equal to stock ticker symbols (F, IBM, XON, etc.), and document B contains x-values

denominated in company names (Ford, International Business Machines, Exxon, etc.), then the x-value transformer **710** will use the "li_class" attributes in the line items of each document to match them up. The X-value transformer **710** sends the object to the primary data store **712** ("PDS") for storage with other active objects of the same type (step **810**). The views (**716**, **720**, **724** and **725**) then display and present information using data from the active objects in the PDS **712** (step **812**).

[0116] Details of the steps and components involved are now discussed in conjunction with FIG. **7**A. Described first is an RDML document **102** defined by the RDML Document Type Definition. Description of the various software components of the data viewer **102** follows.

[0117] The data and metadata of an RDML document **102** may be formatted inside tags which denote the beginning and ending points of each data element. The element tags may also include attributes to be applied to the data elements, a description of what sub-elements may be found within an element, and vocabulary choices for different attribute values.

[0118] A full sample RDML data document **102** is shown at Appendix B. Shown below is a fragment of an RDML document **102** that supplies the data for one line item in the document. Note that element tags are designated within angle brackets ("<" and ">"), and that attributes are listed that can be applied to the data.

```
<line_item
    li_ID = "1"
    li_legend = "Department of Energy"
    li_title = "Outlays - Dept. of Energy"
    li_cat = ""
    y_axis_title = "$ in Thousands"
    level = "1"
    format = "#,##0;(#,##0)"
    relation = "Parent"
    li_notes = ""
    li_desc = ""
    li_prec = "−3"
    li_unit = "$"
    li_mag = "3"
    li_mod = "in"
    li_measure = ""
    li_scale = ""
    li_adjustment = ""
    li_aggregation = "">
  <data_y>
2754567, 2699717, 2726457, 2578954, 2343297, 2252927, 2474440, 2392904, 2392536,2200326,
2298612, 2303643, 2233062, 3229510, 3840973,5049308, 6412986, 7441295,7261157, 11756883,
11657178, 10590471, 10991261, 10587245, 11026443, 10692802, 11166039, 11386923,12083898,
12478820, 15522633, 16941547, 17839298, 17617000, 16203000, 14467000, 14366000,15240000,
15190000, 14938000, 14412000, 14556000
  </data_y>
</line_item>
```

In this example, the 18 lines with an "=" are "attributes" of the <line_item> element, and essentially, the attributes provide machine-readable documentation for the data values specified in the sub-element <y-values>. This particular line item describes "Department of Energy outlays in thousands of dollars," but the specifics of the set of attributes are described below in conjunction with the RDML Document Type Definition **702** which describes the structure and elements of a RDML document **102**.

[0119] RDML documents **102** may be produced by an ordinary text editor, by the RDML data formatter **216**, or by the RDML data server **226**. (XML browsers other than the RDML data viewer **100** are able to do little more than echo the text input to the user's screen since they cannot interpret the RDML tags.)

IV.A.1. Document Type Definition

[0120] FIG. **9** graphically shows elements of the RDML Document Type Definition **702**. In one implementation consistent with the present invention, RDML documents **102** conform to the rules provided by the DTD **702** (also shown on FIG. **7**). In accordance with one implementation of the present invention, an RDML DTD **702** is shown at Appendix A. Attributes and elements of the DTD **702** may also be seen in the full sample RDML document **102** in Appendix B. Those two Appendices A and B are useful for examining specific attributes and elements of the DTD **702**.

[0121] The DTD **702** data structure is optimized to provide information that is needed in order in which it is required, to reduce the learning required on the part of new users to RDML formatting, and to avoid unnecessary duplication. The first line of the DTD **702** in Appendix A starts with "<?xml encoding="UTF-8"?>" because all XML documents start with a line that tells the client application, in this case the data viewer **100**, what type of document it is and the version of XML.

[0122] With further reference to FIG. **9**, the DTD **702** used to define RDML data documents **102** is structured in a hierarchical tree structure of elements. Each element may include a list of attributes (displayed in Appendix A, but not shown on FIG. **9**) and/or an association with one or more sub-elements. The DTD **702** specifies which attributes are required and which are optional for any embodiment of the DTD. Depending on design constraints, the required and optional elements may vary. At the highest level, the DTD **702** has two elements descending from a root element, <rdmldoc> **902**. The first element, <rdmldoc_header> **904**, contains the metadata for the document as a whole and the second, <line_item_set> **906**, contains the set of the line items.

[0123] In one implementation consistent with the present invention, the <rdmldoc_header> element **904** contains sev-

eral attributes itself, and the optional sub-elements <data_source> **908**, <formatting_source> **910**, <rdml_source> **912**, <license_terms> **914**, and <link_set> **916**, each describing some aspect of the source of the data. In this implementation, the <rdmldoc_header> **904** element may include ten attributes describing document information as a whole. These attributes are "rdml_doc_ID," "doc_title," "timestamp," "version," "expiration," "freq_of update," "num_line items," "num_datapoints," "x_indexes," and "first_li_with data."

[0124] The rdml_doc_ID attribute is the unique identification of the RDML document **102** and is typically a file name or URL. The doc_title is a plain language description of the document that will appear at the top of reports and views for the document for use by a user. The timestamp is typically generated by the application that created the document and may denote the time that the document was created or the time the data was accessed for creation of the document. The version describes which variant of the RDML document **102** it is and may be named by the creator. The expiration describes the date and time that the data in the document **102** may no longer be relied upon, typically when the next update is expected to be released. Freq_of_update describes how frequently the document is updated and may be used by applications that want to schedule updates to the data. The next two attributes, num_line items and num_datapoints, are integers describing the total number of line items and number of data values respectively. These attributes are optional and may be used as a "checksum" by a receiving application to ensure that the data has not been accidentally changed or corrupted.

[0125] The next field, x_indexes, denotes three data fields to use as representative data fields in the tree view **720** (described in detail below). X_indexes is a comma-delimited string of three integers, each of which is an index to a selected field. For efficiency, the indexes may denote the end of the list of fields so that, for example, "−3,−2,−1" shows the last three fields in the tree view **720**. Indexes based on the end are useful because most people reading a time series want to see the most recent data. Along, similar lines, the first_li_with data attribute is an integer index that points out which line item is to be displayed on the chart when the document **102** is loaded into the data viewer **100**.

[0126] The <data_source> **908**, <formatting_source> **910**, <rdml_source> **912**, <license_terms> **914** elements, sub-elements of <rdmldoc_header> element **904**, may optionally contain one or more of sub-elements of <contact_info> **918** which contains contact information. This element can be used by the target application to create an email letter, update a contact list, or populate a database of information sources. The same element structure is used for all contact information sub-elements **918** so that the application that created the document **102** only has to create one structure.

[0127] In one implementation, this contact information is represented by eleven attributes: "role," "name," "company," "address," "city," "state," "zip," "country," "email," "form," and "comments." Role is the role played by the party in the creation of the document, i.e., "data source" for the <data_source> **908**, "formatting source" for the <formatting_source> element **910**, etc. "Form" determines whether the hyperlink is a "simple" link or "extended" link. Under the Xlink specification, a language designed to implement links between XML documents and resources, hyperlinks may be simple or extended. Xlink is described in "XML IE5 Programmer's Reference," Alex Homer, Wrox Press, 1999, which is incorporated herein by reference. Simple links are traditional "jump" hyperlinks in which clicking on that link will close the current page and open the target page. Extended links are application-specific and can identify different types of resources, such as multimedia files and other non-document resources.

[0128] The contact information in the <data_source> **908** describes who or what collected the data to create the original database, while the same attributes in <formatting_source> **910** describe who or what added the RDML tags to the original data to create the RDML document **102**. The same information in <rdml_source> **912** describes the person or company that created this particular document and made it available to the outside world.

[0129] In addition to the <contact_info> **918** sub-element in <license_terms> **914** which describes the contact information regarding the licensing of the information, the <license_terms> element has its own set of licensing-related attributes. These attributes include: "copyright_cite," "holder," "license_type," "warranty," "disclaimer," "terms," "date," "email," "state," and "country." The copyright_cite is a string that may appear on reports regarding ownership of the particular data set in the RDML document **102**. A typical example might be "Copyright 2000, e-Numerate Solutions, Inc. All Rights Reserved." The holder attribute lists the full legal name of the owner of the copyright. License_type lists the type of license, such as "none—proprietary and confidential," "public domain," "pay per use," etc., and terms lists the payment terms, if any, such as "$1 per download." The information in these attributes may be used by routines associated with the RDML processor **708** to automatically track and implement licenses and payments.

[0130] Another sub-element of the <license_terms> element **914** is the <linkset> element **916** which, in one implementation, has two attributes and its own sub-element <link> **922**. A <linkset> **916** is a collection of hyperlinks. These hyperlinks may be either HTML files or RDML files. The individual <link> elements **922** hold the actual links and attributes. The <linkset> element's two attributes are form, described above, and href, a standard string for URL or web address, and they designate the HTML or RDML page where a page of hyperlinks may be found. This is useful when the creator does not want to list all of the hyperlinks in the document **102** itself.

[0131] The <link> element **922** describes hyperlinks to other documents and contains, in one implementation, nine attributes: "form," "href," "behavior," "content-role," "content-title," "role," "title," "show," and "actuate." These link related attributes are described in the XML IE5 Programmer's Reference, pp 95-97. The title is a string that appears in the application as a hyperlink title. For example, in an HTML browser, it will appear as highlighted, underlined text. Actuate specifies when the link should be traversed—when the resource that the link points to is retrieved or accessed, and show specifies how the target resource will be displayed. Behavior specifies instructions that control the behavior of the link in the way that the content is displayed or the link is traversed, and role describes what role the target resource plays in the link. Content-role and content-title are alternative places for the title and role, but are not specified in Xlink standards.

[0132] Finally, <rdmldoc_header> **904** may have its own <linkset> **916** having <link> elements **922**. RDML allows users to attach hyperlinks to different elements such as an

entire document, a particular line item, or other element in the RDML document **102**. The reason for the multiple places that hyperlinks may be placed is so that the user can view in one place all the links that apply only to the element under consideration. For example, an RDML document **102** may contain the data for a company's financial statement. The creator of the document may decide that certain links apply to the whole company (links to product lines, competitors, etc.) and that others only apply to single line items (such as a link attached to the "Equipment Leasing" line item that points to the footnote for that line item or an accounting regulation applicable to that account). Even though they are attached to different elements, the links may have the same form. Another reason for multiple linkset elements is to facilitate keeping links together with their logical owners.

[0133] Continuing to refer to FIG. **9**, on the line item side of the <rdmldoc> **902**, the <line_item_set> **906** which contains information on the collection of line items in the RDML document **102** also contains several attributes and several elements. These attributes include: "line_item_set_type," "time_period," "character_set," "missing_values," "null_values," "zero_values," "dates_values," and "percentages."

[0134] The first attribute, the line_item_set_type, is, in one implementation, an important attribute which classifies the line item set into one of three types: time series, category (or cross tab), and x-y plot. Generally, the "type" in this context is the characterization of the x-axis values and whether they represent a time series, a categorization, a x-y plot or other. These line item set types are described in detail below in connection with the x-value transformer **710** which manipulates line items of the same set type. Generally, line item sets of different line item set types may not be actively manipulated together. If the line item is a time series, valid lengths in the time_period attribute may be years, quarter, months, days, etc.

[0135] Character_set designates which standard character set is represented, thereby allowing for support for foreign languages. Missing values holds a designator for the numerical value that represents a missing value, because many views of the data, in particular chart views, need to know which numbers represent blanks. Otherwise, a blank might be interpreted as "0." Null_values designates the character to be treated as null so that it is not confused with "not applicable," or "missing" or "0." Finally, zero_values designates characters that should be interpreted as "0," and not "null," "missing," "not applicable," etc.

[0136] The <line_item_set> **906** has, in one implementation, several sub-elements including <data_x> **924**, <li_class_set> **926**, <linkset> **916**, and one or more <line_item> elements **928**. At the line item set level, metadata regarding line items as a set is shared among all the line items so that the data need not be repeated. In particular, the <data_x> element **924** contains field information common to all line items in the line item set. The <data_x> element **924** includes the x-values and information regarding the x-values of the line items in the set of line items in the RDML document **102**. For example, if the line item set is a time series, the x-values may represent the years, months or other timelines (e.g., 1990, 1991, etc.) listed across the bottom of a chart with which all of the data is associated. Because this information is the same for each line item in the line item set, it is only included once in the RDML document **102**. In one implementation, in addition to the actual x-values, <data_x> **924** also contains the following attributes: "x_title," "format," "x_notes," "x_desc," "x_prec," "x_unit," "x mag," "x_mod," "x_measure," "x_scale," "x_adjustment," and "x_links."

[0137] In <data_x> **924**, x_title is the title displayed on the x-axis as the data is displayed on a chart. Format is a string providing a template for the default representation of the x-axis values. The strings are those familiar from spreadsheet programs (examples may also be seen on FIG. **4**):

[0138] #—digit(s), zeros suppressed

[0139] 0—digit(s), zeros displayed

[0140] .—decimal point

[0141] ,—separator

[0142] A-z, other characters—displayed literally.

[0143] Other formatting codes can also be used (e.g., codes used in scripting languages). X_notes may contain miscellaneous footnotes regarding x-values of the line item set, while x_desc may describe additional description regarding the x-axis values.

[0144] The x_prec attribute describes the precision or number of significant digits for purposes of axis label display. In this attribute, negative numbers cause rounding of amounts greater than zero. For example, a precision of "2" will display a number as "8,254.43". That same number with a precision of "−2" will be displayed as "8,300." The underlying representation of the number will be the full value; only the formatting and representation on the screen will change. The data viewer **100** uses this primarily for formatting the axis labels, but the attribute is available for default formatting as well in other uses such as reports, footnotes, etc.

[0145] The subsequent attributes, x_unit, x_mag, x_mod, x_measure, x_scale, and x_adjustment, represent the meaning of the x-values and are used by the data viewer **100** for manipulation, reconciliation and display with other RDML documents **102**. In RDML, numbers are collectively described by these attributes which describe the numbers' units. They are as follows:

[0146] Unit: the physical unit of the numerator

[0147] Magnitude: the size of the numerator

[0148] Modifier: relation of the numerator to the denominator

[0149] Scale: the size of the denominator

[0150] Measure: the physical unit of the denominator

[0151] Adjustment: special qualifier (i.e., inflation adjusted)

For example, a line item reported to represent "$ in thousands per million people" can be represented as:

$$\frac{[1\ \$US] * (1{,}000)}{[1\ \text{person}] * (1{,}000{,}000)}$$

Therefore, the attributes of the line item are:

Unit:	$US
Magnitude:	1,000
Modifier:	/
Measure:	1 person
Scale:	1,000,000

Access to these attributes for line items provides enormous power to the data viewer **100**. It facilitates the interpretation and transformation of the numbers. It allows multiple lines to be placed on a single chart without conflict and allows macros

to be applied without the requirement of human intervention to answer questions about the units. It further allows reporting templates to make automatic adjustments to provide the most readable reports. In particular, the data viewer **100** uses these attributes to construct y-axis labels and descriptors when the user has made a transformation and the "y_axis_label" attribute is no longer appropriate.

[0152] A standard vocabulary for units and measures may be used for efficiency, and magnitude and scale may be more simply represented as a power of 10, e.g., 3 for thousands, 6 for millions, etc. This permits more rapid transformations and eliminates potential confusion of variant usages and spellings (e.g., million, mille, MM, etc.)

[0153] For an example of the use of these attributes, suppose the RDML data viewer **100** has plotted the following value/measurement:

[0154] 426 US Dollars (in thousands) per Hour, adjusted for inflation (1996=100).

[0155] The user now wants to convert this to:

[0156] "X" Italian Lira (in billions) per Day, in nominal lira

where "X" is the value to be calculated and the rest of the line is the measurement. The data viewer **100** makes this transformation automatically for the user because it has conversion factors for the following:

RDML Attribute:	Begin:	End:	Conversion factor:
Unit	US Dollar	Italian Lira	A* 0.0000234
Mag	Thousands	Billions	A* 1,000,000
Mod	per	per	A* 1
Scale	Hour	Day	A* 24
Measure	1	1	A* 1
Adjustment	Adjusted for infl.	Not adjusted	A* annual factor
Value	426	1.189	

[0157] The data viewer **100** multiplies the conversion factors (or performs any other appropriate mathematical operations) to manipulate the display. The user does not have to look up each of the conversion factors, marshall them into the correct sequence, do the arithmetic, and make corrections such as rounding adjustments. The user may simply select a new unit, magnitude, etc. from a drop-down box and make a selection.

[0158] FIG. **10** illustrates steps used by the data viewer **100** to manipulate the numerical information in an RDML document **102** to produce a desired transformed display. First, the data viewer **100** locates the RDML document **102** (step **1002**). The document may be located either locally or online using a URL, the search engine **224** or any other technique. Next, the data viewer **100** selects and accesses the desired document **102** (step **1004**). The data viewer **100** then accesses the line item that needs to be transformed (step **1006**) and determines the desired transformations (step **1008**). The desired transformations may be received from a user or may be determined by the data viewer **100** automatically to, for example, accommodate the addition of a new document **102** to a display of a current one. The data viewer **100** accesses the unit, magnitude, modifier, scale, measure and adjustment attributes of the document or line item to be transformed (step **1010**). Using these attributes, the data viewer **100** determines the conversion factors, if any, for each (step **1012**). These conversion factors may be stored locally or retrieved online over a network **214**. The data viewer **100** then multiplies the conversion factors to transform the numerical data into the desired display (step **1014**) and displays the transformed line item or document (step **1016**). If more than one line item is to be displayed, the data viewer **100** may repeat these steps so that all appropriate line items may be transformed to the desired display format (step **1018**). Similarly, if more than one document **102** needs to be transformed, the steps may be repeated for each document. In this way, documents **102** having different numerical sets may be automatically manipulated for simultaneous display or quick transformation of display format without human intervention. The system automatically resolves conflicts between different documents in different formats by transforming them into one desired form.

[0159] In one implementation, when the system converts one unit to another unit, it converts the original source unit to a base unit known by the system, and then converts the base unit to the target unit. The system stores conversion factors from base units to other units in a unit list XML file, a portion of which is shown at Appendix C. For instance, suppose the base unit used by the system for length is "meters," and numerical values are to be converted from "yards" to "miles." The viewer **100** converts the yards to meters using the stored conversion factor, and then from the meters to miles using the appropriate stored conversion factor. In this way, the unit list file need only contain conversion factors from the base unit to various other units, and need not list a conversion factor for every possible combination between various units.

[0160] The structure of the unit list file is as follows: a <unitlist> element is the root, and it has one level of child nodes, each of which is a <unit> element. The unit elements each have a number of attributes and elements that describe the characteristics of that unit necessary to convert it into another unit or set of units.

[0161] The conversion element contains the attributes necessary for making a conversion where the source unit and the destination unit are both of the same type. For example, converting "miles" to "inches" is simply a matter of finding the correct multiplier to apply to the number of miles, because both units are measures of type "length."

[0162] The conversion element contains six elements: (1) "conv_target" describes the target unit of measurement that the following conversion factors will bring you to, (2) "conv_factor" is the number to multiply by the source value to arrive at the destination value, (3) "conv_constant" is the constant to be added to the product of the source value and the conversion factor. For example, in the conversion formula for Fahrenheit to Centigrade (F=32+9/5 C), 32 is the "conv_constant", (4) similarly, if the conversion involves a logarithmic conversion, the necessary factors are included in "conv_log", (5) "conv_source" is a description of the standards body that set forth this particular conversion factor, and (6) "conv_href" contains the URL for the approving standards body.

[0163] The type element contains one of the following text strings: (1) Length (base unit=meter), (2) Area (base unit=square meter), (3) Volume (base unit=cubic meter), (4) Mass (base unit=gram), (5) Time (base unit=second), (6) Temperature (base unit=centigrade), (7) Energy (base unit=joule), (8) Currency (base unit=$US), (9) Compound (no base unit), (10) Diverse (no base unit), (11) Collection (no base unit), and (12) Occurrences (no base unit).

[0164] The Compound and Diverse types are constructed from one or more of the basic units. Compound types are simple combinations of others. Example: "miles per hour" is a combination of a length unit and time unit. In order to

convert a Compound type into another type, it is necessary to be able to make the necessary conversions of the decomposed units.

[0165] Diverse types are those that are constructed of descriptions. For example, an "ohm" is an electrical unit described as "the resistance offered to an unvarying electrical current by a column of mercury at the temperature of melting ice, 14.4521 grams in mass, of a constant cross-sectional area, and 106.3 centimeters in length."

[0166] A Collection type is a collection of persons, places, things, etc. For example, a data series denominated in "people in millions" means that one unit of this type is a collection of one million people. Collection types can use any of the conversion elements. For a simple conversion example, suppose there are 2.4 people per family in a sample. Then "people" could be converted to "families" by a simple division by the 2.4 conversion factor.

[0167] An Occurrence type is a collection of events. "Cycle" would be an Occurrence type that could be divided by "seconds" to produce a compound "cycles per second" unit of measurement.

[0168] The "subtype" element is for finer distinctions among types. The "plural" element is for constructing new titles, legends and labels at the completion of a conversion operation. An "alias" element is provided for enabling conversions where data has been entered in a common, but non-standard form. For example, tables often use "in" instead of "inches." The "desc" element is provided so that a plain language description can be given the user. The "icon" element provides a place for giving the unit an icon to be used in lists, drop-down boxes, etc.

[0169] Referring back to the elements and attributes of FIG. **9**, in <x_data> **924**, there is an x_links attribute which may be a comma-delimited string of URL's for linking to other sources.

[0170] In addition to this element, the <li_class_set> **926** element represents the set of line item class elements and, in one implementation, has no attributes but has one or more sub-elements representing line item class, <li_class> **930**. These line item class tags specify categories in various classification systems to which the numbers belong, such as "<US Dollars>" or "<Total Revenues>". The data viewer **100** uses these class tags to select which macros can apply, to adjust report formats, and to make the correct selections of assumptions in analytic processing. The class designations permit validation and conforming of different data sets, thereby allowing the data viewer **100** to combine documents from unrelated sources into a single unified source. Class tags may be used by macros that look at the class tag list to see if it qualifies to act on the particular line item. For example, if a line item in a financial statement is tagged as of the class "debt," the macro knows that it can use this line in calculating "debt-to-equity" ratios. But if the line item is tagged "piano," for instance, the macro will not be applied. Note that, in this implementation, the element names for the classes are entered as comma-delimited strings.

[0171] The <li_class> element **930**, in one implementation, has five attributes. These are "class_name," "parent_class," "form," "href," and "description." Class_name is the name of the class to which the line item set belongs, and parent_class denotes the name of the parent class. These attributes may be used by more advanced features of the data viewer **100** such as the macros.

[0172] The <line_item_set> element **906** further contains a <linkset> **916** similar to the previously described <linkset>. As before, this <linkset> **916** further has a <link> element **922** previously described.

[0173] The <line_item> **928** element may have, in one implementation in accordance with the present invention, four sub-elements and 18 attributes. The elements are <data_x> **938**, which contains the x-values for this line item if they are different from the default x-value in the line_item_set element <data_y> **932** which contains the y-data values, the data numbers or values of the line item, a <linkset> **916** having a <link> **922** as previously described, and a <note_set> element **934**. The <noteset> **934** contains one or more <note> elements **936** which have user readable, plain language notes regarding the line item.

[0174] The attributes of the line item include: "li_ID," "li_legend," "li_title," "li_cat," "y_axis_title," "level," "format," "relation," "li_notes," "li_desc," "li_prec," "li_unit," "li_mag," "li_mod," "li_measure," "li_scale," "li_adjustment," and "li_aggregation." Several of those attributes have the same meaning as attributes previously described except that they specifically describe only the line item and y-values to which they are attached.

[0175] The li_ID is a unique identification number for the <line_item> element **928** and may be numbered from 0 to n (where n is the number of line_item elements). In one implementation consistent with the present invention, the numbers are unique and in order.

[0176] The li_legend attribute is a plain language string describing the line item that does not need to be unique. Generally, it appears in the leftmost column of the views. The li_title is a string defining the general subject of the line item. In the data viewer **100**, this may be used as the title of the chart and as titles in reports. Typically, titles are the same for line items grouped together, but they are not required to be.

[0177] The li_cat attribute represents a line item category. As opposed to the li_legend and the li_title, which are displayed on the chart in the data viewer **100**, the li_cat is not normally displayed. It is generally a non-printing designator for a category that the line item might belong to. Often, this may be a table name, or a primary key in a database, or some other organizing identifier. It may be used to group line items for reports.

[0178] The y_axis_title attribute is a string which will appear on the y-axis as the title of that axis. However, if the user applies a transformation to any variable in the descriptor, this hard-coded y-axis title will be replaced by one generated by the data viewer **100** using other attributes.

[0179] The level attribute and relationship attribute specify hierarchical relationships between line items. Conventional links in relational databases are maintained by matching records on the basis of "key fields." One drawback of this approach is that nothing is known about the character of the relationship except that it exists, and there is no way to tell, absent specific documentation elsewhere, that one record is a child or parent of the other, and whether that nature is a containment, a derivation, and inheritance, etc. In RDML, the creator of the data may specify the hierarchical level of each line item and the nature of that hierarchical relationship. The data viewer **100** uses the level attribute and the relationship attribute to create a hierarchical tree, to place icons representing the relationship in front of each line item to summarize the derivation of numbers and describe their context, and to assist macros and updating data tables. The level attribute specifies

how many levels down from the parent node a line item is, while the relationship attribute specifies the nature of the relationship, such as whether the line item is a child of another line item or contained by another. It may also determine whether the line item is an additive or subtractive subcomponent of a parent, or a subtotal that is dependent on other child line items. These previously mentioned attributes and elements make up a DTD **702** in accordance with methods and systems consistent with the present invention.

[0180] Li_aggregation is an attribute useful if a user wants to "aggregate" or "deaggregate" data based on differing x-axis transformations. This attribute explains to the data viewer **100** how to handle this particular line item when such transformations are attempted. For example, if a line item set presents bank account information, each line item may be a time series and presents quarterly data, but the user may wish to see the data on an annual basis. For some line items in the set, it is simply a matter of summing up four quarters worth of data (e.g., deposits) in which case the attribute value would be "sum," but for other line items (e.g., closing balance), only the last quarter's value need be shown, in which case the attribute value would be "last." Similarly, if a minimum annual balance is desired for four quarters of minimum balances, only the lowest balance for all four quarters would be needed. Such a line item's li_aggregation attribute value would be "minimum." Possible accepted values include: "sum," "average," "minimum," "maximum," "first," "last," and "none."

IV.A.2. Reader, Parser and Processor

[0181] With reference back to FIG. **7**A, the RDML reader **704** may be an object within the RDML data viewer **100** which manages the process of finding an RDML document **102** (locally, on a LAN, or on a Wide Area Network such as the Internet), passes it to the XML parser **706**, relays error notices to the user, and coordinates the updating of other components states to reflect a rejected or damaged RDML document **102**. The user of the RDML data viewer **100** may initiate the download of an RDML document **102** in many different ways including: clicking on an RDML hyperlink (these are like any other hyperlink, except that the target document may end in ".rdm"), typing a ".rdm" URL into the "Address" box of RDML data viewer, or requesting the loading of the document in a macro. Also, while conventional HTML browsers have a cache of only HTML documents represented as the "history" of the browser, the browsers may only display one of these documents at a time. Given an URL address, the RDML reader **704** reads in Document Object Model ("DOM") compliant documents (e.g., RDML documents **102**), discussed below. The XML reader **704** may be implemented by a third-party set of Java classes, such as the XML4J parser developed and licensed by IBM, but others may also be used. The RDML reader **704** may cache multiple documents in RAM if they are compatible with the active data set. Not only are these documents immediately available, but sub-elements of the documents are available immediately because the data viewer **100** may maintain indexes of important data and metadata in the documents. Additionally, macros may be used to find specific elements in the document that is read in by the RDML reader **704**.

[0182] The XML parser **706** takes a serial stream of text characters from the RDML data document **102**, performs basic functions such as eliminating white space, dividing input into words and groups of words and searching for opening and closing characters (primarily "<" and ">"). The XML parser **706** used in the RDML data viewer **100** may also be a third-party set of Java classes, such as the XML4J parser developed and licensed by IBM, but other parsers may also be used.

[0183] The processor **708** receives the parsed text and creates a tree-shaped data structure of the data elements, matching the structure of the RDML DTD **702** hierarchy. The hierarchical structure conforms to the DOM Model, meaning that data is available in a standard form, and that a standard library of methods and functions are available for accessing data, editing elements, searching through nodes to find certain elements, and so forth. The XML DOM standard is controlled by the World Wide Web Consortium, and can be found at "http://www.w3.org/TR/REC-DOM-Level-1/".

[0184] The RDML Processor **708** generally performs three primary functions on the incoming parsed text to create an internal software object: error checking, structuring, and adding functionality. The error checking functions of the processor **708** simply compare the output of the parser **706** against the text expected as defined by the DTD **702**. If the incoming document does not conform, the processor **708** determines whether the defect is: (1) not critical, in which case a warning is sent to a log and work continues, or (2) critical, in which case work stops and an error message is sent to the routine that called the parser **706**.

[0185] The structuring function is a matter of assembling the text into a hierarchical data structure matching the hierarchy described in the DTD **702**. The target data structure may be a vector of vectors, or other collection of collections. When the data structure is created, it is "wrapped" in a software object (an "RDMLDoc" object) that adds an interface to the data so that other software objects can communicate with it. Most of the added functions ("methods") provide access to specific subsets of the data or particular elements or attributes.

[0186] The functions of the RDML processor **708** can be performed by the same class as the RDML Reader **704**, where the RDML reader **704** has been set up on a "callback" relationship with the XML Parser **706**. In that way, when the parser **706** gets a new element from the RDML document **102**, it informs the RDML reader **704** that it found the element and returns it to the reader. In such a way, the RDML reader **704** acts as a processor as well as reader (even though it may hand off the actual element handling to another class).

IV.A.3. X-Value Transformer and Line Item Set Types

[0187] Regarding the X-value transformer **710**, the term "X-value" refers to the fact that the fields of the input data records are plotted along the x-axis of the chart view **716** by default. (The values of each record for each field are plotted on the Y axis.) For example, a time series will, by default, be plotted in the chart year with the time periods plotted on the x-axis. When more than one data document is input, their data fields must be correlated before they can be presented together in a common view. The X-value transformer **710** determines what adjustments have to be made, and then accomplishes them.

[0188] Generally, the RDML data viewer **100** recognizes three different types of line item sets (i.e., (1) "time series," (2) "category," and (3) "X-Y Plot") which account for the majority of end user tables. The X-value transformer **710**, by recognizing these types, can automatically provide the correct display and transformation routines, saving the user the time and expense of changing a broad range of details. To give

an example of this, when a times series table is encountered, the data viewer **100** can recognize that the x-values must fit the permissible types of dates, check them, conform them, and format them, thus sparing the user the work. In one implementation consistent with the present invention, a line item set type is a required attribute of the line item set element **906**.

[0189] FIG. **11** shows the steps used by the X-value transformer **710** to store a new document in the primary data store ("PDS") **712** described below. Generally, the X-value transformer **710** determines whether a newly input data document is of the same type as the one(s) currently stored in the "active documents" list of the PDS **712**. Active documents are available for display in the tree view **720**, to be charted, to be added to the spreadsheet view **724**, and so forth.

[0190] First, the X-value transformer **710** receives a new document **102** (step **1102**). It then determines the type of the active documents in the PDS **712** (step **1104**). If the newly arrived document is the same line item set type as the active documents (step **1106**), it is added to them in the PDS **712** (step **1108**). If it is of a different type than the currently active documents in the PDS **712**, the user is notified that it does not match the currently active documents (step **1110**). The user may choose to reject the new document **102** (step **1112**), in which case the object is not added to the PDS **712** (step **1114**). If the user chooses to erase the currently active documents (step **1116**), the currently active documents are erased (step **1118**) and the new one is loaded (step **1120**). Otherwise, the new document **102** is placed in the PDS **712** as a "standby" document (step **1122**). Standby documents are available for providing data to scripts and macros, but do not interfere with the active document views. Optionally, if the x-value transformer **710** need not perform any transformations, the RDML reader **704** may store the document in the PDS **712**.

[0191] If the newly arriving document is of the same line item set type as the active documents, the X-value transformer **710** matches the data_x fields of the new document to the existing documents. They may be in a different order, may be spelled differently, be in a different form, or otherwise not immediately compatible. The X-value transformer **710** makes the necessary adjustment according to the type of line item set. For example, time series line item sets have elements which are ordered in time. One obvious incompatibility is that periods may be different. Often, one set of data is in years and the other in, for example, months. The X-value transformer **710** uses attributes of the line items to handle each correctly. However, monthly data cannot just be added up to produce a yearly value, for example, because the number might represent a non-additive value. For example, a line item might be "Ending Bank Balance," but adding up 12 monthly ending balances does not produce a year-ending balance. The line item provides a period-length attribute that specifies that it is a "period-end" value, and the X-value transformer **710** uses the last month only to create a yearly value. In another example, monthly "deposits" would be added together, and monthly "average interest rate" might be a "period-average." Each line item provides instructions on how it is to be handled in conversion to other periods; this is provided by the li_aggregation attribute.

[0192] Another change that might be made is in the date format. Some data sets might simply display the year ("YYYY"), others might use a standard date format ("YYYY-MMDD:HHMMSS.MSS"), or some other variant. The X-value transformer **710** puts these all into a common form.

[0193] The data viewer **100** additionally provides tags describing how it is to be handled in the event of a period widening/shortening, or a period shift. Numbers may be tagged as "sum," "median," "average," "last value," "first value" or a specified formula. The X-value transformer **710** and the data viewer **100** may also handle "period shifts," a related type of conformance. For example, a first data source may be based on a calendar year ending on December 31 while a second data source is based on a fiscal year ending on September 30. The RDML data viewer **100** may use the period_length attribute of the x_data element **924** to designate the period length of the data, in conjunction with the li_aggregation attribute of the y_data element. The latter attribute is used to estimate a conforming transformation.

[0194] Y-values, the data values in a line item, may change when the x-values have been conformed. For instance, if twelve months of "average interest rate" is aggregated to produce "annual average interest rate," the updated designation of the number that will appear in legends or axis titles changes. The data viewer **100** recognizes that the resulting values may possibly undergo a transformation based on unit, magnitude, modifier, scale, measure, and adjustment attributes. These attributes allow efficient and automatic interpretation, translation, manipulation and presenting of data in a line items. They further facilitate the automatic changing of text descriptions in charts and reports to be automatically changed by macros.

[0195] Additionally, to conform differing time periods in separate documents, the X-value transformer **710** and the data viewer **100** may prompt user assistance if needed. For example, a first data source may be denominated by fields such as "Week 1," "Week 2," etc., while a second data source is denominated by "April 4, 1999," "April 11, 1999," and so forth. The X-value transformer **710** recognizes this problem (and a broad set of similar circumstances), and presents a dialog box asking the user for the actual date that "Week 1" begins on.

[0196] The Category line item set type is a common type of line item set that is often referred to as a "crosstab." In this line item set type, the x-values are categories. On a chart, for instance, the x-axis may be divided into eight categories for eight companies, with the y-axis showing the values of revenues or profits. Sometimes matching the fields of different source documents by name is too dependent on wording, spelling, or language to permit efficient matching. The challenge for categories line item sets is to handle these differences in usage. For example, company income statements may start with a concept of "sales," but the actual words used may be "revenues," "total revenues," "gross income," or any other designation used in different languages, dialects, or industry-specific terms. To handle these line item sets, the X-value transformer **710** lines up categories from multiple data sets by first matching up any actual matches in spelling (ignoring cases in the default). Second, it looks at the class elements **930** to see if there are standard vocabulary tags; these standards may be different for different industries or uses. When dealing with companies, for example, the ticker symbol may be used as the matching tag. For instance, one data set may have a category for "Ford" another for "Ford Motor Company," and another for "F." All would be matched by the common presence of a tag <"F"> (Ford's ticker sym-

bol) in the class element **930**. If this fails to provide matches, the data viewer **100** presents the user with a dialog box with two lists of fields. Using "drag and drop" techniques, the user can quickly match the two sets of fields, and fields with no match are simply appended as new fields. In addition to creating a mapping dictionary based on text, class sets, and user input, the data viewer **100** can use a mapping file specified by a user or an input document to combine files automatically.

[0197] FIGS. **12**A, **12**B and **12**C depict screenshots of an X-Y plot **1202** in accordance with the present invention. Most commonly found in scientific statistical series, an X-Y plot **1202** by its nature treats every x-value as distinct. This display plots individual data points on the graph. The X-value transformer **710** is only required for collating only exact matches. The screenshot also displays a tree view **720** that corresponds to the data in the X-Y plot **1202** and a legend **1204**. As shown on FIG. **12**A, the X-Y plot **1202** displays the selected line item **1206**, and the legend **1204** changes as the line item selection changes. The FIGS. **12**B and **12**C show the X-Y plots **1202** resulting from the selection of different line items **1206** in the tree view **720**.

IV.A.4. Primary Data Store

[0198] FIG. **13** depicts a primary data store **712** and some objects which it stores. The primary data store **712** is a cache of loaded RDML documents **102** that may be implemented in a number of ways (e.g., as a vector, as a dictionary or hash table, or as some other collection of objects).

[0199] Once the X-value transformer **710** has determined an active or standby status for a newly arrived data document **102**, and made any necessary modifications to the x-values, it passes a new RDMLDoc object **1302** to the PDS **712**, which manages its communications with the various views or plug-in applications. This PDS **712** central storage allows the different views (**716**,**720**, **724**, and **728**) to have access to an object **1302** representing the original source data. The individual views (described below) make their own copies of the portions of the data that they need, and in whatever transformed form they require. The PDS object **712** generally does not perform transformations on data; it simply holds them, adds and removes them, and makes them available in a public interface to other objects. Table 1 below shows an exemplary class diagram of the PDS object **712**. Note that vectors are used to hold the RDML documents **102** in this implementation; it would also be possible to use a hash table or collection data structure.

TABLE 1

PrimaryDataStorage
−Active_RDMLDocs : Vector
−Active_RDMLLines : Vector
−Standby_RDMLDocs : Vector
−Standby_RDMLLines : Vector
+Add_RDMLDoc(rdmldoc : RDMLDoc) : void
+Add_RDMLLine(rdml_li : RDMLLineItem) : void
+getRDMLDoc(rdmldoc : RDMLDoc, Status : int) : RDMLDoc
+getRDMLLineItem(rdml_li : RDMLLineItem, status : int) : RDMLLineItem
+getNumRDMLDocs( ) : int
+getNumRDMLLineItems( ) : int
+clearRDMLDoc(rdmldoc : RDMLDoc) : void
+clearRDMLLineItem(rdml_li : RDMLLineItem) : void

[0200] In the class diagram, the upper section lists the object's variable names followed by their types. The lower section lists the method names with the argument name and type in parentheses followed by the method output type. As shown, the PDS **712** provides variables and methods for storing active and standby RDMLDocs **1302** and RDMLLineItems **1304**. The PDS **712** object includes methods to add, retrieve and clear documents and line items, in addition to methods for determining the number of documents and line items.

[0201] An RDMLDoc object **1302** is a full internal representation of the RDML document **102**. It contains as its central attribute the tree-structured data elements contained in the document's original tags and implements the DOM interface. Applications that work with DOM objects may also work with RDMLDoc objects **1302**. The RDMLDoc object **1302** provides a higher level interface for the different views of the RDML data viewer **100**. The Table 2 below shows a class diagram of an exemplary RDMLDoc object **1302** in accordance with the present invention.

TABLE 2

RDMLDoc
−txDoc1 : txDocument
+RDMLDoc( ) : RDMLDoc
+createDoc(filename : String) : TXDocument
+getAttributeValue(elementname : String, attributeName : String) : String
+getAttValue(lev1_tag : String, lev2_tag : String, lev3_tag : String, att_name : String) : String
+getData_xDefaults( ) : JCVector
+getLinkAttValue(element : String, index : int, attname : String) : Atring
+getLinkText(element : String, index : int) : String
+getNumLineItems( ) : int
+getNumLinksForElement(elementname : String) : int
+getRDMLLineItem(att_name : String, att_value : String) : RDMLLineItem
+getTXDoc( ) : TXDocument
+makeRDMLLineItem(li : Node) : RDMLLineItem
+parseCommaDelimString(in : String) : JCVector
+setTXDoc(txDoc_in : TXDocument) : void
+traverseDOMBranch(node : Node) : void

[0202] Described below are class methods shown in Table 2 of an RDMLDoc object **1302** in accordance with one implementation consistent with the present invention. First, RDMLDoc( ) is a constructor for creating an internal RDMLDoc object **1302**. The method "createDoc" reads in the file indicated by an input URL, parses it, and creates a new TXDocument which the user then usually assigns to this RDMLDoc object **1302**. A TXDocument is an object which implements the Document Object Model (DOM) interface. The TXDocument creates the DOM structure for the file and "wraps" it with various access and administrative methods. It is the DOM-compliant original representation of the document. The "setTXDoc" method sets the underlying TXDocument, and initializes object properties such as the number of line items, and "getTXDoc" returns the underlying TXDocument.

[0203] Whereas an RDML document **102** forms a tree of elements having attributes with values, the "getAttributeValue" method returns the attribute values for the named element, and "getAttVal" returns as a string the attribute value found at an inputted element name and attribute name. The "getLinkAttValue" method gets the attribute value of a hyperlink element, according to the element name and attribute specified and "getLinkText"gets the corresponding hyperlink text.

[0204] When called, "getNumLineItems" returns the number of line items in the RDMLDoc **1302** and similarly "getNumLinksForElement" returns the number of links for an element.

[0205] The "getRDMLLineItem" method supplies the first RDMLLineItem **1304** (described below) based on the value of a particular attribute. For example, specifying "li-ID" and "3" will return the RDML Line item in which the "li-ID" attribute equals "3." The method called "makeRDMLLineItem" takes the indicated node, assigns it to a new RDMLLineItem object **1304** and initializes the object.

[0206] The method "getData_Defaults" returns a vector of the default x-values. Furthermore, "parseCommaDelimString" takes a comma-delimited string as input and returns the values between commas as elements of a vector and returns a vector of the strings. Finally, "traverseDOMBranch" takes an input node as a parameter and then traverses from that node downwards, and at each node, an operation, such as finding an element with a particular name, may occur.

[0207] Similar to the RDMLDoc object **1302**, the "RDMLLineItem" **1304** is an object that provides high-level methods for retrieving data on a line item, any associated links or notes, and the attributes. The views of the RDML data viewer **100** work with RDMLDocs **1302** and RDMLLineItems **1304** to create their presentations. Table 3 shows a class diagram for an exemplary RDMLLineItem object **1304**.

TABLE 3

RDMLLineItem
−data_x : TXElement
−data_y : TXElement
−jcvdata_x : JCVector
−jcvdata_y : JCVector
−li : TXElement
−line_item_set_att : NamedNodeMap
+RDMLLineItem( ) : void
+get_jcvData_X( ) : JCVector
+get_jcvData_Y( ) : JCVector
+get_strX_Value(index : int) : String
+get_strY_Value(index : int) : String
+getAttributeValue(attributeName : String) : String
+getLinkAttribute(index : int, attName : String) : String
+getLinkText(index : int) : String
+getNumDataPoints( ) : int
+getNumLinks( ) : int
+initLineItem(doc : RDMLDoc, lineitem : Node) : void
+set_li(input: TXElement) : void

[0208] Described below are class methods shown on Table 3 of an RDMLLineItem **1304** in accordance with one implementation consistent with the present invention. Methods with the same name as described above in connection with the RDMLDoc object **1302** have the same general function although, since a line item is already specific to an element, the methods take different arguments because they typically do not need an element specified in the given arguments.

[0209] RDMLLineItem( ) is a constructor that creates an RDML LineItem object, and "initLineItem" initializes the line item to the values found in the RDMLDocument. The method "get_jcvData_X" d "get_jcvData_Y" return the x- and y-value vector for the indicated number of the line item. The "get_strX_Value" method and "get_strY_Value" return the x- and y-value at the number of the line item in the x_values vector as a string.

[0210] The "getNumDataPoints" method is called to receive the number of data points, i.e., the number of x-values, in a line item. The method "set_li" allows the calling routine to set the line item in the RDML document **102** that this particular RDMLLineItem is to represent.

[0211] Referring back to FIG. **7**A, in one implementation consistent with the present invention, the chart manager object **714** takes up to six RDMLLineItems **1304** from the PDS **712** and displays them on a chart displayed on the graphical user interface **734** and is typically used in conjunction with the tree view **720** and the macro panel **732**. When a user clicks a mouse on a line item in the tree view **720**, that line item is added to the chart. When the user clicks the mouse on a macro line in the macro panel **732**, the selected line items that are charted are transformed according to the programming of the macro. The chart manager **714** may be separated from the graphical chart view **716** to allow the ability to change chart software components easily should different or better graphic chart components become desirable.

Views

[0212] The data viewer **100** presents the user with a number of different views (**716**, **720**, **724**, and **728** as shown on FIG. **7**A) which the user may use to view the information in RDML documents **102** stored in the PDS **712**. These views include a chart view **716**, which shows graphical charts and graphs of the data, and a tree view **720** showing hierarchical representations of line items. Additionally, the data viewer **100** presents a spreadsheet view **724** which shows a data sheet similar to a spreadsheet, and a footnote view **728** which shows the text of footnotes associated with RDML documents **100**. The views are discussed in detail below.

IV.A.5. Chart View

[0213] Upon receiving RDML markup documents, the chart view transforms, formats, manipulates and displays data stored in the markup documents using the attributes describing the meaning of the data. The chart view uses the attributes of the numbers to, for example, facilitate the simultaneous display of different series of numbers of different types on a single chart and automatically display appropriate descriptive textual components.

[0214] As an example, the chart view automatically determines when a first series is in the "U.S. dollars" and the second series is in "French francs"; it may automatically place them on separate axes or automatically translate the units. It can also determine the titles for these axes and set the labels on the axes. The chart constructs itself automatically using the attributes of the individual elements of the markup document, and these actions may be initiated with a single mouse click.

[0215] FIGS. **14**A-F depict the chart view **716** in the top half of the screen, and the tree view **720** in the lower half. The chart view **716** has two primary components: the chart itself and the chart legend **1402**. The line item **1206** that has been selected in the tree view **720** is automatically graphed in the chart **716**. The chart manager **714** generally has three primary responsibilities: (1) collecting messages from the tree view **720**, macro panel **732** and main menu (not shown) regarding changes to make to the chart **716**, (2) obtaining the correct line items or macros from the PDS **712** or the macro manager **732**, and coordinating transformations to the data, and (3) managing the chart's data object (the "chart data" object **715**), which contains the data in the form in which it will be used in the chart, and the attributes of those line items.

[0216] Generally, the chart manager **714** handles updates and manipulations to the chart itself (e.g., axes, labels, etc.) while the chart data object **715** handles the plotting of the data on the chart **716**. The chart manager object **714** provides the information the chart data object **715** needs to update its internal data structures. Chart data **715** is a data model that is used by the central graphical chart **716** to paint itself, but other components also use the data: the footnotes, the chart legends and titles, and any macros that are operating on the data.

[0217] One way to visualize the role of the chart manager **714** (and its data partner, the chart data object **715**) is to view the steps of a method of a complete sample scenario: the user has selected a line item **1206** in the tree view **720** and the chart manager **714** is notified that this line item is to be added to the chart **716**. There are various ways to set up the chart data/chart manager architecture. One way described in detail below is to create the chart up front and then feed it changes in data (initialization, clearing, updating data series, etc.) A second general approach is to use the data to create a new chart upon every request for a change.

[0218] FIGS. **14**A-F will now be described in greater detail, and in particular, FIGS. **14**A and **14**B will be described in connection with FIGS. **15**A, **15**B, and **15**C, which illustrate steps of a method for updating a chart view **716** upon the selection of a line item **1206** in the tree view **720** in an exemplary scenario in accordance with the present invention. FIG. **15**A illustrates steps mainly involving the tree view **720** and graphical interface **734**, while FIGS. **15**B and **15**C illustrate steps mainly involving the chart data object **715** and chart manager **714** respectively.

[0219] As illustrated in FIG. **15**A, a user selects a line item **1206** in the tree view **720** on the graphical interface **734** (step **1502**). The tree view **720** obtains the ID of the selected line item **1206** (step **1504**) and removes any old macros that are applied (step **1506**). The chart manager **714** then deletes the last series (displayed data of a line item) from the chart view **716** to make way for the newly selected line item (step **1508**).

[0220] Referring now to FIG. **15**B, the chart data object **715** removes existing data from the chart **716** (step **1512**). It then obtains the RDMLDoc object **1302** from the PDS **712** (step **1514**) and the RDMLLineItem object **1304** from the RDMLDoc object (step **1516**). After doing this, the chart data object **715** normalizes the x-value data (step **1518**). For example, if one charted series displays data from 1961 to 1998, and the new one displays data from 1973 to 2005, the chart data object **715** ensures that the chart displays data from 1961 to 2005. The chart data object **715** then fills the x-axis **1404** with data (step **1520**) and fills the y-axis **1406** with data (step **1522**).

[0221] As shown in FIG. **14**B, a chart may have more than one y-axis **1406** charted at a time, (i.e., a different y-axis on either side of the chart) to display multiple line items simultaneously. Thus, the chart data object **715** further marks which y-axis the series is on (step **1524**), and if it is on a Y2 axis **1408** (a second y axis) (step **1526**), it adds that axis (step **1528**). The chart data object **715** sets the number formats for the axis labels **1406** and **1408** (step **1530**) and sets the number precision (step **1532**). Finally, it updates the footnotes (step **1534**) and runs any macros that are applied (step **1536**).

[0222] Referring now to FIG. **15**C, the chart manager **714** then sets the Y1 title (step **1538**) and the Y2 title (step **1540**) using line item attributes. After that, it updates the series styles (step **1542**), the chart title **1410** (step **1544**), the legend **1402** (step **1546**), and the x-axis **1404** (step **1548**). After these updates, and the chart manager **714** updates the number precision (step **1550**), the y-axis **1406** (step **1552**) and the chart types (i.e., area, bar, stacked bar, line, pies, points, etc.) (step **1554**). Subsequently, it updates the footer **1412** (step **1556**) and sets the maximum x-value to the extent of the last used value, disposing of blanks on the right side of the chart **716** (step **1558**). Finally, the graphical interface **734** repaints the graphical chart **716** with the newly created updates (step **1560**).

[0223] The chart manager **714** and chart view **716** can chart different series types on a single chart and handle transformations automatically. Because two (or more) data series may be placed on the chart **716** from different source documents **102**, they are synchronized for purposes of placing them on the common graph. The chart manager **714** uses data_x elements or the metadata tags to automatically transform data to permit different series types to appear together on a chart. It recognizes, for example, when a first series is in "US Dollars" and a second series is in "French Francs"; it makes arrangements automatically to place them on separate axes. There is no need for the user to go through a charting "wizard" or to find, understand, and translate the various units, titles, and adjustments. One click on each of the series' lines in the tree view **720** (potentially with a modifier key (e.g., the CTRL key) depressed) instructs the chart view **716** to construct itself given the metadata of the individual elements. The chart manager **714** and chart data object **715** consider and take into account the following in updating the chart: the unit type, magnitude, scale, modifier, measure, y-axis title, chart title, chart footnote, precision, number format, chart type (line, bar, etc.), legend and colors of the various components.

[0224] The data viewer **100** also permits the adding of a series to a chart using a single click or command. Adding a series to a chart increases the number of series displayed on the chart. In conventional spreadsheets, charting programs, and data graphical interfaces, this task requires the user to either rebuild the whole chart through the wizard, fill in a dialog box with information on the new series, or add the numbers by custom programming. When the data viewer **100** adds the new series to the chart with a single mouse click. The existing data is maintained as it was, and any necessary changes to the chart's type, format, scale, etc. is made automatically by the chart manager **714** and chart view **716** to accommodate the new series.

[0225] Just as a series can be added with one mouse click (or one command from the menu), so can it be removed. There is no need for the user to worry about accidentally deleting something, as no actual information is lost from the data viewer **100**. It can always be added back to the chart **716** with a simple mouse click.

[0226] The chart view **716** also supplies an expandable legend **1402** as shown on FIG. **14**A. A significant problem for most users of spreadsheet programs has been the inability of the user to control the size, format, and handling of the legend **1402**. The result is that charts usually end up with legends such as "MSFT" and "SUNW," rather than longer descriptions with multiple colors and fonts, word-wrapping and other readability enhancements. The chart view **716** chart provides legends that (1) can grow to unlimited sizes, (2) support word-wrapping, (3) can contain multiple fonts, (4) can contain multiple font types (bold, italics, normal), and (5) can contain varying colors for emphasis. If the legend information (typically stored in the li_legend attribute) for a line

item is too long for the legend box on the chart, the information may word-wrap and scroll to accommodate the additional information.

[0227] The chart view **716** permits further convenience by automatically specifying the y-axis title **1414**. Current spreadsheet and charting programs require the user to provide a y-axis title, usually through a chart wizard or by specifying a location to look up a title. The RDML shifts this burden to the data originator, who is in a better position to accurately specify the description of the y-axis values. The y-axis title **1414** specified by the data originator is placed in an attribute field (y_axis_title) of the line item element tag and is used by the chart view **716** as the default y-axis title **1414** when the line item is added to the chart view **716**.

[0228] Often, however, the user wants to make a change to the numbers and display the transformed series on the chart **716**. In this case, the default y-axis title **1414** may no longer be correct. Rather than require the user to manually figure out what the new value description is (a process that could take several minutes or longer with current analytic programs), the chart manager **714** and chart view **716** data automatically generates a new y-axis title **1414** upon transformation of values using the information provided in the modified unit, magnitude, modifier, scale, measurement, and adjustment attributes of the line item **1206**.

[0229] For example, suppose a first series is charted as "$ in Millions," and the user applies a macro that divides every number in the series by 1,000. The chart manager **714** automatically creates a new y-axis title **1414** of "$ in Billions." Number transformations can lead to quite complicated transformations of the y-axis title **1414**. A user may multiply a first series ("Gallons in Millions") by a second series ("US $ per Gallon"); the result will be a series of numbers, a third series ("US $ in Millions"). If there are ambiguities, the data viewer **100** presents the user with a dialog box displaying all the known information regarding the quantities involved and requests that the user supply a title.

[0230] Similarly, the chart manager **714** and chart view **716** can automatically generate the x-axis title and chart titles **1410** using the metadata attributes. In addition to generating y-axis and x-axis titles, the data viewer **100** automatically performs the task of creating a new chart title **1410** when the charted series are changed or when multiple series are added to the same chart. For example, a first series has a default chart title of "Total Sales," a second series has a default chart title of "Total Expenses," and a third series has a default chart title of "Total Sales." The data viewer **100** will create a combined chart title of "Total Sales; Total Expenditures" by combining the dissimilar elements, and eliminating the duplicate elements.

[0231] Three examples illustrate other types of automatic title manipulation. In the first example, suppose a chart has two series placed on it: Series A has a title of "GDP" and a legend of "China", and Series B has a title of "GDP" and a legend of "Malaysia". If both are put on the chart, the titles will duplicate each other. In one implementation consistent with the present invention, duplicate titles are removed such that the title for this chart will be simply "GDP". Because the series legends are different, the legend on the side of the chart will have two entries: "China" and "Malaysia".

[0232] As a second example, suppose the legends are duplicative: Series A has a title of "China" and a legend of "GDP", and Series B has a title of "Malaysia" and a legend of "GDP". Because both legend entries would be "GDP", there may be confusion about which legend applies to which line on the chart. In this case, the data viewer **100** transposes the legend and chart title entries such that the result is the same as in the first example above; the title of the chart is "GDP" (the duplicate is removed) and the legend entries are "China" and "Malaysia".

[0233] Finally, in a third example, suppose the series have different titles and different legends. Series A has a title of "GDP" and a legend of "China", and Series B has a title of "National Savings" and a legend of "Malaysia". The legends are left as is, and a new chart title is created by appending one to the other separated by a ";". The chart title on the display thus becomes "GDP; National Savings", and the first legend becomes "GDP—China" and the second legend becomes "National Savings—Malaysia". All three of these changes are string manipulations (selecting and/or appending).

[0234] The chart manager **714** and chart view **716** can also automatically trim beginning and ending x-values **1404**, thus relieving the user of the need to trim null leading and trailing values from charts. In conventional spreadsheet and charting programs, chart pointers must be recreated or manually adjusted when the underlying data is enlarged or shortened. For example, if a series is charted that runs from 1990 to 1998 and it is replaced by data from 1990 to 1996, there would be two blank spaces at the right side of the chart. The data viewer **100** and chart manager **714** avoid this and similar problems by handling missing or null values at the front or back of line items as indications that the chart should be automatically restructured.

[0235] The chart manager **714** also automatically formats the x- and y-axis labels **1404** and **1406**. RDML shifts the burden of formatting the numbers on the x-axis **1404** and y-axis **1406** from the user (of which there may be thousands or millions, each reformatting the numbers manually one or more times) to the data originator (of which there is one, who only has to do it once.) The format templates are regular expression strings found in current spreadsheets and programming languages. The data viewer **100** uses the formatting strings for the axis labels on the chart view **716**, for the numbers in the tree view **720**, and as defaults for the numbers in reports. The formatting templates are automatically changed if a macro moves the numbers outside of the precision range that is legible on the chart **716**, or out of a format that makes sense in the tree view **720** or in a report.

[0236] As stated previously, one of the RDML line item element attributes is the precision of the number, the number of significant digits to be displayed in a chart. Unlike conventional products, which leave this entirely up to the user to figure out, the data viewer **100** uses the specified precision to set the scale of the y-axis **1406**, and the format and precision of its labels and tick marks.

[0237] Additionally, the chart manager **714** automatically creates and removes a second y-axis **1408** as shown on FIG. **14**B. A chart with two dissimilar series plotted on it will require two axes. The y-values may not be of the same units, measures or scales. A user might, for example, have plotted a series denominated "$ in Millions" and then want to add to the same chart **716** a series denominated "% of GDP," and these two series cannot share a common y-axis. Chart manager **714** recognizes this incompatibility, creates a new y-axis **1408**, and directs all subsequent formatting, macros, etc., to the proper axis. Current spreadsheets and charting programs require that the user restructure the chart with a charting wizard (entailing many directives to be entered, and,much

trial and error to get the various scales, colors, etc., correct), or by custom programming. The data viewer **100** automates this process, creating and formatting a new axis if required by the specifics of the unit and scale attributes of the line items. If the series is removed from the chart, the associated axis is removed and the various scales, colors, etc., of the remaining series are updated to make the chart readable immediately.

[0238] Table 4 shows a class diagram of the chart manager **714**.

TABLE 4

ChartManager
−chart1 : JCChartComponent
−chart_data : ChartData
−chart_legend : ChartLegend
−chart_title : JCTitle
−CDV1 : ChartDataView
−CDV2 : ChartDataView
−DS : DataStore
−LineColors : JCVector
−mainFrame : MainFrame
−series1 : ChartDataViewSeries
−series2 : ChartDataViewSeries
−x_value_labels : JCVector
−xaxis : JCAxis
−xtitle : JCTitle
−y1axis : JCAxis
−y1title : JCTitle
−y2axis : JCAxis
−y2title : JCTitle
−yLabelGenerator1 : YLabelGenerator
−yLabelGenerator2 : YLabelGenerator
+addSeries(key : String) : void
+addY2Axis( ) : void
+ChartManager(mainFrame : MainFrame, chart_comp : JCChartComponent, legend : ChartLegend) : void
+checkYAxisTitle(series : int, y1title : JCAxisTitle, y2title : JCAxisTitle) : int
+deleteLastSeries( ) : void
+deleteSeriesAfterFirst( ) : void
+getAddSeriesFlag( ) : boolean
+getChartData( ) : ChartData
+getYAxisTitle(series : int) : String
+initChart( ) : void
+markWhichYAxis(num_series : int) : void
+replotChart( ) : void
+replotSeries( ) : void
+resetChart( ) : void
+setAddSeriesFlag(flag : boolean) : void
+setChartType(type : int) : void
+setDataStore(ds : DataStore) : void
+setStartPeriod(sp : String) : void
+updateChartTitle( ) : void
+updateChartTypes( ) : void
+updateFooter(num_series : int) : void
+updateFootnotes( ) : void
+updateLegend( ) : void
+updatePrecision( ) : void
+updateSeriesStyles(num_series_local : int) : void
+updateXAxis( ) : void
+updateYAxis(num_series_local : int) : void

[0239] Class methods of a chart manager object in accordance with one implementation consistent with the present invention are described below. ChartManager( ) is a constructor for the chart manager object **714**, and "initChart" initializes the chart to be empty, and "getChartData" gets the chart data object **715**.

[0240] The method "addSeries" adds a series to the chart while "deleteLastSeries" removes the last added series. Similarly, "deleteSeriesAfterFirst" deletes all series beyond the first series.

[0241] A series flag is set to "true" if the next series is to be added in addition to the already charted series. A "false" flag tells the chart to erase the last current series and replace it with the new series. The methods "getAddSeriesFlag" and "setAddSeriesFlag" retrieve and set this flag.

[0242] The method "getYAxisTitle" returns the y-axis title, and "checkYaxisTitle" checks the current y-axis title to see if the newly plotted series is to be on the current axis, or if a new axis is to be created. "AddY2Axis" adds a second y-axis to the chart if needed. The method "markWhichYAxis" tells the ChartData object which axis the new line item has been plotted on.

[0243] The method "resetChart" resets the chart to the state it was in when the data viewer **100** started while "replotChart" updates the physical aspects of the chart. Similarly, "replotSeries" replots a series due to changes.

[0244] The "setChartType" method tells the chart manager what chart type to display upon calling replotChart, and "setDataStore" tells the chart manager what data store object **712** it will be dealing with. If the data is a time series, "setStartPeriod" sets the internal variable for the starting period of the chart. Finally, the update methods each update the corresponding aspect of the chart in response to potential manipulations or changes, e.g., "updatePrecision" updates the precision of the chart.

[0245] Table 5 shows a class diagram of the chart data object **715**.

TABLE 5

ChartData
−chtData : JCVector
−chtHeader : JCVector
−cm : ChartManager
−originalPlottedYear : String
−start_period : String
−zeroData : String[ ][ ]
+addSeriesToChart(ds : DStore, key : String) : void
+decrementNumSeries( ) : void
+deleteLastSeries( ) : void
+deleteSeriesAfterFirst( ) : void
+fillXAxis_CT(rdml_li : RDMLLineItem) : void
+fillXAxis_TS(rdml_li : RDMLLineItem, yearsDiff : int, sizeDiff : int) : void
+fillYAxis_CT( ) : void
+fillYAxis_TS(rdml_li : RDMLLineItem, start : int, yearsDiff : int, sizeDiff : int) : void
+getAddSeriesFlag( ) : boolean
+getChtData( ) : JCVector
+getChtHeader( ) : JCVector
+getChtHeaderElement(series : int, element : String) : String
+getDataInterpretation( ) : int
+getDataItem(row : int, column : int) : Object
+getDifferencesInX(rdml_li : RDMLLineItem, yearsDiff : int[ ], sizeDiff : int[ ]) : void
+getName(series : int) : String
+getNumRows( ) : int
+getNumSeries( ) : int
+getPointLabels( ) : String[ ]
+getRow(row : int) : Vector
+getSeriesLabel(series : int) : String
+getSeriesName(series : int) : String
+getStartPeriod( ) : String
+incrementNumSeries( ) : void
+normalizeValues(rdml_li : RDMLLineItem, xory : int, yearsDiff : int, sizeDiff : int) : JCVector
+setAddSeriesFlag(input : boolean) : void
+setChtData(jcvin : JCVector) : void
+setChtHeader(jcvin : JCVector) : void
+setChtHeaderElement(series : int, element : String, value : String) : void

TABLE 5-continued

ChartData
+setDataItem(row : int, column : int, c : Object) : boolean +setNumSeries(new_num : int) : void +setOriginalPlottedPeriod(in : String) : void +setStartPeriod(in : String) : void +zeroChtData( ) : void

[0246] Below are class methods shown in Table 5 of a chart data object in accordance with one implementation consistent with the present invention. Methods having names that are the same as methods in the chart manager are not described because they perform the same function on the data alone.

[0247] The chart data object uses the methods "fillXAxis_CT," "fillXAxis_TS," "fillYAxis_CT," and "fillYAxis_TS" to fill the x- and y-axes of time series and chart data sets. The methods "decrementNumSeries" and "incrementNumSeries" change a counter storing the number of series on the chart.

[0248] The method "getChtData" returns a vector of chtData, which is a vector of vectors: each element of the outer vector is a vector of data for one line item. The "getChtHeader" method returns a vector of chtHeader, which contains a vector of header information for each line item. This vector is a list of the values of the attributes of a line item, e.g., magnitude, title, etc., and "getChtHeaderElement" gets the value of a particular element from chtHeader for the indicated series.

[0249] Operating on data sets, "getName" returns the data set name, and "getNumRows" returns the number of rows in the data set. The method "getRow" returns one row of a series while "getSeriesLabel" returns the label. The "getDifferencesInX" method aligns the time periods for time series charts, and "getNumSeries" returns the number of series in the num_series variable. Many of the get methods have corresponding set methods that set the value instead of receiving it.

[0250] The chtData variable is a vector of vectors (each sub-vector is the data for one series), and "getDataItem" returns the data value in a particular row and column of chtData. Used by the constructor, "zeroChtData" posts an empty chart. The "getPointLabels" method returns an array of strings, each of which is a point label of chtData

[0251] For a time series, "getStartPeriod" retrieves the start period of the time series, and "normalizeValues" normalizes values upon the addition of a series to the chart. The method "getDataInterpretation" returns either "array" or "general" to describe what form the data source structure is in. (A returned value of "array" is for Times Series and Category data—which share x values—, and a returned value of "general" is for XY data, in which X values are generally independent.)

IV.A.6. Tree View

[0252] Referring back to FIG. **14**A, this screen shot further contains the tree view **720** on the lower half of the screen. The tree view **720** presents a hierarchical view of the data. The tree view **720** serves a different purpose than "datasheet view" of conventional spreadsheets and database management systems. It shows the numbers in their context visually. The user can see the dependency relationships, identify from icons and visual clues how the different line items are related to their parents, peers, and children. The "Units" column **1416** prominently displays the units, scales, magnitudes, etc., of each line item, an important display in mixed data sets, where the unit context changes from line item to line item.

[0253] Each line item in the various active RDML documents **102** is displayed in the original order. In the tree view **720**, each RDML document **102** begins a new top level node. The information displayed in the tree view **720** is a summary of important data from and about the line item, not a display of all the data points as would be found in a typical spreadsheet view. Instead of presenting a potentially confusing matrix of raw data digits that make the discerning of patterns difficult, the tree view **720** shows, in one implementation, the following information for each line item: legend **1402**, units **1416**, three user-selectable representative data points **1418**, and one or more summary columns **1420**. In the example on FIG. **14**A, there is some important documentation **1416** (description, units), some representative data **1418** (in this case, three years worth), and a summary data column **1420** (in this case, the sum of all the data points). The first column **1416** displays the legend of the line item. This is the plain language description; it is repeated in each view where identification of the line item must be made by a human.

[0254] The representative data columns **1418** in the tree view **720** give the user visual clues as the relative importance, the types, and the format of the line items. The RDML data viewer **100** permits the user to select different fields to be displayed. For example, one user might want to see "1940, 1970, 2000" to get a sense of the long term trends, while another might only wish to see "1998, 1999, 2000" to see the recent trends.

[0255] The summary column **1420** allows the user to choose a statistic that is either desired to understand the lines and their context better, or that is desired for purposes of sorting the columns from greatest to least or vice versa. Any of the columns can be sorted simply by clicking on them. The summary column provides much easier statistics for the user than database or spreadsheet formulas because the RDML data viewer **100** provides one-click selection of statistical methods, thus removing the need to write formulas, adjust for missing values, handle nulls in the denominators, etc. Some examples of summary statistics include: (1) sum, (2) average (3), median, (4) minimum, (5) maximum, (6) moving average, (7) variance/standard deviation, (8) % difference (selected periods or categories), (9) % of parent, (10) % of specified line item, (11) correlation with parent, and (12) custom formulas. For each of these statistical measures, the RDML data viewer **100** provides a dialog box in which the user can adjust the assumptions. For example, the "moving average" can be for one period, five periods, ten periods, and so forth.

[0256] The tree view **720** emphasizes that line items are the primary data unit in the RDML data viewer **100**, as opposed to single numbers as are found in spreadsheets as cells. Since each line item **1206** is an object, the RDML data viewer **100** may be thought of as an object-oriented spreadsheet. The icons **1422** for each line item identifies that line item's context. For example, a "+" icon **1422** indicates that adding that line item to its peers will produce the parent line item. This feature addresses a shortcoming of spreadsheets and database datasheet views: the inability to view formulas and data at the same time. It shows the user how the numbers are related to one another.

[0257] Conventional database management systems, spreadsheet and numerical analysis tools have no built-in indication of how one record is related to another. In relational

databases, the position or row may have no relevance to its data. RDML and the tree view **720** changes this by making the position of a line item in a set a usable piece of information by a user, and icons **1422** may visually designate the relationship of a line item to its parent node.

[0258] In one implementation consistent with the present invention, the following values are used for relationship icons: (1) plus, (2) minus, (3) times, (4) divide, (5) equals, (6) computed at, (7) member, (8) collection, (9) child, (10) parent, (11) memo, (12) general, (13) note, (14) none, and (15) root.

[0259] Sub-line items may add up to the parent line item (or may be modified by other relationships of their sibling line items.) "Plus" may add to siblings while "minus" subtracts from them. For example, a line item called "Net Sales" may have two children: "Total Revenues" and "Cost of Goods Sold." If "Total Revenues" has an li_relationship attribute of "PLUS", and "Cost of Goods Sold" has one of "MINUS", then the treeview **720** can show that Net Sales is equal to Total Revenues minus Cost of Goods Sold. "TIMES" and "DIVIDE" show multiplication and division of line items respectively.

[0260] "EQUALS" is the same as "plus," but shows the result of calculations of line items above it in order. "COMPUTED AT" is used for assumptions, such as percentages, interest rates, etc., while "MEMBER" denotes that the line item is simply a member of a collection of line items denoted by the parent line item. In this case, no assumption is made regarding arithmetic relationship, if any.

[0261] "COLLECTION" denotes that the line item has child members one level directly below it and denotes the concepts of sets or collections. "CHILD" illustrates that the line item is simply a "child" of the "parent" line item. It implies a sort of descent, derivation, or inheritance. No assumption is made regarding arithmetic relationship, if any.

[0262] "MEMO" is a line item that might be of interest to those looking at the sibling line items, but which is not necessarily related to the siblings, while "GENERAL" is a generic designator. "NOTE" is usually used for line items with text values, and "NONE" denotes that no relationship is implied. "ROOT" states that the line item is the root line item.

[0263] The tree view **720** also provides other capabilities. It allows the user to chart multiple line items **1206** by holding down the "shift" key. Although number browsing can be done in the data viewer **100** with a mouse, it is also possible for users to graph line items using arrow keys. When the focus is on the tree view **720**, navigating up and down with the arrow keys automatically chart the selected line item **1206**. If the "shift" key is held down, the succeeding data series will be added to the chart, rather than just replacing the previously selected series.

[0264] FIG. **14**C shows that, in one implementation consistent with the present invention, when a user right-clicks on a selected series, a pop-up menu **1424** is displayed showing the different types of documentation available. As shown in FIG. **14**D, selecting "description" shows a window **1426** containing information about the particular series, with the information being transferred from the tag form to a plain language, user-friendly format.

[0265] FIG. **14**E shows that, in one implementation consistent with the present invention, the user may graph multiple line items simply by selecting different "checkboxes" **1450** in line items in the tree view **720**. In this implementation, the collection of selected line items is passed to the chart data object, which is then charted by the chart manager **714**.

[0266] In one embodiment of the present invention, the selection of a contiguous set of lines that is less than all the lines in the tree view **720** is facilitated through a series of mouse events. First, a mouse down event is performed over a line (e.g., Bristol Center). The mouse is then dragged down (highlighting lines in the process) to the last line to be included in the group (e.g., Hamlet West Center). By delaying the mouse up event while retaining the cursor over the last line to be included, the user is able to signal the system (and the system is able to detect) that all elements in the selected/highlighted group are to be added. Accordingly, the system checks their corresponding check boxes.

[0267] The tree view **720** further provides an easy way of creating an RDML document **102** through drag-and-drop techniques. In conventional spreadsheet and DBMS applications, it is possible to create new tables from existing ones by selecting the data rows and cutting and pasting them, or by writing a SQL query. In the tree view **720**, creating a new RDML document **102** complete with necessary documentation can be performed by dragging and dropping the desired line items to an icon that represents the new document. Macros may also be created and manipulated in the same manner.

[0268] The data viewer **100** may also set macros to be executed automatically as the selected line items are changed. Known as "locking" of macros, this permits browsing through data in a transformed state.

[0269] FIG. **14**F shows that a line item may have a visual link associated with it that can be activated by a user. Upon activation of the link **1430**, a list of associated hyperlinks **1432** is displayed for selection by the user. The link **1430** itself may indicate the number of associated hyperlinks **1432**. The user may then select any of the hyperlinks to access the corresponding web site.

IV.A.7. Spreadsheet View

[0270] FIG. **16** depicts a screen shot that shows the spreadsheet view **724** in the lower half and the chart view **716** in the top half. The ultimate goal of many users is to get a set of numbers arranged into a format that will fit into an existing spreadsheet of theirs. While many programs offer cut and paste transfer of numbers from a source application to a target spreadsheet, such an approach still leaves the user with the task of manipulating, normalizing, aligning and transforming the data. A cut-and-paste operation is therefore usually followed by the manual recalculation and retyping of every number. The RDML data viewer **100**, by contrast, allows the user to make the necessary data transforms with mouse-driven operations before loading the numbers into a spreadsheet.

[0271] Referring to FIG. **16**, as line items **1206** are added to and subtracted from the chart view **716** or tree view **724**, they are added to and subtracted from the spreadsheet **724**. In addition, any changes to the lines plotted on the chart view **716** (as the result of applying a macro or combination of macros) are immediately reflected in the numbers in the spreadsheet **724**. This provides one-click addition of information to the spreadsheet view **724**. Therefore, the way to copy data into the spreadsheet is simply to add them to the chart **716**. It is also possible to copy an entire data document **102** or collection of data documents from the tree view **720** to the spreadsheet view **724**, making any desired macro changes in the process.

[0272] Furthermore, RDML documents **102** may be created directly from the spreadsheet view **724**. Whereas a data table is shown in the spreadsheet **724** (either created from another RDML document **102** or typed in from scratch), an RDML document may be created from that data in from the default specified by the user. This performs a task similar to an XML editor, but does so in a table format for the data, which is a more natural way to enter tabular data, not in the tree structure of current XML editors.

[0273] The spreadsheet view **724** may also directly read Internet data using a URL **1602**. It will except formulas that use Xpointers (used by Xlink to specify destination of a link) to read in data from remote RDML documents **102**. In this manner, data may be incorporated into a single spreadsheet from a number of sources with no need to prepare query or provide custom programming code.

[0274] As shown in the class diagram below in Table 6, the spreadsheet manager **722** may be a simple object; the chart manager/chart data **714** and **716** combination may be the actual repositories of the data. The chart manager **714** feeds data to the spreadsheet manager **722**, which places the data in the correct cells. The spreadsheet manager **722** communicates directly with a graphical spreadsheet object **724**, which in the case of the RDML data viewer **100** may be a third-party component.

TABLE 6

SpreadSheetManager
−gridControl : GridDataSheet −chartmanager : ChartManager +fillFromChart( ) : void

IV.A.8. Footnote View

[0275] FIG. **17** is a screenshot which shows the footnote view **728** in the lower half. Generally, footnotes are a type of extended documentation that often get lost in transmitting and displaying numbers. Each line item has, as an attribute, a text string providing short footnotes which may be accessed by a mouse click (that is, by clicking the "Footnotes" tab **1702** at the bottom of the data viewer **100**). As with the spreadsheet view **724**, the default value is for only the plotted series to have their footnotes displayed. However, it is possible to display all of the footnotes of an RDML document **102** in the spreadsheet or style sheet report views.

[0276] The footnotes in the footnotes view **728** are intended to be simple, important reminders about the data. Typically these include usual periods (a fiscal year), adjustments, special problems and so forth. By default, the footnotes view **728** also shows the source of the RDML document **102** and the original underlying data. In one implementation consistent with the present invention, anything requiring more than 255 bytes is represented in an HTML page for which there is a hyperlink in the line item. These longer footnotes may be displayed in the HTML window as HTML documents.

[0277] Furthermore, as the user adds and subtracts series from a chart, the footnotes are automatically updated from the source data, even if there are multiple source documents. The footnotes in the RDML "Footnotes" tab also automatically update their numbers and labels to match the chart. This is in contrast to current spreadsheet and charting programs, which require that the user, not an automated lookup routine, supply the footnotes.

[0278] The macro manager **730** manipulates and implements macros in the data viewer **100**. Macros allow a user to apply transformations or calculations to line items on a one-click basis, instead of having to write formulas or queries.

IV.A.9 Tagging Wizard

[0279] The data viewer **100** may also create XML and RDML documents **102** from spreadsheet files. To this end, it may use a spreadsheet "wizard" to create tagged documents from a table of data in a spreadsheet. In one implementation consistent with the present invention, a wizard (using at least one dialog box) is created in a scripting language (e.g., Excel Visual Basic for Applications) allowing tabular data in a spreadsheet (e.g., Excel) to be used as the source for creating a tagged text document in the RDML format.

[0280] FIG. **21** shows a flowchart illustrating steps used in a method for tagging information from spreadsheets in accordance with the present invention. FIGS. **22**A-D depict exemplary screen shots for different stages in the document creation process.

[0281] FIG. **22**A shows that the user makes the data ready in tabular form (step **2102**). Each row will become one line item; the first row **2202** will become the data for the "data_x" element **924**. The first column **2204** will populate the "li-legend" attributes of the respective line items. Note that most tabular data is already essentially in this form: the category (or time period) descriptions run across the top, the plain-language line item descriptions run down the left, and the values themselves fill the table.

[0282] The user then highlights the legends in the left most column **2204** and opens the first dialog box **2206** (step **2104**), shown on FIG. **22**B, which will insert new columns for information in front of the data table, each column containing one type of attribute (step **2106**).

[0283] FIG. **22**C shows that pressing "OK" on the dialog box **2206** creates the column and fills in the default data (step **2108**). The wizard inputs the desired default values, saving most of the tedious typing, and the user checks the columns **2208** to see if changes need to be made. Appendix F shows exemplary code for routines that perform those functions. For each attribute, a column is added to the spreadsheet, the correct value of the attribute is selected (e.g., blank, hand-worded, or taken from the appropriate field in the dialog box), and the correct number of cells are filled with that value in the appropriate column **2208**.

[0284] FIG. **22**D shows that the user then brings up the document creation dialog **2210** (step **2110**). The user first uses the first entry field **2212** to specify the range of the data table (including the attribute columns). The "default" data file will be used to provide defaults for the rdmldoc-header element **904** values, as well as other elements and attribute values in the line_item_set element **906** (step **2112**). Finally, the user fills out the remaining fields and presses "OK", which causes the tagged RDML document **102** to be created and saved (step **2114**). As would be appreciated by one of ordinary skill in the art from this disclosure, the information gathered in the exemplary dialog boxes could instead be gathered in a single dialog box before creating RDML-compliant data.

[0285] Appendix G provides code used in one implementation to create an RDML document **102**. Generally, the process comprises steps of: (1) opening file and buffers for writing, (2) calling an element-creation method for each element

in the DTD **702** which can be nested within others, and (3) saving and closing the files when finished.

IV.A.10. Aspects of RMDL Markup Documents

[0286] RDML is designed to be used to describe numbers across industries and domains. To do so, it provides a basic set of tags and a matching vocabulary to describe six aspects of a table of numbers: (1) value, (2) structure, (3) format, (4) semantics, (5) provenance, and (6) measurement.

[0287] Value denotes that numbers are transmitted as strings, with additional tags to define their data type, degrees of precision, handling of missing values, handling of nulls, and other directives to the end application.

[0288] Structure refers to a structuring of the data in within a table. RDML permits records to be arranged hierarchically within a table. Although not a standard approach for relational tables, this permits multiple levels of information to be placed in a single two-dimensional table. Users desire this, for example, when viewing financial statements, where a single line item (e.g., "Equipment leasing") may have several sub-components ("Autos," "Trucks," "Office Equipment.")

[0289] Format allows the application to present users with numbers in human readable form. The tags specify default formats for numbers, internationalization issues such as comma/decimal point handling, and default legends and chart titles. These formats may be changed by the users at run time.

[0290] Semantics refers to the fact that RDML provides generic tags in which indicators of the "meaning" of the numbers, including the vocabularies of other SGML and XML markup languages, can be placed. This allows RDML to act as a "wrapper" for data from other markup language documents. Semantic meaning is also conveyed in text-based attributes: legends, titles, labels, footnotes, etc.

[0291] Provenance is the documentation of various elements. RDML elements include information on the source of the data, who marked it up, timestamps and link addresses, and licensing information, etc.

[0292] Finally, in the context of generic numbers, "Measurement" refers to the characteristics necessary to describe the measurement aspects of the domain the number is taken from: units ("meters", "feet"), magnitude ("millions", "billions"), modifiers ("Adjusted for inflation, 1997 index"), and so forth. This permits macros to ensure the results of any calculation are adequately derived and described to the end user.

IV.B. Graphical User Interface and HTML Browser

[0293] The screen shots of FIGS. **14**A-D, **16** and **17** have been of the graphical user interface ("GUI") **734** which has several responsibilities. Generally, it creates itself and other visual components upon start-up of the application, and provides a central storage place for a minimal number of global variables of the application (such as file directories, etc.). Further, it responds to user actions, such as mouse clicks and keyboard shortcuts, and repaints the screen, or portions of the screen, at appropriate moments.

[0294] The HTML browser **736** may be a third party component which displays HTML files. Although this browser has been designated as an HTML browser, one of ordinary skill in the art would appreciate from this disclosure that other browsers (e.g., an XML browser) can likewise be used. This component provides basic web-browsing capabilities and a way to view hyperlinks for RDML documents **102**. Additionally, it acts as a display window for certain pages generated by the RDML data viewer **100** (such as RDML document source code, chart documentation, etc.)

IV.C. Reusable Macro Markup Language

[0295] FIG. **18** graphically shows elements of the RMML Document Type Definition **1800**. In one implementation consistent with the present invention, RMML documents **104** conform to the rules provided by the DTD **1800**. In accordance with one implementation of the present invention, an RMML DTD **1800** is shown at Appendix D. Attributes and elements of the DTD **1800** may also be seen in the full sample RMML document **104** in Appendix E. These two Appendices D and E are useful for examining specific attributes and elements of the RMML DTD **1800**.

[0296] The RMML DTD **1800** data structure is optimized to provide information needed in the order in which it is required, to reduce the learning on the part of new users to RMML Macro development, and to avoid unnecessary duplication. The first line of the DTD **1800** in Appendix D starts with '<?xml encoding="UTF-8"?>' because XML documents start with a line that tells the client application, in this case, the RMML Interpreter **1980** (described below) and the data viewer **100**, what type of document it is and the version of XML.

[0297] With further reference to FIG. **18**, the DTD **1800** used to define RMML macro documents **104** is structured in a hierarchical tree structure of elements. Each element may include a list of attributes (displayed in Appendix D, but not shown on FIG. **18**) and/or an association with one or more sub-elements. As with the RDML DTD described above, some attributes may be required while others may be optional, depending on design parameters. At the highest level, the DTD **1800** has three elements descending from a root element, <macrodoc> **1802**. The first element, <macro_header> **1804**, contains the metadata for the document as a whole. The second, <macro_code> **1806** contains the source code expression to be evaluated, related variables, and instructions to the application regarding the graphical user interfaces for any parameters. The third, <macro_references> **1808** contains elements related to remote data (RDML documents **102**) or other macros (RMML documents **104**).

[0298] The macro_header element **1804** is designed to match, as closely as possible, the rdmldoc_header element of RDML documents **102**. This saves learning time for developers and end users, and allows reusable code modules to be built for both purposes.

[0299] Nevertheless, in one implementation consistent with the present invention, the <macro_header> element **1804** contains several attributes that are unique. In this implementation, there are 8 unique attributes in the <macro_header> element **1804**. The first of these is "macro_type." This attribute tells the application which general capability this particular macro requires within the context of that application. The application uses this attribute in a factory class **1912** to create the correct type of macro object for internal use. Two example types consistent with this implementation are: (1) "TSL" (time series line, a macro that works with time series to create a new line or lines on the chart), and (2) "TSO" (time series overlay, a macro that works with time series to create a new overlay on the chart **716**, such as gray backgrounds behind certain time periods.)

[0300] The result_type attribute tells the RDML data viewer **100** how to display the results of any transformation

created by the macro. There are, in one implementation, five permissible values for this string: "Replace Each," "Replace All," "Replace AB," "Add New," "Add Annotation," and "Add Overlay." Replace Each removes every line on the chart **716** in the RDML data viewer **100**, and replaces it with the transformed version. For example, if there are four series on the chart, all denominated in "miles", and user selects a macro "to kilometers", then every line will be converted to kilometers, the miles lines erased, and the kilometers lines placed on the chart in their place.

[0301] Replace All is used where all current lines are being replaced by one line. For example, if A and B are charted, a macro called "B as % of A" would replace them with a single line. Replace AB is a special case of Replace All where there are only two lines charted. Add New adds a line to whatever is plotted. For example, a macro called "Average" might draw a line through the existing line at the average level. Add Annotation adds a label with a pointer to a certain value on a chart (e.g., "2-3 Stock Split"). Add Overlay adds a shaded area behind certain regions of the chart.

[0302] The attribute "rdmldoc_type" designates the type of RDML Document **102** with which the macro is designed to work. Valid strings for this attribute are TS, CT and XY, corresponding to the types of RDML Documents **102**.

[0303] The elements <macro_source> **1810** and <license_terms> **1812** are identical to, and play the same role as, <data_source> **908** and <license_terms> **914** in the RDML Document Type Definition **702**. The <documentation> **1814** element is a container for two sub-elements: <macro_description> **1816** and <help_page> **1818**. The <macro_description> element contains a short string (e.g., under **50** characters) which describes the basic functionality of the macro. It appears in the description label of the parameters panel **1960** (shown in FIGS. **20**A-D and described below) For users desiring a more detailed description of the macro, the <help_page> **1818** element contains a text block that provides this information. This text block can be read by the data viewer **100** in an HTML pane as part of the regular help system. This text block is intended to provide information on all aspects of the macro that might be of interest to the user: its use, its code, its parameters, and its inputs.

[0304] The second top-level element is <macro_code> **1806**. This section contains the actual source code and related variables. The <code> **1820** element contains one or more expressions which evaluate to a transformation of certain numbers in the RDML data viewer **100**. In one implementation consistent with this invention, the transformations apply to the chart view **716** in the RDML data viewer **102**. But transformations may also be applied to the treeview **720** or other views.

[0305] The expression(s) in this element are formulas similar to those seen in spreadsheet formulas: the expression is a series of (1) operators, (2) literals, (3) variables, (4) functions, and (5) miscellaneous expression delimiters. The main difference from traditional spreadsheet formulas is that the variables may stand for either scalars or vectors, depending on the source or the context. A sample expression follows:

$$A*(B+2000)-IF(A>3, 12, 45)$$

[0306] Operators are: addition (+), subtraction (−), multiplication (*), division (/), less than (<), greater than (>), or (|), and (&). The operators have different meanings based on the types of the sub-expressions they work on. Operating on two vectors is interpreted as element-by-element operation on the two vectors. Thus, A*B, where A and B are vectors, is C={a1*b1, bn}.

[0307] Literals are defined either directly in the expression (e.g., "46"), or assigned to a variable (e.g., "pi=3.14156").

[0308] Variables can come from one of six different places in RMML. First, they can be defined as variables directly in the RMML document **104**. This is done by creating a <variable> element and assigning it a default value. Second, variables can be associated with graphical components in the parameters panel **1960** in the RDML data viewer **102**. In one implementation consistent with this invention, there are four different types of "gui components." These are listed and described below under <gui> element **1824**. Third, a variable can be defined from a line item element identical to those found in an RDML document **102**. Because they are identical, a line item can be simply cut and pasted from an RDML document **102** to an RMML document **104**. Fourth, a variable can be drawn from a remote source. In one implementation consistent with the present invention, that remote source can be a hyperlink to a line item in an RDML document **102**. This is accomplished by using an Xpointer hyperlink in the "href" attribute of a variable element. Fifth, a variable can be defined as one of the series of data that is currently plotted on the chart. In one implementation in accordance with the present invention, there can be a maximum of six series on the chart; each can be accessed by using the reserved words A, B, C, D, E, and F. As would be appreciated by one of ordinary skill in the art, any number of uniquely definable series may be used. If the result type attribute of a macro is "Replace All", then the expression is evaluated once for each series, with A being the series currently being transformed. Sixth, variables can be taken from an RDML document **102** that is already loaded in the RDML data viewer **100**. In this case, the expression indicates the URL and a class string that can be found in one of the li_class elements of a line item element. The expression then uses that line item as the variable value.

[0309] Functions that are built in are provided by the interpreter **1980** in one implementation consistent with the present invention and are a principal means of extending the language. These are in the form "FUNCTION_NAME(expression)". Functions include: IF(x,y,z); SUM(x); AVERAGE(x); COUNT(x); MIN(x); MAX(x) and so forth.

[0310] Miscellaneous delimiters are implemented by separating expressions by a semi-colon (;). This indicates that the expressions are to be evaluated in order. Expressions can also be grouped in parentheses to tell the interpreter **1980** how to evaluate sub-expressions.

[0311] Any string appearing in the <instructions> element **1822** will be displayed in the parameters panel **1960** to give the user any last minute instructions or suggestions. The <gui> element **1824** contains any number of elements that describe graphical components. These graphical components will appear in the parameters panel **1960** to give the user the ability to make changes to the macro's parameters. Four gui components (not shown) may be: <comp_vector>, <comp_list>, <comp_rbutton>, and <comp_ipanel>. The <comp_vector> is a vector variable, where the individual values of the vector can be viewed in a scrolling list box. A <comp_list> element is a scrolling list; each time the user clicks on a different item, the value of the variable attached to that component is changed to the value associated with that item. A <comp_rbutton> is a collection of radio buttons; each is associated with a different value. As the user clicks on different

buttons, the value associated with the component itself is changed, and the macro is re-run. A <comp_ipanel> is an input field that allows the user directly to input changes to the macro.

[0312] Generally, macros are not meant to run blindly on all data. First, the interpreter **1980** checks if the macro has any "qualifiers" that must be checked against the data. If there are any strings in the <qualifiers> element **1826** of the RMML document **104**, these are checked against strings in the <li_class> element **930** or other elements or attributes of the data. If the data is qualified, the interpreter **1980** will proceed with running the macro. For example, if the <qualifiers> element **1826** of the macro specifies "li_unit==currency", then the macro will only be run if the li_unit attribute of the data being operated on is a currency value.

[0313] The <error_handling> element **1828** holds error messages that can be displayed by the RDML data viewer **100** if there are problems of an indicated type. The <testing> element **1830** holds instructions to testing applications regarding automated testing routines. These applications undertake basic unit testing such as checking for out-of-bounds problems, missing value problems, divide-by-zero issues, etc.

[0314] The third major section of the RMML document **104**, the <macro_references> element **1808** holds references to outside macros and data sets that might be incorporated into the macro by reference. The two sub-elements are, accordingly, the <rmmldocs> element **1832** and the <data_docs> element **1834**.

IV.C.1. RMML Macro Package

[0315] Generally, there are three major areas of the RMML Macro Package: the RMML document handling classes (FIG. **19**A), the graphical interface (FIG. **19**B), and the macro interpreter (FIG. **19**C). In one implementation consistent with the present invention, this package of software classes connects to the RDML data viewer **100** in only a few places: it gets data from the ChartManager **714**/ChartData **715** objects, posts its graphical components through the GUI **734** object, and can access the loaded RDML documents **102** in the Primary Data Store **712**.

[0316] RMML Document Handling

[0317] FIG. **19**A shows objects responsible for managing the process of RMML document handling: loading documents, creating internal macro objects from them, cataloging them and caching them, and making them ready for use as objects. The RMMLDoc Reader **1910** locates an RMML Document **104** (either locally or over the internet) passes it to an XML Parser **706** (which may be a third-party component), relays error messages if any to the RDML data viewer **100**, creates an internal representation of the RMML Document **104** as an RMMLDoc **1906** object, and places a reference to the RMMLDoc **1906** in the RMML_Lib **1908**.

[0318] The RMMLDoc **1906** can be structured in two ways: either wrapping a TXDocument object to arrive at an RMMLDoc **1906**, or creating a new RMMLDoc **1906** object with the data from the TXDocument.

[0319] The RMMLDoc **1906** object contains methods for accessing individual elements and attributes of the document in a way that is easy to comprehend in the context of the macro package. The RMML_Lib **1908** object is a cache for loaded and active RMMLDoc objects **1906**.

[0320] The RMMLDoc **1906** is a raw collection of data about a macro—its formula, its help text, etc.—and generally does not act on data sets to transform them. The macro's capabilities first have to be used to create an internal object (macro interface **758**) that is capable of doing the calculations. This internal macro object **758** is created by a collaboration between the MacroLibrary **1926** object (which is a cache of the graphic objects for the active macros) and the MacroFactory **1912** (which determines which type of internal macro to create.)

[0321] There are four types of internal macros: time series (TS), category (CT), xy plot (XY) and overlay (OVERLAY). The macro_type attribute is used by the MacroFactory **1912** to create the correct type of internal macro: Macro_TSL **1918**, Macro_CT **1920**, Macro_XY **1922**, and Macro_OVER **1924** respectively. The MacroAdapter **1916** class performs the work of the macros.

TABLE 7

MacroAdapter
−mm : MacroManager
−mem : Memento
−rmmldoc : RMMLDoc
−eval : Evaluator
−mag : MacroAssumptionGroup
−desc : MacroDescription
−isChangedFlag : boolean
−result_type : int
−curr_li : int
−series_label_modifier : String
−series_label_type : String
+createMemento( ) : void
+evaluateFormula(strExpr : String, index : int) : Vector
+initMacro( ) : void
+performTransformation(result_type : int) : void
+replaceVariable(strExpr : String, index : int) : String
+resetMemento(mem : MacroMemento) : void
+undoTransformation( ) : void
+updateChartTitle( ) : void
+updateLabels( ) : void
+updateLegend( ) : void
+updateYAxisTitle( ) : void

[0322] Described below are class methods shown in Table 7 of a MacroAdapter object **760** in accordance with one implementation consistent with the present invention. First, MacroAdapter( ) is the constructor that creates a MacroAdapter **760** object. Before a macro is run, it has a chance to make a copy of the data that it is about to transform so that undo operations can be performed. The createMemento( ) method takes a snapshot of the data plotted on the chart by copying the ChartData object **715** to a Memento object.

[0323] Also, before a macro is run, the method initMacro( ) is run and gives the macro a chance to load any remote data or macro code. The replaceVariable( ) method runs the macro on multiple series on a chart. For example, if the result_type is "Replace Each" and there are four series charted on the chart, the macro will be run four times. The first time, A in the formula represents the first series, the second time it represents the second series and so forth. The method performTransformation( ) evaluates the transformation string, and updates the various titles and legends. An important part of performTransformation( )'s code is to determine the result_type of the macro and call the evaluateFormula( ) method in the correct manner. For "Replace Each," it is called once for each series, while for "Replace All," it is run only once.

[0324] The performTransformation( ) method also calls the four update methods: updateChartTitle( ) updateLabels( ),

updateLegend( ) and updateYAxisTitle( ). Each of these modifies the relevant strings in the ChartData object **715** so it can be passed on to the chart.

[0325] RMML Graphical Interface

[0326] FIG. **19**B illustrates objects responsible for managing the process of creating, managing, and handling events from the graphical user interface **734**. FIG. **20**A shows a screen shot of the RDML data viewer **100**; the NewMacroPanel **732** is displayed in the lower half of the screen. The available macros are displayed in individual windows in the MacroLibrary panel **1926** on the left side of the lower panel. The right side of the macro panel **732** is the macro information panel **2002** which holds the macro description panel **1958** and the parameter panel **1960**.

[0327] The NewMacroPanel **732** may be a subclass of a JPanel **1942** in Java's Swing set of classes. Those skilled in the art will be able to chose the appropriate class to use for other major platforms. The left side of the NewMacroPanel **732** is a frame for a multiple document interface (in this case, a Desktop for JinternalFrame objects from Java's Swing Set). Each MacroLibrary **1926** that is opened created a new internal frame, which allows users to select macros from multiple libraries at the same time.

[0328] When a MacroLibrary **1926** is opened, all macros within it are loaded and registered. "Registration" is a series of methods wherein the macro's variables are found in various elements of the RMMLDoc **104**, and graphical representations of these variables are built for inclusion in the parameter panel **1960**.

[0329] The graphical components for all of the variables associated with a set of macros are created in the MacroAssumptionGroup **1944** class. This class has a factory method that examines the attributes of the variables reported by the RMMLDoc **104** (variable name, variable value, gui type, default value, etc.) and creates the appropriate MacroGUI class: MacroGUI_List **1952** (see FIG. **20**A), MacroGUI_RadioButton **1954** (see FIG. **20**B), MacroGUI_Vector **1956** (see FIG. **20**C), or MacroGUI_Default **1950** (see FIG. **20**D). Each of these graphical components appears differently in the parameter panel **1960** as shown in the screen shots noted.

[0330] The registration of macros by the MacroLibrary **1926** also involves creating an MVariable **1946** object to go with each variable, and adding these to a cache of available Mvariables **1946**. These Mvariable **1946** objects are used in the actual evaluation of expressions. The registration process also involves registering the MacroGUI **1948** objects as sources for events that the MacroManager **1980** object can use to trigger the running of a macro. Mvariables **1946** encapsulate the various characteristics of a variable: its value, default, and source.

[0331] The description panel **1958** and the parameter panel **1960** are populated with graphical components and text when a particular macro is selected in the treeview **720** listing of a MacroLibrary **1926** internal frame. The macro that is selected provides the description text, the various labels and the MacroGUI **1948** components.

[0332] RMML Interpreter

[0333] The MacroManager object **730** is responsible for detecting that a macro has been selected or a parameter changed, getting the various data sets and variables called up and made available to an Evaluator object **1984**, and that the data set charted (or showing on the treeview **720**) is obtained and transformed and sent back to be recharted on the chart **716** or relisted on the treeview.

[0334] ChartData **715** contains the data from the current chart **716** (or active treeview **720**, depending on the type of the macro). It makes this data available as just another variable to the Evaluator object **1984**, and takes the final result of the Evaluator object **1984**.

[0335] The Evaluator **1984** evaluates the string expression (s) in the <code> element **1920** of the RMML document **104**, or the various expressions from the macros that have been selected. The expression is broken up into tokens by the Tokenizer classes **1994**. These tokens are the various operators, variables, literals, functions and other control symbols used in the RMML expression language detailed above. From these tokens, the Formula object **1990** builds a parse tree, by recursive descent, made up of FormulaNode **1992** objects created from the tokens. The FormulaNode **1992** objects evaluate themselves using the resolver objects VariableResolver **1986** and FunctionResolver **1988**. These resolvers in turn call the Evaluator objects **1984** to give them the current value of a variable or a function. For example, the FormulaNode **1982** evaluation process may have an "A" token; the Evaluator object **1984** knows that this means series A on the chart, and uses the vector of data (it could be an array or other data structure) currently found in the chart **716**. The formula exception **1996** relays errors associated with the processing of a function.

[0336] The foregoing description of an implementation of the present invention has been presented for purposes of illustration and description. It is not exhaustive and does not limit the present invention to the precise form disclosed. Modifications and variations are possible in light of the above teaching or may be acquired from practicing of the present invention. The scope of the present invention is defined by the claims and their equivalents.

1. A computer program product embodied on a non-transitory computer-readable medium comprising:

code for identifying a first markup document including first numerical values and first tags reflecting first characteristics of the first numerical values associated with a first unit of measure, and a second markup document including second numerical values and second tags reflecting second characteristics of the second numerical values associated with a second unit of measure, where the first characteristics of the first numerical values associated with the first unit of measure are different from the second characteristics of the second numerical values associated with the second unit of measure;

code for causing automatic transformation of at least a portion of the numerical values of at least one of the first markup document or the second markup document, so that the at least some of the first numerical values of the first markup document and at least some of the second numerical values of the second markup document have a common unit of measure;

code for processing at least a part of the first markup document and at least a part of the second markup document, resulting in a single markup document; and

code for causing a display of at least a portion of the single markup document.

2. The computer program product of claim **1**, wherein the computer program product is configured such that the first tags and the second tags each include computer-readable semantic tags that describe a semantic meaning of a corre-

sponding one of at least one of the first numerical values or the second numerical values, via a computer-readable tagging association therebetween.

3. The computer program product of claim **2**, wherein the computer program product is configured for allowing a user to edit a mapping of one or more of the computer-readable semantic tags to a corresponding one of at least one of the first numerical values or the second numerical values.

4. The computer program product of claim **1**, wherein the computer program product is operable such that the first unit of measure includes a first currency and the second unit of measure includes a second currency.

5. The computer program product of claim **1**, and further comprising code for manipulating the display of the single markup document using at least one of the first tags reflecting the first characteristics of the first numerical values associated with the first unit of measure, or the second tags reflecting the second characteristics of second numerical values associated with the second unit of measure.

6. The computer program product of claim **1**, wherein the computer program product is configured such that the first markup document and the second markup document each include a XML-compliant data document that includes multiple hierarchical relationships between two line items of corresponding numerical values, and is further capable of including computer-readable semantic tags that each describe a semantic meaning of one or more of the corresponding numerical values.

7. The computer program product of claim **6**, wherein the computer program product is configured such that the computer-readable semantic tags are each computer-readably coupled to the one or more of the corresponding numerical values.

8. The computer program product of claim **1**, wherein the computer program product is configured such that the single markup document includes a XML-compliant data document that includes multiple hierarchical relationships between two line items of corresponding numerical values, and is further capable of including computer-readable semantic tags that each describe a semantic meaning of one or more of the corresponding numerical values.

9. The computer program product of claim **1**, wherein the computer program product is operable such that the single markup document includes a XML-compliant data document that is capable of including at least one of: multiple hierarchical relationships between two line items of corresponding numerical values, or computer-readable semantic tags that each describe a semantic meaning of one or more of corresponding numerical values.

10. The computer program product of claim **9**, wherein the computer program product is configured for utilizing a plurality of computer-readable rules for processing the at least one XML-compliant data document, the computer-readable rules including:

a computer-readable datatype rule for validation of a value type,

a computer-readable calculation rule for validation of a value calculation, and

a computer-readable unit rule for validation of a value unit.

11. The computer program product of claim **9**, wherein the computer program product is configured for validating the at least one XML-compliant data document by:

identifying at least a subset of the computer-readable rules including at least one of:

a computer-readable datatype rule for validation of a value type,

a computer-readable calculation rule for validation of a value calculation, or

a computer-readable unit rule for validation of a value unit; and

processing at least a portion of the at least one XML-compliant data document, utilizing the at least subset of the rules.

12. The computer program product of claim **9**, wherein the computer program product is configured such that the at least one XML-compliant data document includes an extensible semantic tag-equipped markup language component and a hypertext markup language (HTML) component.

13. The computer program product of claim **12**, wherein the computer program product is configured such that at least one XML-compliant data document is capable of being displayed utilizing a network browser for allowing review of the HTML component in addition to access the extensible semantic tag-equipped markup language component.

14. The computer program product of claim **1**, wherein the computer program product is configured for storing at least one object including at least one reference to an original value of at least one of at least one of the first numerical values or the second numerical values.

15. The computer program product of claim **14**, wherein the computer program product is configured for outputting a presentation or report that is based on at least a portion of the at least one object, the presentation or report capable of including at least a portion of at least one of the first numerical values or the second numerical values, including the at least one original value, such that, based on the at least one reference of the at least one object, a change to the at least one original value results in a corresponding change in an instance of the presentation or report.

16. The computer program product of claim **14**, wherein the computer program product is configured such that the single markup document includes a XML-compliant data document that includes multiple hierarchical relationships between two line items of corresponding numerical values, and is further capable of including computer-readable semantic tags that each describe a semantic meaning of one or more of the corresponding numerical values, wherein the computer program product is further configured for outputting the XML-compliant data document based on at least a portion of the at least one object, the XML-compliant data document capable of including at least a portion of at least one of the first numerical values or the second numerical values, including the at least one original value, such that, based on the at least one reference of the at least one object, a change to the at least one original value results in a corresponding change in an instance of the XML-compliant data document.

17. The computer program product of claim **1**, wherein the computer program product is configured such that at least one of:

said code for causing the automatic transformation is capable of automatically transforming the at least portion of the numerical values of the first markup document the second markup document;

said identifying includes receiving;

said first tags or second tags result from tagging;

said characteristics include at least one of a magnitude, scale, modifier, unit, and measurement;

said tags reflect structure;

said processing includes merging or combining;

said processing results in a single data set, and said code for causing the display causes display of the single data set;

said single markup document is caused to be displayed on a single graphical display;

said single markup document includes an RDML document;

said single markup document is caused to be displayed without requiring a user to make manual adjustments; or said at least portion of the single markup document includes the numerical values thereof.

18. A method comprising:

identifying a first markup document including first numerical values and first tags reflecting first characteristics of the first numerical values associated with a first unit of measure, and a second markup document including second numerical values and second tags reflecting second characteristics of the second numerical values associated with a second unit of measure, where the first characteristics of the first numerical values associated with the first unit of measure are different from the second characteristics of the second numerical values associated with the second unit of measure;

automatically transforming at least a portion of the numerical values of at least one of the first markup document or the second markup document, so that the at least some of the first numerical values of the first markup document and at least some of the second numerical values of the second markup document have a common unit of measure;

processing at least a part of the first markup document and at least a part of the second markup document, resulting in a single markup document; and

causing a display of at least a portion of the single markup document.

19. An apparatus, comprising:

means for identifying a first markup document including first numerical values and first tags reflecting first characteristics of the first numerical values associated with a first unit of measure, and a second markup document including second numerical values and second tags reflecting second characteristics of the second numerical values associated with a second unit of measure, where the first characteristics of the first numerical values associated with the first unit of measure are different from the second characteristics of the second numerical values associated with the second unit of measure;

means for automatically transforming at least a portion of the numerical values of at least one of the first markup document or the second markup document, so that the at least some of the first numerical values of the first markup document and at least some of the second numerical values of the second markup document have a common unit of measure;

means for processing at least a part of the first markup document and at least a part of the second markup document, resulting in a single markup document; and

means for causing a display of at least a portion of the single markup document.

* * * * *