US009501878B2

(12) **United States Patent**
Palmer et al.

(10) **Patent No.: US 9,501,878 B2**
(45) **Date of Patent: Nov. 22, 2016**

(54) **VEHICLE EVENT PLAYBACK APPARATUS AND METHODS**

(71) Applicant: **SmartDrive Systems, Inc.**, San Diego, CA (US)

(72) Inventors: **Jason Palmer**, Carlsbad, CA (US); **Slaven Sljivar**, San Diego, CA (US)

(73) Assignee: **SmartDrive Systems, Inc.**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 48 days.

(21) Appl. No.: **14/055,833**

(22) Filed: **Oct. 16, 2013**

(65) **Prior Publication Data**

US 2015/0105934 A1 Apr. 16, 2015

(51) **Int. Cl.**
G07C 5/08 (2006.01)
G11B 27/10 (2006.01)

(52) **U.S. Cl.**
CPC ***G07C 5/0841*** (2013.01); *G07C 5/08* (2013.01); *G11B 27/10* (2013.01)

(58) **Field of Classification Search**
CPC G11B 27/10; G07C 5/08; G07C 5/0841
USPC 701/1
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

673,203	A	4/1901	Freund
673,795	A	5/1901	Hammer
673,907	A	5/1901	Johnson
676,075	A	6/1901	McDougall
679,511	A	7/1901	Richards
681,036	A	8/1901	Burg
681,283	A	8/1901	Waynick
681,998	A	9/1901	Swift
683,155	A	9/1901	Thompson
683,214	A	9/1901	Mansfield
684,276	A	10/1901	Lonergan
685,082	A	10/1901	Wood
685,969	A	11/1901	Campbell
686,545	A	11/1901	Selph

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2469728	12/2005
CA	2469728 A1	12/2005

(Continued)

OTHER PUBLICATIONS

Ambulance Companies Use Video Technology to Improve Driving Behavior, Ambulance Industry Journal, Spring 2003.


(Continued)

Primary Examiner — Khoi Tran
Assistant Examiner — Robert Nguyen
(74) *Attorney, Agent, or Firm* — Sheppard Mullin Richter & Hampton LLP

(57) **ABSTRACT**

Vehicle event data playback systems described herein may provide users means for reviewing events recorded by a vehicle event recorder. Circumstances relating to vehicle operation may be visually presented in these playback systems. Video playback from multiple recording devices may be synchronized with each other and/or with information related to the operation of the vehicle during the recorded events to affect a presentation of information related to operation of the vehicle. A user may be presented with many data types in graphical and/or intuitive arrangements.

23 Claims, 17 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

689,849	A	12/1901	Brown
691,982	A	1/1902	Sturgis
692,834	A	2/1902	Davis
694,781	A	3/1902	Prinz
2,943,141	A	6/1960	Knight
3,634,866	A	1/1972	Meyer
3,781,824	A	12/1973	Caiati
3,812,287	A	5/1974	Lemelson
3,885,090	A	5/1975	Rosenbaum
3,992,656	A	11/1976	Joy
4,054,752	A	10/1977	Dennis
4,072,850	A	2/1978	McGlynn
4,258,421	A	3/1981	Juhasz
4,271,358	A	6/1981	Schwarz
4,276,609	A	6/1981	Patel
4,280,151	A	7/1981	Tsunekawa
4,281,354	A	7/1981	Conte
4,401,976	A	8/1983	Stadelmayr
4,409,670	A	10/1983	Herndon
4,420,773	A	12/1983	Toyoda
4,425,097	A	1/1984	Owens
4,456,931	A	6/1984	Toyoda
4,489,351	A	12/1984	d'Alayer de Costemore
4,496,995	A	1/1985	Colles
4,500,868	A	2/1985	Tokitsu
4,528,547	A	7/1985	Rodney
4,533,962	A	8/1985	Decker
4,558,379	A	12/1985	Hutter
4,588,267	A	5/1986	Pastore
4,593,313	A	6/1986	Nagasaki
4,621,335	A	11/1986	Bluish
4,625,210	A	11/1986	Sagl
4,630,110	A	12/1986	Cotton
4,632,348	A	12/1986	Keesling
4,638,289	A	1/1987	Zottnik
4,646,241	A	2/1987	Ratchford
4,651,143	A	3/1987	Yamanaka
4,671,111	A	6/1987	Lemelson
4,718,685	A	1/1988	Kawabe
4,754,255	A	6/1988	Sanders
4,758,888	A	7/1988	Lapidot
4,763,745	A	8/1988	Eto
4,785,474	A	11/1988	Bernstein
4,789,904	A	12/1988	Peterson
4,794,566	A	12/1988	Richards
4,804,937	A	2/1989	Barbiaux
4,806,931	A	2/1989	Nelson
4,807,096	A	2/1989	Skogler
4,814,896	A	3/1989	Heitzman
4,837,628	A	6/1989	Sasaki
4,839,631	A	6/1989	Tsuji
4,843,463	A	6/1989	Michetti
4,843,578	A	6/1989	Wade
4,853,856	A	8/1989	Hanway
4,853,859	A	8/1989	Morita
4,866,616	A	9/1989	Takeuchi
4,876,597	A	10/1989	Roy
4,883,349	A	11/1989	Mittelhaeuser
4,896,855	A	1/1990	Furnish
4,926,331	A	5/1990	Windle
4,930,742	A	6/1990	Schofield
4,936,533	A	6/1990	Adams
4,939,652	A	7/1990	Steiner
4,942,464	A	7/1990	Milatz
4,945,244	A	7/1990	Castleman
4,949,186	A	8/1990	Peterson
4,980,913	A	12/1990	Skret
4,987,541	A	1/1991	Levente
4,992,943	A	2/1991	McCracken
4,993,068	A	2/1991	Piosenka
4,995,086	A	2/1991	Lilley
5,012,335	A	4/1991	Cohodar
5,027,104	A	6/1991	Reid
5,046,007	A	9/1991	McCrery
5,050,166	A	9/1991	Cantoni
5,056,056	A	10/1991	Gustin
5,057,820	A	10/1991	Markson
5,096,287	A	3/1992	Kakinami
5,100,095	A	3/1992	Haan
5,111,289	A	5/1992	Lucas
5,140,434	A	8/1992	Van Blessinger et al.
5,140,436	A	8/1992	Blessinger
5,140,438	A	8/1992	Blessinger
5,144,661	A	9/1992	Shamosh
5,178,448	A	1/1993	Adams
5,185,700	A	2/1993	Bezos
5,196,938	A	3/1993	Blessinger
5,223,844	A	6/1993	Mansell
5,224,211	A	6/1993	Roe
5,262,813	A	11/1993	Scharton
5,283,433	A	2/1994	Tsien
5,294,978	A	3/1994	Katayama
5,305,214	A	4/1994	Komatsu
5,305,216	A	4/1994	Okura
5,308,247	A	5/1994	Dyrdek
5,309,485	A	5/1994	Chao
5,311,197	A	5/1994	Sorden
5,321,753	A	6/1994	Gritton
5,327,288	A	7/1994	Wellington
5,330,149	A	7/1994	Haan
5,343,527	A	8/1994	Moore
5,353,023	A	10/1994	Mitsugi
5,361,326	A	11/1994	Aparicio
5,387,926	A	2/1995	Bellan
5,388,045	A	2/1995	Kamiya
5,388,208	A	2/1995	Weingartner
5,404,330	A	4/1995	Lee
5,408,330	A	4/1995	Squicciarini
5,422,543	A	6/1995	Weinberg
5,430,431	A	7/1995	Nelson
5,430,432	A	7/1995	Camhi
5,435,184	A	7/1995	Pineroli
5,445,024	A	8/1995	Riley
5,445,027	A	8/1995	Zoerner
5,446,659	A	8/1995	Yamawaki
5,455,625	A	10/1995	Englander
5,455,716	A	10/1995	Suman
5,465,079	A	11/1995	Bouchard
5,473,729	A	12/1995	Bryant
5,477,141	A	12/1995	Nather
5,495,242	A	2/1996	Kick
5,495,243	A	2/1996	McKenna
5,497,419	A	3/1996	Hill
5,499,182	A	3/1996	Ousborne
5,504,482	A	4/1996	Schreder
5,513,011	A	4/1996	Matsumoto
5,515,285	A	5/1996	Garrett
5,519,260	A	5/1996	Washington
5,521,633	A	5/1996	Nakajima
5,523,811	A	6/1996	Wada
5,526,269	A	6/1996	Ishibashi
5,530,420	A	6/1996	Tsuchiya
5,532,678	A	7/1996	Kin
5,537,156	A	7/1996	Katayama
5,539,454	A	7/1996	Williams
5,541,590	A	7/1996	Nishio
5,544,060	A	8/1996	Fujii
5,546,191	A	8/1996	Hibi
5,546,305	A	8/1996	Kondo
5,548,273	A	8/1996	Nicol
5,552,990	A	9/1996	Ihara
5,559,496	A	9/1996	Dubats
5,568,211	A	10/1996	Bamford
5,570,087	A	10/1996	Lemelson
5,570,127	A	10/1996	Schmidt
5,574,424	A	11/1996	Nguyen
5,574,443	A	11/1996	Hsieh
D376,571	S	12/1996	Kokat
5,581,464	A	12/1996	Woll
5,586,130	A	12/1996	Doyle
5,590,948	A	1/1997	Moreno
5,596,382	A	1/1997	Bamford
5,600,775	A	2/1997	King
5,608,272	A	3/1997	Tanguay

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,610,580	A	3/1997	Lai
5,612,686	A	3/1997	Takano
5,631,638	A	5/1997	Kaspar
5,638,273	A	6/1997	Coiner
5,642,106	A	6/1997	Hancock
5,646,856	A	7/1997	Kaesser
5,652,706	A	7/1997	Morimoto
RE35,590	E	8/1997	Bezos
5,654,892	A	8/1997	Fujii
5,659,355	A	8/1997	Barron
5,666,120	A	9/1997	Kline
5,667,176	A	9/1997	Zamarripa
5,669,698	A	9/1997	Veldman
5,671,451	A	9/1997	Takahashi
5,677,979	A	10/1997	Squicciarini
5,680,117	A	10/1997	Arai
5,680,123	A	10/1997	Lee
5,686,765	A	11/1997	Washington
5,686,889	A	11/1997	Hillis
5,689,442	A	11/1997	Swanson
5,696,705	A	12/1997	Zykan
5,706,362	A	1/1998	Yabe
5,706,909	A	1/1998	Bevins
5,712,679	A	1/1998	Coles
5,717,456	A	2/1998	Rudt
5,719,554	A	2/1998	Gagnon
5,758,299	A	5/1998	Sandborg
5,781,101	A	7/1998	Stephen
5,781,145	A	7/1998	Williams
5,784,007	A	7/1998	Pepper
5,784,021	A	7/1998	Oliva
5,784,521	A	7/1998	Nakatani
5,790,403	A	8/1998	Nakayama
5,790,973	A	8/1998	Blaker
5,793,308	A	8/1998	Rosinski
5,793,420	A	8/1998	Schmidt
5,793,739	A	8/1998	Tanaka
5,793,985	A	8/1998	Natarajan
5,794,165	A	8/1998	Minowa
5,797,134	A	8/1998	McMillan
5,798,458	A	8/1998	Monroe
5,800,040	A	9/1998	Santo
5,802,545	A	9/1998	Coverdill
5,802,727	A	9/1998	Blank
5,805,079	A	9/1998	Lemelson
5,813,745	A	9/1998	Fant
5,815,071	A	9/1998	Doyle
5,815,093	A	9/1998	Kikinis
5,819,198	A	10/1998	Peretz
5,825,284	A	10/1998	Dunwoody
5,825,412	A	10/1998	Hobson
5,844,505	A	12/1998	Van
5,845,733	A	12/1998	Wolfsen
5,867,802	A	2/1999	Borza
5,877,897	A	3/1999	Schofield
5,896,167	A	4/1999	Omae
5,897,602	A	4/1999	Mizuta
5,897,606	A	4/1999	Miura
5,899,956	A	5/1999	Chan
5,901,806	A	5/1999	Takahashi
5,914,748	A	6/1999	Parulski
5,919,239	A	7/1999	Fraker
5,926,210	A	7/1999	Hackett
5,928,291	A	7/1999	Jenkins
5,938,321	A	8/1999	Bos
5,946,404	A	8/1999	Bakshi
5,948,038	A	9/1999	Daly
5,959,367	A	9/1999	OFarrell
5,978,017	A	11/1999	Tino
6,002,326	A	12/1999	Turner
6,006,148	A	12/1999	Strong
6,008,723	A	12/1999	Yassan
6,008,841	A	12/1999	Charlson
6,009,370	A	12/1999	Minowa
6,011,492	A	1/2000	Garesche
6,028,528	A	2/2000	Lorenzetti
6,037,860	A	3/2000	Zander
6,037,977	A	3/2000	Peterson
6,041,410	A	3/2000	Hsu
6,049,079	A	4/2000	Noordam
6,057,754	A	5/2000	Kinoshita
6,060,989	A	5/2000	Gehlot
6,064,792	A	5/2000	Fox
6,067,488	A	5/2000	Tano
6,076,026	A	6/2000	Jambhekar
6,084,870	A	7/2000	Wooten
6,088,635	A	7/2000	Cox
6,092,008	A	7/2000	Bateman
6,092,021	A	7/2000	Ehlbeck
6,092,193	A	7/2000	Loomis
6,100,811	A	8/2000	Hsu
6,111,254	A	8/2000	Eden
6,118,768	A	9/2000	Bhatia
6,122,738	A	9/2000	Millard
6,141,611	A	10/2000	Mackey
6,144,296	A	11/2000	Ishida
6,147,598	A	11/2000	Murphy
6,151,065	A	11/2000	Steed
6,163,338	A	12/2000	Johnson
6,163,749	A	12/2000	McDonough
6,167,186	A	12/2000	Kawasaki
6,170,742	B1	1/2001	Yacoob
6,181,373	B1	1/2001	Coles
6,182,010	B1	1/2001	Berstis
6,185,490	B1	2/2001	Ferguson
6,195,605	B1	2/2001	Tabler
6,200,139	B1	3/2001	Clapper
6,208,919	B1	3/2001	Barkesseh
6,211,907	B1	4/2001	Scaman
6,218,960	B1	4/2001	Ishikawa
6,246,933	B1	6/2001	Bague
6,246,934	B1	6/2001	Otake
6,252,544	B1	6/2001	Hoffberg
6,253,129	B1	6/2001	Jenkins
6,259,475	B1	7/2001	Ramachandran
6,263,265	B1	7/2001	Fera
6,266,588	B1	7/2001	McClellan
6,298,290	B1	10/2001	Abe
6,300,875	B1	10/2001	Schafer
6,324,450	B1	11/2001	Iwama
6,333,759	B1	12/2001	Mazzilli
6,337,622	B1	1/2002	Sugano
6,349,250	B1	2/2002	Hart
6,353,734	B1	3/2002	Wright
6,356,823	B1	3/2002	Iannotti
6,360,147	B1	3/2002	Lee
6,366,207	B1	4/2002	Murphy
6,389,339	B1	5/2002	Just
6,389,340	B1	5/2002	Rayner
6,400,835	B1	6/2002	Lemelson
6,405,112	B1	6/2002	Rayner
6,405,132	B1	6/2002	Breed
6,408,232	B1	6/2002	Cannon
6,411,874	B2	6/2002	Morgan
6,421,080	B1	7/2002	Lambert
6,434,510	B1	8/2002	Callaghan
6,449,540	B1	9/2002	Rayner
6,456,321	B1	9/2002	Ito
6,459,988	B1	10/2002	Fan
6,470,241	B2	10/2002	Yoshikawa
6,472,771	B1	10/2002	Frese
6,490,513	B1	12/2002	Fish
6,493,650	B1	12/2002	Rodgers
6,505,106	B1	1/2003	Lawrence
6,507,838	B1	1/2003	Syeda-Mahmood
6,508,400	B1	1/2003	Ishifuji
6,516,256	B1	2/2003	Hartmann
6,518,881	B2	2/2003	Monroe
6,525,672	B2	2/2003	Chainer
6,529,159	B1	3/2003	Fan
6,535,804	B1	3/2003	Chun
6,552,682	B1	4/2003	Fan
6,556,905	B1	4/2003	Mittelsteadt
6,559,769	B2	5/2003	Anthony

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,574,538	B2	6/2003	Sasaki
6,575,902	B1	6/2003	Burton
6,580,373	B1	6/2003	Ohashi
6,580,983	B2	6/2003	Laguer-Diaz
6,593,848	B1	7/2003	Atkins, III
6,594,576	B2	7/2003	Fan
6,611,740	B2	8/2003	Lowrey
6,611,755	B1	8/2003	Coffee
6,624,611	B2	9/2003	Kirmuss
6,629,029	B1	9/2003	Giles
6,629,030	B2	9/2003	Klausner
6,636,791	B2	10/2003	Okada
6,664,922	B1	12/2003	Fan
6,665,613	B2	12/2003	Duvall
6,679,702	B1	1/2004	Rau
6,684,137	B2	1/2004	Takagi
6,694,483	B1	2/2004	Nagata
6,701,234	B1	3/2004	Vogelsang
6,714,894	B1	3/2004	Tobey
6,718,239	B2	4/2004	Rayner
6,721,640	B2	4/2004	Glenn
6,721,652	B1	4/2004	Sanqunetti
6,728,612	B1	4/2004	Carver
6,732,031	B1	5/2004	Lightner
6,732,032	B1	5/2004	Banet
6,735,503	B2	5/2004	Ames
6,737,954	B2	5/2004	Chainer
6,738,697	B2	5/2004	Breed
6,739,078	B2	5/2004	Morley
6,741,168	B2	5/2004	Webb
6,745,153	B2	6/2004	White
6,747,692	B2	6/2004	Patel
6,748,305	B1	6/2004	Klausner
6,760,757	B1	7/2004	Lundberg
6,762,513	B2	7/2004	Landgraf
6,795,017	B1	9/2004	Puranik
6,795,111	B1	9/2004	Mazzilli
6,795,759	B2	9/2004	Doyle
6,798,743	B1	9/2004	Ma
6,804,590	B2	10/2004	Oda
6,810,362	B2	10/2004	Adachi
6,812,831	B2	11/2004	Ikeda
6,819,989	B2	11/2004	Maeda
6,831,556	B1	12/2004	Boykin
6,832,140	B2	12/2004	Fan
6,832,141	B2	12/2004	Skeen
6,836,712	B2	12/2004	Nishina
6,842,762	B2	1/2005	Raithel
6,847,873	B1	1/2005	Li
6,850,823	B2	2/2005	Eun
6,859,695	B2	2/2005	Klausner
6,859,705	B2	2/2005	Rao
6,862,524	B1	3/2005	Nagda
6,865,457	B1	3/2005	Mittelsteadt
6,867,733	B2	3/2005	Sandhu
6,873,261	B2	3/2005	Anthony
6,882,313	B1	4/2005	Fan
6,882,912	B2	4/2005	DiLodovico
6,894,606	B2	5/2005	Forbes
6,895,248	B1	5/2005	Akyol
6,898,492	B2	5/2005	De Leon
6,898,493	B2	5/2005	Ehrman
6,919,823	B1	7/2005	Lock
6,922,566	B2	7/2005	Puranik
6,928,348	B1	8/2005	Lightner
6,931,309	B2	8/2005	Phelan
6,947,817	B2	9/2005	Diem
6,950,122	B1	9/2005	Mirabile
6,954,223	B2	10/2005	Miyazawa
6,988,034	B1	1/2006	Marlatt
7,003,289	B1	2/2006	Kolls
7,012,632	B2	3/2006	Freeman
7,020,548	B2	3/2006	Saito
7,023,333	B2	4/2006	Blanco
7,039,510	B2	5/2006	Gumpinger
7,076,348	B2	7/2006	Bucher
7,079,927	B1	7/2006	Tano
7,082,359	B2	7/2006	Breed
7,082,382	B1	7/2006	Rose et al.
7,088,387	B1	8/2006	Freeman
7,095,782	B1	8/2006	Cohen
7,098,812	B2	8/2006	Hirota
7,100,190	B2	8/2006	Johnson
7,113,853	B2	9/2006	Hecklinger
7,117,075	B1	10/2006	Larschan
7,119,832	B2	10/2006	Blanco
7,138,904	B1	11/2006	Dutu
7,155,321	B2	12/2006	Bromley
7,177,738	B2	2/2007	Diaz
7,209,833	B2	4/2007	Isaji
7,239,252	B2	7/2007	Kato
7,254,482	B2	8/2007	Kawasaki
7,265,663	B2	9/2007	Steele
7,266,507	B2	9/2007	Simon
7,272,179	B2	9/2007	Siemens
7,308,341	B2	12/2007	Schofield
7,317,974	B2	1/2008	Luskin
7,343,306	B1	3/2008	Bates
7,348,895	B2	3/2008	Lagassey
7,349,027	B2	3/2008	Endo
7,370,261	B2	5/2008	Winarski
7,382,933	B2	6/2008	Dorai
7,386,376	B2	6/2008	Basir
7,389,178	B2	6/2008	Raz
7,457,693	B2	11/2008	Olsen
7,471,189	B2	12/2008	Vastad
7,471,192	B2	12/2008	Hara
7,536,457	B2	5/2009	Miller
7,561,054	B2	7/2009	Raz
7,584,033	B2	9/2009	Mittelsteadt
7,623,754	B1	11/2009	McKain
7,659,827	B2	2/2010	Gunderson
7,659,835	B2	2/2010	Jung
7,667,731	B2	2/2010	Kreiner
7,702,442	B2	4/2010	Takenaka
7,725,216	B2	5/2010	Kim
7,768,548	B2	8/2010	Silvernail
7,769,499	B2	8/2010	McQuade
7,783,956	B2	8/2010	Ko
7,804,426	B2	9/2010	Etcheson
7,821,421	B2	10/2010	Tamir
7,853,376	B2	12/2010	Peng
7,893,958	B1	2/2011	DAgostino
7,940,250	B2	5/2011	Forstall
7,941,258	B1	5/2011	Mittelsteadt
7,974,748	B2	7/2011	Goerick
8,054,168	B2	11/2011	McCormick
8,068,979	B2	11/2011	Breed
8,090,598	B2	1/2012	Bauer
8,113,844	B2	2/2012	Huang
8,139,820	B2	3/2012	Plante
8,140,265	B2	3/2012	Grush
8,140,358	B1	3/2012	Ling
8,152,198	B2	4/2012	Breed
8,239,092	B2	8/2012	Plante
8,269,617	B2	9/2012	Cook
8,311,858	B2	11/2012	Everett
8,314,708	B2	11/2012	Gunderson
8,321,066	B2	11/2012	Becker
8,373,567	B2	2/2013	Denson
8,417,562	B1	4/2013	Siemens
8,442,690	B2	5/2013	Goldstein
8,471,701	B2	6/2013	Yariv
8,508,353	B2	8/2013	Cook
8,538,696	B1	9/2013	Cassanova
8,538,785	B2	9/2013	Coleman
8,564,426	B2	10/2013	Cook
8,564,446	B2	10/2013	Gunderson
8,571,755	B2	10/2013	Plante
8,577,703	B2	11/2013	McClellan
8,606,492	B1	12/2013	Botnen
8,635,557	B2	1/2014	Geise
8,676,428	B2	3/2014	Richardson
8,744,642	B2	6/2014	Nemat-Nasser

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,775,067	B2	7/2014	Cho	
8,781,292	B1 *	7/2014	Ross	G11B 27/11 386/223
8,803,695	B2	8/2014	Denson	
8,805,110	B2	8/2014	Rhoads	
8,849,501	B2	9/2014	Cook	
8,855,847	B2	10/2014	Uehara	
8,868,288	B2	10/2014	Plante	
8,880,279	B2	11/2014	Plante	
8,892,310	B1	11/2014	Palmer	
8,989,959	B2	3/2015	Plante	
8,996,234	B1	3/2015	Tamari	
8,996,240	B2	3/2015	Plante	
9,047,721	B1	6/2015	Botnen	
9,183,679	B2	11/2015	Plante	
9,201,842	B2	12/2015	Plante	
9,208,129	B2	12/2015	Plante	
9,226,004	B1	12/2015	Plante	
9,240,079	B2	1/2016	Lambert	
2001/0005217	A1	6/2001	Hamilton	
2001/0005804	A1	6/2001	Rayner	
2001/0018628	A1	8/2001	Jenkins	
2001/0020204	A1	9/2001	Runyon	
2001/0052730	A1	12/2001	Baur	
2002/0019689	A1	2/2002	Harrison	
2002/0027502	A1	3/2002	Mayor	
2002/0029109	A1	3/2002	Wong	
2002/0035422	A1	3/2002	Sasaki	
2002/0044225	A1	4/2002	Rakib	
2002/0059453	A1	5/2002	Eriksson	
2002/0061758	A1	5/2002	Zarlengo	
2002/0067076	A1	6/2002	Talbot	
2002/0087240	A1	7/2002	Raithel	
2002/0091473	A1	7/2002	Gardner	
2002/0105438	A1	8/2002	Forbes	
2002/0107619	A1	8/2002	Klausner	
2002/0111725	A1	8/2002	Burge	
2002/0111756	A1	8/2002	Modgil	
2002/0118206	A1	8/2002	Knittel	
2002/0120374	A1	8/2002	Douros	
2002/0135679	A1	9/2002	Scaman	
2002/0138587	A1	9/2002	Koehler	
2002/0163532	A1	11/2002	Thomas	
2002/0169529	A1	11/2002	Kim	
2002/0169530	A1	11/2002	Laguer-Diaz	
2002/0183905	A1	12/2002	Maeda	
2003/0016753	A1	1/2003	Kim	
2003/0028298	A1	2/2003	Macky	
2003/0053433	A1	3/2003	Chun	
2003/0055557	A1	3/2003	Dutta	
2003/0065805	A1	4/2003	Barnes	
2003/0067541	A1	4/2003	Joao	
2003/0079041	A1	4/2003	Parrella	
2003/0080713	A1	5/2003	Kirmuss	
2003/0080878	A1	5/2003	Kirmuss	
2003/0081121	A1	5/2003	Kirmuss	
2003/0081122	A1	5/2003	Kirmuss	
2003/0081127	A1	5/2003	Kirmuss	
2003/0081128	A1	5/2003	Kirmuss	
2003/0081934	A1	5/2003	Kirmuss	
2003/0081935	A1	5/2003	Kirmuss	
2003/0095688	A1	5/2003	Kirmuss	
2003/0112133	A1	6/2003	Webb	
2003/0125854	A1	7/2003	Kawasaki	
2003/0144775	A1	7/2003	Klausner	
2003/0152145	A1	8/2003	Kawakita	
2003/0154009	A1	8/2003	Basir	
2003/0158638	A1	8/2003	Yakes	
2003/0177187	A1	9/2003	Levine	
2003/0187704	A1	10/2003	Hashiguchi	
2003/0191568	A1	10/2003	Breed	
2003/0195678	A1	10/2003	Betters et al.	
2003/0214585	A1	11/2003	Bakewell	
2003/0220835	A1	11/2003	Barnes	
2003/0222880	A1	12/2003	Waterman	
2004/0008255	A1	1/2004	Lewellen	
2004/0033058	A1	2/2004	Reich	
2004/0039503	A1	2/2004	Doyle	
2004/0039504	A1	2/2004	Coffee	
2004/0044452	A1	3/2004	Bauer	
2004/0044592	A1	3/2004	Ubik	
2004/0054444	A1	3/2004	Abeska	
2004/0054513	A1	3/2004	Laird	
2004/0054689	A1	3/2004	Salmonsen	
2004/0064245	A1	4/2004	Knockeart	
2004/0070926	A1	4/2004	Boykin	
2004/0083041	A1	4/2004	Skeen	
2004/0088090	A1	5/2004	Wee	
2004/0103008	A1	5/2004	Wahlbin	
2004/0103010	A1	5/2004	Wahlbin	
2004/0104842	A1	6/2004	Drury	
2004/0111189	A1	6/2004	Miyazawa	
2004/0138794	A1	7/2004	Saito	
2004/0145457	A1	7/2004	Schofield et al.	
2004/0153244	A1	8/2004	Kellum	
2004/0153362	A1	8/2004	Bauer	
2004/0167689	A1	8/2004	Bromley	
2004/0179600	A1	9/2004	Wells	
2004/0181326	A1	9/2004	Adams	
2004/0184548	A1	9/2004	Kerbiriou	
2004/0203903	A1	10/2004	Wilson	
2004/0209594	A1	10/2004	Naboulsi	
2004/0210353	A1	10/2004	Rice	
2004/0230345	A1	11/2004	Tzamaloukas	
2004/0230370	A1	11/2004	Tzamaloukas	
2004/0230373	A1	11/2004	Tzamaloukas	
2004/0230374	A1	11/2004	Tzamaloukas	
2004/0233284	A1	11/2004	Lesesky	
2004/0236474	A1	11/2004	Chowdhary	
2004/0243285	A1	12/2004	Gounder	
2004/0243308	A1	12/2004	Irish	
2004/0243668	A1	12/2004	Harjanto	
2004/0254689	A1	12/2004	Blazic	
2004/0254698	A1	12/2004	Hubbard	
2005/0021199	A1	1/2005	Zimmerman	
2005/0043869	A1	2/2005	Funkhouser	
2005/0060070	A1	3/2005	Kapolka	
2005/0060071	A1	3/2005	Winner	
2005/0065682	A1	3/2005	Kapadia	
2005/0065716	A1	3/2005	Timko	
2005/0073585	A1	4/2005	Ettinger	
2005/0078423	A1	4/2005	Kim	
2005/0088291	A1	4/2005	Blanco	
2005/0099498	A1	5/2005	Lao	
2005/0100329	A1	5/2005	Lao	
2005/0102074	A1	5/2005	Kolls	
2005/0125117	A1	6/2005	Breed	
2005/0131585	A1	6/2005	Luskin	
2005/0131595	A1	6/2005	Luskin	
2005/0131597	A1	6/2005	Raz	
2005/0136949	A1	6/2005	Barnes	
2005/0137757	A1	6/2005	Phelan	
2005/0137796	A1	6/2005	Gumpinger	
2005/0146458	A1	7/2005	Carmichael	
2005/0149238	A1	7/2005	Stefani	
2005/0149259	A1	7/2005	Cherveny	
2005/0159964	A1	7/2005	Sonnenrein	
2005/0166258	A1	7/2005	Vasilevsky	
2005/0171692	A1	8/2005	Hamblen	
2005/0174217	A1	8/2005	Basir	
2005/0182538	A1	8/2005	Phelan	
2005/0182824	A1	8/2005	Cotte	
2005/0185052	A1	8/2005	Raisinghani	
2005/0185936	A9	8/2005	Lao	
2005/0192749	A1	9/2005	Flann	
2005/0197748	A1	9/2005	Hoist	
2005/0200714	A1	9/2005	Marchese	
2005/0203683	A1	9/2005	Olsen	
2005/0206741	A1	9/2005	Raber	
2005/0209776	A1	9/2005	Ogino	
2005/0212920	A1	9/2005	Evans	
2005/0216144	A1	9/2005	Baldassa	
2005/0228560	A1	10/2005	Doherty	
2005/0233805	A1	10/2005	Okajima	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0251304	A1	11/2005	Cancellara	
2005/0256681	A1	11/2005	Brinton	
2005/0258942	A1	11/2005	Manasseh	
2005/0264691	A1	12/2005	Endo	
2005/0283284	A1	12/2005	Grenier	
2006/0001671	A1	1/2006	Kamijo	
2006/0007151	A1	1/2006	Ram	
2006/0011399	A1	1/2006	Brockway	
2006/0015233	A1	1/2006	Olsen	
2006/0022842	A1	2/2006	Zoladek	
2006/0025897	A1	2/2006	Shostak	
2006/0030986	A1	2/2006	Peng	
2006/0040239	A1	2/2006	Cummins	
2006/0047380	A1	3/2006	Welch	
2006/0053038	A1	3/2006	Warren	
2006/0055521	A1	3/2006	Blanco	
2006/0057543	A1	3/2006	Roald	
2006/0058950	A1	3/2006	Kato	
2006/0072792	A1	4/2006	Toda	
2006/0078853	A1	4/2006	Lanktree	
2006/0082438	A1	4/2006	Bazakos	
2006/0092043	A1	5/2006	Lagassey	
2006/0095175	A1	5/2006	DeWaal	
2006/0095199	A1	5/2006	Lagassey	
2006/0095349	A1	5/2006	Morgan	
2006/0103127	A1	5/2006	Lie	
2006/0106514	A1	5/2006	Liebl	
2006/0111817	A1	5/2006	Phelan	
2006/0122749	A1	6/2006	Phelan	
2006/0129578	A1	6/2006	Kim	
2006/0142913	A1	6/2006	Coffee	
2006/0143435	A1	6/2006	Kwon	
2006/0147187	A1	7/2006	Takemoto	
2006/0161960	A1	7/2006	Benoit	
2006/0168271	A1	7/2006	Pabari	
2006/0178793	A1	8/2006	Hecklinger	
2006/0180647	A1	8/2006	Hansen	
2006/0184295	A1	8/2006	Hawkins	
2006/0192658	A1	8/2006	Yamamura	
2006/0200008	A1	9/2006	Moore-Ede	
2006/0200305	A1	9/2006	Sheha	
2006/0204059	A1	9/2006	Ido	
2006/0209090	A1	9/2006	Kelly et al.	
2006/0209840	A1	9/2006	Paatela	
2006/0212195	A1	9/2006	Veith	
2006/0215884	A1	9/2006	Ota	
2006/0226344	A1	10/2006	Werth	
2006/0229780	A1	10/2006	Underdahl	
2006/0242680	A1	10/2006	Johnson	
2006/0247833	A1	11/2006	Malhotra	
2006/0253307	A1	11/2006	Warren	
2006/0259218	A1	11/2006	Wu	
2006/0261931	A1	11/2006	Cheng	
2007/0001831	A1	1/2007	Raz	
2007/0005404	A1	1/2007	Raz	
2007/0027583	A1	2/2007	Tamir	
2007/0027726	A1	2/2007	Warren	
2007/0035632	A1	2/2007	Silvernail	
2007/0043487	A1	2/2007	Krzystofczyk	
2007/0120948	A1	5/2007	Fujioka	
2007/0124332	A1	5/2007	Ballesty	
2007/0127833	A1	6/2007	Singh	
2007/0132773	A1	6/2007	Plante	
2007/0135979	A1	6/2007	Plante	
2007/0135980	A1	6/2007	Plante	
2007/0136078	A1	6/2007	Plante	
2007/0142986	A1	6/2007	Alaous	
2007/0143499	A1	6/2007	Chang	
2007/0150138	A1	6/2007	Plante	
2007/0150140	A1	6/2007	Seymour	
2007/0173994	A1	7/2007	Kubo	
2007/0179691	A1	8/2007	Grenn	
2007/0183635	A1	8/2007	Weidhaas	
2007/0208494	A1	9/2007	Chapman	
2007/0216521	A1	9/2007	Guensler	
2007/0219685	A1	9/2007	Plante	
2007/0219686	A1	9/2007	Plante	
2007/0241874	A1 *	10/2007	Okpysh	B60Q 1/444 340/479
2007/0244614	A1	10/2007	Nathanson	
2007/0257781	A1	11/2007	Denson	
2007/0257782	A1	11/2007	Etcheson	
2007/0257804	A1	11/2007	Gunderson	
2007/0257815	A1	11/2007	Gunderson	
2007/0260677	A1	11/2007	DeMarco	
2007/0263984	A1	11/2007	Sterner	
2007/0268158	A1	11/2007	Gunderson	
2007/0271105	A1	11/2007	Gunderson	
2007/0273480	A1	11/2007	Burkman	
2007/0279214	A1	12/2007	Buehler	
2007/0299612	A1	12/2007	Kimura	
2008/0035108	A1	2/2008	Ancimer	
2008/0059019	A1	3/2008	Delia	
2008/0071827	A1	3/2008	Hengel	
2008/0111666	A1	5/2008	Plante	
2008/0122603	A1	5/2008	Plante	
2008/0143834	A1	6/2008	Comeau	
2008/0147267	A1 *	6/2008	Plante et al.	701/35
2008/0157510	A1	7/2008	Breed	
2008/0167775	A1	7/2008	Kuttenberger	
2008/0169914	A1	7/2008	Albertson	
2008/0177436	A1	7/2008	Fortson	
2008/0195261	A1	8/2008	Breed	
2008/0204556	A1	8/2008	de Miranda	
2008/0211779	A1	9/2008	Pryor	
2008/0234920	A1	9/2008	Nurminen	
2008/0243389	A1	10/2008	Inoue	
2008/0252412	A1	10/2008	Larsson	
2008/0252485	A1	10/2008	Lagassey	
2008/0252487	A1	10/2008	McClellan	
2008/0269978	A1	10/2008	Shirole	
2008/0281485	A1	11/2008	Plante	
2008/0309762	A1	12/2008	Howard et al.	
2008/0319604	A1	12/2008	Follmer	
2009/0009321	A1	1/2009	McClellan	
2009/0043500	A1	2/2009	Satoh	
2009/0043971	A1	2/2009	Kim	
2009/0051510	A1	2/2009	Follmer	
2009/0138191	A1	5/2009	Engelhard	
2009/0157255	A1	6/2009	Plante	
2009/0216775	A1	8/2009	Ratliff et al.	
2009/0224869	A1	9/2009	Baker	
2009/0290848	A1	11/2009	Brown	
2009/0299622	A1	12/2009	Denaro	
2009/0312998	A1	12/2009	Berckmans	
2009/0326796	A1	12/2009	Prokhorov	
2009/0327856	A1	12/2009	Mouilleseaux	
2010/0030423	A1	2/2010	Nathanson	
2010/0045451	A1	2/2010	Periwal	
2010/0049516	A1	2/2010	Talwar	
2010/0054709	A1	3/2010	Misawa	
2010/0057342	A1	3/2010	Muramatsu	
2010/0063672	A1	3/2010	Anderson	
2010/0063680	A1	3/2010	Tolstedt	
2010/0063850	A1	3/2010	Daniel	
2010/0070175	A1	3/2010	Soulchin	
2010/0076621	A1	3/2010	Kubotani	
2010/0085193	A1	4/2010	Boss	
2010/0085430	A1	4/2010	Kreiner	
2010/0087984	A1	4/2010	Joseph	
2010/0100315	A1	4/2010	Davidson	
2010/0103165	A1	4/2010	Lee	
2010/0104199	A1	4/2010	Zhang	
2010/0153146	A1	6/2010	Angell	
2010/0157061	A1	6/2010	Katsman	
2010/0191411	A1	7/2010	Cook	
2010/0201875	A1	8/2010	Rood	
2010/0220892	A1	9/2010	Kawakubo	
2010/0250020	A1	9/2010	Lee	
2010/0250021	A1	9/2010	Cook	
2010/0250060	A1	9/2010	Maeda	
2010/0250116	A1	9/2010	Yamaguchi	
2010/0253918	A1	10/2010	Seder	
2010/0268415	A1	10/2010	Ishikawa	

(56) **References Cited**

U.S. PATENT DOCUMENTS

2010/0283633	A1	11/2010	Becker	
2010/0312464	A1	12/2010	Fitzgerald	
2011/0035139	A1	2/2011	Konlditslotis	
2011/0043624	A1	2/2011	Haug	
2011/0060496	A1*	3/2011	Nielsen	G06Q 10/0631 701/31.4
2011/0077028	A1	3/2011	Wilkes	
2011/0091079	A1	4/2011	Yu-Song	
2011/0093159	A1	4/2011	Boling	
2011/0112995	A1	5/2011	Chang	
2011/0121960	A1	5/2011	Tsai	
2011/0125365	A1	5/2011	Larschan	
2011/0130916	A1	6/2011	Mayer	
2011/0140884	A1	6/2011	Santiago	
2011/0145042	A1	6/2011	Green	
2011/0153367	A1	6/2011	Amigo	
2011/0161116	A1	6/2011	Peak	
2011/0166773	A1	7/2011	Raz	
2011/0173015	A1	7/2011	Chapman	
2011/0208428	A1	8/2011	Matsubara	
2011/0212717	A1	9/2011	Rhoads	
2011/0213628	A1	9/2011	Peak	
2011/0224891	A1	9/2011	Iwuchukwu	
2011/0251752	A1	10/2011	DeLarocheliere	
2011/0251782	A1	10/2011	Perkins	
2011/0254676	A1	10/2011	Marumoto	
2011/0257882	A1	10/2011	McBurney	
2011/0273568	A1	11/2011	Lagassey	
2011/0283223	A1	11/2011	Vattinen et al.	
2011/0304446	A1	12/2011	Basson	
2012/0021386	A1*	1/2012	Anderson et al.	434/66
2012/0035788	A1	2/2012	Trepagnier	
2012/0041675	A1	2/2012	Juliver	
2012/0046803	A1	2/2012	Inou	
2012/0071140	A1	3/2012	Oesterling	
2012/0078063	A1	3/2012	Moore-Ede	
2012/0081567	A1	4/2012	Cote	
2012/0100509	A1	4/2012	Gunderson	
2012/0109447	A1	5/2012	Yousefi	
2012/0123806	A1	5/2012	Schumann	
2012/0134547	A1	5/2012	Jung	
2012/0150436	A1	6/2012	Rossano	
2012/0176234	A1	7/2012	Taneyhill	
2012/0190001	A1	7/2012	Knight	
2012/0198317	A1*	8/2012	Eppolito	G11B 27/034 715/202
2012/0210252	A1	8/2012	Fedoseyeva	
2012/0277950	A1	11/2012	Plante	
2012/0283895	A1	11/2012	Noda	
2013/0004138	A1	1/2013	Kilar	
2013/0006469	A1	1/2013	Green	
2013/0021148	A1	1/2013	Cook	
2013/0030660	A1	1/2013	Fujimoto	
2013/0073114	A1	3/2013	Nemat-Nasser	
2013/0096731	A1	4/2013	Tamari	
2013/0145269	A1	6/2013	Latulipe	
2013/0151980	A1	6/2013	Lee	
2013/0197774	A1	8/2013	Denson	
2013/0274950	A1	10/2013	Richardson	
2013/0317711	A1	11/2013	Plante	
2013/0332004	A1	12/2013	Gompert et al.	
2013/0345927	A1	12/2013	Cook	
2014/0025225	A1	1/2014	Armitage	
2014/0025254	A1	1/2014	Plante	
2014/0032062	A1	1/2014	Baer	
2014/0046550	A1*	2/2014	Palmer	G08G 1/167 701/48
2014/0047371	A1*	2/2014	Palmer	G06F 3/0484 715/771
2014/0058583	A1*	2/2014	Kesavan	B62D 41/00 701/1
2014/0094992	A1*	4/2014	Lambert	G07C 5/008 701/1
2014/0098228	A1	4/2014	Plante	
2014/0152828	A1	6/2014	Plante	
2014/0226010	A1	8/2014	Molin	
2014/0279707	A1	9/2014	Joshua	
2014/0280204	A1	9/2014	Avery	
2014/0300739	A1	10/2014	Mimar	
2014/0309849	A1	10/2014	Ricci	
2014/0335902	A1	11/2014	Guba	
2014/0336916	A1	11/2014	Yun	
2015/0035665	A1	2/2015	Plante	
2015/0057836	A1	2/2015	Plante	
2015/0112542	A1*	4/2015	Fuglewicz	G07C 5/0858 701/32.2
2015/0112545	A1*	4/2015	Binion	G07C 5/12 701/33.4
2015/0134226	A1	5/2015	Palmer	
2015/0135240	A1	5/2015	Shibuya	
2015/0189042	A1	7/2015	Sun	
2015/0222449	A1	8/2015	Salinger	
2015/0317846	A1	11/2015	Plante	

FOREIGN PATENT DOCUMENTS

CA	2692415		8/2011
CA	2692415	A1	8/2011
DE	20311262		9/2003
DE	202005008238		9/2005
DE	102004004669		12/2005
EP	0708427	A2	4/1996
EP	0840270	A2	5/1998
EP	0848270	A2	5/1998
EP	1170697	A2	1/2002
EP	1324274	A2	7/2003
EP	1355278	A1	10/2003
EP	1427165	A2	6/2004
EP	1818873	A1	8/2007
EP	2104075		9/2009
EP	2320387		5/2011
EP	2407943		1/2012
GB	2268608	A	1/1994
GB	2402530		12/2004
GB	2402530	A	12/2004
GB	2451485		2/2009
GB	2447184	B	6/2011
GB	2446994		8/2011
JP	58085110		5/1983
JP	S5885110	A	5/1983
JP	62091092		4/1987
JP	S6291092	A	4/1987
JP	S62166135	A	7/1987
JP	02056197		2/1990
JP	H0256197	A	2/1990
JP	H04257189	A	9/1992
JP	5294188		11/1993
JP	H09163357	A	6/1997
JP	H09272399	A	10/1997
JP	10076880		3/1998
JP	H1076880	A	3/1998
JP	2002191017		7/2002
KR	1000588169		12/2000
WO	8809023	A1	11/1988
WO	9005076		5/1990
WO	9427844		12/1994
WO	9600957	A1	1/1996
WO	9701246		1/1997
WO	9726750	A1	7/1997
WO	9937503		7/1999
WO	9940545	A1	8/1999
WO	9962741		12/1999
WO	0007150	A1	2/2000
WO	0028410	A1	5/2000
WO	0048033		8/2000
WO	0077620		12/2000
WO	0123214		4/2001
WO	0125054		4/2001
WO	0146710	A2	6/2001
WO	03045514		6/2003
WO	2006022824		3/2006
WO	2006022824	A2	3/2006
WO	2007067767		6/2007
WO	2009081234		7/2009

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	2011055743 A1	5/2011
WO	2013072939	5/2013
WO	2013159853	10/2013

OTHER PUBLICATIONS

Amended Complaint for Patent Infringement, Trade Secret Misappropriation, Unfair Competition and Conversion in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997-H-RBB, for the Southern District of California, Document 34, filed Oct. 20, 2011, pp. 1-15.

Amendment filed Dec. 23, 2009 during prosecution of U.S. Appl. No. 11/566,424.

Answer to Amended Complaint; Counterclaims; and Demand for Jury Trial in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997 H (RBB), for the Southern District of California, Document 47, filed Dec. 13, 2011, pp. 1-15.

U.S. Appl. No. 11/296,906, filed Dec. 8, 2005, File History.

U.S. Appl. No. 11/297,669, filed Dec. 8, 2005, File History.

U.S. Appl. No. 11/297,889, filed Dec. 8, 2005, File History.

U.S. Appl. No. 11/298,069, filed Dec. 9, 2005, File History.

U.S. Appl. No. 11/299,028, filed Dec. 9, 2005, File History.

U.S. Appl. No. 11/593,659, filed Nov. 7, 2006, File History.

U.S. Appl. No. 11/593,682, filed Nov. 7, 2006, File History.

U.S. Appl. No. 11/593,882, filed Nov. 7, 2006, File History.

U.S. Appl. No. 11/595,015, filed Nov. 9, 2006, File History.

U.S. Appl. No. 11/637,754, filed Dec. 13, 2006, File History.

U.S. Appl. No. 11/637,755, filed Dec. 13, 2006, File History.

Bill. 'DriveCam—FAQ', Dec. 12, 2003.

Bill Siuru, 'DriveCam Could Save You Big Bucks', Land Line Magazine, May-Jun. 2000.

Chris Woodyard, 'Shuttles save with DriveCam', Dec. 9, 2003.

Dan Carr, Flash Video Template: Video Presentation with Navigation, Jan. 16, 2006, http://www.adobe.com/devnet/fiash/articles/vidtemplate_mediapreso_flash8.html.

David Cullen, 'Getting a real eyeful', Fleet Owner Magazine, Feb. 2002.

David Maher, 'DriveCam Brochure Folder', Jun. 6, 2005.

David Maher, "DriveCam Brochure Folder", Jun. 8, 2005.

David Vogeleer et al., Macromedia Flash Professional 8Unleashed (Sams Oct. 12, 2005).

Del Lisk, 'DriveCam Training Handout Ver4', Feb. 3, 2005.

Drivecam, Inc., User's Manual for Drivecam Video Systems' Hindsight 20/20 Software Version 4.0 (2003).

DriveCam, Inc.'s Infringement Contentions Exhibit A, U.S. Pat. No. 6,389,340, Document 34.1, Oct. 20, 2011.

DriveCam, Inc.'s Infringement Contentions Exhibit B, U.S. Pat. No. 7,804,426, Document 34.2, Oct. 20, 2011.

DriveCam, Inc.'s Infringement Contentions Exhibit C, U.S. Pat. No. 7,659,827, Document 34.3, Oct. 20, 2011.

DriveCam, Inc.'s Infringement Contentions Exhibit D, Document 34.4, Oct. 20, 2011.

DriveCam—Illuminator Data Sheet, Oct. 2, 2004.

DriveCam Driving Feedback System, Mar. 15, 2004.

First Amended Answer to Amended Complaint and First Amended Counterclaims; and Demand for Jury Trial in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997 H (RBB), for the Southern District of California, Document 53, filed Dec. 20, 2011, pp. 1-48.

First Amended Answer to Amended Complaint and First Amended Counterclaims; and Demand for Jury Trial in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997 H (RBB), for the Southern District of California, Document 55, filed Jan. 3, 2012, pp. 86-103.

Franke, U., et al., Autonomous Driving Goes Downtown, IEEE Intelligent Systems, 13(6):40-48 (1988); Digital Object Identifier 10.1109/5254.736001.

Gallagher, B., et al., Wireless Communications for Vehicle Safety: Radio Link Performance and Wireless Connectivity Methods, Vehicular Technology Magazine, IEEE, 1(4):4-24 (2006); Digital Object Identifier 10.1109/MVT.2006.343641.

Gandhi, T., et al., Pedestrian Protection Systems: Issues, Survey, and Challenges, IEEE Transactions on Intelligent Transportation Systems, 8(3):413-430 (2007); Digital Object Identifier 10.1109/TITS.2007.903444.

Gary and Sophia Rayner, Final Report for Innovations Deserving Exploratory Analysis (IDEA) Intelligent Transportation Systems (ITS) Programs' Project 84, I-Witness Black Box Recorder, San Diego, CA. Nov. 2001.

GE published its VCR User's Guide for Model VG4255 in 1995.

Glenn Oster, 'Hindsight 20/20 v4.0 Software Installation', 1 of 2, Jun. 20, 2003.

Glenn Oster, 'HindSight 20/20 v4.0 Software Installation', 2 of 2, Jun. 20, 2003.

Glenn Oster, 'Illuminator Installation', Oct. 3, 2004.

I/O Port Racing Supplies' website discloses using Traqmate's Data Acquisition with Video Overlay system in conjunction with professional driver coaching sessions (available at http://www.ioportracing.com/Merchant2/ merchant.mvc?Screen=CTGY &Categorys- ub.--Code=coaching)., printed from site on Jan. 11, 2012.

International Search Report and Written Opinion issued in PCT/US07/68325 on Feb. 27, 2008.

International Search Report and Written Opinion issued in PCT/US07/68328 on Oct. 15, 2007.

International Search Report and Written Opinion issued in PCT/US07/68329 on Mar. 3, 2008.

International Search Report and Written Opinion issued in PCT/US07/68332 on Mar. 3, 2008.

International Search Report and Written Opinion issued in PCT/US07/68334 on Mar. 5, 2008.

International Search Report for PCT/US2006/47055, Mailed Mar. 20, 2008 (2 pages).

International Search Report issued in PCT/US2006/47042 mailed Feb. 25, 2008.

J. Gallagher, 'Lancer Recommends Tech Tool', Insurance and Technology Magazine, Feb. 2002.

Jessyca Wallace, 'Analyzing and Processing DriveCam Recorded Events', Oct. 6, 2003.

Jessyca Wallace, 'Overview of the DriveCam Program', Dec. 15, 2005.

Jessyca Wallace, 'The DriveCam Driver Feedback System', Apr. 6, 2004.

Joint Claim Construction Chart, U.S. Pat. No. 6,389,340, 'Vehicle Data Recorder' for Case No. 3:11-CV-00997-H-RBB, Document 43-1, filed Dec. 1, 2011, pp. 1-33.

Joint Claim Construction Chart in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 11-CV-0997-H (RBB), for the Southern District of California, Document 43, filed Dec. 1, 2011, pp. 1-2.

Joint Claim Construction Worksheet, U.S. Pat. No. 6,389,340, 'Vehicle Data Reporter' for Case No. 3:11-CV-00997-H-RBB, Document 44-1, filed Dec. 1, 2011, pp. 1-10.

Joint Claim Construction Worksheet in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997 H (RBB), for the Southern District of California, Document 44, filed Dec. 1, 2011, pp. 1-2.

Joint Motion for Leave to Supplement Disclosure of Asserted Claims and Preliminary Infringement Contentions in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-cv-00997-H-RBB, Document 29, filed Oct. 12, 2011, pp. 1-7.

Julie Stevens, 'DriveCam Services', Nov. 15, 2004.

Julie Stevens, 'Program Support Roll-Out & Monitoring', Jul. 13, 2004.

Jung, Sang-Hack, et al., Egomotion Estimation in Monocular Infrared Image Sequence for Night Vision Applications, IEEE Workshop on Applications of Computer Vision (WACV '7), Feb. 2007, pp. 8-8; Digital Object Identifier 10.1109/WACV.2007.20.

JVC Company of America, JVC Video Cassette Recorder HR-IP820U Instructions (1996).

(56) **References Cited**

OTHER PUBLICATIONS

Kamijo, S., et al., A Real-Time Traffic Monitoring System by Stochastic Model Combination, IEEE International Conference on Systems, Man and Cybernetics, 4:3275-3281 (2003).
Kamijo, S., et al., An Incident Detection System Based on Semantic Hierarchy, Proceedings of the 7th International IEEE Intelligent Transportation Systems Conference, Oct. 3-6, 2004, pp. 853-858; Digital Object Identifier 10.1109/ITSC.2004.1399015.
Karen, 'Downloading Options to HindSight 20120', Aug. 6, 2002.
Karen, 'Managers Guide to the DriveCam Driving Feedback System', Jul. 30, 2002.
Kathy Latus (Latus Design), 'Case Study—Cloud 9 Shuttle', Sep. 23, 2005.
Kathy Latus (Latus Design), 'Case Study—Lloyd Pest Control', Jul. 19, 2005.
Kathy Latus (Latus Design), 'Case Study—Time Warner Cable', Sep. 23, 2005.
Ki, Yong-Kul, et al., A Traffic Accident Detection Model using Metadata Registry, Proceedings of the Fourth International Conference on Software Engineering Research, Management and Applications; Aug. 9-11, 2006 pp. 255-259 Digital Object Identifier 10.1109/SERA.2006.8.
Kitchin, Charles. "Understanding accelerometer scale factor and offset adjustments." Analog Devices (1995).
Lin, Chin-Teng et al., EEG-based drowsiness estimation for safety driving using independent component analysis; IEEE Transactions on Circuits and Systems-I: Regular Papers, 52(12):2726-2738 (2005); Digital Object Identifier 10.1109/TCSI.2005.857555.
Lisa McKenna, 'A Fly on the Windshield?', Pest Control Technology Magazine, Apr. 2003.
Miller, D.P., Evaluation of Vision Systems for Teleoperated Land Vehicles. Control Systems Magazine, IEEE, 8(3):37-41 (1988); Digital Identifier 10.1109/37.475.
Munder, S., et al., Pedestrian Detection and Tracking Using a Mixture of View-Based Shape-Texture Models, IEEE Transactions on Intelligent Transportation Systems, 9(2):333-343 (2008); Digital Identifier 10.1109/TITS.2008.922943.
Panasonic Corporation, Video Cassette Recorder (VCR) Operating Instructions for Models No. PV-V4020/PV-V4520.
Passenger Transportation Mode Brochure, May 2, 2005.
Patent Abstracts of Japan vol. 007, No. 180 (P-215), Aug. 9, 1983 & JP 58 085110 A (Mitsuhisa Ichikawa), May 21, 1983.
Patent Abstracts of Japan vol. 011, No. 292 (E-543), Sep. 19, 1987 & JP 62 091092 A (OK ENG:KK), Apr. 25, 1987.
Patent Abstracts of Japan vol. 012, No. 001 (M-656), Jan. 6, 1988 & JP 62 166135 A (Fuji Electric Co Ltd), Jul. 22, 1987.
Patent Abstracts of Japan vol. 014, No. 222 (E-0926), May 10, 1990 & JP 02 056197 A (Sanyo Electric Co Ltd), Feb. 26, 1990.
Patent Abstracts of Japan vol. 017, No. 039 (E-1311), Jan. 25, 1993 & JP 04 257189 A (Sony Corp), Sep. 11, 1992.
Patent Abstracts of Japan vol. 1997, No. 10, Oct. 31, 1997 & JP 09 163357 A (Nippon Soken Inc), Jun. 20, 1997.
Patent Abstracts of Japan vol. 1998, No. 02, Jan. 30, 1998 & JP 09 272399 A (Nippon Soken Inc), Oct. 21, 1997.
Patent Abstracts of Japan vol. 1998, No. 8, Jun. 30, 1998 & JP 10 076880 A (Muakami Corp), Mar. 24, 1998.
PCT/US2010/022012, Invitation to Pay Additional Fees with Communication of Partial International Search, Jul. 21, 2010.
Quinn Maughan, 'DriveCam Enterprise Services', Jan. 5, 2006.
Quinn Maughan, 'DriveCam Managed Services', Jan. 5, 2006.
Quinn Maughan, 'DriveCam Standard Edition', Jan. 5, 2006.
Quinn Maughan, 'DriveCam Unit Installation', Jul. 21, 2005.
Quinn Maughan, 'Enterprise Services', Apr. 17, 2006.
Quinn Maughan, 'Enterprise Services', Apr. 7, 2006.
Quinn Maughan, 'Hindsight Installation Guide', Sep. 29, 2005.
Quinn Maughan, 'Hindsight Users Guide', Jun. 7, 2005.
Ronnie Rittenberry, 'Eyes on the Road', Jul. 2004.
Traqmate GPS Data Acquisition's Traqmate Data Acquisition with Video Overlay system was used to create a video of a driving event on Oct. 2, 2005 (available at http://www.trackvision.net/phpBB2/viewtopic.php?t=51&sid=1184fbbcbe3be5c87ffa0f2ee6e2da76), printed from site on Jan. 11, 2012.
U.S. Appl. No. 12/691,639, entitled 'Driver Risk Assessment System and Method Employing Selectively Automatic Event Scoring', filed Jan. 21, 2010.
U.S. Appl. No. 11/377,167, Final Office Action dated Nov. 8, 2013.
U.S. Appl. No. 11/377,157, filed Mar. 16, 2006 entitled, "Vehicle Event Recorder Systems and Networks Having Parallel Communications Links".
U.S. Appl. No. 11/377,167, filed Mar. 16, 2006 entitled, "Vehicle Event Recorder Systems and Networks Having Integrated Cellular Wireless Communications Systems".
USPTO Final Office Action for U.S. Appl. No. 11/297,669, mailed Nov. 7, 2011, 15 pages.
USPTO Final Office Action for U.S. Appl. No. 13/957,810, mailed Jun. 27, 2014, 24 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/296,906, mailed Apr. 2, 2009, 7 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/296,906, mailed Nov. 6, 2009, 9 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/297,669, mailed Apr. 28, 2011, 11 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/299,028, mailed Apr. 24, 2008, 9 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Nov. 19, 2007, 7 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Nov. 25, 2011, 9 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Sep. 11, 2008, 8 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,167, mailed Jun. 5, 2008, 11 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/800,876, mailed Dec. 1, 2010, 12 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/800,876, mailed Dec. 20, 2011, 8 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 12/096,591, mailed May 20, 2014, 19 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/296,907, Mailed Mar. 22, 2007 (17 pages).
USPTO Non-final Office Action mailed Aug. 27, 2009 during prosecution of U.S. Appl. No. 11/566,424.
USPTO Non-Final Office Action mailed Nov. 27, 2013 in U.S. Appl. No. 13/957,810, filed Aug. 2, 2013.
Veeraraghavan, H., et al., Computer Vision Algorithms for Intersection Monitoring, IEEE Transactions on Intelligent Transportation Systems, 4(2):78-89 (2003); Digital Object Identifier 10.1109/TITS.2003.821212.
Wijesoma, W.S., et al., Road Curb Tracking in an Urban Environment, Proceedings of the Sixth International Conference of Information Fusion, 1:261-268 (2003).
Inovate Motorsports, OT-1 16 Channel OBD-II Interface User Manual, Version 1.0, Nov. 28, 2007, pp. 3, 4, 21 & 27.
Trivinci Systems, LLC, Race-Keeper Systems User Guide, Jan. 2011, v1, 1.02, pp. 34 and 39.
USPTO Non-Final Office Action for U.S. Appl. No. 14/036,299, mailed Aug. 12, 2014.
DriveCam, Inc.'s Infringement Contentions Exhibit B, U.S. Pat. No. 7,659,827. Aug. 19, 2011. (29 pgs.).
DriveCam, Inc.'s Infringement Contentions Exhibit C, U.S. Pat. No. 7,804,426. Aug. 19, 2011. (47 pgs.).
DriveCam's Disclosure of Asserted Claims and Preliminary Infringement Contentions in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997-H-RBB, for the Southern District of California. Aug. 19, 2011. (6 pgs.).
Preliminary Claim Construction and Identification of Extrinsic Evidence of Defendant/Counterclaimant SmartDriveSystems, Inc. in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997-H (RBB), for the Southern District of California. Nov. 8, 2011. (13 pgs.).
Supplement to DriveCam's Disclosure of Asserted Claims and Preliminary Infringement Contentions in *DriveCam, Inc.* v.

(56) **References Cited**

OTHER PUBLICATIONS

SmartDrive Systems, Inc., Case No. 3:11-CV-00997-H-RBB, for the Southern District of California. Oct. 14, 2011. (7 pgs.).
"DriveCam, Inc's Disclosure of Proposed Constructions and Extrinsic Evidence Pursuant to Patent L.R. 4.1.a & 4.1.b" Disclosure and Extrinsic Evidence in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997-H-RBB, for the Southern District of California. Nov. 8, 2011, 68 pages.
"DriveCam Driving Feedback System", DriveCam brochure, Jun. 12, 2001, Document #6600128, 2 pages.
"DriveCam Driving Feedback System" DriveCam brochure, Mar. 15, 2004, 4 pages.
"DriveCam Passenger Transportation Module", DriveCam brochure, Oct. 26, 2001, 2 pages.
"DriveCam Video Event Data Recorder", DriveCam brochure, Nov. 6, 2002, Document #6600127, 2 pages.
"Responsive Claim Construction and Identification of Extrinsic Evidence of Defendani/Counterclaimant SmartDrive Systems, Inc." Claim Construction and and Extrinsic Evidence in *DriveCam, Inc.* v. *SmartDrive Systems, Inc.*, Case No. 3:11-CV-00997-H (RBB), for the Southern District of California. Nov. 15, 2011, 20 pages.
"Sonic MyDVD 4.0: Tutorial: Trimming video segments". Tutorial for software bundled with Adaptec VideoOh! DVD USB 2.0 Edition, 2003, 13 pages.
"User's Manual for DriveCam Video Systems' HindSight 20/20 Software Version 4.0" DriveCam Manual, San Diego, 2003, Document #6600141-1, 54 pages.
Canadian Office Action issued in Application No. 2,632,685 dated Jan. 30, 2015; 5 pages.
Dan Maher, "DriveCam Taking Risk Out of Driving", DriveCam brochure folder, Jun. 6, 2005, 6 pages.
Del Lisk, "DriveCam Training Seminar" Handout, 2004, 16 pages.
European Examination Report issued in EP 07772812.9 on Jan. 22, 2015; 5 pages.
Jean (DriveCam vendor) "DriveCam Driving Feedback System", DriveCam brochure, Nov. 6, 2002, Document #6600128-1, 2 pages.
Notice of Allowance Allowance for U.S. Appl. No. 14/036,299, mailed Mar. 20, 2015, 5 pages.
Notice of Allowance Application for U.S. Appl. No. 11/566,424, mailed Feb. 26, 2010, 6 pages.
Notice of Allowance for U.S. Appl. No. 11/377,164, mailed Dec. 3, 2014, 5 pages.
Notice of Allowance for U.S. Appl. No. 11/377,164, mailed Feb. 13, 2015, 2 pages.
Notice of Allowance for U.S. Appl. No. 11/377,164, mailed Feb. 25, 2014, 2 pages.
Notice of Allowance for U.S. Appl. No. 11/377,164, mailed Nov. 18, 2013, 7 pages.
Notice of Allowance for U.S. Appl. No. 11/377,167, mailed Apr. 1, 2015, 7 pages.
Notice of Allowance for U.S. Appl. No. 11/800,876, mailed Apr. 19, 2012, 8 pages.
Notice of Allowance for U.S. Appl. No. 13/957,810, mailed Jun. 8, 2015, 10 pages.
USPTO Final Office Action for U.S. Appl. No. 11/296,906, mailed Aug. 8, 2012, 15 pages.
USPTO Final Office Action for U.S. Appl. No. 12/096,591, mailed Dec. 5, 2014, 23 pages.
USPTO Final Office Action for U.S. Appl. No. 12/096,591, mailed Jul. 18, 2012, 15 pages.
USPTO Final Office Action for U.S. Appl. No. 12/096,591, mailed Nov. 7, 2013, 14 pages.
USPTO Final Office Action for U.S. Appl. No. 13/957,810, mailed Jun. 27, 2014, 22 pages.
USPTO Final Office Action for U.S. Appl. No. 14/036,299, mailed Feb. 24, 2015, 9 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/296,906, mailed Apr. 8, 2014, 19 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/296,906, mailed Jun. 12, 2012, 13 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Apr. 7, 2014, 7 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Aug. 18, 2014, 5 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,164, mailed Sep. 10, 2012, 10 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 11/377,167, mailed Jun. 27, 2013, 11 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 12/096,591, mailed Jun. 14, 2011, 8 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 12/096,591, mailed Mar. 27, 2013, 16 pages.
USPTO Non-Final Office Action for U.S. Appl. No. 13/957,810, mailed Apr. 17, 2015, 6 pages.
USPTO Non-final Office Action for U.S. Appl. No. 13/957,810, mailed Nov. 27, 2013, 18 pages.
USPTO Non-Final Office Action mailed Jan. 4, 2016 in U.S. Appl. No. 14/529,134, filed Oct. 30, 2014 (65 pgs).
PCT International Search Report and Written Opinion for PCT/US15/60721 dated Feb. 26, 2016, 11 pages.
Trivinci Systems, LLC, "Race-Keeper System User Guide", V1 .1.02, Jan. 2011, p. 21.
PCT International Search Report and Written Opinion for PCT/IB16/51863, dated Sep. 16, 2016.

* cited by examiner



4
3
Event: OJEC-1WK6 Mar. 15, 2012 Driver:
Driver, John
Coaching
done
15
5
Event List
Review
Severity !! Score 50
Reviewed: Mar 16, 2012
4:19:50.00 PM
Accelerating
Other Task
LOC 32.8295 : -117.2733
BackCam | StreetView | MapView | BirdseyeView
Driver View
11
13
IDF
Green
Brake ON
ABS OFF
ATC OFF
ESC N/A
Throttle 100%
EngLoad 81%
PTO OFF
MIL ON
2260
31
fore/aft
-0.6
0.01
left/right
7
1X
4:19:38.50 PM
9
G force
0.4
0.2
0
-0.2
-0.4
-0.6
4:19:35 PM
4:19:40 PM
4:19:45 PM
4:19:50 PM
4:19:55 PM
4:20:00 PM

FIG. 1A



5
7
9
3
19
15
SMARTDRIVE
EVENT PROPERTIES
EVENT LIST
REVIEW
Following Distance SmartDrive
Shock SmartDrive
Collision Avoidance SmartDrive
EVENT GJEG-255E Aug 28, 2013
DRIVER
BRAKE N/A
ABS OFF
ATC OFF
ESC OFF
3.1 sec
THROTTLE 42%
ENG LOAD N/A
PTO OFF
ENGINE N/A
1277 rpm
14 mph
ECU
11:40:20.00 AM
SELECT ANY 2 OPTIONS
MAP
CHART
SPEED
FORWARD/BACKWARD
SIDE TO SIDE
G force
mph
11:40:20 AM
11:40:25 AM
11:40:30 AM
11:40:35 AM
11:40:40 AM
11:40:45 AM
11:40:50 AM

FIG. 1B



3
5
7
9
15
19
SMARTDRIVE
EVENT
EVENT PROPERTIES
EVENT LIST
REVIEW
MAP
CHART
SELECT ANY 2 OPTIONS
6:52:54.00 AM
6:52:55 AM
6:53:05 AM
6:53:15 AM
6:53:20 AM
mph
54
48
42
36
30
24
18
12
6
LOW
BRAKE
ABS
ATC
ESC
THROTTLE
ENG LOAD
RPC
ENGINE
FORWARD/BACKWARD
SIDE TO SIDE
1369
rpm
55
mph
G force

FIG. 1C



3
4
5
7
9
FORWARD/
BACKWARD
-0.15
SIDE TO SIDE
0.00
1364
rpm
21
mph
rpm
Low
THROTTLE 0%
ENG LOAD N/A
PTO OFF
ENGINE N/A
BRAKE OFF
ABS OFF
ATC OFF
ESC OFF
19
mph 1.2 sec
6:03:29.00 AM
FORWARD/BACKWARD
SIDE TO SIDE
SPEED
SELECT ANY 2 OPTIONS
MAP
CHART
G force
0.5
0
-0.5

FIG. 1D



5
7
5
3
4
50 Feet
34.011545 -117.524565
FORWARD/
BACKWARD
0.00
SIDE TO SIDE
-0.12
16
mph
1384
rpm
9:35:55.00 AM
LOCATION
Harrel St
BRAKE OFF
ABS OFF
A/C N/A
ESC N/A
THROTTLE 30%
ENG LOAD 40%
PTO OFF
ENGINE N/A
MAP
CHART
Road
Aerial
Bird's eye
Street side

FIG. 1E



5
7
5
3
4
FORWARD/
BACKWARD
-0.19
SIDE TO SIDE
-0.02
THROTTLE 30%
ENG LOAD 40%
PTO OFF
ENGINE N/A
598
rpm
19
mph
8:52:01.10 AM
BRAKE OFF
ABS OFF
ATC N/A
ESC N/A
50 Feet
LOCATION
Street side
Bird's eye
Aerial
Road
MAP
CHART

FIG. 1F



7
5
4
15
SMARTDRIVE
EVENT PROPERTIES
EVENT LIST
REVIEW
EVENT OJEG-3F5E Aug 28, 2013
DRIVER White, Johnny [LANORTA-00]
Reading Paperwork
SmartDrive
11:08:26.00 AM
Shock
SmartDrive
Operating Other Mobile Device
SmartDrive
Mobile Phone - Texting/ Calling
SmartDrive
FORWARD/BACKWARD 0.18
SIDE TO SIDE 0.87
11:08:26.15 AM
MAP
CHART
Road
Aerial
Bird's eye
Street side
LOCATION
50 Feet
Howard Blvd
Van Buren Blvd
Mich

FIG. 1G



BackCam | StreetView | MapView | BirdseyeView | Driver View
LOC 32.8295 : -117.2733
24
25
21
selected
19
19
23
1X
4:19:38.50 PM
22

FIG. 2



38
37
31
LOC 32.8295 : -117.2733
BackCam
StreetView
MapView
BirdseyeView
Driver View
34
35
33
selected
1X
4:19:38.50 PM
32

FIG. 3



43
42
46
47
LOC 32.8295 : -117.2733
45
BackCam | StreetView | MapView | BirdseyeView | Driver View
Selected
44
1X
4:19:38.50 PM
41

FIG. 4



57
Nautilus St
Bonair Way
59
58
Bonair St
Bonair St
Bonair Pl
Bonair Pl
Tyrian St
BackCam
StreetView
MapView
BirdseyeView
Driver View
LOC 32.8295 : -117.2733
55
56
54
selected
60
52
1X
4:19:38.50 PM
51
53

FIG. 5



63
64
65
LOC 32.8295 : -117.2733
BackCam
StreetView
MapView
BirdseyeView
Driver View
68
66
selected
67
62
1X
4:19:38.50 PM
61

FIG. 6



76
78
fore/aft
0.28
0.08
left/right
77
75
79
1X
4:19:38.50 PM
72
G force
0.4
0.2
0
-0.2
-0.4
-0.6
74
73
71
710
4:19:35 PM
4:19:40 PM
4:19:45 PM
4:19:50 PM
4:19:55 PM
4:20:00 PM

FIG. 7




FIG. 8



94
96
99
95
98
93
914
IDF
Brake OFF
Throttle
60%
ABS OFF
EngLoad
71%
ATC OFF
PTO OFF
912
ESC N/A
MIL ON
Green
911
910
913
92
1X
4:19:38.50 PM
91

FIG. 9



102
Review
104
Severity !! Score 50
103
105
Reviewed: Mar 16, 2012
106
4:19:50.00 PM
107
Accelerating
Other Task
109
Our driver was occupied with a task or object unrelated to operation of the vehicle for 3 or more seconds while the vehicle was in motion.
1011
108
1010
1012
1X
4:19:38.50 PM
1014
Temperature: -2C
Wind: 18 knots
1013
101
Glare:
θ = 10°
φ = 35°
1015

FIG. 10



Event: OJEC-1WK6 Mar. 15, 2012
Driver:
Driver, John
Coaching
done
112
113
114
115
1X
4:19:38.50 PM
111

FIG. 11

VEHICLE EVENT PLAYBACK APPARATUS AND METHODS

FIELD

The following invention disclosure is generally concerned with multi-media playback systems and specifically concerned with playback systems for vehicle event record playback and analysis.

BACKGROUND

Multi-media players are known. Multi-media players are designed to run on computer systems and play back electronic audio and video files of specific types. The multi-media players typically include user interfaces for users to control playback. For example, a user may control 'Windows Media Player®' to play video encoded media files consistent with a format defined in the MP4 standard.

In some multi-media players the user interface controls are customized based on a user's internet browsing habits, computer system characteristics, and network authentication information. In some multi-media players, a user may control the visual appearance of the information displayed to the user.

SUMMARY

One aspect of the disclosure relates to vehicle event record playback systems including devices and methods. It is a primary function of these systems to provide review and analysis means suited and arranged in view of information captured by vehicle event recorders, active safety systems, and/or other systems installed in and/or coupled to a vehicle. In contrast to the prior art, systems presented here do not suffer limitations which prevent their use for synchronized display of data captured by vehicle event recorders, active safety systems, and/or other systems.

Vehicle event recorders may produce event record datasets in response to anomalies and/or other events detected during vehicle operation. Active safety systems may alert a vehicle driver to potentially dangerous conditions detected in and/or around a vehicle during operation of the vehicle. Because event record datasets and/or information generated by the active safety system may contain considerable amounts of data in many data formats and arrangements, they may be difficult to parse, read, interpret, and/or use. In known systems, some vehicle event recorder and/or active safety system data was manually reviewed and certain data subsets of greatest importance were manually developed from raw data into visual presentations by way of standard software such as spreadsheet plotting utilities.

Vehicle event data playback systems described herein may include advanced playback of vehicle event recorder data, active safety system data, vehicle subsystem data and/or other data. The playback of the vehicle event recorder data, the active safety system data, the vehicle subsystem data, and/or other data may be in real time, and/or may be played back at a later time. The playback of the vehicle event recorder data may be played back via a user interface located in the vehicle, a remotely located user interface, a remotely located computing device, and/or via other systems. These systems may include visual devices arranged to express vehicle performance data in graphical, image and/or alpha-numeric forms. These systems may be arranged to present data in logical arrangements whereby many different types of datasets collected at various vehicle sensors may be presented in time synchronized schemes along with a plurality of complementary data. Data presented in this fashion may permit greater analysis and may enable reviewers to devise coaching feedback, for example.

In a first example, vehicle performance data may be collected by way of a vehicle's onboard electronic control unit (ECU). The ECU may include an engine control module (ECM), for example. The data from the ECU may be included in, and/or associated with other data collected at the same (or nearly same) instant in time from other sources such as data from aftermarket sensors (e.g., an accelerometer) coupled with the vehicle, data from an active safety system installed in and/or coupled with the vehicle, and/or data from other sources that generate information relevant to vehicle operation. An event record may be prepared in a manner where at least some data measurements are associated with a timestamp or other time synchronization scheme. In this way, synchronized playback of data from a plurality of data sources may be enabled.

On playback, a human reviewer may be presented with simultaneous views and expressions of multiple data elements. The individual data elements may be presented in a visual nature on a common display field of a graphical user interface (GUI). Since these data elements often have a high level of interdependence, simultaneous expression of their instantaneous values in a time sequenced series playback enables may enhance vehicle event record review.

Graphical user interfaces of these systems may include control objects. The control objects may be responsive to data values of vehicle event record datasets. The control objects may be expressed visually. A control object may be a visual element in the graphical user interface that is associated with data and/or a data stream from one or more sensors. Control objects may include parametric input couplings, data interfaces, underlying logic code which defines performance, a visual expression, an event set, triggers, an instantaneous state, and/or other control objects. Combinations of various related control objects may operate together in synchronization to characterize and/or describe actions and/or states associated with a vehicle and its many subsystems during a recorded event.

The control objects may be arranged to visually express data collected from vehicle subsystems in graphical and/or alphanumeric forms. In some implementations, the control objects may visually express data associated with standard ECU systems, an active safety system, a vehicle event recorder, and/or other systems, and present that data in one or more visual forms in conjunction with simultaneous playback of related video, for example.

The control objects of the graphical user interface may be coupled to an event timeline whereby presentation of data by the control objects conforms to the event timing. An event timeline may have a start-time, an end-time, and/or a continuous period of time therebetween. An event record dataset may include an event timeline definition for events recorded at a vehicle event recorder. For example, the controls presented by the GUI may be connected to a single timeline and that timeline may be coupled to the event time.

In some implementations of these systems, 'video playback' may be an included feature. Accordingly, video players may generally be included as a primary element of these graphical user interfaces. Video player systems of these devices may include those suitable for playback of common video captured at a vehicle event recorder video camera. These video players may also be suitable for playback of virtual video. Virtual video may include image series playback where the images are from sources other than a vehicle

event recorder. These may include forward and aft video camera views, street view image series, mapview image series, and even bird's eye view playback. Video playback may be synchronized with the ECU data, active safety system data, and/or vehicle event recorder data, for example.

Other control objects found in the playback apparatus may include graphical representations of acceleration data in one or more coupled controls. One feature may relate to a notation facility which may be coupled to an event timeline. The notation facility permits replay of manually prepared notes to which a time Association has been made and assigned in synchronization with event replay.

These and other objects, features, and characteristics of the system and/or method disclosed herein, as well as the methods of operation and functions of the related elements of structure and the combination of parts and economies of manufacture, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limits of the invention. As used in the specification and in the claims, the singular form of "a", "an", and "the" include plural referents unless the context clearly dictates otherwise.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims and drawings where:

FIGS. **1**A-**1**G illustrate examples of a view of a graphical user interface which illustrates a version of these systems;

FIG. **2** presents a timeline control time synchronized with images presented in related image control objects;

FIG. **3** illustrates side-by-side, time synchronized video players coupled to two video data sources related via a vehicle event record dataset;

FIGS. **4-6** show additional versions of side-by-side time synchronized video players similarly coupled to related video from sources other than vehicle event recorders;

FIG. **7** illustrates coupled control objects designed to express data both graphically and alphanumerically, wherein the control objects may be coupled to, and/or responsive to a vehicle event timeline;

FIG. **8** includes illustrations of a version of vehicle speed and engine speed control objects synchronized and commonly coupled to a timeline control;

FIG. **9** is a drawing of a plurality of control objects which are bound to standard vehicle sensors via on-board diagnostics and/or engine control module systems of a subject vehicle;

FIG. **10** presents a time responsive notation field type control object and its contents which are bound and responsive to an event timeline; and

FIG. **11** indicates additional auxiliary elements which may be included in some of these graphical user interface versions.

DETAILED DESCRIPTION

FIGS. **1**A-**1**G illustrate various views **3** of a graphical user interface included in and/or associated with a vehicle event data playback apparatus. The graphical user interface and/or the vehicle event data playback apparatus described herein may be configured to visually present a user with information related to operation of a vehicle. In some implementations, the user may review the information related to operation of the vehicle in real time, responsive to the vehicle being involved in a vehicle event, responsive to an active safety system alert, and/or at other times. The vehicle event may include an active safety system alert (e.g., events on the vehicle bus that indicate activations of active safety system), an accident, a specific driving maneuver, vehicle speed exceeding a set threshold or the posted speed limit, a narrowly avoided accident where a driver braked hard and/or swerved, trigger activations from external systems, a driver pressing a button (an/or gesturing via some other interface) designed to indicate an event, and/or other events. Specific driving maneuvers and/or active safety system alerts may be related to swerving, a U-turn, freewheeling, over-revving, short following (e.g. tailgating), a pedestrian detection and/or collision warning, driving in reverse, vehicle rollover, antilock braking, a forward collision warning, a lane departure warning, other events and/or maneuvers.

In some implementations, an active safety system may be installed in the vehicle at manufacture. In some implementations, the active safety system may be an aftermarket system installed in and/or coupled with the vehicle. The active safety system may be configured to detect and/or alert a vehicle driver to dangerous and/or other driving conditions. An active safety system alert may cause the driver to take action to prevent and/or lessen the severity of collisions, for example, and/or other undesired events. The active safety system may include one or more sensors, one or more processors, a user interface, and/or other components. The one or more active safety system sensors may be configured to generate output signals conveying information related to vehicle safety and/or other information. The one or more processors may be configured to detect unsafe conditions during operation of the vehicle based on the output signals from the active safety system sensors, and/or other sources of information. The one or more processors may be configured to generate one or more alerts responsive to detection of unsafe conditions. The active safety system may be manufactured by one or more manufacturers including, for example, Meritor-Wabco, Bendix, Mobileye and/or other active safety system manufacturers.

The vehicle event data playback apparatus visually presents information that is generated based on output signals from one or more sensors associated with the vehicle. The vehicle event data playback apparatus may synchronize the presented information such that information from individual sensors may be compared and/or viewed at the same time by the user. The information from individual sensors may be compared and/or viewed at the same time by the user at one or more time points before, during, and/or after a vehicle event, an active safety system alert, and/or at other times.

The sensors may be configured to generate output signals conveying information related to the operation and/or the context of the vehicle. The sensors may be configured to generate output signals conveying information related to one or more operating parameters of the vehicle. Information related to the operation of the vehicle, the context of the vehicle, and/or operating parameters of the vehicle may include vehicle safety information, vehicle event information, vehicle environment information, vehicle subsystem information, and/or other information. Information related to the operation of the vehicle, the context of the vehicle, and/or operating parameters of the vehicle may include

feedback information from one or more of the mechanical systems of the vehicle, and/or other information. In some implementations, at least one of the sensors may be an active safety system sensor. In some implementations, at least one of the sensors may be a vehicle system sensor associated with an ECU system of the vehicle. Information related to the context of the vehicle may include information related to the environment in and/or around vehicle. In some implementations, the output signals conveying the information related to the context of the vehicle may be generated via non-standard aftermarket sensors installed in the vehicle as part of a vehicle event recorder, for example. The non-standard aftermarket sensors may include, for example, a video camera, an accelerometer, a gyroscope, a geolocation sensor (e.g., a GPS device), a radar detector, an audio sensor (e.g., a microphone), and/or other sensors.

The vehicle event playback apparatus may include and/or communicate with the vehicle event recorder. The vehicle event recorder may be configured to record data associated with vehicle events. The vehicle events may be triggered to be recorded based on the information generated by the active safety system (e.g., the active safety system sensors and/or the active safety system processor(s)), the information from the non-standard aftermarket sensors installed in the vehicle, the information from the vehicle system sensors associated with an ECU system of the vehicle, pre-determined vehicle event profiles, and/or other information. In some implementations, the vehicle event recorder may be triggered to record the vehicle events based on a trigger, for example. A trigger may include and/or result from a comparison of the information conveyed by the output signals from the sensors to criteria included in the pre-determined vehicle event profiles. A trigger may be one or more logical criteria that is determined to have been met by the system. The vehicle event recorder may be configured to obtain one or more pre-determined vehicle event profiles. The one or more pre-determined vehicle event profiles may include criteria sets associated with the vehicle events. A specific vehicle event may be triggered to be recorded based on the information conveyed by the output signals and the obtained pre-determined vehicle event profiles by comparing the information conveyed by the output signals (and/or information determined based on the output signals) to the criteria sets such that a specific vehicle event is triggered to be recorded responsive to the information in and/or determined from the output signals satisfying one or more individual criteria in a criteria set associated with the specific vehicle event. A vehicle event recorded by the vehicle event recorder may include audio information, video information, information from the ECU, information from the active safety system, and/or other information.

By way of a non-limiting example, the system may detect that a driver has exited his lane 3 times in a 90 second period, where the criteria for triggering the event included activation of a lane departure warning system (e.g., information may be communicated across the ECU to the present system) and time elapsed. As another example, an event may be triggered to be stored based on criteria that include following distance as measured by an active safety system and time (e.g., following distance of less than 1.4 seconds for 10 or more seconds), where the distance is measured and based on a formula inclusive of time.

The vehicle event playback apparatus and/or the vehicle event recorder may include one or more processors. The processors may be configured to synchronize (e.g., systematically align) the information included in the output signals from the one or more sensors associated with the vehicle (e.g., the active safety system sensors, the vehicle system sensors associated with the ECU system of the vehicle, the non-standard aftermarket sensors installed in the vehicle as part of the vehicle event recorder). The processors may synchronize the information even though the information from the individual sensors may not be generated and/or received by the vehicle event playback apparatus at the same time. Synchronization may include associating data from two or more individual output signals with a single event timeline for a given event. An event timeline may have a start-time, an end-time, and/or a continuous period of time therebetween, for example.

In some implementations, the output signals from the one or more sensors may include time information indicating a time the information was generated, the order in which the information was generated, a timing of the generated information (e.g., periodic and/or continuous), and/or other time information. In some implementations, the processors may associate information in the individual output signals with a corresponding time location in the event timeline based on the time information included in the output signals.

In some implementations, associating information in the individual output signals to a corresponding time location in the event timeline based on the time information included in the output signals may not produce a synchronized event timeline. For example, the timing information in a first output signal (e.g., information indicating the start of an event at 2:40:48 PM) may not coincide with the timing information in a second output signal (e.g., information indicating the start of the same event may be received at 2:41:02 PM) even though both output signals include information related to the same event. In such implementations, the one or more processors may analyze information in the individual output signals and associate corresponding information in the individual output signals with the same time location in the event timeline, regardless of any time information in the output signals.

Analyzing the information in the individual output signals may include searching for expected information in individual output signals and associating the expected information with one or more appropriate time locations in the event timeline. Information conveyed by a first output signal may cause the processors to expect information in one or more other output signals. Continuing with the example above, one or more processors may determine that the information in the first output signal indicates the start of an event and may associate the information with the start of an event timeline (e.g., at 2:40 PM). After determining that the information in the first output signal indicates the start of the event, the one or more processors may search the information conveyed by the second output signal for information that also indicates the start of the event, regardless of any time information included in the output signal. After finding information in the second output signal that also indicates the start of the event, the processors may associate the found information with start of the event in the event timeline.

In some implementations, associating information in the individual output signals to a corresponding time location in the event timeline may be performed by the vehicle event playback apparatus. In some implementations, associating information in the individual output signals to a corresponding time location in the event timeline may be performed by the vehicle event recorder. The various data streams recorded within an event may involve some delays in the data collection process. These delays may vary by the signal (e.g., acceleration data may be received "faster" than the OBD vehicle speed data and even "faster" than the GPS

data). These delays may be related to how the underlying sensors collect data. For example, accelerometers may be MEMS sensors that provide sub-millisecond readings. OBD vehicle speed measurement may be derived from an optical wheel speed sensor that generates pulses where the pulse periods are proportional to vehicle speed. This means that the slower the vehicle, the larger the delay in speed measurement because two consecutive pulses are necessary to estimate the vehicle speed. These delays may be measured in tens of milliseconds, but nonetheless represent delays that may result in misalignment of data when compared to accelerometer signals, for example. GPS relies of triangulation of satellite signals to determine the vehicle location. Many GPS systems determine the vehicle location once every second. Two consecutive vehicle locations measurements are necessary to derive the speed (e.g., distance between the points divided by the time interval between the measurements). Therefore, speed measurements from GPS systems are typically delayed by one second. Another reason for the delays in input signals may be related to the various buffers employed by electronic devices as they transmit information. Many communication devices send data in packets, which involved waiting for enough data to become available before sending the packet of information. These wait times further contribute to the input signal delays.

In some implementations, by being aware of these fixed time delays, the system may be constructed to purposefully delay individual signals except for the most delayed signal such that the individual signals become aligned with respect to time (e.g., synchronized) with the most delayed signal. After synchronizing the signals, the vehicle event recorder may store the aligned signals in volatile memory and/or other electronic storage.

Responsive to triggering of a vehicle event, the event data may be saved from a volatile memory to a non-volatile memory. The vehicle event recorder may compensate for the known delay in individual signals such that the saved event may be properly centered around the trigger point. For example, the largest signal delay may be 1.75 seconds. In this example, the individual signals (other than the one with the largest delay) may be purposefully delayed by additional delays (1.75 seconds minus the delay for the particular signal), such that aligned data is written to volatile memory with a 1.75 second delay. At the time that a vehicle event is detected (e.g., at the time a detection trigger signal is received), the vehicle event recorder may record a 30 second event with 15 seconds before the detection and 15 seconds after the detection. Upon receiving the trigger signal, the vehicle event recorder may immediately select the last 16.75 seconds (15 plus 1.75) of event data to be written from volatile to non-volatile memory, and then save the remaining 13.25 seconds of data (15 minus 1.75).

An indication that the vehicle event was detected (e.g., a trigger signal) may also be delayed. Triggers such as external voltage signals, where the trigger is generated on the rising edge, may not involve delays. However, more complex triggers may rely on delayed signals and a triggering algorithm itself may introduce additional delays. For example, a simple accelerometer triggering algorithm that involves measuring braking force may be configured to trigger once deceleration of 0.5 g is maintained over 1.0 seconds. This means that the triggering signal may be generated once the 1.0 seconds elapses with deceleration exceeding 0.5 g. However, the trigger point would ideally be identified in the middle of this interval, or at 0.5 elapsed seconds after the deceleration first exceeds 0.5 g. Therefore, the triggering signal from this triggering algorithm may be considered to be delayed by 0.5 seconds. A vehicle event recorder may compensate for triggering delays when saving event data from the volatile memory to the non-volatile memory. In the above example where all aligned signals written to volatile memory are delayed by 1.75 seconds, upon receiving a trigger signal that is known to be delayed by 0.5 seconds, the vehicle event recorder may compensate for this additional delay by immediately selecting the last 16.25 seconds (15 plus 1.75 minus 0.5) of event data to written from volatile to non-volatile memory, then proceeding to save the remaining 13.75 seconds of data (15 minus 1.75 plus 0.5).

By way of another non-limiting example, the one or more sensors may include an accelerometer (e.g., associated with the vehicle event recorder), a camera (e.g., associated with the vehicle event recorder), a sensor associated with the vehicle ECU, and/or other sensors. The accelerometer may generate output signals indicating that the vehicle has started breaking. The accelerometer information (e.g., the braking start time) may agree with video images that show the vehicle beginning to slow down. Information from the vehicle ECU may not indicate that the vehicle is breaking until a short time later, when the vehicle ECU information is received by the one or more processors of the vehicle event data playback apparatus. In this example, the one or more processors of the vehicle event data playback apparatus may synchronize the information from the accelerometer, the camera, and the vehicle ECU system so the information may be presented to the user in a synchronized manner. The user may better understand the event because of the synchronized information. The user may better understand the cause of the event, the outcome of the event, road and/or other environmental conditions during the event, and/or other information related to the event by viewing the synchronized information.

As shown in FIG. **1**A, view **3** includes a first (e.g., forward looking) video playback view **4**, a second (e.g., vehicle interior driver video) playback view **5**, an event timeline **7**, a graphical representation **9** of information related to the operation and/or the context of the vehicle, one or more visual representations **11** of information related to the operation and/or the context of the vehicle, visual representations **13** of vehicle ECU information, a notation field **15**, and/or other information. In some implementations, view **3** (as shown in FIGS. **1**B-**1**G) may not include all of the components of view **3** shown in FIG. **1**A. The number of video playback views shown in the figures is not intended to be limiting. The number of video playback views does not necessarily correspond to a number of cameras included in the system. For example, even though in some of the figures only two video playback views are shown, there may be 1, 2, 3, 4, 5, or more cameras included in the system. The two views may playback information from any two of the cameras, and/or other components of the system.

In some implementations, view **3** may include additional components now shown in FIG. **1**A (e.g., an additional playback view **5** as shown in FIGS. **1**E, **1**F, and **1**G). In some implementations, the components may be presented with a different visual format. In some implementations, view **3** includes one or more active safety system fields **19** (shown in FIGS. **1**B, **1**C, **1**D, and FIG. **2**). The one or more active safety system fields may present information related to detections and/or alerts by the active safety system. In some implementations, the active safety system fields may present a textual, numeric, graphical, and/or other representative indication of what the active safety system communicates to the driver of the vehicle. For example, the active safety

system may alert a driver via a red/yellow/green color coded display that is part of the active safety system. The red/yellow/green color coded display may be reproduced in the one or more active safety system fields **19** of the graphical user interface of the vehicle event data playback apparatus. In some implementations, the active safety system fields in view **3** may reproduce the active safety system detections and/or alerts presented to the driver in real time and/or at another time.

The additional components of view **3** are described in more detail below. The information presented by the one or more active safety system fields and/or the other components of view **3** of the graphical user interface may be synchronized by the vehicle event recorder and/or the vehicle event data playback apparatus and displayed to the user at the same time. The synchronized display may be in real time (e.g., a remote user may view the synchronized information while the driver is operating the vehicle) and/or at a later time.

The graphical user interface may be specifically designed to function and/or cooperate with the vehicle event recorder, the active safety system, and/or the event dataset/alert information they produce. Such a graphical user interface may be interactive and/or responsive to user/operator inputs affected by a computer and/or other peripheral devices. For example, a 'point-and-click' action of a computer mouse, entering and/or selecting information via a touch screen, and/or other user/operator inputs. In some implementations the graphical user interface may be presented to a driver of the vehicle and/or other users (e.g. located at the vehicle and/or located remotely) via a user interface associated with the active safety system. In some implementations, the graphical user interface may be presented to a driver of the vehicle and/or other users via a user interface separate from the active safety system. In some implementations, the alerts and/or other information generated by the active safety system may be presented to a driver of the vehicle and/or other users via the graphical user interface of the vehicle event record playback system.

This system may include couplings to a vehicle event recorder and/or data captured via the vehicle event recorder, couplings to the active safety system and/or data captured via the active safety system, and/or other systems. This system may include one or more processors, one or more display devices, one or more graphical user interfaces, and/or other components. This system may receive as input vehicle event recorder datasets, information generated by the active safety system, and/or other information. Prescribed program code may be executed by the one or more processors to operate on datasets received from the vehicle event recorder, the active safety system, and/or other sources. Data from these datasets may be passed into control objects as parametric input to drive the various visual states of the control objects.

The graphical user interface of the vehicle event recorder dataset playback system presented herein may be comprised of a plurality of control objects. These control objects may include visual depictions of information which may change in response to user interaction and/or specific data values of a dataset under review. Some of these control objects may be interactive and adjusted responsive to 'point-and-click', 'click and drag', touch screen touches, and/or other user interactions. Control objects of these systems may be coupled to, and/or designed to cooperate with, data types and/or data objects unique to vehicle event recorder event record datasets, information from the active safety system, and/or information from other sources.

The control objects may have an appearance and/or data ranges that are correlated with information generated by vehicle event recorders during operation of vehicles. The control objects of these graphical user interfaces may have be configured to visually express data and/or information which is contained in a vehicle event record event dataset, information generated by the active safety system, and/or other information. Illustrative examples are included herefollowing.

Control objects may include and/or display information based on logic code. Logic code (not visible to a user) may facilitate receipt of input data, parsing that data, processing the data in accordance with prescribed algorithms (e.g., which are part of the logic code), providing outputs which may include adjustments to the visual states of the control objects, and/or other actions.

It should be noted that the series of control objects described below and shown in FIG. **1**-FIG. **11** are not intended to be limiting. The system described herein may be configured to generate control objects related to any vehicle operation information that would be helpful for a user reviewing event data recorded before, during, and/or after a vehicle event.

A vehicle event recorder may be configured to capture compound datasets relating to vehicle operation and/or events during a finite period. Accordingly, one or more aspects of this vehicle event playback system may relate to a timeline control object and/or its relationship with the event dataset, and/or other controls of the graphical user interface. Timeline control objects may include an associated time range equivalent to the time range of the event period. The time range associated with a given event may vary in length from a fraction of a second to several tens of minutes or even hours. However, many events recorded by vehicle event recorders may be a few seconds or a few tens of seconds. Timeline control objects in accordance with these teachings may have one or more of a 'start time', an 'end time', a continuous time period therebetween, and/or other features. The 'continuous' time period between the start time and the end time may include a finite number of frame instants and/or frame stops, for example. These may be discrete moments in the event period for which an image may be captured. A timeline control object of these graphical user interfaces may be synchronized with the time span of events recorded by a vehicle event recorder when its start time and end time are set in accordance with specific related values in an event record dataset. In the example illustrated as FIG. **1**, an event record includes a start time of 4:19:35 and an end time of 4:20:02 for a total event period of 27 seconds.

In some implementations, via the graphical user interface, a user may control the length of the event period, select (e.g., by clicking and/or touching a location) an individual time within the event period, continuously play the frame instants, rewind and/or fast forward the frame instants, and/or control the length of the even period in other ways.

For improved ease of operation of these timeline controls, when playing back vehicle event record data, it may be useful for a user to arrange the control to extend an appreciable length of interface regardless of the event period extent. That is, a timeline control which supports a twenty-seven second event may be the same size as a timeline control which supports a 10 minute event. Thus a timeline control may be 'normalized' to the event period without change of its physical size. In view of the data contained in an event record dataset, the start time and/or the end time may be associated with the timeline control extremities,

and/or 100% of the timeline control length may be divided evenly and/or occupied by the entire event without dependence upon the actual extent of the event period. Accordingly, the timeline control object may cooperate with playback of the vehicle event recorder output in that the timeline may auto-adjust to normalize for events of any period length.

A timeline control object may be adapted to match the extent of a time period of a specific event under replay and/or thereafter may be set to agree with a specific event record. For example, as shown in FIG. **2**, timeline pip markers **23**, which may indicate noteworthy features of the event record, may be distributed about the timeline to provide access to information relating to those features. Timeline pip markers **23** may be pre-encoded elements made responsive to mouse clicks, touch screen touches, and/or other control indications entered and/or selected by a user via the graphical user interface and/or one or more peripheral devices. These pip markers may be associated with an instant in time and/or a time period which is a subset of the entire event period. Other control objects of the graphical user interface may be coupled to these pip marker objects and/or may be responsive thereto. They may be responsive to mouse clicks, touch-screen touches, and/or other control gestures associated with the pip markers. FIG. **2** also illustrates event timeline **22**, image series players **21**, **24**, and a vehicle location **25**.

The timeline object may include a timeline replay instant indicator control object. The instantaneous state of a timeline replay instant indicator may specify a replay instant in time, the replay instant to which other controls may be bound and responsive. A timeline replay instant indicator may mark the present instant of the playback system at a given time. The present instant may represent a moment in the event period between the event start time and the event end time. For controls bound to the timeline control object, the present instant time may be used to set the visual state of the control (individually, or as a coordinated group). The visual state of a control object may be different for the individual instants of the event period. When the timeline replay instant indicator is associated with another time instant of the event period, either manually or during a pre-play execution, individual ones of the controls bound to the timeline control may automatically update their visual state to represent data captured at that moment of the event period. Timeline replay instant indicators may be responsive to click-and-drag, touch, and/or other actions, and/or may be responsive to automated replay controls such as 'play' control, 'fast forward' control, 'rewind' control, etc.

Replay controls of these systems may include, for example, a 'play' control button, 'fast forward', rewind, 'loop', and/or other controls. Timeline control objects of these vehicle event playback systems may also include such controls.

Timeline control may be sensitive to keyboard input. For example, left and right arrow keys may be used to advance the timeline backward or forward, respectively, by one video frame (e.g. 0.25 seconds for 4 frames per second video) at a time. The space key may be used to start and/or pause the event data playback. Page Up and Page Down keys may be used to advance the timeline in larger fixed time intervals, such as 5.0 seconds forward or backward, respectively.

Modes of vehicle event playback systems presented here may include side-by-side playback of a plurality of videos (time series presentation of images). In two separate video control objects, a prescribed video may be played back synchronously. For example, a view from the front of a vehicle and a view from the back of the vehicle may be synchronized to represent separate images taken at the same point in time and played side by side. In some implementations, the synchronized video may be synchronized with vehicle ECU data, for example. This may be useful in gaining an understanding of a complex scene which may have more than one point of view, such as a driving incident. For example, in a driving incident it may be important to consider the precise timing of event in the view of the driver and/or in view of traffic ahead. When these two views are considered together, an expert reviewer may draw more precise conclusions with regard to the event details. Accordingly, the event playback systems may include side-by-side video playback controls for playing back videos of two or more unique viewpoints.

Vehicle event recorder systems may include a plurality of video cameras positioned at a plurality of video capture stations (locations). An individual video capture station may have a unique viewpoint relative to other video capture stations. In some vehicle event recorders, a 'forward-looking' camera may be arranged to capture a traffic view ahead of the vehicle and a second reward looking camera may be arranged to capture a view of a passenger/driver space.

There may be a time relationship between these two video views because actions taken by a vehicle operator may relate to the traffic and conditions ahead. One may understand a driver's response to things which may be discovered observable in the forward view. The vehicle event data playback systems may include a plurality of video players where individual views of the video players may be synchronized in time to the others and/or timeline control objects, and/or with respect to the timeline replay instant indicator. Where vehicle event recorders support more than two video cameras, a single timeline control may be used to synchronize those in a similar manner.

An operator/reviewer of these vehicle event data playback systems may 'scroll' through discrete video frames of the event timeline by adjusting the playback instant indicator, for example via 'click-and-drag', touch, keyboard key strokes, and/or other types of actions. Accordingly, the graphical user interface of this invention may include video playback controls coupled to the playback instant element of a timeline control object. In this way, two separate views about the vehicle environment may be considered simultaneously in a side-by-side arrangement where both views represent substantially the same instant in time as synchronized by the timeline control.

While some versions of these systems include side-by-side playback of forward facing and rear facing (for example) views taken from video cameras in a vehicle event recorder, (e.g., 'real' video), alternative versions may include at least one video playback display in which a 'virtual video' is presented. A virtual video may include a time series of images whereby the images are captured in a system which is not a vehicle event recorder. However, these virtual videos may relate directly to the events captured. For example, one type of virtual video in accordance with this teaching may present images having dependence upon the event timeline. Another example may have dependence upon the vehicle position as a function of time. Still another may have a position dependence with prescribed offset. Other examples are contemplated. More details of these types of virtual videos follow.

In some implementations, as shown in FIG. **3**, an image series player **31** (video player) may be arranged to play an image series which was not recorded by the vehicle event recorder. Rather, a plurality of still images is recalled from

a prepared database to form an image set which may be played in series. Those images when played together as a 'video' in the video player may constitute a 'virtual video' for purposes of this teaching. However, this replay may be well coordinated and having direct dependence with respect to the event record. For example, this virtual video timeline may be synchronized with the event timeline **32**. The actual location of a vehicle as recorded by the vehicle event recorder may be coupled to the viewpoint from which the recalled images are made.

When the timeline control is set into a 'play' mode, the video of actual captured images may appear in a video player control adjacent to a second player which plays the virtual streetview video. This virtual video may include images from the same locations and/or viewpoints with respect to the event period, but these images may include enhancements and augmentations to bring a more complete understanding of the actual event. In one example, street-view images provided by a service like Google's StreetView system may be recalled in view of a plurality of position measurements taken by the vehicle event recorder. For this plurality of locations (vehicle's location as measured by a GPS for example) captured over the period of a given event, a streetview image from a corresponding location may be recalled from the image database. Individual recalled images may then be assigned a time instant corresponding to those times from which the playback timeline is comprised to assemble a virtual video of streetview images which directly corresponds to the video actually captured at the vehicle event recorder cameras. One advantage may lie at least partly in the clarity of the recalled images which may have been provided on a nice sunny day in comparison to images captured by the vehicle event recorder which may be of inferior clarity due, for example, to inclement weather including fog or sun glare, nighttime darkness, a large vehicle that obstructs the view of the event recorder, and/or other factors. Further advantages may be realized in view of the labels which may be may be incorporated with the prepared streetview images. For example, address label **28** may indicate a street address most closely associated with the image viewpoint. FIG. **3** also illustrates event timeline **32**, image series player **34**, vehicle location **35**, a street address **38** corresponding to the vehicle location, a street view image **37** corresponding to the vehicle location, and/or other information.

Another benefit of this approach is that streetview may be further manipulated by the user to gain a better understanding of the environment in which the event was captured. For example, the user may pause the event playback, then rotate the streetview to show the image to the left, right or behind the vehicle. The system may be configured such that this user action would temporarily decouple the streetview from the event playback. Upon restarting the playback of the paused event playback, the system may be configured such that streetview would then realign and show the view in front of the vehicle again.

It may be inconvenient to view many videos simultaneously. To address this, these players may have two players side-by-side with the video type selectable in the interface by way of a tab strip control **33**, which as shown in FIG. **3** for example, may include five tab selections (e.g., "Back-Cam", "StreetView", "MapView", "BirdseyeView", "Driver View", and/or other tab selections). In agreement with which tab is selected and triggered, the video playback may be switched between the possible video presentation types. The player may present a synchronized playback of both real and virtual videos in agreement with the event period and/or the timeline control. The example of two side by side players is not intended to be limiting. The system described herein may have any number of players in the graphical user interface. The multiple players need not be side by side. They may be positioned anywhere in the graphical user interface that is helpful to the user. Additional views that correspond to additional cameras may be provided, for example. In some implementations, the cameras may include a forward road camera, an interior cab camera, a left side backward facing camera, a rear of the vehicle backward facing camera, and/or other cameras. The additional views/cameras may give greater perspective for a review analyst and/or a coach reviewing the information.

There may be another type of virtual video which may be supported by these playback systems which relates to moving maps. A map view virtual video is depicted in FIG. **4**. In a fashion similar to that described in the streetview embodiment, a plurality of map images may be prepared and saved to form an image series consistent with an event record dataset. The vehicle location and/or the event timeline **41** may be considered in forming a series of map images suitable for playback in a mapview video player **42**.

A separate map image **43** with appropriate scale, size and orientation may be presented in the viewer for every discrete instant of the event period as represented in the event timeline. When playback instant control **44** is moved to another time (constant) of the event timeline, the vehicle also moves (in most events). The new vehicle location **45** may cause a new map and/or a separate map image to be allocated and displayed for that time instant. The image in image series player **47** may correspond to vehicle location **45**. The vehicle's position within the map may be indicated by an icon marker **46** to reflect the position of the vehicle as measured by the vehicle event recorder. In a an event replay, the series of map images may be played back synchronously alongside the actual forward view images (for example) captured at the vehicle event recorder camera.

A mapview player in accordance with this teaching may be useful when it is arranged to present maps with enhancements and/or markings which may be derived from information in the event record dataset. For example, when actual vehicle speeds are compared to local speed limits, a determination may be possible with regard to regions in which a speed infraction occurs. A graphical representation of the same may be included superimposed with the maps presented.

With reference to FIG. **5**, timeline control object **51** agrees with the event record dataset from a vehicle event recorder. A playback instant control **52** marks an instantaneous moment of the event period. At the moment 4:19:38.50 p.m. indicated in a numeric label control **53**, the vehicle GPS system determined the vehicle location at latitude 32.8295 and longitude −117.2733 as recorded by the vehicle event recorder's position determining system and position is reported numerically at position label control **55**. In some implementations, the latitude and longitude information may be translated into a street address by the system and/or presented to the user in a field of the graphical user interface.

With the video player set into a map view mode **54** by a tab strip tool **56**, a map image **57** suitable in scale and location may be presented that shows the vehicle's location at the corresponding instant in time. An icon image of a car **58** (for example) may mark the location in the map. In addition, a spatial highlight **59** for example (highlighting portions of Bonair and Draper streets in the image), may be superimposed on the map image to mark regions where speeding infractions have been identified.

Timeline marker **60** may designate a finite period of time within the event period when the speeding occurs. Thus, some timeline controls of these systems may include marker objects aligned and/or cooperative with elements appearing in virtual videos. This cooperation may be due to associations with time instants within the event period.

Both the streetview player and the mapview player may offer advantages in reaching a complete understanding of a scene. They may be augmented based on information collected by a vehicle event recorder.

Another virtual video player that may be included in these systems may be characterized as a bird's eye view virtual video player. Illustrated in FIG. **6**, a bird's eye view video player of these systems may include images taken from an elevated viewpoint, for example images made from an airplane and/or satellite. In consideration of the vehicle's time-dependent position as measured and/or recorded by a vehicle event recorder, images may be selected from a prerecorded database of so described images, and/or obtained from other sources.

Timeline control **61** specifies an instant in time by a playback instant control **62**. Video player display **63** may include an image **64** and a 'car' icon marker **65** to indicate the location of the vehicle at the capture time 4:19:38.50. When tab strip **66** is used to set the video player into a bird's eye view mode **67**, an image series of perspective images made from altitude may be played back in time with respect to the event timeline. As the event player executes playback of event data, images displayed by image series player **68**, bird's eye images **64**, marker icon **65**, and/or other components of the system, may be updated for instants of the timeline to reflect appropriate views of the event scene.

Because the image viewpoint may be selectable, it may be possible to specify that the viewpoint be constant at a virtual location, for example 100 meters behind the car and/or 50 meters above the car, and the view direction may point in the direction of travel with respect to the vehicle. In this way, the bird's eye view playback virtual video may be envisioned as if a helicopter video camera followed the car throughout the event to make the video images. A reviewer may gain a clearer understanding of the event environment as presented in a synchronized manner alongside with other event record information.

Accordingly, these vehicle event data playback systems may include one or more of a real view video player, a virtual video player, and/or other video players which may be arranged to interact with event data recorded in vehicle event recorders. Individual ones of these specialized video players may provide a time synchronized image series in conjunction with a visual presentation of other related event record data.

While the preceding description sets forth several video playback control objects, the following description is directed to other aspects of these vehicle event playback systems which may not be based upon data from image systems. Rather, the graphical user interface may control objects presented herefollowing to express non-image data from a plurality of sources. In some implementations, these sources may include onboard data systems. In some implementations, information sources may include those which are external with respect to a vehicle and/or its vehicle event recorders.

Control objects of graphical user interfaces of these playback systems bound to vehicle onboard systems may have two primary but non-limiting types including: 1) control objects bound to data from sensors deployed as part of a vehicle event recorder apparatus, for example, a vehicle event recorder may include accelerometers which measure G-force levels in two orthogonal spatial dimensions while a vehicle is being used; and 2) a control object bound to vehicle subsystems characterized as those installed by a vehicle manufacturer. Other types are contemplated. Data provided by way of a vehicle's ECU systems may be received, managed, parsed, and/or time-stamped at a vehicle event recorder which forms a dataset to which control objects of the graphical user interfaces may be bound. In some implementations, control objects of graphical user interfaces of these playback systems bound to vehicle onboard systems may include a third type. The third type of control object may be associated with the data generated by analysis modules of the vehicle even recorder, such as a wasted fuel estimate, triggers for dangerous driving maneuvers, calculated fuel consumption from mass air flow sensors, and/or other data generated by analysis module of the vehicle event recorder.

Some control objects of these systems may be bound to data sources not part of a vehicle event recorder system and/or external with regard to vehicle subsystems. These control objects may be nevertheless implicitly strongly coupled to event record datasets which are subject to playback in these devices and methods. In one illustrative example, a notation system which associates an expert reviewer's comments and notes with portions of an event record in a note field or notation control object may be coupled to receive data therefrom. Details of these types follow.

In one version, a control object and/or plurality of control objects may be coupled to the timeline control and thus the event period to affect time synchronization between these. Acceleration control objects may be arranged to visually show acceleration data collected during an event captured with a vehicle event recorder. With respect to acceleration data collected in a vehicle event recorder, it may be useful to present this type of information in two fashions. First, it may be useful to present instantaneous acceleration data associated with an instant of time during the event period. In a second fashion, acceleration data collected over the entire event period (or finite subset thereof) may be displayed in a graph of two axes. Force data may be presented in a form where the abscissa of which may be time, and the ordinate force.

For example, in FIG. **7**, a view **72** of a first acceleration control object includes a line graph **71** representation of acceleration data into orthogonal directions. 'G-force' or acceleration is plotted versus time to form line representations **73** of acceleration data. A playback instant indicator **74** is synchronized with the playback instant indicator **75** of the timeline control object both spatially and with respect to displayed data.

Another related acceleration control object **76** which expresses acceleration data in an alternative visual form is additionally illustrated. This 2-D expression of instantaneous force includes a pointer **77** which gives a visual representation of force in both forward/aft and left/right directions **78** (also synchronized with playback instant indicators **74** and **75**). The acceleration control objects may be bound to information in the event record dataset whereby synchronization is realized with respect to the timeline control and other control objects similarly bound including the video display control objects. Accordingly, control objects may be arranged to present instantaneous data as well as plots of data over time. In both cases, these controls may be bound and/or responsive to the playback timeline **79**.

Vehicle event recorder systems may produce information-rich event record datasets. Event record datasets of vehicle event recorders may include data captured at vehicle subsystems, for example, by way of the onboard diagnostics and/or ECU systems. In vehicle event recorder systems so equipped, data captured at various vehicle subsystems may be time-stamped in a scheme coordinated with the event period and/or with video frame capture rates. Where such data is time-stamped, it may enhance synchronous replay via these vehicle event data playback systems.

Accordingly, these vehicle event data playback systems may be suited for playback of vehicle event records having been formed with time-stamped data from factory installed vehicle subsystems. Some vehicle event recorder systems may be arranged to capture engine speed data and/or to associate a time instant with speed data measurements. Engine speed in 'revolutions per minute' or RPM, may be read from an ECU via a coupling to which a vehicle event recorder may be connected. In some alternative versions, engine speed measurements may be made via 'aftermarket' installed sensors and/or vehicle subsystem detector which may obviate need to directly couple with the ECU. In either case, when event record datasets which are compatible with these playback systems are prepared and recorded, individual engine speed measurements may be associated with an instant in time and/or "time-stamped". In systems common in the art where engine speed is recorded, engine speed is generally recorded without regard for simultaneous and/or synchronized playback. In those systems, engine speed data may not be provided with an association with time. Because it is a goal of these playback systems to playback data in a synchronized fashion, it may be necessary to time stamp data in this way. Where vehicle subsystems, for example an engine tachometer, do not provide measurement data at a rate equal or similar to video camera frame rates, data smoothing and or data averaging may be used to improve a dataset or portion thereof to make it better cooperate with the objectives of these playback systems, which may include a discrete number of time instances on an event timeline. Common vehicle tachometers may not face this restriction and may be otherwise free to take measurements at a convenient rate including those rates having unequal periods between data measurements. To facilitate time synchronization in these playback systems, the moment any measurement is made may be accounted for.

Many modern vehicle manufacturers may include advanced electronic systems with many of the vehicle's subsystems. For example, a mechanical accelerator pedal often includes a transducer from which pedal position may be readily measured. However, electronic data which may exist within a vehicle's proprietary electronic control schemes may not always readily available for third-party use. In some implementations, vehicle event recorders may be unable to record information relating to vehicle performance parameters such as the odometer on light duty vehicles, the fuel flow meter on light duty vehicles, and/or other parameters. This is not intended to be limiting. The system described herein should be understood to utilize any information made available by the vehicle's subsystems. If unavailable types of information are eventually made available by the vehicle manufactures, it should be considered within the scope of this disclosure to include a control object associated with the newly available information.

In implementations where a vehicle event recorder may be successfully coupled to vehicle electronic subsystems to receive the difficult to obtain and/or newly released data, the vehicle event recorder may be adapted to pass the data and/or manage a timestamp scheme in conjunction with the vehicle event recorder. For example, if a vehicle event recorder operates with a video frame rate of 30 frames per second, but the factory installed odometer and/or fuel flow data only update three times per second, a data recording scheme may be set to rectify timing issues between these independent data sources so that an event dataset may accurately reflect an 'instantaneous' time value for the data elements.

Vehicle event recorder systems which record time-stamped engine speed data are not known in the art. As such, synchronized playback of same has been impossible. As shown in FIG. **8**, in systems disclosed herein, engine speed information may be expressed graphically in a visual presentation, in an alphanumeric expression, and/or in other forms as at least part of an engine speed control object **81**. An engine speed control object of this example may be comprised of graphical portions and/or alphanumeric portions. An analog arc **82** may provide a range continuum upon which instantaneous magnitude may be displayed by a pointer **83**. A digital numeric readout **84** may allow an instantaneous report of engine speed for an instant of the event timeline **85**. Playback instant indicator **86** may be moved (e.g. via mouse type computer pointing peripheral device) to any point along the timeline. The engine speed control object, which is bound to the timeline, may be updated to indicate the engine speed recorded at that particular time. In a similar control object, vehicle speed control object **87**, pointer **88** may yield an instantaneous value of '31 mph' on an analog scale, while a digital numeric value **89** may also be provided at vehicle speed label.

Event records which may compatible with, and/or may be played by these vehicle event playback systems may include measurement data from the groups characterized as those including: throttle position data, engine load data, power takeoff system data, malfunction indicator light system data, brake system data, antilock brake system data, automatic traction control system data, electronic stability control system data, excess fuel consumption system data, and/or other data. FIG. **9** illustrates an event timeline **91** having playback instant indicator **92** set at time corresponding to 4:19:53.00 p.m. that is coupled to a plurality of control objects. Individual ones of the control objects may be arranged to express time-stamped data in a visual presentation which may include both graphical and/or alphanumeric representations.

Most vehicle event recorder systems are incapable of recording data related to throttle position. However, this may remain a factor in accident analysis. For example, it may be useful to understand how much time passes between the time a red light traffic signal appears (detectable via forward view video review—for example) and the time a vehicle operator disengages application of power (e.g. removes foot from an accelerator pedal). Because it may be difficult to arrange a custom sensor to detect accelerator position, many vehicle event recorders may include datasets devoid of this critical data.

While access to this information may be available on a vehicle's ECU system, to date, it has been prohibitively difficult to couple vehicle event recorders to the ECU of modern vehicles. Where that has been achieved, the dataset produced by such advanced vehicle event recorders may include time synchronization management schemes with respect to its video camera. These systems may include time-stamped data regarding throttle state where an event record dataset having such timestamp throttle state data are available. These vehicle event data playback systems may be

cooperative and/or provide graphical user interface controls which are suitably responsive to such event record datasets.

A graphical user interface with a throttle state control object may provide graphical expressions of throttle states, and/or other information. The control object may be coupled to an event timeline and/or corresponding event timeline control whereby the instantaneous throttle state for a time in the event period may be selectively displayed by the control.

In some implementations, an instantaneous numeric value **93** (digital) and/or a graphical expression **94** (analog) of the throttle state may be given for individual instants of the timeline control. When the playback instant indicator is moved to another position of the event timeline, the throttle state control may be updated such that data represented there is updated in synchronization with other controls of the graphical user interface, including video.

The video of the video playback control object may indicate a red traffic signal has occurred at 4:19:44. A user/reviewer may be able to see by sliding the playback instant control to that moment of the timeline that the throttle state remained at 100% (recall FIG. **1**). However, when the playback instant control is advanced further down the timeline to about 4:19:46, the throttle position may be at 0%, for example.

This may be verified by considering vehicle speed **710** (shown in FIG. **7**) data presented in a continuum chart. In it, a user/reviewer may see that the vehicle begins to decelerate just before 4:19:45. While the acceleration data may be a good indicator of when the driver releases the throttle, it will remain imprecise because of mechanical delays inherent vehicle powertrain systems and the overall vehicle dynamics. Also, using acceleration data alone will result in misdetection of vehicle deceleration that may be due to vehicle travelling uphill and the force of gravity acting against the forward momentum of the vehicle. That is, the accelerator pedal may stay depressed at 25%, which may maintain vehicle speed while travelling 55 mph on a level road, but will result in vehicle deceleration should the road grade change to 5% uphill. To learn the precise time the throttle was released, the playback instant control may be manipulated to indicate a time prior to 4:19:45 and the throttle state control may be reviewed. This control may more accurately tell a fuller story as it relates to the question "when did the driver respond" rather than the question "when did the vehicle respond". Accordingly, in some circumstances a throttle state control well synchronized with related data and/or bound to a timeline control unit may tell the full story which otherwise could not be known in the absence of throttle state information.

Similarly, a graphical user interface engine load control object **95** may be included in some versions of these vehicle event data playback systems. Engine load data may help a user reviewing an event via the graphical user interface to understand how heavily loaded the engine is at its given speed (RPM). This may inform the user if the vehicle was heavily loaded with cargo, whether the driver had excess power that he could have used for an evasive maneuver, etc. A sensor installed by a vehicle manufacturer may produce data to indicate engine load on a scale from 0% to 100%. Data from the sensor may be available via the ECU, for example. Data which indicates engine load may be periodically detected and/or captured, then added to the event record dataset produced by the vehicle event recorders. This step may be done with attention to time calibration and/or time synchronization. For example, data from the ECU may arrive at irregular intervals. Or the data may arrive with extreme time jitter between successive measurements. This data may be used in playback systems taught herein after being synchronized with other events encoded in event records. It may not be enough, with respect to the present vehicle event data playback systems, to merely collect multiple readings of engine load. Because of the particular playback characteristics suggested here, engine load data (among other data) may be time stamped before being included as part of these event records.

Another information source which may relate to vehicle performance and/or which may be replayed in these event data playback systems may relate to power distribution. It may be useful to know when engine power is needed by, and/or being delivered to, auxiliary systems. If a vehicle engine is delivering power to coupled power consuming subsystems (e.g. refrigeration, hydraulic actuator, et cetera) an event record may be configured to indicate the status of power takeoff systems.

In some implementations, a power takeoff indicator **96** may be embodied as a binary indicator. A power takeoff control object arranged to indicate binary states for every instant of an event timeline may include a graphical portion, an alpha numeric portion, and/or other portions, for example.

As shown in FIG. **9**, other control objects may be provided to visually present data collected from vehicle subsystems. For example, these may include a brake indicator control object **98**, an antilock braking system ABS control object **99**, an automatic traction control (ATC) control object **910**, an electronic stability control ESC control object **911**, and/or other control objects. The graphical user interface control objects may be driven by data contained in a vehicle event recorder event dataset, and/or be responsive thereto. These controls may be bound to the timeline control object whereby visual presentation of data in the controls may be time synchronized. These controls may present data in graphical, alphanumeric, and/or other presentations.

In systems which produce data having a limited few states, it may be convenient to present the data states via prescribed and/or preconfigured icon symbols. For example a malfunction indicator light (MIL) system may operate to provide driver alerts with respect to five types of malfunction in addition to a binary 'ON'-'OFF' value **912**. A low tire pressure icon **913** may be displayed to indicate a malfunction. The control object, which may remain synchronized with event playback, may be showing its 'ON'-'OFF' indication and/or malfunction type via the displayed icon, for example.

In some implementations, vehicle event recorders may include an excess fuel consumption indicator. When a driver takes an action which may be determined to be one associated with excess fuel consumption, an excess fuel consumption indicator may provide a driver with instant feedback to signal the condition. Where vehicles are equipped with such devices, they may also provide data to be included in a vehicle event recorder event record dataset. Accordingly, these vehicle event data playback apparatus may include an instant driver feedback control object **914**. Because feedback may be provided as a three color scheme (for example) in vehicles in which they are deployed, the instant driver feedback control object may similarly express these feedback states. This control object may be an example which illustrates the value of a visual playback of vehicle event records. When an indicator is given to a driver to alert him that a maneuver has caused excess fuel consumption, it may be useful to understand in detail a driver's response in order to administer appropriate coaching. The system described herein may facilitate visualization and/or understanding of

details associated with vehicle operation. For example, a reviewer/coach may decipher a driver response to instant feedback relating to fuel consumption maneuvers.

The description of data collected via vehicle event recorder systems is not intended to be limiting. There may be information sources that are not part of the vehicle event recorder which contribute data that may be played back the systems described herein.

In some implementations, vehicle event recorders may record data from vehicle systems, from event records, and/or from other sources, which details many aspects of vehicle and/or driver performance. In some of these systems, a human reviewer may study video captured in an event record and/or prepare notes in accordance with observations made. Some of these notes may be general to the entire event period (e.g. a 'no seat belt' infraction) and/or others may be particular to specific time portions of the event period and/or a single instant in the event period. Once prepared, the notations may become appended to, and/or part of an event record. When event records are played back in these data players, these notations may be displayed via the graphical user interface.

FIG. **10** shows one illustrated example of a timeline control **101** coupled to a notation field control **102**. The notation field may include numeric review data such as a score value **103** and icon indicator **104** related to severity, a review date label **105** and a note list **106** containing therein a plurality of note entries (two notes entries are shown in the example).

A first note **107** relating to an occurrence of "aggressive accelerating" may be coupled to timeline marker pip **108** while "other task" notation **109** may be coupled to timeline marker pip **1010**. Finally, note field **1011** may contain text which describes the reviewer's observations as those relate to the 'other task' note. Since these notes relate to specific parts of the event period, event playback may be improved when note text is appropriately displayed with respect to the note time association during the event data playback.

Access to several of these notes may also be affected by pointing and clicking, touching, etc., on the timeline pip marker elements. For example, if a user were to click on/touch the diamond shaped marker pip, the "other task" note closes and the "aggressive accelerating" note opens to reveal text of that note. In this way, access to appended notes may be readily available via timeline cues.

The notation control object described in the foregoing graphs may be illustrative of a first kind of information whose source may not be from onboard a vehicle but may be related to a vehicle event playback. There may be other sources which provide information related to a vehicle event but are not part of the vehicle, any of the vehicle's subsystems, or a vehicle event recorder.

Another information source external from the vehicle may include one which reports on environmental conditions related to the time and location of the recorded event. In one type of environment control object **1012**, the state of the weather may be reported as recorded in remote weather reporting stations. For example, if an event recorder produces an event record with location and time information, a weather station may report ambient temperature via text label **1013**. It may report whether or not the roadways were dry or wet at that time via icon display **1014**. It may indicate whether or not the roads were icy or snowy. These systems may indicate whether or not the event occurred during a windy day. In view of sidereal time, and in view of a vehicle's direction of travel (as recorded by a vehicle event recorder), this control object may indicate the level of sun glare **1015** which may have hindered a driver's visibility during an event. A weather reporting station accessed via the internet (for example) before, during, or after an event record is made, may provide such data.

Other information sources external from the vehicle that may be helpful to a user reviewing an event via the graphical user interface may include databases containing speed limit information and/or road type information (e.g., freeway, major boulevard, two-lane road), sources of information about a traffic level, and/or other information.

FIG. **11** illustrates additional features. For reference, event timeline control **111** is illustrated in this drawing. A 'now playing' event label **112** may identify an event which is currently being addressed by, and/or is a subject of the event data player. A driver **113** drop-down type selection box **114** may permit operators of these playback systems to select other fleet drivers to which these playback systems may be pointed to view events associated with that particular driver. Another selection box **115** may enable an administrator to mark an event with additional notations to indicate a training status.

Although the system(s) and/or method(s) of this disclosure have been described in detail for the purpose of illustration based on what is currently considered to be the most practical and preferred implementations, it is to be understood that such detail is solely for that purpose and that the disclosure is not limited to the disclosed implementations, but, on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any implementation can be combined with one or more features of any other implementation.

What is claimed is:

1. A method to synchronize vehicle operation information comprising:

providing a plurality of sensors coupled with a vehicle, the sensors including a first sensor that generates a first output signal conveying information related to a first operating parameter, and a second sensor that generates a second output signal conveying information related to a second operating parameter;

receiving the vehicle operation information via output signals generated by the plurality of sensors, wherein the first output signal is associated with first timing information, and wherein the second output signal is associated with second timing information;

detecting a first vehicle event based on the first output signal and the second output signal, the first vehicle event having a start time and an end time; and

responsive to detecting the first vehicle event:

associating information from the first output signal and the second output signal generated during the first vehicle event to create a first event record, wherein the first timing information includes a first time-stamp that indicates the start time of the first vehicle event, wherein the second timing information includes a second time-stamp that indicates the start time of the first vehicle event, and wherein the first time-stamp does not coincide with the second time-stamp; and

synchronizing the information from the first output signal and the second output signal generated during the first vehicle event based on analysis of the first time-stamp and the second time-stamp, wherein synchronizing includes identifying and correlating corresponding

information associated with physical phenomena in the first output signal and the second output signal during the first vehicle event.

2. The method of claim **1**, wherein the vehicle operation information includes one or more of vehicle safety information, vehicle event information, vehicle environment information, or vehicle subsystem information.

3. The method of claim **1**, wherein the first operating parameter is related to vehicle safety, and wherein vehicle safety information is received via output signals generated by one or more sensors included in an active safety system coupled with the vehicle.

4. The method of claim **3**, wherein the first vehicle event is detected based on the vehicle safety information received from the active safety system.

5. The method of claim **1**, further comprising causing a graphical user interface to present the synchronized vehicle operation information to a user.

6. The method of claim **5**, wherein a view of the graphical user interface includes one or more active safety system fields, the method further comprising causing the one or more active safety system fields to present information related to detections and/or alerts by an active safety system coupled with the vehicle, the active safety system fields presenting one or more of a textual, a numeric, or a graphical indication of information the active safety system communicates to a driver of the vehicle.

7. The method of claim **1**, wherein the first operating parameter is related to vehicle event information and/or vehicle environment information, the method further comprising receiving the vehicle event information and/or the vehicle environment information via output signals generated by one or more sensors included in a vehicle event recorder coupled with the vehicle.

8. The method of claim **1**, wherein the first operating parameter is related to vehicle subsystem information, the method further comprising receiving the vehicle subsystem information via output signals generated by one or more sensors associated with an engine control module installed in the vehicle at manufacture.

9. The method of claim **1**, wherein the first vehicle event is detected based on a comparison of the information conveyed by the output signals to criteria included in predetermined vehicle event profiles.

10. The method of claim **1**, further comprising presenting the synchronized vehicle operation information to a user in real time during operation of the vehicle.

11. A vehicle event data playback apparatus for synchronizing vehicle operation information comprising:

a plurality of sensors coupled with a vehicle, the sensors including a first sensor that generates a first output signal conveying information related to a first operating parameter, and a second sensor that generates a second output signal conveying information related to a second operating parameter;

one or more processors configured to synchronize vehicle operation information, wherein synchronizing the vehicle operation information comprises:

receive the vehicle operation information via output signals generated by the plurality of sensors, wherein the first output signal is associated with first timing information, and wherein the second output signal is associated with second timing information;

detect a first vehicle event based on the first output signal and the second output signal, the first vehicle event having a start time and an end time; and

responsive to detecting the first vehicle event:

associate information from the first output signal and the second output signal generated during the first vehicle event to create a first event record, wherein the first timing information includes a first time-stamp that indicates the start time of the first vehicle event, wherein the second timing information includes a second time-stamp that indicates the start time of the first vehicle event, and wherein the first time-stamp does not coincide with the second time-stamp; and

synchronize the information from the first output signal and the second output signal generated during the first vehicle event based on analysis of the first time-stamp and the second time-stamp, wherein synchronizing includes identifying and correlating corresponding information associated with physical phenomena in the first output signal and the second output signal during the first vehicle event.

12. The vehicle event data playback apparatus of claim **1**, wherein the one or more processors are configured such that synchronizing includes searching for expected phenomena in the second output signal that indicate the start time of the first vehicle event, wherein the first timing information indicating one or more of a time of day the information was generated, an order in which the information was generated, or a periodic and/or continuous timing of the generated information.

13. The vehicle data playback apparatus of claim **11**, wherein the one or more processors are configured such that the vehicle operation information includes one or more of vehicle safety information, vehicle event information, vehicle environment information, or vehicle subsystem information.

14. The vehicle event data playback apparatus of claim **11**, wherein the processors are configured such that the first operating parameter is related to vehicle safety, and wherein the processors receive vehicle safety information via output signals generated by one or more sensors included in an active safety system coupled with the vehicle.

15. The vehicle event data playback apparatus of claim **14**, wherein the processors are configured such that the first vehicle event is detected based on the vehicle safety information received from the active safety system.

16. The vehicle event data playback apparatus of claim **11**, further comprising a graphical user interface configured to present the synchronized vehicle operation information to a user, wherein the processors cause the graphical user interface to present the synchronized vehicle operation information to the user.

17. The vehicle data playback apparatus of claim **16**, wherein a view of the graphical user interface includes one or more active safety system fields, the one or more active safety system fields configured to present information related to detections and/or alerts by an active safety system coupled with the vehicle, the active safety system fields presenting one or more of a textual, a numeric, or a graphical indication of information the active safety system communicates to a driver of the vehicle.

18. The vehicle data playback apparatus of claim **11**, wherein the processors are configured such that the first operating parameter is related to vehicle event information and/or vehicle environment information, and wherein the processors receive the vehicle event information and/or the vehicle environment information via output signals generated by one or more sensors included in a vehicle event recorder coupled with the vehicle.

19. The vehicle data playback apparatus of claim **11**, wherein the processors are configured such that the first

operating parameter is related to vehicle subsystem information, and wherein the processors receive the vehicle subsystem information via output signals generated by one or more sensors associated with an engine control module installed in the vehicle at manufacture.

20. The vehicle data playback apparatus of claim **11**, wherein the processors detect the first vehicle event based on a comparison of the information conveyed by the output signals to criteria included in pre-determined vehicle event profiles.

21. The vehicle data playback apparatus of claim **20**, wherein the processors are configured such that the pre-determined vehicle event profiles include criteria sets associated with vehicle events, and wherein vehicle events are detected by comparing the information conveyed by the output signals to the criteria sets such that the first vehicle event is detected responsive to the information conveyed by the output signals satisfying one or more individual criteria in a first criteria set associated with the first vehicle event.

22. The vehicle event data playback apparatus of claim **11**, further comprising a graphical user interface configured to present the synchronized vehicle operation information to a user, wherein the processors cause the graphical user interface to present the synchronized vehicle operation information to the user in real time during operation of the vehicle.

23. The vehicle event data playback apparatus of claim **11**, wherein the processors receive information from one or more sensors including an active safety system sensor, a video camera, an accelerometer, a gyroscope, a geolocation sensor, a radar detector, an engine RPM sensor, a vehicle speedometer, a tilt sensor, or a braking sensor.

* * * * *