US009574914B2

(12) **United States Patent**
Fennell et al.

(10) **Patent No.: US 9,574,914 B2**
(45) **Date of Patent: *Feb. 21, 2017**

(54) **METHOD AND DEVICE FOR DETERMINING ELAPSED SENSOR LIFE**

(71) Applicant: **Abbott Diabetes Care Inc.**, Alameda, CA (US)

(72) Inventors: **Martin J. Fennell**, Concord, CA (US); **Saeed Nekoomaram**, San mateo, CA (US)

(73) Assignee: **Abbott Diabetes Care Inc.**, Alameda, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 301 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/195,449**

(22) Filed: **Mar. 3, 2014**

(65) **Prior Publication Data**

US 2014/0180047 A1 Jun. 26, 2014

Related U.S. Application Data

(63) Continuation of application No. 12/495,219, filed on Jun. 30, 2009, now Pat. No. 8,665,091, which is a continuation-in-part of application No. 12/117,681, filed on May 8, 2008, now Pat. No. 8,461,985.

(60) Provisional application No. 60/916,744, filed on May 8, 2007.

(51) **Int. Cl.**

A61B 5/1495	(2006.01)
A61B 5/145	(2006.01)
G01D 18/00	(2006.01)
A61B 5/00	(2006.01)

(Continued)

(52) **U.S. Cl.**

CPC ***G01D 18/00*** (2013.01); ***A61B 5/0002*** (2013.01); ***A61B 5/1495*** (2013.01); ***A61B 5/14532*** (2013.01); ***G06F 19/3412*** (2013.01); ***G06F 19/3456*** (2013.01); ***H04Q 9/00*** (2013.01); *A61B 2560/0271* (2013.01); *A61B 2560/0276* (2013.01); *A61B 2562/08* (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC A61B 2560/0271; A61B 2560/0276; A61B 2562/08; A61B 5/0002; A61B 5/14532; A61B 5/1495; G01D 18/00; G06F 19/3412; G06F 19/3456; H04Q 2209/40; H04Q 2209/86; H04Q 2209/883; H04Q 9/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,755,036	A	7/1956	Mikko
3,260,656	A	7/1966	Ross, Jr.
3,304,413	A	2/1967	Lehmann et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE	4234553	1/1995
EP	0010375	4/1980

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 12/550,208, Advisory Action mailed Dec. 4, 2014.

(Continued)

Primary Examiner — Sisay Yacob

(74) *Attorney, Agent, or Firm* — Jackson & Co., LLP

(57) **ABSTRACT**

Methods and systems for determining elapsed sensor life in medical systems, and more specifically continuous analyte monitoring systems.

18 Claims, 16 Drawing Sheets



(51) **Int. Cl.**
G06F 19/00 (2011.01)
H04Q 9/00 (2006.01)

(52) **U.S. Cl.**
CPC *H04Q 2209/40* (2013.01); *H04Q 2209/86* (2013.01); *H04Q 2209/883* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,581,062 A 5/1971 Aston
3,651,318 A 3/1972 Czekajewski
3,653,841 A 4/1972 Klein
3,698,386 A 10/1972 Fried
3,719,564 A 3/1973 Lilly, Jr. et al.
3,768,014 A 10/1973 Smith et al.
3,776,832 A 12/1973 Oswin et al.
3,837,339 A 9/1974 Aisenberg et al.
3,919,051 A 11/1975 Koch et al.
3,926,760 A 12/1975 Allen et al.
3,949,388 A 4/1976 Fuller
3,972,320 A 8/1976 Kalman
3,979,274 A 9/1976 Newman
4,003,379 A 1/1977 Ellinwood, Jr.
4,008,717 A 2/1977 Kowarski
4,016,866 A 4/1977 Lawton
4,021,718 A 5/1977 Konrad
4,031,449 A 6/1977 Trombly
4,036,749 A 7/1977 Anderson
4,055,175 A 10/1977 Clemens et al.
4,059,406 A 11/1977 Fleet
4,076,596 A 2/1978 Connery et al.
4,098,574 A 7/1978 Dappen
4,100,048 A 7/1978 Pompei et al.
4,129,128 A 12/1978 McFarlane
4,151,845 A 5/1979 Clemens
4,154,231 A 5/1979 Russell
4,168,205 A 9/1979 Danninger et al.
4,172,770 A 10/1979 Semersky et al.
4,178,916 A 12/1979 McNamara
4,193,026 A 3/1980 Finger et al.
4,206,755 A 6/1980 Klein
4,224,125 A 9/1980 Nakamura et al.
4,240,438 A 12/1980 Updike et al.
4,240,889 A 12/1980 Yoda et al.
4,245,634 A 1/1981 Albisser et al.
4,247,297 A 1/1981 Berti et al.
4,271,449 A 6/1981 Grogan
4,318,784 A 3/1982 Higgins et al.
4,327,725 A 5/1982 Cortese et al.
4,331,869 A 5/1982 Rollo
4,340,458 A 7/1982 Lerner et al.
4,344,438 A 8/1982 Schultz
4,349,728 A 9/1982 Phillips et al.
4,352,960 A 10/1982 Dormer et al.
4,356,074 A 10/1982 Johnson
4,365,637 A 12/1982 Johnson
4,366,033 A 12/1982 Richter et al.
4,375,399 A 3/1983 Havas et al.
4,384,586 A 5/1983 Christiansen
4,390,621 A 6/1983 Bauer
4,392,933 A 7/1983 Nakamura et al.
4,401,122 A 8/1983 Clark, Jr.
4,404,066 A 9/1983 Johnson
4,407,959 A 10/1983 Tsuji et al.
4,417,588 A 11/1983 Houghton et al.
4,418,148 A 11/1983 Oberhardt
4,420,564 A 12/1983 Tsuji et al.
4,425,920 A 1/1984 Bourland et al.
4,427,004 A 1/1984 Miller et al.
4,427,770 A 1/1984 Chen et al.
4,431,004 A 2/1984 Bessman et al.
4,436,094 A 3/1984 Cerami
4,440,175 A 4/1984 Wilkins
4,441,968 A 4/1984 Emmer et al.
4,444,892 A 4/1984 Malmros
4,445,090 A 4/1984 Melocik et al.
4,450,842 A 5/1984 Zick et al.
4,458,686 A 7/1984 Clark, Jr.
4,461,691 A 7/1984 Frank
4,464,170 A 8/1984 Clemens et al.
4,467,811 A 8/1984 Clark, Jr.
4,469,110 A 9/1984 Slama
4,475,901 A 10/1984 Kraegen et al.
4,477,314 A 10/1984 Richter et al.
4,478,976 A 10/1984 Goertz et al.
4,483,924 A 11/1984 Tsuji et al.
4,484,987 A 11/1984 Gough
4,494,950 A 1/1985 Fischell
4,509,531 A 4/1985 Ward
4,512,348 A 4/1985 Uchigaki et al.
4,522,690 A 6/1985 Venkatsetty
4,524,114 A 6/1985 Samuels et al.
4,526,661 A 7/1985 Steckhan et al.
4,527,240 A 7/1985 Kvitash
4,534,356 A 8/1985 Papadakis
4,538,616 A 9/1985 Rogoff
4,543,955 A 10/1985 Schroeppel
4,545,382 A 10/1985 Higgins et al.
4,552,840 A 11/1985 Riffer
4,560,534 A 12/1985 Kung et al.
4,569,589 A 2/1986 Neufeld
4,571,292 A 2/1986 Liu et al.
4,573,994 A 3/1986 Fischell et al.
4,581,336 A 4/1986 Malloy et al.
4,583,035 A 4/1986 Sloan
4,595,011 A 6/1986 Phillips
4,595,479 A 6/1986 Kimura et al.
4,601,707 A 7/1986 Albisser et al.
4,619,754 A 10/1986 Niki et al.
4,619,793 A 10/1986 Lee
4,627,445 A 12/1986 Garcia et al.
4,627,908 A 12/1986 Miller
4,633,878 A 1/1987 Bombardien
4,633,881 A 1/1987 Moore et al.
4,637,403 A 1/1987 Garcia et al.
4,648,408 A 3/1987 Hutcheson et al.
4,650,547 A 3/1987 Gough
4,653,513 A 3/1987 Dombrowski
4,654,197 A 3/1987 Lilja et al.
4,655,880 A 4/1987 Liu
4,655,885 A 4/1987 Hill et al.
4,658,463 A 4/1987 Sugita et al.
4,671,288 A 6/1987 Gough
4,674,652 A 6/1987 Aten et al.
4,679,562 A 7/1987 Luksha
4,680,268 A 7/1987 Clark, Jr.
4,682,602 A 7/1987 Prohaska
4,684,537 A 8/1987 Graetzel et al.
4,685,463 A 8/1987 Williams
4,685,903 A 8/1987 Cable et al.
4,686,624 A 8/1987 Blum et al.
4,703,324 A 10/1987 White
4,703,756 A 11/1987 Gough et al.
4,711,245 A 12/1987 Higgins et al.
4,717,673 A 1/1988 Wrighton et al.
4,721,601 A 1/1988 Wrighton et al.
4,721,677 A 1/1988 Clark, Jr.
4,726,378 A 2/1988 Kaplan
4,726,716 A 2/1988 McGuire
4,731,726 A 3/1988 Allen, III
4,749,985 A 6/1988 Corsberg
4,750,496 A 6/1988 Reinhardt
4,757,022 A 7/1988 Shults et al.
4,758,323 A 7/1988 Davis et al.
4,759,371 A 7/1988 Franetzki
4,759,828 A 7/1988 Young et al.
4,764,416 A 8/1988 Ueyama et al.
4,776,944 A 10/1988 Janata et al.
4,777,953 A 10/1988 Ash et al.
4,779,618 A 10/1988 Mund et al.
4,781,798 A 11/1988 Gough
4,784,736 A 11/1988 Lonsdale et al.
4,795,707 A 1/1989 Niiyama et al.
4,796,634 A 1/1989 Huntsman et al.
4,803,625 A 2/1989 Fu et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,805,624	A	2/1989	Yao et al.
4,813,424	A	3/1989	Wilkins
4,815,469	A	3/1989	Cohen et al.
4,820,399	A	4/1989	Senda et al.
4,822,337	A	4/1989	Newhouse et al.
4,830,959	A	5/1989	McNeil et al.
4,832,797	A	5/1989	Vadgama et al.
4,835,372	A	5/1989	Gombrich et al.
RE32,947	E	6/1989	Dormer et al.
4,837,049	A	6/1989	Byers et al.
4,840,893	A	6/1989	Hill et al.
RE32,974	E	7/1989	Porat et al.
4,844,076	A	7/1989	Lesho et al.
4,845,035	A	7/1989	Fanta et al.
4,847,785	A	7/1989	Stephens
4,848,351	A	7/1989	Finch
4,854,322	A	8/1989	Ash et al.
4,856,340	A	8/1989	Garrison
4,857,713	A	8/1989	Brown
4,858,617	A	8/1989	Sanders
4,870,561	A	9/1989	Love et al.
4,871,351	A	10/1989	Feingold
4,871,440	A	10/1989	Nagata et al.
4,874,499	A	10/1989	Smith et al.
4,874,500	A	10/1989	Madou et al.
4,890,620	A	1/1990	Gough
4,890,621	A	1/1990	Hakky
4,894,137	A	1/1990	Takizawa et al.
4,897,162	A	1/1990	Lewandowski et al.
4,897,173	A	1/1990	Nankai et al.
4,899,839	A	2/1990	Dessertine et al.
4,909,908	A	3/1990	Ross et al.
4,911,794	A	3/1990	Parce et al.
4,917,800	A	4/1990	Lonsdale et al.
4,919,141	A	4/1990	Zier et al.
4,919,767	A	4/1990	Vadgama et al.
4,920,969	A	5/1990	Suzuki
4,920,977	A	5/1990	Haynes
4,923,586	A	5/1990	Katayama et al.
4,925,268	A	5/1990	Iyer et al.
4,927,516	A	5/1990	Yamaguchi et al.
4,931,795	A	6/1990	Gord
4,934,369	A	6/1990	Maxwell
4,935,105	A	6/1990	Churchouse
4,935,345	A	6/1990	Guilbeau et al.
4,936,956	A	6/1990	Wrighton
4,938,860	A	7/1990	Wogoman
4,942,127	A	7/1990	Wada et al.
4,944,299	A	7/1990	Silvian
4,945,045	A	7/1990	Forrest et al.
4,950,378	A	8/1990	Nagata
4,953,552	A	9/1990	DeMarzo
4,954,129	A	9/1990	Giuliani et al.
4,957,115	A	9/1990	Selker
4,958,632	A	9/1990	Duggan
4,968,400	A	11/1990	Shimomura et al.
4,969,468	A	11/1990	Byers et al.
4,970,145	A	11/1990	Bennetto et al.
4,974,929	A	12/1990	Curry
4,979,509	A	12/1990	Hakky
4,986,271	A	1/1991	Wilkins
4,990,845	A	2/1991	Gord
4,991,582	A	2/1991	Byers et al.
4,994,068	A	2/1991	Hufnagie
4,994,167	A	2/1991	Shults et al.
4,995,402	A	2/1991	Smith et al.
5,000,180	A	3/1991	Kuypers et al.
5,001,054	A	3/1991	Wagner
5,002,054	A	3/1991	Ash et al.
5,007,427	A	4/1991	Suzuki et al.
5,016,172	A	5/1991	Dessertine
5,016,201	A	5/1991	Bryan et al.
5,019,974	A	5/1991	Beckers
5,034,192	A	7/1991	Wrighton et al.
5,035,860	A	7/1991	Kleingeld et al.
5,036,860	A	8/1991	Leigh et al.
5,036,861	A	8/1991	Sembrowich et al.
5,037,527	A	8/1991	Hayashi et al.
5,049,487	A	9/1991	Phillips et al.
5,050,612	A	9/1991	Matsumura
5,051,688	A	9/1991	Murase et al.
5,055,171	A	10/1991	Peck
5,058,592	A	10/1991	Whisler
5,061,941	A	10/1991	Lizzi et al.
5,063,081	A	11/1991	Cozzette et al.
5,068,536	A	11/1991	Rosenthal
5,070,535	A	12/1991	Hochmair et al.
5,073,500	A	12/1991	Saito et al.
5,077,476	A	12/1991	Rosenthal
5,078,854	A	1/1992	Burgess et al.
5,082,550	A	1/1992	Rishpon et al.
5,082,786	A	1/1992	Nakamoto
5,084,828	A	1/1992	Kaufman et al.
5,089,112	A	2/1992	Skotheim et al.
5,094,951	A	3/1992	Rosenberg
5,095,904	A	3/1992	Seligman et al.
5,096,560	A	3/1992	Takai et al.
5,096,836	A	3/1992	Macho et al.
5,097,834	A	3/1992	Skrabal
5,101,814	A	4/1992	Palti
5,106,365	A	4/1992	Hernandez
5,108,564	A	4/1992	Szuminsky et al.
5,109,850	A	5/1992	Blanco et al.
5,111,539	A	5/1992	Hiruta et al.
5,111,818	A	5/1992	Suzuji et al.
5,112,455	A	5/1992	Cozzette et al.
5,114,678	A	5/1992	Crawford et al.
5,120,420	A	6/1992	Nankai et al.
5,120,421	A	6/1992	Glass et al.
5,122,925	A	6/1992	Inpyn
5,124,661	A	6/1992	Zellin et al.
5,126,034	A	6/1992	Carter et al.
5,126,247	A	6/1992	Palmer et al.
5,130,009	A	7/1992	Marsoner et al.
5,133,856	A	7/1992	Yamaguchi et al.
5,134,391	A	7/1992	Okada
5,135,003	A	8/1992	Souma
5,135,004	A	8/1992	Adams et al.
5,139,023	A	8/1992	Stanley et al.
5,140,393	A	8/1992	Hijikihigawa et al.
5,141,868	A	8/1992	Shanks et al.
5,161,532	A	11/1992	Joseph
5,165,407	A	11/1992	Wilson et al.
5,168,046	A	12/1992	Hamamoto et al.
5,174,291	A	12/1992	Schoonen et al.
5,176,644	A	1/1993	Srisathapat et al.
5,176,662	A	1/1993	Bartholomew et al.
5,182,707	A	1/1993	Cooper et al.
5,184,359	A	2/1993	Tsukamura et al.
5,185,256	A	2/1993	Nankai et al.
5,190,041	A	3/1993	Palti
5,192,415	A	3/1993	Yoshioka et al.
5,192,416	A	3/1993	Wang et al.
5,193,539	A	3/1993	Schulman et al.
5,193,540	A	3/1993	Schulman et al.
5,197,322	A	3/1993	Indravudh
5,198,367	A	3/1993	Aizawa et al.
5,200,051	A	4/1993	Cozzette et al.
5,202,261	A	4/1993	Musho et al.
5,205,920	A	4/1993	Oyama et al.
5,206,145	A	4/1993	Cattell
5,208,154	A	5/1993	Weaver et al.
5,209,229	A	5/1993	Gilli
5,215,887	A	6/1993	Saito
5,216,597	A	6/1993	Beckers
5,217,442	A	6/1993	Davis
5,217,595	A	6/1993	Smith et al.
5,227,042	A	7/1993	Zawodzinski et al.
5,229,282	A	7/1993	Yoshioka et al.
5,236,143	A	8/1993	Dragon
5,237,993	A	8/1993	Skrabal
5,245,314	A	9/1993	Kah et al.
5,246,867	A	9/1993	Lakowicz et al.
5,250,439	A	10/1993	Musho et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,251,126	A	10/1993	Kahn et al.
5,257,971	A	11/1993	Lord et al.
5,257,980	A	11/1993	Van Antwerp et al.
5,261,401	A	11/1993	Baker et al.
5,262,035	A	11/1993	Gregg et al.
5,262,305	A	11/1993	Heller et al.
5,264,103	A	11/1993	Yoshioka et al.
5,264,104	A	11/1993	Gregg et al.
5,264,105	A	11/1993	Gregg et al.
5,264,106	A	11/1993	McAleer et al.
5,265,888	A	11/1993	Yamamoto et al.
5,266,179	A	11/1993	Nankai et al.
5,269,212	A	12/1993	Peters et al.
5,271,815	A	12/1993	Wong
5,272,060	A	12/1993	Hamamoto et al.
5,275,159	A	1/1994	Griebel
5,278,079	A	1/1994	Gubinski et al.
5,279,294	A	1/1994	Anderson et al.
5,282,950	A	2/1994	Dietze et al.
5,284,156	A	2/1994	Schramm et al.
5,285,792	A	2/1994	Sjoquist et al.
5,286,362	A	2/1994	Hoenes et al.
5,286,364	A	2/1994	Yacynych et al.
5,288,636	A	2/1994	Pollmann et al.
5,289,497	A	2/1994	Jackobson et al.
5,291,887	A	3/1994	Stanley et al.
5,293,546	A	3/1994	Tadros et al.
5,293,877	A	3/1994	O'Hara et al.
5,299,571	A	4/1994	Mastrototaro
5,304,468	A	4/1994	Phillips et al.
5,307,263	A	4/1994	Brown
5,309,919	A	5/1994	Snell et al.
5,310,885	A	5/1994	Maier et al.
5,320,098	A	6/1994	Davidson
5,320,725	A	6/1994	Gregg et al.
5,322,063	A	6/1994	Allen et al.
5,324,303	A	6/1994	Strong et al.
5,324,316	A	6/1994	Schulman et al.
5,326,449	A	7/1994	Cunningham
5,333,615	A	8/1994	Craelius et al.
5,337,258	A	8/1994	Dennis
5,337,747	A	8/1994	Neftei
5,340,722	A	8/1994	Wolfbeis et al.
5,342,408	A	8/1994	deCoriolis et al.
5,342,789	A	8/1994	Chick et al.
5,352,348	A	10/1994	Young et al.
5,356,348	A	10/1994	Bellio et al.
5,356,786	A	10/1994	Heller et al.
5,358,135	A	10/1994	Robbins et al.
5,358,514	A	10/1994	Schulman et al.
5,360,404	A	11/1994	Novacek et al.
5,364,797	A	11/1994	Olson et al.
5,366,609	A	11/1994	White et al.
5,368,028	A	11/1994	Palti
5,370,622	A	12/1994	Livingston et al.
5,371,687	A	12/1994	Holmes, II et al.
5,371,734	A	12/1994	Fischer
5,371,787	A	12/1994	Hamilton
5,372,133	A	12/1994	Hogen Esch
5,372,427	A	12/1994	Padovani et al.
5,376,070	A	12/1994	Purvis et al.
5,376,251	A	12/1994	Kaneko et al.
5,377,258	A	12/1994	Bro
5,378,628	A	1/1995	Gratzel et al.
5,379,238	A	1/1995	Stark
5,379,764	A	1/1995	Barnes et al.
5,380,422	A	1/1995	Negishis et al.
5,382,346	A	1/1995	Uenoyama et al.
5,387,327	A	2/1995	Khan
5,390,671	A	2/1995	Lord et al.
5,391,250	A	2/1995	Cheney, II et al.
5,393,903	A	2/1995	Gratzel et al.
5,395,504	A	3/1995	Saurer et al.
5,399,823	A	3/1995	McCusker
5,400,782	A	3/1995	Beaubiah
5,400,794	A	3/1995	Gorman
5,408,999	A	4/1995	Singh et al.
5,410,326	A	4/1995	Goldstein
5,410,471	A	4/1995	Alyfuku et al.
5,410,474	A	4/1995	Fox
5,411,647	A	5/1995	Johnson et al.
5,413,690	A	5/1995	Kost et al.
5,422,246	A	6/1995	Koopal et al.
5,425,868	A	6/1995	Pedersen
5,429,602	A	7/1995	Hauser
5,431,160	A	7/1995	Wilkins
5,431,691	A	7/1995	Snell et al.
5,431,921	A	7/1995	Thombre
5,433,710	A	7/1995	Van Antwerp et al.
5,437,973	A	8/1995	Vadgama et al.
5,437,999	A	8/1995	Dieboid et al.
5,438,271	A	8/1995	White et al.
5,438,983	A	8/1995	Falcone
5,445,611	A	8/1995	Eppstein et al.
5,445,920	A	8/1995	Saito
5,456,692	A	10/1995	Smith, Jr. et al.
5,456,940	A	10/1995	Funderburk
5,458,140	A	10/1995	Eppstein et al.
5,460,618	A	10/1995	Harreld
5,462,051	A	10/1995	Oka et al.
5,462,525	A	10/1995	Srisathapat et al.
5,462,645	A	10/1995	Albery et al.
5,466,218	A	11/1995	Srisathapat et al.
5,467,778	A	11/1995	Catt et al.
5,469,846	A	11/1995	Khan
5,472,317	A	12/1995	Field et al.
5,476,460	A	12/1995	Montalvo
5,477,855	A	12/1995	Schindler et al.
5,482,473	A	1/1996	Lord et al.
5,484,404	A	1/1996	Schulman et al.
5,487,751	A	1/1996	Radons et al.
5,491,474	A	2/1996	Suni et al.
5,494,562	A	2/1996	Maley et al.
5,496,453	A	3/1996	Uenoyama et al.
5,497,772	A	3/1996	Schulman et al.
5,499,243	A	3/1996	Hall
5,501,956	A	3/1996	Wada et al.
5,505,709	A	4/1996	Funderburk et al.
5,505,713	A	4/1996	Van Antwerp et al.
5,507,288	A	4/1996	Bocker et al.
5,508,171	A	4/1996	Walling et al.
5,509,410	A	4/1996	Hill et al.
5,514,103	A	5/1996	Srisathapat et al.
5,514,253	A	5/1996	Davis et al.
5,514,718	A	5/1996	Lewis et al.
5,518,006	A	5/1996	Mawhirt et al.
5,520,787	A	5/1996	Hanagan et al.
5,522,865	A	6/1996	Schulman et al.
5,525,511	A	6/1996	D'Costa
5,526,120	A	6/1996	Jina et al.
5,527,307	A	6/1996	Srisathapat et al.
5,529,676	A	6/1996	Maley et al.
5,531,878	A	7/1996	Vadgama et al.
5,532,686	A	7/1996	Urbas et al.
5,538,511	A	7/1996	Van Antwerp et al.
5,544,196	A	8/1996	Tiedmann, Jr. et al.
5,545,152	A	8/1996	Funderburk et al.
5,545,191	A	8/1996	Mann et al.
5,549,113	A	8/1996	Halleck et al.
5,549,115	A	8/1996	Morgan et al.
5,552,027	A	9/1996	Birkle et al.
5,554,166	A	9/1996	Lange et al.
5,556,524	A	9/1996	Albers
5,560,357	A	10/1996	Faupei et al.
5,562,713	A	10/1996	Silvian
5,565,085	A	10/1996	Ikeda et al.
5,567,302	A	10/1996	Song et al.
5,568,806	A	10/1996	Cheney, II et al.
5,569,186	A	10/1996	Lord et al.
5,569,212	A	10/1996	Brown
5,573,647	A	11/1996	Maley et al.
5,575,895	A	11/1996	Ikeda et al.
5,580,527	A	12/1996	Bell et al.
5,580,794	A	12/1996	Allen

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,581,206 A 12/1996 Chevallier et al.
5,582,184 A 12/1996 Erickson et al.
5,582,697 A 12/1996 Ikeda et al.
5,582,698 A 12/1996 Flaherty et al.
5,584,813 A 12/1996 Livingston et al.
5,586,553 A 12/1996 Halili et al.
5,589,326 A 12/1996 Deng et al.
5,593,852 A 1/1997 Heller et al.
5,594,906 A 1/1997 Holmes, II et al.
5,596,150 A 1/1997 Arndy et al.
5,596,994 A 1/1997 Bro
5,600,301 A 2/1997 Robinson, III
5,601,435 A 2/1997 Quy
5,601,694 A 2/1997 Maley et al.
5,605,152 A 2/1997 Slate et al.
5,609,575 A 3/1997 Larson et al.
5,611,900 A 3/1997 Worden et al.
5,615,135 A 3/1997 Waclawsky et al.
5,615,671 A 4/1997 Schoonen et al.
5,616,222 A 4/1997 Maley et al.
5,617,851 A 4/1997 Lipkovker
5,623,925 A 4/1997 Swenson et al.
5,623,933 A 4/1997 Amano et al.
5,628,309 A 5/1997 Brown
5,628,310 A 5/1997 Rao et al.
5,628,890 A 5/1997 Carter et al.
5,629,981 A 5/1997 Nerlikar
5,634,468 A 6/1997 Platt et al.
5,637,095 A 6/1997 Nason et al.
5,640,764 A 6/1997 Strojnik
5,640,954 A 6/1997 Pfeiffer et al.
5,643,212 A 7/1997 Coutre et al.
5,647,853 A 7/1997 Feldmann et al.
5,650,062 A 7/1997 Ikeda et al.
5,651,767 A 7/1997 Schulman et al.
5,651,869 A 7/1997 Yoshioka et al.
5,653,239 A 8/1997 Pompei et al.
5,659,454 A 8/1997 Vermesse
5,660,163 A 8/1997 Schulman et al.
5,665,065 A 9/1997 Colman et al.
5,665,222 A 9/1997 Heller et al.
5,667,983 A 9/1997 Abel et al.
5,670,031 A 9/1997 Hintsche et al.
5,678,571 A 10/1997 Brown
5,679,690 A 10/1997 Andre et al.
5,680,858 A 10/1997 Hansen et al.
5,682,233 A 10/1997 Brinda
5,686,717 A 11/1997 Knowles et al.
5,695,623 A 12/1997 Michel et al.
5,695,949 A 12/1997 Galen et al.
5,701,894 A 12/1997 Cherry et al.
5,704,922 A 1/1998 Brown
5,707,502 A 1/1998 McCaffrey et al.
5,708,247 A 1/1998 McAleer et al.
5,710,630 A 1/1998 Essenpreis et al.
5,711,001 A 1/1998 Bussan et al.
5,711,297 A 1/1998 Iliff et al.
5,711,861 A 1/1998 Ward et al.
5,711,862 A 1/1998 Sakoda et al.
5,711,868 A 1/1998 Maley et al.
5,718,234 A 2/1998 Warden et al.
5,720,733 A 2/1998 Brown
5,720,862 A 2/1998 Hamamoto et al.
5,721,783 A 2/1998 Anderson
5,722,397 A 3/1998 Eppstein
5,724,030 A 3/1998 Urbas et al.
5,726,646 A 3/1998 Bane et al.
5,727,548 A 3/1998 Hill et al.
5,729,225 A 3/1998 Ledzius
5,730,124 A 3/1998 Yamauchi
5,730,654 A 3/1998 Brown
5,733,313 A 3/1998 Barreras, Sr. et al.
5,735,273 A 4/1998 Kurnik et al.
5,735,285 A 4/1998 Albert et al.
5,741,211 A 4/1998 Renirie et al.
5,741,688 A 4/1998 Oxenboll et al.
5,746,217 A 5/1998 Erickson et al.
5,748,103 A 5/1998 Flach et al.
5,749,907 A 5/1998 Mann
5,750,926 A 5/1998 Schulman et al.
5,758,290 A 5/1998 Nealon et al.
5,769,873 A 6/1998 Zadeh
5,770,028 A 6/1998 Maley et al.
5,771,001 A 6/1998 Cobb
5,771,890 A 6/1998 Tamada
5,772,586 A 6/1998 Heinonen et al.
5,777,060 A 7/1998 Van Antwerp
5,779,665 A 7/1998 Mastrototaro et al.
5,781,024 A 7/1998 Blomberg et al.
5,782,814 A 7/1998 Brown et al.
5,785,681 A 7/1998 Indravudh
5,786,439 A 7/1998 Van Antwerp et al.
5,786,584 A 7/1998 Button et al.
5,788,678 A 8/1998 Van Antwerp
5,791,344 A 8/1998 Schulman et al.
5,792,117 A 8/1998 Brown
5,793,292 A 8/1998 Ivey
5,800,420 A 9/1998 Gross et al.
5,804,047 A 9/1998 Karube et al.
5,804,048 A 9/1998 Wong et al.
5,807,315 A 9/1998 Van Antwerp et al.
5,807,375 A 9/1998 Gross et al.
5,814,599 A 9/1998 Mitragotri et al.
5,820,551 A 10/1998 Hill et al.
5,820,570 A 10/1998 Erickson et al.
5,820,622 A 10/1998 Gross et al.
5,822,715 A 10/1998 Worthington et al.
5,825,488 A 10/1998 Kohl et al.
5,827,179 A 10/1998 Lichter et al.
5,827,183 A 10/1998 Kurnik et al.
5,827,184 A 10/1998 Netherly et al.
5,828,943 A 10/1998 Brown
5,830,064 A 11/1998 Bradish et al.
5,830,132 A 11/1998 Robinson
5,830,341 A 11/1998 Gilmartin
5,832,448 A 11/1998 Brown
5,833,603 A 11/1998 Kovacs et al.
5,834,224 A 11/1998 Ruger et al.
5,837,454 A 11/1998 Cozzette et al.
5,837,546 A 11/1998 Allen et al.
5,840,020 A 11/1998 Heinonen et al.
5,842,983 A 12/1998 Abel et al.
5,843,140 A 12/1998 Strojnik
5,846,702 A 12/1998 Deng et al.
5,846,744 A 12/1998 Athey et al.
5,851,197 A 12/1998 Marano et al.
5,854,078 A 12/1998 Asher et al.
5,854,189 A 12/1998 Kruse et al.
5,856,758 A 1/1999 Joffe et al.
5,857,967 A 1/1999 Frid et al.
5,857,983 A 1/1999 Douglas et al.
5,860,917 A 1/1999 Comanor et al.
5,872,713 A 2/1999 Douglas et al.
5,876,484 A 3/1999 Raskin et al.
5,879,163 A 3/1999 Brown et al.
5,879,311 A 3/1999 Duchon et al.
5,880,829 A 3/1999 Kauhaniemi et al.
5,882,494 A 3/1999 Van Antwerp
5,885,211 A 3/1999 Eppstein et al.
5,887,133 A 3/1999 Brown et al.
5,891,049 A 4/1999 Cyrus et al.
5,897,493 A 4/1999 Brown
5,898,025 A 4/1999 Burg et al.
5,899,855 A 5/1999 Brown
5,913,310 A 6/1999 Brown
5,917,346 A 6/1999 Gord
5,918,603 A 7/1999 Brown
5,919,141 A 7/1999 Money et al.
5,925,021 A 7/1999 Castellano et al.
5,931,791 A 8/1999 Saltzstein et al.
5,933,136 A 8/1999 Brown
5,935,099 A 8/1999 Petterson
5,935,224 A 8/1999 Svancarek et al.
5,939,609 A 8/1999 Knapp et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,940,801	A	8/1999	Brown
5,942,979	A	8/1999	Luppino
5,945,345	A	8/1999	Blatt et al.
5,947,921	A	9/1999	Johnson et al.
5,948,512	A	9/1999	Kubota et al.
5,950,632	A	9/1999	Reber et al.
5,951,300	A	9/1999	Brown
5,951,485	A	9/1999	Cyrus et al.
5,951,492	A	9/1999	Douglas et al.
5,951,521	A	9/1999	Mastrototaro et al.
5,951,836	A	9/1999	McAleer et al.
5,954,643	A	9/1999	Van Antwerp
5,954,685	A	9/1999	Tierny
5,954,700	A	9/1999	Kovelman
5,956,501	A	9/1999	Brown
5,957,854	A	9/1999	Besson et al.
5,957,890	A	9/1999	Mann et al.
5,957,958	A	9/1999	Schulman et al.
5,960,403	A	9/1999	Brown
5,961,451	A	10/1999	Reber et al.
5,964,993	A	10/1999	Blubaugh, Jr. et al.
5,965,380	A	10/1999	Heller et al.
5,968,839	A	10/1999	Blatt et al.
5,971,922	A	10/1999	Arita et al.
5,971,941	A	10/1999	Simons et al.
5,974,124	A	10/1999	Schlueter, Jr. et al.
5,977,476	A	11/1999	Guha et al.
5,981,294	A	11/1999	Blatt et al.
5,989,409	A	11/1999	Kurnik et al.
5,994,476	A	11/1999	Shin et al.
5,995,860	A	11/1999	Sun et al.
5,997,476	A	12/1999	Brown
5,999,848	A	12/1999	Gord et al.
5,999,849	A	12/1999	Gord et al.
6,001,067	A	12/1999	Shults et al.
6,002,954	A	12/1999	Van Antwerp et al.
6,002,961	A	12/1999	Mitragotri et al.
6,004,441	A	12/1999	Fujiwara et al.
6,011,984	A	1/2000	Van Antwerp et al.
6,014,577	A	1/2000	Henning et al.
6,018,678	A	1/2000	Mitragotri et al.
6,023,629	A	2/2000	Tamada
6,024,699	A	2/2000	Surwit et al.
6,026,320	A	2/2000	Carlson et al.
6,027,459	A	2/2000	Shain et al.
6,027,692	A	2/2000	Galen et al.
6,028,413	A	2/2000	Brockmann
6,032,059	A	2/2000	Henning et al.
6,032,199	A	2/2000	Lim et al.
6,033,866	A	3/2000	Guo et al.
6,035,237	A	3/2000	Schulman et al.
6,040,194	A	3/2000	Chick et al.
6,041,253	A	3/2000	Kost et al.
6,043,437	A	3/2000	Schulman et al.
6,049,727	A	4/2000	Crothall
6,052,565	A	4/2000	Ishikura et al.
6,055,316	A	4/2000	Perlman et al.
6,056,718	A	5/2000	Funderburk et al.
6,063,459	A	5/2000	Velte
6,066,243	A	5/2000	Anderson et al.
6,066,448	A	5/2000	Wohlstadter et al.
6,067,474	A	5/2000	Schulman et al.
6,068,615	A	5/2000	Brown et al.
6,071,249	A	6/2000	Cunningham et al.
6,071,251	A	6/2000	Cunningham et al.
6,071,294	A	6/2000	Simons et al.
6,071,391	A	6/2000	Gotoh et al.
6,073,031	A	6/2000	Helstab et al.
6,081,736	A	6/2000	Colvin et al.
6,083,710	A	7/2000	Heller et al.
6,088,608	A	7/2000	Schulman et al.
6,091,975	A	7/2000	Daddona et al.
6,091,976	A	7/2000	Pfeiffer et al.
6,091,987	A	7/2000	Thompson
6,093,156	A	7/2000	Cunningham et al.
6,093,167	A	7/2000	Houben et al.
6,093,172	A	7/2000	Funderburk et al.
6,096,364	A	8/2000	Bok et al.
6,097,480	A	8/2000	Kaplan
6,097,831	A	8/2000	Wieck et al.
6,099,484	A	8/2000	Douglas et al.
6,101,478	A	8/2000	Brown
6,103,033	A	8/2000	Say et al.
6,106,780	A	8/2000	Douglas et al.
6,110,148	A	8/2000	Brown et al.
6,110,152	A	8/2000	Kovelman
6,113,578	A	9/2000	Brown
6,117,290	A	9/2000	Say et al.
6,119,028	A	9/2000	Schulman et al.
6,120,676	A	9/2000	Heller et al.
6,121,009	A	9/2000	Heller et al.
6,121,611	A	9/2000	Lindsay et al.
6,122,351	A	9/2000	Schlueter, Jr. et al.
6,125,978	A	10/2000	Ando et al.
6,130,623	A	10/2000	MacLellan et al.
6,134,461	A	10/2000	Say et al.
6,134,504	A	10/2000	Douglas et al.
6,139,718	A	10/2000	Kurnik et al.
6,141,573	A	10/2000	Kurnik et al.
6,142,939	A	11/2000	Eppstein et al.
6,143,164	A	11/2000	Heller et al.
6,144,837	A	11/2000	Quy
6,144,869	A	11/2000	Berner et al.
6,144,871	A	11/2000	Saito et al.
6,144,922	A	11/2000	Douglas et al.
6,148,094	A	11/2000	Kinsella
6,150,128	A	11/2000	Uretsky
6,151,586	A	11/2000	Brown
6,153,062	A	11/2000	Saito et al.
6,153,069	A	11/2000	Pottgen et al.
6,159,147	A	12/2000	Lichter et al.
6,161,095	A	12/2000	Brown
6,162,611	A	12/2000	Heller et al.
6,162,639	A	12/2000	Douglas
6,164,284	A	12/2000	Schulman et al.
6,167,362	A	12/2000	Brown et al.
6,168,563	B1	1/2001	Brown
6,170,318	B1	1/2001	Lewis
6,175,752	B1	1/2001	Say et al.
6,180,416	B1	1/2001	Kurnik et al.
6,186,145	B1	2/2001	Brown
6,192,891	B1	2/2001	Gravel et al.
6,193,873	B1	2/2001	Ohara et al.
6,196,970	B1	3/2001	Brown
6,198,957	B1	3/2001	Green
6,200,265	B1	3/2001	Walsh et al.
6,201,979	B1	3/2001	Kurnik et al.
6,201,980	B1	3/2001	Darrow et al.
6,203,495	B1	3/2001	Bardy et al.
6,206,841	B1	3/2001	Cunningham et al.
6,207,400	B1	3/2001	Kwon
6,208,894	B1	3/2001	Schulman et al.
6,210,272	B1	4/2001	Brown
6,210,976	B1	4/2001	Sabbadini
6,212,416	B1	4/2001	Ward et al.
6,218,809	B1	4/2001	Downs et al.
6,219,565	B1	4/2001	Cupp et al.
6,219,574	B1	4/2001	Cormier et al.
6,224,745	B1	5/2001	Baltruschat
6,232,130	B1	5/2001	Wolf
6,232,370	B1	5/2001	Kubota et al.
6,233,471	B1	5/2001	Berner et al.
6,233,539	B1	5/2001	Brown
6,239,925	B1	5/2001	Ardrey et al.
6,241,862	B1	6/2001	McAleer et al.
6,246,330	B1	6/2001	Nielsen
6,246,992	B1	6/2001	Brown
6,248,065	B1	6/2001	Brown
6,248,067	B1	6/2001	Causey, III et al.
6,248,093	B1	6/2001	Moberg
6,251,260	B1	6/2001	Heller et al.
6,252,032	B1	6/2001	Van Antwerp et al.
6,253,804	B1	7/2001	Safabash
6,254,586	B1	7/2001	Mann et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,256,643 B1 7/2001 Cork et al.
6,259,587 B1 7/2001 Sheldon et al.
6,259,937 B1 7/2001 Schulman et al.
6,260,022 B1 7/2001 Brown
6,266,645 B1 7/2001 Simpson
6,267,724 B1 7/2001 Taylor
6,268,161 B1 7/2001 Han et al.
6,270,445 B1 8/2001 Dean, Jr. et al.
6,270,455 B1 8/2001 Brown
6,272,364 B1 8/2001 Kurnik
6,275,717 B1 8/2001 Gross et al.
6,280,416 B1 8/2001 Van Antwerp et al.
6,280,587 B1 8/2001 Matsumoto
6,281,006 B1 8/2001 Heller et al.
6,283,943 B1 9/2001 Dy et al.
6,284,126 B1 9/2001 Kurnik et al.
6,284,478 B1 9/2001 Heller et al.
6,291,200 B1 9/2001 LeJeune et al.
6,293,925 B1 9/2001 Safabash et al.
6,294,281 B1 9/2001 Heller
6,294,997 B1 9/2001 Paratore et al.
6,295,463 B1 9/2001 Stenzler
6,295,506 B1 9/2001 Heinonen et al.
6,298,254 B2 10/2001 Tamada
6,299,347 B1 10/2001 Pompei
6,299,578 B1 10/2001 Kurnik et al.
6,299,757 B1 10/2001 Feldman et al.
6,301,499 B1 10/2001 Carlson et al.
6,304,766 B1 10/2001 Colvin, Jr. et al.
6,306,104 B1 10/2001 Cunningham et al.
6,307,867 B1 10/2001 Roobol et al.
6,309,351 B1 10/2001 Kurnik et al.
6,309,884 B1 10/2001 Cooper et al.
6,313,749 B1 11/2001 Horne et al.
6,314,317 B1 11/2001 Willis
6,315,721 B2 11/2001 Schulman et al.
6,319,540 B1 11/2001 Van Antwerp et al.
6,326,160 B1 12/2001 Dunn et al.
6,329,161 B1 12/2001 Heller et al.
6,329,929 B1 12/2001 Weijand et al.
6,330,426 B2 12/2001 Brown et al.
6,330,464 B1 12/2001 Colvin, Jr. et al.
6,331,518 B2 12/2001 Hemm et al.
6,334,778 B1 1/2002 Brown
6,336,900 B1 1/2002 Alleckson et al.
6,338,790 B1 1/2002 Feldman et al.
6,340,421 B1 1/2002 Vachon et al.
6,341,232 B1 1/2002 Conn et al.
6,356,776 B1 3/2002 Berner et al.
6,359,270 B1 3/2002 Bridson
6,359,594 B1 3/2002 Junod
6,360,888 B1 3/2002 McIvor et al.
6,366,793 B1 4/2002 Bell et al.
6,366,794 B1 4/2002 Moussy et al.
6,368,141 B1 4/2002 Van Antwerp et al.
6,368,274 B1 4/2002 Van Antwerp et al.
6,370,410 B2 4/2002 Kurnik et al.
6,377,828 B1 4/2002 Chaiken et al.
6,379,301 B1 4/2002 Worthington et al.
6,383,767 B1 5/2002 Polak
6,385,473 B1 5/2002 Haines et al.
6,387,048 B1 5/2002 Schulman et al.
6,391,643 B1 5/2002 Chen et al.
6,393,318 B1 5/2002 Conn et al.
6,398,562 B1 6/2002 Butler et al.
6,400,974 B1 6/2002 Lesho
6,405,066 B1 6/2002 Essenpreis et al.
6,413,393 B1 7/2002 Van Antwerp et al.
6,416,471 B1 7/2002 Kumar et al.
6,418,332 B1 7/2002 Mastrototaro et al.
6,418,346 B1 7/2002 Nelson et al.
6,424,847 B1 7/2002 Mastrototaro et al.
6,427,088 B1 7/2002 Bowman, IV et al.
6,434,409 B1 8/2002 Pfeiffer et al.
6,438,414 B1 8/2002 Conn et al.
6,440,068 B1 8/2002 Brown et al.
6,442,637 B1 8/2002 Hawkins et al.
6,442,672 B1 8/2002 Ganapathy
6,443,942 B2 9/2002 Van Antwerp et al.
6,449,255 B1 9/2002 Waclawsky et al.
6,454,710 B1 9/2002 Ballerstadt et al.
6,462,162 B2 10/2002 Van Antwerp et al.
6,464,848 B1 10/2002 Matsumoto
6,466,810 B1 10/2002 Ward et al.
6,468,222 B1 10/2002 Mault et al.
6,471,689 B1 10/2002 Joseph et al.
6,472,122 B1 10/2002 Schulman et al.
6,475,750 B1 11/2002 Han et al.
6,477,395 B2 11/2002 Schulman et al.
6,478,736 B1 11/2002 Mault
6,480,730 B2 11/2002 Darrow et al.
6,480,744 B2 11/2002 Ferek-Petric
6,482,156 B2 11/2002 Iliff
6,482,158 B2 11/2002 Mault
6,482,604 B2 11/2002 Kwon
6,484,045 B1 11/2002 Holker et al.
6,484,046 B1 11/2002 Say et al.
6,485,138 B1 11/2002 Kubota et al.
6,493,069 B1 12/2002 Nagashimada et al.
6,494,830 B1 12/2002 Wessel
6,496,728 B2 12/2002 Li et al.
6,496,729 B2 12/2002 Thompson
6,497,655 B1 12/2002 Linberg et al.
6,505,059 B1 1/2003 Kollias et al.
6,505,121 B1 1/2003 Russel
6,512,939 B1 1/2003 Colvin et al.
6,513,532 B2 2/2003 Mault et al.
6,514,718 B2 2/2003 Heller et al.
6,515,593 B1 2/2003 Stark et al.
6,520,326 B2 2/2003 McIvor et al.
6,529,755 B2 3/2003 Kurnik et al.
6,529,772 B2 3/2003 Carlson et al.
6,530,915 B1 3/2003 Eppstein et al.
6,534,322 B1 3/2003 Sabbadini
6,534,323 B1 3/2003 Sabbadini
6,535,753 B1 3/2003 Raskas
6,537,243 B1 3/2003 Henning et al.
6,540,675 B2 4/2003 Aceti et al.
6,541,266 B2 4/2003 Modzelweskei et al.
6,544,212 B2 4/2003 Galley et al.
6,546,268 B1 4/2003 Ishikawa et al.
6,546,269 B1 4/2003 Kurnik
6,549,796 B2 4/2003 Sohrab
6,551,276 B1 4/2003 Mann et al.
6,551,494 B1 4/2003 Heller et al.
6,553,244 B2 4/2003 Lesho et al.
6,554,798 B1 4/2003 Mann et al.
6,558,320 B1 5/2003 Causey, III et al.
6,558,321 B1 5/2003 Burd et al.
6,558,351 B1 5/2003 Steil et al.
6,560,471 B1 5/2003 Heller et al.
6,561,975 B1 5/2003 Pool et al.
6,561,978 B1 5/2003 Conn et al.
6,562,001 B2 5/2003 Lebel et al.
6,564,105 B2 5/2003 Starkweather et al.
6,564,807 B1 5/2003 Schulman et al.
6,565,509 B1 5/2003 Say et al.
6,571,128 B2 5/2003 Lebel et al.
6,571,200 B1 5/2003 Mault
6,572,545 B2 6/2003 Knobbe et al.
6,574,510 B2 6/2003 Von Arx et al.
6,576,101 B1 6/2003 Heller et al.
6,576,117 B1 6/2003 Iketaki et al.
6,577,899 B2 6/2003 Lebel et al.
6,579,231 B1 6/2003 Phipps
6,579,498 B1 6/2003 Eglise
6,579,690 B1 6/2003 Bonnecaze et al.
6,580,364 B1 6/2003 Munch et al.
6,584,335 B1 6/2003 Haar et al.
6,585,644 B2 7/2003 Lebel et al.
6,587,705 B1 7/2003 Kim et al.
6,591,125 B1 7/2003 Buse et al.
6,591,126 B2 7/2003 Roeper et al.
6,594,514 B2 7/2003 Berner et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,595,919	B2	7/2003	Berner et al.
6,595,929	B2	7/2003	Stivoric et al.
6,602,678	B2	8/2003	Kwon et al.
6,602,909	B1	8/2003	Jarowski
6,605,200	B1	8/2003	Mao et al.
6,605,201	B1	8/2003	Mao et al.
6,607,509	B2	8/2003	Bobroff et al.
6,608,562	B1	8/2003	Kimura et al.
6,610,012	B2	8/2003	Mault
6,611,206	B2	8/2003	Eshelman et al.
6,612,306	B1	9/2003	Mault
6,615,078	B1	9/2003	Burson et al.
6,616,613	B1	9/2003	Goodman
6,618,603	B2	9/2003	Varalli et al.
6,620,106	B2	9/2003	Mault
6,627,058	B1	9/2003	Chan
6,627,154	B1	9/2003	Goodman et al.
6,629,934	B2	10/2003	Mault et al.
6,633,772	B2	10/2003	Ford et al.
6,635,014	B2	10/2003	Starkweather et al.
6,635,167	B1	10/2003	Batman et al.
6,641,533	B2	11/2003	Causey, III et al.
6,642,015	B2	11/2003	Vachon et al.
6,645,142	B2	11/2003	Braig et al.
6,645,368	B1	11/2003	Beaty et al.
6,648,821	B2	11/2003	Lebel et al.
6,653,091	B1	11/2003	Dunn et al.
6,654,625	B1	11/2003	Say et al.
6,656,114	B1	12/2003	Poulson et al.
6,658,396	B1	12/2003	Tang et al.
6,659,948	B2	12/2003	Lebel et al.
6,668,196	B1	12/2003	Villegas et al.
6,671,554	B2	12/2003	Gibson et al.
6,673,625	B2	1/2004	Satcher, Jr. et al.
6,682,938	B1	1/2004	Satcher, Jr. et al.
6,683,040	B2	1/2004	Bragulla et al.
6,687,522	B2	2/2004	Tamada
6,687,546	B2	2/2004	Lebel et al.
6,689,056	B1	2/2004	Kilcoyne et al.
6,690,276	B1	2/2004	Marino
6,692,446	B2	2/2004	Hoek
6,693,069	B2	2/2004	Korber et al.
6,694,158	B2	2/2004	Polak
6,694,191	B2	2/2004	Starkweather et al.
6,695,860	B1	2/2004	Ward et al.
6,698,269	B2	3/2004	Baber et al.
6,701,270	B1	3/2004	Miller et al.
6,702,857	B2	3/2004	Brauker et al.
6,704,587	B1	3/2004	Kumar et al.
6,708,057	B2	3/2004	Morganroth
6,711,423	B2	3/2004	Colvin, Jr.
6,723,046	B2	4/2004	Lichtenstein et al.
6,728,560	B2	4/2004	Kollias et al.
6,730,025	B1	5/2004	Platt
6,731,976	B2	5/2004	Penn et al.
6,733,446	B2	5/2004	Lebel et al.
6,734,162	B2	5/2004	Van Antwerp et al.
6,735,183	B2	5/2004	O'Toole et al.
6,735,479	B2	5/2004	Fabian et al.
6,736,777	B2	5/2004	Kim et al.
6,736,797	B1	5/2004	Larsen et al.
6,737,401	B2	5/2004	Kim et al.
6,738,654	B2	5/2004	Sohrab
6,740,075	B2	5/2004	Lebel et al.
6,741,163	B1	5/2004	Roberts
6,741,876	B1	5/2004	Scecina et al.
6,741,877	B1	5/2004	Shults et al.
6,746,582	B2	6/2004	Heller et al.
6,748,445	B1	6/2004	Darcey et al.
6,749,587	B2	6/2004	Flaherty
6,750,311	B1	6/2004	Van Antwerp et al.
6,758,810	B2	7/2004	Lebel et al.
6,766,183	B2	7/2004	Walsh et al.
6,766,201	B2	7/2004	Von Arx et al.
6,768,425	B2	7/2004	Flaherty et al.
6,770,030	B1	8/2004	Schaupp et al.
6,770,729	B2	8/2004	Van Antwerp et al.
6,771,995	B2	8/2004	Kurnik et al.
6,773,563	B2	8/2004	Matsumoto
6,780,156	B2	8/2004	Haueter et al.
6,780,297	B2	8/2004	Matsumoto et al.
6,780,871	B2	8/2004	Glick et al.
6,784,274	B2	8/2004	Van Antwerp et al.
6,790,178	B1	9/2004	Mault et al.
6,794,195	B2	9/2004	Colvin, Jr.
6,800,451	B2	10/2004	Daniloff et al.
6,804,544	B2	10/2004	Van Antwerp et al.
6,804,558	B2	10/2004	Haller et al.
6,809,507	B2	10/2004	Morgan et al.
6,809,653	B1	10/2004	Mann et al.
6,810,290	B2	10/2004	Lebel et al.
6,810,309	B2	10/2004	Sadler et al.
6,811,533	B2	11/2004	Lebel et al.
6,811,534	B2	11/2004	Bowman, IV et al.
6,811,659	B2	11/2004	Vachon
6,812,031	B1	11/2004	Carlsson
6,813,519	B2	11/2004	Lebel et al.
6,816,742	B2	11/2004	Kim et al.
6,835,553	B2	12/2004	Han et al.
RE38,681	E	1/2005	Kurnik et al.
6,840,912	B2	1/2005	Kloepfer et al.
6,844,023	B2	1/2005	Schulman et al.
6,849,237	B2	2/2005	Housefield et al.
6,850,790	B2	2/2005	Berner et al.
6,852,104	B2	2/2005	Blomquist
6,852,500	B1	2/2005	Hoss et al.
6,852,694	B2	2/2005	Van Antwerp et al.
6,853,854	B1	2/2005	Proniewicz et al.
6,856,928	B2	2/2005	Harmon
6,858,403	B2	2/2005	Han et al.
6,862,465	B2	3/2005	Shults et al.
6,862,466	B2	3/2005	Ackerman
6,872,200	B2	3/2005	Mann et al.
6,873,268	B2	3/2005	Lebel et al.
6,878,112	B2	4/2005	Linberg et al.
6,881,551	B2	4/2005	Heller et al.
6,882,940	B2	4/2005	Potts et al.
6,885,883	B2	4/2005	Parris et al.
6,889,331	B2	5/2005	Soerensen et al.
6,892,085	B2	5/2005	McIvor et al.
6,893,396	B2	5/2005	Schulze et al.
6,895,263	B2	5/2005	Shin et al.
6,895,265	B2	5/2005	Silver
6,899,683	B2	5/2005	Mault et al.
6,899,684	B2	5/2005	Mault et al.
6,902,207	B2	6/2005	Lickliter
6,902,905	B2	6/2005	Burson et al.
6,904,301	B2	6/2005	Raskas
6,907,127	B1	6/2005	Kravitz et al.
6,915,147	B2	7/2005	Lebel et al.
6,918,874	B1	7/2005	Hatch et al.
6,922,578	B2	7/2005	Eppstein et al.
RE38,775	E	8/2005	Kurnik et al.
6,923,764	B2	8/2005	Aceti et al.
6,923,936	B2	8/2005	Swanson et al.
6,926,670	B2	8/2005	Rich et al.
6,927,246	B2	8/2005	Noronha et al.
6,931,327	B2	8/2005	Goode, Jr. et al.
6,932,894	B2	8/2005	Mao et al.
6,936,006	B2	8/2005	Sabra
6,936,029	B2	8/2005	Mann et al.
6,937,222	B2	8/2005	Numao
6,940,403	B2	9/2005	Kail, IV
6,940,590	B2	9/2005	Colvin, Jr. et al.
6,941,163	B2	9/2005	Ford et al.
6,950,708	B2	9/2005	Bowman IV et al.
6,952,603	B2	10/2005	Gerber et al.
6,954,673	B2	10/2005	Von Arx et al.
6,955,650	B2	10/2005	Mault et al.
6,957,102	B2	10/2005	Silver et al.
6,957,107	B2	10/2005	Rogers et al.
6,958,705	B2	10/2005	Lebel et al.
6,968,294	B2	11/2005	Gutta et al.
6,968,375	B1	11/2005	Brown

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,971,274	B2	12/2005	Olin
6,974,437	B2	12/2005	Lebel et al.
6,978,182	B2	12/2005	Mazar et al.
6,979,326	B2	12/2005	Mann et al.
6,983,176	B2	1/2006	Gardner et al.
6,985,870	B2	1/2006	Martucci et al.
6,987,474	B2	1/2006	Freeman et al.
6,990,317	B2	1/2006	Arnold
6,990,366	B2	1/2006	Say et al.
6,991,096	B2	1/2006	Gottlieb et al.
6,997,907	B2	2/2006	Safabash et al.
6,997,920	B2	2/2006	Mann et al.
6,998,247	B2	2/2006	Monfre et al.
6,999,810	B2	2/2006	Berner et al.
7,003,336	B2	2/2006	Holker et al.
7,003,340	B2	2/2006	Say et al.
7,003,341	B2	2/2006	Say et al.
7,004,901	B2	2/2006	Fish
7,005,857	B2	2/2006	Stiene et al.
7,009,511	B2	3/2006	Mazar et al.
7,011,630	B2	3/2006	Desai et al.
7,018,366	B2	3/2006	Easter
7,018,568	B2	3/2006	Tierney
7,020,508	B2	3/2006	Stivoric et al.
7,022,072	B2	4/2006	Fox et al.
7,024,236	B2	4/2006	Ford et al.
7,024,245	B2	4/2006	Lebel et al.
7,025,743	B2	4/2006	Mann et al.
7,027,931	B1	4/2006	Jones et al.
7,029,444	B2	4/2006	Shin et al.
7,039,810	B1	5/2006	Nichols
7,041,068	B2	5/2006	Freeman et al.
7,041,468	B2	5/2006	Drucker et al.
7,043,305	B2	5/2006	KenKnight et al.
7,049,277	B2	5/2006	Bragulla et al.
7,052,251	B2	5/2006	Nason et al.
7,052,472	B1	5/2006	Miller et al.
7,052,483	B2	5/2006	Wojcik
7,056,302	B2	6/2006	Douglas
7,058,453	B2	6/2006	Nelson et al.
7,060,030	B2	6/2006	Von Arx et al.
7,060,031	B2	6/2006	Webb et al.
7,074,307	B2	7/2006	Simpson et al.
7,081,195	B2	7/2006	Simpson et al.
7,082,334	B2	7/2006	Boute et al.
7,089,780	B2	8/2006	Sunshine et al.
7,098,803	B2	8/2006	Mann et al.
7,108,778	B2	9/2006	Simpson et al.
7,110,803	B2	9/2006	Shults et al.
7,113,821	B1	9/2006	Sun et al.
7,114,502	B2	10/2006	Schulman et al.
7,124,027	B1	10/2006	Ernst et al.
7,125,382	B2	10/2006	Zhou et al.
7,133,710	B2	11/2006	Acosta et al.
7,134,999	B2	11/2006	Brauker et al.
7,136,689	B2	11/2006	Shults et al.
7,150,975	B2	12/2006	Tamada et al.
7,154,398	B2	12/2006	Chen et al.
7,155,112	B2	12/2006	Uno et al.
7,155,290	B2	12/2006	Von Arx et al.
7,163,511	B2	1/2007	Conn et al.
7,167,818	B2	1/2007	Brown
7,171,274	B2	1/2007	Starkweather et al.
7,183,068	B2	2/2007	Burson et al.
7,183,102	B2	2/2007	Monfre et al.
7,189,341	B2	3/2007	Li et al.
7,190,988	B2	3/2007	Say et al.
7,192,450	B2	3/2007	Brauker et al.
7,198,606	B2	4/2007	Boecker et al.
7,203,549	B2	4/2007	Schommer et al.
7,207,974	B2	4/2007	Safabash et al.
7,221,977	B1	5/2007	Weaver et al.
7,222,054	B2	5/2007	Geva
7,226,442	B2	6/2007	Sheppard et al.
7,226,978	B2	6/2007	Tapsak et al.
7,228,162	B2	6/2007	Ward et al.
7,228,163	B2	6/2007	Ackerman
7,228,182	B2	6/2007	Healy et al.
7,233,817	B2	6/2007	Yen
7,237,712	B2	7/2007	DeRocco et al.
7,241,266	B2	7/2007	Zhou et al.
7,258,665	B2	8/2007	Kohls et al.
7,261,691	B1	8/2007	Asomani
7,267,665	B2	9/2007	Steil et al.
7,276,029	B2	10/2007	Goode, Jr. et al.
7,278,983	B2	10/2007	Ireland et al.
7,286,894	B1	10/2007	Grant et al.
7,291,107	B2	11/2007	Hellwig et al.
7,295,867	B2	11/2007	Berner et al.
7,297,112	B2	11/2007	Zhou et al.
7,299,082	B2	11/2007	Feldman et al.
7,310,544	B2	12/2007	Brister et al.
7,318,816	B2	1/2008	Bobroff et al.
7,324,012	B2	1/2008	Mann et al.
7,324,850	B2	1/2008	Persen et al.
7,335,294	B2	2/2008	Heller et al.
7,347,819	B2	3/2008	Lebel et al.
7,354,420	B2	4/2008	Steil et al.
7,364,592	B2	4/2008	Carr-Brendel et al.
7,366,556	B2	4/2008	Brister et al.
7,379,765	B2	5/2008	Petisce et al.
7,384,397	B2	6/2008	Zhang et al.
7,387,010	B2	6/2008	Sunshine et al.
7,398,183	B2	7/2008	Holland et al.
7,399,277	B2	7/2008	Saidara et al.
7,402,153	B2	7/2008	Steil et al.
7,404,796	B2	7/2008	Ginsberg
7,408,132	B2	8/2008	Wambsganss et al.
7,419,573	B2	9/2008	Gundel
7,424,318	B2	9/2008	Brister et al.
7,460,898	B2	12/2008	Brister et al.
7,467,003	B2	12/2008	Brister et al.
7,471,972	B2	12/2008	Rhodes et al.
7,492,254	B2	2/2009	Bandy et al.
7,494,465	B2	2/2009	Brister et al.
7,497,827	B2	3/2009	Brister et al.
7,506,046	B2	3/2009	Rhodes
7,519,408	B2	4/2009	Rasdal et al.
7,547,281	B2	6/2009	Hayes et al.
7,565,197	B2	7/2009	Haubrich et al.
7,569,030	B2	8/2009	Lebel et al.
7,574,266	B2	8/2009	Dudding et al.
7,583,990	B2	9/2009	Goode, Jr. et al.
7,591,801	B2	9/2009	Brauker et al.
7,599,726	B2	10/2009	Goode, Jr. et al.
7,602,310	B2	10/2009	Mann et al.
7,604,178	B2	10/2009	Stewart
7,613,491	B2	11/2009	Boock et al.
7,615,007	B2	11/2009	Shults et al.
7,618,369	B2	11/2009	Hayter et al.
7,632,228	B2	12/2009	Brauker et al.
7,637,868	B2	12/2009	Saint et al.
7,640,048	B2	12/2009	Dobbles et al.
7,651,596	B2	1/2010	Petisce et al.
7,653,425	B2	1/2010	Hayter et al.
7,654,956	B2	2/2010	Brister et al.
7,657,297	B2	2/2010	Simpson et al.
7,659,823	B1	2/2010	Killian et al.
7,668,596	B2	2/2010	Von Arx et al.
7,699,775	B2	4/2010	Desai et al.
7,701,052	B2	4/2010	Borland et al.
7,711,402	B2	5/2010	Shults et al.
7,713,574	B2	5/2010	Brister et al.
7,715,893	B2	5/2010	Kamath et al.
7,741,734	B2	6/2010	Joannopoulos et al.
7,766,829	B2	8/2010	Sloan et al.
7,768,387	B2	8/2010	Fennell et al.
7,771,352	B2	8/2010	Shults et al.
7,774,145	B2	8/2010	Brauker et al.
7,778,680	B2	8/2010	Goode, Jr. et al.
7,779,332	B2	8/2010	Karr et al.
7,782,192	B2	8/2010	Jeckelmann et al.
7,783,333	B2	8/2010	Brister et al.
7,791,467	B2	9/2010	Mazar et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,792,562	B2	9/2010	Shults et al.
7,804,197	B2	9/2010	Iisaka et al.
7,811,231	B2	10/2010	Jin et al.
7,813,809	B2	10/2010	Strother et al.
7,826,382	B2	11/2010	Sicurello et al.
7,826,981	B2	11/2010	Goode, Jr. et al.
7,831,310	B2	11/2010	Lebel et al.
7,833,151	B2	11/2010	Khait et al.
7,860,574	B2	12/2010	Von Arx et al.
7,882,611	B2	2/2011	Shah et al.
7,889,069	B2	2/2011	Fifolt et al.
7,899,511	B2	3/2011	Shults et al.
7,905,833	B2	3/2011	Brister et al.
7,912,674	B2	3/2011	Killoren Clark et al.
7,914,450	B2	3/2011	Goode, Jr. et al.
7,916,013	B2	3/2011	Stevenson
7,948,369	B2	5/2011	Fennell et al.
7,955,258	B2	6/2011	Goscha et al.
7,970,448	B2	6/2011	Shults et al.
7,974,672	B2	7/2011	Shults et al.
7,978,063	B2	7/2011	Baldus et al.
7,999,674	B2	8/2011	Kamen
8,000,918	B2	8/2011	Fjield et al.
8,010,174	B2	8/2011	Goode et al.
8,010,256	B2	8/2011	Oowada
8,072,310	B1	12/2011	Everhart
8,090,445	B2	1/2012	Ginggen
8,093,991	B2	1/2012	Stevenson et al.
8,094,009	B2	1/2012	Allen et al.
8,098,159	B2	1/2012	Batra et al.
8,098,160	B2	1/2012	Howarth et al.
8,098,161	B2	1/2012	Lavedas
8,098,201	B2	1/2012	Choi et al.
8,098,208	B2	1/2012	Ficker et al.
8,102,021	B2	1/2012	Degani
8,102,154	B2	1/2012	Bishop et al.
8,102,263	B2	1/2012	Yeo et al.
8,102,789	B2	1/2012	Rosar et al.
8,103,241	B2	1/2012	Young et al.
8,103,325	B2	1/2012	Swedlow et al.
8,111,042	B2	2/2012	Bennett
8,115,488	B2	2/2012	McDowell
8,116,681	B2	2/2012	Baarman
8,116,683	B2	2/2012	Baarman
8,117,481	B2	2/2012	Anselmi et al.
8,120,493	B2	2/2012	Burr
8,123,686	B2	2/2012	Fennell et al.
8,124,452	B2	2/2012	Sheats
8,130,093	B2	3/2012	Mazar et al.
8,131,351	B2	3/2012	Kalgren et al.
8,131,365	B2	3/2012	Zhang et al.
8,131,565	B2	3/2012	Dicks et al.
8,132,037	B2	3/2012	Fehr et al.
8,135,352	B2	3/2012	Langsweirdt et al.
8,136,735	B2	3/2012	Arai et al.
8,138,925	B2	3/2012	Downie et al.
8,140,160	B2	3/2012	Pless et al.
8,140,168	B2	3/2012	Olson et al.
8,140,299	B2	3/2012	Siess
8,150,321	B2	4/2012	Winter et al.
8,150,516	B2	4/2012	Levine et al.
8,179,266	B2	5/2012	Hermle
8,233,456	B1	7/2012	Kopikare et al.
8,260,393	B2	9/2012	Kamath et al.
8,282,549	B2	10/2012	Brauker et al.
8,417,312	B2	4/2013	Kamath et al.
8,427,298	B2	4/2013	Fennell et al.
8,478,389	B1	7/2013	Brockway et al.
8,560,037	B2	10/2013	Goode, Jr. et al.
8,622,903	B2	1/2014	Jin et al.
8,638,411	B2	1/2014	Park et al.
8,698,615	B2	4/2014	Fennell et al.
8,849,459	B2	9/2014	Ramey et al.
8,937,540	B2	1/2015	Fennell
2001/0011224	A1	8/2001	Brown
2001/0011795	A1	8/2001	Ohtsuka et al.
2001/0016310	A1	8/2001	Brown et al.
2001/0016682	A1	8/2001	Berner et al.
2001/0016683	A1	8/2001	Darrow et al.
2001/0020124	A1	9/2001	Tamada
2001/0029340	A1	10/2001	Mault et al.
2001/0032278	A1	10/2001	Brown et al.
2001/0037060	A1	11/2001	Thompson et al.
2001/0037069	A1	11/2001	Carlson et al.
2001/0037366	A1	11/2001	Webb et al.
2001/0039504	A1	11/2001	Linberg et al.
2001/0041830	A1	11/2001	Varalli et al.
2001/0041831	A1	11/2001	Starkweather et al.
2001/0044581	A1	11/2001	Mault
2001/0044588	A1	11/2001	Mault
2001/0047125	A1	11/2001	Quy
2001/0047127	A1	11/2001	New et al.
2001/0049096	A1	12/2001	Brown
2001/0049470	A1	12/2001	Mault et al.
2002/0002326	A1	1/2002	Causey, III et al.
2002/0002328	A1	1/2002	Tamada
2002/0004640	A1	1/2002	Conn et al.
2002/0010414	A1	1/2002	Coston et al.
2002/0013522	A1	1/2002	Lav et al.
2002/0013538	A1	1/2002	Teller
2002/0016530	A1	2/2002	Brown
2002/0016719	A1	2/2002	Nemeth et al.
2002/0019022	A1	2/2002	Dunn et al.
2002/0019584	A1	2/2002	Schulze et al.
2002/0019586	A1	2/2002	Teller et al.
2002/0019748	A1	2/2002	Brown
2002/0023852	A1	2/2002	McIvor et al.
2002/0026937	A1	3/2002	Mault
2002/0027164	A1	3/2002	Mault et al.
2002/0028995	A1	3/2002	Mault
2002/0040208	A1	4/2002	Flaherty et al.
2002/0042090	A1	4/2002	Heller et al.
2002/0045808	A1	4/2002	Ford et al.
2002/0046300	A1	4/2002	Hanko et al.
2002/0047867	A1	4/2002	Mault et al.
2002/0049482	A1	4/2002	Fabian et al.
2002/0053637	A1	5/2002	Conn et al.
2002/0062069	A1	5/2002	Mault
2002/0063060	A1	5/2002	Gascoyne et al.
2002/0065454	A1	5/2002	Lebel et al.
2002/0068858	A1	6/2002	Braig et al.
2002/0072784	A1	6/2002	Sheppard et al.
2002/0072858	A1	6/2002	Cheng
2002/0074162	A1	6/2002	Su et al.
2002/0077765	A1	6/2002	Mault
2002/0077766	A1	6/2002	Mault
2002/0081559	A1	6/2002	Brown et al.
2002/0083461	A1	6/2002	Hutcheson et al.
2002/0084196	A1	7/2002	Liamos et al.
2002/0087056	A1	7/2002	Aceti et al.
2002/0091312	A1	7/2002	Berner et al.
2002/0091796	A1	7/2002	Higginson et al.
2002/0093969	A1	7/2002	Lin et al.
2002/0103425	A1	8/2002	Mault
2002/0103499	A1	8/2002	Perez et al.
2002/0106709	A1	8/2002	Potts et al.
2002/0107433	A1	8/2002	Mault
2002/0107476	A1	8/2002	Mann et al.
2002/0109600	A1	8/2002	Mault et al.
2002/0109621	A1	8/2002	Khair et al.
2002/0117639	A1	8/2002	Paolini et al.
2002/0118528	A1	8/2002	Su et al.
2002/0119711	A1	8/2002	Van Antwerp et al.
2002/0124017	A1	9/2002	Mault
2002/0126036	A1	9/2002	Flaherty et al.
2002/0128594	A1	9/2002	Das et al.
2002/0130042	A1	9/2002	Moerman et al.
2002/0133378	A1	9/2002	Mault et al.
2002/0147135	A1	10/2002	Schnell
2002/0161286	A1	10/2002	Gerber et al.
2002/0161288	A1	10/2002	Shin et al.
2002/0169394	A1	11/2002	Eppstein et al.
2002/0169635	A1	11/2002	Shillingburg
2002/0177764	A1	11/2002	Sohrab

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0185130	A1	12/2002	Wright et al.
2002/0193679	A1	12/2002	Malave et al.
2003/0004403	A1	1/2003	Drinan et al.
2003/0009203	A1	1/2003	Lebel et al.
2003/0023182	A1	1/2003	Mault et al.
2003/0023317	A1	1/2003	Brauker et al.
2003/0028089	A1	2/2003	Galley et al.
2003/0028120	A1	2/2003	Mault et al.
2003/0032077	A1	2/2003	Itoh et al.
2003/0032867	A1	2/2003	Crothall et al.
2003/0032868	A1	2/2003	Graskov et al.
2003/0032874	A1	2/2003	Rhodes et al.
2003/0040683	A1	2/2003	Rule et al.
2003/0042137	A1	3/2003	Mao et al.
2003/0050537	A1	3/2003	Wessel
2003/0050546	A1	3/2003	Desai et al.
2003/0060689	A1	3/2003	Kohls et al.
2003/0060692	A1	3/2003	Ruchti et al.
2003/0060753	A1	3/2003	Starkweather et al.
2003/0065257	A1	4/2003	Mault et al.
2003/0065273	A1	4/2003	Mault et al.
2003/0065274	A1	4/2003	Mault et al.
2003/0065275	A1	4/2003	Mault et al.
2003/0065308	A1	4/2003	Lebel et al.
2003/0076792	A1	4/2003	Theimer
2003/0081370	A1	5/2003	Haskell et al.
2003/0100040	A1	5/2003	Bonnecaze et al.
2003/0100821	A1	5/2003	Heller et al.
2003/0105407	A1	6/2003	Pearce et al.
2003/0108976	A1	6/2003	Braig et al.
2003/0114897	A1	6/2003	Von Arx et al.
2003/0119457	A1	6/2003	Standke
2003/0122021	A1	7/2003	McConnell et al.
2003/0125612	A1	7/2003	Fox et al.
2003/0130616	A1	7/2003	Steil et al.
2003/0134347	A1	7/2003	Heller et al.
2003/0135100	A1	7/2003	Kim et al.
2003/0135333	A1	7/2003	Aceti et al.
2003/0144579	A1	7/2003	Buss
2003/0146841	A1	8/2003	Koenig
2003/0153820	A1	8/2003	Berner et al.
2003/0153821	A1	8/2003	Berner et al.
2003/0158472	A1	8/2003	Sohrab
2003/0158707	A1	8/2003	Doi
2003/0168338	A1	9/2003	Gao et al.
2003/0175806	A1	9/2003	Rule et al.
2003/0175992	A1	9/2003	Toranto et al.
2003/0176183	A1	9/2003	Drucker et al.
2003/0176933	A1	9/2003	Lebel et al.
2003/0181851	A1	9/2003	Mann et al.
2003/0181852	A1	9/2003	Mann et al.
2003/0187338	A1	10/2003	Say et al.
2003/0187525	A1	10/2003	Mann et al.
2003/0191376	A1	10/2003	Samuels et al.
2003/0191431	A1	10/2003	Mann et al.
2003/0195403	A1	10/2003	Berner et al.
2003/0195462	A1	10/2003	Mann et al.
2003/0199790	A1	10/2003	Boecker et al.
2003/0199791	A1	10/2003	Boecker et al.
2003/0199903	A1	10/2003	Boecker et al.
2003/0203498	A1	10/2003	Neel et al.
2003/0204290	A1	10/2003	Sadler et al.
2003/0208110	A1	11/2003	Mault et al.
2003/0208113	A1	11/2003	Mault et al.
2003/0208114	A1	11/2003	Ackerman
2003/0208133	A1	11/2003	Mault
2003/0208409	A1	11/2003	Mault
2003/0212317	A1	11/2003	Kovatchev et al.
2003/0212364	A1	11/2003	Mann et al.
2003/0212379	A1	11/2003	Bylund et al.
2003/0212579	A1	11/2003	Brown et al.
2003/0216630	A1	11/2003	Jersey-Willuhn et al.
2003/0217966	A1	11/2003	Tapsak et al.
2003/0226695	A1	12/2003	Mault
2003/0229514	A2	12/2003	Brown
2003/0232370	A1	12/2003	Trifiro
2003/0235817	A1	12/2003	Bartkowiak et al.
2004/0010207	A1	1/2004	Flaherty et al.
2004/0011671	A1	1/2004	Shults et al.
2004/0017300	A1	1/2004	Kotzin et al.
2004/0018486	A1	1/2004	Dunn et al.
2004/0030226	A1	2/2004	Quy
2004/0030531	A1	2/2004	Miller et al.
2004/0030581	A1	2/2004	Levin et al.
2004/0039255	A1	2/2004	Simonsen et al.
2004/0039256	A1	2/2004	Kawatahara et al.
2004/0039298	A1	2/2004	Abreu et al.
2004/0040840	A1	3/2004	Mao et al.
2004/0045879	A1	3/2004	Shults et al.
2004/0054263	A1	3/2004	Moerman et al.
2004/0059201	A1	3/2004	Ginsberg
2004/0063435	A1	4/2004	Sakamoto et al.
2004/0064068	A1	4/2004	DeNuzzio et al.
2004/0069164	A1	4/2004	Nakamura et al.
2004/0072357	A1	4/2004	Stiene et al.
2004/0073095	A1	4/2004	Causey, III et al.
2004/0096959	A1	5/2004	Stiene et al.
2004/0100376	A1	5/2004	Lye et al.
2004/0105411	A1	6/2004	Boatwright et al.
2004/0106858	A1	6/2004	Say et al.
2004/0106859	A1	6/2004	Say et al.
2004/0108226	A1	6/2004	Polychronakos et al.
2004/0116786	A1	6/2004	Iijima et al.
2004/0122353	A1	6/2004	Shahmirian et al.
2004/0122489	A1	6/2004	Mazar et al.
2004/0122530	A1	6/2004	Hansen et al.
2004/0133164	A1	7/2004	Funderburk et al.
2004/0133390	A1	7/2004	Osorio et al.
2004/0136377	A1	7/2004	Miyazaki et al.
2004/0138588	A1	7/2004	Saikley et al.
2004/0146909	A1	7/2004	Duong et al.
2004/0147872	A1	7/2004	Thompson
2004/0152622	A1	8/2004	Keith et al.
2004/0152961	A1	8/2004	Carlson et al.
2004/0153585	A1	8/2004	Kawatahara et al.
2004/0162473	A1	8/2004	Sohrab
2004/0164961	A1	8/2004	Bal et al.
2004/0167383	A1	8/2004	Kim et al.
2004/0167464	A1	8/2004	Ireland et al.
2004/0167801	A1	8/2004	Say et al.
2004/0171921	A1	9/2004	Say et al.
2004/0172284	A1	9/2004	Sullivan et al.
2004/0176672	A1	9/2004	Silver et al.
2004/0176913	A1	9/2004	Kawatahara et al.
2004/0186362	A1	9/2004	Brauker et al.
2004/0186365	A1	9/2004	Jin et al.
2004/0193020	A1	9/2004	Chiba et al.
2004/0193025	A1	9/2004	Steil et al.
2004/0193090	A1	9/2004	Lebel et al.
2004/0197846	A1	10/2004	Hockersmith et al.
2004/0199056	A1	10/2004	Husemann et al.
2004/0199059	A1	10/2004	Brauker et al.
2004/0202576	A1	10/2004	Aceti et al.
2004/0204687	A1	10/2004	Mogensen et al.
2004/0204868	A1	10/2004	Maynard et al.
2004/0206916	A1	10/2004	Colvin, Jr. et al.
2004/0208780	A1	10/2004	Faries, Jr. et al.
2004/0212536	A1	10/2004	Mori et al.
2004/0221057	A1	11/2004	Darcey et al.
2004/0225199	A1	11/2004	Evanyk et al.
2004/0225338	A1	11/2004	Lebel et al.
2004/0235446	A1	11/2004	Flaherty et al.
2004/0236200	A1	11/2004	Say et al.
2004/0248204	A1	12/2004	Moerman
2004/0249250	A1	12/2004	McGee et al.
2004/0249253	A1	12/2004	Racchini et al.
2004/0249254	A1	12/2004	Racchini et al.
2004/0249999	A1	12/2004	Connolly et al.
2004/0253736	A1	12/2004	Stout et al.
2004/0254429	A1	12/2004	Yang
2004/0254433	A1	12/2004	Bandis et al.
2004/0254434	A1	12/2004	Goodnow et al.
2004/0260363	A1	12/2004	Arx et al.
2004/0260478	A1	12/2004	Schwamm

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0263354 A1 12/2004 Mann et al.
2004/0267300 A1 12/2004 Mace
2005/0001024 A1 1/2005 Kusaka et al.
2005/0003470 A1 1/2005 Nelson et al.
2005/0004439 A1 1/2005 Shin et al.
2005/0004494 A1 1/2005 Perez et al.
2005/0010087 A1 1/2005 Banet et al.
2005/0010269 A1 1/2005 Lebel et al.
2005/0016276 A1 1/2005 Guan et al.
2005/0017864 A1 1/2005 Tsoukalis
2005/0027177 A1 2/2005 Shin et al.
2005/0027179 A1 2/2005 Berner et al.
2005/0027180 A1 2/2005 Goode, Jr. et al.
2005/0027181 A1 2/2005 Goode, Jr. et al.
2005/0027462 A1 2/2005 Goode, Jr. et al.
2005/0027463 A1 2/2005 Goode, Jr. et al.
2005/0031689 A1 2/2005 Shults et al.
2005/0033132 A1 2/2005 Shults et al.
2005/0038332 A1 2/2005 Saidara et al.
2005/0038680 A1 2/2005 McMahon
2005/0043598 A1 2/2005 Goode, Jr. et al.
2005/0043894 A1 2/2005 Fernandez
2005/0049179 A1 3/2005 Davidson et al.
2005/0049473 A1 3/2005 Desai et al.
2005/0054909 A1 3/2005 Petisce et al.
2005/0059372 A1 3/2005 Arayashiki et al.
2005/0065464 A1 3/2005 Talbot et al.
2005/0070777 A1 3/2005 Cho et al.
2005/0090607 A1 4/2005 Tapsak et al.
2005/0096511 A1 5/2005 Fox et al.
2005/0096512 A1 5/2005 Fox et al.
2005/0096516 A1 5/2005 Soykan et al.
2005/0112169 A1 5/2005 Brauker et al.
2005/0112544 A1 5/2005 Xu et al.
2005/0113648 A1 5/2005 Yang et al.
2005/0113653 A1 5/2005 Fox et al.
2005/0113657 A1 5/2005 Alarcon et al.
2005/0113658 A1 5/2005 Jacobson et al.
2005/0113886 A1 5/2005 Fischell et al.
2005/0114068 A1 5/2005 Chey et al.
2005/0116683 A1 6/2005 Cheng et al.
2005/0118726 A1 6/2005 Schultz et al.
2005/0121322 A1 6/2005 Say et al.
2005/0124873 A1 6/2005 Shults et al.
2005/0131346 A1 6/2005 Douglas
2005/0137471 A1 6/2005 Haar et al.
2005/0137530 A1 6/2005 Campbell et al.
2005/0143635 A1 6/2005 Kamath et al.
2005/0143636 A1 6/2005 Zhang et al.
2005/0148003 A1 7/2005 Kieth et al.
2005/0154271 A1 7/2005 Rasdal et al.
2005/0161346 A1 7/2005 Simpson et al.
2005/0171503 A1 8/2005 Van Den Berghe et al.
2005/0171513 A1 8/2005 Mann et al.
2005/0173245 A1 8/2005 Feldman et al.
2005/0176136 A1 8/2005 Burd et al.
2005/0177036 A1 8/2005 Shults et al.
2005/0177398 A1 8/2005 Watanabe et al.
2005/0181012 A1 8/2005 Saint et al.
2005/0182306 A1 8/2005 Sloan
2005/0182358 A1 8/2005 Veit et al.
2005/0182451 A1 8/2005 Griffin et al.
2005/0187720 A1 8/2005 Goode, Jr. et al.
2005/0192494 A1 9/2005 Ginsberg
2005/0192557 A1 9/2005 Brauker et al.
2005/0195930 A1 9/2005 Spital et al.
2005/0199494 A1 9/2005 Say et al.
2005/0203360 A1 9/2005 Brauker et al.
2005/0203707 A1 9/2005 Tsutsui et al.
2005/0204134 A1 9/2005 Von Arx et al.
2005/0214892 A1 9/2005 Kovatchev et al.
2005/0215871 A1 9/2005 Feldman et al.
2005/0215872 A1 9/2005 Berner et al.
2005/0221504 A1 10/2005 Petruno et al.
2005/0239154 A1 10/2005 Feldman et al.
2005/0239156 A1 10/2005 Drucker et al.
2005/0241957 A1 11/2005 Mao et al.
2005/0242479 A1 11/2005 Petisce et al.
2005/0245795 A1 11/2005 Goode, Jr. et al.
2005/0245799 A1 11/2005 Brauker et al.
2005/0245839 A1 11/2005 Stivoric et al.
2005/0245904 A1 11/2005 Estes et al.
2005/0251033 A1 11/2005 Scarantino et al.
2005/0251083 A1 11/2005 Carr-Brendel et al.
2005/0261660 A1 11/2005 Choi
2005/0267780 A1 12/2005 Ray et al.
2005/0271546 A1 12/2005 Gerber et al.
2005/0271547 A1 12/2005 Gerber et al.
2005/0272640 A1 12/2005 Doyle, III et al.
2005/0272985 A1 12/2005 Kotulla et al.
2005/0277164 A1 12/2005 Drucker et al.
2005/0277912 A1 12/2005 John
2005/0287620 A1 12/2005 Heller et al.
2006/0001538 A1 1/2006 Kraft et al.
2006/0001550 A1 1/2006 Mann et al.
2006/0001551 A1 1/2006 Kraft et al.
2006/0003398 A1 1/2006 Heller et al.
2006/0004270 A1 1/2006 Bedard et al.
2006/0004271 A1 1/2006 Peyser et al.
2006/0007017 A1 1/2006 Mann et al.
2006/0015020 A1 1/2006 Neale et al.
2006/0015024 A1 1/2006 Brister et al.
2006/0016700 A1 1/2006 Brister et al.
2006/0019327 A1 1/2006 Brister et al.
2006/0020186 A1 1/2006 Brister et al.
2006/0020187 A1 1/2006 Brister et al.
2006/0020188 A1 1/2006 Kamath et al.
2006/0020189 A1 1/2006 Brister et al.
2006/0020190 A1 1/2006 Kamath et al.
2006/0020191 A1 1/2006 Brister et al.
2006/0020192 A1 1/2006 Brister et al.
2006/0020300 A1 1/2006 Nghiem et al.
2006/0025663 A1 2/2006 Talbot et al.
2006/0029177 A1 2/2006 Cranford, Jr. et al.
2006/0031094 A1 2/2006 Cohen et al.
2006/0036139 A1 2/2006 Brister et al.
2006/0036140 A1 2/2006 Brister et al.
2006/0036141 A1 2/2006 Kamath et al.
2006/0036142 A1 2/2006 Brister et al.
2006/0036143 A1 2/2006 Brister et al.
2006/0036144 A1 2/2006 Brister et al.
2006/0036145 A1 2/2006 Brister et al.
2006/0036187 A1 2/2006 Vos et al.
2006/0040402 A1 2/2006 Brauker et al.
2006/0052679 A1 3/2006 Kotulla et al.
2006/0058588 A1 3/2006 Zdeblick
2006/0058602 A1 3/2006 Kwiatkowski et al.
2006/0063218 A1 3/2006 Bartkowiak et al.
2006/0074564 A1 4/2006 Bartkowiak et al.
2006/0129733 A1 6/2006 Solbelman
2006/0142651 A1 6/2006 Brister et al.
2006/0154642 A1 7/2006 Scannell
2006/0155180 A1 7/2006 Brister et al.
2006/0166629 A1 7/2006 Reggiardo
2006/0173260 A1 8/2006 Gaoni et al.
2006/0173406 A1 8/2006 Hayes et al.
2006/0173444 A1 8/2006 Choy et al.
2006/0183984 A1 8/2006 Dobbles et al.
2006/0183985 A1 8/2006 Brister et al.
2006/0189863 A1 8/2006 Peyser et al.
2006/0193375 A1 8/2006 Lee et al.
2006/0195029 A1 8/2006 Shults et al.
2006/0200112 A1 9/2006 Paul
2006/0202805 A1 9/2006 Schulman et al.
2006/0202859 A1 9/2006 Mastrototaro et al.
2006/0222566 A1 10/2006 Brauker et al.
2006/0224109 A1 10/2006 Steil et al.
2006/0224141 A1 10/2006 Rush et al.
2006/0226985 A1 10/2006 Goodnow et al.
2006/0229512 A1 10/2006 Petisce et al.
2006/0247508 A1 11/2006 Fennell
2006/0247710 A1 11/2006 Goetz et al.
2006/0247985 A1 11/2006 Liamos et al.
2006/0253296 A1 11/2006 Liisberg et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0258918 A1 11/2006 Burd et al.
2006/0258929 A1 11/2006 Goode, Jr. et al.
2006/0263763 A1 11/2006 Simpson et al.
2006/0264785 A1 11/2006 Dring et al.
2006/0264888 A1 11/2006 Moberg et al.
2006/0270922 A1 11/2006 Brauker et al.
2006/0272652 A1 12/2006 Stocker et al.
2006/0287691 A1 12/2006 Drew
2006/0290496 A1 12/2006 Peeters et al.
2006/0293607 A1 12/2006 Alt et al.
2007/0016381 A1 1/2007 Kamath et al.
2007/0017983 A1 1/2007 Frank et al.
2007/0026440 A1 2/2007 Broderick et al.
2007/0027381 A1 2/2007 Stafford
2007/0027507 A1 2/2007 Burdett et al.
2007/0032706 A1 2/2007 Kamath et al.
2007/0033074 A1 2/2007 Nitzan et al.
2007/0038044 A1 2/2007 Dobbles et al.
2007/0053341 A1 3/2007 Lizzi
2007/0055799 A1 3/2007 Koehler et al.
2007/0060814 A1 3/2007 Stafford
2007/0060869 A1 3/2007 Tolle et al.
2007/0066873 A1 3/2007 Kamath et al.
2007/0066877 A1 3/2007 Arnold et al.
2007/0071681 A1 3/2007 Gadkar et al.
2007/0073129 A1 3/2007 Shah et al.
2007/0078320 A1 4/2007 Stafford
2007/0078321 A1 4/2007 Mazza et al.
2007/0078322 A1 4/2007 Stafford
2007/0078323 A1 4/2007 Reggiardo et al.
2007/0090511 A1 4/2007 Borland et al.
2007/0093786 A1 4/2007 Goldsmith et al.
2007/0100222 A1 5/2007 Mastrototaro et al.
2007/0106135 A1 5/2007 Sloan et al.
2007/0124002 A1 5/2007 Estes et al.
2007/0135697 A1 6/2007 Reggiardo
2007/0149873 A1 6/2007 Say et al.
2007/0149874 A1 6/2007 Say et al.
2007/0149875 A1 6/2007 Ouyang et al.
2007/0151869 A1 7/2007 Heller et al.
2007/0156033 A1 7/2007 Causey, III et al.
2007/0161879 A1 7/2007 Say et al.
2007/0161880 A1 7/2007 Say et al.
2007/0163880 A1 7/2007 Woo et al.
2007/0168224 A1 7/2007 Letzt et al.
2007/0173706 A1 7/2007 Neinast et al.
2007/0173712 A1 7/2007 Shah et al.
2007/0173761 A1 7/2007 Kanderian et al.
2007/0179349 A1 8/2007 Hoyme et al.
2007/0179352 A1 8/2007 Randlov et al.
2007/0179370 A1 8/2007 Say et al.
2007/0179372 A1 8/2007 Say et al.
2007/0191699 A1 8/2007 Say et al.
2007/0191700 A1 8/2007 Say et al.
2007/0191701 A1 8/2007 Feldman et al.
2007/0191702 A1 8/2007 Yodfat et al.
2007/0203407 A1 8/2007 Hoss et al.
2007/0203408 A1 8/2007 Say et al.
2007/0203410 A1 8/2007 Say et al.
2007/0203411 A1 8/2007 Say et al.
2007/0203966 A1 8/2007 Brauker et al.
2007/0208245 A1 9/2007 Brauker et al.
2007/0208247 A1 9/2007 Say et al.
2007/0213610 A1 9/2007 Say et al.
2007/0213657 A1 9/2007 Jennewine et al.
2007/0215491 A1 9/2007 Heller et al.
2007/0218097 A1 9/2007 Heller et al.
2007/0219496 A1 9/2007 Kamen et al.
2007/0222609 A1 9/2007 Duron et al.
2007/0232877 A1 10/2007 He
2007/0232880 A1 10/2007 Siddiqui et al.
2007/0235331 A1 10/2007 Simpson et al.
2007/0244380 A1 10/2007 Say et al.
2007/0244383 A1 10/2007 Talbot et al.
2007/0249919 A1 10/2007 Say et al.
2007/0249920 A1 10/2007 Say et al.
2007/0249922 A1 10/2007 Peyser et al.
2007/0253021 A1 11/2007 Mehta et al.
2007/0255321 A1 11/2007 Gerber et al.
2007/0255348 A1 11/2007 Holtzclaw
2007/0255531 A1 11/2007 Drew
2007/0258395 A1 11/2007 Jollota et al.
2007/0270672 A1 11/2007 Hayter
2007/0271285 A1 11/2007 Eichorn et al.
2007/0282299 A1 12/2007 Hellwig
2007/0285238 A1 12/2007 Batra
2007/0299617 A1 12/2007 Willis
2008/0004515 A1 1/2008 Jennewine et al.
2008/0004601 A1 1/2008 Jennewine et al.
2008/0009304 A1 1/2008 Fry
2008/0009692 A1 1/2008 Stafford
2008/0017522 A1 1/2008 Heller et al.
2008/0018433 A1 1/2008 Pitt-Pladdy
2008/0021666 A1 1/2008 Goode, Jr. et al.
2008/0027586 A1 1/2008 Hern et al.
2008/0029391 A1 2/2008 Mao et al.
2008/0030369 A1 2/2008 Mann et al.
2008/0033254 A1 2/2008 Kamath et al.
2008/0039702 A1 2/2008 Hayter et al.
2008/0045824 A1 2/2008 Tapsak et al.
2008/0055070 A1 3/2008 Bange et al.
2008/0058625 A1 3/2008 McGarraugh et al.
2008/0060955 A1 3/2008 Goodnow
2008/0062055 A1 3/2008 Cunningham et al.
2008/0064937 A1 3/2008 McGarraugh et al.
2008/0064943 A1 3/2008 Talbot et al.
2008/0067627 A1 3/2008 Boeck et al.
2008/0071156 A1 3/2008 Brister et al.
2008/0071157 A1 3/2008 McGarraugh et al.
2008/0071158 A1 3/2008 McGarraugh et al.
2008/0071328 A1 3/2008 Haubrich et al.
2008/0081977 A1 4/2008 Hayter et al.
2008/0083617 A1 4/2008 Simpson et al.
2008/0086042 A1 4/2008 Brister et al.
2008/0086044 A1 4/2008 Brister et al.
2008/0086273 A1 4/2008 Shults et al.
2008/0092638 A1 4/2008 Brenneman et al.
2008/0097289 A1 4/2008 Steil et al.
2008/0108942 A1 5/2008 Brister et al.
2008/0119705 A1 5/2008 Patel et al.
2008/0139910 A1 6/2008 Mastrototaro et al.
2008/0154513 A1 6/2008 Kovatchev et al.
2008/0161666 A1 7/2008 Feldman et al.
2008/0167543 A1 7/2008 Say et al.
2008/0167572 A1 7/2008 Stivoric et al.
2008/0172205 A1 7/2008 Breton et al.
2008/0179187 A1 7/2008 Ouyang et al.
2008/0183060 A1 7/2008 Steil et al.
2008/0183061 A1 7/2008 Goode et al.
2008/0183399 A1 7/2008 Goode et al.
2008/0188731 A1 8/2008 Brister et al.
2008/0188796 A1 8/2008 Steil et al.
2008/0189051 A1 8/2008 Goode et al.
2008/0194934 A1 8/2008 Ray et al.
2008/0194935 A1 8/2008 Brister et al.
2008/0194936 A1 8/2008 Goode et al.
2008/0194937 A1 8/2008 Goode et al.
2008/0194938 A1 8/2008 Brister et al.
2008/0195232 A1 8/2008 Carr-Brendel et al.
2008/0195967 A1 8/2008 Goode et al.
2008/0197024 A1 8/2008 Simpson et al.
2008/0200788 A1 8/2008 Brister et al.
2008/0200789 A1 8/2008 Brister et al.
2008/0200791 A1 8/2008 Simpson et al.
2008/0208025 A1 8/2008 Shults et al.
2008/0208113 A1 8/2008 Damiano et al.
2008/0212600 A1 9/2008 Yoo
2008/0214900 A1 9/2008 Fennell et al.
2008/0214915 A1 9/2008 Brister et al.
2008/0214918 A1 9/2008 Brister et al.
2008/0228051 A1 9/2008 Shults et al.
2008/0228054 A1 9/2008 Shults et al.
2008/0234943 A1 9/2008 Ray et al.
2008/0235469 A1 9/2008 Drew

(56) **References Cited**

U.S. PATENT DOCUMENTS

2008/0242961 A1 10/2008 Brister et al.
2008/0254544 A1 10/2008 Modzelewski et al.
2008/0255434 A1 10/2008 Hayter et al.
2008/0255437 A1 10/2008 Hayter
2008/0255438 A1 10/2008 Saidara et al.
2008/0255808 A1 10/2008 Hayter
2008/0256048 A1 10/2008 Hayter
2008/0262469 A1 10/2008 Brister et al.
2008/0267823 A1 10/2008 Wang et al.
2008/0275313 A1 11/2008 Brister et al.
2008/0278333 A1 11/2008 Fennell et al.
2008/0287761 A1 11/2008 Hayter
2008/0287762 A1 11/2008 Hayter
2008/0287763 A1 11/2008 Hayter
2008/0287764 A1 11/2008 Rasdal et al.
2008/0287765 A1 11/2008 Rasdal et al.
2008/0287766 A1 11/2008 Rasdal et al.
2008/0288180 A1 11/2008 Hayter
2008/0288204 A1 11/2008 Hayter et al.
2008/0294024 A1 11/2008 Cosentino et al.
2008/0296155 A1 12/2008 Shults et al.
2008/0300919 A1 12/2008 Charlton et al.
2008/0300920 A1 12/2008 Brown et al.
2008/0301158 A1 12/2008 Brown et al.
2008/0301436 A1 12/2008 Yao et al.
2008/0301665 A1 12/2008 Charlton et al.
2008/0306368 A1 12/2008 Goode et al.
2008/0306434 A1 12/2008 Dobbles et al.
2008/0306435 A1 12/2008 Kamath et al.
2008/0306444 A1 12/2008 Brister et al.
2008/0312518 A1 12/2008 Jina et al.
2008/0312841 A1 12/2008 Hayter
2008/0312842 A1 12/2008 Hayter
2008/0312844 A1 12/2008 Hayter et al.
2008/0312845 A1 12/2008 Hayter et al.
2008/0320587 A1 12/2008 Vauclair et al.
2009/0005665 A1 1/2009 Hayter et al.
2009/0005666 A1 1/2009 Shin et al.
2009/0006034 A1 1/2009 Hayter et al.
2009/0006133 A1 1/2009 Weinert et al.
2009/0012379 A1 1/2009 Goode et al.
2009/0018424 A1 1/2009 Kamath et al.
2009/0030294 A1 1/2009 Petisce et al.
2009/0033482 A1 2/2009 Hayter et al.
2009/0036747 A1 2/2009 Hayter et al.
2009/0036758 A1 2/2009 Brauker et al.
2009/0036760 A1 2/2009 Hayter
2009/0036763 A1 2/2009 Brauker et al.
2009/0040022 A1 2/2009 Finkenzeller
2009/0043181 A1 2/2009 Brauker et al.
2009/0043182 A1 2/2009 Brauker et al.
2009/0043525 A1 2/2009 Brauker et al.
2009/0043541 A1 2/2009 Brauker et al.
2009/0043542 A1 2/2009 Brauker et al.
2009/0045055 A1 2/2009 Rhodes et al.
2009/0048503 A1 2/2009 Dalal et al.
2009/0054747 A1 2/2009 Fennell
2009/0055149 A1 2/2009 Hayter et al.
2009/0062633 A1 3/2009 Brauker et al.
2009/0062635 A1 3/2009 Brauker et al.
2009/0062767 A1 3/2009 VanAntwerp et al.
2009/0063402 A1 3/2009 Hayter
2009/0076356 A1 3/2009 Simpson et al.
2009/0076359 A1 3/2009 Peyser et al.
2009/0076360 A1 3/2009 Brister et al.
2009/0076361 A1 3/2009 Kamath et al.
2009/0085768 A1 4/2009 Patel et al.
2009/0085873 A1 4/2009 Betts et al.
2009/0093687 A1 4/2009 Telfort et al.
2009/0094680 A1 4/2009 Gupta et al.
2009/0099436 A1 4/2009 Brister et al.
2009/0105554 A1 4/2009 Stahmann et al.
2009/0105560 A1 4/2009 Solomon
2009/0105570 A1 4/2009 Sloan et al.
2009/0105571 A1 4/2009 Fennell et al.
2009/0105636 A1 4/2009 Hayter et al.
2009/0112478 A1 4/2009 Mueller, Jr. et al.
2009/0124877 A1 5/2009 Goode et al.
2009/0124878 A1 5/2009 Goode et al.
2009/0124879 A1 5/2009 Brister et al.
2009/0124964 A1 5/2009 Leach et al.
2009/0131768 A1 5/2009 Simpson et al.
2009/0131769 A1 5/2009 Leach et al.
2009/0131776 A1 5/2009 Simpson et al.
2009/0131777 A1 5/2009 Simpson et al.
2009/0137886 A1 5/2009 Shariati et al.
2009/0137887 A1 5/2009 Shariati et al.
2009/0143659 A1 6/2009 Li et al.
2009/0143660 A1 6/2009 Brister et al.
2009/0146826 A1 6/2009 Gofman et al.
2009/0149717 A1 6/2009 Brauer et al.
2009/0150186 A1 6/2009 Cohen et al.
2009/0156919 A1 6/2009 Brister et al.
2009/0156924 A1 6/2009 Shariati et al.
2009/0163790 A1 6/2009 Brister et al.
2009/0163791 A1 6/2009 Brister et al.
2009/0164190 A1 6/2009 Hayter
2009/0164239 A1 6/2009 Hayter et al.
2009/0164251 A1 6/2009 Hayter
2009/0178459 A1 7/2009 Li et al.
2009/0182217 A1 7/2009 Li et al.
2009/0189738 A1 7/2009 Hermle
2009/0192366 A1 7/2009 Mensinger et al.
2009/0192380 A1 7/2009 Shariati et al.
2009/0192722 A1 7/2009 Shariati et al.
2009/0192724 A1 7/2009 Brauker et al.
2009/0192745 A1 7/2009 Kamath et al.
2009/0192751 A1 7/2009 Kamath et al.
2009/0198118 A1 8/2009 Hayter et al.
2009/0203981 A1 8/2009 Brauker et al.
2009/0204340 A1 8/2009 Feldman et al.
2009/0204341 A1 8/2009 Brauker et al.
2009/0216100 A1 8/2009 Ebner et al.
2009/0216103 A1 8/2009 Brister et al.
2009/0234200 A1 9/2009 Husheer
2009/0237216 A1 9/2009 Twitchell, Jr.
2009/0240120 A1 9/2009 Mensinger et al.
2009/0240128 A1 9/2009 Mensinger et al.
2009/0240193 A1 9/2009 Mensinger et al.
2009/0242399 A1 10/2009 Kamath et al.
2009/0242425 A1 10/2009 Kamath et al.
2009/0247855 A1 10/2009 Boock et al.
2009/0247856 A1 10/2009 Boock et al.
2009/0247931 A1 10/2009 Damgaard-Sorensen
2009/0253973 A1 10/2009 Bashan et al.
2009/0267765 A1 10/2009 Greene et al.
2009/0287073 A1 11/2009 Boock et al.
2009/0287074 A1 11/2009 Shults et al.
2009/0289796 A1 11/2009 Blumberg
2009/0296742 A1 12/2009 Sicurello et al.
2009/0298182 A1 12/2009 Schulat et al.
2009/0299155 A1 12/2009 Yang et al.
2009/0299156 A1 12/2009 Simpson et al.
2009/0299162 A1 12/2009 Brauker et al.
2009/0299276 A1 12/2009 Brauker et al.
2010/0010324 A1 1/2010 Brauker et al.
2010/0010329 A1 1/2010 Taub et al.
2010/0010331 A1 1/2010 Brauker et al.
2010/0010332 A1 1/2010 Brauker et al.
2010/0016687 A1 1/2010 Brauker et al.
2010/0016698 A1 1/2010 Rasdal et al.
2010/0022855 A1 1/2010 Brauker et al.
2010/0025238 A1 2/2010 Gottlieb et al.
2010/0030038 A1 2/2010 Brauker et al.
2010/0030053 A1 2/2010 Goode, Jr. et al.
2010/0030484 A1 2/2010 Brauker et al.
2010/0030485 A1 2/2010 Brauker et al.
2010/0036215 A1 2/2010 Goode, Jr. et al.
2010/0036216 A1 2/2010 Goode, Jr. et al.
2010/0036222 A1 2/2010 Goode, Jr. et al.
2010/0036223 A1 2/2010 Goode, Jr. et al.
2010/0036225 A1 2/2010 Goode, Jr. et al.
2010/0041971 A1 2/2010 Goode, Jr. et al.
2010/0045465 A1 2/2010 Brauker et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2010/0049024	A1	2/2010	Saint et al.
2010/0057040	A1	3/2010	Hayter
2010/0057041	A1	3/2010	Hayter
2010/0057042	A1	3/2010	Hayter
2010/0057044	A1	3/2010	Hayter
2010/0057057	A1	3/2010	Hayter et al.
2010/0063373	A1	3/2010	Kamath et al.
2010/0076283	A1	3/2010	Simpson et al.
2010/0081908	A1	4/2010	Dobbles et al.
2010/0081910	A1	4/2010	Brister et al.
2010/0087724	A1	4/2010	Brauker et al.
2010/0096259	A1	4/2010	Zhang et al.
2010/0099970	A1	4/2010	Shults et al.
2010/0099971	A1	4/2010	Shults et al.
2010/0105999	A1	4/2010	Dixon et al.
2010/0110931	A1	5/2010	Shim et al.
2010/0119693	A1	5/2010	Tapsak et al.
2010/0119881	A1	5/2010	Patel et al.
2010/0121169	A1	5/2010	Petisce et al.
2010/0152554	A1	6/2010	Steine et al.
2010/0160759	A1	6/2010	Celentano et al.
2010/0168538	A1	7/2010	Keenan et al.
2010/0168545	A1	7/2010	Kamath et al.
2010/0174266	A1	7/2010	Estes
2010/0185175	A1	7/2010	Kamen et al.
2010/0190435	A1	7/2010	Cook et al.
2010/0198142	A1	8/2010	Sloan et al.
2010/0213080	A1	8/2010	Celentano et al.
2010/0235439	A1	9/2010	Goodnow et al.
2010/0267161	A1	10/2010	Wu et al.
2010/0312176	A1	12/2010	Lauer et al.
2010/0313105	A1	12/2010	Nekoomaram et al.
2010/0324403	A1	12/2010	Brister et al.
2010/0332142	A1	12/2010	Shadforth et al.
2011/0004276	A1	1/2011	Blair et al.
2011/0031986	A1	2/2011	Bhat et al.
2011/0074349	A1	3/2011	Ghovanloo
2011/0125040	A1	5/2011	Crawford et al.
2011/0148905	A1	6/2011	Simmons et al.
2011/0152637	A1	6/2011	Kateraas et al.
2011/0184268	A1	7/2011	Taub
2011/0191059	A1	8/2011	Farrell et al.
2011/0230741	A1	9/2011	Liang et al.
2011/0257895	A1	10/2011	Brauker et al.
2011/0270112	A1	11/2011	Manera et al.
2011/0287528	A1	11/2011	Fern et al.
2012/0108931	A1	5/2012	Taub et al.
2012/0148054	A1	6/2012	Rank et al.
2012/0215092	A1	8/2012	Harris, III et al.
2013/0035575	A1	2/2013	Mayou et al.
2013/0235166	A1	9/2013	Jones et al.

FOREIGN PATENT DOCUMENTS

EP	0026995	4/1981
EP	0048090	3/1982
EP	0078636	5/1983
EP	0080304	6/1983
EP	0098592	1/1984
EP	0125139	11/1984
EP	0127958	12/1984
EP	0136362	4/1985
EP	0170375	2/1986
EP	0177743	4/1986
EP	0184909	6/1986
EP	0206218	12/1986
EP	0230472	8/1987
EP	0241309	10/1987
EP	0245073	11/1987
EP	0255291	2/1988
EP	0278647	8/1988
EP	0320109	6/1989
EP	0353328	2/1990
EP	0359831	3/1990
EP	0368209	5/1990
EP	0390390	10/1990
EP	0396788	11/1990
EP	0400918	12/1990
EP	0453283	10/1991
EP	0470290	2/1992
EP	0504835	9/1992
EP	0286118	1/1995
EP	0653718	5/1995
EP	0680727	11/1995
EP	0724859	8/1996
EP	0800082	10/1997
EP	0805574	11/1997
EP	0880936	12/1998
EP	0970655	1/2000
EP	0973289	1/2000
EP	0678308	5/2000
EP	1034734	9/2000
EP	1048264	11/2000
EP	1579690	11/2002
EP	1292218	3/2003
EP	1077634	7/2003
EP	1445746	8/2004
EP	1445893	8/2004
EP	1568309	8/2005
EP	1666091	6/2006
EP	1703697	9/2006
EP	1704893	9/2006
EP	1897487	11/2009
EP	1897492	11/2009
EP	2113864	11/2009
EP	1897488	12/2009
EP	1681992	4/2010
EP	1448489	8/2010
EP	1971396	8/2010
EP	2201969	3/2011
EP	1413245	6/2011
EP	2153382	2/2012
EP	2284773	2/2012
GB	1394171	5/1975
GB	1579690	11/1980
GB	1599241	9/1981
GB	2073891	10/1981
GB	2154003	8/1985
GB	2194892	3/1988
GB	2204408	11/1988
GB	2225637	6/1990
GB	2254436	10/1992
GB	2409951	7/2005
SU	1281988	1/1987
WO	WO-85/05119	11/1985
WO	WO-86/00513	1/1986
WO	WO-87/00513	1/1987
WO	WO-87/06040	10/1987
WO	WO-89/02246	3/1989
WO	WO-89/05119	6/1989
WO	WO-89/08713	9/1989
WO	WO-90/00367	1/1990
WO	WO-90/05300	5/1990
WO	WO-90/05910	5/1990
WO	WO-91/01680	2/1991
WO	WO-91/04704	4/1991
WO	WO-91/15993	10/1991
WO	WO-92/01947	2/1992
WO	WO-92/13271	8/1992
WO	WO-94/20602	9/1994
WO	WO-94/27140	11/1994
WO	WO-95/28878	2/1995
WO	WO-95/06240	3/1995
WO	WO-96/07908	3/1996
WO	WO-96/25089	8/1996
WO	WO-96/30431	10/1996
WO	WO-96/35370	11/1996
WO	WO-97/02847	1/1997
WO	WO-97/19344	5/1997
WO	WO-97/20207	6/1997
WO	WO-97/33513	9/1997
WO	WO-97/41421	11/1997
WO	WO-97/42882	11/1997
WO	WO-97/42883	11/1997

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO-97/42886	11/1997
WO	WO-97/42888	11/1997
WO	WO-97/43962	11/1997
WO	WO-97/46868	12/1997
WO	WO-98/09167	3/1998
WO	WO-98/24366	6/1998
WO	WO-98/35053	8/1998
WO	WO-98/52045	11/1998
WO	WO-98/52293	11/1998
WO	WO-99/05966	2/1999
WO	WO-99/32883	7/1999
WO	WO-99/56613	11/1999
WO	WO-00/13580	3/2000
WO	WO-00/18294	4/2000
WO	WO-00/19887	4/2000
WO	WO-00/20626	4/2000
WO	WO-00/33065	6/2000
WO	WO-00/49940	8/2000
WO	WO-00/59370	10/2000
WO	WO-00/60350	10/2000
WO	WO-00/62664	10/2000
WO	WO-00/62665	10/2000
WO	WO-00/78210	12/2000
WO	WO-00/78992	12/2000
WO	WO-01/24038	4/2001
WO	WO-01/33216	5/2001
WO	WO-01/52727	7/2001
WO	WO-01/52935	7/2001
WO	WO-01/54753	8/2001
WO	WO-01/57238	8/2001
WO	WO-01/57239	8/2001
WO	WO-01/67009	9/2001
WO	WO-02/13686	2/2002
WO	WO-02/16905	2/2002
WO	WO-02/17210	2/2002
WO	WO-02/058537	8/2002
WO	WO-02/078512	10/2002
WO	WO-03/036583	5/2003
WO	WO-03/076893	9/2003
WO	WO-03/082091	10/2003
WO	WO-03/085372	10/2003
WO	WO-2004/047445	6/2004
WO	WO-2004/061420	7/2004
WO	WO-2004/098405	11/2004
WO	WO-2005/010756	2/2005
WO	WO-2005/041766	5/2005
WO	WO-2005/045744	5/2005
WO	WO-2005/089103	9/2005
WO	WO-2005/117269	12/2005
WO	WO-2006/024671	3/2006
WO	WO-2006/032653	3/2006
WO	WO-2006/037109	4/2006
WO	WO-2006/064397	6/2006
WO	WO-2006/079114	7/2006
WO	WO-2006/118947	11/2006
WO	WO-2006/119084	11/2006
WO	WO-2006/124099	11/2006
WO	WO-2007/002189	1/2007
WO	WO-2007/007459	1/2007
WO	WO-2007/016399	2/2007
WO	WO-2007/027381	3/2007
WO	WO-2007/027788	3/2007
WO	WO-2007/041069	4/2007
WO	WO-2007/041070	4/2007
WO	WO-2007/041072	4/2007
WO	WO-2007/041248	4/2007
WO	WO-2007/056638	5/2007
WO	WO-2007/101223	9/2007
WO	WO-2007/101260	9/2007
WO	WO-2007/120363	10/2007
WO	WO-2007/126444	11/2007
WO	WO-2007/053832	12/2007
WO	WO-2007/143225	12/2007
WO	WO-2008/003003	1/2008
WO	WO-2008/005780	1/2008
WO	WO-2008/021913	2/2008
WO	WO-2008/042760	4/2008
WO	WO-2008/086541	7/2008
WO	WO-2008/128210	10/2008
WO	WO-2008/130896	10/2008
WO	WO-2008/130897	10/2008
WO	WO-2008/130898	10/2008
WO	WO-2008/143943	11/2008
WO	WO-2008/150428	12/2008
WO	WO-2008/153825	12/2008
WO	WO-2009/018058	2/2009
WO	WO-2009/075697	6/2009
WO	WO-2009/086216	7/2009
WO	WO-2009/096992	8/2009
WO	WO-2009/097594	8/2009
WO	WO-2010/077329	7/2010
WO	WO-2011/022418	2/2011

OTHER PUBLICATIONS

U.S. Appl. No. 12/550,208, Office Action mailed Jul. 31, 2014.
U.S. Appl. No. 12/550,208, Office Action mailed Jul. 9, 2015.
U.S. Appl. No. 13/906,288, Advisory Action mailed Sep. 25, 2014.
U.S. Appl. No. 13/906,288, Notice of Allowance mailed Mar. 3, 2015.
U.S. Appl. No. 13/906,288, Office Action mailed Jan. 22, 2015.
U.S. Appl. No. 13/914,555, Notice of Allowance mailed Aug. 3, 2015.
U.S. Appl. No. 13/914,555, Office Action mailed Apr. 8, 2015.
U.S. Appl. No. 13/914,555, Office Action mailed Dec. 31, 2014.
U.S. Appl. No. 13/914,555, Office Action mailed Jun. 10, 2014.
U.S. Appl. No. 14/087,751, Notice of Allowance mailed Feb. 3, 2015.
U.S. Appl. No. 14/087,751, Office Action mailed Jan. 2, 2015.
U.S. Appl. No. 14/087,751, Office Action mailed Nov. 21, 2014.
U.S. Appl. No. 14/226,780, Office Action mailed Sep. 8, 2015.
U.S. Appl. No. 14/678,226, Office Action mailed Jul. 30, 2015.
U.S. Appl. No. 14/709,392, Office Action mailed Jul. 6, 2015.
Canadian Patent Application No. 2,683,721, Examiner's Report mailed Nov. 3, 2015.
European Patent Application No. 08755195.8, Examination report mailed Jan. 5, 2016.
U.S. Appl. No. 14/678,226, Notice of Allowance mailed Dec. 23, 2015.
U.S. Appl. No. 14/678,226, Office Action mailed Oct. 7, 2015.
U.S. Appl. No. 14/709,392, Office Action mailed Jan. 5, 2016.
Abruna, H. D., et al., "Rectifying Interfaces Using Two-Layer Films of Electrochemically Polymerized Vinylpyridine and Vinylbipyridine Complexes of Ruthenium and Iron on Electrodes", *Journal of the American Chemical Society*, vol. 103, No. 1, 1981, pp. 1-5.
Albery, W. J., et al., "Amperometric Enzyme Electrodes Part II: Conducting Salts as Electrode Materials for the Oxidation of Glucose Oxidase", *Journal of ElectroAnalytical Chemistry*, vol. 194, 1985, pp. 223-235.
Albery, W. J., et al., "Amperometric Enzyme Electrodes", *Philosophical Transactions of the Royal Society of London*, vol. 316, 1987, pp. 107-119.
Alcock, S. J., et al., "Continuous Analyte Monitoring to Aid Clinical Practice", *IEEE Engineering in Medicine and Biology Magazine*, 1994, pp. 319-325.
Anderson, L. B., et al., "Thin-Layer Electrochemistry: Steady-State Methods of Studying Rate Processes", *Journal of ElectroAnalytical Chemistry*, vol. 10, 1965, pp. 295-305.
Armour, J. C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs", *Diabetes*, vol. 39, 1990, pp. 1519-1526.
Bartlett, P. N., et al., "Covalent Binding of Electron Relays to Glucose Oxidase", *Journal of the Chemical Society, Chemical Communications*, 1987, pp. 1603-1604.
Bartlett, P. N., et al., "Modification of Glucose Oxidase by Tetrathiafulvalene", *Journal of the Chemical Society, Chemical Communications*, 1990, pp. 1135-136.

(56) **References Cited**

OTHER PUBLICATIONS

Bartlett, P. N., et al., "Strategies for the Development of Amperometric Enzyme Electrodes", *Biosensors*, vol. 3, 1987/88, pp. 359-379.
Bennion, N., et al., "Alternate Site Glucose Testing: A Crossover Design", *Diabetes Technology & Therapeutics*, vol. 4, No. 1, 2002, pp. 25-33.
Bergman, R., et al., "Physiological Evaluation of Factors Controlling Glucose Tolerance in Man: Measurement of Insulin Sensitivity and Beta-cell Glucose Sensitivity From the Response to Intravenous Glucose", J. Clin. Invest., *The American Society for Clinical Investigation, Inc.*, vol. 68, 1981, pp. 1456-1467.
Bindra, D. S., et al., "Design and in Vitro Studies of a Needle-Type Glucose Sensor for Subcutaneous Monitoring", *Analytical Chemistry*, vol. 63, No. 17, 1991, pp. 1692-1696.
Blank, T. B., et al., "Clinical Results From a Non-Invasive Blood Glucose Monitor", *Optical Diagnostics and Sensing of Biological Fluids and Glucose and Cholesterol Monitoring II, Proceedings of SPIE*, vol. 4624, 2002, pp. 1-10.
Bobbioni-Harsch, E., et al., "Lifespan of Subcutaneous Glucose Sensors and Their Performances During Dynamic Glycaemia Changes in Rats", *Journal of Biomedical Engineering*, vol. 15, 1993, pp. 457-463.
Boedeker Plastics, Inc., "Polyethylene Specifications", *Web Page of Boedeker.com*, 2007, pp. 1-3.
Brandt, J., et al., "Covalent Attachment of Proteins to Polysaccharide Carriers by Means of Benzoquinone", *Biochimica et Biophysica Acta*, vol. 386, 1975, pp. 196-202.
Brooks, S. L., et al., "Development of an On-Line Glucose Sensor for Fermentation Monitoring", *Biosensors*, vol. 3, 1987/88, pp. 45-56.
Brownlee, M., et al., "A Glucose-Controlled Insulin-Delivery System: Semisynthetic Insulin Bound to Lectin", *Science*, vol. 206, 1979, 1190-1191.
Cass, A. E., et al., "Ferricinum Ion as an Electron Acceptor for Oxido-Reductases", *Journal of ElectroAnalytical Chemistry*, vol. 190, 1985, pp. 117-127.
Cass, A. E., et al., "Ferrocene-Medicated Enzyme Electrode for Amperometric Determination of Glucose", *Analytical Chemistry*, vol. 56, No. 4, 1984, 667-671.
Castner, J. F., et al., "Mass Transport and Reaction Kinetic Parameters Determined Electrochemically for Immobilized Glucose Oxidase", *Biochemistry*, vol. 23 No. 10, 1984, 2203-2210.
Cheyne, E. H., et al., "Performance of a Continuous Glucose Monitoring System During Controlled Hypoglycaemia in Healthy Volunteers", *Diabetes Technology & Therapeutics*, vol. 4, No. 5, 2002, pp. 607-613.
Claremont, D. J., et al., "Biosensors for Continuous In Vivo Glucose Monitoring", *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 10, 1988.
Clark Jr., L. C., et al., "Differential Anodic Enzyme Polarography for the Measurement of Glucose", *Oxygen Transport to Tissue: Instrumentation, Methods, and Physiology*, 1973, pp. 127-133.
Clark Jr., L. C., et al., "Electrode Systems for Continuous Monitoring in Cardiovascular Surgery", *Annals New York Academy of Sciences*, 1962, pp. 29-45.
Clark Jr., L. C., et al., "Long-term Stability of Electroenzymatic Glucose Sensors Implanted in Mice", *American Society of Artificial Internal Organs Transactions*, vol. XXXIV, 1988, pp. 259-265.
Clarke, W. L., et al., "Evaluating Clinical Accuracy of Systems for Self-Monitoring of Blood Glucose", *Diabetes Care*, vol. 10, No. 5, 1987, pp. 622-628.
Csoregi, E., et al., "Design and Optimization of a Selective Subcutaneously Implantable Glucose Electrode Based on 'Wired' Glucose Oxidase", *Analytical Chemistry*, vol. 67, No. 7, 1995, pp. 1240-1244.
Csoregi, E., et al., "Design, Characterization, and One-Point in Vivo Calibration of a Subcutaneously Implanted Glucose Electrode", *Analytical Chemistry*, vol. 66 No. 19, 1994, pp. 3131-3138.
Csoregi, E., et al., "On-Line Glucose Monitoring by Using Microdialysis Sampling and Amperometric Detection Based on 'Wired' Glucose Oxidase in Carbon Paste", *Mikrochimica Acta*, vol. 121, 1995, pp. 31-40.
Dai, W. S., et al., "Hydrogel Membranes with Mesh Size Asymmetry Based on the Gradient Crosslinking of Poly(vinyl alcohol)," *Journal of Membrane Science*, vol. 156, 1999, pp. 67-79.
Davis, G., "Electrochemical Techniques for the Development of Amperometric Biosensors", *Biosensors*, vol. 1, 1985, pp. 161-178.
Degani, Y., et al., "Direct Electrical Communication Between Chemically Modified Enzymes and Metal Electrodes. 1. Electron Transfer from Glucose Oxidase to Metal Electrodes via Electron Relays, Bound Covalently to the Enzyme", *The Journal of Physical Chemistry*, vol. 91, No. 6, 1987, pp. 1285-1289.
Degani, Y., et al., "Direct Electrical Communication Between Chemically Modified Enzymes and Metal Electrodes. 2. Methods for Bonding Electron-Transfer Relays to Glucose Oxidase and D-Amino-Acid Oxidase", *Journal of the American Chemical Society*, vol. 110, No. 8, 1988, pp. 2615-2620.
Degani, Y., et al., "Electrical Communication Between Redox Centers of Glucose Oxidase and Electrodes via Electrostatically and Covalently Bound Redox Polymers", *Journal of the American Chemical Society*, vol. 111, 1989, pp. 2357-2358.
Denisevich, P., et al., "Unidirectional Current Flow and Charge State Trapping at Redox Polymer Interfaces on Bilayer Electrodes: Principles, Experimental Demonstration, and Theory", *Journal of the American Chemical Society*, vol. 103, 1981, pp. 4727-4737.
Dicks, J. M., et al., "Ferrocene Modified Polypyrrole with Immobilised Glucose Oxidase and its Application in Amperometric Glucose Microbiosensors", *Annales de Biologie Clinique*, vol. 47, 1989, pp. 607-619.
Diem, P., et al., "Clinical Performance of a Continuous Viscometric Affinity Sensor for Glucose", *Diabetes Technology & Therapeutics*, vol. 6, 2004, pp. 790-799.
Ellis, C. D., et al., "Selectivity and Directed Charge Transfer through an Electroactive Metallopolymer Film", *Journal of the American Chemical Society*, vol. 103, No. 25, 1981, pp. 7480-7483.
Engstrom, R. C., "Electrochemical Pretreatment of Glassy Carbon Electrodes", *Analytical Chemistry*, vol. 54, No. 13, 1982, pp. 2310-2314.
Engstrom, R. C., et al., "Characterization of Electrochemically Pretreated Glassy Carbon Electrodes", *Analytical Chemistry*, vol. 56 No. 2, 1984, pp. 136-141.
Feldman, B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes", *Diabetes Technology & Therapeutics*, vol. 5, No. 5, 2003, pp. 769-779.
Feldman, B., et al., "Correlation of Glucose Concentrations in Interstitial Fluid and Venous Blood During Periods of Rapid Glucose Change", *Abbott Diabetes Care, Inc. Freestyle Navigator Continuous Glucose Monitor Pamphlet*, 2004.
Feldman, B., et al., "Electron Transfer Kinetics at Redox Polymer/Solution Interfaces Using Microelectrodes and Twin Electrode Thin Layer Cells", *Journal of ElectroAnalytical Chemistry*, vol. 194, 1985, pp. 63-81.
Fischer, H., et al., "Intramolecular Electron Transfer Medicated by 4,4'-Bypyridine and Related Bridging Groups", *Journal of the American Chemical Society*, vol. 98, No. 18, 1976, pp. 5512-5517.
Flentge, F., et al., "An Enzyme-Reactor for Electrochemical Monitoring of Choline and Acetylcholine: Applications in High-Performance Liquid Chromatography, Bran Tissue, Microdialysis and Cerebrospinal Fluid," *Analytical Biochemistry*, vol. 204, 1992, pp. 305-310.
Foulds, N. C., et al., "Enzyme Entrapment in Electrically Conducting Polymers: Immobilisation of Glucose Oxidase in Polypyrrole and its Application in Amperometric Glucose Sensors", *Journal of the Chemical Society, Faraday Transactions 1*, vol. 82, 1986, pp. 1259-1264.
Foulds, N. C., et al , "Immobilization of Glucose Oxidase in Ferrocene-Modified Pyrrole Polymers", *Analytical Chemistry*, vol. 60, No. 22, 1988, pp. 2473-2478.

(56) **References Cited**

OTHER PUBLICATIONS

Frew, J. E., et al., "Electron-Transfer Biosensors", *Philosophical Transactions of the Royal Society of London*, vol. 316, 1987, pp. 95-106.
Garg, S., et al., "Improvement in Glycemic Excursions with a Transcutaneous, Real-Time Continuous Glucose Sensor", *Diabetes Care*, vol. 29, No. 1, 2006, pp. 44-50.
Godsland, I. F., et al., "Maximizing the Success Rate of Minimal Model Insulin Sensitivity Measurement in Humans: The Importance of Basal Glucose Levels," *Clinical Science*, vol. 101, 2001, pp. 1-9.
Gorton, L., et al., "Selective Detection in Flow Analysis Based on the Combination of Immobilized Enzymes and Chemically Modified Electrodes", *Analytica Chimica Acta*, vol. 250, 1991, pp. 203-248.
Graham, N. B., "Poly(ethylene oxide) and Related Hydrogels," *Hydrogels in Medicine and Pharmacy*, vol. II: Polymers, Chapter 4, 1987, pp. 95-113.
Gregg, B. A., et al., "Cross-Linked Redox Gels Containing Glucose Oxidase for Amperometric Bionsensor Applications", *Analytical Chemistry*, vol. 62, No. 3, 1990, pp. 258-263.
Gregg, B. A., et al., "Redox Polymer Films Containing Enzymes. 1. A Redox-Conducting Epoxy Cement: Synthesis, Characterization, and Electrocatalytic Oxidation of Hydroquinone", *Journal of Physical Chemistry*, vol. 95, No. 15, 1991, 5970-5975.
Hale, P. D., et al., "A New Class of Amperometric Biosensor Incorporating a Polymeric Electron-Transfer Mediator", *Journal of the American Chemical Society*, vol. 111, No. 9, 1989, pp. 3482-3484.
Harrison, D. J., et al., "Characterization of Perfluorosulfonic Acid Polymer Coated Enzyme Electrodes and a Miniatureized Integrated Potentiostat for Glucose Analysis in Whole Blood", *Analytical Chemistry*, vol. 60, No. 19, 1988, pp. 2002-2007.
Hawkridge, F. M., et al., "Indirect Coulometric Titration of Biological Electron Transport Components", *Analytical Chemistry*, vol. 45, No. 7, 1973, pp. 1021-1027.
Heller, A., "Electrical Connection Enzyme Redox Centers to Electrodes", *Journal of Physical Chemistry*, vol. 96, No. 9, 1990, pp. 3579-3587.
Heller, A., "Electrical Wiring of Redox Enzymes", *Accounts of Chemical Research* vol. 23, No. 5, 1990, 128-134.
Heller, A., et al., "Amperometric Biosensors Based on Three-Dimensional Hydrogel-Forming Epoxy Networks", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 180-183.
Ianniello, R. M., et al., "Differential Pulse Voltammetric Study of Direct Electron Transfer in Glucose Oxidase Chemically Modified Graphite Electrodes", *Analytical Chemistry*, vol. 54, No. 7, 1982, pp. 1098-1101.
Ianniello, R. M., et al , "Immobilized Enzyme Chemically Modified Electrode as an Amperometric Sensor", *Analytical Chemistry*, vol. 53, No. 13, 1981, pp. 2090-2095.
Ikeda, T., et al., "Glucose Oxidase-Immobilized Benzoquinone-Carbon Paste Electrode as a Glucose Sensor", *Agricultural and Biological Chemistry*, vol. 49, No. 2, 1985, pp. 541-543.
Ikeda, T., et al., "Kinetics of Outer-Sphere Electron Transfers Between Metal Complexes in Solutions and Polymeric Films on Modified Electrodes", *Journal of the American Chemical Society*, vol. 103, No. 25, 1981, pp. 7422-7425.
Isermann, R., "Supervision, Fault-Detection and Fault-Diagnosis Methods—An Introduction", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 639-652.
Isermann, R., et al., "Trends in the Application of Model-Based Fault Detection and Diagnosis of Technical Processes", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 709-719.
Johnson, J. M., et al., "Potential-Dependent Enzymatic Activity in an Enzyme Thin-Layer Cell", *Analytical Chemistry*, vol. 54, No. 8, 1982, pp. 1377-1383.
Johnson, K. W., "Reproducible Electrodeposition of Biomolecules for the Fabrication of Miniature Electroenzymatic Biosensors", *Sensors and Actuators B*, vol. 5, 1991, pp. 85-89.
Johnson, K. W., et al., "In vivo Evaluation of an Electroenzymatic Glucose Sensor Implanted in Subcutaneous Tissue", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 709-714.
Johnson, P. C., "Peripheral Circulation", *John Wiley & Sons*, 1978, pp. 198.
Jonsson, G., et al., "An Amperometric Glucose Sensor Made by Modification of a Graphite Electrode Surface With Immobilized Glucose Oxidase and Adsorbed Mediator", *Biosensors*, vol. 1, 1985, pp. 355-368.
Josowicz, M., et al., "Electrochemical Pretreatment of Thin Film Platinum Electrodes", *Journal of the Electrochemical Society*, vol. 135 No. 1, 1988, pp. 112-115.
Jungheim, K., et al., "How Rapid Does Glucose Concentration Change in Daily Life of Patients with Type 1 Diabetes?", 2002, pp. 250.
Jungheim, K., et al., "Risky Delay of Hypoglycemia Detection by Glucose Monitoring at the Arm", *Diabetes Care*, vol. 24, No. 7, 2001, pp. 1303-1304.
Kaplan, S. M., "Wiley Electrical and Electronics Engineering Dictionary", *IEEE Press*, 2004, pp. 141, 142, 548, 549.
Katakis, I., et al., "Electrostatic Control of the Electron Transfer Enabling Binding of Recombinant Glucose Oxidase and Redox Polyelectrolytes", *Journal of the American Chemical Society*, vol. 116, No. 8, 1994, pp. 3617-3618.
Katakis, I., et al., "L-α-Glycerophosphate and L-Lactate Electrodes Based on the Electrochemical 'Wiring' of Oxidases", *Analytical Chemistry*, vol. 64, No. 9, 1992, pp. 1008-1013.
Kemp, G. J., "Theoretical Aspects of One-Point Calibration: Causes and Effects of Some Potential Errors, and Their Dependence on Concentration," *Clinical Chemistry*, vol. 30, No. 7, 1984, pp. 1163-1167.
Kenausis, G., et al., "'Wiring' of Glucose Oxidase and Lactate Oxidase Within a Hydrogel Made with Poly(vinyl pyridine) complexed with $[Os(4,4'\text{-dimethoxy-}2,2'\text{-bipyridine})_2\ C1]^{+/2+}$", *Journal of the Chemical Society, Faraday Transactions*, vol. 92, No. 20, 1996, pp. 4131-4136.
Kerner, W., et al., "The Function of a Hydrogen Peroxide-Detecting Electroenzymatic Glucose Electrode is Markedly Impaired in Human Subcutaneous Tissue and Plasma," *Biosensors & Bioelectronics*, vol. 8, 1993, pp. 473-482.
Kondepati, V., et al., "Recent Progress in Analytical Instrumentation for Glycemic Control in Diabetic and Critically Ill Patients", *Analytical Bioanalytical Chemistry*, vol. 388, 2007, pp. 545-563.
Korf, J., et al., "Monitoring of Glucose and Lactate Using Microdialysis: Applications in Neonates and Rat Brain," *Developmental Neuroscience*, vol. 15, 1993, pp. 240-246.
Koudelka, M., et al., "In-Vivo Behaviour of Hypodermically Implanted Microfabricated Glucose Sensors", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 31-36.
Kulys, J., et al., "Mediatorless Peroxidase Electrode and Preparation of Bienzyme Sensors", *Bioelectrochemistry and Bioenergetics*, vol. 24, 1990, pp. 305-311.
Lager, W., et al., "Implantable Electrocatalytic Glucose Sensor", *Hormone Metabolic Research*, vol. 26, 1994, pp. 526-530.
Laurell, T., "A Continuous Glucose Monitoring System Based on Microdialysis", *Journal of Medical Engineering & Technology*, vol. 16, No. 5, 1992, pp. 187-193.
Lindner, E., et al., "Flexible (Kapton-Based) Microsensor Arrays of High Stability for Cardiovascular Applications", *Journal of the Chemical Society, Faraday Transactions*, vol. 89, No. 2, 1993, pp. 361-367.
Lo, B., et al., "Key Technical Challenges and Current Implementations of Body Sensor Networks", *Body Sensor Networks*, 2005, pp. 1-5.
Lodwig, V., et al., "Continuous Glucose Monitoring with Glucose Sensors: Calibration and Assessment Criteria", *Diabetes Technology& Therapeutics*, vol. 5, No. 4, 2003, pp. 573-587.
Lortz, J., et al., "What is Bluetooth? We Explain the Newest Short-Range Connectivity Technology", *Smart Computing Learning Series, Wireless Computing*, vol. 8, Issue 5, 2002, pp. 72-74.
Maidan, R., et al., "Elimination of Electrooxidizable Interferant-Produced Currents in Amperometric Biosensors", *Analytical Chemistry*, vol. 64, No. 23, 1992, pp. 2889-2896.

(56) **References Cited**

OTHER PUBLICATIONS

Malin, S. F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectoscopy", *Clinical Chemistry*, vol. 45, No. 9, 1999, pp. 1651-1658.
Marko-Varga, G., et al., "Enzyme-Based Biosensor as a Selective Detection Unit in Column Liquid Chromatography", *Journal of Chromatography A*, vol. 660, 1994, pp. 153-167.
Mastrototaro, J. J., et al., "An Electroenzymatic Glucose Sensor Fabricated on a Flexible Substrate", *Sensors and Actuators B*, vol. 5, 1991, pp. 139-144.
Mauras, N., et al., "Lack of Accuracy of Continuous Glucose Sensors in Healthy, Nondiabetic Children: Results of the Diabetes Research in Children Network (DirecNet) Accuracy Study," *Journal of Pediatrics*, 2004, pp. 770-775.
McGarraugh, G., et al., "Glucose Measurements Using Blood Extracted from the Forearm and the Finger", *TheraSense, Inc.*, 2001, 16 Pages.
McGarraugh, G., et al., "Physiological Influences on Off-Finger Glucose Testing", *Diabetes Technology & Therapeutics*, vol. 3, No. 3, 2001, pp. 367-376.
McKean, B. D., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 7, 1988, pp. 526-532.
McNeil, C. J., et al., "Thermostable Reduced Nicotinamide Adenine Dinucleotide Oxidase: Application to Amperometric Enzyme Assay", *Analytical Chemistry*, vol. 61, No. 1, 1989, pp. 25-29.
Miyawaki, O., et al., "Electrochemical and Glucose Oxidase Coenzyme Activity of Flavin Adenine Dinucleotide Covalently Attached to Glassy Carbon at the Adenine Amino Group", *Biochimica et Biophysica Acta*, vol. 838, 1985, pp. 60-68.
Moatti-Sirat, D., et al., "Evaluating In Vitro and In Vivo the Interference of Ascorbate and Acetaminophen on Glucose Detection by a Needle-Type Glucose Sensor", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 345-352.
Moatti-Sirat, D., et al., "Reduction of Acetaminophen Interference in Glucose Sensors by a Composite Nafion Membrane: Demonstration in Rats and Man", *Diabetologia*, vol. 37, 1994, pp. 610-616.
Moatti-Sirat, D., et al., "Towards Continuous Glucose Monitoring: In Vivo Evaluation of a Miniaturized Glucose Sensor Implanted for Several Days in Rat Subcutaneous Tissue", *Diabetologia*, vol. 35, 1992, pp. 224-330.
Morbiducci, U, et al., "Improved Usability of the Minimal Model of Insulin Sensitivity Based on an Automated Approach and Genetic Algorithms for Parameter Estimation", *Clinical Science*, vol. 112, 2007, pp. 257-263.
Mougiakakou, et al., "A Real Time Simulation Model of Glucose-Insulin Metabolism for Type 1 Diabetes Patients", *Proceedings of the 2005 IEEE*, 2005, pp. 298-301.
Nagy, G., et al., "A New Type of Enzyme Electrode: The Ascorbic Acid Eliminator Electrode", *Life Sciences*, vol. 31, No. 23, 1982, pp. 2611-2616.
Nakamura, S., et al., "Effect of Periodate Oxidation on the Structure and Properties of Glucose Oxidase", *Biochimica et Biophysica Acta.*, vol. 445, 1976, pp. 294-308.
Narasimham, K., et al., "p-Benzoquinone Activation of Metal Oxide Electrodes for Attachment of Enzymes", *Enzyme and Microbial Technology*, vol. 7, 1985, pp. 283-286.
Ohara, T. J., "Osmium Bipyridyl Redox Polymers Used in Enzyme Electrodes", *Platinum Metals Review*, vol. 39, No. 2, 1995, pp. 54-62.
Ohara, T. J., et al., "'Wired' Enzyme Electrodes for Amperometric Determination of Glucose or Lactate in the Presence of Interfering Substances", *Analytical Chemistry*, vol. 66, No. 15, 1994, pp. 2451-2457.
Ohara, T. J., et al., "Glucose Electrodes Based on Cross-Linked $[Os(bpy)_2C1]^{+/2+}$Complexed Poly(1-Vinylimidazole) Films", *Analytical Chemistry*, vol. 65, No. 23, 1993, pp. 3512-3517.
Olievier, C. N., et al., "In Vivo Measurement of Carbon Dioxide Tension with a Miniature Electrodes", *Pflugers Archiv: European Journal of Physiology*, vol. 373, 1978, pp. 269-272.
Paddock, R. M., et al., "Electrocatalytic Reduction of Hydrogen Peroxide via Direct Electron Transfer From Pyrolytic Graphite Electrodes to Irreversibly Adsorbed Cyctochrome C Peroxidase", *Journal of ElectroAnalytical Chemistry*, vol. 260, 1989, pp. 487-494.
Palleschi, G., et al., "A Study of Interferences in Glucose Measurements in Blood by Hydrogen Peroxide Based Glucose Probes", *Analytical Biochemistry*, vol. 159, 1986, pp. 114-121.
Pankratov, I., et al., "Sol-Gel Derived Renewable-Surface Biosensors", *Journal of ElectroAnalytical Chemistry*, vol. 393, 1995, pp. 35-41.
Parker, R., et al., "Robust H∞ Glucose Control in Diabetes Using a Physiological Model", *AIChE Journal*, vol. 46, No. 12, 2000, pp. 2537-2549.
Pathak, C., et al., "Rapid Photopolymerization of Immunoprotective Gels in Contact with Cells and Tissue", *Journal of the American Chemical Society*, vol. 114, No. 21, 1992, pp. 8311-8312.
Pickup, J., "Developing Glucose Sensors for In Vivo Use", *Tibtech*, vol. 11, 1993, pp. 285-291.
Pickup, J., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensing Strategy", *Biosensors*, vol. 3, 1987/88, pp. 335-346.
Pickup, J., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer", *Diabetologia*, vol. 32, 1989, pp. 213-217.
Pickup, J., et al., "Potentially-Implantable, Amperometric Glucose Sensors with Mediated Electron Transfer: Improving the Operating Stability", *Biosensors*, vol. 4, 1989, pp. 109-119.
Pishko, M. V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels", *Analytical Chemistry*, vol. 63, No. 20, 1991, pp. 2268-2272.
Poitout, V., et al., "A Glucose Monitoring System for On Line Estimation in Man of Blood Glucose Concentration Using a Miniaturized Glucose Sensor Implanted in the Subcutaneous Tissue and a Wearable Control Unit", *Diabetolgia*, vol. 36, 1993, pp. 658-663.
Poitout, V., et al., "Calibration in Dogs of a Subcutaneous Miniaturized Glucose Sensor Using a Glucose Meter for Blood Glucose Determination", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 587-592.
Poitout, V., et al., "In Vitro and In Vivo Evaluation in Dogs of a Miniaturized Glucose Sensor", *ASAIO Transactions*, vol. 37, No. 3, 1991, pp. M298-M300.
Pollak, A., et al., "Enzyme Immobilization by Condensation Copolymerization into Cross-Linked Polyacrylamide Gels", *Journal of the American Chemical Society*, vol. 102, No. 20, 1980, pp. 6324-6336.
Quinn, C. P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors", *The American Physiological Society*, 1995, E155-E161.
Reach, G., et al., "Can Continuous Glucose Monitoring Be Used for the Treatment of Diabetes?", *Analytical Chemistry*, vol. 64, No. 6, 1992, pp. 381-386.
Rebrin, K., et al., "Automated Feedback Control of Subcutaneous Glucose Concentration in Diabetic Dogs", *Diabetologia*, vol. 32, 1989, pp. 573-576.
Reusch, W., "Other Topics: Organometallic Chemistry: Organometallic Compounds: Main Group Organometallic Compounds," *Virtual Textbook of Organic Chemistry*, 1999, Rev. 2007, 25 pages.
Rodriguez, N., et al., "Flexible Communication and Control Protocol for Injectable Neuromuscular Interfaces", IEEE Transactions on Biomedical Circuits and Systems, vol. 1, No. 1, 2007, pp. 19-27.
Roe, J. N., et al., "Bloodless Glucose Measurements", *Critical Review in Therapeutic Drug Carrier Systems*, vol. 15, Issue 3, 1998, pp. 199-241.

(56) **References Cited**

OTHER PUBLICATIONS

Sacks (ED), "Guidelines and Recommendations for Laboratory Analysis in the Diagnosis and Management of Diabetes Mellitus," *The National Academy of Clinical Biochemistry Presents Laboratory Medicine Practice Guidelines*, vol. 13, 2002, pp. 8-11, 21-23, 52-56, 63.
Sakakida, M., et al., "Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations", *Artificial Organs Today*, vol. 2, No. 2, 1992, pp. 145-158.
Sakakida, M., et al., "Ferrocene-Mediated Needle-Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322.
Salditt, P., "Trends in Medical Device Design and Manufacturing", *SMTA News and Journal of Surface Mount Technology*, vol. 17, 2004, pp. 19-24.
Salehi, C., et al., "A Telemetry-Instrumentation System for Long-Term Implantable Glucose and Oxygen Sensors", *Analytical Letters*, vol. 29, No. 13, 1996, pp. 2289-2308.
Samuels, G. J., et al., "An Electrode-Supported Oxidation Catalyst Based on Ruthenium (IV). pH 'Encapsulation' in a Polymer Film", *Journal of the American Chemical Society*, vol. 103, No. 2, 1981, pp. 307-312.
Sasso, S. V., et al., "Electropolymerized 1,2-Diaminobenzene as a Means to Prevent Interferences and Fouling and to Stabilize Immobilized Enzyme in Electrochemical Biosensors", *Analytical Chemistry*, vol. 62, No. 11, 1990, pp. 1111-1117.
Scheller, F. W., et al., "Second Generation Biosensors," *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 245-253.
Scheller, F., et al., "Enzyme Electrodes and Their Application", *Philosophical Transactions of The Royal Society of London B*, vol. 316, 1987, pp. 85-94.
Schmehl, R. H., et al., "The Effect of Redox Site Concentration on the Rate of Mediated Oxidation of Solution Substrates by a Redox Copolymer Film", *Journal of ElectroAnalytical Chemistry*, vol. 152, 1983, pp. 97-109.
Schmidt, F. J., et al., "Calibration of a Wearable Glucose Sensor", *The International Journal of Artificial Organs*, vol. 15, No. 1, 1992, pp. 55-61.
Schmidtke, D. W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin", *Proceedings of the National Academy of Sciences*, vol. 95, 1998, pp. 294-299.
Shaw, G. W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.
Shichiri, M., et al., "Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas", *Diabetologia*, vol. 24, 1983, pp. 179-184.
Shichiri, M., et al., "In Vivo Characteristics of Needle-Type Glucose Sensor—Measurements of Subcutaneous Glucose Concentrations in Human Volunteers", *Hormone and Metabolic Research Supplement Series*, vol. 20, 1988, pp. 17-20.
Shichiri, M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor", *Diabetes Nutrition and Metabolism*, vol. 2, 1989, pp. 309-313.
Shichiri, M., et al., "Needle-type Glucose Sensor for Wearable Artificial Endocrine Pancreas", *Implantable Sensors for Closed-Loop Prosthetic Systems*, Chapter 15, 1985, pp. 197-210.
Shichiri, M., et al., "Telemetry Glucose Monitoring Device With Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals", *Diabetes Care*, vol. 9, No. 3, 1986, pp. 298-301.
Shichiri, M., et al., "Wearable Artificial Endocrine Pancreas With Needle-Type Glucose Sensor", *The Lancet*, 1982, pp. 1129-1131.
Shults, M. C., et al., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 41, No. 10, 1994, pp. 937-942.
Sittampalam, G., et al., "Surface-Modified Electrochemical Detector for Liquid Chromatography", *Analytical Chemistry*, vol. 55, No. 9, 1983, pp. 1608-1610.
Skoog, D. A., et al., "Evaluation of Analytical Data," *Fundamentals of Analytical Chemistry*, 1966, pp. 55.
Slattery, C., et al., "A Reference Design for High-Performance, Low-Cost Weigh Scales", *Analog Dialogue 39-12*, 2005 pp. 1-6.
Soegijoko, S., et al., "External Artificial Pancreas: A New Control Unit Using Microprocessor", *Hormone and Metabolic Research Supplement Series*, vol. 12, 1982, pp. 165-169.
Sprules, S. D., et al., "Evaluation of a New Disposable Screen-Printed Sensor Strip for the Measurement of NADH and its Modification to Produce a Lactate Biosensor Employing Microliter Volumes", *Electroanalysis*, vol. 8, No. 6, 1996, pp. 539-543.
Sternberg, F., et al., "Calibration Problems of Subcutaneous Glucosensors when Applied 'In-Situ' in Man", *Hormone and Metabolic Research*, vol. 26, 1994, pp. 523-526.
Sternberg, R., et al., "Covalent Enzyme Coupling on Cellulose Acetate Membranes for Glucose Sensor Development", *Analytical Chemistry*, vol. 60, No. 24, 1988, pp. 2781-2786.
Sternberg, R., et al., "Study and Development of Multilayer Needle-Type Enzyme-Based Glucose Microsensors", *Biosensors*, vol. 4, 1988, pp. 27-40.
Suekane, M., "Immobilization of Glucose Isomerase", *Zettschrift fur Allgemeine Mikrobiologie*, vol. 22, No. 8, 1982, pp. 565-576.
Tajima, S., et al., "Simultaneous Determination of Glucose and 1,5-Anydroglucitol", *Chemical Abstracts*, vol. 111, No. 25, 1989, pp. 394.
Takamura, A., et al., Drug release from Poly(vinyl alcohol) Gel Prepared by Freeze-Thaw Procedure, *Journal of Controlled Release*, vol. 20, 1992, pp. 21-27.
Tarasevich, M. R., "Bioelectrocatalysis", *Comprehensive Treatise of Electrochemistry*, vol. 10, 1985, pp. 231-295.
Tatsuma, T., et al., "Enzyme Monolayer—and Bilayer-Modified Tin Oxide Electrodes for the Determination of Hydrogen Peroxide and Glucose", *Analytical Chemistry*, vol. 61, No. 21, 1989, pp. 2352-2355.
Taylor, C., et al., "'Wiring' of Glucose Oxidase Within a Hydrogel Made with Polyvinyl Imidazole Complexed with [(Os-4,4'-dimethoxy-2,2'-bipyridine)C1]$^{+/2+}$", *Journal of ElectroAnalytical Chemistry*, vol. 396, 1995, pp. 511-515.
Thompson, M., et al., "In Vivo Probes: Problems and Perspectives", *Clinical Biochemistry*, vol. 19, 1986, pp. 255-261.
Travenol Laboratories, Inc., *An Introduction to "Eugly"*, Book 1, 1985, pp. 1-22.
Trojanowicz, M., et al., "Enzyme Entrapped Polypyrrole Modified Electrode for Flow-Injection Determination of Glucose", *Biosensors & Bioelectronics*, vol. 5, 1990, pp. 149-156.
Tsalikian, E., et al., "Accuracy of the GlucoWatch G2® Biographer and the Continuous Glucose Monitoring System During Hypoglycemia: Experience of the Diabetes Research in Children Network", *Diabetes Care*, vol. 27, No. 3, 2004, pp. 722-726.
Turner, A., et al., "Diabetes Mellitus: Biosensors for Research and Management", *Biosensors*, vol. 1, 1985, pp. 85-115.
Turner, R. F., et al., "A Biocompatible Enzyme Electrode for Continuous in vivo Glucose Monitoring in Whole Blood", *Sensors and Actuators B*, vol. 1, 1990, pp. 561-564.
Tuzhi, P., et al., "Constant Potential Pretreatment of Carbon Fiber Electrodes for In Vivo Electrochemistry", *Analytical Letters*, vol. 24, No. 6, 1991, pp. 935-945.
Umana, M., "Protein-Modified Electrochemically Active Biomaterial Surface", *U.S. Army Research Office, Analytical and Chemical Sciences Research Triangle Institute*, 1988, pp. 1-9.
Updike, S. J., et al., "Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose from Inside a Subcutaneous Foreign Body Capsule (FBC)", *Biosensors in the Body: Continuous in vivo Monitoring*, Chapter 4, 1997, pp. 117-137.
Urban, G., et al., "Miniaturized Thin-Film Biosensors Using Covalently Immobilized Glucose Oxidase", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 555-562.

(56) **References Cited**

OTHER PUBLICATIONS

Velho, G., et al., "In Vitro and In Vivo Stability of Electrode Potentials in Needle-Type Glucose Sensors", *Diabetes*, vol. 38, No. 2, 1989, pp. 164-171.
Velho, G., et al., "Strategies for Calibrating a Subcutaneous Glucose Sensor", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 957-964.
Von Woedtke, T., et al., "In Situ Calibration of Implanted Electrochemical Glucose Sensors", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 943-952.
Vreeke, M. S., et al., "Hydrogen Peroxide Electrodes Based on Electrical Connection of Redox Centers of Various Peroxidases to Electrodes through a Three-Dimensional Electron-Relaying Polymer Network", *Diagnostic Biosensors Polymers*, Chapter 15, 1993, pp. 180-193.
Vreeke, M., et al., "Hydrogen Peroxide and β-Nicotinamide Adenine Dinucleotide Sensing Amperometric Electrodes Based on Electrical Connection of Horseradish Peroxidase Redox Centers to Electrodes through a Three-Dimensional Electron Relaying Polymer Network", *Analytical Chemistry*, vol. 64, No. 24, 1992, pp. 3084-3090.
Wang, D. L., et al., "Miniaturized Flexible Amperometric Lactate Probe", *Analytical Chemistry*, vol. 65, No. 8, 1993, pp. 1069-1073.
Wang, J., et al., "Activation of Glassy Carbon Electrodes by Alternating Current Electrochemical Treatment", *Analytica Chimica Acta*, vol. 167, 1985, pp. 325-334.
Wang, J., et al., "Amperometric Biosensing of Organic Peroxides with Peroxidase-Modified Electrodes", *Analytica Chimica Acta*, vol. 254, 1991, pp. 81-88.
Wang, J., et al., "Screen-Printable Sol-Gel Enzyme-Containing Carbon Inks", *Analytical Chemistry*, vol. 68, No. 15, 1996, pp. 2705-2708.
Wang, J., et al., "Sol-Gel-Derived Metal-Dispersed Carbon Composite Amperometric Biosensors", *Electroanalysis*, vol. 9, No. 1, 1997, pp. 52-55.
Williams, D. L., et al., "Electrochemical-Enzymatic Analysis of Blood Glucose and Lactate", *Analytical Chemistry*, vol. 42, No. 1, 1970, pp. 118-121.
Wilson, G. S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose", *Clinical Chemistry*, vol. 38, No. 9, 1992, pp. 1613-1617.
Yabuki, S., et al., "Electro-Conductive Enzyme Membrane", *Journal of the Chemical Society, Chemical Communications*, 1989, pp. 945-946.
Yang, C., et al., "A Comparison of Physical Properties and Fuel Cell Performance of Nafion and Zirconium Phosphate/Nafion Composite Membranes," *Journal of Membrane Science*, vol. 237, 2004, pp. 145-161.
Yang, L., et al., "Determination of Oxidase Enzyme Substrates Using Cross-Flow Thin-Layer Amperometry", *Electroanalysis*, vol. 8, No. 8-9, 1996, pp. 716-721.
Yao, S. J., et al., "The Interference of Ascorbate and Urea in Low-Potential Electrochemical Glucose Sensing", *Proceedings of the Twelfth Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12, Part 2, 1990, pp. 487-489.
Yao, T., "A Chemically-Modified Enzyme Membrane Electrode as an Amperometric Glucose Sensor", *Analytica Chimica Acta*, vol. 148, 1983, pp. 27-33.
Ye, L., et al., "High Current Density 'Wired' Quinoprotein Glucose Dehydrogenase Electrode", *Analytical Chemistry*, vol. 65, No. 3, 1993, pp. 238-241.
Yildiz, A., et al., "Evaluation of an Improved Thin-Layer Electrode", *Analytical Chemistry*, vol. 40, No. 7, 1968, pp. 1018-1024.
Zamzow, K., et al., "New Wearable Continuous Blood Glucose Monitor (BGM) and Artificial Pancreas (AP)", *Diabetes*, vol. 39, 1990, pp. 5A-20.
Zhang, Y., et al., "Application of Cell Culture Toxicity Tests to the Development of Implantable Biosensors", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 653-661.
Zhang, Y., et al., "Elimination of the Acetaminophen Interference in an Implantable Glucose Sensor", *Analytical Chemistry*, vol. 66, No. 7, 1994, pp. 1183-1188.
European Patent Application No. 08755195.8, Extended European Search Report mailed Oct. 18, 2013.
PCT Application No. PCT/US2008/063110, International Preliminary Report on Patentability and Written Opinion of the International Searching Authority mailed Nov. 26, 2009.
PCT Application No. PCT/US2008/063110, International Search Report and Written Opinion of the International Searching Authority mailed Nov. 21, 2008.
U.S. Appl. No. 12/117,665, Notice of Allowance mailed Feb. 23, 2011.
U.S. Appl. No. 12/117,665, Office Action mailed Jan. 20, 2011.
U.S. Appl. No. 12/117,665, Office Action mailed Jun. 28, 2010.
U.S. Appl. No. 12/117,677, Advisory Action mailed Aug. 15, 2012.
U.S. Appl. No. 12/117,677, Advisory Action mailed Jul. 27, 2011.
U.S. Appl. No. 12/117,677, Office Action mailed Apr. 14, 2011.
U.S. Appl. No. 12/117,677, Office Action mailed Jun. 9, 2010.
U.S. Appl. No. 12/117,677, Office Action mailed Mar. 9, 2012.
U.S. Appl. No. 12/117,677, Office Action mailed May 5, 2013.
U.S. Appl. No. 12/117,677, Office Action mailed Nov. 1, 2013.
U.S. Appl. No. 12/117,677, Office Action mailed Nov. 4, 2010.
U.S. Appl. No. 12/117,677, Office Action mailed Oct. 14, 2011.
U.S. Appl. No. 12/117,681, Notice of Allowance mailed Feb. 20, 2013.
U.S. Appl. No. 12/117,681, Office Action mailed Apr. 5, 2010.
U.S. Appl. No. 12/117,681, Office Action mailed Mar. 5, 2012.
U.S. Appl. No. 12/117,681, Office Action mailed Oct. 25, 2012.
U.S. Appl. No. 12/117,681, Office Action mailed Sep. 14, 2010.
U.S. Appl. No. 12/117,685, Advisory Action mailed Jun. 7, 2010.
U.S. Appl. No. 12/117,685, Office Action mailed Apr. 8, 2011.
U.S. Appl. No. 12/117,685, Office Action mailed Aug. 16, 2010.
U.S. Appl. No. 12/117,685, Office Action mailed Aug. 7, 2013.
U.S. Appl. No. 12/117,685, Office Action mailed Mar. 22, 2010.
U.S. Appl. No. 12/117,685, Office Action mailed May 31, 2012.
U.S. Appl. No. 12/117,685, Office Action mailed Sep. 2, 2009.
U.S. Appl. No. 12/117,685, Office Action mailed Sep. 27, 2012.
U.S. Appl. No. 12/117,694, Advisory Action mailed Nov. 16, 2012.
U.S. Appl. No. 12/117,694, Office Action mailed Aug. 7, 2012.
U.S. Appl. No. 12/117,694, Office Action mailed Dec. 9, 2011.
U.S. Appl. No. 12/117,694, Office Action mailed Oct. 1, 2013.
U.S. Appl. No. 12/117,698, Notice of Allowance mailed Feb. 5, 2013.
U.S. Appl. No. 12/117,698, Office Action mailed Apr. 5, 2010.
U.S. Appl. No. 12/117,698, Office Action mailed Mar. 7, 2012.
U.S. Appl. No. 12/117,698, Office Action mailed Nov. 13, 2012.
U.S. Appl. No. 12/117,698, Office Action mailed Sep. 15, 2010.
U.S. Appl. No. 12/495,219, Notice of Allowance mailed Nov. 8, 2013.
U.S. Appl. No. 12/495,219, Office Action mailed Jun. 25, 2010.
U.S. Appl. No. 12/495,219, Office Action mailed Mar. 8, 2011.
U.S. Appl. No. 12/550,208, Advisory Action mailed Dec. 6, 2012.
U.S. Appl. No. 12/550,208, Office Action mailed Apr. 12, 2012.
U.S. Appl. No. 12/550,208, Office Action mailed Dec. 31, 2013.
U.S. Appl. No. 12/550,208, Office Action mailed Mar. 20, 2013.
U.S. Appl. No. 12/550,357, Notice of Allowance mailed Dec. 29, 2011.
U.S. Appl. No. 12/550,357, Office Action mailed Jan. 25, 2011.
U.S. Appl. No. 12/550,357, Office Action mailed Jul. 20, 2011.
U.S. Appl. No. 13/089,309, Notice of Allowance mailed Sep. 17, 2012.
U.S. Appl. No. 13/089,309, Office Action mailed Feb. 24, 2012.
U.S. Appl. No. 13/555,066, Notice of Allowance mailed Aug. 6, 2013.
U.S. Appl. No. 13/555,066, Office Action mailed Dec. 28, 2012.
U.S. Appl. No. 13/906,288, Office Action mailed May 28, 2014.
U.S. Appl. No. 13/906,288, Office Action mailed Oct. 25, 2013.
U.S. Appl. No. 13/914,555, Office Action mailed Jan. 7, 2014.
U.S. Appl. No. 14/678,226, Notice of Allowance mailed Feb. 24, 2016.
U.S. Appl. No. 14/928,395, Office Action mailed May 6, 2016.
U.S. Appl. No. 14/928,395, Office Action mailed Nov. 16, 2016.
Canadian Patent Application No. 2686641, Examiner's Report mailed Jan. 3, 2017.


105
DATA PROCESSING TERMINAL/ INFUSION SECTION
104
PRIMARY RECEIVER UNIT
106
SECONDARY RECEIVER UNIT
103
102
TRANSMITTER UNIT
101
SENSOR

100

FIGURE 1


TO RECEIVER UNIT 104
SERIAL COMMUNICATION SECTION
RF TRANSMITTER
POWER SUPPLY
PROCESSOR
ANALOG INTERFACE
LEAK DETECTION CIRCUIT
USER INPUT
TEMPERATURE MEASUREMENT SECTION
CLOCK
W
G
R
C
201
202
203
204
205
206
207
208
209
210
211
212
213
214
102

FIGURE 2


TO DATA PROCESSING TERMINAL 105
309
SERIAL COMMUNICATION SECTION
OUTPUT/DISPLAY
310
POWER SUPPLY
306
307
PROCESSING & STORAGE
POWER CONVERSION AND MONITORING SECTION
308
104
TEST STRIP INTERFACE
RF RECEIVER
USER INPUT
TEMPERATURE MONITOR SECTION
CLOCK
301
302
303
304
305
FROM TRANSMITTER UNIT 102

FIGURE 3


START
INITIALIZE COUNTER:
T = 0
- 410
RETRIEVE ROLLING DATA
AT T
- 420
RETRIEVE TIME SENSITIVE
DATA
- 430
GENERATE DATA PACKET FOR
TRANSMISSION
- 440
INCREMENT T = T + 1
- 450

FIGURE 4


START
RECEIVE DATA PACKET - 510
PARSE RECEIVED DATA PACKET INTO ROLLING DATA AND TIME SENSITIVE DATA - 520
STORE PARSED DATA - 530
END

FIGURE 5


Antenna
Rf Transmitter (FSK)
Close Proximity Receiver (OOK)
Storage Capacitor
620
624
CPU
Electronic Switch
622
Ultra Low Power Voltage Comparator
COUNTER
AMP
623
621
Battery
Sensor Current to Frequency
R1
R2
WRK
REF
CNTR
GRD
R trace
610
611
SENSOR

FIGURE 6


START
RETRIEVE A CLOSE PROXIMITY COMMAND FOR TRANSMISSION - 710
ESTABLISH TRANSMISSION RANGE - 720
TRANSMIT THE CLOSE PROXIMITY COMMAND WHILE WITHIN THE ESTABLISHED TRANSMISSION RANGE - 730
RECEIVE PACKET IN RESPONSE TO THE CLOSE PROXIMITY COMMAND - 740
GENERATE A KEY BASED ON THE RECEIVED PACKET - 750
END

FIGURE 7


START
DETECT CONNECTION TO SENSOR - 810
EXIT POWER DOWN MODE - 820
RECEIVE AND PROCESS SENSOR SIGNAL - 830
TRANSMIT PROCESSED SENSOR SIGNAL - 840
END

FIGURE 8


START
DETECT SENSOR REMOVAL - 910
GENERATE STATUS SIGNAL - 920
TRANSMIT GENERATED STATUS SIGNAL - 930
ENTER POWER DOWN MODE - 940
END

FIGURE 9


START
RECEIVE SENSOR INITIATE COMMAND - 1010
RETRIEVE AND TRANSMIT IDENTIFICATION INFORMATION - 1020
RECEIVE COMMUNICATION KEY - 1030
TRANSMIT SENSOR RELATED DATA WITH KEY - 1040
END

FIGURE 10


START
TRANSMIT SENSOR INITIATE COMMAND - 1110
RECEIVE TRANSMITTER IDENTIFICATION INFORMATION - 1120
GENERATE AND TRANSMIT COMMUNICATION KEY - 1130
END

FIGURE 11


START
DETECT PERIODIC DATA TRANSMISSION - 1210
INCREMENT A COUNT FOR EACH DETECTED DATA TRANSMISSION - 1220
PERIODICALLY TRANSMIT THE COUNT - 1230
STORE THE COUNT - 1240
END

FIGURE 12


START
RECEIVE A CLOSE PROXIMITY COMMAND - 1310
DETERMINE COMMUNICATION STATUS - 1320
MODIFY THE COMMUNICATION STATUS BASED ON THE RECEIVED COMMAND - 1330
END

FIGURE 13


START
RECEIVE SENSOR COUNTER INFORMATION - 1410
RETRIEVE STORED SENSOR COUNTER INFORMATION - 1420
COMPARE THE RECEIVED SENSOR COUNTER INFORMATION WITH THE RETRIEVED SENSOR COUNTER INFORMATION - 1430
GENERATE AND OUTPUT SIGNAL BASED ON THE COMPARISON - 1440
END

FIGURE 14


START
INITIATION OF SENSOR
1510
COUNT TEMPORALLY ASSOCIATED WITH INITIATION OF SENSOR
1520
STORE COUNT ASSOCIATED WITH INITIATION OF SENSOR (COUNT 1)
1530
STORE COUNT ASSOCIATED WITH INITIATION OF SENSOR (COUNT 2) IF A FAULT CONDITION EVENT OCCURS
1540
DETERMINE ELAPSED SENSOR LIFE (COUNT 2 - COUNT 1)
1550
OUTPUT MESSAGE
1560
END
RESTART TIMER
1570

FIGURE 15


T=0
1610
INCREMENT HOBBS COUNTER: T = T+1
1620
SENSOR = NEW?
1630
No
Yes
INCREMENT SENSOR COUNTER: S = S+1
1640
$T_{NEWSENSOR} = T$
1650
SAVE S AND $T_{NEWSENSOR}$
1660
$T - T_{NEWSENSOR} < T_{LIFE}$?
1670
No
ALARM
1680
Yes

FIGURE 16

METHOD AND DEVICE FOR DETERMINING ELAPSED SENSOR LIFE

RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 12/495,219 filed Jun. 30, 2009, now U.S. Pat. No. 8,665,091, which is a continuation-in-part application of U.S. patent application Ser. No. 12/117,681, filed May 8, 2008, now U.S. Pat. No. 8,461,985, entitled "Analyte Monitoring System and Methods," which claims priority under 35 U.S.C. §119(e) to U.S. provisional application No. 60/916,744 filed May 8, 2007, entitled "Analyte Monitoring System and Methods", the disclosures of each of which are incorporated herein by reference for all purposes.

BACKGROUND

The potential for severe complications caused by persistent high analyte levels and analyte fluctuations has provided the impetus to develop data monitoring and management systems. In this regard, attempts have been made to detect and monitor certain analyte levels, e.g., glucose, with the use of analyte monitoring systems designed to continuously or semi-continuously monitor analyte data from a subject. The analyte monitoring systems often include a sensor configured to detect analyte levels and generate signals corresponding to the detected analyte signals. In some analyte monitoring systems, the sensor is inserted in the body of the subject. Typically, such sensors have a sensor life of about a week. Thus, the sensor must be replaced periodically for continuous analyte detection and monitoring.

Occasionally, data monitoring systems undergo a fault condition, such as for example a power loss, power shutdown, Watchdog reset, or various other system or component failures. During these fault conditions, the system often loses data and time so there is no way for the system to recognize the amount of time elapsed during the fault condition. Thus, after fault conditions, it was necessary for the user to replace the sensor even if the fault condition occurred on day 2 of a 5-day or a 7-day sensor. In addition to the financial costs of replacing a sensor that had remaining life expectancy, the new sensor must be calibrated, requiring multiple finger sticks of the user and time. In view of the foregoing, it would be desirable to have a method and apparatus for determining the elapsed sensor life and/or remaining sensor life subsequent to a fault condition in a medical communication system, so that the same sensor can be used after the fault condition.

SUMMARY

The purpose and advantages of the present invention will be set forth in and apparent from the description that follows, as well as will be learned by practice of the invention. Additional advantages of the invention will be realized and attained by the methods and systems particularly pointed out in the written description and claims hereof, as well as from the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the invention, as embodied herein and broadly described, the invention includes devices and methods for analyte monitoring, for example but not limited to, glucose monitoring. In accordance with one aspect of the invention, a method is provided for operating an analyte monitoring system. The method includes providing a signal associated with initiation of an analyte sensor and providing

a count from an incrementing counter. The method further includes storing a count that is temporally associated with the signal associated with initiation of the analyte sensor. In one embodiment, initiation of the sensor and signal occurs after placement of the sensor, e.g., transcutaneous implantation or insertion of the sensor to a user. In this regard, the first count commensurate with sensor initiation is saved, for example, in a memory unit, such as a non-volatile memory. After the first count is stored, the counter continues to incrementally count. The incremental count can be based on a periodic cycle associated with calculation of an analyte measurement by the analyte sensor. The periodic cycle can be based on a time interval, e.g., every 30 or 60 seconds, and/or provided in data packets. The periodic calculations of analyte can be transmitted via the data packets to a receiver or transceiver, as rolling data every period.

In accordance with the invention, the method provides a way to determine elapsed (or remaining) sensor life for a particular sensor, for example, by a comparison between the stored first count and the incremental count based on periodic cycles. Further, the elapsed time can be used to restart a sensor life timer and/or calibration timer, if desired.

In a further aspect of the invention, a second signal can be provided, wherein the second signal temporally associated with a second initiation of an analyte is stored, if a fault conditions occurs. In this regard, the elapsed time of the sensor can be determined by a comparison of the stored counts for the first and second signals that are temporally associated with initiation of the sensor and re-initiation of the sensor after the occurrence of a fault condition. For example, but not limitation, a system failure includes a battery drain, power shut-down (voluntary or involuntary), system reset.

In another aspect of the invention, the method includes providing a second counter that incrementally counts each time a new sensor is initialized. Thus, the method includes a first counter that incrementally counts and a second counter that only incrementally counts when a sensor is initialized. In this regard, the second counter can provide information regarding how many sensors have been employed (or initialized) in the data monitoring system.

In one embodiment, the second counter can be used in conjunction with the first counter to determine the elapsed time for a particular sensor. In this regard, the incremental count of the first counter, such as a Hobbs counter provides an indication of time duration, while the second counter, such as a sensor counter, can provide information regarding the occurrence of sensor initiation. In this regard, the count of the Hobbs counter is saved when the sensor counter indicates initiation of a sensor. Thus, the two counters, i.e., a comparison of information derived from both the first counter and the second counter, can be used to determine the elapsed time of an employed sensor.

In another aspect of the invention, a data processing device configured to determine elapsed life of a sensor is provided. The data processing device includes a data processing section coupled to a data communication unit and at least one counter, e.g., Hobbs counter. In accordance with one aspect of the invention, the elapsed life of a sensor is determined by comparing the stored count with the incremented count. In another embodiment, the data processing device includes two counters, e.g., a Hobbs counter and a sensor counter. Elapsed life can be determined by comparing the counts of both counters in conjunction with each other.

The data processing device can further include a storage unit such as a non-volatile memory unit to store the count. The non-volatile memory unit can be disposed in a trans-

mitter or a receiver unit. Further, the data processing device can include an output unit for outputting a message, such as date and time of sensor expiration, data and time for next calibration, or a value derived from the count information, such as remaining life of the sensor. A method further includes displaying a value derived or otherwise associated with the stored count, and/or the incremented count on a display unit. Further, the output unit can be configured to display an alarm when a calibration is needed, and/or when the sensor is close to expiration. The output unit includes one or more of a visual, audible or tactile output. In accordance with one embodiment, the display unit can be a receiver or, if desired, a transmitter. In one embodiment, the display is an OLED color display.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and are intended to provide further explanation of the invention claimed. The accompanying drawings are included to illustrate and provide a further understanding of the method and device of the invention. Together with the description, the drawings serve to explain the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** illustrates a block diagram of a data monitoring and management system for practicing one or more embodiments of the present invention;

FIG. **2** is a block diagram of the transmitter unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present invention;

FIG. **3** is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present invention;

FIG. **4** is a flowchart illustrating data packet procedure including rolling data for transmission in accordance with one embodiment of the present invention;

FIG. **5** is a flowchart illustrating data processing of the received data packet including the rolling data in accordance with one embodiment of the present invention;

FIG. **6** is a block diagram illustrating the sensor and the transmitter unit of the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **7** is a flowchart illustrating data communication using close proximity commands in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **8** is a flowchart illustrating sensor insertion detection routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **9** is a flowchart illustrating sensor removal detection routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **10** is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **11** is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. **1** in accordance with another embodiment of the present invention;

FIG. **12** is a flowchart illustrating the power supply determination in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **13** is a flowchart illustrating close proximity command for RF communication control in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention;

FIG. **14** is a flowchart illustrating analyte sensor identification routine in accordance with one embodiment of the present invention;

FIG. **15** is a flowchart illustrating the analyte sensor life determination in accordance with one embodiment of the present invention; and

FIG. **16** is a flowchart illustrating the analyte sensor life determination in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION

As summarized above and as described in further detail below, in accordance with various embodiments of the invention, there are provided a method and system for operating an analyte monitoring device.

FIG. **1** illustrates a data monitoring and management system such as, for example, analyte (e.g., glucose) monitoring system **100** in accordance with one embodiment of the present invention. The subject invention is further described primarily with respect to a glucose monitoring system for convenience and such description is in no way intended to limit the scope of the invention. It is to be understood that the analyte monitoring system may be configured to monitor a variety of analytes, e.g., lactate, and the like. Analytes that may be monitored include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and troponin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be monitored. More than one analyte may be monitored by a single system, e.g. a single analyte sensor.

The analyte monitoring system **100** includes a sensor **101**, a transmitter unit **102** coupleable to the sensor **101**, and a primary receiver unit **104** which is configured to communicate with the transmitter unit **102** via a bi-directional communication link **103**. The primary receiver unit **104** may be further configured to transmit data to a data processing terminal **105** for evaluating the data received by the primary receiver unit **104**. Moreover, the data processing terminal **105** in one embodiment may be configured to receive data directly from the transmitter unit **102** via a communication link which may optionally be configured for bi-directional communication. Accordingly, transmitter unit **102** and/or receiver unit **104** may include a transceiver.

Also shown in FIG. **1** is an optional secondary receiver unit **106** which is operatively coupled to the communication link and configured to receive data transmitted from the transmitter unit **102**. Moreover, as shown in the Figure, the secondary receiver unit **106** is configured to communicate with the primary receiver unit **104** as well as the data processing terminal **105**. Indeed, the secondary receiver unit **106** may be configured for bidirectional wireless communication with each or one of the primary receiver unit **104**

and the data processing terminal **105**. As discussed in further detail below, in one embodiment of the present invention, the secondary receiver unit **106** may be configured to include a limited number of functions and features as compared with the primary receiver unit **104**. As such, the secondary receiver unit **106** may be configured substantially in a smaller compact housing or embodied in a device such as a wrist watch, pager, mobile phone, PDA, for example. Alternatively, the secondary receiver unit **106** may be configured with the same or substantially similar functionality as the primary receiver unit **104**. The receiver unit may be configured to be used in conjunction with a docking cradle unit, for example for one or more of the following or other functions: placement by bedside, for re-charging, for data management, for night time monitoring, and/or bidirectional communication device.

In one aspect, sensor **101** may include two or more sensors, each configured to communicate with transmitter unit **102**. Furthermore, while only one transmitter unit **102**, communication link **103**, and data processing terminal **105** are shown in the embodiment of the analyte monitoring system **100** illustrated in FIG. **1**, it will be appreciated by one of ordinary skill in the art that the analyte monitoring system **100** may include one or more sensors, multiple transmitter units **102**, communication links **103**, and data processing terminals **105**. Moreover, within the scope of the present invention, the analyte monitoring system **100** may be a continuous monitoring system, or semi-continuous, or a discrete monitoring system. In a multi-component environment, each device is configured to be uniquely identified by each of the other devices in the system so that communication conflict is readily resolved between the various components within the analyte monitoring system **100**.

In one embodiment of the present invention, the sensor **101** is physically positioned in or on the body of a user whose analyte level is being monitored. The sensor **101** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level into a corresponding data signal for transmission by the transmitter unit **102**. In certain embodiments, the transmitter unit **102** may be physically coupled to the sensor **101** so that both devices are integrated in a single housing and positioned on the user's body. The transmitter unit **102** may perform data processing such as filtering and encoding on data signals and/or other functions, each of which corresponds to a sampled analyte level of the user, and in any event transmitter unit **102** transmits analyte information to the primary receiver unit **104** via the communication link **103**.

In one embodiment, the analyte monitoring system **100** is configured as a one-way RF communication path from the transmitter unit **102** to the primary receiver unit **104**. In such embodiment, the transmitter unit **102** transmits the sampled data signals received from the sensor **101** without acknowledgement from the primary receiver unit **104** that the transmitted sampled data signals have been received. For example, the transmitter unit **102** may be configured to transmit the encoded sampled data signals at a fixed rate (e.g., at one minute intervals) after the completion of the initial power on procedure. Likewise, the primary receiver unit **104** may be configured to detect such transmitted encoded sampled data signals at predetermined time intervals. Alternatively, the analyte monitoring system **100** may be configured with a bi-directional RF (or otherwise) communication between the transmitter unit **102** and the primary receiver unit **104**.

Additionally, in one aspect, the primary receiver unit **104** may include two sections. The first section is an analog interface section that is configured to communicate with the transmitter unit **102** via the communication link **103**. In one embodiment, the analog interface section may include an RF receiver and an antenna for receiving and amplifying the data signals from the transmitter unit **102**, which are thereafter, demodulated with a local oscillator and filtered through a band-pass filter. The second section of the primary receiver unit **104** is a data processing section which is configured to process the data signals received from the transmitter unit **102** such as by performing data decoding, error detection and correction, data clock generation, and data bit recovery.

In operation, upon completing the power-on procedure, the primary receiver unit **104** is configured to detect the presence of the transmitter unit **102** within its range based on, for example, the strength of the detected data signals received from the transmitter unit **102** and/or predetermined transmitter identification information. Upon successful synchronization with the corresponding transmitter unit **102**, the primary receiver unit **104** is configured to begin receiving from the transmitter unit **102** data signals corresponding to the user's detected analyte level. More specifically, the primary receiver unit **104** in one embodiment is configured to perform synchronized time hopping with the corresponding synchronized transmitter unit **102** via the communication link **103** to obtain the user's detected analyte level.

Referring again to FIG. **1**, the data processing terminal **105** may include a personal computer, a portable computer such as a laptop or a handheld device (e.g., personal digital assistants (PDAs)), and the like, each of which may be configured for data communication with the receiver via a wired or a wireless connection. Additionally, the data processing terminal **105** may further be connected to a data network (not shown) for storing, retrieving and updating data corresponding to the detected analyte level of the user.

Within the scope of the present invention, the data processing terminal **105** may include an infusion device such as an insulin infusion pump (external or implantable) or the like, which may be configured to administer insulin to patients, and which may be configured to communicate with the receiver unit **104** for receiving, among others, the measured analyte level. Alternatively, the receiver unit **104** may be configured to integrate or otherwise couple to an infusion device therein so that the receiver unit **104** is configured to administer insulin therapy to patients, for example, for administering and modifying basal profiles, as well as for determining appropriate boluses for administration based on, among others, the detected analyte levels received from the transmitter unit **102**.

Additionally, the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may each be configured for bidirectional wireless communication such that each of the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may be configured to communicate (that is, transmit data to and receive data from) with each other via the wireless communication link **103**. More specifically, the data processing terminal **105** may in one embodiment be configured to receive data directly from the transmitter unit **102** via a communication link, where the communication link, as described above, may be configured for bi-directional communication.

In this embodiment, the data processing terminal **105** which may include an insulin pump, may be configured to receive the analyte signals from the transmitter unit **102**, and thus, incorporate the functions of the receiver unit **104** including data processing for managing the patient's insulin

therapy and analyte monitoring. In one embodiment, the communication link **103** may include one or more of an RF communication protocol, an infrared communication protocol, a Bluetooth® enabled communication protocol, an 802.11x wireless communication protocol, or an equivalent wireless communication protocol which would allow secure, wireless communication of several units (for example, per HIPAA requirements) while avoiding potential data collision and interference.

FIG. **2** is a block diagram of the transmitter of the data monitoring and detection system shown in FIG. **1** in accordance with one embodiment of the present invention. Referring to the Figure, the transmitter unit **102** in one embodiment includes an analog interface **201** configured to communicate with the sensor **101** (FIG. **1**), a user input **202**, and a temperature detection section **203**, each of which is operatively coupled to a transmitter processor **204** such as a central processing unit (CPU). As can be seen from FIG. **2**, there are provided four contacts, three of which are electrodes—work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213**, each operatively coupled to the analog interface **201** of the transmitter unit **102** for connection to the sensor **101** (FIG. **1**). In one embodiment, each of the work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213** may be made using a conductive material that is either printed or etched or ablated, for example, such as carbon which may be printed, or a metal such as a metal foil (e.g., gold) or the like, which may be etched or ablated or otherwise processed to provide one or more electrodes. Fewer or greater electrodes and/or contact may be provided in certain embodiments.

Further shown in FIG. **2** are a transmitter serial communication section **205** and an RF transmitter **206**, each of which is also operatively coupled to the transmitter processor **204**. Moreover, a power supply **207** such as a battery is also provided in the transmitter unit **102** to provide the necessary power for the transmitter unit **102**.

Additionally, as can be seen from the Figure, clock **208** is provided to, among others, supply real time information to the transmitter processor **204**.

In one embodiment, a unidirectional input path is established from the sensor **101** (FIG. **1**) and/or manufacturing and testing equipment to the analog interface **201** of the transmitter unit **102**, while a unidirectional output is established from the output of the RF transmitter **206** of the transmitter unit **102** for transmission to the primary receiver unit **104**. In this manner, a data path is shown in FIG. **2** between the aforementioned unidirectional input and output via a dedicated link **209** from the analog interface **201** to serial communication section **205**, thereafter to the processor **204**, and then to the RF transmitter **206**. As such, in one embodiment, via the data path described above, the transmitter unit **102** is configured to transmit to the primary receiver unit **104** (FIG. **1**), via the communication link **103** (FIG. **1**), processed and encoded data signals received from the sensor **101** (FIG. **1**). Additionally, the unidirectional communication data path between the analog interface **201** and the RF transmitter **206** discussed above allows for the configuration of the transmitter unit **102** for operation upon completion of the manufacturing process as well as for direct communication for diagnostic and testing purposes.

As discussed above, the transmitter processor **204** is configured to transmit control signals to the various sections of the transmitter unit **102** during the operation of the transmitter unit **102**. In one embodiment, the transmitter processor **204** also includes a memory (not shown) for storing data such as the identification information for the transmitter unit **102**, as well as the data signals received from the sensor **101**. The stored information may be retrieved and processed for transmission to the primary receiver unit **104** under the control of the transmitter processor **204**. Furthermore, the power supply **207** may include a commercially available battery, which may be a rechargeable battery.

In certain embodiments, the transmitter unit **102** is also configured such that the power supply section **207** is capable of providing power to the transmitter for a minimum of about three months of continuous operation, e.g., after having been stored for about eighteen months such as stored in a low-power (non-operating) mode. In one embodiment, this may be achieved by the transmitter processor **204** operating in low power modes in the non-operating state, for example, drawing no more than approximately 1 μA of current. Indeed, in one embodiment, a step during the manufacturing process of the transmitter unit **102** may place the transmitter unit **102** in the lower power, non-operating state (i.e., post-manufacture sleep mode). In this manner, the shelf life of the transmitter unit **102** may be significantly improved. Moreover, as shown in FIG. **2**, while the power supply unit **207** is shown as coupled to the processor **204**, and as such, the processor **204** is configured to provide control of the power supply unit **207**, it should be noted that within the scope of the present invention, the power supply unit **207** is configured to provide the necessary power to each of the components of the transmitter unit **102** shown in FIG. **2**.

Referring back to FIG. **2**, the power supply section **207** of the transmitter unit **102** in one embodiment may include a rechargeable battery unit that may be recharged by a separate power supply recharging unit (for example, provided in the receiver unit **104**) so that the transmitter unit **102** may be powered for a longer period of usage time. Moreover, in one embodiment, the transmitter unit **102** may be configured without a battery in the power supply section **207**, in which case the transmitter unit **102** may be configured to receive power from an external power supply source (for example, a battery) as discussed in further detail below.

Referring yet again to FIG. **2**, the temperature detection section **203** of the transmitter unit **102** is configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust the analyte readings obtained from the analog interface **201**. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 315 MHz to approximately 322 MHz, for example, in the United States. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 400 MHz to approximately 470 MHz. Further, in one embodiment, the RF transmitter **206** is configured to modulate the carrier frequency by performing Frequency Shift Keying and Manchester encoding. In one embodiment, the data transmission rate is about 19,200 symbols per second, with a minimum transmission range for communication with the primary receiver unit **104**.

Referring yet again to FIG. **2**, also shown is a leak detection circuit **214** coupled to the guard contact (G) **211** and the processor **204** in the transmitter unit **102** of the data monitoring and management system **100**. The leak detection circuit **214** in accordance with one embodiment of the present invention may be configured to detect leakage current in the sensor **101** to determine whether the measured sensor data are corrupt or whether the measured data from

the sensor **101** is accurate. Exemplary analyte systems that may be employed are described in, for example, U.S. Pat. Nos. 6,134,461, 6,175,752, 6,121,611, 6,560,471, 6,746,582, and elsewhere, the disclosure of each of which are incorporated by reference for all purposes.

FIG. **3** is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **3**, the primary receiver unit **104** includes an analyte test strip, e.g., blood glucose test strip, interface **301**, an RF receiver **302**, an input **303**, a temperature detection section **304**, and a clock **305**, each of which is operatively coupled to a receiver processor **307**. As can be further seen from the Figure, the primary receiver unit **104** also includes a power supply **306** operatively coupled to a power conversion and monitoring section **308**. Further, the power conversion and monitoring section **308** is also coupled to the receiver processor **307**. Moreover, also shown are a receiver serial communication section **309**, and an output **310**, each operatively coupled to the receiver processor **307**.

In one embodiment, the test strip interface **301** includes a glucose level testing portion to receive a manual insertion of a glucose test strip, and thereby determine and display the glucose level of the test strip on the output **310** of the primary receiver unit **104**. This manual testing of glucose may be used to calibrate the sensor **101** or otherwise. The RF receiver **302** is configured to communicate, via the communication link **103** (FIG. **1**) with the RF transmitter **206** of the transmitter unit **102**, to receive encoded data signals from the transmitter unit **102** for, among others, signal mixing, demodulation, and other data processing. The input **303** of the primary receiver unit **104** is configured to allow the user to enter information into the primary receiver unit **104** as needed. In one aspect, the input **303** may include one or more keys of a keypad, a touch-sensitive screen, or a voice-activated input command unit. The temperature detection section **304** is configured to provide temperature information of the primary receiver unit **104** to the receiver processor **307**, while the clock **305** provides, among others, real time information to the receiver processor **307**.

Each of the various components of the primary receiver unit **104** shown in FIG. **3** is powered by the power supply **306** which, in one embodiment, includes a battery. Furthermore, the power conversion and monitoring section **308** is configured to monitor the power usage by the various components in the primary receiver unit **104** for effective power management and to alert the user, for example, in the event of power usage which renders the primary receiver unit **104** in sub-optimal operating conditions. An example of such sub-optimal operating condition may include, for example, operating the vibration output mode (as discussed below) for a period of time thus substantially draining the power supply **306** while the processor **307** (thus, the primary receiver unit **104**) is turned on. Moreover, the power conversion and monitoring section **308** may additionally be configured to include a reverse polarity protection circuit such as a field effect transistor (FET) configured as a battery activated switch.

The serial communication section **309** in the primary receiver unit **104** is configured to provide a bi-directional communication path from the testing and/or manufacturing equipment for, among others, initialization, testing, and configuration of the primary receiver unit **104**. Serial communication section **309** can also be used to upload data to a computer, such as time-stamped blood glucose data. The communication link with an external device (not shown) can be made, for example, by cable, infrared (IR) or RF link. The output **310** of the primary receiver unit **104** is configured to provide, among others, a graphical user interface (GUI) such as a liquid crystal display (LCD) for displaying information. Additionally, the output **310** may also include an integrated speaker for outputting audible signals as well as to provide vibration output as commonly found in handheld electronic devices, such as mobile telephones presently available. In a further embodiment, the primary receiver unit **104** also includes an electro-luminescent lamp configured to provide backlighting to the output **310** for output visual display in dark ambient surroundings.

Referring back to FIG. **3**, the primary receiver unit **104** in one embodiment may also include a storage section such as a programmable, non-volatile memory device as part of the processor **307**, or provided separately in the primary receiver unit **104**, operatively coupled to the processor **307**. The processor **307** may be configured to synchronize with a transmitter, e.g., using Manchester decoding or the like, as well as error detection and correction upon the encoded data signals received from the transmitter unit **102** via the communication link **103**.

Additional description of the RF communication between the transmitter unit **102** and the primary receiver unit **104** (or with the secondary receiver unit **106**) that may be employed in embodiments of the subject invention is disclosed in .U.S. patent application Ser. No. 11/060,365 filed Feb. 16, 2005, now U.S. Pat. No. 8,771,183 entitled "Method and System for Providing Data Communication in Continuous Glucose Monitoring and Management System" the disclosure of which is incorporated herein by reference for all purposes.

Referring to the Figures, in one embodiment, the transmitter unit **102** (FIG. **1**) may be configured to generate data packets for periodic transmission to one or more of the receiver units **104**, **106**, where each data packet includes in one embodiment two categories of data—urgent data and non-urgent data. For example, urgent data such as for example glucose data from the sensor and/or temperature data associated with the sensor may be packed in each data packet in addition to non-urgent data, where the non-urgent data is rolled or varied with each data packet transmission.

That is, the non-urgent data is transmitted at a timed interval so as to maintain the integrity of the analyte monitoring system without being transmitted over the RF communication link with each data transmission packet from the transmitter unit **102**. In this manner, the non-urgent data, for example that are not time sensitive, may be periodically transmitted (and not with each data packet transmission) or broken up into predetermined number of segments and sent or transmitted over multiple packets, while the urgent data is transmitted substantially in its entirety with each data transmission.

Referring again to the Figures, upon receiving the data packets from the transmitter unit **102**, the one or more receiver units **104**, **106** may be configured to parse the received data packet to separate the urgent data from the non-urgent data, and also, may be configured to store the urgent data and the non-urgent data, e.g., in a hierarchical manner. In accordance with the particular configuration of the data packet or the data transmission protocol, more or less data may be transmitted as part of the urgent data, or the non-urgent rolling data. That is, within the scope of the present disclosure, the specific data packet implementation such as the number of bits per packet, and the like, may vary based on, among others, the communication protocol, data transmission time window, and so on.

In an exemplary embodiment, different types of data packets may be identified accordingly. For example, identification in certain exemplary embodiments may include—(1) single sensor, one minute of data, (2) two or multiple sensors, (3) dual sensor, alternate one minute data, and (4) response packet. For single sensor one minute data packet, in one embodiment, the transmitter unit **102** may be configured to generate the data packet in the manner, or similar to the manner, shown in Table 1 below.

TABLE 1

Single Sensor, One Minute of Data	
Number of Bits	Data Field
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 1 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling-Data-1

As shown in Table 1 above, the transmitter data packet in one embodiment may include 8 bits of transmit time data, 14 bits of current sensor data, 14 bits of preceding sensor data, 8 bits of transmitter status data, 12 bits of auxiliary counter data, 12 bits of auxiliary thermistor 1 data, 12 bits of auxiliary thermistor 1 data and 8 bits of rolling data. In one embodiment of the present invention, the data packet generated by the transmitter for transmission over the RF communication link may include all or some of the data shown above in Table 1.

Referring back, the 14 bits of the current sensor data provides the real time or current sensor data associated with the detected analyte level, while the 14 bits of the sensor historic or preceding sensor data includes the sensor data associated with the detected analyte level one minute ago. In this manner, in the case where the receiver unit **104**, **106** drops or fails to successfully receive the data packet from the transmitter unit **102** in the minute by minute transmission, the receiver unit **104**, **106** may be able to capture the sensor data of a prior minute transmission from a subsequent minute transmission.

Referring again to Table 1, the Auxiliary data in one embodiment may include one or more of the patient's skin temperature data, a temperature gradient data, reference data, and counter electrode voltage. The transmitter status field may include status data that is configured to indicate corrupt data for the current transmission (for example, if shown as BAD status (as opposed to GOOD status which indicates that the data in the current transmission is not corrupt)). Furthermore, the rolling data field is configured to include the non-urgent data, and in one embodiment, may be associated with the time-hop sequence number. In addition, the Transmitter Time field in one embodiment includes a protocol value that is configured to start at zero and is incremented by one with each data packet. In one aspect, the transmitter time data may be used to synchronize the data transmission window with the receiver unit **104**, **106**, and also, provide an index for the Rolling data field.

In a further embodiment, the transmitter data packet may be configured to provide or transmit analyte sensor data from two or more independent analyte sensors. The sensors may relate to the same or different analyte or property. In such a case, the data packet from the transmitter unit **102** may be configured to include 14 bits of the current sensor data from both sensors in the embodiment in which 2 sensors are employed. In this case, the data packet does not include the immediately preceding sensor data in the current data packet transmission. Instead, a second analyte sensor data is transmitted with a first analyte sensor data.

TABLE 2

Dual Sensor Data	
Number of Bits	Data Field
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 2 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling-Data-1

In a further embodiment, the transmitter data packet may be alternated with each transmission between two analyte sensors, for example, alternating between the data packet shown in Table 3 and Table 4 below.

TABLE 3

Sensor Data Packet Alternate 1	
Number of Bits	Data Field
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 1 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling-Data-1

TABLE 4

Sensor Data Packet Alternate 2	
Number of Bits	Data Field
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 2 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling-Data-1

As shown above in reference to Tables 3 and 4, the minute by minute data packet transmission from the transmitter unit **102** (FIG. **1**) in one embodiment may alternate between the data packet shown in Table 3 and the data packet shown in Table 4. More specifically, the transmitter unit **102** may be configured in one embodiment to transmit the current sensor data of the first sensor and the preceding sensor data of the first sensor (Table 3), as well as the rolling data, and further, at the subsequent transmission, the transmitter unit **102** may be configured to transmit the current sensor data of the first and the second sensor in addition to the rolling data (Table 4).

In one embodiment, the rolling data transmitted with each data packet may include a sequence of various predetermined types of data that are considered not-urgent or not time sensitive. That is, in one embodiment, the following list

of data shown in Table 5 may be sequentially included in the 8 bits of transmitter data packet, and not transmitted with each data packet transmission of the transmitter (for example, with each 60 second data transmission from the transmitter unit **102**).

TABLE 5

Rolling Data		
Time Slot	Bits	Rolling Data
0	8	Mode
1	8	Glucose 1 Slope
2	8	Glucose 2 Slope
3	8	Ref-R
4	8	Hobbs Counter, Ref-R
5	8	Hobbs Counter
6	8	Hobbs Counter
7	8	Sensor Count

As can be seen from Table 5 above, in one embodiment, a sequence of rolling data are appended or added to the transmitter data packet with each data transmission time slot. In one embodiment, there may be 256 time slots for data transmission by the transmitter unit **102** (FIG. **1**), and where, each time slot is separated by approximately 60 second interval. For example, referring to the Table 5 above, the data packet in transmission time slot 0 (zero) may include operational mode data (Mode) as the rolling data that is appended to the transmitted data packet. At the subsequent data transmission time slot (for example, approximately 60 seconds after the initial time slot (0)), the transmitted data packet may include the analyte sensor **1** calibration factor information (Glucose 1 slope) as the rolling data. In this manner, with each data transmission, the rolling data may be updated over the 256 time slot cycle.

Referring again to Table 5, each rolling data field is described in further detail for various embodiments. For example, the Mode data may include information related to the different operating modes such as, but not limited to, the data packet type, the type of battery used, diagnostic routines, single sensor or multiple sensor input, or type of data transmission (RF communication link or other data link such as serial connection). Further, the Glucose 1-slope data may include an 8-bit scaling factor or calibration data for first sensor (scaling factor for sensor **1** data), while Glucose 2-slope data may include an 8-bit scaling factor or calibration data for the second analyte sensor (in the embodiment including more than one analyte sensors).

In addition, the Ref-R data may include 12 bits of on-board reference resistor used to calibrate the temperature measurement in the thermistor circuit (where 8 bits are transmitted in time slot **3**, and the remaining 4 bits are transmitted in time slot **4**), and the 20-bit Hobbs counter data may be separately transmitted in three time slots (for example, in time slot **4**, time slot **5** and time slot **6**) to add up to 20 bits. In one embodiment, the Hobbs counter may be configured to count each occurrence of the data transmission (for example, a packet transmission at approximately 60 second intervals) and may be incremented by a count of one (1).

In one aspect, the Hobbs counter is stored in a nonvolatile memory of the transmitter unit **102** (FIG. **1**) and may be used to ascertain the power supply status information such as, for example, the estimated battery life remaining in the transmitter unit **102**. That is, with each sensor replacement, the Hobbs counter is not reset, but rather, continues the count with each replacement of the sensor **101** to establish contact with the transmitter unit **102** such that, over an extended usage time period of the transmitter unit **102**, it may be possible to determine, based on the Hobbs count information, the amount of consumed battery life in the transmitter unit **102**, and also, an estimated remaining life of the battery in the transmitter unit **102**.

That is, in one embodiment, the 20 bit Hobbs counter is incremented by one each time the transmitter unit **102** transmits a data packet (for example, approximately each 60 seconds), and based on the count information in the Hobbs counter, in one aspect, the battery life of the transmitter unit **102** may be estimated. In this manner, in configurations of the transmitter unit **620** (see FIG. **6**) where the power supply is not a replaceable component but rather, embedded within the housing the transmitter unit **620**, it is possible to estimate the remaining life of the embedded battery within the transmitter unit **620**. Moreover, the Hobbs counter is configured to remain persistent in the memory device of the transmitter unit **620** such that, even when the transmitter unit power is turned off or powered down (for example, during the periodic sensor replacement, RF transmission turned off period and the like), the Hobbs counter information is retained.

Referring to Table 5 above, the transmitted rolling data may also include 8 bits of sensor count information (for example, transmitted in time slot **7**). The 8 bit sensor counter is incremented by one each time a new sensor is connected to the transmitter unit. The ASIC configuration of the transmitter unit (or a microprocessor based transmitter configuration or with discrete components) may be configured to store in a nonvolatile memory unit the sensor count information and transmit it to the primary receiver unit **104** (for example). In turn, the primary receiver unit **104** (and/or the secondary receiver unit **106**) may be configured to determine whether it is receiving data from the transmitter unit that is associated with the same sensor (based on the sensor count information), or from a new or replaced sensor (which will have a sensor count incremented by one from the prior sensor count). In this manner, in one aspect, the receiver unit (primary or secondary) may be configured to prevent reuse of the same sensor by the user based on verifying the sensor count information associated with the data transmission received from the transmitter unit **102**. In addition, in a further aspect, user notification may be associated with one or more of these parameters. Further, the receiver unit (primary or secondary) may be configured to detect when a new sensor has been inserted, and thus prevent erroneous application of one or more calibration parameters determined in conjunction with a prior sensor, that may potentially result in false or inaccurate analyte level determination based on the sensor data.

FIG. **4** is a flowchart illustrating a data packet procedure including rolling data for transmission in accordance with one embodiment of the present invention. Referring to FIG. **4**, in one embodiment, a counter is initialized (for example, to T=0) (**410**). Thereafter the associated rolling data is retrieved from memory device, for example (**420**), and also, the time sensitive or urgent data is retrieved (**430**). In one embodiment, the retrieval of the rolling data (**420**) and the retrieval of the time sensitive data (**430**) may be retrieved at substantially the same time.

Referring back to FIG. **4**, with the rolling data and the time sensitive data, for example, the data packet for transmission is generated (**440**), and upon transmission, the counter is incremented by one (**450**) and the routine returns to retrieval of the rolling data (**420**). In this manner, in one embodiment, the urgent time sensitive data as well as the

non-urgent data may be incorporated in the same data packet and transmitted by the transmitter unit **102** (FIG. **1**) to a remote device such as one or more of the receivers **104**, **106**. Furthermore, as discussed above, the rolling data may be updated at a predetermined time interval which is longer than the time interval for each data packet transmission from the transmitter unit **102** (FIG. **1**).

FIG. **5** is a flowchart illustrating data processing of the received data packet including the rolling data in accordance with one embodiment of the present invention. Referring to FIG. **5**, when the data packet is received (**510**) (for example, by one or more of the receivers **104**, **106**, in one embodiment), the received data packet is parsed so that the urgent data may be separated from the not-urgent data (stored in, for example, the rolling data field in the data packet) (**520**). Thereafter the parsed data is suitably stored in an appropriate memory or storage device (**530**).

In the manner described above, in accordance with one embodiment of the present invention, there is provided method and apparatus for separating non-urgent type data (for example, data associated with calibration) from urgent type data (for example, monitored analyte related data) to be transmitted over the communication link to minimize the potential burden or constraint on the available transmission time. More specifically, in one embodiment, non-urgent data may be separated from data that is required by the communication system to be transmitted immediately, and transmitted over the communication link together while maintaining a minimum transmission time window. In one embodiment, the non-urgent data may be parsed or broken up in to a number of data segments, and transmitted over multiple data packets. The time sensitive immediate data (for example, the analyte sensor data, temperature data, etc.), may be transmitted over the communication link substantially in its entirety with each data packet or transmission.

FIG. **6** is a block diagram illustrating the sensor and the transmitter unit of the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **6**, in one aspect, a transmitter unit **620** is provided in a substantially water tight and sealed housing. The transmitter unit **620** includes respective contacts (WRK, REF, CNTR, and GRD) for respectively establishing electrical contact with one or more of the working electrode, the reference electrode, the counter electrode and the ground terminal (or guard trace) of the sensor **610**. Also shown in FIG. **6** is a conductivity bar/trace **611** provided on the sensor **610**. For example, in one embodiment, the conductivity bar/trace **611** may comprise a carbon trace on a substrate layer of the sensor **610**. In this manner, in one embodiment, when the sensor **610** is coupled to the transmitter unit **620**, electrical contact is established, for example, via the conductivity bar/trace **611** between the contact pads or points of the transmitter unit **620** (for example, at the counter electrode contact (CNTR) and the ground terminal contact (GRD) such that the transmitter unit **620** may be powered for data communication.

That is, during manufacturing of the transmitter unit **620**, in one aspect, the transmitter unit **620** is configured to include a power supply such as battery **621**.

Further, during the initial non-use period (e.g., post manufacturing sleep mode), the transmitter unit **620** is configured such that it is not used and thus drained by the components of the transmitter unit **620**. During the sleep mode, and prior to establishing electrical contact with the sensor **610** via the conductivity bar/trace **611**, the transmitter unit **620** is provided with a low power signal from, for example, a low power voltage comparator **622**, via an electronic switch **623** to maintain the low power state of, for example, the transmitter unit **620** components. Thereafter, upon connection with the sensor **610**, and establishing electrical contact via the conductivity bar/trace **611**, the embedded power supply **621** of the transmitter unit **620** is activated or powered up so that some of all of the components of the transmitter unit **620** are configured to receive the necessary power signals for operations related to, for example, data communication, processing and/or storage.

In one aspect, since the transmitter unit **620** is configured to a sealed housing without a separate replaceable battery compartment, in this manner, the power supply of the battery **621** is preserved during the post manufacturing sleep mode prior to use.

In a further aspect, the transmitter unit **620** may be disposed or positioned on a separate on-body mounting unit that may include, for example, an adhesive layer (on its bottom surface) to firmly retain the mounting unit on the skin of the user, and which is configured to receive or firmly position the transmitter unit **620** on the mounting unit during use. In one aspect, the mounting unit may be configured to at least partially retain the position of the sensor **610** in a transcutaneous manner so that at least a portion of the sensor is in fluid contact with the analyte of the user. Example embodiments of the mounting or base unit and its cooperation or coupling with the transmitter unit are provided, for example, in U.S. Pat. No. 6,175,752, incorporated herein by reference for all purposes.

In such a configuration, the power supply for the transmitter unit **620** may be provided within the housing of the mounting unit such that, the transmitter unit **620** may be configured to be powered on or activated upon placement of the transmitter unit **620** on the mounting unit and in electrical contact with the sensor **610**. For example, the sensor **610** may be provided pre-configured or integrated with the mounting unit and the insertion device such that, the user may position the sensor **610** on the skin layer of the user using the insertion device coupled to the mounting unit. Thereafter, upon transcutaneous positioning of the sensor **610**, the insertion device may be discarded or removed from the mounting unit, leaving behind the transcutaneously positioned sensor **610** and the mounting unit on the skin surface of the user.

Thereafter, when the transmitter unit **620** is positioned on, over or within the mounting unit, the battery or power supply provided within the mounting unit is configured to electrically couple to the transmitter unit **620** and/or the sensor **610**.

Given that the sensor **610** and the mounting unit are provided as replaceable components for replacement every 3, 5, 7 days or other predetermined time periods, the user is conveniently not burdened with verifying the status of the power supply providing power to the transmitter unit **620** during use. That is, with the power supply or battery replaced with each replacement of the sensor **610**, a new power supply or battery will be provided with the new mounting unit for use with the transmitter unit **620**.

Referring to FIG. **6** again, in one aspect, when the sensor **610** is removed from the transmitter unit **620** (or vice versa), the electrical contact is broken and the conductivity bar/trace **611** returns to an open circuit. In this case, the transmitter unit **620** may be configured, to detect such condition and generate a last gasp transmission sent to the primary receiver unit **104** (and/or the secondary receiver unit **106**) indicating that the sensor **610** is disconnected from the transmitter unit **620**, and that the transmitter unit **620** is entering a powered down (or low power off) state. And the transmitter unit **620**

is powered down into the sleep mode since the connection to the power supply (that is embedded within the transmitter unit **620** housing) is broken.

In this manner, in one aspect, the processor **624** of the transmitter unit **620** may be configured to generate the appropriate one or more data or signals associated with the detection of sensor **610** disconnection for transmission to the receiver unit **104** (FIG. **1**), and also, to initiate the power down procedure of the transmitter unit **620**. In one aspect, the components of the transmitter unit **620** may be configured to include application specific integrated circuit (ASIC) design with one or more state machines and one or more nonvolatile and/or volatile memory units such as, for example, EEPROMs and the like.

Referring again to FIGS. **1** and **6**, in one embodiment, the communication between the transmitter unit **620** (or **102** of FIG. **1**) and the primary receiver unit **104** (and/or the secondary receiver unit **106**) may be based on close proximity communication where bi-directional (or uni-directional) wireless communication is established when the devices are physically located in close proximity to each other. That is, in one embodiment, the transmitter unit **620** may be configured to receive very short range commands from the primary receiver unit **104** (FIG. **1**) and perform one or more specific operations based on the received commands from the receiver unit **104**.

In one embodiment, to maintain secure communication between the transmitter unit and the data receiver unit, the transmitter unit ASIC may be configured to generate a unique close proximity key at power on or initialization. In one aspect, the 4 or 8 bit key may be generated based on, for example, the transmitter unit identification information, and which may be used to prevent undesirable or unintended communication. In a further aspect, the close proximity key may be generated by the receiver unit based on, for example, the transmitter identification information received by the transmitter unit during the initial synchronization or pairing procedure of the transmitter and the receiver units.

Referring again to FIGS. **1** and **6**, in one embodiment, the transmitter unit ASIC configuration may include a 32 KHz oscillator and a counter which may be configured to drive the state machine in the transmitter unit ASIC. The transmitter ASIC configuration may include a plurality of close proximity communication commands including, for example, new sensor initiation, pairing with the receiver unit, and RF communication control, among others. For example, when a new sensor is positioned and coupled to the transmitter unit so that the transmitter unit is powered on, the transmitter unit is configured to detect or receive a command from the receiver unit positioned in close proximity to the transmitter unit. For example, the receiver unit may be positioned within a couple of inches of the on-body position of the transmitter unit, and when the user activates or initiates a command associated with the new sensor initiation from the receiver unit, the transmitter unit is configured to receive the command from the receiver and, in its response data packet, transmit, among others, its identification information back to the receiver unit.

In one embodiment, the initial sensor initiation command does not require the use of the close proximity key. However, other predefined or preconfigured close-proximity commands may be configured to require the use of the 8 bit key (or a key of a different number of bits). For example, in one embodiment, the receiver unit may be configured to transmit a RF on/off command to turn on/off the RF communication module or unit in the transmitter unit **102**. Such RF on/off command in one embodiment includes the close proximity key as part of the transmitted command for reception by the transmitter unit.

During the period that the RF communication module or unit is turned off based on the received close proximity command, the transmitter unit does not transmit any data, including any glucose related data. In one embodiment, the glucose related data from the sensor which are not transmitted by the transmitter unit during the time period when the RF communication module or unit of the transmitter unit is turned off may be stored in a memory or storage unit of the transmitter unit for subsequent transmission to the receiver unit when the transmitter unit RF communication module or unit is turned back on based on the RF-on command from the receiver unit. In this manner, in one embodiment, the transmitter unit may be powered down (temporarily, for example, during air travel) without removing the transmitter unit from the on-body position.

FIG. **7** is a flowchart illustrating data communication using close proximity commands in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **7**, the primary receiver unit **104** (FIG. **1**) in one aspect may be configured to retrieve or generate a close proximity command (**710**) for transmission to the transmitter unit **102**. To establish the transmission range (**720**), the primary receiver unit **104** may be positioned physically close to (that is, within a predetermined distance from) the transmitter unit **102**. For example, the transmission range for the close proximity communication may be established at approximately one foot distance or less between the transmitter unit **102** and the primary receiver unit **104**. When the transmitter unit **102** and the primary receiver unit **104** are within the transmission range, the close proximity command, upon initiation from the receiver unit **104** may be transmitted to the transmitter unit **102** (**730**).

Referring back to FIG. **7**, in response to the transmitted close proximity command, a response data packet or other responsive communication may be received (**740**). In one aspect, the response data packet or other responsive communication may include identification information of the transmitter unit **102** transmitting the response data packer or other response communication to the receiver unit **104**. In one aspect, the receiver unit **104** may be configured to generate a key (for example, an 8 bit key or a key of a predetermined length) based on the transmitter identification information (**750**), and which may be used in subsequent close proximity communication between the transmitter unit **102** and the receiver unit **104**.

In one aspect, the data communication including the generated key may allow the recipient of the data communication to recognize the sender of the data communication and confirm that the sender of the data communication is the intended data sending device, and thus, including data which is desired or anticipated by the recipient of the data communication. In this manner, in one embodiment, one or more close proximity commands may be configured to include the generated key as part of the transmitted data packet. Moreover, the generated key may be based on the transmitter ID or other suitable unique information so that the receiver unit **104** may use such information for purposes of generating the unique key for the bidirectional communication between the devices.

While the description above includes generating the key based on the transmitter unit **102** identification information, within the scope of the present disclosure, the key may be generated based on one or more other information associated with the transmitter unit **102**, and/or the receiver unit com-

bination. In a further embodiment, the key may be encrypted and stored in a memory unit or storage device in the transmitter unit **102** for transmission to the receiver unit **104**.

FIG. **8** is a flowchart illustrating sensor insertion detection routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **8**, connection to an analyte sensor is detected (**810**) based on, for example, a power up procedure where the sensor conduction trace **611** (FIG. **6**) is configured to establish electrical contact with a predetermined one or more contact points on the transmitter unit **102**. That is, when the sensor **101** (for example, the electrodes of the sensor) is correspondingly connected to the contact points on the transmitter unit **102**, the transmitter unit **102** is configured to close the circuit connecting its power supply (for example, the battery **621** (FIG. **6**)) to the components of the transmitter unit **102** and thereby exiting the power down or low power state into active or power up state.

In this manner, as discussed above, in one aspect, the transmitter unit **102** may be configured to include a power supply such as a battery **621** integrally provided within the sealed housing of the transmitter unit **102**. When the transmitter unit **102** is connected or coupled to the respective electrodes of the analyte sensor that is positioned in a transcutaneous manner under the skin layer of the patient, the transmitter unit **102** is configured to wake up from its low power or sleep state (**820**), and power up the various components of the transmitter unit **102**. In the active state, the transmitter unit **102** may be further configured to receive and process sensor signals received from the analyte sensor **101** (FIG. **1**) (**830**), and thereafter, transmit the processed sensor signals (**840**) to, for example, the receiver unit **104** (FIG. **1**).

Accordingly, in one aspect, the sensor **610** (FIG. **6**) may be provided with a conduction trace **611** which may be used to wake up or exit the transmitter unit from its post manufacturing sleep mode into an active state, by for example, establishing a closed circuit with the power supply provided within the transmitter unit **102**.

FIG. **9** is a flowchart illustrating sensor removal detection routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **9**, when the sensor removal is detected (**910**) for example, based on detaching or removing the transmitter unit **102** that was in contact with the sensor **101**, one or more status signal is generated (**920**), that includes, for example, an indication that the sensor removal state has been detected, and/or an indication that the transmitter unit **102** will enter a sleep mode or a powered down status. Thereafter, the generated status signal in one aspect is transmitted, for example, to the receiver unit **104** (**930**), and the transmitter unit **102** is configured to enter the power down mode or low power sleep mode (**940**).

In this manner, in one aspect, when the transmitter unit **102** is disconnected from an active sensor **101**, the transmitter unit **102** is configured to notify the receiver unit **104** that the sensor **101** has been disconnected or otherwise, signals from the sensor **101** are no longer received by the transmitter unit **102**. After transmitting the one or more signals to notify the receiver unit **104**, the transmitter unit **102** in one embodiment is configured to enter sleep mode or low power state during which no data related to the monitored analyte level is transmitted to the receiver unit **104**.

FIG. **10** is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **10**, in one embodiment, the transmitter unit **102** may be configured to receive a sensor initiate close proximity command (**1010**) from the receiver unit **104** positioned within the close transmission range. Based on the received sensor initiate command, the transmitter unit identification information may be retrieved (for example, from a nonvolatile memory) and transmitted (**1020**) to the receiver unit **104** or the sender of the sensor initiate command.

Referring back to FIG. **10**, a communication key optionally encrypted is received in one embodiment (**1030**), and thereafter, sensor related data is transmitted with the communication key on a periodic basis such as, every 60 seconds, five minutes, or any suitable predetermined time intervals (**1040**).

Referring now to FIG. **11**, a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. **1** in accordance with another embodiment of the present invention is shown. That is, in one aspect, FIG. **11** illustrates the pairing or synchronization routine from the receiver unit **104**. Referring back to FIG. **11**, the sensor initiate command is transmitted to the transmitter unit **102** (**1110**) when the receiver unit **104** is positioned within a close transmission range. Thereafter, in one aspect, the transmitter identification information is received (**1120**) for example, from the transmitter unit that received the sensor initiate command. Thereafter, a communication key (optionally encrypted) may be generated and transmitted (**1130**) to the transmitter unit.

In the manner described above, in one embodiment, a simplified pairing or synchronization between the transmitter unit **102** and the receiver unit **104** may be established using, for example, close proximity commands between the devices. As described above, in one aspect, upon pairing or synchronization, the transmitter unit **102** may be configured to periodically transmit analyte level information to the receiver unit **104** for further processing.

FIG. **12** is a flowchart illustrating the power supply determination in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. That is, in one embodiment, using a counter, the receiver unit **104** may be configured to determine the power supply level of the transmitter unit **102** battery so as to determine a suitable time for replacement of the power supply or the transmitter unit **102** itself. Referring to FIG. **12**, periodic data transmission is detected (**1210**), and a corresponding count in the counter is incremented for example, by one with each detected data transmission (**1220**). In particular, a Hobbs counter may be used in the rolling data configuration described above to provide a count that is associated with the transmitter unit data transmission occurrence.

Referring to FIG. **12**, the updated or incremented count stored in the Hobbs counter is periodically transmitted in the data packet (**1230**) from the transmitter unit **102** to the receiver unit **104**. Moreover, the incremented or updated count may be stored (**1240**) in a persistent nonvolatile memory unit of the transmitter unit **102**. Accordingly, based on the number of data transmission occurrences, the battery power supply level may be estimated, and in turn, which may provide an indication as to when the battery (and thus the transmitter unit in the embodiment where the power supply is manufactured to be embedded within the transmitter unit housing) needs to be replaced.

Moreover, in one aspect, the incremented count in the Hobbs counter is stored in a persistent nonvolatile memory such that, the counter is not reset or otherwise restarted with each sensor replacement.

FIG. **13** is a flowchart illustrating close proximity command for RF communication control in the data monitoring and management system of FIG. **1** in accordance with one embodiment of the present invention. Referring to FIG. **13**, a close proximity command associated with communication status, for example is received (**1310**). In one aspect, the command associated with the communication status may include, for example, a communication module turn on or turn off command for, for example, turning on or turning off the associated RF communication device of the transmitter unit **102**. Referring to FIG. **13**, the communication status is determined (**1320**), and thereafter, modified based on the received command (**1330**).

That is, in one aspect, using one or more close proximity commands, the receiver unit **104** may be configured to control the RF communication of the transmitter unit **102** to, for example, disable or turn off the RF communication functionality for a predetermined time period. This may be particularly useful when used in air travel or other locations such as hospital settings, where RF communication devices need to be disabled. In one aspect, the close proximity command may be used to either turn on or turn off the RF communication module of the transmitter unit **102**, such that, when the receiver unit **104** is positioned in close proximity to the transmitter unit **102**, and the RF command is transmitted, the transmitter unit **102** is configured, in one embodiment, to either turn off or turn on the RF communication capability of the transmitter unit **102**.

FIG. **14** is a flowchart illustrating analyte sensor identification routine in accordance with one embodiment of the present invention. Referring to FIG. **14**, periodically, sensor counter information is received (**1410**), for example included as rolling data discussed above. The received sensor counter information may be stored in one or more storage units such as a memory unit. When the sensor counter information is received, a stored sensor counter information is retrieved (**1420**), and the retrieved sensor counter information is compared with the received sensor counter information (**1430**). Based on the comparison between the retrieved sensor counter information and the received sensor counter information, one or more signal is generated and output (**1440**). That is, in one aspect, the sensor counter in the transmitter unit **102** may be configured to increment by one with each new sensor replacement. Thus, in one aspect, the sensor counter information may be associated with a particular sensor from which monitored analyte level information is generated and transmitted to the receiver unit **104**. Accordingly, in one embodiment, based on the sensor counter information, the receiver unit **104** may be configured to ensure that the analyte related data is generated and received from the correct analyte sensor transmitted from the transmitter unit **102**. A method in one embodiment includes detecting a data transmission, incrementing a count associated with the detected data transmission, and storing the count. The count may be incremented by one. In a further aspect, the method may include associating a power supply level information with the stored count.

Moreover, the method may also include generating a signal associated with the stored count, and/or include outputting the generated signal, where outputting the generated signal may include one or more of visually displaying the generated signal, audibly outputting the generated signal, or vibratory outputting the generated signal.

In yet another aspect, the method may include transmitting the count with the data transmission, where the count may be transmitted periodically with the data transmission.

In still another aspect, the method may include associating a power supply status with the count.

A data processing device in another embodiment may include a counter, a data communication unit, and a data processing section coupled to the data communication unit and the counter, the data processing section configured to increment a count stored in the counter based on data transmission by the data communication unit.

In one aspect, the counter may include a nonvolatile memory unit. The counter may include an EEPROM. The data communication unit may include an RF transceiver. The count stored in the counter may be incremented by one with each data transmission by the data communication unit.

The device may include a power supply coupled to the data processing unit, the data communication unit and the counter, where the count stored in the counter is not erased when the power supply is disabled or in low power state.

The data processing unit may be configured to estimate the power supply life based on the stored count in the counter. The device in a further aspect may include an output section for outputting one or more signals associated with the count information, where the output section may include one or more of a display unit, an audible output section, or a vibratory output section.

In accordance with another aspect of the invention, elapsed sensor life and/or remaining sensor life is determinable. In this regard the sensor life is tracked by a counter. Advantageously, after a system failure such as power shutdown, power loss, reset (e.g., Watchdog reset), battery drain, battery failure, the user of the data monitoring and management system of FIG. **1** no longer needs to replace the sensor. Instead, the methods and system of the invention provide sensor life information to the user to enable the user to restart the analyte monitoring system using the same sensor, provided suitable remaining sensor life.

In one embodiment of the invention, as shown in FIG. **1**, an analyte monitoring and management system includes an analyte sensor **101**, a transmitter unit **102**, a first counter (not shown), such as a Hobbs counter, and a receiver unit **104**. The system can be configured to determine the elapsed life (or remaining life) of an employed analyte sensor **101**. Advantageously, a user of the analyte monitoring system is now able to determine a suitable time for replacement of the analyte sensor, for example, in the event of a system failure during which the receiver loses data information about calibration schedule and/or sensor expiration schedule. Prior systems typically require the user to discard the analyte sensor (regardless of remaining life available on the sensor) after the occurrence of a system failure due to the data loss of time and day and calibration.

In accordance with one embodiment of the method, a signal associated with initiation of an analyte sensor is provided. For example, but not limitation, upon initiation of the sensor **101** a signal is generated which contains analyte measurement information. The signal can be at least part of the data which forms a data packet that is encoded by the transmitter unit **102** and/or transmitted via a communication link to a receiver unit **104**. The receiver unit **104** can be configured to expect receipt of a data packet at predetermined time intervals and/or at periodic calculations of analyte. In one embodiment, the data packets are transmitted by a transmitter unit **102** to receiver unit **104** every minute. After the count temporally associated with initiation of the sensor is stored, the counter is configured to continually

count by increments. The increments can be for example, based on a periodic cycle, such as a measurement cycle. Alternatively, the increment can be based on other factors, such as scheduled time interval. Additionally, the incremental count can be commensurate with the transmission of each (or a predetermined limited number) data packets and/or measurement cycles. Thus, for example, the measurement cycle can be a periodic calculation of measured analyte (regardless of whether it is transmitted), or it can be based on a selected time interval, such as for example 30 or 60 seconds, if desired. In some embodiments, the count information incrementally counted by the counter is transmitted to the receiver unit **104** as part of the data packet. Further, the receiver is configured to extract the count from the data packet.

In one embodiment, the count information transmitted in the data packet upon sensor initiation is transmitted to receiver unit **104** where it is stored. Preferably, the count information is stored in nonvolatile memory such that it is not lost during a system failure. Preferably, the nonvolatile memory device is disposed in the receiver unit **104**. However, transmitter unit **102** can be configured to store the count. The counter which can be part of the transmitter device **102**, for example, is a Hobbs counter.

In accordance with one embodiment of the invention, elapsed life of an analyte sensor (or remaining life expectancy of a sensor) can be determined by comparing the stored count which is based on sensor initiation with an incremented count. As described above, the incremental count is based on a known measurement cycle, and/or time interval. Thus, the comparison of the count information can be used to calculate the duration or elapsed time of the sensor use.

Further, the determined elapsed time can be used to restart operating system timers, such as a sensor life timer and/or calibration timer.

FIG. **15** is a flowchart illustrating a method for determining elapsed life of an analyte sensor employed in the analyte monitoring and management system of FIG. **1**. As depicted and embodied herein, an analyte sensor is initiated (**1510**) to detect and/or measure the presence of an analyte in a bodily fluid. For the purpose of illustration, but not limitation, the analyte can be glucose and the bodily fluid can be blood, plasma or interstitial fluid. However, other analytes can be monitored, such as but not limited to lactate. A counter, such as for example a Hobbs counter described above, is configured to incrementally count. The Hobbs counter may be disposed for example in the transmitter of the analyte monitoring system. The count or value that is temporally associated with the initiation of the sensor (**1520**) (or a signal generated by the sensor during initiation) is stored in a memory unit (count 1) (**1530**). In addition to the storage of the first count, the counter continues to incrementally count. As described, the incremental count can be based on a known measurement cycle, such as that of the analyte sensor detecting levels of an analyte in the bodily fluid. Alternatively, the incremental count can be based on a time interval. In the event that a system failure occurs, the counter is configured to store a second count temporally associated with re-initiation of the analyte sensor (count 2) (**1540**). In this regard, the elapsed time or duration of use of the analyte sensor prior to the fault condition can be determined by comparing count 2 and count 1 (**1550**). Thus, provided that at least some life expectancy of the analyte sensor remains, the user may continue to use the analyte sensor, rather than being required to change the sensor with a replacement sensor because all data was lost. In the event that no or less than a predetermined amount of life remains on the analyte sensor, the monitoring system can be configured to display a message or alarm that the sensor expired or is soon to expire (**1560**). In a further embodiment, the determined elapsed time can be used to restart a sensor life timer and/or calibration timer (**1570**).

The term system failure as used herein means a fault condition such as any condition by which the analyte monitoring system loses power. Some non-limiting examples of fault conditions include a reset (e.g., receiver reset), battery drain, battery replacement, power loss, power shut-down, or a fatal error. Typically, after such fault conditions, analyte monitoring systems prompt the user to replace the sensor because information about the life of the sensor was lost at the time of the fault condition. This aspect of the invention, allows the use of the same sensor after a fault condition occurs (provided that the sensor life has not expired), thereby saving the user costs associated with using a new sensor and the hardship of undergoing another calibration schedule.

In another embodiment of the invention, the analyte monitoring and management system includes a first counter to incrementally count based on a time interval, or calculation of an analyte, and a second counter to incrementally count by one only if a new sensor is initiated. In this regard, the incremental count of the second sensor can indicate how many or which sensor is being employed. For example, if the second counter has an incremental count of one, then the first sensor is being employed, if the second counter has an incremental count of 2, then the second sensor is being employed. Thus, the second counter can track how many sensors have been employed. In a further aspect of the invention, if the receiver connects to the transmitter and in response the receiver receives a count change compared to the sensor count before the system failure, the receiver acknowledges that a different sensor was implanted or otherwise employed during the receiver shut down. In this regard, the previous sensor life time is terminated, and a new count begins for the new sensor. Additionally, when the second counter increments by one because a new sensor is used then the count of the first counter is stored.

Referring to another embodiment of the invention, as described in FIG. **16**, the first counter can be a Hobbs counter which is initiated (for example, to T=0) (**1610**). Thereafter the Hobbs counter incrementally counts (for example, to T=T+1) (**1620**). The second counter can be for example a sensor counter that is configured to count incrementally with the initiation of each new analyte sensor (for example, S=S+1) (**1640**). Thus, if there is no new sensor employed, the count of the second counter does not increment (**1630**). Further, a count of the Hobbs counter (**1650**) (which is commensurate with an incremental count of the sensor counter) is stored (**1660**). Thus, the system contains stored data regarding the data and time of each new sensor initiation. Accordingly, the first and second counters in conjunction can be used to determine elapsed life of the analyte sensor. As shown in FIG. **16**, if the sensor life is less than the sensor life expectancy (**1670**), then the cycle is repeated. If the sensor life is expired or close to its expiration, then an alarm or message can be output (**1680**).

In one embodiment, the first counter is a 20-bit counter, and the second counter is an 8-bit counter. However, other types of counters can be utilized.

In another aspect of the invention, an output unit is provided. The output unit can be configured to display a value derived from the count information. In this regard, the output unit can be a display device. The display device can

be an Organic Light Emitting Diode (OLED) display device, for example, a small molecule or polymer OLED. The OLED display device can provide wide viewing angles, high brightness, colors, and contrast levels.

It will be apparent to those skilled in the art that various modifications and alterations in the methods and systems of this invention will be apparent to those skilled in the art without departing from the scope and spirit of the invention. Although the invention has been described in connection with specific embodiments, it should be understood that the invention as claimed should not be unduly limited to such specific embodiments. It is intended that the following claims define the scope of the present invention and that structures and methods within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

1. A method, comprising:

providing a signal associated with initiation of an analyte sensor, the analyte sensor for monitoring analyte level;

providing a count, wherein the count is temporally associated with the signal associated with the initiation of the analyte sensor;

periodically incrementing the count;

storing the count temporally associated with the signal associated with the initiation of the analyte sensor, wherein when sensor life of the initiated analyte sensor has not expired and a system failure is detected, continuing use of the initiated analyte sensor based at least in part on the stored count;

providing a new sensor count; and

incrementing the new sensor count only when a new sensor is first initiated.

2. The method of claim **1**, wherein incrementing the count is associated with a measurement cycle.

3. The method of claim **2**, wherein the measurement cycle comprises a periodic determination of the monitored analyte level.

4. The method of claim **1**, including storing the count temporally associated with the initiation of the analyte sensor in a memory device.

5. The method of claim **4**, wherein the memory device is a nonvolatile memory device, such that count information stored in the memory is not lost during the system failure.

6. The method of claim **1**, wherein the system failure is a component failure.

7. The method of claim **1**, wherein the system failure includes a battery drain, power shut-down, or reset.

8. The method of claim **1**, including outputting a message or alarm when the system failure occurs.

9. The method of claim **1**, wherein incrementing the count is associated with communication of data packets.

10. The method of claim **1**, wherein the analyte sensor comprises a working electrode that includes an analyte responsive enzyme and a mediator, wherein at least one of the analyte responsive enzyme and the mediator is chemically bonded to a polymer disposed on the working electrode, and wherein at least one of the analyte responsive enzyme and the mediator is crosslinked with the polymer.

11. A data processing device, comprising:

a first counter configured to incrementally count;

a data communication unit;

a data processing section coupled to the data communication unit and the first counter, the data processing section configured to determine an elapsed life of an analyte sensor;

wherein when a device failure is detected and the determined elapsed life indicates that analyte sensor life has not expired, continuing use of the analyte sensor based at least in part on the first counter configured to incrementally count; and

a new sensor counter coupled to the data processing section and configured to increment a new sensor count only when a new sensor is first initiated.

12. The data processing device of claim **11**, wherein the analyte sensor is configured to generate a signal associated with a level of monitored analyte.

13. The data processing device of claim **11**, further including a storage unit configured to store a count temporally associated with initiation of the analyte sensor.

14. The data processing device of claim **11**, wherein the analyte sensor includes a glucose sensor.

15. The data processing device of claim **13**, wherein the data processing section is configured to compare the stored count with an incremented count associated with the first counter to determine the elapsed life of the analyte sensor.

16. The data processing device of claim **15**, wherein the data processing section is configured to estimate the remaining sensor life based on the stored count and the incremented count.

17. The data processing device of claim **13**, further including an output unit configured to output one or more signals associated with the count.

18. The data processing device of claim **13**, wherein the analyte sensor comprises a working electrode that includes an analyte responsive enzyme and a mediator, wherein at least one of the analyte responsive enzyme and the mediator is chemically bonded to a polymer disposed on the working electrode, and wherein at least one of the analyte responsive enzyme and the mediator is crosslinked with the polymer.

* * * * *