US010084665B1

(12) **United States Patent**
Arunachalam et al.

(10) **Patent No.: US 10,084,665 B1**
(45) **Date of Patent: Sep. 25, 2018**

(54) **RESOURCE SELECTION USING QUALITY PREDICTION**

(71) Applicant: **Cisco Technology, Inc.**, San Jose, CA (US)

(72) Inventors: **Chidambaram Arunachalam**, Cary, NC (US); **Gonzalo Salgueiro**, Raleigh, NC (US); **Nagendra Kumar Nainar**, Morrisville, NC (US); **Eric Chen**, Palo Alto, CA (US); **Keith Griffin**, Galway (IE)

(73) Assignee: **CISCO TECHNOLOGY, INC.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/663,655**

(22) Filed: **Jul. 28, 2017**

Related U.S. Application Data

(63) Continuation of application No. 15/659,356, filed on Jul. 25, 2017.

(51) **Int. Cl.**
H04L 12/28 (2006.01)
H04L 12/24 (2006.01)
H04L 12/26 (2006.01)

(52) **U.S. Cl.**
CPC ***H04L 41/5009*** (2013.01); ***H04L 43/04*** (2013.01); ***H04L 43/0852*** (2013.01); *H04L 41/0896* (2013.01); *H04L 43/062* (2013.01)

(58) **Field of Classification Search**
CPC H04L 12/5692; H04L 12/66; H04L 29/06027; H04L 65/1009; H04L 65/1069; H04B 7/18539; Y02T 10/7005; A61K 31/765; A61K 31/77; A61K 9/2013; A61K 9/2018; A61K 9/2031
USPC 370/351, 400, 401
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,460,807	A	7/1984	Kerr et al.
4,890,257	A	12/1989	Anthias et al.
5,694,563	A	12/1997	Belfiore et al.
5,699,082	A	12/1997	Marks et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN	101055561	10/2007
CN	102572370	7/2012

(Continued)

OTHER PUBLICATIONS

Author Unknown, "A Primer on the H.323 Series Standard," Version 2.0, available at http://www.packetizer.com/voip/h323/papers/primer, retrieved on Dec. 20, 2006, 17 pages.

(Continued)

Primary Examiner — Binh Kien Tieu
(74) *Attorney, Agent, or Firm* — Polsinelli PC

(57) **ABSTRACT**

Disclosed is a system and method for receiving a communication session request and identifying a plurality of available gateways available to handle the communication session request. For each gateway of the plurality of available gateways, gateway metrics of the performance of the gateway are predicted. Based on the predicted gateway metrics, a user rating for the communication session request being handled by the gateway is predicted. Based on the predicted user rating for each gateway, a gateway is selected from the plurality of available gateways.

20 Claims, 16 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

5,745,711 A 4/1998 Kitahara et al.
5,767,897 A 6/1998 Howell
5,825,858 A 10/1998 Shaffer et al.
5,874,962 A 2/1999 de Judicibus et al.
5,917,537 A * 6/1999 Lightfoot H04L 69/329 348/E7.06
5,970,064 A 10/1999 Clark et al.
5,995,096 A 11/1999 Kitahara et al.
6,023,606 A * 2/2000 Monte H04B 7/18539 455/13.1
6,040,817 A 3/2000 Sumikawa
6,075,531 A 6/2000 DeStefano
6,085,166 A 7/2000 Beckhardt et al.
6,115,393 A 9/2000 Engel et al.
6,191,807 B1 2/2001 Hamada et al.
6,298,351 B1 10/2001 Castelli et al.
6,300,951 B1 10/2001 Filetto et al.
6,392,674 B1 5/2002 Hiraki et al.
6,463,473 B1 10/2002 Gubbi
6,554,433 B1 4/2003 Holler
6,573,913 B1 6/2003 Butler et al.
6,597,684 B1 7/2003 Gulati et al.
6,646,997 B1 11/2003 Baxley et al.
6,665,396 B1 12/2003 Khouri et al.
6,697,325 B1 2/2004 Cain
6,711,419 B1 3/2004 Mori
6,721,899 B1 4/2004 Narvaez-Guarnieri et al.
6,754,321 B1 6/2004 Innes et al.
6,754,335 B1 6/2004 Shaffer et al.
RE38,609 E 10/2004 Chen et al.
6,894,714 B2 5/2005 Gutta et al.
6,954,617 B2 10/2005 daCosta
7,058,164 B1 6/2006 Chan et al.
7,058,710 B2 6/2006 McCall et al.
7,062,532 B1 6/2006 Sweat et al.
7,085,367 B1 8/2006 Lang
7,124,164 B1 10/2006 Chemtob
7,149,499 B1 12/2006 Oran et al.
7,180,993 B2 2/2007 Hamilton
7,185,077 B1 2/2007 O'Toole et al.
7,209,475 B1 4/2007 Shaffer et al.
7,418,664 B2 8/2008 Ben-Shachar et al.
7,441,198 B2 10/2008 Dempski et al.
7,453,864 B2 11/2008 Kennedy et al.
7,478,339 B2 1/2009 Pettiross et al.
7,496,650 B1 2/2009 Previdi et al.
7,530,022 B2 5/2009 Ben-Shachar et al.
7,620,902 B2 11/2009 Manion et al.
7,634,533 B2 12/2009 Rudolph et al.
7,792,277 B2 9/2010 Shaffer et al.
7,826,372 B1 11/2010 Mabe et al.
7,881,450 B1 2/2011 Gentle et al.
7,920,160 B2 4/2011 Tamaru et al.
7,956,869 B1 6/2011 Gilra
8,059,557 B1 11/2011 Sigg et al.
8,063,929 B2 11/2011 Kurtz et al.
8,081,205 B2 12/2011 Baird et al.
8,154,583 B2 4/2012 Kurtz et al.
8,274,893 B2 9/2012 Bansal
8,290,998 B2 10/2012 Stienhans et al.
8,340,268 B2 12/2012 Knaz
8,358,327 B2 1/2013 Duddy
8,385,355 B1 2/2013 Figueira et al.
8,428,234 B2 4/2013 Knaz
8,434,019 B2 4/2013 Nelson
8,456,507 B1 6/2013 Mallappa et al.
8,462,103 B1 6/2013 Moscovitch et al.
8,478,848 B2 7/2013 Minert
8,489,765 B2 7/2013 Vasseur et al.
8,620,840 B2 12/2013 Newnham et al.
8,630,208 B1 1/2014 Kjeldaas
8,630,291 B2 1/2014 Shaffer et al.
8,634,314 B2 1/2014 Banka et al.
8,638,354 B2 1/2014 Leow et al.
8,638,778 B2 1/2014 Lee et al.
8,675,847 B2 3/2014 Shaffer et al.
8,694,587 B2 4/2014 Chaturvedi et al.
8,694,593 B1 4/2014 Wren et al.
8,706,539 B1 4/2014 Mohler
8,707,194 B1 4/2014 Jenkins et al.
8,767,716 B2 7/2014 Trabelsi et al.
8,774,164 B2 7/2014 Klein et al.
8,831,505 B1 9/2014 Seshadri
8,842,161 B2 9/2014 Feng et al.
8,856,584 B2 10/2014 Matsubara
8,862,522 B1 10/2014 Jaiswal et al.
8,880,477 B2 11/2014 Barker et al.
8,890,924 B2 11/2014 Wu
8,892,646 B2 11/2014 Chaturvedi et al.
8,924,862 B1 12/2014 Luo
8,930,840 B1 1/2015 Riskó et al.
8,942,085 B1 1/2015 Pani et al.
9,031,839 B2 5/2015 Thorsen et al.
9,032,028 B2 5/2015 Davidson et al.
9,118,612 B2 8/2015 Fish et al.
9,131,017 B2 9/2015 Kurupacheril et al.
9,137,376 B1 9/2015 Basart et al.
9,143,729 B2 9/2015 Anand et al.
9,197,701 B1 11/2015 Petrov et al.
9,197,848 B2 11/2015 Felkai et al.
9,201,527 B2 12/2015 Kripalani et al.
9,204,099 B2 12/2015 Brown
9,268,398 B2 2/2016 Tipirneni
9,298,342 B2 3/2016 Zhang et al.
9,323,417 B2 4/2016 Sun et al.
9,324,022 B2 4/2016 Williams, Jr. et al.
9,335,892 B2 5/2016 Ubillos
9,338,065 B2 5/2016 Vasseur et al.
9,349,119 B2 5/2016 Desai et al.
9,367,224 B2 6/2016 Ananthakrishnan et al.
9,369,673 B2 6/2016 Ma et al.
9,407,621 B2 8/2016 Vakil et al.
9,432,512 B2 8/2016 You
9,449,303 B2 9/2016 Underhill et al.
9,495,664 B2 11/2016 Cole et al.
9,516,022 B2 12/2016 Borzycki et al.
9,525,711 B2 12/2016 Ackerman et al.
9,553,799 B2 1/2017 Tarricone
9,558,451 B2 1/2017 Nilsson et al.
9,563,480 B2 2/2017 Messerli et al.
9,609,030 B2 3/2017 Sun et al.
9,614,756 B2 4/2017 Joshi
9,667,799 B2 5/2017 Olivier et al.
9,762,709 B1 9/2017 Snyder et al.
2002/0018051 A1 2/2002 Singh
2002/0061001 A1 5/2002 Garcia-Luna-Aceves et al.
2002/0076003 A1 6/2002 Zellner et al.
2002/0078153 A1 6/2002 Chung et al.
2002/0101505 A1 8/2002 Gutta et al.
2002/0105904 A1 8/2002 Hauser et al.
2002/0116154 A1 8/2002 Nowak et al.
2002/0159386 A1 10/2002 Grosdidier et al.
2002/0188522 A1 12/2002 McCall et al.
2003/0005149 A1 1/2003 Haas et al.
2003/0028647 A1 2/2003 Grosu
2003/0046421 A1 3/2003 Horvitz et al.
2003/0061340 A1 3/2003 Sun et al.
2003/0091052 A1 5/2003 Pate et al.
2003/0117992 A1 6/2003 Kim et al.
2003/0133417 A1 7/2003 Badt, Jr.
2003/0174826 A1 9/2003 Hesse
2003/0187800 A1 * 10/2003 Moore G06Q 20/085 705/52
2003/0197739 A1 10/2003 Bauer
2003/0225549 A1 12/2003 Shay et al.
2003/0227423 A1 12/2003 Arai et al.
2004/0054885 A1 3/2004 Bartram et al.
2004/0098456 A1 5/2004 Krzyzanowski et al.
2004/0153563 A1 8/2004 Shay et al.
2004/0210637 A1 10/2004 Loveland
2004/0218525 A1 11/2004 Elie-Dit-Cosaque et al.
2004/0267938 A1 12/2004 Shoroff et al.
2005/0014490 A1 1/2005 Desai et al.
2005/0055405 A1 3/2005 Kaminsky et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0055412 A1 3/2005 Kaminsky et al.
2005/0085243 A1 4/2005 Boyer et al.
2005/0099492 A1 5/2005 Orr
2005/0108328 A1 5/2005 Berkeland et al.
2005/0111487 A1 5/2005 Matta et al.
2005/0114532 A1 5/2005 Chess et al.
2005/0143979 A1 6/2005 Lee et al.
2005/0215229 A1 9/2005 Cheng
2005/0286711 A1* 12/2005 Lee H04L 12/5692 379/399.01
2006/0004911 A1 1/2006 Becker et al.
2006/0026255 A1 2/2006 Malamud et al.
2006/0072471 A1 4/2006 Shiozawa
2006/0083193 A1 4/2006 Womack et al.
2006/0116146 A1 6/2006 Herrod et al.
2006/0133404 A1 6/2006 Zuniga et al.
2006/0164552 A1 7/2006 Cutler
2006/0224430 A1 10/2006 Butt
2006/0250987 A1 11/2006 White et al.
2007/0005752 A1 1/2007 Chawla et al.
2007/0041366 A1 2/2007 Vugenfirer et al.
2007/0047707 A1* 3/2007 Mayer H04M 15/00 379/114.28
2007/0071030 A1 3/2007 Lee
2007/0083650 A1 4/2007 Collomb et al.
2007/0091831 A1 4/2007 Croy et al.
2007/0100986 A1 5/2007 Bagley et al.
2007/0116225 A1 5/2007 Zhao et al.
2007/0120966 A1 5/2007 Murai
2007/0139626 A1 6/2007 Saleh et al.
2007/0149249 A1 6/2007 Chen et al.
2007/0192065 A1 8/2007 Riggs et al.
2007/0198637 A1 8/2007 Deboy et al.
2007/0208590 A1* 9/2007 Dorricott G06Q 10/06 379/265.01
2007/0250567 A1 10/2007 Graham et al.
2008/0049622 A1 2/2008 Previdi et al.
2008/0068447 A1 3/2008 Mattila et al.
2008/0080532 A1 4/2008 O'Sullivan et al.
2008/0089246 A1 4/2008 Ghanwani et al.
2008/0140817 A1 6/2008 Agarwal et al.
2008/0159151 A1 7/2008 Datz et al.
2008/0181259 A1 7/2008 Andreev et al.
2008/0192651 A1 8/2008 Gibbings
2008/0209452 A1 8/2008 Ebert et al.
2008/0293353 A1 11/2008 Mody et al.
2009/0003232 A1 1/2009 Vaswani et al.
2009/0010264 A1 1/2009 Zhang
2009/0012963 A1 1/2009 Johnson et al.
2009/0073988 A1 3/2009 Ghodrat et al.
2009/0100142 A1 4/2009 Stern et al.
2009/0129316 A1 5/2009 Ramanathan et al.
2009/0147714 A1 6/2009 Jain et al.
2009/0147737 A1 6/2009 Tacconi et al.
2009/0168653 A1 7/2009 St. Pierre et al.
2009/0193327 A1 7/2009 Roychoudhuri et al.
2009/0254619 A1 10/2009 Kho et al.
2009/0256901 A1 10/2009 Mauchly et al.
2009/0271467 A1 10/2009 Boers et al.
2009/0292999 A1 11/2009 LaBine et al.
2009/0303908 A1 12/2009 Deb et al.
2009/0309846 A1 12/2009 Trachtenberg et al.
2010/0005142 A1 1/2010 Xiao et al.
2010/0046504 A1 2/2010 Hill
2010/0061538 A1 3/2010 Coleman et al.
2010/0070640 A1 3/2010 Allen, Jr. et al.
2010/0073454 A1 3/2010 Lovhaugen et al.
2010/0094867 A1 4/2010 Badros et al.
2010/0121959 A1 5/2010 Lin et al.
2010/0157978 A1 6/2010 Robbins et al.
2010/0165863 A1 7/2010 Nakata
2010/0211872 A1 8/2010 Rolston et al.
2010/0245535 A1 9/2010 Mauchly
2010/0262925 A1 10/2010 Liu et al.
2010/0303227 A1 12/2010 Gupta
2010/0316207 A1 12/2010 Brunson
2010/0318399 A1 12/2010 Li et al.
2011/0075830 A1 3/2011 Dreher et al.
2011/0082596 A1 4/2011 Meagher et al.
2011/0116389 A1 5/2011 Tao et al.
2011/0131498 A1 6/2011 Chao et al.
2011/0149759 A1 6/2011 Jollota
2011/0228696 A1 9/2011 Agarwal et al.
2011/0255570 A1 10/2011 Fujiwara
2011/0264928 A1 10/2011 Hinckley
2011/0267962 A1 11/2011 J S A et al.
2011/0270609 A1 11/2011 Jones et al.
2011/0271211 A1 11/2011 Jones et al.
2011/0283226 A1 11/2011 Basson et al.
2011/0314139 A1 12/2011 Song et al.
2012/0013704 A1 1/2012 Sawayanagi et al.
2012/0075999 A1 3/2012 Ko et al.
2012/0084714 A1 4/2012 Sirpal et al.
2012/0163177 A1 6/2012 Vaswani et al.
2012/0179502 A1 7/2012 Farooq et al.
2012/0190386 A1 7/2012 Anderson
2012/0192075 A1* 7/2012 Ebtekar H04L 12/6418 715/738
2012/0213062 A1 8/2012 Liang et al.
2012/0213124 A1 8/2012 Vasseur et al.
2012/0246229 A1 9/2012 Carr et al.
2012/0246596 A1 9/2012 Ording et al.
2012/0284635 A1 11/2012 Sitrick et al.
2012/0296957 A1 11/2012 Stinson et al.
2012/0306757 A1 12/2012 Keist et al.
2012/0306993 A1 12/2012 Sellers-Blais
2012/0307629 A1 12/2012 Vasseur et al.
2012/0321058 A1* 12/2012 Eng H04L 45/00 379/90.01
2013/0003542 A1 1/2013 Catovic et al.
2013/0010610 A1 1/2013 Karthikeyan et al.
2013/0028073 A1 1/2013 Tatipamula et al.
2013/0038675 A1 2/2013 Malik
2013/0047093 A1 2/2013 Reuschel et al.
2013/0050398 A1 2/2013 Krans et al.
2013/0063542 A1 3/2013 Bhat et al.
2013/0070755 A1 3/2013 Trabelsi et al.
2013/0090065 A1 4/2013 Fisunenko et al.
2013/0091205 A1 4/2013 Kotler et al.
2013/0091440 A1 4/2013 Kotler et al.
2013/0094647 A1* 4/2013 Mauro H04M 3/5141 379/265.09
2013/0128720 A1 5/2013 Kim et al.
2013/0135837 A1 5/2013 Kemppinen
2013/0141371 A1 6/2013 Hallford et al.
2013/0148789 A1 6/2013 Hillier et al.
2013/0177305 A1 7/2013 Prakash et al.
2013/0185672 A1 7/2013 McCormick et al.
2013/0198629 A1 8/2013 Tandon et al.
2013/0215215 A1 8/2013 Gage et al.
2013/0219278 A1 8/2013 Rosenberg
2013/0222246 A1 8/2013 Booms et al.
2013/0225080 A1 8/2013 Doss et al.
2013/0227433 A1 8/2013 Doray et al.
2013/0250754 A1 9/2013 Vasseur et al.
2013/0275589 A1 10/2013 Karthikeyan et al.
2013/0290421 A1 10/2013 Benson et al.
2013/0297704 A1 11/2013 Alberth, Jr. et al.
2013/0300637 A1 11/2013 Smits et al.
2013/0311673 A1 11/2013 Karthikeyan et al.
2013/0329865 A1 12/2013 Ristock et al.
2013/0335507 A1 12/2013 Aarrestad et al.
2014/0012990 A1 1/2014 Ko
2014/0028781 A1 1/2014 MacDonald
2014/0040819 A1 2/2014 Duffy
2014/0049595 A1 2/2014 Feng et al.
2014/0068452 A1 3/2014 Joseph et al.
2014/0078182 A1 3/2014 Utsunomiya
2014/0108486 A1 4/2014 Borzycki et al.
2014/0126423 A1 5/2014 Vasseur et al.
2014/0133327 A1 5/2014 Miyauchi
2014/0157338 A1 6/2014 Pearce
2014/0161243 A1 6/2014 Contreras et al.
2014/0198175 A1 7/2014 Shaffer et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2014/0204759	A1	7/2014	Guo et al.	
2014/0207945	A1	7/2014	Galloway et al.	
2014/0215077	A1	7/2014	Soudan et al.	
2014/0219103	A1	8/2014	Vasseur et al.	
2014/0237371	A1	8/2014	Klemm et al.	
2014/0280595	A1	9/2014	Mani et al.	
2014/0282213	A1	9/2014	Musa et al.	
2014/0293955	A1	10/2014	Keerthi	
2014/0317561	A1	10/2014	Robinson et al.	
2014/0337840	A1*	11/2014	Hyde	H04W 52/0229 718/1
2014/0351327	A1	11/2014	Huang et al.	
2014/0372908	A1	12/2014	Kashi et al.	
2015/0004571	A1	1/2015	Ironside et al.	
2015/0009278	A1	1/2015	Modai et al.	
2015/0023174	A1	1/2015	Dasgupta et al.	
2015/0029301	A1	1/2015	Nakatomi et al.	
2015/0067552	A1	3/2015	Leorin et al.	
2015/0074189	A1	3/2015	Cox et al.	
2015/0081885	A1	3/2015	Thomas et al.	
2015/0085060	A1	3/2015	Fish et al.	
2015/0089393	A1	3/2015	Zhang et al.	
2015/0089394	A1	3/2015	Chen et al.	
2015/0113050	A1	4/2015	Stahl	
2015/0142702	A1	5/2015	Nilsson et al.	
2015/0172120	A1	6/2015	Dwarampudi et al.	
2015/0304120	A1	10/2015	Xiao et al.	
2015/0304366	A1	10/2015	Bader-Natal et al.	
2015/0319113	A1	11/2015	Gunderson et al.	
2015/0324689	A1	11/2015	Wierzynski et al.	
2015/0373063	A1	12/2015	Vashishtha et al.	
2016/0050079	A1	2/2016	Martin De Nicolas et al.	
2016/0050160	A1	2/2016	Li et al.	
2016/0050175	A1	2/2016	Chaudhry et al.	
2016/0072862	A1	3/2016	Bader-Natal et al.	
2016/0094593	A1	3/2016	Priya	
2016/0105345	A1	4/2016	Kim et al.	
2016/0110056	A1	4/2016	Hong et al.	
2016/0173537	A1	6/2016	Kumar et al.	
2016/0182580	A1	6/2016	Nayak	
2016/0203404	A1	7/2016	Cherkasova et al.	
2016/0277461	A1	9/2016	Sun et al.	
2016/0283909	A1	9/2016	Adiga	
2016/0307165	A1	10/2016	Grodum et al.	
2016/0309037	A1	10/2016	Rosenberg et al.	
2017/0006162	A1	1/2017	Bargetzi et al.	
2017/0006446	A1	1/2017	Harris et al.	
2017/0070706	A1	3/2017	Ursin et al.	
2017/0104961	A1	4/2017	Pan et al.	
2017/0324850	A1	11/2017	Snyder et al.	
2017/0347308	A1	11/2017	Chou et al.	
2017/0353361	A1	12/2017	Chopra et al.	

FOREIGN PATENT DOCUMENTS

CN	102655583	9/2012
CN	102938834	2/2013
CN	102004671	3/2013
CN	103141086	6/2013
CN	204331453	5/2015
EP	959585	11/1999
EP	2341686	8/2016
WO	WO 2012/167262	12/2012
WO	WO 2014/118736	8/2014

OTHER PUBLICATIONS

Author Unknown, ""I can see the future" 10 predictions concerning cell-phones," Surveillance Camera Players, http://www.notbored.org/cell-phones.html, Jun. 21, 2003, 2 pages.

Author Unknown, "Active screen follows mouse and dual monitors," KDE Community Forums, Apr. 13, 2010, 3 pages.

Author Unknown, "Implementing Media Gateway Control Protocols" A RADVision White Paper, Jan. 27, 2002, 16 pages.

Author Unknown, "Manage Meeting Rooms in Real Time," Jan. 23, 2017, door-tablet.com, 7 pages.

Averusa, "Interactive Video Conferencing K-12 applications," "Interactive Video Conferencing K-12 applications" copyright 2012. http://www.averusa.com/education/downloads/hvc brochure goved.pdf (last accessed Oct. 11, 2013).

Cisco Systems, Inc., "Cisco WebEx Meetings Server System Requirements release 1.5." 30 pages, Aug. 14, 2013.

Cisco White Paper, "Web Conferencing: Unleash the Power of Secure, Real-Time Collaboration," pp. 1-8, 2014.

Clarke, Brant, "Polycom Announces RealPresence Group Series" "Polycom Announces RealPresence Group Series" dated Oct. 8, 2012 available at http://www.323.tv/news/polycom-realpresence-group-series (last accessed Oct. 11, 2013).

Clauser, Grant, et al., "Is the Google Home the voice-controlled speaker for you?," The Wire Cutter, Nov. 22, 2016, pp. 1-15.

Cole, Camille, et al., "Videoconferencing for K-12 Classrooms," Second Edition (excerpt), http://www.iste.org/docs/excerpts/VIDCO2-excerpt.pdf (last accessed 1011-2013), 2009.

Epson, "BrightLink Pro Projector," BrightLink Pro Projector. http://www.epson.com/cgi-bin/Store/jsp/Landing/brightlink-pro-interactive-projectors.do?ref=van brightlink-pro—dated 2013 (last accessed 10-112013).

InFocus, "Mondopad," Mondopad. http://www.infocus.com/sites/default/files/InFocus-Mondopad-INF5520a-INF7021-Datasheet-EN.pdf (last accessed Oct. 11, 2013), 2013.

MacCormick, John, "Video Chat with Multiple Cameras," CSCW '13, Proceedings of the 2013 conference on Computer supported cooperative work companion, pp. 195-198, ACM, New York, NY, USA, 2013.

Microsoft, "Positioning Objects on Multiple Display Monitors," Aug. 12, 2012, 2 pages.

Mullins, Robert, "Polycom Adds Tablet Videoconferencing," Mullins, R. "Polycom Adds Tablet Videoconferencing" available at http://www.informationweek.com/telecom/unified-communications/polycom-adds-tablet-videoconferencing/231900680 dated Oct. 12, 2011 (last accessed Oct. 11, 2013).

Nu-Star Technologies, "Interactive Whiteboard Conferencing," Interactive Whiteboard Conferencing. http://www.nu-star.com/interactive-conf.php dated 2013 (last accessed Oct. 11, 2013).

Polycom, "Polycom RealPresence Mobile: Mobile Telepresence & Video Conferencing," http://www.polycom.com/products-services/hd-telepresence-video-conferencing/realpresence-mobile.html#stab1 (last accessed Oct. 11, 2013), 2013.

Polycom, "Polycom Turns Video Display Screens into Virtual Whiteboards with First Integrated Whiteboard Solution for Video Collaboration," Polycom Turns Video Display Screens into Virtual Whiteboards with First Integrated Whiteboard Solution for Video Collaboration—http://www.polycom.com/company/news/press-releases/2011/20111027 2.html—dated Oct. 27, 2011.

Polycom, "Polycom UC Board, Transforming ordinary surfaces into virtual whiteboards" 2012, Polycom, Inc., San Jose, CA, http://www.uatg.com/pdf/polycom/polycom-uc-board-_datasheet.pdf, (last accessed Oct. 11, 2013).

Stevenson, Nancy, "Webex Web Meetings for Dummies" 2005, Wiley Publishing Inc., Indianapolis, Indiana, USA, 339 pages.

Stodle. Daniel, et al., "Gesture-Based, Touch-Free Multi-User Gaming on Wall-Sized, High-Resolution Tiled Displays," 2008, 13 pages.

Thompson, Phil, et al., "Agent Based Ontology Driven Virtual Meeting Assistant," Future Generation Information Technology, Springer Berlin Heidelberg, 2010, 4 pages.

Tno, "Multi-Touch Interaction Overview," Dec. 1, 2009, 12 pages.

Toga, James, et al., "Demystifying Multimedia Conferencing Over the Internet Using the H.323 Set of Standards," Intel Technology Journal Q2, 1998, 11 pages.

Ubuntu, "Force Unity to open new window on the screen where the cursor is?" Sep. 16, 2013, 1 page.

VB Forums, "Pointapi," Aug. 8, 2001, 3 pages.

Vidyo, "VidyoPanorama," VidyoPanorama—http://www.vidyo.com/products/vidyopanorama/ dated 2013 (last accessed Oct. 11, 2013).

(56) **References Cited**

OTHER PUBLICATIONS

Akkaya, Kemal, et al., "A survey on routing protocols for wireless sensor networks" Abtract, 1 page, Ad Hoc Networks, May 2005.
Alsheikh, Mohammad Abu, et al., "Machine Learning in Wireless Sensor Networks: Algorithms, Strategies, and Applications," Mar. 19, 2015, 23 pages.
Author Unknown, "White Paper on Service Enabler Virtualization," Draft dated Nov. 9, 2015, 26 pages, Open Mobile Alliance (OMA), San Diego, CA, USA.
Baccour, Nouha, et al., "Radio Link Quality Estimation in Wireless Sensor Networks: A Survey," 2011, 35 pages.
Fan, Na, "Learning Nonlinear Distance Functions Using Neural Network for Regression with Application to Robust Human Age Estimation," Abstract, 1 page, IEEE International Conference on Computer Vision (ICCV), Nov. 2011, Institute of Electrical and Electronics Engineers, Barcelona, Spain.
Flushing, Eduardo Feo, et al.: "A mobility-assisted protocol for supervised learning of link quality estimates in wireless networks," Feb. 2012, 8 pages.
Fortunato, Santo, "Community Detection in Graphs", arXiv:0906.0612v2 [physics.soc-ph]; Physics Reports 486, 75-174, Jan. 25, 2010, 103 pages.
Godsill, Simon, et al., "Detection and suppression of keyboard transient noise in audio streams with auxiliary keybed microphone," Abstract, 1 page, 2015 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), Apr. 19-24, 2015, Brisbane, QLD, Australia (Abstract available at http://ieeexplore.ieee.org/document/7177995/, downloaded on Feb. 28, 2018.
Hershey, Shawn, et al., "CNN Architectures for Large-Scale Audio Classification," Jan. 10, 2017, 5 pages, Google, Inc., New York, NY, and Mountain View, CA, USA.
Hradis, Michael, et al., "Voice activity detection from gaze in video mediated communication," ACM, Mar. 28-30, 2012 http://medusa.fit.vutbr.cz/TA2/TA2., 4 pages.
Hui, J., et al., "An IPv6 Routing Header for Source Routes with the Routing Protocol for Low-Power and Lossy Networks (RPL)", Request for Comments 6554, Mar. 2012, 12 pages, Internet Engineering Task Force Trust.
Kuklinski, Slawomir, et al., "Design Principles of Generalized Network Orchestrators," 2016 IEEE International Conference on Communications Workshops (ICC), May 23, 2016, pp. 430-435.
Liu, Tao, et al., "Data-driven Link Quality Prediction Using Link Features," ACM Transactions on Sensor Networks, Feb. 2014, 35 pages.
McKenna, Shannon, et al., "Acoustic Event Detection Using Machine Learning: Identifying Train Events," Sep. 2017, pp. 1-5, http://cs229.stanford.edu/proj2012/McKennaMcLaren-AcousticEventDetectionUsingMachineLearningIdentifyingTrainEvents.pdf, downloaded on Feb. 28, 2018.
Newman, M. E. J., "Analysis of weighted networks," Phys. Rev. E 70, 056131, Jul. 20, 2004, 9 pages, http://arxiv.org/pdf/condmat/0407503.pdf.
Newman, W. E. J., "Modularity and Community Structure in Networks", Proceedings of the National Academy of Sciences of the United States of America, Jun. 2006, vol. 103, No. 23, pp. 8577-8582, PNAS, Washington, DC.
Piczak, Karol J., "Environmental Sound Classification With Convolutional Neutral Networks," 2015 IEEE International Workshop on Machine Learning for Signal Processing, Sep. 17-20, 2015, Boston, USA.
Raghavendra, Kulkami V., et al., "Computational Intelligence in Wireless Sensor Networks: A Survey," Abstract, 1 page, IEEE Communications Surveys & Tutorials, May 27, 2010.
Salamon, Justin, et al., "Deep Convolutional Neutral Networks and Data Augmentation for Environmental Sound Classification," IEEE Signal Processing Letters, Accepted Nov. 2016, 5 pages.
Siddiky, Feroz Ahmed, et al., "An Efficient Approach to Rotation Invariant Face Detection Using PCA, Generalized Regression Neural Network and Mahalanobis Distance by Reducing Search Space," Abstract, 1 page, 10th International Conference on Computer and Information Technology, Dec. 2007, Dhaka, Bangladesh.
Singh, Shio Kumar, et al., "Routing Protocols in Wireless Sensor Networks—A Survey," International Journal of Computer Science & Engineering Survey (IJCSES) vol. 1, No. 2, Nov. 2010, pp. 63-83.
Tang, Pengcheng, et al., "Efficient Auto-scaling Approach in the Telco Cloud using Self-learning Algorithm," 2015 IEEE Global Communications Conference (Globecom), Dec. 6, 2015, pp. 1-6.
Tang, Yongning, et al., "Automatic belief network modeling via policy interference for SDN fault localization," Journal of Internet Services and Applications, Jan. 20, 2016, pp. 1-13, Biomed Central Ltd., London, UK.
Ting, Jo-Anne, et al., "Variational Bayesian Least Squares: An Application to Brain-Machine Interface Data," Neural Networks, vol. 21, Issue 8, Oct. 2008, pp. 1112-1131, Elsevier.
Tsang, Yolanda, et al., "Network Radar: Tomography from Round Trip Time Measurements," ICM'04, Oct. 25-27, 2004, Sicily, Italy.
Vasseur, JP., et al., "Routing Metrics Used for Path Calculation in Low-Power and Lossy Networks," Request for Comments 6551, Mar. 2012, 30 pages, Internet Engineering Task Force Trust.
Winter, T., et al., "RPL: IPv6 Routing Protocol for Low-Power and Lossy Networks," Request for Comments 6550, Mar. 2012, 157 pages, Internet Engineering Task Force Trust.
Zhang, Xiaoju, et al., "Dilated convolution neutral network with LeakyReLU for environmental sound classification," Abstract, 1 page, 2017 22nd International Conference on Digital Signal Processing (DSP), Aug. 23-25, 2017, London, U.K.
Zinkevich, Martin, et al. "Parallelized Stochastic Gradient Descent," 2010, 37 pages.

* cited by examiner


100
132
All other participants
Least jitter
Media GW B
114
146b
142b
144
Internet
102
Least delay
Media GW C
116
112
Closest
Media GW A
146a
142a
130
User

FIG. 1


200
212
Collaboration Cloud Cluster 1 @ RTP
214
Collaboration Cloud Cluster 2 @ RCDN
216
Collaboration Cloud Cluster 3 @ SJ
Collaboration Cloud Provider
250
Internet
202
Best Effort Network
User's media quality ratings.
New Meeting Request
230
RTP Building A
232
Home
234
SJ Building A

FIG. 2


300
Media GW C
Media GW B
Media GW A
302c
302b
302a
<Actual>
Time-series
Data
304
Machine
Learning
(Step 1)
306
<Prediction>
Network
Metrics
308
<Actual>
Client Attributes
310
Machine
Learning
(Step 2)
312
<Prediction>
User Rating
314

FIG. 3

FIG. 4A


400
410
GW Metrics Model Training
Past Data
Predictors
Geolocation
Time of the day
Day of week
GW Workload
Cascading
412
Gateway 1 Response
Packet loss
Jitter
Delay
414
Supervised Learning (Regression)
416
430
Prediction Step 1
Current Data
Predictors
Geolocation
Time of the day
Day of week
GW Workload
Cascading
432
Metrics Model for GW1
434
Prediction for GW1
Packet loss
Jitter
Delay
436
To FIG. 4B


401
User Rating Model Training
450
Gateway Responses
Packet loss
Jitter
Delay
452
Merge
Client Predictors
FEC
TCP fallback
ICE failure
AEC algorithm
Noise level
Codec
Resolution
Resource consumption
GPS
Device Type / Spec.
Connectivity Type
Geolocation
454
Client Response
User Ratings (1-5)
456
Past Data
Supervised Learning (Regression)
458
Prediction Step 2
470
Client Predictors
FEC
TCP fallback
ICE failure
AEC algorithm
Noise level
Codec
Resolution
Resource consumption
GPS
Device Type / Spec.
Connectivity Type
Geolocation
472
Merge
Gateway Predictions
Packet loss
Jitter
Delay
Current Data
Model for user rating
476
Prediction
User Ratings (1-5)
478
Predicted from Step-1 ML
436
From FIG. 4A
(Model 434)

FIG. 4B

Geolocation	Meeting time and duration	Day of week	Device Type	Connectivity Type	Media Gateway	User Rating
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-2	5
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-2	5
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-2	5
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-3	4
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-1	3
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Monday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Tuesday	Desktop	Ethernet	Media-Gateway-3	4
RTP Building-A	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Media-Gateway-2	5
RTP Building-A	9:00 - 9:45 EST	Thursday	Desktop	Ethernet	Media-Gateway-1	5
RTP Building-A	9:00 - 9:45 EST	Friday	Desktop	Ethernet	Media-Gateway-1	5

500

FIG. 5

FIG. 6


610
PHASE 1
Generic Prediction for New Users
620
PHASE 2
Profiling
630
PHASE 3
Personalized Prediction for Frequent Users
612
ML Regression
616
Generic Model
618
Predicted MOS
614
Telemetrics
622
ML Clustering
626
ML Collaborative Filtering
624
Actual subjective ratings from user
632
Personalized Model
634
Predicted MOS
614
Telemetrics

FIG. 7B


614
Past Telemetrics (all users)
710
Past MOS (all users)
622
Machine Learning
Clustering
732
Scenarios
Scenario A
Scenario B
Scenario C
Scenario D
User 1
User 2
User 3
User 4
5
2
4
1
1
3
5
3
3
2
730
626
Machine Learning
Collaborative Filtering
632
Personalized Model

FIG. 7A


614
Past Telemetrics (all users)
710
Past MOS (all users)
MOS
RTT
Jitter
Bit Rate
Loss
5
1
3
720
612
Machine Learning
Regression
616
Generic Model


Keith
SIP Server with ML Model
Eric
Pre-INVITE with Eric's extended SDP
Pre-OK with Keith's extended SDP
Machine Learning prediction of MOS based on Eric and Keith's SDP
Pre-INVITE with Eric's extended SDP
Pre-OK with predicted MOS, prediction factors and Keith's extended SDP
INVITE
INVITE
TRYING, RINGING, OK
TRYING, RINGING, OK
Media Stream (RTP)
BYE, OK
BYE, OK
Subjective MOS
Subjective MOS
Update model based on actual MOS
Keith Griffith
Out of Office Till Tomorrow
Our desks are right next to the conference rooms Johannesburg and Durban in Bldg 13. There are also 3 quiet rooms nearby, but they seem occupied most of the time.
Are these large conference rooms in the building that can take 20+ people? Like the ground floor globalization/virtualization rooms that were in 30 by the cafe?
Yes, the largest room we have is SOUTH AFRICA ALPHA that can take exactly 20 people. We may bring in extra chairs to fit more.
OK. Thanks.
Write message
Send
Predicted rating of this call
Why?
Proceed
Cancel
Current Network Conditions
Keith is currently on a network with unusually high latency. This may impact the call quality.
804
820
802
830
832
834
838
838
840
840
842
844
844
848
850
836
846
810A
810
814
816
818
810
812
824
826
822
820
810

FIG. 8

FIG. 9


904
Example of an extended SDP
v=0
o=eric 2890844526 2890842807 IN IP4 10.47.16.5
s=sync-up
i=regular 1:1 sync-up
e=erichen3@cisco.com (Eric Chen)
c=IN IP4 224.2.17.12/127
t=2873397496 2873404696
a=recvonly
m=audio 49170 RTP/AVP 0
m=video 51372 RTP/AVP 99
a=rtpmap:99 h263-1998/90000
b=1324
a=bandwidth_variance:523
a=rtt:213
a=net:wifi
a=ua:ios
a=wme:3.2
a=hw:iPhone6,2
a=...
906
Parameters utilized to contstruct feature vectors for machine learning
902

FIG. 10


START
1002
GENERATE A PLURALITY OF SCENARIOS FROM A PLURALITY OF NETWORK METRICS
1004
RETRIEVE RATINGS FROM A PLURALITY OF USERS
1006
ASSIGN THE RATINGS TO THE PLURALITY OF SCENARIOS
1008
FILTER ONE OR MORE USERS BASED ON SIMILARITIES OF THE RATINGS FOR THE PLURALITY OF SCENARIOS WITH ONE OR MORE CURRENT NETWORK METRICS
1010
FORECAST AN EXPECTED CALL QUALITY BASED ON THE RATINGS OF THE ONE OR MORE FILTERED USERS
END


1100
Westmeadows
Melbourne Airport
1104
Gladstone Park
Keilor
Keilor Downs
1112
Essendon Airport
1110
St Albans
Keilor East
1106
Essendon
Coburg
Preston
2 h 19 min
40 min
34.7 km
Moonee Ponds
Maribyrnong
1108
Brunswick East
Albion
Sunshine
Maribyrnong
Braybrook
Melbourne Zoo
Sunshine West
Footscray
Brooklyn
Yarraville
Melbourne
Port Melbourne
Altona North
Newport
South Yarra
Williamstown
St Kilda
Altona
Elwood Primary School
Elsternwick
1102

FIG. 11

Geolocation	Date	Meeting Time and During	Day of week	Device Type	Connectivity Type	Host Cluster	{Packet loss, Jitter, Delay} = Poor
ALT1	Jan. 9, 2017	9:00 - 9:45 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
ALT1	Jan. 9, 2017	9:05 - 9:45 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M79	Jan. 9, 2017	9:10 - 9:45 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{10%, 1ms, 50ms} = Y
M79	Jan. 9, 2017	9:13 - 9:43 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{10%, 1ms, 50ms} = Y
M1	Jan. 9, 2017	9:20 - 9:50 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M1	Jan. 9, 2017	9:07 - 9:45 EST	Monday	Mobile	LTE, Carrier 1	Cluster-1	{0%, 1ms, 50ms} = N
ALT1	Jan. 10, 2017	8:58 - 9:42 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
ALT1	Jan. 10, 2017	9:00 - 9:45 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M79	Jan. 10, 2017	9:03 - 9:43 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{7%, 1ms, 50ms} = Y
M79	Jan. 10, 2017	9:08 - 9:43 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{7%, 1ms, 50ms} = Y
M1	Jan. 10, 2017	9:00 - 9:45 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M1	Jan. 10, 2017	9:03 - 9:49 EST	Tuesday	Mobile	LTE, Carrier 1	Cluster-1	{0%, 1ms, 50ms} = N
ALT1	Jan. 11, 2017	9:00 - 9:45 EST	Wednesday	Mobile	LTE, Carrier 1	Cluster-2	{1%, 1ms, 50ms} = N
ALT1	Jan. 11, 2017	9:00 - 9:43 EST	Wednesday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M79	Jan. 11, 2017	9:07 - 9:52 EST	Wednesday	Mobile	LTE, Carrier 1	Cluster-1	{15%, 1ms, 50ms} = Y
M79	Jan. 11, 2017	9:00 - 9:49 EST	Wednesday	Mobile	LTE, Carrier 1	Cluster-1	{15%, 1ms, 50ms} = Y
M1	Jan. 11, 2017	9:08 - 9:51 EST	Wednesday	Mobile	4G, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M1	Jan. 11, 2017	9:00 - 9:45 EST	Wednesday	Desktop	Ethernet	Cluster-1	{0%, 1ms, 50ms} = N
ALT1	Jan. 12, 2017	9:03 - 9:43 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-2	{1%, 1ms, 50ms} = N
ALT1	Jan. 12, 2017	9:00 - 9:48 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M79	Jan. 12, 2017	9:11 - 9:53 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-1	{15%, 1ms, 50ms} = Y
M79	Jan. 12, 2017	9:20 - 9:58 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-1	{15%, 1ms, 50ms} = Y
ALT1	Jan. 12, 2017	9:03 - 9:43 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-2	{1%, 1ms, 50ms} = N
ALT1	Jan. 12, 2017	9:00 - 9:48 EST	Thursday	Mobile	LTE, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M2	Jan. 12, 2017	9:03 - 9:51 EST	Thursday	Mobile	4G, Carrier 1	Cluster-1	{1%, 1ms, 50ms} = N
M2	Jan. 12, 2017	9:00 - 9:25 EST	Thursday	Desktop	Ethernet	Cluster-1	{0%, 1ms, 50ms} = N

FIG. 12

1200

FIG. 13


START
1302
RECEIVE AN INDICATION FOR AN INITIATION OF A COLLABORATION
1304
DETERMINE A CURRENT LOCATION AND DESTINATION
1306
RETRIEVE HISTORICAL NETWORK METRICS
1308
DETERMINE POTENTIAL DEGRADATION IN MEDIA QUALITY OF THE COLLABORATION
1310
NOTIFY OF POTENTIAL DEGRADATION
END

FIG. 14


1400
INTERFACES
1402
CPU 1404
MEMORY
1406
PROCESSOR
1408
1410

FIG. 15


1500
Input Device
1545
Output Device
1535
Communication Interface
1540
Memory
1515
ROM
1520
RAM
1525
Storage Device
1530
MOD 1
1532
MOD 2
1534
MOD 3
1536
Connection
1505
cache
1512
Processor
1510

RESOURCE SELECTION USING QUALITY PREDICTION

REFERENCE TO RELATED APPLICATIONS

This application is a Continuation of U.S. application Ser. No. 15/659,356, entitled PREDICTIVE MODEL FOR VOICE/VIDEO OVER IP CALLS, filed Jul. 25, 2017, the contents of which are incorporated by reference in its entirety.

TECHNICAL FIELD

The present technology pertains to media resources and communications, and more particularly pertains to selecting a media resource or communication path based on a quality prediction.

The present technology pertains to voice/video over IP calls, and more particularly pertains to predicting quality of a voice/video over IP call before initiated.

The present technology pertains to collaboration services, and more particularly pertains to prediction of media quality along a route during collaboration services.

BACKGROUND

Conventionally, a media gateway is chosen either based on its location, the location of a requesting client, or both. Media gateways may also be chosen through load-balancing based on the current workload that is distributed over alternative gateways. The former approach overlooks the fact that physical distance does not always correlate to network performance. The latter approach fails to address the varying patterns and requirements of multiple media streams involved in, for example, a web conference call. For example, audio traffic can be smooth while video traffic can have numerous spikes, and audio traffic may be more delay-sensitive than video traffic. Additionally, user preferences, device type, and communication style may result in different network requirements and priorities on a user-by-user basis.

Accordingly, both conventional approaches can lead to sub-par performance in a variety of situations, and as such, it would be desirable to provide an improved ability to perform resource selection.

Although there has been much improvement to the quality of Voice over IP (VoIP), the quality can still fluctuate significantly due to the dynamic nature of underlying networks and can be affected by various factors such as jitter, latency and bandwidth. There is a definite need to mitigate the occurrence of media quality issues to deliver a good collaboration experience to end users.

Subscription-based Cloud Collaboration Services have made consuming services more cost efficient for Enterprises and Collaboration Service Providers. Subscription-based Cloud Collaboration Services generally operate with a "best effort" routing through communication networks (e.g., the Internet). Accordingly, traversing a network using "best effort" removes the Enterprises and Collaboration Service Providers ability to control the end-user media experience.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to describe the manner in which the above-recited and other advantages and features of the disclosure can be obtained, a more particular description of the principles briefly described above will be rendered by reference to

specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only exemplary embodiments of the disclosure and are not therefore to be considered to be limiting of its scope, the principles herein are described and explained with additional specificity and detail through the use of the accompanying drawings in which:

FIG. **1** illustrates an example environment in which aspects of the present disclosure can operate;

FIG. **2** illustrates an example environment in which aspects of the present disclosure can operate;

FIG. **3** illustrates an example modeling and quality prediction process;

FIG. **4**A illustrates an example architecture and associated information flow associated with a method of the present disclosure;

FIG. **4**B illustrates additional components of the example architecture and associated information flow of FIG. **4**A;

FIG. **5** illustrates an example input data set that can be employed by aspects of the present disclosure;

FIG. **6** illustrates a schematic diagram of an example system for forecasting an expected call quality;

FIG. **7**A illustrates a diagram of an example process for generating a generic model for forecasting expected call quality;

FIG. **7**B illustrates a diagram of an example process for generating a personalized model for forecasting expected call quality;

FIG. **8** illustrates a diagram of an example of a predictive modeling use case;

FIG. **9** illustrates an example of an extended session description protocol message format and fields;

FIG. **10** illustrates an example method for forecasting an expected call quality;

FIG. **11** illustrates a map of a travel router during an example collaboration;

FIG. **12** illustrates an example historical data set used to predict quality of a collaboration based on future geolocation;

FIG. **13** illustrates an example method for predicting media quality;

FIG. **14** illustrates an example network device; and

FIG. **15** illustrates an example of a system for implementing certain aspects of the present technology.

DESCRIPTION OF EXAMPLE EMBODIMENTS

Additional features and advantages of the disclosure will be set forth in the description which follows, and in part will be obvious from the description, or can be learned by practice of the herein disclosed principles. The features and advantages of the disclosure can be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. These and other features of the disclosure will become more fully apparent from the following description and appended claims, or can be learned by the practice of the principles set forth herein.

Various embodiments of the disclosure are discussed in detail below. While specific implementations are discussed, it should be understood that this is done for illustration purposes only. A person skilled in the relevant art will recognize that other components and configurations may be used without parting from the spirit and scope of the disclosure.

OVERVIEW

The connection quality offered by a media gateway often fluctuates, and can be difficult to predict, or even account for,

when making a selection of a media gateway to handle a connection request. Accordingly, the approaches herein are provided to address these issues, by providing a two-step modeling process that can predict both quality metrics for a given gateway, as well as predicting an associated user rating corresponding to the quality metrics. In this manner, all available gateways can be analyzed and ranked, such that an incoming connection request is routed to the gateway that is predicted to have the highest user rating.

The quality of calls, such as Voice over IP (VoIP) calls, can fluctuate significantly due to the dynamic nature of networks, and can be affected by various factors such as jitter, latency, and bandwidth, for example. The approaches herein can address call quality issues, including voice/video quality, by forecasting the expected voice/video quality, identifying factors affecting the call quality, and taking proactive actions to improve the call experience. For example, the expected voice/video quality of a call can be forecasted by performing an automated and silent practice, background, or "dry" run and applying predictive models on telemetrics collected from this run. The approaches herein can predict how a user may rate the call experience, and identify the contributing factors. These factors can be used to take proactive action to improve the call experience and make the related information available through the application in the event that UE (User Equipment) designers wish to display call experience reason information to the user.

Disclosed is a system, method and computer readable medium for forecasting an expected quality of a call. In some examples, a system or method can generate a plurality of scenarios from a plurality of network metrics, retrieve historical ratings for the plurality of network metrics from a plurality of users, and assign the historical ratings for the plurality of network metrics to the plurality of scenarios. The system, method and computer readable medium can filter one or more of the plurality of users based on similarities of the historical ratings for the plurality of scenarios with one or more current network metrics, and forecast an expected call quality based on the historical ratings of the one or more filtered users.

Disclosed is an improved system, method and computer readable medium enabling collaboration service providers to more accurately predict packet loss, jitter and delay based on current session, historical session and user location parameters. The prediction can be used to forecast the occurrence of poor media quality at the current location and potential future locations.

Also disclosed is a system, method and computer readable medium for predicting media quality. The system, method and computer readable medium can receive an indication for an initiation of a collaborative virtual meeting, determine a current location and destination of a client device, retrieving historical network metrics data (e.g., location, destination, day of the week, device type, meeting time, connectivity type, and host cluster) and real-time network metrics data (e.g., day of the week, device type, current time, connectivity type, and host cluster), determine possible degradation in media quality of the collaborative virtual meeting for the current location and the destination based on the historical network metrics data and the real-time metrics data and notify the client device of the possible degradation (e.g., the notification can be displayed on the user device a map illustrating the current location and destination and can also display alerts on the map corresponding to the notifications of possible degradation). In other examples, the notification can display one or more routes from the current location to the destination, display the alerts along the routes; and highlight the route with least degradation.

In some examples, the system, method and computer readable medium can determine possible degradation along one or more routes between the current location and the destination and notify the client device on possible degradation along the one or more routes. In some examples, the system, method and computer readable medium can provide a recommended route with the least possible degradation.

DESCRIPTION

Disclosed is a system and method for selection of a media gateway based on the suggested (or required) criteria. While the end-to-end quality of cloud-based web conferencing cannot be fully managed due to the best-effort nature of the Internet, the user experience can be predicted (an optimized) by routing media streams through media gateways that match the suggested (or required) criteria.

FIG. **1** illustrates a first example Environment **100** in which aspects of the present disclosure can operate. In Environment **100**, a First User **130** connects to an online or networked-based communication session with one or more Additional Participants **132**. Such online communication sessions are typically hosted or otherwise provided by a third-party service (e.g., a mobile or web application for transmitting audio, visual, or audiovisual data between participants). In the context of FIG. **1**, the network-based communication session is transmitted over Internet **102**, although it is understood that various other networking protocols and techniques may be employed without departing from the scope of the present disclosure.

Within Environment **100**, a cloud-based third-party communication service provider (not illustrated) provides three Media Gateways **112**, **114**, and **116** that are connected to the Internet **102**. It is noted that the three Media Gateways are provided at geographically distinct locations. For example, although FIG. **1** is not drawn to scale, First User **130** is in closer geographic proximity to Media Gateway **112** than to Media Gateway **114**, and the Additional Participants **132** are in closer geographic proximity to Media Gateway **114** than to Media Gateway **112**. Neither First User **130** nor Additional Participants **132** have Media Gateway **116** as their media gateway in closest geographic proximity.

Under one conventional theory of network routing and operation, an incoming user request will be routed to the media gateway that is closest to the user's geographical location. As illustrated, an incoming request from First User **130** to establish a communication session would be routed to Media Gateway **112**. Similarly, an incoming request from Additional Participants **132** to establish a communication session would be routed to Media Gateway **114**. Under this theory, an incoming request from either First User **130** or Additional Participants **132** would not be routed to Media Gateway **116** as long as Media Gateway **112** and **114** continue to remain available.

However, such an approach is limited by its failure to consider any factors beyond geographical proximity when making routing decisions. For example, the path comprising Segments **146***a* and **146***b* utilizes the closest media gateway to First User **130** and Additional Participants **132**, respectively, but it can often be the case that the path comprising Segments **142***a* and **142***b* may provide a communication session with less delay, even though Media Gateway **116** is farther away from First User **130** than Media Gateway **112**. Such a situation might arise if Media Gateway **116** has more available bandwidth than Media Gateway **112**, is outfitted

with higher speed components, is provided on a higher speed communication link, and various other factors that will be appreciated by one of ordinary skill in the art.

Furthermore, in some scenarios, total delay might not be the most important determining factor. For example, jitter may be a more important factor than delay, particularly in the case of a communication session that transmits video data. In this scenario, the most desirable path for connecting First User **130** and Additional Participants **132** to a communication session would be Path **144**, which causes both parties to make use of the same Media Gateway **114**. Even though this is the farthest media gateway from First User **130**, it can nevertheless be the most desirable gateway to be utilized in a given communication session.

FIG. **2** illustrates a second example Environment **200** in which aspects of the present disclosure may operate. Unlike Environment **100**, where the constituent Media Gateways **112**, **114**, **116** of a communication or application service provider were provided in disparate geographical locations, Environment **200** depicts a collaboration Cloud Provider **250** with constituent Media Gateways (labeled herein as Collaboration Cloud Clusters) **212**, **214**, **216** that are provided in the same geographical location, or in the same geographical location as an associated user location. This enables collaboration Cloud Provider **250** to achieve a greater degree of control, oversight, and predictability over the performance of the Individual Clusters **212**, **214**, **216** as well as the performance of the overall communication or collaboration service that is provided by these clusters.

However, collaboration Cloud Provider **250** remains unable to account for or control various mitigating factors on the customer or participant end. That is, users of collaboration Cloud Provider **250** (e.g. participants in communication sessions) might all experience different qualities of service. Users might be disposed at different geographic and physical locations, such as RTP Building A (referred to herein as Building **230**), Home **232**, and SJ Building A (referred to herein as Building **234**). Each geographic location might be associated with a different network provider or ISP, a different network type (wired, wireless, cellular), a different network quality, a different network load factor, and so on. Each user might be associated with a different type of device, with different properties and capabilities. In short, a variety of factors can influence the end-to-end transmission of a communication session, including the fact that the communication session must traverse Internet **202**, which is an unpredictable, best-effort network.

Even in scenarios in which all user-controlled variables remain constant (e.g. a user joins the same video conference every Monday at 9 AM, using his desktop, from Building **230**, and connecting to collaboration Cloud Cluster **212**), a wide range of performance characteristics can be experienced in terms of the perceived quality of the video conference, due to factors that are both beyond the user's control and beyond the user's ability to see.

For example, on a given Monday where the user experiences degraded quality, a higher than normal number of users in Building **230** might be attending meetings also scheduled to run concurrently with the user's 9 AM video conference. Hence, the network media path between the user's desktop and collaboration Cloud Cluster **212** might experience bandwidth problems due to the high number of media flows. Alternatively, collaboration Cloud Cluster **212** might be handling a large number of meetings from different companies, such that the bandwidth of collaboration Cloud Cluster **212**'s WAN link to its Internet Service Provider is saturated due to the high number of media flows. As a further alternative, other application flows within the Internet Service Provider environment might be impacting the user's perceived quality of his video conference. For example, the Internet Service Provider might be handling a large number of IP media streams for a famous TV show at 9 AM, where the IP media streams are from a content provider cloud in the same geographic location as collaboration Cloud Cluster **212**, such that the content provider cloud connects to the same core network of the Internet Service Provider.

Accordingly, in one aspect of the present disclosure, participants in a video conference or other online communication session are asked to provide a quality rating after the communication session has ended. An example of such quality ratings is seen in FIG. **5**. As will be discussed later, these received user quality ratings are associated with their corresponding network, conference, and other parameters, and are then stored for subsequent use.

FIG. **3** illustrates an example two-step modeling and quality prediction method **300** of the present disclosure. The method is applied to one or more media gateways of the illustrated Media Gateways **302***a*, **302***b*, **302***c*, that are coupled to or otherwise associated with a network, with the end result being that a User Rating **314** of the quality provided by a given media gateway can be predicted given the inputs of current network state **304** and current Client Attributes **310**. In this manner, a user request to join or initiate a communication session can be routed to the media gateway that will yield the highest predicted user rating. It is noted that the method is applied to one media gateway at a time, although multiple media gateways can be analyzed in parallel.

FIG. **3** provides a high-level overview of the processing and data flows that are discussed in greater depth with respect to FIGS. **4**A and **4**B. The two inputs of current time-series Network Data **304** and current Client Attributes **310** can be received simultaneously, although this is not required. The current Network State **304** is fed into a First Machine Learning Module **306**, which generates predicted Network Metrics **308** for the given media gateway being analyzed, where the predicted Network Metrics **308** are based on the current Network Data **304**. First Machine Learning Module **306** is operable to perform this function because it is trained on a series of historical network state data, as will be described below. In general, the current Network Data **304** encompasses a wider variety of parameters than the predicted Network Metrics **308**. In some embodiments, the predicted Network Metrics **308** can be thought of as the factors upon which user rating is based—e.g. packet loss, delay, jitter.

A Second Machine Learning Module **312** receives these predicted Network Metrics **308**, as well as the current Client Attributes **310**. Second Machine Learning Module **312** then generates the predicted User Rating **314** corresponding to the given media gateway being analyzed (which here is Media Gateway **302***a*), where the predicted User Rating **314** is based on both the predicted Network Metrics **308** and the current Client Attributes **310**. Second Machine Learning Module **312** is operable to perform this function because it is trained on a series of historical network metrics, user attribute data, and user rating data, as will be described below.

FIG. **4**A illustrates an example architecture and associated information Flow **400** associated with a method of the present disclosure. In particular, FIG. **4**A presents a detailed view of the first step of the two-step modeling process described in FIG. **3**, as applied to any given media gateway. Recalling that this first step corresponds to generating pre-

dicted network metrics for the given media gateway, e.g. predicted gateway metrics, illustrated are a Gateway Metrics Model Training Module **410** and Gateway Metrics Prediction Module **430**.

Gateway Metrics Model Training Module **410** is operable to train the First Machine Learning Module **416** on a series of historical time-series network data. This historical time-series network data comprises, as illustrated, Network Predictors **412** and Gateway Response **414**. While the predicted gateway metrics are generated for a single given media gateway, the gateway metrics model training is performed over all media gateways. Continuing the example set by FIG. **3**, where three media gateways are present, there are three sets of Network Predictors **412** and three sets of Gateway Response **414** received at Gateway Metrics Model Training Module **410**. These network predictors and gateway responses can be stored in a database that is coupled to the network, such that the network and its constituent components can be polled in order to collect or refresh one or more of the network predictors and gateway responses.

The Network Predictors **412** include geographic location, time of day, day of week, gateway workloads, and cascading information, although it is appreciated that the Network Predictors **412** can comprise additional factors that influence the performance of a media gateway. The Gateway Response **414** are the metrics that result due to various combinations of network predictors. That is, the Gateway Response **414** are factors such as packet loss, jitter, and delay that are influenced by the Network Predictors **412**.

In some instances, a user can specify a threshold of historical data (e.g. Network Predictors **412** and Gateway Response **414**) that must be collected in order for the First Machine Learning Module **416** to be trained. In other words, a user can specify a minimum amount of time that data must span in order for adequate analysis and predictions to be performed. For example, a threshold for the minimum amount of historical data that must be collected in order to detect patterns and make predictions might be four weeks. This can alternatively be referred to as a pattern threshold.

Another type of threshold might also be provided—a lifetime threshold. The lifetime threshold can be employed to remove stale data, as networks evolve over time and may not be adequately or accurately characterized by performance data that are too old. For example, the lifetime threshold might be 90 days. Any data, of either network predictors or gateway responses, that was collected more than 90 days ago will be removed. In another example, a threshold might be a change in hardware or software (e.g., upgrade, replacement, etc.) in a Media Gateway and/or Radio Access Network (RAN) should invalidate the relevant leanings (e.g., the prediction may not be right after such changes).

In essence, the Network Predictors **412** and the Gateway Response **414** are provided as data that are causally linked to one another—but no indication of this causal link is provided. This is the purpose of the First Machine Learning Module **416**, which utilizes Network Predictors **412** and Gateway Response **414** as a training data set to perform machine learning and construct a predictive model of the causal link between the two inputs. The First Machine Learning Module **416** can be provided in some embodiments as a regression module, although other machine learning techniques may additionally be employed without departing from the scope of the present disclosure.

First Machine Learning Module **416** then outputs a predictive model of Gateway Metrics **434** for each of the gateways represented in Network Predictors **412** and gateway responses. In some embodiments, First Machine Learning Module **416** may generate a single predictive model of gateway metrics, rather than generating a predictive model for each gateway.

From here, the Gateway Metrics Model Training Module **410** outputs the one or more predictive models to the Gateway Metrics prediction module **430**. Gateway Metrics Prediction Module **430** receives as input, or utilizes a polling service to collect in real-time, a snapshot of the current Network Predictors **432**. As illustrated, the parameters contained within the current Network Predictors **432** are similar to those contained within the historical Network Predictors **412**, although it is appreciated that the two are not necessarily the same.

The current Network Predictors **432** are then input into the one or more predictive models **434** for each media gateway. The one or more Predictive Models **434** generate a corresponding one or more predicted Gateway Metrics **436** for each gateway being analyzed. As illustrated, the parameters contained within the predicted Gateway Metrics **436** are similar to those contained within the historical Gateway Response **414**, although it is appreciated that the two are not necessarily the same.

While it is possible to measure the actual gateway metrics right before a communication session, rather than relying upon predicted Gateway Metrics **432**, the measurement of the actual gateway metrics is momentary, and therefore has limited use beyond the time at which they are captured. Relying upon the capture of actual gateway metrics before a communication session fails to account for any potential fluctuation or other variations that commonly occur over the course of a communication session. On the other hand, the one or more Predictive Models **434** advantageously enables the gateway metrics to predicted over the entire duration of the communication session. Keeping in mind that a goal is to select the appropriate media gateway for an incoming request for a communication session, it is clear that the ability to understand the gateway metrics over the whole duration of a communication session is far more valuable that simply measuring the gateway metrics at the initiation of a communication session.

As a simplified example, consider the following. At 8:59 AM, a user transmits a request to join a 9 AM video conference. At 8:59 AM, Media Gateway B has low delay and is utilizing only 10% of its bandwidth. Media Gateway A has moderate delay and is utilizing 50% of its bandwidth. A media gateway selection based only upon a snapshot of actual gateway metrics would select Media Gateway B to handle the user request to join the 9 AM video conference.

However, it may be the case that Media Gateway B historically sees a bandwidth utilization in excess of 90% from the hours of 9 AM to noon, while Media Gateway A does not historically see any bandwidth utilization changes. In this case, it is appreciated that it would be preferable to select Media Gateway A to handle the user's request to join the 9 AM video conference, rather than Media Gateway B. This is because over the entire duration of the video conference, Media Gateway A will likely offer a better, higher quality experience than Media Gateway B, even though Media Gateway B is instantaneously offering better connection parameters.

Unlike conventional approaches, the disclosed system and method leverage historical time-series data of network metrics and predictors to perform more sophisticated analysis and ultimately, provide superior gateway selection. This gateway selection process is described with respect to FIG. **4**B, which illustrates an additional portion **401** of the archi-

tecture and associated information flow **400** that is depicted in FIG. **4**A. In particular, FIG. **4**B presents a detailed view of the second step of the two-step modeling process described herein. Illustrated are a User Rating Model Training Module **450** and a User Rating Prediction Module **470**.

User Rating Model Training Module **450** is operable to train the Second Machine Learning Module **458** on a series of historical data. This historical data includes Gateway Responses **452** (which can be similar to the Gateway Response **414** of FIG. **4**A), Historical Client Predictors **454**, and Historical Client Responses **456**. As illustrated, a single model is generated for all users or clients, although it is understood that unique models could be generated for each given user or client, in the same manner in which unique models were generated for each gateway in FIG. **4**A.

The Gateway Responses **452** and the Client Predictors **454** are merged into a single set of state parameters that have a causal relationship with the Historical Client Responses **456**. That is, the combination of a given gateway response and given set of client predictors yielded a corresponding client response. An example of such a data set is illustrated as Data Set **500** of FIG. **5**, which shows a column labeled 'User Rating'. As described with respect to FIG. **4**A, a user may specify a pattern threshold and a lifetime threshold to the historical data that is collected.

The Second Machine Learning Module **458** receives as input the merged Client Predictors **454** and Gateway Responses **452**, and the client responses **456**. These inputs are used as a training data set to perform machine learning and construct a predictive model of the causal link between gateway responses and client predictors as input and client responses as output. The Second Machine Learning Module **458** can be provided in some embodiments as a regression module, although other machine learning techniques may additionally be employed without departing from the scope of the present disclosure.

Second Machine Learning Module **458** then outputs a Predictive Model **476** for user ratings. This Predictive Model **476** is received at the user rating prediction module **470**. User rating Prediction Module **476** receives as an additional input, or utilizes a polling service to collect in real-time, a snapshot of the current Client Predictors **472**. As illustrated, the parameters contained within the current Client Predictors **472** are similar to those contained within the historical Client Predictors **454**, although it is appreciated that the two are not necessarily the same.

The current Client Predictors **472** are then merged with the predicted Gateway Metrics **436** output from model **434** of Gateway Metrics prediction module **430** of FIG. **4**A. The merged list is then input into the model **476** for user rating, which is specifically designed to predict an output user rating based on an input of client predictors and gateway metrics. In this manner, the model **434** generated by First Machine Learning Module **416** is fed forward as input to the model **476** generated by Second Machine Learning Module **458**.

With these inputs, the user rating model **476** generates a predicted user rating **478**, for the given media gateway given the prevailing current conditions of Network Predictors **432** and Client Predictors **472**. This process is performed for each media gateway that is being investigated for a predicted user rating given the current conditions. Ultimately, a predicted user rating is generated for each media gateway being considered (e.g. all available media gateways when a user request is received). With these predicted user ratings, a selection is then made, such that a user request to initiate or join a communication session is handled by the media gateway that will result in the highest predicted user rating, even if this media gateway would not have otherwise been selected by conventional methods.

Consider the following example, which returns to the example described in FIG. **1**. Assume that a communication session provider is operating the three Media Gateways **112**, **114**, and **116**, and that the communication session provider receives a new communication session request from the First User **130**. Media Gateway **112** is in Raleigh, Media Gateway **114** is in RTP, and Media Gateway **116** is in San Jose. First User **130** is also in RTP, and is using a mobile device at 4:30 PM on a Friday. Also assume that a gateway metrics model and a user rating model have been trained by the first and second machine learning modules, respectively, using historical data from sessions processed in the last 90 days.

The first step is to predict the gateway metrics {Packet Loss, Delay, Jitter} for each gateway using the trained gateway metrics model.

Input Features:

Gateway **112**: {RTP-Raleigh, 4:30 PM, Friday, 20% workload}

Gateway **114**: {RTP-RTP, 4:30 PM, Friday, 80% workload}

Gateway **116**: {RTP-San Jose, 4:30 PM, Friday, 75% workload}

Output of Gateway Metrics Prediction Model {Packet Loss, Delay, Jitter}:

Gateway **112**: {0, 50 ms, 20 ms}

Gateway **114**: {10, 50 ms, 20 ms}

Gateway **116**: {5, 100 ms, 20 ms}

The second step is to predict the user rating for each media gateway using the trained user rating model. The predicted gateway metrics from step one, above, are combined with client parameters to form the input to the user rating model

Input Features:

Gateway **112**: {RTP-Raleigh, 4:30 PM, Friday, 20% workload, (0, 50 ms, 20 ms)}

Gateway **114**: {RTP-RTP, 4:30 PM, Friday, 80% workload, (10, 50 ms, 20 ms)}

Gateway **116**: {RTP-San Jose, 4:30 PM, Friday, 75% workload, (5, 100 ms, 20 ms)}

Output of User Rating Prediction Model:

Gateway **112**: **5** (Excellent)

Gateway **114**: **3** (Moderate)

Gateway **116**: **4** (Good)

Final Selection:

Gateway **112** in Raleigh is selected and assigned for the incoming communication request from the mobile device of user **130** in RTP. In instances where two or more gateways have the same rating, a selection can be made by assigning a higher ranking to the gateway with the closest geographic proximity to the user.

Disclosed is a system and method to forecast the expected voice/video quality of a call. The system and method can apply predictive models on historically collected network metrics. The system and method can also predict how the user may rate the call experience, and provide major contributing factors. These factors can be used to take proactive action to improve the call experience and make the related information available through an application in the event that UE (user equipment) designers wish to display call experience reason information to the user.

FIG. **6** shows a schematic diagram of an example system for forecasting an expected call quality. The system can involve Phase **1** (**610**) for generating a generic prediction for

a new user in the system, Phase **2** (**620**) for profiling the user, and Phase **3** (**630**) for generating a personalized prediction for the user.

At Phase **1** (**610**), when a new user without prior rating feedback enters the system, the user's ratings can be predicted based on Generic Model **616**. Generic Model **616** can be generated based on Telemetrics **614** and trained with Regression Algorithm **612** using Telemetrics **614** as input. In some cases, Generic Model **616** can also be pre-trained with Regression Algorithm **612** using the historical feedback of users in the system. Regression Algorithm **612** can rank the importance of one or more factors contributing to call quality. Non-limiting examples of regression algorithms can include Decision Trees, Random Forest and Extreme Gradient Boosting.

Telemetrics **614** can include new type of metrics (e.g., device specification, wireless signal stability, user travel speed, geographic location, etc.) collected for one or more networks and/or calls. In some cases, Telemetrics **614** can be collected periodically on an ongoing basis. Telemetrics **614** can include metrics associated with the quality of a call, such as jitter, packet loss, round trip time (RTT), etc. Table 1 below illustrates non-limiting examples of metrics.

TABLE 1

Example Metrics

GROUP	ATTRIBUTE
Network	Latency
	Packet loss burst length
	Jitter
	Connection type
	Bandwidth
	FEC
	TCP fallback
	ICE failure
	Incoming queuing delay
	Outgoing queuing delay
	Wireless signal strength
Audio	AEC algorithm
	Bit rate
	Noise level
Video	Bit rate
	Frame rate
	Resolution
	Screen size
	Codec
	Simulcast
Client	User agent type
	Version
	Operating System (OS)
	CPU load
	Travel speed
	Geo-location
GPS	Travel speed
	Geo-location

Generic Model **616** used to generate Predicted Mean Opinion Score (MOS) **618**. MOS **618** can include one or more scores representing the predicted user's call quality rating based on Telemetrics **614**.

At Phase **2** (**620**), after the new user spends more time with the system and provides respective feedback, the user can be profiled to generate a personalized model in Phase **3** (**630**), using Clustering Algorithm **622** and Collaborative Filtering Algorithm **626**.

Here, one or more metrics from Telemetrics **614** can be clustered into a number of "scenarios" using Clustering Algorithm **622**. In some scenarios, the audio quality may far exceed the video quality (or vice versa). In other scenarios, video resolution may be traded off for higher frames per second. For this reason, Clustering Algorithm **622** can include one or more clustering algorithms that scale well with the large volume of metrics data. Non-limiting examples of clustering algorithms include K-Means, DBSCAN, Ward hierarchical clustering, and Birch.

The clusters or scenarios generated by Clustering Algorithm **622**, as well as Subjective User Ratings **624**, can be passed to Collaborative Filtering Algorithm **626** to generate results for the clusters or scenarios which can be used to create Personalized Model **632** in Phase **3** (**630**).

Subjective User Ratings **624** can include actual, subjective past ratings from a user. In some cases, Subjective User Ratings **624** can be grouped and averaged into each corresponding scenario. The dataset can be formatted into a rating matrix for Collaborative Filtering Algorithm **626**. Collaborative Filtering Algorithm **626** can be a machine learning algorithm which can provide recommendations and/or pivoted to approximate how a user may rate a call under a scenario. Each row in the rating matrix can be effectively a profile for a user and each profile may have different levels of completeness. To evaluate whether a user is ready to switch from Generic Model **616** to a personalize model (e.g., Personalized Model **634**), a threshold of the level of completeness may be expected to put in place (e.g. 25%).

At Phase **3** (**630**), Telemetrics **614** and the output from Collaborative Filtering Algorithm **626** can be used to generate Personalized Model **632** for the user. Personalized Model **632** can be a predictive machine learning model that is personalized for the user in order to take into account the user's subjective ratings, recognizing that users may rate the same call experience in different ways. Personalized Model **632** can generate Personalized Predicted MOS **634**, which can include an MOS score representing a predicted user rating of the call experience that is personalized for the particular user.

In some cases, if an upcoming scenario defined by Telemetrics **614** has been experienced and rated in the past by the user, then Personalized Predicted MOS **634** can be adapted from past ratings (e.g., Subjective User Ratings **624**). If the scenario is otherwise new to the user, Collaborative Filtering Algorithm **626** can match Subjective User Ratings **624** against other users and find users with similar rating behaviors. The existing ratings of those users for the specific scenario can be used to predict the rating of this particular user (e.g., Personalized Predicted MOS **634**).

FIG. **7**A shows a diagram of an example process for generating Generic Model **616**. In this example, Telemetrics **614** and MOS Scores **710** can be used to generate Matrix **720** mapping individual MOS scores from MOS Scores **710** to example metrics from Telemetrics **614**. Telemetrics **614** can include past or historical telemetrics from users in the system and MOS Scores **710** can include past or historical MOS scores from the users. In some cases, Telemetrics **614** and MOS Scores **710** can include the telemetrics and MOS scores aggregated from all users in the system.

Matrix **720** can be provided as input for Regression Algorithm **612** to generate Generic Model **616**, which can represent a model generalizing MOS scores and telemetrics for the users in the system.

FIG. **7**B shows a diagram of an example process for generating Personalized Model **632**. In this example, Telemetrics **614** can be provided as input to Clustering Algorithm **622** to generate Scenarios **732**. Scenarios **732** can be based on clusters of metrics from Telemetrics **614**. Scenarios **732** and MOS Scores **710** can then be used to generate Rating Matrix **730**.

Rating Matrix **730** can map individual MOS scores to individual scenarios for each user. The mappings in Rating Matrix **730** can represent respective profiles for the users. The profiles can approximate how each user may rate a call under each scenario. Rating Matrix **730** can then be provided as input to Collaborative Filtering Algorithm **626** to generate Personalized Model **632**. As previously mentioned, Personalized Model **632** can provide a personalized machine learning model for predicting call ratings for a particular user.

FIG. **8** shows a diagram of an example of a predictive modeling use case. The example predictive modeling use case is implemented for a call between users Eric **802** and Keith **804**. Graphical User Interface **810** can be presented to Eric **802** on his communication device (e.g., mobile phone, tablet computer, etc.). Graphical User Interface **810** can include Control **810**A for establishing a call, such as a VoIP call, with other users. In this example, Control **810**A is presented in association with contact information for Keith **804**, and allows Eric **802** to establish a call to Keith **804** based on the contact information for Keith **804**.

When Eric **802** selects Control **810**A to establish a call with Keith **804**, Control **810**A can trigger the communication device to generate and send Pre-Invite Packet **830** to Server **820**, which then sends Pre-Invite Packet **830** to a communication device associated with Keith **804**. Pre-Invite Packet **830** can include one or more parameters corresponding to an extended session description protocol (SDP) associated with Eric **802**. An example of an extended SDP is further described below with reference to FIG. **9**.

The communication device associated with Keith **804** can receive Pre-Invite Packet **830** and reply to Server **820** with Pre-OK Packet **832**. Pre-OK Packet **832** can include one or more parameters corresponding to an extended SDP associated with Keith **804**.

Server **820** can receive Pre-OK Packet **832** and collect telemetrics and perform a practice or "dry" run to predict call quality before actually establishing the call. Server **820** include one or more conferencing servers or bridges, such as a SIP (Session Initiation Protocol) server, configured to perform call quality or experience forecasting using machine learning models, such as Generic Model **816** and Personalized Model **832**, as previously explained.

In this example predictive modeling use case, Server **820** host and/or establish communication sessions (e.g., video/audio calls such as VoIP) using SIP or a SIP-like protocol. SIP is used in this example for clarity and explanation purposes. It should be noted that other examples or servers may implement other communication protocols either in combination to SIP or in lieu of SIP, such as, without limitation, H.323.

Moreover, the signaling protocol implemented by Server **820** can be extended to process "pre-INVITE" packets (e.g., Pre-Invite Packet **830**) and "pre-OK" packets (e.g., Pre-OK Packet **832**) without actually triggering a call. Thus, Pre-Invite Packet **830** and Pre-OK Packet **832** can serve as "pre-signaling" packets which enables Server **820** to perform a practice or "dry" run call to collect relevant metrics from other call legs, including call legs corresponding to one or more callees intended by the caller, which in this example is Eric **802**. Taking the metrics and conditions of all callees into account, Server **820** can more accurately predict the likely quality of a conference call. The metrics used to make machine learning based predictions can be passed to Server **820** through the attributes represented as 'a' in standard SDP.

Server **820** can provide machine learning and prediction services before, during, and/or after a call. To illustrate, after receiving Pre-Invite Packet **830** and Pre-OK Packet **832** from Eric **802** and Keith **804**, respectively, Server **820** can collect metrics and generate Predicted MOS **834** based on the SDP associated with Eric **802** and Keith **804**. Predicted MOS **834** can be a machine learning prediction based on one or more machine learning models, such as Generic Model **816** and Personalized Model **832**. In this example, Predicted MOS **834** can be a machine learning prediction generated based on Generic Model **816** and telemetrics associated with other users in the system, such as Predicted MOS **818** generated at Phase **1** (**610**) as previously described with reference to FIG. **6**.

Based on Predicted MOS **818**, Server **820** can send Predicted Pre-OK Packet **836** to Eric **802**. Predicted Pre-OK Packet **836** can include Predicted MOS **818**, the extended SDP of Keith **804**, as one as one or more prediction factors. The communication device used by Eric **802** can receive Predicted Pre-OK Packet **836** from Server **820** and update Graphical User Interface **810** to display or visualize Predicted Rating **812**, which can convey a rating predicted for the call based on Predicted Pre-OK Packet **836**, including information in Predicted Pre-OK Packet **836** such as Predicted MOS **818**, the extended SDP of Keith **804**, and/or the one or more prediction factors.

Graphical User Interface **810** can also present Selectable Controls **814**, **816**, **818**, which can provide various options to Eric **802**. For example, Control **816** can be a selectable control that Eric **802** can select to proceed with the call, and Control **818** can be a selectable control that allows Eric **802** to cancel the call. Control **814** can be a selectable control which provides Eric **802** an option to retrieve and view additional information pertaining to Predicted Rating **812**.

To illustrate, Control **814** can include text (e.g., "Why", "Additional Details", "Reason", "Expand", "Explore", etc.) indicating that Control **814** is operable to generate a further inquiry for additional information or details pertaining to Predicted Rating **812**, such as prediction and/or rating information and description, conditions associated with Predicted Rating **812**, contributing factors associated with Predicted Rating **812**, network information, call information, status information, etc. If Eric **802** selects Control **814**, Graphical User Interface **810** can retrieve and/or display additional information about Predicted Rating **812**. For example, in response to a selection of Control **814**, Graphical User Interface **810** can present Current Network Conditions View **820** which can provide information and data about network conditions detected.

Current Network Conditions View **820** can include Description **822** explaining one or more factors (e.g., negative and/or positive) that contributed to Predicted Rating **812**. In this example, Description **822** indicates "Keith is currently on a network with unusually high latency. This may impact the call quality". Thus, Description **822** describes to Eric **802** a network condition that can impact the quality of the call and consequently the rating(s) in Predicted Rating **812**. Graphical User Interface **810** can also present Respective Rating Information **824**, **826** for the users in the call, which in this example include Eric **802** and Keith **804**. To illustrate, Graphical User Interface **810** can present Respective Rating Information **824** conveying a predicted rating or experience for Keith **802** based on metrics affecting the call experience for Keith **802** (e.g., network conditions, device status, etc.), and Respective Rating Information **826** conveying a predicted rating or experience for Eric **802** based on metrics affecting the call experience for Eric **802**.

As previously mentioned, Control **816** can allow Eric **802** to proceed with the call. When Eric **802** selects Control **816**,

the communication device associated with Eric **802** can generate and send Invite **838** to Server **820**, which can relay it to the communication device associated with Keith **804**. The communication device associated with Keith **804** can generate and send Response **840** to Invite **838**. Response **840** can include, for example, a Trying, Ringing, and/or OK. The communication device associated with Eric **802** can send Response **840** to Server **820**, which can relay to the communication device associated with Eric **802**. Based on Invite **838** and Response **840**, Eric **802** and Keith **804** can establish Media Stream Session **842** through Server **820**.

At the end of Media Stream Session **842**, the session can be terminated through a Bye and OK message. For example, the communication device associated with Keith **804** can send Bye Message **844** when Keith **804** disconnects from Media Stream Session **842**. Server **820** can receive Bye Message **844** and relay it to the communication device associated with Eric **802**.

Eric **802** and Keith **804** can respectively provide Subjective MOS **846**, **848** to Server **820**, which Server **820** can use as Input **850** for updating its machine learning model to account for actual MOS data from Eric **802** and Keith **804**. Subjective MOS **846**, **848** can include actual subjective ratings from Eric **802** and Keith **804**. Server **820** can use Subjective MOS **846**, **848** with its machine learning model to generate a personalized model (e.g., Personalized Model **632**) and/or personalized predicted rating and expectation data for a call.

FIG. **9** shows an example SDP for machine learning call quality predictions. Extended SDP **902** can include Session Description Fields **904** which can include attributes and corresponding values for describing the session. Session Description Fields **904** can include one or more fields from standard SDP, such as protocol version, originator, session name, session information, email address or contact information, connection information, time information, media information, and other session attributes.

Extended SDP **902** can also include Extended SDP Fields **906** which can include other attributes and corresponding values that can be used for machine learning. For example, Extended SDP Fields **906** can include bandwidth attributes, network attributes, protocol attributes, user agent and operating system attributes, device attributes, and so forth. In some cases, one or more of the attributes from Extended SDP Fields **906** can be used to construct feature vectors for machine learning modeling and predictions as previously described.

The fields and attributes illustrated in Extended SDP **902** are non-limiting examples for explanation purposes and can vary in other configurations or examples. For example, other examples can include more or less fields or attributes in Session Description Fields **904** and/or Extended SDP **902**.

FIG. **10** shows an example method for forecasting expected call quality. At step **1002**, the method can involve generating a plurality of scenarios (e.g., scenarios **732**) from a plurality of network metrics (e.g., Telemetrics **614**). For example, a conference system (e.g., Server **620**) can collect network metrics from users and input the metrics into a clustering algorithm (e.g., Clustering Algorithm **622**) to generate scenarios based on the metrics.

At step **1004**, the method can involve retrieving ratings from a plurality of users. The ratings can include actual, subjective ratings (e.g., Subjective Ratings **624**) provided by users for previous calls. The ratings can include subjective MOS scores (e.g., Past MOS **710**) from users, representing the users' call quality ratings and experiences.

At step **1006**, the method can involve assigning the ratings to the plurality of scenarios. For example, the ratings from each user can be mapped to specific scenarios to generate a matrix of ratings and scenarios for users. The mappings can represent profiles for the users.

At step **1008**, the method can involve filtering one or more users based on similarities of the ratings for the plurality of scenarios with one or more current network metrics. In some cases, a matrix of ratings and scenarios generated at step **1006** can be provided as an input to a collaborative filtering algorithm (e.g., Collaborative Filtering Algorithm **626**) which can be used to identify users having similar rating behaviors or statistics which can be used to make predictions for a particular user with rating similarities.

At step **1010**, the method can involve forecasting an expected call quality based on the ratings of the one or more filtered users. As previously mentioned, the one or more filtered users can represent users having similar rating behaviors. Thus, the ratings from the one or more filtered users can be applied to predict a rating for the particular user. While different users may experience a same call quality in different ways, users with similar experiences may provide a better approximation for a particular user having similar rating behaviors. Thus, the one or more filtered users can be used to better approximate a predicted call quality experience for the particular user.

The forecasting method can implement machine learning models for generating rating predictions for users. In some cases, a combination of a generic model and a personalized model can be used to generate a generalized prediction as well as a personalized prediction. The generic model and generalized prediction can be based on metrics and/or ratings from other users in the system, and the personalized model and personalized prediction can further take into account actual ratings from a particular user. The machine learning algorithms can be trained using telemetrics and machine learning algorithms, such as regression algorithms.

In some cases, forecasts can be updated and fine-tuned based on data collected from a particular user as well as other users. For example, the ratings of the one or more filtered users can be compared with the ratings from a particular user initiating the expected call, and the forecast can be updated based on the comparison.

Disclosed is a system and method for enabling Collaboration Service Providers to dynamically predict the occurrence of poor media quality based on historical network metrics and real-time media statistics of an active session and then proactively taking actions, such as notifying the relevant end-users such as meeting host, increasing jitter buffer at the endpoint to adapt to future network impairments etc. Some examples can include geo-location of the user, time of day, week of day, client type, connectivity type, host clusters as input features and packet loss, jitter and delay as output labels.

As shown in FIG. **2**, enterprise users can collaborate with internal and external users (e.g., using virtual meetings). For example, enterprise users in different locations, such as, RTP Building A **230**, Home **232** and SJ Building A **234**, can collaborate (via a virtual meeting) from different geographical locations (e.g., home, office road, air) using a variety of electronic devices (e.g., smartphone, laptop, tablet, desktop, etc.) across different connectivity channels (e.g., wired, wireless, cellular, etc.).

FIG. **11** illustrates a map of an example collaboration (e.g., virtual meeting) as one user travels from a First Location **1102** (e.g., Elwood Primary School) to a Second Location **1104** (e.g., Melbourne Airport). In some examples,

the user drops their child off at school (e.g., at First Location **1102**), on a daily basis, and then travels to work (e.g., to Second Location **1104**). In this example, a Route **1106** from the First Location **1102** (e.g., Elwood Primary School) to the Second Location **1104** (e.g., Melbourne Airport) consists of three roads (e.g., Alt **1**, M**1**, M**79**). An Alternative Routes **1108**, **1112** can use three different roads (e.g., Alt **1**, M**1**, M**2**).

FIG. **12** illustrates an example historical data set **1200** used to predict quality of a collaboration based on future geolocation (e.g., of the user), meeting time, day of the week, device type, connectivity type and host cluster. In some examples, the historical data set can be collected from crowd sourcing methods, such as, network metrics from a plurality of user at different times and locations. Within a predetermined period of time before (and after) a collaboration is initiated, real-time data sets can be used to determine current quality of the collaboration. The real-time data sets can be periodically collected and stored in historical data set **1200**. The combined data sets (e.g., historical and real-time) can be used to determine the possibility of media quality degradation (e.g., of the collaboration) when the user's geolocation changes (e.g., along a route, from one road to another, Alt **1** to M**1**, M**1** to M**79**, etc.).

For example, when a user travels from M**1** to M**79**, the collaboration application (e.g., virtual meeting) can inform collaboration service provider **250** of a change in geolocation. For example, Cluster**1** **212** can be informed of a geolocation change between M**1** and M**79**. In response, Cluster**1** **212** can use the current session details of the collaboration (e.g., time, day, device type, connectivity type, host cluster) and geolocation to predict potential degradation of the collaboration (e.g., packet loss, delay and jitter). In some examples, historical data sets can also be used. The prediction can be used to determine whether there will be a poor media quality occurrence for the geolocation and the future geolocation (e.g., along the navigation path). When the prediction is of poor media quality at the geolocation or future geolocation, Cluster**1** **212** can Notify **1110** the user (and other participants of the collaboration) as shown in FIG. **11**. In some examples, in response of a prediction of poor media quality network parameters can be adjusted to prevent future impairments (e.g., increasing jitter buffer, etc.). In some examples, the cluster can offer Alternate Routes **1108**, **1112** to avoid poor media quality.

FIG. **13** illustrates a method for predicting media quality. At step **1302**, a collaboration cloud can receive an indication a client device want to initiate a collaboration. For example, one or more users of client devices can have a virtual meeting at a specific time via an application (e.g., WebEx, Google Hangouts, etc.).

At step **1304**, a current location and destination of the client device is determined (e.g., at the collaboration cloud). For example, the user can be dropping their child off at Elwood Primary School (e.g., Current Location, **1102**) and traveling to work at Melbourne Airport (e.g., destination, **1104**). At step **1306**, the collaboration cloud can retrieve historical metric data and real-time network metrics. For example, the historical metric data can be retrieved from a cloud storage service, as shown in FIG. **12**. The real-time network metric data can be received through one or more statistical network monitoring tools. At step **1308**, the collaboration cloud can determine potential degradation in media quality for the collaboration based on the historical metric data and the real-time network metric data. For example, the historical metric data can be used to determine historical network issues (e.g., outages, congestion, jitter, latency, bandwidth, etc.) at the current location or destination at similar times and days (e.g., rush hour, no cellular towers, etc.), for example. The real-time network metric data can be used to determine current network issues at the current location and destination (e.g., outages, congestions, jitter, latency, and bandwidth etc.). The combination of the two (or in some examples one of the two) can be used to determine if the user will potentially have degraded media quality during the collaboration.

At step **1310**, when potential degradation is determined, the collaboration cloud can notify the user (as shown in FIG. **11**). In some examples, the collaboration cloud can recommend an alternate route without potential degradation (e.g., **1108**, **1112**).

FIG. **14** illustrates an example network device **1400** suitable for routing, switching, forwarding, traffic management, and load balancing. Network device **1400** can be, for example, a router, a switch, a controller, a server, a gateway, and/or any other L**2** and/or L**3** device.

Network device **1400** can include a master central processing unit (CPU) **1404**, interfaces **1402**, and a bus **1410** (e.g., a PCI bus). When acting under the control of appropriate software or firmware, the CPU **1404** is responsible for executing packet management, error detection, load balancing operations, and/or routing functions. The CPU **1404** can accomplish all these functions under the control of software including an operating system and any appropriate applications software. CPU **1404** may include one or more processors **1408**, such as a processor from the Motorola family of microprocessors or the MIPS family of microprocessors. In an alternative embodiment, processor **1408** is specially designed hardware for controlling the operations of network device **1400**. In a specific embodiment, a memory **1461** (such as non-volatile RAM and/or ROM) also forms part of CPU **1404**. However, there are many different ways in which memory could be coupled to the system.

The interfaces **1402** are typically provided as interface cards (sometimes referred to as "line cards"). Generally, they control the sending and receiving of data packets over the network and sometimes support other peripherals used with the network device **1400**. Among the interfaces that may be provided are Ethernet interfaces, frame relay interfaces, cable interfaces, DSL interfaces, token ring interfaces, and the like. In addition, various very high-speed interfaces may be provided such as fast token ring interfaces, wireless interfaces, Ethernet interfaces, Gigabit Ethernet interfaces, ATM interfaces, HSSI interfaces, POS interfaces, FDDI interfaces and the like. Generally, these interfaces may include ports appropriate for communication with the appropriate media. In some cases, they may also include an independent processor and, in some instances, volatile RAM. The independent processors may control such communications intensive tasks as packet switching, media control and management. By providing separate processors for the communications intensive tasks, these interfaces allow the master microprocessor **1404** to efficiently perform routing computations, network diagnostics, security functions, etc.

Although the system shown in FIG. **14** is one specific network device of the present invention, it is by no means the only network device architecture on which the present invention can be implemented. For example, an architecture having a single processor that handles communications as well as routing computations, etc. is often used. Further, other types of interfaces and media could also be used with the router.

Regardless of the network device's configuration, it may employ one or more memories or memory modules (including memory **1461**) configured to store program instructions for the general-purpose network operations and mechanisms for roaming, route optimization and routing functions described herein. The program instructions may control the operation of an operating system and/or one or more applications, for example. The memory or memories may also be configured to store tables such as mobility binding, registration, and association tables, etc.

For clarity of explanation, in some instances the present technology may be presented as including individual functional blocks including functional blocks comprising devices, device components, steps or routines in a method embodied in software, or combinations of hardware and software.

FIG. **15** shows an example of computing system **1500** in which the components of the system are in communication with each other using connection **1505**. Connection **1505** can be a physical connection via a bus, or a direct connection into processor **1510**, such as in a chipset architecture. Connection **1505** can also be a virtual connection, networked connection, or logical connection.

In some embodiments computing system **1500** is a distributed system in which the functions described in this disclosure can be distributed within a datacenter, multiple datacenters, a peer network, etc. In some embodiments, one or more of the described system components represents many such components each performing some or all of the function for which the component is described. In some embodiments, the components can be physical or virtual devices.

Example system **1500** includes at least one processing unit (CPU or processor) **1510** and connection **1505** that couples various system components including system memory **1515**, such as read only memory (ROM) and random access memory (RAM) to processor **1510**. Computing system **1500** can include a cache of high-speed memory connected directly with, in close proximity to, or integrated as part of processor **1510**.

Processor **1510** can include any general purpose processor and a hardware service or software service, such as services **1532**, **1534**, and **1536** stored in storage device **1530**, configured to control processor **1510** as well as a special-purpose processor where software instructions are incorporated into the actual processor design. Processor **1510** may essentially be a completely self-contained computing system, containing multiple cores or processors, a bus, memory controller, cache, etc. A multi-core processor may be symmetric or asymmetric.

To enable user interaction, computing system **1500** includes an input device **1545**, which can represent any number of input mechanisms, such as a microphone for speech, a touch-sensitive screen for gesture or graphical input, keyboard, mouse, motion input, speech, etc. Computing system **1500** can also include output device **1535**, which can be one or more of a number of output mechanisms known to those of skill in the art. In some instances, multimodal systems can enable a user to provide multiple types of input/output to communicate with computing system **1500**. Computing system **1500** can include communications interface **1540**, which can generally govern and manage the user input and system output. There is no restriction on operating on any particular hardware arrangement and therefore the basic features here may easily be substituted for improved hardware or firmware arrangements as they are developed.

Storage device **1530** can be a non-volatile memory device and can be a hard disk or other types of computer readable media which can store data that are accessible by a computer, such as magnetic cassettes, flash memory cards, solid state memory devices, digital versatile disks, cartridges, random access memories (RAMs), read only memory (ROM), and/or some combination of these devices.

The storage device **1530** can include software services, servers, services, etc., that when the code that defines such software is executed by the processor **1510**, it causes the system to perform a function. In some embodiments, a hardware service that performs a particular function can include the software component stored in a computer-readable medium in connection with the necessary hardware components, such as processor **1510**, connection **1505**, output device **1535**, etc., to carry out the function.

Any of the steps, operations, functions, or processes described herein may be performed or implemented by a combination of hardware and software services or services, alone or in combination with other devices. In some embodiments, a service can be software that resides in memory of a client device and/or one or more servers of a content management system and perform one or more functions when a processor executes the software associated with the service. In some embodiments, a service is a program, or a collection of programs that carry out a specific function. In some embodiments, a service can be considered a server. The memory can be a non-transitory computer-readable medium.

In some embodiments the computer-readable storage devices, mediums, and memories can include a cable or wireless signal containing a bit stream and the like. However, when mentioned, non-transitory computer-readable storage media expressly exclude media such as energy, carrier signals, electromagnetic waves, and signals per se.

Methods according to the above-described examples can be implemented using computer-executable instructions that are stored or otherwise available from computer readable media. Such instructions can comprise, for example, instructions and data which cause or otherwise configure a general purpose computer, special purpose computer, or special purpose processing device to perform a certain function or group of functions. Portions of computer resources used can be accessible over a network. The computer executable instructions may be, for example, binaries, intermediate format instructions such as assembly language, firmware, or source code. Examples of computer-readable media that may be used to store instructions, information used, and/or information created during methods according to described examples include magnetic or optical disks, solid state memory devices, flash memory, USB devices provided with non-volatile memory, networked storage devices, and so on.

Devices implementing methods according to these disclosures can comprise hardware, firmware and/or software, and can take any of a variety of form factors. Typical examples of such form factors include servers, laptops, smart phones, small form factor personal computers, personal digital assistants, and so on. Functionality described herein also can be embodied in peripherals or add-in cards. Such functionality can also be implemented on a circuit board among different chips or different processes executing in a single device, by way of further example.

The instructions, media for conveying such instructions, computing resources for executing them, and other structures for supporting such computing resources are means for providing the functions described in these disclosures.

Although a variety of examples and other information was used to explain aspects within the scope of the appended claims, no limitation of the claims should be implied based on particular features or arrangements in such examples, as one of ordinary skill would be able to use these examples to derive a wide variety of implementations. Further and although some subject matter may have been described in language specific to examples of structural features and/or method steps, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to these described features or acts. For example, such functionality can be distributed differently or performed in components other than those identified herein. Rather, the described features and steps are disclosed as examples of components of systems and methods within the scope of the appended claims.

What is claimed is:

1. A computer-implemented method for selecting a media gateway, the method comprising:

receiving a communication session request;

identifying a plurality of available gateways available to handle the communication session request, and for each gateway of the plurality of available gateways:

predicting gateway metrics of the performance of the gateway; and

based on the predicted gateway metrics, predicting a user rating for the communication session request being handled by the gateway;

selecting a gateway from the plurality of available gateways based on the predicted user rating for each gateway.

2. The computer-implemented method of claim **1**, wherein predicting gateway metrics of the performance of the gateway comprises:

receiving historical network information and historical gateway metrics corresponding to the historical network information;

generating a predictive model of gateway metrics; and

based on current network information and the predictive model of gateway metrics, generating predicted gateway metrics of the performance of the gateway.

3. The computer-implemented method of claim **2**, wherein the predictive model of gateway metrics is generated by training a first machine learning module on the historical network information and historical gateway metrics.

4. The computer-implemented method of claim **2**, wherein predicting a user rating for the communication session request being handled by the gateway comprises:

receiving historical client attributes associated with a client device and historical gateway metrics;

receiving historical user ratings corresponding to the historical client attributes and the historical gateway metrics;

generating a predictive model of user ratings; and

based on current client attributes, the predicted gateway metrics, and the predictive model of user ratings, generating predicted user ratings for the communication session request being handled by the gateway.

5. The computer-implemented method of claim **4**, wherein the predictive model of user ratings is generated by training a second machine learning module on the historical client attributes, the historical gateway metrics, and the historical user ratings.

6. The computer-implemented method of claim **2**, wherein one or more of the historical network information, the historical gateway metrics, and the historical client attributes are polled and collected or updated at a predefined interval.

7. The computer-implemented method of claim **1**, wherein the gateway metrics include one or more of packet loss, jitter, and delay.

8. The computer-implemented method of claim **4**, wherein the client attributes include one or more of time of day, day of week, device type, connectivity type, media gateway or user rating.

9. The computer-implemented method of claim **4**, wherein the current client attributes and the predicted gateway metrics are combined before generating predicted user ratings.

10. The computer-implemented method of claim **1**, wherein selecting a gateway from the plurality of available gateways further comprises:

ranking the predicted user ratings of each gateway of the plurality of gateways; and

selecting the gateway of the plurality of gateways with the highest ranking.

11. The computer-implemented method of claim **10**, wherein two or more gateways of the plurality of available gateways are equally ranked and ranking further comprises assigning the higher ranking to the gateway that is in closer proximity to a device initiating the communication session request.

12. A system comprising:

one or more processors; and

at least one computer-readable storage medium having stored therein instructions which, when executed by the one or more processors, cause the system to:

receive a communication session request;

identify a plurality of available gateways available to handle the communication session request, and for each gateway of the plurality of available gateways:

predict gateway metrics of the performance of the gateway; and

based on the predicted gateway metrics, predict a user rating for the communication session request being handled by the gateway;

select a gateway from the plurality of available gateways based on the predicted user rating for each gateway.

13. The system of claim **12**, wherein the instructions which cause the system to predict gateway metrics of the performance of the gateway comprise instructions which cause the system to:

receive historical network information and historical gateway metrics corresponding to the historical network information;

train a first machine learning module on the historical network information and historical gateway metrics;

generate, based on the first machine learning module, a predictive model of gateway metrics; and

based on current network information and the predictive model of gateway metrics, generate predicted gateway metrics of the performance of the gateway.

14. The system of claim **13**, wherein the instructions which cause the system to predict a user rating for the communication session request being handled by the gateway comprise instructions which cause the system to:

receive historical client attributes associated with a client device and historical gateway metrics;

receive historical user ratings corresponding to the historical client attributes and the historical gateway metrics;

train a second machine learning module on the historical client attributes, the historical gateway metrics, and the historical user ratings

generate, based on the second machine learning module, a predictive model of user ratings; and

based on current client attributes, the predicted gateway metrics, and the predictive model of user ratings, generate predicted user ratings for the communication session request being handled by the gateway.

15. The system of claim **14**, wherein one or more of the historical network information, the historical gateway metrics, and the historical client attributes are polled and collected or updated at a pre-defined interval.

16. The system of claim **12**, wherein the gateway metrics include one or more of packet loss, jitter, and delay.

17. The system of claim **12**, wherein the historical network information is added after a first threshold time period and removed after a second threshold time period.

18. The system of claim **14**, wherein the client attributes include one or more of time of day, day of week, device type, connectivity type, media gateway or user rating.

19. The system of claim **12**, wherein the instructions which cause the system to select a gateway from the plurality of available gateways further comprise instructions which cause the system to:

rank the predicted user ratings of each gateway of the plurality of gateways; and

select the gateway of the plurality of gateways with the highest ranking.

20. The system of claim **19**, wherein two or more gateways of the plurality of available gateways are equally ranked and ranking further comprises assigning the higher ranking to the gateway that is in closer proximity to a device initiating the communication session request.

* * * * *