US006718285B2

(12) **United States Patent**
Schwartz et al.

(10) **Patent No.: US 6,718,285 B2**
(45) **Date of Patent: Apr. 6, 2004**

(54) **OPERATOR REPLACEABLE COMPONENT LIFE TRACKING SYSTEM**

(75) Inventors: **Thomas Leonard Schwartz**, Fairport, NY (US); **Richard Robert Tilney Carling**, Lakeville, NY (US); **Kenneth Thomas Doty**, Rush, NY (US)

(73) Assignee: **NexPress Solutions LLC**, Rochester, NY (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 160 days.

(21) Appl. No.: **10/011,331**

(22) Filed: **Nov. 5, 2001**

(65) **Prior Publication Data**

US 2003/0095278 A1 May 22, 2003

(51) **Int. Cl.**[7] **B41F 1/00**
(52) **U.S. Cl.** **702/184**
(58) **Field of Search** 702/184; 399/9, 399/24, 111, 110, 12; 358/1.14; 347/8; 411/176; 29/407; 397/106; 364/468

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,127,012	A		6/1992	Hiliger 371/29.1
5,210,571	A		5/1993	Peloquin et al. 355/203
5,305,199	A		4/1994	LoBiondo et al. 364/403
5,325,156	A		6/1994	Ulinski 355/209
5,335,048	A		8/1994	Takano et al. 355/204
5,490,089	A		2/1996	Smith et al. ..... 364/514 R
5,502,543	A		3/1996	Aboujaoude 355/202
5,548,375	A	*	8/1996	Mitsuya et al. 399/9
5,636,008	A		6/1997	LoBiondo et al. 399/8
5,666,585	A		9/1997	Nagira et al. 399/10
5,911,776	A		6/1999	Guck 709/217
5,923,834	A		7/1999	Thieret et al. 395/183.01
6,012,071	A		1/2000	Krishna et al. 707/522
6,154,728	A		11/2000	Sattar et al. 705/28
6,188,991	B1		2/2001	Rosenweig et al. 705/29
6,243,548	B1		6/2001	Hebert et al. 399/79
6,263,170	B1		7/2001	Bortnem 399/13


* cited by examiner

Primary Examiner—John Barlow
Assistant Examiner—Tung Lau

(57) **ABSTRACT**

Operator Replaceable Component (ORC) devices are employed; that enable an operator that is not a skilled field engineer or service technician, to perform maintenance on a digital printer, resulting in significantly higher uptime for the press. The ORC devices have an expected life span and the system can track the remaining life for each of the ORC devices and prompts the operator when they should be replaced. Preferably, the recent use of the digital printer is compared against the remaining life of the ORC device with the shortest remaining life. The recent use of the digital printer is used to decrement the remaining life of the ORC devices until an ORC device needs replacement. The operator is then notified of the need to replace the ORC device that has expired.

19 Claims, 4 Drawing Sheets






FIG. 1



M
TO M
TO 213
LCU
213
224
212d
223
281Y
211Y
210Y
275e
285d
222
206Y
203Y
208Y
265Y
291Y
205Y
204Y
281M
211M
212C
275d
221Y
206M
203M
208M
265M
291M
205M
204M
281C
211C
216
210M
275C
285c
221M
205C
203C
208C
265C
291C
205C
204C
281B
211B
216
210C
275b
221C
285b
203B
208B
265B
291B
205B
204B
243B
242B
241B
212a
210B
275a
221B
285a
212b
TO 208B
TO 208C
TO 208M
TO 208Y
POWER SUPPLY
252
262
216
200
226
227
214
260

FIG. 2



POWER UP
311
ORC FILES EXIST ?
312
NO
YES
CREATE AND INITIALIZE ORC FILES
313
GUI CHANGES ORC DATA
310
SORT FILES FOR ORC LIFE REMAINING
314
DETERMINE REMAINING LIFE
315
ORC HAS NOT REACHED END OF LIFE
WAIT FOR X SHEETS
316
ORC HAS REACHED END OF LIFE
319
INCREASE LIFE BY REMINDER INTERVAL
317
SEND ORC EXPIRED MESSAGE
318
GUI SHOWS EXPIRED MESSAGE
320

FIG. 3



400
ORC DATA MGMT. SYSTEM WAITS FOR ORC TO EXPIRE
416
ORC DATA MGMT SYS IDENTIFIES ORC EXPIRED, NOTIFIES GUI
418
GUI NOTIFIES OPERATOR COMPONENT NEEDS TO BE REPLACED.
319
OPERATOR NOTIFIES GUI COMPONENT HAS BEEN REPLACED
410a
GUI NOTIFIES ORC DATA MGMT SYS COMPONENT REPLACED.
410b
ORC DATA MGMT SYS GETS PRIINTER PAGE COUNTS.
412
ORC DATA MGMT SYS ADDS NEW HISTORY ENTRY WITH PAGE COUNTS.
414
NEW ORC COMPONENT LIFE IS CALCULATED BASED ON HISTORY INFORMATION
416
COMPONENT LIFE IS SET TO NEW CALCULATED LIFE
417
SORT FILES
314

FIG. 4

OPERATOR REPLACEABLE COMPONENT LIFE TRACKING SYSTEM

FIELD OF THE INVENTION

The present invention relates to the maintenance of systems, and more particularly, to the operator maintenance of systems having components with predictable life spans.

BACKGROUND OF THE INVENTION

The prior art is replete with complicated systems having numerous parts that wear during normal use. These systems require periodic maintenance to replace worn components. Typically, these complicated systems require service professionals such as field service engineers to repair or replace the components in these systems that wear during periods of normal use. In a number of these complicated systems, the period of time that the system is not working or, working at less than optimum performance, is critical. For many of these systems, it is intended is to keep the system running continuously. A digital printing system is one such system. Minimizing down time is critical to the owners and operators of digital printers.

The prior art has recognized that it is important to count the number of use cycles that are applied to printing devices. One such prior art reference, U.S. Pat. No. 5,383,004 issued to Miller et al. (Miller), discloses a method and apparatus for normalizing the counting of sheets that are printed to compensate for varying sizes of sheets that are printed and provide a more accurate record of the wear on components within the system. However, Miller does not teach a system that will provide the operator with the specific knowledge of the wear on the components within the system, thus enabling the operator with the ability to perform maintenance on the system at optimum times. By not providing optimum timing for replacement of components that wear during normal use, the resulting prints are not assured of being of optimum quality. Therefore, the teachings of Miller have a shortcoming in that the operator is not made aware of the current condition of the numerous parts within a printing system that will wear during use.

One solution that has been presented is embodied in U.S. patent application Ser. No. 09/166,326 filed in the name of Burgess (Burgess), commonly assigned with the present invention. Burgess describes a Service Publication System that provides service related information in the form of Field Replaceable Units (FRUs). Burgess is useful in providing service related information for field service engineers and the like, by providing service diagnostics and browser enabled publications. However, Burgess relates to a system that is strictly intended to be used by field engineers and field service representatives and does not provide a system that enables a printing system to be maintained by the operator. While this system of Burgess is useful in providing data for a field engineer, it does not provide operators with the ability to perform maintenance without the aid of a field service representative. Therefore, on-sight maintenance for sophisticated systems is not enabled by the system taught by the Burgess application.

In view of the foregoing discussion, it should be readily apparent that there remains a need within the prior art for a method and apparatus for a system that enables operator maintenance without requiring the aid of field service persons.

SUMMARY OF THE INVENTION

The present invention addresses the shortcomings in the prior art by providing a system having Operator Replaceable Component (ORC) devices that have a predictable lifetime before the ORC devices have to be replaced. The system of the present invention also provides tracking of the remaining lifetime of the ORC devices. As the system keeps track of the remaining life of the ORC devices, the system will prompt the operator when the ORC devices need to be replaced. The preferred embodiment of the present invention provides tracking of the ORC devices in an ORC tracking table along with an automated transmission of the ORC Tracking Table to a Graphical User Interface (GUI). Page count or other additional parameters related to the type of customer usage are employed to create the ORC tracking chart. The concepts embodied by the present invention empower the operator with the ability to perform maintenance on a sophisticated digital press without the requirement of a field service person. Once an operator replaces an ORC device, the remaining life of that ORC device is reset and the entire system will anticipate the next ORC device expiration based on a different expiration parameter.

These and other objects of the invention are provided by the operator maintenance system of the invention that has a plurality of operator replaceable component devices within the system, each of the operator replaceable devices having an expected lifetime, determining a remaining life span for at least one of the operator replaceable component devices, comparing the remaining life span with a predetermined threshold; and responding to a result of the comparing step indicating that the predetermined threshold has been exceeded.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is an illustration of a system having a digital printer and a user interface that is the preferred embodiment of the invention;

FIG. **2** is an illustration of the digital printer of FIG. **1** with the outer skin removed showing a number of operator replaceable components;

FIG. **3** is a flowchart that details the operations performed to track the expected life of operator replaceable components;

FIG. **4** is a flowchart of events to generate the expected life of the operator replaceable components.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. **1**, which is an illustration of a system **102** as envisioned by the preferred embodiment of the present invention, a digital printer **103** provided with Operator Replaceable Component (ORC) devices that enable a typical operator to perform the majority of maintenance on the system without requiring the services of a field engineer. Digital printer **103**, in the preferred embodiment, is a NexPress® 2100, however, the present invention pertains to systems in general and digital printing systems in particular. The preferred embodiment as illustrated in FIG. **1** includes in system **102** a Digital Front End (DFE) controller **104** which in the preferred embodiment is a NextStation™ adjacent to the NexPress®2100, however in general, virtually any interactive device can function as DFE controller **104**, and specifically any Graphics User Interface (GUI) **106** can function in association with DFE controller **104** as employed by the present invention. The ORC devices as envisioned by the present invention are those components within systems that become worn after periods of use. Specifically, the ORC devices as envisioned by the preferred embodiment herein, are those components used within digi-

tal printing systems that wear with use. These ORC devices within the preferred embodiment have predictable lifetimes that can be anticipated by parameters relative to the use of the digital printer **103**. Therefore, it is possible to anticipate when these ORC devices will need to be replaced before the wear on them results in less than desirable performance in the system **102**.

System **102** has multiple computational elements. The digital printer **103** is provided with computational devices, the most notable computational element within digital printer **103** referred to, herein, as the Digital Front End. The NextStation™ provides a computational element **105** having a Graphical User Interface (GUI) **106** that interfaces with a database management system within the DFE controller **104**. It should be understood that while the preferred embodiment details a system **102** with a digital printer **103** having at least one computational element which interfaces and another computational element associated with GUI **106**, similar systems can be provided with more computational elements or fewer computational elements, and that these variations will be obvious to those skilled in the art. In the preferred embodiment, GUI **106** on the NextStation™ provides the operator with the ability to view the current status of ORC devices on the NexPress® 2100 digital printer **103** and to perform maintenance in response to maintenance information provided on the graphical display on GUI **106** as well as to alerts that are provided from the DFE.

The database management system will receive data for each of the ORC devices that details the usage of each of the ORC devices based on the number of prints made, the types of paper being used, the color composition of the printed pages as well as various sensor inputs. The database management system then takes the received data and creates a life tracking system that keeps track of the remaining life of the ORC devices and informs the operator via the GUI **106**. The preferred embodiment employs tables displayed on the GUI **106** to inform the operators to the current status of the ORC devices. However, it should be noted that numerous variations are possible including, but not limited to, direct messages related to a single ORC device, various types of alarms, or even graphical messages on the GUI **106**. The database management system will also prompt the operator when any of the ORC devices need to be replaced. The digital printing system of the present invention provides tracking of the ORC devices in an ORC tracking table along with an automated transmission of the ORC Tracking Table to the GUI **106**. The preferred embodiment of the present invention uses page count and parameters related to customer usage to create the ORC tracking chart. The concepts embodied by the present invention empower the operator with the ability of performing maintenance on a sophisticated digital press. When an operator replaces an ORC, the life counter for that ORC is reset. Table 1 below illustrates a tracking table for ORC devices that would typically be provided on GUI **106** within the preferred embodiment of the invention.

TABLE 1

Catalog Number	Description	Average Life	Remaining Life	Replaced Qty.	Machine Qty.
*21004	NexPress DryInk, Black	12,500	23	56	1
21054	Pressure Roller Cleaner Sheet	40,000	312	17	1

TABLE 1-continued

Catalog Number	Description	Average Life	Remaining Life	Replaced Qty.	Machine Qty.
*21001	NexPress DryInk, Cyan	25,000	2,852	28	1
*21002	NexPress DryInk, Magenta	25,000	3,257	28	1
*21003	NexPress DryInk, Yellow	25,000	6,941	28	1
21026	Contact Skive Finger	45,000	8,190	120	8
	General Press Maintenance	50,000	11,011	14	1
*21030	Fuser Fluid	100,000	13,063	6	1
*21031	Fuser Cleaning Web	100,000	18,699	6	1
21032	Transport Web	100,000	18,699	6	1
21038	Cleaning Web	550,000	22,578	1	1
21063	Cleaner Sump	125,000	28,814	4	1
*21051	DryInk Collection Bottle	135,000	34,125	5	1
21025	Fuser Roller Ay	150,000	39,002	4	1
21059	Fuser Pads	475,000	40,992	1	1
21029	Donor Roller	375,000	45,671	1	1
21061	Metering Roller	875,000	50,773	0	1
21060	Metering Blade	475,000	52,349	1	1
	Perfector Belt Maintenance	200,000	55,891	3	1
21027	Pressure Roller	200,000	56,129	3	1
**21041	Primary/PreClean Wire	200,000	60,009	48	16
**21042	Conditioner/Tack-down Wire	200,000	61,892	33	11
**21036	IC/BC Cleaning Blade	200,000	63,167	24	8
**21058	Wiper Pads	200,000	64,287	12	4
**21044	Narrow Primary Grid	7,000,000	87,094	0	4
**21045	Wide Primary Grid	3,000,000	87,094	0	8
**21047	Conditioning Charger Grid	1,000,000	91,075	1	2
**21050	PreClean Grid	2,000,000	91,075	0	4
**21035	IC/BC Cleaning Brush	2,200,000	105,245	0	8
**21039	Imaging Cylinder	230,000	105,245	3	4
21017	Developer, Cyan	300,000	220,145	3	1
21018	Developer, Magenta	300,000	220,145	3	1
21019	Developer, Yellow	300,000	220,145	3	1
21020	Developer, Black	300,000	280,569	3	1
**21040	Blanket Cylinder	330,000	301,738	3	4
21064	Water Filter Cartridge	500,000	491,813	1	1
21055	Fuser Lamp	2,000,000	1,000,865	0	1
**21074	BC Charger	1,800,000	1,100,865	0	4
21057	Pressure Roller Lamp	2,000,000	1,300,865	0	1
**21043	PreClean Charger	2,000,000	1,300,865	0	4
**21046	Primary Charger	2,000,000	1,300,865	0	4
21048	Tackdown Charger	2,000,000	1,300,865	0	1
**21033	Imaging Cylinder Cleaner	4,000,000	3,300,865	0	4

Table 1 provides a list of ORC devices, with the ORC devices having the shortest remaining life listed first. Each ORC device is given a catalog number to simplify the ordering process and a description to assist the operator with simple recognition of the ORC device. As readily apparent from Table 1, the ORC devices in Table 1 are listed in increasing amounts of remaining life of the ORC devices.

In Table 1, under the column heading Catalog Number, several of the items listed have a single asterisk (*) in the first position, before the actual Catalog Number. This asterisk (*) is not actually produced on the GUI **106** but is placed on Table 1 as shown to indicate the items that are not used by the preferred embodiment as ORC devices, but instead

have sensors that detect when they must be replenished or replaced. The items in Table 1 having a single asterisk (*) before their Catalog Number generally indicate consumables such as DryInk or fluid. However, there are also items having a single asterisk (*) before their Catalog Number such as the Fuser Cleaning Web or the DryInk collection bottle that are not consumables in the general sense but use a sensor to detect if the items need to be replaced within the preferred embodiment. Since the indication that the replacement of items with a single asterisk (*) in front of their Catalog Number, is signified by a sensor rather than an expected life span, these items are not ORC devices within the context of the present invention. Therefore, even though the items with a single asterisk (*) before their Catalog Number will have an expected life span listed in the Remaining Life column, their respective object files will have the tracking feature from their expected life span disabled to prevent the tracking of those items with a single asterisk (*) before their Catalog Number. It should be noted that the items with a single asterisk (*) in front of their Catalog Number could be used as ORC devices within the context of the present invention simply by using the value for their expected life span as listed in the Remaining Life column to track the use of these items and indicate when they need to be replaced.

Additional information is provided on GUI **106** as illustrated in Table 1, such as Average Life of that specific type of ORC device, the Replaced Quantity which is the number of times that specific ORC device has been replaced, and Machine Quantity. The Machine Quantity is the physical number of times that a specific ORC exists within the system. The ORC devices that have an entry greater than one within the Machine Quantity column, represent ORC devices within the preferred embodiment that would have the tracking feature for their expected life span as listed in the Remaining Life column disabled by indicating that this feature be disabled within their respective object files. These ORC devices within the Machine Quantity column that have an entry greater than one, are indicated with a double asterisk (**) before their respective Catalog Numbers in Table 1 and could easily be employed by the present invention as ORC devices, but they are not employed as ORC devices by the preferred embodiment because they are too numerous within the system. The feature of the preferred embodiment of disabling the expected life tracking feature for those items with a double asterisk (**) before their respective Catalog Numbers in Table 1 is, therefore, a configuration feature of the preferred embodiment and could easily be altered to have the expected life tracking feature for the items with a double asterisk (**) before their respective Catalog Numbers enabled. Additional use of the columns of information in Table 1 will be discussed further below.

Referring now to FIG. **2** of the accompanying drawings, the area inside digital printer **103** is illustrated showing the image forming reproduction apparatus according to the preferred embodiment of the present invention, designated generally by the numeral **200**. The reproduction apparatus **200** is in the form of an electrophotographic reproduction apparatus and more particularly a color reproduction apparatus wherein color separation images are formed in each of four color modules and transferred in register to a receiver member as a receiver member is moved through the apparatus while supported on a transport web (PTW) **216**. The apparatus **200** illustrates the image forming areas for digital printer **103** having four color modules, although the present invention is applicable to printers of all types and more specifically to systems having components that wear with use. FIG. **2** illustrates a system having numerous parts that wear with use and must be periodically replaced.

The elements in FIG. **2** that are similar from module to module have similar reference numerals with a suffix of B, C, M and Y referring to the color module for which it is associated; black, cyan, magenta and yellow, respectively. Each module (**291**B, **291**C, **291**M, **291**Y) is of similar construction. The transport web **216**, which may be in the form of an endless belt, operates with all the modules **291**B, **291**C, **291**M, **291**Y and the receiver member is transported by the PTW **216** from module to module. Four receiver members, or sheets, **212***a, b, c* and *d* are shown simultaneously receiving images from the different modules, it being understood as noted above that each receiver member may receive one color image from each module and that in this example up to four color images can be received by each receiver member. The movement of the receiver member with the PTW **216** is such that each color image transferred to the receiver member at the transfer nip of each module is a transfer that is registered with the previous color transfer so that a four-color image formed on the receiver member has the colors in registered superposed relationship on the receiver member. The receiver members are then serially detacked from the PTW and sent to a fusing station (not shown) to fuse or fix the dry toner images to the receiver member. The PTW is reconditioned for reuse by providing charge to both surfaces using, for example, opposed corona chargers **222**, **223** which neutralize the charge on the two surfaces of the PTW. These chargers **222**, **223** are operator replaceable components within the preferred embodiment and have an expected life span after which chargers **222**, **223** will require replacement.

Each color module includes a primary image-forming member (PIFM), for example a rotating drum **203**B, C, M and Y, respectively. The drums rotate in the directions shown by the arrows and about their respective axes. Each PIFM **203**B, C, M and Y has a photoconductive surface, upon which a pigmented marking particle image is formed. The PIFM **203**B, C, M and Y have predictable lifetimes and constitute operator replaceable components. The photoconductive surface for each PIFM **203**B, C, M and Y within the preferred embodiment is actually formed on an outer sleeves **265**B, C, M and Y, upon which the pigmented marking particle image is formed. These outer sleeves **265**B, C, M and Y, have lifetimes that are predictable and therefore, are operator replaceable components. In order to form images, the outer surface of the PIFM is uniformly charged by a primary charger such as a corona charging devices **205**B, C, M and Y, respectively or other suitable charger such as roller chargers, brush chargers, etc. The corona charging devices **205**B, C, M and Y each have a predictable lifetime and are operator replaceable components. The uniformly charged surface is exposed by suitable exposure means, such as for example a laser **206**B, C, M and Y, respectively or more preferably an LED or other electro-optical exposure device or even an optical exposure device to selectively alter the charge on the surface of the outer sleeves **265**B, C, M and Y, of the PIFM **203**B, C, M and Y to create an electrostatic latent image corresponding to an image to be reproduced. The electrostatic image is developed by application of pigmented charged marking particles to the latent image bearing photoconductive drum by a development station **281** B, C, M and Y, respectively. The development station has a particular color of pigmented toner marking particles associated respectively therewith. Thus, each module creates a series of different color marking particle images on the respective photoconductive drum. The development stations

281B, C, M and Y, have predictable lifetimes before they require replacement and are operator replaceable components. In lieu of a photoconductive drum, which is preferred, a photoconductive belt can be used.

Each marking particle image formed on a respective PIFM is transferred electrostatically to an intermediate transfer module (ITM) **208**B, C, M and Y, respectively. The ITM **208**B, C, M and Y have an expected lifetime and are, therefore, considered to be operator replaceable components. In the preferred embodiment, each ITM **208**B, C, M and Y, have an outer sleeve **243**B, C, M and Y that contains the surface that the image is transferred to from PIFM **203**B, C, M and Y. These outer sleeves **243**B, C, M and Y are considered operator replaceable components with predictable lifetimes. The PIFMs **203**B, C, M and Y are each caused to rotate about their respective axes by frictional engagement with their respective ITM **208**B, C, M and Y. The arrows in the ITMs **208**B, C, M and Y indicate the direction of their rotation. After transfer, the toner image is cleaned from the surface of the photoconductive drum by a suitable cleaning device **204**B, C, M and Y, respectively to prepare the surface for reuse for forming subsequent toner images. Cleaning devices **204**B, C, M and Y are considered operator replaceable components by the present invention.

Marking particle images are respectively formed on the surfaces **242**B, C, M and Y for each of the outer sleeve **243**B, C, M and Y for ITMs **208**B, C, M and Y, and transferred to a toner image receiving surface of a receiver member, which is fed into a nip between the intermediate image transfer member drum and a transfer backing roller (TBR) **221**B, C, M and Y, respectively. The TBRs **221**B, C, M and Y have predictable lifetimes and are considered to be operator replaceable components by the invention. Each TBR **221**B, C, M and Y, is suitably electrically biased by a constant current power supply **252** to induce the charged toner particle image to electrostatically transfer to a receiver sheet. Although a resistive blanket is preferred for TBR **221**B, C, M and Y, the TBR **221**B, C, M and Y can also be formed from a conductive roller made of aluminum or other metal. The receiver member is fed from a suitable receiver member supply (not shown) and is suitably "tacked" to the PTW **216** and moves serially into each of the nips **210**B, C, M and Y where it receives the respective marking particle image in a suitable registered relationship to form a composite multicolor image. As is well known, the colored pigments can overlie one another to form areas of colors different from that of the pigments. The receiver member exits the last nip and is transported by a suitable transport mechanism (not shown) to a fuser where the marking particle image is fixed to the receiver member by application of heat and/or pressure and, preferably both. A detack charger **224** may be provided to deposit a neutralizing charge on the receiver member to facilitate separation of the receiver member from the PTW **216**. The detack charger **224** is another component that is considered to be operator replaceable within the invention. The receiver member with the fixed marking particle image is then transported to a remote location for operator retrieval. The respective ITMs **208**B, C, M and Y are each cleaned by a respective cleaning device **211**B, C, M and Y to prepare it for reuse. Cleaning devices **211**B, C, M and Y are considered by the invention to be operator replaceable components having lifetimes that can be predicted.

Appropriate sensors (not shown) of any well known type, such as mechanical, electrical, or optical sensors for example, are utilized in the reproduction apparatus **200** to provide control signals for the apparatus. Such sensors are located along the receiver member travel path between the receiver member supply through the various nips to the fuser. Further sensors may be associated with the primary image forming member photoconductive drum, the intermediate image transfer member drum, the transfer backing member, and various image processing stations. As such, the sensors detect the location of a receiver member in its travel path, and the position of the primary image forming member photoconductive drum in relation to the image forming processing stations, and respectively produce appropriate signals indicative thereof. Such signals are fed as input information to a microprocessor based logic and control unit LCU which interfaces with a computational element. Based on such signals and a suitable program for the microprocessor, the control unit LCU produces signals to control the timing operation of the various electrostatographic process stations for carrying out the reproduction process and to control drive by motor M of the various drums and belts. The production of a program for a number of commercially available microprocessors, which are suitable for use with the invention, is a conventional skill well understood in the art. The particular details of any such program would, of course, depend on the architecture of the designated microprocessor.

The receiver members utilized with the reproduction apparatus **200** can vary substantially. For example, they can be thin or thick paper stock (coated or uncoated) or transparency stock. As the thickness and/or resistivity of the receiver member stock varies, the resulting change in impedance affects the electric field used in the nips **210**B, C, M, Y to urge transfer of the marking particles to the receiver members. Moreover, a variation in relative humidity will vary the conductivity of a paper receiver member, which also affects the impedance and hence changes the transfer field. Such humidity variations can affect the expected lifetime of operator replaceable components.

In feeding a receiver member onto PTW **216** charge may be provided on the receiver member by charger **226** to electrostatically attract the receiver member and "tack" it to the PTW **216**. A blade **227** associated with the charger **226** may be provided to press the receiver member onto the belt and remove any air entrained between the receiver member and the PTW. The PTW **216**, the charger **226** and the blade **227** are considered operator replaceable components.

The endless transport web (PTW) **216** is entrained about a plurality of support members. For example, as shown in FIG. **2**, the plurality of support members are rollers **213**, **214** with preferably roller **213** being driven as shown by motor M to drive the PTW. Support structures **275***a, b, c, d* and *e* are provided before entrance and after exit locations of each transfer nip to engage the belt on the backside and alter the straight line path of the belt to provide for wrap of the belt about each respective ITM. This wrap allows for a reduced pre-nip ionization and for a post-nip ionization which is controlled by the post-nip wrap. The nip is where the pressure roller contacts the backside of the PTW or where no pressure roller is used, where the electrical field is substantially applied. However, the image transfer region of the nip is a smaller region than the total wrap. Pressure applied by the transfer backing rollers (TBRs) **221**B, C, M and Y is upon the backside of the belt **216** and forces the surface of the compliant ITM to conform to the contour of the receiver member during transfer. The TBRs **221**B, C, M and Y may be replaced by corona chargers, biased blades or biased brushes, each of which would be considered by the invention to be operator replaceable components. Substantial pressure is provided in the transfer nip to realize the benefits of the

compliant intermediate transfer member which are a conformation of the toned image to the receiver member and image content on both a microscopic and macroscopic scale. The pressure may be supplied solely by the transfer biasing mechanism or additional pressure applied by another member such as a roller, shoe, blade or brush, all of which are operator replaceable components as envisioned by the present invention.

FIG. **3** is a flowchart that details the operations that are performed by the system of the present invention. ORC Tracking, generally referred to as **300**, is initialized at Power Up **311** and then begins by executing ORC Files Found **312**. ORC Files Found **312** looks at the object files for the ORC devices to check that all necessary object files are present. If any of the necessary object files are not found, then Create and Initialize ORC Files **313** is run to install these files.

The object files within the preferred embodiment are data structures called records. Each record used as an object file contains information related to a particular ORC device. Other types of data structure can also be used to retain the information related to specific ORC devices, however records are the type of data structure used by the preferred embodiment of the invention. Within the preferred embodiment, entries are made within each of the object files for life history of that particular type of ORC device, the predicted life for that specific ORC device that is currently installed and the amount of use on that ORC device that is currently installed. Additionally, each object file can contain a number of setpoints that can be accessed by various computational elements within system **102**. The provisions of setpoints that can be accessed by the computational element to the GUI **106**, the DFE or any other computational elements in the digital printing system **103** is a feature of the preferred embodiment and it will be readily understood that other architectural configurations can be substituted without departing from the spirit of the present invention. Another item within each of the object files for an ORC device is whether that ORC device is to be dormant. Dormancy as used herein refers to whether a parameter for an ORC device is to be used as a trigger point within the system **102** to alert the operator to a potential problem with that ORC device. The dormancy feature can be either enabled or disabled. The rationale for having a dormancy feature is that with certain types of ORC devices, it might be desirable for the operator to employ visual rather than automatic notification that lifetime of an ORC device has expired. A visual notification would typically be desirable when it is believed that system predictors do not provide sufficient accuracy and that physically looking at the printed output to notice any problems is the best manner by which to determine problems occurring from that ORC. If the dormancy feature for a specific ORC device is disabled, then the trigger mechanism is enabled for that ORC device and will be a potential trigger for an operator alert once the expected lifetime of that ORC device has expired. Another entry that is contained in the object file is for a reminder that is sent to the operator alerting the operator that an ORC device has failed, or will soon fail. As shown in FIG. **3**, the Send Reminder Interval **317** alerts the operator when the expected lifetime for an ORC device has expired. The specifics for Send Reminder Interval **317** are acquired by accessing the object file for that ORC device in question. The Send Reminder Interval **317** is a message to alert the operator via the GUI **106** and is made by accessing the object file for that specific ORC device and reading entries in the object file. As envisioned by the preferred embodiment, the reminder interval is a parameter in the object file that is accessed to acquire the reminder period that is used to remind the operator that the specific ORC has an expired expected lifetime. This period can be a time period used to set a timer from which the operator can repetitively be alerted, or it can be measured in terms of use of that ORC device, which in the preferred embodiment would be a number of sheets printed. The time period can also be set in terms of times and dates to alert the operator per minute, per hour, per day or per week. Other information that is contained in the object file for an ORC is information detailing the quantity of that specific ORC device that has been used in the machine over the lifetime of the machine. Additionally, historical data for each one of the ORC devices for that specific ORC device is provided for increased capabilities in the database manager system. In this manner, a computational element can access the object file for a specific ORC device and acquire all the historical data for that ORC device and calculate an expected lifetime for that ORC based on the history of that ORC as it has been used in that digital printing device **103** for that particular user. Historical data can be used to compute expected lifetimes dynamically and provides for a high degree of personalization for a digital printing system. Personalization is important because of the numerous variables that can effect the lifetime of the ORC devices. These variables will be discussed below in more detail.

Still referring to FIG. **3**, after the ORC Tracking **300** system verifies that the necessary ORC files exist, the system branches to Sort Files **314**, which is a routine that looks at the ORC object files and sorts through them to determine which ORC device should be expected to expire first. The ORC devices within the preferred embodiment have their remaining life determined in terms of the number of remaining **A4** pages that can be expected to be printed before failure and this is the type list shown in Table 1. However, it should be noted that Table 1 provides an example list and does not provide an exhaustive list of every ORC envisioned by the invention. While the preferred embodiment measures remaining life for ORC devices in terms of pages, it is also envisioned by the invention that remaining life can be measured in time, or by specific date depending on the types of use that a system encounters. The Sort Files **314** routine of the present invention will organize the list of ORC devices in terms of the expected remaining life. The ORC device with the shortest estimated life is listed first, the ORC with the second shortest expected life listed second, and so on until all the ORC devices have been listed in terms of their remaining expected life. In this manner, the preferred embodiment has the earliest expiration period listed first and one only needs to look at the first element on the list to provide the operator with information related to the ORC that is expected to expire first. An exception to the foregoing discussion related to the list of ORC devices is where an ORC device has just been replaced or during the first power up of the machine where the Sort Files **314** again must process multiple ORC object files.

The preferred embodiment only requires that the system **102** check the object file for that ORC device that is on the top of the list as shown in Table 1 after the Sort Files **314** routine is run and verify that the most recent use of the digital printer **103** has not exceeded the remaining life of that ORC device with the shortest remaining life. The preferred embodiment only needs this single value checked because this is the ORC that is expected to expire first and results in less processing overhead that is placed on system **102**. The Sort Files **314** routine sorts all the ORC devices and sends the list of ORC devices to the GUI **106**, which allows the operator to view the life expectancies of the various ORC

devices. It should be understood that variations of the above discussed sort routine will be readily apparent to those skilled in the relevant art. There are numerous sort routines known within the art that will provide the necessary functionality required by the present invention.

Determine Remaining Life **315** takes the remaining life values from the object file for each of the ORC devices and decrements the remaining life value for each of the ORC devices by the number of pages that have been printed since the last time Determine Remaining Life **315** has been run. A determination is made if any of the ORC devices lifetime has expired. In the preferred embodiment, a printed sheet would typically be an **A4** page and a sheet that is 11 inches by 17 inches would result in decrementing the remaining life of the ORC device by two pages. Therefore, the remaining life values in the object files for each of the ORC devices are decremented by 1 for each **A4** sheet that is printed and by 2 for each 11 inch by 17 inch sheet that is printed. Duplex pages would typically be counted twice as much as a single sided page in determining the remaining life of the ORC devices. The parameters used to determine the remaining life of the ORC devices can also be related to color. Sheets that require substantial amounts of color or large amounts of particular colors can have individual parameters indicative of the usage of large amounts of that color or colors.

If the result of Determine Remaining Life **315** indicates that an ORC has Reached the End of its Lifetime, then Send Reminder Interval **317** accesses the object file for that object file as previously discussed and sets up the interval with which the operator will be reminded that the expected life span for that ORC has expired. Once Determine Remaining Life **315** makes a determination that one of the ORC devices has reached its expected lifetime, the preferred embodiment has Send ORC Expired Message **318** to provide the operator with a notification of the fact that an ORC has expired by alerting the operator via GUI **106**. It will be readily understood to those skilled in the art, that there are numerous means for notification. The alert can be by any alarm mechanism. The alert can also be via a user interface that is not a graphical user interface.

If Determine Remaining Life **315** indicates that none of the ORC devices have reached their expected lifetime, Wait for Time Period **316** provides a function that will allow a predetermined parameter to expire before branching back to Determining Remaining Life **315**. In the preferred embodiment Wait for Time Period **316** will provide a timer that is set to wait a predetermined period of time before branching back to Determine Remaining Life **315**. The time period set by Wait for Time Period **316** in the preferred embodiment is set to match the remaining life of the ORC device with the lowest expected lifetime. Other parameters can be used instead of time periods to determine the actual period of Wait for Time Period **316**, and the use of other parameters is specifically envisioned by the present invention. Among these different parameters are time periods other than the remaining life of an ORC device, such as a specific number of sheets that have been printed (or possibly every sheet) instead of, or in combination with time periods related to the remaining life of an ORC. Additionally, specific time periods can be used to establish the time period used by Wait for Time Period **316**.

After the parameter used by Wait for Time Period **316** has expired, Determine Remaining Life **315** will again access the remaining life values from the object files for the ORC devices and decrement the remaining life value for each of the ORC devices by the number of pages that have been printed since the last time Determine Remaining Life **315** has been run, as previously stated.

The NexPress® 2100 uses the concept of Operator Replaceable Component (ORC) devices to reduce overall per page print cost and maximize print quality and uptime at the customer site. The ORC devices within the preferred embodiment of the present invention, are components within the printer that are to be replaced by the printer operator without requiring the services of a more highly skilled field engineer. In order for ORC devices to achieve the goal of reducing per page print costs, it is necessary to know when the "optimal" life of an ORC device has been reached. Here "optimal" is used to describe the point after which further printer use with the ORC device that has reached the optimal life will potentially either adversely affect print quality or fail. It is important in any printing system to understand the variables that result in print quality. It is extremely important in systems involving high-end digital printers, that the variables affecting print quality are well known. Additionally, the operators for these printing systems need to be aware of the state of the variables that can affect print quality. The present invention addresses these needs by providing a realtime update of the expected life span for ORC devices upon demand as well as notification of a situation where the expected life span of an ORC device is about to expire, or in fact already has expired. The specific timing of this notification also needs to be as accurate as possible, especially in high-end digital printing systems, because of the high volume of prints that are made, to insure maximum component life is not exceeded, which in turn results in minimizing the per page print cost for that printer and maximizing print quality.

Actual life of a specific ORC in a specific printer is dependent on many factors. Among these factors are the number of pages printed, the size of the pages, printing on one side (simplex) versus both sides (duplex) of the paper, the type of finish, the characteristics of the paper, the environment in which the printer resides (room temperature, air quality, dust contaminants), the number of times the printer is shut down and restarted, and the manufacturing quality of the ORC. While it is not practical for the system to immediately characterize all of the variables that affect the life of an ORC device, it is possible to provide systems that can characterize these variables that have a determining factor in the life of a specific ORC. The present invention envisions predicting the lifetimes of ORC devices accurately by taking into account the past history of the same or similar ORC devices.

To achieve the goal of predicting the life of an ORC device as accurately as possible, the present invention envisions ORC tracking system software that can perform these important tasks. Once a specific ORC device has expired, a replacement for that specific ORC device is placed into the system. The system software then takes the life information for the expired ORC device and places it into a history list file for that ORC device. In the preferred embodiment this history file would be retained in the object file as previously discussed. When that specific ORC device is replaced again, the additional history information is added to this list so that life history for each specific ORC device can be retrieved and used for calculation. After an ORC device is replaced, the system software calculates a new life expectancy based on the life spans of the previous ORC devices. The new life expectancy then becomes the expected life span for the ORC device.

By calculating a new life based on replacement history, the system software can adapt to changes in variables that affect print quality such as printer usage and printer environment. The system software can then reflect the impact of

these variable changes in the predicted life of the ORCs. Once in place with the ability to adapt the predicted life of the ORCs to variable changes, the system software can personalize the predicted ORC life on a per printer basis dynamically as ORCs are replaced and account for all the factors that influence an ORCs life by using historical ORC life data. By accounting for the variable influences on ORC life, the system achieves the goal of optimizing predicted ORC component life on a per printer basis, minimizing per page print costs while maximizing print quality.

FIG. **4** is a flowchart showing the operation of the present invention employing the ORC Tracking previously described used in combination with history data used to predict life span for the ORCs. Generally referred to as **400**, the series of events for determining the predicted life span using ORC history data is a combination of what has previously been discussed for the flowchart shown in FIG. **3** together with the portion that employs ORC data to generate ORC device life expectancy. The series of events from FIG. **3** are present in FIG. **4** in a more high level form for the sake of brevity. Wait for ORC to Expire **416** is essentially equivalent to the series of steps from the flowchart in FIG. **3** Determine Remaining Life **315** and Wait for Time Period **316**. Once an ORC expires (as previously discussed) the system will then perform Identify the ORC Expired and Notify GUI **418**, which is similar to the combination of Send ORC Reminder Interval **317** and Expired Message **318** of FIG. **3**. Identify the ORC Expired and Notify GUI **418** will alert the print operator that the expected lifetime of an ORC has expired and that that ORC needs to be replaced. Notify GUI of ORC Replacement **410***a* is where the operator inputs to the user interface (the GUI **106**) that the expired ORC has been replaced and GUI Notifies ORC Data management of ORC Replacement **410***b* informs the ORC database manager that a new ORC has been installed in place of the ORC that has expired. Update ORC Data Management System With Printer Page Counts **412** updates the ORC database manager with any page counts from recent use of the digital printer **103** that have not yet been accounted for by the system **102**. ORC Data Management System Adds New History Data With Page Count Updates **414** takes the page counts from Update ORC Data Management System With Printer Page Counts **412** and updates the ORC database manager. New ORC Component Life is Calculated **416** takes the updated ORC database manager information and computes a new life expectancy for the ORC that has just been replaced using the equations that have previously been discussed. Component Life is Set **417** takes the computed life and applies it to the ORC that has just been replaced. The system of the preferred embodiment then braches back Waits for ORC to Expire **416** because the preferred embodiment of the present invention has different computational elements perform the flowcharts shown in FIG. **3** and FIG. **4**. The flowchart in FIG. **4** is performed by the computational elements in the NextStation™ and the Sort Files **314** routine of FIG. **3** is performed by the DFE.

In systems having only one computational element, or using only one computational element to perform both the flowcharts shown in FIG. **3** and FIG. **4**, then Sort Files **314** would be run after Components Life is Set **417** as shown by the dotted line in FIG. **4**. Here, the object files for the ORC devices would again be looked at to determine which ORC has the shortest life expectancy. As previously detailed in the discussion related to FIG. **3**, there are numerous ways that the ORC object files can be sorted, and also numerous ways by which time periods can be set. It will be readily apparent to those skilled in the art, that there are alternatives to using the ORC with the shortest life as the basic parameter by which to operate from. Numerous thresholds can be applied. Multiple thresholds can operate simultaneously for different ORC devices to alert the operator when life expectancies are running short.

The foregoing discussion has described the preferred embodiment of the present invention, variations will be readily apparent to those of ordinary skill in the art, therefore, the scope of the invention should be measured by the appended claims.

What is claimed is:

1. A system with operator enabled maintenance comprising:

at least one computational element within said system;

a plurality of operator replaceable component (ORC) devices within said system, each of said ORC devices having an expected life span;

a use mechanism coupled to each said computational element and said ORC devices, said use mechanism tracking use of at least one of said ORC devices using a predetermined parameter;

a comparison mechanism that compares use of said ORC devices to said expected life span; and

an operator alert mechanism responsive to said comparison mechanism to provide said operator alert when the result of said comparison satisfies a predetermined parameter representing at least one of said expected life spans where said expected life span for a single of said ORC devices is the shortest expected life span.

2. The system of claim **1**, wherein said computational element is operatively coupled to a display that can provide a current status of said expected life span for said ORC devices.

3. The system of claim **1**, wherein said operator alert mechanism is a user interface.

4. The system of claim **3**, wherein said user interface is a graphical user interface.

5. The system of claim **1**, wherein said system is a printing device and wherein said predetermined parameter of said use mechanism is the number of pages printed.

6. The system of claim **5**, wherein said predetermined parameter further includes a categorization of pages printed.

7. The system of claim **6**, wherein said predetermined parameter further includes the size of pages printed.

8. The system of claim **6**, wherein said predetermined parameter further includes a color related parameter.

9. The system of claim **1**, wherein said operator alert mechanism further includes a send reminder interval set to alert the operator at a predetermined interval.

10. The system of claim **9**, wherein said send reminder interval is selected as a predetermined number of pages printed.

11. The system of claim **9**, wherein said computational element is operatively coupled to a graphical user interface (GUI), the operator is alerted by said operator alert via said GUI, said operator alert further including said send reminder interval being sent to said GUI and said send reminder interval being alterable by the operator via said GUI.

12. The system of claim **11**, wherein said reminder interval can be enabled and disabled by the operator via said GUI.

13. The system of claim **1**, wherein said predetermined parameter further includes a predetermined threshold relative to said ORC devices.

14. A method for providing operator maintenance on a system having a plurality of operator replaceable component devices, comprising:

providing the expected life span of each of the operator replaceable component devices;

determining a remaining life span for the operator replaceable component device having the shortest expected life span;

comparing said remaining life span with a predetermined threshold;

responding to a result of the comparing step indicating that said predetermined threshold has been exceeded; and

notifying the operator on a periodic basis that said predetermined threshold has been exceeded.

15. The method of claim **14**, wherein the step of responding further includes determining if said operator replaceable component device for which said predetermined threshold has been exceeded has been replaced.

16. The method of claim **15**, wherein the step of responding further includes adjusting said remaining life span for at least one of said operator replaceable component devices and then returning to the determining step and sequentially repeating the steps after the determining step.

17. The method of claim **14**, wherein the step of determining further includes the step of waiting for a predetermined period before performing the comparing step.

18. The method of claim **17**, wherein the step of waiting further includes, as said predetermined period, the same units used to determine said life span.

19. The method of claim **18**, wherein the step of waiting further includes, as said predetermined period, said predetermined threshold.

* * * * *