



US006783565B2

(12) **United States Patent**
Gieseke et al.

(10) **Patent No.:** **US 6,783,565 B2**
(45) **Date of Patent:** **Aug. 31, 2004**

(54) **FILTER ARRANGEMENT; SEALING SYSTEM; AND METHODS**

(75) Inventors: **Steven Scott Gieseke**, Richfield, MN (US); **Carolyn J. Finnerty**, Bloomington, MN (US)

(73) Assignee: **Donaldson Company, Inc.**, Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/424,217**

(22) Filed: **Apr. 25, 2003**

(65) **Prior Publication Data**

US 2003/0182909 A1 Oct. 2, 2003

Related U.S. Application Data

(63) Continuation of application No. 10/055,062, filed on Jan. 22, 2002, now Pat. No. 6,610,117, which is a continuation of application No. 09/502,346, filed on Feb. 10, 2000, now Pat. No. 6,350,291, which is a continuation-in-part of application No. 09/258,481, filed on Feb. 26, 1999, now Pat. No. 6,190,432.

(51) **Int. Cl.⁷** **B01D 46/24**

(52) **U.S. Cl.** **55/385.3; 55/498; 55/502; 123/198 E**

(58) **Field of Search** 55/385.3, 498, 55/502, 503, 504, 506, 507, 510, DIG. 30; 123/198 E

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,025,963 A	3/1962	Bauer
3,209,917 A	10/1965	Yelinek
3,676,242 A	7/1972	Prentice
3,695,437 A	10/1972	Shaltis
3,807,150 A	4/1974	Maracle
3,841,953 A	10/1974	Kohkamp et al.

3,849,241 A	11/1974	Butin et al.
3,878,014 A	4/1975	Melead
4,065,341 A	12/1977	Cub
4,322,231 A	3/1982	Hilzendeger et al.
4,402,830 A	9/1983	Pall
4,449,993 A	5/1984	Bergeron
4,720,292 A	1/1988	Engel et al.
4,925,561 A	5/1990	Ishii et al.
5,304,312 A	4/1994	Forster et al.
5,350,515 A	9/1994	Stark et al.

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0 376 443 A2	7/1990
EP	0 581 695 A1	2/1994
EP	0 704 233 A1	4/1996
GB	703823	2/1954
GB	1275651	5/1972
JP	59-170669	11/1984
JP	1-11971	4/1989
WO	WO 97/40908	11/1997
WO	WO 97/40910	11/1997
WO	WO 97/41939	11/1997

OTHER PUBLICATIONS

Allowed claims from U.S. Ser. No. 09/502,346.
Declaration of Steven S. Gieseke with Exhibits A, B and C.


Primary Examiner—Minh-Chau T. Pham

(74) *Attorney, Agent, or Firm*—Merchant & Gould P.C.

(57) **ABSTRACT**

A filter pack includes a filter construction and a sealing system for sealing the construction within a duct or housing. The filter construction has first and second opposite flow faces and is configured for a straight-through flow. The sealing system includes a frame construction and a compressible seal member. The compressible seal member is molded around a portion of the frame construction. The compressible seal member is sufficiently compressible to form a radial seal between and against the frame construction and a surface of a housing when the filter pack is inserted within the housing.

32 Claims, 16 Drawing Sheets



US 6,783,565 B2

Page 2

U.S. PATENT DOCUMENTS

5,415,677 A	5/1995	Ager et al.	5,730,766 A	3/1998	Clements	
5,435,870 A	7/1995	Takagaki et al.	5,755,843 A	5/1998	Sundquist	
5,484,466 A	1/1996	Brown et al.	5,820,646 A	10/1998	Gillingham et al.	
5,487,767 A	1/1996	Brown	5,863,313 A	1/1999	Coulonvaux	
5,543,007 A	8/1996	Takagaki et al.	5,897,676 A	4/1999	Engel	
5,547,480 A	8/1996	Coulonvaux	6,149,700 A	11/2000	Morgan et al.	
5,613,992 A	3/1997	Engel	6,190,432 B1 *	2/2001	Gieseke et al.	55/385.3
5,645,718 A	7/1997	Hardison et al.	6,350,291 B1 *	2/2002	Gieseke et al.	55/385.3
5,685,985 A	11/1997	Brown et al.	6,610,117 B2 *	8/2003	Gieseke et al.	55/385.3
5,714,126 A	2/1998	Frund				

* cited by examiner




FIG. 1

FIG. 2




FIG. 3




FIG. 7




FIG. 4





FIG. 6






FIG. 8





FIG. 9






FIG. 10




FIG. 11

FIG. 12





FIG. 13







FIG. 15






FIG. 16

FIG. 17





FIG. 18



1

FILTER ARRANGEMENT; SEALING SYSTEM; AND METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of application Ser. No. 10/055,062, filed Jan. 22, 2002, now U.S. Pat. No. 6,610,117 B2. Application Ser. No. 10/055,062 is a continuation of application Ser. No. 09/502,346 filed Feb. 10, 2000 and issued as U.S. Pat. No. 6,350,291 B1. Application Ser. No. 09/502,346 is a continuation-in-part of U.S. application Ser. No. 09/258,481, filed Feb. 26, 1999 and issued as U.S. Pat. No. 6,190,432 B1. The disclosures of Ser. Nos. 09/258,481, 09/502,346, and 10/055,062 are incorporated herein by reference.

FIELD OF THE INVENTION

This disclosure concerns filter constructions for engines and methods of filtering and filter preparation. In particular, the disclosure describes a filter arrangement having a sealing system.

BACKGROUND OF THE INVENTION

Gas streams often carry particulate material therein. In many instances, it is desirable to remove some or all of the particulate material from a gas flow stream. For example, air intake streams to engines for motorized vehicles or power generation equipment, gas streams directed to gas turbines, and air streams to various combustion furnaces, often include particulate material therein. The particulate material, should it reach the internal workings of the various mechanisms involved, can cause substantial damage thereto. It is therefore preferred, for such systems, to remove the particulate material from the gas flow upstream of the engine, turbine, furnace or other equipment involved. A variety of air filter or gas filter arrangements have been developed for particulate removal. In general, however, continued improvements are sought.

SUMMARY OF THE DISCLOSURE

This disclosure describes an engine air flow system. The air flow system comprises a filter element construction including a media pack and a sealing system. In preferred configurations, the sealing system will have a frame arrangement and a seal member, where the frame arrangement includes an extension projecting axially from one of the flow faces of the media pack. In particularly preferred arrangements, the seal member is supported by the extension of the frame arrangement.

Filter element constructions are described herein. Preferred filter element constructions will include ones such as those characterized above.

Methods of filtering systems, servicing filtration systems, and constructing filter arrangements are described herein. Preferred methods will use filter elements and constructions as characterized above.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic, perspective view of one embodiment a filter pack, according to certain principles of this disclosure;

FIG. 2 is a schematic, perspective view of a portion of filter media usable in the arrangements of FIG. 1;

FIG. 3 is a schematic, perspective view of one approach to manufacturing a filter pack usable in the arrangements of FIG. 1;

2

FIG. 4 is a schematic, plan view of one embodiment a sealing system of the filter pack of FIG. 1;

FIG. 5 is a schematic, fragmented, cross-sectional view of the arrangement of FIG. 1, depicted sealed in an air cleaner for use;

FIG. 6 is a schematic, cross-sectional view of the frame of the sealing system of FIG. 4, taken along the line 6—6 of FIG. 4;

FIG. 7 is an enlarged fragmented schematic cross-sectional view of one embodiment the compressible seal member of the sealing system of FIG. 4, according to principles of this disclosure;

FIG. 8 is a schematic, perspective view of one embodiment of an air cleaner, in which a filter pack according to principles of this disclosure can be used;

FIG. 9 is a schematic, cross-sectional view of the air cleaner depicted in FIG. 8, showing the filter pack depicted in FIG. 1 installed therewithin;

FIG. 10 is a schematic, perspective view of a first alternative embodiment of a filter pack, according to certain principles of this disclosure;

FIG. 11 is a schematic, perspective view of a filter media portion of the filter pack of FIG. 10;

FIG. 12 is a schematic, perspective view of one embodiment of a frame portion for a sealing system of the filter pack depicted in FIG. 10;

FIG. 13 is a schematic, cross-sectional view of one embodiment of the sealing system usable in the filter pack depicted in FIG. 10, taken along the line 13—13 of FIG. 10;

FIG. 14 is a schematic, side elevational view of an alternate embodiment of an air cleaner, according to principles of this disclosure;

FIG. 15 is a schematic, cross-sectional view of the air cleaner depicted in FIG. 14 and taken along the line 15—15 and showing the filter pack of FIG. 10 installed within;

FIG. 16 is a schematic view of one embodiment of a system in which air cleaners according to the present disclosure are used;

FIG. 17 is an end elevational view of an alternative embodiment of the filter pack depicted in FIG. 1; and

FIG. 18 is an end elevational view of another embodiment of the filter pack depicted in FIG. 1.

DETAILED DESCRIPTION

A. FIGS. 1–7

Attention is directed to FIG. 1. FIG. 1 is a perspective view of a first embodiment of a filter pack 50. The preferred filter pack 50 depicted includes filter media 55 and a sealing system 60. In preferred constructions, the filter media 55 is designed to remove particulates from a fluid, such as air, passing through the filter media 55, while the sealing system 60 is designed to seal the filter pack 50 against a sidewall of a housing or duct, as shown in FIGS. 8 and 9. By the term “seal,” it is meant that the sealing system 60, under normal conditions, prevents unintended levels of fluid from passing through a region between the filter pack 50 and the sidewall of the housing or duct; i.e., the sealing system 60 inhibits fluid flow from avoiding passage through the filtering media 55 of filter pack 50.

In certain preferred arrangements, the filter media 55 will be configured for straight-through flow. By “straight-through flow,” it is meant that the filter media 55 is configured in a construction 100 with a first flow face 105 (corresponding to an inlet end, in the illustrated embodiment) and an opposite, second flow face 110

3

(corresponding to an outlet end, in the illustrated embodiment), with fluid flow entering in one direction **114** through the first flow face **105** and exiting in the same direction **116** from the second flow face **110**. When used with an inline-flow housing, in general, the fluid will enter through the inlet of the housing in one direction, enter the filter construction **100** through the first flow face **105** in the same direction, exit the filter construction **100** in the same direction from the second flow face **110**, and exit the housing through the housing outlet also in the same direction.

Although the first flow face **105** is described above as corresponding to an inlet end, and the second flow face **110** is described above as corresponding to an outlet end, the inlet and outlet ends can be reversed. That is, the first flow face **105** depicted in FIG. 1 can correspond to an outlet end, while the second flow face **110** depicted in FIG. 1 can correspond to an inlet end.

In FIG. 1, the first flow face **105** and the second flow face **110** are depicted as planar and as parallel. In other embodiments, the first flow face **105** and the second flow face **110** can be non-planar, for example, frusto-conical. Further, the first flow face **105** and second flow face **110** need not be parallel to each other.

Generally, the filter construction **100** will be a wound construction. That is, the construction **100** will typically include a layer of filter media that is turned completely or repeatedly about a center point. Typically, the wound construction will be a coil, in that a layer of filter media will be rolled a series of turns around a center point. In arrangements where a wound, coiled construction is used, the filter construction **100** will be a roll of filter media, typically permeable fluted filter media.

Attention is now directed to FIG. 2. FIG. 2 is schematic, perspective view demonstrating the principles of operation of certain preferred media usable in the filter constructions herein. In FIG. 2, a fluted construction is generally designated at **122**. Preferably, the fluted construction **122** includes: a layer **123** of corrugations having a plurality of flutes **124** and a face sheet **132**. The FIG. 2 embodiment shows two sections of the face sheet **132**, at **132A** (depicted on top of the corrugated layer **123**) and at **132B** (depicted below the corrugated layer **123**). Typically, the preferred media construction **125** used in arrangements described herein will include the corrugated layer **123** secured to the bottom face sheet **132B**. When using this media construction **125** in a rolled construction, it typically will be wound around itself, such that the bottom face sheet **132B** will cover the top of the corrugated layer **123**. The face sheet **132** covering the top of the corrugated layer is depicted as **132A**. It should be understood that the face sheet **132A** and **132B** are the same sheet **132**.

When using this type of media construction **125**, the flute chambers **124** preferably form alternating peaks **126** and troughs **128**. The troughs **128** and peaks **126** divide the flutes into an upper row and lower row. In the particular configuration shown in FIG. 2, the upper flutes form flute chambers **136** closed at the downstream end, while flute chambers **134** having their upstream end closed form the lower row of flutes. The fluted chambers **134** are closed by a first end bead **138** that fills a portion of the upstream end of the flute between the fluting sheet **130** and the second facing sheet **132B**. Similarly, a second end bead **140** closes the downstream end of alternating flutes **136**. In some preferred systems, both the first end bead **138** and second end bead **140** are straight along all portions of the media construction **125**, never deviating from a straight path. In some preferred systems, the first end bead **138** is both straight and never

4

deviates from a position at or near one of the ends of the media construction **125**, while the second end bead **140** is both straight and never deviates from a position at or near one of the ends of the media construction **125**. The flutes **124** and end beads **138**, **140** provide the media construction **125** that can be formed into filter construction **100** and be structurally self-supporting without a housing.

When using media constructed in the form of media construction **125**, during use, unfiltered fluid, such as air, enters the flute chambers **136** as indicated by the shaded arrows **144**. The flute chambers **136** have their upstream ends **146** open. The unfiltered fluid flow is not permitted to pass through the downstream ends **148** of the flute chambers **136** because their downstream ends **148** are closed by the second end bead **140**. Therefore, the fluid is forced to proceed through the fluting sheet **130** or face sheets **132**. As the unfiltered fluid passes through the fluting sheet **130** or face sheets **132**, the fluid is cleaned or filtered. The cleaned fluid is indicated by the unshaded arrow **150**. The fluid then passes through the flute chambers **134** (which have their upstream ends **151** closed) to flow through the open downstream end **152** (FIG. 1) out the fluted construction **122**. With the configuration shown, the unfiltered fluid can flow through the fluted sheet **130**, the upper facing sheet **132A**, or lower facing sheet **132B**, and into a flute chamber **134**.

Typically, the media construction **125** will be prepared and then wound to form a rolled construction **100** of filter media. When this type of media is selected for use, the media construction **125** prepared includes the sheet of corrugations **123** secured with the end bead **138** to the bottom face sheet **132B** (as shown in FIG. 2, but without the top face sheet **132A**). In these types of arrangements, the media construction **125** will include a leading edge at one end and a trailing edge at the opposite end, with a top lateral edge and a bottom lateral edge extending between the leading and trailing edges. By the term "leading edge", it is meant the edge that will be initially turned or rolled, such that it is at or adjacent to the center or core of the rolled construction. The "trailing edge" will be the edge on the outside of the rolled construction, upon completion of the turning or coiling process.

The leading edge and the trailing edge should be sealed between the corrugated sheet **123** and the bottom face sheet **132B**, before winding the sheet into a coil, in these types of media constructions **125**. While a number of ways are possible, in certain methods, the seal at the leading edge is formed as follows: (a) the corrugated sheet **123** and the bottom face sheet **132B** are cut or sliced along a line or path extending from the top lateral edge to the bottom lateral edge (or, from the bottom lateral edge to the top lateral edge) along a flute **124** forming a peak **126** at the highest point (or apex) of the peak **126**; and (b) sealant is applied between the bottom face sheet **132B** and the sheet of corrugations **123** along the line or path of cut. The seal at the trailing edge can be formed analogously to the process of forming the seal at the leading edge. While a number of different types of sealant may be used for forming these seals, one usable material is a non-foamed sealant available from H.B. Fuller, St. Paul, Minn., identified under the designation HL0842.

When using the media construction **125**, it may be desired by the system designer to wind the construction **125** into a rolled construction of filter media, such as the filter construction **100** of FIG. 1. A variety of ways can be used to coil or roll the media. Attention is directed to FIG. 3. In the particular embodiment shown in FIG. 3, the media construction **125** is wound about a center mandrel **154** or other element to provide a mounting member for winding. The

5

center mandrel **154** may be removed or left to plug to act as a core at the center of the cylindrical filter construction **100** (FIG. **1**). It can be appreciated that non-round center winding members may be utilized for making other filtering media shapes, such as filter media having an oblong, oval, rectangular, or racetrack-shaped profile.

The media construction **125** can also be wound without a mandrel or center core. One method of forming a coreless rolled construction is as follows: (a) the troughs **128** of the first few corrugations of the corrugated sheet **123** spaced from the leading edge are scored from the top lateral edge to the bottom lateral edge (or from the bottom lateral edge to the top lateral edge) to help in rolling the construction **125**; for example, the first four corrugations from the leading edge will have a score line cut along the troughs **128**; (b) the bead **140** of sealant is applied along the top of the sheet of corrugation **123** along the lateral edge opposite from the lateral edge having end bead **138**; (c) the leading edge is initially turned or rolled over against itself and then pinched together to be sealed with the sealant bead **140**; and (d) the remaining corrugated sheet **123** having the bottom face sheet **132B** secured thereto is coiled or rolled or turned around the pinched leading edge.

In other methods, coreless constructions can be made from the media construction **125** by automated processes, as described in U.S. Pat. Nos. 5,543,007 and 5,435,870, each incorporated by reference herein. In still other methods, the media construction can be rolled by hand.

When using rolled constructions such as the filter construction **100**, the system designer will want to ensure that the outside periphery of the construction **100** is closed or locked in place to prevent the filter construction **100** from unwinding. There are a variety of ways to accomplish this. In some applications, the outside periphery is wrapped with a periphery layer. The periphery layer can be a non-porous, adhesive material, such as plastic with an adhesive on one side. When this type of layer is utilized, the periphery layer prevents the filter construction **100** from unwinding and prevents the fluid from passing through the outside periphery of the filter construction **100**, maintaining straight-through flow through the filter construction **100**.

In some applications, the filter construction **100** is secured in its rolled construction by sealing the trailing edge of the media construction **125** with an adhesive or sealant along a line **160** (FIG. **1**) to secure the trailing edge to the outside surface of the filter construction **100**. For example, a bead of hot-melt may be applied along the line **160**.

Attention is again directed to FIG. **1**. In FIG. **1**, the second flow face **110** is shown schematically. There is a portion at **112** in which the flutes including the open ends **152** and closed ends **148** are depicted. It should be understood that this section **112** is representative of the entire flow face **110**. For the sake of clarity and simplicity, the flutes are not depicted in the other remaining portions of the flow face **110**. Top and bottom plan views, as well as side elevational views of a filter pack **50** usable in the systems and arrangements described herein are depicted in copending and commonly assigned U.S. patent application Ser. No. 29/101,193, filed Feb. 26, 1999, and entitled, "Filter Element Having Sealing System," herein incorporated by reference.

Turning now to FIG. **9**, the filter construction **100** is shown installed in a housing **305** (which can be part of an air intake duct into an engine or turbo). In the arrangement shown, air flows into the housing **305** at **306**, through the filter construction **100**, and out of the housing **305** at **307**. When media constructions such as filter constructions **100** of the type shown are used in a duct or housing **305**, a sealing

6

system **60** will be needed to ensure that air flows through the media construction **100**, rather than bypass it.

Referring now to FIG. **5**, showing an enlarged, fragmented view of the filter construction **100** installed in the housing **305**, the particular sealing system **60** depicted includes a frame construction **170** and a seal member **250**. When this type of sealing system **60** is used, the frame construction **170** provides a support structure or backing against which the seal member **250** can be compressed against to form a radial seal **172** with the duct or housing **305**.

Still in reference to FIG. **5**, in the particular embodiment shown, the frame construction **170** includes a rigid projection **174** that projects or extends from at least a portion of one of the first and second flow faces **105**, **110** of the filter construction **100**. The rigid projection **174**, in the particular arrangement shown in FIG. **5**, extends axially from the second flow face **110** of the filter construction **100**. The particular FIG. **5** embodiment shows the projection **174** axially projecting above the entire second flow face **110**, due to the planar shape of the second flow face **110**. In arrangements where the flow face is non-planar, such as frusto-conical, the projection **174** can be designed to project above only a portion of the flow face. For example, in a frusto-conical filter construction, there could be a center portion at or near the core that extends above the projection **174**.

FIG. **6** depicts a cross-sectional view the particular frame construction **170** depicted in FIG. **5**. In FIG. **6**, the projection **174** shown has a pair of opposite sides **176**, **178** joined by an end tip **180**. In preferred arrangements, one of the first and second sides **176**, **178** will provide a support or backing to the seal member **250** such that a seal **172** can be formed between and against the selected side **176** or **178** and the appropriate surface of the housing or duct. When this type of construction is used, the projection **174** will be a continuous member forming a closed loop structure **182** (FIG. **4**). The seal member **250** can engage or be adjacent to either an interior side **184** of the loop structure **182**, or the exterior side **186** of the loop structure **182**. When engaging the interior side **184** of the loop structure **182**, the seal member **250** can be compressed between the projection **174** and a tubular member inserted within the loop, such that the projection **174** and seal member **250** circumscribes the tubular member. This would form a radial seal between and against the outer portion of the tubular member and the interior side **176** of the projection **174** (and the loop structure **182**).

The seal member **250** can also engage the exterior portion **186** of the loop structure **182**. When this type of construction is used, a housing or duct may circumscribe the projection **174** and loop structure **182** including the seal member **250** to form a seal between and against the outer side **178** of the projection **174** and an inner surface of the housing or duct.

In certain preferred arrangements, the seal member **250** engages or covers both of the interior side **184** and exterior side **186** of the loop structure **182**. In the particular embodiment shown in FIG. **5**, the seal member **250** engages the end tip **180** of the projection **174** as well, such that the seal member **250** covers the projection **174** from the exterior side **186**, over the end tip **180**, and to the interior side **184**.

Attention is directed to FIGS. **4**, **5** and **6**. FIG. **4** is a schematic, plan view of the sealing system **60** of FIG. **1**; FIG. **5** is a fragmented, schematic, cross-sectional view of the filter pack **50** of FIG. **1** installed in housing **305**; and FIG. **6** is a schematic, cross-sectional view of the frame construction **170** of the sealing system **60** of FIG. **4**.

In general, when using frame constructions **170** such as those described herein, the frame construction **170** will

7

include a frame **205**. The frame **205** may be a variety of shapes. In the particular embodiment illustrated in FIG. 4, the shape of the frame **205** is generally circular. The frame **205** depicted in FIG. 4 is convenient in that it is arranged and configured for attachment to the second flow face **110** of the filter construction **100**.

Referring now to FIG. 6, in the particular arrangement depicted, the frame **205** has a band, skirt, or depending lip **251** that is generally circular and has an inside diameter. Preferably, the inside diameter is approximately equal to the outside diameter of the filter construction **100**. The depending lip **251** depends or extends down a first distance from a bottom **252** surface of cross braces **210**. The depending lip **251** is arranged and configured to extend radially around the second flow face **110** of the filter construction **100**. Referring now to FIG. 5, in the particular embodiment depicted, the depending lip **251** extends radially around the second flow face **110** of the filter media **100**, such that the depending lip **251** extends inboard the first distance of the second flow face **110** of the filter construction **100**, defining an overlap region **255**.

The frame **205** is preferably secured to the filter construction **100**. A variety of ways to secure the frame **205** to the filter construction **100** are possible. One particularly preferred way to secure the frame **205** to the filter construction **100** is by use of an adhesive. In the particular embodiment depicted in FIG. 5, the adhesive is oriented in the overlap region **255** between the depending lip **251** and the filter construction **100**.

Preferably, the adhesive permanently affixes the frame **205** to the filter construction **100** while preventing the fluid from leaking out through the overlap region **255** between the filter construction **100** and the frame **205**. In alternative embodiments, the frame **205** may be temporarily attached to the filter construction **100**. By the term "temporarily," it is meant that the frame **205** may be removed from the filter construction **100** without damaging either the sealing system **60** or the filter construction **100**.

During use of frames **205** of the type depicted herein, inward forces are exerted around the circumference of the frame **205**. Cross braces **210** support the frame **205**. By the term "support," it is meant that the cross braces **210** prevent the frame **205** from radially collapsing under the forces exerted around the circumference of the frame **205**.

Referring again to FIG. 6, the particular projection **174** depicted preferably includes a tip portion **263**, or annular sealing support. In the one depicted in FIG. 6, the tip portion **263** is generally circular and is arranged and configured for insertion into a housing or duct. When circular, the tip portion **263** defines an inside diameter. Between the tip portion **263** and the depending lip **251**, the frame **205** includes a step **253**. The step **253** provides a transition area between the larger inside diameter of the depending lip **251** and the smaller inside diameter of the tip portion **263**.

When constructed according to the arrangement shown in FIGS. 5 and 6, the tip portion **263** provides support for the compressible seal member **250**. The compressible seal member **250** is preferably constructed and arranged to be sufficiently compressible to be compressed between the tip portion **263** of the frame **205** and a sidewall **260** of a housing or duct. When sufficiently compressed between the tip portion **263** and the sidewall **260**, radial seal **172** is formed between the filter pack **50** and the sidewall **260**.

A variety of ways are possible to secure the seal member **250** to the tip portion **263**. One particularly convenient and preferred way is by molding the seal member **250** to engage, cover, or overlap both the outer radial side **270** of the tip

8

portion **263** and the inner radial side **271** of the tip portion **263**, including the end tip **180** (FIG. 7). One particular embodiment of this configuration is depicted in FIG. 7. The seal member **250**, in FIG. 7, completely covers the tip portion **263**.

The tip portion **263** of the frame **205** defines a wall or support structure between and against which a radial seal **172** may be formed by the compressible seal member **250**. The compression of the compressible seal member **250** at the sealing system **60** is preferably sufficient to form a radial seal under insertion pressures of no greater than 80 lbs., typically, no greater than 50 lbs., for example, about 20–40 lbs., and light enough to permit convenient and easy change out by hand. Preferably, the amount of compression of the compressible seal member **250** is at least fifteen percent, preferably no greater than forty percent, and typically between twenty and thirty-three percent. By "amount of compression" it is meant the physical displacement of an outermost portion of the seal member **250** radially toward the tip portion **263** as a percentage of the outermost portion of the seal member **250** in a resting, undisturbed state and not installed within a duct or subject to other forces.

Attention is directed to FIG. 7. FIG. 7 is an enlarged schematic, fragmented view of a particular preferred seal member **250** in an uncompressed state. In the preferred embodiment shown, the seal member **250** is a stepped cross-sectional configuration of decreasing outermost dimensions (diameter, when circular) from a first end **264** to a second end **265**, to achieve desirable sealing. Preferred specifications for the profile of the particular arrangement shown in FIG. 7 are as follows: a polyurethane foam material having a plurality of (preferably at least three) progressively larger steps configured to interface with the sidewall **260** (FIG. 5) and provide a fluid-tight seal.

The compressible seal member **250** defines a gradient of increasing internal diameters of surfaces for interfacing with the sidewall **260**. Specifically, in the example shown in FIG. 7, the compressible seal member **250** defines three steps **266**, **267**, **268**. The cross-sectional dimension or width of the steps **266**, **267**, **268** increases the further the step **266**, **267**, **268** is from the second end **265** of the compressible seal member **250**. The smaller diameter at the second end **265** allows for easy insertion into a duct or housing. The larger diameter at the first end **264** ensures a tight seal.

In general, for a properly functioning radially sealing structure, the compressible seal member **250** needs to be compressed when the element is mounted in the housing **305** or duct. In many preferred constructions, it is compressed between about fifteen percent and forty percent (often about twenty to thirty-three percent) of its thickness, in the thickest portion, to provide for a strong robust seal yet still be one that can result from hand installation of the element with forces on the order of 80 pounds or less, preferably 50 pounds or less, and generally 20–40 pounds.

In general, the filter pack **50** can be arranged and configured to be press-fit against the sidewall **260** of the housing **305** or duct. In the specific embodiment shown in FIG. 5, the compressible seal member **250** is compressed between the sidewall **260** and the tip portion **263** of the frame **205**. After compression, the compressible seal member **250** exerts a force against the sidewall **260** as the compressible seal member **250** tries to expand outwardly to its natural state, forming radial seal **172** between and against the tip portion **263** and the sidewall **260**.

B. FIGS. 8 and 9

Attention is directed to FIG. 8. FIG. 8 is a schematic, perspective view of an air cleaner **300**. In certain systems,

the filter pack **50** is designed to be inserted into a housing **305** of an air cleaner **300**. The housing **305** is typically part of ductwork in airflow communication with an air intake system for an engine. As used herein, the term "ductwork" or "duct" will include structures such as pipes, tubes, and air cleaner housings.

A variety of housings are usable with the filter pack **50**. In the particular embodiment depicted in FIG. **8**, the housing **305** includes a body member or a first housing compartment **310** and a removable cover or second housing compartment **315**. In some arrangements, the first housing compartment **310** is affixed to an object, such as a truck. The second housing compartment **315** is removably secured to the first housing compartment **310** by a latching device **320**. Preferably, the latching device **320** includes a plurality of latches **325**.

While the housing may have a variety of cross-sectional configurations in the particular embodiment illustrated, the first and second housing compartments **310**, **315** are circular. In the arrangement depicted, the first housing compartment **310** has an outlet region **330**. The outlet region **330** is designed to allow the fluid to flow out of the filter assembly **300** during use. Similarly, the second housing compartment **315** has an inlet region **335**. The inlet region **335** is designed to allow the fluid to flow into the filter assembly **300** during use. In preferred constructions, the housing **305** will be an in-line housing. As such, the outlet region **330** and inlet region **335** are coaxially aligned, to permit air to flow through the inlet region **335** and flow through the outlet region **330** in the same direction. This can be seen in FIG. **9**.

The filter pack **50** is preferably constructed and arranged to be press-fit against the sidewall **260** of the housing **305**. In the illustrated embodiment in FIG. **9**, the second end **10** of the filter pack **50** with the attached frame **205** and compressible seal member **250** is inserted into the first housing compartment **310**. The filter pack **50** is press-fit into the first housing compartment **310** such that the compressible seal member **250** is compressed between and against the tip portion **263** of the frame **205** and the sidewall **260** of the first housing compartment **310**, to form radial seal **172** therebetween.

During use of the arrangement depicted in FIG. **9**, the fluid enters the housing assembly **300** at the inlet region **335** of the second housing compartment **315**, in the direction shown at **306**. The fluid passes through the filter construction **100**. As the fluid passes through the filter construction **100**, contaminants are removed from the fluid. The fluid exits the housing assembly **300** at the outlet region **330**, in the direction of **307**. The compressible seal member **250** of the sealing system **60** forms radial seal **172** to prevent contaminated fluid from exiting the housing assembly **300**, without first passing through the filter construction **100**.

C. FIGS. **17** and **18**

It should be appreciated that the filter pack **50** can have additional separators for ensuring that the appropriate degree of filtering is conducted. The separators can be either upstream of the filter pack **50** or downstream of the filter pack **50**, depending upon the particular application and the desired results. These separators can take the form of pre-cleaners in some embodiments, or post-cleaners (such as safety filters or secondary filters). In addition, these separators may be in the form of single or multiple layers of filtering media, located either upstream or downstream of the filter construction **100**. The filter media used in these applications will typically be selected based upon the degree of filtering desired and the amount of restriction introduced

by the filter media. For example, it may be that in certain applications, it is desired to filter out large particles (that is, debris such as leaves, butterflies, clumps of dirt) while introducing little more additional restriction. In this application, a layer of media such as a sieve or screen can be used upstream of the filter construction **100**. It may also be desired to introduce an additional amount of filtering just downstream of the filter construction **100**. This can be accomplished by a layer (or multiple layers) of media immediately downstream of the filter construction **100**.

Attention is directed to FIG. **17**. FIG. **17** illustrates an alternative embodiment of the filter pack **50**, shown generally at **50'**. The filter pack **50'** is configured and constructed analogously as the filter pack **50**, illustrated in FIG. **1**, with the exception of the first flow face **105'**, that corresponds to an upstream or an inlet end **106'**. FIG. **17** illustrates an end elevational view of the filter pack **50'**, viewing the upstream end **106'**. In the particular filter pack **50'** illustrated in FIG. **17**, the entire upstream end **106'** is covered by a layer of media **107'** for separating large particles from the gas stream before the gas stream reaches the filter construction **100**. Depending upon the application and the desired degree of filtration and restriction, the media **107'** can be of a variety of types. In many typical applications, the media **107'** will be sized to allow for the removal of particles such as butterflies, leaves, large clumps of dirt, and other types of debris. One type of media usable has the following characteristics and properties: polyester material; 50% of the fibers being about 15 denier and 50% of the fibers being about 6 denier by weight; the binder holding the fibers together being oil resistant rubber modified PVC; a basis weight of 6.6 oz/yd² (224 g/m²); a thickness of about 0.37 inches; a permeability of about 3500 ft/m in a 0.5 in. H₂O restriction.

As described above, it may also be desirable to introduce separation downstream of the filter construction **100**. One example is illustrated in FIG. **18**. FIG. **18** is an end elevational view of an alternative embodiment of the filter pack **55**, as viewed from the second flow face **110**. The filter pack **50** shown in FIG. **18** is constructed analogously as the filter pack **50** of FIG. **1**, with the exception of an additional separator **111** located downstream of the filter construction **100**. While a variety of embodiments are contemplated, in the particular embodiment illustrated in FIG. **18**, the separator **111** is in the form of a layer of media **112** located downstream of the filter construction **100**. The layer of media **112** can be either immediately adjacent and against the filter construction **100**, or it may be located downstream of the frame **205**. In the one illustrated in FIG. **18**, the media **112** is immediately downstream of and against the filter construction **100**. That is, the media **112** is located between the filter construction **100** and the cross braces **210** of the frame **205**.

The type of media **112** utilized will depend upon the desired degree of filtering and the amount of restriction that is introduced. The media **112** can be a single layer or multiple layers. In the one illustrated in FIG. **18**, the media **112** includes nonwoven, nonpleated, fibrous depth media **113**. One usable material for depth media **113** has the following characteristics: 1 layer of 4.0–4.8 oz/yd² (136–163 g/m²) polyester fiber depth media (mixed fibers); 0.55–0.70" (14–18 mm) thickness freestate (as measured under 0.002 psi compression); average fiber diameter about 21.0 micron (mass weighted average) or about 16.3 micron (length weighted average); permeability (minimum) 500 ft/min (152 m/min.); free state solidity about 0.6–1.0%, typically about 0.7%.

It is contemplated that in certain applications, it will be desired to have a filter pack **50** that includes both an upstream filter **107'** and a downstream filter **111**.

D. FIGS. 10-15

Attention is directed to FIG. 10. FIG. 10 is a perspective view of another embodiment of a filter pack 450. In the construction depicted, the filter pack 450 includes filter media 455 and a sealing system 460. The filter media 455 is designed to remove contaminants from a fluid, such as air, passing through the filter media 455. The sealing system 460 is designed to seal the filter media 455 to a housing or duct.

In certain preferred arrangements, the filter media 455 will be configured in a filter construction 470 with a first flow face 471 and an opposite, second flow face 472. Attention is directed to FIG. 11. In the particular embodiment illustrated in FIG. 11, the filter construction 470 is configured for straight-through flow. This means, as explained above, that fluid to be filtered will enter the first flow face 471 in a certain direction 477 (FIG. 10) and exit the second flow face 472 in the same direction 478 (FIG. 10).

The filter construction 470 can have a variety of configurations and cross-sectional shapes. In the particular embodiment illustrated in FIG. 11, the filter construction 470 has a non-circular cross-section. In particular, the FIG. 11 embodiment of the filter construction 470 has an ob-round or "racetrack" cross-sectional shape. By "racetrack" cross-sectional shape, it is meant that the filter construction 470 includes first and second semicircular ends 511, 512 joined by a pair of straight segments 513, 514.

In general, the filter construction 470 will be a wound construction. That is, the construction 470 will include a layer of filter media that is turned completely or repeatedly about a centerpoint. In certain preferred arrangements, the wound construction will be a coil, in that a layer of filter media will be rolled a series of turns about a centerpoint. In further preferred arrangements, the filter construction 470 will be a rolled construction, typically a roll of filter media, for example permeable fluted filter media.

Many different ways of manufacturing the media construction 470 can be used. In some techniques, a single-faced filter media, such as the filter media 122 illustrated in FIG. 2, is wound about a center mandrel or other structure to provide a mounting member for winding. The center mandrel may be removed or left to plug the center of the filter construction 470. In the particular embodiment shown in FIG. 11, a center core 454 is illustrated as occupying the center of the coil of filter media 455.

In FIGS. 10 and 11, certain portions 475 are depicted showing the flutes, including the open and closed ends. It should be understood that this portion or section 475 is representative of the entire flow face 472 (as well as the first flow face 471). For the sake of clarity and simplicity, the flutes are not depicted in the other remaining portions of the flow face 472. Top and bottom plan views, as well as side elevational views of the filter pack 450 usable in the systems and arrangements described herein are depicted in copending and commonly assigned U.S. patent application Ser. No. 29/101,193, filed Feb. 26, 1999, and entitled, "Filter Element Having Sealing System," herein and incorporated by reference.

As with the embodiment of FIG. 1, the filter pack 450 includes a sealing system 460. In preferred constructions, the sealing system 460 includes a frame 605 and a seal member 650.

While a variety of configurations are contemplated herein, one particularly preferred embodiment of the frame 605 is shown in perspective view in FIG. 12.

In the particular arrangement depicted in FIG. 12, the frame 605 has a non-circular, for example, obround and in

particular, a racetrack shape and is arranged and configured for attachment to the second end 510 of the filter media 455. In particular, the frame 605 has a band or skirt or depending lip 651 that is generally racetrack shaped. The depending lip 651 depends or extends down a distance from a bottom surface 652 of cross braces 610. The depending lip 651 is arranged and configured to extend radially around the second end 570 of filter construction 470. Referring now to FIG. 10, in the embodiment depicted, the depending lip 651 of the frame 605 extends radially around the second end 510 of the filter construction 470, such that the depending lip 651 extends inboard the distance from bottom surface 652 of cross braces 610 of the second end 510 of the filter construction 470, defining an overlap region 555 (FIG. 15).

The frame 605 can be secured to the filter construction 470 in a number of ways. One particularly convenient way is by securing the frame 605 to the filter construction 470 by adhesive. In the specific embodiment illustrated and FIG. 15, the adhesive is placed in the overlap region 555 between the frame 605 and the filter construction 470 as previously described herein.

During use of the arrangements depicted, inward forces are exerted around the circumference of the frame 605. Inward forces exerted against the semicircular ends 511, 512 can cause the straight segments 513, 514 to bow or bend. Structure is provided as part of the frame 605 to prevent the straight segments 513, 514 from bowing. While a variety of structures are contemplated herein, in the particular embodiment illustrated in FIG. 12, cross braces 610 are provided to provide structural rigidity and support to the straight segments 513, 514. As can be seen in FIG. 12, the particular cross braces 610 depicted form a truss system 612 between the opposing straight segments 513, 514. The truss system 612 includes a plurality of rigid struts 614, preferably molded as a single piece with the remaining portions of the frame 605.

In certain preferred constructions, the frame 605 is constructed analogously to the frame 205. As such, and in reference now to FIGS. 12 and 13, the frame 605 includes a tip portion 663. In preferred arrangements, the tip portion 663 acts as an annular sealing support. In the construction depicted, the tip portion 663 has the same cross-sectional configuration as the filter construction 470. In the particular embodiment illustrated in FIG. 12, the tip portion is noncircular, specifically, racetrack shaped. In preferred implementations, and in reference to the particular embodiment shown in FIG. 13, between the tip portions 663 and the depending lip 651, the frame 605 includes a step 653. The step 653 provides a transition area between the cross-sectional width of the depending lip 651 and the smaller cross-sectional width of the tip portion 663.

In preferred systems, the compressible seal member 650 has structure analogous to the that of the compressible seal member 250 of FIG. 7.

Preferably, the filter pack 450 will be installed in a duct or an air cleaner housing. In certain preferred applications, the air cleaner housing will be an in-line housing. FIG. 14 illustrates an air cleaner 670 having one type of in-line housing 672. In FIG. 14, the housing depicted is a two-piece housing including a cover 674 and a body member 676. The cover 674 defines an airflow inlet 678. The body member 676 defines an airflow outlet 680. The housing further includes a pre-cleaner arrangement 679 upstream of the filter pack 450, such as that described in U.S. Pat. Nos. 2,887,177 and 4,162,906, incorporated by reference herein. In the one depicted, the pre-cleaner arrangement 679 is in the cover 674. The cover 674 includes a dust ejector 681 that expels dust and debris collected in the pre-cleaner 679.

13

FIG. 15 is a schematic cross-sectional view of the air cleaner 670 of FIG. 14 and showing the filter pack 450 installed therewithin.

The compressible seal member 650 is compressed between the sidewall 660 and the tip portion 663 of the frame 605. As the filter pack 450 is press-fit, the compressible seal member 650 is compressed between and against the frame 605 (specifically, in the particular embodiment shown, the tip portion 663) and the sidewall 660. After compression, the compressible seal member 650 exerts a force against the sidewall 660 as the compressible seal member 650 tries to expand outwardly to its natural state, forming a radial seal 685 with the sidewall 660.

E. Systems and Methods of Operation

The filter constructions and arrangements described herein are usable in a variety of systems. One particular type of system is depicted schematically in FIG. 16 generally at 700. In FIG. 16, equipment 702, such as a vehicle, having an engine 703 with some defined rated air flow demand, for example at least 500 cfm, and typically 700–1200 cfm is shown schematically. The equipment 702 may comprise a bus, an over-the-highway truck, an off-road vehicle, a tractor, or marine application such as a powerboat. The engine 703 powers the equipment 702, through use of an air and fuel mixture. In FIG. 16, air flow is shown drawn into the engine 703 at an intake region 705. An optional turbo 706 is shown in phantom, as optionally boosting the air intake into the engine 703. An air cleaner 710 having a filter construction 712 and a secondary element 713 is upstream of the engine 703 and the turbo 706. In general, in operation, air is drawn in at arrow 714 into the air cleaner 710 and through a primary element 712 and secondary element 713. There, particles and contaminants are removed from the air. The cleaned air flows downstream at arrow 716 into the intake 705. From there, the air flows into the engine 703 to power the equipment 702.

F. Change Out and Replacement

In certain preferred applications, the filter packs described herein are removable and replaceable from whatever system in which they are installed. For example, the filter pack 50, or filter pack 650, will be installed in an air cleaner housing such as those shown in FIGS. 9 and 15, respectively. After a certain number of hours of use, the media in the filter constructions will become occluded, and the restriction in the filter packs will increase. In preferred applications, the filter packs will be periodically replaced to maintain the appropriate removal of particulates from a fluid, without introducing too high of a restriction.

In some applications, the filter constructions herein will include a visual indicator of useful life. Some systems may include a restriction indicator to provide information to the user regarding the appropriate time to change out the filter pack.

To service the air cleaner arrangements described herein, the user will need access the filter pack. For example, if the filter pack is installed in an air cleaner housing such as those shown in FIG. 9 or FIG. 15, the user will unlatch the cover from the body member, and remove the cover from the body member. This will expose an opening. The user will grasp the filter pack and break the radial seal formed by the filter pack against the sidewall of the housing or duct. In certain systems, the seal member and the housing or duct will be designed such that the user will need to exert a force of no more than about 80 lbs., preferably no more than 50 lbs., and in some applications between 15 and 40 lbs. to break the radial seal and remove the filter pack. The user will then pull the filter pack through the opening formed by the body

14

member. The old filter pack may then be disposed of. In certain preferred systems, the filter pack will be constructed of non-metallic materials, such that it is readily incineratable. For example, in some preferred constructions, the filter pack will comprise at least 95 percent, and typically at least 98 percent nonmetallic materials.

To install a new filter pack, the user grasps the filter pack and inserts it through an opening in the duct or housing. The filter pack is inserted into the opening until the seal member is sufficiently compressed against the inner annular wall of the housing to form a radial seal between and against the housing wall and the tip portion of the frame. The cover may then be oriented over the exposed end of the filter pack to close the opening. The cover may then be latched to the body member.

G. Example Construction

In this section, examples are provided of a set of operating specifications. These are intended as an example. A wide variety of alternate sizes can be used.

1. FIGS. 1–8.

The axial length of the filter media 100 of FIG. 2 will be between 3 inches (about 8 cm) and 10 inches (about 25 cm), and in one example would be approximately 6 inches (about 15 cm). The outside diameter of the filter media 100 will be between 3 inches (about 8 cm) and 15 inches (about 38 cm), and in one example would be approximately 10 inches (about 25 cm).

The distance (FIG. 5) that the depending lip 251 of the frame 205 (FIG. 5) extends inboard of the second end 110 (FIG. 5) of the filter construction 100 will be between 0.2 inches (about 5 mm) and 1 inch (about 2.5 cm), and in one example would be 0.6 inches (about 1.5 cm). The diameter of the depending lip 251 will be between 3 inches (about 7 cm) and 15 inches (about 38 cm), and in one example would be approximately 10 inches (about 25 cm). The diameter of the tip portion 263 will be between 2.5 inches (about 6 cm) and 14 inches (36 cm), and in one example would be approximately 9.5 inches (about 24 cm).

The filter element will provide at least 5 sq. ft and typically 20–130 sq. ft., for example about 45 sq. ft. of media surface area. It will occupy a volume of no greater than about 1 ft³, and typically between 0.03–0.5 ft³, and for example about 0.2–0.4 ft³.

2. FIG. 9

The diameter of the outlet region 330 (FIG. 9) of the first housing compartment 310 (FIG. 9) will be between 3 inches (about 8 cm) and 10 inches (about 25 cm), and in one example would be 7 inches (about 18 cm). The diameter (FIG. 9) of the inlet region 335 (FIG. 9) of the second housing compartment 315 (FIG. 9) will be between 3 inches (about 8 cm) and 10 inches (about 25 cm), and in one example would be 5.8 inches (about 15 cm).

3. FIGS. 10–14

The axial length of the filter construction 470 will be between 3 inches (about 8 cm) and 10 inches (about 25 cm), and in one example would be approximately 6 inches (about 15 cm). The semicircular ends 511, 512 will have a radius of between 1 inch (about 2.5 cm) and 5 inches (about 13 cm), and in one example have a radius of 2.7 inches (about 7 cm). The straight segments 513, 514 will have a length greater than 0.1 inches (about 2.5 mm), and in one example, would be 4.9 inches (about 12 cm).

Preferably, the distance that the frame 605 extends inboard of the filter construction 470 will be between 0.2 inches (about 5 mm) and 1 inch (about 2.5 cm), and in one example would be 0.6 inches (about 1.5 cm).

The filter element will provide at least 5 sq. ft and typically 20–130 sq. ft., for example about 45 sq. ft. of media

15

surface area. It will occupy a volume of no greater than about 1 ft³, and typically between 0.03–0.5 ft³, and for example about 0.2–0.4 ft³.

H. Example Materials

In this section, examples are provided of usable materials. The particular choice for any given material will vary, depending on the filtering application. In other words, the particular material selected for the systems usable herein will be decided upon by the system designer based on the system requirements. A variety of materials are possible. The following section provides examples of materials that have been found to be suitable.

The media **122** can comprise cellulose. One example of media usable in the system described above is as follows: cellulose media with the following properties: a basis weight of about 45–55 lbs./3000 ft² (84.7 g/m²), for example, 48–54 lbs./3000 ft²; a thickness of about 0.005–0.015 in, for example about 0.010 in. (0.25 mm); frazier permeability of about 20–25 ft/min, for example, about 22 ft/min (6.7 m/min); pore size of about 55–65 microns, for example, about 62 microns; wet tensile strength of at least about 7 lbs./in, for example, 8.5 lbs./in (3.9 kg/in); burst strength wet off of the machine of about 15–25 psi, for example, about 23 psi (159 kPa).

The cellulose media can be treated with fine fiber, for example, fibers having a size (diameter) of 5 microns or less, and in some instances, submicron. A variety of methods can be utilized for application of the fine fiber to the media. Some such approaches are characterized, for example, in U.S. Pat. No. 5,423,892, column 32, at lines 48–60. More specifically, such methods are described in U.S. Pat. Nos. 3,878,014; 3,676,242; 3,841,953; and 3,849,241, incorporated herein by reference. An alternative is a trade secret approach comprising a fine polymeric fiber web positioned over conventional media, practiced under trade secret by Donaldson Company under the designation ULTRA-WEB®. With respect to the configurations of the filter element and the operation of the sealing system, there is no particular preference for: how the fine fibers are made; and, what particular method is used to apply the fine fibers. Enough fine fiber would be applied until the resulting media construction would have the following properties: initial efficiency of 99.5% average, with no individual test below 90%, tested according to SAE J726C, using SAE fine dust; and an overall efficiency of 99.98% average, according to SAE J726C.

The frame **205** (FIG. 5) will be constructed of a material that will provide structural integrity and is not subject to creep. The frame **205** will be constructed of a non-metallic material such that it is environmentally friendly and either recyclable or readily incineratable. The frame **205** can be constructed from most plastics, for example, glass reinforced plastic. One usable reinforced plastic is propylene or nylon. Of course, other suitable materials may be used.

The compressible seal member **250** (FIG. 6) can be made from a variety of materials. There is no particular preference, provided that the seal member **250** forms a seal in the proper location under compression. One usable material will be a soft polymeric material, such as foamed urethane. One example usable material includes foamed polyurethane, processed to an end product having an “as molded” density of fourteen to twenty-two pounds per cubic foot. Foamed polyurethanes are available from a variety of sources, such as BASF Corporation of Wyandotte, Mich. One example of a foamed polyurethane comprises a material made with 135453R resin and 13050U isocyanate, which is sold exclusively to the assignee Donaldson by BASF Corporation.

16

The materials should be mixed in a mix ratio of 100 parts 135453 resin to 36.2 parts 13050U isocyanate (by weight). The specific gravity of the resin is 1.04 (8.7 pounds/gallon), and for the isocyanate it is 1.20 (10 pounds/gallon). The materials are typically mixed with a high dynamic shear mixer. The component temperatures should be seventy to ninety-five degrees Fahrenheit. The mold temperatures should be 115–135 degrees Fahrenheit.

The resin material 135453R has the following description:

- (a) Average molecular weight
 - 1) Base polyether polyol=500–15,000
 - 2) Diols=60–10,000
 - 3) Triols=500–15,000
- (b) Average functionality
 - 1) total system=1.5–3.2
- (c) Hydroxyl number
 - 1) total systems=100–300
- (d) Catalysts
 - 1) amine=Air Products 0.1–3.0 PPH
 - 2) tin=Witco 0.01–0.5 PPH
- (e) Surfactants
 - 1) total system=0.1–2.0 PPH
- (f) Water
 - 1) total system=0.03–3.0 PPH
- (g) Pigments/dyes
 - 1) total system=1–5% carbon black
- (h) Blowing agent
 - 1) 0.1–6.0% HFC 134A.

The 13050U isocyanate description is as follows:

- (a) NCO content—22.4–23.4 wt %
- (b) Viscosity, cps at 25° C.=600–800
- (c) Density=1.21 g/cm³ at 25° C.
- (d) Initial boiling pt.—190° C. at 5 mm Hg
- (e) Vapor pressure=0.0002 Hg at 25° C.
- (f) Appearance—colorless liquid
- (g) Flash point (Densky-Martins closed cup)=200° C.

The above is a complete description of principles of the invention. Many embodiments can be made according to principles of this disclosure.

We claim:

1. A filter element arrangement comprising:

- (a) a media pack having first and second opposite flow faces and a plurality of flutes;
 - (i) each of said flutes having a first end portion adjacent to said first flow face and a second end portion adjacent to said second flow face;
 - (ii) selected ones of said flutes being open at said first end portion and closed at said second end portion; and selected ones of said flutes being closed at said first end portion and open at said second end portion;
 - (iii) said media pack having a longitudinal axis passing through the first flow face and the second flow face;
- (b) a sealing system including a frame construction and a seal member;
 - (i) said frame construction including an extension projecting axially from one of said first and second flow faces and in a same direction as the longitudinal axis;
 - (ii) said seal member being supported by said extension of said frame arrangement; and
 - (iii) said frame construction having a portion extending across one of said first flow face and second flow face.

2. A filter element arrangement according to claim 1 wherein:

17

- (a) said extension includes an end tip; an outer circumferential surface, and an opposite inner surface; and
- (b) said seal member includes a first portion being oriented against said outer circumferential surface of said extension. 5
- 3.** A filter element arrangement according to claim 2 wherein:
 - (a) said seal member includes a second portion oriented against said end tip; and a third portion oriented against said inner surface. 10
- 4.** A filter element arrangement according to claim 1 wherein:
 - (a) said extension of said frame construction projects from a lip member secured to an outer periphery of the media pack. 15
- 5.** A filter element arrangement according to claim 4 wherein:
 - (a) said lip member is part of said frame construction.
- 6.** A filter element arrangement according to claim 4 wherein:
 - (a) said lip member comprises glass reinforced plastic. 20
- 7.** A filter element arrangement according to claim 2 wherein:
 - (a) said seal member defines a cross-sectional configuration at least one step. 25
- 8.** A filter element arrangement according to claim 2 wherein:
 - (a) said seal member defines a cross-sectional configuration of at least two steps increasing from said end tip of said extension toward said filter pack. 30
- 9.** A filter element arrangement according to claim 2 wherein:
 - (a) said seal member defines a cross-sectional configuration of three steps increasing from said end tip of said extension toward said filter pack. 35
- 10.** A filter element arrangement according to claim 1 wherein:
 - (a) said frame construction portion extending across one of said first flow face and second flow face comprises cross braces; and 40
 - (b) said seal member comprises polyurethane foam.
- 11.** A filter element arrangement according to claim 1 wherein:
 - (a) said media pack has a racetrack cross-sectional shape. 45
- 12.** A filter element arrangement according to claim 1 wherein:
 - (a) said media pack has a circular cross-sectional shape.
- 13.** An air cleaner comprising: 50
 - (a) a housing arrangement including at least a cover and a body member;
 - (i) said cover defining an air flow inlet;
 - (b) a removeable and replaceable filter element oriented in said body member; said filter element including: 55
 - (i) a coiled media construction having: first and second ends; a first flow face at the first end; and a second flow face at the second end;
 - (A) the media within said coiled media construction forming a plurality of flutes; each of the flutes having a first end positioned adjacent to the first flow face and a second end positioned adjacent to the second flow face; 60
 - (B) a first set of selected ones of the flutes being open at the first end and closed at the second end; and 65
 - (C) a second set of selected ones of said flutes being closed at the first end and open at the second end;

18

- (ii) a seal member oriented with respect to said coiled media construction to form a releasable, peripherally directed seal between the filter element and an internal annular sealing surface of the housing arrangement;
- (iii) a frame construction mounted on said coiled media construction;
 - (A) said frame construction having a portion extending across one of said first flow face and second flow face;
 - (B) said frame construction supporting said seal member; and
- (c) a precleaner arrangement oriented in the cover and upstream of said filter element.
- 14.** An air cleaner according to claim 13 further including:
 - (a) a post-cleaner oriented in said housing arrangement downstream of said filter element.
- 15.** An air cleaner according to claim 14 wherein:
 - (a) said post-cleaner comprises a layer of media downstream of said filter element.
- 16.** An air cleaner according to claim 15 wherein:
 - (a) said post-cleaner layer of media is immediately adjacent to and against said second flow face of said coiled media construction.
- 17.** An air cleaner according to claim 13 wherein:
 - (a) said cover includes a dust ejector.
- 18.** An air cleaner according to claim 13 wherein:
 - (a) said frame construction includes an extension projecting axially from one of the first and second flow faces;
 - (i) said seal member being supported by said extension.
- 19.** An air cleaner according to claim 18 wherein:
 - (a) the extension of the frame construction has an outer circumferential surface; and
 - (b) the extension of the frame construction comprises an annular sealing support for the seal member.
- 20.** An air cleaner according to claim 19 wherein:
 - (a) said releasable, peripherally directed seal is formed by compression of the seal member between and against the annular sealing support and the internal annular sealing surface of the housing arrangement.
- 21.** An air cleaner according to claim 19 wherein:
 - (a) said frame construction includes a lip member circumscribing and secured to an outer periphery of the coiled media construction;
 - (i) said extension of said frame construction projecting from said lip member.
- 22.** An air cleaner according to claim 13 wherein:
 - (a) said filter element has a circular cross-section.
- 23.** An air cleaner according to claim 13 wherein:
 - (a) said filter element has a racetrack cross-sectional shape.
- 24.** An air cleaner according to claim 13 wherein:
 - (a) said frame construction portion extending across one of said first flow face and second flow face comprises cross braces.
- 25.** An air cleaner comprising:
 - (a) a housing arrangement including at least a cover and a body member;
 - (i) said cover defining an air flow inlet;
 - (b) a removeable and replaceable filter element oriented in said body member; said filter element including:

19

- (i) a coiled media construction having: first and second ends; a first flow face at the first end; and a second flow face at the second end;
- (A) the media within said coiled media construction forming a plurality of flutes; each of the flutes having a first end positioned adjacent to the first flow face and a second end positioned adjacent to the second flow face;
- (B) a first set of selected ones of the flutes being open at the first end and closed at the second end; and
- (C) a second set of selected ones of said flutes being closed at the first end and open at the second end;
- (ii) a seal member oriented with respect to said coiled media construction to form a releasable, peripherally directed seal between the filter element and an internal annular sealing surface of the housing arrangement;
- (iii) a frame construction mounted on said coiled media construction;
- (A) said frame construction having a portion extending across one of said first flow face and second flow face;
- (B) said frame construction supporting said seal member; and
- (c) a post-cleaner oriented in said housing arrangement downstream of said filter element.

20

- 26. An air cleaner according to claim 25 wherein:
- (a) said post-cleaner comprises a layer of media downstream of said filter element.
- 27. An air cleaner according to claim 26 wherein:
- (a) said post-cleaner layer of media is immediately adjacent to and against said second flow face of said coiled media construction.
- 28. An air cleaner according to claim 25 wherein:
- (a) said cover includes a pre-cleaner and a dust ejector.
- 29. An air cleaner according to claim 25 wherein:
- (a) said frame construction includes an extension projecting axially from one of the first and second flow faces;
- (i) said seal member being supported by said extension.
- 30. An air cleaner according to claim 25 wherein:
- (a) said filter element has a circular cross-section.
- 31. An air cleaner according to claim 25 wherein:
- (a) said filter element has a racetrack cross-sectional shape.
- 32. An air cleaner according to claim 25 wherein:
- (a) said frame construction portion extending across one of said first flow face and second flow face comprises cross braces.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,783,565 B2
DATED : August 31, 2004
INVENTOR(S) : Gieseke et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, insert

-- 4,282,186 8/1981 Nonnenmann et al.
4,285,909 8/1981 Mizusawa et al.
4,617,176 10/1986 Merry
5,683,660 11/1997 Wirth et al. --

FOREIGN PATENT DOCUMENTS, insert

-- EP 0 486 276 A1 5/1992
EP 0 492 250 A1 7/1992
EP 0 529 921 A1 3/1993
EP 0 581 695 A1 2/1994
WO 97/45200 12/1997
WO 98/35144 8/1998
WO 99/37381 7/1999 --

Column 15,


Line 66, delete "135453R" and insert -- I35453R --;
Line 66, delete "13050U" and insert -- I3050U --;

Column 16,

Line 2, delete "135453" and insert -- I35453 --;
Line 2, delete "13050U" and insert -- I3050U --;
Line 9, delete "135453R" and insert -- I35453R --; and
Line 29, delete "13050U" and insert -- I3050U --.

Signed and Sealed this

Thirtieth Day of November, 2004

A handwritten signature in black ink on a light gray dotted background. The signature is written in a cursive, stylized font and appears to read "Jon W. Dudas".

JON W. DUDAS

Director of the United States Patent and Trademark Office