



US008149117B2

(12) **United States Patent**
Fennell et al.

(10) **Patent No.:** **US 8,149,117 B2**
(45) **Date of Patent:** ***Apr. 3, 2012**

(54) **ANALYTE MONITORING SYSTEM AND METHODS**

600/500–508, 529–538, 544–545, 310, 316,
435, 347; 128/900, 903–904, 920–925; 707/E17.05,
707/999.1

(75) Inventors: **Martin J. Fennell**, Concord, CA (US);
Lei He, Moraga, CA (US); **Mark K. Sloan**, Redwood City, CA (US); **Gary Alan Hayter**, Oakland, CA (US)

See application file for complete search history.

(73) Assignee: **Abbott Diabetes Care Inc.**, Alameda, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 59 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/550,357**

(22) Filed: **Aug. 29, 2009**

(65) **Prior Publication Data**

US 2009/0318789 A1 Dec. 24, 2009

Related U.S. Application Data

(63) Continuation of application No. 12/117,681, filed on May 8, 2008.

(60) Provisional application No. 60/916,744, filed on May 8, 2007.

(51) **Int. Cl.**
G08B 21/00 (2006.01)

(52) **U.S. Cl.** **340/540**; 340/500; 340/539.1;
340/539.14; 340/539.23; 340/573.1; 600/310;
600/316; 600/345; 600/347

(58) **Field of Classification Search** 340/540,
340/539.1, 539.14, 539.23, 384.5, 693.9,
340/573.1, 500; 600/300, 301, 481–486,

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,755,036 A	7/1956	Mikko
3,260,656 A	7/1966	Ross, Jr.
3,304,413 A	2/1967	Lehmann et al.
3,581,062 A	5/1971	Aston
3,651,318 A	3/1972	Czekajewski
3,653,841 A	4/1972	Klein
3,698,386 A	10/1972	Fried
3,719,564 A	3/1973	Lilly, Jr. et al.
3,768,014 A	10/1973	Smith et al.
3,776,832 A	12/1973	Oswin et al.
3,837,339 A	9/1974	Aisenberg et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 4234553 1/1995

(Continued)

OTHER PUBLICATIONS

Abruna, H. D., et al., "Rectifying Interfaces Using Two-Layer Films of Electrochemically Polymerized Vinylpyridine and Vinylbipyridine Complexes of Ruthenium and Iron on Electrodes", *Journal of the American Chemical Society*, vol. 103, No. 1, 1981, pp. 1-5.

(Continued)

Primary Examiner — George Bugg


Assistant Examiner — Sisay Yacob

(74) *Attorney, Agent, or Firm* — Jackson & Co., LLP

(57) **ABSTRACT**

Methods and systems for providing data communication in medical systems are disclosed.

54 Claims, 14 Drawing Sheets



US 8,149,117 B2

Page 2

U.S. PATENT DOCUMENTS

3,919,051 A	11/1975	Koch et al.	4,560,534 A	12/1985	Kung et al.
3,926,760 A	12/1975	Allen et al.	4,569,589 A	2/1986	Neufeld
3,949,388 A	4/1976	Fuller	4,571,292 A	2/1986	Liu et al.
3,972,320 A	8/1976	Kalman	4,573,994 A	3/1986	Fischell et al.
3,979,274 A	9/1976	Newman	4,581,336 A	4/1986	Malloy et al.
4,003,379 A	1/1977	Ellinwood, Jr.	4,595,011 A	6/1986	Phillips
4,008,717 A	2/1977	Kowarski	4,595,479 A	6/1986	Kimura et al.
4,016,866 A	4/1977	Lawton	4,601,707 A	7/1986	Albisser et al.
4,021,718 A	5/1977	Konrad	4,619,754 A	10/1986	Niki et al.
4,036,749 A	7/1977	Anderson	4,619,793 A	10/1986	Lee
4,055,175 A	10/1977	Clemens et al.	4,627,445 A	12/1986	Garcia et al.
4,059,406 A	11/1977	Fleet	4,627,908 A	12/1986	Miller
4,076,596 A	2/1978	Connery et al.	4,633,878 A	1/1987	Bombardien
4,098,574 A	7/1978	Dappen	4,633,881 A	1/1987	Moore et al.
4,100,048 A	7/1978	Pompei et al.	4,637,403 A	1/1987	Garcia et al.
4,129,128 A	12/1978	McFarlane	4,648,408 A	3/1987	Hutcheson et al.
4,151,845 A	5/1979	Clemens	4,650,547 A	3/1987	Gough
4,154,231 A	5/1979	Russell	4,653,513 A	3/1987	Dombrowski
4,168,205 A	9/1979	Danninger et al.	4,654,197 A	3/1987	Lilja et al.
4,172,770 A	10/1979	Semersky et al.	4,655,880 A	4/1987	Liu
4,178,916 A	12/1979	McNamara	4,655,885 A	4/1987	Hill et al.
4,193,026 A	3/1980	Finger et al.	4,658,463 A	4/1987	Sugita et al.
4,206,755 A	6/1980	Klein	4,671,288 A	6/1987	Gough
4,224,125 A	9/1980	Nakamura et al.	4,674,652 A	6/1987	Aten et al.
4,240,438 A	12/1980	Updike et al.	4,679,562 A	7/1987	Luksha
4,240,889 A	12/1980	Yoda et al.	4,680,268 A	7/1987	Clark, Jr.
4,245,634 A	1/1981	Albisser et al.	4,682,602 A	7/1987	Prohaska
4,247,297 A	1/1981	Berti et al.	4,684,537 A	8/1987	Graetzel et al.
4,271,449 A	6/1981	Grogan	4,685,463 A	8/1987	Williams
4,318,784 A	3/1982	Higgins et al.	4,685,903 A	8/1987	Cable et al.
4,327,725 A	5/1982	Cortese et al.	4,686,624 A	8/1987	Blum et al.
4,331,869 A	5/1982	Rollo	4,703,756 A	11/1987	Gough et al.
4,340,458 A	7/1982	Lerner et al.	4,711,245 A	12/1987	Higgins et al.
4,344,438 A	8/1982	Schultz	4,717,673 A	1/1988	Wrighton et al.
4,349,728 A	9/1982	Phillips et al.	4,721,601 A	1/1988	Wrighton et al.
4,352,960 A	10/1982	Dormer et al.	4,721,677 A	1/1988	Clark, Jr.
4,356,074 A	10/1982	Johnson	4,726,378 A	2/1988	Kaplan
4,365,637 A	12/1982	Johnson	4,726,716 A	2/1988	McGuire
4,366,033 A	12/1982	Richter et al.	4,731,726 A	3/1988	Allen, III
4,375,399 A	3/1983	Havas et al.	4,749,985 A	6/1988	Corsberg
4,384,586 A	5/1983	Christiansen	4,750,496 A	6/1988	Reinhart
4,390,621 A	6/1983	Bauer	4,757,022 A	7/1988	Shults et al.
4,392,933 A	7/1983	Nakamura et al.	4,758,323 A	7/1988	Davis et al.
4,401,122 A	8/1983	Clark, Jr.	4,759,371 A	7/1988	Franetzki
4,404,066 A	9/1983	Johnson	4,759,828 A	7/1988	Young et al.
4,407,959 A	10/1983	Tsuji et al.	4,764,416 A	8/1988	Ueyama et al.
4,417,588 A	11/1983	Houghton et al.	4,776,944 A	10/1988	Janata et al.
4,418,148 A	11/1983	Oberhardt	4,777,953 A	10/1988	Ash et al.
4,420,564 A	12/1983	Tsuji et al.	4,779,618 A	10/1988	Mund et al.
4,425,920 A	1/1984	Bourland et al.	4,781,798 A	11/1988	Gough
4,427,004 A	1/1984	Miller et al.	4,784,736 A	11/1988	Lonsdale et al.
4,427,770 A	1/1984	Chen et al.	4,795,707 A	1/1989	Niiyama et al.
4,431,004 A	2/1984	Bessman et al.	4,796,634 A	1/1989	Huntsman et al.
4,436,094 A	3/1984	Cerami	4,803,625 A	2/1989	Fu et al.
4,440,175 A	4/1984	Wilkins	4,805,624 A	2/1989	Yao et al.
4,441,968 A	4/1984	Emmer et al.	4,813,424 A	3/1989	Wilkins
4,444,892 A	4/1984	Malmros	4,815,469 A	3/1989	Cohen et al.
4,450,842 A	5/1984	Zick et al.	4,820,399 A	4/1989	Senda et al.
4,458,686 A	7/1984	Clark, Jr.	4,822,337 A	4/1989	Newhouse et al.
4,461,691 A	7/1984	Frank	4,830,959 A	5/1989	McNeil et al.
4,467,811 A	8/1984	Clark, Jr.	4,832,797 A	5/1989	Vadgama et al.
4,469,110 A	9/1984	Slama	4,835,372 A	5/1989	Gombrich et al.
4,477,314 A	10/1984	Richter et al.	RE32,947 E	6/1989	Dormer et al.
4,478,976 A	10/1984	Goertz et al.	4,837,049 A	6/1989	Byers et al.
4,483,924 A	11/1984	Tsuji et al.	4,840,893 A	6/1989	Hill et al.
4,484,987 A	11/1984	Gough	RE32,974 E	7/1989	Porat et al.
4,494,950 A	1/1985	Fischell	4,844,076 A	7/1989	Lesho et al.
4,509,531 A	4/1985	Ward	4,845,035 A	7/1989	Fanta et al.
4,512,348 A	4/1985	Uchigaki et al.	4,848,351 A	7/1989	Finch
4,522,690 A	6/1985	Venkatesetty	4,854,322 A	8/1989	Ash et al.
4,524,114 A	6/1985	Samuels et al.	4,856,340 A	8/1989	Garrison
4,526,661 A	7/1985	Steckhan et al.	4,857,713 A	8/1989	Brown
4,527,240 A	7/1985	Kvitash	4,858,617 A	8/1989	Sanders
4,534,356 A	8/1985	Papadakis	4,870,561 A	9/1989	Love et al.
4,538,616 A	9/1985	Rogoff	4,871,351 A	10/1989	Feingold
4,543,955 A	10/1985	Schroeppel	4,871,440 A	10/1989	Nagata et al.
4,545,382 A	10/1985	Higgins et al.	4,874,499 A	10/1989	Smith et al.
4,552,840 A	11/1985	Riffer	4,874,500 A	10/1989	Madou et al.
			4,890,620 A	1/1990	Gough

4,890,621 A	1/1990	Hakky	5,120,421 A	6/1992	Glass et al.
4,894,137 A	1/1990	Takizawa et al.	5,122,925 A	6/1992	Inpyn
4,897,162 A	1/1990	Lewandowski et al.	5,124,661 A	6/1992	Zelin et al.
4,897,173 A	1/1990	Nankai et al.	5,126,034 A	6/1992	Carter et al.
4,899,839 A	2/1990	Dessertine et al.	5,126,247 A	6/1992	Palmer et al.
4,909,908 A	3/1990	Ross et al.	5,130,009 A	7/1992	Marsoner et al.
4,911,794 A	3/1990	Parce et al.	5,133,856 A	7/1992	Yamaguchi et al.
4,917,800 A	4/1990	Lonsdale et al.	5,134,391 A	7/1992	Okada
4,919,141 A	4/1990	Zier et al.	5,135,003 A	8/1992	Souma
4,919,767 A	4/1990	Vadgama et al.	5,139,023 A	8/1992	Stanley et al.
4,920,969 A	5/1990	Suzuki	5,140,393 A	8/1992	Hijikihigawa et al.
4,920,977 A	5/1990	Haynes	5,141,868 A	8/1992	Shanks et al.
4,923,586 A	5/1990	Katayama et al.	5,161,532 A	11/1992	Joseph
4,925,268 A	5/1990	Iyer et al.	5,165,407 A	11/1992	Wilson et al.
4,927,516 A	5/1990	Yamaguchi et al.	5,168,046 A	12/1992	Hamamoto et al.
4,931,795 A	6/1990	Gord	5,174,291 A	12/1992	Schoonen et al.
4,934,369 A	6/1990	Maxwell	5,176,644 A	1/1993	Srisathapat et al.
4,935,105 A	6/1990	Churchouse	5,176,662 A	1/1993	Bartholomew et al.
4,935,345 A	6/1990	Guilbeau et al.	5,182,707 A	1/1993	Cooper et al.
4,936,956 A	6/1990	Wrighton	5,184,359 A	2/1993	Tsukamura et al.
4,938,860 A	7/1990	Wogoman	5,185,256 A	2/1993	Nankai et al.
4,942,127 A	7/1990	Wada et al.	5,190,041 A	3/1993	Palti
4,944,299 A	7/1990	Silvian	5,192,415 A	3/1993	Yoshioka et al.
4,945,045 A	7/1990	Forrest et al.	5,192,416 A	3/1993	Wang et al.
4,950,378 A	8/1990	Nagata	5,193,539 A	3/1993	Schulman et al.
4,953,552 A	9/1990	DeMarzo	5,193,540 A	3/1993	Schulman et al.
4,954,129 A	9/1990	Giuliani et al.	5,197,322 A	3/1993	Indravudh
4,957,115 A	9/1990	Selker	5,198,367 A	3/1993	Aizawa et al.
4,958,632 A	9/1990	Duggan	5,200,051 A	4/1993	Cozzette et al.
4,968,400 A	11/1990	Shimomura et al.	5,202,261 A	4/1993	Musho et al.
4,969,468 A	11/1990	Byers et al.	5,205,920 A	4/1993	Oyama et al.
4,970,145 A	11/1990	Bennetto et al.	5,206,145 A	4/1993	Cattell
4,974,929 A	12/1990	Curry	5,208,154 A	5/1993	Weaver et al.
4,979,509 A	12/1990	Hakky	5,209,229 A	5/1993	Gilli
4,986,271 A	1/1991	Wilkins	5,215,887 A	6/1993	Saito
4,990,845 A	2/1991	Gord	5,216,597 A	6/1993	Beckers
4,991,582 A	2/1991	Byers et al.	5,217,442 A	6/1993	Davis
4,994,068 A	2/1991	Hufnagle	5,217,595 A	6/1993	Smith et al.
4,994,167 A	2/1991	Shults et al.	5,227,042 A	7/1993	Zawodzinski et al.
4,995,402 A	2/1991	Smith et al.	5,229,282 A	7/1993	Yoshioka et al.
5,000,180 A	3/1991	Kuypers et al.	5,236,143 A	8/1993	Dragon
5,001,054 A	3/1991	Wagner	5,237,993 A	8/1993	Skrabal
5,002,054 A	3/1991	Ash et al.	5,246,867 A	9/1993	Lakowicz et al.
5,007,427 A	4/1991	Suzuki et al.	5,250,439 A	10/1993	Musho et al.
5,016,172 A	5/1991	Dessertine	5,251,126 A	10/1993	Kahn et al.
5,016,201 A	5/1991	Bryan et al.	5,257,971 A	11/1993	Lord et al.
5,019,974 A	5/1991	Beckers	5,257,980 A	11/1993	Van Antwerp et al.
5,034,192 A	7/1991	Wrighton et al.	5,261,401 A	11/1993	Baker et al.
5,035,860 A	7/1991	Kleingeld et al.	5,262,035 A	11/1993	Gregg et al.
5,036,860 A	8/1991	Leigh et al.	5,262,305 A	11/1993	Heller et al.
5,036,861 A	8/1991	Sembrowich et al.	5,264,103 A	11/1993	Yoshioka et al.
5,037,527 A	8/1991	Hayashi et al.	5,264,104 A	11/1993	Gregg et al.
5,049,487 A	9/1991	Phillips et al.	5,264,105 A	11/1993	Gregg et al.
5,050,612 A	9/1991	Matsumura	5,264,106 A	11/1993	McAleer et al.
5,055,171 A	10/1991	Peck	5,265,888 A	11/1993	Yamamoto et al.
5,058,592 A	10/1991	Whisler	5,266,179 A	11/1993	Nankai et al.
5,063,081 A	11/1991	Cozzette et al.	5,269,212 A	12/1993	Peters et al.
5,068,536 A	11/1991	Rosenthal	5,271,815 A	12/1993	Wong
5,070,535 A	12/1991	Hochmair et al.	5,272,060 A	12/1993	Hamamoto et al.
5,073,500 A	12/1991	Saito et al.	5,275,159 A	1/1994	Griebel
5,077,476 A	12/1991	Rosenthal	5,278,079 A	1/1994	Gubinski et al.
5,078,854 A	1/1992	Burgess et al.	5,279,294 A	1/1994	Anderson et al.
5,082,550 A	1/1992	Rishpon et al.	5,282,950 A	2/1994	Dietze et al.
5,082,786 A	1/1992	Nakamoto	5,284,156 A	2/1994	Schramm et al.
5,084,828 A	1/1992	Kaufman et al.	5,285,792 A	2/1994	Sjoquist et al.
5,089,112 A	2/1992	Skotheim et al.	5,286,362 A	2/1994	Hoenes et al.
5,094,951 A	3/1992	Rosenberg	5,286,364 A	2/1994	Yacynych et al.
5,095,904 A	3/1992	Seligman et al.	5,288,636 A	2/1994	Pollmann et al.
5,096,560 A	3/1992	Takai et al.	5,291,887 A	3/1994	Stanley et al.
5,096,836 A	3/1992	Macho et al.	5,293,546 A	3/1994	Tadros et al.
5,097,834 A	3/1992	Skrabal	5,293,877 A	3/1994	O'Hara et al.
5,101,814 A	4/1992	Palti	5,299,571 A	4/1994	Mastrototaro
5,106,365 A	4/1992	Hernandez	5,304,468 A	4/1994	Phillips et al.
5,108,564 A	4/1992	Szuminsky et al.	5,307,263 A	4/1994	Brown
5,109,850 A	5/1992	Blanco et al.	5,309,919 A	5/1994	Snell et al.
5,111,539 A	5/1992	Hiruta et al.	5,310,885 A	5/1994	Maier et al.
5,111,818 A	5/1992	Suzuki et al.	5,320,098 A	6/1994	Davidson
5,114,678 A	5/1992	Crawford et al.	5,320,725 A	6/1994	Gregg et al.
5,120,420 A	6/1992	Nankai et al.	5,322,063 A	6/1994	Allen et al.

5,324,303 A	6/1994	Strong et al.	5,509,410 A	4/1996	Hill et al.
5,324,316 A	6/1994	Schulman et al.	5,514,103 A	5/1996	Srisathapat et al.
5,326,449 A	7/1994	Cunningham	5,514,253 A	5/1996	Davis et al.
5,333,615 A	8/1994	Craelius et al.	5,514,718 A	5/1996	Lewis et al.
5,337,258 A	8/1994	Dennis	5,518,006 A	5/1996	Mawhirt et al.
5,337,747 A	8/1994	Neftei	5,520,787 A	5/1996	Hanagan et al.
5,340,722 A	8/1994	Wolfbeis et al.	5,522,865 A	6/1996	Schulman et al.
5,342,408 A	8/1994	deCoriolis et al.	5,525,511 A	6/1996	D'Costa
5,342,789 A	8/1994	Chick et al.	5,526,120 A	6/1996	Jina et al.
5,352,348 A	10/1994	Young et al.	5,527,307 A	6/1996	Srisathapat et al.
5,356,348 A	10/1994	Bellio et al.	5,529,676 A	6/1996	Maley et al.
5,356,786 A	10/1994	Heller et al.	5,531,878 A	7/1996	Vadgama et al.
5,358,135 A	10/1994	Robbins et al.	5,538,511 A	7/1996	Van Antwerp et al.
5,358,514 A	10/1994	Schulman et al.	5,545,152 A	8/1996	Funderburk et al.
5,360,404 A	11/1994	Novacek et al.	5,545,191 A	8/1996	Mann et al.
5,364,797 A	11/1994	Olson et al.	5,549,113 A	8/1996	Halleck et al.
5,366,609 A	11/1994	White et al.	5,549,115 A	8/1996	Morgan et al.
5,368,028 A	11/1994	Palti	5,552,027 A	9/1996	Birkle et al.
5,370,622 A	12/1994	Livingston et al.	5,554,166 A	9/1996	Lange et al.
5,371,687 A	12/1994	Holmes, II et al.	5,556,524 A	9/1996	Albers
5,371,734 A	12/1994	Fischer	5,560,357 A	10/1996	Faupei et al.
5,372,133 A	12/1994	Hogen Esch	5,562,713 A	10/1996	Silvian
5,372,427 A	12/1994	Padovani et al.	5,565,085 A	10/1996	Ikeda et al.
5,376,070 A	12/1994	Purvis et al.	5,567,302 A	10/1996	Song et al.
5,376,251 A	12/1994	Kaneko et al.	5,568,806 A	10/1996	Cheney, II et al.
5,377,258 A	12/1994	Bro	5,569,186 A	10/1996	Lord et al.
5,378,628 A	1/1995	Gratzel et al.	5,569,212 A	10/1996	Brown
5,379,238 A	1/1995	Stark	5,573,647 A	11/1996	Maley et al.
5,379,764 A	1/1995	Barnes et al.	5,575,895 A	11/1996	Ikeda et al.
5,380,422 A	1/1995	Negishis et al.	5,580,527 A	12/1996	Bell et al.
5,382,346 A	1/1995	Uenoyama et al.	5,580,794 A	12/1996	Allen
5,387,327 A	2/1995	Khan	5,582,184 A	12/1996	Erickson et al.
5,390,671 A	2/1995	Lord et al.	5,582,697 A	12/1996	Ikeda et al.
5,391,250 A	2/1995	Cheney, II et al.	5,582,698 A	12/1996	Flaherty et al.
5,393,903 A	2/1995	Gratzel et al.	5,584,813 A	12/1996	Livingston et al.
5,395,504 A	3/1995	Saurer et al.	5,586,553 A	12/1996	Halili et al.
5,399,823 A	3/1995	McCusker	5,589,326 A	12/1996	Deng et al.
5,400,782 A	3/1995	Beaubiah	5,593,852 A	1/1997	Heller et al.
5,408,999 A	4/1995	Singh et al.	5,594,906 A	1/1997	Holmes, II et al.
5,410,326 A	4/1995	Goldstein	5,596,150 A	1/1997	Arndy et al.
5,410,471 A	4/1995	Alyfuku et al.	5,596,994 A	1/1997	Bro
5,410,474 A	4/1995	Fox	5,601,435 A	2/1997	Quy
5,411,647 A	5/1995	Johnson et al.	5,601,694 A	2/1997	Maley et al.
5,413,690 A	5/1995	Kost et al.	5,605,152 A	2/1997	Slate et al.
5,422,246 A	6/1995	Koopal et al.	5,609,575 A	3/1997	Larson et al.
5,425,868 A	6/1995	Pedersen	5,611,900 A	3/1997	Worden et al.
5,431,160 A	7/1995	Wilkins	5,615,135 A	3/1997	Waclawsky et al.
5,431,691 A	7/1995	Snell et al.	5,615,671 A	4/1997	Schoonen et al.
5,431,921 A	7/1995	Thombre	5,616,222 A	4/1997	Maley et al.
5,433,710 A	7/1995	Van Antwerp et al.	5,617,851 A	4/1997	Lipkovker
5,437,973 A	8/1995	Vadgama et al.	5,623,925 A	4/1997	Swenson et al.
5,437,999 A	8/1995	Diebold et al.	5,623,933 A	4/1997	Amano et al.
5,438,271 A	8/1995	White et al.	5,628,309 A	5/1997	Brown
5,445,611 A	8/1995	Eppstein et al.	5,628,310 A	5/1997	Rao et al.
5,445,920 A	8/1995	Saito	5,628,890 A	5/1997	Carter et al.
5,456,692 A	10/1995	Smith, Jr. et al.	5,629,981 A	5/1997	Nerlikar
5,456,940 A	10/1995	Funderburk	5,637,095 A	6/1997	Nason et al.
5,458,140 A	10/1995	Eppstein et al.	5,640,764 A	6/1997	Strojniak
5,460,618 A	10/1995	Harreld	5,640,954 A	6/1997	Pfeiffer et al.
5,462,525 A	10/1995	Srisathapat et al.	5,643,212 A	7/1997	Coutre et al.
5,462,645 A	10/1995	Albery et al.	5,647,853 A	7/1997	Feldmann et al.
5,466,218 A	11/1995	Srisathapat et al.	5,650,062 A	7/1997	Ikeda et al.
5,467,778 A	* 11/1995	Catt et al. 600/551	5,651,767 A	7/1997	Schulman et al.
5,469,846 A	11/1995	Khan	5,651,869 A	7/1997	Yoshioka et al.
5,472,317 A	12/1995	Field et al.	5,653,239 A	8/1997	Pompei et al.
5,476,460 A	12/1995	Montalvo	5,660,163 A	8/1997	Schulman et al.
5,477,855 A	12/1995	Schindler et al.	5,665,065 A	9/1997	Colman et al.
5,482,473 A	1/1996	Lord et al.	5,665,222 A	9/1997	Heller et al.
5,484,404 A	1/1996	Schulman et al.	5,667,983 A	9/1997	Abel et al.
5,487,751 A	1/1996	Radons et al.	5,670,031 A	9/1997	Hintsche et al.
5,491,474 A	2/1996	Suni et al.	5,678,571 A	10/1997	Brown
5,494,562 A	2/1996	Maley et al.	5,679,690 A	10/1997	Andre et al.
5,496,453 A	3/1996	Uenoyama et al.	5,680,858 A	10/1997	Hansen et al.
5,497,772 A	3/1996	Schulman et al.	5,682,233 A	10/1997	Brinda
5,501,956 A	3/1996	Wada et al.	5,686,717 A	11/1997	Knowles et al.
5,505,709 A	4/1996	Funderburk	5,695,623 A	12/1997	Michel et al.
5,505,713 A	4/1996	Van Antwerp et al.	5,695,949 A	12/1997	Galen et al.
5,507,288 A	4/1996	Bocker et al.	5,701,894 A	12/1997	Cherry et al.
5,508,171 A	4/1996	Walling et al.	5,704,922 A	1/1998	Brown

US 8,149,117 B2

Page 5

5,707,502 A	1/1998	McCaffrey et al.	5,899,855 A	5/1999	Brown
5,708,247 A	1/1998	McAleer et al.	5,913,310 A	6/1999	Brown
5,710,630 A	1/1998	Essenpreis et al.	5,917,346 A	6/1999	Gord
5,711,001 A	1/1998	Bussan et al.	5,918,603 A	7/1999	Brown
5,711,297 A	1/1998	Iliff et al.	5,925,021 A	7/1999	Castellano et al.
5,711,861 A	1/1998	Ward et al.	5,931,791 A	8/1999	Saltzstein et al.
5,711,862 A	1/1998	Sakoda et al.	5,933,136 A	8/1999	Brown
5,711,868 A	1/1998	Maley et al.	5,935,224 A	8/1999	Svancarek et al.
5,718,234 A	2/1998	Warden et al.	5,939,609 A *	8/1999	Knapp et al. 73/1.01
5,720,733 A	2/1998	Brown	5,940,801 A	8/1999	Brown
5,720,862 A	2/1998	Hamamoto et al.	5,942,979 A	8/1999	Luppino
5,721,783 A	2/1998	Anderson	5,945,345 A	8/1999	Blatt et al.
5,722,397 A	3/1998	Eppstein	5,947,921 A	9/1999	Johnson et al.
5,727,548 A	3/1998	Hill et al.	5,948,512 A	9/1999	Kubota et al.
5,730,124 A	3/1998	Yamauchi	5,950,632 A	9/1999	Reber et al.
5,730,654 A	3/1998	Brown	5,951,300 A	9/1999	Brown
5,735,273 A	4/1998	Kurnik et al.	5,951,492 A	9/1999	Douglas et al.
5,735,285 A	4/1998	Albert et al.	5,951,521 A	9/1999	Mastrototaro et al.
5,741,211 A	4/1998	Renirie et al.	5,951,836 A	9/1999	McAleer et al.
5,741,688 A	4/1998	Oxenboll et al.	5,954,643 A	9/1999	Van Antwerp
5,746,217 A	5/1998	Erickson et al.	5,954,685 A	9/1999	Tierney
5,750,926 A	5/1998	Schulman et al.	5,954,700 A	9/1999	Kovelman
5,770,028 A	6/1998	Maley et al.	5,956,501 A	9/1999	Brown
5,771,001 A	6/1998	Cobb	5,957,854 A	9/1999	Besson et al.
5,771,890 A	6/1998	Tamada	5,957,890 A	9/1999	Mann et al.
5,772,586 A	6/1998	Heinonen et al.	5,957,958 A	9/1999	Schulman et al.
5,777,060 A	7/1998	Van Antwerp	5,960,403 A	9/1999	Brown
5,779,665 A	7/1998	Mastrototaro et al.	5,961,451 A	10/1999	Reber et al.
5,781,024 A	7/1998	Blomberg et al.	5,964,993 A	10/1999	Blubaugh, Jr. et al.
5,782,814 A	7/1998	Brown et al.	5,965,380 A	10/1999	Heller et al.
5,785,681 A	7/1998	Indravudh	5,968,839 A	10/1999	Blatt et al.
5,786,439 A	7/1998	Van Antwerp et al.	5,971,922 A	10/1999	Arita et al.
5,786,584 A	7/1998	Button et al.	5,971,941 A	10/1999	Simons et al.
5,788,678 A	8/1998	Van Antwerp	5,974,124 A	10/1999	Schlueter, Jr. et al.
5,791,344 A	8/1998	Schulman et al.	5,977,476 A	11/1999	Guha et al.
5,792,117 A	8/1998	Brown	5,981,294 A	11/1999	Blatt et al.
5,793,292 A	8/1998	Ivey	5,989,409 A	11/1999	Kurnik et al.
5,800,420 A	9/1998	Gross et al.	5,994,476 A	11/1999	Shin et al.
5,804,048 A	9/1998	Wong et al.	5,995,860 A	11/1999	Sun et al.
5,807,315 A	9/1998	Van Antwerp et al.	5,997,476 A	12/1999	Brown
5,807,375 A	9/1998	Gross et al.	5,999,848 A	12/1999	Gord et al.
5,814,599 A	9/1998	Mitragotri et al.	5,999,849 A	12/1999	Gord et al.
5,820,551 A	10/1998	Hill et al.	6,001,067 A	12/1999	Shults et al.
5,820,570 A	10/1998	Erickson et al.	6,002,954 A	12/1999	Van Antwerp et al.
5,820,622 A	10/1998	Gross et al.	6,002,961 A	12/1999	Mitragotri et al.
5,822,715 A	10/1998	Worthington et al.	6,004,441 A	12/1999	Fujiwara et al.
5,825,488 A	10/1998	Kohl et al.	6,011,984 A	1/2000	Van Antwerp et al.
5,827,179 A	10/1998	Lichter et al.	6,014,577 A	1/2000	Henning et al.
5,827,183 A	10/1998	Kurnik et al.	6,018,678 A	1/2000	Mitragotri et al.
5,827,184 A	10/1998	Netherly et al.	6,023,629 A	2/2000	Tamada
5,828,943 A	10/1998	Brown	6,024,699 A	2/2000	Surwit et al.
5,830,064 A	11/1998	Bradish et al.	6,026,320 A	2/2000	Carlson et al.
5,830,341 A	11/1998	Gilmartin	6,027,459 A	2/2000	Shain et al.
5,832,448 A	11/1998	Brown	6,027,692 A	2/2000	Galen et al.
5,834,224 A	11/1998	Ruger et al.	6,032,059 A	2/2000	Henning et al.
5,837,454 A	11/1998	Cozzette et al.	6,032,199 A	2/2000	Lim et al.
5,837,546 A	11/1998	Allen et al.	6,033,866 A	3/2000	Guo et al.
5,840,020 A	11/1998	Heinonen et al.	6,035,237 A	3/2000	Schulman et al.
5,842,983 A	12/1998	Abel et al.	6,040,194 A	3/2000	Chick et al.
5,843,140 A	12/1998	Strojniak	6,041,253 A	3/2000	Kost et al.
5,846,702 A	12/1998	Deng et al.	6,043,437 A	3/2000	Schulman et al.
5,846,744 A	12/1998	Athey et al.	6,049,727 A	4/2000	Crothall
5,851,197 A	12/1998	Marano et al.	6,052,565 A	4/2000	Ishikura et al.
5,854,078 A	12/1998	Asher et al.	6,056,718 A	5/2000	Funderburk et al.
5,854,189 A	12/1998	Kruse et al.	6,063,459 A	5/2000	Velte
5,856,758 A	1/1999	Joffe et al.	6,066,243 A	5/2000	Anderson et al.
5,857,967 A	1/1999	Frid et al.	6,067,474 A	5/2000	Schulman et al.
5,857,983 A	1/1999	Douglas et al.	6,068,615 A	5/2000	Brown et al.
5,860,917 A	1/1999	Comanor et al.	6,071,249 A	6/2000	Cunningham et al.
5,872,713 A	2/1999	Douglas et al.	6,071,251 A	6/2000	Cunningham et al.
5,876,484 A	3/1999	Raskin et al.	6,071,294 A	6/2000	Simons et al.
5,879,163 A	3/1999	Brown et al.	6,071,391 A	6/2000	Gotoh et al.
5,879,311 A	3/1999	Duchon et al.	6,073,031 A	6/2000	Helstab et al.
5,880,829 A	3/1999	Kauhaniemi et al.	6,081,736 A	6/2000	Colvin et al.
5,882,494 A	3/1999	Van Antwerp	6,083,710 A	7/2000	Heller et al.
5,885,211 A	3/1999	Eppstein et al.	6,088,608 A	7/2000	Schulman et al.
5,887,133 A	3/1999	Brown et al.	6,091,975 A	7/2000	Daddona et al.
5,897,493 A	4/1999	Brown	6,091,976 A	7/2000	Pfeiffer et al.
5,898,025 A	4/1999	Burg et al.	6,093,156 A	7/2000	Cunningham et al.

US 8,149,117 B2

Page 6

6,093,167	A	7/2000	Houben et al.	6,266,645	B1	7/2001	Simpson
6,093,172	A	7/2000	Funderburk et al.	6,267,724	B1	7/2001	Taylor
6,097,480	A	8/2000	Kaplan	6,268,161	B1	7/2001	Han et al.
6,097,831	A	8/2000	Wieck et al.	6,270,445	B1	8/2001	Dean, Jr. et al.
6,099,484	A	8/2000	Douglas et al.	6,272,364	B1	8/2001	Kurnik
6,101,478	A	8/2000	Brown	6,275,717	B1	8/2001	Gross et al.
6,103,033	A	8/2000	Say et al.	6,280,416	B1	8/2001	Van Antwerp et al.
6,106,780	A	8/2000	Douglas et al.	6,280,587	B1	8/2001	Matsumoto
6,110,148	A	8/2000	Brown et al.	6,281,006	B1	8/2001	Heller et al.
6,110,152	A	8/2000	Kovelman	6,283,943	B1	9/2001	Dy et al.
6,113,578	A	9/2000	Brown	6,284,126	B1	9/2001	Kurnik et al.
6,117,290	A	9/2000	Say et al.	6,284,478	B1	9/2001	Heller et al.
6,119,028	A	9/2000	Schulman et al.	6,293,925	B1	9/2001	Safabash et al.
6,120,676	A	9/2000	Heller et al.	6,294,281	B1	9/2001	Heller
6,121,009	A	9/2000	Heller et al.	6,295,463	B1	9/2001	Stenzler
6,121,611	A	9/2000	Lindsay et al.	6,295,506	B1	9/2001	Heinonen et al.
6,122,351	A	9/2000	Schlueter, Jr. et al.	6,298,254	B2	10/2001	Tamada
6,125,978	A	10/2000	Ando et al.	6,299,578	B1	10/2001	Kurnik et al.
6,134,461	A	10/2000	Say et al.	6,299,757	B1	10/2001	Feldman et al.
6,134,504	A	10/2000	Douglas et al.	6,301,499	B1	10/2001	Carlson et al.
6,139,718	A	10/2000	Kurnik et al.	6,304,766	B1	10/2001	Colvin, Jr. et al.
6,141,573	A	10/2000	Kurnik et al.	6,306,104	B1	10/2001	Cunningham et al.
6,142,939	A	11/2000	Eppstein et al.	6,307,867	B1	10/2001	Roobol et al.
6,143,164	A	11/2000	Heller et al.	6,309,351	B1	10/2001	Kurnik et al.
6,144,837	A	11/2000	Quy	6,309,884	B1	10/2001	Cooper et al.
6,144,869	A	11/2000	Berner et al.	6,313,749	B1	11/2001	Horne et al.
6,144,922	A	11/2000	Douglas et al.	6,315,721	B2	11/2001	Schulman et al.
6,148,094	A	11/2000	Kinsella	6,319,540	B1	11/2001	Van Antwerp et al.
6,150,128	A	11/2000	Uretsky	6,326,160	B1	12/2001	Dunn et al.
6,151,586	A	11/2000	Brown	6,329,161	B1	12/2001	Heller et al.
6,153,062	A	11/2000	Saito et al.	6,329,929	B1	12/2001	Weijand et al.
6,153,069	A	11/2000	Pottgen et al.	6,330,426	B2	12/2001	Brown et al.
6,159,147	A	12/2000	Lichter et al.	6,330,464	B1	12/2001	Colvin, Jr. et al.
6,161,095	A	12/2000	Brown	6,331,518	B2	12/2001	Hemm et al.
6,162,611	A	12/2000	Heller et al.	6,334,778	B1	1/2002	Brown
6,162,639	A	12/2000	Douglas	6,336,900	B1	1/2002	Alleckson et al.
6,164,284	A	12/2000	Schulman et al.	6,338,790	B1	1/2002	Feldman et al.
6,167,362	A	12/2000	Brown et al.	6,340,421	B1	1/2002	Vachon et al.
6,168,563	B1	1/2001	Brown	6,341,232	B1	1/2002	Conn et al.
6,170,318	B1	1/2001	Lewis	6,356,776	B1	3/2002	Berner et al.
6,175,752	B1	1/2001	Say et al.	6,360,888	B1	3/2002	Mclvor et al.
6,180,416	B1	1/2001	Kurnik et al.	6,366,793	B1	4/2002	Bell et al.
6,186,145	B1	2/2001	Brown	6,366,794	B1	4/2002	Moussy et al.
6,192,891	B1	2/2001	Gravel et al.	6,368,141	B1	4/2002	Van Antwerp et al.
6,193,873	B1	2/2001	Ohara et al.	6,368,274	B1	4/2002	Van Antwerp et al.
6,196,970	B1	3/2001	Brown	6,370,410	B2	4/2002	Kurnik et al.
6,198,957	B1	3/2001	Green	6,377,828	B1	4/2002	Chaiken et al.
6,200,265	B1	3/2001	Walsh et al.	6,379,301	B1	4/2002	Worthington et al.
6,201,979	B1	3/2001	Kurnik et al.	6,383,767	B1	5/2002	Polak
6,201,980	B1	3/2001	Darrow et al.	6,387,048	B1	5/2002	Schulman et al.
6,203,495	B1	3/2001	Bardy et al.	6,391,643	B1	5/2002	Chen et al.
6,206,841	B1	3/2001	Cunningham et al.	6,393,318	B1	5/2002	Conn et al.
6,207,400	B1	3/2001	Kwon	6,398,562	B1	6/2002	Butler et al.
6,208,894	B1	3/2001	Schulman et al.	6,405,066	B1	6/2002	Essenpreis et al.
6,210,272	B1	4/2001	Brown	6,413,393	B1	7/2002	Van Antwerp et al.
6,210,976	B1	4/2001	Sabbadini	6,416,471	B1	7/2002	Kumar et al.
6,212,416	B1	4/2001	Ward et al.	6,418,332	B1	7/2002	Mastrototaro et al.
6,219,565	B1	4/2001	Cupp et al.	6,424,847	B1	7/2002	Mastrototaro et al.
6,219,574	B1	4/2001	Cormier et al.	6,427,088	B1	7/2002	Bowman, IV et al.
6,224,745	B1	5/2001	Baltruschat	6,434,409	B1	8/2002	Pfeiffer et al.
6,232,130	B1	5/2001	Wolf	6,438,414	B1	8/2002	Conn et al.
6,232,370	B1	5/2001	Kubota et al.	6,440,068	B1	8/2002	Brown et al.
6,233,471	B1	5/2001	Berner et al.	6,442,637	B1	8/2002	Hawkins et al.
6,233,539	B1	5/2001	Brown	6,443,942	B2	9/2002	Van Antwerp et al.
6,239,925	B1	5/2001	Ardrey et al.	6,449,255	B1	9/2002	Waclawsky et al.
6,241,862	B1	6/2001	McAleer et al.	6,454,710	B1	9/2002	Ballerstadt et al.
6,246,330	B1	6/2001	Nielsen	6,462,162	B2	10/2002	Van Antwerp et al.
6,246,992	B1	6/2001	Brown	6,464,848	B1	10/2002	Matsumoto
6,248,065	B1	6/2001	Brown	6,466,810	B1	10/2002	Ward et al.
6,248,067	B1	6/2001	Causey, III et al.	6,468,222	B1	10/2002	Mault et al.
6,248,093	B1	6/2001	Moberg	6,472,122	B1	10/2002	Schulman et al.
6,251,260	B1	6/2001	Heller et al.	6,475,750	B1	11/2002	Han et al.
6,252,032	B1	6/2001	Van Antwerp et al.	6,477,395	B2	11/2002	Schulman et al.
6,253,804	B1	7/2001	Safabash	6,478,736	B1	11/2002	Mault
6,254,586	B1	7/2001	Mann et al.	6,480,730	B2	11/2002	Darrow et al.
6,256,643	B1	7/2001	Cork et al.	6,482,156	B2	11/2002	Iliff
6,259,587	B1	7/2001	Sheldon et al.	6,482,158	B2	11/2002	Mault
6,259,937	B1	7/2001	Schulman et al.	6,482,604	B2	11/2002	Kwon
6,260,022	B1	7/2001	Brown	6,484,045	B1	11/2002	Holker et al.

US 8,149,117 B2

Page 7

6,484,046	B1	11/2002	Say et al.	6,683,040	B2	1/2004	Bragulla et al.
6,485,138	B1	11/2002	Kubota et al.	6,687,522	B2	2/2004	Tamada
6,494,830	B1	12/2002	Wessel	6,687,546	B2	2/2004	Lebel et al.
6,496,728	B2	12/2002	Li et al.	6,689,056	B1	2/2004	Kilcoyne et al.
6,505,059	B1	1/2003	Kollias et al.	6,690,276	B1	2/2004	Marino
6,505,121	B1	1/2003	Russell	6,693,069	B2	2/2004	Korber et al.
6,512,939	B1	1/2003	Colvin et al.	6,694,158	B2	2/2004	Polak
6,513,532	B2	2/2003	Mault et al.	6,694,191	B2	2/2004	Starkweather et al.
6,514,718	B2	2/2003	Heller et al.	6,695,860	B1	2/2004	Ward et al.
6,515,593	B1	2/2003	Stark et al.	6,698,269	B2	3/2004	Baber et al.
6,520,326	B2	2/2003	McIvor et al.	6,701,270	B1	3/2004	Miller et al.
6,529,755	B2	3/2003	Kurnik et al.	6,702,857	B2	3/2004	Brauker et al.
6,529,772	B2	3/2003	Carlson et al.	6,704,587	B1	3/2004	Kumar et al.
6,530,915	B1	3/2003	Eppstein et al.	6,708,057	B2	3/2004	Morganroth
6,534,322	B1	3/2003	Sabbadini	6,711,423	B2	3/2004	Colvin, Jr.
6,534,323	B1	3/2003	Sabbadini	6,723,046	B2	4/2004	Lichtenstein et al.
6,535,753	B1	3/2003	Raskas	6,728,560	B2	4/2004	Kollias et al.
6,537,243	B1	3/2003	Henning et al.	6,731,976	B2	5/2004	Penn et al.
6,540,675	B2	4/2003	Aceti et al.	6,733,446	B2	5/2004	Lebel et al.
6,541,266	B2	4/2003	Modzelewski et al.	6,734,162	B2	5/2004	Van Antwerp et al.
6,544,212	B2	4/2003	Galley et al.	6,736,777	B2	5/2004	Kim et al.
6,546,269	B1	4/2003	Kurnik	6,736,797	B1	5/2004	Larsen et al.
6,549,796	B2	4/2003	Sohrab	6,737,401	B2	5/2004	Kim et al.
6,551,276	B1	4/2003	Mann et al.	6,738,654	B2	5/2004	Sohrab
6,551,494	B1	4/2003	Heller et al.	6,740,075	B2	5/2004	Lebel et al.
6,553,244	B2	4/2003	Lesho et al.	6,741,163	B1	5/2004	Roberts
6,554,798	B1	4/2003	Mann et al.	6,741,876	B1	5/2004	Seccina et al.
6,558,320	B1	5/2003	Causey, III et al.	6,741,877	B1	5/2004	Shults et al.
6,558,321	B1	5/2003	Burd et al.	6,746,582	B2	6/2004	Heller et al.
6,558,351	B1	5/2003	Steil et al.	6,748,445	B1	6/2004	Darcy et al.
6,560,471	B1	5/2003	Heller et al.	6,749,587	B2	6/2004	Flaherty
6,561,978	B1	5/2003	Conn et al.	6,750,311	B1	6/2004	Van Antwerp et al.
6,562,001	B2	5/2003	Lebel et al.	6,758,810	B2	7/2004	Lebel et al.
6,564,105	B2	5/2003	Starkweather et al.	6,766,183	B2	7/2004	Walsh et al.
6,564,807	B1	5/2003	Schulman et al.	6,766,201	B2	7/2004	Von Arx et al.
6,565,509	B1	5/2003	Say et al.	6,768,425	B2	7/2004	Flaherty et al.
6,571,128	B2	5/2003	Lebel et al.	6,770,030	B1	8/2004	Schaupp et al.
6,571,200	B1	5/2003	Mault	6,770,729	B2	8/2004	Van Antwerp et al.
6,576,101	B1	6/2003	Heller et al.	6,771,995	B2	8/2004	Kurnik et al.
6,576,117	B1	6/2003	Iketaki et al.	6,773,563	B2	8/2004	Matsumoto
6,577,899	B2	6/2003	Lebel et al.	6,780,156	B2	8/2004	Haueter et al.
6,579,498	B1	6/2003	Eglise	6,780,297	B2	8/2004	Matsumoto et al.
6,579,690	B1	6/2003	Bonnecaze et al.	6,780,871	B2	8/2004	Glick et al.
6,584,335	B1	6/2003	Haar et al.	6,784,274	B2	8/2004	Van Antwerp et al.
6,585,644	B2	7/2003	Lebel et al.	6,790,178	B1	9/2004	Mault et al.
6,587,705	B1	7/2003	Kim et al.	6,794,195	B2	9/2004	Colvin, Jr.
6,591,125	B1	7/2003	Buse et al.	6,800,451	B2	10/2004	Daniloff et al.
6,591,126	B2	7/2003	Roeper et al.	6,804,544	B2	10/2004	Van Antwerp et al.
6,594,514	B2	7/2003	Berner et al.	6,809,507	B2	10/2004	Morgan et al.
6,595,919	B2	7/2003	Berner et al.	6,809,653	B1	10/2004	Mann et al.
6,595,929	B2	7/2003	Stivoric et al.	6,810,290	B2	10/2004	Lebel et al.
6,602,678	B2	8/2003	Kwon et al.	6,810,309	B2	10/2004	Sadler et al.
6,602,909	B1	8/2003	Jarowski	6,811,533	B2	11/2004	Lebel et al.
6,605,200	B1	8/2003	Mao et al.	6,811,534	B2	11/2004	Bowman, IV et al.
6,605,201	B1	8/2003	Mao et al.	6,811,659	B2	11/2004	Vachon
6,607,509	B2	8/2003	Bobroff et al.	6,812,031	B1	11/2004	Carlsson
6,608,562	B1	8/2003	Kimura et al.	6,813,519	B2	11/2004	Lebel et al.
6,610,012	B2	8/2003	Mault	6,816,742	B2	11/2004	Kim et al.
6,612,306	B1	9/2003	Mault	6,835,553	B2	12/2004	Han et al.
6,615,078	B1	9/2003	Burson et al.	RE38,681	E	1/2005	Kurnik et al.
6,616,613	B1	9/2003	Goodman	6,840,912	B2	1/2005	Kloepfer et al.
6,618,603	B2	9/2003	Varalli et al.	6,844,023	B2	1/2005	Schulman et al.
6,620,106	B2	9/2003	Mault	6,849,237	B2	2/2005	Housefield et al.
6,627,058	B1	9/2003	Chan	6,850,790	B2	2/2005	Berner et al.
6,629,934	B2	10/2003	Mault et al.	6,852,104	B2	2/2005	Blomquist
6,633,772	B2	10/2003	Ford et al.	6,852,500	B1	2/2005	Hoss et al.
6,635,014	B2	10/2003	Starkweather et al.	6,852,694	B2	2/2005	Van Antwerp et al.
6,641,533	B2	11/2003	Causey, III et al.	6,853,854	B1	2/2005	Proniewicz et al.
6,642,015	B2	11/2003	Vachon et al.	6,856,928	B2	2/2005	Harmon
6,645,142	B2	11/2003	Braig et al.	6,858,403	B2	2/2005	Han et al.
6,645,368	B1	11/2003	Beaty et al.	6,862,465	B2	3/2005	Shults et al.
6,648,821	B2	11/2003	Lebel et al.	6,862,466	B2	3/2005	Ackerman
6,653,091	B1	11/2003	Dunn et al.	6,872,200	B2	3/2005	Mann et al.
6,654,625	B1	11/2003	Say et al.	6,873,268	B2	3/2005	Lebel et al.
6,659,948	B2	12/2003	Lebel et al.	6,881,551	B2	4/2005	Heller et al.
6,668,196	B1	12/2003	Villegas et al.	6,882,940	B2	4/2005	Potts et al.
6,671,554	B2	12/2003	Gibson et al.	6,885,883	B2	4/2005	Parris et al.
6,673,625	B2	1/2004	Satcher, Jr. et al.	6,892,085	B2	5/2005	McIvor et al.
6,682,938	B1	1/2004	Satcher, Jr. et al.	6,895,263	B2	5/2005	Shin et al.

US 8,149,117 B2

Page 8

6,895,265	B2	5/2005	Silver	7,183,068	B2	2/2007	Burson et al.
6,899,683	B2	5/2005	Mault et al.	7,183,102	B2	2/2007	Monfre et al.
6,899,684	B2	5/2005	Mault et al.	7,189,341	B2	3/2007	Li et al.
6,902,207	B2	6/2005	Lickliter	7,190,988	B2	3/2007	Say et al.
6,902,905	B2	6/2005	Burson et al.	7,192,450	B2	3/2007	Brauker et al.
6,904,301	B2	6/2005	Raskas	7,198,606	B2	4/2007	Boecker et al.
6,907,127	B1	6/2005	Kravitz et al.	7,221,977	B1	5/2007	Weaver et al.
6,915,147	B2	7/2005	Lebel et al.	7,226,442	B2	6/2007	Sheppard et al.
6,918,874	B1	7/2005	Hatch et al.	7,226,978	B2	6/2007	Tapsak et al.
6,922,578	B2	7/2005	Eppstein et al.	7,228,163	B2	6/2007	Ackerman
RE38,775	E	8/2005	Kurnik et al.	7,233,817	B2	6/2007	Yen
6,923,764	B2	8/2005	Aceti et al.	7,241,266	B2	7/2007	Zhou et al.
6,923,936	B2	8/2005	Swanson et al.	7,261,691	B1	8/2007	Asomani
6,927,246	B2	8/2005	Noronha et al.	7,267,665	B2	9/2007	Steil et al.
6,931,327	B2	8/2005	Goode, Jr. et al.	7,276,029	B2	10/2007	Goode, Jr. et al.
6,932,894	B2	8/2005	Mao et al.	7,278,983	B2	10/2007	Ireland et al.
6,936,006	B2	8/2005	Sabra	7,291,107	B2	11/2007	Hellwig et al.
6,936,029	B2	8/2005	Mann et al.	7,295,867	B2	11/2007	Berner et al.
6,940,590	B2	9/2005	Colvin, Jr. et al.	7,297,112	B2	11/2007	Zhou et al.
6,941,163	B2	9/2005	Ford et al.	7,299,082	B2	11/2007	Feldman et al.
6,950,708	B2	9/2005	Bowman, IV et al.	7,310,544	B2	12/2007	Brister et al.
6,952,603	B2	10/2005	Gerber et al.	7,324,012	B2	1/2008	Mann et al.
6,954,673	B2	10/2005	Von Arx et al.	7,335,294	B2	2/2008	Heller et al.
6,955,650	B2	10/2005	Mault et al.	7,354,420	B2	4/2008	Steil et al.
6,957,102	B2	10/2005	Silver et al.	7,364,592	B2	4/2008	Carr-Brendel et al.
6,957,107	B2	10/2005	Rogers et al.	7,366,556	B2	4/2008	Brister et al.
6,958,705	B2	10/2005	Lebel et al.	7,379,765	B2	5/2008	Petisce et al.
6,968,294	B2	11/2005	Gutta et al.	7,398,183	B2	7/2008	Holland et al.
6,968,375	B1	11/2005	Brown	7,402,153	B2	7/2008	Steil et al.
6,971,274	B2	12/2005	Olin	7,424,318	B2	9/2008	Brister et al.
6,974,437	B2	12/2005	Lebel et al.	7,460,898	B2	12/2008	Brister et al.
6,978,182	B2	12/2005	Mazar et al.	7,467,003	B2	12/2008	Brister et al.
6,979,326	B2	12/2005	Mann et al.	7,471,972	B2	12/2008	Rhodes et al.
6,985,870	B2	1/2006	Martucci et al.	7,494,465	B2	2/2009	Brister et al.
6,990,366	B2	1/2006	Say et al.	7,497,827	B2	3/2009	Brister et al.
6,991,096	B2	1/2006	Gottlieb et al.	7,519,408	B2	4/2009	Rasdal et al.
6,997,907	B2	2/2006	Safabash et al.	7,547,281	B2	6/2009	Hayes et al.
6,997,920	B2	2/2006	Mann et al.	7,569,030	B2	8/2009	Lebel et al.
6,998,247	B2	2/2006	Monfre et al.	7,583,990	B2	9/2009	Goode, Jr. et al.
6,999,810	B2	2/2006	Berner et al.	7,591,801	B2	9/2009	Brauker et al.
7,003,336	B2	2/2006	Holker et al.	7,599,726	B2	10/2009	Goode, Jr. et al.
7,003,340	B2	2/2006	Say et al.	7,613,491	B2	11/2009	Boock et al.
7,003,341	B2	2/2006	Say et al.	7,615,007	B2	11/2009	Shults et al.
7,004,901	B2	2/2006	Fish	7,618,369	B2	11/2009	Hayter et al.
7,005,857	B2	2/2006	Stiene et al.	7,632,228	B2	12/2009	Brauker et al.
7,011,630	B2	3/2006	Desai et al.	7,637,868	B2	12/2009	Saint et al.
7,018,366	B2	3/2006	Easter	7,640,048	B2	12/2009	Dobbles et al.
7,018,568	B2	3/2006	Tierney	7,651,596	B2	1/2010	Petisce et al.
7,022,072	B2	4/2006	Fox et al.	7,654,956	B2	2/2010	Brister et al.
7,024,236	B2	4/2006	Ford et al.	7,657,297	B2	2/2010	Simpson et al.
7,024,245	B2	4/2006	Lebel et al.	7,711,402	B2	5/2010	Shults et al.
7,025,743	B2	4/2006	Mann et al.	7,713,574	B2	5/2010	Brister et al.
7,029,444	B2	4/2006	Shin et al.	7,715,893	B2	5/2010	Kamath et al.
7,039,810	B1	5/2006	Nichols	7,768,387	B2	8/2010	Fennell et al.
7,041,068	B2	5/2006	Freeman et al.	7,813,809	B2	10/2010	Strother et al.
7,041,468	B2	5/2006	Drucker et al.	2001/0011224	A1	8/2001	Brown
7,049,277	B2	5/2006	Bragulla et al.	2001/0016310	A1	8/2001	Brown et al.
7,052,251	B2	5/2006	Nason et al.	2001/0016682	A1	8/2001	Berner et al.
7,052,472	B1	5/2006	Miller et al.	2001/0016683	A1	8/2001	Darrow et al.
7,052,483	B2	5/2006	Wojcik	2001/0020124	A1	9/2001	Tamada
7,056,302	B2	6/2006	Douglas	2001/0029340	A1	10/2001	Mault et al.
7,060,030	B2	6/2006	Von Arx et al.	2001/0032278	A1	10/2001	Brown et al.
7,074,307	B2	7/2006	Simpson et al.	2001/0037060	A1	11/2001	Thompson et al.
7,081,195	B2	7/2006	Simpson et al.	2001/0037069	A1	11/2001	Carlson et al.
7,089,780	B2	8/2006	Sunshine et al.	2001/0039504	A1	11/2001	Linberg et al.
7,098,803	B2	8/2006	Mann et al.	2001/0041830	A1	11/2001	Varalli et al.
7,108,778	B2	9/2006	Simpson et al.	2001/0041831	A1	11/2001	Starkweather et al.
7,110,803	B2	9/2006	Shults et al.	2001/0044581	A1	11/2001	Mault
7,113,821	B1	9/2006	Sun et al.	2001/0044588	A1	11/2001	Mault
7,114,502	B2	10/2006	Schulman et al.	2001/0047125	A1	11/2001	Quy
7,125,382	B2	10/2006	Zhou et al.	2001/0049096	A1	12/2001	Brown
7,133,710	B2	11/2006	Acosta et al.	2001/0049470	A1	12/2001	Mault et al.
7,134,999	B2	11/2006	Brauker et al.	2002/0002326	A1	1/2002	Causey, III et al.
7,136,689	B2	11/2006	Shults et al.	2002/0002328	A1	1/2002	Tamada
7,150,975	B2	12/2006	Tamada et al.	2002/0004640	A1	1/2002	Conn et al.
7,155,112	B2	12/2006	Uno et al.	2002/0010414	A1	1/2002	Coston et al.
7,155,290	B2	12/2006	Von Arx et al.	2002/0016530	A1	2/2002	Brown
7,163,511	B2	1/2007	Conn et al.	2002/0016719	A1	2/2002	Nemeth et al.
7,171,274	B2	1/2007	Starkweather et al.	2002/0019022	A1	2/2002	Dunn et al.

2002/0019586	A1	2/2002	Teller et al.	2003/0187338	A1	10/2003	Say et al.
2002/0019748	A1	2/2002	Brown	2003/0187525	A1	10/2003	Mann et al.
2002/0026937	A1	3/2002	Mault	2003/0191376	A1	10/2003	Samuels et al.
2002/0027164	A1	3/2002	Mault et al.	2003/0191431	A1	10/2003	Mann et al.
2002/0028995	A1	3/2002	Mault	2003/0195403	A1	10/2003	Berner et al.
2002/0040208	A1	4/2002	Flaherty et al.	2003/0195462	A1	10/2003	Mann et al.
2002/0042090	A1	4/2002	Heller et al.	2003/0199790	A1	10/2003	Boecker et al.
2002/0047867	A1	4/2002	Mault et al.	2003/0199791	A1	10/2003	Boecker et al.
2002/0053637	A1	5/2002	Conn et al.	2003/0199903	A1	10/2003	Boecker et al.
2002/0062069	A1	5/2002	Mault	2003/0203498	A1	10/2003	Neel et al.
2002/0063060	A1	5/2002	Gascoyne et al.	2003/0208110	A1	11/2003	Mault et al.
2002/0068858	A1	6/2002	Braig et al.	2003/0208113	A1	11/2003	Mault et al.
2002/0072784	A1	6/2002	Sheppard et al.	2003/0208133	A1	11/2003	Mault
2002/0072858	A1	6/2002	Cheng	2003/0208409	A1	11/2003	Mault
2002/0077765	A1	6/2002	Mault	2003/0212317	A1	11/2003	Kovatchev et al.
2002/0077766	A1	6/2002	Mault	2003/0212364	A1	11/2003	Mann et al.
2002/0081559	A1	6/2002	Brown et al.	2003/0212379	A1	11/2003	Bylund et al.
2002/0083461	A1	6/2002	Hutcheson et al.	2003/0216630	A1	11/2003	Jersey-Willuhn et al.
2002/0087056	A1	7/2002	Aceti et al.	2003/0217966	A1	11/2003	Tapsak et al.
2002/0091312	A1	7/2002	Berner et al.	2003/0226695	A1	12/2003	Mault
2002/0103425	A1	8/2002	Mault	2003/0229514	A2	12/2003	Brown
2002/0103499	A1	8/2002	Perez et al.	2003/0232370	A1	12/2003	Trifiro
2002/0106709	A1	8/2002	Potts et al.	2003/0235817	A1	12/2003	Bartkowiak et al.
2002/0107433	A1	8/2002	Mault	2004/0010207	A1	1/2004	Flaherty et al.
2002/0107476	A1	8/2002	Mann et al.	2004/0011671	A1	1/2004	Shults et al.
2002/0109600	A1	8/2002	Mault et al.	2004/0018486	A1	1/2004	Dunn et al.
2002/0119711	A1	8/2002	Van Antwerp et al.	2004/0030226	A1	2/2004	Quy
2002/0124017	A1	9/2002	Mault	2004/0039256	A1	2/2004	Kawatahara et al.
2002/0126036	A1	9/2002	Flaherty et al.	2004/0039298	A1	2/2004	Abreu
2002/0128594	A1	9/2002	Das et al.	2004/0040840	A1	3/2004	Mao et al.
2002/0130042	A1	9/2002	Moerman et al.	2004/0045879	A1	3/2004	Shults et al.
2002/0133378	A1	9/2002	Mault et al.	2004/0054263	A1	3/2004	Moerman et al.
2002/0147135	A1	10/2002	Schnell	2004/0059201	A1	3/2004	Ginsberg
2002/0161286	A1	10/2002	Gerber et al.	2004/0064068	A1	4/2004	DeNuzzio et al.
2002/0161288	A1	10/2002	Shin et al.	2004/0069164	A1	4/2004	Nakamura et al.
2002/0169394	A1	11/2002	Eppstein et al.	2004/0072357	A1	4/2004	Stiene et al.
2002/0169635	A1	11/2002	Shillingburg	2004/0073095	A1	4/2004	Causey, III et al.
2002/0177764	A1	11/2002	Sohrab	2004/0096959	A1	5/2004	Stiene et al.
2002/0193679	A1	12/2002	Malave et al.	2004/0106858	A1*	6/2004	Say et al. 600/345
2003/0004403	A1	1/2003	Drinan et al.	2004/0108226	A1	6/2004	Polychronakos et al.
2003/0023182	A1	1/2003	Mault et al.	2004/0122353	A1	6/2004	Shahmiran et al.
2003/0023317	A1	1/2003	Brauker et al.	2004/0122489	A1	6/2004	Mazar et al.
2003/0028089	A1	2/2003	Galley et al.	2004/0122530	A1	6/2004	Hansen et al.
2003/0028120	A1	2/2003	Mault et al.	2004/0133164	A1	7/2004	Funderburk et al.
2003/0032077	A1	2/2003	Itoh et al.	2004/0138588	A1	7/2004	Saikley et al.
2003/0032867	A1	2/2003	Crothall et al.	2004/0146909	A1	7/2004	Duong et al.
2003/0032868	A1	2/2003	Graskov et al.	2004/0152622	A1	8/2004	Keith et al.
2003/0032874	A1	2/2003	Rhodes et al.	2004/0152961	A1	8/2004	Carlson et al.
2003/0040683	A1	2/2003	Rule et al.	2004/0153585	A1	8/2004	Kawatahara et al.
2003/0042137	A1	3/2003	Mao et al.	2004/0162473	A1	8/2004	Sohrab
2003/0050537	A1	3/2003	Wessel	2004/0164961	A1	8/2004	Bal et al.
2003/0050546	A1	3/2003	Desai et al.	2004/0167383	A1	8/2004	Kim et al.
2003/0065257	A1	4/2003	Mault et al.	2004/0167464	A1	8/2004	Ireland et al.
2003/0065273	A1	4/2003	Mault et al.	2004/0167801	A1	8/2004	Say et al.
2003/0065274	A1	4/2003	Mault et al.	2004/0171921	A1	9/2004	Say et al.
2003/0065275	A1	4/2003	Mault et al.	2004/0172284	A1	9/2004	Sullivan et al.
2003/0065308	A1	4/2003	Lebel et al.	2004/0176672	A1	9/2004	Silver et al.
2003/0081370	A1	5/2003	Haskell et al.	2004/0176913	A1	9/2004	Kawatahara et al.
2003/0100040	A1	5/2003	Bonnecaze et al.	2004/0186362	A1	9/2004	Brauker et al.
2003/0100821	A1	5/2003	Heller et al.	2004/0186365	A1	9/2004	Jin et al.
2003/0105407	A1	6/2003	Pearce et al.	2004/0193025	A1	9/2004	Steil et al.
2003/0108976	A1	6/2003	Braig et al.	2004/0193090	A1	9/2004	Lebel et al.
2003/0122021	A1	7/2003	McConnell et al.	2004/0197846	A1	10/2004	Hockersmith et al.
2003/0125612	A1	7/2003	Fox et al.	2004/0199059	A1	10/2004	Brauker et al.
2003/0130616	A1	7/2003	Steil et al.	2004/0202576	A1	10/2004	Aceti et al.
2003/0134347	A1	7/2003	Heller et al.	2004/0204687	A1	10/2004	Mogensen et al.
2003/0135100	A1	7/2003	Kim et al.	2004/0208780	A1	10/2004	Faries, Jr. et al.
2003/0135333	A1	7/2003	Aceti et al.	2004/0221057	A1	11/2004	Darcy et al.
2003/0146841	A1	8/2003	Koenig	2004/0225338	A1	11/2004	Lebel et al.
2003/0153820	A1	8/2003	Berner et al.	2004/0235446	A1	11/2004	Flaherty et al.
2003/0153821	A1	8/2003	Berner et al.	2004/0236200	A1	11/2004	Say et al.
2003/0158472	A1	8/2003	Sohrab	2004/0248204	A1	12/2004	Moerman
2003/0158707	A1	8/2003	Doi	2004/0249250	A1	12/2004	McGee et al.
2003/0168338	A1	9/2003	Gao et al.	2004/0249253	A1	12/2004	Racchini et al.
2003/0175806	A1	9/2003	Rule et al.	2004/0249254	A1	12/2004	Racchini et al.
2003/0176183	A1	9/2003	Drucker et al.	2004/0249999	A1	12/2004	Connolly et al.
2003/0176933	A1	9/2003	Lebel et al.	2004/0253736	A1	12/2004	Stout et al.
2003/0181851	A1	9/2003	Mann et al.	2004/0254429	A1	12/2004	Yang
2003/0181852	A1	9/2003	Mann et al.	2004/0254433	A1	12/2004	Bandis et al.

US 8,149,117 B2

Page 10

2004/0254434	A1	12/2004	Goodnow et al.	2005/0277164	A1	12/2005	Drucker et al.
2004/0260363	A1	12/2004	Von Arx et al.	2005/0287620	A1	12/2005	Heller et al.
2004/0263354	A1	12/2004	Mann et al.	2006/0001538	A1	1/2006	Kraft et al.
2004/0267300	A1	12/2004	Mace	2006/0001550	A1	1/2006	Mann et al.
2005/0003470	A1	1/2005	Nelson et al.	2006/0001551	A1	1/2006	Kraft et al.
2005/0004439	A1	1/2005	Shin et al.	2006/0003398	A1	1/2006	Heller et al.
2005/0004494	A1	1/2005	Perez et al.	2006/0004270	A1	1/2006	Bedard et al.
2005/0010087	A1	1/2005	Banet et al.	2006/0004271	A1	1/2006	Peyser et al.
2005/0010269	A1	1/2005	Lebel et al.	2006/0007017	A1	1/2006	Mann et al.
2005/0016276	A1	1/2005	Guan et al.	2006/0015020	A1	1/2006	Neale et al.
2005/0027177	A1	2/2005	Shin et al.	2006/0015024	A1	1/2006	Brister et al.
2005/0027179	A1	2/2005	Berner et al.	2006/0016700	A1*	1/2006	Brister et al. 205/777.5
2005/0027180	A1	2/2005	Goode, Jr. et al.	2006/0019327	A1	1/2006	Brister et al.
2005/0027181	A1	2/2005	Goode, Jr. et al.	2006/0020186	A1	1/2006	Brister et al.
2005/0027462	A1	2/2005	Goode, Jr. et al.	2006/0020187	A1	1/2006	Brister et al.
2005/0027463	A1	2/2005	Goode, Jr. et al.	2006/0020188	A1	1/2006	Kamath et al.
2005/0031689	A1	2/2005	Shults et al.	2006/0020189	A1	1/2006	Brister et al.
2005/0033132	A1	2/2005	Shults et al.	2006/0020190	A1	1/2006	Kamath et al.
2005/0038332	A1	2/2005	Saidara et al.	2006/0020191	A1	1/2006	Brister et al.
2005/0038680	A1	2/2005	McMahon	2006/0020192	A1	1/2006	Brister et al.
2005/0043598	A1	2/2005	Goode, Jr. et al.	2006/0025663	A1	2/2006	Talbot et al.
2005/0043894	A1	2/2005	Fernandez	2006/0029177	A1	2/2006	Cranford, Jr. et al.
2005/0049473	A1	3/2005	Desai et al.	2006/0031094	A1	2/2006	Cohen et al.
2005/0054909	A1	3/2005	Petisce et al.	2006/0036139	A1	2/2006	Brister et al.
2005/0065464	A1	3/2005	Talbot et al.	2006/0036140	A1	2/2006	Brister et al.
2005/0090607	A1	4/2005	Tapsak et al.	2006/0036141	A1	2/2006	Kamath et al.
2005/0096511	A1	5/2005	Fox et al.	2006/0036142	A1	2/2006	Brister et al.
2005/0096512	A1	5/2005	Fox et al.	2006/0036143	A1	2/2006	Brister et al.
2005/0112169	A1	5/2005	Brauker et al.	2006/0036144	A1	2/2006	Brister et al.
2005/0112544	A1	5/2005	Xu et al.	2006/0036145	A1	2/2006	Brister et al.
2005/0113653	A1	5/2005	Fox et al.	2006/0036187	A1	2/2006	Vos et al.
2005/0113657	A1	5/2005	Alarcon et al.	2006/0040402	A1	2/2006	Brauker et al.
2005/0113658	A1	5/2005	Jacobson et al.	2006/0052679	A1	3/2006	Kotulla et al.
2005/0113886	A1	5/2005	Fischell et al.	2006/0058602	A1	3/2006	Kwiatkowski et al.
2005/0114068	A1	5/2005	Chey et al.	2006/0063218	A1	3/2006	Bartkowiak et al.
2005/0118726	A1	6/2005	Schultz et al.	2006/0074564	A1	4/2006	Bartkowiak et al.
2005/0121322	A1	6/2005	Say et al.	2006/0142651	A1	6/2006	Brister et al.
2005/0124873	A1	6/2005	Shults et al.	2006/0155180	A1	7/2006	Brister et al.
2005/0131346	A1	6/2005	Douglas	2006/0166629	A1	7/2006	Reggiardo
2005/0137471	A1	6/2005	Haar et al.	2006/0173260	A1	8/2006	Gaoni et al.
2005/0143635	A1	6/2005	Kamath et al.	2006/0173406	A1	8/2006	Hayes et al.
2005/0143636	A1	6/2005	Zhang et al.	2006/0173444	A1	8/2006	Choy et al.
2005/0148003	A1	7/2005	Keith et al.	2006/0183985	A1	8/2006	Brister et al.
2005/0154271	A1	7/2005	Rasdal et al.	2006/0189863	A1	8/2006	Peyser et al.
2005/0161346	A1	7/2005	Simpson et al.	2006/0195029	A1	8/2006	Shults et al.
2005/0171503	A1	8/2005	Van Den Berghe et al.	2006/0200112	A1	9/2006	Paul
2005/0171513	A1	8/2005	Mann et al.	2006/0222566	A1	10/2006	Brauker et al.
2005/0173245	A1	8/2005	Feldman et al.	2006/0224109	A1	10/2006	Steil et al.
2005/0176136	A1	8/2005	Burd et al.	2006/0224141	A1	10/2006	Rush et al.
2005/0177036	A1	8/2005	Shults et al.	2006/0226985	A1	10/2006	Goodnow et al.
2005/0177398	A1	8/2005	Watanabe et al.	2006/0229512	A1	10/2006	Petisce et al.
2005/0181012	A1	8/2005	Saint et al.	2006/0247508	A1	11/2006	Fennell
2005/0182306	A1	8/2005	Sloan	2006/0247985	A1	11/2006	Liamos et al.
2005/0182451	A1	8/2005	Griffin et al.	2006/0258918	A1*	11/2006	Burd et al. 600/310
2005/0187720	A1	8/2005	Goode et al.	2006/0258929	A1	11/2006	Goode, Jr. et al.
2005/0192494	A1	9/2005	Ginsberg	2006/0263763	A1	11/2006	Simpson et al.
2005/0192557	A1	9/2005	Brauker et al.	2006/0272652	A1	12/2006	Stocker et al.
2005/0195930	A1	9/2005	Spital et al.	2006/0290496	A1	12/2006	Peeters et al.
2005/0199494	A1	9/2005	Say et al.	2007/0016381	A1	1/2007	Kamath et al.
2005/0203360	A1	9/2005	Brauker et al.	2007/0027381	A1	2/2007	Stafford
2005/0203707	A1	9/2005	Tsutsui et al.	2007/0033074	A1	2/2007	Nitzan et al.
2005/0214892	A1	9/2005	Kovatchev et al.	2007/0060814	A1	3/2007	Stafford
2005/0215871	A1	9/2005	Feldman et al.	2007/0066873	A1	3/2007	Kamath et al.
2005/0215872	A1	9/2005	Berner et al.	2007/0071681	A1	3/2007	Gadkar et al.
2005/0239154	A1	10/2005	Feldman et al.	2007/0073129	A1	3/2007	Shah et al.
2005/0239156	A1	10/2005	Drucker et al.	2007/0078320	A1	4/2007	Stafford
2005/0241957	A1	11/2005	Mao et al.	2007/0078321	A1	4/2007	Mazza et al.
2005/0245795	A1	11/2005	Goode, Jr. et al.	2007/0078322	A1	4/2007	Stafford
2005/0245799	A1	11/2005	Brauker et al.	2007/0078323	A1	4/2007	Reggiardo et al.
2005/0245839	A1	11/2005	Stivorac et al.	2007/0106135	A1	5/2007	Sloan et al.
2005/0245904	A1	11/2005	Estes et al.	2007/0124002	A1	5/2007	Estes et al.
2005/0251033	A1	11/2005	Scarantino et al.	2007/0149873	A1	6/2007	Say et al.
2005/0251083	A1	11/2005	Carr-Brendel et al.	2007/0149874	A1	6/2007	Say et al.
2005/0261660	A1	11/2005	Choi	2007/0149875	A1	6/2007	Ouyang et al.
2005/0267780	A1	12/2005	Ray et al.	2007/0151869	A1	7/2007	Heller et al.
2005/0271546	A1	12/2005	Gerber et al.	2007/0161879	A1	7/2007	Say et al.
2005/0271547	A1	12/2005	Gerber et al.	2007/0161880	A1	7/2007	Say et al.
2005/0272640	A1	12/2005	Doyle, III et al.	2007/0163880	A1	7/2007	Woo et al.
2005/0272985	A1	12/2005	Kotulla et al.	2007/0168224	A1	7/2007	Letzt et al.

2007/0173706	A1	7/2007	Neinast et al.	2008/0278333	A1	11/2008	Fennell et al.
2007/0173761	A1	7/2007	Kanderian et al.	2008/0287761	A1	11/2008	Hayter
2007/0179349	A1	8/2007	Hoyme et al.	2008/0287762	A1	11/2008	Hayter
2007/0179352	A1	8/2007	Randlov et al.	2008/0287763	A1	11/2008	Hayter
2007/0179370	A1	8/2007	Say et al.	2008/0287764	A1	11/2008	Rasdal et al.
2007/0179372	A1	8/2007	Say et al.	2008/0287765	A1	11/2008	Rasdal et al.
2007/0191699	A1	8/2007	Say et al.	2008/0287766	A1	11/2008	Rasdal et al.
2007/0191700	A1	8/2007	Say et al.	2008/0288180	A1	11/2008	Hayter
2007/0191701	A1	8/2007	Feldman et al.	2008/0288204	A1	11/2008	Hayter et al.
2007/0203407	A1	8/2007	Hoss et al.	2008/0296155	A1	12/2008	Shults et al.
2007/0203408	A1	8/2007	Say et al.	2008/0300919	A1	12/2008	Charlton et al.
2007/0203410	A1	8/2007	Say et al.	2008/0300920	A1	12/2008	Brown et al.
2007/0203411	A1	8/2007	Say et al.	2008/0301158	A1	12/2008	Brown et al.
2007/0203966	A1	8/2007	Brauker et al.	2008/0301665	A1	12/2008	Charlton et al.
2007/0208247	A1	9/2007	Say et al.	2008/0306368	A1	12/2008	Goode et al.
2007/0213610	A1	9/2007	Say et al.	2008/0306434	A1	12/2008	Dobbles et al.
2007/0213657	A1	9/2007	Jennewine et al.	2008/0306435	A1	12/2008	Kamath et al.
2007/0215491	A1	9/2007	Heller et al.	2008/0306444	A1	12/2008	Brister et al.
2007/0218097	A1	9/2007	Heller et al.	2008/0312841	A1	12/2008	Hayter
2007/0232877	A1	10/2007	He	2008/0312842	A1	12/2008	Hayter
2007/0235331	A1	10/2007	Simpson et al.	2008/0312844	A1	12/2008	Hayter et al.
2007/0244380	A1	10/2007	Say et al.	2008/0312845	A1	12/2008	Hayter et al.
2007/0249919	A1	10/2007	Say et al.	2009/0005665	A1	1/2009	Hayter et al.
2007/0249920	A1	10/2007	Say et al.	2009/0006034	A1	1/2009	Hayter et al.
2007/0249922	A1	10/2007	Peyser et al.	2009/0012379	A1	1/2009	Goode et al.
2007/0299617	A1	12/2007	Willis	2009/0018424	A1	1/2009	Kamath et al.
2008/0004515	A1	1/2008	Jennewine et al.	2009/0030294	A1	1/2009	Petisce et al.
2008/0004601	A1	1/2008	Jennewine et al.	2009/0033482	A1	2/2009	Hayter et al.
2008/0009692	A1	1/2008	Stafford	2009/0036747	A1	2/2009	Hayter et al.
2008/0017522	A1	1/2008	Heller et al.	2009/0036758	A1	2/2009	Brauker et al.
2008/0021666	A1	1/2008	Goode, Jr. et al.	2009/0036760	A1	2/2009	Hayter
2008/0029391	A1	2/2008	Mao et al.	2009/0036763	A1	2/2009	Brauker et al.
2008/0033254	A1	2/2008	Kamath et al.	2009/0043181	A1	2/2009	Brauker et al.
2008/0039702	A1	2/2008	Hayter et al.	2009/0043182	A1	2/2009	Brauker et al.
2008/0045824	A1	2/2008	Tapsak et al.	2009/0043525	A1	2/2009	Brauker et al.
2008/0058625	A1	3/2008	McGarraugh et al.	2009/0043541	A1	2/2009	Brauker et al.
2008/0064937	A1	3/2008	McGarraugh et al.	2009/0043542	A1	2/2009	Brauker et al.
2008/0071156	A1	3/2008	Brister et al.	2009/0045055	A1	2/2009	Rhodes et al.
2008/0071157	A1	3/2008	McGarraugh et al.	2009/0055149	A1	2/2009	Hayter et al.
2008/0071158	A1	3/2008	McGarraugh et al.	2009/0062633	A1	3/2009	Brauker et al.
2008/0081977	A1	4/2008	Hayter et al.	2009/0062635	A1	3/2009	Brauker et al.
2008/0083617	A1	4/2008	Simpson et al.	2009/0062767	A1	3/2009	VanAntwerp et al.
2008/0086042	A1	4/2008	Brister et al.	2009/0063402	A1	3/2009	Hayter
2008/0086044	A1	4/2008	Brister et al.	2009/0076356	A1	3/2009	Simpson et al.
2008/0086273	A1	4/2008	Shults et al.	2009/0076360	A1	3/2009	Brister et al.
2008/0097289	A1	4/2008	Steil et al.	2009/0076361	A1	3/2009	Kamath et al.
2008/0108942	A1	5/2008	Brister et al.	2009/0099436	A1	4/2009	Brister et al.
2008/0154513	A1	6/2008	Kovatchev et al.	2009/0105636	A1	4/2009	Hayter et al.
2008/0167543	A1	7/2008	Say et al.	2009/0124877	A1	5/2009	Goode, Jr. et al.
2008/0172205	A1	7/2008	Breton et al.	2009/0124878	A1	5/2009	Goode et al.
2008/0183060	A1	7/2008	Steil et al.	2009/0124879	A1	5/2009	Brister et al.
2008/0183061	A1	7/2008	Goode et al.	2009/0124964	A1	5/2009	Leach et al.
2008/0183399	A1	7/2008	Goode et al.	2009/0131768	A1	5/2009	Simpson et al.
2008/0188731	A1	8/2008	Brister et al.	2009/0131769	A1	5/2009	Leach et al.
2008/0188796	A1	8/2008	Steil et al.	2009/0131776	A1	5/2009	Simpson et al.
2008/0189051	A1	8/2008	Goode et al.	2009/0131777	A1	5/2009	Simpson et al.
2008/0194935	A1	8/2008	Brister et al.	2009/0137886	A1	5/2009	Shariati et al.
2008/0194936	A1	8/2008	Goode et al.	2009/0137887	A1	5/2009	Shariati et al.
2008/0194937	A1	8/2008	Goode et al.	2009/0143659	A1	6/2009	Li et al.
2008/0194938	A1	8/2008	Brister et al.	2009/0143660	A1	6/2009	Brister et al.
2008/0195232	A1	8/2008	Carr-Brendel et al.	2009/0149717	A1	6/2009	Brauer et al.
2008/0195967	A1	8/2008	Goode et al.	2009/0156919	A1	6/2009	Brister et al.
2008/0197024	A1	8/2008	Simpson et al.	2009/0156924	A1	6/2009	Shariati et al.
2008/0200788	A1	8/2008	Brister et al.	2009/0163790	A1	6/2009	Brister et al.
2008/0200789	A1	8/2008	Brister et al.	2009/0163791	A1	6/2009	Brister et al.
2008/0200791	A1	8/2008	Simpson et al.	2009/0164190	A1	6/2009	Hayter
2008/0208025	A1	8/2008	Shults et al.	2009/0164239	A1	6/2009	Hayter et al.
2008/0208113	A1	8/2008	Damiano et al.	2009/0164251	A1	6/2009	Hayter
2008/0214915	A1	9/2008	Brister et al.	2009/0178459	A1	7/2009	Li et al.
2008/0214918	A1	9/2008	Brister et al.	2009/0182217	A1	7/2009	Li et al.
2008/0228051	A1	9/2008	Shults et al.	2009/0192366	A1	7/2009	Mensinger et al.
2008/0228054	A1	9/2008	Shults et al.	2009/0192380	A1	7/2009	Shariati et al.
2008/0242961	A1	10/2008	Brister et al.	2009/0192722	A1	7/2009	Shariati et al.
2008/0255434	A1	10/2008	Hayter et al.	2009/0192724	A1	7/2009	Brauker et al.
2008/0255437	A1	10/2008	Hayter	2009/0192745	A1	7/2009	Kamath et al.
2008/0255808	A1	10/2008	Hayter	2009/0192751	A1	7/2009	Kamath et al.
2008/0256048	A1	10/2008	Hayter	2009/0198118	A1	8/2009	Hayter et al.
2008/0262469	A1	10/2008	Brister et al.	2009/0203981	A1	8/2009	Brauker et al.
2008/0275313	A1	11/2008	Brister et al.	2009/0204341	A1	8/2009	Brauker et al.

2009/0216103	A1	8/2009	Brister et al.	EP	0653718	5/1995
2009/0240120	A1	9/2009	Mensinger et al.	EP	0800082	10/1997
2009/0240128	A1	9/2009	Mensinger et al.	EP	0880936	12/1998
2009/0240193	A1	9/2009	Mensinger et al.	EP	0970655	1/2000
2009/0242399	A1	10/2009	Kamath et al.	EP	1034734	9/2000
2009/0242425	A1	10/2009	Kamath et al.	EP	1048264	11/2000
2009/0247855	A1	10/2009	Boock et al.	EP	1445746	8/2004
2009/0247856	A1	10/2009	Boock et al.	GB	1394171	5/1975
2009/0287073	A1	11/2009	Boock et al.	GB	1579690	11/1980
2009/0287074	A1	11/2009	Shults et al.	GB	1599241	9/1981
2009/0299155	A1	12/2009	Yang et al.	GB	2073891	10/1981
2009/0299156	A1	12/2009	Simpson et al.	GB	2154003	8/1985
2009/0299162	A1	12/2009	Brauker et al.	GB	2194892	3/1988
2009/0299276	A1	12/2009	Brauker et al.	GB	2204408	11/1988
2010/0010324	A1	1/2010	Brauker et al.	GB	2225637	6/1990
2010/0010331	A1	1/2010	Brauker et al.	GB	2254436	10/1992
2010/0010332	A1	1/2010	Brauker et al.	SU	1281988	1/1987
2010/0016687	A1	1/2010	Brauker et al.	WO	WO-85/05119	11/1985
2010/0016698	A1	1/2010	Rasdal et al.	WO	WO-86/00513	1/1986
2010/0022855	A1	1/2010	Brauker et al.	WO	WO-87/00513	1/1987
2010/0030038	A1	2/2010	Brauker et al.	WO	WO-87/06040	10/1987
2010/0030053	A1	2/2010	Goode, Jr. et al.	WO	WO-89/02246	3/1989
2010/0030484	A1	2/2010	Brauker et al.	WO	WO-89/05119	6/1989
2010/0030485	A1	2/2010	Brauker et al.	WO	WO-89/08713	9/1989
2010/0036215	A1	2/2010	Goode, Jr. et al.	WO	WO-90/00367	1/1990
2010/0036216	A1	2/2010	Goode, Jr. et al.	WO	WO-90/05300	5/1990
2010/0036222	A1	2/2010	Goode, Jr. et al.	WO	WO-90/05910	5/1990
2010/0036223	A1	2/2010	Goode, Jr. et al.	WO	WO-91/01680	2/1991
2010/0036225	A1	2/2010	Goode, Jr. et al.	WO	WO-91/04704	4/1991
2010/0041971	A1	2/2010	Goode, Jr. et al.	WO	WO-91/15993	10/1991
2010/0045465	A1	2/2010	Brauker et al.	WO	WO-92/01947	2/1992
2010/0049024	A1	2/2010	Saint et al.	WO	WO-92/13271	8/1992
2010/0057040	A1	3/2010	Hayter	WO	WO-94/20602	9/1994
2010/0057041	A1	3/2010	Hayter	WO	WO-94/27140	11/1994
2010/0057042	A1	3/2010	Hayter	WO	WO-95/06240	3/1995
2010/0057044	A1	3/2010	Hayter	WO	WO-96/07908	3/1996
2010/0057057	A1	3/2010	Hayter et al.	WO	WO-96/25089	8/1996
2010/0063373	A1	3/2010	Kamath et al.	WO	WO-96/30431	10/1996
2010/0076283	A1	3/2010	Simpson et al.	WO	WO-96/35370	11/1996
2010/0081908	A1	4/2010	Dobbles et al.	WO	WO-97/02847	1/1997
2010/0081910	A1	4/2010	Brister et al.	WO	WO-97/19344	5/1997
2010/0087724	A1	4/2010	Brauker et al.	WO	WO-97/20207	6/1997
2010/0096259	A1	4/2010	Zhang et al.	WO	WO-97/41421	11/1997
2010/0099970	A1	4/2010	Shults et al.	WO	WO-97/42882	11/1997
2010/0099971	A1	4/2010	Shults et al.	WO	WO-97/42883	11/1997
2010/0119693	A1	5/2010	Tapsak et al.	WO	WO-97/42886	11/1997
2010/0121169	A1	5/2010	Petisce et al.	WO	WO-97/42888	11/1997
FOREIGN PATENT DOCUMENTS				WO	WO-97/43962	11/1997
EP	0010375	4/1980		WO	WO-97/46868	12/1997
EP	1579690	11/1980		WO	WO-98/09167	3/1998
EP	0026995	4/1981		WO	WO-98/24366	6/1998
EP	0048090	3/1982		WO	WO-98/35053	8/1998
EP	0078636	5/1983		WO	WO-98/52045	11/1998
EP	0080304	6/1983		WO	WO-98/52293	11/1998
EP	0098592	1/1984		WO	WO-99/05966	2/1999
EP	0125139	11/1984		WO	WO-99/32883	7/1999
EP	0127958	12/1984		WO	WO-99/56613	11/1999
EP	0136362	4/1985		WO	WO-00/13580	3/2000
EP	0170375	2/1986		WO	WO-00/18294	4/2000
EP	0177743	4/1986		WO	WO-00/19887	4/2000
EP	0184909	6/1986		WO	WO-00/20626	4/2000
EP	0206218	12/1986		WO	WO-00/33065	6/2000
EP	0230472	8/1987		WO	WO-00/49940	8/2000
EP	0241309	10/1987		WO	WO-00/59370	10/2000
EP	0245073	11/1987		WO	WO-00/62664	10/2000
EP	0255291	2/1988		WO	WO-00/62665	10/2000
EP	0278647	8/1988		WO	WO-00/78210	12/2000
EP	0320109	6/1989		WO	WO-00/78992	12/2000
EP	0353328	2/1990		WO	WO-01/24038	4/2001
EP	0359831	3/1990		WO	WO-01/33216	5/2001
EP	0368209	5/1990		WO	WO-01/52727	7/2001
EP	0390390	10/1990		WO	WO-01/52935	7/2001
EP	0396788	11/1990		WO	WO-01/54753	8/2001
EP	0400918	12/1990		WO	WO-01/57238	8/2001
EP	0453283	10/1991		WO	WO-01/57239	8/2001
EP	0470290	2/1992		WO	WO-01/67009	9/2001
EP	0504835	9/1992		WO	WO-02/13686	2/2002
EP	0286118	1/1995		WO	WO-02/16905	2/2002
				WO	WO-02/17210	2/2002

WO	WO-02/058537	8/2002
WO	WO-02/078512	10/2002
WO	WO-03/036583	5/2003
WO	WO-03/076893	9/2003
WO	WO-03/082091	10/2003
WO	WO-03/085372	10/2003
WO	WO-2004/061420	7/2004
WO	WO-2005/041766	5/2005
WO	WO-2005/089103	9/2005
WO	WO-2006/024671	3/2006
WO	WO-2006/037109	4/2006
WO	WO-2006/079114	7/2006
WO	WO-2006/118947	11/2006
WO	WO-2006/119084	11/2006
WO	WO-2007/002189	1/2007
WO	WO-2007/016399	2/2007
WO	WO-2007/027381	3/2007
WO	WO-2007/027788	3/2007
WO	WO-2007/041069	4/2007
WO	WO-2007/041070	4/2007
WO	WO-2007/041072	4/2007
WO	WO-2007/041248	4/2007
WO	WO-2007/056638	5/2007
WO	WO-2007/101223	9/2007
WO	WO-2007/101260	9/2007
WO	WO-2007/120363	10/2007
WO	WO-2007/126444	11/2007
WO	WO-2007/053832	12/2007
WO	WO-2007/143225	12/2007
WO	WO-2008/003003	1/2008
WO	WO-2008/005780	1/2008
WO	WO-2008/021913	2/2008
WO	WO-2008/042760	4/2008
WO	WO-2008/128210	10/2008
WO	WO-2008/130896	10/2008
WO	WO-2008/130897	10/2008
WO	WO-2008/130898	10/2008
WO	WO-2008/143943	11/2008
WO	WO-2008/150428	12/2008
WO	WO-2008/153825	12/2008
WO	WO-2009/018058	2/2009
WO	WO-2009/075697	6/2009
WO	WO-2009/086216	7/2009
WO	WO-2009/096992	8/2009
WO	WO-2009/097594	8/2009

OTHER PUBLICATIONS

Albery, W. J., et al., "Amperometric Enzyme Electrodes Part II: Conducting Salts as Electrode Materials for the Oxidation of Glucose Oxidase", *Journal of ElectroAnalytical Chemistry*, vol. 194, 1985, pp. 223-235.

Albery, W. J., et al., "Amperometric Enzyme Electrodes", *Philosophical Transactions of the Royal Society of London*, vol. 316, 1987, pp. 107-119.

Alcock, S. J., et al., "Continuous Analyte Monitoring to Aid Clinical Practice", *IEEE Engineering in Medicine and Biology Magazine*, 1994, pp. 319-325.

Anderson, L. B., et al., "Thin-Layer Electrochemistry: Steady-State Methods of Studying Rate Processes", *Journal of ElectroAnalytical Chemistry*, vol. 10, 1965, pp. 295-305.

Armour, J. C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs", *Diabetes*, vol. 39, 1990, pp. 1519-1526.

Bartlett, P. N., et al., "Covalent Binding of Electron Relays to Glucose Oxidase", *Journal of the Chemical Society, Chemical Communications*, 1987, pp. 1603-1604.

Bartlett, P. N., et al., "Modification of Glucose Oxidase by Tetrathiafulvalene", *Journal of the Chemical Society, Chemical Communications*, 1990, pp. 1135-1136.

Bartlett, P. N., et al., "Strategies for the Development of Amperometric Enzyme Electrodes", *Biosensors*, vol. 3, 1987/88, pp. 359-379.

Bennion, N., et al., "Alternate Site Glucose Testing: A Crossover Design", *Diabetes Technology & Therapeutics*, vol. 4, No. 1, 2002, pp. 25-33.

Bindra, D. S., et al., "Design and in Vitro Studies of a Needle-Type Glucose Sensor for Subcutaneous Monitoring", *Analytical Chemistry*, vol. 63, No. 17, 1991, pp. 1692-1696.

Blank, T. B., et al., "Clinical Results From a Non-Invasive Glucose Blood Glucose Monitor", *Optical Diagnostics and Sensing of Biological Fluids and Cholesterol Monitoring II, Proceedings of SPIE*, vol. 4624, 2002, pp. 1-10.

Bobbioni-Harsch, E., et al., "Lifespan of Subcutaneous Glucose Sensors and Their Performances During Dynamic Glycaemia Changes in Rats", *Journal of Biomedical Engineering*, vol. 15, 1993, pp. 457-463.

Boedeker Plastics, Inc., "Polyethylene Specifications", *Web Page of Boedeker.com*, 2007, pp. 1-3.

Brandt, J., et al., "Covalent Attachment of Proteins to Polysaccharide Carriers by Means of Benzoquinone", *Biochimica et Biophysica Acta*, vol. 386, 1975, pp. 196-202.

Brooks, S. L., et al., "Development of an On-Line Glucose Sensor for Fermentation Monitoring", *Biosensors*, vol. 3, 1987/88, pp. 45-56.

Brownlee, M., et al., "A Glucose-Controlled Insulin-Delivery System: Semisynthetic Insulin Bound to Lectin", *Science*, vol. 206, 1979, 1190-1191.

Cass, A. E., et al., "Ferricinium Ion As an Electron Acceptor for Oxido-Reductases", *Journal of ElectroAnalytical Chemistry*, vol. 190, 1985, pp. 117-127.

Cass, A. E., et al., "Ferrocene-Medicated Enzyme Electrode for Amperometric Determination of Glucose", *Analytical Chemistry*, vol. 56, No. 4, 1984, 667-671.

Castner, J. F., et al., "Mass Transport and Reaction Kinetic Parameters Determined Electrochemically for Immobilized Glucose Oxidase", *Biochemistry*, vol. 23 No. 10, 1984, 2203-2210.

Claremont, D. J., et al., "Biosensors for Continuous In Vivo Glucose Monitoring", *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 10, 1988.

Clark Jr., L. C., et al., "Differential Anodic Enzyme Polarography for the Measurement of Glucose", *Oxygen Transport to Tissue: Instrumentation, Methods, and Physiology*, 1973, pp. 127-133.

Clark Jr., L. C., et al., "Electrode Systems for Continuous Monitoring in Cardiovascular Surgery", *Annals New York Academy of Sciences*, 1962, pp. 29-45.

Clark Jr., L. C., et al., "Long-term Stability of Electroenzymatic Glucose Sensors Implanted in Mice", *American Society of Artificial Internal Organs Transactions*, vol. XXXIV, 1988, pp. 259-265.

Clarke, W. L., et al., "Evaluating Clinical Accuracy of Systems for Self-Monitoring of Blood Glucose", *Diabetes Care*, vol. 10, No. 5, 1987, pp. 622-628.

Csoregi, E., et al., "Design and Optimization of a Selective Subcutaneously Implantable Glucose Electrode Based on 'Wired' Glucose Oxidase", *Analytical Chemistry*, vol. 67, No. 7, 1995, pp. 1240-1244.

Csoregi, E., et al., "Design, Characterization and One-Point in Vivo Calibration of a Subcutaneously Implanted Glucose Electrode", *Analytical Chemistry*, vol. 66 No. 19, 1994, pp. 3131-3138.

Csoregi, E., et al., "On-Line Glucose Monitoring by Using Microdialysis Sampling and Amperometric Detection Based on 'Wired' Glucose Oxidase in Carbon Paste", *Mikrochimica Acta*, vol. 121, 1995, pp. 31-40.

Dai, W. S., et al., "Hydrogel Membranes with Mesh Size Asymmetry Based on the Gradient Crosslinking of Poly(vinyl alcohol)", *Journal of Membrane Science*, vol. 156, 1999, pp. 67-79.

Davis, G., "Electrochemical Techniques for the Development of Amperometric Biosensors", *Biosensors*, vol. 1, 1985, pp. 161-178.

Degani, Y., et al., "Direct Electrical Communication Between Chemically Modified Enzymes and Metal Electrodes. 1. Electron Transfer from Glucose Oxidase to Metal Electrodes via Electron Relays, Bound Covalently to the Enzyme", *The Journal of Physical Chemistry*, vol. 91, No. 6, 1987, pp. 1285-1289.

Degani, Y., et al., "Direct Electrical Communication Between Chemically Modified Enzymes and Metal Electrodes. 2. Methods for Bonding Electron-Transfer Relays to Glucose Oxidase and D-Amino-Acid Oxidase", *Journal of the American Chemical Society*, vol. 110, No. 8, 1988, pp. 2615-2620.

Degani, Y., et al., "Electrical Communication Between Redox Centers of Glucose Oxidase and Electrodes via Electrostatically and Covalently Bound Redox Polymers", *Journal of the American Chemical Society*, vol. 111, 1989, pp. 2357-2358.


- Denisevich, P., et al., "Unidirectional Current Flow and Charge State Trapping at Redox Polymer Interfaces on Bilayer Electrodes: Principles, Experimental Demonstration, and Theory", *Journal of the American Chemical Society*, vol. 103, 1981, pp. 4727-4737.
- Dicks, J. M., et al., "Ferrocene Modified Polypyrrole with Immobilised Glucose Oxidase and its Application in Amperometric Glucose Microbiosensors", *Annales de Biologie Clinique*, vol. 47, 1989, pp. 607-619.
- Ellis, C. D., et al., "Selectivity and Directed Charge Transfer through an Electroactive Metallopolymer Film", *Journal of the American Chemical Society*, vol. 103, No. 25, 1981, pp. 7480-7483.
- Engstrom, R. C., "Electrochemical Pretreatment of Glassy Carbon Electrodes", *Analytical Chemistry*, vol. 54, No. 13, 1982, pp. 2310-2314.
- Engstrom, R. C., et al., "Characterization of Electrochemically Pretreated Glassy Carbon Electrodes", *Analytical Chemistry*, vol. 56 No. 2, 1984, pp. 136-141.
- Feldman, B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes", *Diabetes Technology & Therapeutics*, vol. 5, No. 5, 2003, pp. 769-779.
- Feldman, B., et al., "Correlation of Glucose Concentrations in Interstitial Fluid and Venous Blood During Periods of Rapid Glucose Change", *Abbott Diabetes Care, Inc. Freestyle Navigator Continuous Glucose Monitor Pamphlet*, 2004.
- Feldman, B., et al., "Electron Transfer Kinetics at Redox Polymer/Solution Interfaces Using Microelectrodes and Twin Electrode Thin Layer Cells", *Journal of ElectroAnalytical Chemistry*, vol. 194, 1985, pp. 63-81.
- Fischer, H., et al., "Intramolecular Electron Transfer Medicated by 4,4'-Bipyridine and Related Bridging Groups", *Journal of the American Chemical Society*, vol. 98, No. 18, 1976, pp. 5512-5517.
- Flentge, F., et al., "An Enzyme-Reactor for Electrochemical Monitoring of Choline and Acetylcholine: Applications in High-Performance Liquid Chromatography, Bran Tissue, Microdialysis and Cerebrospinal Fluid", *Analytical Biochemistry*, vol. 204, 1992, pp. 305-310.
- Foulds, N. C., et al., "Enzyme Entrapment in Electrically Conducting Polymers: Immobilisation of Glucose Oxidase in Polypyrrole and its Application in Amperometric Glucose Sensors", *Journal of the Chemical Society, Faraday Transactions 1*, vol. 82, 1986, pp. 1259-1264.
- Foulds, N. C., et al., "Immobilization of Glucose Oxidase in Ferrocene-Modified Pyrrole Polymers", *Analytical Chemistry*, vol. 60, No. 22, 1988, pp. 2473-2478.
- Frew, J. E., et al., "Electron-Transfer Biosensors", *Philosophical Transactions of the Royal Society of London*, vol. 316, 1987, pp. 95-106.
- Godsland, I. F., et al., "Maximizing the Success Rate of Minimal Model Insulin Sensitivity Measurement in Humans: The Importance of Basal Glucose Levels", *Clinical Science*, vol. 101, 2001, pp. 1-9.
- Gorton, L., et al., "Selective Detection in Flow Analysis Based on the Combination of Immobilized Enzymes and Chemically Modified Electrodes", *Analytica Chimica Acta*, vol. 250, 1991, pp. 203-248.
- Graham, N. B., "Poly(ethylene oxide) and Related Hydrogels", *Hydrogels in Medicine and Pharmacy, vol. II: Polymers, Chapter 4*, 1987, pp. 95-113.
- Gregg, B. A., et al., "Cross-Linked Redox Gels Containing Glucose Oxidase for Amperometric Biosensor Applications", *Analytical Chemistry*, vol. 62, No. 3, 1990, pp. 258-263.
- Gregg, B. A., et al., "Redox Polymer Films Containing Enzymes. 1. A Redox-Conducting Epoxy Cement: Synthesis, Characterization, and Electrocatalytic Oxidation of Hydroquinone", *Journal of Physical Chemistry*, vol. 95, No. 15, 1991, 5970-5975.
- Hale, P. D., et al., "A New Class of Amperometric Biosensor Incorporating a Polymeric Electron-Transfer Mediator", *Journal of the American Chemical Society*, vol. 111, No. 9, 1989, pp. 3482-3484.
- Harrison, D. J., et al., "Characterization of Perfluorosulfonic Acid Polymer Coated Enzyme Electrodes and a Miniaturized Integrated Potentiostat for Glucose Analysis in Whole Blood", *Analytical Chemistry*, vol. 60, No. 19, 1988, pp. 2002-2007.
- Hawkrige, F. M., et al., "Indirect Coulometric Titration of Biological Electron Transport Components", *Analytical Chemistry*, vol. 45, No. 7, 1973, pp. 1021-1027.
- Heller, A., "Electrical Connection Enzyme Redox Centers to Electrodes", *Journal of Physical Chemistry*, vol. 96, No. 9, 1990, pp. 3579-3587.
- Heller, A., "Electrical Wiring of Redox Enzymes", *Accounts of Chemical Research* vol. 23, No. 5, 1990, 128-134.
- Heller, A., et al., "Amperometric Biosensors Based on Three-Dimensional Hydrogel-Forming Epoxy Networks", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 180-183.
- Ianniello, R. M., et al., "Differential Pulse Voltammetric Study of Direct Electron Transfer in Glucose Oxidase Chemically Modified Graphite Electrodes", *Analytical Chemistry*, vol. 54, No. 7, 1982, pp. 1098-1101.
- Ianniello, R. M., et al., "Immobilized Enzyme Chemically Modified Electrode as an Amperometric Sensor", *Analytical Chemistry*, vol. 53, No. 13, 1981, pp. 2090-2095.
- Ikeda, T., et al., "Glucose Oxidase-Immobilized Benzoquinone-Carbon Paste Electrode as a Glucose Sensor", *Agricultural and Biological Chemistry*, vol. 49, No. 2, 1985, pp. 541-543.
- Ikeda, T., et al., "Kinetics of Outer-Sphere Electron Transfers Between Metal Complexes in Solutions and Polymeric Films on Modified Electrodes", *Journal of the American Chemical Society*, vol. 103, No. 25, 1981, pp. 7422-7425.
- Isermann, R., "Supervision, Fault-Detection and Fault-Diagnosis Methods—An Introduction", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 639-652.
- Isermann, R., et al., "Trends in the Application of Model-Based Fault Detection and Diagnosis of Technical Processes", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 709-719.
- Johnson, J. M., et al., "Potential-Dependent Enzymatic Activity in an Enzyme Thin-Layer Cell", *Analytical Chemistry*, vol. 54, No. 8, 1982, pp. 1377-1383.
- Johnson, K. W., "Reproducible Electrodeposition of Biomolecules for the Fabrication of Miniature Electroenzymatic Biosensors", *Sensors and Actuators B*, vol. 5, 1991, pp. 85-89.
- Johnson, K. W., et al., "In vivo Evaluation of an Electroenzymatic Glucose Sensor Implanted in Subcutaneous Tissue", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 709-714.
- Johnson, P. C., "Peripheral Circulation", *John Wiley & Sons*, 1978, pp. 198.
- Jonsson, G., et al., "An Amperometric Glucose Sensor Made by Modification of a Graphite Electrode Surface With Immobilized Glucose Oxidase and Adsorbed Mediator", *Biosensors*, vol. 1, 1985, pp. 355-368.
- Josowicz, M., et al., "Electrochemical Pretreatment of Thin Film Platinum Electrodes", *Journal of the Electrochemical Society*, vol. 135 No. 1, 1988, pp. 112-115.
- Jungheim, K., et al., "How Rapid Does Glucose Concentration Change in Daily Life of Patients with Type 1 Diabetes?", 2002, pp. 250.
- Jungheim, K., et al., "Risky Delay of Hypoglycemia Detection by Glucose Monitoring at the Arm", *Diabetes Care*, vol. 24, No. 7, 2001, pp. 1303-1304.
- Kaplan, S. M., "Wiley Electrical and Electronics Engineering Dictionary", *IEEE Press*, 2004, pp. 141, 142, 548, 549.
- Katakis, I., et al., "Electrostatic Control of the Electron Transfer Enabling Binding of Recombinant Glucose Oxidase and Redox Polyelectrolytes", *Journal of the American Chemical Society*, vol. 116, No. 8, 1994, pp. 3617-3618.
- Katakis, I., et al., "L- α -Glycerophosphate and L-Lactate Electrodes Based on the Electrochemical 'Wiring' of Oxidase", *Analytical Chemistry*, vol. 64, No. 9, 1992, pp. 1008-1013.
- Kemp, G. J., "Theoretical Aspects of One-Point Calibration: Causes and Effects of Some Potential Errors, and Their Dependence on Concentration", *Clinical Chemistry*, vol. 30, No. 7, 1984, pp. 1163-1167.
- Kenausis, G., et al., "'Wiring' of Glucose Oxidase and Lactate Oxidase Within a Hydrogel Made with Poly(vinyl pyridine) complexed with [Os(4,4'-dimethoxy-2,2'-bipyridine)₂Cl]⁺²⁺", *Journal of the Chemical Society, Faraday Transactions*, vol. 92, No. 20, 1996, pp. 4131-4136.

- Kerner, W., et al., "The Function of a Hydrogen Peroxide-Detecting Electroenzymatic Glucose Electrode is Markedly Impaired in Human Subcutaneous Tissue and Plasma," *Biosensors & Bioelectronics*, vol. 8, 1993, pp. 473-482.
- Korf, J., et al., "Monitoring of Glucose and Lactate Using Microdialysis: Applications in Neonates and Rat Brain," *Developmental Neuroscience*, vol. 15, 1993, pp. 240-246.
- Koudelka, M., et al., "In-Vivo Behaviour of Hypodermically Implanted Microfabricated Glucose Sensors," *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 31-36.
- Kulys, J., et al., "Mediatorless Peroxidase Electrode and Preparation of Bionzyme Sensors," *Bioelectrochemistry and Bioenergetics*, vol. 24, 1990, pp. 305-311.
- Lager, W., et al., "Implantable Electrocatalytic Glucose Sensor," *Hormone Metabolic Research*, vol. 26, 1994, pp. 526-530.
- Laurell, T., "A Continuous Glucose Monitoring System Based on Microdialysis," *Journal of Medical Engineering & Technology*, vol. 16, No. 5, 1992, pp. 187-193.
- Lindner, E., et al., "Flexible (Kapton-Based) Microsensor Arrays of High Stability for Cardiovascular Applications," *Journal of the Chemical Society, Faraday Transactions*, vol. 89, No. 2, 1993, pp. 361-367.
- Lortz, J., et al., "What is Bluetooth? We Explain the Newest Short-Range Connectivity Technology," *Smart Computing Learning Series, Wireless Computing*, vol. 8, Issue 5, 2002, pp. 72-74.
- Maidan, R., et al., "Elimination of Electrooxidizable Interferant-Produced Currents in Amperometric Biosensors," *Analytical Chemistry*, vol. 64, No. 23, 1992, pp. 2889-2896.
- Malin, S. F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy," *Clinical Chemistry*, vol. 45, No. 9, 1999, pp. 1651-1658.
- Marko-Varga, G., et al., "Enzyme-Based Biosensor as a Selective Detection Unit in Column Liquid Chromatography," *Journal of Chromatography A*, vol. 660, 1994, pp. 153-167.
- Mastrototaro, J. J., et al., "An Electroenzymatic Glucose Sensor Fabricated on a Flexible Substrate," *Sensors and Actuators B*, vol. 5, 1991, pp. 139-144.
- Mauras, N., et al., "Lack of Accuracy of Continuous Glucose Sensors in Healthy, Nondiabetic Children: Results of the Diabetes Research in Children Network (DirecNet) Accuracy Study," *Journal of Pediatrics*, 2004, pp. 770-775.
- McGarraugh, G., et al., "Glucose Measurements Using Blood Extracted from the Forearm and the Finger," *TheraSense, Inc.*, 2001, 16 pages.
- McGarraugh, G., et al., "Physiological Influences on Off-Finger Glucose Testing," *Diabetes Technology & Therapeutics*, vol. 3, No. 3, 2001, pp. 367-376.
- McKean, B. D., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors," *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 7, 1988, pp. 526-532.
- McNeil, C. J., et al., "Thermostable Reduced Nicotinamide Adenine Dinucleotide Oxidase: Application to Amperometric Enzyme Assay," *Analytical Chemistry*, vol. 61, No. 1, 1989, pp. 25-29.
- Miyawaki, O., et al., "Electrochemical and Glucose Oxidase Coenzyme Activity of Flavin Adenine Dinucleotide Covalently Attached to Glassy Carbon at the Adenine Amino Group," *Biochimica et Biophysica Acta*, vol. 838, 1985, pp. 60-68.
- Moatti-Sirat, D., et al., "Evaluating In Vitro and In Vivo the Interference of Ascorbate and Acetaminophen on Glucose Detection by a Needle-Type Glucose Sensor," *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 345-352.
- Moatti-Sirat, D., et al., "Reduction of Acetaminophen Interference in Glucose Sensors by a Composite Nafion Membrane: Demonstration in Rats and Man," *Diabetologia*, vol. 37, 1994, pp. 610-616.
- Moatti-Sirat, D., et al., "Towards Continuous Glucose Monitoring: In Vivo Evaluation of a Miniaturized Glucose Sensor Implanted for Several Days in Rat Subcutaneous Tissue," *Diabetologia*, vol. 35, 1992, pp. 224-230.
- Nagy, G., et al., "A New Type of Enzyme Electrode: The Ascorbic Acid Eliminator Electrode," *Life Sciences*, vol. 31, No. 23, 1982, pp. 2611-2616.
- Nakamura, S., et al., "Effect of Periodate Oxidation on the Structure and Properties of Glucose Oxidase," *Biochimica et Biophysica Acta*, vol. 445, 1976, pp. 294-308.
- Narasimham, K., et al., "p-Benzoquinone Activation of Metal Oxide Electrodes for Attachment of Enzymes," *Enzyme and Microbial Technology*, vol. 7, 1985, pp. 283-286.
- Ohara, T. J., "Osmium Bipyridyl Redox Polymers Used in Enzyme Electrodes," *Platinum Metals Review*, vol. 39, No. 2, 1995, pp. 54-62.
- Ohara, T. J., et al., "'Wired' Enzyme Electrodes for Amperometric Determination of Glucose or Lactate in the Presence of Interfering Substances," *Analytical Chemistry*, vol. 66, No. 15, 1994, pp. 2451-2457.
- Ohara, T. J., et al., "Glucose Electrodes Based on Cross-Linked [Os(bpy)₂Cl]⁺²⁺Complexed Poly(1-Vinylimidazole) Films," *Analytical Chemistry*, vol. 65, No. 23, 1993, pp. 3512-3517.
- Olievier, C. N., et al., "In Vivo Measurement of Carbon Dioxide Tension with a Miniature Electrodes," *Pflügers Archiv: European Journal of Physiology*, vol. 373, 1978, pp. 269-272.
- Paddock, R. M., et al., "Electrocatalytic Reduction of Hydrogen Peroxide via Direct Electron Transfer From Pyrolytic Graphite Electrodes to Irreversibly Adsorbed Cytochrome C Peroxidase," *Journal of Electroanalytical Chemistry*, vol. 260, 1989, pp. 487-494.
- Palleschi, G., et al., "A Study of Interferences in Glucose Measurements in Blood by Hydrogen Peroxide Based Glucose Probes," *Analytical Biochemistry*, vol. 159, 1986, pp. 114-121.
- Pankratov, I., et al., "Sol-Gel Derived Renewable-Surface Biosensors," *Journal of Electroanalytical Chemistry*, vol. 393, 1995, pp. 35-41.
- Pathak, C., et al., "Rapid Photopolymerization of Immunoprotective Gels in Contact with Cells and Tissue," *Journal of the American Chemical Society*, vol. 114, No. 21, 1992, pp. 8311-8312.
- Pickup, J., "Developing Glucose Sensors for in Vivo Use," *Tibtech*, vol. 11, 1993, pp. 285-291.
- Pickup, J., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensing Strategy," *Biosensors*, vol. 3, 1987/88, pp. 335-346.
- Pickup, J., et al., "In Vivo Molecular Sensing in Diabetes Mellitus: An Implantable Glucose Sensor with Direct Electron Transfer," *Diabetologia*, vol. 32, 1989, pp. 213-217.
- Pickup, J., et al., "Potentially-Implantable, Amperometric Glucose Sensors with Mediated Electron Transfer: Improving the Operating Stability," *Biosensors*, vol. 4, 1989, pp. 109-119.
- Pishko, M. V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels," *Analytical Chemistry*, vol. 63, No. 20, 1991, pp. 2268-2272.
- Poitout, V., et al., "A Glucose Monitoring System for On Line Estimation in Man of Blood Glucose Concentration Using a Miniaturized Glucose Sensor Implanted in the Subcutaneous Tissue and a Wearable Control Unit," *Diabetologia*, vol. 36, 1993, pp. 658-663.
- Poitout, V., et al., "Calibration in Dogs of a Subcutaneous Miniaturized Glucose Sensor Using a Glucose Meter for Blood Glucose Determination," *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 587-592.
- Poitout, V., et al., "In Vitro and in Vivo Evaluation in Dogs of a Miniaturized Glucose Sensor," *ASAIO Transactions*, vol. 37, No. 3, 1991, pp. M298-M300.
- Pollak, A., et al., "Enzyme Immobilization by Condensation Copolymerization into Cross-Linked Polyacrylamide Gels," *Journal of the American Chemical Society*, vol. 102, No. 20, 1980, pp. 6324-6336.
- Quinn, C. P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors," *The American Physiological Society*, 1995, E155-E161.
- Reach, G., et al., "Can Continuous Glucose Monitoring Be Used for the Treatment of Diabetes?," *Analytical Chemistry*, vol. 64, No. 6, 1992, pp. 381-386.
- Rebrin, K., et al., "Automated Feedback Control of Subcutaneous Glucose Concentration in Diabetic Dogs," *Diabetologia*, vol. 32, 1989, pp. 573-576.
- Reusch, W., "Other Topics: Organometallic Chemistry: Organometallic Compounds: Main Group Organometallic Compounds," *Virtual Textbook of Organic Chemistry*, 1999, Rev. 2007, 25 pages.

- Roe, J. N., et al., "Bloodless Glucose Measurements", *Critical Review in Therapeutic Drug Carrier Systems*, vol. 15, Issue 3, 1998, pp. 199-241.
- Sacks (ED), "Guidelines and Recommendations for Laboratory Analysis in the Diagnosis and Management of Diabetes Mellitus," *The National Academy of Clinical Biochemistry Presents Laboratory Medicine Practice Guidelines*, vol. 13, 2002, pp. 8-11, 21-23, 52-56, 63.
- Sakakida, M., et al., "Development of Ferrocene-Mediated Needle-Type Glucose Sensor as a Measure of True Subcutaneous Tissue Glucose Concentrations", *Artificial Organs Today*, vol. 2, No. 2, 1992, pp. 145-158.
- Sakakida, M., et al., "Ferrocene-Mediated Needle-Type Glucose Sensor Covered with Newly Designed Biocompatible Membrane", *Sensors and Actuators B*, vol. 13-14, 1993, pp. 319-322.
- Salehi, C., et al., "A Telemetry-Instrumentation System for Long-Term Implantable Glucose and Oxygen Sensors", *Analytical Letters*, vol. 29, No. 13, 1996, pp. 2289-2308.
- Samuels, G. J., et al., "An Electrode-Supported Oxidation Catalyst Based on Ruthenium (IV) pH 'Encapsulation' in a Polymer Film", *Journal of the American Chemical Society*, vol. 103, No. 1981, pp. 307-312.
- Sasso, S. V., et al., "Electropolymerized 1,2-Diaminobenzene as a Means to Prevent Interferences and Fouling and to Stabilize Immobilized Enzyme in Electrochemical Biosensors", *Analytical Chemistry*, vol. 62, No. 11, 1990, pp. 1111-1117.
- Scheller, F. W., et al., "Second Generation Biosensors," *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 245-253.
- Scheller, F., et al., "Enzyme Electrodes and Their Application", *Philosophical Transactions of The Royal Society of London B*, vol. 316, 1987, pp. 85-94.
- Schmehl, R. H., et al., "The Effect of Redox Site Concentration on the Rate of Mediated Oxidation of Solution Substrates by a Redox Copolymer Film", *Journal of ElectroAnalytical Chemistry*, vol. 152, 1983, pp. 97-109.
- Schmidt, F. J., et al., "Calibration of a Wearable Glucose Sensor", *The International Journal of Artificial Organs*, vol. 15, No. 1, 1992, pp. 55-61.
- Schmidtke, D. W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin", *Proceedings of the National Academy of Sciences*, vol. 95, 1998, pp. 294-299.
- Shaw, G. W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.
- Shichiri, M., et al., "Glycaemic Control in Pancreatectomized Dogs with a Wearable Artificial Endocrine Pancreas", *Diabetologia*, vol. 24, 1983, pp. 179-184.
- Shichiri, M., et al., "In Vivo Characteristics of Needle-Type Glucose Sensor—Measurements of Subcutaneous Glucose Concentrations in Human Volunteers", *Hormone and Metabolic Research Supplement Series*, vol. 20, 1988, pp. 17-20.
- Shichiri, M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor", *Diabetes Nutrition and Metabolism*, vol. 2, 1989, pp. 309-313.
- Shichiri, M., et al., "Needle-type Glucose Sensor for Wearable Artificial Endocrine Pancreas", *Implantable Sensors for Closed-Loop Prosthetic Systems*, Chapter 15, 1985, pp. 197-210.
- Shichiri, M., et al., "Telemetry Glucose Monitoring Device With Needle-Type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals", *Diabetes Care*, vol. 9, No. 3, 1986, pp. 298-301.
- Shichiri, M., et al., "Wearable Artificial Endocrine Pancreas With Needle-Type Glucose Sensor", *The Lancet*, 1982, pp. 1129-1131.
- Shults, M. C., et al., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors", *IEEE Transactions on Biomedical Engineering*, vol. 41, No. 10, 1994, pp. 937-942.
- Sittampalam, G., et al., "Surface-Modified Electrochemical Detector for Liquid Chromatography", *Analytical Chemistry*, vol. 55, No. 9, 1983, pp. 1608-1610.
- Skoog, D. A., et al., "Evaluation of Analytical Data," *Fundamentals of Analytical Chemistry*, 1966, pp. 55.
- Soegijoko, S., et al., "External Artificial Pancreas: A New Control Unit Using Microprocessor", *Hormone and Metabolic Research Supplement Series*, vol. 12, 1982, pp. 165-169.
- Sprules, S. D., et al., "Evaluation of a New Disposable Screen-Printed Sensor Strip for the Measurement of NADH and Its Modification to Produce a Lactate Biosensor Employing Microliter Volumes", *Electroanalysis*, vol. 8, No. 6, 1996, pp. 539-543.
- Sternberg, F., et al., "Calibration Problems of Subcutaneous Glucosensors when Applied 'In-Situ' in Man", *Hormone and Metabolic Research*, vol. 26, 1994, pp. 523-526.
- Sternberg, R., et al., "Covalent Enzyme Coupling on Cellulose Acetate Membranes for Glucose Sensor Development", *Analytical Chemistry*, vol. 60, No. 24, 1988, pp. 2781-2786.
- Sternberg, R., et al., "Study and Development of Multilayer Needle-Type Enzyme-Based Glucose Microsensors", *Biosensors*, vol. 4, 1988, pp. 27-40.
- Suekane, M., "Immobilization of Glucose Isomerase", *Zeitschrift für Allgemeine Mikrobiologie*, vol. 22, No. 8, 1982, pp. 565-576.
- Tajima, S., et al., "Simultaneous Determination of Glucose and 1,5-Anhydroglucitol", *Chemical Abstracts*, vol. 111, No. 25, 1989, pp. 394.
- Takamura, A., et al., Drug release from Poly(vinyl alcohol) Gel Prepared by Freeze-Thaw Procedure, *Journal of Controlled Release*, vol. 20, 1992, pp. 21-27.
- Tarasevich, M. R., "Bioelectrocatalysis", *Comprehensive Treatise of Electrochemistry*, vol. 10, 1985, pp. 231-295.
- Tatsuma, T., et al., "Enzyme Monolayer- and Bilayer-Modified Tin Oxide Electrodes for the Determination of Hydrogen Peroxide and Glucose", *Analytical Chemistry*, vol. 61, No. 21, 1989, pp. 2352-2355.
- Taylor, C., et al., "'Wiring' of Glucose Oxidase Within a Hydrogel Made with Polyvinyl Imidazole Complexed with [(Os-4,4'-dimethoxy-2,2'-bipyridine)Cl]⁺²", *Journal of ElectroAnalytical Chemistry*, vol. 396, 1995, pp. 511-515.
- Thompson, M., et al., "In Vivo Probes: Problems and Perspectives", *Clinical Biochemistry*, vol. 19, 1986, pp. 255-261.
- Travenol Laboratories, Inc., *An Introduction to "Eugly"*, Book 1, 1985, pp. 1-22.
- Trojanowicz, M., et al., "Enzyme Entrapped Polypyrrole Modified Electrode for Flow-Injection Determination of Glucose", *Biosensors & Bioelectronics*, vol. 5, 1990, pp. 149-156.
- Tsalikian, E., et al., "Accuracy of the GlucoWatch G2® Biographer and the Continuous Glucose Monitoring System During Hypoglycemia: Experience of the Diabetes Research in Children Network", *Diabetes Care*, vol. 27, No. 3, 2004, pp. 722-726.
- Turner, A., et al., "Diabetes Mellitus: Biosensors for Research and Management", *Biosensors*, vol. 1, 1985, pp. 85-115.
- Turner, R. F., et al., "A Biocompatible Enzyme Electrode for Continuous in vivo Glucose Monitoring in Whole Blood", *Sensors and Actuators B*, vol. 1, 1990, pp. 561-564.
- Tuzhi, P., et al., "Constant Potential Pretreatment of Carbon Fiber Electrodes for In Vivo Electrochemistry", *Analytical Letters*, vol. 24, No. 6, 1991, pp. 935-945.
- Umana, M., "Protein-Modified Electrochemically Active Biomaterial Surface", *U.S. Army Research Office, Analytical and Chemical Sciences Research Triangle Institute*, 1988, pp. 1-9.
- Updike, S. J., et al., "Principles of Long-Term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose from Inside a Subcutaneous Foreign Body Capsule (FBC)", *Biosensors in the Body: Continuous in vivo Monitoring*, Chapter 4, 1997, pp. 117-137.
- Urban, G., et al., "Miniaturized Thin-Film Biosensors Using Covalently Immobilized Glucose Oxidase", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 555-562.
- Velho, G., et al., "In Vitro and In Vivo Stability of Electrode Potentials in Needle-Type Glucose Sensors", *Diabetes*, vol. 38, No. 2, 1989, pp. 164-171.
- Velho, G., et al., "Strategies for Calibrating a Subcutaneous Glucose Sensor", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 957-964.
- Von Woedtke, T., et al., "In Situ Calibration of Implanted Electrochemical Glucose Sensors", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 943-952.

- Vreeke, M. S., et al., "Hydrogen Peroxide Electrodes Based on Electrical Connection of Redox Centers of Various Peroxidases to Electrodes through a Three-Dimensional Electron-Relaying Polymer Network", *Diagnostic Biosensors Polymers, Chapter 15*, 1993, pp. 180-193.
- Vreeke, M., et al., "Hydrogen Peroxide and β -Nicotinamide Adenine Dinucleotide Sensing Amperometric Electrodes Based on Electrical Connection of Horseradish Peroxidase Redox Centers to Electrodes through a Three-Dimensional Electron Relaying Polymer Network", *Analytical Chemistry*, vol. 64, No. 24, 1992, pp. 3084-3090.
- Wang, D. L., et al., "Miniaturized Flexible Amperometric Lactate Probe", *Analytical Chemistry*, vol. 65, No. 8, 1993, pp. 1069-1073.
- Wang, J., et al., "Activation of Glassy Carbon Electrodes by Alternating Current Electrochemical Treatment", *Analytica Chimica Acta*, vol. 167, 1985, pp. 325-334.
- Wang, J., et al., "Amperometric Biosensing of Organic Peroxides with Peroxidase-Modified Electrodes", *Analytica Chimica Acta*, vol. 254, 1991, pp. 81-88.
- Wang, J., et al., "Screen-Printable Sol-Gel Enzyme-Containing Carbon Inks", *Analytical Chemistry*, vol. 68, No. 15, 1996, pp. 2705-2708.
- Wang, J., et al., "Sol-Gel-Derived Metal-Dispersed Carbon Composite Amperometric Biosensors", *Electroanalysis*, vol. 9, No. 1, 1997, pp. 52-55.
- Williams, D. L., et al., "Electrochemical-Enzymatic Analysis of Blood Glucose and Lactate", *Analytical Chemistry*, vol. 42, No. 1, 1970, pp. 118-121.
- Wilson, G. S., et al., "Progress Toward the Development of an Implantable Sensor for Glucose", *Clinical Chemistry*, vol. 38, No. 9, 1992, pp. 1613-1617.
- Yabuki, S., et al., "Electro-Conductive Enzyme Membrane", *Journal of the Chemical Society, Chemical Communications*, 1989, pp. 945-946.
- Yang, C., et al., "A Comparison of Physical Properties and Fuel Cell Performance of Nafion and Zirconium Phosphate/Nafion Composite Membranes", *Journal of Membrane Science*, vol. 237, 2004, pp. 145-161.
- Yang, L., et al., "Determination of Oxidase Enzyme Substrates Using Cross-Flow Thin-Layer Amperometry", *Electroanalysis*, vol. 8, No. 8-9, 1996, pp. 716-721.
- Yao, S. J., et al., "The Interference of Ascorbate and Urea in Low-Potential Electrochemical Glucose Sensing", *Proceedings of the Twelfth Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 12, Part 2, 1990, pp. 487-489.
- Yao, T., "A Chemically-Modified Enzyme Membrane Electrode as an Amperometric Glucose Sensor", *Analytica Chimica Acta*, vol. 148, 1983, pp. 27-33.
- Ye, L., et al., "High Current Density 'Wired' Quinoprotein Glucose Dehydrogenase Electrode", *Analytical Chemistry*, vol. 65, No. 3, 1993, pp. 238-241.
- Yildiz, a., et al., "Evaluation of an Improved Thin-Layer Electrode", *Analytical Chemistry*, vol. 40, No. 7, 1968, pp. 1018-1024.
- Zamzow, K., et al., "New Wearable Continuous Blood Glucose Monitor (BGM) and Artificial Pancreas (AP)", *Diabetes*, vol. 39, 1990, pp. 5A-20.
- Zhang, Y., et al., "Application of Cell Culture Toxicity Tests to the Development of Implantable Biosensors", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 653-661.
- Zhang, Y., et al., "Elimination of the Acetaminophen Interference in an Implantable Glucose Sensor", *Analytical Chemistry*, vol. 66, No. 7, 1994, pp. 1183-1188.
- PCT Application No. PCT/US2008/063110, International Search Report and Written Opinion of the International Searching Authority mailed Nov. 21, 2008.
- PCT Application No. PCT/US2008/063110, International Preliminary Report on Patentability mailed Nov. 26, 2009.
- U.S. Appl. No. 12/117,665, Office Action mailed Jun. 28, 2010.
- U.S. Appl. No. 12/117,677, Office Action mailed Jun. 9, 2010.
- U.S. Appl. No. 12/117,681, Office Action mailed Apr. 5, 2010.
- U.S. Appl. No. 12/117,681, Office Action mailed Sep. 14, 2010.
- U.S. Appl. No. 12/117,685, Advisory Action mailed Jun. 7, 2010.
- U.S. Appl. No. 12/117,685, Office Action mailed Aug. 16, 2010.
- U.S. Appl. No. 12/117,685, Office Action mailed Mar. 22, 2010.
- U.S. Appl. No. 12/117,685, Office Action mailed Sep. 2, 2009.
- U.S. Appl. No. 12/117,698, Office Action mailed Apr. 5, 2010.
- U.S. Appl. No. 12/117,698, Office Action mailed Sep. 15, 2010.
- U.S. Appl. No. 12/495,219, Office Action mailed Jun. 25, 2010.
- U.S. Appl. No. 12/117,665, Notice of Allowance mailed Feb. 23, 2011.
- U.S. Appl. No. 12/117,665, Office Action mailed Jan. 20, 2011.
- U.S. Appl. No. 12/117,677, Advisory Action mailed Jul. 27, 2011.
- U.S. Appl. No. 12/117,677, Office Action mailed Apr. 14, 2011.
- U.S. Appl. No. 12/117,677, Office Action mailed Nov. 4, 2010.
- U.S. Appl. No. 12/117,685, Office Action mailed Apr. 8, 2011.
- U.S. Appl. No. 12/495,219, Office Action mailed Mar. 8, 2011.

* cited by examiner



100

FIGURE 1




FIGURE 2






FIGURE 3

**FIGURE 4**

**FIGURE 5**




FIGURE 6





FIGURE 7

**FIGURE 8**





FIGURE 9

**FIGURE 10**







FIGURE 11

**FIGURE 12**

**FIGURE 13**

**FIGURE 14**

1

ANALYTE MONITORING SYSTEM AND METHODS

The present application claims is a continuation of U.S. patent application Ser. No. 12/117,681, entitled "Analyte Monitoring System and Methods," filed May 8, 2008, which claims priority under 35 U.S.C. §119(e) to U.S. provisional application No. 60/916,744 filed May 8, 2007, entitled "Analyte Monitoring System and Methods", the disclosures of which is incorporated herein by reference for all purposes.

FIELD OF THE INVENTION

Background of the Invention

Analyte, e.g., glucose monitoring systems including continuous and discrete monitoring systems generally include a small, lightweight battery powered and microprocessor controlled system which is configured to detect signals proportional to the corresponding measured glucose levels using an electrometer. RF signals may be used to transmit the collected data. One aspect of certain analyte monitoring systems include a transcutaneous or subcutaneous analyte sensor configuration which is, for example, at least partially positioned through the skin layer of a subject whose analyte level is to be monitored. The sensor may use a two or three-electrode (work, reference and counter electrodes) configuration driven by a controlled potential (potentiostat) analog circuit connected through a contact system.

An analyte sensor may be configured so that a portion thereof is placed under the skin of the patient so as to contact analyte of the patient, and another portion or segment of the analyte sensor may be in communication with the transmitter unit. The transmitter unit may be configured to transmit the analyte levels detected by the sensor over a wireless communication link such as an RF (radio frequency) communication link to a receiver/monitor unit. The receiver/monitor unit may perform data analysis, among other functions, on the received analyte levels to generate information pertaining to the monitored analyte levels.

Transmission of control or command data over wireless communication link is often constrained to occur within a substantially short time duration. In turn, the time constraint in data communication imposes limits on the type and size of data that may be transmitted during the transmission time period.

In view of the foregoing, it would be desirable to have a method and apparatus for optimizing the RF communication link between two or more communication devices, for example, in a medical communication system

SUMMARY

Devices and methods for analyte monitoring, e.g., glucose monitoring, are provided. Embodiments include transmitting information from a first location to a second, e.g., using a telemetry system such as RF telemetry.

Systems herein include continuous analyte monitoring systems and discrete analyte monitoring system. In one embodiment, a method including detecting a data transmission, incrementing a count associated with the detected data transmission, and storing the count, is disclosed, as well as devices and systems for the same.

These and other objects, features and advantages of the present invention will become more fully apparent from the

2

following detailed description of the embodiments, the appended claims and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a block diagram of a data monitoring and management system for practicing one or more embodiments of the present invention;

FIG. 2 is a block diagram of the transmitter unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention;

FIG. 3 is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention;

FIG. 4 is a flowchart illustrating data packet procedure including rolling data for transmission in accordance with one embodiment of the present invention;

FIG. 5 is a flowchart illustrating data processing of the received data packet including the rolling data in accordance with one embodiment of the present invention;

FIG. 6 is a block diagram illustrating the sensor unit and the transmitter unit of the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 7 is a flowchart illustrating data communication using close proximity commands in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 8 is a flowchart illustrating sensor insertion detection routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 9 is a flowchart illustrating sensor removal detection routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 10 is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 11 is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. 1 in accordance with another embodiment of the present invention;

FIG. 12 is a flowchart illustrating the power supply determination in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 13 is a flowchart illustrating close proximity command for RF communication control in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention; and

FIG. 14 is a flowchart illustrating analyte sensor identification routine in accordance with one embodiment of the present invention

DETAILED DESCRIPTION OF THE EMBODIMENTS

As summarized above and as described in further detail below, in accordance with the various embodiments of the present invention, there is provided a method and system detecting a data transmission, incrementing a count associated with the detected data transmission, and storing the count.

FIG. 1 illustrates a data monitoring and management system such as, for example, analyte (e.g., glucose) monitoring

3

system **100** in accordance with one embodiment of the present invention. The subject invention is further described primarily with respect to a glucose monitoring system for convenience and such description is in no way intended to limit the scope of the invention. It is to be understood that the analyte monitoring system may be configured to monitor a variety of analytes, e.g., lactate, and the like.

Analytes that may be monitored include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and tropoin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be monitored. More than one analyte may be monitored by a single system, e.g. a single analyte sensor.

The analyte monitoring system **100** includes a sensor unit **101**, a transmitter unit **102** coupleable to the sensor unit **101**, and a primary receiver unit **104** which is configured to communicate with the transmitter unit **102** via a bi-directional communication link **103**. The primary receiver unit **104** may be further configured to transmit data to a data processing terminal **105** for evaluating the data received by the primary receiver unit **104**. Moreover, the data processing terminal **105** in one embodiment may be configured to receive data directly from the transmitter unit **102** via a communication link which may optionally be configured for bi-directional communication. Accordingly, transmitter unit **102** and/or receiver unit **104** may include a transceiver.

Also shown in FIG. 1 is an optional secondary receiver unit **106** which is operatively coupled to the communication link and configured to receive data transmitted from the transmitter unit **102**. Moreover, as shown in the Figure, the secondary receiver unit **106** is configured to communicate with the primary receiver unit **104** as well as the data processing terminal **105**. Indeed, the secondary receiver unit **106** may be configured for bidirectional wireless communication with each or one of the primary receiver unit **104** and the data processing terminal **105**. As discussed in further detail below, in one embodiment of the present invention, the secondary receiver unit **106** may be configured to include a limited number of functions and features as compared with the primary receiver unit **104**. As such, the secondary receiver unit **106** may be configured substantially in a smaller compact housing or embodied in a device such as a wrist watch, pager, mobile phone, PDA, for example. Alternatively, the secondary receiver unit **106** may be configured with the same or substantially similar functionality as the primary receiver unit **104**. The receiver unit may be configured to be used in conjunction with a docking cradle unit, for example for one or more of the following or other functions: placement by bedside, for re-charging, for data management, for night time monitoring, and/or bidirectional communication device.

In one aspect sensor unit **101** may include two or more sensors, each configured to communicate with transmitter unit **102**. Furthermore, while only one, transmitter unit **102**, communication link **103**, and data processing terminal **105** are shown in the embodiment of the analyte monitoring system **100** illustrated in FIG. 1. However, it will be appreciated by one of ordinary skill in the art that the analyte monitoring system **100** may include one or more sensors, multiple transmitter units **102**, communication links **103**, and data processing terminals **105**. Moreover, within the scope of the present invention, the analyte monitoring system **100** may be a continuous monitoring system, or semi-continuous, or a discrete

4

monitoring system. In a multi-component environment, each device is configured to be uniquely identified by each of the other devices in the system so that communication conflict is readily resolved between the various components within the analyte monitoring system **100**.

In one embodiment of the present invention, the sensor unit **101** is physically positioned in or on the body of a user whose analyte level is being monitored. The sensor unit **101** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level into a corresponding data signal for transmission by the transmitter unit **102**. In certain embodiments, the transmitter unit **102** may be physically coupled to the sensor unit **101** so that both devices are integrated in a single housing and positioned on the user's body. The transmitter unit **102** may perform data processing such as filtering and encoding on data signals and/or other functions, each of which corresponds to a sampled analyte level of the user, and in any event transmitter unit **102** transmits analyte information to the primary receiver unit **104** via the communication link **103**.

In one embodiment, the analyte monitoring system **100** is configured as a one-way RF communication path from the transmitter unit **102** to the primary receiver unit **104**. In such embodiment, the transmitter unit **102** transmits the sampled data signals received from the sensor unit **101** without acknowledgement from the primary receiver unit **104** that the transmitted sampled data signals have been received. For example, the transmitter unit **102** may be configured to transmit the encoded sampled data signals at a fixed rate (e.g., at one minute intervals) after the completion of the initial power on procedure. Likewise, the primary receiver unit **104** may be configured to detect such transmitted encoded sampled data signals at predetermined time intervals. Alternatively, the analyte monitoring system **100** may be configured with a bi-directional RF (or otherwise) communication between the transmitter unit **102** and the primary receiver unit **104**.

Additionally, in one aspect, the primary receiver unit **104** may include two sections. The first section is an analog interface section that is configured to communicate with the transmitter unit **102** via the communication link **103**. In one embodiment, the analog interface section may include an RF receiver and an antenna for receiving and amplifying the data signals from the transmitter unit **102**, which are thereafter, demodulated with a local oscillator and filtered through a band-pass filter. The second section of the primary receiver unit **104** is a data processing section which is configured to process the data signals received from the transmitter unit **102** such as by performing data decoding, error detection and correction, data clock generation, and data bit recovery.

In operation, upon completing the power-on procedure, the primary receiver unit **104** is configured to detect the presence of the transmitter unit **102** within its range based on, for example, the strength of the detected data signals received from the transmitter unit **102** and/or a predetermined transmitter identification information. Upon successful synchronization with the corresponding transmitter unit **102**, the primary receiver unit **104** is configured to begin receiving from the transmitter unit **102** data signals corresponding to the user's detected analyte level. More specifically, the primary receiver unit **104** in one embodiment is configured to perform synchronized time hopping with the corresponding synchronized transmitter unit **102** via the communication link **103** to obtain the user's detected analyte level.

Referring again to FIG. 1, the data processing terminal **105** may include a personal computer, a portable computer such as a laptop or a handheld device (e.g., personal digital assistants (PDAs)), and the like, each of which may be configured for

5

data communication with the receiver via a wired or a wireless connection. Additionally, the data processing terminal **105** may further be connected to a data network (not shown) for storing, retrieving and updating data corresponding to the detected analyte level of the user.

Within the scope of the present invention, the data processing terminal **105** may include an infusion device such as an insulin infusion pump (external or implantable) or the like, which may be configured to administer insulin to patients, and which may be configured to communicate with the receiver unit **104** for receiving, among others, the measured analyte level. Alternatively, the receiver unit **104** may be configured to integrate or otherwise couple to an infusion device therein so that the receiver unit **104** is configured to administer insulin therapy to patients, for example, for administering and modifying basal profiles, as well as for determining appropriate boluses for administration based on, among others, the detected analyte levels received from the transmitter unit **102**.

Additionally, the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may each be configured for bi-directional wireless communication such that each of the transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may be configured to communicate (that is, transmit data to and receive data from) with each other via the wireless communication link **103**. More specifically, the data processing terminal **105** may in one embodiment be configured to receive data directly from the transmitter unit **102** via the communication link **106**, where the communication link **106**, as described above, may be configured for bi-directional communication.

In this embodiment, the data processing terminal **105** which may include an insulin pump, may be configured to receive the analyte signals from the transmitter unit **102**, and thus, incorporate the functions of the receiver **103** including data processing for managing the patient's insulin therapy and analyte monitoring. In one embodiment, the communication link **103** may include one or more of an RF communication protocol, an infrared communication protocol, a Bluetooth enabled communication protocol, an 802.11x wireless communication protocol, or an equivalent wireless communication protocol which would allow secure, wireless communication of several units (for example, per HIPPA requirements) while avoiding potential data collision and interference.

FIG. 2 is a block diagram of the transmitter of the data monitoring and detection system shown in FIG. 1 in accordance with one embodiment of the present invention. Referring to the Figure, the transmitter unit **102** in one embodiment includes an analog interface **201** configured to communicate with the sensor unit **101** (FIG. 1), a user input **202**, and a temperature detection section **203**, each of which is operatively coupled to a transmitter processor **204** such as a central processing unit (CPU). As can be seen from FIG. 2, there are provided four contacts, three of which are electrodes—work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213**, each operatively coupled to the analog interface **201** of the transmitter unit **102** for connection to the sensor unit **101** (FIG. 1). In one embodiment, each of the work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213** may be made using a conductive material that is either printed or etched or ablated, for example, such as carbon which may be printed, or a metal such as a metal foil (e.g., gold) or the like, which may be etched or ablated or otherwise

6

processed to provide one or more electrodes. Fewer or greater electrodes and/or contact may be provided in certain embodiments.

Further shown in FIG. 2 are a transmitter serial communication section **205** and an RF transmitter **206**, each of which is also operatively coupled to the transmitter processor **204**. Moreover, a power supply **207** such as a battery is also provided in the transmitter unit **102** to provide the necessary power for the transmitter unit **102**. Additionally, as can be seen from the Figure, clock **208** is provided to, among others, supply real time information to the transmitter processor **204**.

In one embodiment, a unidirectional input path is established from the sensor unit **101** (FIG. 1) and/or manufacturing and testing equipment to the analog interface **201** of the transmitter unit **102**, while a unidirectional output is established from the output of the RF transmitter **206** of the transmitter unit **102** for transmission to the primary receiver unit **104**. In this manner, a data path is shown in FIG. 2 between the aforementioned unidirectional input and output via a dedicated link **209** from the analog interface **201** to serial communication section **205**, thereafter to the processor **204**, and then to the RF transmitter **206**. As such, in one embodiment, via the data path described above, the transmitter unit **102** is configured to transmit to the primary receiver unit **104** (FIG. 1), via the communication link **103** (FIG. 1), processed and encoded data signals received from the sensor unit **101** (FIG. 1). Additionally, the unidirectional communication data path between the analog interface **201** and the RF transmitter **206** discussed above allows for the configuration of the transmitter unit **102** for operation upon completion of the manufacturing process as well as for direct communication for diagnostic and testing purposes.

As discussed above, the transmitter processor **204** is configured to transmit control signals to the various sections of the transmitter unit **102** during the operation of the transmitter unit **102**. In one embodiment, the transmitter processor **204** also includes a memory (not shown) for storing data such as the identification information for the transmitter unit **102**, as well as the data signals received from the sensor unit **101**. The stored information may be retrieved and processed for transmission to the primary receiver unit **104** under the control of the transmitter processor **204**. Furthermore, the power supply **207** may include a commercially available battery, which may be a rechargeable battery.

In certain embodiments, the transmitter unit **102** is also configured such that the power supply section **207** is capable of providing power to the transmitter for a minimum of about three months of continuous operation, e.g., after having been stored for about eighteen months such as stored in a low-power (non-operating) mode. In one embodiment, this may be achieved by the transmitter processor **204** operating in low power modes in the non-operating state, for example, drawing no more than approximately 1 .mu.A of current. Indeed, in one embodiment, a step during the manufacturing process of the transmitter unit **102** may place the transmitter unit **102** in the lower power, non-operating state (i.e., post-manufacture sleep mode). In this manner, the shelf life of the transmitter unit **102** may be significantly improved. Moreover, as shown in FIG. 2, while the power supply unit **207** is shown as coupled to the processor **204**, and as such, the processor **204** is configured to provide control of the power supply unit **207**, it should be noted that within the scope of the present invention, the power supply unit **207** is configured to provide the necessary power to each of the components of the transmitter unit **102** shown in FIG. 2.

Referring back to FIG. 2, the power supply section **207** of the transmitter unit **102** in one embodiment may include a

rechargeable battery unit that may be recharged by a separate power supply recharging unit (for example, provided in the receiver unit **104**) so that the transmitter unit **102** may be powered for a longer period of usage time. Moreover, in one embodiment, the transmitter unit **102** may be configured without a battery in the power supply section **207**, in which case the transmitter unit **102** may be configured to receive power from an external power supply source (for example, a battery) as discussed in further detail below.

Referring yet again to FIG. 2, the temperature detection section **203** of the transmitter unit **102** is configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust the analyte readings obtained from the analog interface **201**. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 315 MHz to approximately 322 MHz, for example, in the United States. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 400 MHz to approximately 470 MHz. Further, in one embodiment, the RF transmitter **206** is configured to modulate the carrier frequency by performing Frequency Shift Keying and Manchester encoding. In one embodiment, the data transmission rate is about 19,200 symbols per second, with a minimum transmission range for communication with the primary receiver unit **104**.

Referring yet again to FIG. 2, also shown is a leak detection circuit **214** coupled to the guard electrode (G) **211** and the processor **204** in the transmitter unit **102** of the data monitoring and management system **100**. The leak detection circuit **214** in accordance with one embodiment of the present invention may be configured to detect leakage current in the sensor unit **101** to determine whether the measured sensor data are corrupt or whether the measured data from the sensor **101** is accurate. Describe sensor, calibration (single point), etc. Exemplary analyte systems that may be employed are described in, for example, U.S. Pat. Nos. 6,134,461, 6,175, 752, 6,121,611, 6,560,471, 6,746,582, and elsewhere, the disclosure of each of which are incorporated by reference for all purposes.

FIG. 3 is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 3, the primary receiver unit **104** includes an analyte test strip, e.g., blood glucose test strip, interface **301**, an RF receiver **302**, an input **303**, a temperature detection section **304**, and a clock **305**, each of which is operatively coupled to a receiver processor **307**. As can be further seen from the Figure, the primary receiver unit **104** also includes a power supply **306** operatively coupled to a power conversion and monitoring section **308**. Further, the power conversion and monitoring section **308** is also coupled to the receiver processor **307**. Moreover, also shown are a receiver serial communication section **309**, and an output **310**, each operatively coupled to the receiver processor **307**.

In one embodiment, the test strip interface **301** includes a glucose level testing portion to receive a manual insertion of a glucose test strip, and thereby determine and display the glucose level of the test strip on the output **310** of the primary receiver unit **104**. This manual testing of glucose may be used to calibrate the sensor unit **101** or otherwise. The RF receiver **302** is configured to communicate, via the communication link **103** (FIG. 1) with the RF transmitter **206** of the transmitter unit **102**, to receive encoded data signals from the transmitter unit **102** for, among others, signal mixing, demodulation, and other data processing. The input **303** of the primary

receiver unit **104** is configured to allow the user to enter information into the primary receiver unit **104** as needed. In one aspect, the input **303** may include one or more keys of a keypad, a touch-sensitive screen, or a voice-activated input command unit. The temperature detection section **304** is configured to provide temperature information of the primary receiver unit **104** to the receiver processor **307**, while the clock **305** provides, among others, real time information to the receiver processor **307**.

Each of the various components of the primary receiver unit **104** shown in FIG. 3 is powered by the power supply **306** which, in one embodiment, includes a battery. Furthermore, the power conversion and monitoring section **308** is configured to monitor the power usage by the various components in the primary receiver unit **104** for effective power management and to alert the user, for example, in the event of power usage which renders the primary receiver unit **104** in sub-optimal operating conditions. An example of such sub-optimal operating condition may include, for example, operating the vibration output mode (as discussed below) for a period of time thus substantially draining the power supply **306** while the processor **307** (thus, the primary receiver unit **104**) is turned on. Moreover, the power conversion and monitoring section **308** may additionally be configured to include a reverse polarity protection circuit such as a field effect transistor (FET) configured as a battery activated switch.

The serial communication section **309** in the primary receiver unit **104** is configured to provide a bi-directional communication path from the testing and/or manufacturing equipment for, among others, initialization, testing, and configuration of the primary receiver unit **104**. Serial communication section **104** can also be used to upload data to a computer, such as time-stamped blood glucose data. The communication link with an external device (not shown) can be made, for example, by cable, infrared (IR) or RF link. The output **310** of the primary receiver unit **104** is configured to provide, among others, a graphical user interface (GUI) such as a liquid crystal display (LCD) for displaying information. Additionally, the output **310** may also include an integrated speaker for outputting audible signals as well as to provide vibration output as commonly found in handheld electronic devices, such as mobile telephones presently available. In a further embodiment, the primary receiver unit **104** also includes an electro-luminescent lamp configured to provide backlighting to the output **310** for output visual display in dark ambient surroundings.

Referring back to FIG. 3, the primary receiver unit **104** in one embodiment may also include a storage section such as a programmable, non-volatile memory device as part of the processor **307**, or provided separately in the primary receiver unit **104**, operatively coupled to the processor **307**. The processor **307** may be configured to synchronize with a transmitter, e.g., using Manchester decoding or the like, as well as error detection and correction upon the encoded data signals received from the transmitter unit **102** via the communication link **103**.

Additional description of the RF communication between the transmitter **102** and the primary receiver **104** (or with the secondary receiver **106**) that may be employed in embodiments of the subject invention is disclosed in pending application Ser. No. 11/060,365 filed Feb. 16, 2005 entitled "Method and System for Providing Data Communication in Continuous Glucose Monitoring and Management System" the disclosure of which is incorporated herein by reference for all purposes.

Referring to the Figures, in one embodiment, the transmitter **102** (FIG. 1) may be configured to generate data packets

for periodic transmission to one or more of the receiver units **104, 106**, where each data packet includes in one embodiment two categories of data—urgent data and non-urgent data. For example, urgent data such as for example glucose data from the sensor and/or temperature data associated with the sensor may be packed in each data packet in addition to non-urgent data, where the non-urgent data is rolled or varied with each data packet transmission.

That is, the non-urgent data is transmitted at a timed interval so as to maintain the integrity of the analyte monitoring system without being transmitted over the RF communication link with each data transmission packet from the transmitter **102**. In this manner, the non-urgent data, for example that are not time sensitive, may be periodically transmitted (and not with each data packet transmission) or broken up into predetermined number of segments and sent or transmitted over multiple packets, while the urgent data is transmitted substantially in its entirety with each data transmission.

Referring again to the Figures, upon receiving the data packets from the transmitter **102**, the one or more receiver units **104, 106** may be configured to parse the received the data packet to separate the urgent data from the non-urgent data, and also, may be configured to store the urgent data and the non-urgent data, e.g., in a hierarchical manner. In accordance with the particular configuration of the data packet or the data transmission protocol, more or less data may be transmitted as part of the urgent data, or the non-urgent rolling data. That is, within the scope of the present disclosure, the specific data packet implementation such as the number of bits per packet, and the like, may vary based on, among others, the communication protocol, data transmission time window, and so on.

In an exemplary embodiment, different types of data packets may be identified accordingly. For example, identification in certain exemplary embodiments may include—(1) single sensor, one minute of data, (2) two or multiple sensors, (3) dual sensor, alternate one minute data, and (4) response packet. For single sensor one minute data packet, in one embodiment, the transmitter **102** may be configured to generate the data packet in the manner, or similar to the manner, shown in Table 1 below.

TABLE 1

Single sensor, Data Field	
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 1 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling Data-1

As shown in Table 1 above, the transmitter data packet in one embodiment may include 8 bits of transmit time data, 14 bits of current sensor data, 14 bits of preceding sensor data, 8 bits of transmitter status data, 12 bits of auxiliary counter data, 12 bits of auxiliary thermistor 1 data, 12 bits of auxiliary thermistor 2 data and 8 bits of rolling data. In one embodiment of the present invention, the data packet generated by the transmitter for transmission over the RF communication link may include all or some of the data shown above in Table 1.

Referring back, the 14 bits of the current sensor data provides the real time or current sensor data associated with the detected analyte level, while the 14 bits of the sensor historic

or preceding sensor data includes the sensor data associated with the detected analyte level one minute ago. In this manner, in the case where the receiver unit **104, 106** drops or fails to successfully receive the data packet from the transmitter **102** in the minute by minute transmission, the receiver unit **104, 106** may be able to capture the sensor data of a prior minute transmission from a subsequent minute transmission.

Referring again to Table 1, the Auxiliary data in one embodiment may include one or more of the patient's skin temperature data, a temperature gradient data, reference data, and counter electrode voltage. The transmitter status field may include status data that is configured to indicate corrupt data for the current transmission (for example, if shown as BAD status (as opposed to GOOD status which indicates that the data in the current transmission is not corrupt)). Furthermore, the rolling data field is configured to include the non-urgent data, and in one embodiment, may be associated with the time-hop sequence number. In addition, the Transmitter Time field in one embodiment includes a protocol value that is configured to start at zero and is incremented by one with each data packet. In one aspect, the transmitter time data may be used to synchronize the data transmission window with the receiver unit **104, 106**, and also, provide an index for the Rolling data field.

In a further embodiment, the transmitter data packet may be configured to provide or transmit analyte sensor data from two or more independent analyte sensors. The sensors may relate to the same or different analyte or property. In such a case, the data packet from the transmitter **102** may be configured to include 14 bits of the current sensor data from both sensors in the embodiment in which 2 sensors are employed. In this case, the data packet does not include the immediately preceding sensor data in the current data packet transmission. Instead, a second analyte sensor data is transmitted with a first analyte sensor data.

TABLE 2

Dual Sensor Data	
8	Transmit Time
14	Sensor 1 Current Data
14	Sensor 2 Current Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling Data 1

In a further embodiment, the transmitter data packet may be alternated with each transmission between two analyte sensors, for example, alternating between the data packet shown in Table 3 and Table 4 below.

TABLE 3

Sensor Data Packet Alternate 1	
8	Transmitter Time
14	Sensor 1 Current Data
14	Sensor 1 Historic Data
8	Transmit Status
12	AUX Counter
12	AUX Thermistor 1
12	AUX Thermistor 2
8	Rolling Data 1

11

TABLE 4

Sensor Data Packet Alternate 2		
8	Transmit Time	
14	Sensor 1 Current Data	
14	Sensor 2 Current Data	
8	Transmit Status	
12	AUX Counter	
12	AUX Thermistor 1	
12	AUX Thermistor 2	
8	Rolling Data 1	

As shown above in reference to Tables 3 and 4, the minute by minute data packet transmission from the transmitter **102** (FIG. 1) in one embodiment may alternate between the data packet shown in Table 3 and the data packet shown in Table 4. More specifically, the transmitter **102** may be configured in one embodiment transmit the current sensor data of the first sensor and the preceding sensor data of the first sensor (Table 3), as well as the rolling data, and further, at the subsequent transmission, the transmitter **102** may be configured to transmit the current sensor data of the first and the second sensor in addition to the rolling data.

In one embodiment, the rolling data transmitted with each data packet may include a sequence of various predetermined types of data that are considered not-urgent or not time sensitive. That is, in one embodiment, the following list of data shown in Table 5 may be sequentially included in the 8 bits of transmitter data packet, and not transmitted with each data packet transmission of the transmitter (for example, with each 60 second data transmission from the transmitter **102**).

TABLE 5

Rolling Data		
Time Slot	Bits	Rolling Data
0	8	Mode
1	8	Glucose 1 Slope
2	8	Glucose 2 Slope
3	8	Ref-R
4	8	Hobbs Counter, Ref-R
5	8	Hobbs Counter
6	8	Hobbs Counter
7	8	Sensor Count

As can be seen from Table 5 above, in one embodiment, a sequence of rolling data are appended or added to the transmitter data packet with each data transmission time slot. In one embodiment, there may be 256 time slots for data transmission by the transmitter **102** (FIG. 1), and where, each time slot is separately by approximately 60 second interval. For example, referring to the Table 5 above, the data packet in transmission time slot **0** (zero) may include operational mode data (Mode) as the rolling data that is appended to the transmitted data packet. At the subsequent data transmission time slot (for example, approximately 60 seconds after the initial time slot **0**), the transmitted data packet may include the analyte sensor **1** calibration factor information (Glucose1 slope) as the rolling data. In this manner, with each data transmission, the rolling data may be updated over the 256 time slot cycle.

Referring again to Table 5, each rolling data field is described in further detail for various embodiments. For example, the Mode data may include information related to the different operating modes such as, but not limited to, the data packet type, the type of battery used, diagnostic routines, single sensor or multiple sensor input, type of data transmis-

12

sion (rf communication link or other data link such as serial connection). Further, the Glucose1-slope data may include an 8-bit scaling factor or calibration data for first sensor (scaling factor for sensor **1** data), while Glucose2-slope data may include an 8-bit scaling factor or calibration data for the second analyte sensor (in the embodiment including more than one analyte sensors).

In addition, the Ref-R data may include 12 bits of on-board reference resistor used to calibrate our temperature measurement in the thermistor circuit (where 8 bits are transmitted in time slot **3**, and the remaining 4 bits are transmitted in time slot **4**), and the 20-bit Hobbs counter data may be separately transmitted in three time slots (for example, in time slot **4**, time slot **5** and time slot **6**) to add up to 20 bits. In one embodiment, the Hobbs counter may be configured to count each occurrence of the data transmission (for example, a packet transmission at approximately 60 second intervals) and may be incremented by a count of one (1).

In one aspect, the Hobbs counter is stored in a nonvolatile memory of the transmitter unit **102** (FIG. 1) and may be used to ascertain the power supply status information such as, for example, the estimated battery life remaining in the transmitter unit **102**. That is, with each sensor replacement, the Hobbs counter is not reset, but rather, continues the count with each replacement of the sensor unit **101** to establish contact with the transmitter unit **102** such that, over an extended usage time period of the transmitter unit **102**, it may be possible to determine, based on the Hobbs count information, the amount of consumed battery life in the transmitter unit **102**, and also, an estimated remaining life of the battery in the transmitter unit **102**.

That is, in one embodiment, the 20 bit Hobbs counter is incremented by one each time the transmitter unit **102** transmits a data packet (for example, approximately each 60 seconds), and based on the count information in the Hobbs counter, in one aspect, the battery life of the transmitter unit **102** may be estimated. In this manner, in configurations of the transmitter unit **620** (see FIG. 6) where the power supply is not a replaceable component but rather, embedded within the housing the transmitter unit **620**, it is possible to estimate the remaining life of the embedded battery within the transmitter unit **620**. Moreover, the Hobbs counter is configured to remain persistent in the memory device of the transmitter unit **620** such that, even when the transmitter unit power is turned off or powered down (for example, during the periodic sensor unit replacement, RF transmission turned off period and the like), the Hobbs counter information is retained.

Referring to Table 5 above, the transmitted rolling data may also include 8 bits of sensor count information (for example, transmitted in time slot **7**). The 8 bit sensor counter is incremented by one each time a new sensor unit is connected to the transmitter unit. The ASIC configuration of the transmitter unit (or a microprocessor based transmitter configuration or with discrete components) may be configured to store in a nonvolatile memory unit the sensor count information and transmit it to the primary receiver unit **104** (for example). In turn, the primary receiver unit **104** (and/or the secondary receiver unit **106**) may be configured to determine whether it is receiving data from the transmitter unit that is associated with the same sensor unit (based on the sensor count information), or from a new or replaced sensor unit (which will have a sensor count incremented by one from the prior sensor count). In this manner, in one aspect, the receiver unit (primary or secondary) may be configured to prevent reuse of the same sensor unit by the user based on verifying the sensor count information associated with the data transmission received from the transmitter unit **102**. In addition, in

13

a further aspect, user notification may be associated with one or more of these parameters. Further, the receiver unit (primary or secondary) may be configured to detect when a new sensor has been inserted, and thus prevent erroneous application of one or more calibration parameters determined in conjunction with a prior sensor, that may potentially result in false or inaccurate analyte level determination based on the sensor data.

FIG. 4 is a flowchart illustrating a data packet procedure including rolling data for transmission in accordance with one embodiment of the present invention. Referring to FIG. 4, in one embodiment, a counter is initialized (for example, to T=0) (410). Thereafter the associated rolling data is retrieved from memory device, for example (420), and also, the time sensitive or urgent data is retrieved (430). In one embodiment, the retrieval of the rolling data (420) and the retrieval of the time sensitive data (430) may be retrieved at substantially the same time.

Referring back to FIG. 4, with the rolling data and the time sensitive data, for example, the data packet for transmission is generated (440), an upon transmission, the counter is incremented by one and the routine returns to retrieval of the rolling data (420). In this manner, in one embodiment, the urgent time sensitive data as well as the non-urgent data may be incorporated in the same data packet and transmitted by the transmitter 102 (FIG. 1) to a remote device such as one or more of the receivers 104, 106. Furthermore, as discussed above, the rolling data may be updated at a predetermined time interval which is longer than the time interval for each data packet transmission from the transmitter 102 (FIG. 1).

FIG. 5 is a flowchart illustrating data processing of the received data packet including the rolling data in accordance with one embodiment of the present invention. Referring to FIG. 5, when the data packet is received (510) (for example, by one or more of the receivers 104, 106, in one embodiment the received data packet is parsed so that the urgent data may be separated from the not-urgent data (stored in, for example, the rolling data field in the data packet). Thereafter the parsed data is suitably stored in an appropriate memory or storage device (530).

In the manner described above, in accordance with one embodiment of the present invention, there is provided method and apparatus for separating non-urgent type data (for example, data associated with calibration) from urgent type data (for example, monitored analyte related data) to be transmitted over the communication link to minimize the potential burden or constraint on the available transmission time. More specifically, in one embodiment, non-urgent data may be separated from data that is required by the communication system to be transmitted immediately, and transmitted over the communication link together while maintaining a minimum transmission time window. In one embodiment, the non-urgent data may be parsed or broken up in to a number of data segments, and transmitted over multiple data packets. The time sensitive immediate data (for example, the analyte sensor data, temperature data etc), may be transmitted over the communication link substantially in its entirety with each data packet or transmission.

FIG. 6 is a block diagram illustrating the sensor unit and the transmitter unit of the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 6, in one aspect, a transmitter unit 620 is provided in a substantially water tight and sealed housing. The transmitter unit 620 includes respective contacts (wrk, Ref, Cntr, and gnd) for respectively establishing electrical contact with one or more of the working electrode, the reference electrode, the counter electrode and the

14

ground terminal (or guard trace) of the sensor unit 610. Also shown in FIG. 6 is a conductivity bar/trace 611 provided on the sensor unit 610. For example, in one embodiment, the conductivity bar/trace 611 may comprise a carbon trace on a substrate layer of the sensor unit 610. In this manner, in one embodiment, when the sensor unit 610 is coupled to the transmitter unit 620, electrical contact is established, for example, via the conductivity bar/trace 611 between the contact pads or points of the transmitter unit 620 (for example, at the counter electrode contact (cntr) and the ground terminal contact (gnd) such that the transmitter unit 620 may be powered for data communication.

That is, during manufacturing of the transmitter unit 620, in one aspect, the transmitter unit 620 is configured to include a power supply such as battery 621. Further, during the initial non-use period (e.g., post manufacturing sleep mode), the transmitter unit 620 is configured such that it is not used and thus drained by the components of the transmitter unit 620. During the sleep mode, and prior to establishing electrical contact with the sensor unit 610 via the conductivity bar/trace 611, the transmitter unit 620 is provided with a low power signal from, for example, a low power voltage comparator 622, via an electronic switch 623 to maintain the low power state of, for example, the transmitter unit 620 components. Thereafter, upon connection with the sensor unit 610, and establishing electrical contact via the conductivity bar/trace 611, the embedded power supply 621 of the transmitter unit 620 is activated or powered up so that some of all of the components of the transmitter unit 620 are configured to receive the necessary power signals for operations related to, for example, data communication, processing and/or storage.

In one aspect, since the transmitter unit 620 is configured to a sealed housing without a separate replaceable battery compartment, in this manner, the power supply of the battery 621 is preserved during the post manufacturing sleep mode prior to use.

In a further aspect, the transmitter unit 620 may be disposed or positioned on a separate on-body mounting unit that may include, for example, an adhesive layer (on its bottom surface) to firmly retain the mounting unit on the skin of the user, and which is configured to receive or firmly position the transmitter unit 620 on the mounting unit during use. In one aspect, the mounting unit may be configured to at least partially retain the position of the sensor unit 610 in a transcutaneous manner so that at least a portion of the sensor unit is in fluid contact with the analyte of the user. Example embodiments of the mounting or base unit and its cooperation or coupling with the transmitter unit are provided, for example, in U.S. Pat. No. 6,175,752, incorporated herein by reference for all purposes.

In such a configuration, the power supply for the transmitter unit 620 may be provided within the housing of the mounting unit such that, the transmitter unit 620 may be configured to be powered on or activated upon placement of the transmitter unit 620 on the mounting unit and in electrical contact with the sensor unit 610. For example, the sensor unit 610 may be provided pre-configured or integrated with the mounting unit and the insertion device such that, the user may position the sensor unit 610 on the skin layer of the user using the insertion device coupled to the mounting unit. Thereafter, upon transcutaneous positioning of the sensor unit 610, the insertion device may be discarded or removed from the mounting unit, leaving behind the transcutaneously positioned sensor unit 610 and the mounting unit on the skin surface of the user.

Thereafter, when the transmitter unit 620 is positioned on, over or within the mounting unit, the battery or power supply

15

provided within the mounting unit is configured to electrically couple to the transmitter unit **620** and/or the sensor unit **610**.

Given that the sensor unit **610** and the mounting unit are provided as replaceable components for replacement every 3, 5, 7 days or other predetermined time periods, the user is conveniently not burdened with verifying the status of the power supply providing power to the transmitter unit **620** during use. That is, with the power supply or battery replaced with each replacement of the sensor unit **610**, a new power supply or battery will be provided with the new mounting unit for use with the transmitter unit **620**.

Referring to FIG. 6 again, in one aspect, when the sensor unit **610** is removed from the transmitter unit **620** (or vice versa), the electrical contact is broken and the conductivity bar/trace **611** returns to an open circuit. In this case, the transmitter unit **620** may be configured, to detect such condition and generate a last gasp transmission sent to the primary receiver unit **104** (and/or the secondary receiver unit **106**) indicating that the sensor unit **610** is disconnected from the transmitter unit **620**, and that the transmitter unit **620** is entering a powered down (or low power off) state. And the transmitter unit **620** is powered down into the sleep mode since the connection to the power supply (that is embedded within the transmitter unit **620** housing) is broken.

In this manner, in one aspect, the processor **624** of the transmitter unit **620** may be configured to generate the appropriate one or more data or signals associated with the detection of sensor unit **610** disconnection for transmission to the receiver unit **104** (FIG. 1), and also, to initiate the power down procedure of the transmitter unit **620**. In one aspect, the components of the transmitter unit **620** may be configured to include application specific integrated circuit (ASIC) design with one or more state machines and one or more nonvolatile and/or volatile memory units such as, for example, EEPROMs and the like.

Referring again to FIGS. 1 and 6, in one embodiment, the communication between the transmitter unit **620** (or **102** of FIG. 1) and the primary receiver unit **104** (and/or the secondary receiver unit **106**) may be based on close proximity communication where bi-directional (or uni-directional) wireless communication is established when the devices are physically located in close proximity to each other. That is, in one embodiment, the transmitter unit **620** may be configured to receive very short range commands from the primary receiver unit **104** (FIG. 1) and perform one or more specific operations based on the received commands from the receiver unit **104**.

In one embodiment, to maintain secure communication between the transmitter unit and the data receiver unit, the transmitter unit ASIC may be configured to generate a unique close proximity key at power on or initialization. In one aspect, the 4 or 8 bit key may be generated based on, for example, the transmitter unit identification information, and which may be used to prevent undesirable or unintended communication. In a further aspect, the close proximity key may be generated by the receiver unit based on, for example, the transmitter identification information received by the transmitter unit during the initial synchronization or pairing procedure of the transmitter and the receiver units.

Referring again to FIGS. 1 and 6, in one embodiment, the transmitter unit ASIC configuration may include a 32 KHz oscillator and a counter which may be configured to drive the state machine in the transmitter unit ASIC. The transmitter ASIC configuration may include a plurality of close proximity communication commands including, for example, new sensor initiation, pairing with the receiver unit, and RF communication control, among others. For example, when a new

16

sensor unit is positioned and coupled to the transmitter unit so that the transmitter unit is powered on, the transmitter unit is configured to detect or receive a command from the receiver unit positioned in close proximity to the transmitter unit. For example, the receiver unit may be positioned within a couple of inches from the on-body position of the transmitter unit, and when the user activates or initiates a command associated with the new sensor initiation from the receiver unit, the transmitter unit is configured to receive the command from the receiver and, in its response data packet, transmit, among others, its identification information back to the receiver unit.

In one embodiment, the initial sensor unit initiation command does not require the use of the close proximity key. However, other predefined or preconfigured close-proximity commands may be configured to require the use of the 8 bit key (or a key of a different number of bits). For example, in one embodiment, the receiver unit may be configured to transmit a RF on/off command to turn on/off the RF communication module or unit in the transmitter unit **102**. Such RF on/off command in one embodiment includes the close proximity key as part of the transmitted command for reception by the transmitter unit.

During the period that the RF communication module or unit is turned off based on the received close proximity command, the transmitter unit does not transmit any data, including any glucose related data. In one embodiment, the glucose related data from the sensor unit which are not transmitted by the transmitter unit during the time period when the RF communication module or unit of the transmitter unit is turned off may be stored in a memory or storage unit of the transmitter unit for subsequent transmission to the receiver unit when the transmitter unit RF communication module or unit is turned back on based on the RF-on command from the receiver unit. In this manner, in one embodiment, the transmitter unit may be powered down (temporarily, for example, during air travel) without removing the transmitter unit from the on-body position.

FIG. 7 is a flowchart illustrating data communication using close proximity commands in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 7, the primary receiver unit **104** (FIG. 1) in one aspect may be configured to retrieve or generate a close proximity command (**710**) for transmission to the transmitter unit **102**. To establish the transmission range (**720**), the primary receiver unit **104** may be positioned physically close to (that is, within a predetermined distance from) the transmitter unit **102**. For example, the transmission range for the close proximity communication may be established at approximately one foot distance or less between the transmitter unit **102** and the primary receiver unit **104**. When the transmitter unit **102** and the primary receiver unit **104** are within the transmission range, the close proximity command, upon initiation from the receiver unit **104** may be transmitted to the transmitter unit **102** (**730**).

Referring back to FIG. 7, in response to the transmitted close proximity command, a response data packet or other responsive communication may be received (**740**). In one aspect, the response data packet or other responsive communication may include identification information of the transmitter unit **102** transmitting the response data packet or other response communication to the receiver unit **104**. In one aspect, the receiver unit **104** may be configured to generate a key (for example, an 8 bit key or a key of a predetermined length) based on the transmitter identification information

17

(750), and which may be used in subsequent close proximity communication between the transmitter unit 102 and the receiver unit 104.

In one aspect, the data communication including the generated key may allow the recipient of the data communication to recognize the sender of the data communication and confirm that the sender of the data communication is the intended data sending device, and thus, including data which is desired or anticipated by the recipient of the data communication. In this manner, in one embodiment, one or more close proximity commands may be configured to include the generated key as part of the transmitted data packet. Moreover, the generated key may be based on the transmitter ID or other suitable unique information so that the receiver unit 104 may use such information for purposes of generating the unique key for the bi-directional communication between the devices.

While the description above includes generating the key based on the transmitter unit 102 identification information, within the scope of the present disclosure, the key may be generated based on one or more other information associated with the transmitter unit 102, and/or the receiver unit combination. In a further embodiment, the key may be encrypted and stored in a memory unit or storage device in the transmitter unit 102 for transmission to the receiver unit 104.

FIG. 8 is a flowchart illustrating sensor insertion detection routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 8, connection to an analyte sensor is detected (810), based on for example, a power up procedure where the sensor conduction trace 611 (FIG. 6) is configured to establish electrical contact with a predetermined one or more contact points on the transmitter unit 102. That is, when the sensor unit 101 (for example, the electrodes of the sensor) is correspondingly connected to the contact points on the transmitter unit 102, the transmitter unit 102 is configured to close the circuit connecting its power supply (for example, the battery 621 (FIG. 6)) to the components of the transmitter unit 102 and thereby exiting the power down or low power state into active or power up state.

In this manner, as discussed above, in one aspect, the transmitter unit 102 may be configured to include a power supply such as a battery 621 integrally provided within the sealed housing of the transmitter unit 102. When the transmitter unit 102 is connected or coupled to the respective electrodes of the analyte sensor that is positioned in a transcutaneous manner under the skin layer of the patient, the transmitter unit 102 is configured to wake up from its low power or sleep state (820), and power up the various components of the transmitter unit 102. In the active state, the transmitter unit 102 may be further configured to receive and process sensor signals received from the analyte sensor (FIG. 1) (830), and thereafter, transmit the processed sensor signals (840) to, for example, the receiver unit 104 (FIG. 1).

Accordingly, in one aspect, the sensor unit 610 (FIG. 6) may be provided with a conduction trace 611 which may be used to wake up or exit the transmitter unit from its post manufacturing sleep mode into an active state, by for example, establishing a closed circuit with the power supply provided within the transmitter unit 102.

FIG. 9 is a flowchart illustrating sensor removal detection routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 9, when the sensor removal is detected (910) for example, based on detaching or removing the transmitter unit 102 that was in contact with the sensor unit 101, one or more status signal is generated (920), that includes, for example, an indication that the sensor removal

18

state has been detected, and/or an indication that the transmitter unit 102 will enter a sleep mode or a powered down status. Thereafter, the generated status signal in one aspect is transmitted, for example, to the receiver unit 104 (930), and the transmitter unit 102 is configured to enter the power down mode or low power sleep mode (940).

In this manner, in one aspect, when the transmitter unit 102 is disconnected with an active sensor unit 101, the transmitter unit 102 is configured to notify the receiver unit 104 that the sensor unit 101 has been disconnected or otherwise, signals from the sensor unit 101 is no longer received by the transmitter unit 102. After transmitting the one or more signals to notify the receiver unit 104, the transmitter unit 102 in one embodiment is configured to enter sleep mode or low power state during which no data related to the monitored analyte level is transmitted to the receiver unit 104.

FIG. 10 is a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 10, in one embodiment, the transmitter unit 102 may be configured to receive a sensor initiate close proximity command (1010) from the receiver unit 104 positioned within the close transmission range. Based on the received sensor initiate command, the transmitter unit identification information may be retrieved (for example, from a nonvolatile memory) and transmitted (1020) to the receiver unit 104 or the sender of the sensor initiate command.

Referring back to FIG. 10, a communication key (1030) optionally encrypted is received in one embodiment, and thereafter, sensor related data is transmitted with the communication key on a periodic basis such as, every 60 seconds, five minutes, or any suitable predetermined time intervals.

Referring now to FIG. 11, a flowchart illustrating the pairing or synchronization routine in the data monitoring and management system of FIG. 1 in accordance with another embodiment of the present invention is shown. That is, in one aspect, FIG. 11 illustrates the pairing or synchronization routine from the receiver unit 104. Referring back to FIG. 11, the sensor initiate command is transmitted to the transmitter unit 102 (1110) when the receiver unit 104 is positioned within a close transmission range. Thereafter, in one aspect, the transmitter identification information is received (1120) for example, from the transmitter unit that received the sensor initiate command. Thereafter, a communication key (optionally encrypted) may be generated and transmitted (1130) to the transmitter unit.

In the manner described above, in one embodiment, a simplified pairing or synchronization between the transmitter unit 102 and the receiver unit 104 may be established using, for example, close proximity commands between the devices. As described above, in one aspect, upon pairing or synchronization, the transmitter unit 102 may be configured to periodically transmit analyte level information to the receiver unit for further processing.

FIG. 12 is a flowchart illustrating the power supply determination in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. That is, in one embodiment, using a counter, the receiver unit 104 may be configured to determine the power supply level of the transmitter unit 102 battery so as to determine a suitable time for replacement of the power supply or the transmitter unit 102 itself. Referring to FIG. 12, periodic data transmission is detected (1210), and a corresponding count in the counter is incremented for example, by one with each detected data transmission (1220). In particular, a Hobbs counter may be used in the rolling data configuration

19

described above to provide a count that is associated with the transmitter unit data transmission occurrence.

Referring to FIG. 12, the updated or incremented count stored in the Hobbs counter is periodically transmitted in the data packet from the transmitter unit 102 to the receiver unit 104. Moreover, the incremented or updated count may be stored (1240) in a persistent nonvolatile memory unit of the transmitter unit 102. Accordingly, based on the number of data transmission occurrences, the battery power supply level may be estimated, and in turn, which may provide an indication as to when the battery (and thus the transmitter unit in the embodiment where the power supply is manufactured to be embedded within the transmitter unit housing) needs to be replaced.

Moreover, in one aspect, the incremented count in the Hobbs counter is stored in a persistent nonvolatile memory such that, the counter is not reset or otherwise restarted with each sensor unit replacement.

FIG. 13 is a flowchart illustrating close proximity command for RF communication control in the data monitoring and management system of FIG. 1 in accordance with one embodiment of the present invention. Referring to FIG. 13, a close proximity command associated with communication status, for example is received (1310). In one aspect, the command associated with the communication status may include, for example, a communication module turn on or turn off command for, for example, turning on or turning off the associated RF communication device of the transmitter unit 102. Referring to FIG. 13, the communication status is determined (1320), and thereafter, modified based on the received command (1330).

That is, in one aspect, using one or more close proximity commands, the receiver unit 104 may be configured to control the RF communication of the transmitter unit 102 to, for example, disable or turn off the RF communication functionality for a predetermined time period. This may be particularly useful when used in air travel or other locations such as hospital settings, where RF communication devices need to be disabled. In one aspect, the close proximity command may be used to either turn on or turn off the RF communication module of the transmitter unit 102, such that, when the receiver unit 104 is positioned in close proximity to the transmitter unit 102, and the RF command is transmitted, the transmitter unit 102 is configured, in one embodiment, to either turn off or turn on the RF communication capability of the transmitter unit 102.

FIG. 14 is a flowchart illustrating analyte sensor identification routine in accordance with one embodiment of the present invention. Referring to FIG. 14, periodically, sensor counter information is received (1410), for example included as rolling data discussed above. The received sensor counter information may be stored in one or more storage units such as a memory unit. When the sensor counter information is received, a stored sensor counter information is retrieved (1420), and the retrieved sensor counter information is compared with the received sensor counter information (1430). Based on the comparison between the retrieved sensor counter information and the received sensor counter information, one or more signal is generated and output (1440).

That is, in one aspect, the sensor counter in the transmitter unit 102 may be configured to increment by one with each new sensor replacement. Thus, in one aspect, the sensor counter information may be associated with a particular sensor from which monitored analyte level information is generated and transmitted to the receiver unit 104. Accordingly, in one embodiment, based on the sensor counter information, the receiver unit 104 may be configured to ensure that the

20

analyte related data is generated and received from the correct analyte sensor transmitted from the transmitter unit 102.

A method in one embodiment includes detecting a data transmission, incrementing a count associated with the detected data transmission, and storing the count.

The count may be incremented by one.

In a further aspect, the method may include associating a power supply level information with the stored count.

Moreover, the method may also include generating a signal associated with the stored count, and/or include outputting the generated signal, where outputting the generated signal may include one or more of visually displaying the generated signal, audibly outputting the generated signal, or vibratorily outputting the generated signal.

In yet another aspect, the method may include transmitting the count with the data transmission, where the count may be transmitted periodically with the data transmission.

In still another aspect, the method may include associating a power supply status with the count.

A data processing device in another embodiment may include a counter, a data communication unit, and a data processing section coupled to the data communication unit and the counter, the data processing section configured to increment a count stored in the counter based on data transmission by the data communication unit.

In one aspect, the counter may include a nonvolatile memory unit. The counter may include an EEPROM.

The data communication unit may include an RF transceiver.

The count stored in the counter may be incremented by one with each data transmission by the data communication unit.

The device may include a power supply coupled to the data processing unit, the data communication unit and the counter, where the count stored in the counter is not erased when the power supply is disabled or in low power state.

The data processing unit may be configured to estimate the power supply life based on the stored count in the counter.

The device in a further aspect may include an output section for outputting one or more signals associated with the count information, where the output section may include one or more of a display unit, an audible output section, or a vibratory output section.

Various other modifications and alterations in the structure and method of operation of this invention will be apparent to those skilled in the art without departing from the scope and spirit of the invention. Although the invention has been described in connection with specific preferred embodiments, it should be understood that the invention as claimed should not be unduly limited to such specific embodiments. It is intended that the following claims define the scope of the present invention and that structures and methods within the scope of these claims and their equivalents be covered thereby.

What is claimed is:

1. An analyte monitoring system, the system comprising: a transcutaneous analyte sensor; a transmitter coupled to the analyte sensor; a receiver configured to communicate with the transmitter; and a first counter configured to incrementally count when the analyte sensor is transcutaneously positioned and coupled to the transmitter and upon initialization of the transcutaneously positioned analyte sensor, wherein the incremental count is used to verify the identity of the transcutaneously positioned analyte sensor.
2. The analyte monitoring system of claim 1, wherein the counter is a 20-bit counter.

21

3. The analyte monitoring system of claim 1, wherein the counter is an 8-bit counter.

4. The analyte monitoring system of claim 1, wherein the transmitter is configured to transmit a data packet to the receiver, wherein the data packet includes the incremental count.

5. The analyte monitoring system of claim 1, wherein the incremental count is associated with a particular analyte sensor.

6. The analyte monitoring system of claim 1, the receiver is configured to store the incremental count.

7. The analyte monitoring system of claim 1, further including a display to output a message associated with the incremental count.

8. The analyte monitoring system of claim 1, further comprising a second counter configured to incrementally count.

9. The analyte monitoring system of claim 8, wherein the second counter is configured to incrementally count by one when a data packet is transmitted.

10. The analyte monitoring system of claim 8, wherein second counter is a 20-bit counter.

11. The analyte monitoring system of claim 1, wherein the analyte sensor and transmitter are physically coupled in a single housing.

12. The analyte monitoring of claim 1, wherein the analyte sensor includes electrodes disposed on a surface thereof.

13. The analyte monitoring system of claim 12, wherein the electrodes comprise gold.

14. The analyte monitoring system of claim 13, wherein the gold electrodes are formed by at least a laser ablation technique.

15. The analyte monitoring system of claim 1, wherein the transmitter and the receiver are configured for bidirectional communication.

16. The analyte monitoring system of claim 1, wherein the transmitter and the receiver are configured for unidirectional communication.

17. The analyte monitoring system of claim 1, wherein the transmitter includes an application specific integrated circuit (ASIC).

18. The analyte monitoring system of claim 17, wherein the ASIC is configured to generate a close proximity key.

19. The analyte monitoring system of claim 18, wherein the ASIC includes a plurality of close proximity communication commands.

20. The analyte monitoring system of claim 19, wherein the close proximity communication commands include a new sensor initiation command, RF communication control command, and receiver and transmitter pairing command.

21. The analyte monitoring system of claim 1, wherein the transmitter and receiver are configured to transmit and receive data by a bidirectional communication link.

22. An analyte monitoring system, the system comprising:
a transcutaneous analyte sensor;
a transmitter coupled to the analyte sensor;
a receiver configured to communicate with the transmitter;
a first counter configured to incrementally count when the analyte sensor is transcutaneously positioned and coupled to the transmitter and upon initialization of the analyte sensor, wherein the incremental count is used to verify the identity of the transcutaneously positioned analyte sensor; and

a second counter configured to incrementally count every time detected data based on signals generated by the analyte sensor is transmitted to the receiver, the incremental count of the second counter associated with a power supply level of the transmitter.

22

23. The analyte monitoring system of claim 22, wherein the transmitter is configured to transmit a data packet to the receiver, and further wherein the data packet includes the incremental count from at least one of the first or second counter.

24. The analyte monitoring system of claim 22, wherein the first counter is an 8-bit counter, and the second counter is a 20-bit counter.

25. The analyte monitoring system of claim 22, wherein the incremental count of the first counter is associated with a particular analyte sensor.

26. The analyte monitoring system of claim 22, wherein the receiver is configured to store the incremental count from at least one of the first or second counters.

27. The analyte monitoring system of claim 22, further including a display for outputting a message associated with the incremental count of at least one of the first or second counters.

28. The analyte monitoring system of claim 22, wherein the transmitter and receiver are configured for unidirectional communication.

29. The analyte monitoring system of claim 22, wherein the transmitter and receiver are configured for bidirectional communication.

30. The analyte monitoring system of claim 22, wherein the transmitter includes an application specific integrated circuit (ASIC).

31. The analyte monitoring system of claim 30, wherein the ASIC is configured to generate a close proximity key.

32. The analyte monitoring system of claim 31, wherein the ASIC includes a plurality of close proximity communication commands.

33. The analyte monitoring system of claim 32, wherein the close proximity communication commands include a new sensor initiation command, RF communication control command, and receiver and transmitter pairing command.

34. The analyte monitoring of claim 22, wherein the analyte sensor includes electrodes disposed on a surface thereof.

35. The analyte monitoring system of claim 34, wherein the electrodes comprise gold.

36. The analyte monitoring system of claim 35, wherein the gold electrodes are formed by at least a laser ablation technique.

37. A method of operating an analyte monitoring system, the method comprising:

transcutaneously positioning an analyte sensor in fluid contact with an interstitial fluid under a skin layer;
coupling the analyte sensor to a data processing device having a counter configured to incrementally count;
determining, using the data processing device, when the transcutaneously positioned analyte sensor is initialized;
incrementally counting, using the counter, when a sensor is coupled to the data processing device and upon initialization of the transcutaneously positioned analyte sensor, wherein the incremental count is used to verify the identity of the transcutaneously positioned analyte sensor; and

transmitting the incremental count to a receiver.

38. The method of claim 37, wherein the sensor is coupled to the data processing device in a single housing.

39. The method of claim 37, wherein the counter incrementally counts by one every time a sensor is coupled to the data processing device.

40. The method of claim 37, wherein the incremental count is transmitted in a data packet.

23

41. The method of claim 37, further including the step of incrementally counting by a second counter.

42. The method of claim 41, wherein the second counter incrementally counts by one each time a data packet is transmitted.

43. The method of claim 42, wherein a data packet is transmitted every one minute.

44. The method of claim 37, further including the step of storing the incremental count.

45. The method of claim 44, wherein the stored incremental count is associated with a particular analyte sensor.

46. The method of claim 44, further including the step of comparing the stored incremental count with transmitted incremental count information to determine if the transmitted data packet is associated with a particular analyte sensor.

47. The method of claim 46, further including the step of generating a message based on the compared count information.

48. The method of claim 47, further including the step of outputting the generated message.

24

49. The method of claim 48, wherein the generated message is displayed.

50. The method of claim 49, wherein the displayed message comprises a visual, audible, vibratory display or any combination thereof.

51. The method of claim 37, wherein the data processing device includes an application specific integrated circuit (ASIC).

52. The method of claim 51, wherein the ASIC is configured to generate a close proximity key.

53. The method of claim 52, wherein the ASIC includes a plurality of close proximity communication commands.

54. The method of claim 53, wherein the close proximity communication commands include a new sensor initiation command, RF communication control command, and receiver and transmitter pairing command.

* * * * *