



US008228588B2

(12) **United States Patent**
McCabe et al.

(10) **Patent No.:** **US 8,228,588 B2**
(45) **Date of Patent:** **Jul. 24, 2012**

(54) **INTERIOR REARVIEW MIRROR
INFORMATION DISPLAY SYSTEM FOR A
VEHICLE**

(75) Inventors: **Ian A. McCabe**, Holland, MI (US);
Hamid Habibi, Holland, MI (US);
Desaraju V. Varaprasad, Holland, MI
(US); **Niall R. Lynam**, Holland, MI (US)

(73) Assignee: **Donnelly Corporation**, Holland, MI
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 89 days.

(21) Appl. No.: **12/965,052**

(22) Filed: **Dec. 10, 2010**

(65) **Prior Publication Data**

US 2011/0084198 A1 Apr. 14, 2011

Related U.S. Application Data

(63) Continuation of application No. 12/555,276, filed on
Sep. 8, 2009, now Pat. No. 7,859,737, which is a
continuation of application No. 12/342,452, filed on
Dec. 23, 2008, now Pat. No. 7,586,666, which is a
continuation of application No. 11/860,223, filed on
Sep. 24, 2007, now Pat. No. 7,471,438, which is a
continuation of application No. 10/528,269, filed as
application No. PCT/US03/29776 on Sep. 19, 2003,
now Pat. No. 7,274,501.

(60) Provisional application No. 60/412,275, filed on Sep.
20, 2002, provisional application No. 60/424,116,
filed on Nov. 5, 2002, provisional application No.
60/489,816, filed on Jul. 24, 2003.

(51) **Int. Cl.**
G02F 1/15 (2006.01)

(52) **U.S. Cl.** **359/265; 359/267**

(58) **Field of Classification Search** 359/265
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,096,452 A 5/1914 Perrin
(Continued)

FOREIGN PATENT DOCUMENTS

AU A-40317/95 2/1995
(Continued)

OTHER PUBLICATIONS

Stewart, James W.; HP SnapLED: LED Assemblies for Automotive
Signal Applications; Nov. 1, 1998; Hewlett-Packard Journal; vol. 50,
No. 1, www.hpl.hp.com/hpjournal/98nov/nov98al.pdf.

(Continued)


Primary Examiner — James Jones

(74) *Attorney, Agent, or Firm* — Gardner, Linn, Burkhardt &
Flory, LLP

(57) **ABSTRACT**

An interior rearview mirror information display system for a
vehicle includes an interior rearview mirror assembly includ-
ing an electrochromic reflective element. A display device is
disposed behind a transfective mirror reflector of the reflect-
ive element and includes a display screen backlit by a plu-
rality of light emitting diodes supported by a circuit board
disposed rearward of the fourth surface of the rear substrate.
The light emitting diodes of the circuit board are disposed to
the rear of the display screen to provide backlighting of the
display screen when activated. Information displayed by the
display device is viewable by a driver of the equipped vehicle.
When the plurality of light emitting diodes is activated and the
display device is displaying information, light emitted by the
plurality of light emitting diodes passes through the display
screen and through the transfective mirror reflector for view-
ing by the driver of the equipped vehicle.

86 Claims, 33 Drawing Sheets



U.S. PATENT DOCUMENTS

1,563,258 A	11/1925	Cunningham	4,288,814 A	9/1981	Talley et al.
2,069,368 A	2/1937	Horinstein	RE30,835 E	12/1981	Giglia
2,166,303 A	7/1939	Hodny et al.	4,306,768 A	12/1981	Egging
2,263,382 A	11/1941	Gotzinger	4,310,851 A	1/1982	Pierrat
2,414,223 A	1/1947	DeVirgilis	4,331,382 A	5/1982	Graff
2,457,348 A	12/1948	Chambers	4,338,000 A	7/1982	Kamimori et al.
2,561,582 A	7/1951	Marbel	4,377,613 A	3/1983	Gordon
2,580,014 A	12/1951	Gazda	4,398,805 A	8/1983	Cole
3,004,473 A	10/1961	Arthur et al.	4,419,386 A	12/1983	Gordon
3,075,430 A	1/1963	Woodward et al.	4,420,238 A	12/1983	Felix
3,141,393 A	7/1964	Platt	4,425,717 A	1/1984	Marcus
3,152,216 A	10/1964	Woodward	4,435,042 A	3/1984	Wood et al.
3,162,008 A	12/1964	Berger et al.	4,435,048 A	3/1984	Kamimori et al.
3,185,020 A	5/1965	Thelen	4,436,371 A	3/1984	Wood et al.
3,266,016 A	8/1966	Maruyama et al.	4,438,348 A	3/1984	Casper et al.
3,280,701 A	10/1966	Donnelly et al.	4,443,057 A	4/1984	Bauer et al.
3,432,225 A	3/1969	Rock	4,446,171 A	5/1984	Thomas
3,451,741 A	6/1969	Manos	4,465,339 A	8/1984	Baucke et al.
3,453,038 A	7/1969	Kissa et al.	4,473,695 A	9/1984	Wrighton et al.
3,467,465 A	9/1969	Van Noord	4,490,227 A	12/1984	Bitter
3,473,867 A	10/1969	Byrnes	4,491,390 A	1/1985	Tong-Shen
3,480,781 A	11/1969	Mandalakas	4,499,451 A	2/1985	Suzuki et al.
3,499,112 A	3/1970	Heilmeyer et al.	4,521,079 A	6/1985	Leenhouts et al.
3,499,702 A	3/1970	Goldmacher et al.	4,524,941 A	6/1985	Wood et al.
3,521,941 A	7/1970	Deb et al.	4,538,063 A	8/1985	Bulat
3,543,018 A	11/1970	Barcus et al.	4,546,551 A	10/1985	Franks
3,557,265 A	1/1971	Chisholm et al.	4,555,694 A	11/1985	Yanagishima et al.
3,565,985 A	2/1971	Schrenk et al.	4,561,625 A	12/1985	Weaver
3,612,654 A	10/1971	Klein	4,572,619 A	2/1986	Reininger et al.
3,614,210 A	10/1971	Caplan	4,580,196 A	4/1986	Task
3,628,851 A	12/1971	Robertson	4,581,827 A	4/1986	Higashi
3,676,668 A	7/1972	Collins et al.	4,588,267 A	5/1986	Pastore
3,680,951 A	8/1972	Jordan et al.	4,603,946 A	8/1986	Kato et al.
3,689,695 A	9/1972	Rosenfield et al.	4,623,222 A	11/1986	Itoh et al.
3,711,176 A	1/1973	Alfrey, Jr. et al.	4,625,210 A	11/1986	Sagl
3,712,710 A	1/1973	Castellion et al.	4,626,850 A	12/1986	Chey
3,748,017 A	7/1973	Yamamura et al.	4,630,040 A	12/1986	Haertling
3,781,090 A	12/1973	Sumita	4,630,109 A	12/1986	Barton
3,806,229 A	4/1974	Schoot et al.	4,630,904 A	12/1986	Pastore
3,807,832 A	4/1974	Castellion	4,634,835 A	1/1987	Suzuki
3,807,833 A	4/1974	Graham et al.	4,635,033 A	1/1987	Inukai et al.
3,821,590 A	6/1974	Kosman et al.	4,636,782 A	1/1987	Nakamura et al.
3,837,129 A	9/1974	Losell	4,638,287 A	1/1987	Umebayashi et al.
3,860,847 A	1/1975	Carley	4,646,210 A	2/1987	Skogler et al.
3,862,798 A	1/1975	Hopkins	4,652,090 A	3/1987	Uchikawa et al.
3,870,404 A	3/1975	Wilson et al.	4,655,549 A	4/1987	Suzuki et al.
3,876,287 A	4/1975	Sprokel	4,665,311 A	5/1987	Cole
3,932,024 A	1/1976	Yaguchi et al.	4,665,430 A	5/1987	Hiroyasu
3,940,822 A	3/1976	Emerick et al.	4,669,827 A	6/1987	Fukada et al.
3,956,017 A	5/1976	Shigemasa	4,671,615 A	6/1987	Fukada et al.
3,978,190 A	8/1976	Kurz, Jr. et al.	4,671,619 A	6/1987	Kamimori et al.
3,985,424 A	10/1976	Steinacher	4,678,281 A	7/1987	Bauer
4,006,546 A	2/1977	Anderson et al.	4,679,906 A	7/1987	Brandenburg
4,035,681 A	7/1977	Savage	4,682,083 A	7/1987	Alley
4,040,727 A	8/1977	Ketchpel	4,692,798 A	9/1987	Seko et al.
4,052,712 A	10/1977	Ohama et al.	4,694,295 A	9/1987	Miller et al.
4,075,468 A	2/1978	Marcus	4,697,883 A	10/1987	Suzuki et al.
4,088,400 A	5/1978	Assouline et al.	4,701,022 A	10/1987	Jacob
4,093,364 A	6/1978	Miller	4,702,566 A	10/1987	Tukude et al.
4,097,131 A	6/1978	Nishiyama	4,704,740 A	11/1987	McKee et al.
4,109,235 A	8/1978	Bouthors	4,711,544 A	12/1987	Iino et al.
4,139,234 A	2/1979	Morgan	4,712,879 A	12/1987	Lynam et al.
4,159,866 A	7/1979	Wunsch et al.	4,713,685 A	12/1987	Nishimura et al.
4,161,653 A	7/1979	Bedini et al.	RE32,576 E	1/1988	Pastore
4,171,875 A	10/1979	Taylor et al.	4,718,756 A	1/1988	Lancaster
4,174,152 A	11/1979	Gilia et al.	4,721,364 A	1/1988	Itoh et al.
4,200,361 A	4/1980	Malvano et al.	4,729,068 A	3/1988	Ohe
4,202,607 A	5/1980	Washizuka et al.	4,729,076 A	3/1988	Masami et al.
4,211,955 A	7/1980	Ray	4,731,669 A	3/1988	Hayashi et al.
4,214,266 A	7/1980	Myers	4,733,335 A	3/1988	Serizawa et al.
4,219,760 A	8/1980	Ferro	4,733,336 A	3/1988	Skogler et al.
4,221,955 A	9/1980	Joslyn	4,740,838 A	4/1988	Mase et al.
4,228,490 A	10/1980	Thillays	4,761,061 A	8/1988	Nishiyama et al.
4,247,870 A	1/1981	Gabel et al.	4,773,740 A	9/1988	Kawakami et al.
4,257,703 A	3/1981	Goodrich	4,780,752 A	10/1988	Angerstein et al.
4,274,078 A	6/1981	Isobe et al.	4,781,436 A	11/1988	Armbruster
4,277,804 A	7/1981	Robison	4,789,904 A	12/1988	Peterson
4,281,899 A	8/1981	Oskam	4,793,690 A	12/1988	Gahan et al.
			4,793,695 A	12/1988	Wada et al.

US 8,228,588 B2

Page 3

4,794,261 A	12/1988	Rosen	5,076,673 A	12/1991	Lynam et al.
D299,491 S	1/1989	Masuda	5,076,674 A	12/1991	Lynam
4,799,768 A	1/1989	Gahan	5,078,480 A	1/1992	Warszawski
4,803,599 A	2/1989	Trine et al.	5,096,287 A	3/1992	Kakinami et al.
4,807,096 A	2/1989	Skogler et al.	5,100,095 A	3/1992	Haan et al.
4,820,933 A	4/1989	Hong et al.	5,101,139 A	3/1992	Lechter
4,825,232 A	4/1989	Howdle	5,105,127 A	4/1992	Lavaud et al.
4,826,289 A	5/1989	Vandenbrink et al.	5,115,346 A	5/1992	Lynam
4,827,086 A	5/1989	Rockwell	5,117,346 A	5/1992	Gard
4,837,551 A	6/1989	Iino	5,119,220 A	6/1992	Narita et al.
4,842,378 A	6/1989	Flasck et al.	5,121,200 A	6/1992	Choi
4,845,402 A	7/1989	Smith	5,122,619 A	6/1992	Dlubak
4,847,772 A	7/1989	Michalopoulos et al.	5,123,077 A	6/1992	Endo et al.
4,855,161 A	8/1989	Moser et al.	5,124,845 A	6/1992	Shimojo
4,855,550 A	8/1989	Schultz, Jr.	5,124,890 A	6/1992	Choi et al.
4,859,813 A	8/1989	Rockwell	5,128,799 A	7/1992	Byker
4,859,867 A	8/1989	Larson et al.	5,130,898 A	7/1992	Akahane
4,860,171 A	8/1989	Kojima	5,131,154 A	7/1992	Schierbeek et al.
4,862,594 A	9/1989	Schierbeek et al.	5,134,507 A	7/1992	Ishii
4,871,917 A	10/1989	O'Farrell et al.	5,134,549 A	7/1992	Yokoyama
4,872,051 A	10/1989	Dye	5,135,298 A	8/1992	Feltman
4,882,466 A	11/1989	Friel	5,136,483 A	8/1992	Schöniger et al.
4,882,565 A	11/1989	Gallmeyer	5,140,455 A	8/1992	Varaprasad et al.
4,883,349 A	11/1989	Mittelhäuser	5,140,465 A	8/1992	Yasui et al.
4,884,135 A	11/1989	Schiffman	5,142,407 A	8/1992	Varaprasad et al.
4,886,960 A	12/1989	Molyneux et al.	5,145,609 A	9/1992	Varaprasad et al.
4,889,412 A	12/1989	Clerc et al.	5,150,232 A	9/1992	Gunkima et al.
4,891,828 A	1/1990	Kawazoe	5,151,816 A	9/1992	Varaprasad et al.
4,892,345 A	1/1990	Rachael, III	5,151,824 A	9/1992	O'Farrell
4,902,103 A	2/1990	Miyake et al.	5,154,617 A	10/1992	Suman et al.
4,902,108 A	2/1990	Byker	5,158,638 A	10/1992	Osanami et al.
4,906,085 A	3/1990	Sugihara et al.	5,160,200 A	11/1992	Cheselske
4,909,606 A	3/1990	Wada et al.	5,160,201 A	11/1992	Wrobel
4,910,591 A	3/1990	Petrossian et al.	5,166,815 A	11/1992	Elderfield
4,916,374 A	4/1990	Schierbeek et al.	5,168,378 A	12/1992	Black et al.
4,926,170 A	5/1990	Beggs et al.	5,173,881 A	12/1992	Sindle
4,930,742 A	6/1990	Schofield et al.	5,177,031 A	1/1993	Buchmann et al.
4,933,814 A	6/1990	Sanai	5,178,448 A	1/1993	Adams et al.
4,935,665 A	6/1990	Murata	5,179,471 A	1/1993	Caskey et al.
4,936,533 A	6/1990	Adams et al.	5,183,099 A	2/1993	Bechu
4,937,796 A	6/1990	Tendler	5,184,956 A	2/1993	Langlarais et al.
4,937,945 A	7/1990	Schofield et al.	5,189,537 A	2/1993	O'Farrell
4,943,796 A	7/1990	Lee	5,193,029 A	3/1993	Schofield et al.
4,948,242 A	8/1990	Desmond et al.	5,197,562 A	3/1993	Kakinama et al.
4,953,305 A	9/1990	Van Lente et al.	5,202,950 A	4/1993	Arego et al.
4,956,591 A	9/1990	Schierbeek et al.	5,207,492 A	5/1993	Roberts
4,957,349 A	9/1990	Clerc et al.	5,210,967 A	5/1993	Brown
4,959,247 A	9/1990	Moser et al.	5,212,819 A	5/1993	Wada
4,959,865 A	9/1990	Stettiner et al.	5,214,408 A	5/1993	Asayama
4,970,653 A	11/1990	Kenue	5,217,794 A	6/1993	Schrenk
4,973,844 A	11/1990	O'Farrell et al.	5,223,814 A	6/1993	Suman
4,974,122 A	11/1990	Shaw	5,223,844 A	6/1993	Mansell et al.
4,978,196 A	12/1990	Suzuki et al.	5,229,975 A	7/1993	Truesdell et al.
4,983,951 A	1/1991	Igarashi et al.	5,230,400 A	7/1993	Kakinama et al.
4,985,809 A	1/1991	Matsui et al.	5,233,461 A	8/1993	Dornan et al.
4,987,357 A	1/1991	Masaki	5,235,316 A	8/1993	Qualizza
4,996,083 A	2/1991	Moser et al.	5,239,405 A	8/1993	Varaprasad et al.
5,001,386 A	3/1991	Sullivan et al.	5,239,406 A	8/1993	Lynam
5,001,558 A	3/1991	Burley et al.	5,243,417 A	9/1993	Pollard
5,005,213 A	4/1991	Hanson et al.	5,245,422 A	9/1993	Borcherts et al.
5,006,971 A	4/1991	Jerkins	5,252,354 A	10/1993	Cronin et al.
5,014,167 A	5/1991	Roberts	5,253,109 A	10/1993	O'Farrell et al.
5,016,988 A	5/1991	Imura	5,255,442 A	10/1993	Schierbeek et al.
5,016,996 A	5/1991	Ueno	5,260,626 A	11/1993	Takase et al.
5,017,903 A	5/1991	Krippelz, Sr.	5,277,986 A	1/1994	Cronin et al.
5,018,839 A	5/1991	Yamamoto et al.	5,280,555 A	1/1994	Ainsburg
5,027,200 A	6/1991	Petrossian et al.	5,285,060 A	2/1994	Larson et al.
5,037,182 A	8/1991	Groves et al.	5,289,321 A	2/1994	Secor
5,038,255 A	8/1991	Nishihashi et al.	5,296,924 A	3/1994	de Saint Blancard et al.
5,052,163 A	10/1991	Czekala	5,303,075 A	4/1994	Wada et al.
5,056,899 A	10/1991	Warszawski	5,303,205 A	4/1994	Gauthier et al.
5,057,974 A	10/1991	Mizobe	5,304,980 A	4/1994	Maekawa
5,058,851 A	10/1991	Lawlor et al.	5,305,012 A	4/1994	Faris
5,059,015 A	10/1991	Tran	5,307,136 A	4/1994	Saneyoshi
5,066,108 A	11/1991	McDonald	5,313,335 A	5/1994	Gray et al.
5,066,112 A	11/1991	Lynam et al.	5,325,096 A	6/1994	Pakett
5,069,535 A	12/1991	Baucke et al.	5,325,386 A	6/1994	Jewell et al.
5,070,323 A	12/1991	Iino et al.	5,327,288 A	7/1994	Wellington et al.
5,073,012 A	12/1991	Lynam	5,330,149 A	7/1994	Haan et al.

5,331,312 A	7/1994	Kudoh	5,550,677 A	8/1996	Schofield et al.
5,331,358 A	7/1994	Schurle et al.	5,555,172 A	9/1996	Potter
5,339,075 A	8/1994	Abst et al.	5,561,333 A	10/1996	Darius
5,339,529 A	8/1994	Lindberg	5,566,244 A	10/1996	Kato et al.
5,341,437 A	8/1994	Nakayama	5,567,360 A	10/1996	Varaprasad et al.
D351,370 S	10/1994	Lawlor et al.	5,568,316 A	10/1996	Schrenck et al.
5,354,965 A	10/1994	Lee	5,570,127 A	10/1996	Schmidt
5,355,118 A	10/1994	Fukuhara	5,572,354 A	11/1996	Desmond et al.
5,355,245 A	10/1994	Lynam	5,574,426 A	11/1996	Shisgal et al.
5,355,284 A	10/1994	Roberts	5,574,443 A	11/1996	Hsieh
5,361,190 A	11/1994	Roberts et al.	5,575,552 A	11/1996	Faloon et al.
5,363,294 A	11/1994	Yamamoto et al.	5,576,687 A	11/1996	Blank et al.
5,371,659 A	12/1994	Pastrick et al.	5,576,854 A	11/1996	Schmidt et al.
5,373,482 A	12/1994	Gauthier	5,576,975 A	11/1996	Sasaki et al.
5,379,146 A	1/1995	Defendini	5,578,404 A	11/1996	Kliem
5,386,285 A	1/1995	Asayama	5,587,236 A	12/1996	Agrawal et al.
5,386,306 A	1/1995	Gunjima et al.	5,587,699 A	12/1996	Faloon et al.
5,400,158 A	3/1995	Ohnishi et al.	5,593,221 A	1/1997	Evanicky et al.
5,402,103 A	3/1995	Tashiro	5,594,222 A	1/1997	Caldwell
5,406,395 A	4/1995	Wilson et al.	5,594,560 A	1/1997	Jelley et al.
5,406,414 A	4/1995	O'Farrell et al.	5,594,615 A	1/1997	Spijkerman et al.
5,408,353 A	4/1995	Nichols et al.	5,602,542 A	2/1997	Widmann et al.
5,408,357 A	4/1995	Beukema	5,602,670 A	2/1997	Keegan
5,410,346 A	4/1995	Saneyoshi et al.	5,603,104 A	2/1997	Phelps, III et al.
5,414,439 A	5/1995	Groves et al.	5,608,550 A	3/1997	Epstein et al.
5,414,461 A	5/1995	Kishi et al.	5,609,652 A	3/1997	Yamada et al.
5,416,313 A	5/1995	Larson et al.	5,610,380 A	3/1997	Nicolaisen
5,416,478 A	5/1995	Morinaga	5,610,756 A	3/1997	Lynam et al.
5,418,610 A	5/1995	Fischer	5,611,966 A	3/1997	Varaprasad et al.
5,422,756 A	6/1995	Weber	5,614,885 A	3/1997	Van Lente et al.
5,424,726 A	6/1995	Beymer	5,615,023 A	3/1997	Yang
5,424,865 A	6/1995	Lynam	5,615,857 A	4/1997	Hook
5,424,952 A	6/1995	Asayama	5,617,085 A	4/1997	Tsutsumi et al.
5,426,524 A	6/1995	Wada et al.	5,619,374 A	4/1997	Roberts
5,430,431 A	7/1995	Nelson	5,619,375 A	4/1997	Roberts
5,432,496 A	7/1995	Lin	5,626,800 A	5/1997	Williams et al.
5,432,626 A	7/1995	Sasuga et al.	5,631,089 A	5/1997	Center, Jr. et al.
5,436,741 A	7/1995	Crandall	5,631,638 A	5/1997	Kaspar et al.
5,437,931 A	8/1995	Tsai et al.	5,631,639 A	5/1997	Hibino et al.
5,439,305 A	8/1995	Santo	5,632,092 A	5/1997	Blank et al.
5,444,478 A	8/1995	Lelong et al.	5,632,551 A	5/1997	Roney et al.
5,446,576 A	8/1995	Lynam et al.	5,634,709 A	6/1997	Iwama
5,455,716 A	10/1995	Suman et al.	5,640,216 A	6/1997	Hasegawa et al.
5,461,361 A	10/1995	Moore	5,642,238 A	6/1997	Sala
D363,920 S	11/1995	Roberts et al.	5,644,851 A	7/1997	Blank et al.
5,469,187 A	11/1995	Yaniv	5,646,614 A	7/1997	Abersfelder et al.
5,469,298 A	11/1995	Suman et al.	5,649,756 A	7/1997	Adams et al.
5,475,366 A	12/1995	Van Lente et al.	5,649,758 A	7/1997	Dion
5,475,494 A	12/1995	Nishida et al.	5,650,765 A	7/1997	Park
5,481,409 A	1/1996	Roberts	5,650,929 A	7/1997	Potter et al.
5,483,453 A	1/1996	Uemura et al.	5,661,455 A	8/1997	Van Lente et al.
5,485,161 A	1/1996	Vaughn	5,661,651 A	8/1997	Geschke et al.
5,485,378 A	1/1996	Franke et al.	5,661,804 A	8/1997	Dykema et al.
5,487,522 A	1/1996	Hook	5,662,375 A	9/1997	Adams et al.
5,488,496 A	1/1996	Pine	5,666,157 A	9/1997	Aviv
5,497,305 A	3/1996	Pastrick et al.	5,667,289 A	9/1997	Akahane et al.
5,497,306 A	3/1996	Pastrick	5,668,663 A	9/1997	Varaprasad et al.
5,500,760 A	3/1996	Varaprasad et al.	5,668,675 A	9/1997	Fredricks
5,506,701 A	4/1996	Ichikawa	5,669,698 A	9/1997	Veldman et al.
5,509,606 A	4/1996	Breithaupt et al.	5,669,699 A	9/1997	Pastrick et al.
5,510,983 A	4/1996	Iino	5,669,704 A	9/1997	Pastrick
5,515,448 A	5/1996	Nishitani	5,669,705 A	9/1997	Pastrick et al.
5,519,621 A	5/1996	Worthuman	5,670,935 A	9/1997	Schofield et al.
5,521,744 A	5/1996	Mazurek	5,671,996 A	9/1997	Bos et al.
5,521,760 A	5/1996	De Young et al.	5,673,994 A	10/1997	Fant, Jr. et al.
5,523,811 A	6/1996	Wada et al.	5,673,999 A	10/1997	Koenck
5,523,877 A	6/1996	Lynam	5,677,598 A	10/1997	De Hair et al.
5,525,264 A	6/1996	Cronin et al.	5,679,283 A	10/1997	Tonar et al.
5,525,977 A	6/1996	Suman	5,680,123 A	10/1997	Lee
5,528,422 A	6/1996	Roberts	5,680,245 A	10/1997	Lynam
5,528,474 A	6/1996	Roney et al.	5,680,263 A	10/1997	Zimmermann et al.
5,529,138 A	6/1996	Shaw et al.	5,686,975 A	11/1997	Lipton
5,530,240 A	6/1996	Larson et al.	5,686,979 A	11/1997	Weber et al.
5,530,420 A	6/1996	Tsuchiya et al.	5,689,241 A	11/1997	Clark, Sr. et al.
5,530,421 A	6/1996	Marshall et al.	5,689,370 A	11/1997	Tonar et al.
5,535,056 A	7/1996	Caskey et al.	5,691,848 A	11/1997	Van Lente et al.
5,535,144 A	7/1996	Kise	5,692,819 A	12/1997	Mitsutake et al.
5,539,397 A	7/1996	Asanuma et al.	5,696,529 A	12/1997	Evanicky et al.
5,541,590 A	7/1996	Nishio	5,696,567 A	12/1997	Wada et al.

5,699,044 A	12/1997	Van Lente et al.	5,877,707 A	3/1999	Kowalick
5,699,188 A	12/1997	Gilbert et al.	5,877,897 A	3/1999	Schofield et al.
5,703,568 A	12/1997	Hegy	5,878,353 A	3/1999	ul Azam et al.
5,708,410 A	1/1998	Blank et al.	5,878,370 A	3/1999	Olson
5,708,415 A	1/1998	Van Lente et al.	5,879,074 A	3/1999	Pastrick
5,708,857 A	1/1998	Ishibashi	5,883,605 A	3/1999	Knapp
5,715,093 A	2/1998	Schierbeek et al.	5,883,739 A	3/1999	Ashihara et al.
5,724,187 A	3/1998	Varaprasad et al.	5,888,431 A	3/1999	Tonar et al.
5,724,316 A	3/1998	Brunts	5,894,196 A	4/1999	McDermott
5,729,194 A	3/1998	Spears et al.	D409,540 S	5/1999	Muth
5,737,226 A	4/1998	Olson et al.	5,899,551 A	5/1999	Neijzen et al.
5,741,966 A	4/1998	Handfield et al.	5,899,956 A	5/1999	Chan
5,744,227 A	4/1998	Bright et al.	5,904,729 A	5/1999	Ruzicka
5,745,050 A	4/1998	Nakagawa	5,910,854 A	6/1999	Varaprasad et al.
5,745,266 A	4/1998	Smith	5,914,815 A	6/1999	Bos
5,748,172 A	5/1998	Song et al.	5,917,664 A	6/1999	O'Neill et al.
5,748,287 A	5/1998	Takahashi et al.	5,918,180 A	6/1999	Dimino
5,751,211 A	5/1998	Shirai et al.	5,922,176 A	7/1999	Caskey
5,751,246 A	5/1998	Hertel	5,923,027 A	7/1999	Stam et al.
5,751,390 A	5/1998	Crawford et al.	5,923,457 A	7/1999	Byker et al.
5,751,489 A	5/1998	Caskey et al.	5,924,212 A	7/1999	Domanski
5,754,099 A	5/1998	Nishimura et al.	5,926,087 A	7/1999	Busch et al.
D394,833 S	6/1998	Muth	5,927,792 A	7/1999	Welling et al.
5,760,828 A	6/1998	Cortes	5,928,572 A	7/1999	Tonar et al.
5,760,931 A	6/1998	Saburi et al.	5,929,786 A	7/1999	Schofield et al.
5,760,962 A	6/1998	Schofield et al.	5,931,555 A	8/1999	Akahane et al.
5,761,094 A	6/1998	Olson et al.	5,935,702 A	8/1999	Macquart et al.
5,762,823 A	6/1998	Hikmet	5,936,774 A	8/1999	Street
5,764,139 A	6/1998	Nojima et al.	5,938,320 A	8/1999	Crandall
5,765,940 A	6/1998	Levy et al.	5,938,321 A	8/1999	Bos et al.
5,767,793 A	6/1998	Agravante et al.	5,938,721 A	8/1999	Dussell et al.
5,768,020 A	6/1998	Nagao	5,940,011 A	8/1999	Agravante et al.
5,775,762 A	7/1998	Vitito	5,940,120 A	8/1999	Frankhouse et al.
5,777,779 A	7/1998	Hashimoto et al.	5,940,201 A	8/1999	Ash et al.
5,780,160 A	7/1998	Allemand et al.	5,942,895 A	8/1999	Popovic et al.
5,786,772 A	7/1998	Schofield et al.	5,947,586 A	9/1999	Weber
5,788,357 A	8/1998	Muth et al.	5,949,331 A	9/1999	Schofield et al.
5,790,298 A	8/1998	Tonar	5,949,506 A	9/1999	Jones et al.
5,790,502 A	8/1998	Horinouchi et al.	5,956,079 A	9/1999	Ridgley
5,790,973 A	8/1998	Blaker et al.	5,956,181 A	9/1999	Lin
5,793,308 A	8/1998	Rosinski et al.	5,959,367 A	9/1999	O'Farrell et al.
5,793,420 A	8/1998	Schmidt	5,959,555 A	9/1999	Furuta
5,796,094 A	8/1998	Schofield et al.	5,959,577 A	9/1999	Fan et al.
5,796,176 A	8/1998	Kramer et al.	5,963,247 A	10/1999	Banitt
5,798,057 A	8/1998	Hikmet	5,963,284 A	10/1999	Jones et al.
5,798,575 A	8/1998	O'Farrell et al.	5,965,247 A	10/1999	Jonza et al.
5,798,688 A	8/1998	Schofield	5,968,538 A	10/1999	Snyder, Jr.
5,800,918 A	9/1998	Chartier et al.	5,971,552 A	10/1999	O'Farrell et al.
5,802,727 A	9/1998	Blank et al.	5,973,760 A	10/1999	Dehmlow
5,803,579 A	9/1998	Turnbull et al.	5,975,715 A	11/1999	Bauder
5,805,330 A	9/1998	Byker et al.	5,984,482 A	11/1999	Rumsey et al.
5,805,367 A	9/1998	Kanazawa	5,986,730 A	11/1999	Hansen et al.
5,806,879 A	9/1998	Hamada et al.	5,990,469 A	11/1999	Bechtel et al.
5,806,965 A	9/1998	Deese	5,990,625 A	11/1999	Meissner et al.
5,808,197 A	9/1998	Dao	5,995,180 A	11/1999	Moriwaki et al.
5,808,566 A	9/1998	Behr et al.	5,998,617 A	12/1999	Srinivasa et al.
5,808,589 A	9/1998	Ferguson	5,998,929 A	12/1999	Bechtel et al.
5,808,713 A	9/1998	Broer et al.	6,000,823 A	12/1999	Desmond et al.
5,808,777 A	9/1998	Lynam et al.	6,001,486 A	12/1999	Varaprasad et al.
5,808,778 A	9/1998	Bauer et al.	6,002,511 A	12/1999	Varaprasad et al.
5,812,321 A	9/1998	Schierbeek et al.	6,002,544 A	12/1999	Yatsu
5,813,745 A	9/1998	Fant, Jr. et al.	6,002,983 A	12/1999	Alland et al.
5,818,625 A	10/1998	Forgette et al.	6,005,724 A	12/1999	Todd
5,820,097 A	10/1998	Spooner	6,007,222 A	12/1999	Thau
5,820,245 A	10/1998	Desmond et al.	6,008,486 A	12/1999	Stam et al.
5,822,023 A	10/1998	Suman et al.	6,008,871 A	12/1999	Okumura
5,823,654 A	10/1998	Pastrick et al.	6,009,359 A	12/1999	El-Hakim et al.
5,825,527 A	10/1998	Forgette et al.	6,016,035 A	1/2000	Eberspächer et al.
5,835,166 A	11/1998	Hall et al.	6,016,215 A	1/2000	Byker
5,837,994 A	11/1998	Stam et al.	6,019,411 A	2/2000	Carter et al.
5,844,505 A	12/1998	Van Ryzin	6,019,475 A	2/2000	Lynam et al.
5,848,373 A	12/1998	DeLorme et al.	6,020,987 A	2/2000	Baumann et al.
5,850,176 A	12/1998	Kinoshita et al.	6,021,371 A	2/2000	Fultz
5,850,205 A	12/1998	Blouin	6,023,229 A	2/2000	Bugno et al.
5,863,116 A	1/1999	Pastrick et al.	6,025,872 A	2/2000	Ozaki et al.
5,864,419 A	1/1999	Lynam	6,028,537 A	2/2000	Suman et al.
5,867,801 A	2/1999	Denny	6,037,689 A	3/2000	Bingle et al.
5,871,275 A	2/1999	O'Farrell et al.	6,040,939 A	3/2000	Demiryont et al.
5,871,843 A	2/1999	Yoneda et al.	6,042,253 A	3/2000	Fant, Jr. et al.

6,042,934 A	3/2000	Guiselin et al.	6,152,590 A	11/2000	Fürst et al.
6,045,243 A	4/2000	Muth et al.	6,154,149 A	11/2000	Tyckowski et al.
6,045,643 A	4/2000	Byker et al.	6,154,306 A	11/2000	Varaprasad et al.
6,046,766 A	4/2000	Sakata	6,157,294 A	12/2000	Urai et al.
6,046,837 A	4/2000	Yamamoto	6,157,418 A	12/2000	Rosen
6,049,171 A	4/2000	Stam et al.	6,157,424 A	12/2000	Eichenlaub
D425,466 S	5/2000	Todd et al.	6,157,480 A	12/2000	Anderson et al.
6,060,989 A	5/2000	Gehlot	6,158,655 A	12/2000	DeVries, Jr. et al.
6,061,002 A	5/2000	Weber et al.	6,161,865 A	12/2000	Rose et al.
6,062,920 A	5/2000	Jordan et al.	6,164,564 A	12/2000	Franco et al.
6,064,508 A	5/2000	Forgette et al.	6,166,625 A	12/2000	Teowee et al.
6,065,840 A	5/2000	Caskey et al.	6,166,629 A	12/2000	Hamma et al.
6,066,920 A	5/2000	Torihara et al.	6,166,834 A	12/2000	Taketomi et al.
6,067,111 A	5/2000	Hahn et al.	6,166,847 A	12/2000	Tench et al.
6,067,500 A	5/2000	Morimoto et al.	6,166,848 A	12/2000	Cammenga et al.
6,068,380 A	5/2000	Lynn et al.	6,167,755 B1	1/2001	Damson et al.
D426,506 S	6/2000	Todd et al.	6,169,955 B1	1/2001	Fultz
D426,507 S	6/2000	Todd et al.	6,170,956 B1	1/2001	Rumsey et al.
D427,128 S	6/2000	Mathieu	6,172,600 B1	1/2001	Kakinama et al.
6,072,391 A	6/2000	Suzukie et al.	6,172,601 B1	1/2001	Wada et al.
6,074,077 A	6/2000	Pastrick et al.	6,172,613 B1	1/2001	DeLine et al.
6,074,777 A	6/2000	Reimers et al.	6,173,501 B1	1/2001	Blank et al.
6,076,948 A	6/2000	Bukosky et al.	6,175,164 B1	1/2001	O'Farrell et al.
6,078,355 A	6/2000	Zengel	6,175,300 B1	1/2001	Kendrick
6,078,865 A	6/2000	Koyanagi	6,176,602 B1	1/2001	Pastrick et al.
D428,372 S	7/2000	Todd et al.	6,178,034 B1	1/2001	Allemand et al.
D428,373 S	7/2000	Todd et al.	6,178,377 B1	1/2001	Ishihara et al.
6,082,881 A	7/2000	Hicks	6,181,387 B1	1/2001	Rosen
6,084,700 A	7/2000	Knapp et al.	6,182,006 B1	1/2001	Meek
6,086,131 A	7/2000	Bingle et al.	6,183,119 B1	2/2001	Desmond et al.
6,086,229 A	7/2000	Pastrick	6,184,679 B1	2/2001	Popovic et al.
6,087,012 A	7/2000	Varaprasad et al.	6,184,781 B1	2/2001	Ramakesavan
6,087,953 A	7/2000	DeLine et al.	6,185,492 B1	2/2001	Kagawa et al.
6,091,343 A	7/2000	Dykema et al.	6,185,501 B1	2/2001	Smith et al.
6,093,976 A	7/2000	Kramer et al.	6,188,505 B1	2/2001	Lompvey et al.
6,094,618 A	7/2000	Harada	6,191,704 B1	2/2001	Takenaga et al.
D428,842 S	8/2000	Todd et al.	6,193,912 B1	2/2001	Thieste et al.
D429,202 S	8/2000	Todd et al.	6,195,194 B1	2/2001	Roberts et al.
D430,088 S	8/2000	Todd et al.	6,196,688 B1	3/2001	Caskey et al.
6,097,023 A	8/2000	Schofield et al.	6,198,409 B1	3/2001	Schofield et al.
6,097,316 A	8/2000	Liaw et al.	6,199,014 B1	3/2001	Walker et al.
6,099,131 A	8/2000	Fletcher et al.	6,199,810 B1	3/2001	Wu et al.
6,099,155 A	8/2000	Pastrick et al.	6,200,010 B1	3/2001	Anders
6,102,546 A	8/2000	Carter	6,201,642 B1	3/2001	Bos
6,102,559 A	8/2000	Nold et al.	6,206,553 B1	3/2001	Boddy et al.
6,104,552 A	8/2000	Thau et al.	6,207,083 B1	3/2001	Varaprasad et al.
6,106,121 A	8/2000	Buckley et al.	6,210,008 B1	4/2001	Hoekstra et al.
6,111,498 A	8/2000	Jobes, I et al.	6,210,012 B1	4/2001	Broer
6,111,683 A	8/2000	Cammenga et al.	6,212,470 B1	4/2001	Seymour et al.
6,111,684 A	8/2000	Forgette et al.	6,217,181 B1	4/2001	Lynam et al.
6,111,685 A	8/2000	Tench et al.	6,218,934 B1	4/2001	Regan
6,111,696 A	8/2000	Allen et al.	6,222,447 B1	4/2001	Schofield et al.
6,115,086 A	9/2000	Rosen	6,222,460 B1	4/2001	DeLine et al.
6,115,651 A	9/2000	Cruz	6,222,689 B1	4/2001	Higuchi et al.
6,116,743 A	9/2000	Hoek	6,227,689 B1	5/2001	Miller
6,118,219 A	9/2000	Okigami et al.	6,232,937 B1	5/2001	Jacobsen et al.
6,122,597 A	9/2000	Saneyoshi et al.	6,236,514 B1	5/2001	Sato
6,122,921 A	9/2000	Brezoczky et al.	6,239,851 B1	5/2001	Hatazawa et al.
6,124,647 A	9/2000	Marcus et al.	6,239,898 B1	5/2001	Byker et al.
6,124,886 A	9/2000	DeLine et al.	6,239,899 B1	5/2001	DeVries et al.
6,127,919 A	10/2000	Wysin	6,243,003 B1	6/2001	DeLine et al.
6,127,945 A	10/2000	Mura-Smith	6,244,716 B1	6/2001	Steenwyk et al.
6,128,576 A	10/2000	Nishimoto et al.	6,245,262 B1	6/2001	Varaprasad et al.
6,130,421 A	10/2000	Bechtel et al.	6,247,820 B1	6/2001	Van Order
6,130,448 A	10/2000	Bauer et al.	6,249,214 B1	6/2001	Kashiwazaki
6,132,072 A	10/2000	Turnbull et al.	6,249,310 B1	6/2001	Lefkowitz
6,137,620 A	10/2000	Guarr et al.	6,249,369 B1	6/2001	Theiste et al.
6,139,171 A	10/2000	Waldmann	6,250,148 B1	6/2001	Lynam
6,139,172 A	10/2000	Bos et al.	6,250,766 B1	6/2001	Strumolo et al.
6,140,933 A	10/2000	Bugno et al.	6,250,783 B1	6/2001	Stidham et al.
6,142,656 A	11/2000	Kurth	6,255,639 B1	7/2001	Stam et al.
6,146,003 A	11/2000	Thau	6,257,746 B1	7/2001	Todd et al.
6,147,934 A	11/2000	Arikawa et al.	6,259,412 B1	7/2001	Duroux
6,148,261 A	11/2000	Obradovich et al.	6,259,475 B1	7/2001	Ramachandran et al.
6,149,287 A	11/2000	Pastrick et al.	6,260,608 B1	7/2001	Kim
6,150,014 A	11/2000	Chu et al.	6,262,842 B1	7/2001	Ouderkirk et al.
6,151,065 A	11/2000	Steed et al.	6,264,353 B1	7/2001	Caraher et al.
6,151,539 A	11/2000	Bergholz et al.	6,265,968 B1	7/2001	Betzitza et al.
6,152,551 A	11/2000	Annas	6,268,803 B1	7/2001	Gunderson et al.

6,268,837	B1	7/2001	Kobayashi et al.	6,407,468	B1	6/2002	LeVesque et al.
6,269,308	B1	7/2001	Kodaka et al.	6,407,847	B1	6/2002	Poll et al.
6,271,901	B1	8/2001	Ide et al.	6,408,247	B1	6/2002	Ichikawa et al.
6,274,221	B2	8/2001	Smith et al.	6,411,204	B1	6/2002	Bloomfield et al.
6,276,821	B1	8/2001	Pastrick et al.	6,412,959	B1	7/2002	Tseng
6,276,822	B1	8/2001	Bedrosian et al.	6,412,973	B1	7/2002	Bos et al.
6,277,471	B1	8/2001	Tang	6,414,910	B1	7/2002	Kaneko et al.
6,278,271	B1	8/2001	Schott	6,415,230	B1	7/2002	Maruko et al.
6,278,377	B1	8/2001	DeLine et al.	6,416,208	B2	7/2002	Pastrick et al.
6,278,941	B1	8/2001	Yokoyama	6,417,786	B2	7/2002	Learman et al.
6,280,068	B1	8/2001	Mertens et al.	6,418,376	B1	7/2002	Olson
6,280,069	B1	8/2001	Pastrick et al.	6,419,300	B1	7/2002	Pavao et al.
6,281,804	B1	8/2001	Haller et al.	6,420,036	B1	7/2002	Varaprasad et al.
6,286,965	B1	9/2001	Caskey et al.	6,420,800	B1	7/2002	LeVesque et al.
6,286,984	B1	9/2001	Berg	6,420,975	B1	7/2002	DeLine et al.
6,289,332	B2	9/2001	Menig et al.	6,421,081	B1	7/2002	Markus
6,290,378	B1	9/2001	Buchalla et al.	6,424,272	B1	7/2002	Gutta et al.
6,291,905	B1	9/2001	Drummond et al.	6,424,273	B1	7/2002	Gutta et al.
6,291,906	B1	9/2001	Marcus et al.	6,424,786	B1	7/2002	Beeson et al.
6,294,989	B1	9/2001	Schofield et al.	6,424,892	B1	7/2002	Matsuoka
6,296,379	B1	10/2001	Pastrick	6,426,492	B1	7/2002	Bos et al.
6,297,781	B1	10/2001	Turnbull et al.	6,426,568	B2	7/2002	Turnbull et al.
6,299,333	B1	10/2001	Pastrick et al.	6,427,349	B1	8/2002	Blank et al.
6,300,879	B1	10/2001	Ragan et al.	6,428,172	B1	8/2002	Hutzel et al.
6,301,039	B1	10/2001	Tench	6,433,676	B2	8/2002	DeLine et al.
6,304,173	B2	10/2001	Pala et al.	6,433,680	B1	8/2002	Ho
6,305,807	B1	10/2001	Schierbeek	6,433,914	B1	8/2002	Lompfrey et al.
6,310,611	B1	10/2001	Caldwell	6,437,688	B1	8/2002	Kobayashi
6,310,714	B1	10/2001	Lompfrey et al.	6,438,491	B1	8/2002	Farmer
6,310,738	B1	10/2001	Chu	6,439,755	B1	8/2002	Fant, Jr. et al.
6,313,454	B1	11/2001	Bos et al.	6,441,872	B1	8/2002	Ho
6,314,295	B1	11/2001	Kawamoto	6,441,943	B1	8/2002	Roberts et al.
6,315,440	B1	11/2001	Satoh	6,441,963	B2	8/2002	Murakami et al.
6,317,057	B1	11/2001	Lee	6,441,964	B1	8/2002	Chu et al.
6,317,180	B1	11/2001	Kuroiwa et al.	6,445,287	B1	9/2002	Schofield et al.
6,317,248	B1	11/2001	Agrawal et al.	6,447,128	B1	9/2002	Lang et al.
6,318,870	B1	11/2001	Spooner et al.	6,449,082	B1	9/2002	Agrawal et al.
6,320,176	B1	11/2001	Schofield et al.	6,452,533	B1	9/2002	Yamabuchi et al.
6,320,282	B1	11/2001	Caldwell	6,452,572	B1	9/2002	Fan et al.
6,320,612	B1	11/2001	Young	6,462,795	B1	10/2002	Clarke
6,324,295	B1	11/2001	Valery et al.	6,463,369	B2	10/2002	Sadano et al.
6,326,613	B1	12/2001	Heslin et al.	6,466,701	B1	10/2002	Ejiri et al.
6,326,900	B2	12/2001	DeLine et al.	6,471,362	B1	10/2002	Carter et al.
6,329,925	B1	12/2001	Skiver et al.	6,472,977	B1	10/2002	Pöschmüller
6,330,511	B2	12/2001	Ogura et al.	6,472,979	B2	10/2002	Schofield et al.
6,331,066	B1	12/2001	Desmond et al.	6,473,001	B1	10/2002	Blum
6,333,759	B1	12/2001	Mazzilli	6,474,853	B2	11/2002	Pastrick et al.
6,335,680	B1	1/2002	Matsuoka	6,476,731	B1	11/2002	Miki et al.
6,336,737	B1	1/2002	Thau	6,477,460	B2	11/2002	Kepler
6,340,850	B2	1/2002	O'Farrell et al.	6,477,464	B2	11/2002	McCarthy et al.
6,341,523	B2	1/2002	Lynam	6,483,429	B1	11/2002	Yasui et al.
6,344,805	B1	2/2002	Yasui et al.	6,483,438	B2	11/2002	DeLine et al.
6,346,698	B1	2/2002	Turnbull	6,483,613	B1	11/2002	Woodgate et al.
6,347,880	B1	2/2002	Fürst et al.	6,487,500	B2	11/2002	Lemelson et al.
6,348,858	B2	2/2002	Weis et al.	6,494,602	B2	12/2002	Pastrick et al.
6,351,708	B1	2/2002	Takagi et al.	6,498,620	B2	12/2002	Schofield et al.
6,353,392	B1	3/2002	Schofield et al.	6,501,387	B2	12/2002	Skiver et al.
6,356,206	B1	3/2002	Takenaga et al.	6,512,203	B2	1/2003	Jones et al.
6,356,376	B1	3/2002	Tonar et al.	6,512,624	B2	1/2003	Tonar et al.
6,356,389	B1	3/2002	Nilsen et al.	6,513,252	B1	2/2003	Schierbeek et al.
6,357,883	B1	3/2002	Strumolo et al.	6,515,581	B1	2/2003	Ho
6,362,121	B1	3/2002	Chopin et al.	6,515,582	B1	2/2003	Teowee
6,362,548	B1	3/2002	Bingle et al.	6,515,597	B1	2/2003	Wada et al.
6,363,326	B1	3/2002	Scully	6,516,664	B2	2/2003	Lynam
6,366,013	B1	4/2002	Leenders et al.	6,518,691	B1	2/2003	Baba
6,366,213	B2	4/2002	DeLine et al.	6,519,209	B1	2/2003	Arikawa et al.
6,370,329	B1	4/2002	Teuchert	6,520,667	B1	2/2003	Mousseau
6,371,636	B1	4/2002	Wesson	6,522,451	B1	2/2003	Lynam
6,379,013	B1	4/2002	Bechtel et al.	6,522,969	B2	2/2003	Kannonji
6,379,788	B2	4/2002	Choi et al.	6,525,707	B1	2/2003	Kaneko et al.
6,382,805	B1	5/2002	Miyabukuro	6,534,884	B2	3/2003	Marcus et al.
6,385,139	B1	5/2002	Arikawa et al.	6,538,709	B1	3/2003	Kurihara et al.
6,386,742	B1	5/2002	DeLine et al.	6,539,306	B2	3/2003	Turnbull et al.
6,390,529	B1	5/2002	Bingle et al.	6,542,085	B1	4/2003	Yang
6,390,626	B2	5/2002	Knox	6,542,182	B1	4/2003	Chautorash
6,390,635	B2	5/2002	Whitehead et al.	6,543,163	B1	4/2003	Ginsberg
6,396,397	B1	5/2002	Bos et al.	6,545,598	B1	4/2003	de Villeroche
6,396,408	B2	5/2002	Drummond et al.	6,549,253	B1	4/2003	Robbie et al.
6,396,637	B2	5/2002	Roest et al.	6,549,335	B1	4/2003	Trapani et al.

US 8,228,588 B2

Page 8

6,550,949	B1	4/2003	Bauer et al.	6,690,268	B2	2/2004	Schofield et al.
6,552,326	B2	4/2003	Turnbull	6,690,413	B1	2/2004	Moore
6,553,308	B1	4/2003	Uhlmann et al.	6,690,438	B2	2/2004	Sekiguchi
6,559,902	B1	5/2003	Kusuda et al.	6,693,517	B2	2/2004	McCarthy et al.
6,560,004	B2	5/2003	Theiste et al.	6,693,518	B2	2/2004	Kumata et al.
6,560,027	B2	5/2003	Meine	6,693,519	B2	2/2004	Keirstead
6,566,821	B2	5/2003	Nakatsuka et al.	6,693,524	B1	2/2004	Payne
6,567,060	B1	5/2003	Sekiguchi	6,700,692	B2	3/2004	Tonar et al.
6,568,839	B1	5/2003	Pastrick et al.	6,709,136	B2	3/2004	Pastrick et al.
6,572,233	B1	6/2003	Northman et al.	6,713,783	B1	3/2004	Mase et al.
6,573,957	B1	6/2003	Suzuki	6,717,109	B1	4/2004	Macher et al.
6,573,963	B2	6/2003	Ouderkirk et al.	6,717,610	B1	4/2004	Bos et al.
6,575,582	B2	6/2003	Tenmyo	6,717,712	B2	4/2004	Lynam et al.
6,575,643	B2	6/2003	Takahashi	6,719,215	B2	4/2004	Droulliard
6,578,989	B2	6/2003	Osumi et al.	6,724,446	B2	4/2004	Motomura et al.
6,580,373	B1	6/2003	Ohashi	6,726,337	B2	4/2004	Whitehead et al.
6,580,479	B1	6/2003	Sekiguchi et al.	6,727,807	B2	4/2004	Trajkovic et al.
6,580,562	B2	6/2003	Aoki et al.	6,727,808	B1	4/2004	Uselmann et al.
6,581,007	B2	6/2003	Hasegawa et al.	6,727,844	B1	4/2004	Zimmermann et al.
6,583,730	B2	6/2003	Lang et al.	6,731,332	B1	5/2004	Yasui et al.
6,591,192	B2	7/2003	Okamura et al.	6,734,807	B2	5/2004	King
6,592,230	B2	7/2003	Dupay	6,736,526	B2	5/2004	Matsuba et al.
6,593,565	B2	7/2003	Heslin et al.	6,737,629	B2	5/2004	Nixon et al.
6,593,984	B2	7/2003	Arakawa et al.	6,737,630	B2	5/2004	Turnbull
6,594,065	B2	7/2003	Byker et al.	6,737,964	B2	5/2004	Samman et al.
6,594,067	B2	7/2003	Poll et al.	6,738,088	B1	5/2004	Uskolovsky et al.
6,594,090	B2	7/2003	Kruschwitz et al.	6,742,904	B2	6/2004	Bechtel et al.
6,594,583	B2	7/2003	Ogura et al.	6,744,353	B2	6/2004	Sjonnell
6,594,614	B2	7/2003	Studt et al.	6,746,775	B1	6/2004	Boire et al.
6,595,649	B2	7/2003	Hoekstra et al.	6,747,716	B2	6/2004	Kuroiwa et al.
6,597,489	B1	7/2003	Guarr et al.	6,748,211	B1	6/2004	Isaac et al.
6,606,183	B2	8/2003	Ikai et al.	6,749,308	B1	6/2004	Niendorf et al.
6,611,202	B2	8/2003	Schofield et al.	6,755,542	B2	6/2004	Bechtel et al.
6,611,227	B1	8/2003	Nebiyeloul-Kifle et al.	6,756,912	B2	6/2004	Skiver et al.
6,611,759	B2	8/2003	Brosche	6,757,039	B2	6/2004	Ma
6,614,387	B1	9/2003	Deadman	6,757,109	B2	6/2004	Bos
6,614,419	B1	9/2003	May	D493,131	S	7/2004	Lawlor et al.
6,614,579	B2	9/2003	Roberts et al.	D493,394	S	7/2004	Lawlor et al.
6,615,438	B1	9/2003	Franco et al.	6,759,113	B1	7/2004	Tang
6,616,313	B2	9/2003	Fürst et al.	6,759,945	B2	7/2004	Richard
6,616,764	B2	9/2003	Krämer et al.	6,760,157	B1	7/2004	Allen et al.
6,618,672	B2	9/2003	Sasaki et al.	6,773,116	B2	8/2004	De Vaan et al.
6,621,616	B1	9/2003	Bauer et al.	6,774,356	B2	8/2004	Heslin et al.
6,624,936	B2	9/2003	Kotchick et al.	6,774,810	B2	8/2004	DeLine et al.
6,627,918	B2	9/2003	Getz et al.	6,778,904	B2	8/2004	Iwami et al.
6,630,888	B2	10/2003	Lang et al.	6,779,900	B1	8/2004	Nolan-Brown
6,636,190	B2	10/2003	Hirakata et al.	6,784,129	B2	8/2004	Seto et al.
6,636,258	B2	10/2003	Strumolo	6,797,396	B1	9/2004	Liu et al.
6,638,582	B1	10/2003	Uchiyama et al.	6,800,871	B2	10/2004	Matsuda et al.
6,639,360	B2	10/2003	Roberts et al.	6,801,283	B2	10/2004	Koyama et al.
6,642,840	B2	11/2003	Lang et al.	6,805,474	B2	10/2004	Walser et al.
6,642,851	B2	11/2003	DeLine et al.	6,806,452	B2	10/2004	Bos et al.
6,646,697	B1	11/2003	Sekiguchi et al.	6,806,922	B2	10/2004	Ishitaka
6,648,477	B2	11/2003	Hutzel et al.	6,810,323	B1	10/2004	Bullock et al.
6,650,457	B2	11/2003	Busscher et al.	6,812,907	B1	11/2004	Gennetten et al.
6,657,607	B1	12/2003	Evanicky et al.	6,819,231	B2	11/2004	Berberich et al.
6,657,708	B1	12/2003	Drevillon et al.	6,824,281	B2	11/2004	Schofield et al.
6,661,482	B2	12/2003	Hara	6,831,268	B2	12/2004	Bechtel et al.
6,661,830	B1	12/2003	Reed et al.	6,832,848	B2	12/2004	Pastrick
6,665,592	B2	12/2003	Kodama	6,834,969	B2	12/2004	Bade et al.
6,669,109	B2	12/2003	Ivanov et al.	6,836,725	B2	12/2004	Millington et al.
6,669,285	B1	12/2003	Park et al.	6,842,276	B2	1/2005	Poll et al.
6,670,207	B1	12/2003	Roberts	6,845,805	B1	1/2005	Köster
6,670,910	B2	12/2003	Delcheccolo et al.	6,846,098	B2	1/2005	Bourdelaais et al.
6,670,941	B2	12/2003	Albu et al.	6,847,424	B2	1/2005	Gotoh et al.
6,671,080	B2	12/2003	Poll et al.	6,847,487	B2	1/2005	Burgner
6,672,731	B2	1/2004	Schnell et al.	6,848,817	B2	2/2005	Bos et al.
6,672,734	B2	1/2004	Lammers	6,849,165	B2	2/2005	Klöppel et al.
6,672,744	B2	1/2004	DeLine et al.	6,853,491	B1	2/2005	Ruhle et al.
6,672,745	B1	1/2004	Bauer et al.	6,861,789	B2	3/2005	Wei
6,674,370	B2	1/2004	Rodewald et al.	6,870,655	B1	3/2005	Northman et al.
6,675,075	B1	1/2004	Engelsburg et al.	6,870,656	B2	3/2005	Tonar et al.
6,678,083	B1	1/2004	Anstee	6,871,982	B2	3/2005	Holman et al.
6,678,614	B2	1/2004	McCarthy et al.	6,877,888	B2	4/2005	DeLine et al.
6,679,608	B2	1/2004	Bechtel et al.	6,882,287	B2	4/2005	Schofield
6,683,539	B2	1/2004	Trajkovic et al.	6,889,064	B2	5/2005	Baratono et al.
6,683,969	B1	1/2004	Nishigaki et al.	6,891,563	B2	5/2005	Schofield et al.
6,685,348	B2	2/2004	Pastrick et al.	6,891,677	B2	5/2005	Nilsen et al.
6,690,262	B1	2/2004	Winnett	6,902,284	B2	6/2005	Hutzel et al.

6,904,348 B2	6/2005	Drummond et al.	7,206,697 B2	4/2007	Olney et al.
6,906,632 B2	6/2005	DeLine et al.	7,209,277 B2	4/2007	Tonar et al.
6,909,486 B2	6/2005	Wang et al.	7,215,238 B2	5/2007	Buck et al.
6,910,779 B2	6/2005	Abel et al.	7,215,473 B2	5/2007	Fleming
6,912,396 B2	6/2005	Sziraki et al.	7,221,363 B2	5/2007	Roberts et al.
6,916,099 B2	7/2005	Su et al.	7,224,324 B2	5/2007	Quist et al.
6,922,902 B2	8/2005	Schierbeek et al.	7,227,472 B1	6/2007	Roe
6,928,180 B2	8/2005	Stam et al.	7,230,523 B2	6/2007	Harter, Jr. et al.
6,928,366 B2	8/2005	Ockerse et al.	7,232,231 B2	6/2007	Shih
6,930,737 B2	8/2005	Weindorf et al.	7,233,304 B1	6/2007	Aratani et al.
6,934,067 B2	8/2005	Ash et al.	7,235,918 B2	6/2007	McCullough et al.
6,946,978 B2	9/2005	Schofield	7,241,030 B2	7/2007	Mok et al.
6,947,576 B2	9/2005	Stam et al.	7,241,037 B2	7/2007	Mathieu et al.
6,947,577 B2	9/2005	Stam et al.	7,245,207 B1	7/2007	Dayan et al.
6,949,772 B2	9/2005	Shimizu et al.	7,245,231 B2	7/2007	Kiefer et al.
6,951,410 B2	10/2005	Parsons	7,245,336 B2	7/2007	Hiyama et al.
6,951,681 B2	10/2005	Hartley et al.	7,248,305 B2	7/2007	Ootsuta et al.
6,952,312 B2	10/2005	Weber et al.	7,251,079 B2	7/2007	Capaldo et al.
6,958,495 B2	10/2005	Nishijima et al.	7,255,451 B2	8/2007	McCabe et al.
6,958,683 B2	10/2005	Mills et al.	7,255,465 B2	8/2007	DeLine et al.
6,961,178 B2	11/2005	Sugino et al.	7,259,036 B2	8/2007	Borland et al.
6,963,438 B2	11/2005	Busscher et al.	7,262,406 B2	8/2007	Heslin et al.
6,968,973 B2	11/2005	Uyttendaele et al.	7,262,916 B2	8/2007	Kao et al.
6,972,888 B2	12/2005	Poll et al.	7,265,342 B2	9/2007	Heslin et al.
6,974,236 B2	12/2005	Tenmyo	7,268,841 B2	9/2007	Kasajima et al.
6,975,215 B2	12/2005	Schofield et al.	7,269,327 B2	9/2007	Tang
6,977,702 B2	12/2005	Wu	7,269,328 B2	9/2007	Tang
6,980,092 B2	12/2005	Turnbull et al.	7,271,951 B2	9/2007	Weber et al.
6,985,291 B2	1/2006	Watson et al.	7,274,501 B2	9/2007	McCabe et al.
6,992,718 B1	1/2006	Takahara	7,281,491 B2	10/2007	Iwamaru
7,001,058 B2	2/2006	Inditsky	7,286,280 B2	10/2007	Whitehead et al.
7,004,592 B2	2/2006	Varaprasad et al.	7,287,868 B2	10/2007	Carter et al.
7,004,593 B2	2/2006	Weller et al.	7,289,037 B2	10/2007	Uken et al.
7,006,173 B1	2/2006	Hiyama et al.	7,290,919 B2	11/2007	Pan et al.
7,009,751 B2	3/2006	Tonar et al.	7,292,208 B1	11/2007	Park et al.
7,012,543 B2	3/2006	DeLine et al.	7,300,183 B2	11/2007	Kiyomoto et al.
7,029,156 B2	4/2006	Suehiro et al.	7,302,344 B2	11/2007	Olney et al.
7,038,577 B2	5/2006	Pawlicki et al.	7,308,341 B2	12/2007	Schofield et al.
7,041,965 B2	5/2006	Heslin et al.	7,310,177 B2	12/2007	McCabe et al.
7,042,616 B2	5/2006	Tonar et al.	7,311,428 B2	12/2007	DeLine et al.
7,046,418 B2	5/2006	Lin et al.	7,316,485 B2	1/2008	Roose
7,046,448 B2	5/2006	Burgner	7,317,386 B2	1/2008	Lengning et al.
7,050,908 B1	5/2006	Schwartz et al.	7,318,664 B2	1/2008	Hatanaka et al.
7,057,681 B2	6/2006	Hinata et al.	7,323,819 B2	1/2008	Hong et al.
7,063,893 B2	6/2006	Hoffman	7,324,043 B2	1/2008	Purden et al.
7,064,882 B2	6/2006	Tonar et al.	7,324,172 B2	1/2008	Yamazaki et al.
7,074,486 B2	7/2006	Boire et al.	7,324,174 B2	1/2008	Hafuka et al.
7,081,810 B2	7/2006	Henderson et al.	7,324,261 B2	1/2008	Tonar et al.
7,092,052 B2	8/2006	Okamoto et al.	7,327,225 B2	2/2008	Nicholas et al.
7,095,567 B2	8/2006	Troxell et al.	7,327,226 B2	2/2008	Turnbull et al.
7,106,213 B2	9/2006	White	7,327,855 B1	2/2008	Chen
7,106,392 B2	9/2006	You	7,328,103 B2	2/2008	McCarthy et al.
7,108,409 B2	9/2006	DeLine et al.	7,329,013 B2	2/2008	Blank et al.
7,114,554 B2	10/2006	Bergman et al.	7,329,850 B2	2/2008	Drummond et al.
7,121,028 B2	10/2006	Shoen et al.	7,331,415 B2	2/2008	Hawes et al.
7,125,131 B2	10/2006	Olczak	7,338,177 B2	3/2008	Lynam
7,130,727 B2	10/2006	Liu et al.	7,344,284 B2	3/2008	Lynam et al.
7,132,064 B2	11/2006	Li et al.	7,349,143 B2	3/2008	Tonar et al.
7,136,091 B2	11/2006	Ichikawa et al.	7,349,582 B2	3/2008	Takeda et al.
7,138,974 B2	11/2006	Hirakata et al.	7,355,524 B2	4/2008	Schofield
7,149,613 B2	12/2006	Stam et al.	7,360,932 B2	4/2008	Uken et al.
7,151,515 B2	12/2006	Kim et al.	7,362,505 B2	4/2008	Hikmet et al.
7,151,997 B2	12/2006	Uhlmann et al.	7,368,714 B2	5/2008	Remillard et al.
7,153,588 B2	12/2006	McMan et al.	7,370,983 B2	5/2008	DeWind et al.
7,154,657 B2	12/2006	Poll et al.	7,372,611 B2	5/2008	Tonar et al.
7,158,881 B2	1/2007	McCarthy et al.	7,375,895 B2	5/2008	Brynielsson
7,160,017 B2	1/2007	Lee et al.	7,379,224 B2	5/2008	Tonar et al.
7,161,567 B2	1/2007	Homma et al.	7,379,225 B2	5/2008	Tonar et al.
7,167,796 B2	1/2007	Taylor et al.	7,379,243 B2	5/2008	Horsten et al.
7,168,830 B2	1/2007	Pastrick et al.	7,379,814 B2	5/2008	Ockerse et al.
7,175,291 B1	2/2007	Li	7,379,817 B1	5/2008	Tyson et al.
7,176,790 B2	2/2007	Yamazaki	7,380,633 B2	6/2008	Shen et al.
7,184,190 B2	2/2007	McCabe et al.	7,389,171 B2	6/2008	Rupp
7,185,995 B2	3/2007	Hatanaka et al.	7,391,563 B2	6/2008	McCabe et al.
7,187,498 B2	3/2007	Bengoechea et al.	7,396,147 B2	7/2008	Munro
7,188,963 B2	3/2007	Schofield et al.	7,411,732 B2	8/2008	Kao et al.
7,193,764 B2	3/2007	Lin et al.	7,412,328 B2	8/2008	Uhlmann et al.
7,195,381 B2	3/2007	Lynam et al.	7,417,781 B2	8/2008	Tonar et al.
7,199,767 B2	4/2007	Spero	7,420,159 B2	9/2008	Heslin et al.

7,446,462 B2	11/2008	Lim et al.	7,734,392 B2	6/2010	Schofield et al.
7,446,650 B2	11/2008	Schofield et al.	7,746,534 B2	6/2010	Tonar et al.
7,446,924 B2	11/2008	Schofield et al.	7,787,077 B2	8/2010	Kondoh et al.
7,448,776 B2	11/2008	Tang	7,791,694 B2	9/2010	Molsen et al.
7,452,090 B2	11/2008	Weller et al.	7,795,675 B2	9/2010	Darwish et al.
7,453,057 B2	11/2008	Drummond et al.	7,830,583 B2	11/2010	Neuman et al.
7,455,412 B2	11/2008	Rottcher	7,842,154 B2	11/2010	Lynam
7,460,007 B2	12/2008	Schofield et al.	2001/0019356 A1	9/2001	Takeda et al.
7,467,883 B2	12/2008	DeLine et al.	2001/0022616 A1	9/2001	Rademacher et al.
7,468,651 B2	12/2008	DeLine et al.	2001/0026215 A1	10/2001	Nakaho et al.
7,471,438 B2	12/2008	McCabe et al.	2001/0026316 A1	10/2001	Senatore
7,474,963 B2	1/2009	Taylor et al.	2001/0030857 A1	10/2001	Futhey et al.
7,477,439 B2	1/2009	Tonar et al.	2001/0035853 A1	11/2001	Hoelen et al.
7,480,149 B2	1/2009	DeWard et al.	2001/0045981 A1	11/2001	Gloger et al.
7,488,080 B2	2/2009	Skiver et al.	2002/0036828 A1	3/2002	Wong
7,488,099 B2	2/2009	Fogg et al.	2002/0044065 A1	4/2002	Quist et al.
7,489,374 B2	2/2009	Utsumi et al.	2002/0049535 A1	4/2002	Rigo et al.
7,490,007 B2	2/2009	Taylor et al.	2002/0085155 A1	7/2002	Arikawa
7,490,943 B2	2/2009	Kikuchi et al.	2002/0092958 A1	7/2002	Lusk
7,490,944 B2	2/2009	Blank et al.	2002/0118321 A1	8/2002	Ge
7,494,231 B2	2/2009	Varaprasad et al.	2002/0133144 A1	9/2002	Chan et al.
7,495,719 B2	2/2009	Adachi et al.	2002/0149727 A1	10/2002	Wang
7,496,439 B2	2/2009	McCormick	2002/0154007 A1	10/2002	Yang
7,502,156 B2	3/2009	Tonar et al.	2002/0196639 A1	12/2002	Weidel
7,505,188 B2	3/2009	Niiyama et al.	2003/0002165 A1	1/2003	Mathias et al.
7,511,607 B2	3/2009	Hubbard et al.	2003/0002179 A1	1/2003	Roberts et al.
7,511,872 B2	3/2009	Tonar et al.	2003/0007261 A1	1/2003	Hutzel et al.
7,525,715 B2	4/2009	McCabe et al.	2003/0016287 A1	1/2003	Nakayama et al.
7,526,103 B2	4/2009	Schofield et al.	2003/0016542 A1	1/2003	Pastrick et al.
7,533,998 B2	5/2009	Schofield et al.	2003/0025596 A1	2/2003	Lang et al.
7,538,316 B2	5/2009	Heslin et al.	2003/0030546 A1	2/2003	Tseng
7,540,620 B2	6/2009	Weller et al.	2003/0030724 A1	2/2003	Okamoto
7,541,570 B2	6/2009	Drummond et al.	2003/0035050 A1	2/2003	Mizusawa et al.
7,542,193 B2	6/2009	McCabe et al.	2003/0043269 A1	3/2003	Park
7,543,947 B2	6/2009	Varaprasad et al.	2003/0043589 A1	3/2003	Blank
7,547,467 B2	6/2009	Olson et al.	2003/0048639 A1	3/2003	Boyd et al.
7,548,291 B2	6/2009	Lee et al.	2003/0052969 A1	3/2003	Satoh et al.
7,551,354 B2	6/2009	Horsten et al.	2003/0058338 A1	3/2003	Kawauchi et al.
7,561,181 B2	7/2009	Schofield et al.	2003/0069690 A1	4/2003	Correia et al.
7,562,985 B2	7/2009	Cortenraad et al.	2003/0080877 A1	5/2003	Takagi et al.
7,567,291 B2	7/2009	Bechtel et al.	2003/0088361 A1	5/2003	Sekiguchi
7,571,038 B2	8/2009	Butler et al.	2003/0090568 A1	5/2003	Pico
7,571,042 B2	8/2009	Taylor et al.	2003/0090569 A1	5/2003	Poechmueller
7,572,490 B2	8/2009	Park et al.	2003/0090570 A1	5/2003	Takagi et al.
7,579,939 B2	8/2009	Schofield et al.	2003/0095331 A1	5/2003	Bengoechea et al.
7,579,940 B2	8/2009	Schofield et al.	2003/0098908 A1	5/2003	Misaiji et al.
7,580,795 B2	8/2009	McCarthy et al.	2003/0101749 A1	6/2003	Lingle et al.
7,581,859 B2	9/2009	Lynam	2003/0103142 A1	6/2003	Hitomi et al.
7,581,867 B2	9/2009	Lee et al.	2003/0117522 A1	6/2003	Okada
7,583,184 B2	9/2009	Schofield et al.	2003/0122929 A1	7/2003	Minuado et al.
7,586,566 B2	9/2009	Nelson et al.	2003/0133014 A1	7/2003	Mendoza
7,586,666 B2	9/2009	McCabe et al.	2003/0137586 A1	7/2003	Lewellen
7,589,893 B2	9/2009	Rottcher	2003/0141965 A1	7/2003	Gunderson et al.
7,600,878 B2	10/2009	Blank et al.	2003/0146831 A1	8/2003	Berberich et al.
7,605,883 B2	10/2009	Yamaki et al.	2003/0156193 A1	8/2003	Nakamura
7,619,508 B2	11/2009	Lynam et al.	2003/0169158 A1	9/2003	Paul, Jr.
7,623,202 B2	11/2009	Araki et al.	2003/0179293 A1	9/2003	Oizumi
7,626,749 B2	12/2009	Baur et al.	2003/0202096 A1	10/2003	Kim
7,633,567 B2	12/2009	Yamada et al.	2003/0206256 A1	11/2003	Drain et al.
7,636,188 B2	12/2009	Baur et al.	2003/0214576 A1	11/2003	Koga
7,636,195 B2	12/2009	Nieuwkerk et al.	2003/0214584 A1	11/2003	Ross, Jr.
7,636,930 B2	12/2009	Chang	2003/0214733 A1	11/2003	Fujikawa et al.
7,643,200 B2	1/2010	Varaprasad et al.	2003/0222793 A1	12/2003	Tanaka et al.
7,643,927 B2	1/2010	Hils	2003/0222983 A1	12/2003	Nobori et al.
7,651,228 B2	1/2010	Skiver et al.	2003/0227546 A1	12/2003	Hilborn et al.
7,658,521 B2	2/2010	DeLine et al.	2004/0004541 A1	1/2004	Hong
7,663,798 B2 *	2/2010	Tonar et al. 359/265	2004/0027695 A1	2/2004	Lin
7,667,579 B2	2/2010	DeLine et al.	2004/0032321 A1	2/2004	McMahon et al.
7,670,016 B2	3/2010	Weller et al.	2004/0032655 A1	2/2004	Kikuchi et al.
7,688,495 B2	3/2010	Tonar et al.	2004/0032676 A1	2/2004	Drummond et al.
7,695,174 B2	4/2010	Takayanagi et al.	2004/0036768 A1	2/2004	Green
7,696,964 B2	4/2010	Lankhorst et al.	2004/0046870 A1	3/2004	Leigh Travis
7,706,046 B2	4/2010	Bauer et al.	2004/0051634 A1	3/2004	Schofield et al.
7,710,631 B2	5/2010	McCabe et al.	2004/0056955 A1	3/2004	Berberich et al.
7,711,479 B2	5/2010	Taylor et al.	2004/0057131 A1	3/2004	Hutzel et al.
7,726,822 B2	6/2010	Blank et al.	2004/0064241 A1	4/2004	Sekiguchi
7,728,276 B2	6/2010	Drummond et al.	2004/0066285 A1	4/2004	Sekiguchi
7,728,721 B2	6/2010	Schofield et al.	2004/0075603 A1	4/2004	Kodama
7,728,927 B2	6/2010	Nieuwkerk et al.	2004/0077359 A1	4/2004	Bernas et al.

2004/0080404	A1	4/2004	White	2009/0201137	A1	8/2009	Weller et al.
2004/0085196	A1	5/2004	Miller et al.	2009/0219394	A1	9/2009	Heslin et al.
2004/0085499	A1	5/2004	Baek	2009/0231741	A1	9/2009	Weller et al.
2004/0090314	A1	5/2004	Iwamoto	2009/0237820	A1	9/2009	McCabe et al.
2004/0090317	A1	5/2004	Rothkop	2009/0243824	A1	10/2009	Hook et al.
2004/0096082	A1	5/2004	Nakai et al.	2009/0244740	A1	10/2009	Takayanagi et al.
2004/0098196	A1	5/2004	Sekiguchi	2009/0262192	A1	10/2009	Schofield et al.
2004/0105614	A1	6/2004	Kobayashi et al.	2009/0262422	A1	10/2009	Cross et al.
2004/0107030	A1	6/2004	Nishira et al.	2009/0290369	A1	11/2009	Schofield et al.
2004/0109060	A1	6/2004	Ishii	2009/0296190	A1	12/2009	Anderson et al.
2004/0114039	A1	6/2004	Ishikura	2010/0033797	A1	2/2010	Schofield et al.
2004/0170008	A1	9/2004	Tenmyo	2010/0045790	A1	2/2010	Lynam et al.
2004/0202001	A1	10/2004	Roberts et al.	2010/0045899	A1	2/2010	Ockerse
2004/0239243	A1	12/2004	Roberts et al.	2010/0046059	A1	2/2010	McCabe et al.
2004/0239849	A1	12/2004	Wang	2010/0053723	A1	3/2010	Varaprasad et al.
2004/0243303	A1	12/2004	Padmanabhan	2010/0085645	A1	4/2010	Skiver et al.
2004/0264011	A1	12/2004	Lynam	2010/0091509	A1	4/2010	DeLine et al.
2005/0018738	A1	1/2005	Duan et al.	2010/0110523	A1	5/2010	Varaprasad et al.
2005/0024591	A1	2/2005	Lian et al.	2010/0110553	A1	5/2010	Anderson et al.
2005/0024729	A1	2/2005	Ockerse et al.	2010/0117815	A1	5/2010	Deline et al.
2005/0078389	A1	4/2005	Kulas et al.	2010/0126030	A1	5/2010	Weller et al.
2005/0079326	A1	4/2005	Varaprasad et al.	2010/0165437	A1	7/2010	Tonar et al.
2005/0099559	A1	5/2005	Lee et al.	2010/0172008	A1	7/2010	McCabe et al.
2005/0099693	A1	5/2005	Schofield et al.	2010/0174485	A1	7/2010	Taylor et al.
2005/0111070	A1	5/2005	Lin et al.	2010/0194890	A1	8/2010	Weller et al.
2005/0117095	A1	6/2005	Ma	2010/0195226	A1	8/2010	Heslin et al.
2005/0134983	A1	6/2005	Lynam	2010/0201896	A1	8/2010	Ostreko et al.
2005/0140855	A1	6/2005	Utsumi et al.	2010/0202075	A1	8/2010	Blank et al.
2005/0168995	A1	8/2005	Kittlemann et al.	2010/0207013	A1	8/2010	Drummond et al.
2005/0169003	A1	8/2005	Lindahl et al.	2010/0214662	A1	8/2010	Takayanagi et al.
2005/0172504	A1	8/2005	Ohm et al.	2010/0219985	A1	9/2010	Schofield et al.
2005/0237440	A1	10/2005	Sugimura et al.	2010/0222963	A1	9/2010	Schofield et al.
2005/0270766	A1	12/2005	Kung et al.	2010/0245701	A1	9/2010	Sato et al.
2006/0001641	A1	1/2006	Degwekar et al.	2010/0246017	A1	9/2010	Tonar et al.
2006/0050018	A1	3/2006	Hutzel et al.	2010/0277786	A1	11/2010	Anderson et al.
2006/0061008	A1	3/2006	Karner et al.	2010/0289995	A1	11/2010	Hwang et al.
2006/0076860	A1	4/2006	Hoss	2011/0109746	A1	5/2011	Schofield et al.
2006/0139953	A1	6/2006	Chou et al.	2011/0141543	A1	6/2011	Uken et al.
2006/0164230	A1	7/2006	DeWind et al.				
2006/0171704	A1	8/2006	Bingle et al.				
2006/0187378	A1	8/2006	Bong et al.				
2006/0274218	A1	12/2006	Xue	CN	1189224		7/1998
2006/0279522	A1	12/2006	Kurihara	DE	941408		4/1956
2007/0041096	A1	2/2007	Nieuwkerk et al.	DE	944531		7/1956
2007/0058257	A1	3/2007	Lynam	DE	7323996		11/1973
2007/0064108	A1	3/2007	Haler	DE	3248511	A1	7/1984
2007/0080585	A1	4/2007	Lyu	DE	3301945		7/1984
2007/0118287	A1	5/2007	Taylor et al.	DE	3614882		11/1987
2007/0183037	A1	8/2007	De Boer et al.	DE	3720848		1/1989
2007/0183066	A1	8/2007	Varaprasad et al.	DE	9306989.8	U1	7/1993
2007/0184284	A1	8/2007	Varaprasad et al.	DE	4329983		8/1995
2007/0201122	A1	8/2007	Dozeman et al.	DE	4444443	A1	6/1996
2007/0262732	A1	11/2007	Shen	DE	29703084	U1	6/1997
2008/0002106	A1	1/2008	Van De Witte et al.	DE	29805142	U1	5/1998
2008/0030311	A1	2/2008	Dayan et al.	DE	19741896		4/1999
2008/0068520	A1	3/2008	Minikey, Jr. et al.	DE	19755008		7/1999
2008/0077882	A1	3/2008	Kramer et al.	DE	29902344	U1	7/1999
2008/0094685	A1	4/2008	Varaprasad et al.	DE	19934999		2/2001
2008/0180529	A1	7/2008	Taylor et al.	DE	19943355		3/2001
2008/0180781	A1	7/2008	Varaprasad et al.	DE	20118868		3/2002
2008/0212189	A1	9/2008	Baur et al.	DE	10131459		1/2003
2008/0225538	A1	9/2008	Lynam et al.	EP	0299509	A2	1/1989
2008/0231704	A1	9/2008	Schofield et al.	EP	0513476	A1	11/1992
2008/0266389	A1	10/2008	DeWind et al.	EP	0524766		1/1993
2008/0291522	A1	11/2008	Varaprasad et al.	EP	0729864	A1	12/1995
2009/0002491	A1	1/2009	Haler	EP	0728618	A2	8/1996
2009/0015736	A1	1/2009	Weller et al.	EP	0825477		2/1998
2009/0033837	A1	2/2009	Molsen et al.	EP	0830985		3/1998
2009/0040465	A1	2/2009	Conner et al.	EP	0928723	A2	7/1999
2009/0040588	A1	2/2009	Tonar et al.	EP	937601	A2	8/1999
2009/0040778	A1	2/2009	Takayanagi et al.	EP	1075986		2/2001
2009/0052003	A1	2/2009	Schofield et al.	EP	1097848	A	5/2001
2009/0067032	A1	3/2009	Varaprasad et al.	EP	1152285	A2	11/2001
2009/0080055	A1	3/2009	Baur et al.	EP	1193773		3/2002
2009/0085729	A1	4/2009	Nakamura et al.	EP	1256833		11/2002
2009/0096937	A1	4/2009	Bauer et al.	EP	0899157		10/2004
2009/0141331	A1	6/2009	Skiver et al.	EP	1315639		2/2006
2009/0174776	A1	7/2009	Taylor et al.	FR	1021987	A	2/1953
2009/0184904	A1	7/2009	S. et al.	FR	1461419		12/1966
				FR	2585991		2/1987

FR	2672857	A1	8/1992
FR	2673499	A1	9/1992
FR	2759045		8/1998
GB	810010		3/1959
GB	934037		8/1963
GB	1008411		10/1965
GB	1136134		12/1968
GB	1553376		9/1979
GB	2137573	A	10/1984
GB	2161440		1/1986
GB	2192370		1/1988
GB	2222991		3/1990
GB	2255539	A	11/1992
GB	2351055	A	12/2000
GB	2362494		11/2001
JP	50-000638	A	1/1975
JP	52-146988		11/1977
JP	55-039843		3/1980
JP	57-30639		2/1982
JP	57-208530		12/1982
JP	58-030729		2/1983
JP	58020954		2/1983
JP	58-110334		6/1983
JP	58-180347		10/1983
JP	58-209635		12/1983
JP	59-114139		7/1984
JP	60-212730		10/1985
JP	60-261275		12/1985
JP	61127186		6/1986
JP	61-260217		11/1986
JP	62-043543		2/1987
JP	62-075619		4/1987
JP	62-122487		6/1987
JP	62131232		6/1987
JP	63-02753		1/1988
JP	63085525		4/1988
JP	63-106730		5/1988
JP	63-106731		5/1988
JP	63-274286		11/1988
JP	64-14700		1/1989
JP	01-123587		5/1989
JP	01130578		5/1989
JP	02-122844		10/1990
JP	03-28947		3/1991
JP	03-052097		3/1991
JP	30-061192		3/1991
JP	328947		3/1991
JP	03-110855		5/1991
JP	03198026		8/1991
JP	03-243914		10/1991
JP	04-114587		4/1992
JP	04-245886		9/1992
JP	05080716		4/1993
JP	05183194		7/1993
JP	05-213113		8/1993
JP	05-257142		10/1993
JP	60-80953	A	3/1994
JP	61-07035	A	4/1994
JP	62-27318	A	8/1994
JP	06318734		11/1994
JP	07146467		6/1995
JP	07-175035		7/1995
JP	07191311		7/1995
JP	07-266928		10/1995
JP	07-277072		10/1995
JP	07-281185		10/1995
JP	07267002		10/1995
JP	07281150		10/1995
JP	08-008083		1/1996
JP	08-083581		3/1996
JP	08-216789		8/1996
JP	08227769		9/1996
JP	09033886		2/1997
JP	09-260074		3/1997
JP	05-077657		7/1997
JP	09-220976		8/1997
JP	09230827		9/1997

JP	09-266078	10/1997
JP	09-288262	11/1997
JP	10-076880	3/1998
JP	10-199480	7/1998
JP	10190960	7/1998
JP	10-206643	8/1998
JP	10221692	8/1998
JP	10239659	9/1998
JP	10276298	10/1998
JP	11-038381	2/1999
JP	11-067485	3/1999
JP	11-078693	3/1999
JP	11-109337	4/1999
JP	11-160539	6/1999
JP	11-212073	8/1999
JP	11-283759	10/1999
JP	11-298058	10/1999
JP	11-305197	11/1999
JP	2000-131681	5/2000
JP	2000-153736	6/2000
JP	2000-159014	6/2000
JP	2000-255321	9/2000
JP	2000-330107	11/2000
JP	2001-083509	3/2001
JP	2001-222005	8/2001
JP	200272901	3/2002
JP	2002-120649	4/2002
JP	2002-122860	4/2002
JP	2002162626	6/2002
JP	2002-352611	12/2002
JP	2003-267129	9/2003
JP	2004-182156	7/2004
JP	2005-148119	6/2005
JP	2005-327600	11/2005
JP	38-46073	11/2006
JP	2008083657	4/2008
KR	20060038856	5/2006
KR	100663930	1/2007
WO	WO 82/02448	7/1982
WO	WO8606179	10/1986
WO	WO 94/19212	9/1994
WO	WO 96/21581	7/1996
WO	WO 98/14974	4/1998
WO	WO 98/38547	9/1998
WO	WO 99/15360	4/1999
WO	WO 00/23826	4/2000
WO	WO 00/52661	9/2000
WO	WO 00/55685	9/2000
WO	WO 01/01192	1/2001
WO	WO 02/18174	3/2002
WO	WO 02/49881	6/2002
WO	WO 03/021343	3/2003
WO	WO03078941	9/2003

OTHER PUBLICATIONS

Edgar, Julian; Goodbye 12 Volts . . . Hello 42 Volts!; Oct. 5, 1999; Autospeed 50; Issue 50; www.autospeed.co.nz/cms/A_0319/article.html.

Kobe, Gerry; 42 Volts Goes Underhood; Mar. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_3_180/ai_61361677.

Jewett, Dale; Aug. 2000; Automotive Industries; Cahners Publishing Company; www.findarticles.com/p/articles/mi_m3012/is_8_180ai_64341779.

National Semiconductor, LM78S40, Universal Switching Regulator Subsystem, National Semiconductor Corporation, Apr. 1996, p. 6.

Dana H. Ballard and Christopher M. Brown, Computer Vision, article, 4 pages Prentice-Hall, Englewood Cliffs, New Jersey, believed to be published more than one year prior to the filing date of the present application.

G. Wang, D. Renshaw, P.B. Denyer and M. Lu, CMOS Video Cameras, article, 1991, 4 pages, University of Edinburgh, UK.

* cited by examiner




FIG. 1
(PRIOR ART)













FIG. 1A
(PRIOR ART)








FIG. 11




FIG. 11A




FIG. 11B






FIG. 12

**FIG. 12A**

BLUE-GREEN VF DISPLAY: EMISSION SPECTRUM

IMPROVED DOD TUNED TO BLUE-GREEN VF DISPLAY

FIG. 12B





FIG. 13

**FIG. 13A**




FIG. 14




FIG. 14A




FIG. 14B





FIG. 15

**FIG. 15A**





FIG. 16

**FIG. 16A**





FIG. 17

**FIG. 17A**





FIG. 18



9
10
11
12




FIG. 20





FIG. 21

**FIG. 22**





FIG. 23



24
E.G.







FIG. 25

**FIG. 26**

**FIG. 27**

**FIG. 28**




FIG. 29




FIG. 30




FIG. 31




FIG. 32

1

INTERIOR REARVIEW MIRROR INFORMATION DISPLAY SYSTEM FOR A VEHICLE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 12/555,276, filed Sep. 8, 2009, now U.S. Pat. No. 7,859,737, which is a continuation of U.S. patent application Ser. No. 12/342,452, filed Dec. 23, 2008, now U.S. Pat. No. 7,586,666, which is a continuation of U.S. patent application Ser. No. 11/860,223, filed Sep. 24, 2007, now U.S. Pat. No. 7,471,438, which is a continuation of U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501, which is a 371 application of PCT Application No. PCT/US2003/029776, filed Sep. 19, 2003, which claims priority of U.S. provisional applications, Ser. No. 60/412,275, filed Sep. 20, 2002; Ser. No. 60/424,116, filed Nov. 5, 2002; and Ser. No. 60/489,816, filed Jul. 24, 2003, which are all hereby incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

The present invention relates to a mirror reflective element assembly for a vehicle, such as an electro-optic mirror reflective element assembly, such as an electrochromic interior or exterior rearview mirror reflective element assembly, and, more particularly, to a rearview mirror reflective element assembly which provides transmission of display information or illumination or radiant energy through the reflective element of the mirror reflective element assembly, while providing sufficient reflectance of the reflective element. Aspects of the present invention are equally applicable to interior and exterior mirror reflective element assemblies, as well as to prismatic mirror reflective element assemblies or other mirror reflective element assemblies having a single glass substrate.

BACKGROUND OF THE INVENTION

Variable reflectivity mirror assemblies, such as electrochromic mirror assemblies are known and are widely implemented in vehicles. The reflective element of the mirror assemblies often include two substrates or glass elements. The back or outer surface of the second substrate (commonly referred to as the "fourth surface" of the reflective element) may include a silvered coating to provide reflectance of an image. In embodiments where the mirror assembly may include a display, a window may be formed, such as by sand blasting, laser etching or the like, through the silvered coating, such that display information may be transmitted through the window for viewing by the driver. The window provides a highly transmissive, generally spectrally neutral window for the display. However, the window defines an area of the reflective element that no longer has the reflective coating, such that reflectivity is lost in the window area. Therefore, the size and the quantity of displays that can be provided at the mirror reflective element is limited.

It is known to provide a metallic reflective layer on an inward surface of the second substrate of the electrochromic reflective element (commonly known in the art as a "third surface" of the reflective element), such as disclosed in U.S. Pat. No. 3,280,701, which is hereby incorporated herein by reference. An electrochromic medium may be positioned between the metallic layer and a transparent electrically conductive layer on the inward surface of the first substrate (i.e.,

2

the "second surface" of the reflective element). However, there are concerns with the electrochromic medium of such mirror assemblies contacting the metallic layer, since chemical and/or electrochemical attack on the metallic layer may result in corrosion of the metallic layer.

As disclosed in U.S. Pat. No. 5,724,187, which is hereby incorporated herein by reference, a metallic conductive layer may be disposed on the third surface, with a protective layer, such as a transparent semi-conductive layer of indium tin oxide, disposed on the metallic layer. The electrochromic medium is then positioned between the protective layer and a conductive layer on the inward surface of the first substrate. It is preferable for such designs to include an adhesion layer, such as a second transparent semi-conductive layer, such as indium tin oxide, or another metallic layer, between the metallic layer and the inward surface of the second substrate, in order to enhance adhesion of the metallic layer to the second substrate.

In electrochromic mirror assemblies which include a display that may transmit through the substrates of the reflective element, the metallic layer or coating must be thin enough to be transmissive to allow viewing of the display through the metallic coating. It is known to provide a thinner metallic coating in a display area to provide increased transmissivity (but with a consequently reduced reflectivity) only in the display area or areas of the reflective element, such as disclosed in U.S. Pat. No. 6,356,376, which is hereby incorporated herein by reference. However, such designs have layers or coatings that are relatively thin (often less than 150 Å or thereabouts in thickness) and so any variation in metallic layer thickness may lead to a significant variation in light transmission through such thin metallic coatings. Thus, such significantly thin metallic coatings or layers may have a substantially low variability tolerance for the thickness and may require a substantially uniform thickness coating, in order to provide the desired results. Such tolerances and uniformity may be difficult to achieve through sputter coating or other coating processes typically used in the manufacture of such reflective elements. Therefore, such significantly thin metallic coatings may be difficult and costly to manufacture.

An example of a known electrochromic reflective element is shown in FIG. 1. The reflective element includes an electrochromic (EC) medium layer and a metallic reflective layer sandwiched between conductive layers at the front and rear glass substrates. A display is positioned at a rear surface of the rear substrate (the fourth surface of the reflective element). The display emits light through the substrates and layers therebetween so as to be viewable by a person viewing the first surface of the reflective element. Such known reflective elements provide little or no spectrally selective transmission characteristics of visible light, as can be seen with reference to FIG. 1A (which shows the transmissivity of the ITO and silver layers at the rear substrate versus the wavelength of the radiant energy), and may be subject to chemical/electrochemical corrosion through contact with the EC medium.

Sometimes it is desired to have an illumination source and/or a camera or imaging device or sensor at an interior rearview mirror assembly for illuminating and/or capturing images of the interior cabin of the vehicle, such as part of a cabin monitoring system, a driver alertness/drowsiness detection system, an intrusion detection system, a seat occupancy detection system and/or the like. The illumination sources and imaging device, if provided at the interior rearview mirror assembly, are typically positioned around the bezel, chin or eyebrow portion of the mirror casing or at a pod or module associated with the mirror assembly or elsewhere in the vehicle. The illumination sources and imaging device cannot

3

typically be positioned within the mirror casing due to the difficulties encountered in projecting light or illumination through the reflective element to the cabin and allowing light from within the cabin to pass through the reflective element to the imaging device. Typically, such transmissivity of light, even of infrared or near infrared light, through the reflective element may not be achieved utilizing reflective coatings that comprise a metallic layer, such as a thin silver or silver alloy or aluminum or aluminum alloy layer or the like. In such applications, the infrared or near infrared light emitted by the illumination source may reflect back into the cavity of the mirror casing, such that a desired amount of light may not reach the cabin and such that the imaging device may be adversely affected by the reflectant light.

Therefore, there is a need in the art for an electrochromic mirror assembly which provides sufficient reflectivity and sufficient transmissivity to allow for transmission of display information or illumination through the reflective element, and which overcomes the above disadvantages and shortcomings of the prior art.

SUMMARY OF THE INVENTION

The present invention provides an interior or exterior rear-view mirror assembly that has a mirror reflective element that may be spectrally tuned to substantially transmit light having a particular wavelength or range of wavelengths, while substantially reflecting other light. The mirror reflective element may comprise a third surface reflective element having a particular combination or stack of at least partially conductive layers (such as semi-conductive layers formed of at least partially conducting inorganic oxides, such as doped or undoped indium oxide, doped or undoped tin oxide, doped or undoped zinc oxide, doped or undoped nickel oxide, and/or doped or undoped tungsten oxide or the like) and metallic layer(s) at the third surface. The mirror assembly is suitable for including a display element which emits and transmits viewable information through the reflective element of the mirror assembly. More particularly, the mirror assembly of the present invention is suitable for including a display on demand (DOD) type of display. The mirror assembly of the present invention provides a particular combination of reflector design or designs suitable for a display on demand type of display which are economical and which match and/or make most beneficial use of a particular light emitting display element and color thereof. The present invention thus provides a spectrally selective transmission of visible light characteristic to the reflective element of the mirror assembly, while maintaining a substantially non-spectrally selective, substantially untinted reflectant characteristic, and while maintaining a relatively high photopic reflectance, such as greater than approximately 60% photopic reflectivity, more preferably greater than approximately 70% photopic reflectivity, and most preferably greater than approximately 80% photopic reflectivity. The spectrally selective transmissivity of the reflective element may thus be selected or tuned to optimize transmission of a particular spectral band or range of light wavelengths at least primarily emitted by the display element.

According to an aspect of the present invention, a mirror assembly for a vehicle comprises a mirror element including at least one substrate having a forward surface facing towards a viewer of the mirror assembly and a rearward surface facing away from a viewer of the mirror assembly. The mirror element comprises at least one substantially reflective metallic layer sandwiched between a respective pair of substantially transparent non-metallic layers. Each of the substantially transparent non-metallic layers and the substantially reflect-

4

tive metallic layer have a selected refractive index and a selected physical thickness such that the reflective element is selectively spectrally tuned to substantially transmit at least one preselected spectral band of radiant energy therethrough while substantially reflecting other radiant energy. A radiant energy emitting element is disposed at or near the rearward surface of the at least one substrate. The radiant energy emitting element is operable to emit radiant energy towards the rearward surface and through the mirror element. The radiant energy emitting element is operable to emit radiant energy with a peak intensity within the at least one preselected spectral band.

Optionally, the at least one preselected spectral band may comprise a preselected band of visible light, while the radiant energy emitting element may be operable to emit visible radiant energy or light with a peak intensity within the preselected spectral band of visible light. The radiant energy emitting element thus may provide a display on demand type of display for viewing of displayed or emitted information through the reflective element.

Optionally, the at least one preselected spectral band may comprise first and second preselected bands of radiant energy, while the radiant energy emitting element comprises first and second radiant energy emitting elements. The first radiant energy emitting element may be operable to emit radiant energy with a peak intensity within the first preselected spectral band of radiant energy and the second radiant energy emitting element may be operable to emit visible radiant energy with a peak intensity within the second preselected spectral band of radiant energy.

Optionally, the at least one preselected spectral band may comprise a preselected band of near infrared radiant energy, while the radiant energy emitting element may be operable to emit near infrared radiant energy with a peak intensity within the preselected spectral band of near infrared radiant energy. The mirror assembly may include an imaging sensor at or near the rear surface that may be sensitive to near infrared radiant energy.

Optionally, the mirror reflective element may comprise an electro-optic or electrochromic mirror element, and may comprise an electrochromic medium sandwiched between a pair of substrates. The non-metallic and metallic layers may be disposed on a third surface (the surface of the rear substrate that opposes electrochromic medium and the front substrate).

Optionally, the mirror reflective element may comprise a prismatic mirror element. The alternating non-metallic and metallic layers may be disposed on a rear surface of the prismatic element or substrate. The radiant energy emitting element may be positioned at a rear layer of the alternating layers and operable to emit radiant energy or light through the layers and the prismatic substrate, such that the information displayed or emitted by the radiant energy emitting element is viewable through the prismatic reflective element by a driver or occupant of the vehicle, while the prismatic reflective element substantially reflects light having other wavelengths or spectral bands. The radiant energy emitting element thus may provide a display on demand type of display to the prismatic mirror element.

According to another aspect of the present invention, an electrochromic mirror assembly for a vehicle comprises an electrochromic mirror element comprising a first substrate having first and second surfaces and a second substrate having third and fourth surfaces. The first and second substrates are arranged so that the second surface opposes the third surface with an electrochromic medium disposed therebetween. The third surface of the second substrate comprises a transreflective reflector comprising a first substantially trans-

5

parent semi-conductive non-metallic layer contacting the electrochromic medium, a second substantially transparent semi-conductive non-metallic layer, and a substantially reflective metallic conductive layer sandwiched between (and electrically in contact/connection with) the first and second substantially transparent semi-conductive non-metallic layers. When the mirror element is viewed from outside the first surface (such as by a driver or passenger within the vehicle), the mirror element is substantially spectrally untinted (i.e., is substantially spectrally unselective in photopic reflectivity) when no voltage is applied across the electrochromic medium. The mirror element is at least partially spectrally selective in transmission (i.e., is at least partially tinted for transmittant light) and exhibits a spectrally selective transmission characteristic, which is established by the refractive indices and physical thicknesses of the first and second substantially transparent semi-conductive non-metallic layers and the substantially reflective metallic conductive layer. The mirror assembly includes a light emitting or display element disposed at the fourth surface of the second substrate which is operable to emit light having an emitted spectral characteristic through the mirror element. The transfective reflector is configured to exhibit a spectrally selective transmission characteristic so as to substantially transmit light having a spectral band in regions at or near the emitted spectral characteristic and to substantially reflect other light.

Optionally, the second substantially transparent semi-conductive non-metallic layer may contact the third surface of the second substrate. Optionally, the transfective reflector may comprise two or more substantially reflective metallic conductive layers. Each of the two or more substantially reflective metallic conductive layers may be sandwiched between a respective pair of substantially transparent semi-conductive non-metallic layers disposed between the electrochromic medium and the second substrate.

Optionally, the transfective reflector may substantially transmit light or radiant energy having a spectral band in the near infrared region of the spectrum, while the light emitting or display element may emit near infrared light or radiant energy through the transfective reflector. The mirror assembly may include an imaging sensor at the fourth surface that is operable to sense near infrared light.

Optionally, the transfective reflector may substantially transmit light having a first spectral band at a first visible region of the spectrum, and may also substantially transmit light having a second spectral band at a second visible region of the spectrum. The light emitting or display element may emit light that has a peak intensity at or near the first visible region, while the mirror assembly may include a second light emitting element at the fourth surface that may emit light that has a peak intensity at or near the second visible region.

According to another aspect of the present invention, an electro-optic mirror assembly, such as an electrochromic mirror assembly, for a vehicle comprises an electrochromic mirror element comprising a first substrate having first and second surfaces and a second substrate having third and fourth surfaces. The first and second substrates are arranged so that the second surface opposes the third surface, with an electrochromic medium disposed between the second substrate and the first substrate. The mirror element comprises a transfective reflector at the third surface, which comprises at least one conductive metallic reflective layer sandwiched between first and second substantially transparent semi-conductive non-metallic layers. The first substantially transparent semi-conductive non-metallic layer contacts the electrochromic medium. The mirror assembly includes a display element at the fourth surface of the second substrate. A refractive index

6

and a physical thickness of each of the first and second substantially transparent semi-conductive non-metallic layers and the substantially reflective metallic conductive layer are selected such that the transfective reflector is selectively spectrally tuned to substantially transmit at least one preselected spectral band of visible light therethrough while substantially reflecting other visible light. The display element is configured to emit visible light with a peak intensity within the preselected spectral band.

According to another aspect of the present invention, a mirror assembly for a vehicle includes a mirror element and a radiant energy emitting element. The mirror element includes a substrate having a forward surface facing towards a viewer of the mirror assembly and a rearward surface facing away from a viewer of the mirror assembly. The mirror element includes at least one substantially reflective metallic layer sandwiched between a respective pair of substantially transparent non-metallic layers disposed at the rearward surface of the substrate. Each of the substantially transparent non-metallic layers and the substantially reflective metallic layer having a selected refractive index and a selected physical thickness such that the mirror element is selectively spectrally tuned to substantially transmit at least one preselected spectral band of radiant energy therethrough while substantially reflecting other radiant energy. The radiant energy emitting element is operable to emit radiant energy towards the rearward surface and through the mirror element. The radiant energy emitting element is operable to emit radiant energy with a peak intensity within the at least one preselected spectral band.

The substrate may comprises a single substrate. The single substrate may comprise a prismatic or wedge-shaped substrate. The radiant energy emitting element and alternating layers thus may provide for a display on demand type of display for a prismatic (or flat or curved) mirror assembly.

According to other aspects of the present invention, an electrochromic mirror assembly for a vehicle includes an electrically variable mirror element. The mirror element includes a first substrate having first and second surfaces and a second substrate having third and fourth surfaces. The first and second substrates are arranged so that the second surface opposes the third surface. The second substrate includes a conductive stack on the third surface. The conductive stack may comprise a first electrically conductive or semi-conductive layer deposited on the third surface, a reflective or metallic layer of reflective or metallic material on the first electrically semi-conductive layer, and a second electrically conductive or semi-conductive layer on the reflective layer. The mirror element includes an electrochromic medium disposed between the second electrically semi-conductive layer of the second substrate and the electrically semi-conductive coating on the second surface of the first substrate. The thicknesses and materials of the layers are selected to provide or exhibit a spectrally selective visible light transmission characteristic for a particular spectral band or range of wavelengths to provide enhanced transmissivity of the spectral band of light through the reflective element while providing sufficient reflectivity of other light.

In one form, the electrochromic mirror assembly may include a display element positioned at the fourth surface, wherein the display element is operable to emit light through the mirror element for viewing by a driver of the vehicle. The thicknesses of the particular layers of the conductive stack are selected such that the mirror element is spectrally tuned to transmit a predetermined spectral band of light therethrough. The spectral band that is transmittable through the mirror element may be selected to match a spectral band or range of

light wavelengths emitted by the display element, such that the mirror element is spectrally tuned for the particular display element positioned at the fourth surface of the mirror element. The mirror element thus may be spectrally tuned to match at least a portion of the transmissive band or range of wavelengths of the mirror element to a particular band or range of wavelengths of the light being emitted by the display element. In one form, the peak transmissivity of the transmissive band of the mirror element is selected to match the peak intensity of the spectral band emitted by the display element. The conductive stack preferably provides at least approximately 60 percent photopic reflectance (preferably as measured in accordance with Society of Automotive Engineers test procedure SAE J964a, which is hereby incorporated herein by reference in its entirety), more preferably at least approximately 70 percent photopic reflectance, and most preferably at least approximately 80 percent photopic reflectance, while providing at least approximately 10 percent transmission, preferably at least approximately 15 percent transmission, more preferably at least approximately 20 percent transmission, and most preferably at least approximately 30 percent transmission, of at least a particular spectral band of light. Preferably, the physical thicknesses of the layers are selected to limit tinting and/or color interference affects as seen in the mirror element (i.e. to provide a neutral reflector) and to spectrally tune the mirror element for a transmission characteristic for providing enhanced transmissivity through the mirror element for a particular spectral band or range of wavelengths, in order to match the transmissivity of the mirror element to the spectral band of emission of light from the display element.

The semi-conductive layers and metallic layer of the conductive stack may be deposited at the third surface via a sputter coating process. The present invention thus may provide a low cost reflective element which provides for sufficient transmission of a particular spectral band or bands of visible light and sufficient reflectance at the third surface of the mirror assembly (with at least 60% photopic reflectance preferred, more preferably, with at least 70% photopic reflectance, and most preferably, with at least 75% photopic reflectance). Preferably, the semi-conductive layers, such as indium tin oxide or the like, sandwiching the metallic layer are formed of the same material. Thus, for example, a conductive stack of alternating layers may comprise a metallic layer of silver sandwiched between two semi-conductive layers of indium tin oxide.

According to another aspect of the present invention, an electro-optic or electrochromic interior rearview mirror assembly comprises an electro-optic or electrochromic mirror reflective element. The electro-optic mirror element provides a substantially reflective mirror element having a first region having a first reflectivity and a first transmissivity and a second region having a second reflectivity and a second transmissivity. The electro-optic mirror element includes a display element positioned at or behind the second region and operable to transmit light through the second region. The first reflectivity is greater than the second reflectivity. Preferably, the second region provides at least approximately 25% transmissivity of light from the display.

Therefore, the present invention provides a mirror reflective element, such as a third surface reflective element or mirror element or a fourth surface reflective element or a prismatic reflective element or the like, which is sufficiently and spectrally selectively transmissive or spectrally tuned to allow a particular spectral range or band of light to pass therethrough from a display at the rear surface of the mirror reflective element. The layers of the reflective element are

selected or spectrally tuned to match one or more predetermined or selected spectral bands or ranges of wavelengths and to thus pass the predetermined spectral bands of light therethrough, while being substantially reflective to other spectral bands or wavelengths of light, and do not require windows or apertures formed in the reflective metallic layer of the reflective element.

These and other objects, advantages, purposes, and features of the present invention will become more apparent from the study of the following description taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a sectional view of a conventional electrochromic mirror reflective element;

FIG. 1A is a graphical depiction of the transmissivity of visible light of the conventional electrochromic mirror reflective element of FIG. 1;

FIG. 2 is a perspective view of an interior rearview mirror assembly in accordance with the present invention;

FIG. 3 is a sectional view of the mirror assembly taken along the line III-III in FIG. 2;

FIG. 4 is a sectional view of a second substrate and opaque conductive and reflective layers suitable for use in the mirror assembly of FIG. 2;

FIG. 5 is a front elevation of a second substrate of a reflective element in accordance with the present invention, with a tab-out portion to facilitate electrical connection with the conductive layers;

FIG. 6 is a sectional view of the second substrate taken along the line VI-VI in FIG. 5;

FIG. 7 is a perspective view of another interior rearview mirror assembly in accordance with the present invention, with a display;

FIG. 8 is a sectional view of a reflective element of the mirror assembly taken along the line VIII-VIII in FIG. 7;

FIG. 9 is a sectional view similar to FIG. 6 of a second substrate in accordance with the present invention, which is suitable for use in the mirror assembly of FIG. 7, and includes a tab-out portion to facilitate electrical connection with the conductive layers;

FIG. 10 is a sectional view of another second substrate and transmissive conductive and reflective layer or stack in accordance with the present invention suitable for use in a mirror assembly having a display;

FIG. 11 is another sectional view of a particular embodiment of a reflective element of the present invention;

FIG. 11A is a graphical depiction of the transmissivity of the reflective element of FIG. 11;

FIG. 11B is a graphical depiction of the emission spectrum of the display element for the reflective element of FIG. 11;

FIG. 12 is a sectional view of another particular embodiment of a reflective element of the present invention;

FIG. 12A is a graphical depiction of the transmissivity of the reflective element of FIG. 12;

FIG. 12B is a graphical depiction of the emission spectrum of the display element for the reflective element of FIG. 12;

FIG. 13 is a sectional view of another particular embodiment of a reflective element of the present invention;

FIG. 13A is a graphical depiction of the transmissivity of the reflective element of FIG. 13;

FIG. 14 is a sectional view of a particular embodiment of a double stack reflective element of the present invention;

FIG. 14A is a graphical depiction of the transmissivity of the double stack reflective element of FIG. 14;

FIG. 14B is a graphical depiction of the emission spectrum of the display element for the double stack reflective element of FIG. 14;

FIG. 15 is a sectional view of another particular embodiment of a double stack reflective element of the present invention;

FIG. 15A is a graphical depiction of the transmissivity of the double stack reflective element of FIG. 15;

FIG. 16 is a sectional view of a particular embodiment of a multiple stack reflective element of the present invention;

FIG. 16A is a graphical depiction of the transmissivity of the multiple stack reflective element of FIG. 16;

FIG. 17 is a sectional view of another particular embodiment of a multiple stack reflective element of the present invention;

FIG. 17A is a graphical depiction of the transmissivity of the multiple stack reflective element of FIG. 17;

FIG. 18 is a forward facing view of another electro-optic mirror reflective element in accordance with of the present invention;

FIG. 19 is a sectional view of another reflective element in accordance with the present invention, which is capable of transmitting near infrared illumination therethrough;

FIG. 20 is a sectional view of another reflective element in accordance with the present invention;

FIG. 21 is a sectional view of another reflective element in accordance with the present invention;

FIG. 22 is a graphical depiction of the transmissivity of light through the cover and rear substrate of the reflective elements of FIGS. 19-21;

FIG. 23 is a sectional view of another reflective element in accordance with the present invention, which is capable of transmitting near infrared illumination therethrough;

FIG. 24 is a sectional view of another reflective element in accordance with the present invention;

FIG. 25 is a sectional view of another reflective element in accordance with the present invention;

FIG. 26 is a graphical depiction of the transmissivity of light through the rear substrate and IRT stack of the reflective elements of FIGS. 23-25;

FIG. 27 is a graphical depiction of the transmissivity of light through the front substrate and enhanced semi-conductive layers of the reflective element of FIG. 24;

FIG. 28 is a graphical depiction of the transmissivity of light through the front substrate and enhanced semi-conductive layers of the reflective element of FIG. 25;

FIG. 29 is a sectional view of a reflective element similar to the reflective element of FIG. 25, with an anti-reflective stack or layers on a rear surface of the rear substrate in accordance with the present invention;

FIG. 30 is a sectional view of another reflective element in accordance with the present invention; and

FIG. 31 is a graphical depiction of the transmissivity of light through the rear substrate and IRT-DOD stack of the reflective element of FIG. 30; and

FIG. 32 is a sectional view of a prismatic reflective element in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings and the illustrative embodiments depicted therein, an electrochromic interior rearview mirror assembly 10 is mounted to a mounting button 12 mounted at an interior surface of a windshield 14 of a vehicle (FIG. 2). Mirror assembly 10 includes a housing or casing 15 and an electrochromic reflective element or mirror element or cell 16 which has electrically variable reflectivity. Reflective element 16 includes first and second glass substrates 22, 24,

and provides a third surface reflective element, whereby the reflective coating of the reflective element 16 is deposited on the third surface 24a of the substrates (FIG. 3). An electrochromic medium 40 and a plurality of metallic and non-metallic conductive or semi-conductive layers 28 are disposed between the electrochromic medium 40 and the second substrate 24. The refractive indices and physical thicknesses of the layers are selected to maximize transmission of a particular spectral band of light while substantially reflecting other light to provide a desired degree of photopic reflectance, while also providing the desired degree of conductivity across the layers.

Although shown and described herein as being implemented in an interior rearview mirror assembly of a vehicle, the reflective element or mirror element of the present invention is equally suitable for or applicable to other electro-optic reflective elements, or reflective elements for exterior rearview mirror assemblies for vehicles or for other mirror assemblies, without affecting the scope of the present invention. Also, although shown and described as an electrochromic reflective element, aspects of the present invention may be equally applicable to prismatic reflective elements (such as described below with respect to FIG. 32) or to exterior reflective elements, without affecting the scope of the present invention. Also, the mirror element of the present invention may comprise a substantially flat element or substrate or may comprise a curved element or substrate, such as a convex element or aspheric element or the like, without affecting the scope of the present invention.

Electrochromic reflective element 16 comprises a first or front substantially transparent substrate 22 and a second or rear substantially transparent substrate 24 (which may be glass substrates or the like). The first substrate 22 includes an electrically conductive or semi-conductive layer 26, such as a tin oxide (doped or undoped) or indium tin oxide (ITO) or any other transparent electrically semi-conductive layer or coating or the like (such as indium cerium oxide (ICO), indium tungsten oxide (IWO), or indium oxide (IO) layers or the like or a zinc oxide layer or coating, or a zinc oxide coating or the like doped with aluminum or other metallic materials, such as silver or gold or the like, or other oxides doped with a suitable metallic material or the like), deposited on an inward surface 22a of first substrate 22 (i.e., the second surface 22a of the reflective element 16).

Also, the first (or forward or outermost) surface 22b of front substrate 22 (exposed to the atmosphere exterior of the mirror assembly) may be optionally coated with an anti-wetting property such as via a hydrophilic coating (or stack of coatings), such as is disclosed in U.S. Pat. Nos. 6,193,378; 5,854,708; 6,071,606; and 6,013,372, the entire disclosures of which are hereby incorporated by reference herein. Also, or otherwise, the first (outermost) surface 22b of front substrate 22 may be optionally coated with an anti-wetting property such as via a hydrophobic coating (or stack of coatings), such as is disclosed in U.S. Pat. No. 5,724,187, the entire disclosure of which is hereby incorporated by reference herein. Such hydrophobic property on the first/outermost surface of electrochromic mirror reflective elements (and on the first/outermost surface of non-electrochromic mirror, non-electro-optical conventional reflective elements) can be achieved by a variety of means, such as by use of organic and inorganic coatings utilizing a silicone moiety (for example, a urethane incorporating silicone moieties) or by utilizing diamond-like carbon coatings. For example, long-term stable water-repellent and oil-repellent ultra-hydrophobic coatings, such as described in PCT Application Nos. WO0192179 and WO0162682, the entire disclosures of which are hereby

11

incorporated by reference herein, can be disposed on the first (outermost) surface **22b** of front substrate **22**. Such ultra-hydrophobic layers comprise a nano structured surface covered with a hydrophobic agent which is supplied by an underlying replenishment layer (such as is described in Classen et al., "Towards a True 'Non-Clean' Property: Highly Durable Ultra-Hydrophobic Coating for Optical Applications", ECC 2002 "Smart Coatings" Proceedings, 2002, 181-190, the entire disclosure of which is hereby incorporated by reference herein).

Second or rear substrate **24** includes at least three layers or coatings defining a reflective and conductive layer or stack or ISI layer or stack **28** (i.e., the combination or stack of a layer of: a semi-conducting coating, such as an ITO layer or the like; a metallic layer, such as a layer of silver, aluminum or an alloy of silver or an alloy of aluminum or other metal or metal alloy; and another layer of a semi-conducting coating, such as an ITO layer or the like, as discussed below, is referred to herein as an ISI stack or layer) on an inward surface **24a** of second substrate **24** (or the third surface of the reflective element). Thus, an ISI stack **28** comprises a metallic layer sandwiched between two semi-conducting layers (both of which preferably are the same material, but either of which can be different from the other). In the illustrated embodiment of FIG. 4, ISI layer **28** comprises a first semi-conductive layer **30** disposed on inward surface **24a** of second substrate **24**, a second semi-conductive layer or adhesion layer **32** disposed on semi-conductive layer **30**, a metallic layer or coating **34** disposed on semi-conductive layer **32**, and a transparent semi-conductive layer or passivation layer **36** disposed on metallic layer **34**. As shown in FIGS. 3 and 4, first semi-conductive layer **30** extends outwardly from the other ISI layers **32**, **34** and **36**, in order to provide for electrical connection with bus bars **38** of mirror assembly **10**. Although referred to herein as an "ISI layer" or an "ISI stack", the conductive and reflective stack or layers of the present invention may comprise materials or coatings other than ITO, ICO, IO, IWO layers or coatings or the like and silver or silver alloy layers or coatings, without affecting the scope of the present invention. For example, a semi-conducting layer of doped zinc oxide, or a semi-conducting layer of cadmium stannate, or a semi-conducting layer of titanium nitride or other titanium compound or the like may be used in the stack, without affecting the scope of the present invention.

As shown in FIG. 3, the first and second substrates **22**, **24** are positioned in spaced-apart relationship with one another with an electrochromic medium **40** disposed between semi-conductive layer **26** and semi-conductive layer **36**. The electrochromic medium **40** changes color or darkens in response to electricity or voltage applied to or through the semi-conductive layers **26** and **30** at either side of the electrochromic medium. The electrochromic medium **40** disposed between the front and rear substrates **22**, **24** may be a solid polymer matrix electrochromic medium, such as is disclosed in U.S. Pat. No. 6,154,306, which is hereby incorporated by reference herein, or other suitable medium, such as a liquid or solid medium or thin film or the like, such as the types disclosed in U.S. patent application Ser. No. 09/793,002, entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, filed Feb. 26, 2001, now U.S. Pat. No. 6,690,268, and in U.S. Pat. Nos. 5,668,663 and 5,724,187, the entire disclosures of which are hereby incorporated by reference herein, without affecting the scope of the present invention. The electrochromic mirror element may utilize the principles disclosed in commonly assigned U.S. Pat. Nos. 5,140,455; 5,151,816; 6,178,034; 6,154,306; 6,002,544; 5,567,360; 5,525,264; 5,610,756; 5,406,414; 5,253,109; 5,076,673;

12

5,073,012; 5,117,346; 5,724,187; 5,668,663; 5,910,854; 5,142,407 or 4,712,879, which are hereby incorporated herein by reference, or as disclosed in the following publications: N. R. Lynam, "Electrochromic Automotive Day/Night Mirrors", SAE Technical Paper Series 870636 (1987); N. R. Lynam, "Smart Windows for Automobiles", SAE Technical Paper Series 900419 (1990); N. R. Lynam and A. Agrawal, "Automotive Applications of Chromogenic Materials", Large Area Chromogenics Materials and Devices for Transmittance Control, C. M. Lampert and C. G. Granquist, EDS., Optical Engineering Press, Wash. (1990), which are hereby incorporated by reference herein, and in U.S. patent application Ser. No. 09/793,002, filed Feb. 26, 2001 by Schofield et al. for VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, now U.S. Pat. No. 6,690,268, which is hereby incorporated herein by reference. Reflective element **16** may also include a seal **41** positioned around the outer portions of the layers **32**, **34**, **36** and the electrochromic medium **40** to seal the layers and avoid corrosion of the metallic layer **34**.

During operation, a voltage may be applied to reflective element **16** via bus bars **38** positioned around and engaging the outer edges of the semi-conductive layers **26**, **30** (FIG. 3). The voltage applied by bus bars **38** is bled from semi-conductive layer **30** and through the layers **32**, **34**, **36** to the electrochromic medium **40**. The ISI layer **28** of the present invention preferably provides for reduced resistance through the layers, which provides for faster, more uniform coloration of the electrochromic medium **40**, since the electrons applied via bus bars **38** at semi-conductive layer **30** may bleed through the semi-conductive layers **32**, **36** faster due to the enhanced conductivity in the conductive layers **32**, **36**. Preferably, the ISI layer or stack **28** provides a sheet resistance of less than approximately 10 ohms per square, more preferably less than approximately 5 ohms per square, and most preferably less than approximately 2 ohms per square. Desirably, and particularly for larger area mirrors, the sheet resistance is less than approximately 1 ohm per square, such as in the range of approximately 0.1 to 0.7 ohms per square.

In order to provide enhanced performance of the electrochromic element, each of the layers of the ISI layer or stack has substantial conductivity and none of the layers significantly retard electron/electrical conductivity from one layer to the other throughout the stack, and, thus, do not impede the flow of electrons into the electrochromic (EC) medium. In this regard, it is desirable that one or more of the metallic layers comprises a metallic material (which is preferably a highly reflective material, such as silver or silver alloys or the like) having a specific resistivity of preferably less than approximately 5×10^{-5} ohm-cm, more preferably less than approximately 1×10^{-5} ohm-cm, and most preferably less than approximately 5×10^{-6} ohm-cm. Preferably, such a highly conductive metallic layer or layers is/are sandwiched between two non-metallic, partially conducting layers, preferably formed of a non-metallic material (such as a semi-conducting oxide, such as indium oxide, tungsten oxide, tin oxide, doped tin oxide or the like) having a specific resistivity of less than approximately 1×10^{-2} ohm-cm, more preferably less than approximately 1×10^{-3} ohm-cm, and most preferably less than approximately 5×10^{-4} ohm-cm.

In the illustrated embodiment of FIGS. 3 and 4, first semi-conductive layer **30** is deposited on inward surface **24a** of second substrate **24**. The semi-conductive layer **30** may be deposited on the glass or substrate **24** via any suitable process. The particular thickness of the conductive layer may vary depending on the particular application of reflective element **16**, as discussed below. In the illustrated embodiments of

13

FIGS. 2-4, the semi-conductive layer 30 need not be transparent and may comprise a chromium layer or the like. However, the semi-conductive layer 30 may comprise a generally transparent semi-conductive layer of coating, such as a tin oxide layer, an indium tin oxide (ITO) layer or the like, without affecting the scope of the present invention. In a preferred embodiment, semi-conductive layer 30 may comprise a chromium layer on surface 24a of second substrate 24.

The transparent semi-conductive layers 32 and 36 of ISI layer 28 on second substrate 24 may comprise non-metallic transparent electrically conducting or semi-conducting materials, such as tin oxide, indium oxide, indium cerium oxide, indium tungsten oxide, nickel oxide, tungsten oxide, indium tin oxide, half-wave indium tin oxide, full wave indium tin oxide, doped tin oxides, such as antimony-doped tin oxide and fluorine-doped tin oxide, doped zinc oxides, such as antimony-doped zinc oxide and aluminum-doped zinc oxide, and/or the like. Both of the semi-conductive layers 32, 36 may comprise the same type of material for ease of manufacturing, as discussed below.

Metallic layer or coating 34 comprises a thin film or layer of metal, such as silver, aluminum, or alloys thereof, or the like, with a selected thickness to provide sufficient reflectivity and/or transmissivity, as discussed below. The selected metallic material may comprise silver, but may otherwise comprise a material selected from aluminum, silver alloys, aluminum alloys (such as 6061 or 1100 aluminum alloys or the like), manganese, chromium or rhodium, or any other metallic material which is sufficiently reflective and/or transmissive at a selected thickness. The thickness of metallic layer 34 is preferably selected to be thick enough (such as approximately 60-100 nm or 600-1000 Å) to be substantially reflective and not transmissive, such that the ISI layer 28 is substantially opaque or non-transparent.

In a preferred embodiment, the semi-conductive layer 30 comprises indium tin oxide (ITO) and is deposited onto surface 24a of substrate 24 via a hot deposition process, involving, for example, sputter deposition onto a heated substrate, with the heated substrate often being heated to a temperature of greater than about 200° C., sometimes greater than 300° C., as is known in the art. The combination of the semi-conductive layer 30 on the substrate 24 defines a conductive substrate which may be used for various embodiments of the present invention, as discussed below.

The semi-conductive layer 32 of ISI layer 28 may be deposited onto semi-conductive layer 30 via a cold deposition process, such as sputter coating or the like onto an unheated substrate. Preferably, each of the layers 32, 34, 36 of ISI layer 28 is deposited on second substrate 24 by a sputter deposition process. More particularly, the substrate 24 (including the semi-conductive layer 30 already deposited thereon) may be positioned in one or more sputter deposition chambers with either planar or rotary magnetron targets, and with deposition of the layers being achieved by either reactive deposition of an oxide coating by sputtering from a metal target (or from a conductive, pressed oxide target) in an oxygen-rich atmosphere, or by DC sputtering from an oxide target, such as an IO, IWO, ITO or ICO target or the like. For example, the substrate 24 may be sputter coated with two targets in a single chamber, such as by depositing the ITO layer 32 on semi-conductive layer 30, turning or flipping the targets for sputter coating of the metallic layer 34, and then turning the targets back to deposit the second ITO layer or passivation layer 36 on the metallic layer 34. With such a process, it is important that the two ITO layers 30, 34 comprise the same conductive material. Alternately, two targets may be positioned in a row, such that the substrate 24 is moved from one target (for the

14

first ITO coating) to the other (for the metallic coating) and then back to the first (for the second ITO coating). It is further envisioned that three targets may be positioned in a row, with each target depositing the layer in order on the substrate (in which case it would not be as important to have the semi-conductive or ITO layers 32, 36 comprise the same material). Other processes for applying or depositing layers of conductive material or layers and metallic material or layers may be implemented, without affecting the scope of the present invention. In the illustrated embodiment of FIGS. 2 and 3, semi-conductive layer 30 may be deposited or applied to substantially the entire surface 24a of substrate 24, while the outer region or edge of semi-conductive layer 30 and substrate 24 may be masked during the deposition process so that layers 32, 34, 36 do not cover the outer edge of substrate 24 and semi-conductive layer 30.

Because the embodiment of the reflective element of the present invention illustrated in FIG. 4 does not include a display on demand or other type of display transmitting or projecting through the electrochromic reflective element, it is desirable to have a thick metallic or silver layer 34, such as in a range of approximately 60-100 nm (600-1000 Å), because the metallic layer does not have to be transmissive of any light therethrough. It is also unnecessary for the second substrate to be transparent. However, it is desirable to avoid tinting or color interference affects as seen in reflection from the reflector (which may arise when stacking layers of conductive coatings and/or metallic coatings on top of one another), because it is desirable to have a neutral or non-colored/non-tinted reflector when no voltage is applied across the electrochromic medium.

Optionally, the metallic layer may be absent or removed at portions, such as to create a local window for placement therebehind of a light emitting display, such as a compass display or PSIR display or other informational display or the like, such as a display of the type disclosed in commonly assigned U.S. Pat. Nos. 6,222,460 and 6,326,900, which are hereby incorporated herein by reference in their entireties, but while maintaining at least the underlying semi-conducting ITO layer at the local window region so that electrical connection through the electrochromic medium at that local region is sustained. In this regard, it is preferable to have an ITO underlayer with a sheet resistance of less than approximately 80 ohms per square, more preferably less than approximately 25 ohms per square, and most preferably less than approximately 15 ohms per square.

In order to avoid such undesirable tinting or color interference affects, such as yellow tinting or other color tinting of the compound or stacked reflective element, as seen in the reflection when the electrochromic reflective element is unpowered, the physical thicknesses of the conductive layers and the metallic layer are selected to provide a desired combination of layer thicknesses to achieve the desired results. For example, the ISI layer 28 may include an adhesion layer or undercoating semi-conductive layer 32 of approximately 100 Å+/-50 Å of ITO or the like, a silver layer 34 of approximately 800 Å+/-200 Å and a passivation semi-conductive layer 36 of approximately 120 Å+/-25 Å of ITO or the like, which provides a desired result with minimal yellow tinting or other color tinting or color interference affects as seen in the reflection.

The range of thicknesses of the layers may be selected to provide a desired untinted affect in the reflection, such that the reflective element may be spectrally tuned to provide a desired reflectant untinted appearance. Testing of various embodiments has shown that the thicknesses of the layers may vary by approximately 25 percent or more from a desired

15

or targeted dimension, yet will still provide the desired results. Such tolerances significantly ease the processing of the ISI layer, since this is well within the capability of typical sputter coating equipment. The layers of the reflective element and ISI stack may be selected such that the reflective element provides a substantially spectrally untinted reflection when viewed by a driver or passenger in the vehicle when no voltage is applied across the electrochromic medium. Also, the layers may be selected and combined to exhibit a spectrally selective transmissive characteristic, which is established by the refractive indices and physical thicknesses of the layers disposed between the electrochromic medium and the third surface of the second substrate.

Although the above embodiment provides a desired neutral color/tint for the reflector, if the passivation layer **36** is increased in thickness, the reflector may become tinted or yellowed. However, if the passivation layer is further increased in thickness to approximately 680 Å, then the non-tinting is approximately the same as when the passivation layer has a thickness of approximately 120 Å. This periodic change in tinting affect in response to the thicknesses of the layers or coatings of the ISI layer of the present invention allows for selection of different thicknesses of the layers depending on the particular application and desired result of the electrochromic reflective element of the present invention.

Referring now to FIGS. **5** and **6**, a reflective element **116** may have alternating layers or an ISI stack or layer **128** comprising a first semi-conductive layer or adhesion layer **132** deposited or sputter coated directly onto surface **24a** of second substrate **24**, a metallic layer **134** deposited on semi-conductive layer **132**, and a second semi-conductive layer or passivation layer **136** deposited on metallic layer **134**. The second or rear substrate **24** is masked around substantially the entire outer region **24c** of surface **24a** during the deposition process, such that the ISI layer **128** is not deposited in the masked region **24c**. However, the substrate is not masked over the entire outer edge or region of substrate **24**, in order to allow deposition of the ISI layer at a particular area, such that a tab-out portion or area **131** is formed in the ISI layer **128**. The tab out area **131** facilitates electrical connection with the conductive coatings **132**, **134**, **136**, such that the first semi-conductive layer **30** of reflective element **16** is not required. In a preferred embodiment of the present invention, the reflective element **116** may include a semi-conductive layer **132** of an ITO coating which has a thickness of approximately 100 Å \pm 25 Å, a silver layer **134** having a thickness of approximately 900 Å \pm 100 Å, and a second semi-conductive layer **136** of ITO or the like having a thickness of approximately 120 Å \pm 25 Å. Such an arrangement of semi-conductive layers and a sandwiched metallic layer provides a neutral reflectance with minimal tinting or color interference affects as seen in reflectance and with the electrochromic medium unpowered.

The opaque ISI layer **28**, **128** and the third surface reflective element of the present invention therefore provides an economical, low cost electrochromic reflective element, which provides a neutral color reflection. Typically, for a sputter coating operation, a range of within \pm 5% of a nominal target for uniformity of coating is desired. However, in the present invention, the uniformity tolerance is approximately \pm 25% for each of the coatings or layers from cell to cell. The ISI layer on the second substrate thus may be easy and fast to manufacture due to the thicknesses and the tolerances for the thickness of each particular coating.

Referring now to FIGS. **7** and **8**, a mirror assembly **210** in accordance with the present invention (shown as an interior

16

rearview mirror assembly in FIG. **7**; however, the reflective element **216** may be implemented at an exterior mirror assembly or other mirror assembly, without affecting the scope of the present invention) may include a display system or element **218** which is operable to provide, emit or display information or light through a mirror element or reflective element **216** of the mirror assembly. The light is emitted through the reflective element **216** at a display area **220** of mirror assembly **210**, such that the display information or light is viewable by a driver of the vehicle. The reflective element **216** includes first (or front) and second (or rear) substrates **222**, **224**, and a conductive and transmissive ISI stack or layer or DOD stack or layer **228** disposed on the inward surface **224a** of the second substrate (or the third surface of the reflective element). The second substrate **224** and ISI layer **228** comprise a transreflective one way mirror, such as disclosed in commonly assigned U.S. patent application, Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, which is hereby incorporated herein by reference. Preferably, the mirror reflective element (behind which the display is disposed so that the information displayed is visible by viewing through the mirror reflective element) of the mirror assembly comprises a transreflective mirror reflector, such that the mirror reflective element is significantly transmitting to visible light incident from its rear (i.e., the portion furthest from the driver in the vehicle), while simultaneously the mirror reflective element is substantially reflective to visible light incident from its front (i.e. the position closest to the driver when the interior mirror assembly is mounted in the vehicle). The transreflective electrochromic reflective mirror element (such as is disclosed in U.S. patent application Ser. No. 09/793,002, entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, filed Feb. 26, 2001, now U.S. Pat. No. 6,690,268, and in U.S. Pat. Nos. 5,668,663 and 5,724,187, the entire disclosures of which are hereby incorporated by reference herein) comprises an electrochromic medium sandwiched between the first and second substrates.

The ISI stack or layer **228** includes a conductive metallic layer **234**, which is thin enough to be sufficiently transparent or transmissive to allow the display information to be transmitted through the ISI or DOD layer **228** and through reflective element **216** for viewing by the driver of the vehicle. As the thickness of the metallic layer **234** decreases, the transmissivity increases, but the reflectivity decreases. Therefore, a desired thickness of the metallic layer (along with a desired thickness of the other layers of the ISI stack or layer) must be selected to provide sufficient reflectivity and transmissivity, as discussed below. Because the metallic layer **234** is at least partially transmissive, it is desirable to provide an opaque coating or tape or the like **225** on an outer surface **224b** of second substrate **224** (or the fourth surface of the reflective element **216**). The coating or tape **225** may be a black tape or other color tape or coating.

Display system **218** preferably comprises a display on demand type of display and includes a display element or light emitting device **218a** positioned at the back surface **224b** of second substrate **224**. Display element **218a** is operable to emit light, such as in the form of indicia, alphanumeric characters, images, or the like, in response to a control or input. Display element **218a** may be a vacuum fluorescent (VF) display element, a light emitting diode (LED) display element, an organic light emitting diode (OLED) display element, a gas discharge display element, a plasma display element, a cathode ray tube display element, a backlit active matrix LCD screen, an electroluminescent display element, a field emission display element or the like, without affecting

17

the scope of the present invention. The particular display element may be selected to provide a desired color to the display. For example, a VF display element may provide a blue-green color or other colors to the information displayed (depending on the phosphor selected for the display), while a light emitting diode display element may provide other colors, such as reds, ambers, or other colors to the information displayed.

Preferably, the display is a display-on-demand type of display, such as of the type disclosed in commonly assigned U.S. Pat. Nos. 5,668,663 and 5,724,187, and/or in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381; and Ser. No. 09/793,002, filed Feb. 26, 2001 by Schofield et al. for VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, now U.S. Pat. No. 6,690,268, which are all hereby incorporated herein by reference. With such a display, it is not only desirable to adjust the display brightness according to ambient lighting conditions, but it is also desirable to adjust the display brightness such that a sufficient contrast ratio is maintained against the variable background brightness of the reflected scene. Also, it may be desirable to compensate for changes in transmission of the electrochromic device effected to control rearward glare sources, so that the display brightness appears to be maintained at a generally constant level.

It is envisioned that the display **218** may include a filter or spectral element **217** positioned between the illumination source or display element **218a** of the display **218** and the outer or fourth surface **224b** of second substrate **224**. The filter **217** may function to filter out light having a wavelength outside of the desired band of light being emitted by the display element or, in other words, the filter or spectral element **217** may transmit a band width of light that substantially matches the particular spectral output of the display or that substantially matches a desired color for the display information. By transmitting only the spectral band which at least generally matches the spectral output of the display device, the filter functions to filter out ghost images of the display, where ambient light may enter the display, such that the display characters may be visible through the reflective element when the display is off.

Because the reflectivity of the metallic layer **234** provides sufficient reflectance over its entire surface (i.e., there are no “windows” formed in or through the metallic layer), mirror assembly **210** may include other displays or multiple display on demand type displays, or other types of displays, such as one or more “display on need” type displays or the like. For example, one or more display on need type displays **213** (FIG. 7) may be provided, such as to indicate to the driver of the vehicle that a door of the vehicle is ajar, or that the driver’s seat belt is not fastened, or any other condition or status that may be important to the driver or occupant of the vehicle. The display on need type display or displays may provide indicia, alphanumeric characters, symbols, or the like via one or more light emitting sources (not shown) behind the second substrate in a similar manner as display system **218** discussed above, and may include a filter (also not shown) for filtering out light that is not within the desired spectral band of the particular display system.

In the illustrated embodiment of FIG. 8, ISI or DOD layer or stack **228** includes a first semi-conductive layer **230**, a second semi-conductive layer or adhesion layer **232**, a reflective and transmissive metallic layer **234** and a semi-conductive or passivation layer **236**. Similar to ISI layer **28**, discussed above, semi-conductive layer **230** may be deposited or applied to substantially the entire surface **224a** of substrate

18

224, while the outer region or edge of semi-conductive layer **230** and substrate **224** may be masked during the deposition process so that the layers **232**, **234**, **236** do not cover the outer edge of substrate **224** and semi-conductive layer **230**.

Preferably, the physical thicknesses and materials of the metallic layer **234** and the semi-conductive layers **230**, **232** and **236** are selected to provide sufficient transmissivity of at least a particular spectral band or range of wavelengths of light which generally matches the peak intensity spectral band of light being emitted by the display. Such spectral tuning or matching of the layers to the display allows the display information to transmit through the reflective element for viewing of the display information by the driver of the vehicle, while also providing sufficient reflectivity over the entire reflective element, and while minimizing the tinting or color interference affects on the reflected image (or targeting such tinting affects toward a desired color). Preferably, the light transmission of the particular spectral band through the reflective element is greater than approximately 15 percent and the reflectivity of the reflective element to other wavelengths of light is greater than approximately 80 percent. More preferably, the light transmission of the particular spectral band is greater than approximately 20 percent, and most preferably greater than approximately 25 percent.

The reflective element **216** is spectrally tuned to maximize transmissivity of a particular desired or targeted range or ranges of wavelengths or spectral bands and to substantially reflect or not transmit other wavelengths of light. The particular choices or thicknesses/materials of the layers is influenced by the spectral emission of the display being used in the mirror assembly. In one exemplary embodiment of the present invention, a transmissive ISI or DOD layer or stack **228** includes a metallic layer **234** of approximately 350 Å sandwiched between a semi-conductive passivation layer **236** of approximately 68 nm (680 Å) and a semi-conductive adhesion layer **232** of approximately 41 nm (410 Å). The adhesion layer **232** is deposited on a semi-conductive layer **230** having a thickness of approximately 30 nm (300 Å). In this embodiment, the ISI layer **228** is spectrally tuned for transmission of an orange light (having a peak intensity wavelength in the range of approximately 600 nm) emitting from display device **218a**.

In certain conditions, the ambient light intensity within the cabin of the vehicle may be sufficiently high so that reflected light from the mirror reflective element and, in particular, from the display region **220**, tends to “wash-out” the display. It is envisioned that this glare may be reduced by taking advantage of the electrochromic function of the mirror assembly. More particularly, the electrochromic medium **240** of the electrochromic mirror reflective element **216** may be colored or darkened in the area of the display by constructing a locally addressable region across the display (as shown at **220**, **220a** of FIG. 7). This may be achieved by creating a deletion line in the second surface semi-conductive layer **226** at the second surface of the first or front substrate **222** (FIG. 8) and/or in the third surface semi-conductive layer **230** (or a third surface semi-conductive layer of the type shown in FIG. 9 and described below at **332**), hence breaking electrical continuity from the rest of the electrochromic cell. An ambient light sensor (not shown) may be used to detect the critical ambient light levels at which “wash-out” is a problem. The addressable region may then be separately colored or darkened to the appropriate level to reduce the glare from the display area in response to the ambient light sensor. Although such a glare problem could be solved by coloring the entire mirror, by localizing the region of coloration to only the display area, the electrochromic mirror assembly of the present invention

allows the rest of the mirror reflective area, which does not incorporate the display, to retain full reflectivity while the display area is colored or darkened (such as may be useful when driving by day).

In another exemplary embodiment of the present invention, a transmissive ISI or DOD layer includes a metallic layer **234** of approximately 40 nm (400 Å) sandwiched between a semi-conductive passivation layer **236** of approximately 43 nm (430 Å) and a semi-conductive adhesion layer **232** of approximately 10 nm (100 Å). The semi-conductive adhesion layer **232** is deposited on an adhesion or semi-conductive layer **230** having a thickness of approximately 30 nm (300 Å). In this embodiment, the ISI or DOD layer **228** is spectrally tuned for spectrally selective transmission of a blue-green light (having a peak intensity wavelength of approximately 505 nm) emitting from display device **218a**.

The thickness of the first semi-conductive layer **230** may be the same for each embodiment described above (and for the particular embodiments discussed below, such as with respect to FIGS. **10-17**), in order to provide a common conductive substrate (including the semi-conductive layer **230** already deposited or coated on the surface of the substrate) for the different particular applications of the substrate and ISI layers of the present invention. This may ease the manufacturing of the reflective elements, since the same hot ITO coating or the like may be applied to common substrates for various applications, and then the conductive substrates may be coated with different thickness layers of conductive and metallic coatings for different applications of the reflective element (such as for mirrors having different colored displays).

As discussed above with respect to ISI layer **128**, and with reference now to FIG. **9**, a second substrate **324** may have an ISI or DOD layer **328** on its inward or forward surface **324a** which may include layers **332**, **334**, **336** which may have a tab-out portion **331** for electrical connections, so as to not require the first conductive layer, without affecting the scope of the present invention. Because the metallic layer **334** is thin and not as conductive as the metallic layer **134**, discussed above, the tab-out portion **331** of ISI layer **328** is preferably substantially larger in size or width than the tab-out portion **131** may have been for ISI layer **128**. In a particular exemplary embodiment of the substrate **324** and ISI layer **328** of a reflective element as shown in FIG. **9**, where the conductive layer **332** is deposited directly on the surface **324a** of substrate **324**, the ISI layer **328** may include a metallic layer **334** of approximately 35 nm (350 Å) sandwiched between a passivation layer **336** of approximately 70 nm (700 Å) and an adhesion layer **332** of approximately 70 nm (700 Å). This combination or stack of layers on the glass or substrate **324** provides a transmissive reflective element which is at least approximately 20 percent transmissive and which is spectrally tuned to pass a particular band of light being emitted by display device **218a** of display system **218**. In this particular embodiment, the transmissive reflective element is spectrally tuned to pass light having a peak intensity wavelength of approximately 605 nanometers, while substantially reflecting other light.

Other thicknesses and materials of the layers may be selected for different displays having different colors or wavelengths of emitted light, without affecting the scope of the present invention. The thicknesses and particular materials of the layers of the ISI or DOD stack and transmissive reflector are selected such that their combination provides enhanced or substantial transmissivity of the spectral band or bands corresponding to the spectral band of light emitted by the particular display implemented in the reflective element, while providing substantial reflectance of other visible light.

Referring now to FIG. **10**, a second substrate **424** of a reflective element may have multiple layers or a double ISI or DOD layer or stack **428** applied to inward surface **424a**. Double ISI layer **428** includes a first semi-conductive layer **430** applied to or deposited on inward surface **424a**, a second semi-conductive or adhesion layer **432a** deposited on semi-conductive layer **430**, a first metallic layer **434a** deposited on semi-conductive layer **432** and another semi-conductive layer **436a** deposited on metallic layer **434a**. Double ISI layer **428** further includes a second metallic layer **434b** deposited on semi-conductive layer **436a** with another semi-conductive layer **436b** deposited on second metallic layer **434b**. Therefore, the ISI stack or layer **428** is an alternating stack or combination of dielectric or transparent semi-conductive layers and metallic layers, whereby each metallic layer is sandwiched between a respective pair of conductive or semi-conductive non-metallic layers.

Such an arrangement may be used to provide a desired amount or increased amount of spectrally selective transmission of one or more particular spectral bands of light through the ISI or DOD layers, while increasing the reflectivity or maintaining the reflectivity of the ISI or DOD layers with respect to other spectral bands of light over the single ISI or DOD stack designs discussed above. More particularly, the double stack arrangement (or more layers if desired) provides for increased transmission of a narrower spectral band of light, which allows the reflective element to transmit a high percentage (such as greater than approximately 50 percent transmissivity) of a selected narrow spectral band of light. The narrow spectral band is selected so as to be substantially pinpointed or targeted at the particular peak intensity wavelength or wavelengths of light being emitted by the display device. Such an arrangement is particularly suitable for use with display devices incorporating light emitting diodes, which may emit light within a particular, narrow spectral band. The particular thickness and material for each layer or coating may be selected depending on the particular application and desired results.

For example, in a single ISI or DOD stack design which provides approximately 20-25 percent transmissivity of a particular spectral band or range, the reflectance of the ISI layer may be approximately 60-70 percent with respect to other light. If it is desired that the mirror have approximately 70 percent photopic reflectance or higher and increased transmissivity of a desired spectral band of light, a double ISI or DOD stack may be implemented. One particular embodiment of such a double ISI stack provides a semi-conductive layer (**430** and/or **432**) of approximately 71 nm (such as a layer **430** of approximately 30 nm (300 Å) and a layer **432a** of approximately 41 nm (410 Å) or other combinations) of ITO or the like, a first metallic layer **434a** of approximately 41 nm (410 Å), a semi-conductive layer **436a** of approximately 101 nm (1010 Å) of ITO or the like, a second metallic layer **434b** of approximately 36 nm (360 Å) and a semi-conductive layer **436b** of approximately 10 nm (100 Å) of ITO or the like. This embodiment provides increased reflectivity of the reflective element to most wavelengths of light, while achieving the desired amount of transmissivity of the particular, targeted spectral band or bands. This is because the two metallic layers **434a**, **434b**, which are generally planar and parallel to each other, are separated by a distance of the order of approximately 100 nm (1000 Å), which gives rise to multiple beam interference of the incident light, resulting in constructive interference at certain wavelengths and destructive interference at other wavelengths. This particular example provides a reflective element which is spectrally tuned to substantially

transmit light with a wavelength of approximately 602 nanometers, while substantially reflecting other visible light.

Other materials (with other refractive indices) and other physical thicknesses for the layers may be selected to transmit other desired wavelengths or ranges of wavelengths, without affecting the scope of the present invention. Also, additional repeating layers may be added to form a multiple stack, such as an additional metallic conducting layer and an additional semi-conductive ITO layer (or the like), in order to achieve the desired affect. The repeating and alternating layers form a narrow band ISI stack (which may have seven or nine or more layers of conductive layers and metallic layers), which functions to pass or transmit only such light which corresponds to one or more particular, substantially narrow spectral bands or ranges of wavelengths. The additional layers may provide enhanced performance of the reflective element with only an incremental increase in cost, since the additional layers are preferably deposited onto the other layers as part of the sputter coating process. With each additional set or stack of layers, each of the reflective, metallic layers may be reduced in thickness, which may provide increased transmissivity through the stack for a targeted spectral band, while still providing the desired amount of reflectivity over the reflective element. For example, a nine layer ISI or DOD stack (such as shown in FIG. 17 and discussed below) may provide a reflective element that has a greater than approximately 60 percent transmissivity of one or more particular, narrow spectral bands, and which is tuned or substantially pinpointed to match the emission spectrum from a particular display device (such as a display device including a light emitting diode).

Referring now to FIGS. 11-17, several particular examples of a reflective element or mirror element in accordance with the present invention are shown. The reflective elements of FIGS. 11-17 incorporate the design and functional aspects of the reflective elements discussed above, and are provided as specific examples or embodiments of the present invention. The materials and physical thicknesses of the layers are selected to provide different refractive indices and thicknesses to provide different beam interference of the incident light, thereby resulting in the desired transmissive range for a particular display element. In each embodiment of FIGS. 11-17, the various layers and substrates are given similar reference numbers as shown with respect to the reflective elements shown in FIGS. 2-10, but with each embodiment adding 100 to the reference numbers of the previous embodiment. Clearly, the scope of the present invention includes other combinations of layers that may be implemented to provide for enhanced transmissivity of one or more particular spectral bands of light, while providing substantial reflectance of other light.

With reference to FIG. 11, a reflective element 516 has a front substrate 522 and a rear substrate 524 and a display element 518 at a rear or fourth surface of rear substrate 524. A semi-conductive ITO layer (or the like) 530 of approximately 30 nm is deposited on the forward or third surface of rear substrate 524, while a semi-conductive layer 526 (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate 522. An ISI or DOD stack or layer 528 and an electrochromic (EC) medium 540 and seal 541 are provided between the semi-conductive layers 526, 530. ISI layer 528 comprises a substantially transparent semi-conducting non-metallic adhesion layer 532 of approximately 41 nm of ITO, ICO, IWO or the like, a metallic conducting layer 534 of approximately 35 nm of silver or silver alloy or the like, and a substantially transparent semi-conducting non-metallic passivation layer 536 of approximately 68 nm of ITO, ICO, IWO or the like. As shown in FIG. 11A, such a

configuration provides a transmissivity of light through reflective element 516 with a peak transmissivity of light having a wavelength of approximately 580 nm. The transreflective reflector of the reflective element 516 is thus spectrally tuned to transmit orange light, such as light emitted from an orange vacuum fluorescent display 518, which emits light having a peak intensity of approximately 580 nm, as shown in FIG. 11B. The display 518 may also include a color filter 517, such as discussed above with respect to display 218.

In another particular embodiment similar to that of FIG. 11, an automotive DOD electrochromic mirror cell may include a transparent conductive layer, such as an ITO layer or the like (having, for example, approximately 12 ohms per square resistivity, which is commercially available as an ITO coated substrate), at the innermost, second surface of the front substrate, and a three layer coating or stack deposited on a transparent conductive layer, such as an ITO layer, at the rear substrate, itself deposited on the inner facing third surface of the rear substrate in a front/rear twin substrate laminate cell construction. The ITO layer at the rear substrate layer may have, for example, approximately 80 ohms per square resistivity, and the rear substrate may be a commercially available ITO coated substrate. The three layer stack or layers may be applied to the appropriate ITO coated surface of the rear substrate, such as via sputter coating or the like. For example, the rear glass element or substrate may be placed in a coating mask fixture to mask the perimeter and may be placed in a vacuum deposition system. The transreflective third surface reflector/conductor may be made on or applied to the intended surface of the rear substrate (or to the ITO layer on the "third surface") by sequentially depositing first approximately 41 nm of ITO, second approximately 40 nm of silver metal and third approximately 65 nm of ITO onto the ITO layer at the third surface of the rear substrate.

The front and rear substrates are spaced apart using an epoxy perimeter seal (as is known and practiced in the electrochromic mirror art) with the conductive surfaces facing each other and preferably with an offset for the purpose of attaching an electrode clip or busbar. The spacing between the conductive planar surfaces is, for example, approximately 90 μ m. After curing of the epoxy seal, the reflective element may be vacuum filled with an electrochromic medium, such as an electrochromic monomer material or the like. After filling the reflective element with the electrochromic monomer, the filling port of the reflective element or cell may be plugged with a UV curable adhesive which may then be cured by exposure to UV radiation. The reflective element or cell may then be cured in an oven to form a solid polymer matrix electrochromic medium.

When such an embodiment was formed and tested, a voltage of approximately 1.2 volts was applied to the reflective element and it was observed to color rapidly and uniformly. The photopic reflectance of the reflective element was initially approximately 67%, with a neutral silvery appearance, and decreased to approximately 7% in less than approximately 8 seconds with the voltage applied. The transmittance of the reflective element in its bleached state was approximately 19% for light having wavelengths between approximately 600 nm and 620 nm. When the voltage was disconnected or stopped, the reflectance of the reflective element substantially uniformly returned to its original value of approximately 67% within about 10 seconds. The DOD stack of the present invention thus may provide for enhanced transmittance of light having a preselected wavelength or range or band of wavelengths, even when in the bleached or colored or darkened state.

23

It is further envisioned that one or more adhesion enhancement layers or passivation layers, such as a layer or layers of nichrome (NiCr), palladium (Pd), platinum (Pt) or the like, may be applied or disposed at one or both sides of the metallic or silver layer **534**, in order to increase the corrosion resistance of the metallic layer and to enhance the adhesion and the mechanical stability of the metallic layer. For example, an adhesion or passivation layer may be applied or disposed between metallic layer **534** and semi-conductive layer **532**, and another adhesion or passivation layer may be applied or disposed between metallic layer **534** and semi-conductive layer **536**. The adhesion or passivation layer or layers may have a thickness of approximately 0.5 nm to approximately 10 nm or thereabouts. The adhesion or passivation layers may be disposed at one or both sides or surfaces of the metallic layer or layers of any of the reflective element embodiments described herein or of other types of electrochromic reflective elements, without affecting the scope of the present invention. Such adhesion or passivation layers may be applied at the metallic layer or layers of other stacks or layers of the present invention described herein.

With reference to FIG. 12, a reflective element **616** has a front substrate **622** and a rear substrate **624** and a display element **618** at a rear or fourth surface of rear substrate **624**. A semi-conductive ITO layer (or the like) **630** of approximately 30 nm is deposited on the forward or third surface of rear substrate **624**, while a semi-conductive layer **626** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **622**. An ISI or DOD stack or layer **628** and EC medium **640** and seal **641** are provided between the semi-conductive layers **626**, **630**. ISI layer **628** comprises an adhesion layer **632** of approximately 10 nm of ITO, ICO, IWO or the like, a metallic layer **634** of approximately 40 nm of silver or silver alloy or the like, and a passivation layer **636** of approximately 43 nm of ITO, ICO, IWO or the like. As shown in FIG. 12A, such a configuration provides a transmissivity of light through the reflective element with a peak transmissivity of light having a wavelength of approximately 500 nm. The reflective element **616** is thus spectrally tuned to transmit light emitted from a blue-green vacuum fluorescent display **618**, which may emit light having a peak intensity of approximately 500 nm, as shown in FIG. 12B.

With reference to FIG. 13, a reflective element **616'** provides a substantially spectrally neutral transmission characteristic and has a front substrate **622'** and a rear substrate **624'** and a display element **618'** at a rear or fourth surface of rear substrate **624'**. A semi-conductive ITO layer (or the like) **630'** of approximately 30 nm is deposited on the forward or third surface of rear substrate **624'**, while a semi-conductive layer **626'** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **622'**. An ISI or DOD stack or layer **628'** and EC medium **640'** and seal **641'** are provided between the semi-conductive layers **626'**, **630'**. ISI layer **628'** comprises an adhesion layer **632'** of approximately 78 nm of ITO, ICO, IWO or the like, a metallic layer **634'** of approximately 31 nm of silver or silver alloy or the like, and a passivation layer **636'** of approximately 63 nm of ITO, ICO, IWO or the like. As shown in FIG. 13A, such a configuration provides a generally neutral transmission of light through the transreflective reflective element for most wavelengths of visible light.

With reference to FIG. 14, a reflective element **716** has a front substrate **722** and a rear substrate **724** and a display element **718** at a rear or fourth surface of rear substrate **724**. A semi-conductive ITO layer (or the like) **730** of approximately 30 nm is deposited on the forward or third surface of rear substrate **724**, while a semi-conductive layer **726** (such as

24

ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **722**. A double stack ISI or DOD stack or layer **728** and EC medium **740** and seal **741** are provided between the semi-conductive layers **726**, **730**. Double stack ISI layer **728** comprises a semi-conductive adhesion layer **732** of approximately 60 nm of ITO, ICO, IWO or the like, a first metallic layer **734a** of approximately 33 nm of silver or silver alloy or the like, a semi-conductive layer **736a** of approximately 117 nm of ITO, ICO, IWO or the like, a second metallic layer **734b** of approximately 33 nm of silver, silver alloy or the like, and a semi-conductive layer **736b** of approximately 86 nm of ITO, ICO, IWO or the like. As shown in FIG. 14A, such a configuration provides a transmissivity of light through the reflective element with a peak transmissivity of light having a wavelength of approximately 650 nm. The reflective element **716** is thus spectrally tuned to transmit red light, such as light emitted from a red light emitting diode display **718**, which may emit light having a peak intensity of approximately 650 nm, as shown in FIG. 14B. As can be seen with reference to FIGS. 14A and 11A, the transreflective reflector and double stack ISI or DOD layer **728** provide a narrower band of transmissivity for the desired spectral band or range of wavelengths being emitted by the display. Such a configuration thus may provide enhanced reflectivity of light outside of the targeted spectral band.

With reference to FIG. 15, a reflective element **816** has a front substrate **822** and a rear substrate **824** and a display element **818** at a rear or fourth surface of rear substrate **824**. A semi-conductive ITO layer (or the like) **830** of approximately 30 nm is deposited on the forward or third surface of rear substrate **824**, while a semi-conductive layer **826** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **822**. A double stack ISI or DOD stack or layer **828** and EC medium **840** and seal **841** are provided between the semi-conductive layers **826**, **830**. Double stack ISI layer **828** comprises a semi-conductive adhesion layer **832** of approximately 23 nm of ITO, ICO, IWO or the like, a first metallic layer **834a** of approximately 30 nm of silver or silver alloy or the like, a semi-conductive layer **836a** of approximately 204 nm of ITO, ICO, IWO or the like, a second metallic layer **834b** of approximately 34 nm of silver, silver alloy or the like, and a semi-conductive layer **836b** of approximately 47 nm of ITO, ICO, IWO or the like. As shown in FIG. 15A, such a configuration provides a transmissivity of light through the reflective element with a peak transmissivity of light having a wavelength of approximately 500 nm. The reflective element **816** is thus spectrally tuned to transmit blue-green light, such as light emitted from a blue-green light emitting diode display **818**, which may emit light having a peak intensity of approximately 500 nm. Similar to double stack ISI layer **728** discussed above, the transreflective reflector and double stack ISI layer **828** provide a narrower band of transmissivity for the desired spectral band or range of wavelengths being emitted by the display. Such a configuration thus may provide enhanced transmissivity of the pre-selected or targeted spectral band and enhanced reflectivity of light outside of the targeted spectral band.

With reference to FIG. 16, a reflective element **916** has a front substrate **922** and a rear substrate **924** and a display element **918** at a rear or fourth surface of rear substrate **924**. A semi-conductive ITO layer (or the like) **930** of approximately 30 nm is deposited on the forward or third surface of rear substrate **924**, while a semi-conductive layer **926** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **922**. A multiple stack ISI or DOD stack or layer **928**, EC medium **940**, seal **941** and encapsulant **943** are provided between the semi-conductive layers **926**,

25

930. The ISI or DOD stack or layer **928** may be provided on ITO layer **930** so as to have a tab out portion as discussed above with respect to ISI layer **328**. The encapsulant **943** is provided along the edges of the tab out portion of reflective element **916**, and the seal **941** is provided between the tab out portion and the ITO layer **926** on front substrate **922** and between the ITO layers **924**, **926** around ISI layer **928** where there is no tab out portion.

Multiple ISI or DOD stack or layer **928** comprises an adhesion layer **932** of approximately 80 nm of ITO, ICO, IWO or the like, a first metallic-layer **934a** of approximately 30 nm of silver or silver alloy or the like, a layer **936a** of approximately 101 nm of silicon oxide or the like, a layer **934b** of approximately 60 nm of titanium oxide or the like, a layer **936b** of approximately 95 nm of silicon oxide or the like, a layer **934c** of approximately 161 nm of titanium oxide or the like, a layer **936c** of approximately 53 nm of silicon oxide or the like, a metallic layer **934d** of approximately 50 nm of silver or silver alloy or the like, and a layer **936d** of approximately 72 nm of ITO, ICO or the like. As shown in FIG. **16A**, such a configuration provides a transmissivity of light through the reflective element with a peak transmissivity of light having a wavelength of approximately 650 nm. The reflective element **916** is thus spectrally tuned to transmit red light, such as light emitted from a red light emitting diode display **918**, which may emit light having a peak intensity of approximately 650 nm. The transreflective reflector and multiple stack ISI layer **928** provide an extra narrow band of transmissivity for the desired spectral band or range of wavelengths being emitted by the display. Such a configuration thus may provide enhanced reflectivity of light outside of the targeted spectral band. As can be seen in FIG. **16A**, reflective element **916** may also transmit spectral bands of light at certain other wavelengths or ranges of wavelengths as well, such as at approximately 410 nm and 470 nm.

With reference to FIG. **17**, a reflective element **1016** has a front substrate **1022** and a rear substrate **1024** and a display element **1018** at a rear or fourth surface of rear substrate **1024**. A semi-conductive ITO layer (or the like) **1030** of approximately 30 nm is deposited on the forward or third surface of rear substrate **1024**, while a semi-conductive layer **1026** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **1022**. A multiple stack ISI or DOD stack or layer **1028**, EC medium **1040**, seal **1041** and encapsulant **1043** (around a tab out portion of the ISI layer, as discussed above) are provided between the semi-conductive layers **1026**, **1030**.

Multiple stack ISI or DOD layer **1028** comprises an adhesion layer **1032** of approximately 80 nm of ITO, ICO, IWO or the like, a first metallic layer **1034a** of approximately 46 nm of silver or silver alloy or the like, a layer **1034b** of approximately 80 nm of titanium oxide or the like, a layer **1036a** of approximately 85 nm of silicon oxide or the like, a layer **1034c** of approximately 188 nm of titanium oxide or the like, a layer **1036b** of approximately 48 nm of silicon oxide or the like, a metallic layer **1034d** of approximately 42 nm of silver or silver alloy or the like, and a layer **1036c** of approximately 77 nm of ITO, ICO or the like. As shown in FIG. **17A**, such a configuration provides a transmissivity of light through the reflective element with two peak transmission bands, namely, a first spectral band having a peak transmissivity of light having a wavelength of approximately 465 nm and a second spectral band having a peak transmissivity of light having a wavelength of approximately 645 nm. The reflective element **1016** is thus spectrally tuned to substantially transmit both blue light, such as light emitted from a blue light emitting diode display **1018a**, which may emit light having a peak

26

intensity of approximately 465 nm, and red light, such as light emitted from a red light emitting diode display **1018b**, which may emit light having a peak intensity of approximately 645 nm. The transreflective reflector and multiple stack ISI layer **1028** provide an extra narrow band of transmissivity for each of the desired spectral bands or ranges of wavelengths being emitted by the displays. Such a configuration thus may facilitate the implementation of different colored display elements, while providing enhanced reflectivity of light outside of the targeted spectral bands.

Referring now to FIG. **18**, an electro-optic or electrochromic mirror element **1116** comprises a pair of substrates (a front substrate **1122** is shown in FIG. **18**), with an electrochromic medium (not shown in FIG. **18**) sandwiched therebetween. Electrochromic mirror element **1116** may comprise a reflective metallic layer or layers and transparent, at least partially conductive layers, such as discussed above, to provide a transreflective mirror element. The electrochromic mirror element **1116** includes one or more display elements, such as the three display elements **1118a**, **1118b**, **1118c** shown in FIG. **18**, positioned behind the rear substrate and operable to emit or transmit light through the substrates and layers and electrochromic medium for viewing at the front substrate **1122**.

The electrochromic mirror element **1116** comprises at least two regions, such as the three regions **1116a**, **1116b**, **1116c** shown in FIG. **18**. A central or principle viewing region **1116a** provides a respective reflectivity and transmissivity, such as via layers or coatings as described above. One or both side regions **1116b**, **1116c** also provide a respective reflectivity and transmissivity. In the illustrated embodiment, the display element or elements **1118a**, **1118b**, **1118c** are positioned at the side or display regions **1116b**, **1116c**. The conductive metallic and semiconductive non-metallic layers may be selected and adjusted so that the transmissivity in the side regions **1116b**, **1116c** may be greater than the transmissivity in the central region **1116a**, while the reflectivity in the central region **1116a** may be greater than the reflectivity in the side or display regions **1116b**, **1116c**. The present invention thus provides greater transmissivity in the display regions to enhance viewing of the displays, while providing greater reflectivity in the central or main region of the mirror element to provide enhanced reflectivity in the principle viewing area.

In the illustrated embodiment, the transmissivity at the display regions may be approximately 25%, while the transmissivity in the central or principle viewing region may be approximately 20%. Likewise, the reflectivity in the central or principle viewing region may be approximately 65%, while the reflectivity in the display regions may be approximately 60%. Other reflective and transmissive characteristics may be achieved without affecting the scope of the present invention.

The difference in the reflectivity and transmissivity between the regions is achieved by selecting different combinations of vapor source and masking of the regions to achieve the desired effect. For example, the thicknesses of different layers of the conductive metallic layer or layers and of the transparent, at least partially conductive layers may be selected or adjusted across the mirror element to achieve a desired amount of transmissivity at the display regions, while maintaining sufficient reflectivity in these regions, and to achieve a desired or optimum or maximum reflectivity at the central or principle viewing area or region of the mirror element. For example, a reflective metallic coating or layer may be thicker at the principle viewing region than at the display region or regions, while a transparent layer or coating may be thinner at the principle viewing region than at the display

region or regions. Although shown as having display regions at the side regions of the mirror element, clearly displays and associated display regions providing enhanced transmissivity may be positioned elsewhere around the mirror element, without affecting the scope of the present invention.

Therefore, the reflective element or mirror element of the present invention allows for a display element to be positioned behind the reflective layer and transmits light from the display element through the mirror element, while providing sufficient reflectivity across the entire mirror element and not requiring any windows or thinned areas of reduced reflectivity in the display region. The present invention thus provides a mirror assembly which may include multiple display-on-demand type displays or display-on-need type displays, without adversely affecting the reflective nature of the reflective element. Furthermore, the transmissivity of the ISI or DOD stack or layer or the multiple stack ISI or DOD layers of the transmissive reflector of the present invention may match or pinpoint the particular spectral band corresponding to the light emitted by the display element or device, in order to provide improved transmission of the display information or light through the stack (and thus through the reflective element), while providing a desired neutral reflectance over the entire surface of the reflector. The present invention thus may provide a reflective element which has a transmissivity level of greater than at least approximately 20 percent, more preferably at least approximately 30 percent, and most preferably at least approximately 50 percent, for light within a particular narrow spectral band or range of wavelengths, while providing substantial reflectance of light outside of the particular, selected spectral band or range of wavelengths. The reflective element of the present invention also provides for generally uniform thickness of the ISI or DOD layers, since none of the layers have to be etched or masked or reduced in thicknesses to allow for the display to transmit therethrough, thereby enhancing the manufacturing processing of the reflective element.

Optionally, the mirror assembly may include an illumination source for providing illumination, such as near infrared and/or infrared illumination, within the cabin of the vehicle. For example, the illumination source may be directed toward the head of the driver of the vehicle (or the area or location where a typical driver's head would be), and may be used in conjunction with a camera device or imaging device or the like. The imaging device or imaging system may comprise a cabin monitoring system, such as a monitoring system utilizing the principles disclosed in U.S. Pat. Nos. 6,523,964; and 6,302,545, and U.S. patent application Ser. No. 10/372,873, filed Feb. 24, 2003, now U.S. Pat. No. 6,802,617; Ser. No. 09/793,002, entitled VIDEO MIRROR SYSTEMS INCORPORATING AN ACCESSORY MODULE, filed Feb. 26, 2001, now U.S. Pat. No. 6,690,268; and Ser. No. 10/054,633, filed Jan. 22, 2002 by Lynam et al. for VEHICULAR LIGHTING SYSTEM, now U.S. Pat. No. 7,195,381, which are hereby incorporated by reference herein. Optionally, the illumination source may be operable to illuminate the head of the driver while the imaging device is operable to capture images of the driver's head, such as for a video conferencing function, a driver alertness detection function (which may detect drowsiness issues, such as unorthodox head movement, nodding, glazed eyes, dilating eyes or other characteristics which may be indicative of driver fatigue or reduced alertness), a seat occupancy detection function, an intrusion detection function or any other desired functions. The illumination source or sources may comprise infrared or near infrared emitting sources, such as light emitting diodes (LEDs) or the like, to minimize the affect on or visibility to the driver of the

vehicle, such as disclosed in U.S. Pat. Nos. 6,523,964; and 6,302,545, and U.S. patent application Ser. No. 10/372,873, filed Feb. 24, 2003, now U.S. Pat. No. 6,802,617, which are hereby incorporated herein by reference. The imaging device thus may be capable of sensing infrared light, and may be particularly sensitive to infrared or near infrared light, and may comprise a CMOS imaging array or the like, such as disclosed in U.S. Pat. Nos. 5,550,677; 5,670,93.5; 5,760,962; 5,796,094 and 5,877,897, which are hereby incorporated herein by reference.

The interior rearview mirror assembly may provide the illumination source or sources at the bezel or chin or eyebrow of the mirror assembly, or at a module or pod or the like associated with the mirror assembly. Optionally, the mirror assembly may include the illumination source or sources within the mirror casing and behind the electrochromic cell of the mirror assembly, whereby the illumination source may emit near infrared light or radiant energy and project the light through a transmissive electrochromic element, which may have sufficient transmissivity in the near infrared range of the spectrum, while limiting transmissivity of light in the visible range and providing a desired amount of untinted photopic reflectance, as discussed below. The illumination source thus may be positioned behind the rear substrate of the electrochromic cell and may project the near infrared illumination through both substrates of the reflective element or cell to sufficiently illuminate or bathe or flood the targeted area with near infrared illumination. The imaging device may also be positioned within the mirror casing and behind the transmissive electrochromic element to capture images of the scene illuminated by the near infrared illumination source or sources.

The transmissive display on demand type reflective element preferably maintains an untinted, high photopic reflectance of visible light, while also providing sufficient transmissivity of near infrared light or radiant energy (such as within the range of approximately 750 nm to approximately 1100 nm). Preferably, the transmissive display on demand element provides at least approximately 30% transmissivity of near infrared light, preferably at least approximately 40%, more preferably at least approximately 60% and most preferably at least approximately 80% transmissivity of near infrared light. Typically, such near infrared transmissivity may not be achieved utilizing reflective coatings or stacks of coatings that comprise or include a metallic layer, such as a thin silver or silver alloy or aluminum or aluminum alloy layer or the like. In such applications, the infrared or near infrared light emitted by the illumination source may reflect back into the cavity of the mirror casing. The present invention overcomes this by providing an infrared or near infrared transmitting stack of dielectric layers or coatings which substantially transmit near infrared light while the transmissive element also provides high photopic reflectance of visible light. The transmissive element may provide high photopic reflectance and may meet the specifications set forth in SAE J964A, which is hereby incorporated herein by reference. Preferably, the transmissive element provides greater than approximately 55%, more preferably greater than approximately 65% and most preferably greater than approximately 75%, of such photopic reflectance.

Referring now to FIGS. 19-22, a transmissive electrochromic element or cell 1216 includes a front substrate 1222 and a rear substrate 1224, and an illumination source 1244 and an imaging device 1246 at a rear or fourth surface of rear substrate 1224. A semi-conductive layer or coating (such as ITO, tin oxide or the like) 1230 is deposited on the forward or third surface of rear substrate 1224, while a semi-conductive layer

1226 (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate 1222. An electrochromic medium 1240 and seal 1241 are provided or sandwiched between the semi-conductive layers 1226, 1230, with an electrical connector 1248 positioned at least partially along at least one edge of each of the semi-conductive layers 1226, 1230. The transreflective cell 1216 further includes an infrared or near infrared transmitting (IRT) stack or layers 1228, which, in the illustrated embodiment of FIG. 19, is positioned or stacked on the rear surface of the rear substrate 1224. A protective cover or glass sheet 1225 is adhered or secured to the rear surface of the IRT stack 1228, such as via an adhesive layer 1225a, which preferably is an index matching adhesive that matches the index of the protective cover or sheet. The protective cover may comprise glass, or may comprise other transparent or substantially clear materials, such as plastic, polycarbonate, acrylic or the like, without affecting the scope of the present invention.

IRT stack 1228 comprises multiple layers of dielectric layers or coatings across the rear surface of rear substrate 1224 which function as a cold mirror stack that allows near infrared and infrared light or radiant energy to pass therethrough while substantially reflecting visible light. The IRT stack 1228 may comprise layers of titanium oxide alternating with silicon oxide layers. The titanium oxide layers provide a higher refractive index while the silicon oxide layers provide a lower refractive index. The alternating combination of the lower and higher refracting indices of alternating layers provides enhanced near infrared transmissivity, while providing reflectivity of visible light.

In an exemplary embodiment, IRT stack 1228 comprises nineteen such alternating layers having: a first titanium oxide layer approximately 72 nm thick on the rear surface of substrate 1224, a first silicon oxide layer approximately 32 nm thick on the first titanium oxide layer, a second titanium oxide layer approximately 94 nm thick on the first silicon oxide layer, a second silicon oxide layer approximately 110 nm thick on the second titanium oxide layer, a third titanium oxide layer approximately 64 nm thick on the second silicon oxide layer, a third silicon oxide layer approximately 85 nm thick on the third titanium oxide layer, a fourth titanium oxide layer approximately 62 nm thick on the third silicon oxide layer, a fourth silicon oxide layer approximately 128 nm thick on the fourth titanium oxide layer, a fifth titanium oxide layer approximately 60 nm thick on the fourth silicon oxide layer, a fifth silicon oxide layer approximately 98 nm thick on the fifth titanium oxide layer, a sixth titanium oxide layer approximately 57 nm thick on the fifth silicon oxide layer, a sixth silicon oxide layer approximately 94 nm thick on the sixth titanium oxide layer, a seventh titanium oxide layer approximately 54 nm thick on the sixth silicon oxide layer, a seventh silicon oxide layer approximately 77 nm thick on the seventh titanium oxide layer, an eighth titanium oxide layer approximately 36 nm thick on the seventh silicon oxide layer, an eighth silicon oxide layer approximately 83 nm thick on the eighth titanium oxide layer, a ninth titanium oxide layer approximately 58 nm thick on the eighth silicon oxide layer, a ninth silicon oxide layer approximately 97 nm thick on the ninth titanium oxide layer, and a tenth titanium oxide layer approximately 28 nm thick on the ninth silicon oxide layer. Clearly, other thicknesses and combinations of layers may be implemented to achieve the desired levels of transmissivity and reflectivity, without affecting the scope of the present invention. The transreflective element thus provides a fourth surface transreflective mirror element, with multiple alternating layers of silicon oxide and titanium oxide to enhance the near infrared transmissivity through the ITO layers and substrates.

The transmissivity percentage of such a substrate versus the light wavelength is shown in FIG. 22. As can be seen in FIG. 22, the substrate 1224 and IRT stack 1228 transmit more than 90% of near infrared light, while substantially not transmitting light in the visible range of the spectrum. The transreflective element 1216 is thus spectrally tuned to transmit near infrared light emitted from illumination source 1244, and may transmit the near infrared light from the scene back to the imaging sensor 1246. As can be seen in FIG. 22, the transmission is generally constant or flat for the desired wavelengths at an angle of incidence of the light source relative to the substrate between approximately 0 degrees and approximately 50 degrees.

The arrangement shown in FIG. 19 may allow the mirror manufacturer to purchase the rear substrate sheet or material, which may be purchased from a glass or substrate supplier or vendor with the front ITO layer or coating and the cold mirror stack or IRT stack already applied thereto or deposited thereon. The ITO layers and alternating silicon oxide and titanium oxide layers may be deposited on the respective surfaces or layers via any known manner, such as vacuum deposition or the like, and such as disclosed in U.S. Pat. Nos. 5,668,663; 5,724,187; and 6,002,511, which are hereby incorporated herein by reference. This allows the mirror manufacturer to select an appropriate rear substrate, depending on the desired function or application of the mirror assembly, and to assemble the transreflective element with the selected substrate. The mirror manufacturer may purchase the substrates, cut out the desired shape for the mirror reflective element and glue or adhere or otherwise join the substrates (with coatings thereon) together (and sandwich the electrochromic medium between the front and rear substrate) to form the desired transreflective element.

Prior to deposition, it is desirable/beneficial to clean the substrate using a plasma source or an ion source, such as a linear ion source or the like, which may result in enhanced adhesion of the thin films to the substrate. It is preferable that the substrate cleaning is accomplished in one single pump down cycle of the vacuum coating process. For example, glass substrates can enter a vacuum chamber via a load-lock, and pass under a plasma source, such as a linear ion source or the like, where the surface-to-be-coated is activated/cleaned by exposure to a plasma and/or by ion bombardment or the like. The now plasma activated/ion-bombardment cleaned surface is then coated with an ITO layer, followed by a metallic layer (such as silver), followed by an ITO layer such as described herein. Optionally, and preferably, a three-sided target assembly is used, for example, one side may be a linear ion source, another side may be an ITO target, and the third side may be a silver target. The three-sided target assembly can, for example, rotate (such as clockwise) to first ion clean the substrate, then rotate clockwise again to deposit ITO, then rotate clockwise again to deposit silver, and then rotate counterclockwise to deposit ITO again. Suitable ion sources for such a cleaning purpose include Anode Layer Sources (ALS), Kaufmann sources, gridded sources, non-gridded sources, RF sources and DC glow discharge sources and the like. The most preferred are the linear ion sources of the ALS type, such as are available from Veeco Instruments, Inc. of Colorado and Advanced Energy (AE) of Colorado.

Optionally, and desirably, the substrates 1222, 1224 may have a low absorption characteristic in the near infrared range or band of the energy spectrum, whereby the substrates provide low absorption of near infrared radiant energy, such as at wavelengths of around 880 nm or thereabouts. The substrates thus may provide enhanced transmissivity of such near infrared radiant energy through the transreflective electrochromic

element or cell. Such low absorption characteristics may be accomplished by selecting a material for the substrates that provides the desired results. For example, the substrates may comprise a borosilicate material, such as the type that is commercially available from Schott Glass Corp. under the name BOROFLOAT™, or may comprise a B270 material or SUPERWHITE™, also commercially available from Schott Glass Corp., or may comprise other materials, such as fused silica or quartz materials or the like, that may also or otherwise provide the desired degree of low absorption of near infrared radiant energy. Other materials may be selected for the substrates of the transfective electrochromic cell, without affecting the scope of the present invention.

Optionally, and with reference to FIG. 20, a transfective element **1216'** may provide the IRT stack **1228'** on a front surface of the protective cover or glass substrate or sheet **1225**. In such an embodiment, the IRT stack **1228'** and cover **1225** are adhered or secured to the rear surface of rear substrate **1224'** via the index matching adhesive **1225a** or the like. The arrangement shown in FIG. 20 allows the IRT stack to be manufactured on a separate glass sheet or protective cover, whereby the mirror manufacturer may purchase the front and rear substrates or sheets (with the ITO layers already applied thereto or deposited thereon) and the third glass sheet or protective cover with the IRT stack already deposited thereon. The protective cover may comprise glass, or may comprise other transparent or substantially clear materials, such as plastic, polycarbonate, acrylic or the like, without affecting the scope of the present invention. The IRT stack and other components of transfective element **1216'** may be substantially similar to the IRT stack and components of transfective element **1216** discussed above, such that a detailed discussion of these elements will not be repeated herein.

Optionally, and with reference to FIG. 21, a transfective element **1216"** may be substantially similar to transfective element **1216** of FIG. 19, discussed above, and may include a titanium oxide layer or coating **1227** on the rear surface of the front substrate **1222'** and between the front substrate **1222'** and the ITO layer or coating **1226'**. The titanium oxide layer **1227** may function to partially cancel out or compensate for any near infrared reflectivity by the ITO layers of the cell or element to further enhance the performance of the transfective element.

Referring now to FIG. 23, a transfective electrochromic element or cell **1316** includes a front substrate **1322** and a rear substrate **1324**, and an illumination source **1344** and an imaging device **1346** at a rear or fourth surface of rear substrate **1324**. A semi-conductive layer or coating **1326** (such as ITO, tin oxide or the like) is deposited on the rear or second surface of front substrate **1322**. An IRT stack **1328** is applied to or deposited on the front surface of rear substrate **1324**, and a semi-conductive layer or coating **1330** (such as ITO, tin oxide or the like) is deposited on IRT stack **1328**. An electrochromic medium **1340** and seal **1341** are provided or sandwiched between the semi-conductive layers **1326**, **1330**, with an electrical connector **1348** positioned at least partially along at least one edge of each of the semi-conductive layers **1326**, **1330**.

Similar to IRT stack **1228** discussed above, IRT stack **1328** comprises multiple layers of dielectric layers or coatings. IRT stack or cold mirror stack **1328** is deposited on the front surface of rear substrate **1324** and may comprise alternating layers of titanium oxide alternating with silicon oxide layers. The titanium oxide layers provide a higher refractive index while the silicon oxides provide a lower refractive index. The combination of the lower and higher refractive indices of the

alternating layers provides enhanced near infrared transmissivity, while providing reflectivity of visible light.

In an exemplary embodiment, IRT stack **1328** comprises nineteen such alternating layers with a twentieth layer of ITO deposited on the outermost IRT stack layer. For example, the IRT stack may comprise a first titanium oxide layer approximately 53 nm thick on the rear surface of substrate **1324**, a first silicon oxide layer approximately 57 nm thick on the first titanium oxide layer, a second titanium oxide layer approximately 84 nm thick on the first silicon oxide layer, a second silicon oxide layer approximately 103 nm thick on the second titanium oxide layer, a third titanium oxide layer approximately 58 nm thick on the second silicon oxide layer, a third silicon oxide layer approximately 96 nm thick on the third titanium oxide layer, a fourth titanium oxide layer approximately 64 nm thick on the third silicon oxide layer, a fourth silicon oxide layer approximately 108 nm thick on the fourth titanium oxide layer, a fifth titanium oxide layer approximately 63 nm thick on the fourth silicon oxide layer, a fifth silicon oxide layer approximately 93 nm thick on the fifth titanium oxide layer, a sixth titanium oxide layer approximately 44 nm thick on the fifth silicon oxide layer, a sixth silicon oxide layer approximately 70 nm thick on the sixth titanium oxide layer, a seventh titanium oxide layer approximately 37 nm thick on the sixth silicon oxide layer, a seventh silicon oxide layer approximately 61 nm thick on the seventh titanium oxide layer, an eighth titanium oxide layer approximately 58 nm thick on the seventh silicon oxide layer, an eighth silicon oxide layer approximately 102 nm thick on the eighth titanium oxide layer, a ninth titanium oxide layer approximately 31 nm thick on the eighth silicon oxide layer, a ninth silicon oxide layer approximately 55 nm thick on the ninth titanium oxide layer, and a tenth titanium oxide layer approximately 49 nm thick on the ninth silicon oxide layer. The semi-conductive layer **1330** may comprise an ITO layer approximately 130 nm thick. Clearly, other thicknesses and combinations of layers may be implemented to achieve the desired levels of transmissivity and reflectivity, without affecting the scope of the present invention. The transfective element thus provides a third surface transfective mirror element, with multiple layers of silicon oxide and titanium oxide to enhance the near infrared transmissivity through the ITO layers and substrates.

The transmissivity percentage of such a substrate versus the light wavelength is shown in FIG. 26. As can be seen in FIG. 26, such a rear substrate transmits more than approximately 90% of near infrared light, while substantially not transmitting light in the visible range of the spectrum. The transfective element **1316** is thus spectrally tuned to transmit near infrared light emitted from illumination source **1344**, and may transmit the near infrared light from the scene back to the imaging sensor **1346**. As can be seen in FIG. 26, the transmission is generally constant or flat for the desired wavelengths at an angle of incidence of the light source relative to the substrate between approximately 0 degrees and approximately 50 degrees.

The arrangement shown in FIG. 23 may allow the mirror manufacturer to purchase the rear substrate sheet or material, which may be purchased from a glass or substrate supplier or vendor with the IRT or cold mirror stack and the front ITO layer or coating already applied thereto or deposited thereon. The ITO layers and silicon oxide and titanium oxide layers may be deposited on the front surface or other layers via any known manner, such as vacuum deposition or the like, and such as disclosed in U.S. Pat. Nos. 5,668,663; 5,724,187; and 6,002,511, which are hereby incorporated herein by reference. This allows the mirror manufacturer to select an appro-

priate rear substrate, depending on the desired function or application of the mirror assembly, and to assemble the trans-reflective element with the selected substrate. The mirror manufacturer may purchase the substrates, cut out the desired shape for the mirror reflective element and glue, adhere or otherwise join the substrates (with coatings thereon)-together (and sandwich the electrochromic medium between the front and rear substrate) to form the desired transreflective element.

Optionally, and with reference to FIG. 24, a transreflective element **1316'** in accordance with the present invention may be substantially similar to transreflective element **1316** discussed above, and may include a titanium oxide layer or coating **1327** on the rear surface of the front substrate **1322'** and between the front substrate **1322'** and the ITO layer or coating **1326'**. In an exemplary embodiment, the titanium oxide layer **1327** may be approximately 250 nm thick, while the ITO layer **1326'** may be approximately 130 nm-thick, but other thicknesses may be implemented to achieve the desired result, without affecting the scope of the present invention. The titanium oxide layer **1327** may function to partially cancel out or compensate for any near infrared reflectivity by the ITO layers of the cell or element. This arrangement provides an enhanced semi-conductive layer or coating on the rear surface of the front substrate. A graphical depiction of the transmissivity of front substrate **1322'** versus wavelength of light is shown in FIG. 27. In the illustrated embodiment, the peak transmissivity wavelength is approximately 880 nm. Such a reflective element or cell thus may be particularly suited for use with an imaging device or camera that has a peak sensitivity or response to light having a wavelength of approximately 880 nm.

Optionally, and with reference to FIG. 25, another transreflective element **1316"** in accordance with the present invention may be substantially similar to transreflective element **1316** of FIG. 23, discussed above, and may include an enhanced semi-conductive layer on the rear surface of the front substrate **1322"**. The enhanced semi-conductive layer includes a titanium oxide layer or coating **1329** deposited on the rear surface of the front substrate **1322"**, a silicon oxide layer **1327'** deposited on titanium oxide layer **1329**, and an ITO layer **1326"** deposited on silicon oxide layer **1327'**. In an exemplary embodiment, the titanium oxide layer **1329** may be approximately 109 nm thick, while the silicon oxide layer **1327'** may be approximately 277 nm thick and the ITO layer **1326"** may be approximately 130 nm thick. Other thicknesses may be implemented to achieve the desired result, without affecting the scope of the present invention. The titanium oxide layer **1329** and silicon oxide layer **1327'** may function to partially cancel out or compensate for any near infrared reflectivity by the ITO layers of the cell or element to enhance the near infrared transmissivity of the front substrate and semi-conductive layers. A graphical depiction of the transmissivity of front substrate **1322"** versus wavelengths of light is shown in FIG. 28. In the illustrated embodiment, the peak transmissivity wavelength is approximately 880 nm. Such a reflective element or cell thus may be particularly suited for use with an imaging device or camera that has a peak sensitivity or response to light having a wavelength of approximately 880 nm.

Optionally, and as shown in FIG. 29, a transreflective element **1316'''** may include the substrates **1322"**, **1324'** and coatings or layers such as described above with respect to transreflective element **1316"** (FIG. 25), and may further include an anti-reflective (AR) stack or layers **1352** at the rear surface of the rear substrate **1324'**. The anti-reflective stack or layers **1352** may be selected to minimize the reflectance of light at a desired or targeted wavelength or range of wave-

lengths or spectral band to enhance the overall transmissivity at the desired or targeted spectral band. For example, the anti-reflective stack **1352** may be selected to minimize the reflectance of near infrared radiant energy, such as radiant energy having a wavelength of approximately 880 nm or thereabouts, such that the transmission of such radiant energy may be enhanced. In an exemplary embodiment, anti-reflective stack or layers **1352** comprises a layer of titanium oxide **1352a** deposited on or disposed at the rear surface of the rear substrate **1324** and a layer of silicon oxide **1352b** deposited on or disposed at the titanium oxide layer **1352a**. In one embodiment, titanium oxide layer **1352a** may have a thickness of approximately 25 nm, while silicon oxide layer **1352b** may have a thickness of approximately 205 nm, such that the anti-reflective stack or layers **1352** reduces the reflectance of near infrared radiant energy having a wavelength of approximately 880 nm or thereabouts. Other layers or thicknesses may be selected to achieve other desired results, and may be selected depending on the particular reflective element design and the particular application of the reflective element, without affecting the scope of the present invention. Such anti-reflective surfaces may be applied to or disposed on the rearward surface of other mirror elements of the present invention described herein.

Therefore, the present invention provides a transreflective electrochromic element or cell which may allow transmittance of near infrared light through the substrates while providing a desired amount of untinted photopic reflectance, and while also providing the desired degree of conductivity at the conductive or semi-conductive layers. The transreflective element may include multiple dielectric layers or coatings on one of the substrates or on a rear cover or glass sheet of the transreflective element. The dielectric layers cooperate to enhance transmissivity of infrared or near infrared light through the substrates, while providing the desired level of untinted photopic reflectance. The transreflective element thus may allow the mirror assembly to include a near infrared light emitting diode or other near infrared emitting light source to be positioned behind the transreflective element and within the mirror casing, whereby the light source may emit or project near infrared light through the transreflective element toward and into the cabin of the vehicle. The mirror assembly may also include an imaging device which may be positioned behind the transreflective element and may receive or capture images of the interior cabin of the vehicle which is covered by the near infrared light of the light source.

Optionally, and with reference to FIG. 30, it is envisioned that a transreflective element **1416** in accordance with the present invention may provide high transmissivity of near infrared radiant energy, while also providing high transmissivity of a particular wavelength or range of wavelengths or spectral band or region of visible light, yet still providing high photopic reflectance of the other visible light and sufficient conductivity. Transreflective element **1416** may be substantially similar to the transreflective elements **1316**, **1316'**, **1316"**, discussed above, but may include an infrared transmitting and display on demand stack **1428** (IRT-DOD stack) of alternating titanium oxide layers (or the like) and silicon oxide layers (or the like) that may provide for high transmissivity of near infrared radiant energy and high transmissivity of a desired visible light color, such as, for example, visible light having a wavelength of approximately 430 nm (blue). Different combinations of alternating layers may be selected to provide sufficient transmissivity of near infrared radiant energy and of other desired spectral bands, without affecting the scope of the present invention.

The titanium oxide layers provide a higher refractive index while the silicon oxides provide a lower refractive index. The combination of the lower and higher refractive indices of the alternating layers provides enhanced near infrared transmissivity, while providing high photopic reflectivity of most of the visible light, except the visible light in the desired spectral region or having the desired or selected or targeted wavelength. The transfective element thus may be used with a near infrared light emitting source **1444**, which may be used in conjunction with an imaging source or camera **1446**, and a display on demand element **1450** that may emit light at the desired or selected wavelength or color (such as, for example, blue light having a wavelength of 430 nm) so that it is viewable through the reflective element by a driver or occupant of the vehicle.

The other elements of the transfective element **1416** may be substantially similar to the transfective elements **1316**, **1316'**, **1316"**, discussed above, such that a detailed discussion of these elements will not be repeated herein. The similar or common elements are shown in FIG. **30** with similar reference numbers to those of FIG. **24**, but with one hundred added to each number. In the illustrated embodiment of FIG. **29**, the transfective element **1416** is shown with a titanium oxide (TiO_2) layer or coating **1427** on the rear surface of the front substrate **1422** and between the front substrate **1422** and the ITO layer or coating **1426**, similar to transfective element **1316'** of FIG. **24**. However, other coatings or layers may be deposited on or applied to the front substrate of the transfective element, such as, for example, the other layers discussed above, without affecting the scope of the present invention.

In an exemplary embodiment of the infrared transmitting and visible light transmitting transfective element **1416**, the IRT-DOD stack **1428** comprises nineteen such alternating layers with a twentieth layer of ITO **1430** deposited on the outermost IRT-DOD stack or layers. For example, the IRT-DOD stack may comprise a first titanium oxide layer approximately 50 nm thick on the surface of the substrate, a first silicon oxide layer approximately 83 nm thick on the first titanium oxide layer, a second titanium oxide layer approximately 48 nm thick on the first silicon oxide layer, a second silicon oxide layer approximately 159 nm thick on the second titanium oxide layer, a third titanium oxide layer approximately 50 nm thick on the second silicon oxide layer, a third silicon oxide layer approximately 97 nm thick on the third titanium oxide layer, a fourth titanium oxide layer approximately 61 nm thick on the third silicon oxide layer, a fourth silicon oxide layer approximately 104 nm thick on the fourth titanium oxide layer, a fifth titanium oxide layer approximately 59 nm thick on the fourth silicon oxide layer, a fifth silicon oxide layer approximately 84 nm thick on the fifth titanium oxide layer, a sixth titanium oxide layer approximately 35 nm thick on the fifth silicon oxide layer, a sixth silicon oxide layer approximately 65 nm thick on the sixth titanium oxide layer, a seventh titanium oxide layer approximately 46 nm thick on the sixth silicon oxide layer, a seventh silicon oxide layer approximately 76 nm thick on the seventh titanium oxide layer, an eighth titanium oxide layer approximately 48 nm thick on the seventh silicon oxide layer, an eighth silicon oxide layer approximately 175 nm thick on the eighth titanium oxide layer, a ninth titanium oxide layer approximately 19 nm thick on the eighth silicon oxide layer, a ninth silicon oxide layer approximately 61 nm thick on the ninth titanium oxide layer, and a tenth titanium oxide layer approximately 37 nm thick on the ninth silicon oxide layer. The semi-conductive layer **1430** may comprise an ITO layer or the like of approximately 130 nm thick. Clearly, other thicknesses and combinations of layers may be implemented

to achieve the desired levels of transmissivity and reflectivity, such as high transmissivity of other colors or spectral regions of the spectrum, without affecting the scope of the present invention. The transfective element thus provides a third surface transfective mirror element, with multiple layers of silicon oxide and titanium oxide to enhance the near infrared transmissivity and particular visible light wavelength or wavelengths through the ITO layers and substrates.

The transmissivity percentage of such a substrate versus the light wavelength is shown in FIG. **31**. As can be seen in FIG. **31**, such a substrate transmits more than approximately 90% of near infrared light, while substantially reflecting or not transmitting light in the visible range of the spectrum, except for light having a wavelength of approximately 430 nm, which is also highly transmitted (such as at greater than approximately 90% transmissivity) by the substrate and alternating layers of the IRT-DOD stack. The transfective element is thus spectrally tuned to transmit near infrared light that may be emitted from an illumination source **1444**, and may transmit the near infrared light from the scene back to an imaging sensor **1446**. The transfective element may also transmit light having a desired or targeted wavelength to allow for a colored display element or illumination source or indicator **1450** to be viewed through the transfective element.

Although shown and described as being implemented on a third surface of an electrochromic mirror element, it is envisioned that the layers or stacks of the present invention may be implemented at a fourth surface of the electrochromic reflective element, such as for a fourth surface reflective element, without affecting the scope of the present invention. In such an application, a radiant energy emitting device or element and/or an imaging sensor may be positioned rearward of the stack or layers for emitting or receiving radiant energy through the reflective element. Also, a protective layer or cover may be provided over the rearwardmost layer of the alternating layers and over or around the display element or sensor to protect the layers at the rear of the reflective element.

Also, although shown and described as being implemented in an electrochromic reflective element or cell, the alternating layers or stacks of the present invention may be implemented at a rear surface (second surface) of a prismatic reflective element, without affecting the scope of the present invention. For example, and with reference to FIG. **32**, a prismatic reflective element **1516** may comprise a prismatic or wedge-shaped substrate **1522** having a forward or outwardly facing surface **1522a** and a rearward surface **1522b** opposite the forward surface **1522a**. Prismatic reflective element **1522** includes alternating layers or a stack **1528** disposed at rear surface **1522b** of prismatic substrate **1522**. As shown in FIG. **32**, a protective layer or coating **1525** may be applied over the stack **1528**. The layers of stack **1528** may comprise alternating layers of metallic and non-metallic layers or coatings, such as layers or stacks similar to the ISI stacks or DOD stacks or IRT stacks or IRT-DOD stacks of the present invention, as discussed above, depending on the particular application of the prismatic reflective element. The particular materials and thicknesses of the layers may be selected to provide the desired transmissivity of a particular selected spectral band or bands of radiant energy through the prismatic reflective element, while providing sufficient reflectivity of other spectral bands of radiant energy.

Prismatic reflective element **1516** may include a display element or radiant energy emitting device or illumination source **1544** positioned at a rear surface of the rearward most layer of stack **1528** and operable to emit radiant energy, such as visible light, near infrared radiant energy or infrared radi-

ant energy through stack 1528 and prismatic substrate 1522. The thicknesses and materials of the layers of stack 1528 may be selected to provide enhanced transmissivity of radiant energy or light within a particular spectral band through stack 1528 and prismatic substrate 1522, while providing sufficient reflectivity of light having wavelengths outside of the selected particular spectral band. The particular spectral band may be selected to match the spectral band of light or radiant energy emitted by radiant energy emitting device 1544, such as in the manners discussed above. Optionally, the prismatic reflective element may include an imaging sensor or the like, such as discussed above with respect to electrochromic reflective element 1316 or 1416, without affecting the scope of the present invention.

The radiant energy emitting element or display element thus may be viewable through the prismatic substrate without requiring windows or the like formed in the reflective layer at the rear of the prismatic substrate. The layers or stacks of the present invention thus may provide an improved display on demand or display on need type of display element for a prismatic reflective element. Although shown as a prismatic or wedge-shaped substrate, the substrate may comprise a substantially flat substrate or may comprise a curved substrate having one or more curved surfaces, without affecting the scope of the present invention.

Although described as being implemented with interior rearview mirror assemblies, it is further envisioned that the layers or stacks of the present invention may be implemented with reflective elements for exterior rearview mirror assemblies, such as exterior electrochromic rearview mirror assemblies or other exterior rearview mirror assemblies, such as exterior rearview mirror assemblies having a single flat substrate or having a curved outer surface or substrate or the like, without affecting the scope of the present invention. For example, an exterior reflective element may have a stack of alternating layers (such as the types discussed above) that may have enhanced transmissivity of visible light that has a spectral band that matches a color output of a turn signal indicator or other indicator or light emitting device positioned behind the reflective element, such as within the casing of the exterior rearview mirror assembly. The indicator may thus be viewable through the reflective element when the indicator is activated, while the reflective element substantially reflects other light over its entire viewing surface. The exterior rearview mirror assembly of the present invention thus may provide an indicator for viewing through the reflective element without requiring a window to be formed in the reflective layer or surface of the exterior reflective element. The present invention thus may provide a display on demand or display on need type of display to an exterior rearview mirror assembly. Optionally, the alternating layers may comprise an IRT stack or IRT-DOD stack, such as described above, and the exterior rearview mirror assembly may include an infrared or near infrared emitting element, and may include an imaging sensor or device or camera, such as for a side or rearward imaging system of the vehicle (such as for a viewing system such as the types disclosed in U.S. Pat. Nos. 5,550,677; 5,670,935 and 6,201,642, which are hereby incorporated herein by reference, or such as for a lane change assist system or side objection detection system or the like, such as the types disclosed in U.S. patent application Ser. No. 10/209,173, filed Jul. 31, 2002 by Schofield for AUTOMOTIVE LANE CHANGE AID, now U.S. Pat. No. 6,882,287, Ser. No. 10/427,051, filed Apr. 30, 2003 by Pawlicki et al. for OBJECT DETECTION SYSTEM FOR VEHICLE, now U.S. Pat. No. 7,038,577, which are hereby incorporated herein by reference). The near infrared emitting element or elements may be

positioned within the exterior rearview mirror assembly and behind the reflective element and may provide illumination at the side of the vehicle without distracting or adversely affecting the view or vision of drivers of other vehicles at the side of the subject vehicle.

The present invention thus provides mirror reflective elements that provide substantial visible reflectivity, and that may provide substantial transmissivity of near infrared light, and that may also or otherwise provide substantial transmissivity of visible light within a selected spectral band or region or range of wavelengths. The mirror reflective elements of the present invention thus may be spectrally tuned for the desired application, while still providing the desired degree of photopic reflectivity and the desired conductivity on the conductive or semi-conductive layers, such that the electrochromic medium of the mirror cell colors or darkens in a desired manner.

The electrical connectors for the transreflective electrochromic cells or elements of the present invention may comprise clip connectors, electrical busbars or the like, such as disclosed in U.S. Pat. Nos. 5,066,112 and 6,449,082, which are hereby incorporated herein by reference. Although shown as having the substrates and connectors offset, clearly the transreflective element may comprise a flush element, such as described in U.S. Pat. No. 5,066,112, or such as described in U.S. provisional applications, Ser. No. 60/490,111, filed Jul. 25, 2003 by McCabe et al. for FLUSH ELECTROCHROMIC CELL; and Ser. No. 60/423,903, filed Nov. 5, 2002 by McCabe for ONE SIDED FLUSH ELECTROCHROMIC CELL, which are all hereby incorporated herein by reference. Such a flush transreflective element may facilitate a no-bezel or bezelless or low bezel mirror casing or assembly, with minimal or no offset between the substrates of the mirror assembly.

As discussed above, the mirror assembly of the present invention may include a display for providing information for viewing by the driver of the vehicle on the reflective element so that the driver can easily see the display. In order to maintain easy viewing of the display, it is desirable to adjust the display intensity in response to ambient light levels (in order to avoid washout during daytime driving conditions and glare during nighttime driving conditions) and in response to the degree of transmissivity of the electrochromic reflective element. For example, in low lighting conditions, such as during the nighttime, the intensity of the display may be dimmed to avoid glare, while in higher lighting conditions, such as during the daytime, the intensity of the display may be increased to provide sufficient visibility of the display to the driver of the vehicle. The mirror assembly may include light sensors for sensing the ambient light in the cabin of the vehicle or at the mirror assembly and may include a control which is operable to automatically adjust the display intensity and/or the transmissivity of the electrochromic medium in response to the ambient light sensors.

Further, automatic dimming circuitry used in electrochromic mirror assemblies utilizing the reflective elements of the current invention may utilize one or more (typically two) photo sensors to detect glaring and/or ambient lighting. For example, a silicon photo sensor such as a TSL235R Light-to-Frequency converter (available from Texas Advanced Optoelectronic Solutions Inc. of Plano, Tex.) can be used as such photo sensors. Such light-to-frequency converters comprise the combination of a silicon photodiode and a current-to-frequency converter on a single monolithic CMOS integrated circuit.

The mirror assembly or assemblies of the present invention may also include or house a plurality of electrical or elec-

tronic devices, such as antennas, including global positioning system (GPS) or cellular phone antennas, such as disclosed in U.S. Pat. No. 5,971,552, a communication module, such as disclosed in U.S. Pat. No. 5,798,688, displays, such as shown in U.S. Pat. Nos. 5,530,240 and 6,329,925, blind spot detection systems, such as disclosed in U.S. Pat. No. 5,929,786 or 5,786,772, transmitters and/or receivers, such as garage door openers, a digital network, such as described in U.S. Pat. No. 5,798,575, a high/low head lamp controller, such as disclosed in U.S. Pat. No. 5,715,093, a memory mirror system, such as disclosed in U.S. Pat. No. 5,796,176, a hands-free phone attachment, a video device for internal cabin surveillance and/or video telephone function, such as disclosed in U.S. Pat. Nos. 5,760,962 and 5,877,897, a remote keyless entry receiver, map lights, such as disclosed in U.S. Pat. Nos. 5,938,321; 5,813,745; 5,820,245; 5,673,994; 5,649,756; or 5,178,448, microphones, such as disclosed in U.S. Pat. Nos. 6,243,003 and 6,278,377, speakers, a compass, such as disclosed in U.S. Pat. No. 5,924,212 or U.S. patent application Ser. No. 10/456,599, filed Jun. 6, 2003 by Weller et al. for INTERIOR REARVIEW MIRROR SYSTEM WITH COMPASS, now U.S. Pat. No. 7,004,593, seat occupancy detector, a trip computer, an ONSTAR® system or the like (with all of the above-referenced patents and applications being commonly assigned to Donnelly Corporation, and with the disclosures of the referenced patents and applications being hereby incorporated herein by reference in their entireties).

The mirror assembly and/or reflective element of the present invention may include a printed circuit board (PCB) which may be attached to its rear surface (e.g. the fourth surface) by, for example, a suitable adhesive or the like. An example of such an arrangement is disclosed in commonly assigned U.S. Pat. No. 5,820,245, which is incorporated in its entirety by reference herein. The PCB optionally may include glare sensing and ambient photo sensors and electrochromic circuitry that automatically dims the reflectivity of the electrochromic mirror element when glare conditions are detected, such as at nighttime or the like. Alternately, the PCB may be snap connected, by a clip or otherwise attached, to a plastic plate that itself is adhered to the electrochromic element.

The printed circuit board may include electronic or electrical circuitry for actuating the variable reflectance of the reflective element and for operating other electrical or electronic functions supported in the rearview mirror assembly. The circuit board may support, for example, light emitting diodes (LEDs) for illuminating indicia on display elements provided on the chin of the bezel of the mirror assembly or display devices provided on the reflective element, or map or dash board lights or the like. The circuit board may be independently supported from the reflective element or in the casing or may be mounted to the reflective element's rear or fourth surface on a separate plate or may be directly adlied to the rear surface by a suitable adhesive. Reference is made to U.S. Pat. Nos. 5,671,996 and 5,820,245, the disclosures of which are hereby incorporated herein by reference in their entireties.

Therefore, the present invention provides a reflective element which provides a combination of substantially transparent, conductive or semi-conductive layers and substantially reflective, conductive metallic layer or layers on one of the surfaces of the reflective element, such as the inward surface (or third surface) of a second substrate of an electrochromic reflective element or a rear surface (or fourth surface) of an electrochromic reflective element or a rear surface of a prismatic reflective element or the like. The reflective element of the present invention provides enhanced manufacturing pro-

cessing of the reflective element, since the thicknesses of the layers and tolerances associated therewith are sufficiently large enough to be sputter coated or otherwise deposited via a low cost process. The reflective element of the present invention also provides for a reflective and transmissive element which allows transmission of display information through the reflective element, while still providing sufficient reflectance over the entire surface of the reflective element, even in the display area. Accordingly, multiple displays may be positioned on, at or around the reflective element, without loss of reflectivity of the element. The materials and thicknesses of the layers of the reflective element may be selected to spectrally tune the reflective element to allow transmission of one or more particular spectral bands or range of wavelengths, in order to tune the reflective element for use with a particular spectral band of light being emitted by a particular display. The materials and thicknesses of the layers may also be selected to spectrally tune the reflective element to enhance transmissivity of near infrared radiant energy. Also, the thicknesses of one or more layers may be varied across the mirror element to provide regions or areas of increased transmissivity for a display, while maintaining a desired level of reflectivity at the principle viewing area of the mirror element. The mirror element may comprise an electrochromic element or a prismatic element and may be implemented at an interior rearview mirror assembly or an exterior rearview mirror assembly. Optionally, the mirror element may comprise a substantially flat element or may comprise a curved element, such as a convex element or aspheric element or the like.

Changes and modifications in the specifically described embodiments can be carried out without departing from the principles of the invention, which is intended to be limited only by the scope of the appended claims, as interpreted according to the principles of patent law.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said transfective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

a display device disposed behind said transfective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

a circuit board for mounting electrical components, wherein said circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said circuit board supports said plurality of light emitting diodes;

wherein said circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said

41

electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system;

wherein said plurality of light emitting diodes of said circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle; and wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transfective mirror reflector for viewing by the driver of the equipped vehicle.

2. The interior rearview mirror information display system of claim 1, wherein said display screen comprises an active matrix liquid crystal display screen.

3. The interior rearview mirror information display system of claim 2, wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes.

4. The interior rearview mirror information display system of claim 1, wherein said displayed information comprises information related to a driver assist function.

5. The interior rearview mirror information display system of claim 4, wherein said driver assist function comprises at least one of (a) a door ajar status, (b) a seat belt status, (c) a lane change assist, (d) a blind spot detection and (e) a backup assist.

6. The interior rearview mirror information display system of claim 1, wherein circuitry supported at least in part by said printed circuit board is operable to operate at least one other electrical accessory disposed in or at said interior rearview mirror assembly.

7. The interior rearview mirror information display system of claim 1, wherein said mirror reflector is established at said third surface of said rear substrate.

8. The interior rearview mirror information display system of claim 7, wherein said mirror reflector comprises a multi-zone mirror reflector established at said third surface of said rear substrate, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transfective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone mirror reflector.

9. The interior rearview mirror information display system of claim 8, wherein said display screen is disposed at said reflective element to generally coincide with said second zone of said multi-zone mirror reflector.

10. The interior rearview mirror information display system of claim 9, wherein said display screen, when operating to display information, is viewable through said transfective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transfective mirror reflector at said second zone of said multi-zone mirror reflector.

42

11. The interior rearview mirror information display system of claim 10, wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

12. The interior rearview mirror information display system of claim 10, wherein the transmissivity of visible light at said second zone of said multi-zone mirror reflector is at least about 10 percent, and wherein the transmissivity of visible light at said first zone of said multi-zone mirror reflector is less than about 10 percent.

13. The interior rearview mirror information display system of claim 8, wherein said multi-zone mirror reflector is established at said third surface so that the reflectivity of visible light at said first zone of said multi-zone mirror reflector is greater than the reflectivity of visible light at said second zone of said multi-zone mirror reflector.

14. The interior rearview mirror information display system of claim 8, wherein said multi-zone mirror reflector comprises a substantially neutral spectral reflectance when no voltage is applied across said electrochromic medium.

15. The interior rearview mirror information display system of claim 8, wherein at least one metallic reflective layer of said multi-zone mirror reflector is established during vacuum deposition utilizing a mask.

16. The interior rearview mirror information display system of claim 1, wherein said mirror reflector comprises at least three layers, and wherein said at least three layers comprise a metallic layer and a metal oxide layer.

17. The interior rearview mirror information display system of claim 16, wherein two of said at least three layers comprise transparent metal oxide layers.

18. The interior rearview mirror information display system of claim 17, wherein said metallic layer comprises one of a silver layer and a silver alloy layer.

19. The interior rearview mirror information display system of claim 18, wherein said transparent metal oxide layers comprise at least one of a semiconducting metal oxide layer, an indium tin oxide layer, a titanium oxide layer, a silicon oxide layer and a tin oxide layer.

20. The interior rearview mirror information display system of claim 18, wherein said metallic layer comprises a specific resistivity of less than approximately 5×10^{-5} ohm.cm.

21. The interior rearview mirror information display system of claim 16, wherein said at least three layers comprise said metallic layer and two metal oxide layers.

22. The interior rearview mirror information display system of claim 21, wherein said metal oxide layers are disposed between said metallic layer and said third surface of said rear substrate.

23. The interior rearview mirror information display system of claim 22, wherein one of said metal oxide layers comprises a titanium oxide layer and the other of said metal oxide layers comprises an indium tin oxide layer.

24. The interior rearview mirror information display system of claim 23, wherein said indium tin oxide layer is disposed between said titanium oxide layer and said third surface of said rear substrate.

25. The interior rearview mirror information display system of claim 16, wherein said at least three layers of said mirror reflector are established at said third surface of said rear substrate by vacuum deposition comprising sputtering from multiple sputtering targets in a single vacuum deposition chamber.

26. The interior rearview mirror information display system of claim 25, wherein at least one of said multiple sputtering targets comprises a silver alloy metal target.

43

27. The interior rearview mirror information display system of claim 26, wherein at least another of said multiple sputtering targets comprises a metal oxide target.

28. The interior rearview mirror information display system of claim 27, wherein said metal oxide target comprises an indium tin oxide target.

29. The interior rearview mirror information display system of claim 25, wherein, during sputtering of said metallic layer of said mirror reflector, a perimeter region of said third surface of said rear substrate is masked so that said metallic layer does not encompass the masked perimeter region of said third surface of said rear substrate.

30. The interior rearview mirror information display system of claim 29, wherein a portion of the perimeter region of said third surface of said rear substrate is not masked so that said metallic layer comprises a tab out portion that encompasses the unmasked portion of the perimeter region of said third surface of said rear substrate.

31. The interior rearview mirror information display system of claim 16, wherein said metallic layer has a thickness of at least about 60 nm.

32. The interior rearview mirror information display system of claim 1, wherein said circuit board comprises a printed circuit board.

33. The interior rearview mirror information display system of claim 1, wherein said circuit board is attached at said fourth surface of said rear substrate.

34. The interior rearview mirror information display system of claim 33, wherein said circuit board is adhesively attached at said fourth surface of said rear substrate.

35. The interior rearview mirror information display system of claim 33, wherein said circuit board is attached to a backing plate that is adhesively attached at said fourth surface of said rear substrate.

36. The interior rearview mirror information display system of claim 1, wherein said circuit board includes at least one photosensor disposed thereon, and wherein said circuitry is operable to vary the reflectivity of said electrochromic reflective element responsive to a light level detected by said at least one photosensor.

37. The interior rearview mirror information display system of claim 36, wherein said at least one photosensor comprises a glare sensing photosensor.

38. The interior rearview mirror information display system of claim 37, wherein said at least one photosensor comprises an ambient light sensing photosensor.

39. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said transfective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

44

a display device disposed behind said transfective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

wherein said display screen comprises an active matrix liquid crystal display screen, and wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes;

a circuit board for mounting electrical components, wherein said circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said circuit board supports said plurality of light emitting diodes;

wherein said circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system;

wherein said plurality of light emitting diodes of said circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle;

wherein said displayed information comprises information related to a driver assist function; and

wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transfective mirror reflector for viewing by the driver of the equipped vehicle.

40. The interior rearview mirror information display system of claim 39, wherein said mirror reflector comprises a multi-zone mirror reflector established at said third surface of said rear substrate, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transfective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone mirror reflector, and wherein said display screen is disposed at said reflective element to generally coincide with said second zone of said multi-zone mirror reflector, and wherein said display screen, when operating to display information, is viewable through said transfective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transfective mirror reflector at said second zone of said multi-zone mirror reflector.

41. The interior rearview mirror information display system of claim 40, wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

42. The interior rearview mirror information display system of claim 40, wherein the transmissivity of visible light at said second zone of said multi-zone mirror reflector is at least about 10 percent, and wherein the transmissivity of visible light at said first zone of said multi-zone mirror reflector is less than about 10 percent.

43. The interior rearview mirror information display system of claim 40, wherein said multi-zone mirror reflector

45

comprises a substantially neutral spectral reflectance when no voltage is applied across said electrochromic medium.

44. The interior rearview mirror information display system of claim 40, wherein at least one metallic reflective layer of said multi-zone mirror reflector is established during vacuum deposition utilizing a mask.

45. The interior rearview mirror information display system of claim 39, wherein said mirror reflector comprises at least three layers, and wherein said at least three layers comprise a metallic layer and a metal oxide layer.

46. The interior rearview mirror information display system of claim 45, wherein two of said at least three layers comprise transparent metal oxide layers.

47. The interior rearview mirror information display system of claim 46, wherein said metallic layer comprises one of a silver layer and a silver alloy layer, and wherein said transparent metal oxide layers comprise at least one of a semiconducting metal oxide layer, an indium tin oxide layer, a titanium oxide layer, a silicon oxide layer and a tin oxide layer.

48. The interior rearview mirror information display system of claim 45, wherein said at least three layers comprise said metallic layer and two metal oxide layers, and wherein said metal oxide layers are disposed between said metallic layer and said third surface of said rear substrate, and wherein one of said metal oxide layers comprises a titanium oxide layer and the other of said metal oxide layers comprises an indium tin oxide layer, and wherein said indium tin oxide layer is disposed between said titanium oxide layer and said third surface of said rear substrate.

49. The interior rearview mirror information display system of claim 45, wherein said at least three layers of said mirror reflector are established at said third surface of said rear substrate by vacuum deposition comprising sputtering from multiple sputtering targets in a single vacuum deposition chamber, and wherein at least one of said multiple sputtering targets comprises a silver alloy metal target, and wherein at least another of said multiple sputtering targets comprises a metal oxide target.

50. The interior rearview mirror information display system of claim 49, wherein, during sputtering of said metallic layer of said mirror reflector, a perimeter region of said third surface of said rear substrate is masked so that said metallic layer does not encompass the masked perimeter region of said third surface of said rear substrate.

51. The interior rearview mirror information display system of claim 50, wherein a portion of the perimeter region of said third surface of said rear substrate is not masked so that said metallic layer comprises a tab out portion that encompasses the unmasked portion of the perimeter region of said third surface of said rear substrate.

52. The interior rearview mirror information display system of claim 39, wherein said circuit board comprises a printed circuit board.

53. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

46

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said transfective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

wherein said mirror reflector is established at said third surface of said rear substrate, and wherein said mirror reflector comprises a multi-zone mirror reflector established at said third surface of said rear substrate, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transfective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone mirror reflector;

a display device disposed behind said transfective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

wherein said display screen comprises a liquid crystal display screen, and wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes;

a circuit board for mounting electrical components, wherein said circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said circuit board supports said plurality of light emitting diodes;

wherein said circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system;

wherein said plurality of light emitting diodes of said circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle; and wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transfective mirror reflector for viewing by the driver of the equipped vehicle.

54. The interior rearview mirror information display system of claim 53, wherein said display screen, when operating to display information, is viewable through said transfective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transfective mirror reflector at said second zone of said multi-zone mirror reflector.

55. The interior rearview mirror information display system of claim 53, wherein said displayed information comprises information related to a driver assist function, and wherein said driver assist function comprises at least one of (a) a lane change assist, (b) a blind spot detection and (c) a backup assist.

47

56. The interior rearview mirror information display system of claim 53, wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

57. The interior rearview mirror information display system of claim 53, wherein the transmissivity of visible light at said second zone of said multi-zone mirror reflector is at least about 10 percent, and wherein the transmissivity of visible light at said first zone of said multi-zone mirror reflector is less than about 10 percent.

58. The interior rearview mirror information display system of claim 53, wherein said multi-zone mirror reflector comprises a substantially neutral spectral reflectance when no voltage is applied across said electrochromic medium.

59. The interior rearview mirror information display system of claim 53, wherein at least one metallic reflective layer of said multi-zone mirror reflector is established during vacuum deposition utilizing a mask.

60. The interior rearview mirror information display system of claim 53, wherein said mirror reflector comprises at least three layers, and wherein said at least three layers comprise a metallic layer and a metal oxide layer.

61. The interior rearview mirror information display system of claim 60, wherein two of said at least three layers comprise transparent metal oxide layers.

62. The interior rearview mirror information display system of claim 61, wherein said metallic layer comprises one of a silver layer and a silver alloy layer, and wherein said transparent metal oxide layers comprise at least one of a semiconducting metal oxide layer, an indium tin oxide layer, a titanium oxide layer, a silicon oxide layer and a tin oxide layer.

63. The interior rearview mirror information display system of claim 60, wherein said at least three layers comprise said metallic layer and two metal oxide layers, and wherein said metal oxide layers are disposed between said metallic layer and said third surface of said rear substrate, and wherein one of said metal oxide layers comprises a titanium oxide layer and the other of said metal oxide layers comprises an indium tin oxide layer, and wherein said indium tin oxide layer is disposed between said titanium oxide layer and said third surface of said rear substrate.

64. The interior rearview mirror information display system of claim 60, wherein said at least three layers of said mirror reflector are established at said third surface of said rear substrate by vacuum deposition comprising sputtering from multiple sputtering targets in a single vacuum deposition chamber, and wherein at least one of said multiple sputtering targets comprises a silver alloy metal target, and wherein at least another of said multiple sputtering targets comprises a metal oxide target.

65. The interior rearview mirror information display system of claim 64, wherein, during sputtering of said metallic layer of said mirror reflector, a perimeter region of said third surface of said rear substrate is masked so that said metallic layer does not encompass the masked perimeter region of said third surface of said rear substrate.

66. The interior rearview mirror information display system of claim 65, wherein a portion of the perimeter region of said third surface of said rear substrate is not masked so that said metallic layer comprises a tab out portion that encompasses the unmasked portion of the perimeter region of said third surface of said rear substrate.

67. The interior rearview mirror information display system of claim 53, wherein said circuit board comprises a printed circuit board and wherein said display screen comprises an active matrix liquid crystal display screen.

48

68. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said transfective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

wherein said transfective mirror reflector comprises one of a silver metallic layer and a silver alloy metallic layer; a display device disposed behind said transfective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

wherein said display screen comprises an active matrix liquid crystal display screen and wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes;

a printed circuit board for mounting electrical components, wherein said printed circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said printed circuit board supports said plurality of light emitting diodes;

wherein said printed circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system;

wherein said plurality of light emitting diodes of said printed circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle; and wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transfective mirror reflector for viewing by the driver of the equipped vehicle.

69. The interior rearview mirror information display system of claim 68, wherein said displayed information comprises information related to a driver assist function.

70. The interior rearview mirror information display system of claim 69, wherein said driver assist function comprises at least one of (a) a lane change assist, (b) a blind spot detection and (c) a backup assist.

71. The interior rearview mirror information display system of claim 68, wherein circuitry supported at least in part by said printed circuit board is operable to operate at least one other electrical accessory disposed in or at said interior rear-

49

view mirror assembly, and wherein said mirror reflector is established at said third surface of said rear substrate.

72. The interior rearview mirror information display system of claim 71, wherein said mirror reflector comprises a multi-zone mirror reflector established at said third surface of said rear substrate, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transfective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone mirror reflector, and wherein said display screen is disposed at said reflective element to generally coincide with said second zone of said multi-zone mirror reflector, and wherein said display screen, when operating to display information, is viewable through said transfective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transfective mirror reflector at said second zone of said multi-zone mirror reflector, and wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

73. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said transfective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

wherein said transfective mirror reflector comprises a metallic layer established at said third surface of said rear substrate;

a display device disposed behind said transfective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

wherein said display screen comprises an active matrix liquid crystal display screen and wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes;

a printed circuit board for mounting electrical components, wherein said printed circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said printed circuit board supports said plurality of light emitting diodes;

wherein said plurality of light emitting diodes of said printed circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated

50

is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle;

wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transfective mirror reflector for viewing by the driver of the equipped vehicle; and

wherein said displayed information comprises information related to a driver assist function.

74. The interior rearview mirror information display system of claim 73, wherein said driver assist function comprises at least one of (a) a lane change assist, (b) a blind spot detection and (c) a backup assist.

75. The interior rearview mirror information display system of claim 74, wherein said mirror reflector comprises a multi-zone mirror reflector, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transfective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone mirror reflector, and wherein said display screen is disposed at said reflective element to generally coincide with said second zone of said multi-zone mirror reflector, and wherein said display screen, when operating to display information, is viewable through said transfective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transfective mirror reflector at said second zone of said multi-zone mirror reflector, and wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

76. The interior rearview mirror information display system of claim 75, wherein said transfective mirror reflector comprises a silver metallic layer.

77. The interior rearview mirror information display system of claim 75, wherein said transfective mirror reflector comprises a silver alloy metallic layer.

78. The interior rearview mirror information display system of claim 73, wherein said printed circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system.

79. An interior rearview mirror information display system for a vehicle, said interior rearview mirror information display system comprising:

an interior rearview mirror assembly comprising a reflective element;

wherein said reflective element comprises an electrochromic reflective element comprising a front substrate and a rear substrate, said front substrate having first and second surfaces and said rear substrate having third and fourth surfaces, and wherein said front substrate and said rear substrate are arranged so that said second surface of said front substrate opposes said third surface of said rear substrate with an electrochromic medium disposed therebetween;

wherein a mirror reflector is established at a surface of said rear substrate and wherein said mirror reflector comprises a transfective mirror reflector and wherein said

51

transflective mirror reflector is at least partially transmissive to visible light and partially reflective of visible light incident thereat;

a display device disposed behind said transflective mirror reflector of said reflective element, wherein said display device comprises a display screen backlit by a plurality of light emitting diodes;

wherein said display screen comprises a liquid crystal display screen and wherein said plurality of light emitting diodes comprises a plurality of white light-emitting light emitting diodes;

a printed circuit board for mounting electrical components, wherein said printed circuit board is disposed rearward of said fourth surface of said rear substrate, and wherein said printed circuit board supports said plurality of light emitting diodes;

wherein said plurality of light emitting diodes of said printed circuit board is disposed to the rear of said display screen to provide backlighting of said display screen when said plurality of light emitting diodes is activated;

wherein information displayed by said display device when said plurality of light emitting diodes is activated is viewable by a driver of the equipped vehicle when the driver is normally operating the equipped vehicle;

wherein, when said plurality of light emitting diodes is activated and said display device is displaying information, light emitted by said plurality of light emitting diodes passes through said display screen and through said transflective mirror reflector for viewing by the driver of the equipped vehicle; and

wherein said mirror reflector comprises a multi-zone mirror reflector established at said third surface of said rear substrate, and wherein said multi-zone mirror reflector comprises at least a first zone and a second zone, and wherein at least said second zone of said multi-zone mirror reflector comprises said transflective mirror reflector, and wherein said second zone of said multi-zone mirror reflector has a degree of transmissivity of visible light therethrough that is greater than a degree of transmissivity of visible light through said first zone of said multi-zone minor reflector, and wherein said dis-

52

play screen is disposed at said reflective element to generally coincide with said second zone of said multi-zone mirror reflector, and wherein said display screen, when operating to display information, is viewable through said transflective mirror reflector at said second zone of said multi-zone mirror reflector and, when not operating to display information, is rendered substantially covert by said transflective mirror reflector at said second zone of said multi-zone mirror reflector, and wherein said first zone of said multi-zone mirror reflector is substantially non-transmissive to visible light.

80. The interior rearview mirror information display system of claim **79**, wherein said transflective mirror reflector comprises a silver metallic layer.

81. The interior rearview mirror information display system of claim **79**, wherein said transflective mirror reflector comprises a silver alloy metallic layer.

82. The interior rearview mirror information display system of claim **79**, wherein said displayed information comprises information related to a driver assist function.

83. The interior rearview mirror information display system of claim **82**, wherein said driver assist function comprises at least one of (a) a lane change assist, (b) a blind spot detection and (c) a backup assist.

84. The interior rearview mirror information display system of claim **79**, wherein said printed circuit board supports, at least in part, circuitry that is operable to vary the reflectivity of said electrochromic reflective element responsive to a light condition detected by a photosensor during nighttime driving of a vehicle equipped with said interior rearview mirror information display system.

85. The interior rearview mirror information display system of claim **84**, wherein circuitry supported at least in part by said printed circuit board is operable to operate at least one other electrical accessory disposed in or at said interior rearview mirror assembly, and wherein said mirror reflector is established at said third surface of said rear substrate.

86. The interior rearview mirror information display system of claim **84**, wherein said display screen comprises an active matrix liquid crystal display screen.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,228,588 B2
APPLICATION NO. : 12/965052
DATED : July 24, 2012
INVENTOR(S) : Ian A. McCabe et al.

Page 1 of 2

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6

Line 4, “transflective” should be --transflective--

Column 10

Line 38, “(10)” should be --(IO)--

Column 12

Line 4, “Electrocliromic” should be --Electrochromic--

Line 9, “Chromogenic” should be --Chromogenic:”--

Column 19

Line 46, “30 m” should be --30nm--

Column 26

Line 55, “Tegions” should be --regions--

Column 28

Line 16, “electroclromic” should be --electrochromic--

Column 29

Line 22-23, “therethirough” should be --therethrough--

Line 52, “77 n” should be --77 nm--


Column 31

Line 34, “transflective” should be --transflective--

Column 33

Line 16, “250 mm” should be --250 nm--

Signed and Sealed this
Eighteenth Day of December, 2012

A handwritten signature in black ink, reading "David J. Kappos". The signature is written in a cursive, flowing style with a large initial "D".

David J. Kappos
Director of the United States Patent and Trademark Office

CERTIFICATE OF CORRECTION (continued)

Page 2 of 2

U.S. Pat. No. 8,228,588 B2

Column 36

Line 26, “electroclromic” should be --electrochromic--

Column 39

Line 6, “No.” should be --Nos.--

Line 53, “adliered” should be --adhered--

Column 43

Line 48, Claim 39, “minor” should be --mirror--

Column 51

Line 42, Claim 79, “minor” should be --mirror--